

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406193
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Ramanasankaran; Rajiv et al.

Building data platform with digital twin triggers and actions

Abstract

A building system including one or more storage devices storing instructions thereon that, when executed cause the one or more processors to store a data structure of a digital twin of an entity of a building, execute a learning algorithm to construct a trigger rule and an action rule as an input to the learning algorithm, store the trigger rule and the action rule in the digital twin, determine that the trigger rule of the digital twin is triggered by comparing at least some of the information of the data structure against one or more conditions of the trigger rule by querying the data structure for data values and comparing the data values against the one or more conditions of the trigger rule, determine an action of the action rule of the digital twin responsive to determining that the trigger rule is triggered by executing the action rule, and cause one or more devices to operate based on the action determined by the action rule.

Inventors: Ramanasankaran; Rajiv (San Jose, CA), Lee; Young M. (Old Westbury, NY)

Applicant: Tyco Fire & Security GmbH (Neuhausen am Rheinfall, CH)

Family ID: 86323663

Assignee: TYCO FIRE & SECURITY GMBH (Neuhausen am Rheinfall, CH)

Appl. No.: 18/372469

Filed: September 25, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240086740 A1	Mar. 14, 2024

Related U.S. Application Data

continuation parent-doc US 17529120 20211117 US 11769066 child-doc US 18372469

Publication Classification

Int. Cl.: G06N5/025 (20230101); G06F16/901 (20190101); G06F16/9035 (20190101); G06F16/906 (20190101); G06N5/022 (20230101)

U.S. Cl.:

CPC G06N5/025 (20130101); G06F16/9024 (20190101); G06F16/9035 (20190101); G06F16/906 (20190101); G06N5/022 (20130101);

Field of Classification Search

CPC: G06N (5/025); G06N (5/022); G06F (16/906); G06F (16/9035); G06F (16/9024)

USPC: 707/47; 706/47

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5301109	12/1993	Landauer et al.	N/A	N/A
5446677	12/1994	Jensen et al.	N/A	N/A
5581478	12/1995	Cruse et al.	N/A	N/A
5812962	12/1997	Kovac	N/A	N/A
5960381	12/1998	Singers et al.	N/A	N/A
5973662	12/1998	Singers et al.	N/A	N/A
6014612	12/1999	Larson et al.	N/A	N/A
6031547	12/1999	Kennedy	N/A	N/A
6134511	12/1999	Subbarao	N/A	N/A
6157943	12/1999	Meyer	N/A	N/A
6285966	12/2000	Brown et al.	N/A	N/A
6363422	12/2001	Hunter et al.	N/A	N/A
6385510	12/2001	Hoog et al.	N/A	N/A
6389331	12/2001	Jensen et al.	N/A	N/A
6401027	12/2001	Xu et al.	N/A	N/A
6437691	12/2001	Sandelman et al.	N/A	N/A
6477518	12/2001	Li et al.	N/A	N/A
6487457	12/2001	Hull et al.	N/A	N/A
6493755	12/2001	Hansen et al.	N/A	N/A
6577323	12/2002	Jamieson et al.	N/A	N/A
6626366	12/2002	Kayahara et al.	N/A	N/A
6646660	12/2002	Patty	N/A	N/A
6704016	12/2003	Oliver et al.	N/A	N/A
6732540	12/2003	Sugihara et al.	N/A	N/A
6764019	12/2003	Kayahara et al.	N/A	N/A
6782385	12/2003	Natsumeda et al.	N/A	N/A
6813532	12/2003	Eryurek et al.	N/A	N/A
6816811	12/2003	Seem	N/A	N/A
6823680	12/2003	Jayanth	N/A	N/A

6826454	12/2003	Sulfstede	N/A	N/A
6865511	12/2004	Frerichs et al.	N/A	N/A
6925338	12/2004	Eryurek et al.	N/A	N/A
6986138	12/2005	Sakaguchi et al.	N/A	N/A
7031880	12/2005	Seem et al.	N/A	N/A
7401057	12/2007	Eder	N/A	N/A
7552467	12/2008	Lindsay	N/A	N/A
7627544	12/2008	Chkodrov et al.	N/A	N/A
7818249	12/2009	Lovejoy et al.	N/A	N/A
7889051	12/2010	Billig et al.	N/A	N/A
7996488	12/2010	Casabella et al.	N/A	N/A
8078330	12/2010	Brickfield et al.	N/A	N/A
8104044	12/2011	Scofield et al.	N/A	N/A
8229470	12/2011	Ranjan et al.	N/A	N/A
8401991	12/2012	Wu et al.	N/A	N/A
8495745	12/2012	Schrecker et al.	N/A	N/A
8516016	12/2012	Park et al.	N/A	N/A
8532808	12/2012	Drees et al.	N/A	N/A
8532839	12/2012	Drees et al.	N/A	N/A
8600556	12/2012	Nesler et al.	N/A	N/A
8635182	12/2013	Mackay	N/A	N/A
8682921	12/2013	Park et al.	N/A	N/A
8731724	12/2013	Drees et al.	N/A	N/A
8737334	12/2013	Ahn et al.	N/A	N/A
8738334	12/2013	Jiang et al.	N/A	N/A
8751487	12/2013	Byrne et al.	N/A	N/A
8788097	12/2013	Drees et al.	N/A	N/A
8805995	12/2013	Oliver	N/A	N/A
8843238	12/2013	Wenzel et al.	N/A	N/A
8874071	12/2013	Sherman et al.	N/A	N/A
8941465	12/2014	Pineau et al.	N/A	N/A
8990127	12/2014	Taylor	N/A	N/A
9070113	12/2014	Shafiee et al.	N/A	N/A
9116978	12/2014	Park et al.	N/A	N/A
9185095	12/2014	Moritz et al.	N/A	N/A
9189527	12/2014	Park et al.	N/A	N/A
9196009	12/2014	Drees et al.	N/A	N/A
9229966	12/2015	Aymeloglu et al.	N/A	N/A
9286582	12/2015	Drees et al.	N/A	N/A
9311807	12/2015	Schultz et al.	N/A	N/A
9344751	12/2015	Ream et al.	N/A	N/A
9354968	12/2015	Wenzel et al.	N/A	N/A
9507686	12/2015	Horn et al.	N/A	N/A
9524594	12/2015	Ouyang et al.	N/A	N/A
9558196	12/2016	Johnston et al.	N/A	N/A
9652813	12/2016	Gifford et al.	N/A	N/A
9753455	12/2016	Drees	N/A	N/A
9811249	12/2016	Chen et al.	N/A	N/A
9817383	12/2016	Sinha et al.	N/A	N/A
9838844	12/2016	Emeis et al.	N/A	N/A

9886478	12/2017	Mukherjee	N/A	N/A
9948359	12/2017	Horton	N/A	N/A
10055114	12/2017	Shah et al.	N/A	N/A
10055206	12/2017	Park et al.	N/A	N/A
10116461	12/2017	Fairweather et al.	N/A	N/A
10169454	12/2018	Ait-Mokhtar et al.	N/A	N/A
10171297	12/2018	Stewart et al.	N/A	N/A
10171586	12/2018	Shaashua et al.	N/A	N/A
10187258	12/2018	Nagesh et al.	N/A	N/A
10514963	12/2018	Shrivastava et al.	N/A	N/A
10515098	12/2018	Park et al.	N/A	N/A
10521968	12/2018	Locke et al.	N/A	N/A
10534326	12/2019	Sridharan et al.	N/A	N/A
10536295	12/2019	Fairweather et al.	N/A	N/A
10564993	12/2019	Deutsch et al.	N/A	N/A
10705492	12/2019	Harvey	N/A	N/A
10708078	12/2019	Harvey	N/A	N/A
10739029	12/2019	Sinha et al.	N/A	N/A
10747183	12/2019	Sinha et al.	N/A	N/A
10760815	12/2019	Janakiraman et al.	N/A	N/A
10762475	12/2019	Song et al.	N/A	N/A
10798175	12/2019	Knight	N/A	G05B 19/048
10824120	12/2019	Ahmed	N/A	N/A
10845771	12/2019	Harvey	N/A	N/A
10854194	12/2019	Park et al.	N/A	N/A
10862928	12/2019	Badawy et al.	N/A	N/A
10901373	12/2020	Locke et al.	N/A	N/A
10921760	12/2020	Harvey	N/A	N/A
10921972	12/2020	Park et al.	N/A	N/A
10969133	12/2020	Harvey	N/A	N/A
10986121	12/2020	Stockdale et al.	N/A	N/A
11016998	12/2020	Park et al.	N/A	N/A
11024292	12/2020	Park et al.	N/A	N/A
11038709	12/2020	Park et al.	N/A	N/A
11041650	12/2020	Li et al.	N/A	N/A
11054796	12/2020	Holaso	N/A	N/A
11070390	12/2020	Park et al.	N/A	N/A
11073976	12/2020	Park et al.	N/A	N/A
11085663	12/2020	Ellis et al.	N/A	N/A
11108587	12/2020	Park et al.	N/A	N/A
11113295	12/2020	Park et al.	N/A	N/A
11120012	12/2020	Park et al.	N/A	N/A
11131473	12/2020	Risbeck et al.	N/A	N/A
11210591	12/2020	Alanqar et al.	N/A	N/A
11215375	12/2021	Alanqar et al.	N/A	N/A
11229138	12/2021	Harvey et al.	N/A	N/A
11243503	12/2021	Przybylski et al.	N/A	N/A
11274849	12/2021	Bell et al.	N/A	N/A
11276125	12/2021	Pancholi et al.	N/A	N/A

11314726	12/2021	Park et al.	N/A	N/A
11314788	12/2021	Park et al.	N/A	N/A
11556105	12/2022	Cooley et al.	N/A	N/A
11561522	12/2022	Cooley et al.	N/A	N/A
11561523	12/2022	Cooley et al.	N/A	N/A
11573551	12/2022	Cooley et al.	N/A	N/A
11586167	12/2022	Cooley et al.	N/A	N/A
2002/0010562	12/2001	Schleiss et al.	N/A	N/A
2002/0016639	12/2001	Smith et al.	N/A	N/A
2002/0059229	12/2001	Natsumeda et al.	N/A	N/A
2002/0123864	12/2001	Eryurek et al.	N/A	N/A
2002/0147506	12/2001	Eryurek et al.	N/A	N/A
2002/0177909	12/2001	Fu et al.	N/A	N/A
2003/0005486	12/2002	Ridolfo et al.	N/A	N/A
2003/0014130	12/2002	Grumelart	N/A	N/A
2003/0073432	12/2002	Meade, II	N/A	N/A
2003/0158704	12/2002	Triginai et al.	N/A	N/A
2003/0171851	12/2002	Brickfield et al.	N/A	N/A
2003/0200059	12/2002	Ignatowski et al.	N/A	N/A
2004/0068390	12/2003	Saunders	N/A	N/A
2004/0128314	12/2003	Katibah et al.	N/A	N/A
2004/0133314	12/2003	Ehlers et al.	N/A	N/A
2004/0199360	12/2003	Friman et al.	N/A	N/A
2005/0055308	12/2004	Meyer et al.	N/A	N/A
2005/0108262	12/2004	Fawcett et al.	N/A	N/A
2005/0154494	12/2004	Ahmed	N/A	N/A
2005/0278703	12/2004	Lo et al.	N/A	N/A
2005/0283337	12/2004	Sayal	N/A	N/A
2006/0095521	12/2005	Patinkin	N/A	N/A
2006/0140207	12/2005	Eschbach et al.	N/A	N/A
2006/0184479	12/2005	Levine	N/A	N/A
2006/0200476	12/2005	Gottumukkala et al.	N/A	N/A
2006/0265751	12/2005	Cosquer et al.	N/A	N/A
2006/0271589	12/2005	Horowitz et al.	N/A	N/A
2007/0028179	12/2006	Levin et al.	N/A	N/A
2007/0203693	12/2006	Estes	N/A	N/A
2007/0261062	12/2006	Bansal et al.	N/A	N/A
2007/0273497	12/2006	Kuroda et al.	N/A	N/A
2007/0273610	12/2006	Baillot	N/A	N/A
2008/0034425	12/2007	Overcash et al.	N/A	N/A
2008/0094230	12/2007	Mock et al.	N/A	N/A
2008/0097816	12/2007	Freire et al.	N/A	N/A
2008/0186160	12/2007	Kim et al.	N/A	N/A
2008/0249756	12/2007	Chaisuparasmikul	N/A	N/A
2008/0252723	12/2007	Park	N/A	N/A
2008/0281472	12/2007	Podgorny et al.	N/A	N/A
2009/0195349	12/2008	Frader-Thompson et al.	N/A	N/A
2009/0271169	12/2008	Minto et al.	N/A	N/A
2010/0045439	12/2009	Tak et al.	N/A	N/A

2010/0058248	12/2009	Park	N/A	N/A
2010/0131533	12/2009	Ortiz	N/A	N/A
2010/0274366	12/2009	Fata et al.	N/A	N/A
2010/0281387	12/2009	Holland et al.	N/A	N/A
2010/0286937	12/2009	Hedley et al.	N/A	N/A
2010/0324962	12/2009	Nesler et al.	N/A	N/A
2011/0015802	12/2010	Imes	N/A	N/A
2011/0047418	12/2010	Drees et al.	N/A	N/A
2011/0061015	12/2010	Drees et al.	N/A	N/A
2011/0071685	12/2010	Huneycutt et al.	N/A	N/A
2011/0077950	12/2010	Hughston	N/A	N/A
2011/0087650	12/2010	Mackay et al.	N/A	N/A
2011/0087988	12/2010	Ray et al.	N/A	N/A
2011/0088000	12/2010	Mackay	N/A	N/A
2011/0125737	12/2010	Pothering et al.	N/A	N/A
2011/0137853	12/2010	Mackay	N/A	N/A
2011/0153603	12/2010	Adiba et al.	N/A	N/A
2011/0154363	12/2010	Karmarkar	N/A	N/A
2011/0157357	12/2010	Weisensale et al.	N/A	N/A
2011/0178977	12/2010	Drees	N/A	N/A
2011/0191343	12/2010	Heaton et al.	N/A	N/A
2011/0205022	12/2010	Cavallaro et al.	N/A	N/A
2011/0218777	12/2010	Chen et al.	N/A	N/A
2012/0011126	12/2011	Park et al.	N/A	N/A
2012/0011141	12/2011	Park et al.	N/A	N/A
2012/0022698	12/2011	Mackay	N/A	N/A
2012/0062577	12/2011	Nixon	N/A	N/A
2012/0064923	12/2011	Imes et al.	N/A	N/A
2012/0083930	12/2011	Ilic et al.	N/A	N/A
2012/0100825	12/2011	Sherman et al.	N/A	N/A
2012/0101637	12/2011	Imes et al.	N/A	N/A
2012/0135759	12/2011	Imes et al.	N/A	N/A
2012/0136485	12/2011	Weber et al.	N/A	N/A
2012/0158633	12/2011	Eder	N/A	N/A
2012/0259583	12/2011	Noboa et al.	N/A	N/A
2012/0272228	12/2011	Marndi et al.	N/A	N/A
2012/0278051	12/2011	Jiang et al.	N/A	N/A
2013/0007063	12/2012	Kalra et al.	N/A	N/A
2013/0038430	12/2012	Blower et al.	N/A	N/A
2013/0038707	12/2012	Cunningham et al.	N/A	N/A
2013/0060820	12/2012	Bulusu et al.	N/A	N/A
2013/0086497	12/2012	Ambuhl et al.	N/A	N/A
2013/0097706	12/2012	Titonis et al.	N/A	N/A
2013/0103221	12/2012	Raman et al.	N/A	N/A
2013/0167035	12/2012	Imes et al.	N/A	N/A
2013/0170710	12/2012	Kuoch et al.	N/A	N/A
2013/0204836	12/2012	Choi et al.	N/A	N/A
2013/0246916	12/2012	Reimann et al.	N/A	N/A
2013/0247205	12/2012	Schrecker et al.	N/A	N/A
2013/0262035	12/2012	Mills	N/A	N/A

2013/0275174	12/2012	Bennett et al.	N/A	N/A
2013/0275908	12/2012	Reichard	N/A	N/A
2013/0297050	12/2012	Reichard et al.	N/A	N/A
2013/0298244	12/2012	Kumar et al.	N/A	N/A
2013/0331995	12/2012	Rosen	N/A	N/A
2013/0338970	12/2012	Reggetti	N/A	N/A
2014/0032506	12/2013	Hoey et al.	N/A	N/A
2014/0059483	12/2013	Mairs et al.	N/A	N/A
2014/0081652	12/2013	Klindworth	N/A	N/A
2014/0107993	12/2013	Cheng	N/A	N/A
2014/0135952	12/2013	Maehara	N/A	N/A
2014/0152651	12/2013	Chen et al.	N/A	N/A
2014/0172184	12/2013	Schmidt et al.	N/A	N/A
2014/0189861	12/2013	Gupta et al.	N/A	N/A
2014/0207282	12/2013	Angle et al.	N/A	N/A
2014/0258052	12/2013	Khuti et al.	N/A	N/A
2014/0269614	12/2013	Maguire et al.	N/A	N/A
2014/0277765	12/2013	Karimi et al.	N/A	N/A
2014/0278461	12/2013	Artz	N/A	N/A
2014/0327555	12/2013	Sager et al.	N/A	N/A
2015/0019174	12/2014	Kiff et al.	N/A	N/A
2015/0042240	12/2014	Aggarwal et al.	N/A	N/A
2015/0105917	12/2014	Sasaki et al.	N/A	N/A
2015/0145468	12/2014	Ma et al.	N/A	N/A
2015/0156031	12/2014	Fadell et al.	N/A	N/A
2015/0168931	12/2014	Jin	N/A	N/A
2015/0172300	12/2014	Cochenour	N/A	N/A
2015/0178421	12/2014	Borrelli et al.	N/A	N/A
2015/0185261	12/2014	Frader-Thompson et al.	N/A	N/A
2015/0186777	12/2014	Lecue et al.	N/A	N/A
2015/0202962	12/2014	Habashima et al.	N/A	N/A
2015/0204563	12/2014	Imes et al.	N/A	N/A
2015/0235267	12/2014	Steube et al.	N/A	N/A
2015/0241895	12/2014	Lu et al.	N/A	N/A
2015/0244730	12/2014	Vu et al.	N/A	N/A
2015/0244732	12/2014	Golshan et al.	N/A	N/A
2015/0261863	12/2014	Dey et al.	N/A	N/A
2015/0263900	12/2014	Polyakov et al.	N/A	N/A
2015/0286969	12/2014	Warner et al.	N/A	N/A
2015/0295796	12/2014	Hsiao et al.	N/A	N/A
2015/0304193	12/2014	Ishii et al.	N/A	N/A
2015/0316918	12/2014	Schleiss et al.	N/A	N/A
2015/0324422	12/2014	Elder	N/A	N/A
2015/0341212	12/2014	Hsiao et al.	N/A	N/A
2015/0348417	12/2014	Ignaczak et al.	N/A	N/A
2015/0379080	12/2014	Jochimski	N/A	N/A
2016/0011753	12/2015	McFarland et al.	N/A	N/A
2016/0033946	12/2015	Zhu et al.	N/A	N/A
2016/0035246	12/2015	Curtis	N/A	N/A

2016/0065601	12/2015	Gong et al.	N/A	N/A
2016/0070736	12/2015	Swan et al.	N/A	N/A
2016/0078229	12/2015	Gong et al.	N/A	N/A
2016/0090839	12/2015	Stolarczyk	N/A	N/A
2016/0119434	12/2015	Dong et al.	N/A	N/A
2016/0127712	12/2015	Alfredsson et al.	N/A	N/A
2016/0139752	12/2015	Shim et al.	N/A	N/A
2016/0163186	12/2015	Davidson et al.	N/A	N/A
2016/0170390	12/2015	Xie et al.	N/A	N/A
2016/0171862	12/2015	Das et al.	N/A	N/A
2016/0173816	12/2015	Huenerfauth et al.	N/A	N/A
2016/0179315	12/2015	Sarao et al.	N/A	N/A
2016/0179342	12/2015	Sarao et al.	N/A	N/A
2016/0179990	12/2015	Sarao et al.	N/A	N/A
2016/0195856	12/2015	Spero	N/A	N/A
2016/0212165	12/2015	Singla et al.	N/A	N/A
2016/0239660	12/2015	Azvine et al.	N/A	N/A
2016/0239756	12/2015	Aggour et al.	N/A	N/A
2016/0247129	12/2015	Song et al.	N/A	N/A
2016/0260063	12/2015	Harris et al.	N/A	N/A
2016/0313751	12/2015	Risbeck et al.	N/A	N/A
2016/0313752	12/2015	Przybylski	N/A	N/A
2016/0313902	12/2015	Hill et al.	N/A	N/A
2016/0350364	12/2015	Anicic et al.	N/A	N/A
2016/0357521	12/2015	Zhang et al.	N/A	N/A
2016/0357828	12/2015	Tobin et al.	N/A	N/A
2016/0358432	12/2015	Branscomb et al.	N/A	N/A
2016/0363336	12/2015	Roth et al.	N/A	N/A
2016/0370258	12/2015	Perez	N/A	N/A
2016/0378306	12/2015	Kresl et al.	N/A	N/A
2016/0379326	12/2015	Chan-Gove et al.	N/A	N/A
2017/0006135	12/2016	Siebel	N/A	N/A
2017/0011318	12/2016	Vigano et al.	N/A	N/A
2017/0017221	12/2016	Lamparter et al.	N/A	N/A
2017/0039255	12/2016	Raj et al.	N/A	N/A
2017/0052536	12/2016	Warner et al.	N/A	N/A
2017/0053441	12/2016	Nadumane et al.	N/A	N/A
2017/0063894	12/2016	Muddu et al.	N/A	N/A
2017/0068409	12/2016	Nair	N/A	N/A
2017/0070775	12/2016	Taxier et al.	N/A	N/A
2017/0075984	12/2016	Deshpande et al.	N/A	N/A
2017/0084168	12/2016	Janchookiat	N/A	N/A
2017/0090437	12/2016	Veeramani et al.	N/A	N/A
2017/0093700	12/2016	Gilley et al.	N/A	N/A
2017/0098086	12/2016	Hoernecke et al.	N/A	N/A
2017/0103327	12/2016	Penilla et al.	N/A	N/A
2017/0103403	12/2016	Chu et al.	N/A	N/A
2017/0123389	12/2016	Baez et al.	N/A	N/A
2017/0134415	12/2016	Muddu et al.	N/A	N/A
2017/0177715	12/2016	Chang et al.	N/A	N/A

2017/0180147	12/2016	Brandman et al.	N/A	N/A
2017/0188216	12/2016	Koskas et al.	N/A	N/A
2017/0212482	12/2016	Boettcher et al.	N/A	N/A
2017/0212668	12/2016	Shah et al.	N/A	N/A
2017/0220641	12/2016	Chi et al.	N/A	N/A
2017/0230930	12/2016	Frey	N/A	N/A
2017/0235817	12/2016	Deodhar et al.	N/A	N/A
2017/0251182	12/2016	Siminoff et al.	N/A	N/A
2017/0270124	12/2016	Nagano et al.	N/A	N/A
2017/0277769	12/2016	Pasupathy et al.	N/A	N/A
2017/0278003	12/2016	Liu	N/A	N/A
2017/0294132	12/2016	Colmenares	N/A	N/A
2017/0315522	12/2016	Kwon et al.	N/A	N/A
2017/0315697	12/2016	Jacobson et al.	N/A	N/A
2017/0322534	12/2016	Sinha et al.	N/A	N/A
2017/0323389	12/2016	Vavrasek	N/A	N/A
2017/0329289	12/2016	Kohn et al.	N/A	N/A
2017/0336770	12/2016	MacMillan	N/A	N/A
2017/0345287	12/2016	Fuller et al.	N/A	N/A
2017/0351957	12/2016	Lecue et al.	N/A	N/A
2017/0357225	12/2016	Asp et al.	N/A	N/A
2017/0357490	12/2016	Park et al.	N/A	N/A
2017/0357908	12/2016	Cabadi et al.	N/A	N/A
2018/0012159	12/2017	Kozloski et al.	N/A	N/A
2018/0013579	12/2017	Fairweather et al.	N/A	N/A
2018/0024520	12/2017	Sinha et al.	N/A	N/A
2018/0039238	12/2017	Gartner et al.	N/A	N/A
2018/0048485	12/2017	Pelton et al.	N/A	N/A
2018/0069932	12/2017	Tiwari et al.	N/A	N/A
2018/0114140	12/2017	Chen et al.	N/A	N/A
2018/0137288	12/2017	Polyakov	N/A	N/A
2018/0157930	12/2017	Rutschman et al.	N/A	N/A
2018/0162400	12/2017	Abdar	N/A	N/A
2018/0176241	12/2017	Manadhata et al.	N/A	N/A
2018/0198627	12/2017	Mullins	N/A	N/A
2018/0203961	12/2017	Aisu et al.	N/A	N/A
2018/0239982	12/2017	Rutschman et al.	N/A	N/A
2018/0275625	12/2017	Park et al.	N/A	N/A
2018/0276962	12/2017	Butler et al.	N/A	N/A
2018/0292797	12/2017	Lamparter et al.	N/A	N/A
2018/0313561	12/2017	Sinha et al.	N/A	N/A
2018/0329763	12/2017	George et al.	N/A	N/A
2018/0336785	12/2017	Ghannam et al.	N/A	N/A
2018/0356775	12/2017	Harvey	N/A	N/A
2018/0359111	12/2017	Harvey	N/A	N/A
2018/0364654	12/2017	Locke et al.	N/A	N/A
2019/0005025	12/2018	Malabarba	N/A	N/A
2019/0005200	12/2018	Zimmerman et al.	N/A	N/A
2019/0013023	12/2018	Pourmohammad et al.	N/A	N/A
2019/0017719	12/2018	Sinha et al.	N/A	N/A

2019/0025771	12/2018	Park et al.	N/A	N/A
2019/0026359	12/2018	Park et al.	N/A	N/A
2019/0037135	12/2018	Hedge	N/A	N/A
2019/0042988	12/2018	Brown et al.	N/A	N/A
2019/0088106	12/2018	Grundstrom	N/A	N/A
2019/0094824	12/2018	Xie et al.	N/A	N/A
2019/0096217	12/2018	Pourmohammad et al.	N/A	N/A
2019/0098113	12/2018	Park et al.	N/A	N/A
2019/0102840	12/2018	Perl et al.	N/A	N/A
2019/0121801	12/2018	Jethwa et al.	N/A	N/A
2019/0138512	12/2018	Pourmohammad et al.	N/A	N/A
2019/0138662	12/2018	Deutsch et al.	N/A	N/A
2019/0139315	12/2018	Locke et al.	N/A	N/A
2019/0147883	12/2018	Mellenthin et al.	N/A	N/A
2019/0158309	12/2018	Park	N/A	H04L 12/2812
2019/0163152	12/2018	Worrall et al.	N/A	N/A
2019/0268178	12/2018	Fairweather et al.	N/A	N/A
2019/0294975	12/2018	Sachs	N/A	N/A
2019/0310979	12/2018	Masuzaki et al.	N/A	N/A
2019/0347353	12/2018	Lawlor et al.	N/A	N/A
2019/0361411	12/2018	Park et al.	N/A	N/A
2019/0361412	12/2018	Park et al.	N/A	N/A
2019/0377306	12/2018	Harvey	N/A	N/A
2020/0076196	12/2019	Lee et al.	N/A	N/A
2020/0092127	12/2019	Park	N/A	H04L 12/2809
2020/0118053	12/2019	Chapin	N/A	N/A
2020/0133213	12/2019	Park et al.	N/A	N/A
2020/0142365	12/2019	Sharma et al.	N/A	N/A
2020/0159182	12/2019	Goyal	N/A	N/A
2020/0226156	12/2019	Borra et al.	N/A	N/A
2020/0234220	12/2019	Ma	N/A	G08G 1/148
2020/0285203	12/2019	Thakur et al.	N/A	N/A
2020/0285464	12/2019	Brebner	N/A	N/A
2020/0313924	12/2019	Park et al.	N/A	N/A
2020/0336328	12/2019	Harvey	N/A	N/A
2020/0348632	12/2019	Harvey	N/A	N/A
2020/0370771	12/2019	Alanqar et al.	N/A	N/A
2020/0387576	12/2019	Brett et al.	N/A	N/A
2020/0393157	12/2019	Turney et al.	N/A	N/A
2020/0394351	12/2019	Roemerman et al.	N/A	N/A
2020/0396208	12/2019	Brett et al.	N/A	N/A
2021/0010351	12/2020	Sun et al.	N/A	N/A
2021/0025612	12/2020	Sinha et al.	N/A	N/A
2021/0042299	12/2020	Migliori	N/A	N/A
2021/0043221	12/2020	Yelchuru et al.	N/A	N/A
2021/0104317	12/2020	Warner et al.	N/A	N/A
2021/0133670	12/2020	Cella	N/A	G06N 3/044
2021/0157312	12/2020	Cella et al.	N/A	N/A

2021/0173969	12/2020	Abbey	N/A	G06F 30/13
2021/0208546	12/2020	Locke et al.	N/A	N/A
2021/0240147	12/2020	Papadopoulos et al.	N/A	N/A
2021/0248289	12/2020	Fasano	N/A	N/A
2021/0258371	12/2020	Sundaresan	N/A	N/A
2021/0325070	12/2020	Endel et al.	N/A	N/A
2021/0342961	12/2020	Winter et al.	N/A	N/A
2021/0344695	12/2020	Palani et al.	N/A	N/A
2021/0381711	12/2020	Harvey et al.	N/A	N/A
2021/0381712	12/2020	Harvey et al.	N/A	N/A
2021/0382445	12/2020	Harvey et al.	N/A	N/A
2021/0383041	12/2020	Harvey et al.	N/A	N/A
2021/0383042	12/2020	Harvey et al.	N/A	N/A
2021/0383200	12/2020	Harvey et al.	N/A	N/A
2021/0383219	12/2020	Harvey et al.	N/A	N/A
2021/0383235	12/2020	Harvey et al.	N/A	N/A
2021/0383236	12/2020	Harvey et al.	N/A	N/A
2022/0066402	12/2021	Harvey et al.	N/A	N/A
2022/0066405	12/2021	Harvey	N/A	N/A
2022/0066432	12/2021	Harvey et al.	N/A	N/A
2022/0066434	12/2021	Harvey et al.	N/A	N/A
2022/0066528	12/2021	Harvey et al.	N/A	N/A
2022/0066722	12/2021	Harvey et al.	N/A	N/A
2022/0066754	12/2021	Harvey et al.	N/A	N/A
2022/0066761	12/2021	Harvey et al.	N/A	N/A
2022/0067226	12/2021	Harvey et al.	N/A	N/A
2022/0067227	12/2021	Harvey et al.	N/A	N/A
2022/0067230	12/2021	Harvey et al.	N/A	N/A
2022/0069863	12/2021	Harvey et al.	N/A	N/A
2022/0070293	12/2021	Harvey et al.	N/A	N/A
2022/0121965	12/2021	Chatterji et al.	N/A	N/A
2022/0138684	12/2021	Harvey	N/A	N/A
2022/0147000	12/2021	Cooley et al.	N/A	N/A
2022/0150124	12/2021	Cooley et al.	N/A	N/A
2022/0171907	12/2021	Chang et al.	N/A	N/A
2022/0215264	12/2021	Harvey et al.	N/A	N/A
2023/0010757	12/2022	Preciado	N/A	N/A
2023/0071312	12/2022	Preciado et al.	N/A	N/A
2023/0076011	12/2022	Preciado et al.	N/A	N/A
2023/0083703	12/2022	Meiners	N/A	N/A
2023/0214555	12/2022	Harvey et al.	N/A	N/A
2023/0252205	12/2022	Harvey et al.	N/A	N/A
2023/0334200	12/2022	Meiners	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019226217	12/2019	AU	N/A
2019226264	12/2019	AU	N/A
101415011	12/2008	CN	N/A

102136099	12/2010	CN	N/A
102136100	12/2010	CN	N/A
102650876	12/2011	CN	N/A
104040583	12/2013	CN	N/A
104603832	12/2014	CN	N/A
104919484	12/2014	CN	N/A
106204392	12/2015	CN	N/A
106406806	12/2016	CN	N/A
106960269	12/2016	CN	N/A
107147639	12/2016	CN	N/A
107598928	12/2017	CN	N/A
2 528 033	12/2011	EP	N/A
3 268 821	12/2017	EP	N/A
3 324 306	12/2017	EP	N/A
4 226 263	12/2022	EP	N/A
H10-049552	12/1997	JP	N/A
2003-162573	12/2002	JP	N/A
2007-018322	12/2006	JP	N/A
4073946	12/2007	JP	N/A
2008-107930	12/2007	JP	N/A
2013-152618	12/2012	JP	N/A
2014-044457	12/2013	JP	N/A
2016/0102923	12/2015	KR	N/A
WO-2009/020158	12/2008	WO	N/A
WO-2011/100255	12/2010	WO	N/A
WO-2013/050333	12/2012	WO	N/A
WO-2015/106702	12/2014	WO	N/A
WO-2015/145648	12/2014	WO	N/A
WO-2017/035536	12/2016	WO	N/A
WO-2017/192422	12/2016	WO	N/A
WO-2017/192770	12/2016	WO	N/A
WO-2017/194244	12/2016	WO	N/A
WO-2017/205330	12/2016	WO	N/A
WO-2017/213918	12/2016	WO	N/A
WO-2018/132112	12/2017	WO	N/A
WO-2018/204384	12/2017	WO	N/A
WO-2018/232147	12/2017	WO	N/A
WO-2019/018304	12/2018	WO	N/A
WO 2020/018147	12/2019	WO	G05B 15/02
WO-2020/061621	12/2019	WO	N/A
WO 2020/264095	12/2019	WO	G06Q 50/10
WO-2021/163287	12/2020	WO	N/A
WO-2022/042925	12/2021	WO	N/A
WO-2022/103812	12/2021	WO	N/A
WO-2022/103813	12/2021	WO	N/A
WO-2022/103820	12/2021	WO	N/A
WO-2022/103822	12/2021	WO	N/A
WO-2022/103824	12/2021	WO	N/A

WO-2022/103829	12/2021	WO	N/A
WO-2022/103831	12/2021	WO	N/A

OTHER PUBLICATIONS

Hietala, Jani, “Real-time two-way data transfer with a Digital Twin via web interface”, Master's Thesis, Aalto University School of Engineering, Espoo, Finland, Feb. 5, 2020, 54 pages. cited by examiner

Jaensch, Florian, et al., “Digital Twins of Manufacturing Systems as a Base for Machine Learning”, M2VIP 2018, Stuttgart, Germany, Nov. 20-22, 2018, pp. 1-6. cited by examiner

Xia, Kaishu, et al., “A digital twin to train deep reinforcement learning agent for smart manufacturing plants: Environment, interfaces and intelligence”, Journal of Manufacturing Systems, vol. 58, Part B, Jan. 2021, pp. 210-230. cited by examiner

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, 2018 (20 pages). cited by applicant

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, Sep. 15, 2018, 3 pages, (Abstract). cited by applicant

Balaji et al, “Demo Abstract: Portable Queries Using the Brick Schema for Building Applications,” BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (2 pages). cited by applicant

Balaji, B. et al., “Brick: Towards a Unified Metadata Schema For Buildings.” BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (10 pages). cited by applicant

Barricelli et al., “Human Digital Twin for Fitness Management,” IEEE Access, Feb. 2020, vol. 8 (pp. 26637-26664). cited by applicant

Bhattacharya et al., “Short Paper: Analyzing Metadata Schemas for Buildings—The Good, The Bad and The Ugly,” BuildSys '15, Seoul, South Korea, Nov. 4-5, 2015 (4 pages). cited by applicant

Bhattacharya, A., “Enabling Scalable Smart-Building Analytics,” Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2016-201, Dec. 15, 2016 (121 pages). cited by applicant

Brick, “Brick Schema: Building Blocks for Smart Buildings,” URL: chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://www.memoori.com/wp-content/uploads/2016/06/Brick_Schema_Whitepaper.pdf, Mar. 2019 (17 pages). cited by applicant

Brick, “Brick: Towards a Unified Metadata Schema for Buildings,” URL: chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://brickschema.org/papers/Brick_BuildSys_Presentation.pdf, Presented at BuildSys '16, Nov. 2016, 32 pages. cited by applicant

Brick, “Metadata Schema for Buildings,” URL: <https://brickschema.org/docs/Brick-Leaflet.pdf>, retrieved from internet Dec. 24, 2019 (3 pages). cited by applicant

Chinese Office Action on CN Appl. Ser. No. 201780003995.9 dated Apr. 8, 2021 (21 pages with English language translation). cited by applicant

Chinese Office action on CN Appl. Ser. No. 201780043400.2 dated Apr. 25, 2021 (15 pages with English language translation). cited by applicant

Clark et al., “Rule Induction with CN2: Some Recent Improvements,” Machine Learning—EWSL '91, Porto, Portugal, Mar. 6-8, 1991 (pp. 151-163). cited by applicant

Cronrath et al., “Enhancing Digital Twins through Reinforcement Learning,” 2019 IEEE 15th International Conference on Automation Science and Engineering (CASE), 2019 (6 pages). cited by applicant

Curry, E et al., “Linking building data in the cloud: Integrating cross-domain building data using linked data.” Advanced Engineering Informatics, 2013, 27 (pp. 206-219). cited by applicant

Digital Platform Litigation Documents Part 1, includes cover letter, dismissal of case DDE-1-21-cv-01796, IPR2023-00022 (documents filed Jan. 26, 2023-Oct. 7, 2022), and IPR2023-00085 (documents filed Jan. 26, 2023-Oct. 20, 2022) (748 pages total). cited by applicant

Digital Platform Litigation Documents Part 10, includes DDE-1-21-cv-01796 (documents filed Nov. 1, 2022-Dec. 22, 2021 (1795 pages total). cited by applicant

Digital Platform Litigation Documents Part 2, includes IPR2023-00085 (documents filed Oct. 20, 2022) (172 pages total). cited by applicant

Digital Platform Litigation Documents Part 3, includes IPR2023-00085 (documents filed Oct. 20, 2022) and IPR2023-00170 (documents filed Nov. 28, 2022-Nov. 7, 2022) (397 pages total). cited by applicant

Digital Platform Litigation Documents Part 4, includes IPR2023-00170 (documents filed Nov. 7, 2022) and IPR2023-00217 (documents filed Jan. 18, 2023-Nov. 15, 2022) (434 pages total). cited by applicant

Digital Platform Litigation Documents Part 5, includes IPR2023-00217 (documents filed Nov. 15, 2022) and IPR2023-00257 (documents filed Jan. 25, 2023-Nov. 23, 2022) (316 pages total). cited by applicant

Digital Platform Litigation Documents Part 6, includes IPR2023-00257 (documents filed Nov. 23, 2022) and IPR 2023-00346 (documents filed Jan. 3, 2023-Dec, 13, 2022) (295 pages total). cited by applicant

Digital Platform Litigation Documents Part 7, includes IPR 2023-00346 (documents filed Dec. 13, 2022) and IPR2023-00347 (documents filed Jan. 3, 2023-Dec. 13, 2022) (217 pages total). cited by applicant

Digital Platform Litigation Documents Part 8, includes IPR2023-00347 (documents filed Dec. 13, 2022), EDTX-2-22-cv-00243 (documents filed Sep. 20, 2022-Jun. 29, 2022), and DDE-1-21-cv-01796 (documents filed Feb. 3, 2023-Jan. 10, 2023 (480 pages total). cited by applicant

Digital Platform Litigation Documents Part 9, includes DDE-1-21-cv-01796 (documents filed Jan. 10, 2023-Nov. 1, 2022 (203 pages total). cited by applicant

Ding et al., “MB2C Mode1-Based Deep Reinforcement Learning for Multi-zone Building Control,” BuildSys '20, Virtual Event, Japan, Nov. 18-20, 2020 (pp. 50-59). cited by applicant

Ding et al., “MB2C Model-Based Deep Reinforcement Learning for Multi-zone Building Control,” BuildSys '20, Virtual Event, Japan, Nov. 18-20, 2020 (10 pages). cited by applicant

El Kaed, C. et al., “Building management insights driven by a multi-system semantic representation approach,” 2016 IEEE 3rd World Forum on Internet of Things (WF-IoT), Dec. 12-14, 2016, (pp. 520-525). cited by applicant

Ellis, C. et al., “Creating a room connectivity graph of a building from per-room sensor units.” BuildSys '12, Toronto, ON, Canada, Nov. 6, 2012 (7 pages). cited by applicant

Extended European Search Report on EP Application No. 18196948.6 dated Apr. 10, 2019 (9 pages). cited by applicant

Fierro et al., “Beyond a House of Sticks: Formalizing Metadata Tags with Brick,” BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (10 pages). cited by applicant

Fierro et al., “Dataset: An Open Dataset and Collection Tool for BMS Point Labels,” DATA'19, New York, NY, USA, Nov. 10, 2019 (3 pages). cited by applicant

Fierro et al., “Design and Analysis of a Query Processor for Brick,” ACM Transactions on Sensor Networks, Jan. 2018, vol. 1, No. 1, art. 1 (25 pages). cited by applicant

Fierro et al., “Design and Analysis of a Query Processor for Brick,” BuildSys '17, Delft, Netherlands, Nov. 8-9, 2017 (10 pages). cited by applicant

Fierro et al., “Mortar: An Open Testbed for Portable Building Analytics,” BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Fierro et al., “Why Brick is a Game Changer for Smart Buildings,” URL: https://brickschema.org/papers/Brick_Memoori_Webinar_Presentation.pdf, Memoori Webinar, 2019 (67 pages). cited by applicant

Fierro, “Writing Portable Building Analytics with the Brick Metadata Schema,” UC Berkeley, ACM E-Energy, 2019, 19 pages. cited by applicant

Fierro, G., “Design of an Effective Ontology and Query Processor Enabling Portable Building Applications,” Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2019-106, Jue 27, 2019 (118 pages). cited by applicant

File History for U.S. Appl. No. 12/776,159, filed May 7, 2010, 2 entries (513 + 209 = 722 pages). cited

by applicant

Final Conference Program, ACM BuildSys 2016, Stanford, Ca, USA, Nov. 15-17, 2016 (7 pages). cited by applicant

Gao et al., "A large-scale evaluation of automated metadata inference approaches on sensors from air handling units," Advanced Engineering Informatics, 2018, 37, 2 entries (12 + 5 = 17 pages). cited by applicant

Privat, Gilles, "Graph Models for Systems-of-Systems Digital Twins," Orange Innovation, IT & Services, Meylan, FR, Jun. 2021 (8 pages). cited by applicant

Gomez-Berbis et al., "SEdit: Semantic Digital Twin Based on Industrial IoT Data Management and Knowledge Graphs", Communications in Computer and Information Science, CCIS, vol. 1124, Springer Nature Switzerland AG, 2019 (pp. 178-188). cited by applicant

Harvey, T., "Quantum Part 3: The Tools of Autonomy, How PassiveLogic's Quantum Creator and Autonomy Studio software works," URL:

<https://www.automatedbuildings.com/news/jan22/articles/passive/211224010000passive.html>, Jan. 2022 (7 pages). cited by applicant

Harvey, T., "Quantum: The Digital Twin Standard for Buildings," URL:

<https://www.automatedbuildings.com/news/feb21/articles/passivelogic/210127124501passivelogic.html>, Feb. 2021 (6 pages). cited by applicant

Hu, S. et al., "Building performance optimisation: A hybrid architecture for the integration of contextual information and time-series data," Automation in Construction, 2016, 70 (pp. 51-61). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/013831 dated Mar. 31, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/035524 dated Jul. 24, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion on PCT Appl. No. PCT/US2022/034101 dated Oct. 10, 2022 (21 pages). cited by applicant

International Search Report and Written Opinion on PCT No. PCT/US2022/050079 dated Mar. 28, 2023 (21 pages). cited by applicant

International Search Report and Written Opinion on PCT/US2017/052060, mailed Oct. 5, 2017, 11 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052633, mailed Oct. 23, 2017, 9 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052829, mailed Nov. 27, 2017, 24 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/024068, mailed Jun. 15, 2018, 22 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052971, dated Mar. 1, 2019, 19 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052974, mailed Dec. 19, 2018, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052975, mailed Jan. 2, 2019, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052994, mailed Jan. 7, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2019/015481, dated May 17, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2020/058381, dated Jan. 27, 2021, 30 pages. cited by applicant

Invitation to Pay Additional Fees and, Where Applicable, Protest Fee on PCT Appl. No. PCT/US2022/050079, dated Feb. 6, 2023 (17 pages). cited by applicant

Japanese Office Action on JP Appl. Ser. No. 2018-534963 dated May 11, 2021 (16 pages with English language translation). cited by applicant

Kaur et al., "The Convergence of Digital Twin, IoT, and Machine Learning: Transforming Data into Action," Digital Twin Technologies and Smart Cities, Part of the Internet of Things: Technology, Communications and Computing (ITTCC) book series, first online: Jul. 23, 2019, Springer Link (pp. 3-17). cited by applicant

Kernighan, et al., "The C Programming Language," Prentice-Hall, Inc., Englewood Cliffs, NJ, 1978 (pp. 47-48 and 51-63). cited by applicant

Koh et al., "Plaster: An Integration, Benchmark, and Development Framework for Metadata Normalization Methods," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., "Scrabble: Transferrable Semi-Automated Semantic Metadata Normalization using Intermediate Representation," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., "Who can Access What, and When?" BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (4 pages). cited by applicant

Li et al., "Event Stream Processing with Out-of-Order Data Arrival," International Conferences on Distributed Computing Systems, 2007, (8 pages). cited by applicant

Molinaro, R. et al., "Embedding data analytics and CFD into the digital twin concept," Computers and Fluids, Jan. 15, 2021, vol. 214 (pp. 1-13). cited by applicant

Mostafa, F. et al., "An effective architecture of digital twin system to support human decision making and AI-driven autonomy," Concurrency and Computation: Practice and Experience, 2020, vol. 33 (pp. 1-15). cited by applicant

Nissin Electric Co., Ltd., "Smart power supply system (SPSS)," Outline of the scale verification plan, Nissin Electric Technical Report, Japan, Apr. 23, 2014, vol. 59, No. 1 (23 pages with English language abstract). cited by applicant

Passivelogic, "Explorer: Digital Twin Standard for Autonomous Systems. Made interactive." URL: <https://passivelogic.com/software/quantum-explorer/>, retrieved from internet Jan. 4, 2023 (13 pages). cited by applicant

Passivelogic, "Quantum: The Digital Twin Standard for Autonomous Systems, A physics-based ontology for next-generation control and AI." URL: <https://passivelogic.com/software/quantum-standard/>, retrieved from internet Jan. 4, 2023 (20 pages). cited by applicant

Quantum Alliance, "Quantum Explorer Walkthrough," 2022, (7 pages) (screenshots from video). cited by applicant

Results of the Partial International Search for PCT/US2018/052971, dated Jan. 3, 2019, 3 pages. cited by applicant

Sinha, Sudhi and Al Huraimel, Khaled, "Reimagining Businesses with AI" John Wiley & Sons, Inc., Hoboken, Nj, USA, First ed. published 2020, 152 pages. cited by applicant

Sinha, Sudhi R. and Park, Youngchoon, "Building an Effective IoT Ecosystem for Your Business," Johnson Controls International, Springer International Publishing, 2017 (286 pages). cited by applicant

Sinha, Sudhi, "Making Big Data Work for Your Business: A guide to effective Big Data analytics," Impackt Publishing Ltd., Birmingham, UK, Oct. 2014 (170 pages). cited by applicant

The Virtual Nuclear Tourist, "Calvert Cliffs Nuclear Power Plant," URL: <http://www.nucleartourist.com/us/calvert.htm>, Jan. 11, 2006 (2 pages). cited by applicant

University of California at Berkeley, EECS Department, "Enabling Scalable Smart-Building Analytics," URL: <https://www2.eecs.berkeley.edu/Pubs/TechRpts/2016/EECS-2016-201.html>, retrieved from internet Feb. 15, 2023 (7 pages). cited by applicant

Van Hoof, Bert, "Announcing Azure Digital Twins: Create digital replicas of spaces and infrastructure using cloud, AI and IoT," URL: <https://azure.microsoft.com/en-us/blog/announcing-azure-digital-twins-create-digital-replicas-of-spaces-and-infrastructure-using-cloud-ai-and-iot/>, Sep. 24, 2018 (11 pages). cited by applicant

W3C, "SPARQL: Query Language for RDF," located on The Wayback Machine, URL: <https://web.archive.org/web/20161230061728/http://www.w3.org/TR/rdf-sparql-query/>), retrieved from internet Nov. 15, 2022 (89 pages). cited by applicant

Wang et al., "Linking energy-cyber-physical systems with occupancy prediction and interpretation through WiFi probe-based ensemble classification," *Applied Energy*, 2019, vol. 236 (pp. 55-69). cited by applicant

Wei et al., "Development and Implementation of Software Gateways of Fire Fighting Subsystem Running on EBI," *Control, Automation and Systems Engineering, IITA International Conference on, IEEE*, Jul. 2009 (pp. 9-12). cited by applicant

White et al., "Reduce building maintenance costs with AWS IoT TwinMaker Knowledge Graph," *The Internet of Things on AWS—Official Blog*, URL: <https://aws.amazon.com/blogs/iot/reduce-building-maintenance-costs-with-aws-iot-twinmaker-knowledge-graph/>, Nov. 18, 2022 (10 pages). cited by applicant

Wikipedia, "Digital Twin," URL: https://en.wikipedia.org/wiki/Neural_network, Retrieved from Internet Feb. 15, 2022 (7 pages). cited by applicant

Wikipedia, "Neural Network", URL: https://en.wikipedia.org/wiki/Neural_network, Retrieved from Internet Feb. 18, 2022 (7 pages). cited by applicant

Yao et al., "State of the art review on model predictive control (MPC) in Heating Ventilation and Air-conditioning (HVAC) field," *Building and Environment*, 2021, vol. 200 (18 pages). cited by applicant

Zhou, Q et al., "Knowledge-infused and Consistent Complex Event Processing over Real-time and Persistent Streams," *Further Generation Computer Systems*, 2017, 76 (pp. 391-406). cited by applicant

Primary Examiner: Stevens; Robert

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/529,120 filed Nov. 17, 2021 which is incorporated herein by reference in its entirety.

BACKGROUND

(1) This application relates generally to a building system of a building. This application relates more particularly to systems for managing and processing data of the building system.

(2) A building may aggregate and store building data received from building equipment and/or other data sources. The building data can be stored in a database. The building can include a building system that operates control algorithms against the data of the database to control the building equipment. However, the development of the control algorithms may be time consuming and require a significant amount of software development. Furthermore, the control algorithms may lack flexibility to adapt to changing circumstances in the building.

SUMMARY

(3) A building system including one or more storage devices storing instructions thereon that, when executed by one or more processors, cause the one or more processors to store a data structure of a digital twin of an entity of a building, the data structure storing information associated with at least one of the entity or a plurality of entities of the building, execute a learning algorithm to construct a trigger rule and an action rule with the data structure of the digital twin as an input to the learning algorithm, store the trigger rule and the action rule in the digital twin, determine that the trigger rule of the digital twin is triggered by comparing at least some of the information of the data

structure against one or more conditions of the trigger rule by querying the data structure for data values and comparing the data values against the one or more conditions of the trigger rule, determine an action of the action rule of the digital twin responsive to determining that the trigger rule is triggered by executing the action rule, and cause one or more devices to operate based on the action determined by the action rule.

(4) In some embodiments, the instructions cause the one or more processors to provide the action to one or more other digital twins, determine that the action triggers one or more trigger rules of the one or more other digital twins, and determine one or more actions of one or more action rules of the one or more other digital twins by executing the one or more action rules responsive to the action triggering the one or more trigger rules.

(5) In some embodiments, the data structure is a graph data structure including nodes and edges between the nodes, wherein the nodes represent the entity, the entities, and data points of the entity and the entities. In some embodiments, the edges represent relationships between the entity, the entities, and the data points of the entity and the entities.

(6) In some embodiments, the instructions cause the one or more processors to cause the one or more devices to operate based on the action by sending a command to the one or more devices to perform the action or store the action in the data structure and retrieve the action from the data structure and send the command based on the action retrieved from the data structure to the one or more devices.

(7) In some embodiments, the instructions cause the one or more processors to perform a learning algorithm to learn the trigger rule and the action rule.

(8) In some embodiments, the instructions cause the one or more processors to perform a learning algorithm to learn one or more first parameters for the trigger rule and subsequently learn one or more second parameters for the action rule based at least in part on the one or more first parameters for the trigger rule.

(9) In some embodiments, the instructions cause the one or more processors to learn one or more parameters of the trigger rule or the action rule by adjusting a value of the one or more parameters of the trigger rule or the action rule to different values and simulating one or more states resulting from the different values of the one or more parameters of the trigger rule or the action rule. In some embodiments, the instructions cause the one or more processors to determine one or more updated values for the one or more parameters of the trigger rule or the action rule based on the one or more states resulting from the different values of the one or more parameters of the trigger rule or the action rule.

(10) In some embodiments, the instructions cause the one or more processors to determine the one or more updated value for the one or more parameters of the trigger rule or the action rule by determining a particular reward for the one or more states resulting from the different values of the one or more parameters of the trigger rule or the action rule, training a model that predicts a reward based on the particular reward for the one or more states and the different values of the one or more parameters of the trigger rule or the action rule, and performing an optimization that determines the one or more updated value for the one or more parameters of the trigger rule or the action rule based on the model and the reward.

(11) In some embodiments, the instructions cause the one or more processors to generate the digital twin by identifying actions and data associated with the entity based on the data structure, identifying that the entities are related to the entity based on the data structure, identifying actions and data associated with the entities based on the data structure, and generating the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the entities.

(12) In some embodiments, the instructions cause the one or more processors to generate the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the entities by determining trigger rules for the data of the entity and

the data of the entities, determining action rules for the actions of the entity and the actions of the entities, simulating combinations of the trigger rules and action rules and determining rewards for the combinations, and selecting the trigger rule and the action rule from the combinations of the trigger rules and the action rules based on the rewards of the combinations.

(13) In some embodiments, the instructions cause the one or more processors to generate the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the entities by determining trigger rules for the data of the entity and the data of the entities, the trigger rules including the trigger rule, determining action rules for the actions of the entity and the actions of the entities, the action rules including the action rule, monitoring behavior of the building system of the building, determine a relationship between the trigger rule of the trigger rules and the action rule of the action rules indicated by the behavior of the building system, and selecting the trigger rule from the trigger rules and the action rule from the action rules based on the relationship.

(14) Another implementation of the present disclosure is a method including storing, by a processing circuit, a data structure of a digital twin of an entity of a building, the data structure storing information associated with at least one of the entity or a plurality of entities of the building, executing, by the processing circuit, a learning algorithm to construct a trigger rule and an action rule with the data structure of the digital twin as an input to the learning algorithm, storing, by the processing circuit, the trigger rule and the action rule in the digital twin, determining, by the processing circuit, that the trigger rule of the digital twin is triggered by comparing at least some of the information of the data structure against one or more conditions of the trigger rule by querying the data structure for data values and comparing the data values against the one or more conditions of the trigger rule, determining, by the processing circuit, an action of the action rule of the digital twin responsive to determining that the trigger rule is triggered by executing the action rule, and causing, by the processing circuit, one or more devices to operate based on the action determined by the action rule.

(15) In some embodiments, the method includes providing, by the processing circuit, the action to one or more other digital twins, determining, by the processing circuit, that the action triggers one or more trigger rules of the one or more other digital twins, and determining, by the processing circuit, one or more actions of one or more action rules of the one or more other digital twins by executing the one or more action rules responsive to the action triggering the one or more trigger rules.

(16) In some embodiments, the data structure is a graph data structure including nodes and a edges between the nodes, wherein the nodes represent the entity, the entities, and data points of the entity and the entities. In some embodiments, the edges represent relationships between the entity, the entities, and the data points of the entity and the entities.

(17) In some embodiments, causing, by the processing circuit, the one or more devices to operate based on the action includes sending a command to the one or more devices to perform the action or store the action in the data structure and retrieve the action from the data structure and send the command based on the action retrieved from the data structure to the one or more devices.

(18) In some embodiments, the method includes performing, by the processing circuit, a learning algorithm to learn the trigger rule and the action rule.

(19) In some embodiments, the method includes performing, by the processing circuit, a learning algorithm to learn one or more first parameters for the trigger rule and subsequently learn one or more second parameters for the action rule based at least in part on the one or more first parameters for the trigger rule.

(20) In some embodiments, the method includes learning, by the processing circuit, one or more parameters of the trigger rule or the action rule by adjusting a value of the one or more parameters of the trigger rule or the action rule to different values, simulating one or more states resulting from the different values of the one or more parameters of the trigger rule or the action rule, and

determining one or more updated values for the one or more parameters of the trigger rule or the action rule based on the one or more states resulting from the different values of the one or more parameters of the trigger rule or the action rule.

(21) In some embodiments, the method includes generating, by the processing circuit, the digital twin by identifying actions and data associated with the entity based on the data structure, identifying that the entities are related to the entity based on the data structure, identifying actions and data associated with the entities based on the data structure, and generating the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the entities.

(22) Another implementation is one or more non-transitory computer-readable media storing instructions that, when executed by one or more processors, cause the one or more processors to perform operations. The operations include storing a data structure of a digital twin of an entity of a building, the data structure storing information associated with at least one of the entity or a plurality of entities of the building, executing a learning algorithm to construct a trigger rule and an action rule with the data structure of the digital twin as an input to the learning algorithm, storing the trigger rule and the action rule in the digital twin, determining that the trigger rule of the digital twin is triggered by comparing at least some of the information of the data structure against one or more conditions of the trigger rule by querying the data structure for data values and comparing the data values against the one or more conditions of the trigger rule, determining an action of the action rule of the digital twin responsive to determining that the trigger rule is triggered by executing the action rule, and causing one or more devices to operate based on the action determined by the action rule.

(23) In one implementation, the operations further include identifying that a relationship exists between the trigger rule and the action rule and determining the action of the action rule responsive to determining that the trigger rule is triggered and that the relationship exists between the trigger rule and the action rule.

(24) In one implementation, the operations further include storing a second digital twin associated with a second entity of the building, the second digital twin comprising a second action rule, identifying a relationship between the trigger rule of the digital twin and the action rule of the second digital twin, and determining a second action based on the second action rule of the second digital twin responsive to determining that the trigger rule of the digital twin is triggered.

(25) In one implementation, the operations further include: receiving first timeseries data from the entity, receiving second timeseries data from a second entity of the building separate from the entity, and determining that the trigger rule of the digital twin is triggered by comparing the first timeseries data and the second timeseries data against the one or more conditions of the trigger rule.

(26) In one implementation, the one or more non-transitory computer-readable media the operations to generate the digital twin further include: identifying actions and data associated with the entity based on the data structure, identifying that the plurality of entities are related to the entity based on the data structure, identifying actions and data associated with the plurality of entities based on the data structure, and generating the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the plurality of entities.

(27) In one implementation, the one or more non-transitory computer-readable media operations further cause the one or more processors to generate the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the plurality of entities by: determining trigger rules for the data of the entity and the data of the plurality of entities, determining action rules for the actions of the entity and the actions of the plurality of entities, simulating combinations of the trigger rules and action rules and determining

rewards for the combinations, and selecting the trigger rule and the action rule from the combinations of the trigger rules and the action rules based on the rewards of the combinations.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Various objects, aspects, features, and advantages of the disclosure will become more apparent and better understood by referring to the detailed description taken in conjunction with the accompanying drawings, in which like reference characters identify corresponding elements throughout. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.
- (2) FIG. 1 is a block diagram of a building data platform including an edge platform, a cloud platform, and a twin manager, according to an exemplary embodiment.
- (3) FIG. 2 is a graph projection of the twin manager of FIG. 1 including application programming interface (API) data, capability data, policy data, and services, according to an exemplary embodiment.
- (4) FIG. 3 is another graph projection of the twin manager of FIG. 1 including application programming interface (API) data, capability data, policy data, and services, according to an exemplary embodiment.
- (5) FIG. 4 is a graph projection of the twin manager of FIG. 1 including equipment and capability data for the equipment, according to an exemplary embodiment.
- (6) FIG. 5 is a block diagram of a system for managing a digital twin where an artificial intelligence agent can be executed to infer information for an entity of a graph, according to an exemplary embodiment.
- (7) FIG. 6 is a flow diagram of a process for executing an artificial intelligence agent to infer and/or predict information, according to an exemplary embodiment.
- (8) FIG. 7 is a diagram of a digital twin including a connector and a database, according to an exemplary embodiment.
- (9) FIG. 8 is a block diagram of a digital twin including triggers, connectors, actions, and a graph, according to an exemplary embodiment.
- (10) FIG. 9 is a block diagram of a people counter digital twin, an HVAC digital twin, and a facility manager digital twin that have triggers and actions that are interconnected, according to an exemplary embodiment.
- (11) FIG. 10 is a block diagram of an employee digital twin, a calendar digital twin, a meeting room digital twin, and a cafeteria digital twin that have triggers and actions that are interconnected, according to an exemplary embodiment.
- (12) FIG. 11 is a flow diagram an agent of a digital twin executing a trigger rule and an action rule, according to an exemplary embodiment.
- (13) FIG. 12 is a block diagram of a trigger rule of a thermostat digital twin where parameters of the trigger rule is trained, according to an exemplary embodiment.
- (14) FIG. 13 is a flow diagram of a process for identifying values for the parameters of the trigger rule of FIG. 12, according to an exemplary embodiment.
- (15) FIG. 14 is a minimization that can be performed to identify the values for the parameters of the trigger rule of FIGS. 12-13, according to an exemplary embodiment.
- (16) FIG. 15 is a block diagram of an action rule of a thermostat digital twin where parameters of the action rule is trained, according to an exemplary embodiment.
- (17) FIG. 16 is lists of states of a zone and of an air handler unit that can be used to train the parameters of the trigger rule and the action rule of the thermostat digital twins of FIGS. 12-15, according to an exemplary embodiment.

- (18) FIG. 17 is a block diagram of a trigger rule of a chemical reactor digital twin where parameters of the trigger rule are trained, according to an exemplary embodiment.
- (19) FIG. 18 is a flow diagram of a process for identifying values for the parameters of the trigger rule of FIG. 17, according to an exemplary embodiment.
- (20) FIG. 19 is a minimization that can be performed to identify the values for the parameters of the trigger rule of FIGS. 17-18, according to an exemplary embodiment.
- (21) FIG. 20 is a block diagram of an action rule of a chemical reactor digital twin where parameters of the action rule are trained, according to an exemplary embodiment.
- (22) FIG. 21 is lists of states of a reactor and a feed of a reactor that can be included in the trigger rule and the action rule of FIGS. 12-15, according to an exemplary embodiment.
- (23) FIG. 22 is a block diagram of triggers and actions that can be constructed and learned for a digital twin, according to an exemplary embodiment.
- (24) FIG. 23 is a flow diagram of a process for constructing triggers and actions for a digital twin, according to an exemplary embodiment.

DETAILED DESCRIPTION

(25) Overview

- (26) Referring generally to the FIGURES, systems and methods for digital twins of a building are shown, according to various exemplary embodiments. A digital twin can be a virtual representing of a building and/or an entity of the building (e.g., space, piece of equipment, occupant, etc.). Furthermore, the digital twin can represent a service performed in a building, e.g., facility management, equipment maintenance, etc.
- (27) In some embodiments, the digital twin can include an information data store and a connector. The information data store can store the information describing the entity that the digital twin operates for (e.g., attributes of the entity, measurements associated with the entity, control points or commands of the entity, etc.). In some embodiments, the data store can be a graph including various nodes and edges. The connector can be a software component the provides telemetry from the entity (e.g., physical device) to the information store. Furthermore, the digital twin can include artificial intelligence (AI), e.g., an AI agent. The AI can be one or more machine learning algorithms and/or models that operate based on information of the information data store and outputs information.
- (28) In some embodiments, the AI agent for the digital twin can call an AI service to determine inferences about potential future events and/or predict future data values. In some embodiments, the inferences are potential future states. In some embodiments, the inferences predict a timeseries of a data point into the future. The inferences could be inferred indoor temperature for an hour, inferred future air quality from 15 minute air quality readings, etc. In some embodiments, the digital twin can store and inferred information in a graph data store as a node in the graph data store related to an entity that the digital twin represents. In some embodiments, the digital twin, or other digital twins, can operate against the inferred data, e.g., operate to construct and implement control algorithms for operating equipment of a building based on predicted future data points of the building.
- (29) Furthermore, the AI agent can include various triggers and/or actions, conditions that define when and how command and control occurs for an entity. The triggers and actions can be rule based conditional and operational statements that are associated with a specific digital twin, e.g., are stored and executed by an AI agent of the digital twin. In some embodiments, the building system can identify actions and/or triggers (or parameters for the actions and/or triggers) through machine learning algorithms. In some embodiments, the building system can evaluate the conditions/context of the graph and determine and/or modify the triggers and actions of a digital twin.
- (30) Referring now to FIG. 1, a building data platform **100** including an edge platform **102**, a cloud platform **106**, and a twin manager **108** are shown, according to an exemplary embodiment. The

edge platform **102**, the cloud platform **106**, and the twin manager **108** can each be separate services deployed on the same or different computing systems. In some embodiments, the cloud platform **106** and the twin manager **108** are implemented in off premises computing systems, e.g., outside a building. The edge platform **102** can be implemented on-premises, e.g., within the building. However, any combination of on-premises and off-premises components of the building data platform **100** can be implemented.

(31) The building data platform **100** includes applications **110**. The applications **110** can be various applications that operate to manage the building subsystems **122**. The applications **110** can be remote or on-premises applications (or a hybrid of both) that run on various computing systems. The applications **110** can include an alarm application **168** configured to manage alarms for the building subsystems **122**. The applications **110** include an assurance application **170** that implements assurance services for the building subsystems **122**. In some embodiments, the applications **110** include an energy application **172** configured to manage the energy usage of the building subsystems **122**. The applications **110** include a security application **174** configured to manage security systems of the building.

(32) In some embodiments, the applications **110** and/or the cloud platform **106** interacts with a user device **176**. In some embodiments, a component or an entire application of the applications **110** runs on the user device **176**. The user device **176** may be a laptop computer, a desktop computer, a smartphone, a tablet, and/or any other device with an input interface (e.g., touch screen, mouse, keyboard, etc.) and an output interface (e.g., a speaker, a display, etc.).

(33) The applications **110**, the twin manager **108**, the cloud platform **106**, and the edge platform **102** can be implemented on one or more computing systems, e.g., on processors and/or memory devices. For example, the edge platform **102** includes processor(s) **118** and memories **120**, the cloud platform **106** includes processor(s) **124** and memories **126**, the applications **110** include processor(s) **164** and memories **166**, and the twin manager **108** includes processor(s) **148** and memories **150**.

(34) The processors can be a general purpose or specific purpose processors, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. The processors may be configured to execute computer code and/or instructions stored in the memories or received from other computer readable media (e.g., CDROM, network storage, a remote server, etc.).

(35) The memories can include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. The memories can include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. The memories can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. The memories can be communicably connected to the processors and can include computer code for executing (e.g., by the processors) one or more processes described herein.

(36) The edge platform **102** can be configured to provide connection to the building subsystems **122**. The edge platform **102** can receive messages from the building subsystems **122** and/or deliver messages to the building subsystems **122**. The edge platform **102** includes one or multiple gateways, e.g., the gateways **112-116**. The gateways **112-116** can act as a gateway between the cloud platform **106** and the building subsystems **122**. The gateways **112-116** can be the gateways described in U.S. Provisional Patent Application No. 62/951,897 filed Dec. 20, 2019, the entirety of which is incorporated by reference herein. In some embodiments, the applications **110** can be deployed on the edge platform **102**. In this regard, lower latency in management of the building subsystems **122** can be realized.

(37) The edge platform **102** can be connected to the cloud platform **106** via a network **104**. The network **104** can communicatively couple the devices and systems of building data platform **100**. In some embodiments, the network **104** is at least one of and/or a combination of a Wi-Fi network, a wired Ethernet network, a ZigBee network, a Bluetooth network, and/or any other wireless network. The network **104** may be a local area network or a wide area network (e.g., the Internet, a building WAN, etc.) and may use a variety of communications protocols (e.g., BACnet, IP, LON, etc.). The network **104** may include routers, modems, servers, cell towers, satellites, and/or network switches. The network **104** may be a combination of wired and wireless networks.

(38) The cloud platform **106** can be configured to facilitate communication and routing of messages between the applications **110**, the twin manager **108**, the edge platform **102**, and/or any other system. The cloud platform **106** can include a platform manager **128**, a messaging manager **140**, a command processor **136**, and an enrichment manager **138**. In some embodiments, the cloud platform **106** can facilitate messaging between the building data platform **100** via the network **104**.

(39) The messaging manager **140** can be configured to operate as a transport service that controls communication with the building subsystems **122** and/or any other system, e.g., managing commands to devices (C2D), commands to connectors (C2C) for external systems, commands from the device to the cloud (D2C), and/or notifications. The messaging manager **140** can receive different types of data from the applications **110**, the twin manager **108**, and/or the edge platform **102**. The messaging manager **140** can receive change on value data **142**, e.g., data that indicates that a value of a point has changed. The messaging manager **140** can receive timeseries data **144**, e.g., a time correlated series of data entries each associated with a particular time stamp. Furthermore, the messaging manager **140** can receive command data **146**. All of the messages handled by the cloud platform **106** can be handled as an event, e.g., the data **142-146** can each be packaged as an event with a data value occurring at a particular time (e.g., a temperature measurement made at a particular time).

(40) The cloud platform **106** includes a command processor **136**. The command processor **136** can be configured to receive commands to perform an action from the applications **110**, the building subsystems **122**, the user device **176**, etc. The command processor **136** can manage the commands, determine whether the commanding system is authorized to perform the particular commands, and communicate the commands to the commanded system, e.g., the building subsystems **122** and/or the applications **110**. The commands could be a command to change an operational setting that control environmental conditions of a building, a command to run analytics, etc.

(41) The cloud platform **106** includes an enrichment manager **138**. The enrichment manager **138** can be configured to enrich the events received by the messaging manager **140**. The enrichment manager **138** can be configured to add contextual information to the events. The enrichment manager **138** can communicate with the twin manager **108** to retrieve the contextual information. In some embodiments, the contextual information is an indication of information related to the event. For example, if the event is a timeseries temperature measurement of a thermostat, contextual information such as the location of the thermostat (e.g., what room), the equipment controlled by the thermostat (e.g., what VAV), etc. can be added to the event. In this regard, when a consuming application, e.g., one of the applications **110** receives the event, the consuming application can operate based on the data of the event, the temperature measurement, and also the contextual information of the event.

(42) The enrichment manager **138** can solve a problem that when a device produces a significant amount of information, the information may contain simple data without context. An example might include the data generated when a user scans a badge at a badge scanner of the building subsystems **122**. This physical event can generate an output event including such information as "DeviceBadgeScannerID," "BadgeID," and/or "Date/Time." However, if a system sends this data to a consuming application, e.g., Consumer A and a Consumer B, each customer may need to call the building data platform knowledge service to query information with queries such as, "What

space, build, floor is that badge scanner in?” or “What user is associated with that badge?”

(43) By performing enrichment on the data feed, a system can be able to perform inferences on the data. A result of the enrichment may be transformation of the message “DeviceBadgeScannerId, BadgeId, Date/Time,” to “Region, Building, Floor, Asset, DeviceId, BadgeId, UserName, EmployeeId, Date/Time Scanned.” This can be a significant optimization, as a system can reduce the number of calls by $1/n$, where n is the number of consumers of this data feed.

(44) By using this enrichment, a system can also have the ability to filter out undesired events. If there are 100 building in a campus that receive 100,000 events per building each hour, but only 1 building is actually commissioned, only $1/10$ of the events are enriched. By looking at what events are enriched and what events are not enriched, a system can do traffic shaping of forwarding of these events to reduce the cost of forwarding events that no consuming application wants or reads.

(45) An example of an event received by the enrichment manager **138** may be:

(46) TABLE-US-00001 { “id”: “someguid”, “eventType”: “Device_Heartbeat”, “eventTime”: “2018-01-27T00:00:00+00:00” “eventValue”: 1, “deviceId”: “someguid” }

(47) An example of an enriched event generated by the enrichment manager **138** may be:

(48) TABLE-US-00002 { “id”: “someguid”, “eventType”: “Device_Heartbeat”, “eventTime”: “2018-01-27T00:00:00+00:00” “eventValue”: 1, “deviceId”: “someguid”, “buildingName”: “Building-48”, “buildingID”: “SomeGuid”, “panelID”: “SomeGuid”, “panelName”: “Building-48-Panel-13”, “cityID”: 371, “cityName”: “Milwaukee”, “stateID”: 48, “stateName”: “Wisconsin (WI)”, “countryID”: 1, “countryName”: “United States” }

(49) By receiving enriched events, an application of the applications **110** can be able to populate and/or filter what events are associated with what areas. Furthermore, user interface generating applications can generate user interfaces that include the contextual information based on the enriched events.

(50) The cloud platform **106** includes a platform manager **128**. The platform manager **128** can be configured to manage the users and/or subscriptions of the cloud platform **106**. For example, what subscribing building, user, and/or tenant utilizes the cloud platform **106**. The platform manager **128** includes a provisioning service **130** configured to provision the cloud platform **106**, the edge platform **102**, and the twin manager **108**. The platform manager **128** includes a subscription service **132** configured to manage a subscription of the building, user, and/or tenant while the entitlement service **134** can track entitlements of the buildings, users, and/or tenants.

(51) The twin manager **108** can be configured to manage and maintain a digital twin. The digital twin can be a digital representation of the physical environment, e.g., a building. The twin manager **108** can include a change feed generator **152**, a schema and ontology **154**, a projection manager **156**, a policy manager **158**, an entity, relationship, and event database **160**, and a graph projection database **162**.

(52) The graph projection manager **156** can be configured to construct graph projections and store the graph projections in the graph projection database **162**. Examples of graph projections are shown in FIGS. **11-13**. Entities, relationships, and events can be stored in the database **160**.

(53) The graph projection manager **156** can retrieve entities, relationships, and/or events from the database **160** and construct a graph projection based on the retrieved entities, relationships and/or events. In some embodiments, the database **160** includes an entity-relationship collection for multiple subscriptions. Subscriptions can be subscriptions of a particular tenant as described in FIG. **24**.

(54) In some embodiment, the graph projection manager **156** generates a graph projection for a particular user, application, subscription, and/or system. In this regard, the graph projection can be generated based on policies for the particular user, application, and/or system in addition to an ontology specific for that user, application, and/or system. In this regard, an entity could request a graph projection and the graph projection manager **156** can be configured to generate the graph projection for the entity based on policies and an ontology specific to the entity. The policies can

indicate what entities, relationships, and/or events the entity has access to. The ontology can indicate what types of relationships between entities the requesting entity expects to see, e.g., floors within a building, devices within a floor, etc. Another requesting entity may have an ontology to see devices within a building and applications for the devices within the graph.

(55) The graph projections generated by the graph projection manager **156** and stored in the graph projection database **162** can be a knowledge graph and is an integration point. For example, the graph projections can represent floor plans and systems associated with each floor. Furthermore, the graph projections can include events, e.g., telemetry data of the building subsystems **122**. The graph projections can show application services as nodes and API calls between the services as edges in the graph. The graph projections can illustrate the capabilities of spaces, users, and/or devices. The graph projections can include indications of the building subsystems **122**, e.g., thermostats, cameras, VAVs, etc. The graph projection database **162** can store graph projections that keep up a current state of a building.

(56) The graph projections of the graph projection database **162** can be digital twins of a building. Digital twins can be digital replicas of physical entities that enable an in-depth analysis of data of the physical entities and provide the potential to monitor systems to mitigate risks, manage issues, and utilize simulations to test future solutions. Digital twins can play an important role in helping technicians find the root cause of issues and solve problems faster, in supporting safety and security protocols, and in supporting building managers in more efficient use of energy and other facilities resources. Digital twins can be used to enable and unify security systems, employee experience, facilities management, sustainability, etc.

(57) In some embodiments the enrichment manager **138** can use a graph projection of the graph projection database **162** to enrich events. In some embodiments, the enrichment manager **138** can identify nodes and relationships that are associated with, and are pertinent to, the device that generated the event. For example, the enrichment manager **138** could identify a thermostat generating a temperature measurement event within the graph. The enrichment manager **138** can identify relationships between the thermostat and spaces, e.g., a zone that the thermostat is located in. The enrichment manager **138** can add an indication of the zone to the event.

(58) Furthermore, the command processor **136** can be configured to utilize the graph projections to command the building subsystems **122**. The command processor **136** can identify a policy for a commanding entity within the graph projection to determine whether the commanding entity has the ability to make the command. For example, the command processor **136**, before allowing a user to make a command, determine, based on the graph projection database **162**, to determine that the user has a policy to be able to make the command.

(59) In some embodiments, the policies can be conditional based policies. For example, the building data platform **100** can apply one or more conditional rules to determine whether a particular system has the ability to perform an action. In some embodiments, the rules analyze a behavioral based biometric. For example, a behavioral based biometric can indicate normal behavior and/or normal behavior rules for a system. In some embodiments, when the building data platform **100** determines, based on the one or more conditional rules, that an action requested by a system does not match a normal behavior, the building data platform **100** can deny the system the ability to perform the action and/or request approval from a higher level system.

(60) For example, a behavior rule could indicate that a user has access to log into a system with a particular IP address between 8 A.M. through 5 P.M. However, if the user logs in to the system at 7 P.M., the building data platform **100** may contact an administrator to determine whether to give the user permission to log in.

(61) The change feed generator **152** can be configured to generate a feed of events that indicate changes to the digital twin, e.g., to the graph. The change feed generator **152** can track changes to the entities, relationships, and/or events of the graph. For example, the change feed generator **152** can detect an addition, deletion, and/or modification of a node or edge of the graph, e.g., changing

the entities, relationships, and/or events within the database **160**. In response to detecting a change to the graph, the change feed generator **152** can generate an event summarizing the change. The event can indicate what nodes and/or edges have changed and how the nodes and edges have changed. The events can be posted to a topic by the change feed generator **152**.

(62) The change feed generator **152** can implement a change feed of a knowledge graph. The building data platform **100** can implement a subscription to changes in the knowledge graph. When the change feed generator **152** posts events in the change feed, subscribing systems or applications can receive the change feed event. By generating a record of all changes that have happened, a system can stage data in different ways, and then replay the data back in whatever order the system wishes. This can include running the changes sequentially one by one and/or by jumping from one major change to the next. For example, to generate a graph at a particular time, all change feed events up to the particular time can be used to construct the graph.

(63) The change feed can track the changes in each node in the graph and the relationships related to them, in some embodiments. If a user wants to subscribe to these changes and the user has proper access, the user can simply submit a web API call to have sequential notifications of each change that happens in the graph. A user and/or system can replay the changes one by one to reinstitute the graph at any given time slice. Even though the messages are “thin” and only include notification of change and the reference “id/seq id,” the change feed can keep a copy of every state of each node and/or relationship so that a user and/or system can retrieve those past states at any time for each node. Furthermore, a consumer of the change feed could also create dynamic “views” allowing different “snapshots” in time of what the graph looks like from a particular context. While the twin manager **108** may contain the history and the current state of the graph based upon schema evaluation, a consumer can retain a copy of that data, and thereby create dynamic views using the change feed.

(64) The schema and ontology **154** can define the message schema and graph ontology of the twin manager **108**. The message schema can define what format messages received by the messaging manager **140** should have, e.g., what parameters, what formats, etc. The ontology can define graph projections, e.g., the ontology that a user wishes to view. For example, various systems, applications, and/or users can be associated with a graph ontology. Accordingly, when the graph projection manager **156** generates an graph projection for a user, system, or subscription, the graph projection manager **156** can generate a graph projection according to the ontology specific to the user. For example, the ontology can define what types of entities are related in what order in a graph, for example, for the ontology for a subscription of “Customer A,” the graph projection manager **156** can create relationships for a graph projection based on the rule:

Region.Math.Building.Math.Floor.Math.Space.Math.Asset

(65) For the ontology of a subscription of “Customer B,” the graph projection manager **156** can create relationships based on the rule:

Building.Math.Floor.Math.Asset

(66) The policy manager **158** can be configured to respond to requests from other applications and/or systems for policies. The policy manager **158** can consult a graph projection to determine what permissions different applications, users, and/or devices have. The graph projection can indicate various permissions that different types of entities have and the policy manager **158** can search the graph projection to identify the permissions of a particular entity. The policy manager **158** can facilitate fine grain access control with user permissions. The policy manager **158** can apply permissions across a graph, e.g., if “user can view all data associated with floor 1” then they see all subsystem data for that floor, e.g., surveillance cameras, HVAC devices, fire detection and response devices, etc.

(67) The twin manager **108** includes a query manager **165** and a twin function manager **167**. The query manger **164** can be configured to handle queries received from a requesting system, e.g., the user device **176**, the applications **110**, and/or any other system. The query manager **165** can receive

queries that include query parameters and context. The query manager **165** can query the graph projection database **162** with the query parameters to retrieve a result. The query manager **165** can then cause an event processor, e.g., a twin function, to operate based on the result and the context. In some embodiments, the query manager **165** can select the twin function based on the context and/or perform operations based on the context. In some embodiments, the query manager **165** is configured to perform the operations described with reference to FIGS. 5-10.

(68) The twin function manager **167** can be configured to manage the execution of twin functions. The twin function manager **167** can receive an indication of a context query that identifies a particular data element and/or pattern in the graph projection database **162**. Responsive to the particular data element and/or pattern occurring in the graph projection database **162** (e.g., based on a new data event added to the graph projection database **162** and/or change to nodes or edges of the graph projection database **162**, the twin function manager **167** can cause a particular twin function to execute. The twin function can execute based on an event, context, and/or rules. The event can be data that the twin function executes against. The context can be information that provides a contextual description of the data, e.g., what device the event is associated with, what control point should be updated based on the event, etc. The twin function manager **167** can be configured to perform the operations of the FIGS. 11-15.

(69) Referring now to FIG. 2, a graph projection **200** of the twin manager **108** including application programming interface (API) data, capability data, policy data, and services is shown, according to an exemplary embodiment. The graph projection **200** includes nodes **202-240** and edges **250-272**. The nodes **202-240** and the edges **250-272** are defined according to the key **201**. The nodes **202-240** represent different types of entities, devices, locations, points, persons, policies, and software services (e.g., API services). The edges **250-272** represent relationships between the nodes **202-240**, e.g., dependent calls, API calls, inferred relationships, and schema relationships (e.g., BRICK relationships).

(70) The graph projection **200** includes a device hub **202** which may represent a software service that facilitates the communication of data and commands between the cloud platform **106** and a device of the building subsystems **122**, e.g., door actuator **214**. The device hub **202** is related to a connector **204**, an external system **206**, and a digital asset “Door Actuator” **208** by edge **250**, edge **252**, and edge **254**.

(71) The cloud platform **106** can be configured to identify the device hub **202**, the connector **204**, the external system **206** related to the door actuator **214** by searching the graph projection **200** and identifying the edges **250-254** and edge **258**. The graph projection **200** includes a digital representation of the “Door Actuator,” node **208**. The digital asset “Door Actuator” **208** includes a “DeviceNameSpace” represented by node **207** and related to the digital asset “Door Actuator” **208** by the “Property of Object” edge **256**.

(72) The “Door Actuator” **214** has points and timeseries. The “Door Actuator” **214** is related to “Point A” **216** by a “has_a” edge **260**. The “Door Actuator” **214** is related to “Point B” **218** by a “has_A” edge **258**. Furthermore, timeseries associated with the points A and B are represented by nodes “TS” **220** and “TS” **222**. The timeseries are related to the points A and B by “has_a” edge **264** and “has_a” edge **262**. The timeseries “TS” **220** has particular samples, sample **210** and **212** each related to “TS” **220** with edges **268** and **266** respectively. Each sample includes a time and a value. Each sample may be an event received from the door actuator that the cloud platform **106** ingests into the entity, relationship, and event database **160**, e.g., ingests into the graph projection **200**.

(73) The graph projection **200** includes a building **234** representing a physical building. The building includes a floor represented by floor **232** related to the building **234** by the “has_a” edge from the building **234** to the floor **232**. The floor has a space indicated by the edge “has_a” **270** between the floor **232** and the space **230**. The space has particular capabilities, e.g., is a room that can be booked for a meeting, conference, private study time, etc. Furthermore, the booking can be

anceled. The capabilities for the floor 232 are represented by capabilities 228 related to space 230 by edge 280. The capabilities 228 are related to two different commands, command “book room” 224 and command “cancel booking” 226 related to capabilities 228 by edge 284 and edge 282 respectively.

(74) If the cloud platform 106 receives a command to book the space represented by the node, space 230, the cloud platform 106 can search the graph projection 200 for the capabilities for the 228 related to the space 230 to determine whether the cloud platform 106 can book the room.

(75) In some embodiments, the cloud platform 106 could receive a request to book a room in a particular building, e.g., the building 234. The cloud platform 106 could search the graph projection 200 to identify spaces that have the capabilities to be booked, e.g., identify the space 230 based on the capabilities 228 related to the space 230. The cloud platform 106 can reply to the request with an indication of the space and allow the requesting entity to book the space 230.

(76) The graph projection 200 includes a policy 236 for the floor 232. The policy 236 is related set for the floor 232 based on a “To Floor” edge 274 between the policy 236 and the floor 232. The policy 236 is related to different roles for the floor 232, read events 238 via edge 276 and send command 240 via edge 278. The policy 236 is set for the entity 203 based on has edge 251 between the entity 203 and the policy 236.

(77) The twin manager 108 can identify policies for particular entities, e.g., users, software applications, systems, devices, etc. based on the policy 236. For example, if the cloud platform 106 receives a command to book the space 230. The cloud platform 106 can communicate with the twin manager 108 to verify that the entity requesting to book the space 230 has a policy to book the space. The twin manager 108 can identify the entity requesting to book the space as the entity 203 by searching the graph projection 200. Furthermore, the twin manager 108 can further identify the edge has 251 between the entity 203 and the policy 236 and the edge 1178 between the policy 236 and the command 240.

(78) Furthermore, the twin manager 108 can identify that the entity 203 has the ability to command the space 230 based on the edge 1174 between the policy 236 and the edge 270 between the floor 232 and the space 230. In response to identifying the entity 203 has the ability to book the space 230, the twin manager 108 can provide an indication to the cloud platform 106.

(79) Furthermore, if the entity makes a request to read events for the space 230, e.g., the sample 210 and the sample 212, the twin manager 108 can identify the edge has 251 between the entity 203 and the policy 236, the edge 1178 between the policy 236 and the read events 238, the edge 1174 between the policy 236 and the floor 232, the “has_a” edge 270 between the floor 232 and the space 230, the edge 268 between the space 230 and the door actuator 214, the edge 260 between the door actuator 214 and the point A 216, the “has_a” edge 264 between the point A 216 and the TS 220, and the edges 268 and 266 between the TS 220 and the samples 210 and 212 respectively.

(80) Referring now to FIG. 3, a graph projection 300 of the twin manager 108 including application programming interface (API) data, capability data, policy data, and services is shown, according to an exemplary embodiment. The graph projection 300 includes the nodes and edges described in the graph projection 200 of FIG. 2. The graph projection 300 includes a connection broker 354 related to capabilities 228 by edge 398a. The connection broker 354 can be a node representing a software application configured to facilitate a connection with another software application. In some embodiments, the cloud platform 106 can identify the system that implements the capabilities 228 by identifying the edge 398a between the capabilities 228 and the connection broker 354.

(81) The connection broker 354 is related to an agent that optimizes a space 356 via edge 398b. The agent represented by the node 356 can book and cancel bookings for the space represented by the node 230 based on the edge 398b between the connection broker 354 and the node 356 and the edge 398a between the capabilities 228 and the connection broker 354.

(82) The connection broker 354 is related to a cluster 308 by edge 398c. Cluster 308 is related to connector B 302 via edge 398e and connector A 306 via edge 398d. The connector A 306 is related

to an external subscription service **304**. A connection broker **310** is related to cluster **308** via an edge **311** representing a rest call that the connection broker represented by node **310** can make to the cluster represented by cluster **308**.

(83) The connection broker **310** is related to a virtual meeting platform **312** by an edge **354**. The node **312** represents an external system that represents a virtual meeting platform. The connection broker represented by node **310** can represent a software component that facilitates a connection between the cloud platform **106** and the virtual meeting platform represented by node **312**. When the cloud platform **106** needs to communicate with the virtual meeting platform represented by the node **312**, the cloud platform **106** can identify the edge **354** between the connection broker **310** and the virtual meeting platform **312** and select the connection broker represented by the node **310** to facilitate communication with the virtual meeting platform represented by the node **312**.

(84) A capabilities node **318** can be connected to the connection broker **310** via edge **360**. The capabilities **318** can be capabilities of the virtual meeting platform represented by the node **312** and can be related to the node **312** through the edge **360** to the connection broker **310** and the edge **354** between the connection broker **310** and the node **312**. The capabilities **318** can define capabilities of the virtual meeting platform represented by the node **312**. The node **320** is related to capabilities **318** via edge **362**. The capabilities may be an invite bob command represented by node **316** and an email bob command represented by node **314**. The capabilities **318** can be linked to a node **320** representing a user, Bob. The cloud platform **106** can facilitate email commands to send emails to the user Bob via the email service represented by the node **304**. The node **304** is related to the connect a node **306** via edge **398f**. Furthermore, the cloud platform **106** can facilitate sending an invite for a virtual meeting via the virtual meeting platform represented by the node **312** linked to the node **318** via the edge **358**.

(85) The node **320** for the user Bob can be associated with the policy **236** via the “has” edge **364**. Furthermore, the node **320** can have a “check policy” edge **366** with a portal node **324**. The device API node **328** has a check policy edge **370** to the policy node **236**. The portal node **324** has an edge **368** to the policy node **236**. The portal node **324** has an edge **323** to a node **326** representing a user input manager (UIM). The portal node **324** is related to the UIM node **326** via an edge **323**. The UIM node **326** has an edge **323** to a device API node **328**. The UIM node **326** is related to the door actuator node **214** via edge **372**. The door actuator node **214** has an edge **374** to the device API node **328**. The door actuator **214** has an edge **335** to the connector virtual object **334**. The device hub **332** is related to the connector virtual object via edge **380**. The device API node **328** can be an API for the door actuator **214**. The connector virtual object **334** is related to the device API node **328** via the edge **331**.

(86) The device API node **328** is related to a transport connection broker **330** via an edge **329**. The transport connection broker **330** is related to a device hub **332** via an edge **378**. The device hub represented by node **332** can be a software component that hands the communication of data and commands for the door actuator **214**. The cloud platform **106** can identify where to store data within the graph projection **300** received from the door actuator by identifying the nodes and edges between the points **216** and **218** and the device hub node **332**. Similarly, the cloud platform **308** can identify commands for the door actuator that can be facilitated by the device hub represented by the node **332**, e.g., by identifying edges between the device hub node **332** and an open door node **352** and an lock door node **350**. The door actuator **114** has an edge “has mapped an asset” **280** between the node **214** and a capabilities node **348**. The capabilities node **348** and the nodes **352** and **350** are linked by edges **396** and **394**.

(87) The device hub **332** is linked to a cluster **336** via an edge **384**. The cluster **336** is linked to connector A **340** and connector B **338** by edges **386** and the edge **389**. The connector A **340** and the connector B **338** is linked to an external system **344** via edges **388** and **390**. The external system **344** is linked to a door actuator **342** via an edge **392**.

(88) Referring now to FIG. 4, a graph projection **400** of the twin manager **108** including equipment

and capability data for the equipment is shown, according to an exemplary embodiment. The graph projection **400** includes nodes **402-456** and edges **360-498f**. The cloud platform **106** can search the graph projection **400** to identify capabilities of different pieces of equipment.

(89) A building node **404** represents a particular building that includes two floors. A floor **1** node **402** is linked to the building node **404** via edge **460** while a floor **2** node **406** is linked to the building node **404** via edge **462**. The floor **2** includes a particular room **2023** represented by edge **464** between floor **2** node **406** and room **2023** node **408**. Various pieces of equipment are included within the room **2023**. A light represented by light node **416**, a bedside lamp node **414**, a bedside lamp node **412**, and a hallway light node **410** are related to room **2023** node **408** via edge **466**, edge **472**, edge **470**, and edge **468**.

(90) The light represented by light node **416** is related to a light connector **426** via edge **484**. The light connector **426** is related to multiple commands for the light represented by the light node **416** via edges **484**, **486**, and **488**. The commands may be a brightness setpoint **424**, an on command **425**, and a hue setpoint **428**. The cloud platform **106** can receive a request to identify commands for the light represented by the light **416** and can identify the nodes **424-428** and provide an indication of the commands represented by the node **424-428** to the requesting entity. The requesting entity can then send commands for the commands represented by the nodes **424-428**.

(91) The bedside lamp node **414** is linked to a bedside lamp connector **481** via an edge **413**. The connector **481** is related to commands for the bedside lamp represented by the bedside lamp node **414** via edges **492**, **496**, and **494**. The command nodes are a brightness setpoint node **432**, an on command node **434**, and a color command **436**. The hallway light **410** is related to a hallway light connector **446** via an edge **498d**. The hallway light connector **446** is linked to multiple commands for the hallway light node **410** via edges **498g**, **498f**, and **498e**. The commands are represented by an on command node **452**, a hue setpoint node **450**, and a light bulb activity node **448**.

(92) The graph projection **400** includes a name space node **422** related to a server A node **418** and a server B node **420** via edges **474** and **476**. The name space node **422** is related to the bedside lamp connector **481**, the bedside lamp connector **444**, and the hallway light connector **446** via edges **482**, **480**, and **478**. The bedside lamp connector **444** is related to commands, e.g., the color command node **440**, the hue setpoint command **438**, a brightness setpoint command **456**, and an on command **454** via edges **498c**, **498b**, **498a**, and **498**.

(93) Referring now to FIG. 5, a system **500** for managing a digital twin where an artificial intelligence agent can be executed to infer and/or predict information for an entity of a graph is shown, according to an exemplary embodiment. The system **500** can be components of the building data platform **100**, e.g., components run on the processors and memories of the edge platform **102**, the cloud platform **106**, the twin manager **108**, and/or the applications **110**. The system **500** can, in some implementations, implement a digital twin with artificial intelligence.

(94) A digital twin (or a shadow) may be a computing entity that describes a physical thing (e.g., a building, spaces of a building, devices of a building, people of the building, equipment of the building, etc.) through modeling the physical thing through a set of attributes that define the physical thing. A digital twin can refer to a digital replica of physical assets (a physical device twin) and can be extended to store processes, people, places, systems that can be used for various purposes. The digital twin can include both the ingestion of information and actions learned and executed through artificial intelligence agents.

(95) In FIG. 5, the digital twin can be a graph **529** managed by the twin manager **108** and/or artificial intelligence agents **570**. In some embodiments, the digital twin is the combination of the graph **529** with the artificial intelligence agents **570**. In some embodiments, the digital twin enables the creation of a chronological time-series database of telemetry events for analytical purposes. In some embodiments, the graph **529** uses the BRICK schema.

(96) The twin manager **108** stores the graph **529** which may be a graph data structure including various nodes and edges interrelating the nodes. The graph **529** may be the same as, or similar to,

the graph projections described herein with reference to FIGS. 1-4. The graph 529 includes nodes 510-526 and edges 528-546. The graph 529 includes a building node 526 representing a building that has a floor indicated by the “has” edge 546 to the floor node 522. The floor node 522 is related to a zone node 510 via a “has” edge 544 indicating that the floor represented by the node 522 has a zone represented by the zone 510.

(97) The floor node 522 is related to the zone node 518 by the “has” edge 540 indicating that the floor represented by the floor node 522 has another zone represented by the zone node 518. The floor node 522 is related to another zone node 524 via a “has” edge 542 representing that the floor represented by the floor node 522 has a third zone represented by the zone node 524.

(98) The graph 529 includes an AHU node 514 representing an AHU of the building represented by the building node 526. The AHU node 514 is related by a “supplies” edge 530 to the VAV node 512 to represent that the AHU represented by the AHU node 514 supplies air to the VAV represented by the VAV node 512. The AHU node 514 is related by a “supplies” edge 536 to the VAV node 520 to represent that the AHU represented by the AHU node 514 supplies air to the VAV represented by the VAV node 520. The AHU node 514 is related by a “supplies” edge 532 to the VAV node 516 to represent that the AHU represented by the AHU node 514 supplies air to the VAV represented by the VAV node 516.

(99) The VAV node 516 is related to the zone node 518 via the “serves” edge 534 to represent that the VAV represented by the VAV node 516 serves (e.g., heats or cools) the zone represented by the zone node 518. The VAV node 520 is related to the zone node 524 via the “serves” edge 538 to represent that the VAV represented by the VAV node 520 serves (e.g., heats or cools) the zone represented by the zone node 524. The VAV node 512 is related to the zone node 510 via the “serves” edge 528 to represent that the VAV represented by the VAV node 512 serves (e.g., heats or cools) the zone represented by the zone node 510.

(100) Furthermore, the graph 529 includes an edge 533 related to a timeseries node 564. The timeseries node 564 can be information stored within the graph 529 and/or can be information stored outside the graph 529 in a different database (e.g., a timeseries database). In some embodiments, the timeseries node 564 stores timeseries data (or any other type of data) for a data point of the VAV represented by the VAV node 516. The data of the timeseries node 564 can be aggregated and/or collected telemetry data of the timeseries node 564.

(101) Furthermore, the graph 529 includes an edge 537 related to a timeseries node 566. The timeseries node 566 can be information stored within the graph 529 and/or can be information stored outside the graph 529 in a different database (e.g., a timeseries database). In some embodiments, the timeseries node 566 stores timeseries data (or any other type of data) for a data point of the VAV represented by the VAV node 516. The data of the timeseries node 564 can be inferred information, e.g., data inferred by one of the artificial intelligence agents 570 and written into the timeseries node 564 by the artificial intelligence agent 570. In some embodiments, the timeseries 546 and/or 566 are stored in the graph 529 but are stored as references to timeseries data stored in a timeseries database.

(102) The twin manager 108 includes various software components. For example, the twin manager 108 includes a device management component 548 for managing devices of a building. The twin manager 108 includes a tenant management component 550 for managing various tenant subscriptions. The twin manager 108 includes an event routing component 552 for routing various events. The twin manager 108 includes an authentication and access component 554 for performing user and/or system authentication and granting the user and/or system access to various spaces, pieces of software, devices, etc. The twin manager 108 includes a commanding component 556 allowing a software application and/or user to send commands to physical devices. The twin manager 108 includes an entitlement component 558 that analyzes the entitlements of a user and/or system and grants the user and/or system abilities based on the entitlements. The twin manager 108 includes a telemetry component 560 that can receive telemetry data from physical systems and/or

devices and ingest the telemetry data into the graph **529**. Furthermore, the twin manager **108** includes an integrations component **562** allowing the twin manager **108** to integrate with other applications.

(103) The twin manager **108** includes a gateway **506** and a twin connector **508**. The gateway **506** can be configured to integrate with other systems and the twin connector **508** can be configured to allow the gateway **506** to integrate with the twin manager **108**. The gateway **506** and/or the twin connector **508** can receive an entitlement request **502** and/or an inference request **504**. The entitlement request **502** can be a request received from a system and/or a user requesting that an AI agent action be taken by the AI agent **570**. The entitlement request **502** can be checked against entitlements for the system and/or user to verify that the action requested by the system and/or user is allowed for the user and/or system. The inference request **504** can be a request that the AI agent **570** generates an inference, e.g., a projection of information, a prediction of a future data measurement, an extrapolated data value, etc.

(104) The cloud platform **106** is shown to receive an entitlement request **586**. The request **586** can be received from a system, application, and/or user device (e.g., from the applications **110**, the building subsystems **122**, and/or the user device **176**). The entitlement request **586** may be a manual or automated request. In some embodiments, the request **586** can be automated via an API request, e.g., when such an entitlement to an AI model is enabled for a particular tenant/end-customer of the data platform **100**. In some embodiments, the request **586** may be a manual request by a person asking for an inference/future state of the building. The request **586** could be automatically made to keep the state updated on a particular cadence. In some embodiments, a request for a future state of one digital twin can cause a re-calculation of the future states of related digital twins automatically. For example, based on a request asking for the future occupancy of a room in a building in the coming week, a re-calculation of the future AHU operating value recommendations to reduce the spread of infectious diseases may be triggered. The results of these automatic triggers determining future states not directly requested by the request **586** can be collected and presented to the caller of the request **586** as causal future states.

(105) The entitlement request **586** may be a request for the AI agent **570** to perform an action, e.g., an action that the requesting system and/or user has an entitlement for. The cloud platform **106** can receive the entitlement request **586** and check the entitlement request **586** against an entitlement database **584** storing a set of entitlements to verify that the requesting system has access to the user and/or system. The cloud platform **106**, responsive to the entitlement request **586** being approved, can create a job for the AI agent **570** to perform. The created job can be added to a job request topic **580** of a set of topics **578**.

(106) The job request topic **580** can be fed to AI agents **570**. For example, the topics **580** can be fanned out to various AI agents **570** based on the AI agent that each of the topics **580** pertains to (e.g., based on an identifier that identifies an agent and is included in each job of the topic **580**). The AI agents **570** include a service client **572**, a connector **574**, and a model **576**. The model **576** can be loaded into the AI agent **570** from a set of AI models stored in the AI model storage **568**. The AI model storage **568** can store models for making energy load predictions for a building, weather forecasting models for predicting a weather forecast, action/decision models to take certain actions responsive to certain conditions being met, an occupancy model for predicting occupancy of a space and/or a building, etc. The models of the AI model storage **568** can be neural networks (e.g., convolutional neural networks, recurrent neural networks, deep learning networks, etc.), decision trees, support vector machines, and/or any other type of artificial intelligence, machine learning, and/or deep learning category. In some embodiments, the models are rule based triggers and actions that include various parameters for setting a condition and defining an action.

(107) The AI agent **570** can include triggers **595** and actions **597**. The triggers **595** can be conditional rules that, when met, cause one or more of the actions **597**. The triggers **595** can be executed based on information stored in the graph **529** and/or data received from the building

subsystems **122**. The actions **597** can be executed to determine commands, actions, and/or outputs. The output of the actions **597** can be stored in the graph **529** and/or communicated to the building subsystems **122**.

(108) In some embodiments, the triggers **595** and/or the actions **597** are stored as nodes in the graph **529**. The nodes for the triggers **595** and/or the actions **597** can be stored as capability nodes. Capability nodes may be nodes that describe operations that a digital twin can perform (e.g., is configured and/or capable of performing). Capabilities are described with reference to FIGS. **1-4**. In some embodiments, the graph **529** stores a first node representing a particular digital twin, agent, artificial intelligence, machine learning entity, etc. The graph **529** can further store one or more second nodes related to the first node via one or more edges (or one or more nodes). The one or more second nodes may describe capabilities of the digital twin, agent, artificial intelligence, machine learning entity, etc. The capabilities may be triggers and/or actions (e.g., the triggers **595** and/or actions **597**). The first node may be related to a particular component node (e.g., the VAV node **516**) via another edge to represent that the digital twin, agent, artificial intelligence, machine learning entity, etc. makes inferences or other data determinations for the component (e.g., a VAV) represented by the particular component node (e.g., the VAV node **516**).

(109) The AI agent **570** can include a service client **572** that causes an instance of an AI agent to run. The instance can be hosted by the artificial intelligence service client **588**. The client **588** can cause a client instance **592** to run and communicate with the AI agent **570** via a gateway **590**. The client instance **592** can include a service application **594** that interfaces with a core algorithm **598** via a functional interface **596**. The core algorithm **598** can run the model **576**, e.g., train the model **576** and/or use the model **576** to make inferences and/or predictions.

(110) In some embodiments, the core algorithm **598** can be configured to perform learning based on the graph **529**. In some embodiments, the core algorithm **598** can read and/or analyze the nodes and relationships of the graph **529** to make decisions. In some embodiments, the core algorithm **598** can be configured to use telemetry data (e.g., the timeseries data **564**) from the graph **529** to make inferences on and/or perform model learning. In some embodiments, the result of the inferences can be the timeseries **566**. In some embodiments, the timeseries **564** is an input into the model **576** that predicts the timeseries **566**.

(111) In some embodiments, the core algorithm **598** can generate the timeseries **566** as an inference for a data point, e.g., a prediction of values for the data point at future times. The timeseries **564** may be actual data for the data point. In this regard, the core algorithm **598** can learn and train by comparing the inferred data values against the true data values. In this regard, the model **576** can be trained by the core algorithm **598** to improve the inferences made by the model **576**.

(112) Referring now to FIG. **6**, a process **600** for executing an artificial intelligence agent to infer and/or predict information is shown, according to an exemplary embodiment. The process **600** can be performed by the system **500** and/or components of the system **500**. The process **600** can be performed by the building data platform **100**. Furthermore, the process **600** can be performed by any computing device described herein.

(113) In step **602**, the twin manager **108** receives information from a physical device and stores the information, or a link to the information, in the graph **529**. For example, the telemetry component **560** can receive telemetry data from physical devices, e.g., the building subsystems **122**. The telemetry can be measured data values, a log of historical equipment commands, etc. The telemetry component **560** can store the received information in the graph **529** by relating a node storing the information to a node representing the physical device. For example, the telemetry component **560** can store timeseries data as the timeseries **566** along by identifying that the physical device is a VAV represented by the VAV node **516** and that an edge **537** relates the VAV node **516** to the timeseries node **566**.

(114) In step **604**, the twin manager **108** and/or the cloud platform **106** receives an indication to execute an artificial intelligence agent of an entity represented in the graph **529**, the AI agent being

associated with a model. In some embodiments, the indication is created by a user and provided via the user device **176**. In some embodiments, the indication is created by an application, e.g., one of the applications **110**. In some embodiments, the indication is a triggering event that triggers the agent and is received from the building subsystems **122** and/or another agent (e.g., an output of one agent fed into another agent).

(115) In some embodiments, the AI agent is an agent for a specific entity represented in the graph **529**. For example, the agent could be a VAV maintenance agent configured to identify whether a VAV (e.g., a VAV represented by the nodes **512**, **530**, and/or **516**) should have maintenance performed at a specific time. Another agent could be a floor occupant prediction agent that is configured to predict the occupancy of a particular floor of a building, e.g., the floor represented by the floor node **522**.

(116) Responsive to receiving the indication, in step **606**, the AI agent **570** causes a client instance **592** to run the model **576** based on the information received in step **602**. In some embodiments, the information received in step **602** is provided directly to the AI agent **570**. In some embodiments, the information is read from the graph **529** by the AI agent **570**.

(117) In step **608**, the AI agent **570** stores the inferred and/or predicted information in the graph **529** (or stores the inferred and/or predicted information in a separate data structure with a link to the graph **529**). In some embodiments, the AI agent **570** identifies that the node that represents the physical entity that the AI agent **570** inferred and/or predicted information for, e.g., the VAV represented by the VAV **516**. The AI agent **570** can identify that the timeseries node **566** stores the inferred and/or predicted information by identifying the edge **537** between the VAV node **516** and the timeseries node **566**.

(118) In step **610**, the AI agent **570** can retrieve the inferred or predicted information from the graph **529** responsive to receiving an indication to execute the model of the AI agent **570** of the inferred or predicted information, e.g., similar to the step **604**. In step **612**, the AI agent **570** can execute one or more actions based on the inferred and/or predicted information of the step **610** based the inferred and/or predicted information retrieved from the graph **529**. In some embodiments, the AI agent **570** executes the model **576** based on the inferred and/or predicted information.

(119) In step **614**, the AI agent **570** can train the model **576** based on the inferred or predicted information read from the graph **529** and received actual values for the inferred or predicted information. In some embodiments, the AI agent **570** can train and update parameters of the model **576**. For example, the timeseries **564** may represent actual values for a data point of the VAV represented by the VAV node **516**. The timeseries **566** can be the inferred and/or predicted information. The AI agent **570** can compare the timeseries **564** and the timeseries **566** to determine an error in the inferences and/or predictions of the model **576**. The error can be used by the model **576** to update and train the model **576**.

(120) Referring now to FIG. 7, a digital twin **700** including a connector and a database is shown, according to an exemplary embodiment. The digital twin **700** can be a software component stored and/or managed by the building data platform **100**. The building data platform **100** includes connectors **702** and a database **704**. The database **704** can store data attributes for a physical entity, e.g., a building, a VAV, etc. that describe the current state and/or operation of the physical entity. The connector **702** can be a software component that receives data from the physical device represented by the digital twin **700** and updates the attributes of the database **704**. For example, the connector **702** can ingest device telemetry data into the database **704** to update the attributes of the digital twin **700**.

(121) Referring now to FIG. 8, a digital twin **800** including triggers **802**, connectors **804**, actions **806**, and a graph **808** is shown, according to an exemplary embodiment. The digital twin **800** can be a digital replica of physical assets (e.g., a physical device twin, sensor twin, actuator twin, building device twin, etc.) and can be used to store processes, people, places, systems that can be

used for various purposes. The digital twins can be created, managed, stored, and/or operated on by the building data platform **100**.

(122) In some cases, the devices can also be actuated on (told to perform an action). For example, a thermostat has sensors to measure temperature and humidity. A thermostat can also be asked to perform an action of setting the setpoint for a HVAC system. In this regard, the digital twin **800** can be configured so that information that the digital twin **800** can be made aware of can be stored by the digital twin **800** and there are also actions that the digital twin **800** can take.

(123) The digital twin **800** can include a connector **804** that ingests device telemetry into the graph **808** and/or update the digital twin attributes stored in the graph **808**. In some embodiments, the connectors **804** can ingest external data received from external data sources into the graph **808**. The external data could be weather data, calendar data, etc. In some embodiments, the connectors **804** can send commands back to the devices, e.g., the actions determined by the actions **806**.

(124) The digital twin **800** includes triggers **802** which can set conditional logic for triggering the actions **706**. The digital twin **800** can apply the attributes stored in the graph **808** against a rule of the triggers **802**. When a particular condition of the rule of the triggers **802** involving that attribute is met, the actions **706** can execute. One example of a trigger could be a conditional question, “when the temperature of the zone managed by the thermostat reaches x degrees Fahrenheit.” When the question is met by the attributes stored in the graph **808**, a rule of the actions **706** can execute.

(125) The digital twin **800** can, when executing the actions **806**, update an attribute of the graph **808**, e.g., a setpoint, an operating setting, etc. These attributes can be translated into commands that the building data platform **100** can send to physical devices that operate based on the setpoint, the operating setting, etc. An example of an action rule for the actions **806** could be the statement, “update the setpoint of the HVAC system for a zone to x Degrees Fahrenheit.”

(126) In some embodiments, the triggers **802** and/or the actions **806** are predefined and/or manually defined through user input of the user device **176**. In some cases, it may be difficult for a user to determine what the parameter values of the trigger rule should be (e.g., what values maximize a particular reward or minimize a particular penalty). Similarly, it may be difficult for a user to determine what the parameter values of the action rule should be (e.g., what values maximize the particular reward or minimize the particular penalty). Furthermore, even if the user is able to identify the ideal parameter values for the triggers **802** and the actions **806**, the ideal values for the parameters may not be constant and may instead change over time. Therefore, it would be desirable if the values of the attributes for the triggers **802** and the actions **806** are tuned optimally and automatically by the building data platform **100** by observing the responses from other related digital twins.

(127) Causal patterns between one or more digital twins having their triggering conditions satisfied and one or more digital twins (including the triggering digital twin) actuating by sending specific commands to their physical counterparts could be learned and defined by the building data platform **100**. Automated learning can be used by the building data platform **100** during real operations, by running simulations using digital twins, or using predicted inference within the digital twin. There may not even be the need for all standard operating procedures in building systems to be defined upfront by a user since patterns of interaction between digital twins can be learned by the building data platform **100** to define and recommend those to building and facility owners.

(128) Referring now to FIG. 9, a system **900** of digital twins including a people counter digital twin **902**, an HVAC digital twin **904**, and a facility manager digital twin **906** that are interconnected is shown, according to an exemplary embodiment. In FIG. 9, the people counter digital twin **902** includes triggers **908**, connectors **910**, actions, and/or the graph **926**.

(129) The system **900** further includes an HVAC digital twin **904** that includes triggers, connectors **916**, actions **918**, and/or the graph **928**. The system further includes the facility manager **906** that includes triggers, connectors **922**, actions **924**, and/or the graph **930**. In some embodiments, the

graph **926**, the graph **928**, and the graph **930** are the same graph or different graphs. In some embodiments, the graphs **926-930** are the graph **529**.

(130) The people counter digital twin **902** can output a “low occupancy” attribute which can be stored in the graph **926** and/or provided to the HVAC digital twin **904** and/or the facility manager digital twin **906**, in some embodiments. In some embodiments, if all of the digital twins use and/or have access to the same graph, if the people counter digital twin **902** stores the low occupancy indicator in the graph, the HVAC digital twin **904** and the facility manager digital twin **906** can read the attribute from the graph. In some embodiment, a rules engine **926** can store rules that link the twins **902**, **904**, and **906** together. The rules engine **926** can determine whether the triggers of the various digital twins are triggered, e.g., the trigger **908**. Furthermore, the rules engine **926** can determine (based on one or more rules stored by the rules engine **926**) that if the trigger **908** of the people counter digital twin **902** is triggered, the actions **918** of the HVAC digital twin **904** and the actions **924** of the facility manager digital twin **906** should be executed.

(131) In some embodiments, the trigger **908** is the logical condition, “when there are less than twenty people in a particular area.” Responsive to an occupancy count of the particular area is less than twenty, which the people counter digital twin **902** can determine from models and/or information of the graph **926**, a low occupancy indication can be generated.

(132) Responsive to the trigger **908** being triggered, the rules engine **926** can cause the actions **918** to execute to switch an HVAC mode to an economy mode. The economy mode status for an HVAC system can be stored in the graph **928** and/or communicated to an HVAC controller to execute on. Responsive to the trigger **908** being triggered, the rules engine **926** can cause the actions **924** to execute to notify a facility manager of the low occupancy status, e.g., send a notification to a user device of the facility manager.

(133) In some embodiments, the digital twins of the system **900** can be solution twins, e.g., the people counter twin **902**, the HVAC digital twin **904**, the facility manager twin **906**, etc. The digital twin can be a solution twin because it represents a particular software solutions for the building. For example, in some embodiments, an occupancy sensor digital twin of a zone could be triggered with under-utilized criteria (e.g., the triggering of the people counter digital twin **902** shown in FIG. 9). The people counter digital twin **902** could be configured to identify what AHU is serving the zone that it has made an occupancy detection for based on the nodes and/or edges of the graph **926** relating a zone node for the zone and an AHU node for the AHU. In some embodiments, the AHU digital twin can evaluate the desired setting for the zone through running a simulation with one or more models. In some embodiments, an FM digital twin can evaluate space arrangement and/or purposing.

(134) Referring now to FIG. 10, a system **1000** including an employee digital twin **1002**, a calendar digital twin **1006**, a meeting room digital twin **1004**, and a cafeteria digital twin **1008** that are interconnected is shown, according to an exemplary embodiment. The system **1000** includes a solution digital twin for an employee, a meeting room, a cafeteria, and a calendar. In the system **1000**, an employee digital twin **1002** and a calendar digital twin **1006** trigger and a rules engine **926** causes one or more associated digital twins, a meeting room digital twin **1004** and a cafeteria digital twin **1008** to execute responsive to the triggers. The calendar digital twin **1006** can include a connector **1016**, the meeting room digital twin can include a connector **1022**, and the cafeteria digital twin **1008** can include a connector **1028** for ingesting information into the graphs **1034-1038**. In some embodiment, the rules engine **926** can store rules that link the twins **1002**, **1006**, **1004**, and/or **1008** together. The rules engine **926** can determine whether the triggers of the various digital twins are triggered, e.g., the triggers **1010** and/or **1014**. Furthermore, the rules engine **926** can determine (based on one or more rules stored by the rules engine **926**) that if the triggers **1010** and **1014** are triggered, the actions **1024** and **1030** should be executed.

(135) In FIG. 10, the employee digital twin **1002** includes a graph **1032**, the calendar digital twin **1006** includes a graph **1036**, the meeting room digital twin **1004** includes a graph **1034**, and the

cafeteria digital twin **1008** includes a graph **1038**. The graphs **1032-1038** can be the same graphs and/or different graphs and can be the same as, or similar to, the graph **529**.

(136) The employee digital twin **1002** can generate an indication of whether a particular occupant is near a particular office via an action responsive to the trigger **1010** triggering when a particular occupant is a particular instance (e.g., 250 meters) from their office. The digital twin **1002** can identify the occupant, the occupant's office, and the location of the office through analyzing the nodes and/or edge of the graph **1032**. The calendar digital twin **1006** determines, based on calendar data (e.g., calendar data stored in the graph **1036**), whether it is a work day via the trigger **1014** (e.g., is a day Monday through Friday). Responsive to determining that it is a work day, the calendar digital twin **1006** generates an indication that it is a work day via actions of the calendar digital twin **1006**.

(137) The meeting room digital twin **1004** can receive the work day indication from the calendar digital twin **1006** and can receive the occupant near office indication from the employee digital twin **1002**. The rules engine **926** can cause the meeting room digital twin **1004** to take actions to reserve a meeting room via the actions **1024** responsive to the triggers **1010** and **1014** being triggered. The rules engine **926** can cause the cafeteria digital twin **1008** to trigger the ordering of a coffee for the occupant via the action **1030** responsive to the triggers **1010** and **1014** being triggered.

(138) Referring now to FIG. **11**, a process **1100** of an agent executing a trigger rule and an action rule is shown, according to an exemplary embodiment. The process **1100** can be performed by the system **500** and/or components of the system **500**. In some embodiments, the building data platform **100** can perform the process **1100**. Furthermore, the process **1100** can be performed by any computing device described herein.

(139) In step **1102**, the building data platform can store an agent **570** in a data structure. The agent **570** can include a trigger rule indicating a condition for executing an action rule and an action rule indicating an action to be performed responsive to the condition being met. In some embodiments, the model **576** includes, or can be replaced with, the trigger rule and the action rule. The trigger rule and the action rule can be logical statements and/or conditions that include parameter values and/or create an output action. The parameter values can, in some embodiments, be identified through a learning process, e.g., as described through FIGS. **12-22**.

(140) In step **1104**, the agent **570** can receive information from at least one of a physical device and/or from the graph **529**. The information can be generated by a physical device, e.g., the building subsystems **122**. The building data platform **100** can, in some embodiments, receive the information from the physical device, ingest the information into the graph **529**, and the agent **570** can read the information from the graph **529**. In some embodiments, the agent **570** can check the information of the graph **529** against a trigger rule at a set period.

(141) In step **1106**, the agent **570** determines whether the information received in the step **1104** causes the condition to be met. The agent **570** can apply the information to the trigger rule to determine whether the trigger rule is triggered, i.e., the condition of the trigger rule being met.

(142) In step **1108**, the agent **570** can perform the action responsive to the condition being met by the information determined in step **1106**. The action may cause a physical device to be operated or information be sent to another agent including another trigger rule and another action rule. In some embodiments, the action can be performed by executing the action rule of the agent **570**. The action rule can perform an action based on one or more parameter value of the action rule. In some embodiments, the action output of the action rule can be sent directly to the physical device, e.g., the building subsystems **122**. In some embodiments, the action output can be stored into the graph **529**. Another operating component of the building data platform **100**, e.g., the command processor **136**, can read the action from the graph **529** can communicate a corresponding command to the building subsystems **122**.

(143) In some embodiments, instead of a digital twin triggering its own action, a trigger of the

digital twin can trigger an action of another digital twin. For example, a rules engine of the twin manager **108** (e.g., the rules engine **926** described in FIGS. **9-10**) can link multiple triggers and actions of various digital twins together. For example, the rules engine **926** can store a logical rule with conditional requirements, e.g., triggers being tripped of one or more digital twins, Boolean logic and/or operations (e.g., AND, OR, XOR, NAND, NOT, XNOR, NOR, greater than, less than, equals, etc.), etc. The rule can indicate that when conditions of various triggers of various digital twins are satisfied, one or more actions of various digital twins should be executed.

(144) Referring generally to FIGS. **12-23**, systems and methods for using artificial intelligence to determine triggers and actions for an agent is shown. The triggers can trigger autonomously based on received data and cause an action to occur. In some embodiments, multiple digital twins can interact with each other by identifying interrelationships between each other via the graph **529**, e.g., a VAV digital twin could interact with an AHU digital twin responsive to identifying that a VAV represented by the VAV digital twin is related to an AHU represented by the AHU digital twin via the graph **529**. The digital twins can in some embodiments, simulate the impact of triggers and/or actions to validate and learn triggers and/or actions.

(145) In some embodiments, the building data platform **100** can perform q-learning (Reinforcement Learning) to train and/or retrain the triggers and/or actions of the agents. In some embodiments, the data used to train and/or retrain the triggers and/or actions can be simulated data determined by another digital twin.

(146) One digital twin may have trigger conditions such as, “when the outside temperature is x.sub.0,” “when the inside humidity is x %,” “when an AI-driven algorithm's threshold is reached,” and “when it is a certain day of the week.” In responsive to one or multiple triggers being met, the digital twin can perform actions (e.g., capabilities of a device either inherent and/or digital twin enhanced). The actions can include setting a setpoint to a value x.sub.0. The actions can be to run a fan for x minutes. The actions can be to start an AI-driven energy saving schedule. The actions can be to change a mode status to an away status. In some embodiments, the building data platform **100** can use other digital twins to simulate a reward for various values of the triggers and/or actions. The reward can be optimized to determine values for the parameters of the triggers and/or actions.

(147) In some embodiments, allowing the digital twin to learn and adjust the parameters of the triggers and/or rules allows the digital twin to optimize responses to internal and/or external events in real-time. In some embodiments, the digital twin performs operations with the correlation of contextual relationships to provide spatial intelligence. In some embodiments, the digital twin allows for AI-based self-learning solutions to operate on top of the digital twin. The digital twin can capture comprehensive data that drives rich analytics for security, compliance, etc. In some embodiments, the digital twin can enable and perform simulations.

(148) In some embodiments, the building data platform **100** can identify events and/or event patterns if the building data platform **100** identifies a pattern that suggests a trigger and/or action should be updated. For example, if the building data platform **100** identifies a pattern occurring in a building, the building data platform **100** can set triggers and/or actions in digital twins to allow the pattern to occur automatically. For example, if a user closes their blinds at 5:00 P.M. regularly on weekdays, this could indicate that the user desires the blinds to be closed at 5:00 P.M. each day. The building data platform **100** can set a blind control digital twin to trigger a blind closing action at 5:00 P.M. each day.

(149) In some embodiments, an agent of a digital twin can predict an inference in the future indicating that some action should be performed in the future. The building data platform **100** can identify that the action should be performed in the future and can set up a flow so that a prediction of one digital twin can be fed into another digital twin that can perform the action.

(150) Referring now to FIG. **12**, a system **1200** of a trigger rule **1202** of a thermostat digital twin where parameters of the trigger rule **1202** are trained is shown, according to an exemplary embodiment. In some embodiments, the system **1200** can implement a model that rewards triggers

and/or actions of the thermostat digital twin using a neural network that is trained from data aggregated from a related digital twin of the thermostat digital twin, an air handler unit digital twin. (151) The building data platform **100** can perturb parameters, $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$ of the trigger rule **1202** of the thermostat digital twin. The trigger rule **1202** may be that if a number of occupants is greater than $\epsilon_{\text{sub.1}}$ and a zone temperature is less than $\epsilon_{\text{sub.2}}^{\circ}\text{C}$, the rule is triggered and a corresponding action be performed. The corresponding action can be to increase a supply air temperature setpoint of an AHU to 22°C . The perturbation of the parameters can be increasing or decreasing the parameters in set amounts from existing values. The perturbation of the parameters can be selecting a space of values for the parameters and/or randomizing the parameters and/or parameter space.

(152) With the perturbed values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$, the AHU digital twin **1204** can simulate the state of the AHU via the AHU digital twin **1204** for various conditions of occupant number and zone temperature. The result of the various states of the AHU digital twin **1204**. The simulation can be performed by the AI agent **570** via the model **576**. The output of the model **576** can be the simulated states, e.g., timeseries **566**.

(153) The building data platform **100** can analyze the states produced by the AHU digital twin **1204** to determine energy and comfort results from the states of the AHU digital twin **1204**. For example, an energy score can be generated for each state. For example, a power consumption level can be determined for each state. Similarly, a comfort violation score can be determined for each state. The comfort violation can indicate whether or not a temperature, humidity, or other condition of a physical space controlled by the AHU would be uncomfortable for a user (e.g., go below or above certain levels).

(154) The building data platform **100** can generate accumulated training data. The accumulated training data can include the values of the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$, the state of the AHU digital twin **1204** for each value of the parameters, and the energy score and comfort violation score for each state. In some embodiments, the triggers and/or actions that can be recommended for the thermostat digital twin can be determined by observing the responses of other digital twins on perturbed thresholds of existing triggers and/or actions.

(155) The building data platform **100** can generate neural networks **1210** for predicting an energy score based on the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. Furthermore, the neural networks **1210** can indicate a comfort violation score for the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. The neural networks **1210** can be trained by the building data platform **100** based on the accumulated training data **1208**.

(156) Based on the trained neural network models **1210**, the building data platform **100** can determine optimal values for the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. The building data platform **100** can search a space of potential values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$ that consider predicted energy scores and/or comfort violation scores predicted by the trained neural network models **1210**. The optimization can be the relation **1400** shown in FIG. **14**. The optimization **1212** performed by the building data platform **100** can be a method of computing the optimal threshold of a trigger conditions using the neural network models **1210** of rewards (e.g., energy and comfort) and solving constrained optimization model. Similarly, the optimization **1212** performed by the building data platform **100** to determine the optimal threshold of action commands using the neural network models **1210** of rewards and solving constrained optimization.

(157) In some embodiments, the optimal values for the parameters found by the building data platform **100** can be presented to a user for review and/or approval via a user interface, e.g., via the user device **176**. In some embodiments, the recommendations produced by the building data platform **100** through the components **1202-1212** can be restricted by only looking at state/value changes of digital twins that are nearest neighbors in the graph **529**, e.g., two nodes are directed related by one edge, e.g., a thermostat node for the thermostat digital twin is directed to an AHU node for the AHU digital twin **1204**. In some embodiments, the building data platform **100** can use spatial correlation to assume contextual relationship between assets that can affect each other's

attribute states/values.

(158) Referring now to FIG. 13, a process **1300** for identifying values for the parameters of the trigger rule **1202** of FIG. 12 is shown, according to an exemplary embodiment. The process **1300** can be performed by the building data platform **100** and/or any component of the building data platform **100**. The process **1300** can be performed by the system **500** and/or components of the system **500**. Furthermore, the process **1300** can be performed by any computing device described herein.

(159) In step **1302**, the building data platform **100** can perturb a thermostat digital twin (e.g., the thermostat digital twin rule **1202**) with various value for thresholds and/or other parameters, e. The result of the perturbed parameters can result in various states, s. The states can be states predicted by the thermostat digital twin or another digital twin that operates based on the thresholds and/or parameters e, e.g., the AHU digital twin **1204**. The perturbations and simulated states can result in pairs (S, ϵ). The pairs can be used to determine feedback for energy and/or comfort, e.g., (E, C).

(160) In step **1304**, the building data platform **100** can building neural network models, e.g., the neural networks **1210** based on the data determined in step **1302**. The neural networks **1210** can predict energy rewards as a function of the state and the parameters, e.g., $E=f(s, \epsilon)$. Furthermore, the neural networks **1210** can predict comfort rewards as a function of the state and the parameters, e.g., $C=f(s, \epsilon)$.

(161) In step **1306**, the building data platform **100** can determine a value for the parameter, ϵ that minimizes a relation, $(\alpha.\text{sub.1}.\text{Math.E}+\alpha.\text{sub.2}.\text{Math.C})$. The minimization is shown in relation **1400** of FIG. 14. The values of $\alpha.\text{sub.1}$ and $\alpha.\text{sub.2}$ can weigh the various rewards in the relation that is minimized, e.g., the energy reward and/or the comfort reward. In step **1308**, the building data platform **100** can periodically repeat the steps **1302-1306**. For example. For example, the building data platform **100** can repeat the steps at a defined time period. In some embodiments, the building data platform **100** can compute rewards for the actions of the thermostat digital twin. If the rewards indicate that the thermostat digital twin need retraining, the building data platform **100** can repeat the steps **1302-1308**.

(162) Referring now to FIG. 15, a system **1500** of components where an action rule **1502** of a thermostat digital twin is shown where parameters of the action rule **1502** are trained, according to an exemplary embodiment. The system **1500** can include similar and/or the same components of FIG. 14. The process **1300** of FIG. 13 can be applied to the action rule **1502** to train the parameters of the action rule **1502**.

(163) The thermostat digital twin rule **1502** can be an action rule that if a trigger is met (e.g., the trigger **1402**), the action rule **1502** executes to command the AHU digital twin **1204**. The trigger rule may be to execute the action rule if an occupant count is greater than ten and a zone temperature is less than twenty degrees Celsius. The action rule **1502** may be to increase an AHU supply air temperature setpoint to a value, e.g., ϵ . The value can, in some embodiments, be 22 degrees Celsius.

(164) The building data platform **100** can predict states resulting from perturbed values of ϵ by executing the AHU digital twin **1204** to simulate the states. The building data platform **100** can collect rule feedback **1206** to construct accumulated training data **1208**. Furthermore, the building data platform **100** can train neural network models **1210** based on the accumulated training data **1208** and find optimal values for the parameter ϵ based on the trained neural network models **1210**

(165) Referring now to FIG. 16, a list **1600** and a list **1602** of states of a zone and of an air handler unit that can be used to train the parameters of the trigger rule and the action rule of the thermostat digital twins of FIGS. 12-15 is shown, according to an exemplary embodiment. The list **1600** includes states for a zone. The states can be zone temperature, zone humidity, outdoor air temperature, outdoor air humidity, zone occupancy, etc. These states can be predicted and/or determined based on a digital twin for a space based on perturbed parameter values for a trigger rule, an action rule, weather forecasts, etc. In this regard, the rule feedback **1206**, in some

embodiments, can be generated based on the digital twin for the space and used to tune the values of the parameters for the trigger rule **1402** and/or the action rule **1502**.

(166) The list **1602** includes states for an AHU. The states can be supply air temperature, supply air flow rate, return air temperature, return air flow rate, outdoor air flow rate, etc. These states can be predicted and/or determined based on a digital twin for an AHU (e.g., the AHU digital twin **1204**) based on perturbed parameter values for a trigger rule, an action rule, etc. In this regard, the rule feedback **1206** in some embodiments, can be generated based on the digital twin for the AHU and used to tune the values of the parameters for the trigger rule **1402** and/or the action rule **1502**.

(167) Referring now to FIG. **17**, a system **1700** of a trigger rule of a chemical reactor digital twin where parameters of a trigger rule are trained is shown, according to an exemplary embodiment. A reactor feed digital twin which may model the feed of a chemical reactor can include various trigger rules and/or action rules, e.g., the trigger rule **1702**. The trigger rule **1702** can be that if a chemical concentration of a first chemical A is less than $\epsilon_{\text{sub.1}}$ (e.g., 10 g/l) and a chemical concentration of a second chemical B is less than $\epsilon_{\text{sub.2}}$ (e.g., 20 g/l) then an action rule is triggered. The action rule may be increase a catalyst C feed amount to 300 g/s.

(168) The building data platform **100** can perturb the values for the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$ of the reactor feed digital twin trigger rule **1702** (e.g., pseudo-randomly, increasing and/or decreasing in a particular number of predefined increments, etc.). A chemical reactor digital twin **1704** can simulate a state of the chemical reactor for the various perturbed parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. The building data platform **100** can determine a rule feedback **1706** for the state simulate by the chemical reactor digital twin **1704**. The rule feedback **1706** can identify scores for production throughput (P) and chemical property (C).

(169) The building data platform **100** can accumulate training data **1708**. The accumulated training data **1708** can include the feedback **1706**, the state simulated by the chemical reactor digital twin **1704**, and/or the parameter values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. The building data platform **100** can train neural network models **1710** to predict production throughput and/or chemical property for the various parameter and/or state pairs, e.g., the state resulting from the parameters of the trigger rule **1702**. The building data platform **100** can use the trained neural network models **1710** to identify optimal values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. In element **1712**, the building data platform **100** can identify values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$ that minimize the relation **1900** shown in FIG. **19**. In some embodiment, the optimization can optimize production throughput and/or chemical property.

(170) Referring now to FIG. **18**, a process **1800** for identifying values for the parameters of the trigger rule of FIG. **17** is shown, according to an exemplary embodiment. The process **1800** can be performed by the building data platform **100** and/or any component of the building data platform **100**. The process **1900** can be performed by the system **500** and/or components of the system **500**. Furthermore, the process **1900** can be performed by any computing device described herein. The steps **1802-1808** can be the same as or similar to the steps **1302-1308**. However, the steps **1802-1808** can be executed for a reactor digital twin and the reward for training the neural networks and be production throughput and chemical property.

(171) In step **1802**, the building data platform **100** can perturb a reactor digital twin **1704** with various values of a threshold ϵ of a trigger rule **1702** with various values which cause the reactor digital twin to determine resulting states for the various values of the threshold, ϵ . The states and the values for the threshold ϵ can create state threshold pairs. The pairs can be used to determine feedback, e.g., production throughput and chemical property.

(172) In step **1804**, after some accumulation of feedback data, the building data platform **100** can build neural network models **1710** based on the pairs that predict production throughput and chemical property based on the values for the threshold ϵ . In step **1806**, the building data platform **100** can determine a value for the threshold ϵ that maximizes a reward and/or minimizes a penalty. The building data platform **100** can minimize the relation **1900** of FIG. **19**. In step **1808**, the building data platform **100** can periodically retrain the values for the threshold ϵ for the trigger rule

1702.

(173) Referring now to FIG. 20, a system **2000** including an action rule **2002** of a chemical reactor digital twin where parameters of the action rule **2002** are trained is shown, according to an exemplary embodiment. The reactor feed twin rule **2002** can be an action rule to increase a catalyst C feed amount to $\epsilon_{\text{sub.1}}$ g/s in response to a trigger rule being triggered, e.g., the trigger rule **1702**. The building data platform **100** can perturb the values of the parameter $\epsilon_{\text{sub.1}}$ and the reactor digital twin **1704** can predict states resulting from the perturbed parameter. The building data platform **100** can determine rule feedback **1706** and generate accumulated training data **1708** based on the rule feedback **1706**. The building data platform **100** can train the neural network models **1710**. Based on the neural network models **1710**, the building data platform **100** can find optimal values for the parameter $\epsilon_{\text{sub.1}}$.

(174) Referring now to FIG. 21, a list **2100** and a list **2102** of states of a feed of a reactor and a reactor that can be included in the trigger rule and the action rule of FIGS. 12-15 are shown, according to an exemplary embodiment. The list **2100** includes states for a feed of a chemical reactor. The states can be reactants feed amount, catalysts feed amount, feed stream temperature, etc. These states can be predicted and/or determined based on a digital twin for a space based on perturbed parameter values for a trigger rule, an action rule, etc. In this regard, the rule feedback **1706** in some embodiments, can be generated based on the digital twin for the space and used to tune the values of the parameters for the trigger rule **1702** and/or the action rule **2002**.

(175) The list **2102** includes states for a chemical reactor. The states can be product concentration, cooling coil temperature, product temperature, etc. These states can be predicted and/or determined based on a digital twin for a chemical reactor (e.g., the reactor digital twin **1704**) based on perturbed parameter values for a trigger rule, an action rule, etc. In this regard, the rule feedback **1706** in some embodiments, can be generated based on the digital twin for the chemical reactor and used to tune the values of the parameters for the trigger rule **1702** and/or the action rule **2002**.

(176) Referring now to FIG. 22, a system **2200** where triggers and actions that can be constructed and learned for a digital twin is shown, according to an exemplary embodiment. Considering a building where a room in the building has a thermostat, the building data platform **100** can construct triggers and/or actions of an agent of a digital twin or the room. The triggers and/or actions can be determined with an energy reduction reward function **2204** by a learning service **2206**. The energy reduction reward function **2204** can produce triggers and/or actions that have values that minimize energy usage.

(177) In some embodiments, the building data platform **100** can search the graph **529** to identify information related to the space, e.g., related pieces of equipment, spaces, people, etc. For example, the building data platform **100** can identify which entities of the graph **529** are related and operate to affect each other. The building data platform **100** can identify which actions each entity can perform and/or what measurements each entity can make, e.g., by identifying related data nodes for each entity. The identified entities, measurements, and/or commands can be combined into the rule **2202** by the building data platform **100**.

(178) In some embodiments, the learning service **2206**, which may be a component of the building data platform **100**, can run a learning process with the rule **2202** and/or one or more reward functions (e.g., comfort reward function, carbon footprint reduction reward function, the energy reduction reward function **2204**, etc.). The learning service **2206** can learn the rule **2208** from the rule **2202** and/or the energy reduction reward function **2204**.

(179) The learning service **2206** can run an optimization to determine combinations between measurements and actions triggered based on the measurements. The learning service **2206** can determine values for each measurement and/or action. Furthermore, the learning service **2206** can identify the relational operations for causing a trigger, e.g., equals to, greater than, less than, not equal to, etc. Furthermore, the learning service **2206** can identify action operations, e.g., increase by a particular amount, decrease by a particular amount, set an output equal to a value, run a

particular algorithm, etc.

(180) Referring now to FIG. **23**, a process **2300** for constructing triggers and actions for a digital twin is shown, according to an exemplary embodiment. In some embodiments, the process **2300** can be performed by the building data platform **100**. In some embodiments, the process **2300** can be performed by the learning service **2206**.

(181) In step **2302**, the building data platform **100** can determine actions that a particular entity can take and data that the entity can measure by analyzing a graph **529**. The entity can be a thermostat, an air handler unit, a zone of a building, a person, a VAV unit, and/or any other entity. For example, if the entity is a thermostat the building data platform **100** could identify room temperature measurements for a thermostat and/or a cooling stage command, a heating stage command, a fan command, etc. that the thermostat can perform. Responsive to identifying data that the entity can measure, the building data platform **100** can generate a trigger condition based on the data type, e.g., when the temperature is equal to, less than, greater than, and/or not equal to some parameter value, trigger an action.

(182) In step **2304**, the building data platform **100** identifies, based on the graph **529**, entities related to the entity and actions that the entities can take and data that the entities can measure. For example, if the entity is for a thermostat for a zone, the building data platform **100**, could identify a shade control system for controlling a shade of the zone, an air handler unit that serves the zone, a VAV that serves the zone, etc. For example, the building data platform **100** can identify, based on the building graph **529**, that a binds node is associated with a zone node that the thermostat node is related to. The building data platform **100** can identify a list of actions that the entities can perform, e.g., setting blind position from 0% (fully open) to 100% (fully closed).

(183) In some **2306**, the building data platform **100** can simulate various combinations of triggers that are based on the data that the entity and/or entities can measure and actions that are based on the actions that the entity and/or entities can make. The building data platform **100** can simulate various combinations, trigger operations, action operations, and/or parameters.

(184) In step **2308**, the building data platform **100** can identify a combination of triggers and actions that maximizes a reward. The building data platform **100** can search the simulated combinations of triggers and/or actions to identify a trigger and/or action that maximizes a reward and/or minimizes a reward. In some embodiments, the building data platform **100** uses a policy gradient and value function instead of brute force to try out combinations of the triggers and/or actions in the steps **2306-2308**.

(185) In some embodiments, the building data platform **100** can identify the operations for the triggers and/or actions. For example, the operation could be comparing a measurement to a threshold, determining whether a measurement is less than a threshold, determining whether a measurement is greater than the threshold, determining whether the measurement is not equal to the threshold, etc.

(186) In step **2310**, the building data platform **100** can generate a digital twin for the entity. The entity can include (or reference) the graph **529** and include an agent that operates the triggers and/or actions. The triggers and/or actions can operate based on the graph **529** and/or based on data received building equipment, e.g., the building subsystems **122**.

(187) In step **2312**, the building data platform **100** can run a building system of a building and monitor the behavior of the entity and entities of the building. In some embodiments, the building system can be the building subsystems **122**. In step **2314**, the building data platform **100** can identify relationships between the measurements and actions of the entity and/or the entities based on the monitored behavior. The building data platform **100** can discover existing relationships by identifying how the measurements are currently affecting actions based on the monitored behavior. In step **2316**, the building data platform **100** can optimize the identified relationships between the measurements and the actions by maximizing a reward or minimizing a penalty.

Configuration of Exemplary Embodiments

(188) The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

(189) The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a machine, the machine properly views the connection as a machine-readable medium. Thus, any such connection is properly termed a machine-readable medium. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(190) Although the figures show a specific order of method steps, the order of the steps may differ from what is depicted. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule based logic and other logic to accomplish the various connection steps, processing steps, comparison steps and decision steps.

(191) In various implementations, the steps and operations described herein may be performed on one processor or in a combination of two or more processors. For example, in some implementations, the various operations could be performed in a central server or set of central servers configured to receive data from one or more devices (e.g., edge computing devices/controllers) and perform the operations. In some implementations, the operations may be performed by one or more local controllers or computing devices (e.g., edge devices), such as controllers dedicated to and/or located within a particular building or portion of a building. In some implementations, the operations may be performed by a combination of one or more central or offsite computing devices/servers and one or more local controllers/computing devices. All such implementations are contemplated within the scope of the present disclosure. Further, unless otherwise indicated, when the present disclosure refers to one or more computer-readable storage

media and/or one or more controllers, such computer-readable storage media and/or one or more controllers may be implemented as one or more central servers, one or more local controllers or computing devices (e.g., edge devices), any combination thereof, or any other combination of storage media and/or controllers regardless of the location of such devices.

Claims

1. A building system comprising one or more storage devices storing instructions thereon that, when executed by one or more processors, cause the one or more processors to: store a data structure of a digital twin of an entity of a building, the data structure storing information associated with at least one of the entity or a plurality of entities of the building; execute a learning algorithm to construct a trigger rule and an action rule with the data structure of the digital twin as an input to the learning algorithm; store the trigger rule and the action rule in the digital twin; determine that the trigger rule of the digital twin is triggered by comparing at least some of the information of the data structure against one or more conditions of the trigger rule by querying the data structure for data values and comparing the data values against the one or more conditions of the trigger rule; determine an action of the action rule of the digital twin responsive to determining that the trigger rule is triggered by executing the action rule; and cause one or more devices to operate based on the action determined by the action rule.
2. The building system of claim 1, wherein the instructions cause the one or more processors to: provide the action to one or more other digital twins; determine that the action triggers one or more trigger rules of the one or more other digital twins; and determine one or more actions of one or more action rules of the one or more other digital twins by executing the one or more action rules responsive to the action triggering the one or more trigger rules.
3. The building system of claim 1, wherein the data structure is a graph data structure comprising a plurality of nodes and a plurality of edges between the plurality of nodes, wherein the plurality of nodes represent the entity, the plurality of entities, and data points of the entity and the plurality of entities; wherein the plurality of edges represent relationships between the entity, the plurality of entities, and the data points of the entity and the plurality of entities.
4. The building system of claim 1, wherein the instructions cause the one or more processors to cause the one or more devices to operate based on the action by: sending a command to the one or more devices to perform the action; or store the action in the data structure and retrieve the action from the data structure and send the command based on the action retrieved from the data structure to the one or more devices.
5. The building system of claim 1, wherein the instructions cause the one or more processors to learn one or more parameters of the trigger rule or the action rule by: adjusting a value of the one or more parameters of the trigger rule or the action rule to a plurality of different values; simulating one or more states resulting from the plurality of different values of the one or more parameters of the trigger rule or the action rule; and determine one or more updated values for the one or more parameters of the trigger rule or the action rule based on the one or more states resulting from the plurality of different values of the one or more parameters of the trigger rule or the action rule.
6. The building system of claim 5, wherein the instructions cause the one or more processors to determine the one or more updated values for the one or more parameters of the trigger rule or the action rule by: determining a particular reward for the one or more states resulting from the plurality of different values of the one or more parameters of the trigger rule or the action rule; training a model that predicts a reward based on the particular reward for the one or more states and the plurality of different values of the one or more parameters of the trigger rule or the action rule; and performing an optimization that determines the one or more updated values for the one or more parameters of the trigger rule or the action rule based on the model and the reward.
7. The building system of claim 6, wherein the instructions cause the one or more processors to

generate construct the trigger rule and the action rule based on actions and the information associated with the entity and actions and the information associated with the plurality of entities by: determining trigger rules for the information associated with the entity and the information associated with the plurality of entities; determining action rules for the actions of the entity and the actions of the plurality of entities; simulating combinations of the trigger rules and the action rules, and determining rewards for the combinations; and selecting the trigger rule and the action rule from the combinations of the trigger rules and the action rules based on the rewards of the combinations.

8. The building system of claim 6, wherein the instructions cause the one or more processors to construct the trigger rule and the action rule based on actions and the information associated with the entity and actions and the information associated with the plurality of entities by: determining trigger rules for the information associated with the entity and the information associated with the plurality of entities, the trigger rules including the trigger rule; determining action rules for the actions of the entity and the actions of the plurality of entities, the action rules including the action rule; monitoring behavior of the building system of the building; determining a relationship between the trigger rule of the trigger rules and the action rule of the action rules indicated by the behavior of the building system; and selecting the trigger rule from the trigger rules and the action rule from the action rules based on the relationship.

9. A method comprising: storing, by a processing circuit, a data structure of a digital twin of an entity, the data structure storing information associated with at least one of the entity or a plurality of entities; executing, by the processing circuit, a learning algorithm to construct a trigger rule and an action rule with the data structure of the digital twin as an input to the learning algorithm; storing, by the processing circuit, the trigger rule and the action rule in the digital twin; determining, by the processing circuit, that the trigger rule of the digital twin is triggered by comparing at least some of the information of the data structure against one or more conditions of the trigger rule by querying the data structure for data values and comparing the data values against the one or more conditions of the trigger rule; determining, by the processing circuit, an action of the action rule of the digital twin responsive to determining that the trigger rule is triggered by executing the action rule; and causing, by the processing circuit, one or more devices to operate based on the action determined by the action rule.

10. The method of claim 9, further comprising: providing, by the processing circuit, the action to one or more other digital twins; determining, by the processing circuit, that the action triggers one or more trigger rules of the one or more other digital twins; and determining, by the processing circuit, one or more actions of one or more action rules of the one or more other digital twins by executing the one or more action rules responsive to the action triggering the one or more trigger rules.

11. The method of claim 9, wherein the data structure is a graph data structure comprising a plurality of nodes and a plurality of edges between the plurality of nodes, wherein the plurality of nodes represent the entity, the plurality of entities, and data points of the entity and the plurality of entities; wherein the plurality of edges represent relationships between the entity, the plurality of entities, and the data points of the entity and the plurality of entities.

12. The method of claim 9, wherein causing, by the processing circuit, the one or more devices to operate based on the action comprises: sending a command to the one or more devices to perform the action; or storing the action in the data structure and retrieve the action from the data structure and send the command based on the action retrieved from the data structure to the one or more devices.

13. The method of claim 9, further comprising learning, by the processing circuit, one or more parameters of the trigger rule or the action rule by: adjusting a value of the one or more parameters of the trigger rule or the action rule to a plurality of different values; simulating one or more states resulting from the plurality of different values of the one or more parameters of the trigger rule or

the action rule; and determining one or more updated values for the one or more parameters of the trigger rule or the action rule based on the one or more states resulting from the plurality of different values of the one or more parameters of the trigger rule or the action rule.

14. The method of claim 9, further comprising generating, by the processing circuit, the digital twin by: identifying actions and data associated with the entity based on the data structure; identifying that the plurality of entities are related to the entity based on the data structure; identifying actions and data associated with the plurality of entities based on the data structure; and generating the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the plurality of entities.

15. One or more non-transitory computer-readable media storing instructions that, when executed by one or more processors, cause the one or more processors to perform operations comprising: storing a data structure of a digital twin of an entity of a building, the data structure storing information associated with at least one of the entity or a plurality of entities of the building; executing a learning algorithm to construct a trigger rule and an action rule with the data structure of the digital twin as an input to the learning algorithm; storing the trigger rule and the action rule in the digital twin; determining that the trigger rule of the digital twin is triggered by comparing at least some of the information of the data structure against one or more conditions of the trigger rule by querying the data structure for data values and comparing the data values against the one or more conditions of the trigger rule; determining an action of the action rule of the digital twin responsive to determining that the trigger rule is triggered by executing the action rule; and causing one or more devices to operate based on the action determined by the action rule.

16. The one or more non-transitory computer-readable media of claim 15, the operations further comprising: identifying that a relationship exists between the trigger rule and the action rule; and determining the action of the action rule responsive to determining that the trigger rule is triggered and that the relationship exists between the trigger rule and the action rule.

17. The one or more non-transitory computer-readable media of claim 15, the operations further comprising: storing a second digital twin associated with a second entity of the building, the second digital twin comprising a second action rule; identifying a relationship between the trigger rule of the digital twin and the action rule of the second digital twin; and determining a second action based on the second action rule of the second digital twin responsive to determining that the trigger rule of the digital twin is triggered.

18. The one or more non-transitory computer-readable media of claim 15, the operations further comprising: receiving first timeseries data from the entity; receiving second timeseries data from a second entity of the building separate from the entity; and determining that the trigger rule of the digital twin is triggered by comparing the first timeseries data and the second timeseries data against the one or more conditions of the trigger rule.

19. The one or more non-transitory computer-readable media of claim 15, the operations to generate the digital twin further comprising: identifying actions and data associated with the entity based on the data structure; identifying that the plurality of entities are related to the entity based on the data structure; identifying actions and data associated with the plurality of entities based on the data structure; and generating the trigger rule and the action rule based on the actions and the data associated with the entity and the actions and the data associated with the plurality of entities.

20. The one or more non-transitory computer-readable media of claim 15, the operations further cause the one or more processors to construct the trigger rule and the action rule based on actions and the information associated with the entity and actions and the information associated with the plurality of entities by: determining trigger rules for the information associated with the entity and the information associated with the plurality of entities; determining action rules for the actions of the entity and the actions of the plurality of entities; simulating combinations of the trigger rules and the action rules, and determining rewards for the combinations; and selecting the trigger rule

and the action rule from the combinations of the trigger rules and the action rules based on the rewards of the combinations.
