

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12407720

Kind Code

B1

Date of Patent

September 02, 2025

Inventor(s)

Shemesh; Yaniv et al.

Methods for protecting web based resources from D/Dos attacks and devices thereof

Abstract

A method, non-transitory computer readable medium and device that assists with preventing distributed denial of service attack includes receiving a request for a web resource from a client computing device. The received requested for the web resource is determined for presence of referrer header information. When the received request is determined to include the referrer header information, then the referrer header information is checked whether it includes a known domain and a valid cookie associated with the known domain. A distributed denial of service attack is prevented by providing a proactive challenge to the requesting client computing device when received request for the web resource does not include the referrer header information or when the referrer header information comprises the known domain and does not include the valid cookie.

Inventors: Shemesh; Yaniv (Sammanish, WA), Stav; David (Mountain View, CA)

Applicant: F5, Inc. (Seattle, WA)

Family ID: 85722687

Assignee: F5, Inc. (Seattle, WA)

Appl. No.: 18/112987

Filed: February 22, 2023

Related U.S. Application Data

continuation parent-doc US 15149981 20160509 US 11616806 child-doc US 18112987
us-provisional-application US 62158945 20150508

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC **H04L63/1458** (20130101); **H04L63/1416** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4783828	12/1987	Sadjadi	N/A	N/A
6118893	12/1999	Li	N/A	N/A
6537488	12/2002	Okumura et al.	N/A	N/A
6748056	12/2003	Bapriotti	N/A	N/A
6769066	12/2003	Botros	N/A	N/A
7406606	12/2007	Chawla	N/A	N/A
7441429	12/2007	Nucci	N/A	N/A
7519834	12/2008	Dondeti	N/A	N/A
7568224	12/2008	Jennings	N/A	N/A
7624447	12/2008	Horowitz	N/A	N/A
7743415	12/2009	Poletto et al.	N/A	N/A
8572733	12/2012	Rockwood	N/A	N/A
8578482	12/2012	Yang	N/A	N/A
8756684	12/2013	Frantz	N/A	N/A
8886620	12/2013	Mukerji	707/705	G06F 16/954
8943588	12/2014	Speegle	N/A	N/A
9032519	12/2014	Maher	N/A	N/A
9077709	12/2014	Dall	N/A	N/A
9203837	12/2014	Pierson	N/A	N/A
9578055	12/2016	Khanal	N/A	H04L 63/1491
9628499	12/2016	Yu	N/A	N/A
9654485	12/2016	Neumann	N/A	N/A
9900344	12/2017	Smith	N/A	N/A
9942250	12/2017	Stiansen	N/A	N/A
9948629	12/2017	Eisen	N/A	N/A
9967250	12/2017	Johansson	N/A	N/A
10050792	12/2017	Johnson	N/A	N/A
10237298	12/2018	Nguyen	N/A	N/A
10397250	12/2018	Shemesh	N/A	N/A
10693901	12/2019	Chan	N/A	H04L 67/02
11228609	12/2021	Finkelshtein	N/A	N/A
11336575	12/2021	Milley et al.	N/A	N/A
2002/0116615	12/2001	Nguyen	N/A	N/A
2003/0042439	12/2002	Rusu	N/A	N/A
2003/0073091	12/2002	Krylov	N/A	N/A
2003/0145232	12/2002	Poletto	N/A	N/A
2003/0199762	12/2002	Fritz	N/A	N/A

2004/0037326	12/2003	D'Souza	N/A	N/A
2004/0103283	12/2003	Hornak	N/A	N/A
2004/0170123	12/2003	Carpenter	N/A	N/A
2005/0027846	12/2004	Nolfe	N/A	N/A
2005/0111367	12/2004	Jonathan Chao	N/A	N/A
2005/0195840	12/2004	Krapp	N/A	N/A
2005/0198519	12/2004	Tamura	N/A	N/A
2006/0031483	12/2005	Lund	N/A	N/A
2006/0031928	12/2005	Conley	N/A	N/A
2007/0014276	12/2006	Bettink	N/A	N/A
2007/0118894	12/2006	Bhatia	N/A	N/A
2007/0280114	12/2006	Chao	N/A	N/A
2007/0294187	12/2006	Scherrer	N/A	N/A
2008/0028467	12/2007	Kommareddy	N/A	N/A
2008/0263215	12/2007	Schnellbaecher	N/A	N/A
2008/0320567	12/2007	Shulman	726/4	H04L 63/1441
2009/0024737	12/2008	Goldspink	709/224	G06F 16/958
2009/0199297	12/2008	Jarrett	N/A	N/A
2010/0031315	12/2009	Feng	N/A	N/A
2010/0070451	12/2009	Hugues	N/A	N/A
2010/0284282	12/2009	Solie	N/A	N/A
2010/0325418	12/2009	Kanekar	N/A	N/A
2011/0012586	12/2010	Montanar	N/A	N/A
2011/0072516	12/2010	Cohen	726/22	H04L 63/1408
2011/0154026	12/2010	Edstrom	N/A	N/A
2011/0264905	12/2010	Ovvsiannikov	N/A	N/A
2012/0051236	12/2011	Hegde	N/A	N/A
2012/0079592	12/2011	Pandrangi	N/A	N/A
2012/0117239	12/2011	Holloway	709/226	H04L 67/59
2012/0144487	12/2011	Kim	N/A	N/A
2012/0167210	12/2011	Oro	N/A	N/A
2012/0173710	12/2011	Rodriguez	N/A	N/A
2012/0227106	12/2011	Shulman	N/A	N/A
2012/0323700	12/2011	Aleksandrovich	705/14.69	G06F 21/36
2013/0080407	12/2012	Levow	N/A	N/A
2013/0263268	12/2012	Kim	N/A	N/A
2013/0276114	12/2012	Fiedrichs	N/A	N/A
2013/0305365	12/2012	Rubin	N/A	N/A
2014/0095865	12/2013	Yerra	N/A	N/A
2014/0289854	12/2013	Mahvi	N/A	N/A
2014/0298419	12/2013	Boubez	N/A	N/A
2014/0310805	12/2013	Kandekar	N/A	N/A
2014/0317739	12/2013	Be'ery	726/23	H04L 63/14
2015/0067328	12/2014	Yin	N/A	N/A
2015/0088662	12/2014	Moller	N/A	N/A
2015/0163234	12/2014	Tal	N/A	N/A
2015/0215334	12/2014	Bingham	N/A	N/A
2015/0271179	12/2014	Nang	N/A	N/A
2015/0295945	12/2014	Canzanese	N/A	N/A
2015/0310196	12/2014	Turgeman	N/A	N/A

2016/0021084	12/2015	Eisen	N/A	N/A
2016/0021117	12/2015	Harmon	N/A	N/A
2016/0127406	12/2015	Smith	N/A	N/A
2016/0182542	12/2015	Staniford	N/A	N/A
2016/0337314	12/2015	Yu	N/A	N/A
2017/0171231	12/2016	Reybok, Jr.	N/A	N/A
2017/0249306	12/2016	Alien	N/A	N/A
2017/0318053	12/2016	Singh	N/A	N/A
2018/0124073	12/2017	Scherman	N/A	N/A
2018/0124300	12/2017	Brook	N/A	N/A
2018/0139228	12/2017	Kanakarajan	N/A	N/A
2018/0165457	12/2017	Holz	N/A	N/A
2020/0296125	12/2019	Alderson	N/A	N/A
2020/0351244	12/2019	Moore et al.	N/A	N/A
2021/0075790	12/2020	Hebert	N/A	N/A
2021/0248631	12/2020	Cheesman	N/A	N/A
2022/0121362	12/2021	Liu et al.	N/A	N/A
2023/0146962	12/2022	Reddy et al.	N/A	N/A
2024/0265057	12/2023	Kol	N/A	N/A
2024/0283674	12/2023	Kanda	N/A	N/A
2024/0291744	12/2023	Chhabra	N/A	N/A
2024/0291745	12/2023	Chhabra	N/A	N/A
2025/0007835	12/2024	Chhabra	N/A	N/A
2025/0007937	12/2024	Mittal	N/A	N/A
2025/0148034	12/2024	Shribman	N/A	N/A
2025/0159039	12/2024	Shribman	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109 391 600	12/2018	CN	N/A
110 365 712	12/2018	CN	N/A
WO 02/35860	12/2001	WO	N/A

OTHER PUBLICATIONS

BIG-1P® Analytics: Implementations, version 11.3, Nov. 15, 2012, F5 Networks, Inc., pp. 1-40. cited by applicant

F5 Networks, “BIG-1 P Local Traffic Manager: Concepts”, version 11.4, pp. 1-178, retrieved from https://support.f5.com/kb/en-us/products/bigip_ltm/manuals/product/lm-concepts-11-4-0.html on Feb. 12, 2015. cited by applicant

F5 Networks, “BIG-1P Local Traffic Manager: Implementations”, version 11.4, pp. 1-234, retrieved from https://support.f5.com/kb/en-us/products/bigip_ltm/manuals/product/lm-implementations-11-4-0.html on Feb. 12, 2015. cited by applicant

F5 Networks, “BIG-1 P Local Traffic Manager: Monitors Reference”, version 11.4, pp. 1-106, retrieved from https://support.f5.com/kb/en-us/products/bigip_ltm/manuals/product/lm-monitorsreference-11-4-0.html on Feb. 12, 2015. cited by applicant

F5 Networks, “Operations Guide 1.0 F5 Local Traffic Manager and Global Traffic Manager”, p. 1.144, retrieved from https://support.f5.com/kb/en-us/products/bigip_ltm/manuals/product/f5-1_tmgm-operations-guide-1-0.html on Feb. 12, 2015. cited by applicant

F5 Networks, “Release Note: BIG-IP L TM and TMOS”, version 11.4.1, pp. 1-58, retrieved from https://support.f5.com/kb/en-us/products/bigip_ltm/releases/relnote-ltm-11-4-1.html on Feb. 12, 2015. cited by applicant

Feb. 12, 2015. cited by applicant
F5 Networks, Inc., "BIG-IP Application Security Manager Operations Guide", Manual, Feb. 5, 2016, pp. 1-181, F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP ASM 11.5.0", Release Notes, Apr. 12, 2016, Version 11.5.0. cited by applicant
F5 Networks, Inc., "BIG-IPASM", Release Notes, Jun. 13, 2016, pp. 1-18, version 11.6.1 F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP® Analytics: Implementations", Manual, Jan. 31, 2014, pp. 1-50, Version 11.5. cited by applicant
F5 Networks, Inc., "BIG-IP® Analytics: Implementations", Manual, Aug. 25, 2014, pp. 1-62, v11.6, F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP® Application Security Manager TM: Getting Started", Manual, Aug. 25, 2014, pp. 1-78, version 11.6, F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP® Application Security Manager TM: Implementations", Manual, Aug. 25, 2014, pp. 1-420, version 11.6, F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP® Application Security ManagerTM: Implementations", Manual, Jan. 31, 2014, pp. 1-396, Version 11.5. cited by applicant
F5 Networks, Inc., "BIG-IP® Application Security ManagerTM:Implementations", F5 Networks, Inc., Dec. 10, J014, version 11.6, pp. 1-420. cited by applicant
F5 Networks, Inc., "BIG-IP® Local Traffic Management: Basics", Manual, Aug. 25, 2014, pp. 1-74, version 11.6, F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP® Network Firewall: Policies and Implementations", Manual, Aug. 10, 2016, pp. 1-166, ,11.6, F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP® Systems: DoS Protection and Protocol Firewall Implementations", Manual, Aug. 25, 2014, pp. 1-108, v11.6, F5 Networks, Inc. cited by applicant
F5 Networks, Inc., "BIG-IP200 TMOS®: Concepts", Manual, Nov. 11, 2014, pp. 1-148, Version 11.5. cited by applicant
F5 Networks, Inc., "BIG-IP® TMOS®: Implementations", Manual, Jan. 31, 2014, pp. 1-274, Version 11.5. cited by applicant
F5 Networks, Inc., "F5 BIG-IP TMOS: Operations Guide", Manual, Mar. 5, 2015, pp. 1-276 version 11.6, F5 Networks, Inc. cited by applicant
5 Networks, Inc., "BIG-IP Application Security Manager: Implementations", F5 Networks, Inc., Dec. 10, 2014, version 11.6, pp. 1-420. cited by applicant
F5 Networks, Inc., "BIG-IP® Application Security Manager™: Implementations", Manual, Nov. 10, 2017, pp. 1-348, version 13.0, F5 Networks, Inc. cited by applicant
European Search Report Dated Feb. 17, 2025. European Patent Appln No. 24216113.1. cited by applicant
International Search Report dated Mar. 25, 2024 issued in International Application No. PCT/US2023/083393. cited by applicant
European Search Report Date Dec. 18, 2024. European Patent Application No. 24193938.8. cited by applicant

Primary Examiner: Traore; Fatoumata

Attorney, Agent or Firm: Troutman Pepper Locke LLP

Background/Summary

(1) This application is a continuation of U.S. patent application Ser. No. 15/149,981, filed May 9, 2016, and which claims the benefit of U.S. Provisional Patent Application Ser. No. 62/158,945, filed May 8, 2015, which is hereby incorporated by reference in its entirety.

FIELD

(1) This technology generally relates to methods and devices for network traffic management and, more particularly, to methods for protecting web based resources from distributed denial of service attacks and devices thereof.

BACKGROUND

(2) Web applications provide end users with client access to server functionality through a set of Web pages. These pages often contain Javascript code to be executed dynamically within the client web browser. However, Web applications, such as web browsers, are subject to attacks, such as cross-site scripting, or cookie theft, among many others.

(3) Of the current attacks on web applications, script injection based attacks are by far the most common. Script injection vulnerability may be present whenever a web application includes data of uncertain origin. In a typical attack, malicious data with surreptitiously embedded scripts is included in requests to a benign web application server. Later, the server may include that data and scripts in web pages it returns to unsuspecting users. Since web browsers execute scripts on a page with web application, these returned scripts can give attackers control over the user's web application activities and/or client devices and initiate distributed denial of service attacks on the web servers.

SUMMARY

(4) A method for preventing distributed denial of service attack includes receiving by an application manager apparatus a request for a web resource from a client computing device. The received requested for the web resource is determined for presence of referrer header information by the application manager apparatus. When the received request is determined to include the referrer header information, then the referrer header information is checked whether it includes a known domain and a valid cookie associated with the known domain by the application manager apparatus. A distributed denial of service attack is prevented by the application manager apparatus by providing a proactive challenge to the requesting client computing device when received request for the web resource does not include the referrer header information or when the referrer header information comprises the known domain and does not include the valid cookie.

(5) A non-transitory computer readable medium having stored thereon instructions for preventing distributed denial of service attack comprising machine executable code which when executed by at least one processor, causes the processor to perform steps includes receiving a request for a web resource from a client computing device. The received requested for the web resource is determined for presence of referrer header information. When the received request is determined to include the referrer header information, then the referrer header information is checked whether it includes a known domain and a valid cookie associated with the known domain. A distributed denial of service attack is prevented by providing a proactive challenge to the requesting client computing device when received request for the web resource does not include the referrer header information or when the referrer header information comprises the known domain and does not include the valid cookie.

(6) An application manager apparatus including one or more processors coupled to a memory and configured to be capable of executing programmed instructions comprising and stored in the memory to receive a request for a web resource from a client computing device. The received requested for the web resource is determined for presence of referrer header information. When the received request is determined to include the referrer header information, then the referrer header information is checked whether it includes a known domain and a valid cookie associated with the known domain. A distributed denial of service attack is prevented by providing a proactive

challenge to the requesting client computing device when received request for the web resource does not include the referrer header information or when the referrer header information comprises the known domain and does not include the valid cookie.

(7) This technology provides a number of advantages including providing a method, non-transitory computer readable medium and apparatus that effectively assists with preventing distributed denial of service attack on web resources. Using the technique illustrated below, the technology is able to distinguish between bots and authenticated client devices and so does not provide bots the requested web resources thereby preventing the distributed denial of service attacks on the server.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an example of a block diagram of an environment including an application manager apparatus for protecting web based resources from D/Dos attacks;
- (2) FIG. 2 is an example of a block diagram of the application manager apparatus;
- (3) FIG. 3 is an exemplary flowchart of a method for protecting web based resources from D/Dos attacks;
- (4) FIG. 4 is an exemplary sequence diagram illustrating the method for protecting web based resources from D/Dos attacks; and
- (5) FIG. 5 is an exemplary sequence diagram illustrating the technique for obtaining a cookie from a different domain.

DETAILED DESCRIPTION

(6) An example of a network environment **10** for protecting web based resources from distributed denial of service (D/DOS) attacks with the application manager apparatus **14** is illustrated in FIGS. **1** and **2**. The exemplary environment **10** includes a plurality of client computing devices **12(1)-12(n)**, an application manager apparatus **14**, and a plurality of web servers **16(1)-16(n)** which are coupled together by communication networks **30**, although the environment can include other types and numbers of systems, devices, components, and/or elements and in other topologies and deployments. While not shown, the exemplary environment **10** may include additional network components, such as routers, switches and other devices, which are well known to those of ordinary skill in the art and thus will not be described here. This technology provides a number of advantages including protecting web based resources from D/Dos attacks.

(7) Referring more specifically to FIGS. **1** and **2**, application manager apparatus **14** is coupled to the plurality of client computing devices **12(1)-12(n)** through the communication network **30**, although the plurality of client computing devices **12(1)-12(n)**, and application manager apparatus **14** may be coupled together via other topologies. Additionally, application manager apparatus **14** is coupled to the plurality of web servers **16(1)-16(n)** through the communication network **30**, although the plurality of web servers **16(1)-16(n)** and application manager apparatus **14** may be coupled together via other topologies.

(8) The application manager apparatus **14** assists with protecting web based resources from D/Dos attacks as illustrated and described by way of the examples herein, although application manager apparatus **14** may perform other types and/or numbers of functions. As illustrated in FIG. **2**, the application manager apparatus **14** may include a processor or central processing unit (CPU) **18**, a memory **20**, optional configurable hardware logic **21**, obfuscated JavaScript database **22**, and a communication system **24** which are coupled together by a bus **26**, although the application manager apparatus **14** may comprise other types and numbers of elements in other configurations. In this example, the bus **26** is a PCI Express bus in this example, although other bus types and links may be used.

(9) The processor **18** within the application manager apparatus **14** may execute one or more

computer-executable instructions stored in the memory **20** for the methods illustrated and described with reference to the examples herein, although the processor can execute other types and numbers of instructions and perform other types and numbers of operations. The processor **18** may comprise one or more central processing units (“CPUs”) or general purpose processors with one or more processing cores, such as AMD® processor(s), although other types of processor(s) could be used (e.g., Intel®).

(10) Memory **20** within the application manager apparatus **14** may comprise one or more tangible storage media, such as RAM, ROM, flash memory, CD-ROM, floppy disk, hard disk drive(s), solid state memory, DVD, or any other memory storage types or devices, including combinations thereof, which are known to those of ordinary skill in the art. The memory **20** may store one or more non-transitory computer-readable instructions of this technology as illustrated and described with reference to the examples herein that may be executed by the processor **18**. The exemplary flowchart shown in FIG. **3** is representative of example steps or actions of this technology that may be embodied or expressed as one or more non-transitory computer or machine readable instructions stored in memory **20** that may be executed by the processor **18** and/or may be implemented by configured logic in the optional configurable logic **21**.

(11) Additionally, the memory of the application manager apparatus **14** can store one or more applications that can include computer executable instructions that, when executed by the application manager apparatus **14**, causes the application manager apparatus **14** to perform actions, such as to transmit, receive, or otherwise process messages, for example, and to perform other actions described and illustrated below with reference to FIGS. **3-4**. The application(s) can be implemented as module or components of another application. Further, the application(s) can be implemented as operating system extensions, module, plugins, or the like. The application(s) can be implemented as module or components of another application. Further, the application(s) can be implemented as operating system extensions, module, plugins, or the like. Even further, the application(s) may be operative in a cloud-based computing environment. The application(s) can be executed within virtual machine(s) or virtual server(s) that may be managed in a cloud-based computing environment. Also, the application(s), including the application manager apparatus **14** itself, may be located in virtual server(s) running in a cloud-based computing environment rather than being tied to one or more specific physical network computing devices. Also, the application(s) may be running in one or more virtual machines (VMs) executing on the application manager apparatus **14**. Additionally, in at least one of the various embodiments, virtual machine(s) running on the mobile application manager apparatus **14** may be managed or supervised by a hypervisor.

(12) The optional configurable hardware logic **21** in the application manager apparatus **14** may comprise specialized hardware configured to implement one or more steps of this technology as illustrated and described with reference to the examples herein. By way of example only, the optional configurable logic hardware device **21** may comprise one or more of field programmable gate arrays (“FPGAs”), field programmable logic devices (“FPLDs”), application specific integrated circuits (ASICs”) and/or programmable logic units (“PLUS”).

(13) The communication system **24** in the application manager apparatus **14** is used to operatively couple and communicate between the application manager apparatus **14**, the plurality of client computing devices **12(1)-12(n)**, and the plurality of web servers **16(1)-16(n)** which are all coupled together by communication network such as one or more local area networks (LAN) and/or the wide area network (WAN), although other types and numbers of communication networks or systems with other types and numbers of connections and configurations to other devices and elements. By way of example only, the communication network such as local area networks (LAN) and the wide area network (WAN) can use TCP/IP over Ethernet and industry-standard protocols, including NFS, CIFS, SOAP, XML, LDAP, and SNMP, although other types and numbers of communication networks, can be used. In this example, the bus **26** is a PCI Express bus in this

example, although other bus types and links may be used.

(14) Each of the plurality of client computing devices **12(1)-12(n)**, include a central processing unit (CPU) or processor, a memory, input/display device interface, configurable logic device and an input/output system or I/O system, which are coupled together by a bus or other link. The plurality of client computing devices **12(1)-12(n)**, in this example, may run interface applications, such as Web browsers, that may provide an interface to make requests for and send and/or receive data to and/or from the plurality of web servers **16(1)-16(n)** via the application manager apparatus **14**. Additionally, the plurality of client computing devices **12(1)-12(n)** can include any type of computing device that can receive, render, and facilitate user interaction, such as client computers, network computer, mobile computers, virtual machines (including cloud-based computer), or the like. Each of the plurality of client computing devices **12(1)-12(n)** utilizes the application manager apparatus **14** to conduct one or more operations with the plurality of web servers **16(1)-16(n)**, such as to obtain data from one of the plurality of web servers **16(1)-16(n)**, by way of example only, although other numbers and/or types of systems could be utilizing these resources and other types and numbers of functions utilizing other types of protocols could be performed.

(15) Each of the plurality of web servers **16(1)-16(n)** include a central processing unit (CPU) or processor, a memory, and a communication system, which are coupled together by a bus or other link, although other numbers and/or types of network devices could be used. Generally, the plurality of web servers **16(1)-16(n)** process requests for providing access to one or more enterprise web applications received from the plurality of client computing devices **12(1)-12(n)**, application manager apparatus **14**, via the communication network **30** according to the HTTP-based application RFC protocol or the CIFS or NFS protocol in this example, but the principles discussed herein are not limited to this example and can include other application protocols. A series of applications may run on the plurality servers **16(1)-16(n)** that allows the transmission of applications requested by the plurality of client computing devices **12(1)-12(n)**, or the application manager apparatus **14**. The plurality of web servers **16(1)-16(n)** may provide data or receive data in response to requests directed toward the respective applications on the plurality of web servers **16(1)-16(n)** from the plurality of client computing devices **12(1)-12(n)** or the application manager apparatus **14**. It is to be understood that the plurality of web servers **16(1)-16(n)** may be hardware or software or may represent a system with multiple external resource servers, which may include internal or external networks. In this example the plurality of web servers **16(1)-16(n)** may be any version of Microsoft® IIS servers or Apache® servers, although other types of servers may be used.

(16) Although the plurality of web servers **16(1)-16(n)** are illustrated as single web application servers, one or more actions of each of the servers **16(1)-16(n)** may be distributed across one or more distinct network computing devices. Moreover, the servers **16(1)-16(n)** are not limited to a particular configuration. Thus, the plurality servers **16(1)-16(n)** may contain a plurality of network computing devices that operate using a master/slave approach, whereby one of the network computing devices of the servers **16(1)-16(n)** operate to manage and/or otherwise coordinate operations of the other network computing devices. The plurality of web servers **16(1)-16(n)** may operate as a plurality of network computing devices within cluster architecture, a peer-to peer architecture, virtual machines, or within a cloud architecture.

(17) Thus, the technology disclosed herein is not to be construed as being limited to a single environment and other configurations and architectures are also envisaged. For example, one or more of the servers **16(1)-16(n)** depicted in FIG. 1 can operate within application manager apparatus **14** rather than as a stand-alone server communicating with application manager apparatus **14** via the communication network(s) **30**. In this example the servers **16(1)-16(n)** operate within the memory of the application manager apparatus **14**.

(18) While application manager apparatus **14** is illustrated in this example as including a single device, application manager apparatus **14** in other examples can include a plurality of devices or

blades each with one or more processors each processor with one or more processing cores that implement one or more steps of this technology. In these examples, one or more of the devices can have a dedicated communication interface or memory. Alternatively, one or more of the devices can utilize the memory, communication interface, or other hardware or software components of one or more other communicably coupled of the devices. Additionally, one or more of the devices that together comprise application manager apparatus **14** in other examples can be standalone devices or integrated with one or more other devices or applications, such as one of the plurality of web servers **16(1)-16(n)** or, the application manager apparatus **14**, or applications coupled to the communication network(s), for example. Moreover, one or more of the devices of application manager apparatus **14** in these examples can be in a same or a different communication network **30** including one or more public, private, or cloud networks, for example.

(19) Although an exemplary environment **10** with the plurality of client computing devices **12(1)-12(n)**, the application manager apparatus **14**, and the plurality of web servers **16(1)-16(n)**, communication networks **30** are described and illustrated herein, other types and numbers of systems, devices, blades, components, and elements in other topologies can be used. It is to be understood that the systems of the examples described herein are for exemplary purposes, as many variations of the specific hardware and software used to implement the examples are possible, as will be appreciated by those skilled in the relevant art(s).

(20) Further, each of the systems of the examples may be conveniently implemented using one or more general purpose computer systems, microprocessors, digital signal processors, and micro-controllers, programmed according to the teachings of the examples, as described and illustrated herein, and as will be appreciated by those of ordinary skill in the art.

(21) One or more of the components depicted in the network, such as application manager apparatus **14**, plurality of client computing devices **12(1)-12(n)**, or plurality of web servers **16(1)-16(n)**, for example, may be configured to operate as virtual instances on the same physical machine. In other words, one or more of application manager apparatus **14**, plurality of client computing devices **12(1)-12(n)**, or plurality of web servers **16(1)-16(n)** illustrated in FIG. **1** may operate on the same physical device rather than as separate devices communicating through a network as depicted in FIG. **1**. There may be more or fewer plurality of client computing devices **12(1)-12(n)**, application manager apparatus **14**, or plurality of web servers **16(1)-16(n)** than depicted in FIG. **1**. The plurality of client computing devices **12(1)-12(n)** or the plurality of web servers **16(1)-16(n)** could be implemented as applications on application manager apparatus **14**.

(22) In addition, two or more computing systems or devices can be substituted for any one of the systems or devices in any example. Accordingly, principles and advantages of distributed processing, such as redundancy and replication also can be implemented, as desired, to increase the robustness and performance of the devices and systems of the examples. The examples may also be implemented on computer system(s) that extend across any suitable network using any suitable interface mechanisms and traffic technologies, including by way of example only teletraffic in any suitable form (e.g., voice and modem), wireless traffic media, wireless traffic networks, cellular traffic networks, G3 traffic networks, Public Switched Telephone Network (PSTNs), Packet Data Networks (PDNs), the Internet, intranets, and combinations thereof.

(23) The examples may also be embodied as a non-transitory computer readable medium having instructions stored thereon for one or more aspects of the technology as described and illustrated by way of the examples herein, which when executed by a processor (or configurable hardware), cause the processor to carry out the steps necessary to implement the methods of the examples, as described and illustrated herein.

(24) An example of a method for protecting web based resources from D/Dos attacks will now be described with reference to FIGS. **1-5**. The exemplary method begins at step **305** where the application manager apparatus **14** receiving a request for a web resource from one of the plurality of client computing devices **12(1)-12(n)**, although the application manager apparatus **14** can

receive other types or amounts of resources. In this example, web resource relates to an image, although the web resource can relate to other types or amounts of information. Additionally in this example, the application manager apparatus **14** receives the request for an image inside a hypertext markup language (HTML) page or the request for the image can be received as uniform resource locator (URL) link to the image from the web browser executing on the requesting one of the plurality of client computing devices **12(1)-12(n)**, although the application manager apparatus **14** can receive the request for other types or web resources.

(25) In the next step **310**, the application manager apparatus **14** determines when the received request for the web resource includes referrer information in the header of the received request, although the application manager apparatus **14** could be looking for other types and/or amounts of information or other data. By way of example only, the referrer information relates to the URL of the requested image present in the header of the received request, although the referrer information can include other types and/or amounts of information associated with the requested image. Accordingly, when the application manager apparatus **14** determines that the received request does not include the referrer information, then the No branch is taken to step **315**.

(26) In next step **315**, the application manager apparatus **14** obtains a proactive defense challenge, although the application manager apparatus **14** can obtain other types and/or number of challenges or other tests. By way of example only, the proactive defense challenge can be an obfuscated JavaScript that is obtained from the obfuscated JavaScript database **22**, although the proactive defense challenge can include other types and/or numbers of challenges that can be obtained from other locations.

(27) Next in step **320**, the application manager apparatus **14** sends the obtained JavaScript challenge to the requesting one of the plurality of client computing devices **12(1)-12(n)**. By way of example only, the application manager apparatus **14** can inject the obtained obfuscated JavaScript in a URL and send it to the requesting one of the plurality of client computing devices **12(1)-12(n)**. Alternatively in another example, the application manager apparatus **14** can redirect the web browser executing on the requesting one of the plurality of client computing devices **12(1)-12(n)** to a different webpage to respond to the proactive challenge.

(28) Alternatively in another example, the application manager apparatus **14** can also determine whether the obfuscated JavaScript can be injected into the received URL of web resource. When the application manager apparatus **14** determines that the obfuscated JavaScript cannot be injected, the application manager apparatus **14** can proceed to drop the received request for the web resource and end the exemplary method ends at step **355**.

(29) In the next step **325**, the application manager apparatus **14** determines when a response was received to the proactive challenge that was sent in the previous step **320**. By way of example only, the application manager apparatus **14** can wait for a predetermined amount of duration, such as sixty seconds by way of example only, to receive a response from the requesting one of the client computing devices **12(1)-12(n)**, although the application manager apparatus **14** can wait for any other duration of time. Accordingly, when the application manager apparatus **14** determines that the response to the challenge was not received, then the No branch is taken to end the exemplary method at step **355**. By way of example only, the application manager apparatus **14** can receive the response to the proactive challenged from the requesting one of the plurality of client computing devices **12(1)-12(n)** when the requesting one of the plurality of client computing devices **12(1)-12(n)** executes the obfuscated JavaScript in the web browser, although the application manager apparatus **14** can receive the response based on other types or amounts of operation that can be performed by the web browser of the requesting one of the plurality of client computing devices **12(1)-12(n)**. In this example, the application manager apparatus **14** determines the requesting one of the plurality of client computing device to be a bot and therefore does not provide the requested web resources from the plurality of servers **16(1)-16(n)** thereby preventing the distributed denial of service attacks on the server. However, when the application manager

apparatus **14** determines that the response was received, then the Yes branch is taken to step **330**.

(30) In the next step **330**, the application manager apparatus **14** determines when the received response is accurate. In this example, the application manager apparatus **14** has a stored table of the challenges and the corresponding answers for the challenges. The application manager apparatus **14** compares the received response with the stored answer to determine when the received response is accurate. Accordingly, when the application manager apparatus **14** determines that the received response is not accurate, then the No branch is taken to end the exemplary method at step **355**. However, when the application manager apparatus **14** determines that the received response is accurate, then the Yes branch is taken to step **335**.

(31) In step **335**, the application manager apparatus **14** provides the requested web resource to the requesting one of the plurality of client computing devices **12(1)-12(n)** and the exemplary method ends at step **355**.

(32) However, back in step **310**, when the application manager apparatus **14** determines that the received request includes the referrer information, then the Yes branch is taken to step **340**.

(33) In step **340**, the application manager apparatus **14** determines when the information in the referrer is related to a known domain. In this example, the application manager apparatus **14** includes a list of all the domains known to the application manager apparatus **14** and therefore the application manager apparatus **14** can compare the domain in the referrer information against the stored list of domain information to determine when the domain in the referrer information is known. Accordingly, when the application manager computing device determines that the domain in the referrer information is known, then the Yes branch is taken to step **350** which will be further illustrated below.

(34) Alternatively, when the application manager apparatus **14** determines that the referrer information includes the same domain information as the host header information, then the application manager apparatus **14** can proceed to reject the requested web resource and end the exemplary method at step **355**.

(35) However, when the application manager apparatus **14** determines that the domain in the referrer information is not known, then the No branch is taken to step **345**.

(36) In step **345**, the application manager apparatus **14** determines when the domain in the referrer information is a known subdomain, or a cross domain or a related external domain. In this example, a subdomain relates to domain that is part of a larger domain. Additionally, cross domain relates to a domain that enables transfer of information between two domains. Furthermore, related external domain relates to a domain that is related to a known domain, although related external domain can include other types or amounts of domains. Accordingly, when the application manager apparatus **14** determines that the domain in the referrer information is not a subdomain, cross domain or a related external domain, then the No branch is taken to the step **315** of obtaining JavaScript obfuscation challenge.

(37) However, when the application manager apparatus **14** determines that the domain in the referrer information is a subdomain, cross domain or a related external domain, then the Yes branch is taken to step **350**.

(38) In step **350**, the application manager apparatus **14** determines when there is a valid cookie for the domain in the referrer information. Additionally in this example, the application manager apparatus **14** determines when the subdomain, cross domain or related external domain includes a valid cookie by temporarily redirecting to a referenced page to obtain the cookie. By way of example only, when the received request for a web resource is for an image in b.com (referrer information in the header) which is referenced by a webpage a.com, then the application manager apparatus **14** temporarily redirects to a.com to obtain the cookie and set the obtained cookie to b.com. The technique of temporarily redirecting to a.com to obtain the cookie and set the obtained cookie to b.com is further illustrated in FIG. 5. In this example, a valid cookie relates to an encrypted cookie that was previously sent to the requesting one of the plurality of client computing

devices **12(1)-12(n)** responsive to a previous request to access a webpage or a resource on the webpage. Additionally, the valid cookie is also an encrypted cookie that has not expired as each encrypted cookie sent by the application manager apparatus **14** has an expiration time. By way of example only, the encrypted cookie includes information, such as the internet protocol (IP) address of the requesting one of the plurality of client computing devices **12(1)-12(n)** (obtained based on previous requests), time stamp information (the time at which the request was received), an index to a client-server key and encrypted using a private key at the application manager apparatus **14**, although the encrypted cookie can include other types or amounts of information and encrypted using other public-private keys. Accordingly, when the application manager apparatus **14** determines that there is no valid cookie for the domain in the referrer information, then the No branch is taken back to step **315** of obtaining and sending the JavaScript challenge.

(39) However, when the application manager apparatus **14** determines that there is a valid cookie for the domain in the referrer information, then the Yes branch is taken to the step **335** of providing the requested web resource to the requesting one of the plurality of client computing devices **12(1)-12(n)** and the exemplary method ends at step **355**.

(40) Having thus described the basic concept of the technology, it will be rather apparent to those skilled in the art that the foregoing detailed disclosure is intended to be presented by way of example only, and is not limiting. Various alterations, improvements, and modifications will occur and are intended to those skilled in the art, though not expressly stated herein. These alterations, improvements, and modifications are intended to be suggested hereby, and are within the spirit and scope of the technology. Additionally, the recited order of processing elements or sequences, or the use of numbers, letters, or other designations therefore, is not intended to limit the claimed processes to any order except as may be specified in the claims. Accordingly, the technology is limited only by the following claims and equivalents thereto.

Claims

1. A method for preventing D/DOS attack on a web resource, the method implemented by a network traffic management system comprising one or more network traffic apparatuses, client devices, or server devices, the method comprising: receiving a request for a web resource from a client, wherein the request comprises referrer header information; determining whether the domain in the referrer header information is one of a subdomain, a cross domain, or a related external domain; in response to determining the domain is not one of the subdomain, the cross domain, or the related external domain, determining the received referrer header information comprises a known domain and a valid cookie associated with the known domain to designate the received header information as validated referral header information; and preventing a distributed denial of service attack by providing a proactive challenge to the requesting client then the determination indicates the received referrer header information is the validated referrer header information, wherein the proactive challenge comprises: injecting an obtained obfuscated JavaScript in a URL; and transmitting the URL to the client.
2. The method as set forth in claim 1 further comprising providing the requested web resource when the received referrer header information is determined to include the known domain and the valid cookie associated with the known domain.
3. The method as set forth in claim 1 further comprising determining when the received referrer header information comprises a subdomain, a cross domain or, a related external domain when the received referrer header information is determined not to include the known domain.
4. The method as set forth in claim 1 further comprising: determining when there is the valid cookie associated with the subdomain, the cross domain or, the related external domain when the received referrer header information is determined to include the subdomain, the cross domain or, the related external domain; and preventing the distributed denial of service attack by providing the

proactive challenge to the requesting client when cookie is not determined to be valid.

5. The method as set forth in claim 1 wherein the preventing further comprises: receiving a response for the proactive challenge from the client; determining when the received response is accurate by comparing the received response with a stored response; and providing access to the requested web resource when the received response is determined to be accurate.
