

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407885
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Sadler; Robert et al.

Adaptive content composite generation and control

Abstract

Systems, methods, and machine-readable media to facilitate adaptive content composite generation with respect to digitally distributed content are disclosed. Observation data corresponding to detected media device operations associated with media devices in a particular geolocation may be processed and mapped to events. An identifier of a particular event may be selected based on the observation data, and a content composite corresponding to the particular event may be created. An adaptable content object may be identified based on the observation data and may be configured with a content object. The content composite may be output for presentation so that the endpoint media device performs operations relating to the content composite. Signals corresponding to the operations triggered by the content composite and indicative interface options may be processed.

Inventors: Sadler; Robert (Denver, CO), Meyer; Timothy (Denver, CO), Kuhrt; Christopher (Englewood, CO), Montgomery; Jesse (Denver, CO), Ryan; Shaun (Colorado Springs, CO)

Applicant: DISH Network L.L.C. (Englewood, CO)

Family ID: 85980872

Assignee: DISH Network L.L.C. (Englewood, CO)

Appl. No.: 17/505393

Filed: October 19, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230118189 A1	Apr. 20, 2023

Publication Classification

Int. Cl.: H04N21/258 (20110101); H04N21/2665 (20110101); H04N21/845 (20110101)

U.S. Cl.:

CPC **H04N21/25841** (20130101); **H04N21/2665** (20130101); **H04N21/8455** (20130101);

Field of Classification Search

USPC: None

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9288539	12/2015	Johnson	N/A	N/A
2008/0066111	12/2007	Ellis et al.	N/A	N/A
2011/0287825	12/2010	Hoover	N/A	N/A
2013/0007191	12/2012	Klappert	709/217	H04N 21/25866
2018/0304146	12/2017	Dayal et al.	N/A	N/A
2018/0359506	12/2017	Hodge	N/A	H04L 65/70
2019/0158787	12/2018	Pino, Jr. et al.	N/A	N/A
2019/0273954	12/2018	Evans	N/A	H04N 21/25883
2020/0357246	12/2019	Nelson et al.	N/A	N/A
2021/0056750	12/2020	Rowley	N/A	N/A
2021/0076099	12/2020	Ganschow et al.	N/A	N/A
2022/0103905	12/2021	Montgomery et al.	N/A	N/A
2022/0157127	12/2021	Tadepalli	N/A	G07F 17/3288
2022/0377427	12/2021	Montgomery et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3691286	12/2019	EP	H04N 21/23418
WO-2017079778	12/2016	WO	A63B 71/0605
WO-2020251533	12/2019	WO	H04N 21/2146

Primary Examiner: Lin; Jason K

Attorney, Agent or Firm: Kilpatrick Townsend & Stockton LLP

Background/Summary

(1) This disclosure generally relates to content corresponding to televised and streamed events, and more particularly to adaptive content composite generation and control.

BACKGROUND

(2) Users of televisions and other video distribution platforms are now exposed to more varying types of content than ever before. However, with the proliferation of different content corresponding to televised and streamed events, a viewer can encounter a number of difficulties. The difficulties can include system performance deficiencies, as well as the amount of time and effort necessary to search for and interact with various systems providing content corresponding to events viewed via the platforms. The process of locating and interacting with optimal content features can be difficult, inefficient, and limited. Viewers are in need of better viewer experiences and interactive features.

(3) Thus, there is a need for systems, methods, and processor-readable media that address the foregoing problems in order. This and other needs are addressed by the present disclosure.

BRIEF SUMMARY

(4) Certain embodiments of the present disclosure relate generally to content corresponding to televised and streamed events, and more particularly to adaptive content composite generation and control.

(5) In one aspect, a system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event is disclosed. The system may include one or more processing devices and memory communicatively coupled with and readable by the one or more processing devices and having stored therein processor-readable instructions which, when executed by the one or more processing devices, cause the one or more processing devices to perform operations. In another aspect, a method for adaptive content composite interaction with respect to digitally distributed content corresponding to an event is disclosed. In yet another aspect, one or more non-transitory, machine-readable media is disclosed as having machine-readable instructions thereon which, when executed by one or more processing devices, cause the one or more processing devices to perform operations. The operations and steps of the system, method, and non-transitory, machine-readable media may include one or a combination of the following. A set of one or more electronic communications received via one or more interfaces may be detected. One or more signals of one or more events that are specified for digital distribution from a set of one or more events may be detected from the set of one or more electronic communications. A set of observation data corresponding to indications of detected media device operations associated with a set of one or more media devices in a particular geolocation may be processed and mapped to the set of one or more events. An identifier of a particular event of the set of one or more events may be selected based at least in part on the set of observation data. A content composite corresponding to the particular event may be created. An adaptable content object corresponding to the particular event may be identified based at least in part on the set of observation data. A content object received by the one or more processing devices from a system that is remote from the one or more processing devices may be processed. The adaptable content object may be configured with the content object so that the content composite causes presentation of the adaptable content object adapted with the content object for at least part of a presentation time when the content composite is presented. The content composite may be output for presentation where, consequent to providing the content composite to an endpoint media device, the endpoint media device performs at least one operation relating to the content composite. At least one signal corresponding to the at least one operation relating to the content composite that is triggered by the content composite and that is indicative of activation of an interface option caused by the content composite may be processed.

(6) In various embodiments, the set of observation data may correspond to indications of detected media device operations associated with a plurality of media devices in the particular geolocation. In various embodiments, the set of observation data may correspond to indications of detected

media device operations associated with a particular endpoint identifier. In various embodiments, the detected media device operations may include one or more previous interactions with one or more previous content composites. In various embodiments, the detected media device operations may include one or more previous operational settings of the media device. In various embodiments, the creating the content composite may be a function of the current geolocation of the media device and a set of rules mapped to the current geolocation. In various embodiments, one or both of the adaptable content object and the content object may be identified as a function of a current geolocation mapped to a media device associated with the particular endpoint identifier. (7) Further areas of applicability of the present disclosure will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating various embodiments, are intended for purposes of illustration only and are not intended to necessarily limit the scope of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A further understanding of the nature and advantages of various embodiments may be realized by reference to the following figures. In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.
- (2) FIG. 1 illustrates a content distribution system, in accordance with disclosed embodiments per the present disclosure.
- (3) FIG. 2 illustrates a functional diagram of an adaptive content composite generation/control system, in accordance with disclosed embodiments per the present disclosure.
- (4) FIG. 3 illustrates a portion of the content composite generation/control system with aggregation and transformation features, in accordance with disclosed embodiments per the present disclosure.
- (5) FIG. 4 illustrates a subsystem data flow, in accordance with disclosed embodiments per the present disclosure.
- (6) FIG. 5 illustrates a content composite interaction subsystem, in accordance with disclosed embodiments per the present disclosure.
- (7) FIG. 6 illustrates an example method for content composite generation with respect to digitally distributed content corresponding to an event, in accordance with disclosed embodiments per the present disclosure.
- (8) FIG. 7 illustrates an example method for state-based content composite generation with respect to digitally distributed content corresponding to an event, in accordance with disclosed embodiments per the present disclosure.
- (9) FIG. 8 illustrates example method for adaptive content composite interaction with respect to digitally distributed content corresponding to an event, in accordance with disclosed embodiments per the present disclosure.
- (10) FIG. 9 illustrates a receiver that makes use of, interacts with, and/or at least partially includes the content composite generation/control system, in accordance with disclosed embodiments per the present disclosure.
- (11) FIG. 10 illustrates a system including one non-limiting example of a computing device configured to facilitate adaptive content composite generation/control, in accordance with disclosed embodiments of the present disclosure.

DETAILED DESCRIPTION

(12) The ensuing description provides preferred exemplary embodiment(s) only, and is not intended to limit the scope, applicability or configuration of the disclosure. Rather, the ensuing description of the preferred exemplary embodiment(s) will provide those skilled in the art with an enabling description for implementing a preferred exemplary embodiment of the disclosure. It should be understood that various changes may be made in the function and arrangement of elements without departing from the spirit and scope of the disclosure as set forth in the appended claims.

(13) Specific details are given in the following description to provide a thorough understanding of the embodiments. However, it will be understood by one of ordinary skill in the art that the embodiments may be practiced without these specific details. For example, circuits may be shown in block diagrams in order not to obscure the embodiments in unnecessary detail. In other instances, well-known circuits, processes, algorithms, structures, and techniques may be shown without unnecessary detail in order to avoid obscuring the embodiments.

(14) Also, it is noted that the embodiments may be described as a process which is depicted as a flowchart, a flow diagram, a data flow diagram, a structure diagram, or a block diagram. Although a flowchart may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process is terminated when its operations are completed but could have additional steps not included in the figure. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, etc. When a process corresponds to a function, its termination corresponds to a return of the function to the calling function or the main function.

(15) Various embodiments will now be discussed in greater detail with reference to the accompanying figures, beginning with FIG. 1.

(16) FIG. 1 illustrates a content distribution system **100**, in accordance with disclosed embodiments of the present disclosure. For brevity, system **100** is depicted in a simplified and conceptual form, and may generally include more or fewer systems, devices, networks, and/or other components as desired. Further, the number and types of features or elements incorporated within the system **100** may or may not be implementation-specific, and at least some of the aspects of the system **100** may be similar to a cable television distribution system, an IPTV (Internet Protocol Television) content distribution system, and/or another type of media or content distribution system.

(17) The system **100** may include content television service provider system **102** (e.g., a television service provider system), satellite uplink **104**, a plurality of orbiting (e.g., geosynchronous) satellites **106**, satellite receiver **108**, one or more television receivers **110**, one or more content sources **112** (e.g., online content sources), computing devices **116-1**, **116-2**, **116-3**, **116-4** (referenced generally herein with **116**), and service provider systems **103**. In some embodiments, each of the television receivers **110** may include a content composite subsystem **111**. Additionally or alternatively, the content provider **102** may include a content composite subsystem **111** in whole or in part. Additionally or alternatively, one or more service provider systems **103** may include a content composite subsystem **111** in whole or in part. Additionally or alternatively, one or more computing devices **116** may include a content composite subsystem **111** in whole or in part. The content composite subsystem **111** may be configured to facilitate various content composite generation/control features in accordance with various embodiments disclosed herein. The extent to which the media devices **116** may be configured to provide features of the subsystem **111** (e.g., by way of software updates and communications from the system **102-1**) may depend on the processing power and storage capabilities of a given device **116**. The system **102-1** may communicate with a given device **116** to pull specifications and current device capability information from the device **116**. Based on such communications, the system **102-1** may the extent to which the device **116** can be configured to provide features of the subsystem **111** and may operate accordingly. For example, the system **102-1** may push one or more software packages to the device **116** to configure the device **116** to provide a set of one or more features of the subsystem **111**. In instances where the device **116** lacks sufficient processing and/or storage capabilities, the

subsystem **111** may operate on the system **102-1**. As one example with respect to many features disclosed herein, the filtering of composites **180** may be performed on the backend at system **102-1** when the device **116** lacks sufficient resources to perform the filtering itself. Further, in some embodiments, additionally or alternatively, one or more service provider systems **103-1** may include a content composite subsystem **111** in whole or in part. The content composite subsystem **111** may be configured to facilitate various content adaptation features in accordance with various embodiments disclosed herein.

(18) In general, the system **100** may include a plurality of networks **120** that can be used for bi-directional communication paths for data transfer between components of system **100**. Disclosed embodiments may transmit and receive data, including video content, via the networks **120** using any suitable protocol(s). The networks **120** may be or include one or more next-generation networks (e.g., 5G wireless networks and beyond). Further, the plurality of networks **120** may correspond to a hybrid network architecture with any number of terrestrial and/or non-terrestrial networks and/or network features, for example, cable, satellite, wireless/cellular, or Internet systems, or the like, utilizing various transport technologies and/or protocols, such as radio frequency (RF), optical, satellite, coaxial cable, Ethernet, cellular, twisted pair, other wired and wireless technologies, and the like. In various instances, the networks **120** may be implemented with, without limitation, satellite communication with a plurality of orbiting (e.g., geosynchronous) satellites, a variety of wireless network technologies such as 5G, 4G, LTE (Long-Term Evolution), 3G, GSM (Global System for Mobile Communications), another type of wireless network (e.g., a network operating under Bluetooth®, any of the Institute of Electrical and Electronics (IEEE) 802.11 suite of protocols, and/or any other wireless protocol), a wireless local area network (WLAN), a HAN (Home Area Network) network, another type of cellular network, the Internet, a wide area network (WAN), a local area network (LAN) such as one based on Ethernet, Token-Ring and/or the like, such as through etc., a gateway, and/or any other appropriate architecture or system that facilitates the wireless and/or hardwired packet-based communications of signals, data, and/or message in accordance with embodiments disclosed herein. In various embodiments, the networks **120** and its various components may be implemented using hardware, software, and communications media such wires, optical fibers, microwaves, radio waves, and other electromagnetic and/or optical carriers; and/or any combination of the foregoing and/or the like. In some embodiments, the networks **120** may include a telephone network that may be circuit switched, package switched, or partially circuit switched and partially package switched. For example, the telephone network may partially use the Internet to carry phone calls (e.g., through VoIP). In various instances, the networks **120** may transmit data using any suitable communication protocol(s), such as TCP/IP (Transmission Control Protocol/Internet protocol), SNA (systems network architecture), IPX (Internet packet exchange), UDP, AppleTalk, and/or the like.

(19) Many embodiments may include a large number of content provider systems **102**, data source systems **103**, and/or such media devices. The content provider systems **102** may distribute broadcast video content to the endpoint devices **116** and receivers **110** via one or more networks of the networks **120**. For example, a content provider system **102** may be configured to stream, via the networks **120**, television channels, live sporting events and other competitions, on-demand programming, movies, other shows, television programs or portions of television programs following and/or during a live broadcast of the television programs, announcement content and commercials, programming information (e.g., table data, electronic programming guide (EPG) content, etc.), and/or other services to endpoint devices **116** and receivers **110** via satellite, 5G, 4G, and/or LTE wireless communication protocols and network components, in accordance with embodiments disclosed herein. The content provider system **102** may include one or more content server systems configured to stream television programming, including televised events such as sports events, to the computing devices **116** via the network **120**. When the streaming content servers stream content to the computing devices **116**, the stream content may be processed and

displayed by the computing devices **116** using one or more applications installed on the computing devices **116**. Some such streaming services may require a subscription and may require user authentication, e.g., with a username and/or password which may or may not be associated with an account map to the television receiver **110**. Accordingly, the streaming services may make a television program available for streaming or download during the live broadcast of the television program.

(20) The content provider system **102** may include one or more adaptable content object repositories **176**. The content provider system **102** may store adaptable content objects in a repository **176**. The one or more adaptable content object repositories **176** may be implemented in various ways. For example, one or more data processing systems may store adaptable content objects. One or more relational or object-oriented databases, or flat files on one or more computers or networked storage devices, may store adaptable content objects. In some embodiments, a centralized system stores adaptable content objects; additionally or alternatively, a distributed/cloud system, network-based system, such as being implemented with a peer-to-peer network, or Internet, may store adaptable content objects.

(21) Content objects **176** and/or content object objects **177** may correspond to any one or combination of raw data, unstructured data, structured data, information, and/or content which may include media content, text, documents, files, instructions, code, executable files, images, video, audio, audio video, and/or any other suitable content suitable for embodiments of the present disclosure. For example, the adaptable content objects **176** may correspond to visual and/or audiovisual announcements with graphical and/or audio components particularized to certain types of services. In some embodiments, the announcements may correspond to commercials to be presented during commercial breaks of television programming, such as televised events, and/or streamed events. In some instances, the content objects **176** may be sourced by one or more of the service provider systems **103**. In some embodiments, the adaptable content objects **176** may correspond to video and/or audio video file structures with one or more transition points, hooks, frames, windows, and/or the like for merging with one or more particularized content objects, content objects **177**, particularized to certain services (e.g., services of online gambling/betting platforms, content, and features) of the service provider systems **103**. As disclosed herein, the adaptable content objects **176** may be merged, blended, joined, overlaid, customized, and/or the like in any suitable manner with other particularized content objects **177** in order to create electronic content composites **180** particularized to certain types of services. In various embodiments, as further disclosed herein, the adaptable content objects **176** and/or the other content objects are adjusted and/or otherwise prepared to facilitate the merging, blending, joining, overlaying, customizing, and/or the like and insertion into a content stream as disclosed further herein.

(22) In some embodiments, the content provider system **102** may provide the adaptable content objects **176** and, in some embodiments, the particularized content objects **177**, to the devices **116** via one or more of the networks **120**. Additionally or alternatively to providing the adaptable content objects **176** and/or particularized content objects **177**, the content provider system **102** may provide content composites **180** to the television receiver **110** through such means. In some embodiments, the content provider system **102** may provide the adaptable content objects **176** and, in some embodiments, the particularized content objects **177**, to the television receiver **110** as part of a data transfer that is sent through the satellite **106**. For example, in some embodiments, the television receiver **110** may receive a downlinked satellite signal that includes the data for adaptable content objects **176** and/or particularized content objects **177** transferred on a designated line in the vertical blanking interval (VBI) or other portion of the broadcast service communication that does not interfere with other transmitted content. Additionally or alternatively, the content provider **102** may provide adaptable content objects **176** and/or particularized content objects **177** to the television receiver **110** via the one or more data networks **120**. The television receiver **110**

may store the adaptable content objects **176** and/or particularized content objects **177** in an adaptable content object **176** repository and/or a particularized content objects **177** repository included in the television receiver **110** or otherwise local to the television receiver **110**.

Consequently, the television receiver **110** may use one or more of the adaptable content objects **176** and one or more of the particularized content objects **177** to create electronic content composites **180** in accordance with embodiments disclosed herein. Additionally or alternatively to providing the adaptable content objects **176** and/or particularized content objects **177**, the content provider system **102** may provide content composites **180** to the television receiver **110** through such means.

(23) The content provider system **102** and satellite transmitter equipment (which may include the satellite uplink **104**) may be operated by a content provider. A content provider may distribute television channels, on-demand programing, programming information, and/or other services to users via satellite and one or more of the networks **120**. The content provider system **102** may receive feeds of such content from various sources. The television channels may include multiple television channels that contain the same content (but may be in different formats, such as high-definition and standard-definition). To distribute such video content to endpoint devices **116**, feeds of the video content may be relayed to endpoint equipment and the endpoint devices **116** via one or more satellites in the form of transponder streams. Satellite transmitter equipment may be used to transmit a feed of one or more television channels from the content provider system **102** to one or more satellites **106**. While a single content provider system **102** and satellite uplink **104** are illustrated as part of the television distribution system **100**, it should be understood that multiple instances of transmitter equipment may be used, possibly scattered geographically to communicate with satellites **106**. Such multiple instances of satellite transmitting equipment may communicate with the same or with different satellites **106**.

(24) The data source systems **103** may correspond to any suitable sources of data such as one or more computer systems, databases, websites, portals, any repositories of data in any suitable form, server systems, other endpoint devices like endpoint devices **116** but functioning as data sources, and/or the like. In some instances, the data source systems **103** may include one or more mobile computing device locator services that provide information regarding the location of one or more of the endpoint devices **116** and/or the adaptive routers **110**. In various instances, the data source systems **103** may provide various details relating to IP addresses, cellular tower identification and location data, mobile device triangulation data, LAN identification data, Wi-Fi identification data, access point identification and location data, and/or the like data that facilitates location of one or more of the endpoint devices **116** and/or the adaptive routers **110**.

(25) In various embodiments, the data from one or more of the data source systems **103** may be retrieved and/or received by a content provider system **102** via one or more data acquisition interfaces through network(s) **120** and/or through any other suitable means of transferring data. In various embodiments, the content provider system **102** the data source systems **103** could use any suitable means for direct communication. In various embodiments, the content provider system **102** may actively gather and/or pull from one or more of the data source systems **103**. Additionally or alternatively, the content provider system **102** may wait for updates from one or more of the data source systems **103**. The data collected (location data, IP address, content objects **177**, etc.) may be curated so that only the data necessary for the transaction is collected. The one or more data acquisition interfaces may include one or more application programming interfaces (APIs) that define protocols and routines for interfacing with the data source systems **103**. The APIs may specify application programming interface (API) calls to/from data source systems **103**. In some embodiments, the APIs may include a plug-in to integrate with an application of a data source systems **103**. The data acquisition interfaces, in some embodiments, could use a number of API translation profiles configured to allow interface with the one or more additional applications of the data sources to access data (e.g., a database or other data store) of the data source systems **103**. The API translation profiles may translate the protocols and routines of the data source systems **103** to

integrate at least temporarily with the system and allow communication with the system by way of API calls.

(26) The television receivers **110**, as described throughout, may generally be any type of television receiver (such as an STB (set-top box), for example) configured to decode signals received for output and presentation via a display device **160**. In another example, television receiver **110** (which may include another remote television receiver **110**) may be integrated as part of or into a television, a DVR, a computing device, such as a tablet computing device, or any other computing system or device, as well as variations thereof. In some embodiments, a television receiver **110** may be a component that is added into the display device **160**, such as in the form of an expansion card. A television receiver **110** and network **120** together with television receivers **110** and/or one or more computing devices **116**, may form at least a portion of a particular home computing network, and may each be respectively configured such as to enable communications in accordance with any particular communication protocol(s) and/or standard(s) including, for example, TCP/IP (Transmission Control Protocol/Internet Protocol), DLNA/DTCP-IP (Digital Living Network Alliance/Digital Transmission Copy Protection over Internet Protocol), HDMI/HD-CP (High-Definition Multimedia Interface/High-Bandwidth Digital Content Protection), etc. While only a limited number of television receivers **110**, display devices **160**, computing devices **116**, etc. are illustrated in FIG. **1**, it should be understood that multiple (e.g., tens, thousands, millions) instances of such equipment, corresponding to various users in various geolocations, may be included the system **100**.

(27) In some embodiments, broadcast televised events may be delivered to television receivers, including a television receiver **110**, via satellite according to a schedule. On-demand content may also be delivered to a television receiver **110** via satellite. Satellites **106** may be configured to receive uplink signals **122** from satellite uplink **104**. In this example, uplink signals **122** may contain one or more transponder streams of particular data or content, such as particular television channels, each of which may be supplied by content provider **102**. For example, each of uplink signals **122** may contain various media content such as HD (High Definition) television channels, SD (Standard Definition) television channels, on-demand programming, programming information (e.g., table data), and/or any other content in the form of at least one transponder stream, and in accordance with an allotted carrier frequency and bandwidth. In this example, different media content may be carried using different satellites of satellites **106**. Further, different media content may be carried using different transponders of a particular satellite (e.g., satellite **106-1**); thus, such media content may be transmitted at different frequencies and/or different frequency ranges. For example, a first television channel and a second television channel may be carried on a first carrier frequency over a first transponder (as part of a single transponder stream) of satellite **106-1**, and a third, fourth, and fifth television channel may be carried on a second carrier frequency (as part of another transponder stream) over a transponder of satellite **106-3**, or, the third, fourth, and fifth television channel may be carried on a second carrier frequency over a second transponder of satellite **106-1**, etc.

(28) The satellites **106** may be further configured to relay uplink signals **122** to the satellite receiver **108** as downlink signals **124**. Similar to the uplink signals **122**, each of the downlink signals **124** may contain one or more transponder streams of particular data or content, such as various encoded and/or at least partially scrambled television channels, on-demand programming, etc., in accordance with an allotted carrier frequency and bandwidth. The satellite receiver **108**, which may include a satellite dish, a low noise block (LNB), and/or other components, may be provided for use to receive television channels, such as on a subscription basis, distributed by the content provider **102** via the satellites **106**. For example, the satellite receiver **108** may be configured to receive particular transponder streams as downlink signals **124**, from one or more of the satellites **106**. Based at least in part on the characteristics of a given television receiver **110** and/or satellite receiver **108**, it may only be possible to capture transponder streams from a limited number of

transponders of the satellites **106** concurrently. For example, a tuner of the television receiver **110** may only be able to tune to a single transponder stream from a transponder of a single satellite, such as the satellite **106-1**, at a time.

(29) The television receiver **110**, which may be communicatively coupled to the satellite receiver **108**, may subsequently select, via a tuner, decode, and relay television programming to a television for display thereon. Broadcast television programming or content may be presented “live,” or from a recording as previously stored on, by, or at the television receiver **110**. For example, an HD channel may be output to a television by the television receiver **110** in accordance with the HDMI/HDCP content protection technologies. Other embodiments are possible. For example, in some embodiments, an HD channel may be output to a television in accordance with the MoCA® (Multimedia over Coax Alliance) home entertainment networking standard. Other embodiments are possible.

(30) The television receiver **110** may select via tuner, decode, and relay particular transponder streams to one or more of television receivers **110**, which may in turn relay particular transponder streams to one or more display devices **160**, **160-1**. For example, the satellite receiver **108** and the television receiver **110** may, respectively, be configured to receive, decode, and relay at least one television channel to a television by way of a television receiver **110**. Similar to the above example, a television channel may generally be presented “live,” or from a recording as previously stored by the television receiver **110**, and may be output to the display device **160**, **160-1** by way of the television receiver **110** in accordance with a particular content protection technology and/or networking standard. Other embodiments are possible.

(31) In various embodiments, the content resources **126** may be used to provide the television receiver **110** with content (e.g., televised and streamed events). The content resources **126** may be used to retrieve televised and/or otherwise streamed events or portions of thereof following and/or during a live broadcast of the televised and/or otherwise streamed events. The content resources **126** may include the content provider **102**, the service provider systems **103**, the online content sources **112**, one or more other television receivers **110**, and/or the like.

(32) The content provider **102**, which may distribute broadcast televised and/or otherwise streamed events to the television receivers **110** via a satellite-based television programming distribution arrangement (or some other form of television programming distribution arrangement, such as a cable-based network, fiber-based network, or IP-based network, may use an alternate communication path, such as via one or more of the networks **120**, to provide televised and/or otherwise streamed events to the television receivers **110**. The television receivers **110** may be permitted to request various television programs or portions of televised and/or otherwise streamed events from the content provider **102** via the network **120**. For instance, the content provider **102** may be permitted to transmit a portion of a television program or an entire television program during and/or after a time at which the television program was broadcast live by the content provider via a satellite-based television programming distribution arrangement.

(33) In some embodiments, the content provider **102** may provide a televised and/or otherwise streamed event via on-demand content. Such on-demand content may be provided via the satellite-based distribution arrangement and/or via the network **120**. On-demand content provided via the satellite-based distribution arrangement may be stored locally by the television receiver **110** to allow on-demand access. On-demand content may also be retrieved via the network **120** from the content provider **102**.

(34) The computing devices **116** represent various computerized devices that may be associated with a user of the television receiver **110** and that may be configured to facilitate various adaptive content features disclosed in various embodiments herein. As indicated by **116a**, the computing devices **116** may include a laptop computer, a desktop computer, a home server, or another similar form of computerized device. As indicated by **116b** and **116c**, the computing devices **116** may include a cellular phone and/or smartphone, a tablet computer, or another similar form of mobile

device. As indicated by **116d**, the computing devices **116** may include smart glasses or another similar form of wearable computing device.

(35) In various embodiments, the television receiver **110** may be provided with access credentials that allow access to content stored and/or accessible through one or more of the computing devices **116**. Likewise, in various embodiments, one or more of the computing devices **116** may be provided with access credentials that allow access to content stored and/or accessible through the television receiver **110** and/or account associated therewith and/or associated with an application installed on the one or more of the computing devices **116**. It should be understood that computing devices **116** are exemplary in nature. Content may be accessible through a lesser or greater number of computerized devices associated with a user of the television receiver **110**.

(36) In some embodiments, the online content sources **112** may represent content resources through which televised and/or otherwise streamed events may be retrieved by the television receiver **110** via the network **120**. Each of the online content sources **112** may represent different websites available via the Internet. Periodically, the television receiver **110** may poll online content sources **112** to determine which televised and/or otherwise streamed events are available and/or which television programs are scheduled to be available in the future. In some embodiments, the television receiver **110** may poll online content sources **112** regarding the availability of at least a portion of a specific televised and/or otherwise streamed event.

(37) The service provider systems **103** may correspond to one or more data sources **112** that are any suitable source of data to facilitate embodiments disclosed further herein. In various embodiments, the service provider systems **103** may include one or more computer systems, a database, a website, a portal, any repository of data in any suitable form, a server system, and/or the like. With some embodiments, the data sources **112** may include one or more mobile computing device locator services that provide information regarding the location of one or more computing devices **116**. With some embodiments, the data sources **112** may provide various details relating to IP addresses, cellular tower identification and location data, mobile device triangulation data, LAN identification data, Wi-Fi identification data, access point identification and location data, and/or the like data that facilitates location of one or more computing devices **116**. With some embodiments, the data sources **112** may provide demographic data about an area encompassing the location of one or more computing devices **116**.

(38) In various embodiments, the data from the one or more data sources **112** may be retrieved and/or received by the content provider system **102** and/or the subsystem(s) **111** via one or more data acquisition interfaces through network(s) **120** and/or through any other suitable means of transferring data. Data, as referenced herein, may correspond to any one or combination of raw data, unstructured data, structured data, information, and/or content which may include media content, text, documents, files, instructions, code, executable files, images, video, audio, and/or any other suitable content suitable for embodiments of the present disclosure. In various embodiments, the content provider system **102** and/or the subsystem(s) **111** and the data sources **112** could use any suitable means for direct communication. In various embodiments, content objects **176** and/or **177** may be actively gathered and/or pulled from one or more data sources **112**, for example, by accessing a repository and/or by “crawling” various repositories. Additionally or alternatively, the content provider system **102** and/or the subsystem(s) **111** may wait for updates from one or a combination of the content source systems **112**. Content objects **176** and/or **177** pulled and/or pushed from the one or more data sources **112** may be transformed, and the transformed content objects **176** and/or **177** and/or other data generated based thereon may be made available by the content provider system **102** and/or the subsystem(s) **111** for use by the subsystem(s) **111** in creating content composites **180**.

(39) The television receiver **110** may be able to retrieve at least a portion of a television program through other television receivers **110**, which can function as content resources. Similarly, the television receiver **110** may be able to cast at least a portion of a television program through other

television receivers **110** and/or to computing devices **116**. For instance, a Slingbox® (or other form of media streaming device) functioning in concert with a television receiver **110** may permit television programs to be captured and streamed over the network **120**. In some embodiments, the television receivers **110** may have such media streaming capabilities integrated. In some embodiments, the television receivers **110** may cast programming content to the computing devices **116** via wireless signals. For example, the programming content from the television receiver **110** may be indirectly transmitted via a local network (e.g., via Wi-Fi) or directly transmitted to the computing device **116** via a casting device integrated with the television receiver **110** or coupled to the television receiver **110** (e.g., via a dongle). In some embodiments, the programming content may be cast to the computing device **116** via a wired connection (e.g., via one or more of HDMI, USB, lightning connector, etc.). Some embodiments of the television receivers **110** may provide for simulcasting such that the same programming that is being displayed on the display device **160** is being displayed on one or more of the computing devices **116** simultaneously or substantially simultaneously.

(40) While network configuration data may be broadcast repeatedly via satellite to television receivers **110**, it should be understood that a similar arrangement may be used in cable-based television programming broadcast networks to broadcast network configuration. For any of the various type of network, various other forms of data may be transmitted via an Internet-based network **120** connection rather than using the content provider's proprietary network. For instance, EPG data may be transmitted to television receivers via the network **120** (e.g., Internet) connection. As another example, firmware and/or software updates may be transmitted on demand to a television receiver via the Internet rather than the television receiver receiving the update via the television programming broadcast network.

(41) The system **102** with the content composite subsystem **111** may be configured to perform one or more methods for facilitating adaptive content composite generation and interaction with respect to digitally distributed content corresponding to an event, as disclosed herein. The one or more methods may include containerizing and adapting content objects as content composites, as disclosed herein. The event may correspond to a live event. The digital distribution of content corresponding to the event may include one or a combination of streaming, live streaming, other online delivery, over the air delivery, cable-television distribution, satellite television distribution, and/or the like. Thus, as one example, the event may correspond to a live, televised event.

(42) In various embodiments, one or more media devices (e.g., one or more of devices **110** and/or **116** and/or the system **102**) may perform all or part of the methods, with a single media device or multiple media devices performing the methods. In various embodiments, part or all of the methods may be performed while an endpoint media device (e.g., one or more of device **110** and/or **116**) is receiving televised, streamed and/or otherwise digitally distributed content and/or is outputting the content for display. In various embodiments, at least part of the methods may be performed in advance of the televised, streamed and/or otherwise digitally distributed event and, thus, may be performed while the content is scheduled but before the content is transmitted to endpoint media devices and/or before the content is output by an endpoint media device for display.

(43) Teachings of the present disclosure may be implemented in a variety of configurations that may correspond to the configurations disclosed herein. As such, certain aspects of the methods disclosed herein may be omitted, and the order of the steps may be shuffled in any suitable manner and may depend on the implementation chosen. Moreover, while the aspects of the methods disclosed herein, may be separated for the sake of description, it should be understood that certain steps may be performed simultaneously or substantially simultaneously.

(44) FIG. **6** illustrates an example method **600** for content composite generation with respect to digitally distributed content corresponding to an event, in accordance with embodiments of the present disclosure. One or a combination of the aspects of the method **600** may be performed in conjunction with one or more other aspects disclosed herein, and the method **600** is to be

interpreted in view of other features disclosed herein and may be combined with one or more of such features in various embodiments.

(45) As indicated by block **602**, one or more sets of one or more electronic communications may be received via one or more interfaces (e.g., of a media device) and detected. As indicated by block **604**, one or more indicators of one or more events of a set of one or more events for which corresponding content is specified for digital distribution may be detected from the one or more sets of one or more electronic communications. For example, the one or more events may include televised events, and the set may include a set of one or more televised events. The corresponding content may be specified for upcoming digital distribution (e.g., for the next 24 hours or any suitable upcoming time period) and/or current, ongoing digital distribution (e.g., a live event is currently in progress and being televised, streamed, etc.). The indicators may include or otherwise correspond to metadata regarding the events, as disclosed further herein. The metadata may be received on-demand (e.g., it may be pulled when needed or on scheduled basis), periodically, and/or on a scheduled basis, in various embodiments. For example, the metadata may be pulled responsive to user activation of a device **116**, which may correspond to opening of an app installed on the device **116**.

(46) As indicated by block **606**, in various embodiments, a set of observation data may be processed, the set of observation data corresponding to indications of detected media device operations associated with a set of one or more media devices **110** and/or **116** in a particular geolocation and mapped to the set of one or more events. The set of observation data may correspond to indications of detected media device operations associated with a plurality of media devices **110** and/or **116** in the particular geolocation. Additionally or alternatively, the set of observation data may correspond to indications of detected media device operations associated with a particular endpoint identifier. Such detected media device operations may include one or more previous interactions with one or more previous content composites **180**. Additionally or alternatively, such detected media device operations may include one or more previous operational settings of the plurality of media devices **110** and/or **116** and/or of one or more media devices **110** and/or **116** associated with the particular endpoint identifier. As indicated by block **608**, based at least in part on the set of observation data, an identifier of a particular event of the set of one or more events may be selected. Accordingly, the event may be identified for content composite creation.

(47) As indicated by block **610**, a content composite **180** corresponding to the particular event may be created, as disclosed further herein. For example, the content composite **180** may be created at least in part by one or a combination of the following. As indicated by block **612**, an adaptable content object **176** corresponding to the particular event may be identified based at least in part on the set of observation data. This may include selecting the adaptable content object **176** from a plurality of adaptable content objects **176**. As disclosed further herein, such selection may be based at least in part on matching specifications of one or more adaptable content objects **176** with specifications (e.g., the one or more indicators) of the particular event. In various embodiments, the adaptable content object **176** may be received from a system (e.g., **102** or **103**) that is remote from the one or more processing devices (which, in various embodiments, may be included in the devices **116**, **110**, and/or system **102**). As indicated by block **614**, a particularized content object **177** corresponding to the particular event may be processed. The content object **177** may be received by the one or more processing devices from a system (e.g., **102** or **103**) that is remote from the one or more processing devices. As disclosed further herein, the content object **177** may be pushed from the remote system or pulled from the remote system by the one or more processing devices responsive to the one or more processing devices transmitting one or more specifications of the particular event, the adaptable content object **176**, and/or the content object **177**.

(48) In some embodiments, the creating the content composite **180** may be a function of the current geolocation of the media device **110** and/or **116** associated with the particular endpoint identifier

and a set of rules mapped to the current geolocation. In various embodiments, one or both of the adaptable content object **176** and the content object **177** are identified as a function of a current geolocation mapped to the media device **110** and/or **116** associated with the particular endpoint identifier.

(49) As indicated by block **616**, the adaptable content object **176** may be configured with the content object **177** so that the content composite **180** causes presentation of the adaptable content object **176** adapted with the content object **177** for at least part of a presentation time when the content composite **180** is presented, as disclosed further herein. As indicated by block **618**, subsequently, the content composite **180** may be output by the one or more processing devices for presentation. Consequent to providing the content composite to an endpoint media device **110** and/or **116**, the endpoint media device **110** and/or **116** may perform at least one operation relating to the content composite **180**, as disclosed further herein. As indicated by block **620**, at least one signal corresponding to the at least one operation relating to the content composite **180** that is triggered by the content composite **180** and that is indicative of activation of an interface option caused by the content composite **180** may be processed, also as disclosed further herein.

(50) FIG. 7 illustrates an example method **700** for state-based content composite generation with respect to digitally distributed content corresponding to an event, in accordance with embodiments of the present disclosure. One or a combination of the aspects of the method **700** may be performed in conjunction with one or more other aspects disclosed herein, and the method **700** is to be interpreted in view of other features disclosed herein and may be combined with one or more of such features in various embodiments. In various embodiments, one or more of the methods may additionally or alternatively include one or a combination of the following.

(51) As indicated by block **702**, a first set of one or more electronic communications may be received via one or more interfaces and detected. As indicated by block **704**, one or more indicators of one or more events of a set of one or more events for which corresponding content is specified for digital distribution may be detected from the one or more sets of one or more electronic communications. As indicated by block **706**, the one or more processing devices may detect one or more additional electronic communications received via the one or more interfaces. As indicated by block **708**, when listening for data changes in the one or more additional electronic communications with respect to one or more events of a set of one or more events (e.g., the first set, the second set, or another set), the one or more processing devices may detect one or more data changes that are generated based at least in part on at least one event of the set of one or more events. As indicated by block **710**, the one or more processing devices may identify a specification of criteria that apply to the one or more data changes. As indicated by block **712**, the one or more processing devices may determine whether the one or more data changes correspond to one or more state changes specified in the specification of criteria. As indicated by block **714**, consequent to determining that the one or more data changes correspond to the one or more state changes, a content composite **180** corresponding to the at least one event may be created. As indicated by block **716**, the content composite **180** may be created at least in part by identifying an adaptable content object **176** corresponding to the at least one event. As indicated by block **718**, the content composite **180** may be created at least in part by processing a content object **177** received from a system **102** or **103** that is remote from the one or more processing devices. As indicated by block **720**, the content composite **180** may be created at least in part by configuring the adaptable content object **176** with the content object **177** so that the content composite **180** causes presentation of the adaptable content object **176** adapted with the content object **177** for at least part of a presentation time when the content composite **180** is presented. As indicated by block **722**, the content composite **180** may be output by the one or more processing devices for presentation, where, consequent to providing the content composite **180** to an endpoint media device **110** and/or **116**, the endpoint media device **110** and/or **116** may perform at least one operation relating to the content composite **180**. As indicated by block **722**, at least one signal corresponding to the at least one

operation relating to the content composite **180** that is triggered by the content composite **180** and that is indicative of activation of an interface option caused by the content composite **180** may be processed.

(52) As disclosed further herein, the content object **177** may be based at least in part on the one or more state changes. The one or more state changes may correspond to one or more changes occurring within the at least one event. One or more indicators of the one or more state changes with respect to the event may indicate real-time, real-world, and/or physical state changes such as those disclosed further herein. Additionally or alternatively, the one or more state changes correspond to one or more changes from at least one previous parameter corresponding to the at least one event to at least one updated parameter corresponding to the at least one event, as disclosed further herein. Thus, the content composite **180** may cause display of an interface element that allows user selection to cause communication to the system **102** or **103** of an instruction to configure an executable function in accordance with a set of parameters, where the set of parameters includes the at least one updated parameter. This may correspond to placing a bet with a process-performing system **103** in accordance with a set of parameters that may specify the event, the type of bet, odds, amount placed, and/or the like. Further, the determining whether the one or more data changes correspond to one or more state changes specified in the specification of criteria may include scoring the at least one event according to the criteria. The one or more data changes may correspond to a plurality of data changes, the at least one event may correspond to a plurality of events, and each event may be scored according to the specification of criteria. The plurality of events may be ranked according to the scoring, and the at least one event may be the top-ranked event according to the ranking. Further, the one or more state changes may include upcoming state changes such as commercial breaks, upcoming within a time threshold (e.g., a number of seconds and/or minutes)

(53) In some embodiments, the operations of the methods may begin with or may be initiated by the media device **116** or **110** receiving and processing an electronic communication from a user interface, the electronic communication corresponding to an indicator of content. For example, the indicator may correspond to a selection corresponding to a televised/streamed event, may correspond to an initialization/powering up of the device **116** or **110**, a channel and/or stream selection such as a selection to tune to a channel that is streaming the event or that is scheduled to stream the event, an application selection such as a selection to download or otherwise stream the event which may be by way of an application installed on the device **116** or **110**, a selection to view and/or record a particular event, and/or the like. Additionally or alternatively, the operations of the methods may begin with or may be initiated separately from such communications. For example, one or more of the operations may be performed as background processes.

(54) The media device **116** or **110** may receive content corresponding to an event and may output the content for display with a display device **160** and/or with a display component of a device **116**. The content may be determined to include the televised/streamed event, as preceding the event, and/or as being delivered within a temporal proximity to the event. This may include identifying one or more specifications of the event from the programming content; metadata associated with the programming content; EPG or other schedule data received by the receiver **110** and/or device **116** from the content provider system **102** and mapping such data to the content, channel, and/or current or upcoming time/time period; and/or the like. Some embodiments may further include identifying the televised/streamed event as likely to be viewed by a particular viewer based at least in part on viewer pattern data, even though the viewer has not yet made a selection to view and/or record the event. For example, as disclosed herein, the pattern data may indicate a preference for a particular type of event. The subsystem **111** may determine that the event corresponds to the preference and that temporal specifications for the event satisfy one or more temporal thresholds. In some instances, the subsystem **111** may determine that the event is currently ongoing and available for viewing on another channel, stream, or other viewing options that the viewer has not

yet selected. Likewise, in some instances, the subsystem **111** may determine that the event is scheduled to be available within a suitable time for threshold (e.g., a number of minutes, hours, days, weeks, and/or the like) for viewing on the same channel, stream, or other viewing option that the viewer has selected or on a different channel, stream, or other viewing option that the viewer has not yet selected.

(55) FIG. 2 illustrates a functional diagram of an adaptive content composite generation/control system **200**, in accordance with disclosed embodiments of the present disclosure. In various embodiments, the content composite system **200** may be included in whole or in part in the content provider system **102** and/or an endpoint media device **116**. In some embodiments, the content composite system **200** may be separate from, and provide content to, the content provider system **102**. In some embodiments, the content composite system **200** may be included in the end-user system and may be included in the television receiver **110** and/or one or more of the computing devices **116**. In some embodiments, various features of the content composite generation/control system **200** may be distributed between the television receiver **110** and upstream of the television receiver **110**. Likewise, in some embodiments, various features of the content composite generation/control system **200** may be distributed between one or more of the computing devices **116** and upstream of the one or more computing devices **116**. While not all components of the adaptive content composite generation/control system **200** are shown, the system **200** may include one or a combination of such components.

(56) As depicted, the content composite generation/control system **200** includes a content composite subsystem **111**. The content composite subsystem **111** may include or otherwise correspond to an audiovisual control engine that, as with disclosed embodiments of the other engines, may include instructions retained in processor-readable media and to be executed by one or more processors. The content composite subsystem **111** may be communicatively coupled with interface components and communication channels (e.g., of the television receiver **110** and/or the computing device **116**, which may take various forms in various embodiments as disclosed herein) configured to receive programming content **202**, which may correspond to televised sporting events, other competitions, television programs, portions thereof, and/or the like. In various embodiments, the programming content **202** may include audiovisual content broadcast and/or otherwise transmitted by the content provider **102** and/or one or more other service providers **103** by way of one or a combination of streaming, live streaming, other online delivery, over the air delivery, cable-television distribution, satellite television distribution, and/or the like. The programming content **202** may include various components, including without limitation, one or more video tracks, audio tracks, audio video tracks, metadata tracks, close captioning information, and/or the like. In some embodiments, the content composite generation/control system **200** may retain received programming content **202** in content storage **222**. The content storage **222** may include any suitable form of storage media, such as any suitable form disclosed herein.

(57) The content composite subsystem **111** may be further configured to receive adaptable content objects **176** and particularized content objects **177**. The content composite subsystem **111** may include a harvesting engine **236** configured to aggregate adaptable content objects **176**, particularized content objects **177**, and/or programming content **202** in order to facilitate content composite generation/control features disclosed herein. The content composite subsystem **111** may include a matching engine **238**, which, in various embodiments, may be configured to analyze, classify, categorize, characterize, tag, and/or annotate adaptable content objects **176**, particularized content objects **177**, and/or programming content **202**.

(58) The content composite subsystem **111** may include a content composite splicing engine **242**. In some embodiments, the content composite splicing engine **242** may include a multiplexer. In various embodiments, the multiplexer may create a digital stream of data packets containing the video, audio, and, in some embodiments, the metadata to output the programming content **202**, adaptable content objects **176**, and/or the composites **180** created with selected adaptable content

objects **176**. In various embodiments, the content composite splicing engine **242** may be implemented at the receiver **110**, the device **116**, and/or the service provider system **102**.

(59) In embodiments where the content composite splicing engine **242** is implemented at the service provider system **102**, the multiplexed data stream may be transmitted via the one or more networks **124** for provisioning to computing devices **116** or via a particular transponder stream via a transponder of a satellite for provisioning to receivers **110**. The multiplexer may create a digital stream of data packets containing the video, audio, and entitlement control messages (ECMs), to be transmitted on the transponder data stream. The data stream, which includes video and/or audio data packets that are not scrambled, may be passed to a scrambling engine, which may use a control word to scramble video or audio present in a data packet. Some audio and video packets may also pass through with no scrambling, if desired by the content provider **102**. A control word generator may generate the control word that is used by a scrambling engine to scramble the video or audio present in the data packet. Control words generated by the control word generator may be passed to a security system, which may be operated by the content provider or by a third-party security provider. The control words generated by control word generator may be used by security system to generate an ECM. Each ECM may indicate two control words. The control words indicated may be the current control word being used to scramble video and audio, and the control word that will next be used to scramble video and audio. The security system may output an ECM to the multiplexer for communication to subscribers' set-top boxes. Each data packet, whether it contains audio, video, an ECM, or some other form of data, may be associated with a particular PID. This PID may be used by the set-top box in combination with a networking information table to determine which television channel the data contained within the data packet corresponds. Accordingly, the transponder data streams may contain scrambled video packet stream and audio packet stream and also an encrypted ECM packet stream which contains the control words necessary to descramble the scrambled video and audio packets.

(60) In some embodiments, the harvesting engine **236** may be configured to receive, pull, process, buffer, organize, rank, and/or store adaptable content objects **176**, particularized content objects **177**, programming content **202**, and/or data source input **212**. In various embodiments, the content provider system **102**, the television receiver **110**, and/or the computing device **116** may include one or more applications to facilitate the subsystem **111** analyzing and consolidating data source input **212** (e.g., data feeds and/or event updates) received from various data sources **112**, which may or may not be included in the service provider systems **103**. As an example, data source input **212** may include, but are not limited to, updates (real-time and/or otherwise) and/or continuous data streams received from one or more data sources **112**, which may include real-time events related to bookmakers, bookies, sportsbooks, oddsmakers, sports event and/or other competition information, gambling/betting, Twitter® feeds, Instagram® posts, Facebook® updates, and/or the like.

(61) As disclosed above, the adaptable content objects **176** may be particularized to certain services. In some embodiments, the adaptable content objects **176** may correspond to commercials to be presented during commercial breaks of the programming content **202**. Additionally or alternatively, the adaptable content objects **176** may correspond to announcements or other content to be presented as overlays, in windows/frames and/or in pop-ups during, before, and/or after events, in various embodiments. Additionally or alternatively, the adaptable content objects **176** may correspond to announcements or other content to be transmitted and presented as text messages, push notifications, email notifications, and other notifications which would typically be received via one or more apps on the device **116** and cause user-detectable notifications in response during, before, and/or after events, in various embodiments. Additionally, the adaptable content objects **176** may allow for invoking, waking up, opening, and/or otherwise activating an application of the endpoint media device **116**, in some instances, when the application is offline and/or otherwise not online with respect to the system **102**, **200**, and/or another system **103**. In various embodiments, the content objects **176** may include audiovisual content broadcast and/or

otherwise transmitted by the content provider **102**. In some embodiments, adaptable content objects **176** may be pushed by the content provider **102** to the subsystem **111**. In addition or in alternative, adaptable content objects **176** may be pulled by the subsystem **111** (e.g., by the harvesting engine **236**) from the content provider **102**.

(62) The particularized content objects **177** may correspond to content that is particularized to certain types of services and that is sourced by one or more of the service provider systems **103**. In various embodiments, the service provider systems **103** may correspond to process-performing systems that may receive instructions to configure executable functions in accordance with set of parameters and, in response, configure the executable functions in accordance with set of parameters. In various embodiments, the service provider systems **103** may correspond to one or more sources of data and/or services corresponding to bookmakers, bookies, sportsbooks, oddsmakers, sports information, event information, gambling/betting, social media websites, and/or the like, and particularized content objects **177** may correspond to the specific data and/or services sourced by a specific service provider system **103** for a specific event. For example, the data may correspond to odds information with respect to a particular sporting event and a particular outcome of the sporting event and/or of certain potential results/actions that could occur within the event. The data may correspond to particular digital content, a matrix code such as a QR code, and/or the like. The services may, for example, correspond to the bookmaker/sportsbook services offered to facilitate betting with respect to the sporting event. In some embodiments, particularized content objects **177** may include content that is particularized to one or more viewers based at least in part on observation data learned about the one or more viewers, as disclosed further herein. As disclosed above, the adaptable content objects **176** and/or the content object objects **177** may correspond to any one or combination of raw data, unstructured data, structured data, information, and/or content which may include media content, text, documents, files, instructions, code, executable files, images, video, audio, audio video, and/or any other suitable content suitable for embodiments of the present disclosure.

(63) In various embodiments, sets of one or more adaptable content objects **176** and/or sets of one or more content object objects **177** may be transmitted to the subsystem **111** in batches. For example, sets of one or more adaptable content objects **176** and/or sets of one or more content object objects **177** may be transmitted to the subsystem **111** on a periodic or otherwise scheduled basis. The subsystem **111** may store the adaptable content objects **176** locally and, subsequently select one or more of the adaptable content objects **176** when needed for presentation during an upcoming break in the programming content **202** corresponding to an event and/or when needed for presentation during the programming content **202** corresponding to the event based at least in part on the subsystem **111** determining specifications of the event, a temporal progression in the event (e.g., the fourth quarter, the second round, etc.), a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), and/or the like.

(64) In various embodiments, sets of one or more adaptable content objects **176** and/or sets of one or more content object objects **177** may be transmitted to the subsystem **111** on an as-needed basis when the subsystem **111** is receiving programming content **202** corresponding to a certain type (e.g., a televised sporting event for which sports betting information and services are available), is scheduled to receive such programming content **202**, is predicted to receive programming content **202** based at least in part on a detected viewing pattern of past viewing of previous programming content **202** (e.g., of a certain type of event, at certain times, on certain days, etc.), and/or is predicted to receive programming content **202** based at least in part on a detected pattern of past viewer responses to content composites for previous programming content **202** of that type. Additionally or alternatively, in some embodiments, sets of one or more adaptable content objects **176** and/or sets of one or more content object objects **177** may be selected (e.g., the service provider system **102**) as tailored for particular event viewing habits, betting patterns, and inferred interests of viewers.

(65) In various embodiments, sets of one or more adaptable content objects **176** may be selected (e.g., by the service provider system **102**) for particular time periods and may be transmitted to the subsystem **111** with an assignment (e.g., by way of tag data or other metadata) for the designated time period. Additionally or alternatively, in some embodiments, sets of one or more adaptable content objects **176** may be selected (e.g., by the service provider system **102**) for particular channels and/or television programs and may be transmitted to the subsystem **111** with an assignment (e.g., by way of tag data or other metadata) for the designated channels and/or television programs. The communication of the sets of one or more adaptable content objects **176** may be in response to the subsystem **111** pulling the sets of one or more adaptable content objects **176** from the service provider system **102**. For example, the subsystem **111** may pull adaptable content objects **176** based at least in part on detecting programming content **202** currently being viewed via a television receiver **110** or computing device **116**, detecting programming content **202** scheduled to be viewed or recorded, predicting programming content **202** of interest to a viewer based on detected viewing and/or betting patterns (e.g., patterns of interacting with content objects **176**, **177**), determining upcoming programming content **202** based on electronic programming guide information received, and/or the like.

(66) In a similar manner, sets of one or more content object objects **177** may be pulled from or pushed by one or more service provider systems **103**, in various embodiments using one or more of the various methods disclosed, to the subsystem **111** directly or indirectly (e.g., by way of the content provider system **102**, which may then transmit the content object objects **177** to the subsystem **111**) for particular time periods, with assignments for designated channels and/or television programs. For example, in conjunction with the selection of sets of one or more adaptable content objects **176**, sets of one or more content object objects **177** that match the one or more adaptable content objects **176** may be pulled from one or more service provider systems **103**. In various examples, the matching may be based at least in part on specifications of the event, a temporal progression in the event (e.g., the fourth quarter, the second round, etc.), a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), and/or the like.

(67) In disclosed embodiments, the content provider **102** and/or the subsystem **111** may selectively aggregate content. By way of example, FIG. 3 is a simplified illustration of a portion of the content composite generation/control system **200** with aggregation and transformation features, in accordance with disclosed embodiments of the present disclosure. In some embodiments, the subsystem **111** may correspond at least in part to the content provider **102** and may include one or more data management servers. The subsystem **111** may include one or more aggregation and/or transformation engines **231**, which may correspond to the content harvesting engine **236** in some embodiments. In various embodiments, the aggregation and/or transformation engine **231** may correspond to an integral engine or separate engines working in conjunction. The aggregation/transformation engines **231** may translate, transform, or otherwise adjust data collected. The aggregation and transformation engines **231** may provide a pipeline that processes data input from regulatory data sources, applies rules, transforms the data into jurisdiction-specific regulatory rules **218**, and uses the rules **218** to adaptively control content composite creation, the delivery of such content, and interactions with such content.

(68) In various embodiments, the harvesting engine **236** may include or otherwise operate in conjunction with the matching engine **238**, which may operate at partially as a consolidation engine. The matching engine **238** may process manifold data sets that may, for instance, come from different sources **112** or the same source **112**, for example, by way of one or more updates to data previously provided by a particular source **112**, and the matching engine **238** may consolidate the data sets to form a composite data set. The consolidation may include organizing, categorizing, qualifying, and/or comparing the sets of information; detecting, identifying, and/or handling errors/discrepancies; identifying redundancies; removing redundancies; and/or otherwise

processing the data sets. In some embodiments, regulatory objects are consolidated to form set of consolidated rules **218**. The objects may correspond to structured data, text, files, documents, and/or the like specifying conditions, criteria, and requirements of jurisdiction-specific regulations. In some embodiments, objects are consolidated and transformed into organized, indexed, categorized, and qualified rules, workflows, and/or decision trees. In some embodiments, the matching engine **238** may identify a subset of data, regulatory rules, and/or one or more data sources **112** (e.g., regulatory authority) that are more important than the rest and may process the subset first. In some embodiments, the matching engine **238** may follow an order of precedence in consolidating the data, rules, and/or data sources. In some embodiments, the consolidation may include removing and/or minimizing redundancy of information and requirements of rules to form a compact set of composite information, requirements, and/or restrictions for a particular location, a particular type of event, a particular type of betting, a particular type of bookmaker/sportsbook, a particular type of device, and/or the like. The matching engine **238** may operate to build one or more sets of data, content, rules, one or more indexes, one or more workflows, one or more decision trees, and/or one or more files particularized to one or more locations and based at least in part on selectively aggregated rules **218**. In some embodiments, the matching engine **238** may build multiple sets that relate to one or more rules, but are tailored for different geolocations, jurisdictions, types of events, types of betting, types of bookmakers/sportsbooks, and/or the like. (69) In some embodiments, the matching engine **238** may translate the data into understandable data, information, and/or content. The transformed data, information, and/or content may be directed to certain tables, indexes, and/or storages based on one or more particular rules, geolocations, jurisdictions, types of events, types of betting, types of bookmakers/sportsbooks, and/or the like. In some embodiments, the selective aggregation, consolidation, and/or feed actions may be performed on an as-needed basis. For example, the selective aggregation, consolidation, and/or feed actions may be triggered when a change to rules is detected consequent to periodic polling of data source systems **103** for updates to rules and/or comparing newly harvested information to previously harvested information. In some embodiments, the selective aggregation, consolidation, and/or feed actions may be performed on a periodic basis based on any suitable time period.

(70) The service provider systems **103** may include manifold content source systems **112**, including, for example, sources **112** of objects corresponding to federal information, state information, local information, and/or the like. The harvesting engine **236** may include logic for implementing content aggregation features in various embodiments. In some embodiments, the harvesting engine **236** may be configured to gather data about rules from one or more service provider systems **103** and/or other data source systems sourcing information (e.g., government systems) through one or more networks **120**. By way of example without limitation, the engine(s) with one or more the processors, may utilize one or more network interfaces to pull and/or push code from various entities. As disclosed herein, content may be actively gathered by accessing a repository that corresponds to such entities, and content could be gathered by “crawling” the various repositories in some embodiments. Updates for content source systems **112** may be periodically found. Additionally or alternatively, the content provider system **102** and/or the subsystem(s) **111** may wait for updates from one or a combination of the content source systems **112**. With some embodiments, any one or combination of the content source systems **112** may provide notifications to the content provider system **102** and/or the subsystem **112** of data to be transferred, such as updated information not previously pulled/pushed to the content provider system **102** and/or the subsystem **112**. Certain embodiments may also include data being pre-loaded and/or directly transferred to the content provider system **102** and/or the subsystem **112** (e.g., via a storage medium) in addition to or in lieu of transferring data via a network **120**. The harvesting engine **236** could handle processing, extracting, formatting, and/or storing in content storage **222** data including data for code portions. The harvested data may then be analyzed to

determine one or more attributes of the code portions.

(71) Various sets of rules **218** may provide for various types of restrictions and/or specifications on creating and/or provisioning content composites **180**. In addition to geolocation restrictions/specifications, the various types of restrictions and/or specifications may include time restrictions, such as limits on a time of day when content composites **180** may be presented, limits on time in advance particular event (e.g., days, hours, etc.) and/or portion thereof (e.g., round, quarter, period, etc.) ahead of which content composites **180** may be presented, and the like. Additionally or alternatively, the various types of restrictions and/or specifications may include restrictions on and/or specifications of types of events (e.g., football, soccer, martial arts, types of racing, etc.) for which content composites **180** may or may not be presented and the manner in which content composites **180** may be presented for the different types of events. In some instances, the number and/or frequency of composite **180** presentation may be limited on a per-event basis. Further, the type of betting (e.g., the actions subject to wager) may be restricted by the rules **218** in various ways, depending on the location. Thus, provisioning of content composites **180** may be further differentiated according to event type, with time, place, and/or manner restrictions/specifications contingent on event type. Restrictions on and/or specifications of the manner in which content composites **180** may be presented may include distinguishing types of devices (e.g., smart phone versus laptop computer, laptop computer versus television receiver, etc.) which will display the content composites **180**.

(72) To facilitate geo-discrimination to differentiate which sets of rules **218** apply to a given content provisioning instance with respect to an event, disclosed embodiments may provide for capturing and analyzing location data for the receiver **110** and/or device **116** to determine a current location of the receiver **110** and/or device **116** and which content objects **176**, **177** to select and present as a function of the current device **116** location, disclosed embodiments may provide for capturing and analyzing location data for the device **116** to determine a current location of the device **116**. Location data may be captured to facilitate geo-sensitive adaptive content composite generation/control adaptive content composite generation/control with respect to content **202** corresponding to a televised event as a function of a location detected for the receiver **110** and/or device **116** that receives the content and is to cause display of content composites **180** in conjunction with the content. In various embodiments, the matching engine **238** may include a location correlation engine that may correlate location data to a set of one or more zip codes (or other postal codes) and a corresponding rule set identifier for a set of one or more rules **218** mapped to the set of one or more zip codes (or other postal codes) via identifiers keyed with one or more tables and/or indexes.

(73) In various embodiments, location data may be determined by television receivers **110** and/or devices **116**, and such data may be sent to the system **102**. The television receivers **110** and/or devices **116** may, in some embodiments, have location detection capabilities based at least in part on location data provided by way of device GPS capabilities, Wi-Fi, cellular, other access points, subscriber/account information, and/or the like techniques for determining a current location of the respective receiver **110** and/or device **116**, and corresponding location data may be transmitted to the system **102**. In some embodiments, the system **102** may gather the location data. In some embodiments, where the location data does not explicitly indicate a geolocation, the system **102** may determine geo-locations by cross-referencing subscriber/account identifiers with stored geolocation data associated with subscribers/accounts.

(74) In some embodiments, the receiver **110** and/or device **116** may include at least one antenna for wireless data transfer to communicate through a cellular network, a wireless provider network, and/or a mobile operator network, such as GSM, for example without limitation, to send and receive Short Message Service (SMS) messages or Unstructured Supplementary Service Data (USSD) messages. The antenna may include a cellular antenna (e.g., for sending and receiving cellular voice and data communication, such as through a network such as a 3G, 4G, or 5G

network). In addition, the receiver **110** and/or device **116** may include one or more interfaces in addition to the antenna, e.g., a wireless interface coupled to an antenna. The receiver **110** and/or device **116** may include one or more communications interfaces that can provide a near field communication interface (e.g., contactless interface, Bluetooth, optical interface, etc.) and/or wireless communications interfaces capable of communicating through a cellular network, such as GSM, or through Wi-Fi, such as with a wireless local area network (WLAN). Accordingly, the receiver **110** and/or device **116** may include may be capable of transmitting and receiving information wirelessly through both short range, radio frequency (RF) and cellular and Wi-Fi connections.

(75) Additionally, in some embodiments, the receiver **110** and/or device **116** may be capable of communicating with a Global Positioning System (GPS) in order to determine to location of the respective receiver **110** and/or device **116**. The antenna may be a GPS receiver or otherwise include a GPS receiver. In various embodiments, communication with the receiver **110** and/or device **116** may be conducted with a single antenna configured for multiple purposes (e.g., cellular, transactions, GPS, etc.), or with further interfaces (e.g., three, four, or more separate interfaces). In some embodiments, an application installed on the receiver **110** and/or device **116** may cooperate with the system **102** to facilitate tracking of locations of the receiver **110** and/or device **116**. For example, the receiver **110** and/or device **116** may transmit location data to any suitable backend system component. The location data may be a combination of data based on one or a combination of GPS, Wi-Fi, cellular, device sensor(s) such as a barometric sensor or accelerometer, RFID device signals, and/or other techniques for determining a current location of the receiver **110** and/or device **116**.

(76) The receiver **110** and/or device **116** may access the one or more networks **120** through one or more wireless links to one or more access points. The access points may be of any suitable type or types. For example, an access point may be a cellular base station, an access point for wireless local area network (e.g., a Wi-Fi access point), an access point for wireless personal area network (e.g., a Bluetooth access point), etc. The access point may connect the receiver **110** and/or device **116** to the one or more networks **120**, which may include the Internet, an intranet, a local area network, a public switched telephone network (PSTN), private communication networks, etc. In some embodiments, access point(s) may be used in obtaining location data for the receiver **110** and/or device **116**.

(77) FIG. 3 is a simplified illustration of a composite build engine **240**, in accordance with disclosed embodiments of the present disclosure. In various embodiments, the composite build engine **240** may be included in the subsystem **111** or may be separate from the subsystem **111**. The composite build engine **240** may, in some embodiments, be included in the content provider system **102**. Having processed an adaptable content object **176**, the subsystem **111** may create one or more content composites **180** that may include the adaptable content object **176**.

(78) To create the content composites **180**, disclosed embodiments may configure the content object **176** with at least in part as a containerization object that containerizes at least part of the particularized content object **177** to facilitate various features disclosed herein. The composite build engine **240** may configure the content composites **180** to include a composite flag that may include one or more parameters and may indicate one or more composite specifications. For example, in various embodiments, the composite flag may include indicia of access and reference to one or more other composite specifications, access and reference to other metadata, and/or the like. Further, the composite build engine **240** may configure the composite **180** to include the composite specifications to facilitate performance of a set of one or more operations by the one or more endpoint media devices **116** or **110** with respect to the composite **180** consequent to the one or more endpoint devices **116** or **110** receiving the content composite **180**. In various embodiments, the composite specifications may include one or a combination of instructions, metadata, one or more URLs, instructions to configure an executable function in accordance with a set of

parameters, and/or the like to specify and facilitate performance of the set of one or more operations by an endpoint media device **116** or **110**. In some embodiments, the composite specifications may include at least part of the particularized content object **177**.

(79) The composite build engine **240** may identify one or more portions of adaptable content object **176** to be augmented based at least in part on content object **177**, which may, in various embodiments, be identified by image analysis and/or analysis of tag data that defines one or more areas within frames that correspond to certain portions represented within the frames for augmentation. As disclosed herein, such tag data could define the area of interest in any suitable way in various embodiments which could be by way of any one or combination of mattes, masks, pixel identification (which could, for example, include identification of pixel coordinates and ranges thereof to define areas of interest), pixel color component characteristics such as color component values, overlays, and/or the like, allowing for correlation to the area to be augmented in any suitable way. In some embodiments, a processor (such as a main processor, a core processor, digital signal processor, and/or like) may take a definition of the augmentation area with respect to one or more reference frames and may perform auto-correlation of related images in a video stream to identify/define the augmentation areas in other frames of the video sequence that represent the portion to be augmented. Image characteristics (e.g., color, brightness, etc.) of the area of interest with respect to the reference frame(s) could be measured, quantified, and/or otherwise identified, and matched with measured image characteristics of the other frames to define the area to be augmented in multiple frames in an image-changing sequence. Accordingly, certain embodiments may allow for handling the complexity of multiple on-screen options by distinguishing particular areas in dynamic, image-changing content.

(80) Accordingly, the content composite **180** may include at least part of the content object **177** and the particularized content object **177** at the time the content composite **180** is transmitted to one or more endpoint media devices **116**, with the particularized content object **177** separate from or grafted into the content object **176** such that the content object **176** is an adapted content object **176** adapted with the particularized content object **177**. In some embodiments, the content composite **180** may not include a particularized content object **177** at the time the content composite **180** is transmitted to one or more endpoint media devices **116** or **110**. In such instances, the particularized content object **177** may be fetched per the composite specifications from the system **102**, **200**, another data source **103**, or from storage of the endpoint media device **116** or **110**, and may be used by an endpoint media device **116** or **110** to adapt the content object **176**. The composite specifications may include instructions and build specifications according to which the endpoint media device **116** or **110** may merge the pulled/retrieved particularized content object **177** with the content object **176**.

(81) In some embodiments, the composite flag and/or composite specifications may prompt the endpoint media device **116** or **110** to execute the instructions to perform at least one operation of the set of one or more operations facilitated by the composite object **180**. In some embodiments, APIs may be used to instruct the endpoint media device **116** as to what to do with the composite flag and/or composite specifications. In some embodiments, the composite flag and/or composite specifications may allow for invoking, waking up, opening, and/or otherwise activating an application of the endpoint media device **116** responsive to the decryption of the composite flag and/or composite specifications, in some instances, when the application is offline and/or otherwise not online with respect to the system **102**, **200**, and/or another system **103**. The composite flag and/or composite specifications may prompt the endpoint media device **116** or **110** to causes display of an interface element that allows user selection to cause communication to the process-performing system **103** of an instruction to configure an executable function in accordance with a set of parameters. In some embodiments, the composite flag and/or composite specifications may include a report flag that triggers one or more return channel communications. The corresponding instructions may instruct the endpoint media device **116** or **110** to report to the system **102**, **200**,

and/or another system **103** with one or more return channel communications indicating detection of one or more operations executed consequent to the presentation of a composite **180** such as opening a mobile app the endpoint media device **116**, utilizing the composite **180** to place a bet, bets placed, metrics of the operations (e.g., time of execution); and/or the like. The return channel communications may contribute to the observation data **229** and feedback loop features disclosed further herein.

(82) Additionally, in various embodiments, with selection of a content composite **180** to select an executable function for a system **103**, the devices **110** and/or **116** may automatically record the event corresponding to the content composite **180**. This feature may to any of the composite **180** selections disclosed herein such that, where the selections instruct the system **103**, the parallel instructions are issued to the devices **110** and/or **116** to record the corresponding event. When the selections are made via the receiver **110**, the composite instructions may directly instruct the receiver **110** to record the event. However, when the selections are made via a device **116**, the instruction may be communicated from the device **116** to a receiver **110** that is associated with the account identifier. Such instruction may be made directly to the receiver **110** when it is determined that the device **116** and the receiver **110** are communicatively couplable, such as in the subsystem **300**. The communication of the instruction may be made directly via Bluetooth, Wi-Fi, and/or the like when such connections are available. However, when such connections are not available directly to the receiver **110**, the instruction may be communicated indirectly via return channel communications as disclosed herein. However, when it is determined that no such receiver **110** is associated with the account identifier, instruction may be communicated to the service provider system **102** via return channel communications, and the system **102** may record the events or, where such recording is already automatically provided by the system **102**, the system **102** may receive the instruction and later make the recordings accessible to the device **116**.

(83) Further, as disclosed further herein, the subsystem **111** may detect triggers corresponding to a viewer's previous selections of composites **180**, or the triggers may correspond to shifting odds due to developments occurring within the event (e.g., underdog is actually close or ahead, an upset is imminent, etc.), detecting a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), and/or the like. The subsystem **111** may compare such developments and state changes to the viewer's previous selections of composites **180**. This may correspond to comparing the evolution of the games and odds and bets already placed by the viewer. The subsystem **111** may identity where the bets have become increasingly unlikely to result in a win, or where the bets are close or highly likely to result in a win. Responsive to detecting one or more of such situations, the subsystem **111** may create additional composites **180**. Such composites **180** may indicate the detection of such situations, may notify the viewer of the watch ability of the event, that the viewer may want to tune in or pay attention to the ongoing event, and/or may identify additional possible executable functions that could be selected in view of the developments detected for the events. Still further, the subsystem **111** may correlate such developments in the events to timing specifications for the recordings of the events may highlight, mark, and/or otherwise record presentation times corresponding to the developments within the recordings of the events. In various embodiments, the subsystem **111** may then create selectable options for skipping to the corresponding segments within the recordings, and/or may create cuts of the recordings corresponding to the segments for highlights that can be made accessible and viewable to the viewer. Listings of the recorded content for the events and/or highlights may be made available with any suitable graphical indicia and descriptive content be additional composites **180** and/or the augmentation interface disclosed herein.

(84) To facilitate the content composite **180**, the composite build engine **240** may include a metadata handler **208** that may generate metadata (e.g., one or more tags) corresponding to identifiers, attributes, characteristics, and/or categories of programming content **202**, adaptable content objects **176**, and/or particularized content objects **177**. In various embodiments, the

metadata **210** may be inserted into the output programming content **202**, output adaptable content objects **176**, and/or output particularized content objects **177**. In some embodiments, the one or more tags **210** may not be inserted into the programming content **202**, adaptable content objects **176**, and/or particularized content objects **177** but may be sent with the output programming content **202**, output adaptable content objects **176**, and/or output particularized content objects **177**. composite build engine **240** may assign packet identifiers to identify data of the content that is to be transmitted as part of a data stream to a receiver **110** and/or device **116** and that is to be associated with one or more tags. Accordingly, the content splicing subsystem **111** may output one or a combination of metadata-augmented programming content **202-1**, metadata-augmented content objects **176-1**, and/or metadata-augmented content objects **177-1**. In some embodiments, one or a combination of metadata-augmented programming content **202-1**, metadata-augmented content objects **176-1**, and/or metadata-augmented content objects **177-1** may be stored at least temporarily in one or more repositories **222**. In some embodiments, tag data may be stored at least temporarily in one or more repositories **222**. The content matching engine **238** may identify a televised event in the programming content **202** and may identify one or more corresponding identifiers, attributes, characteristics, and/or categories of programming content **202**, adaptable content objects **176**, and/or particularized content objects **177** of one or more adaptable content objects **176** and/or one or more particularized content objects **177**. Based at least in part on such identification, the composite build engine **240** may create metadata, which, in some embodiments, may correspond to tag data.

(85) Tag data may include an indication of a period of time (or other measure of time, e.g., a number of frames), a start frame, an end frame, and/or the like. Tag data may include or otherwise be associated with a tag identifier and may include event, attribute, characteristic, and/or category identifiers. For example, the metadata for the televised event may identify the particular event. The metadata may further identify one or more attributes of the particular event (e.g., any suitable identifier for the participating entities, the location of an event, and/or the like). In some embodiments, at least a portion of the metadata augmentation may be performed at the content provider system **102** such that one or more tagged composite components may be provided to an endpoint media device **116**. Subsequently, the endpoint media device **116** may identify composite components, for example, by processing the metadata.

(86) The metadata for adaptable content objects **176** may, for example, identify the adaptable content objects **176** as being adaptable with any suitable identifier, such as a flag, field value, etc. Additionally or alternatively, the metadata for the adaptable content objects **176** may identify that the adaptable content objects **176** are designated for a certain event or category of events with any suitable identifier. The metadata for the adaptable content objects **176** may further identify one or more attributes of the particular event (e.g., any suitable identifier for associated entities, location, a temporal attribute such as a time of an event, and/or the like). Additionally or alternatively, the metadata for the adaptable content objects **176** may identify transition points, hooks, frames, windows, other portions designated for overlays, and/or the like for merging with content objects **177** such that content from the content objects **177** is merged at the transition points, hooks, frames, windows, other portions designated for overlays, and/or the like.

(87) In some embodiments, metadata-augmented adaptable content objects **176** may be provided by the system **102** to the receivers **110** and/or devices **116**, after which the receivers **110** and/or devices **116**, each having at least a portion of the content composite subsystems **111**, may process and use the metadata to facilitate matching adaptable content objects **176** with corresponding televised events of the programming content **202**. Likewise, the receivers **110** and/or devices **116** may process and use the metadata to facilitate matching adaptable content objects **176** with corresponding content objects **177** and then creating content composites **180** therefrom. Thus, the metadata may facilitate the receivers **110** and/or devices **116** appropriately providing corresponding content composites **180** for display with appropriate placement with respect to televised events at

commercial breaks and/or during event presentation of the televised events.

(88) In a similar manner, metadata-augmented content objects **177** may be provided by the service provider system **102** to the receivers **110** and/or devices **116**. The metadata for adaptable content objects content object **177** may, for example, identify an identifier of the particular event (e.g., any suitable identifier for a game, match, competition, and/or the like). The metadata for the content objects **177** may further identify fields and content for one or more attributes of the particular event, such as any suitable identifier for the competitors, the location of the event, a temporal attribute such as a time of the event or a progression of the event, performance metrics of one or more competitors in the event (e.g., possession time, attempts, hits, strikes, takedowns, interceptions, completions, baskets, assists, fouls, etc.), a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), odds information with respect to a particular sporting event and a particular outcome of the sporting event and/or of certain potential results/actions that could occur within the event, URLs and hyperlinks to betting platforms/websites of systems **103** and/or sites for further information, and/or the like. In some embodiments, at least a portion of the metadata augmentation may be performed at the service provider system **102** and/or the service provider system **103** such that tagged content objects **177** are provided to the receivers **110** and/or devices **116** from the systems **102** and/or **103**.

Subsequently, the receivers **110** and/or devices **116** may process and use the metadata to facilitate matching adaptable content objects **176** with corresponding content objects **177** and then creating content composites **180** therefrom. Thus, the metadata may facilitate the receivers **110** and/or devices **116** matching adaptable content objects **176** with corresponding content objects **177** and then creating content composites **180**. Alternatively, the receivers **110** and/or devices **116**, having at least a portion of the content splicing subsystem **111**, may process the content objects **177** in the form in which they are received (e.g., directly from a service provider **103**) and, based on such processing, may match the content objects **177** to a particular event and/or may identify other attributes of the content objects **177** without the content objects **177** being received as augmented with metadata. In any case, in some embodiments, the receivers **110** and/or devices **116**, each having at least a portion of the subsystems **111**, may create the content composites **180**. Yet, as another alternative, the service provider **102**, having at least a portion of the subsystem **111**, may create the content composites **180** and transmit the content composites **180** to the receivers **110** and/or devices **116**.

(89) The learning engine **239** that may be an analysis engine that employs machine learning. The learning engine **239** may further employ deep learning. Accordingly, the learning engine **239** may facilitate machine learning or, more specifically, deep learning, to facilitate creation, development, and/or use of viewer pattern data **216**. As disclosed herein, the subsystem **111** may determine an event that the viewer actually is viewing, is about to view (e.g., the televised event is scheduled to play on the channel that the viewer is currently viewing), or is likely to view as determined with the learning engine **239**. The subsystem **111** may push information indicating the event to one or more service provider systems **102** and/or **103**. In some embodiments, the service provider system **102** may select one or more adaptable content objects **176** matching the televised event for transfer to the subsystem **111** which, as disclosed herein, may be a part of the content provider system **201** and/or may be part of the receiver **110** and/or devices **116**. The subsystem **111** may select from the one or more adaptable content objects **176** as matching particular segments of the event and, utilizing a content composite splicing engine **242** in some embodiments, may output one or more corresponding content composites **180** for display after the particular segments and/or simultaneously with the particular segments.

(90) In various embodiments, one or more of the service provider systems **102**, **103** may select one or more particularized content objects **177** matching the event for transfer to the subsystem **111**. In some embodiments, one or more of the service provider systems **102**, **103** may select a set of one or more particularized content objects **177** for transfer (e.g., based on recency of information

updates corresponding to the content objects **177**) for transfer to the subsystem **111**, and the subsystem **111** may determine which content objects **177** from the set that match the event. As disclosed above, the content composite subsystem **111** may include a matching engine **238** that may include logic to implement and/or otherwise facilitate any taxonomy, classification, categorization, correlation, mapping, qualification, scoring, organization, and/or the like features disclosed herein. (91) FIG. **4** illustrates certain aspects of the AI-based subsystem data flow **400**, in accordance with various embodiments of the present disclosure. The content processing subsystem **111** may be configured to gather observation data **229**, which may be specific to one or more particular identified users and/or may be generally related to particular receivers/devices **110**, **116**. The observation data **229** may be gathered from one or more receivers **110** and/or devices **116**, aggregated, consolidated, and transformed into viewer pattern profiles that include personalized pattern data **216**.

(92) In embodiments where the learning engine **239** is included in a receiver/device **110**, **116**, the receiver/device **110**, **116** may be a self-observer that may additionally gather additional observation data **229**. In various embodiments, the data from the one or more receivers/devices **110**, **116** may be retrieved and/or received by the content processing subsystem **111** via one or more data acquisition interfaces, which may include interfaces of the content processing subsystem **111**, the one or more receivers/devices **110**, **116**, and/or the like—through network(s) **120** in various embodiments, through any suitable means for direct communication, and/or through any other suitable means of transferring data. According to various embodiments where the subsystem **111** is included in a service provider system **102**, observation data **229** may be actively gathered and/or pulled from the one or more receivers/devices **110**, **116**.

(93) As disclosed herein, in various embodiments, the one or more data acquisition interfaces may include one or more APIs that define protocols and routines for interfacing with the one or more receivers/devices **110**, **116** and which may specify API calls to/from one or more receivers/devices **110**, **116**. In various embodiments, the APIs may include a plug-in to integrate with an application of one or more receivers/devices **110**, **116**. The API translation profiles may translate the protocols and routines of the data source component and/or system to integrate at least temporarily with the system and allow one-way communication to the system **102** and/or two-way communication with system **102** in various embodiments by way of API calls.

(94) Various embodiments of the subsystem **111** may aggregate observation data **229** to derive device identification data **404**, device operations **406**, temporal data **408**, and/or contextual data **410**. The device identification data **404** may include any suitable data for identifying and tracking particular receivers **110** and devices **116**; associated accounts, subscribers, and viewers; and/or the like disclosed herein. The device operations data **406** may include any suitable data for identifying and tracking device operations and interactions as those disclosed herein. The contextual data **410** may include metrics and patterns of viewer interactions/responses pursuant to provisioning of content composites **180** and biasing **181**. For example, viewer responses to content composites **180** provisioning may include indications of whether the viewer selected a user-selectable options provided with composites **180**, the types of such selections, and/or types of consequent interactions with service provider systems **103**. For example, the metrics and patterns may take into account whether the viewer opted out of content composites **180**, whether the viewer selected links of composites **180** to interact with the platforms and sites of one or more service provider systems **103**, whether the viewer selected options to redirect content composites **180** and/or notifications from service provider systems **103** to a secondary device **116**, which service provider systems **103** the viewer selected, whether the viewer placed bets and the types of the viewer's bets and other interactions with service provider systems **103**, which types of events and outcomes the viewer placed bets on, amounts wagered, and/or the like. The temporal data **408** may include metrics such as any information to facilitate detection, recognition, and differentiation of one or combination of temporal factors correlated or which the content processing subsystem **111** correlates to other

observation data **229** such as device identification data **404**, contextual data **410**, and/or the like. For example, the temporal data **408** may include time of day information, time of week information, time of year information, holiday information, etc. when the viewer made selections and bets; when during the progression of the events, sports seasons, postseasons, championships, and/or similar stages that the viewer made selections and placed bets; and/or the like.

(95) As disclosed herein, the subsystem **111** may be configured to receive, pull, process, buffer, organize, rank, and/or store data source input **212**, which may be included in the observation data **229**. This may include collecting data source input **212** from a plurality of devices **110** and/or **116** and/or from one or more data source systems **112** via the one or more data acquisition interfaces. As disclosed herein, data source input **212** may include, but are not limited to, updates (real-time and/or otherwise) and/or continuous data streams received from one or more data sources **112**, which may include real-time events related to bookmakers, bookies, sportsbooks, oddsmakers, sports event and/or other competition information, gambling/betting, Twitter® feeds, Instagram® posts, Facebook® updates, and/or the like. Observation data **229** may be actively gathered and/or pulled from one or more data sources, for example, by accessing a repository and/or by “crawling” various repositories. The observation data **229** may include user indications of preference of entities and subject matter, such as positive ratings, indication of liking an entity, sharing entity-specific and/or subject-matter-specific information with others that the user has made via webpages and/or social media. This information may be compiled in real-time or near real-time and may be used to trigger composite **180** generation and communication. The subsystem **111** may determine based at least in part on the observation data collected from one or more of the data source systems (e.g., a social media system) strong preferences and/or aversions to particular sports teams/competitors. For example, an aversion may be inferred from negative indicia (e.g., dislikes of the particular team on a social media profile of the contact) and/or positive indicia (e.g., likes of another team that is a determined rival of the particular team), and, in some instances) recent games (i.e., wins/losses) of the two teams.

(96) The contextual data **410** may include viewership data. In some embodiments, the service provider system **102** may include a viewership data engine that is configured to facilitate identification, aggregation, consolidation, and qualification of viewership data pertinent to a plurality of viewers of devices **116** and **110** in various geolocations. The harvesting engine **236** may be configured with logic to process, analyze, retrieve, pull, cause communication of, derive, compile, aggregate, categorize, characterize, rank, handle, store, report, and/or present any suitable information/content pertaining to viewership—e.g., implicit content ratings derived from histories and patterns of viewing and recording, and explicit content ratings input by viewers. The harvesting engine **236** may be configured to cause viewership information to be transmitted from devices **116** and **110** to the service provider system **102** for identification, aggregation, consolidation, and qualification of viewership data pertinent to a plurality of viewers of devices **116** and **110** in various geolocations. In some embodiments, the viewership data engine may correspond to the harvesting engine **236**. In some embodiments, the viewership data and the determination of viewership characteristics may be based at least in part on real-time or near real-time back-channel information from viewing devices **116** and **110** indicating the channels and/or events being viewed and/or recorded, viewer profiles, viewer selections, viewer geolocations, viewer ratings of events, viewing history, explicit user preferences, user characteristics, and/or the like. Aggregated viewership data may be analyzed to identify a set of one or more viewership characteristics with respect to events. Based at least in part on the viewership data, content matching engine **238** and/or the learning engine **239** may differentiate and qualify one or a combination of events being viewed and/or recorded, viewer profiles, viewer selections, viewer geolocations, viewer ratings of events, viewing history, explicit user preferences, viewer characteristics (e.g., demographics), and/or the like. Some embodiments may employ a decision tree, checklist, workflow, and/or the like to capture various aspects of viewership data and assess those aspects to infer event qualification.

(97) Some embodiments may qualify an event according to a graduated viewership scale. Any suitable viewership scale may be used in various embodiments. In some embodiments, a viewership scale could entail a categorization scheme, with categories such as high viewership, medium viewership, and low viewership, or any suitable categories. In some embodiments, a viewership scale could entail an event scoring system. The event scoring system could be correlated to the category scheme in some embodiments, such that certain scores correspond to certain categories. Some embodiments may score an event with a numerical expression, for example, a viewership score. A viewership score may be an assessment of an event's current, past, and/or predicted viewership. Accordingly, a viewership score may indicate which events have had, currently have, and/or are forecasted to have greater viewership than other events. In addition to or in alternative to employing real-time viewership qualification, certain embodiments may predict viewership of events based at least in part on historical viewership data of specific events and/or of one or more categories to which events are mapped. Such categories may include one or a combination of geolocation, event type, executable function type (e.g., bet type), parameters for the executable function (e.g., bet parameters, odds, etc.), demographics, social trending, particular competitors (e.g., rivals), tournament/playoffs versus regular season, and/or the like which may be correlated to viewership scores to refine the viewership qualifications for correlation to particular viewers in order to trigger composite **180** generation and presentation for the particular viewer as a function of one or more of these categories. Accordingly, certain embodiments may accord viewership scores based at least in part on such corresponding historical viewership data, which may include previous viewership score, and some embodiments may employ geo-discrimination to differentiate which events are likely to have greater viewership in certain geo-locations as compared to other events. For example, a viewership score for a football game may be assigned a greater number of points when the service area includes a hometown of one of the football teams playing in the game. Hence, the viewership score for the game may be higher when there is a correlation between the game a particular geolocation than when there is not such a correlation. Likewise, the system **102** may recognize situations where a significant viewership exists in geolocations that not hometowns of the football teams playing in the game. For example, a geo-tailored viewership score for the football game may be assigned a greater number of points when the service area includes a significant number of fans even though there is no explicit connection to the football game. Hence, the viewership score for the game may be higher when the system **102** accounts for a significant pocket of fans of the Kansas team that are located in Colorado, even though the team from Colorado is not playing the game. Accordingly, certain embodiments may more accurately differentiate which events are likely to have greater viewership in various geo-locations.

(98) The learning engine **239** may map one or a combination of various extra-composite metrics of the observation data **229** to the metrics of the particular composites **180** provided to a particular viewer. Based at least in part on taking into account such observation data **229** as part of a feedback loop, the learning engine **239** may employ an ongoing learning mode to develop personalized pattern data **216** for particular viewers or content receivers/devices generally, and to confirm, correct, and/or refine determinations made for personalized pattern data **216** for particular viewers or content receivers/devices generally. The content processing subsystem **111** may be configured to employ machine learning to process the observation data **229** and the content objects **180** and to derive and develop the personalized pattern data **216**. The content processing subsystem **111** may be configured to employ deep learning to process the observation data **229** and the content objects **180** and to derive and develop the personalized pattern data **216**. The learning engine **239** may be configured to perform any one or combination of features directed to matching or otherwise correlating the observation data **229**—such as the device identification data **404**, the device operation identification data **406**, the temporal data **408**, the contextual data **410**, descriptive information of the content objects **180**, and/or the like—with intra-content metrics of the content

objects **180**. The learning engine **239** may include logic to implement and/or otherwise facilitate any taxonomy, classification, categorization, correlation, mapping, qualification, scoring, organization, and/or the like features disclosed herein. In some embodiments, the learning engine **239** may include the matching engine **238**.

(99) The learning engine **239** may include a reasoning module to make logical inferences from a set of the detected and differentiated data to infer one or more patterns of activity for particular viewers and/or receivers/devices generally. A pattern-based reasoner could be employed to use various statistical techniques in analyzing the data in order to infer personalized pattern data **216** from the observation data **229**. A transitive reasoner may be employed to infer relationships from a set of relationships related to the observation data **229**. In various embodiments, the system automatically establishes and develops the personalized pattern data **216**. However, the personalized pattern data **216** may be set up and/or tailored by users. With various embodiments, the personalized pattern data **216** may be automatically established and developed by the system.

(100) The feedback could be used for training the system to heuristically adapt conclusions, profiles, correlations, attributes, triggers, patterns, and/or the like to learn particular viewers and adapt content composite **180** provisioning to particular viewers, which may include requesting, searching for, and/or selecting particular types of adaptable content objects **176** and/or content objects **177** (e.g., which may be based at least in part on the metadata features disclosed herein) for content composite **180** creation. For example, the learning engine **239** may learn that a particular viewer tends to interact with content composites **180** that are directed to only certain types of events. Such event type differentiation may be on the macro level, such as recognizing that a viewer tends to interact more with composites **180** directed to certain types of sports and not other types of sports. Accordingly, the subsystem **111** may bias content composites **180** provisioning toward the types of sports that tend to cause viewer interaction and decrease composite **180** provisioning frequency or cease provisioning for other types.

(101) Further, the learning engine **239** may learn that a particular viewer tends to interact with content composites **180** that are directed to only types of events within a particular category (e.g., more high-profile events such as post-season events and/or championship events as opposed to regular season and/or non-championship events). Accordingly, the subsystem **111** may likewise bias content composites **180** provisioning toward such types of events and decrease or cease provisioning with respect to other types. Further, viewer interaction differentiation may be on the micro level, such as recognizing that a viewer tends to interact more with composites **180** directed to certain types of outcomes and state changes with respect to particular events. For example, the learning engine **239** may detect a viewer pattern of interacting only with composites **180** directed to the potential final outcomes/results of an event (e.g., final score, winner, etc.) or may detect a viewer pattern of interacting with more micro-level potential outcomes that can occur within an event (e.g., scoring on particular drives, takedowns, fumbles, per-competitor performance, etc.). Accordingly, the subsystem **111** may likewise bias content composites **180** provisioning toward such types of outcomes and decrease or cease provisioning with respect to other types. Thus, the subsystem **111** may adapt composite **180** provisioning to maximize viewer engagement, and, when the subsystem **111** detects state changes in televised events that are mapped to viewer patterns of composite **180** interaction corresponding to such state changes and events, the subsystem **111** may initiate the polling of one or more corresponding adaptable content objects **176**, the polling of one or more corresponding content objects **177**, and/or the creation of one or more corresponding composites **180** as a function of the detected state change and the detected viewer pattern in order to provide tailored composites **180** to a viewer in response to the detected state change.

(102) Further, in situations where a pattern of more micro-level interactions detected for particular viewer, the subsystem **111** biasing **181** of composites **180** may include serial provisioning of composites **180** in a serial drill-down manner such that the first composites **180** provisioned may be directed to a more macro-level outcome and one or more composites **180** subsequently provisioned

may be directed to more micro-level outcomes in accordance with the detected pattern. Thus, disclosed embodiments may provide for serial matching of composites **180** with respect to one another in order to provision the composites **180** with a trend that matches the detected pattern. (103) Accordingly, as part of such learning and adaptation processes, the subsystem **111** may bias **181** composite **180** provisioning (which may correspond to bet recommendations) toward a particular viewer based at least in part on what the subsystem **111** has learned about a number of factors. Composite **180** creation and provisioning may be a function of pattern data **216** specific to one or a combination of location, geo-specific viewership, learning about the viewer and correlated viewership metrics, devices used, personal viewership, demographic viewership, social viewership, learned betting behavior, types of bets, live viewership trends (who's setting recordings for events and/or tuning in), event types/categories, specific competitors, rivalries, time spent watching particular games, regular season versus post-season, upcoming events, real-time state changes based on what's actually happening in events, parameters such as odds information, other observations data **229**, other data source input **212**, and/or the like criteria disclosed herein. The learning engine **239** and/or the matching engine **238** may perform correlation based at least in part on correlation rules that govern correlation of the personalized pattern data **216** to content objects **177** and corresponding sources of the content objects **177** based at least in part on metrics and availabilities of the content objects **177** from the particular source systems **103**. In various embodiments, the correlation may be based at least in part on the profiles of the service provider systems **103**. By way of example, the correlation rules **218** may include correlation criteria that could include respective weightings assigned to the particular criteria. Hence, each type of the above criteria could be assigned a weight according to its significance. Specifications of the criteria and weightings could be implemented in any suitable manner, including lists, tables, matrices, and/or the like, and could be organized in a rank order and/or any hierarchical structure according to weight. Some embodiments may have specifications of the criteria and weightings organized according to decision tree, with contingencies so that only certain combinations of criteria may be considered. In some embodiments, the learning engine **239** and/or the matching engine **238** may employ a scoring system to quantify correlations with a numerical expression, for example, a match/watchability score, with higher scores being assigned to higher correlations. Higher scores may be assigned for greater extents of matching. Accordingly, the learning engine **239** and/or the matching engine **238** may learn a viewer's top-ranked interests in types of events, participating entities, geolocations, types of bets, odds, and/or the like observation data **229**.

(104) In accordance with the pattern data **216**, the subsystem **111** may detect a trigger for composite **180** creation that corresponds to a need for presentation of one or more composites **180** in view of an upcoming event, a continuation of an ongoing event, and/or during the presentation of content corresponding to the event. Detecting a trigger may include determining timing specifications of the event that matches the viewer pattern data **216**, odds information that matches the viewer pattern data **216**, a temporal progression in the event (e.g., the fourth quarter, the second round, etc.) and/or shifting odds due to developments occurring within the event (e.g., underdog is actually close or ahead, an upset is imminent, etc.), detecting a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), and/or the like. As one example case out of many possibilities, say a state change in an event occurs (e.g., a score change, one team or competitor leading or falling behind, a takedown, a foul, etc.) and/or temporal progression benchmark (e.g., the fourth quarter, the second round, etc.) is reached. The subsystem **111** may detect the state change and, in response, initiate creation of composites **180** for presentation at an upcoming break or during the event. The composite **180** may be dynamically inserted in the content stream within a short time (e.g., substantially, seconds, within a minute, with environments, etc.) after the state change. As disclosed herein, in various embodiments, the subsystem **111** may detect the state change and other triggers by way of analyzing and consolidating data source input **212** (e.g., data feeds and/or event updates) received from various

data sources **112**, particularized content objects **177** from systems **103**, and/or analysis of content **202** by keyword recognition of a dialogue from an announcer (e.g., detecting words such as touchdown, goal, takedown, foul, minutes on the clock, etc.), sudden changes in crowd noise, and/or image recognition (e.g., detecting graphics displayed with a televised event such as a scoreboard, streaming tickers or overlays typically positioned and/or scrolling across a portion of the display area, etc.).

(105) When the subsystem **111** detects a trigger, the subsystem **111** may receive, pull, and/or select one or more content objects **177** from a process-performing system **103**, and may receive, pull, and/or select from one or more adaptable content objects **176** provided by the system **102** as matching particular segments of the event and the one or more content objects **177** to generate and output for display, utilizing the content composite splicing engine **242**, one or more composites **180** to display as a commercial during a programming break after a particular segment or as an intra-program overlay, frame, window, pop-up, and/or the like presented concurrently with the event.

(106) FIG. 5 is a simplified illustration of a content composite interaction subsystem **500**, in accordance with certain embodiments of the present disclosure. The interaction subsystem **500** may include the television receiver **110-1**. The interaction subsystem **500** may include a display device **160-1** communicatively coupled with the television receiver **110-1**. The television receiver **110-1** may be communicatively coupled with a media service back-end **502**, which may correspond to certain upstream elements of FIG. 1 and may include the network **120-1**. The interaction subsystem **500** may include any one or combination of computing devices **116a-d**. Depicted are two examples of a computing device **116c** and a computing device **116d**. Though both examples are depicted, a user may only use one computing device **116** in certain use cases. A number of other examples are possible, but not shown. In some embodiments, the display **160-1** and/or the television receiver **110-1** may be controlled by the user using the computing device **116** to send wireless signals **576** to communicate with the television receiver device **110-1** and/or the display **160-1**. The computing device **116** may receive wireless signals **577** from the television receiver device **110-1** to effectuate bi-directional communication. The computing device **116** may further receive and send wireless signals **586**, **587** from the network **120** through various means such as a Wi-Fi router, modem, cellular access points, and/or the like.

(107) For example, a content object **177** may include text, one or more images, links, URLs, buttons, other user interface elements, and/or the like which the content splicing engine **242** may aggregate, process, format, crop, rescale, and/or otherwise prepare and include in composites **180** for insertion into the content stream for output with the programming content **202** and/or during breaks of the programming content **202**. By way of example, a content composite **180** may include a combination of graphics, video, audio, and/or one or more links along with the message such as: “The Buffs are up 38-36 at halftime—check out the latest odds,” “KU is up 42-40, place a bet on the second half of the game,” or “Think Denver can come back? The current odds are 7:1.” Thus, the content composite splicing engine **242** may identify content portions for augmentation by processing the content object **177**, reading the object **177** or certain portions thereof, and determine portions for augmentation in video segments. In some embodiments, portions of images and/or frames of the adaptable content object **176** may be overwritten with captured content from the content object **177**.

(108) Referring again more particularly to FIG. 2, the matching engine **238** may be configured to match adaptable content objects **176** to objects **177** and segments of programming content **202** based at least in part on metadata at a service provider system **102** side or at a television receiver **110** and/or device **116**, in accordance with various embodiments. For example, metadata may be extracted when or before a given segment of programming content **202** is to be output for display and before a transition point. In some embodiments, the matching engine **238** may read the metadata and perform a search of the repositories **222** for one or more adaptable content objects **176** that have metadata matching the extracted metadata with respect to one or more of event

identification, event category identification, and/or temporal identification, with the highest preference given to the adaptable content object **176** that has metadata most closely matching the metadata of the previous segment. Alternatively, the matching engine **238** may read the metadata mapped to the segment and pull one or more adaptable content objects **176** from the service provider system **102**. In so doing, the subsystem **111** may transmit at least a portion of the metadata of the objects **177** and/or programming content **202** to the service provider system **102** in order to facilitate matching the extracted metadata with one or more adaptable content objects **176** with respect to one or more of event identification, event category identification, and/or temporal identification. Consequently, the service provider system **102** may transmit one or more matching adaptable content objects **176** to the subsystem **111**, which may be integrated with a receiver **110** and/or device **116**. Some embodiments may include the subsystem **111** configured to perform a search of the repositories **222** for one or more adaptable content objects **176** that have metadata matching the extracted metadata in addition to pulling one or more adaptable content objects **176** from the service provider system **102**. For example, the subsystem **111** may first perform a search of the repositories **222** for any matching adaptable content objects **176** and then only pull one or more adaptable content objects **176** from the service provider system **102** when no adaptable content objects **176** are found in the search of the repositories **222** that match the extracted metadata with a sufficient match score that indicates a level of correlation satisfying a correlation threshold.

(109) Additionally or alternatively, the matching engine **238** may pull one or more content objects **177** from the service provider system **102** and/or one or more service provider systems **103** based at least in part on particulars detected with the trigger. In so doing, the subsystem **111** may transmit at least a portion of metadata of the trigger and/or the programming content **202** to the service provider system **102** and/or one or more service provider systems **103** in order to facilitate matching the extracted metadata with one or more content objects **177** with respect to one or more of event identification, event category identification, and/or temporal identification. Consequently, the service provider system **102** and/or one or more service provider systems **103** may transmit one or more matching content objects **177** to the subsystem **111**. Additionally or alternatively, in some embodiments, the subsystem **111** first obtain one or more matching adaptable content objects **176**, then read metadata from the one or more matching adaptable content objects **176**, and transmit at least a portion of the metadata to the service provider system **102** and/or one or more service provider systems **103** in order to facilitate matching the metadata with one or more content objects **177**.

(110) In determining whether to initiate and/or the restrictions governing the creation and/or provisioning of content composites **180**, the subsystem **111** may detect a location corresponding to the computing device **116** and the receiver **111** and may determine from rules **218** whether the provisioning of content composites **180** of certain type are prohibited for the location. In the case where the subsystem **111** determines that there is no prohibition for the location, the subsystem **111** may determine a set of the rules **218** that govern timing restrictions and specifications, event type restrictions and specifications, place and manner restrictions and specifications, and types of adaptations of the adaptable content objects **176** with the particularized content objects **177** to create the composites **180**. Various sets of rules **218** may provide for various types of adaptations of the adaptable content objects **176** with the particularized content objects **177**, and the subsystem **111** may determine which set of rules **218** apply to a given receiver **110** and/or device **116** as a function of the location of the receiver **110** and/or device **116**.

(111) The place and manner restrictions and specifications of the geo-specific rules **218** may govern how composites are provisioned with respect to programming content **202** (e.g., as a commercial, as a real-time pop-up, as a real-time overlay, as an inset frame, and/or like), which may be a function of the type of event and/or the type of end-user device. For example, a set of rules **218** may specify that composites **180** may only be provided during commercial breaks of

televised event. Another set of rules **218** may specify that composites **180** may be provided as overlays, frames, and/or pop-ups during the televised event. In such cases, the rules **218** may require the user opt in and request such overlays, frames, and/or pop-ups during presentation of the televised event. Accordingly, one or more user-selectable options may be presented to the user via the receiver **110** and/or device **116** to allow request overlays, frames, and/or pop-ups during presentation of the televised event. Such user-selectable options may be provided with composites **180** that are presented and during commercial breaks. Thus, contingent upon user selection of the options, presentation of composites **180** may transition to overlays, frames, and/or pop-ups during presentation of the televised event. Likewise, one or more user-selectable options may be presented to the user via the receiver **110** and/or device **116** to prohibit content composite **180** provisioning. Upon user selection of such prohibition, the subsystem **111** may present alternative content objects in lieu of content composites **180** during commercial breaks.

(112) In like manner, one or more user-selectable options may be presented to the user via the receiver **110** and/or device **116** to allow content composite **180** provisioning to a secondary device **116** concurrently with the presentation of the televised event. Such provisioning to a secondary device **116** may be provided by way of one or combination of application installed on the secondary device **116**, communications from the receiver **110**, communications from the service provider system **102**, a near field communication interface (e.g., contactless interface, Bluetooth, optical interface, etc.), wireless communications interfaces capable of communicating through a cellular data network, or through Wi-Fi, such as with a wireless local area network (WLAN), and/or the network **120**. By way of example, a composite **180** may be presented via a television receiver **110** on a display **160** with one or more user-selectable options that allow redirection of composites **180** to a secondary device **116** consequent to user selection. The redirection of composites **180** to the secondary device **116** may include options to cast the televised event from the receiver **110** to the secondary device **116** and/or the composites **180**. To facilitate such a mode of operation, various embodiments may include the receiver **110** and/or the device **116** incorporating at least portions of the subsystem **111** provide various features.

(113) According to one option, the secondary device **116** (e.g., device **116c** or **116d** as illustrated in FIG. 5) may receive the same content, including composites **180** as commercial segments and/or overlays, being displayed on the display device **160** with simulcasting to the secondary device **116** so that the secondary device **116** need only display the augmented content. According to another option, the television receiver **110** may provide the programming content to the display device **160**, and the secondary device **116** may receive the programming content and splice composites **180** into the content displayed with the device **116**. In various embodiments, the device **116** may receive the composites **180** for composite generation/control from the receiver **110**, may receive the composites **180** for composite generation/control from the service provider system **102**, and/or may receive adaptable content objects **176** and content objects **177** from the receiver **110** and/or the system **102** in order that the device **116** may create and provision composites **180** therefrom. In some modes of operation, the television receiver **110** may present alternative content objects with the display device **160** in lieu of content composites **180**, while the content composites may be shunted to the secondary device **116**. Thus, the secondary device **116** may receive composites **180** that would otherwise be displayed on the display device **160**. In some embodiments and options, the receiver **110** may not cast to the televised event, but the device **116** may present composites **180** without the televised event. For example, according to some options, an application for the device **116** may be downloaded, installed, and initiated to facilitate content provisioning on the device **116** and interaction with one or a combination of the receiver **110**, system **102**, and/or one or more systems **103**. Accordingly, various embodiments may provide various user-selectable options for transitioning from just viewing a televised event to displaying and interacting with composites **180** and service provider systems **103** via a secondary device **116**, while a televised event corresponding to the composites **180** is being displayed on another device such as display device

160 the receiver **110**.

(114) The user-selectable options presented with the composite **180** may allow for taking actions, such as selecting one or more URLs and/or hyperlinks to one or more betting platforms, websites, and/or sites for further information and placing bets. As disclosed herein, the user-selectable options may include one or more options to transition provisioning of one or more composites **180** to a secondary device **116** and/or to request notifications from the one or more betting platforms, websites, and/or sites be sent to the secondary device **116** so that the secondary device **116** may be used to interact with the platforms and sites via an application installed on the secondary device **116**. In that way, a user may place bets and otherwise interact with the one or more platforms and sites via the secondary device **116** while viewing the televised event on a primary display associated with a receiver **110** and/or primary device **116**.

(115) As disclosed herein, various embodiments may provide for an interface (augmentation interface) that facilitates the adaptive content composite interaction that is jurisdiction-smart, geo-adaptable, and jurisdiction-adaptable. In combination with other features disclosed herein, various embodiments may differentiate what features are available for a location and jurisdiction and then provide only those features that are available/allowed. Further, the features and recommendations provided by various embodiments may be a function of access rights of particular viewers. The interfaces of various embodiments may orchestrate the services of different systems **103**, biasing content composites **180** and announcements to particular viewers, surfacing available content composites **180** and executable functions from the systems **103**, while providing comparisons of the various corresponding options and parameters. In various embodiments, the augmentation interface may be similar to or different from interface elements disclosed with the example of FIG. 5 and in U.S. application Ser. No. 17/505,135, which application is filed concurrently herewith and is hereby incorporated by reference in its entirety for all purposes.

(116) FIG. 8 illustrates an example method **800** for adaptive content composite interaction with respect to digitally distributed content corresponding to an event, in accordance with embodiments of the present disclosure. One or a combination of the aspects of the method **800** may be performed in conjunction with one or more other aspects disclosed herein, and the method **800** is to be interpreted in view of other features disclosed herein and may be combined with one or more of such features in various embodiments. Thus, in various embodiments, one or more of the methods may additionally or alternatively include one or a combination of the following.

(117) As indicated by block **802**, in various embodiments, one or more processing devices of one or more media devices may perform discovery with respect to a plurality of events at least in part by one or a combination of the following operations, which are disclosed further herein. As indicated by block **804**, a set of one or more electronic communications may be received via one or more interfaces and detected. As indicated by block **806**, one or more indicators of one or more events of a first set of one or more events for which corresponding content is specified for digital distribution may be detected from the one or more sets of one or more electronic communications. As indicated by block **808**, the one or more processing devices may detect a particular endpoint identifier mapped to a set of one or more media devices **110** and/or **116**. As indicated by block **810**, a set of access specifications mapped to the particular endpoint identifier may be determined. In some embodiments, the set of access specifications may be further determined to be mapped to the set of one or more media devices **110** and/or **116**. As indicated by block **812**, a second set of one or more events may be determined from the first set of one or more events as a function of the first set of access specifications. In some instances, the second set may be a subset of the first set; in some instances, the second set may include or be equivalent to the first set.

(118) As indicated by blocks **816**, the one or more processing devices may receive, from a remote system **102** or **103** via a network **120**, one or more content objects **177** corresponding to the second set of one or more events. As indicated by blocks **816**, the one or more processing devices may create mapping specifications of the one or more content objects **177** correlated to the second set of

one or more events and the first set of access specifications. For example, a first set of one or more content objects **177** received by the one or more processing devices from the remote system **102** or **103** may be processed, and a second set of one or more content objects **177** from the first set of one or more content objects **177** may be identified as a function of the one or more rules mapped to the current geolocation. As indicated by blocks **818**, **820**, and **822**, the one or more processing devices may create a set of one or more content composites **180** corresponding to the mapping specifications at least in part by, for each content object **177** of the second set of one or more content objects **177**: selecting, based at least in part on the second set of one or more events, an adaptable content object **176** from a plurality of adaptable content objects **176**; and configuring the adaptable content object **176** with the content object **177** to form a content composite **180** configured to facilitate presentation of the adaptable content object **176** adapted with the content object **177** for at least part of a presentation time when the content composite **180** is presented. As indicated by block **824**, the set of one or more content composites **180** may be stored. As indicated by block **826**, the set of one or more content composites **180** may be used to facilitate an augmentation interface. The augmentation interface may correspond to a graphical layout of the set of one or more content composites **180**, where each content composite **180** causes display of an interface element that allows user selection to cause communication to the process-performing system **103** of an instruction to configure an executable function in accordance with a set of parameters. Where the set of one or more content composites **180** corresponds to a plurality of content composites **180**, and the graphical layout of the plurality of content composites **180** may hierarchically arrange the plurality of content composites **180** according to one or more parameters of the executable functions of the plurality of content composites **180**. For example, in various embodiments, the augmentation interface may organize betting options for various events from various systems **103** by best odds, over under numbers, and/or the like. This could include bets placed, pending and completed, won and lost, current event developments for the corresponding events, as well as options for further selection. Further, the interface may indicate events which the viewer does not currently have access to but could upgrade access rights with a single click.

(119) In some embodiments, the creating the content composite **180** and/or the adaptation of the one or more content objects **176** with one or more particular objects **177** may be a function of a current geolocation of the endpoint media device **116** or **110**, with a set of rules mapped to the current geolocation and specifying geo-specific criteria for creating content composites **180**, selecting content objects **176** and particularized content objects **177**, adapting the content objects **176** with particularized content objects **177**, and provisioning the content objects **176** and particularized content objects **177**. Thus, in various embodiments, the one or more processing devices may detect a current geolocation of a particular media device **110** and/or **116** of the set of one or more media devices **110** and/or **116**, as disclosed further herein. The one or more processing devices may retrieve one or more rules mapped to the current geolocation of the particular media device **110** and/or **116**. The current geolocation of the media device may be determined at a time when the content corresponding to the event is being output for display and/or prior to being output for display. With the content composite **180** created and, in some instances, the one or more content objects **176** adapted, the one or more content objects **176** corresponding to the content may be output for display (during a commercial break and/or during the event as a window, overlay, etc.), where the content objects **176** and particularized content objects **177** are selected based at least in part on location metadata mapped to the content objects **176** and particularized content objects **177** specifying location indicia for the content objects **176** and particularized content objects **177**.

(120) FIG. **9** illustrates a receiver **900** that makes use of, interacts with, and/or at least partially includes the content composite generation/control system **200**, in accordance with disclosed embodiments of the present disclosure. Certain embodiments of the receiver **900** may include set top boxes (STBs), television receivers, and over-the-top receivers. In some embodiments, the receiver **900** may correspond to the television receiver **110**. In various embodiments, in addition to

being in the form of a STB, a receiver may be incorporated as part of another device, such as a television or other form of display device, such as a computer, smartphone, tablet, or other handheld portable electronic device. For example, a television may have an integrated receiver (which does not involve an external STB being coupled with the television). One or a combination of the content harvesting engine **236-1**, the content matching engine **238-1**, learning engine **239-1**, composite build engine **240-1**, and/or content splicing engine **242-1** may be provided in conjunction with content harvesting module **236-2**, the content matching module **238-2**, composite build module **240-2**, and/or content composite splicing module **242-2** to implement various functionalities of the content composite subsystem **111** into the receiver **900**.

(121) The receiver **900** may represent receiver **110** of FIG. **1** and may be in the form of a STB that communicates with a display device such as a television. The receiver **900** may be incorporated as part of a television, such as the display device **160** of FIG. **1** or television **900** of FIG. **9**, etc. The receiver **900** may include: processors **910** (which may include control processor **910-1**, tuning management processor **910-2**, and possibly additional processors), tuners **915**, network interface **920**, non-transitory computer-readable storage medium **925**, electronic programming guide (EPG) database **930**, networking information table (NIT) **940**, digital video recorder (DVR) database **945**, on-demand programming **927**, content store **222-3**, user interface **950**, decryption device **960**, decoder module **933**, interface **935**, and/or descrambling engine **965**. In other embodiments of receiver **900**, fewer or greater numbers of components may be present. It should be understood that the various components of receiver **900** may be implemented using hardware, firmware, software, and/or some combination thereof. Functionality of components may be combined; for example, functions of descrambling engine **965** may be performed by tuning management processor **910-2**. Further, functionality of components may be spread among additional components; for example, PID filters **955** may be handled by separate hardware from program map table **957**. The receiver **900** may be in data communication with service providers, such as by way of network interface **920**.

(122) The network interface **920** may be used to communicate via an alternate communication channel with a content provider, if such communication channel is available. The primary communication channel may be via satellite (which may be unidirectional to the receiver **900**) and the alternate communication channel (which may be bidirectional) may be via a network, such as the Internet. Referring back to FIG. **1**, receiver **110** may be able to communicate with content provider system **102** via a network **120**, such as the Internet. This communication may be bidirectional: data may be transmitted from the receiver **110** to the content provider system **102** and from the content provider system **102** to the receiver **110**. Referring back to FIG. **9**, the network interface **920** may be configured to communicate via one or more networks, such as the Internet, to communicate with content provider system **102** of FIG. **1**. Other information may be transmitted and/or received via the network interface **920** such as adaptable content objects **176**, content objects **177**, composites **180**, metadata, and/or the like as disclosed herein.

(123) The storage medium **925** may represent one or more non-transitory computer-readable storage mediums. The storage medium **925** may include memory and/or a hard drive. The storage medium **925** may store information related to the EPG database **930**, augmentation module **932** and related preferences, other non-video/audio data **931**, DVR database **945**, the other modules, and/or the like. Recorded television programs may be stored using the storage medium **925** as part of the DVR database **945**.

(124) The EPG database **930** may store information related to television channels and the timing of programs appearing on such television channels. The EPG database **930** may be stored using the storage medium **925**, which may be a hard drive. Information from the EPG database **930** may be used to inform users of what television channels or programs are popular and/or provide recommendations to the user. Information from the EPG database **930** may provide the user with a visual interface displayed by a television that allows a user to browse and select television channels

and/or television programs for viewing and/or recording. Information used to populate the EPG database **930** may be received via the network interface **920** and/or via satellites, such as the satellite **106** of FIG. **1** via the tuners **915**. For instance, updates to the EPG database **930** may be received periodically via satellite. The EPG database **930** may serve as an interface for a user to control DVR functions of the receiver **900**, and/or to enable viewing and/or recording of multiple television channels simultaneously. Information from EPG database **930** may be output as a video stream to a display device. A particular user may issue commands indicating that an EPG interface be presented. A user issuing a command that an EPG be displayed may constitute a change command. In some embodiments, content composites **180** may be created and presented in conjunction with the EPG. For example, content composites **180** could pertain to televised events indicated in the EPG. Hence, content composite **180** features may extend to EPG views in some embodiments.

(125) The television interface **935** may serve to output a signal to a television (or another form of display device) in a proper format for display of video and playback of audio. As such, the television interface **935** may output one or more television channels, stored television programming from the storage medium **925** (e.g., television programs from the DVR database **945**, information from the EPG database **930**, etc.) to a television for presentation.

(126) User profiles may also be stored in the storage medium **945** and may include stored user preferences that may be inferred by the television receiver **900** based at least in part on viewing history. The television receiver **900** may communicate user profile information to the service system(s) **102**, **103** to request adaptable content objects **176** and content objects **177** tailored to the inferred user preferences to provision composites **180** in accordance with certain embodiments disclosed herein. The user profiles may include profiles for multiple users or may include a single profile for the television receiver in general. In some embodiments, the user profiles may include preferences for customized content presentation adjustments disclosed herein. The user profiles may further include user feedback, via user-selectable options, received from the user regarding customizations. The feedback data may be used to refine the customizations for particular viewers and types of content customizations.

(127) The user interface **950** may include a remote control (physically separate from the receiver **900**) and/or one or more buttons on the receiver **900** that allow a user to interact with the receiver **900**. The user interface **950** may be used to select a television channel for viewing, view information from the EPG database **930**, and/or program a timer stored to DVR database **945**, wherein the timer is used to control the DVR functionality of the control processor **910-1**. The user interface **950** may also be used to transmit commands to the receiver **900** and make user selections to customize user preferences.

(128) For simplicity, the receiver **900** of FIG. **9** has been reduced to a block diagram; commonly known parts, such as a power supply, have been omitted. Further, some routing between the various modules of the receiver **900** has been illustrated. Such illustrations are for exemplary purposes only. The state of two modules not being directly or indirectly connected does not indicate the modules cannot communicate. Rather, connections between modules of the receiver **900** are intended only to indicate possible common data routing. It should be understood that the modules of the receiver **900** may be combined into a fewer number of modules or divided into a greater number of modules.

(129) Further, the components of the television receiver **900** may be part of another device, such as built into a television. The television receiver **900** may include one or more instances of various computerized components, such as disclosed in relation to computer systems disclosed further herein. While the television receiver **900** has been illustrated as a satellite receiver, it is to be appreciated that techniques below may be implemented in other types of television receiving devices, such as cable receivers, terrestrial receivers, IPTV receivers or the like. In some embodiments, the television receiver **900** may be configured as a hybrid receiving device, capable

of receiving content from disparate communication networks, such as satellite and terrestrial television broadcasts. In some embodiments, the tuners may be in the form of network interfaces capable of receiving content from designated network locations.

(130) FIG. **10** is a block diagram of a system **1000** including one non-limiting example of a computing device **116** configured to facilitate adaptive content composite generation/control, in accordance with disclosed embodiments of the present disclosure. The computing device **116** may be a portable device suitable for sending and receiving information to/from the receiver **110** and over a network to/from remote data sources (e.g., service providers **103** and online content sources **112**) in accordance with embodiments described herein. For example, in various embodiments, the computing device **116** may correspond to one or more of computing devices **116a**, **106b**, **116c**, **116d** depicted in FIG. **1**.

(131) In some embodiments, the computing device **116** may be provided with an application **1051**, which may, in some embodiments, correspond to a mobile application configured to run on the computing device **116** to facilitate various embodiments of this disclosure. For example without limitation, the mobile application **1051** may transform the computing device **116** into an adaptive content composite generation/control device to facilitate features of various embodiments disclosed herein. In various embodiments, the mobile application **1051** may allow the device **116** to be configured to provide one or a combination of the content harvesting engine **236-1**, the content matching engine **238-1**, learning engine **239-1**, content augmentation engine **240-1**, and/or content composite splicing engine **242-1** may be provided in conjunction with the content harvesting module **236-2**, the content matching module **238-2**, content augmentation module **240-2**, and/or content composite generation/control module **242-2** to implement various functionalities of the content composite subsystem **111** into the device **116**.

(132) In various embodiments, the application **1051** can be any suitable computer program that can be installed and run on the computing device **116**, and, in some embodiments, the application **1051** may not be a mobile app but may be another type of application, set of applications, and/or other executable code configured to facilitate embodiments disclosed herein. The application **1051** may be provided in any suitable way. For non-limiting example, the application **1051** may be made available from a website, an application store, the service provider **102**, etc. for download to the computing device **116**; alternatively, it may be pre-installed on the computing device **116**.

(133) In various embodiments, the computing device **116** configured with the application **1051** may provide one or more display screens that may each include one or more user interface elements. A user interface may include any text, image, and/or device that can be displayed on a display screen for providing information to a user and/or for receiving user input. A user interface may include one or more widgets, text, text boxes, text fields, tables, grids, charts, hyperlinks, buttons, lists, combo boxes, checkboxes, radio buttons, and/or the like. As shown in FIG. **10**, the computing device **116** includes a display **1020** and input elements **1032** to allow a user to input information into the computing device **116**. By way of example without limitation, the input elements **1032** may include one or more of a keypad, a trackball, a touchscreen, a touchpad, a pointing device, a microphone, a voice recognition device, or any other appropriate mechanism for the user to provide input.

(134) In various embodiments, the computing device **116** may pull content objects **176**, content objects **177**, and/or composites **180** from the receiver **110** and/or from systems **102** and/or **103** via the network **120** in order to provide the content composites **180** to a user of the computing device **116** through the application **1051**. The application **1051** can include a utility that communicates with the receiver **110** and/or from online data sources via the network **120** to control downloading, displaying, caching, and/or other operations concerning the handling of content objects **176**, content objects **177**, and/or composites **180**. The application **1051** and the computing device **116** may cooperate with the receiver **110** to facilitate tracking of (and customizations of user profiles and other features disclosed herein based at least in part on) user selections in response to content

objects displayed through the one or more additional applications.

(135) The user selection of a user-selectable option corresponding to the application **1051** may involve any one or combination of various user inputs. The user selection may be in the form of a keyboard/keypad input, a touch pad input, a track ball input, a mouse input, a voice command, etc. For example, the content object may be selected by the user by pointing and clicking on a content object. As another example, a content object may be selected by an appropriate tap or movement applied to a touch screen or pad of the computing device **116**.

(136) The computing device **116** includes a memory **1034** communicatively coupled to a processor **1036** (e.g., a microprocessor) for processing the functions of the computing device **116**. The computing device **116** may include at least one antenna for wireless data transfer to communicate through a cellular network, a wireless provider network, and/or a mobile operator network, such as GSM, for example without limitation, to send and receive Short Message Service (SMS) messages or Unstructured Supplementary Service Data (USSD) messages. The computing device **116** may also include a microphone to allow a user to transmit voice communication through the computing device **116**, and a speaker to allow the user to hear voice communication. The antenna may include a cellular antenna (e.g., for sending and receiving cellular voice and data communication, such as through a network such as a 3G, 4G, or 5G network). In addition, the computing device **116** may include one or more interfaces in addition to the antenna, e.g., a wireless interface coupled to an antenna.

(137) The communications interfaces **1044** can provide a near field communication interface (e.g., contactless interface, Bluetooth, optical interface, infrared interface, etc.) and/or wireless communications interfaces capable of communicating through a cellular network, such as GSM, or through Wi-Fi, such as with a wireless local area network (WLAN). Accordingly, the computing device **116** may be capable of transmitting and receiving information wirelessly through both short range, radio frequency (RF), cellular, and Wi-Fi connections. The computing device **116** may access the network **108** through a wireless link to an access point. For example, a computing device **116** may access the network **108** through one or more access points **1006**. The access points **1006** may be of any suitable type or types. For example, an access point **1006** may be a cellular base station, an access point for wireless local area network (e.g., a Wi-Fi access point), an access point for wireless personal area network (e.g., a Bluetooth access point), etc. The access point **1006** may connect the computing device **116** to the network **108**, which may include the Internet, an intranet, a local area network, private communication networks, etc. In some embodiments, the communications interfaces may allow computing device **116** to receive programming content cast from the television receiver. For example, the programming content from the television receiver may be indirectly transmitted via a local network (e.g., via Wi-Fi) or directly transmitted to the computing device via a casting device integrated with the television receiver or coupled to the television receiver (e.g., via a dongle). As another example, the television receiver may cast programming content to the computing device via a wired connection (e.g., via one or more of HDMI, USB, lightning connector, etc.). Some embodiments may provide for simulcasting such that the same programming that is being displayed on the display device is being displayed on the computing device **116** simultaneously or substantially simultaneously.

(138) The computing device **116** can also include at least one computer-readable medium **1046** coupled to the processor **1036**, which stores application programs and other computer code instructions for operating the device, such as an operating system (OS) **1048**. In some embodiments, the application **1051** may be stored in the memory **1034** and/or computer-readable media **1046**. Again, the example of computing device **116** is non-limiting. Other devices, such as those disclosed herein, may be used.

(139) It will be apparent to those skilled in the art that substantial variations may be made in accordance with specific requirements. For example, customized hardware might also be used, and/or particular elements might be implemented in hardware, software (including portable

software, such as applets, etc.), or both. Further, connection to other computing devices such as network input/output devices may be employed.

(140) The terms “machine-readable medium,” “computer-readable storage medium” and “computer-readable medium,” as used herein, refer to any medium that participates in providing data that causes a machine to operate in a specific fashion. These mediums may be non-transitory. In an embodiment implemented using the computer systems disclosed herein, various computer-readable media might be involved in providing instructions/code to processor(s) for execution and/or might be used to store and/or carry such instructions/code. In many implementations, a computer-readable medium is a physical and/or tangible storage medium. Such a medium may take the form of a non-volatile media or volatile media. Non-volatile media include, for example, optical and/or magnetic disks, such as the non-transitory storage device(s). Volatile media include, without limitation, dynamic memory, such as the working memory.

(141) Common forms of physical and/or tangible computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, a CD-ROM, any other optical medium, any other physical medium with patterns of marks, a RAM, a PROM, EPROM, a FLASH-EPROM, any other memory chip or cartridge, or any other medium from which a computer can read instructions and/or code.

(142) Various forms of computer-readable media may be involved in carrying one or more sequences of one or more instructions to the processor(s) for execution. Merely by way of example, the instructions may initially be carried on a magnetic disk and/or optical disc of a remote computer. A remote computer might load the instructions into its dynamic memory and send the instructions as signals over a communication medium to be received and/or executed by the computer system. The communications subsystems of computer systems disclosed herein (and/or components thereof) generally will receive signals, and the bus then might carry the signals (and/or the data, instructions, etc. carried by the signals) to the working memory, from which the processor(s) retrieves and executes the instructions. The instructions received by the working memory may optionally be stored on a non-transitory storage device either before or after execution by the processor(s).

(143) It should further be understood that the components of computer systems can be distributed across a network. For example, some processing may be performed in one location using a first processor while other processing may be performed by another processor remote from the first processor. Other components of computer systems may be similarly distributed. As such, the computer systems may be interpreted as a distributed computing system that performs processing in multiple locations. In some instances, computer systems may be interpreted as a single computing device, such as a distinct laptop, desktop computer, or the like, depending on the context.

(144) The methods, systems, and devices discussed above are examples. Various configurations may omit, substitute, or add various procedures or components as appropriate. For instance, in alternative configurations, the methods may be performed in an order different from that described, and/or various stages may be added, omitted, and/or combined. Also, features described with respect to certain configurations may be combined in various other configurations. Different aspects and elements of the configurations may be combined in a similar manner. Also, technology evolves and, thus, many of the elements are examples and do not limit the scope of the disclosure or claims.

(145) Specific details are given in the description to provide a thorough understanding of example configurations (including implementations). However, configurations may be practiced without these specific details. For example, well-known circuits, processes, algorithms, structures, and techniques have been shown without unnecessary detail in order to avoid obscuring the configurations. This description provides example configurations only, and does not limit the scope, applicability, or configurations of the claims. Rather, the preceding description of the

configurations will provide those skilled in the art with an enabling description for implementing described techniques. Various changes may be made in the function and arrangement of elements without departing from the spirit or scope of the disclosure.

(146) Also, configurations may be described as a process which is depicted as a flow diagram or block diagram. Although each may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may have additional steps not included in the figure. Furthermore, examples of the methods may be implemented by hardware, software, firmware, middleware, microcode, hardware description languages, or any combination thereof. When implemented in software, firmware, middleware, or microcode, the program code or code segments to perform the necessary tasks may be stored in a non-transitory computer-readable medium such as a storage medium. Processors may perform the described tasks.

(147) Having described several example configurations, various modifications, alternative constructions, and equivalents may be used without departing from the spirit of the disclosure. For example, the above elements may be components of a larger system, wherein other rules may take precedence over or otherwise modify the application of the invention. Also, a number of steps may be undertaken before, during, or after the above elements are considered.

(148) Furthermore, the example embodiments described herein may be implemented as logical operations in a computing device in a networked computing system environment. The logical operations may be implemented as: (i) a sequence of computer implemented instructions, steps, or program modules running on a computing device; and (ii) interconnected logic or hardware modules running within a computing device.

(149) Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

(150) Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. The indefinite articles “a” or “an,” as used in the claims, are defined herein to mean one or more than one of the element that the particular article introduces; and subsequent use of the definite article “the” is not intended to negate that meaning. Furthermore, the use of ordinal number terms, such as “first,” “second,” etc., to clarify different elements in the claims is not intended to impart a particular position in a series, or any other sequential character or order, to the elements to which the ordinal number terms have been applied.

Claims

1. A system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event, the system comprising: one or more processing devices; and memory communicatively coupled with and readable by the one or more processing devices and having stored therein processor-readable instructions which, when executed by the one or more processing devices, cause the one or more processing devices to perform: detecting a set of one or more electronic communications received via one or more interfaces; detecting, from the set of one or more electronic communications, one or more signals of one or more events that are specified for digital distribution from a set of one or more events; processing a set of viewership data corresponding to indications of detected media device operations associated with a set of media devices in a particular geolocation and mapped to the set of one or more events, wherein the viewership data is aggregated data from the set of media devices and is indicative of viewership corresponding to a plurality of viewers in the particular geolocation; predicting a viewership of a particular event based at least in part on the set of viewership data of the set of one or more events and of betting odds data mapped to the set of one or more events and received from one or more

remote systems; selecting an identifier of the particular event; creating a content composite corresponding to the particular event, as a function of the predicted viewership and one or more previous interactions of a viewer with one or more previous content composites, at least in part by: identifying, based at least in part on the set of viewership data correlated to feedback data relating the one or more previous interactions of the viewer with the one or more previous content composites, an adaptable content object corresponding to the particular event; processing a content object received by the one or more processing devices from a system that is remote from the one or more processing devices; configuring the adaptable content object with the content object so that the content composite causes presentation of the adaptable content object adapted with the content object for at least part of a presentation time when the content composite is presented; and outputting the content composite for presentation where, consequent to providing the content composite to an endpoint media device, the endpoint media device performs at least one operation relating to the content composite.

2. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 1, where the indications of the detected media device operations are associated with a particular endpoint identifier.

3. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 2, where the detected media device operations comprise one or more previous interactions with one or more previous content composites.

4. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 2, where the detected media device operations comprise one or more previous operational settings of the endpoint media device.

5. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 2, where the creating the content composite is a function of a current geolocation of the endpoint media device and a set of rules mapped to the current geolocation.

6. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 5, where one or both of the adaptable content object and the content object are identified as a function of the current geolocation mapped to the endpoint media device associated with the particular endpoint identifier.

7. A method for adaptive content composite generation with respect to digitally distributed content corresponding to an event, the method comprising: detecting, by one or more processing devices, a set of one or more electronic communications received via one or more interfaces; detecting, by the one or more processing devices from the set of one or more electronic communications, one or more signals of one or more events that are specified for digital distribution from a set of one or more events; processing, by the one or more processing devices, a set of viewership data corresponding to indications of detected media device operations associated with a set of media devices in a particular geolocation and mapped to the set of one or more events, wherein the viewership data is aggregated data from the set of media devices and is indicative of viewership corresponding to a plurality of viewers in the particular geolocation; predicting a viewership of a particular event based at least in part on the set of viewership data of the set of one or more events and of betting odds data mapped to the set of one or more events and received from one or more remote systems; selecting, by the one or more processing devices, an identifier of the particular event; creating, by the one or more processing devices, a content composite corresponding to the particular event, as a function of the predicted viewership and one or more previous interactions of a viewer with one or more previous content composites, at least in part by: identifying, based at least in part on the set of viewership data correlated to feedback data relating the one or more previous interactions of the viewer with the one or more previous content composites, an adaptable content object corresponding to the particular event; processing a content object received by the

one or more processing devices from a system that is remote from the one or more processing devices; configuring the adaptable content object with the content object so that the content composite causes presentation of the adaptable content object adapted with the content object for at least part of a presentation time when the content composite is presented; and outputting, by the one or more processing devices, the content composite for presentation where, consequent to providing the content composite to an endpoint media device, the endpoint media device performs at least one operation relating to the content composite.

8. The method for adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 7, where the indications of the detected media device operations are associated with a particular endpoint identifier.

9. The method for adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 8, where the detected media device operations comprise one or more previous interactions with one or more previous content composites.

10. The method for adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 8, where the detected media device operations comprise one or more previous operational settings of the endpoint media device.

11. The method for adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 8, where the creating the content composite is a function of a current geolocation of the endpoint media device and a set of rules mapped to the current geolocation.

12. The method for adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 11, where one or both of the adaptable content object and the content object are identified as a function of the current geolocation mapped to the endpoint media device associated with the particular endpoint identifier.

13. One or more non-transitory, machine-readable media having machine-readable instructions thereon which, when executed by one or more processing devices, cause the one or more processing devices to perform: detecting a set of one or more electronic communications received via one or more interfaces; detecting, from the set of one or more electronic communications, one or more signals of one or more events that are specified for digital distribution from a set of one or more events; processing a set of viewership data corresponding to indications of detected media device operations associated with a set of media devices in a particular geolocation and mapped to the set of one or more events, wherein the viewership data is aggregated data from the set of media devices and is indicative of viewership corresponding to a plurality of viewers in the particular geolocation; predicting a viewership of a particular event based at least in part on the set of viewership data of the set of one or more events and of betting odds data mapped to the set of one or more events and received from one or more remote systems; selecting an identifier of the particular event; creating a content composite corresponding to the particular event, as a function of the predicted viewership and one or more previous interactions of a viewer with one or more previous content composites, at least in part by: identifying, based at least in part on the set of viewership data correlated to feedback data relating the one or more previous interactions of the viewer with the one or more previous content composites, an adaptable content object corresponding to the particular event; processing a content object received by the one or more processing devices from a system that is remote from the one or more processing devices; configuring the adaptable content object with the content object so that the content composite causes presentation of the adaptable content object adapted with the content object for at least part of a presentation time when the content composite is presented; and outputting the content composite for presentation where, consequent to providing the content composite to an endpoint media device, the endpoint media device performs at least one operation relating to the content composite.

14. The one or more non-transitory, machine-readable media as recited in claim 13, where the

indications of the detected media device operations are associated with a particular endpoint identifier.

15. The one or more non-transitory, machine-readable media as recited in claim 14, where the detected media device operations comprise one or more previous interactions with one or more previous content composites.

16. The one or more non-transitory, machine-readable media as recited in claim 14, where the detected media device operations comprise one or more previous operational settings of the endpoint media device.

17. The one or more non-transitory, machine-readable media as recited in claim 14, where the creating the content composite is a function of a current geolocation of the endpoint media device and a set of rules mapped to the current geolocation.

18. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 1, wherein the creating the content composite is triggered based at least in part on a viewership score correlated to the particular event and the betting odds data.

19. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 1, wherein the creating the content composite is triggered based at least in part on shifting odds at least partially indicated by the betting odds data and comparing the shifting odds to the one or more previous interactions of the viewer with the one or more previous content composites.

20. The system to facilitate adaptive content composite generation with respect to digitally distributed content corresponding to an event as recited in claim 1, wherein the creating the content composite is triggered based at least in part on matching the betting odds data to viewer pattern data for the viewer.
