

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                      |
|----------------------|----------------------|
| United States Patent | 12407927             |
| Kind Code            | B2                   |
| Date of Patent       | September 02, 2025   |
| Inventor(s)          | Jang; Su Bong et al. |

---

### Sensor shifting module and camera module having the same

---

#### Abstract

A sensor shifting module is provided. The module includes a fixed body, a movable body movably disposed inside the fixed body and including an image sensor having an imaging plane oriented in a first direction, and a driving unit moving the movable body in a direction, perpendicular to the first direction, with respect to the fixed body, and rotating the movable body about an axis parallel to the first direction. The driving unit includes a driving coil coupled to one of the fixed body and the movable body, and a driving yoke coupled to the other of the fixed body and the movable body, the driving yoke faces the driving coil in a direction perpendicular to the first direction. When a current is applied to the driving coil, the movable body moves in a direction perpendicular to the first direction, or rotates about an axis parallel to the first direction.

---

**Inventors:** Jang; Su Bong (Suwon-si, KR), Lee; Sang Jong (Suwon-si, KR), Yoon; Hee Soo (Suwon-si, KR), Yun; Tae Ho (Suwon-si, KR), Song; Seung Jae (Suwon-si, KR)

**Applicant:** Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)

**Family ID:** 86310662

**Assignee:** Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)

**Appl. No.:** 17/961859

**Filed:** October 07, 2022

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20230156333 A1          | May. 18, 2023           |

#### Foreign Application Priority Data

|    |                 |               |
|----|-----------------|---------------|
| KR | 10-2021-0156825 | Nov. 15, 2021 |
|----|-----------------|---------------|

---

Publication Classification

Int. Cl.: H04N5/335 (20110101); H01F7/08 (20060101); H04N23/54 (20230101); H04N23/68 (20230101)

U.S. Cl.:

CPC H04N23/687 (20230101); H01F7/08 (20130101); H04N23/54 (20230101);

Field of Classification Search

CPC: H01F (7/08)

References Cited

U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name     | U.S. Cl.   | CPC            |
|--------------|-------------|-------------------|------------|----------------|
| 8279293      | 12/2011     | Noto              | 348/208.7  | H04N<br>23/68  |
| 8908086      | 12/2013     | Kawai             | 348/208.99 | G03B 5/08      |
| 9288394      | 12/2015     | Yazawa            | N/A        | H04N<br>23/682 |
| 10197887     | 12/2018     | Enta              | N/A        | N/A            |
| 10863094     | 12/2019     | Sharma et al.     | N/A        | N/A            |
| 11128788     | 12/2020     | Wade              | N/A        | N/A            |
| 11163212     | 12/2020     | Fu                | N/A        | G02B<br>27/646 |
| 2007/0297780 | 12/2006     | Enomoto           | 348/E5.025 | G03B 5/02      |
| 2010/0202766 | 12/2009     | Takizawa et al.   | N/A        | N/A            |
| 2011/0097061 | 12/2010     | Lee               | 396/55     | H04N<br>23/54  |
| 2012/0268642 | 12/2011     | Kawai             | N/A        | N/A            |
| 2017/0155847 | 12/2016     | Ito               | N/A        | F16M<br>13/022 |
| 2018/0173080 | 12/2017     | Enta              | N/A        | H04N<br>23/57  |
| 2019/0020822 | 12/2018     | Sharma            | N/A        | G03B 3/10      |
| 2019/0104239 | 12/2018     | Aschwanden et al. | N/A        | N/A            |
| 2020/0120242 | 12/2019     | Wade              | N/A        | G02B 7/02      |
| 2020/0218082 | 12/2019     | Choi et al.       | N/A        | N/A            |
| 2020/0314338 | 12/2019     | Johnson et al.    | N/A        | N/A            |
| 2021/0271049 | 12/2020     | Seo et al.        | N/A        | N/A            |
| 2022/0094853 | 12/2021     | Xu                | N/A        | H04N<br>23/55  |
| 2022/0191359 | 12/2021     | Oh                | N/A        | H04N<br>23/55  |
| 2023/0353858 | 12/2022     | Oh                | N/A        | H04N<br>23/58  |

## FOREIGN PATENT DOCUMENTS

| Patent No.      | Application Date | Country | CPC |
|-----------------|------------------|---------|-----|
| 102749697       | 12/2011          | CN      | N/A |
| 107615160       | 12/2017          | CN      | N/A |
| 111045278       | 12/2019          | CN      | N/A |
| 210381098       | 12/2019          | CN      | N/A |
| 112702534       | 12/2020          | CN      | N/A |
| 112799203       | 12/2020          | CN      | N/A |
| 113325652       | 12/2020          | CN      | N/A |
| 5453220         | 12/2013          | JP      | N/A |
| 10-1567107      | 12/2014          | KR      | N/A |
| 10-2018-0118720 | 12/2017          | KR      | N/A |
| 10-2020-0086482 | 12/2019          | KR      | N/A |

## OTHER PUBLICATIONS

Korean Office Action Issued on Feb. 3, 2023, in Counterpart Korean Patent Application No. 10-2021-0156825 (7 Pages in English, 5 Pages in Korean). cited by applicant

Chinese Office Action issued on Feb. 26, 2025, in corresponding Chinese Patent Application No. 202211369021.1. (9pages in English, 19pages in Chinese). cited by applicant

Chinese Office Action issued on Jun. 26, 2025, in counterpart Chinese Patent Application No. 202211369021.1(8 pages in English, 14 pages in Chinese). cited by applicant

---

*Primary Examiner:* Vieaux; Gary C

*Attorney, Agent or Firm:* NSIP Law

---

## Background/Summary

### CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit under 35 USC § 119(a) of Korean Patent Application No. 10-2021-0156825, filed on Nov. 15, 2021, in the Korean Intellectual Property Office, the entire disclosure of which is incorporated herein by reference for all purposes.

### BACKGROUND

1. Field

(2) The following description relates to a sensor shifting module and camera module having the sensor shifting module.

2. Description of Related Art

(3) With the development of communications technology, mobile devices such as, but not limited to, smartphones, are widely distributed, and accordingly, the demand for increased functions of the cameras in such mobile devices are gradually increasing. For example, a camera included in a mobile device may be manufactured to provide advanced image capturing functions (e.g., an autofocus function, an anti-shake function, and the like) implemented in a typical digital single-lens reflex (DSLR) camera despite the small size thereof.

(4) The optical image stabilization (OIS) function, for example, the hand shake correction function, is a function that prevents image blurring from occurring when the camera is shaken during the exposure time, and is necessary when images are captured in low-light environments in which there is a lot of shaking and the exposure time is long. Image stabilization is largely divided into Digital

image stabilization (DIS), Electronic IS (EIS), and Optical IS (OIS). There-among, OIS (Optical IS) fundamentally blocks image deterioration caused by shaking by moving the lens or image sensor in a direction perpendicular to the optical axis to correct the optical path. Since a mechanical actuator is necessary, the implementation of the device is complicated and provides a best compensation performance at the cost of high price.

(5) Since the lens barrel contains an internal optical system, a relatively large amount of force may be necessary to drive the lens barrel. Since the image sensor is relatively light, it is advantageous to implement an excellent image stabilization function even with a small force. However, when the actuator that drives the image sensor includes a permanent magnet, the magnetic field caused by the permanent magnet affects the surrounding electronic components. Specifically, when the mobile device includes multiple cameras disposed adjacently to each other, a permanent magnet inside one camera may negatively affect the operation of a neighboring camera. Therefore, cameras may not be located close to each other, or it may be difficult to dispose electronic components inside the camera.

## SUMMARY

(6) This Summary is provided to introduce a selection of concepts in simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(7) In a general aspect, a sensor shifting module includes a fixed body; a movable body, movably disposed inside the fixed body, and comprising an image sensor having an imaging plane oriented in a first direction; and a driving unit, configured to move the movable body in a direction, perpendicular to a first direction, with respect to the fixed body, and configured to rotate the movable body about an axis parallel to the first direction, wherein the driving unit includes a driving coil coupled to one of the fixed body and the movable body, and a driving yoke coupled to the other one of the fixed body and the movable body, wherein the driving yoke faces the driving coil in a direction perpendicular to the first direction, and wherein, when a current is applied to the driving coil, the movable body is configured to move in a direction perpendicular to the first direction by an electromagnetic interaction between the driving coil and the driving yoke, or is configured to rotate about an axis parallel to the first direction.

(8) The movable body may have four side surfaces which form a quadrangle, and the driving coil or the driving coil is disposed adjacent to both ends of the four side surfaces.

(9) The driving unit may include a first unit driving part, a second unit driving part, a third unit driving part and a fourth unit driving part, each comprising a driving coil and a driving yoke that are configured to move each of the first unit driving part, the second unit driving part, the third unit driving part and the fourth unit driving part in a second direction, perpendicular to the first direction, and respectively face the second direction, and wherein the first unit driving part and the second unit driving part may be spaced apart from each other on a first side surface of the movable body, and the third unit driving part and the fourth unit driving part are spaced apart from each other on a second side surface of the movable body, the first side and the second side disposed in opposite directions to each other.

(10) The image sensor may be disposed between the first unit driving part and the second unit driving part when viewed in the second direction.

(11) The first unit driving part and the third unit driving part may be arranged in the second direction, and the second unit driving part and the fourth unit driving part are arranged in the second direction.

(12) The movable body may include a first side surface and a third side surface that extend in different directions from a corner of the movable body, and the driving unit may include a first unit driving part and a fifth unit driving part disposed adjacent to a corner on the first side surface and the third side surface, respectively, wherein the first unit driving part may include a driving coil and

a driving yoke opposed in a second direction, perpendicular to the first direction, and the fifth unit driving part may include a driving coil and a driving yoke opposed in a third direction, perpendicular to the first direction, the second direction and the third direction intersecting each other.

(13) A surface of the driving yoke, opposite to the driving coil, may be convex.

(14) A surface of the driving yoke, opposite to the driving coil, may include an inclined surface that extends from a central portion of the driving yoke to ends of the driving yoke.

(15) The driving yoke and the driving coil may be opposite to each other in a second direction, perpendicular to the first direction, and a distance in the second direction from a central portion of the driving yoke to the driving coil may be shorter than a distance in the second direction from a first end and a second end of the driving yoke to the driving coil.

(16) The driving yoke may be a soft magnetic material.

(17) The driving unit may further include a first yoke disposed on a first side of the driving coil, wherein the driving coil is disposed between the driving yoke and the first yoke.

(18) The module may further include a substrate that mechanically connects the movable body to the fixed body, and is configured to deform based on a movement of the movable body with respect to the fixed body.

(19) The substrate may include electric traces electrically connected to the image sensor.

(20) The substrate may include a floating part fixedly coupled to the movable body, a fixed part fixedly coupled to the fixed body, and a support part that interconnects the floating part and the fixed part, wherein the support part comprises a plurality of bridges that embed the electric traces therein.

(21) The support part may include a guide disposed between the floating part and the fixed part, and may be connected to the floating part and the fixed part through the plurality of bridges.

(22) The plurality of bridges may include first bridges that extend in a second direction, perpendicular to the first direction, from the floating part to the guide, and second bridges which extend from the guide to the fixed part in a third direction, perpendicular to the first direction, the second direction and the third direction intersecting each other.

(23) The driving unit may include a position sensor disposed on one of the fixed body and the movable body, and a sensing magnet disposed on the other one of the fixed body and the movable body and facing the position sensor in the first direction.

(24) In a general aspect, a camera module includes a lens module including at least one lens; and a sensor shifting module, wherein the sensor shifting module includes a fixed body; a movable body movably disposed inside the fixed body, and including an image sensor oriented in a first direction; a substrate that mechanically connects the movable body to the fixed body, and is configured to deform based on a movement of the movable body with respect to the fixed body; and a driving unit configured to move the movable body in a direction, perpendicular to the first direction, with respect to the fixed body, and rotate the movable body about an axis parallel to the first direction, wherein the driving unit comprises a driving coil coupled to one of the fixed body and the movable body, and a driving yoke coupled to the other one of the fixed body and the movable body, and wherein the driving yoke faces the driving coil in a direction, perpendicular to the first direction, and a space between the driving yoke and the driving coil is an air gap.

(25) The driving yoke may be a soft magnetic material.

(26) The driving unit may include a first unit driving part, a second unit driving part, a third unit driving part and a fourth unit driving part, each comprising a driving coil and a driving yoke that are configured to move each of the first unit driving part, the second unit driving part, the third unit driving part, and the fourth unit driving part in a second direction, perpendicular to the first direction, and respectively facing the second direction, wherein the first unit driving part and the second unit driving part are spaced apart from each other on a first side surface of the movable body, and the third unit driving part and the fourth unit driving part are spaced apart from each

other on a second side surface of the movable body, the first side surface and the second side surface being in opposite directions to each other.

(27) In a general aspect, an electronic apparatus includes a housing, a camera module disposed in the housing, the camera module including a movable sensor carrier disposed on a flexible substrate; a plurality of actuator unit driving parts configured to move the movable sensor carrier in a first direction perpendicular to an optical axis direction, a second direction perpendicular to the optical axis direction, and further configured to rotate the movable sensor carrier with respect to a fixed body in a direction parallel to the optical axis direction; wherein the flexible substrate comprises a floating part on which the movable sensor carrier is disposed, a fixed part that is fixed to the fixed body, and a support part that connects the floating part to the fixed part.

(28) Two actuator unit driving parts may be disposed on each of four sides of the movable sensor carrier.

(29) The floating part may be configured to move relative to the fixed body.

(30) The apparatus may further include a position sensor disposed on a base portion of the fixed body, and configured to measure the movement of the moveable sensor carrier in the first direction and the second direction, and measure an amount of rotation of the movable sensor carrier. The apparatus may further include a sensing magnet, disposed on the floating part, and disposed to face the position sensor.

(31) The position sensor may be one of a Hall sensor and a magnetoresistance sensor.

(32) Other features and aspects will be apparent from the following detailed description, the drawings, and the claims

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 schematically illustrates components constituting an example camera module, in accordance with one or more embodiments.

(2) FIG. 2 illustrates an example sensor shifting module, in accordance with one or more embodiments.

(3) FIG. 3 illustrates a top view of a substrate on which an image sensor is mounted, in accordance with one or more embodiments.

(4) FIG. 4 is a top view of an example OIS driver, in accordance with one or more embodiments.

(5) FIG. 5A, FIG. 5B, FIG. 5C, and FIG. 5D illustrate a movement of a movable body based on the OIS driver of FIG. 4.

(6) FIG. 6 and FIG. 7 illustrate a rotation of the movable body based on the OIS driver of FIG. 4.

(7) FIG. 8A, FIG. 8B, FIG. 8C, and FIG. 8D illustrate the deformation of a substrate, in accordance with one or more embodiments.

(8) FIG. 9A and FIG. 9B illustrate a sensor holder of a different type from that of FIG. 2.

(9) Throughout the drawings and the detailed description, the same reference numerals may refer to the same, or like, elements. The drawings may not be to scale, and the relative size, proportions, and depiction of elements in the drawings may be exaggerated for clarity, illustration, and convenience.

### DETAILED DESCRIPTION

(10) The following detailed description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. However, various changes, modifications, and equivalents of the methods, apparatuses, and/or systems described herein will be apparent after an understanding of the disclosure of this application. For example, the sequences of operations described herein are merely examples, and are not limited to those set forth herein, but may be changed as will be apparent after an understanding of the disclosure of this

application, with the exception of operations necessarily occurring in a certain order. Also, descriptions of features that are known, after an understanding of the disclosure of this application, may be omitted for increased clarity and conciseness, noting that omissions of features and their descriptions are also not intended to be admissions of their general knowledge.

(11) The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided merely to illustrate some of the many possible ways of implementing the methods, apparatuses, and/or systems described herein that will be apparent after an understanding of the disclosure of this application.

(12) Herein, it is noted that use of the term “may” with respect to an example or embodiment, e.g., as to what an example or an example may include or implement, means that at least one example or embodiment exists in which such a feature is included or implemented while all examples and examples are not limited thereto.

(13) Throughout the specification, when an element, such as a layer, region, or substrate, is described as being “on,” “connected to,” or “coupled to” another element, it may be directly “on,” “connected to,” or “coupled to” the other element, or there may be one or more other elements intervening therebetween. In contrast, when an element is described as being “directly on,” “directly connected to,” or “directly coupled to” another element, there may be no other elements intervening therebetween. Likewise, expressions, for example, “between” and “immediately between” and “adjacent to” and “immediately adjacent to” may also be construed as described in the foregoing.

(14) As used herein, the term “and/or” includes any one and any combination of any two or more of the associated listed items.

(15) Although terms such as “first,” “second,” and “third” may be used herein to describe various members, components, regions, layers, or sections, these members, components, regions, layers, or sections are not to be limited by these terms. Rather, these terms are only used to distinguish one member, component, region, layer, or section from another member, component, region, layer, or section. Thus, a first member, component, region, layer, or section referred to in examples described herein may also be referred to as a second member, component, region, layer, or section without departing from the teachings of the examples.

(16) Spatially relative terms such as “above,” “upper,” “below,” and “lower” may be used herein for ease of description to describe one element's relationship to another element as illustrated in the figures. Such spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, an element described as being “above” or “upper” relative to another element will then be “below” or “lower” relative to the other element. Thus, the term “above” encompasses both the above and below orientations depending on the spatial orientation of the device. The device may also be oriented in other manners (for example, rotated 90 degrees or at other orientations), and the spatially relative terms used herein are to be interpreted accordingly.

(17) The terminology used herein is for the purpose of describing particular examples only, and is not to be used to limit the disclosure. As used herein, the singular forms “a,” “an,” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. As used herein, the term “and/or” includes any one and any combination of any two or more of the associated listed items. As used herein, the terms “include,” “comprise,” and “have” specify the presence of stated features, numbers, operations, elements, components, and/or combinations thereof, but do not preclude the presence or addition of one or more other features, numbers, operations, elements, components, and/or combinations thereof. The use of the term “may” herein with respect to an example or embodiment (for example, as to what an example or embodiment may include or implement) means that at least one example or embodiment exists where such a feature is included or implemented, while all examples are not limited thereto.

(18) Unless otherwise defined, all terms, including technical and scientific terms, used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure pertains consistent with and after an understanding of the present disclosure. Terms, such as those defined in commonly used dictionaries, are to be interpreted as having a meaning that is consistent with their meaning in the context of the relevant art and the present disclosure, and are not to be interpreted in an idealized or overly formal sense unless expressly so defined herein.

(19) Due to manufacturing techniques and/or tolerances, variations of the shapes illustrated in the drawings may occur. Thus, the examples described herein are not limited to the specific shapes illustrated in the drawings, but include changes in shape occurring during manufacturing.

(20) The features of the examples described herein may be combined in various manners as will be apparent after gaining an understanding of the disclosure of this application. Further, although the examples described herein have a variety of configurations, other configurations are possible as will be apparent after gaining an understanding of the disclosure of this application.

(21) The drawings may not be to scale, and the relative sizes, proportions, and depiction of elements in the drawings may be exaggerated for clarity, illustration, and convenience.

(22) In this document, the X-direction, the Y-direction, and the Z-direction indicate a direction parallel to the X-axis, a direction parallel to the Y-axis, and a direction parallel to the Z-axis illustrated in the drawings, respectively. In addition, unless otherwise stated, the X direction is a concept including both the +X-axis direction and the -X-axis direction, and this is also applied to the Y-direction and the Z-direction.

(23) When two directions (or axes) are parallel to or perpendicular to each other in this document, it also includes examples in which the two directions (or axes) are substantially parallel to each other or substantially side by side. For example, the first axis and the second axis being perpendicular to each other indicates that the first axis and the second axis form an angle of 90 degrees or close to 90 degrees.

(24) Paragraphs beginning with “in one/an example” in this document do not necessarily refer to the same examples. The specific features, structures, or characteristics may be combined in any suitable manner consistent with the present disclosure.

(25) In this document, “configured to” indicates that a component includes a structure necessary to implement a certain function.

(26) Hereinafter, an example of the present disclosure will be described in detail with reference to the drawings. However, the spirit of the present disclosure is not limited to the presented example. For example, those skilled in the art who understand the spirit of the present disclosure will be able to propose other examples included within the scope of the spirit of the present disclosure through addition, change or deletion of components, or the like, but this will also be included within the scope of the spirit of the present disclosure.

(27) One or more examples relate to a method of implementing optical image stabilization by driving an image sensor.

(28) Camera Module

(29) FIG. 1 schematically illustrates components constituting an example camera module **1**, in accordance with one or more embodiments.

(30) In one example, a camera module **1** includes a lens module **20** including at least one lens **21** and a lens barrel **22** that accommodates the at least one lens **21**, and an image sensor **11**. Light **L** passes through the lens module **20** and contacts an imaging plane of the image sensor **11**. The camera module **1** may include an AF driving unit **23** that moves the lens module **20** in the optical axis direction to adjust the focal length. The AF driving unit **23** may include, for example, a coil and a magnet facing each other. The coil is fixedly coupled to the lens module **20**, the magnet is coupled to a fixed body such as a housing, and electromagnetic interaction between the coil and the magnet may cause the lens module **20** to move in the optical axis direction.

(31) In an example, the camera module **1** may provide an optical image stabilization (hereinafter,



'OIS') function. The camera module **1** may provide an OIS function by driving the image sensor **11**. For example, the camera module **1** may include an OIS driver **12** that moves or drives the image sensor **11** in a direction perpendicular to the optical axis, or rotates the image sensor about an axis parallel to the optical axis or about an axis perpendicular to the optical axis.

(32) In an example, the camera module **1** may include a sensor shifting module **10**. The sensor shifting module **10** may include components necessary to implement the OIS function by driving the image sensor **11**. For example, the sensor shifting module **10** may include the image sensor **11** and the OIS driver **12** which drives the image sensor **11**. As another example, the sensor shifting module **10** may mean only the OIS driver **12** excluding the image sensor **11**.

(33) In one example, the camera module **1** may further include an optical element in addition to the lens module **20** and the image sensor **11**. In one example, the camera module **1** may include two or more lens modules. For example, a first optical element **30** and/or a second optical element **40** may be a lens module distinct from the lens module **20**.

(34) In an example, the camera module **1** may include an optical path changing element disposed in front of the lens module **20**. For example, the first optical element **30** may be a prism or a mirror. In another example, the optical path changing element may be disposed between the image sensor **11** and the lens module **20**. For example, the second optical element **40** may be a prism or a mirror.

(35) Hereinafter, a sensor shifting module **100** or the OIS driver **120** described with reference to FIGS. **2** to **9B** may be applied to the camera module **1** of FIG. **1**.

(36) **2. Sensor Shift**

(37) **2.1. Structure**

(38) FIG. **2** illustrates the sensor shifting module **100** according to an example. The sensor shifting module **100** may include an OIS driver **120** that drives an image sensor **111**. In an example, the OIS driver **120** includes a movable body **110** including the image sensor **111**, and a fixed body **130**. The movable body **110** may be movably disposed inside the fixed body **130**. The movable body **110** is a component that moves together with the image sensor **111**. For example, the movable body **110** may include a sensor substrate **112** on which the image sensor **111** is mounted, and a sensor holder **113** coupled to the sensor substrate **112**.

(39) Referring to FIG. **2**, the sensor holder **113** may include a plate **113a** connected to the lower portion of the sensor substrate **112**, and an extension portion **113b** extending upwardly (e.g., in the +Z direction) from the edge of the plate **113a**. The extension portion **113b** may face a driving coil **122**, and a driving yoke **121** may be seated on the extension portion **113b**. In another example, the driving yoke **121** may be mounted on the fixed body **130**, and the driving coil **122** may be mounted on the sensor holder **113**. In this example, the driving coil **122** and/or the yoke **123** may be seated on the extension portion **113b**.

(40) A signal from the image sensor **111** may be transmitted to another electronic component (e.g., an image signal processor (ISP)) through the sensor substrate **112** and a connector **150**.

(41) The fixed body **130** may include a base **131** and components fixedly coupled to the base **131**. For example, the fixed body **130** may include the driving coil **122** and a yoke **123** to be described later.

(42) Through the OIS driver **120**, the movable body **110** may move in a direction orthogonal to the direction in which the imaging plane **111a** of the image sensor **111** faces. In an example, the OIS driver **120** may correct the shaking of the camera module **1** or the electronic device in which the image sensor **111** is mounted in a direction perpendicular to an optical axis O. The OIS driver **120** may move the image sensor **111** in a first direction and a second direction perpendicular to the optical axis O. The first direction and the second direction may intersect each other. For example, the OIS driver **120** may move the movable body **110** in the X direction and/or the Y direction perpendicular to the Z-axis, and accordingly, may correct shake in the X-direction and/or the Y-direction.

(43) In an example, the OIS driver **120** may rotate the movable body **110** with respect to the fixed

body based on an axis parallel to the optical axis O. The OIS driver **120** may correct rotation of the camera module **1** or the electronic device in which the image sensor **111** is mounted, based on an axis parallel to the optical axis O.

(44) In one or more examples, the direction in which the imaging plane **111a** of the image sensor **111** faces may be referred to as an optical axis O direction. For example, the movable body **110** may move in a direction perpendicular to the optical axis O with respect to the fixed body **130**. In the drawings of the one or more examples, the optical axis (**0**) is illustrated parallel to the Z axis, and thus the Z direction indicates a direction parallel to the optical axis (**0**). In addition, the X direction or Y direction indicates a direction perpendicular to the optical axis (**0**). For example, in one or more examples, moving the movable body **110** in the X direction may be understood as moving the movable body **110** in a direction perpendicular to the optical axis O. In another example, it may be understood that the driving yoke **121** and the driving coil **122** opposing each other in the X direction indicates that the driving yoke **121** and the driving coil **122** face each other in a direction perpendicular to the optical axis O. Additionally, the X direction or the Y direction is an example of two directions perpendicular to the optical axis O and intersecting each other, and in the one or more examples, the X direction and the Y direction may be understood as two directions perpendicular to the optical axis O and intersecting each other.

#### (45) 2.1.1. PCB Spring

(46) In an example, the sensor shifting module **100** may include a substrate **140** that mechanically connects the movable body **110** to the fixed body **130**. The substrate **140** may couple the movable body **110** to the fixed body **130** to be movable with respect to the fixed body **130** in a direction perpendicular to the optical axis O. A portion of the substrate **140** may be deformed according to the movement of the movable body **110** with respect to the fixed body **130**. For example, a portion of the substrate **140** may be flexible. When the substrate **140** is deformed, a restoring force is generated in the substrate **140**, and this restoring force may return the movable body **110** to an original position thereof. The movable body **110** in the equilibrium state moves with respect to the fixed body **130** as a current is applied to the driving coil **122**, and when the current does not flow in the driving coil **122**, the movable body **110** may return to the original position by the substrate **140**.

(47) FIG. 3 illustrates a top view of the substrate **140** on which the image sensor **111** is mounted, in accordance with one or more embodiments. Referring to FIGS. 2 and 3, the substrate **140** may include a floating part **141** on which the sensor substrate **112** is seated, and a fixed part **142** fixed to the fixed body **130**. The sensor substrate **112** and the floating part **141** may be electrically connected to each other through solder balls at corresponding contact points P1 and P2.

(48) While the movable body **110** (or the image sensor **111**) moves with respect to the fixed body **130**, the floating part **141** moves with respect to the fixed part **142**. The substrate **140** may include a support part **143** connecting the floating part **141** and the fixed part **142** to each other. The support part **143** may be deformed at least partially according to a relative movement between the floating part **141** and the fixed body **130**. In an example, the support part **143** may be formed of a flexible substrate. The flexible substrate may be provided in a form in which a conductive pattern (or an electric trace **145**) is formed inside a film formed of a polyimide material.

(49) In an example, the substrate **140** may include a plurality of bridge elements **144** connecting the floating part **141** and the fixed part **142**. The plurality of bridge elements **144** may constitute at least a portion of the support part **143**. The plurality of bridge elements **144** are formed of a flexible material, and may be deformed when the floating part **141** moves with respect to the fixed part **142**. When the movable body **110** moves with respect to the fixed body **130**, the floating part **141** may move with respect to the fixed part **142**, and the bridge elements **144** may be deformed. The restoring force generated while the bridge elements **144** are deformed may return the movable body **110** or the floating part **141** to the original position thereof. The plurality of bridge elements **144** may respectively contain at least one electric trace **145**. For example, the plurality of bridge elements **144** may mechanically and electrically connect the floating part **141** (or the movable body

**110**) to the fixed part **142** (or the fixed body **130**). For example, the bridge elements **144** support the image sensor **111** and may function as a passage through which a signal of the image sensor **111** is transmitted.

(50) In an example, the substrate **140** may include a guide **146** disposed between the floating part **141** and the fixed part **142**. For example, the guide **146** may be provided in the form of a frame surrounding the floating part **141**. The fixed part **142**, the guide **146**, and the floating part **141** may be connected via the bridge elements **144**. For example, the substrate **140** may include a first bridge **147** extending from the floating part **141** to the guide **146**, and a second bridge **148** extending from the guide **146** to the fixed part **142**. The first bridge **147** and the second bridge **148** may extend in a direction perpendicular to the optical axis O. The first bridge **147** and the second bridge **148** may extend in directions intersecting each other. For example, the first bridge **147** may extend in the Y direction, and the second bridge **148** may extend in the Z direction.

(51) The first bridge **147** and the second bridge **148** may each include one or more bridge elements **144**. In FIG. 3, the first bridge **147** includes four bridge elements **144** extending in the X direction, and the second bridge **148** includes four bridge elements **144** extending in the Y direction. The substrate **140** of FIG. 3 has an illustrative shape, and the shape of the support part **143** connecting the floating part **141** and the fixed part **142** may be various. For example, the support part **143** may be comprised of the plurality of bridge elements **144** extending directly from the floating part **141** to the fixed part **142**. As another example, the first bridge **147** or the second bridge **148** may include five bridge elements **144**. The number of bridge elements **144** constituting the first bridge **147** or the second bridge **148** may be as many as the number corresponding to the number of terminals of the image sensor **111**.

(52) The substrate **140** may include the electric trace **145** that transmits a signal of the image sensor **111**. The plurality of bridge elements **144** constituting the support part **143** embed the electric trace **145**. The image sensor **111** is mounted on the sensor substrate **112**, and the sensor substrate **112** is electrically connected to the fixed part **142** of the substrate **140**. The electric trace **145** may extend from each of the contact points P2 formed in the floating part **141**. The electric trace **145** may extend through bridge element **144** to fixed part **142**. The electric trace **145** extending to the fixed part may be electrically connected to another substrate or electronic component.

(53) On the other hand, FIG. 3 schematically illustrates the electric trace **145** formed on the substrate **140**, and only the electric trace **145** extending from some contact points is illustrated for convenience of description.

(54) 2.1.2. Position Sensor

(55) Referring to FIG. 2, in an example, the OIS driver **120** may include a position sensor **127** that may measure how much the movable body **110** moves in a direction perpendicular to the optical axis O, or how much the movable body rotates based on an axis parallel to the optical axis O. The position sensor **127** may be, as examples, a Hall sensor or a magnetoresistance sensor.

(56) The OIS driver **120** may include a sensing magnet **124** that moves together with the movable body **110** and faces the position sensor **127**. The position sensor **127** may be disposed to face the sensing magnet **124**. For example, the position sensor **127** may be disposed on the base **131**, and the sensing magnet **124** may be disposed on the substrate to face the position sensor **127** in the optical axis O direction (e.g., in the Z direction). As another example, the position sensor **127** may be disposed on the substrate, and the sensing magnet **124** may be disposed on the base **131**. The position sensor **127** and the sensing magnet **124** may be provided in two or more pairs.

(57) 2.2. Actuator

(58) Referring to FIG. 2, in an example, the OIS driver **120** may include a driving coil **122** coupled to one of the movable body **110** or the fixed body **130**, and a driving yoke **121** coupled to the other one of the movable body **110** or the fixed body **130**. For example, referring to FIG. 2, in an example, the driving coil **122** and the driving yoke **121** may be coupled to the base **131** and the sensor holder **113**, respectively. The driving yoke **121** and the driving coil **122** may face each other

in a direction perpendicular to the optical axis O. The electromagnetic interaction between the driving yoke **121** and the driving coil **122** causes the movable body **110** to move in a direction perpendicular to the optical axis O with respect to the fixed body **130**. In addition, electromagnetic interaction between the driving yoke **121** and the driving coil **122** may rotate the movable body **110** with respect to the fixed body **130** about an axis parallel to the optical axis O.

(59) In an example, the OIS driver **120** may further include a yoke **123** disposed on one side of the coil. The yoke **123** allows the magnetic field generated in the coil to be concentrated only in a direction toward the driving yoke **121**. Since the yoke **123** is disposed on one side of the driving coil **122**, the magnetic field generated by the driving coil **122** may be prevented from affecting other electronic components, or may significantly reduce the magnetic field from affecting other electronic components.

(60) In one or more examples, the driving coil **122** and the driving yoke **121** are consistently described as being coupled to the fixed body **130** and the movable body **110**, respectively. However, this is only an example, and in another example, the driving coil **122** and the driving yoke **121** may be coupled to the movable body **110** and the fixed body **130**, respectively. For example, the driving coil **122** and the driving yoke **121** may be coupled to the sensor holder **113** and the base **131**, respectively.

(61) An air gap may be formed between the driving coil **122** and the driving yoke **121**. Alternatively, the space between the driving coil **122** and the driving yoke **121** may be an air gap. For example, there may be no other member (e.g., a magnet) between the driving coil **122** and the driving yoke **121**. The driving coil **122** and the driving yoke **121** directly face each other with an air gap therebetween.

(62) FIG. 2 illustrates components of the OIS driver **120**, and the one or more examples are not limited by the structure of FIG. 2.

(63) 2.2.1. Reluctance

(64) In an example, the OIS driver **120** may not include a permanent magnet. In an example, when no current flows in the driving coil **122**, the magnetic field due to the driving yoke **121** may be zero or a very small level. Accordingly, the magnetic field caused by the OIS driver **120** itself may be prevented or significantly reduced from affecting other electronic components (e.g., other electronic components inside the camera module **1**, or other electronic components inside another camera module **1**).

(65) In an example, the driving yoke **121** may be formed of a soft magnetic material. A soft magnetic material has low coercive force and is magnetized when exposed to a magnetic field, but loses magnetism or may have a relatively low level of magnetism when the magnetic field disappears.

(66) When a current is applied to the driving coil **122**, the driving yoke **121** is magnetized, thereby generating a reluctance force between the driving coil **122** and the driving yoke **121**. An attractive force is generated in a direction in which the driving yoke **121** and the driving coil **122** face each other, which causes the movable body **110** to move with respect to the fixed body **130** in the corresponding direction. For example, referring to FIG. 4, when current is applied to a first unit driving part **120-1** and a second unit driving part **120-2**, an attractive force is generated between the driving coil **122** and the driving yoke **121** constituting the unit driving parts **120-1** and **120-2**, which may move the movable body **110** in the -X direction. Conversely, when current is applied to a third unit driving part **120-3** and a fourth unit driving part **120-4**, attractive force is generated between the driving coil **122** and the driving yoke **121** constituting the unit driving parts **120-3** and **120-4**, which may move the movable body **110** in the +X direction.

(67) 2.2.2. Array (Translation+Rolling)

(68) FIG. 4 is a top view of the OIS driver **120**, in accordance with one or more embodiments.

(69) The OIS driver **120** may include a plurality of unit driving parts **120-1**, **120-2**, **120-3**, **120-4**, **120-5**, **120-6**, **120-7**, and **120-8**. The unit driving parts **120-1**, **120-2**, **120-3**, **120-4**, **120-5**, **120-6**,

**120-7**, and **120-8** may each include one driving yoke **121** and one driving coil **122** facing each other. The driving yoke **121** and the driving coil **122** may be mounted to face each other on the movable body **110** or the fixed body **130**. It may be understood that the unit driving parts **120-1**, **120-2**, **120-3**, **120-4**, **120-5**, **120-6**, **120-7**, and **120-8** further include a yoke **123** disposed on one side of the driving coil **122**.

(70) In an example, the OIS driver **120** may include at least one unit driving part disposed in the  $-X$  direction and the  $+X$  direction of the movable body **110**, respectively, to correct the shake in the  $X$  direction. For example, referring to FIG. 4, the OIS driver **120** may include a first unit driving part **120-1**, a second unit driving part **120-2**, a third unit driving part **120-3**, and a fourth unit driving part **120-4**. The first unit driving part **120-1** and the second unit driving part **120-2** are disposed in the  $-X$  direction of the movable body **110**, and may move the movable body **110** in the  $-X$  direction when a current is applied. The third unit driving part **120-3** and the fourth unit driving part **120-4** are disposed in the  $+X$  direction of the movable body **110**, and may move the movable body **110** in the  $+X$  direction when current is applied.

(71) The first unit driving part **120-1** and the third unit driving part **120-3** may be arranged in a first direction (e.g.,  $X$  direction) perpendicular to the optical axis  $O$ . Additionally, the second unit driving part **120-2** and the fourth unit driving part **120-4** may be arranged in the first direction. For example, when viewed in the first direction, the first unit driving part **120-1** and the third unit driving part **120-3** overlap each other, and the second unit driving part **120-2** and the fourth unit driving part **120-4** overlap each other.

(72) In an example, the OIS driver **120** may include at least one unit driving part disposed in the  $-X$  direction and the  $+X$  direction of the movable body **110**, respectively, to correct the shake in the  $X$  direction. For example, the OIS driver **120** may include a fifth unit driving part **120-5**, a sixth unit driving part **120-6**, a seventh unit driving part **120-7**, and an eighth unit driving part **120-8**. The fifth unit driving part **120-5** and the sixth unit driving part **120-6** are disposed in the  $+Y$  direction of the movable body **110**, and may move the movable body **110** in the  $+Y$  direction when current is applied. The seventh unit driving part **120-7** and the eighth unit driving part **120-8** are disposed in the  $-Y$  direction of the movable body **110**, and may move the movable body **110** in the  $-Y$  direction when current is applied.

(73) The fifth unit driving part **120-5** and the seventh unit driving part **120-7** may be arranged in a second direction (e.g., a  $Y$  direction) perpendicular to the optical axis  $O$ . Additionally, the sixth unit driving part **120-6** and the eighth unit driving part **120-8** may be arranged in the second direction. For example, when viewed in the second direction, the fifth unit driving part **120-5** and the seventh unit driving part **120-7** overlap each other, and the sixth unit driving part **120-6** and the eighth unit driving part **120-8** overlap each other.

(74) In an example, the movable body **110** has four side surfaces **113b-1**, **113b-2**, **113b-3**, and **113b-4** that form a quadrangle, and a driving coil **122** or a driving yoke **121** may be disposed adjacently to ends of each of the four side surfaces **113b-1**, **113b-2**, **113b-3** and **113b-4**. The first unit driving part **120-1** and the second unit driving part **120-2** may be disposed on the first side surface **113b-1** of the movable body **110**, and may be spaced apart from each other. For example, the first side surface **113b-1** may face the  $-X$  direction, and the first unit driving part **120-1** and the second unit driving part **120-2** may be spaced apart from each other in the  $Y$  direction. The first unit driving part **120-1** and the second unit driving part **120-2** may be disposed adjacently to both ends of the first side surface **113b-1**, respectively. When viewed in the  $X$  direction, the optical axis  $O$  (or the image sensor **111**) may be positioned between the first unit driving part **120-1** and the second unit driving part **120-2**. Accordingly, when a current is applied to either the first unit driving part **120-1** or the second unit driving part **120-2**, a  $Z$ -axis moment may be generated in the movable body **110**, which causes the movable body **110** to be rotated with respect to the fixed body about the  $Z$  axis.

(75) The third unit driving part **120-3** and the fourth unit driving part **120-4** are disposed on the second side surface **113b-2** of the movable body **110** and are spaced apart from each other. The

second side surface **113b-2** and the first side surface **113b-1** face opposite directions. For example, the second side surface **113b-2** may face the +X direction, and the third unit driving part **120-3** and the fourth unit driving part **120-4** may be spaced apart from each other in the Y direction. The third unit driving part **120-3** and the fourth unit driving part **120-4** may be disposed close to both ends of the second side surface **113b-2**, respectively. When viewed in the X direction, the optical axis O (or the image sensor **111**) may be positioned between the third unit driving part **120-3** and the fourth unit driving part **120-4**. Accordingly, when a current is applied to either the third unit driving part **120-3** or the fourth unit driving part **120-4**, a Z-axis moment may be generated in the movable body **110**, which causes the movable body **110** to be rotated with respect to the fixed body about the Z axis.

(76) The fifth unit driving part **120-5** and the sixth unit driving part **120-6** are disposed on the third side surface **113b-3** of the movable body **110** and are spaced apart from each other. The fifth unit driving part **120-5** and the sixth unit driving part **120-6** may be spaced apart from each other in the X direction. The fifth unit driving part **120-5** and the sixth unit driving part **120-6** may be disposed close to both ends of the third side surface **113b-3**, respectively. When viewed in the Y direction, the optical axis O (or the image sensor **111**) may be positioned between the fifth unit driving part **120-5** and the sixth unit driving part **120-6**. Accordingly, when a current is applied to one of the fifth unit driving part **120-5** or the sixth unit driving part **120-6**, a Z-axis moment may be generated in the movable body **110**, which causes the movable body **110** to be rotated with respect to the fixed body about the Z axis.

(77) The seventh unit driving part **120-7** and the eighth unit driving part **120-8** are disposed on the fourth side surface **113b-4** of the movable body **110**, and are spaced apart from each other. The fourth side surface **113b-4** faces opposite directions to the third side surface **113b-3**. The seventh unit driving part **120-7** and the eighth unit driving part **120-8** may be spaced apart from each other in the X direction. The seventh unit driving part **120-7** and the eighth unit driving part **120-8** may be disposed close to both ends of the fourth side surface **113b-4**. When viewed in the Y direction, the optical axis O (or the image sensor **111**) may be positioned between the seventh unit driving part **120-7** and the eighth unit driving part **120-8**. Accordingly, when a current is applied to one of the seventh unit driving part **120-7** or the eighth unit driving part **120-8**, a Z-axis moment may be generated in the movable body **110**, which causes the movable body **110** to be rotated with respect to the fixed body about the Z axis.

(78) The OIS driver **120** may include a plurality of unit driving parts to correct rotation with respect to an axis parallel to the optical axis O. The OIS driver **120** may include at least one unit driving part generating a Z-axis moment in the movable body **110**.

(79) For example, when current is applied to at least one of the first unit driving part **120-1**, the fourth unit driving part, the sixth unit driving part **120-6**, or the seventh unit driving part, a moment in the +Z direction (direction coming out of the ground) may be generated in the movable body **110** by the attractive force between the driving yoke and the driving coil. For another example, when current is applied to at least one of the second unit driving part **120-2**, the third unit driving part, the fifth unit driving part, or the eighth unit driving part, a moment in the -Z direction (the direction entering the ground) may occur in the movable body **110** by the attractive force between the driving yoke and the driving coil.

(80) In an example, the unit driving part may be disposed adjacent to a corner of the movable body **110**. The movable body **110** includes a first side surface **113b-1** and a third side surface **113b-3** extending in different directions from a first corner **113a-1**, respectively. The first unit driving part **120-1** is disposed on the first side surface **113b-1**, to be close to the first corner **113a-1**, and the fifth unit driving part is disposed on the third side surface **113b-3**, to be close to the first corner **113a-1**. The movable body **110** includes the first side surface **113b-1** and the fourth side surface **113b-4** extending in different directions from a second corner **113a-2**, respectively. The second unit driving part **120-2** is disposed on the first side surface **113b-1**, to be close to the second corner

**113a-2**, and the seventh unit driving part **120-2** is disposed on the fourth side surface **113b-4**, to be close to the second corner **113b-4**. The movable body **110** includes the second side surface **113b-2** and the third side surface **113b-3** extending in different directions from the third corner **113a-3**, respectively. The third unit driving part **120-3** is disposed on the second side surface **113b-2**, to be close to the third corner **113a-3**, and the sixth unit driving part **120-6** is disposed on the third side surface **113b-3**, to be close to the third corner **113a-3**. The movable body **110** includes the second side surface **113b-2** and the fourth side surface **113b-4** extending in different directions from the fourth corner **113a-4**, respectively. The fourth unit driving part **120-4** is disposed on the second side surface **113b-2**, to be close to the fourth corner **113a-4**, and the eighth unit driving part **120-4** is disposed on the fourth side surface **113b-4**, to be close to the fourth corner **113a-4**.

(81) In one or more examples, being disposed close to the corner may indicate that the unit driving part is spaced apart from the optical axis O when viewed from the side. For example, when viewed in the X direction, the first unit driving part **120-1** may be disposed at a position away from the optical axis O in the +Y direction. Alternatively, when viewed in the Y direction, the fifth unit driving part **120-5** may be disposed at a position away from the optical axis O in the -X direction. Accordingly, the unit driving part may generate a moment in the direction parallel to the optical axis O in the movable body **110**.

(82) The arrangement or number of the unit driving parts illustrated in FIG. 4 is merely an example, and the one or more examples are not limited thereto. For example, additional unit driving parts other than the unit driving parts illustrated in FIG. 4 may be provided. As another example, a portion of the unit driving parts illustrated in FIG. 4 may be omitted.

(83) Referring to FIG. 4, the driving yoke **121** may be configured so that it does not interfere with the corresponding driving coil **122** when the movable body **110** rotates. In an example, a surface of the driving yoke **121**, opposite to the driving coil **122**, may be convex. The thickness of the driving yoke **121** may decrease from a central portion **121a** to both ends **121b**. Since the driving yoke **121** is provided to be convex, the rotation range of the movable body **110** may be increased.

(84) For example, the opposite surface of the driving yoke **121** to the driving coil **122** may include an inclined surface **121c** extending from the central portion **121a** to both ends **121b**. Referring to the enlarged view of the upper right of FIG. 4, the driving yoke **121** and the driving coil **122** face in the Y direction perpendicular to the optical axis O, and a distance d1 between the central portion **121a** of the driving yoke **121** and the driving coil **122** in the Y direction may be shorter than a distance d2 between an end **121b** of the driving yoke **121** and the driving coil **122** in the Y direction.

(85) 2.3. Movement

(86) 2.3.1. Translation

(87) FIGS. 5A to 5D illustrate the movement of the movable body **110** based on the OIS driver **120** of FIG. 4.

(88) Referring to FIG. 5A, when current is applied to the first unit driving part **120-1** and the second unit driving part **120-2**, a force in the direction of the arrow is applied to the movable body **110**, which causes the movable body **110** to move in the -X direction. Referring to FIG. 5B, when a current is applied to the third unit driving part **120-3** and the fourth unit driving part **120-4**, a force in the direction of the arrow acts on the movable body **110**, which causes the movable body **110** to move in the +X direction. Referring to FIG. 5C, when current is applied to the fifth unit driving part **120-5** and the sixth unit driving part **120-6**, a force in the direction of the arrow is applied to the movable body **110**, which causes the movable body **110** to move in the +Y direction. Referring to FIG. 5D, when a current is applied to the seventh unit driving part **120-7** and the eighth unit driving part **120-8**, a force in the direction of the arrow acts on the movable body **110**, which causes the movable body **110** to move in the -Y direction.

(89) 2.3.2. Rolling

(90) FIGS. 6 and 7 illustrate rotation of the movable body **110** by the OIS driver **120** of FIG. 4.

(91) Referring to FIG. 6, when a current is applied to the first unit driving part **120-1**, the fourth unit driving part, the sixth unit driving part **120-6**, or the seventh unit driving part, the force of the respective driving parts in the direction of the arrow generates a +Z-direction moment in the movable body **110**, which may rotate the movable body **110** counterclockwise with respect to the fixed body.

(92) Referring to FIG. 7, when current is applied to the second unit driving part **120-2**, the third unit driving part, the fifth unit driving part, or the eighth unit driving part, the force of the respective driving parts in the direction of the arrow generates -Z direction moment in the movable body **110**, which may rotate the movable body **110** clockwise with respect to the fixed body.

(93) 2.5. Flexible Substrate Deformation

(94) FIGS. **8A** to **8D** illustrate deformation of the substrate **140** according to the movement of the movable body **110**, in accordance with one or more embodiments.

(95) Referring to FIG. **8A**, when the movable body **110** moves in the -X direction, the floating part **141** of the substrate **140** also moves in the -X direction, and therefore, the first bridge **147** connecting the guide **146** and the fixed part **142** to each other may be deformed. Since the bridge elements **144** constituting the first bridge **147** have elasticity, the deformed first bridge **147** provides a restoring force to return the floating part **141** to the direction (e.g., the +X direction) opposite to the moving direction. Accordingly, when no current is applied to the OIS driver **120**, the floating part **141** moves in the -X direction.

(96) Referring to FIG. **8B**, when the movable body **110** moves in the +X direction, the floating part **141** of the substrate **140** also moves in the +X direction, and thus, the first bridge **147** connecting the guide **146** and the fixed part **142** to each other is deformed. Since the bridge elements **144** constituting the first bridge **147** have elasticity, the deformed first bridge **147** provides a restoring force to return the floating part **141** to the direction (e.g., the -X direction) opposite to the moving direction.

(97) Referring to FIG. **8C**, when the movable body **110** moves in the +Y direction, the floating part **141** of the substrate **140** also moves in the +Y direction, and thus, the second bridge **148** connecting the guide **146** and the fixed part **142** is deformed. Since the bridge elements **144** constituting the second bridge **148** have elasticity, the deformed second bridge **148** provides a restoring force to return the floating part **141** to the direction (e.g., the -Y direction) opposite to the moving direction.

(98) Referring to FIG. **8D**, when the movable body **110** moves in the -Y direction, the floating part **141** of the substrate **140** also moves in the -Y direction, and thus, the second bridge **148** connecting the guide **146** and the fixed part **142** is deformed. Since the bridge elements **144** constituting the second bridge **148** have elasticity, the deformed second bridge **148** provides a restoring force to return the floating part **141** to the direction (e.g., the +Y direction) opposite to the moving direction.

(99) Although the rotation of the movable body **110** is not described in FIGS. **8A** to **8B**, the substrate may provide a restoring force in the opposite direction according to the rotation of the movable body **110**. For example, when the movable body **110** rotates counterclockwise as illustrated in FIG. **6**, the bridge elements of the substrate are deformed to provide a clockwise restoring force to the movable body **110**. When the movable body **110** rotates in the clockwise direction as illustrated in FIG. **7**, the bridge elements of the substrate are deformed to provide a counterclockwise restoring force to the movable body **110**.

(100) 2.6. Mover Change

(101) FIGS. **9A** and **9B** illustrate a sensor holder **213** in a different form from that of FIG. **2**.

(102) Referring to FIG. **9A**, the sensor holder **213** may be disposed on the sensor substrate **112**. In an example, the sensor holder **213** includes a plate **213a** disposed on the sensor substrate **112**, and an extension **213b** that extends downward (e.g., in the -Z direction) from the edge of the plate **213a**. The extension **213b** faces the driving coil (e.g., the driving coil **122** of FIG. **2**) of the OIS



driver **120**, and the driving yoke (e.g., the driving yoke **121** of FIG. 2) of the OIS driver **120** may be seated on the extension **213b**. In another example, the driving yoke is mounted on the fixed body **130** and the driving coil may be mounted on the sensor holder **213**. In this example, the driving coil and/or the yoke (e.g., the yoke **123** in FIG. 2) may be seated on the extension **213b**. Compared with the sensor holder **213** of FIG. 2, the sensor holder **213** of FIG. 9A may be more advantageous in avoiding interference with a solder ball connecting the sensor substrate **112** and the substrate **140**. Additionally, when the sensor holder **213** is disposed on the upper side of the sensor substrate **112**, the thickness of the sensor holder **213** may be relatively freely increased, which may improve the mechanical rigidity of the sensor holder **213**.

(103) Referring to FIG. 9A, the image sensor **111** may be electrically connected to the sensor substrate **112** through conductive vias.

(104) Referring to FIG. 9B, the sensor holder **313** may be disposed on the sensor substrate **112**. In an example, the sensor holder **313** may include a plate **313a** disposed on the sensor substrate **112**, and an extension **313b** that extends downward (e.g., in the  $-Z$  direction) from the edge of the plate **313a**. The extension **313b** faces the driving coil (e.g., the driving coil **122** of FIG. 2) of the OIS driver **120**, and the driving yoke (e.g., the driving yoke **121** of FIG. 2) of the OIS driver **120** may be seated on the extension **313b**. In an example, the driving yoke may be mounted on the fixed body **130** and the driving coil may be mounted on the sensor holder **313**. In this example, the driving coil and/or the yoke (e.g., the yoke **123** in FIG. 2) may be seated on the extension **313b**. Compared with the sensor holder **313** of FIG. 2, the sensor holder **313** of FIG. 9B may be more advantageous in avoiding interference with the solder ball connecting the sensor substrate **112** and the substrate **140**. Additionally, when the sensor holder **313** is disposed on the upper side of the sensor substrate **112**, the thickness of the sensor holder **313** may be relatively freely increased, which may improve the mechanical rigidity of the sensor holder **313**.

(105) Referring to FIG. 9B, the image sensor **111** may be directly mounted on the sensor substrate **112**. Accordingly, the sensor holder **313** may include a through portion **313c** in a portion corresponding to the image sensor **111**. The image sensor **111** is seated on the sensor substrate **112**, and a terminal of the image sensor **111** and a terminal of the sensor substrate **112** may be connected to each other through wire bonding.

(106) As set forth above, according to an example, the camera may provide an effective optical image stabilization operation even with a small amount of power. Alternatively, in an example, the effect of a magnetic field of an actuator driving the image sensor on an electronic component disposed outside the camera may be eliminated or significantly reduced.

(107) While this disclosure includes specific examples, it will be apparent to one of ordinary skill in the art, after an understanding of the disclosure of this application, that various changes in form and details may be made in these examples without departing from the spirit and scope of the claims and their equivalents. The examples described herein are to be considered in a descriptive sense only, and not for purposes of limitation. Descriptions of features or aspects in each example are to be considered as being applicable to similar features or aspects in other examples. Suitable results may be achieved if the described techniques are performed in a different order, and/or if components in a described system, architecture, device, or circuit are combined in a different manner, and/or replaced or supplemented by other components or their equivalents. Therefore, the scope of the disclosure is defined not by the detailed description, but by the claims and their equivalents, and all variations within the scope of the claims and their equivalents are to be construed as being included in the disclosure.

## Claims

1. A sensor shifting module, comprising: a fixed body; a movable body, movably disposed inside the fixed body, and comprising an image sensor having an imaging plane oriented in an optical axis

direction; and a driving unit, configured to move the movable body in a direction, perpendicular to the optical axis direction, with respect to the fixed body, and configured to rotate the movable body about the optical axis direction, wherein the driving unit comprises driving coils coupled to one of the fixed body and the movable body, and driving yokes coupled to the other one of the fixed body and the movable body, wherein parallel surfaces of the driving yokes and the driving coils face each other in a direction perpendicular to the optical axis direction, wherein, when a current is applied to the driving coils, the movable body is configured to move in a direction perpendicular to the optical axis direction based on an electromagnetic interaction between each of the driving coils and each of the driving yokes, or is configured to rotate about the optical axis direction, and wherein a surface of the driving yokes, disposed opposite to the driving coils, comprises an inclined surface that extends from a central portion of the driving yokes to ends of the driving yokes.

2. The module of claim 1, wherein the movable body has four side surfaces which form a quadrangle, and the driving coils or the driving yokes are disposed adjacent to ends of the four side surfaces.

3. The module of claim 1, wherein the driving unit comprises a first unit driving part, a second unit driving part, a third unit driving part and a fourth unit driving part, each comprising a driving coil of the driving coils and a driving yoke of the driving yokes that are configured to move each of the first unit driving part, the second unit driving part, the third unit driving part and the fourth unit driving part in a first direction, perpendicular to the optical axis direction, and respectively face the first direction, and wherein the first unit driving part and the second unit driving part are spaced apart from each other on a first side surface of the movable body, and the third unit driving part and the fourth unit driving part are spaced apart from each other on a second side surface of the movable body, the first side and the second side disposed in opposite directions to each other.

4. The module of claim 3, wherein the image sensor is disposed between the first unit driving part and the second unit driving part when viewed in the first direction.

5. The module of claim 3, wherein the first unit driving part and the third unit driving part are arranged in the first direction, and the second unit driving part and the fourth unit driving part are arranged in the first direction.

6. The module of claim 1, wherein the movable body comprises a first side surface and a third side surface that extend in different directions from a corner of the movable body, and the driving unit comprises a first unit driving part and a fifth unit driving part disposed adjacent to a corner on the first side surface and the third side surface, respectively, wherein the first unit driving part comprises a first driving coil of the driving coils and a first driving yoke of the driving yokes opposed in a first direction, perpendicular to the optical axis direction, and the fifth unit driving part comprises a fifth driving coil of the driving coils and a fifth driving yoke of the driving yokes opposed in a second direction, perpendicular to the optical axis direction, the first direction and the second direction intersecting each other.

7. The module of claim 1, wherein a surface of each of the driving yokes, respectively disposed opposite to each of the driving coils, is convex.

8. The module of claim 7, wherein the driving yokes and the driving coils are disposed opposite to each other in a first direction, perpendicular to the optical axis direction, and a distance in the first direction from a central portion of at least one of the driving yokes to at least one of the driving coils is shorter than a distance in the first direction from a first end and a second end of the at least one of the driving yokes to the at least one driving coils.

9. The module of claim 1, wherein each of the driving yokes is a soft magnetic material.

10. The module of claim 1, wherein the driving unit further comprises a first yoke disposed on a first side of one of the driving coils, wherein the one of the driving coils is disposed between one of the driving yokes and the first yoke.

11. The module of claim 1, further comprising a substrate that mechanically connects the movable

body to the fixed body, and is configured to deform based on a movement of the movable body with respect to the fixed body.

12. The module of claim 11, wherein the substrate comprises electric traces electrically connected to the image sensor.

13. The module of claim 12, wherein the substrate comprises a floating part fixedly coupled to the movable body, a fixed part fixedly coupled to the fixed body, and a support part that interconnects the floating part and the fixed part, wherein the support part comprises a plurality of bridges that embed the electric traces therein.

14. The module of claim 13, wherein the support part comprises a guide disposed between the floating part and the fixed part, and is connected to the floating part and the fixed part through the plurality of bridges.

15. The module of claim 14, wherein the plurality of bridges comprise first bridges that extend in a first direction, perpendicular to the optical axis direction, from the floating part to the guide, and second bridges which extend from the guide to the fixed part in a second direction, perpendicular to the optical axis direction, the first direction and the second direction intersecting each other.

16. The module of claim 1, wherein the driving unit comprises a position sensor disposed on one of the fixed body and the movable body, and a sensing magnet disposed on another of the fixed body and the movable body and facing the position sensor in the optical axis direction.

17. A camera module, comprising: a lens module comprising at least one lens; and a sensor shifting module, wherein the sensor shifting module comprises: a fixed body; a movable body movably disposed inside the fixed body, and including an image sensor oriented in an optical axis direction; a substrate that mechanically connects the movable body to the fixed body, and is configured to deform based on a movement of the movable body with respect to the fixed body; and a driving unit configured to move the movable body in a direction, perpendicular to the optical axis direction, with respect to the fixed body, and rotate the movable body about the optical axis direction, wherein the driving unit comprises a driving coil coupled to one of the fixed body and the movable body, and a driving yoke coupled to the other one of the fixed body and the movable body, and wherein parallel surfaces of the driving yoke and the driving coil face each other in a direction perpendicular to the optical axis direction, and a space between the driving yoke and the driving coil is an air gap, and wherein a surface of the driving yoke, disposed opposite to the driving coil, comprises an inclined surface that extends from a central portion of the driving yoke to ends of the driving yoke.

18. The camera module of claim 17, wherein the driving yoke is a soft magnetic material.

19. The camera module of claim 17, wherein the driving unit comprises a first unit driving part, a second unit driving part, a third unit driving part and a fourth unit driving part, each comprising a driving coil and a driving yoke that are configured to move each of the first unit driving part, the second unit driving part, the third unit driving part, and the fourth unit driving part in a first direction, perpendicular to the optical axis direction, and respectively facing the first direction, wherein the first unit driving part and the second unit driving part are spaced apart from each other on a first side surface of the movable body, and the third unit driving part and the fourth unit driving part are spaced apart from each other on a second side surface of the movable body, the first side surface and the second side surface being in opposite directions to each other.

---