

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12389286
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Kang; Minhoo et al.

Apparatus and method for switching communication interface in wireless communication system

Abstract

According to an embodiment of the disclosure, an operating method of an electronic device in a wireless communication system includes: establishing a wireless communication connection for transmitting and receiving data to and from an access point in a first communication method; receiving a state detection message from the access point; identifying an internal state of the electronic device in response to the state detection message being received; and determining whether to switch a communication interface, based on the identified internal state, and the internal state includes a received signal strength indicator (RSSI) value of the wireless communication connection, information regarding whether a network switching mode of the electronic device is enabled, information regarding whether an application related to the data is enabled, and/or information regarding use of the data.

Inventors: Kang; Minhoo (Gyeonggi-do, KR), Nam; Chounjong (Gyeonggi-do, KR), Lim; Junhak (Gyeonggi-do, KR)

Applicant: Samsung Electronics Co., Ltd. (Gyeonggi-do, KR)

Family ID: 80118255

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 17/861357

Filed: July 11, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220345966 A1	Oct. 27, 2022

Foreign Application Priority Data

KR	10-2020-0097524	Aug. 04, 2020
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2021/010264 20210804 PENDING child-doc US 17861357

Publication Classification

Int. Cl.: **H04W36/00** (20090101); **H04W76/10** (20180101); H04W36/30 (20090101);
H04W36/36 (20090101)

U.S. Cl.:

CPC **H04W36/0058** (20180801); **H04W76/10** (20180201); H04W36/302 (20230501);
H04W36/362 (20230501)

Field of Classification Search

CPC: H04W (36/0058); H04W (76/10); H04W (36/302); H04W (36/362); H04W (48/20);
H04W (76/30); H04W (84/12); H04W (88/06); H04W (48/16); H04L (43/0817); H04L
(43/0876); H04L (43/16); H04L (43/065)

USPC: 370/331

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9008045	12/2014	Srivastava et al.	N/A	N/A
10206154	12/2018	Ganesan	N/A	N/A
2005/0255847	12/2004	Han et al.	N/A	N/A
2012/0163344	12/2011	Bakthavathsalu et al.	N/A	N/A
2012/0208540	12/2011	Kim	455/436	H04W 36/0094
2015/0131460	12/2014	Sridhara	370/252	H04W 48/20
2015/0289183	12/2014	Iimori	370/331	H04W 36/302
2016/0020890	12/2015	Sirotkin	370/352	H04W 76/22
2016/0360489	12/2015	Boodannavar	N/A	H04B 7/0413
2016/0373989	12/2015	Tinnakornsrisuphap et al.	N/A	N/A
2019/0090171	12/2018	Yoon et al.	N/A	N/A
2019/0166524	12/2018	Mohamed et al.	N/A	N/A
2020/0077324	12/2019	Choi et al.	N/A	N/A
2021/0204175	12/2020	Rangaraju	N/A	H04W 12/037

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

103079286	12/2012	CN	N/A
2946594	12/2014	EP	N/A
10-0643766	12/2005	KR	N/A
10-1594875	12/2015	KR	N/A
10-2019-0007104	12/2018	KR	N/A
10-2023402	12/2018	KR	N/A

OTHER PUBLICATIONS

European Search Report dated Nov. 22, 2023. cited by applicant

Primary Examiner: Yao; Kwang B

Assistant Examiner: Bokhari; Syed M

Attorney, Agent or Firm: Cha & Reiter, LLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is continuation of International Application No. PCT/KR2021/010264 filed on Aug. 4, 2021, which claims priority to Korean Patent Application No. 10-2020-0097524, filed on Aug. 4, 2020, in the Korean Intellectual Property Office, the disclosure of which is herein incorporated by reference in its entirety.

BACKGROUND

Field

(1) the present disclosure relates generally to a wireless communication system, and for example, to an apparatus and a method for switching a communication interface.

Description of Related Art

(2) Various services and functions provided through an electronic device, for example, a portable electronic device such as a smart phone, are gradually increasing. The electronic device may exchange data with another electronic device through a wireless network. For example, the wireless network may include cellular communication done via a base station or a wireless local area network (WLAN) (or Wi-Fi communication) configured using an access point (AP). In the electronic device connected to the access point and the wireless network, the state (e.g., communication quality) of the wireless network may change as the electronic device moves.

SUMMARY

(3) When an electronic device with an established wireless connection with an access point (AP) moves and gets out of coverage of the access point, the electronic device should determine whether to discover another access point or whether to switch its wireless communication interface to cellular communication, and may have a problem where the quality of the wireless communication service that the user receives is degraded due to time delay caused during that process.

(4) According to an aspect of the disclosure, an operating method of an electronic device in a wireless communication system may include: establishing a wireless communication connection for transmitting and receiving data to and from an access point in a first communication method; receiving a state detection message from the access point; identifying a communication state of the electronic device in response to the state detection message being received; and determining whether to switch a communication interface, based on the identified communication state, and the communication state may include a received signal strength indicator (RSSI) value of the wireless communication connection, information regarding whether a network switching mode of the

electronic device is enabled, or information regarding whether an application related to the data is enabled.

(5) According to an aspect of the disclosure, an apparatus of an electronic device may include: a communication unit; and at least one controller electrically connected with the communication unit, and the at least one controller may be configured to: establish a wireless communication connection for transmitting and receiving data to and from an access point in a first communication method; receive a state detection message from the access point; identify a communication state of the electronic device in response to the state detection message being received; and determine whether to switch a communication interface, based on the identified communication state, and the communication state may include at least one of a received signal strength indicator (RSSI) value of the wireless communication connection, information regarding whether a network switching mode of the electronic device is enabled, or information regarding whether an application related to the data is enabled.

(6) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 illustrates a block diagram of an electronic device in a network environment according to an embodiment of the disclosure;

(3) FIG. 2 illustrates a communication interface switching process in a wireless communication system according to an embodiment of the disclosure;

(4) FIG. 3 illustrates a configuration of an electronic device in a wireless communication system according to an embodiment of the disclosure;

(5) FIG. 4 illustrates switching of a communication interface in a conventional wireless communication system;

(6) FIG. 5 illustrates a flowchart for an operation of an electronic device for switching a communication interface in a wireless communication system according to embodiments of the disclosure;

(7) FIG. 6 illustrates a flowchart for a communication state detection operation of an electronic device according to an embodiment of the disclosure;

(8) FIG. 7 illustrates a process of an access point for starting an operation of identifying a communication state of an electronic device in a wireless communication system according to an embodiment of the disclosure;

(9) FIG. 8 illustrates operations related to the identification of the communication state of the electronic device in the wireless communication system according to an embodiment of the disclosure;

(10) FIG. 9 illustrates operations related to the identification of the communication state of the electronic device in the wireless communication system according to another embodiment of the disclosure; and

(11) FIG. 10 illustrates operations related to the identification of the communication state of the electronic device in the wireless communication system according to still another embodiment of the disclosure.

DETAILED DESCRIPTION

(12) Based on the above-described discussion, certain embodiments of the disclosure may provide

an apparatus and a method for switching communication networks based on the communication quality between the electronic device and the access point in a wireless communication system.

(13) Terms used in the present disclosure are used only to describe specific embodiments, and may not be intended to limit the scope of other embodiments. The singular expression may include the plural expression unless the context clearly dictates otherwise. Terms used herein, including technical or scientific terms, may have the same meanings as commonly understood by one of ordinary skill in the art described in the present disclosure. Terms defined in a general dictionary among terms used in the present disclosure may be interpreted as having the same or similar meaning as the meaning in the context of the related art, and unless explicitly defined in the present disclosure, not interpreted as ideal or excessively formal meanings. In some cases, even terms defined in the present disclosure cannot be construed to exclude embodiments of the present disclosure. In various embodiments of the present disclosure described below, a hardware access method will be described as an example. However, since various embodiments of the present disclosure include technology using both hardware and software, various embodiments of the present disclosure do not exclude a software-based approach.

(14) Hereinafter, the instant disclosure generally describes techniques for reducing a delay experienced by the user by reducing time required to switch a communication network in a wireless communication system, through an apparatus and a method for switching the communication network based on communication quality between an electronic device and an access point in the wireless communication system.

(15) In the following description, a physical channel and a signal may be used interchangeably with data or a control signal. For example, a physical downlink shared channel (PDSCH) is a term that refers to a physical channel through which data is transmitted, but the PDSCH may also be used to refer to data. That is, in the present disclosure, an expression “transmitting a physical channel” may be interpreted equivalently to an expression “transmitting data or a signal through a physical channel.” Hereinafter, in the present disclosure, higher signaling may refer to a signal transmission method in which data from a base station is transmitted to an electronic device using a downlink data channel of a physical layer or from an electronic device to the base station using an uplink data channel of a physical layer. Upper signaling may be understood as radio resource control (RRC) signaling or media access control (MAC) control element (CE). In addition, various embodiments of the present disclosure describe various embodiments using terms used in some communication standards (e.g., 3rd generation partnership project (3GPP)), but this is only an example for description. Various embodiments of the present disclosure may be easily modified and applied in other communication systems.

(16) FIG. 1 is a block diagram illustrating an electronic device **101** in a network environment **100** according to certain embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input device **150**, a sound output device **155**, a display device **160**, an audio module **170**, a sensor module **176**, an interface **177**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments, at least one (e.g., the display device **160** or the camera module **180**) of the components may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments, some of the components may be implemented as single integrated circuitry. For example, the sensor module **176** (e.g., a fingerprint sensor, an iris sensor, or an illuminance sensor) may be implemented as embedded in the display device **160** (e.g., a display).

(17) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **120** may load a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), and an auxiliary processor **123** (e.g., a graphics processing unit (GPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. Additionally or alternatively, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(18) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display device **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**.

(19) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(20) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(21) The input device **150** may receive a command or data to be used by other component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input device **150** may include, for example, a microphone, a mouse, a keyboard, or a digital pen (e.g., a stylus pen).

(22) The sound output device **155** may output sound signals to the outside of the electronic device **101**. The sound output device **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record, and the receiver may be used for an incoming call. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(23) The display device **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display device **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display device **160** may include touch circuitry adapted to detect a touch, or sensor circuitry (e.g., a pressure sensor) adapted to measure the intensity of force incurred by the touch.

(24) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input device **150**, or output the sound via the sound output device **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(25) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state.

According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(26) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(27) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**). According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(28) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(29) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(30) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(31) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(32) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a cellular network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(33) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g.,

the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., PCB). According to an embodiment, the antenna module **197** may include a plurality of antennas. In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(34) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(35) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** and **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, or client-server computing technology may be used, for example.

(36) The electronic device **101** may provide an ultra-low latency service using, for example, distributed computing or mobile edge computing. In another embodiment, the external electronic device **104** may include an Internet of things (IoT) device. The server **108** may be an intelligent server using machine learning and/or neural networks. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to an intelligent service (e.g., smart home, smart city, smart car, or health care) based on 5G communication technology and IoT-related technology.

(37) FIG. 2 illustrates a communication interface switching process in a wireless communication system according to an embodiment of the disclosure.

(38) Referring to FIG. 2, in certain embodiments of the disclosure, the apparatus or method for switching a communication interface in a wireless communication system may be configured based on a relationship between the electronic device (for example, the electronic device **101** of FIG. 1) and the access point **210**. The access point **210** may form a network for providing a wireless communication service to the electronic device. The access point **210** may communicate with the electronic device **101** in a predetermined region (for example, a coverage area) formed with reference to the access point **210**. Communication between the access point **210** and the electronic device **101** may be achieved by transmitting and receiving signals or data, and may be performed through at least one communication interface (for example, the communication module **190** of FIG. 1). The access point **210** may be related to one communication interface. According to certain embodiments, the communication interface may include a short-range communication network (for

example, Bluetooth, wireless fidelity (Wi-Fi) direct or infrared data association (IrDA)), and a cellular communication network (for example, a legacy cellular network, 5G network, next-generation communication network). The communication interface according to an embodiment may be understood as meaning all interfaces for transmitting and receiving data or signals. For example, changing the communication interface may refer to changing one of the short-range communication network and/or the cellular communication network to the other one while the electronic device **101** is performing communication with an external electronic device (for example, the electronic device **102**, the electronic device **104**, or the server **108** of FIG. **1**) using one of the short-range communication network and/or the cellular communication network. The access point **210** shown in FIG. **2** may be an access point **210** that provides the Wi-Fi network. In this case, the access point **210** may be understood as a device providing Wi-Fi. In addition, a first radius **250a** formed with reference to the corresponding access point **210** may indicate the region where the access point **210** can smoothly provide a wireless communication service. For example, the first radius **250a** formed with reference to the access point **210** may be set based on the signal strength or the transmission speed set at the access point **210** and/or the electronic device **101**. According to an embodiment, when the electronic device **101** is located within the first radius **250a**, the distance between the access point **210** and the electronic device **101** may be variable. For example, the distance between the access point **210** and the electronic device **101** may vary according to the position and/or performance of an antenna of the access point **210** and/or the electronic device **101**.

(39) The first radius **250a** formed with reference to the corresponding access point **210** may indicate a service region of the access point **210**. The access point **210** forming the service region may form a communication network with at least one electronic device (for example, the electronic device **101**) existing within the service region, and may transmit and receive data to and from the electronic device. The service region may be understood as a certain region where wireless communication between the access point **210** and the electronic device **101** is smoothly performed. Accordingly, when the electronic device **101** is out of the service region, wireless communication such as transmission and reception of data, or communication efficiency may be degraded. That is, the region defined by the first radius **250a** may be where wireless communication between the electronic device **101** and the access point **210** is smoothly performed, and the region defined by a second radius **250b** may be where the electronic device **101** is out of the service region, and communication efficiency is degraded and smooth wireless communication is not performed. A predetermined threshold value may determine the first radius. When the electronic device **101** receives a signal greater than or equal to a threshold value from the access point **210**, a region where the corresponding electronic device **101** is located may be a region within the first radius **250a**, that is, the service region. In addition, when the electronic device **101** receives a signal less than the threshold value from the access point **210**, a region where the corresponding electronic device **101** is located may be a region that is out of the first radius **250a** and within the second radius **250b**. At least one electronic device (for example, the electronic device **101**) may exist within the service region, and the at least one electronic device (for example, the electronic device **101**) may perform wireless communication with the access point **210** while existing in the service region. For example, the access point **210** and electronic devices (for example, the electronic device **101**) existing within the service region may constitute a wireless communication system. In an embodiment, at least one electronic device (for example, the electronic device **101**) may be installed to be fixed within the service region, or may move in or out of the service region. In another example, at least one (for example, the electronic device **101**) of a plurality of electronic devices may move randomly according to user's intent, behavior pattern or an environment, and this operation may be performed within a range that is not predictable by the access point **210**. Communication quality of at least one electronic device (for example, the electronic device **101**) existing within the service region may vary according to a distance from the access point **210**.

When the electronic device (for example, the electronic device **101**) is located at a position **230a** close to the access point **210**, the access point **210** may provide a wireless communication service of good quality, and, when the electronic device (for example, the electronic device **101**) is located at a position **230b** far from the access point **210**, the access point **210** may provide a wireless communication service of poor quality. The close position **230a** and the far position **230b** may be physical positions, and there may be threshold values for determining these positions. There may be a difference in wireless communication quality according to the physical position between the electronic device (for example, the electronic device **101**) and the access point **210**, but it may be assumed that at least one electronic device (for example, the electronic device **101**) existing within the service region is located at a distance corresponding to smooth wireless communication service. For example, the electronic device (for example, the electronic device **101**) existing within the service region may communicate with the access point **210** with a signal greater than or equal to a designated threshold value or at a speed higher than or equal to a designated threshold value. When the electronic device **101** moves due to an external factor, gets out of the service region, and is located in another region (for example, a region larger than or equal to the first radius **250a** and within the second radius **250b** larger than the first radius **250a**), quality of a wireless communication service performed between the electronic device **101** and the access point **210** may be lower than quality of the wireless communication service performed between the electronic device **101** and the access point **210** within the service region. In addition, as the electronic device approaches the boundary of the service region, smooth communication between the electronic device **101** and the access point **210** may become difficult even if the electronic device **101** is not out of the service region. Smooth communication between the electronic device **101** and the access point **210** becoming difficult may refer to a state in which the access point **210** does not transmit a sufficient quantity of data requested by the electronic device **101** for a given time period.

(40) Whether smooth communication service is possible may be determined based on a pre-set threshold value. When the quantity of data transmitted and received between the electronic device **101** and the access point **210** does not reach the pre-defined threshold value, the electronic device **101** or the access point **210** may determine that smooth wireless communication service is not provided. In this case, the threshold value may be set differently according to the type of wireless communication service and/or application. For example, in the case of a high-quality media streaming service, the threshold value may be set to be higher than that in the case for text messaging or photo transmission service.

(41) When it is determined that it is difficult to provide smooth wireless communication service in the electronic device **101** or the access point **210**, the electronic device **101** may discover another access point according to its own determination or by referring to information received from the access point **210**. The process of discovering another access point may be performed when the electronic device **101** exists within the service region but approaches the boundary of the service region, or when the electronic device **101** is out of the service region. The electronic device **101** out of the service region may discover another access point that provides service in the region **250b**. On the assumption that the access point **210** provides Wi-Fi communication, the process of discovering another access point may be performed through an operation of scanning another access point. The electronic device **101** out of the service region may identify the number of other neighboring access points, positions, identification information, and/or signal strength, by performing the discovering process (for example, the operation of scanning). According to an embodiment, even when the electronic device **101** is out of the service region of the access point **210**, the electronic device **101** may maintain the connection with the access point **210**. In this case, the electronic device **101** may transmit information acquired through the discovering process to the access point **210**. Since the electronic device **101** may not exactly know whether another connectable access point is, the access point **210** may receive the information acquired by the electronic device **101** through the discovering process from the electronic device **101**, and may

confirm whether another access point can be connected with the electronic device **101**. After the confirmation process, the access point **210** may recommend another access point that can provide better wireless communication service to the electronic device **101**. The recommendation may be included a request message transmitted to the electronic device **101**.

(42) FIG. 3 illustrates a configuration of an electronic device in a wireless communication system according to an embodiment of the disclosure. The configuration illustrated in FIG. 3 may be understood as a configuration of an electronic device **300**. The term “unit” or certain terms ending with suffixes “-er,” and “-or” used in the following description refer to a unit processing at least one function or operation, and may be implemented by hardware, software, or a combination of hardware and software. The electronic device **101** of FIG. 1, the electronic device **101** of FIG. 2, and the electronic device **300** of FIG. 3 may perform the same or similar functions.

(43) Referring to FIG. 3, the electronic device **300** may include a controller **310** (for example, the processor **120** of FIG. 1), a communication unit **330** (for example, the communication module **190** of FIG. 1), a storage **350** (for example, the memory **130** of FIG. 1). The communication unit **330** may perform functions for transmitting and receiving signals via a wireless channel. For example, the communication unit **330** may perform the function of converting between a baseband signal and a bit stream according to the physical layer standard of the system. For example, when transmitting data, the communication unit **330** may generate complex symbols by encoding and modulating a transmission bit stream. In addition, when receiving data, the communication unit **330** may restore a reception bit stream by demodulating and decoding a baseband signal. In addition, the communication unit **330** may up-convert a baseband signal into a radio frequency (RF) band signal, and then may transmit the signal via an antenna, and may down-convert an RF band signal received via an antenna into a baseband signal. For example, the communication unit **330** may include a transmission filter, a reception filter, an amplifier, a mixer, an oscillator, a digital-to-analogue converter (DAC), and/or an analogue-to-digital converter (ADC).

(44) In addition, the communication unit **330** may include a plurality of transmission and reception paths. Furthermore, the communication unit **330** may include at least one antenna array including a plurality of antenna elements. As far as hardware is concerned, the communication unit **330** may include a digital circuit and an analog circuit (for example, a radio frequency integrated circuit (RFIC)). Herein, the digital circuit and the analogue circuit may be implemented as a single package. In addition, the communication unit **330** may include a plurality of RF chains. Furthermore, the communication unit **330** may perform beamforming.

(45) In addition, the communication unit **330** may include different communication modules to process signals of different frequency bands. Furthermore, the communication unit **330** may include a plurality of communication modules to support a plurality of different wireless access technologies. For example, the different wireless access technologies may include Bluetooth low energy (BLE), wireless fidelity (Wi-Fi), Wi-Fi Gigabyte (WiGig), a cellular network (for example, long term evolution (LTE)). In addition, the different frequency bands may include a super high frequency (SHF) (for example, 2.5 GHz, 5 GHz, or 6 GHz) band, or a millimeter (mm) wave (for example, 60 GHz) band.

(46) The communication unit **330** may transmit and receive signals as described above. Accordingly, the entirety or a portion of the communication unit **510** may be referred to as a “transmitter,” “receiver,” or “transceiver.” In addition, in the following description, transmitting and receiving via a wireless channel may mean processing by the communication unit **330** as described above.

(47) The storage **350** may store data such as a basic program for the operation of the electronic device **300** (e.g. an operating system), an application program, configuration information, etc. The storage **350** may be a volatile memory, a nonvolatile memory, or a combination of a volatile memory and a nonvolatile memory. In addition, the storage **350** may provide stored data according to a request of the controller **310**.

(48) The controller **310** may control overall operations of the electronic device **300**. For example, the controller **310** may transmit and receive signals via the communication unit **330**. In addition, the controller **310** may write and read out data on or from the storage **350**. In addition, the controller **310** may perform functions of a protocol stack required by communication standards. To achieve this, the controller **310** may include at least one processor or microprocessor, or may be a portion of a processor. In addition, a portion of the communication unit **310** and the controller **310** may be referred to as a communication processor (CP). According to certain embodiments, the controller **310** may be included a band sharing system and may transmit control commands to respective devices constituting the band sharing system. Herein, the control command may be an instruction set or a code stored in the storage **350**, and may be an instruction/code at least temporarily resided in the controller **310**, or a storage space storing an instruction/code, or may be a portion of a circuitry constituting the controller **310**. The controller **310** may include a microprocessor or any suitable type of processing circuitry, such as one or more general-purpose processors (e.g., ARM-based processors), a Digital Signal Processor (DSP), a Programmable Logic Device (PLD), an Application-Specific Integrated Circuit (ASIC), a Field-Programmable Gate Array (FPGA), a Graphical Processing Unit (GPU), a video card controller, etc. In addition, it would be recognized that when a general purpose computer accesses code for implementing the processing shown herein, the execution of the code transforms the general purpose computer into a special purpose computer for executing the processing shown herein. Certain of the functions and steps provided in the Figures may be implemented in hardware, software or a combination of both and may be performed in whole or in part within the programmed instructions of a computer. No claim element herein is to be construed under the provisions of 35 U.S.C. § 112(f), unless the element is expressly recited using the phrase “means for.” In addition, an artisan understands and appreciates that a “processor” or “microprocessor” may be hardware in the claimed disclosure. Under the broadest reasonable interpretation, the appended claims are statutory subject matter in compliance with 35 U.S.C. § 101.

(49) According to certain embodiments, the controller **310** may continuously measure the received signal strength of an access point (for example, the access point **210** of FIG. 2), which is currently connected with the electronic device **300**, may determine whether to discover another access point by determining whether the electronic device **300** will be out of the service region, and accordingly, may determine whether to move to a Wi-Fi network of another access point or whether to change the communication interface to cellular communication, and may control to perform these operations.

(50) In addition, the controller **310** of the electronic device **300** may include a determination unit and an operation unit.

(51) According to an embodiment, the determination unit may determine which operation the controller **310** will perform, based on information received through the communication unit **330**. For example, the determination unit may determine which operation the controller **310** will perform, based on information stored in the storage **350**. According to an embodiment, the determination unit may determine whether an application processor (AP) is in a sleep (or suspend) state. The determination unit may determine whether an application installed in the electronic device **300** is executed.

(52) According to an embodiment, the determination unit may determine whether the application processor is in the sleep state. When the application processor is in the sleep state, an application related to wireless communication (for example, data transmission and reception) of the access point **210** may be disabled. When the application is disabled, it may be understood that the corresponding application is not executed or is executed in the background. For example, when the user executes another operation in the middle of transmitting and receiving data through an application for wireless communication, the determination unit may determine whether the application for wireless communication is executed in the background. That is, when the

application processor is in the sleep state, it may be understood that an application related to wireless communication is not executed or is executed in the background.

(53) According to an embodiment, the determination unit may determine whether an application installed in the electronic device **300** is used. Even when the installed application is used in the background, the determination unit may determine whether the user is not currently using the application, for example, when the display is turned off. Accordingly, the determination unit may determine whether an application related to transmission and reception of wireless data is used by the user. For example, the determination unit may identify whether an application for providing voice and/or video streaming service or cloud-based service (for example, a cloud game) is used in real time. In the case of a real-time video streaming service, the determination unit may determine that a corresponding application is not used when the screen is turned off. In the case of a voice streaming service, the determination unit may determine that a corresponding application is not used when a speaker is in a mute state.

(54) The determination unit may determine whether an application is in a sleep mode, based on at least one of an electronic device using pattern of the user, a history of using applications, a current data transmission and reception rate, and/or a type of data.

(55) According to an embodiment, the determination unit may identify whether data is currently used and the quantity of used data. For example, data may include data that is received from the access point and/or data that is transmitted to the access point in a state where a communication connection with the access point is maintained. For example, the quantity of used data may include the type of data or the size of data, and may be expressed as a quantity of data transmitted per second, or a total quantity of data transmitted and received after the connection with the access point is set. The electronic device **300** may periodically or intermittently update the information regarding whether data is used and the quantity of used data in the storage **350**.

(56) According to an embodiment, the determination unit may identify user preference. For example, the user preference may refer to user's preference for a specific communication interface. In an environment where there exist a plurality of communication interfaces for providing wireless communication service, history data of the communication interface used may be used to determine the user preference. For example, when the electronic device **300** and the access point (for example, the access point **210** of FIG. 2) maintain Wi-Fi connection, and it is determined that quality of the Wi-Fi connection is lower than a predetermined value, the determination unit may inquire of the user about whether to switch to cellular communication or whether to maintain the existing Wi-Fi connection, and may store data regarding the communication interface preferred by the user according to a response of the user to the inquiry. According to an embodiment, in order to establish data regarding the communication interface preferred by the user, the electronic device **300** may analyze user's data consumption habit, the environment where data is used, and/or information regarding the difference of normal connection quality of the cellular communication service used by the user from the Wi-Fi communication service. For example, the environment in which data is used may be implemented as environmental information regarding whether the region where the user is positioned smoothly provides cellular communication, and/or how fast the user moves.

(57) According to an embodiment, the electronic device **300** may periodically inquire of the user about which of Wi-Fi communication or cellular communication will be used to maintain a wireless communication connection, according to a change in the wireless communication environment, and may estimate user's preference by synthesizing data regarding user's response to the inquiry. The data regarding the user's preference may be expressed as numerical values, and may be updated in an external server (for example, the server **108** of FIG. 1) or may be stored in the storage **350** of the electronic device **300**.

(58) According to an embodiment, the determination unit may identify a cellular data plan of the user. For example, the cellular data plan may be understood as being related to the type of a cellular

service that is provided by a base station so as to allow the electronic device **300** of the user to use cellular communication. When a mobile operator, which provides the cellular communication service through the base station, provides restricted cellular data to the electronic device **300**, the electronic device **300** may monitor how much cellular data remains, and may store the result of monitoring in the storage **350**, and may allow the result to be used for operations of the operation unit. In this case, the remaining data may be understood as a quantity of data remaining until data usage defined by the cellular data plan of the user is reached. When the user uses cellular data in excess of defined data usage, the quantity of data used thereafter may incur additional fees. Therefore, the determination unit may monitor data usage and may provide relevant information to the user, and this information may be used for determining user preference. If remaining cellular data is 0, the user may be expected to prefer Wi-Fi communication over cellular communication, which may be used as a determination factor for performing a switching operation of a communication interface.

(59) According to an embodiment, the determination unit may identify information regarding mobility of the electronic device **300**.

(60) A network switching mode may be used to solve degradation of network quality caused by movement of the electronic device **300**, and it may be determined whether the user is moving by measuring network quality. However, there may be other factors that influence network quality in addition to movement of the electronic device **300**, and these factors may not be overcome by switching the communication interface. Therefore, in order to appropriately distinguish these factors and to switch a network as necessary, it may be required to identify information regarding the mobility of the electronic device **300** in real time. According to an embodiment, the electronic device **300** may identify an absolute position of the electronic device **300** or a relative position which is determined based on a relationship with an access point (for example, the access point **210** of FIG. 2), by using a sensor (for example, the sensor module **176** of FIG. 1) provided in the electronic device **300** or position information included in a signal transmitted from the electronic device **300**. In this case, the sensor may use a GPS device provided in the electronic device **300**.

(61) According to an embodiment, the determination unit may identify a Wi-Fi parameter. For example, the Wi-Fi parameter may refer to a performance parameter regarding a Wi-Fi connection between the access point (for example, the access point **210** of FIG. 2) and the electronic device **300**. The Wi-Fi parameter may be understood as including a parameter value regarding at least one element that may influence performance when Wi-Fi communication is used, such as a surrounding environment where the electronic device **300** is used, performance of the access point (for example, the access point **210** of FIG. 2), an installation position of the access point (for example, the access point **210** of FIG. 2), and/or the type of the communication module (for example, the communication unit **330**) mounted in the electronic device **300**. According to an embodiment, the determination unit may identify a plurality of parameters that may influence Wi-Fi communication, or may apply weights to various parameters.

(62) According to an embodiment, the determination unit may identify a cellular parameter. For example, the cellular parameter may be understood as including a parameter value regarding at least one element that may influence performance when cellular communication is used, such as the type of cellular communication provided by a base station, a cellular data plan to which the user subscribes, a surrounding environment where the electronic device is used by the user, or some other metric to measure the user's experience. According to an embodiment, the determination unit may identify a plurality of parameters that may influence cellular communication, or may apply weights to various parameters.

(63) According to an embodiment, the determination unit may determine which communication interface can result in the best performance of the electronic device **300**, by comparing the Wi-Fi parameter and the cellular parameter, and may transmit information regarding the determination to the operation unit or may instruct the operation unit.

(64) According to an embodiment, the operation unit may perform an operation based on information identified by the determination unit. For example, the operation may be disconnecting the Wi-Fi connection with the access point (for example, the access point **210** of FIG. 2) which is currently connected with the electronic device **300**, and switching the communication interface to cellular communication. In another example, the operation may be performing Wi-Fi roaming to another access point which is discovered by the electronic device **300**. According to an embodiment, the electronic device **300** may selectively perform the operation of performing Wi-Fi roaming to another access point which is searched nearby, or the operation of switching to cellular communication. In another example, the operation may be changing a threshold value of an application for managing a data bearer. The electronic device **300** may efficiently switch the network by adjusting the threshold value according to the surrounding environment or a situation of the user.

(65) FIG. 4 illustrates switching of a communication interface in a conventional wireless communication system.

(66) FIG. 4 discloses conventional operations done to switch the communication interface when the electronic device **101** is moving.

(67) When the electronic device **101** of the user moves while being connected with the access point **210**, which provides wireless communication service, communication quality of the electronic device **101** of the user may be changed according to the distance to the access point **210**. When the electronic device **101** is out of the maximum region of the access point **210** for providing smooth wireless communication service, or approaches the boundary of the maximum region, data transmission and reception efficiency between the electronic device **101** of the user and the access point **210** may be degraded, and the electronic device **101** may determine whether to discover another access point for providing better wireless communication service, or whether to switch to cellular communication. In this case, when the connection with the existing access point is maintained in the background, time required to determine whether to switch to another access point or to cellular communication may delay wireless communication and cause user inconvenience.

(68) When the user carrying the electronic device **101** gets out of a service region of the access point **210** currently connected with the electronic device **101**, communication quality that the user experiences may be degraded. When the Wi-Fi connection between the access point **210** and the electronic device **101** becomes weaker and smooth communication is impossible, the electronic device **101** may restart the communication connection by using cellular communication rather than the Wi-Fi connection. In addition, the electronic device **101** may discover another access point existing around the electronic device **101**, and, when quality of a communication connection service provided by the access point **210** found by discovering is better than quality of the communication connection service of the access point **210** currently connected, the electronic device **101** may perform roaming to the access point **210** that provides the better service quality.

(69) When the electronic device **101** exists within a service region (for example, the service region of FIG. 2) of the access point **210**, the electronic device **101** may receive Wi-Fi service of good quality. However, when the electronic device **101** gets out of the service region, connection quality of the Wi-Fi service that the electronic device **101** receives may be degraded. In this case, the electronic device **101** may switch the communication interface to cellular communication at the boundary of the service region. Switching of the communication interface may be performed upon receiving a switching request from the access point **210**.

(70) In this case, even when the electronic device **101** gets out of the service region, the Wi-Fi communication connection between the electronic device **101** and the access point **210** may not immediately be disconnected and the electronic device **101** may maintain the current connection with the access point **210** until the electronic device **101** determines to switch to the cellular communication. In this case, the connection between the access point **210** and the electronic device **101** may be maintained in the background. Accordingly, the electronic device **101** may receive low-

quality Wi-Fi service from the access point **210** until the electronic device **101** determines to discover better Wi-Fi or to switch to cellular communication. In general, the electronic device **101** may start the discovering procedure when the electronic device **101** reaches the boundary of the service region, and may determine to discover better Wi-Fi or to switch the communication interface to cellular communication. But even so, for example, 6-10 seconds may be required to disconnect the Wi-Fi communication connection with the current access point **210**. Accordingly, the electronic device **101** may maintain low-quality Wi-Fi connection for 6-10 seconds. In certain embodiments of the instant disclosure, processes for rapidly determining whether to disconnect the communication connection in order to reduce user inconvenience caused as described above are explained.

(71) FIG. 5 is a flowchart illustrating an operation of an electronic device **101** for switching a communication interface in a wireless communication system according to an embodiment of the disclosure.

(72) According to an embodiment, in operation **501**, the electronic device **101** may receive a state detection message from the access point **210**. The state detection may refer to detection of a communication state of the electronic device **101**, and for example, may refer to detection regarding whether a wireless communication state between the electronic device **101** and the access point **210** changes to the extent that the communication interface needs to be switched. The state detection message may be received in the form of a switching request. The access point **210** may refer to an access point **210** that currently maintains the connection with the electronic device **101**. The process of receiving the switching request may be performed when the electronic device **101** gets out of a service region (for example, the service region of FIG. 2) provided by the access point **210**, or approaches the boundary of the service region. Herein, the service region provided by the access point **210** may be understood as a threshold region in which wireless communication connection is smoothly achieved between the electronic device **101** and the access point **210**, and in this case, the threshold region may be associated with a volume of physical space. According to an embodiment, the access point **210** may detect the state of the electronic device **101** during a continuous communication process with the electronic device **101**, or may identify that the electronic device **101** moves farther away from the access point **210** or exists in a region where a smooth service is impossible, based on information provided from the electronic device **101**. According to another embodiment, the access point **210** may continuously, periodically receive information regarding movement of the electronic device **101** from the electronic device **101**, and accordingly, when the electronic device **101** currently exists in the service region, but is expected to get out of the service region after a predetermined time, the access point **210** may transmit the switching request to the electronic device **101**. Accordingly, when the electronic device **101** receives the switching request from the access point **210**, the electronic device **101** may detect that quality of the wireless communication service has been degraded or may be degraded.

(73) According to an embodiment, the switching request may include recommendation information that is determined by the access point **210**. For example, the recommendation information may include information regarding another access point that is connectable by the electronic device **101**. The connectable access point may be another access point that may provide a smooth wireless communication service to the electronic device **101**, and may refer to another access point whose service region includes the current position of the electronic device **101**, or whose service region includes a position to which the electronic device **101** is expected to move within a predetermined time.

(74) According to an embodiment, the recommendation information may be determined by the access point **210** based on information provided from the electronic device **101**. For example, the electronic device **101** may perform a searching operation and may transmit information regarding existence of another access point around the electronic device **101**, identification information, position, or the current position of the electronic device **101** to the access point **210**. The access

point **210** which acquires the information may generate recommendation information according to a pre-set criterion, based on the information provided from the electronic device **101**. According to an embodiment, the recommendation information may be included in the switching request message and may be transmitted. However, the message including the recommendation information is not limited to being transmitted as a switching request, and, as long as the message includes recommendation information for recommending, suggesting information on another access point to the electronic device, and information for instructing the electronic device **101** to determine whether to switch the communication interface, there is no limit to the form or method of the transmitted message.

(75) According to an embodiment, in operation **503**, the electronic device **101** may identify a communication state of the electronic device **101** in response to the state detection message being received from the access point **210**. For example, the communication state may refer to an internal state of the electronic device **101**, and may be understood as including a communication performance parameter of the electronic device and/or a received signal strength. In the following description, the internal state may refer to a state of internal software or hardware (whether a specific application is in a sleep mode) of the electronic device. The internal state and the communication state may be used interchangeably in the following description. For example, the process of the electronic device **101** identifying the internal state may be understood as an operation of identifying the type and the size of data transmitted and received between the electronic device **101** and the access point **210**, and/or a transmission time. In another example, the process of the electronic device **101** identifying the internal state may be understood as an operation of internally identifying a connection state with the access point **210**. In still another example, the process of identifying the internal state may be understood as an operation of identifying whether a processor which executes an application or a program connecting the electronic device **101** to the access point **210** is in sleep mode. In yet another example, the process of the electronic device **101** identifying the internal state may be understood as including a process of identifying whether a network switching mode is enabled in the electronic device **101**.

(76) According to an embodiment, the operation of the electronic device **101** identifying the communication state of the electronic device **101** may be started in response to the switching request being received from the access point **210**. According to another embodiment, the operation of the electronic device **101** identifying the internal state may be started in response to recommendation information being received from the access point **210**. However, the above-description does not limit the operation of identifying the internal state of the electronic device **101** to being determined depending on the received recommendation information. The operation of the electronic device **101** identifying the internal state of the electronic device **101** and performing a subsequent operation may be performed regardless of contents of the recommendation information transmitted from the access point **210**, or may be performed by referring to the recommendation information. Herein, the acquisition of the switching request including the recommendation information by the electronic device **101** may be understood as an operation for triggering the operation of the electronic device **101** identifying the internal state.

(77) According to an embodiment, in operation **505**, the electronic device **101** may determine whether to switch a network in response to the communication state being identified. For example, the electronic device **101** may identify the internal state of the electronic device **101**, and may determine whether to disconnect the connection with the access point **210**, based on the identified information. In another example, the electronic device **101** may determine whether to maintain the connection with the access point **210**, based on the identified information. When the electronic device **101** determines to disconnect the connection between the access point **210** and the electronic device **101**, the electronic device **101** may determine whether to perform roaming to another access point or whether to switch to cellular communication, as a subsequent operation. The electronic device **101** may identify a received signal strength indication (RSSI) with the access point **210**

currently connected thereto, using the internal state information of the electronic device **101**. The electronic device **101** may compare the identified RSSI and a pre-defined threshold value, and may determine whether to switch the network according to the result of comparing. The pre-defined threshold value may be understood as an RSSI that enables smooth wireless communication between the access point **210** and the electronic device **101**. The pre-defined threshold value may be referred to as a threshold RSSI. The threshold RSSI may be differently determined based on at least one of the type of the electronic device **101**, the state of the electronic device **101** as described herein, the type of the content to be transmitted, data to be transmitted, and/or identification information of the access point **210** currently connected with the electronic device. The threshold RSSI may be a value pre-defined by the user or may be a value determined according to information received from an external device.

(78) The electronic device **101** according to certain embodiments may identify whether an application processor of the electronic device **101** is in sleep mode, through the process of identifying the internal state of the electronic device **101**. For example, the sleep mode may refer to the mode in which a processor executing a corresponding application goes into idle state in order to efficiently utilize resources. The application processor may refer to a processor that executes an application related to data transmission performed between the access point **210** and the electronic device **101**. When data transmission between the electronic device **101** and the access point **210** is in the idle state, substantial data transmission may not be performed even if the electronic device **101** is out of the service region of the access point **210**, and accordingly, the electronic device may maintain the connection with the currently connected access point **210** without having to discover another access point or switch into cellular communication.

(79) The electronic device **101** according to certain embodiments may further perform a process of identifying whether a network switching mode of the electronic device **101** is enabled. For example, the network switching mode may refer to a mode in which it is possible to switch the communication interface from Wi-Fi communication to cellular communication or from cellular communication into Wi-Fi communication. When the network switching mode is enabled, the electronic device **101** may switch the communication interface according to a change in an external environment or a pre-defined criterion, and, when the corresponding mode is disabled, the communication interface may be only switched by a user input. The process of identifying whether the network switching mode is enabled may precede the process of identifying a current RSSI or identifying whether the application processor of the electronic device **101** is in sleep mode.

(80) According to certain embodiments, the electronic device **101** may receive the switching request from the access point **210** currently connected therewith, and may identify the internal state in response to the reception. Herein, the internal state may include a connection state between the electronic device **101** and the access point **210**, information regarding whether the application processor is in the sleep mode, information regarding whether the electronic device **101** supports the network switching mode or whether the network switching mode of the electronic device **101** is currently enabled. In addition, the internal state may include information regarding whether data is currently used by the user and data usage, user preference, the cellular data plan, mobility information of the electronic device, and/or a value of the result of comparing a Wi-Fi parameter and a cellular parameter. When the internal state is identified and a specific condition is satisfied, the electronic device **101** may disconnect or maintain the connection with the access point **210** currently connected therewith. When the electronic device **101** disconnects the connection with the access point **210** currently connected therewith, the electronic device **101** may perform a subsequent operation, that is, an operation of discovering another neighboring access point, and an operation of, when quality of a connection between another access point and the electronic device **101** is better than that of the current access point **210**, or an RSSI greater than or equal to a pre-set threshold is identified in the connection with another access point, performing roaming to another access point. In addition, when another access point is discovered, but quality of the connection is

not better than that of the current access point **210** or an RSSI less than the pre-set threshold value is identified in the connection between the electronic device **101** and another access point, the electronic device **101** may switch the communication interface to cellular communication.

(81) FIG. **6** is a flowchart illustrating an internal state detection operation of an electronic device **101** according to an embodiment of the disclosure.

(82) According to an embodiment, in operation **601**, the electronic device **101** may receive a state detection message from an access point (for example, the access point **210** of FIG. **2**).

(83) According to an embodiment, in operation **603**, the electronic device **101** may determine whether a network switching mode of the electronic device **101** is enabled.

(84) The network switching mode may refer to a mode in which a communication interface of the electronic device **101** can switch from Wi-Fi communication to cellular communication based on a communication state and/or a state of the electronic device **101**. For example, when the network switching mode is enabled and a pre-set criterion is satisfied, the electronic device **101** may switch the communication interface by itself even if a user does not perform an additional input for switching the communication interface.

(85) The network switching mode being disabled may be understood as meaning that the communication interface is switched from Wi-Fi communication to cellular communication or from cellular communication to Wi-Fi communication only by user's selection. For example, when the network switching mode is disabled, the user may enable only one of cellular communication or Wi-Fi communication of the electronic device **101** or may terminate communication for all communication interfaces. However, since it is assumed that the electronic device **101** is currently connected with the current access point **210**, it may be understood that the cellular communication of the electronic device **101** is disabled. In another example, the network switching mode may refer to a mode in which, even when the cellular communication is enabled, user's approval is required so that switching from Wi-Fi communication to cellular communication is not automatic. In this case, the electronic device **101** may output a pop-up message inquiring of the user about whether to switch from Wi-Fi communication to cellular communication to a display (for example, the display module **160** of FIG. **1**) of the electronic device **101**.

(86) In an embodiment, when a switching request is received in a state where the network switching mode is disabled, the electronic device **101** may not disconnect the current connection. For example, when it is identified that the position of the electronic device **101** is out of the service region of the currently connected access point **210**, but the electronic device **101** receiving the switching request determines that the network switching mode is disabled, the electronic device **101** may maintain the connection with the access point **210** currently connected therewith in operation **611**. In this case, the electronic device **101** may transmit information indicating that the network switching mode is disabled to the current access point **210**. The transmitted information may be transmitted in the form of a switching response message or may be included in the switching response message.

(87) According to an embodiment, the electronic device **101** may transmit information regarding whether the network switching mode is supported to the access point **201**. For example, the electronic device **101** may transmit the information regarding whether the electronic device **101** supports the network switching mode to the access point **210** during an operation of connecting the Wi-Fi network with the access point **210** or after connecting the Wi-Fi network. When it is determined that the electronic device **101** does not support the network switching mode, the access point **201** may not transmit the state detection message to the electronic device **101**.

(88) According to an embodiment, the electronic device **101** may transmit information regarding whether the network switching mode is enabled or disabled to the access point **201**. For example, when the network switching mode is enabled or disabled, the electronic device **101** may transmit information regarding whether the network switching mode is enabled or disabled to the access point **210**. When the electronic device **101** determines that the network switching mode is disabled,

the access point **201** may not transmit the state detection message to the electronic device **101**.

(89) When it is determined that the network switching mode is enabled, the electronic device **101** may proceed to operation **605**.

(90) According to an embodiment, in operation **605**, the electronic device **101** may determine whether an application is in sleep mode. The sleep mode may refer to a temporary idle state or a mode in which the application in the electronic device **101** is not executing. The application being in the sleep mode may be understood as meaning that the processor for executing the application is also in the sleep mode. Herein, the application may refer to an application that is executed to transmit and receive data to and from the currently connected access point **210**, or an application associated therewith. When the application is not executing, it may be determined that there is no substantial data exchange between the electronic device **101** and the access point **210**, and there is less need to switch the communication interface to continuously transmit and receive data.

Accordingly, when the application is in sleep mode, there may be less need to disconnect the connection with the currently connected access point **210** and to discover a new access point **210**. Accordingly, when the application is in the sleep mode, the electronic device **101** may determine to maintain the current connection, and in operation **609**, the electronic device **101** may transmit information regarding whether the application in the electronic device **101** is in the sleep mode to the currently connected access point **210**, through the switching response message. The electronic device having performed operation **609** may maintain the connection with the currently connected access point **210** in operation **611**.

(91) When it is determined that the application of the electronic device **101** is not in the sleep mode, the electronic device **101** may perform operation **607**.

(92) According to an embodiment, in operation **607**, the electronic device **101** may identify whether a current RSSI is greater than a threshold value.

(93) For example, the RSSI may refer to a received signal strength, and may be a criterion for determining quality of the communication connection with the access point **210** which is currently connected with the electronic device **101**.

(94) The current RSSI may refer to the connection quality when data is transmitted and received in the relationship with the currently connected access point **210**. When a high RSSI is measured, it may be estimated that the electronic device **101** can perform smooth wireless communication with the access point **210** currently connected therewith. For example, when the current RSSI identified by the electronic device **101** is higher than a designated threshold value, it may be understood that the electronic device **101** is positioned within the service region of the currently connected access point **210**. In another example, when the current RSSI identified by the electronic device **101** is higher than the designated threshold value, it may be estimated that there is low possibility that the electronic device **101** will move out of the service region such that quality of the connection with the access point **210** is degraded. Herein, the designated threshold value may be understood as a minimum signal strength that is required for the electronic device **101** to smoothly perform wireless communication with the access point **210** currently connected therewith. The threshold value may be determined according to selection of the user or based on information provided by another entity, taking into consideration the type of the access point **210**, the surrounding environment of the electronic device **101** and/or the access point **210**, and/or interference by another electronic device (for example, the electronic device **102** of FIG. 1) existing in the service region. In an embodiment, when it is identified that the designated threshold value is higher than a currently measured RSSI, the electronic device **101** may estimate that it is difficult to smoothly perform wireless communication with the currently connected access point **210**. For example, it may be determined that the electronic device **101** is out of the service region of the current access point **210**. Accordingly, the electronic device **101** may proceed to operation **613** to discover another neighboring access point. However, when the current RSSI is higher than the threshold value, it may be estimated that the electronic device **101** exists within the service region of the currently

connected access point **210**, and may not have to disconnect the current connection or perform roaming to another access point. Accordingly, in this case, in operation **609**, the electronic device **101** may transmit information identifying that the current RSSI is higher than the threshold value to the currently connected access point **210**. In this case, the corresponding information may be transmitted in the form of a switching response message or may be included in the switching response message. The electronic device **101** which has performed operation **609** may maintain the connection with the currently connected access point in operation **611**.

(95) The flowchart of FIG. **6** does not limit the sequence of operation **603**, operation **605**, and operation **607**, and at least one of these operations may be performed in a different order as shown in FIG. **6** or two or more operations may be performed simultaneously. In other embodiments of the disclosure, a subsequent operation may be performed based on information determined in these operations.

(96) According to an embodiment, in operation **613**, the electronic device **101** may perform an operation of identifying whether there exists another access point that provides Wi-Fi network, in addition to the currently connected access point **210**. For example, the electronic device **101** may identify the number of other neighboring access points, positions, identification information and/or signal strength by performing a process of discovering around the electronic device **101** (for example, an operation of scanning).

(97) According to an embodiment, in operation **615**, the electronic device **101** may identify whether another connectable access point is discovered. Another connectable access point may refer to an access point that satisfies a pre-set condition regarding communication quality. Whether the pre-set condition is satisfied may be understood as whether a strength of a signal received from another access point is greater than or equal to a threshold value, whether the access point is connectable with the electronic device by higher than predetermined communication quality, and/or whether roaming is possible.

(98) For example, the connectable access point may refer to another access point that provides better connection quality than the access point **210** currently connected with the electronic device **101**. In addition, since it is identified that the current RSSI of the electronic device **101** is smaller than the threshold value, it may be estimated that the current position of the electronic device **101** is in a service region of an access point other than the currently connected access point **210**.

Accordingly, operations **613** to **615** may be understood as a process of discovering another access point having a service region that includes the current position of the electronic device **101**. When the electronic device **101** discovers a plurality of other access points having service regions including the current position of the electronic device **101**, the electronic device **101** may determine one of the other access points that has the best communication quality as a connectable access point. Herein, one access point having the best communication quality may refer to an access point in which a highest RSSI value is measured.

(99) When the connectable access point is discovered, operation **621** may be performed. When the connectable access point is not discovered, operation **617** may be performed.

(100) According to an embodiment, in operation **617**, the electronic device **101** may transmit a switching response message to the access point **210**.

(101) The switching response message transmitted by the electronic device **101** to the access point **210** in operation **617** may include information indicating that the network switching mode of the electronic device **101** is enabled, the application is not in the sleep mode, and the current RSSI is smaller than the threshold value. In addition, the switching response message may include information indicating that a connectable access point is not found as a result of discovering another access point. For example, the switching response message may include information indicating that the electronic device **101** is disconnecting the connection with the access point **210** and is switching to cellular communication. The switching response message transmitted by the electronic device **101** in operation **617** may be transmitted to the access point **210** which is

currently connected with the electronic device **101**. The access point **210** which is currently connected with the electronic device **101** may be informed that the electronic device **101** switches the communication interface to cellular communication, by receiving the switching response message transmitted by the electronic device **101** in operation **617**.

(102) In operation **619**, the electronic device **101** may disconnect the connection with the access point **210** currently connected therewith.

(103) In the next operation, the electronic device **101** may start switching the communication interface to cellular communication.

(104) According to an embodiment, in operation **621**, the electronic device **101** may transmit a switching response message to the access point **210**.

(105) For example, the switching response message transmitted by the electronic device **101** in operation **621** may include information indicating that the network switching mode of the electronic device **101** is enabled, the application is not in the sleep mode, and the current RSSI is smaller than the threshold value. In addition, the switching response message may include information indicating that a connectable access point is found as a result of discovering another access point. The switching response message may be transmitted to the access point **210** which is currently connected with the electronic device **101**.

(106) According to an embodiment, in operation **623**, the electronic device **101** may perform roaming to the connectable access point. In this case, the communication interface may not be switched. The access point **210** which is currently connected with the electronic device **101** may find that the electronic device **101** performs roaming to the connectable access point from the access point **210**, by receiving the switching response message transmitted by the electronic device **101** in operation **621**.

(107) FIG. 7 illustrates a process of an electronic device **230** for starting an operation of identifying an internal state of the electronic device **230** based on information received from an access point **210** in a wireless communication system according to an embodiment of the disclosure.

(108) Referring to FIG. 7, the electronic device **230** (for example, the electronic device **101** of FIG. 1 or the electronic device **300** of FIG. 3) may receive a message for triggering identification of an internal state of the electronic device **230** from the access point **210**.

(109) According to an embodiment, in operation **701**, the access point **210** may detect quality of the wireless communication connection with the electronic device **230** which is currently connected therewith. Since the access point **210** provides a defined service region, the access point **210** may be connected with at least one electronic device (for example, the electronic device **230**) existing within the service region. In this case, the access point **210** may perform an operation of detecting quality of the communication connection of an individual electronic device (for example, the electronic device **230**). The process of detecting the communication connection quality may be periodically performed and may be performed by exchanging signals with the electronic device **230**. The access point **210** may intermittently or periodically perform the process of detecting quality of the communication connection with the electronic device **230** which is currently connected therewith or the electronic device **230** identified as existing in the service region.

(110) According to an embodiment, in operation **703**, the electronic device **230** may receive a beacon reporting request from the access point. For example, the access point **210** may detect quality of the communication connection with at least one electronic device, and, when the access point **210** determines that the communication connection quality is not good with a specific electronic device (for example, the electronic device **230**), the corresponding electronic device (for example, the electronic device **230**) may receive a beacon reporting request from the access point. For example, the access point **210** may determine that the communication connection quality is not good, based on a pre-defined threshold value.

(111) According to an embodiment, the access point **210** may transmit the beacon reporting request to the electronic device **230** and may acquire information regarding other access points on the

periphery of the electronic device **230**. For example, the beacon reporting request may include a specific SSID. The specific SSID may be the SSID of the access point **210** which is currently connected with the electronic device **230**, or an SSID of another access point existing within a predetermined region with reference to a current position of the electronic device **230**. According to an embodiment, the access point **210** may receive a beacon message transmitted by another neighboring access point, and may transmit the beacon reporting request including an SSID included in the received beacon message to the electronic device **230**.

(112) According to an embodiment, in operation **705**, the electronic device **230** may perform scanning. For example, the electronic device **230** may perform discovering in response to the beacon reporting request being received from the access point **210**. According to an embodiment, discovering performed by the electronic device (for example, scanning) may be an operation of identifying whether there exists another access point on the periphery of the electronic device **230**, identifying identification information of another neighboring access point, or identifying information regarding whether the electronic device **230** belongs to a service region of another access point. According to another embodiment, by performing the discovering or scanning, the electronic device **230** may identify the relative position between the electronic device **230** and the access point **210**, based on whether the electronic device **230** is relatively far away from the access point **210** currently connected therewith or whether the electronic device **230** approaches the boundary of the service region.

(113) According to an embodiment, in operation **707**, the electronic device **230** may transmit a beacon reporting response to the access point **210**. For example, in response to discovering being performed, the electronic device **230** may transmit the beacon reporting response to the access point **210** which is currently connected therewith. In this case, the beacon reporting response may be transmitted in the form of a message, and information identified by the electronic device **230** through discovering (for example, the number of other neighboring access points, positions, identification information and/or a signal strength) may be included in the beacon reporting response message. The access point **210** may receive the beacon reporting response message transmitted from the electronic device **230**.

(114) According to an embodiment, in operation **709**, the access point **210** may generate network switching recommendation information. For example, the access point **210** may determine whether the electronic device **230** should switch the communication interface to cellular communication, in response to the beacon reporting response message being received from the electronic device **230**. The access point **210** may analyze the beacon reporting response message received from the electronic device **230**, and may determine whether there exists another access point that is connectable by the electronic device **230**, based on information regarding other access points existing on the periphery of the electronic device **230**, and, when there does not exist another connectable access point, may determine whether the electronic device **230** should switch to cellular communication. When the access point **210** determines whether the electronic device **230** switches the communication interface or whether roaming to another access point is performed, the access point **210** may generate recommendation information based on the result of determining.

(115) According to an embodiment, in operation **711**, the electronic device **230** may receive a switching request message from the access point **210**. The switching request message may include the recommendation information generated by the access point **210**. The switching request message may be referred to as a state detection message or may perform a similar function to the state detection message. In addition, the switching request message may include information regarding whether there does not exist a neighboring access point **210** on the periphery of the electronic device **230**, whether the neighboring access point does not provide a sufficient wireless communication service to the electronic device **230** although there exists a neighboring access point **210**, and may include information regarding RSSIs of other access points. The electronic device **230** which receives the switching request message may determine whether to switch the

communication interface to cellular communication or whether to perform roaming to another access point, by referring to the corresponding recommendation information. According to an embodiment, the electronic device **230** may determine whether to maintain or disconnect the connection with the access point **210** currently connected therewith. For example, since the recommendation information is determined and generated by the access point **210**, the electronic device **230** may determine whether to switch or to perform roaming, by referring to the recommendation information. According to another embodiment, the electronic device **230** may identify an internal state regardless of the determination by the access point **210**, and may determine whether to switch or to perform roaming by itself, based on information determined based on the internal state. For example, the electronic device **230** may also determine whether to disconnect the connection with the access point **210** currently connected therewith, according to internal information identified by the electronic device **230**.

(116) According to an embodiment, in operation **713**, the electronic device **230** may identify a communication state. For example, the electronic device **230** may identify the communication state of the electronic device **230** in response to the switching request message being received from the access point **210**. Herein, the communication state may refer to an internal state of the electronic device **230**. The operation of identifying the internal state of the electronic device **230** may be understood as an operation of identifying an RSSI value regarding a communication connection in the relationship with the access point **210** currently connected therewith, an operation of identifying whether a network switching mode of the electronic device **230** is enabled, an operation of identifying whether an application associated in performing a communication connection with the access point **210** currently connected with the electronic device **230** is in a sleep mode. In addition, the internal state may include information regarding whether data is currently used by the user and data usage, user preference, a cellular data plan, mobility information of the electronic device, and/or a value of a result of comparing a Wi-Fi parameter and a cellular parameter.

(117) FIG. **8** illustrates operations related to identification of an internal state of the electronic device **230** in the wireless communication system according to an embodiment of the disclosure.

(118) According to an embodiment, the electronic device **230** may identify an internal state in response to a switching request message being received from the access point **210** (**801**). In operation **801**, the electronic device **230** may perform the operation of identifying the internal state (**803**). According to another embodiment, the electronic device **230** may periodically or intermittently (for example, in the case of transmitting and receiving data) scan a communication state. For example, after identifying the communication state or internal state, the electronic device **230** may receive the switching request message from the access point **210**. According to an embodiment, in operation **805**, the electronic device **230** may perform a process of identifying whether at least one of the conditions described below is satisfied.

(119) According to an embodiment, it may be identified whether a network switching mode of the electronic device **230** is disabled. The network switching mode may refer to a mode in which the communication network can be switched from Wi-Fi communication to cellular communication. For example, the network switching mode may be understood as a mode in which the electronic device **230** can change the communication interface, which is a means for connecting to a network to use communication service provided in the wireless communication system, based on state information of the electronic device **230**. The state information may refer to information regarding an internal state of the electronic device **230**. The internal state may include information regarding whether data is currently used by the user and data usage, user preference, a cellular data plan, mobility information of the electronic device, and/or a value of a result of comparing a Wi-Fi parameter and a cellular parameter. According to certain embodiments, the network switching mode may be understood as including not only switching from Wi-Fi communication to cellular communication, but also switching from cellular communication to Wi-Fi communication. When the network switching mode is disabled, switching of the communication interface may not be

performed automatically according to an internal state of the electronic device **230** or external factors or according to pre-set rules, but may be performed only by user's selection or command. According to an embodiment, when the network switching mode is enabled, it may be possible to set the communication interface to be switched automatically according to a change in the RSSI value, and/or the type or size of content transmitted or received by the electronic device **230**. According to another embodiment, in the state where the network switching mode is disabled, even when the electronic device **230** goes farther away from the access point **210** currently connected therewith due to movement of the user carrying the electronic device **230**, the communication interface may not be switched to cellular communication. However, in this case, a message for inquiring of the user about whether to switch to cellular communication or whether to maintain current Wi-Fi communication may be outputted to an output unit such as a display (for example, the display module **160** of FIG. **1**). When a user input on the corresponding message is detected by the electronic device **230**, the input may be recognized as user's selection and switching to a corresponding communication interface may be performed.

(120) According to an embodiment, the access point **210** may transmit, to the electronic device **230**, the switching request message to allow the electronic device **230** to check its state, to determine whether to perform roaming to a connectable access point based on a result of checking the state, whether to switch the communication interface to cellular communication, or whether to maintain the current connection. According to an embodiment, in the state where the network switching mode is disabled, even when pre-defined conditions are satisfied, the electronic device **230** may not switch the communication interface without user's selection. Therefore, the electronic device **230** may first identify whether the network switching mode is disabled. However, the instant disclosure is not so limited and the identification of whether the network switching mode is disabled may not be performed first.

(121) According to an embodiment, the electronic device **230** may detect an RSSI value in the relationship with the access point **210** currently connected therewith. The RSSI value may refer to a received signal strength, and, when the RSSI value is greater than or equal to a predetermined value, a wireless communication service between the electronic device **230** and the access point **210** may be smoothly provided. A threshold value for serving as a reference for the smooth wireless communication service may be pre-defined. This may be referred to as an RSSI threshold value. The RSSI threshold value may be a value that is already inputted by the user, and may be periodically or intermittently updated through an external server. The RSSI threshold value may vary according to at least one of performance of the electronic device **230**, performance of the access point **210**, a characteristic of a service region occupied by the access point **210**, and/or a surrounding environment of the electronic device **230** or the access point **210**. The RSSI threshold value may be understood as a minimum RSSI value that is measured by the electronic device **230** to provide a smooth wireless communication service between the access point **210** and the electronic device **230**. It may be normally expected that a value similar to the RSSI threshold value is measured from the electronic device **230** positioned on the outermost portion of the service region of the access point. However, as described above, the RSSI threshold value may vary according to a position of the service region, and information of the RSSI threshold value which is determined by considering all factors may be already transmitted to the electronic device **230**. The RSSI value may vary according to the distance between the electronic device **230** and the access point **210** even within the service region. The RSSI value information may be continuously updated by exchanging signals with the access point **210**. The electronic device **230** may compare the already known RSSI threshold value and an RSSI value measured through the internal state identification process. When it is determined that the measured RSSI value is greater than the RSSI threshold value through the above-described comparing process, the electronic device **230** may maintain the connection with the access point **210** currently connected therewith. This is because measurement of the RSSI greater than or equal to the RSSI threshold value means that a smooth

wireless communication service can be performed between the electronic device **230** and the access point **210**, and it is not necessary to determine whether to disconnect the connection with the currently connected access point **210** or whether to perform roaming with another access point. (122) According to an embodiment, the electronic device **230** may determine whether an application is in sleep mode. The application may refer to an application that is associated with transmission and reception of data in a state where the access point **210** currently connected with the electronic device **230**. For example, when the electronic device **230** uses a media streaming service through the access point **210**, the application may correspond to an application or a program that is executed by the electronic device **230** to provide the corresponding media streaming service. The sleep mode may refer to a mode that is set to be switched to a low-power mode when the application is not used, and to manage resources efficiently. The application being in the sleep mode may be understood as the processor for executing the corresponding application being in the sleep mode. In this case, it may be understood that data transmission and reception between the access point **210** and the electronic device **230** is not temporarily performed. In the case of the sleep mode in which data transmission is not performed between the electronic device **230** and the access point **210**, it may not be necessary to determine whether to disconnect the connection between the electronic device **230** and the access point **210** or whether to maintain the connection. In addition, it may not be necessary to discover a connectable access point other than the access point **210** currently connected with the electronic device **230**. The reason to discover another access point or to determine whether to disconnect the connection with the current access point **210** and whether to switch to cellular communication is that a delay that the user feels can be minimized by providing a continuous wireless communication service to the electronic device **230**. Therefore, when the user does not substantially perform wireless communication, the above-described process may not need to be performed. According to an embodiment, when the electronic device **230** determines that the application is in the sleep mode, the electronic device **230** may determine to maintain the current connection.

(123) The electronic device **230** may determine whether the above-described conditions are satisfied through the process of identifying the internal state. When the electronic device **230** determines that at least one of the above-described conditions (for example, the condition where the network switching mode is disabled, the condition where the measured RSSI value is greater than or equal to the RSSI threshold value, and/or the condition where the application is in the sleep mode) is satisfied, the electronic device **230** may maintain the connection with the access point **210** currently connected therewith. That is, the electronic device **230** may not disconnect the connection with the access point **210** currently connected therewith.

(124) According to certain embodiments, when the electronic device **230** determines that the network switching mode of the electronic device **230** is disabled, that the RSSI value is greater than the pre-set threshold RSSI value in the relationship with the access point **210** currently connected with the electronic device **230**, and/or that the application related to the communication service provided by the access point **210** is in the sleep mode, the electronic device **230** may maintain the connection with the access point **210** currently connected with the electronic device **230**.

(125) According to an embodiment, in operation **807**, the electronic device **230** may transmit a switching response message to the access point **210**. For example, the electronic device **230** may identify the internal state of the electronic device **230**, and, when it is determined whether the application is in the sleep mode, whether the network switching mode is disabled, or whether the RSSI value exceeds the threshold value, the electronic device **230** may transmit a switching response message to the access point **210** currently connected therewith. In addition, the operation of transmitting the switching response message may be performed based on information regarding whether data is currently used by the user and data usage, user preference, a cellular data plan, mobility information of the electronic device, and/or a value of a result of comparing a Wi-Fi parameter and a cellular parameter.

(126) The switching response message may include information identified through identification of the internal state. For example, the electronic device **230** may include, in the switching response message, information regarding whether the network switching mode of the electronic device **230** is disabled, whether the RSSI value is greater than the pre-set threshold RSSI value in the relationship with the access point **210** currently connected with the electronic device **230**, and/or whether the application related to the communication service provided from the access point **210** is in the sleep mode, and may transmit the switching response message to the access point **210**.

(127) According to an embodiment, in operation **809**, the electronic device **230** may determine to maintain Wi-Fi connection. For example, when the RSSI value is greater than the pre-set threshold RSSI value, the application related to the communication service provided by the access point **210** is in the sleep mode, and/or the network switching mode is disabled, the electronic device **230** may maintain the Wi-Fi connection with the access point **210** currently connected therewith.

(128) FIG. **9** illustrates operations related to the identification of the internal state of the electronic device **230** in the wireless communication system according to another embodiment of the disclosure.

(129) According to an embodiment, in operation **903**, the electronic device **230** may scan a communication state. For example, the electronic device **230** may identify a communication state or an internal state in response to a switching request message being received from the access point **210** (**901**). According to another embodiment, the electronic device **230** may periodically or intermittently (for example, in the case of transmitting and receiving data) scan the communication state. For example, the electronic device **230** may identify the communication state or the internal state, and then, may receive the switching request message from the access point **210**.

(130) According to an embodiment, in operation **905**, the electronic device **230** may identify the communication state. The process of identifying the internal state may include a process of the electronic device **230** for identifying whether the three following conditions are all satisfied: i) whether a network switching mode of the electronic device **230** is enabled. ii) whether an RSSI value is smaller than a pre-defined threshold RSSI value. iii) whether an application is not in sleep mode.

(131) According to an embodiment, in operation **907**, the electronic device **230** may discover neighboring access points. For example, the electronic device **230** may identify the internal state of the electronic device **230**, and may perform the process of discovering other neighboring access points only when the above-described three conditions are all satisfied. Other neighboring access points may refer to access points other than the access point **210** currently connected with the electronic device **230**. Herein, the electronic device **230** may identify whether another access point found through discovering is better than the access point **210** currently connected with the electronic device **230**. Whether another access point is better than the access point **210** may be determined with reference to quality of a wireless communication connection between the access point **210** and the electronic device **230**. According to an embodiment, when an RSSI value of the electronic device **230** and another access point is higher than an RSSI value of the electronic device **230** and the current access point **210**, another access point discovered may be regarded as being better than the current access point **210**. According to another embodiment, when the RSSI value on the connection between another access point and the electronic device **230** is higher than the pre-defined threshold RSSI value simultaneously, another access point discovered may be regarded as being better than the current access point **210**. When another access point having the RSSI value exceeding all of the threshold RSSI value and the RSSI value of the current access point **210** is not found, the electronic device **230** may determine that there does not exist a connectable access point. When the electronic device **230** determines that there does not exist a connectable access point, the electronic device **230** may have difficulty in continuously receiving the wireless communication service through Wi-Fi communication, and thus may recognize that it is necessary to switch the communication interface to cellular.

(132) According to an embodiment, in operation **909**, the electronic device **230** may transmit a switching response to the access point **210**. For example, the electronic device **230** may identify the internal state of the electronic device **230**, and, when it is determined that the application is not in the sleep mode, that the network switching mode is enabled, and that the RSSI value is less than the threshold value, the electronic device **230** may transmit the switching response message to the access point **210** currently connected therewith. The switching response message may include information regarding whether all of the conditions are satisfied. Specifically, the electronic device **230** may include, in the switching response message, information regarding whether the network switching mode of the electronic device **230** is disabled, whether the RSSI value in the relationship with the access point **210** currently connected with the electronic device **230** is greater than the pre-set threshold RSSI value, whether the application related to the communication service provided from the access point **210** is in the sleep mode, and may transmit the switching response message to the access point **210**. According to an embodiment, since the electronic device **230** does not find a connectable access point, the switching request message may further include information indicating that an access point better than the access point **210** currently connected with the electronic device **230** is not found on the periphery of the electronic device **230**. According to another embodiment, when a connectable access point is not found, the electronic device **230** may perform operation **907** and may include information of other access points searched on the periphery of the electronic device **230** (for example, the number of other neighboring access points, positions, identification information and/or a signal strength) in the switching request message, and may transmit the switching request message.

(133) According to an embodiment, in operation **911**, the electronic device **230** may disconnect the Wi-Fi connection. For example, when a connectable access point is not found through discovering of neighboring access points, the electronic device **230** may disconnect the Wi-Fi connection with the access point **210** currently connected therewith in order to switch the communication interface to cellular communication.

(134) FIG. **10** illustrates operations related to the identification of the internal state of the electronic device **230** in the wireless communication system according to still another embodiment of the disclosure.

(135) According to an embodiment, in operation **1003**, the electronic device **230** may scan a communication state. For example, the electronic device **230** may identify a communication state or an internal state in response to a switching request message being received from the access point **210** (**1001**). According to another embodiment, the electronic device **230** may periodically or intermittently (for example, in the case of transmitting and receiving data) scan the communication state. For example, the electronic device **230** may identify the communication state or the internal state, and then, may receive the switching request message from the access point **210**.

(136) According to an embodiment, in operation **1005**, the electronic device **230** may identify the communication state. For example, the electronic device **230** may identify the internal state through scanning to identify the communication state. The process of identifying the internal state may include a process of the electronic device **230** identifying whether the three following conditions are all satisfied: i) whether a network switching mode of the electronic device **230** is enabled. ii) whether an RSSI value is smaller than a pre-defined threshold RSSI value. iii) whether an application is not in sleep mode.

(137) According to an embodiment, in operation **1007**, the electronic device **230** may discover neighboring access points. For example, the electronic device **230** may scan the internal state of the electronic device **230**, and may perform the process of discovering other neighboring access points only when all of the above-described three conditions are satisfied. Other neighboring access points may refer to access points other than the access point **210** currently connected with the electronic device **230**. According to an embodiment, the electronic device **230** may identify whether another access point found through discovering is better than the access point **210** currently connected with

the electronic device **230**. Whether another access point is better than the access point **210** may be determined with reference to quality of a wireless communication connection formed between the access point **210** and the electronic device **230**. According to an embodiment, when an RSSI value of the electronic device **230** and another access point is higher than an RSSI value of the electronic device **230** and the current access point **210**, another access point discovered may be regarded as being better than the current access point **210**. According to another embodiment, when the RSSI value on the connection between another access point and the electronic device **230** is higher than the pre-defined threshold RSSI value simultaneously, another access point discovered may be regarded as being better than the current access point **210**. According to an embodiment, when an access point **210** having an RSSI value exceeding all of the threshold RSSI value and the RSSI value of the current access point **210** is found, the electronic device **230** may determine to perform roaming to the corresponding access point **210**. The connectable access point determined in this case may be referred to as a target access point.

(138) According to an embodiment, in operation **1009**, the electronic device **230** may transmit a switching response to the access point **210**. For example, the electronic device **230** may identify the internal state of the electronic device **230**, and, when it is determined whether the application is not in the sleep mode, whether the network switching mode is enabled, and whether the RSSI value is less than the threshold value, the electronic device **230** may transmit the switching response message to the access point **210** currently connected therewith. The switching response message may include information regarding whether all of the conditions are satisfied. For example, the electronic device **230** may include, in the switching response message, information regarding whether the network switching mode of the electronic device **230** is disabled, whether the RSSI value in the relationship with the access point **210** currently connected with the electronic device **230** is greater than the pre-set threshold RSSI value, and/or whether the application related to the communication service provided from the access point **210** is in the sleep mode, and may transmit the switching response message to the access point **210**. According to an embodiment, when a connectable access point is found, the electronic device **230** may also transmit identification information of the target access point to the current access point **210**.

(139) According to an embodiment, in operation **1011**, the electronic device **230** may perform a roaming procedure to the target access point **210**. For example, the electronic device **230** may disconnect the communication connection with the access point **210** currently connected therewith, and may perform an operation of establishing a Wi-Fi communication connection with the target access point (for example, Wi-Fi roaming). In this case, the communication interface of the electronic device **230** may not be switched.

(140) According to an embodiment of the disclosure, an operating method of an electronic device **300** in a wireless communication system may include: establishing a wireless communication connection for transmitting and receiving data to and from an access point **210** in a first communication method; receiving a state detection message from the access point **210**; identifying an internal state of the electronic device **300** in response to the state detection message being received; and determining whether to switch a communication interface, based on the identified internal state, and the internal state may include at least one of a received signal strength indicator (RSSI) value of the wireless communication connection, information regarding whether a network switching mode of the electronic device **300** is enabled, information regarding whether an application related to the data is enabled, or information regarding use of the data.

(141) According to an embodiment, identifying the internal state may further include comparing the RSSI value and a pre-defined threshold RSSI value.

(142) According to an embodiment, the method may further include discovering other access points, based on the identified internal state.

(143) According to an embodiment, at least one of the other access points may transmit, to the electronic device **300**, a signal that has an RSSI value greater than the RSSI value of the wireless

communication connection to the access point **210** and greater than the threshold RSSI value.

(144) According to an embodiment, when the other access points are not discovered, the communication interface may be switched to a second communication method.

(145) According to an embodiment, the first communication method may be related to a first performance parameter, the second communication method may be related to a second performance parameter, and switching the communication interface may be determined based on values of the first performance parameter and the second performance parameter.

(146) According to an embodiment, the method may further include: acquiring position information of the electronic device **300**, and determining whether to disconnect the wireless communication connection, based on the position information.

(147) According to an embodiment, the method may further include transmitting information regarding whether the application is enabled and information regarding a result of comparing the values of the first performance parameter and the second performance parameter.

(148) According to an embodiment, discovering the other access points may be performed when the application is enabled, the network switching mode of the electronic device is enabled, and the RSSI value is smaller than the threshold RSSI value.

(149) According to an embodiment, the method may further include, when the other access points are not discovered, disconnecting the wireless communication connection in the first communication method with the access point **210**.

(150) According to an embodiment, an electronic device **300** in a wireless communication system may include: a communication unit **330**; and at least one processor **310** electrically connected with the communication unit **330**, and the at least one processor **310** may be configured to: establish a wireless communication connection for transmitting and receiving data to and from an access point **210** in a first communication method; receive a state detection message from the access point **210**; identify an internal state of the electronic device **300** in response to the state detection message being received; and determine whether to switch a communication interface, based on the identified internal state, and the internal state may include at least one of a received signal strength indicator (RSSI) value of the wireless communication connection, information regarding whether a network switching mode of the electronic device is enabled, information regarding whether an application related to the data is enabled, or information regarding use of the data.

(151) According to an embodiment, the at least one processor **310** may further be configured to compare the RSSI value and a pre-defined threshold RSSI value to identify the internal state.

(152) According to an embodiment, the at least one processor **310** may further be configured to discover other access points, based on the identified internal state.

(153) According to an embodiment, at least one of the other access points may transmit, to the electronic device **300**, a signal that has an RSSI value greater than the RSSI value of the wireless communication connection to the access point **210** and greater than the threshold RSSI value.

(154) According to an embodiment, the at least one processor **310** may further be configured to, when the other access points are not discovered, switch the communication interface to a second communication method.

(155) According to an embodiment, the first communication method may be related to a first performance parameter, the second communication method may be related to a second performance parameter, and the at least one processor may further be configured to determine based on values of the first performance parameter and the second performance parameter to switch the communication interface.

(156) According to an embodiment, the at least one processor **310** may further be configured to: acquire position information of the electronic device **300**, and determine whether to disconnect the wireless communication connection, based on the position information.

(157) According to an embodiment, the at least one processor **310** may further be configured to transmit information regarding whether the application is enabled and information regarding a

result of comparing the values of the first performance parameter and the second performance parameter.

(158) According to an embodiment, the at least one processor **310** may further be configured to discover the other access points when the application is enabled, the network switching mode of the electronic device is enabled, and the RSSI value is smaller than the threshold RSSI value.

(159) According to an embodiment, the at least one processor **310** may further be configured to, when the other access points are not discovered, disconnect the wireless communication connection in the first communication method with the access point **210**.

(160) The apparatus and the method according to certain embodiments of the disclosure can reduce a delay experienced by the user by reducing time required to switch a communication network in a wireless communication system.

(161) The effect achieved by the disclosure is not limited to those mentioned above, and other effects that are not mentioned above may be clearly understood to those skilled in the art based on the description provided above.

(162) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or alternatives for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the items, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(163) As used herein, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(164) An embodiment of the disclosure may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(165) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be

distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., Play Store™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(166) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in other components. According to an embodiment, one or more of the above-described components or operations may be omitted, or one or more other components or operations may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to an embodiment, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(167) Certain of the above-described embodiments of the present disclosure can be implemented in hardware, firmware or via the execution of software or computer code that can be stored in a recording medium such as a CD ROM, a Digital Versatile Disc (DVD), a magnetic tape, a RAM, a floppy disk, a hard disk, or a magneto-optical disk or computer code downloaded over a network originally stored on a remote recording medium or a non-transitory machine readable medium and to be stored on a local recording medium, so that the methods described herein can be rendered via such software that is stored on the recording medium using a general purpose computer, or a special processor or in programmable or dedicated hardware, such as an ASIC or FPGA. As would be understood in the art, the computer, the processor, microprocessor controller or the programmable hardware include memory components, e.g., RAM, ROM, Flash, etc. that may store or receive software or computer code that when accessed and executed by the computer, processor or hardware implement the processing methods described herein.

(168) While the present disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the present disclosure as defined by the appended claims and their equivalents.

Claims

1. A method performed by an electronic device in a wireless communication system, the method comprising: establishing a wireless communication connection with a first access point supporting a first communication scheme; receiving, from the first access point, a request message for switching a communication scheme or an access point for transmitting and receiving signals; identifying whether an application processor of the electronic device is in a sleep mode based on the request message; performing a discovery procedure for a second access point supporting the first communication scheme, in case that the application processor is not in the sleep mode and a first received signal strength indicator (RSSI) value of first signals from the first access point is lower than a threshold; in case that the second access point is discovered via the discovery procedure, switching the access point from the first access point to the second access point; in case that the second access point is not discovered via the discovery procedure: identifying that a value of a first parameter associated with a performance of the first communication scheme is lower than a value of a second parameter associated with a performance of a second communication scheme;

and switching the communication scheme from the first communication scheme to the second communication scheme.

2. The method of claim 1, further comprising: identifying the first RSSI value of the first signals received from the first access point via the wireless communication connection; and comparing the first RSSI value and the threshold.
3. The method of claim 2, further comprising: transmitting, to the first access point, a response message including information on whether the application processor is in the sleep mode and information on a result of comparison between the first RSSI value and the threshold.
4. The method of claim 1, wherein second signals received from the second access point have a second RSSI value greater than the first RSSI value of the first signals and greater than the threshold.
5. The method of claim 1, further comprising: acquiring position information of the electronic device; and determining whether to disconnect the wireless communication connection, based on the position information.
6. The method of claim 1, wherein the discovery procedure is performed, in case that the application processor is not in the sleep mode, a network switching mode of the electronic device is enabled, and the first RSSI value is lower than the threshold.
7. The method of claim 6, further comprising: in case that the second access point is not discovered, disconnecting the wireless communication connection associated with the first communication scheme; and establishing a wireless communication connection associated with the second communication scheme with the first access point.
8. The method of claim 1, wherein the value of the first parameter is determined based on at least one of a communication performance of the first access point, or a location of the first access point, and wherein the value of the second parameter is determined based on at least one of a communication performance of the second access point, or a location of the second access point.
9. The method of claim 1, wherein, in case that the application processor is in the sleep mode, the communication scheme corresponding to the first communication scheme is maintained.
10. An electronic device in a wireless communication system, the electronic device comprising: a transceiver; at least one processor electrically coupled with the transceiver and including an application processor; and memory storing instructions that, when executed by the at least one processor collectively or individually, cause the electronic device to: establish a wireless communication connection with a first access point supporting a first communication scheme, receive, from the first access point, a request message for switching a communication scheme or an access point for transmitting and receiving signals, identify whether the application processor is in a sleep mode based on the request message, perform a discovery procedure for a second access point supporting the first communication scheme, in case that the application processor is not in the sleep mode and a first received signal strength indicator (RSSI) value of first signals from the first access point is lower than a threshold, in case that the second access point scheme is discovered via the discovery procedure, switch the access point from the first access point to the second access point, in case that the second access point is not discovered via the discovery procedure: identify that a value of a first parameter associated with a performance of the first communication scheme is lower than a value of a second parameter associated with a performance of a second communication scheme, and switch the communication scheme from the first communication scheme to the second communication scheme.
11. The electronic device of claim 10, wherein the instructions, when executed by the at least one processor collectively or individually, cause the electronic device to: identify the first RSSI value of the first signals received from the first access point via the wireless communication connection, and compare the first RSSI value and the threshold.
12. The electronic device of claim 11, wherein the instructions, when executed by the at least one processor collectively or individually, cause the electronic device to: transmit, to the first access

point, a response message including information on whether the application processor is in the sleep mode and information on a result of comparison between the first RSSI value and the threshold.

13. The electronic device of claim 10, wherein second signals received from the second access point have a second RSSI value greater than the first RSSI value of the first signals and greater than the threshold.

14. The electronic device of claim 10, wherein the instructions, when executed by the at least one processor collectively or individually, cause the electronic device to: acquire position information of the electronic device, and determine whether to disconnect the wireless communication connection, based on the position information.

15. The electronic device of claim 10, wherein the discovery procedure is performed, in case that the application processor is not in the sleep mode, a network switching mode of the electronic device is enabled, and the first RSSI value is lower than the threshold.

16. The electronic device of claim 15, wherein the instructions, when executed by the at least one processor collectively or individually, cause the electronic device to: in case that the second access point is not discovered, disconnect the wireless communication connection associated with the first communication scheme, and establish a wireless communication connection associated with the second communication scheme with the first access point.

17. The electronic device of claim 10, wherein the value of the first parameter is determined based on at least one of a communication performance of the first access point, or a location of the first access point, and wherein the value of the second parameter is determined based on at least one of a communication performance of the second access point, or a location of the second access point.

18. The electronic device of claim 10, wherein the instructions, when executed by the at least one processor collectively or individually, cause the electronic device to: in case that the application processor is in the sleep mode, maintain the communication scheme corresponding to the first communication scheme.
