

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12385697
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Lewis; Ryan John et al.

Micropillar-enabled thermal ground plane

Abstract

A thermal ground plane (TGP) is disclosed. A TGP may include a first planar substrate member comprising copper and a second planar substrate member comprising a metal, wherein the first planar substrate member and the second planar substrate member enclose a working fluid. The TGP may include a first plurality of pillars disposed on an interior surface of the first planar substrate and a mesh layer disposed on the top of the first plurality of pillars, wherein the mesh layer comprises at least one of copper, polymer encapsulated with copper, or stainless steel encapsulated with copper. The TGP may also include a second plurality of pillars disposed on an interior surface of the second planar substrate member within an area defined by the perimeter of the second planar substrate member and the second plurality of pillars extend from the second planar substrate member to the mesh layer.

Inventors: Lewis; Ryan John (Boulder, CO), Liew; Li-Anne (Westminster, CO), Lin; Ching-Yi (Longmont, CO), Coolidge; Collin Jennings (Longmont, CO), Xu; Shanshan (Boulder, CO), Yang; Ronggui (Boulder, CO), Lee; Yung-Cheng (Boulder, CO)

Applicant: Kelvin Thermal Technologies, Inc. (Boulder, CO)

Family ID: 88308374

Assignee: Kelvin Thermal Technologies, Inc. (Boulder, CO)

Appl. No.: 18/180122

Filed: March 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230332841 A1	Oct. 19, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 15930016 20200512 US 11598594 child-doc US 18180122
continuation-in-part parent-doc US 14857567 20150917 US 10731925 child-doc US 15930016
us-provisional-application US 62069564 20141028
us-provisional-application US 62051761 20140917

Publication Classification

Int. Cl.: F28F21/08 (20060101); F28D15/02 (20060101); F28D15/04 (20060101)

U.S. Cl.:

CPC F28D15/046 (20130101);

Field of Classification Search

CPC: F28D (15/046); F28D (15/04); F28D (15/0233); H05K (7/20336)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4000776	12/1976	Kroebig et al.	N/A	N/A
4196504	12/1979	Eastman	N/A	N/A
4274479	12/1980	Eastman	N/A	N/A
4279294	12/1980	Fitzpatrick et al.	N/A	N/A
4545799	12/1984	Rhodes et al.	N/A	N/A
4854379	12/1988	Shaubach et al.	N/A	N/A
5000256	12/1990	Tousignant	N/A	N/A
5157893	12/1991	Benson et al.	N/A	N/A
5175975	12/1992	Benson et al.	N/A	N/A
5343940	12/1993	Jean	N/A	N/A
5360058	12/1993	Koepl et al.	N/A	N/A
5560423	12/1995	Larson et al.	N/A	N/A
5735339	12/1997	Davenport et al.	N/A	N/A
6056044	12/1999	Benson et al.	N/A	N/A
6082443	12/1999	Yamamoto et al.	N/A	N/A
6139974	12/1999	Atkinson et al.	N/A	N/A
6158502	12/1999	Thomas	N/A	N/A
6269866	12/2000	Yamamoto et al.	N/A	N/A
6446706	12/2001	Rosenfeld et al.	N/A	N/A
6533029	12/2002	Phillips	N/A	N/A
6561262	12/2002	Osakabe et al.	N/A	N/A
6763671	12/2003	Klett et al.	N/A	N/A
6896039	12/2004	Dussinger et al.	N/A	N/A
6912130	12/2004	Osanai et al.	N/A	N/A
6938481	12/2004	Paterek et al.	N/A	N/A
6994151	12/2005	Zhou et al.	N/A	N/A
7028713	12/2005	Koyama	N/A	N/A

7037400	12/2005	Shaw et al.	N/A	N/A
7069978	12/2005	Rosenfeld et al.	N/A	N/A
7100680	12/2005	Dussinger et al.	N/A	N/A
7219713	12/2006	Gelorme et al.	N/A	N/A
7278469	12/2006	Sasaki et al.	N/A	N/A
8018128	12/2010	Egawa et al.	N/A	N/A
8069907	12/2010	Bryant	361/679.52	F28D 15/04
8560031	12/2012	Barnett et al.	N/A	N/A
8579018	12/2012	Roper et al.	N/A	N/A
8646281	12/2013	Lim	N/A	N/A
8807203	12/2013	MacDonald et al.	N/A	N/A
8921702	12/2013	Carter et al.	N/A	N/A
8985197	12/2014	Wang	N/A	N/A
9127898	12/2014	Wong	N/A	N/A
9149896	12/2014	Batty et al.	N/A	N/A
9163883	12/2014	Yang et al.	N/A	N/A
9597657	12/2016	Zhamu et al.	N/A	N/A
9600041	12/2016	Ady et al.	N/A	N/A
9651312	12/2016	Yang et al.	N/A	N/A
9700930	12/2016	Yang	N/A	N/A
9835383	12/2016	Roper et al.	N/A	N/A
9909814	12/2017	Yang et al.	N/A	N/A
9921004	12/2017	Lewis et al.	N/A	N/A
10066876	12/2017	Zhou et al.	N/A	N/A
10281220	12/2018	Lin et al.	N/A	N/A
10458719	12/2018	Bozorgi et al.	N/A	N/A
10527358	12/2019	Yang et al.	N/A	N/A
10544994	12/2019	Wakaoka et al.	N/A	N/A
10571200	12/2019	Yang et al.	N/A	N/A
10973151	12/2020	Wakaoka et al.	N/A	N/A
10980148	12/2020	Cheng	N/A	N/A
11054189	12/2020	Salim Shirazy et al.	N/A	N/A
11054190	12/2020	Inagaki et al.	N/A	N/A
11058031	12/2020	Numoto et al.	N/A	N/A
11150030	12/2020	Kishimoto et al.	N/A	N/A
11445636	12/2021	Wakaoka et al.	N/A	N/A
2001/0054495	12/2000	Yevin et al.	N/A	N/A
2003/0042009	12/2002	Phillips	N/A	N/A
2003/0051859	12/2002	Chesser et al.	N/A	N/A
2003/0079863	12/2002	Sugito et al.	N/A	N/A
2003/0102118	12/2002	Sagal et al.	N/A	N/A
2003/0136547	12/2002	Gollan et al.	N/A	N/A
2003/0136550	12/2002	Tung et al.	N/A	N/A
2003/0136551	12/2002	Bakke	N/A	N/A
2003/0159806	12/2002	Sehmbey et al.	N/A	N/A
2004/0011509	12/2003	Siu	N/A	N/A
2004/0050533	12/2003	Chesser et al.	N/A	N/A
2004/0131877	12/2003	Hasz et al.	N/A	N/A
2004/0134548	12/2003	Koyama	N/A	N/A

2004/0211549	12/2003	Garner et al.	N/A	N/A
2004/0244951	12/2003	Dussinger et al.	N/A	N/A
2005/0059238	12/2004	Chen et al.	N/A	N/A
2005/0126757	12/2004	Bennett et al.	N/A	N/A
2005/0190810	12/2004	Butterworth et al.	N/A	N/A
2005/0230085	12/2004	Valenzuela	N/A	N/A
2005/0280128	12/2004	Mok et al.	N/A	N/A
2005/0280162	12/2004	Mok et al.	N/A	N/A
2006/0032615	12/2005	Dussinger et al.	N/A	N/A
2006/0037737	12/2005	Chen et al.	N/A	N/A
2006/0090882	12/2005	Sauciuc	N/A	N/A
2006/0098411	12/2005	Lee et al.	N/A	N/A
2006/0124280	12/2005	Lee et al.	N/A	N/A
2006/0131002	12/2005	Mochizuki et al.	N/A	N/A
2006/0162905	12/2005	Hsu	N/A	N/A
2006/0196640	12/2005	Siu	N/A	N/A
2006/0196641	12/2005	Hong et al.	N/A	N/A
2006/0213648	12/2005	Chen et al.	N/A	N/A
2006/0283574	12/2005	Huang	N/A	N/A
2006/0283576	12/2005	Lai et al.	N/A	N/A
2007/0006993	12/2006	Meng et al.	N/A	N/A
2007/0035927	12/2006	Erturk et al.	N/A	N/A
2007/0056714	12/2006	Wong	N/A	N/A
2007/0068657	12/2006	Yamamoto et al.	N/A	N/A
2007/0077165	12/2006	Hou et al.	N/A	N/A
2007/0089864	12/2006	Chang et al.	N/A	N/A
2007/0095507	12/2006	Henderson et al.	N/A	N/A
2007/0107875	12/2006	Lee et al.	N/A	N/A
2007/0107878	12/2006	Hou et al.	N/A	N/A
2007/0158050	12/2006	Norley et al.	N/A	N/A
2008/0017356	12/2007	Gruss et al.	N/A	N/A
2008/0029249	12/2007	Hsiao	N/A	N/A
2008/0067502	12/2007	Chakrapani et al.	N/A	N/A
2008/0111151	12/2007	Teraki et al.	N/A	N/A
2008/0128116	12/2007	Dangelo et al.	N/A	N/A
2008/0128898	12/2007	Henderson et al.	N/A	N/A
2008/0210407	12/2007	Kim et al.	N/A	N/A
2008/0224303	12/2007	Funakoshi et al.	N/A	N/A
2008/0272482	12/2007	Jensen et al.	N/A	N/A
2008/0283222	12/2007	Chang et al.	N/A	N/A
2009/0020269	12/2008	Chang et al.	N/A	N/A
2009/0020272	12/2008	Shimizu	N/A	N/A
2009/0025910	12/2008	Hoffman et al.	N/A	N/A
2009/0056917	12/2008	Majumdar et al.	N/A	N/A
2009/0151906	12/2008	Lai et al.	N/A	N/A
2009/0159242	12/2008	Zhao et al.	N/A	N/A
2009/0205812	12/2008	Meyer, IV et al.	N/A	N/A
2009/0236080	12/2008	Lin et al.	N/A	N/A
2009/0294104	12/2008	Lin et al.	N/A	N/A
2009/0316335	12/2008	Simon et al.	N/A	N/A

2010/0028604	12/2009	Bhushan et al.	N/A	N/A
2010/0053899	12/2009	Hashimoto et al.	N/A	N/A
2010/0071879	12/2009	Hou	N/A	N/A
2010/0084113	12/2009	Lee	N/A	N/A
2010/0139767	12/2009	Hsieh et al.	N/A	N/A
2010/0157535	12/2009	Oniki et al.	N/A	N/A
2010/0175854	12/2009	Gratton	N/A	N/A
2010/0200199	12/2009	Habib et al.	N/A	N/A
2010/0252237	12/2009	Hashimoto et al.	N/A	N/A
2010/0254090	12/2009	Trautman	N/A	N/A
2010/0290190	12/2009	Chester et al.	N/A	N/A
2010/0294200	12/2009	Zhang et al.	N/A	N/A
2010/0300656	12/2009	Lu et al.	N/A	N/A
2011/0017431	12/2010	Yang et al.	N/A	N/A
2011/0027311	12/2010	Deng et al.	N/A	N/A
2011/0083829	12/2010	Hung et al.	N/A	N/A
2011/0088873	12/2010	Yang	N/A	N/A
2011/0108142	12/2010	Liu et al.	N/A	N/A
2011/0120674	12/2010	MacDonald	29/890.03	F28D 15/046
2011/0174474	12/2010	Liu et al.	N/A	N/A
2011/0198059	12/2010	Gavillet et al.	N/A	N/A
2011/0205708	12/2010	Andry et al.	N/A	N/A
2012/0037210	12/2011	Lim	N/A	N/A
2012/0048516	12/2011	He et al.	N/A	N/A
2012/0061127	12/2011	Fields et al.	N/A	N/A
2012/0168435	12/2011	Chen et al.	N/A	N/A
2012/0186784	12/2011	Yang et al.	N/A	N/A
2012/0189839	12/2011	Aoki et al.	N/A	N/A
2012/0241216	12/2011	Coppeta et al.	N/A	N/A
2012/0312504	12/2011	Suzuki et al.	N/A	N/A
2012/0325437	12/2011	Meyer, IV et al.	N/A	N/A
2013/0014919	12/2012	Dai et al.	N/A	N/A
2013/0043000	12/2012	Wang	N/A	N/A
2013/0049018	12/2012	Ramer et al.	N/A	N/A
2013/0168057	12/2012	Semenic et al.	N/A	N/A
2013/0199770	12/2012	Cherian	N/A	N/A
2013/0269913	12/2012	Ueda	165/104.26	F28D 15/0233
2013/0327504	12/2012	Bozorgi et al.	N/A	N/A
2014/0009883	12/2013	Fujiwara et al.	N/A	N/A
2014/0017456	12/2013	Xiao et al.	N/A	N/A
2014/0055954	12/2013	Wu	N/A	N/A
2014/0174700	12/2013	Lin et al.	N/A	N/A
2014/0174701	12/2013	Kare et al.	N/A	N/A
2014/0237823	12/2013	Yang	N/A	N/A
2014/0238645	12/2013	Enright	N/A	N/A
2014/0238646	12/2013	Enright	N/A	N/A
2014/0247556	12/2013	Eid et al.	N/A	N/A
2015/0000884	12/2014	Jiang et al.	N/A	N/A
2015/0181756	12/2014	Sato et al.	N/A	N/A

2015/0226493	12/2014	Yang et al.	N/A	N/A
2015/0237762	12/2014	Holt et al.	N/A	N/A
2015/0289413	12/2014	Rush et al.	N/A	N/A
2016/0018165	12/2015	Ahamed et al.	N/A	N/A
2016/0076820	12/2015	Lewis et al.	N/A	N/A
2016/0081227	12/2015	Lee et al.	N/A	N/A
2016/0123678	12/2015	Hulse et al.	N/A	N/A
2016/0131437	12/2015	Wu	N/A	N/A
2016/0161193	12/2015	Lewis et al.	N/A	N/A
2016/0216042	12/2015	Bozorgi et al.	N/A	N/A
2016/0295980	12/2015	Wu	N/A	N/A
2016/0343639	12/2015	Groothuis et al.	N/A	N/A
2017/0030654	12/2016	Yang et al.	N/A	N/A
2017/0064868	12/2016	Rush et al.	N/A	N/A
2017/0122672	12/2016	Lin	N/A	N/A
2017/0241717	12/2016	Sun et al.	N/A	N/A
2017/0292793	12/2016	Sun et al.	N/A	N/A
2017/0318702	12/2016	Basu et al.	N/A	N/A
2017/0343293	12/2016	Hurbi et al.	N/A	N/A
2017/0350657	12/2016	Yeh et al.	N/A	N/A
2018/0010861	12/2017	Wakaoka et al.	N/A	N/A
2018/0106554	12/2017	Lewis et al.	N/A	N/A
2018/0320984	12/2017	Lewis et al.	N/A	N/A
2018/0320985	12/2017	Salim Shirazy et al.	N/A	N/A
2019/0271511	12/2018	Kishimoto et al.	N/A	N/A
2019/0323780	12/2018	Ahamed et al.	N/A	N/A
2019/0390919	12/2018	Lewis et al.	N/A	N/A
2020/0003501	12/2019	Wakaoko	N/A	N/A
2020/0045847	12/2019	Wakaoka et al.	N/A	N/A
2020/0045848	12/2019	Wakaoko et al.	N/A	N/A
2020/0049421	12/2019	Wakaoka et al.	N/A	N/A
2020/0060044	12/2019	Numoto et al.	N/A	N/A
2020/0124352	12/2019	Wakaoka et al.	N/A	N/A
2020/0240718	12/2019	Wakaoko et al.	N/A	N/A
2021/0025061	12/2020	Yang et al.	N/A	N/A
2021/0136955	12/2020	Wakaoka et al.	N/A	N/A
2021/0148646	12/2020	Sun et al.	N/A	N/A
2022/0120510	12/2021	Wu et al.	N/A	N/A
2022/0128314	12/2021	Inagaki et al.	N/A	N/A
2022/0294485	12/2021	Li et al.	N/A	N/A
2023/0017904	12/2022	Lai et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2522409	12/2001	CN	N/A
2715467	12/2004	CN	N/A
1672258	12/2004	CN	N/A
1877241	12/2005	CN	N/A

1957221	12/2006	CN	N/A
101022718	12/2006	CN	N/A
101080359	12/2006	CN	N/A
101151950	12/2007	CN	N/A
100480611	12/2008	CN	N/A
100508708	12/2008	CN	N/A
101754656	12/2009	CN	N/A
102019543	12/2010	CN	N/A
102066864	12/2010	CN	N/A
202928418	12/2012	CN	N/A
103398613	12/2012	CN	N/A
103952729	12/2013	CN	N/A
209930339	12/2019	CN	N/A
19729922	12/1998	DE	N/A
202009016739	12/2009	DE	N/A
1369918	12/2002	EP	N/A
1379825	12/2003	EP	N/A
2713132	12/2013	EP	N/A
2529512	12/2015	GB	N/A
H1197871	12/1998	JP	N/A
2011080679	12/2010	JP	N/A
2013148289	12/2012	JP	N/A
2018204941	12/2017	JP	N/A
2019016883	12/2018	JP	N/A
M544733	12/2016	TW	N/A
03103835	12/2002	WO	N/A
2006052763	12/2005	WO	N/A
2006115326	12/2005	WO	N/A
2006123049	12/2005	WO	N/A
2007124028	12/2006	WO	N/A
2008044823	12/2007	WO	N/A
2008045004	12/2007	WO	N/A
2008146129	12/2007	WO	N/A
2009079084	12/2008	WO	N/A
2010036442	12/2009	WO	N/A
2013144444	12/2012	WO	N/A
2015172136	12/2014	WO	N/A
2015193153	12/2014	WO	N/A
2016044180	12/2015	WO	N/A

OTHER PUBLICATIONS

Restriction Requirement dated Jul. 23, 2012 in U.S. Appl. No. 12/719,775, 9 pages. cited by applicant

Non-Final Office Action dated Nov. 9, 2012 in U.S. Appl. No. 12/719,775, 15 pages. cited by applicant

Final Office Action dated May 9, 2013 in U.S. Appl. No. 12/719,775, 15 pages. cited by applicant

Advisory Action dated Aug. 2, 2013 in U.S. Appl. No. 12/719,775, 4 pages. cited by applicant

Non-Final Office Action dated Oct. 2, 2013 in U.S. Appl. No. 12/719,775, 17 pages. cited by applicant

Final Office Action dated Mar. 26, 2014 in U.S. Appl. No. 12/719,775, 23 pages. cited by applicant

Advisory Action dated Jun. 20, 2014 in U.S. Appl. No. 12/719,775, 4 pages. cited by applicant

Non-Final Office Action dated Feb. 6, 2015 in U.S. Appl. No. 12/719,775, 24 pages. cited by applicant

Restriction Requirement dated Jul. 28, 2015 in U.S. Appl. No. 14/681,624, 5 pages. cited by applicant

Notice of Allowance in dated Aug. 4, 2015 U.S. Appl. No. 12/719,775, 9 pages. cited by applicant

Non-Final Office Action dated Oct. 23, 2015 in U.S. Appl. No. 14/681,624, 11 pages. cited by applicant

International Search Report and Written Opinion dated Dec. 18, 2015 as received in PCT Application No. PCT/US2015/050031, 13 pages. cited by applicant

International Search Report and Written Opinion dated Dec. 18, 2015 as received in PCT Application No. PCT/US2015/050771, 13 pages. cited by applicant

Final Office Action dated May 5, 2016 in U.S. Appl. No. 14/681,624, 11 pages. cited by applicant

International Search Report and Written Opinion mailed dated Jul. 15, 2016 as received in PCT Application No. PCT/US2015/057885, 10 pages. cited by applicant

Notice of Allowance dated Nov. 17, 2016 in U.S. Appl. No. 14/681,624, 7 pages. cited by applicant

International Preliminary Report on Patentability dated Mar. 21, 2017 as received in PCT Application No. PCT/US2015/050031, 8 pages. cited by applicant

International Preliminary Report on Patentability dated Mar. 21, 2017 as received in PCT Application No. PCT/US2015/050771, 6 pages. cited by applicant

International Preliminary Report on Patentability dated May 2, 2017 as received in PCT Application No. PCT/US2015/057885, 5 pages. cited by applicant

Preinterview First Office Action dated May 9, 2017 in U.S. Appl. No. 14/861,708, 9 pages. cited by applicant

Non-Final Office Action dated Aug. 9, 2017 in U.S. Appl. No. 14/925,787, 16 pages. cited by applicant

Restriction Requirement dated Aug. 30, 2017 in U.S. Appl. No. 14/853,833, 7 pages. cited by applicant

Final Office Action dated Sep. 28, 2017 in U.S. Appl. No. 14/925,787, 9 pages. cited by applicant

Non-Final Office Action dated Oct. 6, 2017 in U.S. Appl. No. 14/853,833, 13 pages. cited by applicant

Notice of Allowance dated Oct. 25, 2017 in U.S. Appl. No. 14/861,708, 9 pages. cited by applicant

Notice of Allowance dated Nov. 9, 2017 in U.S. Appl. No. 14/925,787, 7 pages. cited by applicant

Preinterview First Office Action dated Nov. 21, 2017 in U.S. Appl. No. 14/857,567, 12 pages. cited by applicant

International Search Report and Written Opinion mailed dated Jan. 17, 2018 as received in PCT Application No. PCT/US2017/060550, 13 pages. cited by applicant

Extended European search report Application mailed Feb. 22, 2018, as received in EP Application No. 15842101.6, 7 pages. cited by applicant

Final Office Action dated Mar. 8, 2018 in U.S. Appl. No. 14/857,567, 25 pages. cited by applicant

Extended European search report mailed Mar. 26, 2018, as received in EP Application No. 15841403.7, 10 pages. cited by applicant

Final Office Action dated Apr. 25, 2018 in U.S. Appl. No. 14/853,833, 12 pages. cited by applicant

First Office Action mailed May 9, 2018, as received in CN Application No. 201580049534, 13 pages. cited by applicant

Advisory Action dated May 30, 2018 in U.S. Appl. No. 14/857,567, 7 pages. cited by applicant

Non-Final Office Action dated Aug. 2, 2018 in U.S. Appl. No. 14/857,567, 30 pages. cited by applicant

First Office Action mailed Aug. 28, 2018, as received in CN Application No. 201580059333, 10 pages. cited by applicant

Restriction Requirement dated Aug. 30, 2018 in U.S. Appl. No. 15/292,932, 5 pages. cited by applicant

Non-Final Office Action dated Sep. 27, 2018 in U.S. Appl. No. 15/787,455, 15 pages. cited by applicant

Restriction Requirement dated Oct. 10, 2018 in U.S. Appl. No. 15/436,632, 5 pages. cited by applicant

International Search Report and Written Opinion mailed dated Oct. 15, 2018 received in PCT Application No. PCT/US2018/031632, 15 pages. cited by applicant

Final Office Action dated Oct. 30, 2018 in U.S. Appl. No. 14/857,567, 28 pages. cited by applicant

Non-Final Office Action dated Nov. 19, 2018 in U.S. Appl. No. 14/853,833, 11 pages. cited by applicant

Non-Final Office Action dated Dec. 11, 2018 in U.S. Appl. No. 15/292,932, 13 pages. cited by applicant

Second Office Action mailed Dec. 29, 2018, as received in CN Application No. 201580049534, 14 pages. cited by applicant

Non-Final Office Action dated Feb. 5, 2019 in U.S. Appl. No. 15/436,632, 10 pages. cited by applicant

Non-Final Office Action dated Mar. 21, 2019 in U.S. Appl. No. 14/857,567, 28 pages. cited by applicant

Final Office Action dated Mar. 29, 2019 in U.S. Appl. No. 14/853,833, 12 pages. cited by applicant

Final Office Action dated Mar. 29, 2019 in U.S. Appl. No. 15/292,932, 13 pages. cited by applicant

Final Office Action dated Apr. 1, 2019 in U.S. Appl. No. 15/787,455, 20 pages. cited by applicant

Non-Final Office Action dated Apr. 5, 2019 in U.S. Appl. No. 15/806,723, 12 pages. cited by applicant

International Preliminary Report on Patentability dated May 14, 2019 as received in PCT Application No. PCT/US2017/060550, 7 pages. cited by applicant

Final Office Action dated May 28, 2019 in U.S. Appl. No. 15/436,632, 14 pages. cited by applicant

Advisory Action dated Jul. 19, 2019 in U.S. Appl. No. 15/292,932, 4 pages. cited by applicant

Advisory Action dated Aug. 22, 2019 in U.S. Appl. No. 15/787,455, 4 pages. cited by applicant

Final Office Action dated Aug. 26, 2019 in U.S. Appl. No. 14/857,567, 27 pages. cited by applicant

Notice of Allowance dated Sep. 12, 2019 in U.S. Appl. No. 15/292,932, 7 pages. cited by applicant

Non-Final Office Action dated Sep. 17, 2019 in U.S. Appl. No. 15/787,455, 20 pages. cited by applicant

Notice of Allowance dated Oct. 10, 2019 in U.S. Appl. No. 15/436,632, 10 pages. cited by applicant

Final Office Action dated Oct. 11, 2019 in U.S. Appl. No. 15/806,723, 18 pages. cited by applicant

Advisory Action dated Nov. 7, 2019 in U.S. Appl. No. 14/857,567, 7 pages. cited by applicant

International Preliminary Report on Patentability dated Nov. 12, 2019 received in PCT Application No. PCT/US2018/031632, 7 pages. cited by applicant

Non-Final Office Action dated Nov. 29, 2019 in U.S. Appl. No. 14/857,567, 32 pages. cited by applicant

Advisory Action dated Feb. 3, 2020 in U.S. Appl. No. 15/806,723, 5 pages. cited by applicant

Restriction Requirement dated Feb. 13, 2020 in U.S. Appl. No. 15/974,306, 5 pages. cited by applicant

Office Action mailed Feb. 18, 2020, as received in EP Application No. 15841403.7, 4 pages. cited by applicant

Final Office Action dated Feb. 18, 2020 in U.S. Appl. No. 15/787,455, 17 pages. cited by applicant

Non-Final Office Action dated Mar. 18, 2020 in U.S. Appl. No. 15/806,723, 6 pages. cited by applicant

International Search Report and Written Opinion dated Apr. 8, 2020 as received in PCT Application

No. PCT/US2019/065701, 16 pages. cited by applicant
Office Action mailed Apr. 9, 2020, as received in EP Application No. 15842101.6, 7 pages. cited by applicant
Notice of Allowance dated Apr. 15, 2020 in U.S. Appl. No. 14/857,567, 13 pages. cited by applicant
Notice of Allowance dated Apr. 20, 2020 in U.S. Appl. No. 15/806,723, 8 pages. cited by applicant
Advisory Action dated May 1, 2020 in U.S. Appl. No. 15/787,455, 4 pages. cited by applicant
Non-Final Office Action dated May 29, 2020 in U.S. Appl. No. 15/974,306, 11 pages. cited by applicant
First Office Action received Jun. 1, 2020, in related CN application No. 201910233277.1, 18 Pages. cited by applicant
First Office Action mailed Jun. 4, 2020, as received in CN Application No. 201580050472, 15 pages. cited by applicant
Extended European search report Application mailed Jun. 12, 2020, as received in EP Application No. 17870153.8, 9 pages. cited by applicant
First Office Action mailed Jul. 24, 2020, as received in CN Application No. 201910754250, 19 pages. cited by applicant
International Search Report and Written Opinion Application mailed Jul. 13, 2020, as received in PCT Application No. PCT/US2020/030911, 9 pages. cited by applicant
First Office Action mailed Sep. 24, 2020, as received in CN Application No. 201880030856, 19 pages. cited by applicant
Restriction Requirement dated Oct. 14, 2020 in U.S. Appl. No. 16/539,848, 8 pages. cited by applicant
Non-Final Office Action dated Oct. 26, 2020 in U.S. Appl. No. 16/539,848, 13 pages. cited by applicant
Office Action mailed Nov. 17, 2020, as received in EP Application No. 15842101.6, 5 pages. cited by applicant
Office Action mailed Nov. 18, 2020, as received in EP Application No. 15841403.7, 5 pages. cited by applicant
Extended European search report Application mailed Dec. 16, 2020, as received in EP Application No. 18798835.7, 8 pages. cited by applicant
Final Office Action dated Jan. 11, 2021 in U.S. Appl. No. 15/974,306, 12 pages. cited by applicant
Final Office Action dated Feb. 2, 2021 in U.S. Appl. No. 16/539,848, 10 pages. cited by applicant
Second Office Action mailed Mar. 16, 2021, as received in CN Application No. 201910233277.1, 21 pages. cited by applicant
Restriction Requirement dated Apr. 9, 2021 in U.S. Appl. No. 16/710,180, 8 pages. cited by applicant
Advisory Action dated Apr. 9, 2021 in U.S. Appl. No. 16/539,848, 4 pages. cited by applicant
Advisory Action dated Apr. 16, 2021 in U.S. Appl. No. 15/974,306, 4 pages. cited by applicant
Third Office Action mailed Apr. 19, 2021, as received in CN Application No. 201580049534, 7 pages. cited by applicant
Non-Final Office Action dated May 11, 2021 in U.S. Appl. No. 16/539,848, 10 pages. cited by applicant
Non-Final Office Action dated May 17, 2021 in U.S. Appl. No. 15/974,306, 9 pages. cited by applicant
International Preliminary Report on Patentability dated Jun. 8, 2021 as received in PCT Application No. PCT/US2019/065701, 7 pages. cited by applicant
Restriction Requirement dated Jun. 9, 2021 in U.S. Appl. No. 16/680,480, 6 pages. cited by applicant
Non-Final Office Action dated Jul. 9, 2021 in U.S. Appl. No. 15/930,016, 18 pages. cited by

applicant
Final Office Action dated Dec. 17, 2021 in U.S. Appl. No. 15/930,016, 19 pages. cited by applicant
Restriction Requirement dated Jul. 19, 2021 in U.S. Appl. No. 16/710,180, 7 pages. cited by applicant
Restriction Requirement dated Aug. 30, 2021 in U.S. Appl. No. 17/352,250, 7 pages. cited by applicant
Notice of Allowance dated Sep. 9, 2021 in U.S. Appl. No. 15/787,455, 8 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/864,236 dated Nov. 29, 2023, 11 pages. cited by applicant
Non-Final Office Action dated Oct. 5, 2021 in U.S. Appl. No. 16/680,480, 12 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/710,180 dated Dec. 13, 2021, 14 pages. cited by applicant
International Search Report and Written Opinion in PCT Application No. PCT/US2021/038152 mailed on Sep. 29, 2021, 14 pages. cited by applicant
Advisory Action dated Feb. 9, 2022 in U.S. Appl. No. 16/539,848, 4 pages. cited by applicant
Restriction Requirement in U.S. Appl. No. 16/864,236 dated Feb. 7, 2022, 8 pages. cited by applicant
Final Office Action in U.S. Appl. No. 16/539,848 dated Nov. 29, 2021, 11 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/539,848 dated Mar. 28, 2022, 11 pages. cited by applicant
Final Office Action in U.S. Appl. No. 16/710,180 dated Apr. 7, 2022, 15 pages. cited by applicant
Notice of Allowance dated Feb. 28, 2022 in U.S. Appl. No. 16/680,480, 9 pages. cited by applicant
Final Office Action in U.S. Appl. No. 15/787,455 dated Feb. 24, 2022, 24 pages. cited by applicant
Non-Final Office Action dated Nov. 5, 2021 in U.S. Appl. No. 17/352,250, 17 pages. cited by applicant
Final Office Action in U.S. Appl. No. 17/352,250 dated Mar. 11, 2022, 17 pages. cited by applicant
Non-Final Office Action dated Nov. 8, 2021 in U.S. Appl. No. 15/787,455, 17 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/864,236 mailed on Oct. 6, 2022, 11 pages. cited by applicant
China Office Action in CN Application No. 201780082663.4 dated Sep. 20, 2022, 22 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 17/529,248 mailed on Dec. 22, 2022, 9 pages. cited by applicant
Advisory Action in U.S. Appl. No. 16/710,180 dated Sep. 23, 2022, 3 pages. cited by applicant
Final Office Action in U.S. Appl. No. 16/710,180 dated Nov. 14, 2022, 14 pages. cited by applicant
Advisory Action in U.S. Appl. No. 16/539,848 dated Nov. 28, 2022, 3 pages. cited by applicant
Final Office Action in U.S. Appl. No. 16/539,848 dated Sep. 13, 2022, 11 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 16/539,848 dated Dec. 29, 2022, 12 pages. cited by applicant
Non-Final Office Action in U.S. Appl. No. 15/930,016 dated Jul. 27, 2022, 16 pages. cited by applicant
Notice of Allowance in U.S. Appl. No. 15/930,016 dated Dec. 1, 2022, 9 pages. cited by applicant
Final Office Action dated May 17, 2023 in U.S. Appl. No. 16/539,848, 10 pages. cited by applicant
Final Office Action in U.S. Appl. No. 16/710,180 dated Mar. 24, 2023, 14 pages. cited by applicant
Final Office Action in U.S. Appl. No. 16/864,236 mailed on Apr. 10, 2023, 11 pages. cited by applicant
Final Office Action in U.S. Appl. No. 17/529,248 mailed on Apr. 25, 2023, 7 pages. cited by applicant

Restriction Requirement dated Apr. 20, 2023 in U.S. Appl. No. 17/666,537, 6 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/666,537 dated Aug. 1, 2023, 10 pages. cited by applicant

Notice of Allowance in U.S. Appl. No. 17/666,537 dated Feb. 15, 2024, 9 pages. cited by applicant

Restriction Requirement in U.S. Appl. No. 17/592,490 dated Jun. 10, 2024, 8 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/592,490 dated Nov. 19, 2024, 17 pages. cited by applicant

International Search Report and Written Opinion in PCT Application No. PCT/US2024/027116 mailed on Sep. 4, 2024, 12 pages. cited by applicant

Junjiao, H., et al., "Development of heat pipe cooling technology in high heat flux electronic components", Chemical Industry and Engineering Progress, Chemical Industry and Engineering Progress, vol. 34, Issue. 5, pp. 1220-1231 (May 5, 2015). cited by applicant

Restriction Requirement in U.S. Appl. No. 18/666,811 dated Dec. 5, 2024, 5 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 17/951,075 mailed on Jun. 4, 2024, 21 pages. cited by applicant

Final Office Action in U.S. Appl. No. 17/951,075 mailed on Nov. 20, 2024, 20 pages. cited by applicant

Restriction Requirement in U.S. Appl. No. 18/004,059 dated May 2, 2024, 7 pages. cited by applicant

Restriction Requirement in U.S. Appl. No. 18/004,059 dated Sep. 30, 2024, 7 pages. cited by applicant

Final Office Action in U.S. Appl. No. 16/864,236 mailed on Jun. 7, 2024, 11 pages. cited by applicant

Non-Final Office Action in U.S. Appl. No. 16/864,236 mailed on Dec. 20, 2024, 13 pages. cited by applicant

Primary Examiner: Nouketcha; Lionel

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation in part of patent application Ser. No. 14/857,567, filed Sep. 17, 2015, titled MICROPILLAR-ENABLED THERMAL GROUND PLANE, which claims priority from U.S. Provisional Patent Application No. 62/051,761, filed Sep. 17, 2014, titled MICROPILLAR-ENABLED THERMAL GROUND PLANE; and a non-provisional of U.S. Provisional Patent Application No. 62/069,564, filed Oct. 28, 2014, titled POLYMER-BASED MICROFABRICATED THERMAL GROUND PLANE, each of which are incorporated into this disclosure by reference in their entireties.

SUMMARY

(1) A thermal ground plane (TGP) is disclosed. The TGP may include a first planar substrate member configured to enclose a working fluid; a second planar substrate member configured to enclose the working fluid; a plurality of wicking structures disposed on the first planar substrate; and one or more planar spacers disposed on the second planar substrate. The first planar substrate and the second planar substrate may be hermetically sealed.

(2) In some embodiments, the plurality of wicking structures comprise a plurality of pillars or

channels disposed on the first planar substrate member and/or the plurality of wicking structures comprise a plurality of pillars or channels formed on the second planar substrate member.

(3) In some embodiments, the first planar substrate member and/or the second planar substrate member comprise a metallic layer, a copper-cladded polymer layer with thermal vias, a copper-cladded polymer layer without thermal vias, a polymer-coated copper layer, a metallic layer encapsulated by a hydrophilic coating, a copper metallic layer encapsulated by a hydrophilic hydrophobic coating, and/or a polymer layer encapsulated by a metallic layer, a polymer layer encapsulated by a hydrophilic coating, and/or a polymer layer encapsulated by a hydrophobic coating. In some embodiments, the first planar substrate member (e.g., a metal cladding layer) and/or the second planar substrate member may be thicker in one or more regions such as, for example, regions near the evaporator or the condenser.

(4) In some embodiments, the plurality of wicking structures comprise a plurality of copper pillars bonded with a mesh layer.

(5) In some embodiments, the plurality of wicking structures may comprise a material with at least one property selected from the list consisting of copper mesh, stainless steel mesh, metal mesh, polymer mesh, copper-encapsulated mesh, a mesh encapsulated by a hydrophilic coating, a mesh encapsulated by a hydrophobic coating, and a mesh encapsulated by a hermetic seal.

(6) In some embodiments, the plurality of wicking structures comprise copper pillars bonded with a stainless steel mesh encapsulated by copper or a copper mesh.

(7) In some embodiments, the one or more planar spacers comprise copper pillars bonded with a stainless steel mesh encapsulated by copper or a copper mesh.

(8) In some embodiments, the one or more planar spacers comprise a plurality of copper pillars or channels.

(9) In some embodiments, the one or more planar spacers comprise a plurality of pillars or channels with various star-shaped cross sections, such as rectangular, circular, and/or star-shaped.

(10) In some embodiments, the plurality of wicking structures comprise polymer pillars hermetically sealed by copper or other coatings, and/or enhanced with a hydrophilic coating or a hydrophobic coating.

(11) In some embodiments, the plurality of wicking structures comprise a mesh layer. The mesh layer, for example, may include a mesh selected from the list consisting of copper mesh, stainless steel mesh, metal mesh, polymer mesh and copper-encapsulated mesh. The mesh layer, for example, may include a hydrophilic coating or a hydrophobic coating or hermetic coating.

(12) In some embodiments, the plurality of wicking structures and/or the one or more planar spacers are deposited using a lithographic patterning process.

(13) In some embodiments, the hermetical seal can be an ultrasound-welded, an electrostatic-welded, or a laser-welded copper-to-copper interface.

(14) In some embodiments, the hermetical seal can include a seal selected from the list consisting of a copper-silver sintered interface, a tin/lead solder, and a lead-free solder alloy.

(15) A thermal ground plane (TGP) is disclosed. The TGP may include a top layer; a mesh layer comprising a plurality of arteries formed along a length of the mesh layer; and a bottom layer comprising a plurality of pillars that extend into the plurality of arteries/. The bottom layer and the top layer may be sealed around at least one edge of the top layer and at least one edge of the bottom layer. Each of the plurality of pillars may have at least one dimension that is less than a dimension of at least one of the plurality of arteries.

(16) In some embodiments, the plurality of arteries may be cut from the mesh layer. In some embodiments, the TGP may include a micro-wick layer disposed on the bottom layer. In some embodiments, the TGP may include a plurality of pillars disposed on the top layer.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.
- (2) These and other features, aspects, and advantages of the present disclosure are better understood when the following Detailed Description is read with reference to the accompanying drawings. The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.
- (3) FIG. 1 is a graph illustrating the maximum allowable surface temperatures of a mobile system using different materials with different contact duration.
- (4) FIG. 2 is an example infrared image of illustrating a non-uniformly heated mobile device without effective heat spreading according to some embodiments.
- (5) FIG. 3 illustrates an example diagram of a thermal ground plane (TGP) according to some embodiments.
- (6) FIG. 4 illustrates examples of flexible thermal ground planes according to some embodiments.
- (7) FIG. 5 illustrates the thermal resistance from an evaporation region to a condensation region of a TGP according to some embodiments calibrated with a 1 inch by 1 inch heater injecting heat to the TGP and 1 inch by 1 inch heat sink extracting heat from the TGP.
- (8) FIG. 6 illustrates a TGP according to some embodiments.
- (9) FIG. 7 shows a TGP with a top layer having pillars formed therein, a bottom layer having pillars formed therein, and a wicking structure according to some embodiments.
- (10) FIG. 8 illustrates the thinness of TGPs manufactured according to some embodiments.
- (11) FIG. 9 illustrates an example TGP having a bottom layer with copper pillars electroplated and bonded with a copper-coated stainless steel mesh according to some embodiments.
- (12) FIG. 10 shows a top layer with a plurality of copper pillars according to some embodiments.
- (13) FIG. 11 shows an experimental setup that can be used to characterize the properties of a thin flexible TGP with a condensation region defined by a cold plate according to some embodiments.
- (14) FIG. 12 is a graph showing the thermal resistances of a TGP manufactured according to some embodiments and using the experimental setups shown in FIG. 11.
- (15) FIG. 13 shows an experimental setup that can be used to characterize the properties of a thin flexible TGP with distributed condensers condensation where the heat is extracted by nature air convection according to some embodiments.
- (16) FIG. 14A illustrates another example TGP according to some embodiments.
- (17) FIG. 14B shows a TGP according to some embodiments.
- (18) FIG. 15 illustrates another example TGP according to some embodiments.
- (19) FIG. 16 illustrates an example process for fabricating a TGP according to some embodiments.
- (20) FIG. 17 illustrates a top view of another TGP 700 according to some embodiments.
- (21) FIGS. 18A, 18B, and 18C illustrate side views of the TGP shown in FIG. 17 according to some embodiments.
- (22) FIG. 19 illustrates a block diagram of a wicking structures according to some embodiments.
- (23) FIG. 20 illustrates a TGP according to some embodiments.

DETAILED DESCRIPTION

(24) One challenge for mobile systems, e.g., smartphones, tablets and wearable electronics, is the control of the skin temperatures. The skin temperature is the temperature of an exterior portion of a device (e.g., the case) that is touched by fingers, hands, face, ears, or any other part of a human body. When the temperature of a portion of a device reaches beyond the maximum allowable temperature, a user would consider the temperature of the device to be hot. Of course, this perception of heat is dependent on the materials and the duration of the contact; it also varies from

one person to another one due to their difference in thermal physiology. FIG. 1 illustrates a graph of acceptable skin temperatures for a number of different materials considering different touch duration.

(25) As illustrated in FIG. 2, a hot spot or region with a much higher temperature than other locations on a smart phone (or other device) could be generated by an electronic chip such as, for example, a 5-Watt processor or a 1-Watt, small-size wireless amplifier. These hot spots or regions could be removed by effective heat spreading since the temperatures in the area outside these hot spots can be much lower.

(26) Typically, a metal heat spreader, such as, for example, an aluminum or copper heat spreader, may be effective. However, the thickness of the metal heat spreader is being reduced in order to meet the demand for the reduction of the total system's thickness. For most mobile systems, a thinner configuration is usually desirable. With a thin metal heat spreader, its thermal resistance increases since it is affected by the thermal conductivity and cross-section area for heat conduction. Alternative approaches can use high thermal conductivity graphite heat spreaders. However, the thermal conductivity of graphite heat spreaders generally decreases with the thickness of the graphite layer. The high thermal conductivity graphite, e.g., thermal conductivity of 1,500 W/mK, is too thin, e.g., 0.017 mm, to be effective to transfer heat over a large area.

(27) Some embodiments include a thin thermal ground plane (TGP) with improved thermal performance. For example, a TGP may use phase-change heat transfer mechanisms with an evaporation-vapor transport-condensation-liquid return path for heat transfer. As another example, a TGP may be a very good heat spreader with effective thermal conductivities higher than that of a copper (see FIG. 5). In some embodiments, a TGP may include components and/or may be manufactured with processes described in U.S. patent application Ser. No. 12/719,775, entitled "Flexible Thermal Ground Plane and Manufacturing the Same," which is incorporated herein in its entirety for all purposes.

(28) Embodiments may also include a top layer including a plurality of spacers (or pillars) sealed with a bottom layer having a plurality of pillars. In some embodiments, the spacers may be deposited on the top layer using a lithographic patterning process. In some embodiments, the pillars may be deposited on the bottom layer using a lithographic patterning process. In some embodiments, the pillars and spacers may be bonded or scribed on the first and/or second planar substrate. In some embodiments, the pillars may have a diameter that is less than or greater than the diameter of the pillars and/or spacers. In some embodiments, the spacers pillars may have a spacing that is less than or greater than the spacing diameter of the pillars. In some embodiments, the pillars in the spacers may have a height, diameter or spacing that is less than or greater than the spacing of the pillars in the wicking structure.

(29) FIG. 3 illustrates a diagram of an example TGP **300** according to some embodiments. In this example, the TGP **300** includes a top layer **310**, a bottom layer **315**, a liquid channel **320**, and/or a vapor core **325**. The TGP **300**, for example, may operate with evaporation, vapor transport, condensation, and/or liquid return of water or other cooling media for heat transfer between the evaporation region **330** and the condensation region **335**. The top layer **310** may include copper, polyimide, polymer-coated copper, copper-cladded Kapton, etc. The top bottom layer **315** may include copper, polyimide, polymer-coated copper, copper-cladded Kapton, etc. In some embodiments, the top layer **310** and the bottom layer **315** of the TGP may be sealed together using solder, laser welding, ultrasonic welding, electrostatic welding, or thermo-pressure compression or a sealant **340**.

(30) In some embodiments, the liquid channel **320** may include copper mesh, stainless-steel mesh, or meshes made of other materials but encapsulated with copper. The liquid channel **320**, for example, may include one, two, three, four, five, six or more layers of mesh of the same or different materials. In some embodiments, the liquid channel **320** may be bonded and/or sealed using FEP (fluorinated ethylene propylene), electroplating, sintering, and/or other adhesives or sealants with

the top layer **310**. In some embodiments, in order to enhance hydrophilic properties of the metallic mesh, atomic layer deposition (ALD) of Al.sub.2O.sub.3, TiO.sub.2, SiO.sub.2, or other coatings may be used to encapsulate meshes of the liquid channel **320** with desirable functionality.

(31) In some embodiments, the vapor core **325** may include a plurality of pillars and/or channels disposed on the top layer **310**. The pillars and/or channels may be deposited using any type of deposition technique such as, for example, vapor deposition, etc.

(32) FIG. 4 illustrates examples of flexible thermal ground planes according to some embodiments. The TGP may include may an active region of various sizes, for example, the TGP may have at least one dimension (e.g., length, width, radius, diameter, etc.) that is less than 2 cm, 5 cm, 10 cm, 20 cm, 50 cm, 100 cm, 500 cm, 1000 cm, etc. and/or a thickness less than 0.1 mm, 0.25 mm, 0.5 mm, 1 mm, 10 mm 50 mm, 100 mm, etc. In a specific example, the active region may have dimensions of 9.5 cm×5 cm×0.1 cm.

(33) In some embodiments, a TGP may include a copper-cladded Kapton bottom layer and a copper-cladded Kapton top layer with a copper or metallic mesh and/or a polymer spacer sandwiched in between. The metallic mesh may be copper mesh, stainless-steel mesh with or without a copper coating, or meshes made of other materials but encapsulated with copper. The copper mesh layer, for example, may include one, two, three, four, five, six or more layers of mesh. In some embodiments, portions of the TGP (e.g., the copper mesh and/or the polymer spacer) may be bonded and sealed using FEP (fluorinated ethylene propylene), electroplating, sintering, and/or other sealants. In some embodiments, in order to enhance hydrophilic properties of the metallic mesh, atomic layer deposition (ALD) of Al.sub.2O.sub.3, TiO.sub.2, SiO.sub.2, or other coatings may be used to encapsulate the meshes with desirable functionality.

(34) FIG. 5 illustrates the thermal resistance from the evaporator evaporation region to the condensation region of a TGP manufactured according to some embodiments. In this example, the TGP includes is characterized with a 1 inch by 1 inch heater injecting the heat to the TGP and a 1 inch by 1 inch heat sink extracting the heat from the TGP. In this example, the active region of the test sample is about 200 mm×50 mm×1 mm. The results are compared with those obtained for a copper reference sample with the same dimensions.

(35) In some embodiments, the TGP may include a layer having a plurality of pillars manufactured with electroplating processes that produces, for example, large bonding pads with copper-nickel-gold layers. Additionally or alternatively, in some embodiments, an ALD hydrophilic or hydrophobic coating process may be used to change the wettability of the pillars.

(36) As shown in FIG. 5, the thermal resistances of a TGP manufactured according to embodiments are compared with those of a copper reference sample with the same dimensions. The thermal resistance from the evaporator to the condenser is a function of input power of the heater. As shown in the graph, the thermal resistance drops from 7 K/W to about 2 K/W when the power increases from 5 to 25 Watts. The corresponding thermal resistance of the copper sample is about 10 K/W. The effective thermal conductivity of the TGP reaches about 2,000 W/mK at 25 Watts since its resistance is about 1/5 of the copper with the thermal conductivity of 400 W/mK. In another test, our customer ran the power all the way to 35 Watts and reached the effective thermal conductivities up to 4,000 to 7,000 W/mK.

(37) In some embodiments, thermal vias with higher thermal conductivity than the substrate materials may be used. However, thermal vias were not used in this sample which was used to create generate the illustration results shown in the graph in FIG. 5; therefore, there is a relatively large and undesirable thermal resistance across the 50-um thick Kapton layer due to the low thermal conductivity of Kapton. With the use of thermal vias, the total thermal resistance of the TGP may increase with an effective thermal conductivity over 3,000 W/mK even at the 25-Watt power level.

(38) FIG. 6 illustrates a TGP **600** according to some embodiments. In this example, the top layer **310** and/or the bottom layer **315** may include copper cladded Kapton and/or may be similar to the

top layer **310** and the bottom layer **315** described above in conjunction with FIG. 3. In some embodiments, the top layer **310** and the bottom layer **315** of the TGP **600** may be sealed together using solder, laser welding, ultrasonic welding, electrostatic welding, or thermo-pressure compression. In between the top layer **310** and the bottom layer **315** the TGP **600** may include a liquid channel, a wicking structure, and/or a vapor core.

(39) The wicking structure **610**, for example, may include a copper mesh, stainless-steel mesh with or without a copper coating, or one or more mesh made of other materials but encapsulated with copper. The wicking structure **610**, for example, may include one, two, three, four, five, six or more layers of mesh of the same or different material. In some embodiments, the wicking structure **610** may be bonded and/or sealed using FEP (fluorinated ethylene propylene) electroplating, sintering, and/or other adhesives or sealants with the top layer **310**. In some embodiments, in order to enhance hydrophilic properties of the wicking structure **610**, atomic layer deposition (ALD) of Al.sub.2O.sub.3, TiO.sub.2, SiO.sub.2, or other coatings may be used to encapsulate meshes of the liquid channel **615** with desirable functionality. In some embodiments, the wicking structure **610** may be bonded with or on a plurality of pillars of the liquid channel **615**.

(40) In some embodiments, the wicking structure **610** may include a woven mesh that may be bonded to the pillars of the liquid channel **615** and/or the vapor core **605** through an electroplating process. In some embodiments, the mesh may be a copper woven mesh or a metallic mesh. During this process, for example, the wicking structure **610** (e.g., woven mesh) may be encapsulated by copper. The top layer **310** with the vapor core **605** and the bottom layer **315** with the liquid channel **615** may be sealed together with the wicking structure **610** with a mesh in between. After sealing, the TGP **600** may be charged with a working fluid, such as water, methane, ammonia, or other coolants or refrigerants that are compatible with the surfaces exposed to the working fluid.

(41) The liquid channel **615**, for example, may include a plurality of pillars (e.g., electroplated pillars).

(42) The vapor core **605**, for example, may include a plurality of pillars (e.g., electroplated pillars). In some embodiments, the pillars in the vapor core **605** may have at least one dimension (e.g., height, width, length, diameter, etc.) that is smaller than at least one dimension (e.g., height, width, length, diameter, etc.) of the pillars of the liquid channel **615**.

(43) In some embodiments, a photo-lithographic patterning process may be used to fabricate the pillars in the liquid channel **615** and/or the vapor core **605**. For example, a photo-lithography process may be used to form a plurality of pillars on the top layer **310** to form the vapor core **605** and/or a photo-lithographic patterning process may be used to form a plurality of pillars on the bottom layer **315** to form the liquid channel **615**. The photo-lithographic patterning process, for example, may control the positioning and/or the heights of the pillars with a resolution of a few microns. The plurality of pillars on the top layer **310** and/or on the bottom layer **315** may be formed by the mechanical scribing process.

(44) In some embodiments, the thickness of a TGP (e.g., TGP **300** or TGP **600**, or any other TGP described in this disclosure) may be a few millimeters or even less than about 500, 450, 400, 350, 300, 250, 200, 150, or 100 microns. For example, the top layer **310** and/or the liquid channel **615** may be 5, 10, 20, 30, 40, 50, 60, etc. microns thick, the wicking structure (e.g., wicking structure **610**) may be 5, 10, 20, 30, 40, 50, 60, etc. microns thick, and/or the vapor core (e.g., vapor core **605**) may be 10, 20, 30, 40, 50, 75, 100, 125, 150, etc. microns thick.

(45) FIG. 7 shows an example of a TGP **600** with a top layer **310** having pillars formed thereon to form the vapor core **605**, a bottom layer **315** having pillars formed thereon to form the liquid channel **615** and a wicking structure **610** disposed in between according to some embodiments.

(46) In some embodiments, the pillars may be fabricated using electroplating over photo-lithography-defined openings. In some embodiments, TGPs manufactured according to some embodiments may have a thickness larger than or less than 0.25 mm as shown in FIG. 8. The total thickness can be reduced further since all dimensions of critical features are defined by the photo-

lithography processes. In some embodiments, TGPs may have a thickness less than about 0.25, 0.2, 0.15, 0.1, 0.05 mm, etc.

(47) In some embodiments, the pillars of the liquid channel **615** and/or the vapor core **605** may allow the TGP to remain effective under different mechanical loadings even in an extremely thin configuration.

(48) FIG. **9** illustrates an example TGP with a plurality of electroplated pillars and mesh according to some embodiments. For example, the pillars on the top layer and/or the bottom layer may be fabricated using a photo-lithographic patterning process and/or may have any dimension such as, for example, 100 μm $\times$ 100 μm squares with 60 μm spacing in between each square. These pillars, for example, may be bonded to a stainless steel woven mesh (e.g., having 500 wires/inch, 50 μm thick) through various bonding techniques such as, for example, copper electroplating. The mesh, for example, may also be at least partially or completely encapsulated by electroplated copper.

(49) In some embodiments, the combined mesh-pillar structure may achieve low capillary radius (or high pumping pressure) in the evaporation regions and higher flow hydraulic radius (or low flow pressure drop) in the fluid channel.

(50) In some embodiments, a controlled over-plating process may be used to form the pillars with rounded heads. In some embodiments, this shape may be beneficial, for example, to form a sharp angle of each interface between a pillar and the mesh bonded. These sharp angles, for example, may enhance the capillary pumping force pulling the liquid returned from the condenser to the evaporator.

(51) FIG. **10** shows an example top layer with copper pillars electroplated through a photolithography-defined opening according to some embodiments. In this example, the height of the pillars is 100 microns, the diameter (or width) of the pillars is 1 mm, and the spacing between the pillars is 2 mm. In this example, the pillars may define the gap of the vapor core. With large spacing (e.g., a spacing between pillars that is greater than the diameter of the individual pillars or a spacing between pillars that is greater than or equal to twice the diameter of the individual pillars) the flow resistance may be reasonably low.

(52) In some embodiments, the pillars formed on the top layer and/or on the bottom layer may be hydrophilic. In some embodiments, the pillars may have a cross section that is round; oval; polygonal; star shaped as shown, for example, in FIG. **6**; hexagonal; octagonal; pentagonal; square; rectangular; triangular; etc. In some embodiments, condensation of vapor can occur along the vapor core. In some embodiments, the hydrophilic property of the pillars in the vapor core can reduce the size of vapor droplets or bubbles. In some embodiments, the star-shaped pillars can further enhance the hydrophilic properties or wettability.

(53) In some embodiments, the pillars may be constructed from material other than copper. The pillars, for example, may be manufactured from polymer using photo-lithographic deposition and etching techniques. Such polymer pillars, for example, can be baked, followed by hermetic encapsulation with copper, ALD moisture barrier coating or other sealing materials. In some embodiments, the thermal conductivities of polymer pillars may be much lower than that of copper.

(54) In some embodiments, the process of manufacturing a TGP may include a removing air out of the TGP followed by charging the TGP with water or other working fluid that is compatible with an exposed TGP inner surface. In some embodiments, a small diameter copper tube may be coupled with the TGP to allow for vacuuming and/or charging. After water charging, for example, this tube can be pinch-sealed. In some embodiments, the pinch-sealed tube can be removed by an additional seal separating the active region from the region with the tube.

(55) FIG. **11** shows an experimental setup that can be used to characterize the properties of a thin flexible TGP according to some embodiments. In this example, the evaporator (e.g., heater) region was defined by the heater size was of 8 mm $\times$ 8 mm and the condensation region was defined by the condenser block was with an area of 5 cm $\times$ 2.5 cm. The temperature difference between the evaporator evaporation region and the condenser condensation region was measured, and this

difference per unit of heat transferred to the condenser heater's input power was used to calculate considered the thermal resistance. The entire setup was covered by thermal insulation to reduce air natural convection effect by air.

(56) FIG. **12** is a graph showing the thermal resistances as a function of heater's input power of a TGP manufactured according to some embodiments and using the experimental setups shown in FIG. **11**. As shown in the figures, TGPs manufactured according to embodiments outperform copper. From these results, the thin TGP's, effective thermal conductivity may be between 500 and 5,000 W/mK or 1,000 and 1,500 W/mK.

(57) In some embodiments, the location of heat extraction condensation may affect a TGP's performance. FIG. **13** shows an experimental setup that can be used to characterize the properties of a thin flexible TGP with distributed condensers condensation cooled by air nature air convection without an active cooling heat sink according to some embodiments. In the Figure, a 1 inch×1 inch heater placed at the center of each sample's bottom side with wicking layer attached, the temperature difference between an upper region and the center (the heated region) on the top side with spacer layer attached was about 0.6° C. for the TGP sample with 4 W input. This temperature difference was increased to 5.4° C. for the copper sample with the same 4 W input. With distributed condensation over a large area, comparing to copper, the heat spreading performance of the TGP's was improved significantly, even without an active heat sink.

(58) FIG. **14A** illustrates a TGP **400** according to some embodiments. TGP **400** may be constructed with any of the following configurations. For example, the material on the interior surface exposed to water may be copper. As another example, a stainless steel mesh **405** may be used that is encapsulated by copper. As another example, a copper mesh can be used. As another example, the spacer **420** for the vapor core may be defined by a polymer mesh such as, for example, a nylon mesh or a PEEK mesh in conjunction with or in addition to copper pillars. In addition the spacer **420** may be a copper mesh. In some embodiments, one or more copper clad Kapton layers **410** and **420** may be included. In some embodiments, a wicking layer **405** may be included. One or more layers may be combined and/or bonded together.

(59) FIG. **14B** shows an example TGP according to some embodiments. In this example, a plurality of meshes (e.g., a copper mesh and a nylon/peek spacer) may be sealed between copper clad Kapton layers.

(60) The bottom layer and/or the top layer may be assembled and/or sealed with one or more sealing techniques such as, for example, ultrasound welding, laser welding, pressure thermo-compression between two layers and/or with a solder seal to form a high-yield hermetic seal. Any other technique may be used to hermetically seal the TGP such as, for example, photolithography-defined solder masking, copper-to-copper seam welding including ultrasonic welding or laser welding, copper-silver sintering, solder dipping, etc. In this example, a first seal **455** and a second seal **455** may be used.

(61) FIG. **15** illustrates another example TGP according to some embodiments. In this example, a bottom layer of copper clad Kapton and a top layer of copper clad Kapton can be bonded by copper silver sintering using a silver paste. The silver paste, in some embodiments, may allow for lower temperature soldering or sintering. For example, silver paste may be used for bonding at 250° C. without any pressure applied. In some embodiments, the copper surface may be treated with gold, silver and/or palladium. In some embodiments, the organic binder in the paste may be removed by a drying process before sintering.

(62) FIG. **16** illustrates an example process for fabricating a TGP according to some embodiments. At block **505**, a plurality of pillars may be formed on a bottom layer. These pillars, for example, may be used to form a liquid layer or channels. The pillars may be formed using any type of lithographic patterning process or mechanical scribing process. The pillars may have a height less than a millimeter, a diameter of less than 5 millimeters, and a spacing between pillars that is greater than the diameter of the individual pillars. The pillars may be metal and/or polymers based, and/or

include a hydrophilic coating or a hydrophobic coating.

(63) At block **510**, a plurality of spacers may be formed on a top layer. These spacers, for example, may be used to form a vapor core layer. The spacers may be formed using any type of lithographic patterning process. The spacers may have a height less than a millimeter, a diameter of less than 5 millimeters, and a spacing between pillars that is greater than the diameter of the individual pillars. In some embodiments, the spacers may have a diameter of less than the diameter of the pillars and/or a space between pillars that is greater than the diameter of the individual pillars. The spacers may be metal and/or polymer based and/or encapsulated by copper and/or include a hydrophilic coating and/or include a hydrophobic coating.

(64) At block **515**, a mesh layer may be sandwiched between the top layer and the bottom layer. The mesh may be a metal mesh, a metal-encapsulated mesh, or a copper-encapsulated stainless steel mesh. The mesh may be a woven mesh. The woven mesh, for example, may have a weave that is less than 75 microns in thickness. In some embodiments, the mesh may be copper encapsulated. In some embodiments, the mesh may have a desirable wettability with hydrophilic or hydrophobic coatings. In some embodiments, the reaction of the mesh with water may be negligible. In some embodiments, the mesh can be bonded to the bottom layer by electroplated copper.

(65) At block **520** the top layer and the bottom layer may be sealed to create a void cavity within which a working fluid may be placed. Any type of sealing may be used including those described herein and those not described herein. A tube may extend through the sealing to allow evacuation and charging of the TGP.

(66) At block **525** any air or non-condensable gas or other material within the void may be evacuated using any technique. At block **530** the TGP may be charged with a working fluid such as, for example, water, methane, ammonia, or other working fluid that is compatible with the exposed TGP inner surface.

(67) The various steps in the process shown in FIG. **16** may occur in any order and/or any block may be removed.

(68) In some embodiments, a TGP may be sealed with tin/lead solder (or similar lead-free solder alloys) according to some embodiments. Tin/lead solder's reaction with water may be limited.

(69) FIG. **17** illustrates a top view of another TGP **700** and FIGS. **18A**, **18B**, and **18C** illustrate side views of the TGP **700** according to some embodiments. The TGP **700** includes a top layer (**805** in FIG. **18**) and a bottom layer **705**. FIG. **17** shows the TGP **700** with the top layer **805** removed. The top layer **805** and/or the bottom layer **705** may include copper and/or polyimide material. In some embodiments, the top layer **805** and/or the bottom layer **705** may include layers of both copper and polyimide.

(70) The TGP **700** includes a mesh return layer **715** that includes a plurality of return arteries **710** formed or cut within the mesh return layer **715**. In some embodiments, the return arteries **710** may not extend into the evaporator region **720** of the TGP **700**. In some embodiments, the width of the return arteries **710** may be less than 30 microns. In some embodiments, the width of the return arteries **710** may be less than 100 microns. In some embodiments, the mesh return layer **715** may include a wick. In some embodiments, the mesh return layer **715** may include a steel mesh such as, for example, a mesh with wires that are less than 50 microns or 25 microns thick. In some embodiments, the mesh return layer **715** may include a mesh with a simple weave at **200**, **300**, **400**, **500**, **600**, **700**, etc. wires/inch. In some embodiments, the mesh return layer **715** may be electroplated with copper. The mesh return layer **715** may include a specified evaporator region that may provide a specific location for a heat source. In some embodiments, the mesh return layer **715** may have a thickness of about 40 microns.

(71) The mesh return layer **715** may have any number of shapes and/or configurations. In some embodiments, the mesh return layer **715** may have a polygonal or circular shape. In some embodiments, the mesh return layer **715** may have multiple sections without return arteries **710**. In

some embodiments, the mesh return layer **715** may include any number, shape or configuration of return arteries **710**. In some embodiments, the return arteries **710** may have one or more pillars or other mechanisms disposed within the return arteries **710**.

(72) In some embodiments, return pillars **835** (see FIG. **18**) may extend from the bottom layer **705** through the return arteries **710** of the mesh return layer **715**. In some embodiments, the return pillars **835** may form vapor regions running parallel to the mesh return layer **715**. In some embodiments, the return pillars **835** may form arteries in the adiabatic and/or condenser regions of the TGP **700**.

(73) The return pillars **835** may have at least one dimension that is smaller than the width of the return arteries **710**. In some embodiments, these pillars may have at least one dimension (e.g., height, width, length, diameter, etc.) that is less than 10 microns. In some embodiments, these pillars may have at least one dimension (e.g., height, width, length, diameter, etc.) that is less than 50 microns. In some embodiments, these pillars may have at least one dimension (e.g., height, width, length, diameter, etc.) that is less 100 microns.

(74) FIG. **18A** shows a side view of TGP **700** cut through Section A shown in FIG. **17**. In FIG. **18A**, the TGP **700** is cut through a region where a return arteries **710** extends along a portion of the mesh return layer **715**. As shown in FIG. **18A**, the mesh return layer **715** is present in the evaporator region. The return pillars **835** are shown extending through the return arteries **710**. The TGP **700** also includes a plurality of top pillars **825** disposed on the top layer **805**. The top pillars **825** may have at least one dimension (e.g., height, width, length, diameter, etc.) that is larger than the return pillars **835**. The top pillars **825** may have at least one dimension (e.g., height, width, length, diameter, etc.) that is larger than 0.25 mm, 0.5 mm, 0.75 mm, 1.0 mm, 1.25 mm, etc.

(75) In some embodiments, the TGP **700** may include a micro wick layer **815**. The micro wick layer **815**, for example, may include a plurality of pillars (e.g., electroplated pillars). The micro wick layer **815** may have at least one dimension (e.g., pillar height, width, length, diameter, pitch, etc.) that is smaller than the return pillars **835**. The micro wick layer **815** may have at least one dimension (e.g., height, width, length, diameter, etc.) that is smaller than 5 μm , 10 μm , 15 μm , 20 μm , 25 μm , etc. The micro wick layer **815** may be aligned with the return arteries **710**.

(76) FIG. **18B** shows a side view of TGP **700** cut through Section B shown in FIG. **17**. In FIG. **18B**, the TGP is cut through a region without the return arteries **710** extending along a portion of the mesh return layer **715**. Instead, the mesh return layer **715** extends along the length of the TGP **700** along this section of the TGP **700**.

(77) FIG. **18C** shows an end view of TGP **700** cut through Section C shown in FIG. **17**. In FIG. **18C**, the TGP is cut through the mesh return layer **715** showing both the mesh return layer **715** and the return arteries **710** formed in the mesh return layer **715**. In some embodiments, the return pillars **835** may extend through the return arteries **710**. In some embodiments, one or more of the return pillars **835** may contact one or more of the top pillars **825**.

(78) In some embodiments, the top layer **805** and the bottom layer **705** are sealed along at least one edge of the top layer **805** and along at least one edge of the bottom layer **705**. In some embodiments, the top layer **805** and the bottom layer **705** are sealed along at least two edges of the top layer **805** and along at least two edges of the bottom layer **705**.

(79) In some embodiments, as shown in FIG. **19**, the plurality of wicking structures **990** comprise a mesh layer. The mesh layer, for example, may include a mesh selected from the list consisting of copper mesh, stainless steel mesh, metal mesh, polymer mesh and copper-encapsulated mesh. The mesh layer, for example, may include a hydrophilic coating **995** or a hydrophobic coating or hermetic coating.

(80) FIG. **20** illustrates a TGP **2000** according to some embodiments. In this example, the top layer **310** and/or the bottom layer **315** may include copper cladded Kapton and/or may be similar to the top layer **310** and the bottom layer **315** described above in conjunction with FIG. **3**. In some embodiments, the top layer **310** and the bottom layer **315** of the TGP **2000** may be sealed together

using solder, laser welding, ultrasonic welding, electrostatic welding, or thermo-pressure compression. In between the top layer **310** and the bottom layer **315** the TGP **600** may include a liquid channel, a wicking structure, and/or a vapor core.

(81) In some embodiments, the top layer **310** and/or the bottom layer **315** may comprise copper and stainless steel, copper and a polymer, copper, copper clad Kapton, polymer, etc. In some embodiments, the top layer **310** and the bottom layer **315** may include the same material or different material.

(82) The mesh **610**, for example, may include a copper mesh, stainless-steel mesh with or without a copper coating, or one or more mesh made of other materials but encapsulated with copper. The, for example, may include one, two, three, four, five, six or more layers of mesh of the same or different material. In some embodiments, the mesh may be bonded and/or sealed using FEP (fluorinated ethylene propylene) electroplating, sintering, and/or other adhesives or sealants with the top layer **310**. In some embodiments, in order to enhance hydrophilic properties of the, atomic layer deposition (ALD) of Al_2O_3 , TiO_2 , SiO_2 , or other coatings may be used to encapsulate the plurality of pillars of the liquid channel **615** with desirable functionality. In some embodiments, the mesh may be bonded with or on a plurality of pillars of the liquid channel **615**.

(83) In some embodiments, the mesh **610** may include a woven mesh that may be bonded to the second plurality of pillars of the liquid channel **615** and/or the vapor core **605** through an electroplating process. In some embodiments, the mesh may be a copper woven mesh or a metallic mesh. During this process, for example, the (e.g., woven mesh) may be encapsulated by copper. The top layer **310** with the vapor core **605** and the bottom layer **315** with the liquid channel **615** may be sealed together with the mesh in between. After sealing, the TGP **600** may be charged with a working fluid, such as water, methane, ammonia, or other coolants or refrigerants that are compatible with the surfaces exposed to the working fluid.

(84) The liquid channel **615**, for example, may include a first plurality of pillars (e.g., electroplated pillars).

(85) The vapor core **605**, for example, may include a second plurality of pillars (e.g., electroplated pillars). In some embodiments, the second plurality of pillars in the vapor core **605** may have at least one dimension (e.g., height, width, length, diameter, etc.) that is smaller than at least one dimension (e.g., height, width, length, diameter, etc.) of the second plurality of pillars of the liquid channel **615**. The second plurality of pillars may be disposed on the bottom layer **315**. The second plurality of pillars may extend to the mesh **610** and/or may not extend to the top layer **310**.

(86) In some embodiments, a third plurality of pillars **620** may extend from the bottom layer **315** to the top layer **310**. The third plurality of pillars **620** may extend through or around the mesh **610**.

(87) In some embodiments, a photo-lithographic patterning process may be used to fabricate the pillars in the liquid channel **615** and/or the vapor core **605**. For example, a photo-lithography process may be used to form a plurality of pillars on the top layer **310** to form the vapor core **605** and/or a photo-lithographic patterning process may be used to form a plurality of pillars on the bottom layer **315** to form the liquid channel **615**. The photo-lithographic patterning process, for example, may control the positioning and/or the heights of the pillars with a resolution of a few microns. The plurality of pillars on the top layer **310** and/or on the bottom layer **315** may be formed by the mechanical scribing process.

(88) In some embodiments, the thickness of a TGP (e.g., TGP **300** or TGP **600**, or any other TGP described in this disclosure) may be a few millimeters or even less than about 500, 450, 400, 350, 300, 250, 200, 150, or 100 microns. For example, the top layer **310** and/or the liquid channel **615** may be 5, 10, 20, 30, 40, 50, 60, etc. microns thick, the wicking structure (e.g.,) may be 5, 10, 20, 30, 40, 50, 60, etc. microns thick, and/or the vapor core (e.g., vapor core **605**) may be 10, 20, 30, 40, 50, 75, 100, 125, 150, etc. microns thick.

(89) In some embodiments, a buffer region can be created by design to collect and store any non-condensable gas through passive convection. For example, a space of a few millimeters can be

formed in the area outside the mesh (e.g., outside the mesh region shown in FIG. 6). This space can be added prior to bonding. This space may collect any non-condensable gases that would move to this space because of its different density, and thus its effect on evaporation and condensation can be reduced substantially.

(90) Various other sealing techniques may be used such as, for example, thermosonic or thermo-compression bonding, ultrasonic welding, laser welding, electron beam welding, electroplating; solder sealing with alloys with negligible reaction with water; and polymer bonding encapsulated by moisture barrier coatings such as atomic layer deposition (ALD)-based coatings.

(91) Some embodiments may include a pillar-enabled TGP. In some embodiments, the TGP may include a copper-cladded Kapton film that includes three layers. These layers may, for example, include copper and Kapton layers. Each layer may be about 12 μm thick. In some embodiments, a stainless steel woven mesh may be included and may have a thickness less than 75 μm . In some embodiments, the pillars may allow for fluid and/or vapor transport between the pillars under different mechanical loadings.

(92) In some embodiments, a plurality of pillars may be formed on a copper layer (e.g., the top layer and/or the bottom layer) using any of various lithography lithographic patterning processes.

(93) In some embodiments, a copper-encapsulated stainless steel mesh may be sandwiched between the top layer and the bottom layer. The stainless steel mesh, for example, may have a weave that is less than 75 microns in thickness. In some embodiments, the mesh may be copper encapsulated. In some embodiments, the mesh may be hydrophilic. In some embodiments, the reaction of the mesh with water may be negligible.

(94) In some embodiments, a TGP may include a mesh-pillar wicking structure. The mesh-pillar wicking structure may allow the TGP to achieve a low capillary radius (high p umping pressure) in the evaporation regions and/or a higher flow hydraulic radius (low flow pressure drop) in the fluid channel.

(95) In some embodiments, a TGP may include pillars with rounded heads. For example, the pillars may be formed with controlled over-plating. In some embodiments, the pillars may form very sharp angle at the interface between a pillar and the mesh bonded. In some embodiments, these sharp angles may be used, for example, to enhance the capillary p umping force pulling the liquid returned from the condenser to the evaporator.

(96) In some embodiments, a plurality of star-shaped pillars may be constructed on either the top layer and/or the bottom layer that have a star-shaped polygon various cross section.

(97) In some embodiments, a plurality of hydrophilic pillars may be constructed on either the top layer and/or the bottom layer.

(98) In some embodiments, heat rejection through condensation can be distributed throughout the external surface of the TGP.

(99) In some embodiments, pillars and/or spacers may be disposed on a layer with densities (spacing between pillars or spacers) that vary across the layer, with diameters that vary across the layer, with spacing that vary across the layer, etc.

(100) The Figures are not drawn to scale.

(101) The term “substantially” means within 5% or 10% of the value referred to or within manufacturing tolerances.

(102) Numerous specific details are set forth herein to provide a thorough understanding of the claimed subject matter. However, those skilled in the art will understand that the claimed subject matter may be practiced without these specific details. In other instances, methods, apparatuses, or systems that would be known by one of ordinary skill have not been described in detail so as not to obscure claimed subject matter.

(103) The use of “adapted to” or “configured to” herein is meant as open and inclusive language that does not foreclose devices adapted to or configured to perform additional tasks or steps. Additionally, the use of “based on” is meant to be open and inclusive, in that a process, step,

calculation, or other action “based on” one or more recited conditions or values may, in practice, be based on additional conditions or values beyond those recited. Headings, lists, and numbering included herein are for ease of explanation only and are not meant to be limiting.

(104) While the present subject matter has been described in detail with respect to specific embodiments thereof, it will be appreciated that those skilled in the art, upon attaining an understanding of the foregoing, may readily produce alterations to, variations of, and equivalents to such embodiments. Accordingly, it should be understood that the present disclosure has been presented for purposes of example rather than limitation, and does not preclude inclusion of such modifications, variations, and/or additions to the present subject matter as would be readily apparent to one of ordinary skill in the art.

Claims

1. A thermal ground plane comprising: a first substrate member comprising copper; a second substrate member comprising a metal, wherein the first substrate member and the second substrate member are sealed together so as to be in direct contact and to enclose a working fluid; a first plurality of pillars disposed on an interior surface of the first substrate; a mesh layer disposed on the top of the first plurality of pillars, wherein the mesh layer comprises at least one of copper, polymer encapsulated with copper, or stainless steel encapsulated with copper, wherein the mesh is entirely disposed in a cavity defined by the first substrate member and the second substrate member; and a second plurality of pillars disposed on an interior surface of the second substrate member within an area defined by the perimeter of the second substrate member and the second plurality of pillars extend from the second substrate member to the mesh layer.
2. The thermal ground plane according to claim 1, wherein the second plurality of pillars are not in contact with the first substrate member.
3. The thermal ground plane according to claim 1, wherein the thermal ground plane has a thickness less than 300 microns.
4. The thermal ground plane according to claim 1, wherein the mesh layer is bonded with the first plurality of pillars.
5. The thermal ground plane according to claim 1, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises the same material as the other mesh layers.
6. The thermal ground plane according to claim 1, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises a different material than the other mesh layers.
7. The thermal ground plane according to claim 1, wherein a perimeter of the first substrate member and a perimeter of the second substrate member are hermetically sealed together.
8. The thermal ground plane according to claim 7, wherein the hermetical seal is a thermocompression-bonded, an ultrasound-welded, an electrostatic welded, or a laser-welded copper-to-copper interface.
9. The thermal ground plane according to claim 1, wherein the spacing between each pillar of the second plurality of pillars is larger than two times of the diameter of each pillar of the second plurality of pillars.
10. The thermal ground plane according to claim 1, wherein the mesh layer may include a mesh selected from the list consisting of copper mesh, stainless steel mesh, metal mesh, polymer mesh and copper-encapsulated mesh.
11. A thermal ground plane comprising: a first substrate member comprising at copper and either stainless steel or polymer; a second substrate member comprising a metal, wherein a perimeter of the first substrate member and a perimeter of the second substrate member are hermetically sealed together so as to be in direct contact, wherein the first substrate member and the second substrate member enclose a working fluid; a mesh layer bonded with the first substrate member, wherein the mesh layer comprises at least one of copper, polymer encapsulated with copper, or stainless steel

encapsulated with copper, wherein the mesh is entirely disposed in a cavity defined by the first substrate member and the second substrate member; and a plurality of pillars disposed on an interior surface of the second substrate member within an area defined by the perimeter of the second substrate member and the second plurality of pillars extend from the second substrate member to the mesh layer and are not in contact with the first substrate member.

12. The thermal ground plane according to claim 11, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises the same material as the other mesh layers.

13. The thermal ground plane according to claim 11, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises a different material than the other mesh layers.

14. The thermal ground plane according to claim 11, wherein the thermal ground plane has a thickness less than 300 microns.

15. The thermal ground plane according to claim 11, wherein the mesh layer may include a mesh selected from the list consisting of copper mesh, stainless steel mesh, metal mesh, polymer mesh and copper-encapsulated mesh.

16. A thermal ground plane comprising: a first substrate member comprising copper; a second substrate member comprising a metal, wherein the first substrate member and the second substrate member are sealed together so as to be in direct contact and to enclose a working fluid; a mesh layer bonded with the first substrate member, wherein the mesh layer comprises at least one of copper, polymer encapsulated with copper, or stainless steel encapsulated with copper, wherein the mesh is entirely disposed in a cavity defined by the first substrate member and the second substrate member; and a second plurality of pillars disposed on an interior surface of the second substrate member within an area defined by the perimeter of the second substrate member and the second plurality of pillars extend from the second substrate member to the mesh layer and are not in contact with the first substrate member.

17. The thermal ground plane according to claim 16, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises the same material as the other mesh layers.

18. The thermal ground plane according to claim 16, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises a different material than the other mesh layers.

19. A thermal ground plane comprising: a first substrate member comprising copper; a second substrate member comprising a metal, wherein the first substrate member and the second substrate member are sealed together so as to be in direct contact and to enclose a working fluid; a mesh layer bonded with the first substrate member, wherein the mesh layer comprises at least one of copper, polymer encapsulated with copper, or stainless steel encapsulated with copper, wherein the mesh is entirely disposed in a cavity defined by the first substrate member and the second substrate member; and a second plurality of pillars disposed on an interior surface of the second substrate member within an area defined by the perimeter of the second substrate member and the second plurality of pillars extend from the second substrate member to the mesh layer.

20. The thermal ground plane according to claim 19, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises the same material as the other mesh layers.

21. The thermal ground plane according to claim 19, wherein the mesh layer comprises at least two mesh layers and each mesh layer comprises a different material than the other mesh layers.
