

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12414828

Kind Code

B2

Date of Patent

September 16, 2025

Inventor(s)

Nowlin; William C. et al.

Teleoperated surgical system with surgeon skill level based instrument control

Abstract

A teleoperated surgical system is provided comprising: a first robotic surgical instrument; an image capture; a user display; a user input command device coupled to receive user input commands to control movement of the first robotic surgical instrument; and a movement controller coupled to scale a rate of movement of the first robotic surgical instrument, based at least in part upon a surgical skill level at using the first robotic surgical instrument of the user providing the received user input commands, from a rate of movement indicated by the user input commands received at the user input command device.

Inventors: Nowlin; William C. (Los Altos Hills, CA), Azizian; Mahdi (San Jose, CA), DiMaio; Simon P. (San Carlos, CA), Hoffman; Brian D. (Mountain View, CA), Jarc; Anthony M. (Johns Creek, GA), Lin; Henry C. (Cupertino, CA), Liu; May Quo-Mei (Rougemont, NC), McDowall; Ian E. (San Francisco, CA), Tokarchuk; Brent (San Carlos, CA)

Applicant: Intuitive Surgical Operations, Inc. (Sunnyvale, CA)

Family ID: 1000008818266

Assignee: Intuitive Surgical Operations, Inc. (Sunnyvale, CA)

Appl. No.: 18/416759

Filed: January 18, 2024

Prior Publication Data

Document Identifier

Publication Date

US 20240197421 A1

Jun. 20, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **A61B34/35** (20160101); **A61B34/00** (20160101); **A61B34/10** (20160101); **A61B34/20** (20160101); A61B17/00 (20060101); A61B18/00 (20060101); A61B34/30 (20160101); A61B90/00 (20160101)

U.S. Cl.:

CPC **A61B34/35** (20160201); **A61B34/10** (20160201); **A61B34/20** (20160201); **A61B34/25** (20160201); A61B2017/00477 (20130101); A61B2018/00595 (20130101); A61B2018/00988 (20130101); A61B2034/101 (20160201); A61B2034/256 (20160201); A61B2034/302 (20160201); A61B2090/3612 (20160201); A61B2090/364 (20160201); A61B90/37 (20160201)

Field of Classification Search

CPC: A61B (2017/00477); A61B (2018/00595); A61B (2018/00988); A61B (2034/101); A61B (2034/256); A61B (2034/258); A61B (2034/302); A61B (2090/3612); A61B (2090/364); A61B (34/10); A61B (34/20); A61B (34/25); A61B (34/35); A61B (34/74); A61B (34/77); A61B (90/37)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9026247	12/2014	White et al.	N/A	N/A
9649164	12/2016	Kim	N/A	B25J 9/1676
11931122	12/2023	Nowlin et al.	N/A	N/A
2007/0083098	12/2006	Stern et al.	N/A	N/A
2007/0172803	12/2006	Hannaford et al.	N/A	N/A
2010/0234857	12/2009	Itkowitz et al.	N/A	N/A
2011/0054689	12/2010	Nielsen et al.	N/A	N/A
2011/0208338	12/2010	Eteminan et al.	N/A	N/A
2011/0306986	12/2010	Lee et al.	N/A	N/A
2012/0143182	12/2011	Ullrich et al.	N/A	N/A
2013/0172908	12/2012	Sang et al.	N/A	N/A
2014/0051049	12/2013	Jarc et al.	N/A	N/A
2014/0094968	12/2013	Taylor et al.	N/A	N/A
2014/0287393	12/2013	Kumar et al.	N/A	N/A
2014/0378995	12/2013	Kumar et al.	N/A	N/A
2015/0305936	12/2014	Hajishah et al.	N/A	N/A
2015/0359597	12/2014	Gombert et al.	N/A	N/A
2016/0098933	12/2015	Reiley et al.	N/A	N/A
2016/0183930	12/2015	Herzlinger et al.	N/A	N/A

2016/0314710	12/2015	Jarc et al.	N/A	N/A
2016/0331474	12/2015	Lacal et al.	N/A	N/A
2017/0360522	12/2016	Beira	N/A	N/A
2018/0032130	12/2017	Meglan	N/A	N/A
2018/0271603	12/2017	Nir	N/A	A61B 34/25
2019/0282311	12/2018	Nowlin et al.	N/A	N/A
2019/0282312	12/2018	Nowlin et al.	N/A	N/A
2022/0061933	12/2021	Deboeuf et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102525644	12/2011	CN	N/A
203381739	12/2013	CN	N/A
203433729	12/2013	CN	N/A
106054737	12/2015	CN	N/A
102008036290	12/2009	DE	N/A
H0871072	12/1995	JP	N/A
2009131374	12/2008	JP	N/A
2009142379	12/2008	JP	N/A
2012521568	12/2011	JP	N/A
2014520279	12/2013	JP	N/A
20150027618	12/2014	KR	N/A
WO-2016028858	12/2015	WO	N/A
WO-2016053657	12/2015	WO	N/A

OTHER PUBLICATIONS

Chinese Patent Office, First Chinese Office Action for Application No. 201780073370X, mailed Jan. 29, 2022 with English Translation, 30 pages. cited by applicant

Extended European Search Report for Application No. 17869216.6, mailed on Jun. 16, 2020, 7 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2017/061136, mailed on May 23, 2019, 9 pages (ISRG07810/PCT). cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2017/061136, mailed on Feb. 19, 2018, 12 pages (ISRG07810/PCT). cited by applicant

Office Action for Chinese Application No. 201780073370, mailed Sep. 5, 2022, 31 pages. cited by applicant

Office Action for Korean Application No. KR20197016223, mailed May 24, 2022, 6 pages. cited by applicant

Vertut, J., and Coiffet, P., "Robot Technology: Teleoperation and Robotics Evolution and Development," English translation, Prentice-Hall, Inc., Englewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages. cited by applicant

Primary Examiner: Cook; Christopher L

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CLAIM OF PRIORITY (1) This application is a continuation of U.S. application Ser. No. 16/349,202, filed May 10, 2019, which is a U.S. National Stage filing under 35 U.S.C. 371 from International Application PCT/US2017/061136, filed Nov. 10, 2017, which claims the benefit of priority to U.S. Patent application 62/421,072, filed on Nov. 11, 2016, each of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field of Invention

(1) Inventive aspects are associated with medical devices used during surgery. More specifically, aspects are associated with surgical instrument use in accordance with surgeon skill level.

2. Art

(2) Surgeons typically undertake extensive study before performing a surgical procedure.

Traditionally, surgeons were limited to the study of generic anatomical models, such as photographs or drawings. More recently, various pre-operative diagnostic procedures (e.g., x-ray, CT, MRI, etc.) have made patient-specific anatomical information available.

(3) In some cases, it is desirable to make additional, relevant anatomic and surgical procedure information available to a surgeon. In one aspect, it is desirable to provide a surgeon planning an operation on a particular patient with a surgical site video recording of an earlier surgical procedure performed on the particular patient. In another aspect, it is desirable to provide a surgeon with one or more surgical video recordings of surgical procedures on other patients that are similar to the surgical procedure planned for a particular patient. In one aspect, it is desirable to provide such information to a surgeon prior to the surgeon undertaking a particular surgical procedure. And in another aspect, it may be desirable to provide this information to a surgeon intraoperatively.

(4) In one aspect, it is desirable to configure a video database that includes intraoperative surgical site video recordings of various procedures undergone by various patients. In one aspect, it is desirable to configure a medical device capable of video recording to further include an input that enables a surgeon using the medical device to highlight and annotate the video recording in real time as it is being recorded. In one aspect, it is desirable to configure a computer-based pattern matching algorithm to search through the individual records of the video database, identify relevant video records, and provide a surgeon with this relevant information for a particular surgical procedure.

SUMMARY

(5) The following summary introduces certain aspects of the inventive subject matter in order to provide a basic understanding. This summary is not an extensive overview of the inventive subject matter, and it is not intended to identify key or critical elements or to delineate the scope of the inventive subject matter. Although this summary contains information that is relevant to various aspects and embodiments of the inventive subject matter, its sole purpose is to present some aspects and embodiments in a general form as a prelude to the more detailed description below.

(6) A surgical method is provided for use with a teleoperated surgical system that includes a robotic surgical instrument. An image capture device is orientable toward a surgical site for capturing images of anatomical tissue and of robotic surgical instrument. A user display is coupled to the image capture device to show to a user, the captured images of the anatomical tissue and of the robotic surgical instrument. A user input command device is coupled to receive user input commands to control movement of the robotic surgical instrument. A movement controller circuit is coupled to receive the user input commands from the input command device. The movement controller circuit is configured to control movement of the robotic surgical instrument in response to the user input commands. The movement controller circuit is further configured to scale a rate of movement of the robotic surgical instrument, based at least in part upon a surgical skill level at using the robotic surgical instrument of the user providing the received user input commands, from a rate of movement indicated by the user input commands received at the user input command

device.

(7) A method is provided to operate a teleoperated surgical system that includes a robotic surgical instrument manipulator. User input commands are received from a user to control movement of a robotic surgical instrument mounted at the robotic surgical instrument manipulator. An identification determination is made of a robotic surgical instrument mounted at the robotic surgical instrument manipulator during the receiving the user input commands. A rate of movement of the robotic surgical instrument is scaled, based at least in part upon a skill level of the user at use of the identified surgical instrument, from a rate of movement indicated by the user input commands.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a plan view of a minimally invasive teleoperated surgical system.
- (2) FIG. 2 is a perspective view of a surgeon's console.
- (3) FIG. 3 is a perspective view of an electronics cart.
- (4) FIG. 4 is a diagrammatic illustration of a teleoperated surgical system.
- (5) FIG. 5 is a perspective view of a patient-side cart.
- (6) FIG. 6 is an elevation view of a surgical instrument.
- (7) FIG. 7 is a perspective view of an instrument manipulator.
- (8) FIG. 8 is a diagrammatic illustration of a surgical planning tool.
- (9) FIG. 9 is a flow diagram of a method of using a surgical planning tool.
- (10) FIG. 10 is an illustrative drawing representing storage atlas in a computer readable storage device in accordance with some embodiments.
- (11) FIG. 11 is an illustrative drawing representing an example of the ninth information structure included within the atlas in the storage device, which associates recorded video information from an individual surgery with corresponding surgical instrument actuator state information and surgeon eye movement information in accordance with some embodiments.
- (12) FIGS. 12A-12C are illustrative drawings showing an example surgical instrument and an actuator assembly in which the surgical instrument is shown in three different example operational states in accordance with some embodiments.
- (13) FIG. 13 is an illustrative drawing representing an example tenth information structure of the atlas stored in the computer readable storage device **1004** that corresponds to an example surgical procedure to be performed by an example surgeon.
- (14) FIG. 14 is an illustrative flow diagram representing configuration of a processor to scale kinematic translation of user-to-instrument movement according to a surgical instrument safety actuation state based at least in part upon surgeon skill level information in accordance with some embodiments.

DETAILED DESCRIPTION

(15) This description and the accompanying drawings that illustrate inventive aspects, embodiments, implementations, or applications should not be taken as limiting—the claims define the protected invention. Various mechanical, compositional, structural, electrical, and operational changes may be made without departing from the scope of this description and the claims. In some instances, well-known circuits, structures, or techniques have not been shown or described in detail in order not to obscure the invention. Like numbers in two or more figures represent the same or similar elements.

(16) Elements described in detail with reference to one embodiment, implementation, or application may, whenever practical, be included in other embodiments, implementations, or applications in which they are not specifically shown or described. For example, if an element is described in detail with reference to one embodiment and is not described with reference to a

second embodiment, the element may nevertheless be claimed as included in the second embodiment. Thus, to avoid unnecessary repetition in the following description, one or more elements shown and described in association with one embodiment, implementation, or application may be incorporated into other embodiments, implementations, or aspects unless specifically described otherwise, unless the one or more elements would make an embodiment or implementation non-functional, or unless two or more of the elements provide conflicting functions.

(17) Aspects of the invention are described primarily in terms of an implementation using a da Vinci® Surgical System (specifically, a Model IS4000, marketed as the da Vinci® Xi™ ID™ Surgical System), commercialized by Intuitive Surgical, Inc. of Sunnyvale, California. Knowledgeable persons will understand, however, that inventive aspects disclosed herein may be embodied and implemented in various ways, including robotic and, if applicable, non-robotic embodiments and implementations. Implementations on da Vinci® Surgical Systems (e.g., the Model IS4000 da Vinci® Xi™ Surgical System, the Model IS3000 da Vinci Si® Surgical System) are merely exemplary and are not to be considered as limiting the scope of the inventive aspects disclosed herein.

(18) In accordance with various aspects, the present disclosure describes a surgical planning tool that includes a medical device configured to video record the performance of surgical procedures. The video recordings can be embedded with various metadata, e.g., highlights made by a medical person. Additionally, the video recordings can be tagged with various metadata, e.g., text annotations describing certain subject matter of the video, the identity of the patient to whom the video recording corresponds, biographical or medical information about the patient, and the like. In one aspect, tagged metadata is embedded in the video recordings.

(19) In accordance with further aspects, the present disclosure describes a teleoperated medical device that includes a surgical instrument used to perform at least one surgical activity during a surgical procedure. Different stages of a surgical activities may require different surgical skill levels. In some embodiments, a surgical level in a surgical activity may be determined based at least in part upon a comparison of the surgeon's performance level of the surgical activity with the performance levels of other surgeons in the activity. A surgery may involve use of different surgical instruments during different portions of a surgical procedure. Each surgical instrument used during a surgery is controlled by one or more surgical instrument actuators operable in multiple actuator states. Which surgical instrument is in use during different portions of a surgery is tracked. In some embodiments, an actuator state of an actuator controlling a surgical instrument that is in use is tracked during surgical procedures. In some embodiments, surgeon eye movement also is tracked using a camera to determine direction of surgeon gaze during the surgery. In some embodiments, an information structure in a computer readable storage device associates surgical instrument in use and surgical instrument actuator states with surgical guidance information for presentation to a surgeon in response to a surgical instrument's use to perform the at least one surgical activity. In some embodiments, the surgical guidance information that is presented to a surgeon is determined based at least in part upon the surgeon's surgical skill level. In some embodiments, an information structure in a computer readable storage device associates at least one of a surgical instrument use during surgery or its specific actuator states during the performance of the at least one surgical activity with safety transition information for use to cause the surgical instrument actuator to transition to an actuator safety state of operation that matches a surgeon's skill level. In some embodiments, the surgical instrument actuator safety state of operation is determined based at least in part upon a surgeon's skill level.

(20) In a teleoperated surgical system, different instruments may be used at different stages of a surgical procedure. Moreover, the same instrument may be used in different actuator states at different stages of a surgical procedure. As used herein, the term actuator state refers to a mechanical disposition of a surgical instrument as determined by an actuator, such as a motor, in

response to input commands received from a surgeon or other surgical team member.

(21) The video recordings and information structures that associate surgical instrument's use or specific actuator states with surgical guidance or actuator safety state information can be archived on an electronic medical record database implemented locally or on a cloud data storage service. The video recordings can be made available to interested health care providers. The information structures can be made available for use with the teleoperated medical device to provide surgical guidance and to control surgical instrument actuator state during performance of at least one surgical activity during performance of a surgical procedure.

(22) Health care providers can search the medical device database based upon surgeon skill level for videos and information structure relationships of interest using the metadata tags described above. Additionally, in one aspect, the surgical planning tool includes a computer-based pattern matching and analysis algorithm. In one aspect, the pattern-matching algorithm culls through the videos stored on the electronic medical record database to identify correlations between visual characteristics in the video recordings and associated metadata tags made by medical persons. The surgical planning tool can apply these correlations to newly encountered anatomy, and thereby assist medical persons performing a procedure in making determinations about patient anatomy, preferred surgical approaches, disease states, potential complications, etc. In another aspect, the pattern matching algorithm culls through videos stored on the electronic medical record database to identify correlations between visual characteristics in the video recordings and patient health record information to identify patient anatomical characteristics that correlate with surgeon skill level information. The surgical planning tool can apply these correlations between anatomy and surgeon skill level records to a current patient's anatomy and health records, and thereby assist medical persons planning and performing a surgical procedure involving the current patient.

Minimally Invasive Teleoperated Surgical System

(23) Referring now to the drawings, in which like reference numerals represent like parts throughout the several views, FIG. 1 is a plan view of a minimally invasive teleoperated surgical system **10**, typically used for performing a minimally invasive diagnostic or surgical procedure on a patient **12** who is lying on an operating table **14**. The system includes a surgeon's console **16** for use by a surgeon **18** during the procedure. One or more assistants **20** may also participate in the procedure. The minimally invasive teleoperated surgical system **10** further includes a patient-side cart **22** and an electronics cart **24**. The patient-side cart **22** can manipulate at least one removably coupled surgical instrument **26** through a minimally invasive incision in the body of the patient **12** while the surgeon **18** views the surgical site through a user display within the surgeon's console **16**. An image of the surgical site can be obtained by an image capture device such as a stereoscopic endoscope **28**, which can be manipulated by the patient-side cart **22** to orient the endoscope **28** so as to capture images of patient anatomical structures and one or more surgical instruments at a surgical site. Computer processors located on the electronics cart **24** can be used to process the images of the surgical site for subsequent display to the surgeon **18** through a stereoscopic display at the surgeon's console **16**. The number of surgical instruments **26** used at one time will generally depend on the diagnostic or surgical procedure and the space constraints within the operating room among other factors. If it is generally necessary to change one or more of the surgical instruments **26** being used during a procedure, an assistant **20** can remove the surgical instrument **26** from the patient-side cart **22**, and replace it with another surgical instrument **26** from a tray **30** in the operating room.

(24) FIG. 2 is a perspective view of the surgeon's console **16**. The surgeon's console **16** includes a user display that includes a left eye display **32** and a right eye display **34** for presenting the surgeon **18** with a coordinated stereoscopic view of the surgical site that enables depth perception. The console **16** further includes an input command device that includes one or more manual control inputs that include hand grips **36**, **38**. One or more surgical instruments installed for use on the patient-side cart **22** (shown in FIG. 1) move in response to surgeon **18**'s manipulation of the one or

more control inputs **36, 38**. The control inputs **36, 38** can provide the same mechanical degrees of freedom as their associated surgical instruments **26** (shown in FIG. **1**) to provide the surgeon **18** with telepresence, or the perception that the control inputs **36, 38** are integral with the instruments **26** so that the surgeon has a strong sense of directly controlling the instruments **26**. To this end, position, force, and tactile feedback sensors (not shown) may be employed to transmit position, force, and tactile sensations from the surgical instruments **26** back to the surgeon's hands through the control inputs **36, 38**.

(25) The surgeon's console **16** is usually located in the same room as the patient so that the surgeon can directly monitor the procedure, be physically present if necessary, and speak to a patient-side assistant directly rather than over the telephone or other communication medium. But, the surgeon can be located in a different room, a completely different building, or other remote location from the patient allowing for remote surgical procedures.

(26) FIG. **3** is a perspective view of the electronics cart **24**. The electronics cart **24** can be coupled with the endoscope **28** and includes a computer processor to process captured images for subsequent display, such as to a surgeon on the surgeon's console **16**, or on another suitable display located locally and/or remotely. For example, if a stereoscopic endoscope is used, a computer processor on electronics cart **24** can process the captured images to present to the surgeon at the left and right eye displays **32, 34**, coordinated stereo images of the surgical site. Such coordination can include alignment between the opposing images and can include adjusting the stereo working distance of the stereoscopic endoscope. As another example, image processing can include the use of previously determined camera calibration parameters to compensate for imaging errors of the image capture device, such as optical aberrations. Optionally, equipment in electronics cart may be integrated into the surgeon's console or the patient-side cart, or it may be distributed in various other locations in the operating room.

(27) FIG. **4** diagrammatically illustrates a teleoperated surgical system **50** (such as the minimally invasive teleoperated surgical system **10** of FIG. **1**). A surgeon's console **52** (such as surgeon's console **16** in FIG. **1**) can be used by a surgeon to control a patient-side cart **54** (such as patient-side cart **22** in FIG. **1**) during a minimally invasive procedure. The patient-side cart **54** can use an imaging device, such as a stereoscopic endoscope, to capture images of a surgical site and output the captured images to a computer processor located on an electronics cart **56** (such as the electronics cart **24** in FIG. **1**). The computer processor typically includes one or more data processing boards purposed for executing computer readable code stored in a non-volatile memory device of the computer processor. In one aspect, the computer processor can process the captured images in a variety of ways prior to any subsequent display. For example, the computer processor can overlay the captured images with a virtual control interface prior to displaying the combined images to the surgeon via the surgeon's console **52**.

(28) Additionally, or in the alternative, the captured images can undergo image processing by a computer processor located outside of electronics cart **56**. In one aspect, teleoperated surgical system **50** includes an optional computer processor **58** (as indicated by dashed line), which includes one or more central processing units (CPUs) similar to the computer processor located on electronics cart **56**, and patient-side cart **54** outputs the captured images to computer processor **58** for image processing prior to display on the surgeon's console **52**. In another aspect, captured images first undergo image processing by the computer processor on electronics cart **56** and then undergo additional image processing by computer processor **58** prior to display on the surgeon's console **52**. Teleoperated surgical system **50** can include an optional display **60**, as indicated by dashed line. Display **60** is coupled with the computer processor located on the electronics cart **56** and with computer processor **58**, and captured images processed by these computer processors can be displayed on display **60** in addition to being displayed on a display of the surgeon's console **52**.

(29) Moreover, the control inputs **36, 38** are coupled to receive user input commands to control movement of one or more surgical instruments at the surgical site. The processor **58** acts as a

kinematic movement controller circuit that is coupled to receive the user input commands from the control inputs **36, 38**. The processor **58** translates user input in the form of physical movement of the control inputs **36, 38** to control signals to control motors to control corresponding movement of one or more surgical instruments to a movement controller within the patient side cart **54** to impart corresponding movement to an endoscope or to one or more surgical instruments. The translation of user input movement imparted by a user's hand motions upon control inputs **36, 38** to corresponding instrument movement imparted by motors coupled to the surgical instruments involves kinematic movement translation, which typically involves scaling of distances such that an instrument may be moved by only a small fraction of the distance that a control inputs **36** or **38** is moved to impart a user command to cause the instrument movement. In other words, user input movement imparted to control inputs **36, 38** in user space is translated to corresponding smaller scale movements in instrument space at the surgical site. An example of kinematic movement translation in a teleoperated surgical system is described in U.S. Pat. No. 6,424,885.

(30) FIG. 5 is a perspective view of a patient-side cart **500** of a minimally invasive teleoperated surgical system, in accordance with embodiments of the present invention. The patient-side cart **500** includes one or more support assemblies **510**. A surgical instrument manipulator **512** is mounted at the end of each support assembly **510**. Additionally, each support assembly **510** can optionally include one or more unpowered, lockable setup joints that are used to position the attached surgical instrument manipulator **512** with reference to the patient for surgery. As depicted, the patient-side cart **500** rests on the floor. In other embodiments, operative portions of the patient-side cart can be mounted to a wall, to the ceiling, to the operating table **526** that also supports the patient's body **522**, or to other operating room equipment. Further, while the patient-side cart **500** is shown as including four surgical instrument manipulators **512**, more or fewer surgical instrument manipulators **512** may be used.

(31) A functional minimally invasive teleoperated surgical system will generally include a vision system portion that enables a user of the teleoperated surgical system to view the surgical site from outside the patient's body **522**. The vision system typically includes a camera instrument **528** for capturing video images and one or more video displays for displaying the captured video images. In some surgical system configurations, the camera instrument **528** includes optics that transfer the images from a distal end of the camera instrument **528** to one or more imaging sensors (e.g., CCD or CMOS sensors) outside of the patient's body **522**. Alternatively, the imaging sensor(s) can be positioned at the distal end of the camera instrument **528**, and the signals produced by the sensor(s) can be transmitted along a lead or wirelessly for processing and display on the one or more video displays. One example of a video display is the stereoscopic display on the surgeon's console in surgical systems commercialized by Intuitive Surgical, Inc., Sunnyvale, California.

(32) Referring to FIG. 5, mounted to each surgical instrument manipulator **512** is a surgical instrument **520** that operates at a surgical site within the patient's body **522**. Each surgical instrument manipulator **512** can be provided in a variety of forms that allow the associated surgical instrument to move with one or more mechanical degrees of freedom (e.g., all six Cartesian degrees of freedom, five or fewer Cartesian degrees of freedom, etc.). Typically, mechanical or control constraints restrict each manipulator **512** to move its associated surgical instrument around a center of motion on the instrument that stays stationary with reference to the patient, and this center of motion is typically located at the position where the instrument enters the body.

(33) In one aspect, surgical instruments **520** are controlled through computer-assisted teleoperation. A functional minimally invasive teleoperated surgical system includes a control input that receives inputs from a user of the teleoperated surgical system (e.g., a surgeon or other medical person). The control input is in communication with one or more computer-controlled teleoperated actuators, such as one or more motors to which surgical instrument **520** is coupled. In this manner, the surgical instrument **520** moves in response to a medical person's movements of the control input. In one aspect, one or more control inputs are included in a surgeon's console such as surgeon's console

16 shown at FIG. 2. A surgeon can manipulate control inputs **36** of surgeon's console **16** to operate teleoperated actuators of patient-side cart **500**. The forces generated by the teleoperated actuators are transferred via drivetrain mechanisms, which transmit the forces from the teleoperated actuators to the surgical instrument **520**.

(34) Referring to FIG. 5, in one aspect, a surgical instrument **520** and a cannula **524** are removably coupled to manipulator **512**, with the surgical instrument **520** inserted through the cannula **524**. One or more teleoperated actuators of the manipulator **512** move the surgical instrument **512** as a whole. The manipulator **512** further includes an instrument carriage **530**. The surgical instrument **520** is detachably connected to the instrument carriage **530**. In one aspect, the instrument carriage **530** houses one or more teleoperated actuators inside that provide a number of controller motions that the surgical instrument **520** translates into a variety of movements of an end effector on the surgical instrument **520**. Thus the teleoperated actuators in the instrument carriage **530** move only one or more components of the surgical instrument **520** rather than the instrument as a whole. Inputs to control either the instrument as a whole or the instrument's components are such that the input provided by a surgeon or other medical person to the control input (a “master” command) is translated into a corresponding action by the surgical instrument (a “slave” response).

(35) In an alternate embodiment, instrument carriage **530** does not house teleoperated actuators. Teleoperated actuators that enable the variety of movements of the end effector of the surgical instrument **520** are housed in a location remote from the instrument carriage **530**, e.g., elsewhere on patient-side cart **500**. A cable-based force transmission mechanism or the like is used to transfer the motions of each of the remotely located teleoperated actuators to a corresponding instrument-interfacing actuator output located on instrument carriage **530**. In some embodiments, the surgical instrument **520** is mechanically coupled to a first actuator, which controls a first motion of the surgical instrument such as longitudinal (z-axis) rotation. The surgical instrument **520** is mechanically coupled to a second actuator, which controls second motion of the surgical instrument such as two-dimensional (x, y) motion. The surgical instrument **520** is mechanically coupled to a third actuator, which controls third motion of the surgical instrument such as opening and closing or a jaws end effector.

(36) FIG. 6 is a side view of a surgical instrument **520**, which includes a distal portion **650** and a proximal control mechanism **640** coupled by an elongate tube **610** having an elongate tube centerline axis **611**. The surgical instrument **520** is configured to be inserted into a patient's body and is used to carry out surgical or diagnostic procedures. The distal portion **650** of the surgical instrument **520** can provide any of a variety of end effectors **654**, such as the forceps shown, a needle driver, a cautery device, a cutting tool, an imaging device (e.g., an endoscope or ultrasound probe), or the like. The surgical end effector **654** can include a functional mechanical degree of freedom, such as jaws that open or close, or a knife that translates along a path. In the embodiment shown, the end effector **654** is coupled to the elongate tube **610** by a wrist **652** that allows the end effector to be oriented relative to the elongate tube centerline axis **611**. Surgical instrument **520** can also contain stored (e.g., on a semiconductor memory inside the instrument) information, which may be permanent or may be updatable by a surgical system configured to operate the surgical instrument **520**. Accordingly, the surgical system may provide for either one-way or two-way information communication between the surgical instrument **520** and one or more components of the surgical system.

(37) FIG. 7 is a perspective view of surgical instrument manipulator **512**. Instrument manipulator **512** is shown with no surgical instrument installed. Instrument manipulator **512** includes an instrument carriage **530** to which a surgical instrument (e.g., surgical instrument **520**) can be detachably connected. Instrument carriage **530** houses a plurality of teleoperated actuators. Each teleoperated actuator includes an actuator output **705**. When a surgical instrument is installed onto instrument manipulator **512**, one or more instrument inputs (not shown) of an instrument proximal control mechanism (e.g., proximal control mechanism **640** at FIG. 6) are mechanically coupled

with corresponding actuator outputs **705**. In one aspect, this mechanical coupling is direct, with actuator outputs **705** directly contacting corresponding instrument inputs. In another aspect, this mechanical coupling occurs through an intermediate interface, such as a component of a drape configured to provide a sterile barrier between the instrument manipulator **512** and an associated surgical instrument.

(38) In one aspect, movement of one or more instrument inputs by corresponding teleoperated actuators results in a movement of a surgical instrument mechanical degree of freedom. For example, in one aspect, the surgical instrument installed on instrument manipulator **512** is surgical instrument **520**, shown at FIG. **6**. Referring to FIG. **6**, in one aspect, movement of one or more instrument inputs of proximal control mechanism **640** by corresponding teleoperated actuators rotates elongate tube **610** (and the attached wrist **652** and end effector **654**) relative to the proximal control mechanism **640** about elongate tube centerline axis **611**. In another aspect, movement of one or more instrument inputs by corresponding teleoperated actuators results in a movement of wrist **652**, orienting the end effector **654** relative to the elongate tube centerline axis **611**. In another aspect, movement of one or more instrument inputs by corresponding teleoperated actuators results in a movement of one or more moveable elements of the end effector **654** (e.g., a jaw member, a knife member, etc.). Accordingly, various mechanical degrees of freedom of a surgical instrument installed onto an instrument manipulator **512** can be moved by operation of the teleoperated actuators of instrument carriage **530**.

Annotating a Recorded Video

(39) FIG. **8** shows a schematic diagram of an exemplary surgical planning tool **800**. In one aspect, surgical planning tool **800** includes a teleoperated surgical system **850** in data communication with an electronic medical device record database **830**. Teleoperated surgical system **850** shown here is similar to teleoperated surgical system **850** shown at FIG. **4**. In one aspect, electronic medical record database **830** includes the medical records of patients that have undergone treatment at a particular hospital. Database **830** can be implemented on a server located on-site at the hospital. The medical record entries contained in the database **830** can be accessed from hospital computers through an intranet network. Alternatively, database **830** can be implemented on a remote server located off-site from the hospital, e.g., using one of a number of cloud data storage services. In this case, medical record entries of database **830** are stored on the cloud server, and can be accessed by a computer with internet access.

(40) In one aspect, a surgical procedure is performed on a first patient using teleoperated surgical system **850**. An imaging device associated with teleoperated surgical system **850** captures images of the surgical site and displays the captured images as frames of a video on a display of surgeon's console **52**. In one aspect, a medical person at surgeon's console **52** highlights or annotates certain patient anatomy shown in the displayed video using an input device of surgeon's console **52**. An example of such an input device is control input **36** shown at FIG. **2**, which is coupled to a cursor that operates in conjunction with a graphic user interface overlaid onto the displayed video. The graphic user interface can include a QWERTY keyboard, a pointing device such as a mouse and an interactive screen display, a touch-screen display, or other means for data or text entry. Accordingly, the medical person can highlight certain tissue of interest in the displayed image or enter a text annotation.

(41) In one aspect, the surgical site video is additionally displayed on a display located on electronics cart **56**. In one aspect, the display of electronics cart is a touch-screen user interface usable by a medical person to highlight and annotate certain portions of patient anatomy shown on an image that is displayed for viewing on the display on the electronics cart. A user, by touching portions of patient anatomy displayed on the touch-screen user interface, can highlight portions of the displayed image. Additionally, a graphic interface including a QWERTY keyboard can be overlaid on the displayed image. A user can use the QWERTY keyboard to enter text annotations.

(42) In one aspect, the surgical site video captured by the imaging device associated with

teleoperated surgical system **850** is recorded by the teleoperated surgical system **850**, and stored on database **830**, in addition to being displayed in real time or near real time to a user. Highlights and/or annotations associated with the recorded video that were made by the user can also be stored on database **830**. In one aspect, the highlights made by the user are embedded with the recorded video prior to its storage on database **830**. At a later time, the recorded video can be retrieved for viewing. In one aspect, a viewer of the recorded video can select whether the highlights are displayed or suppressed from view. Similarly, annotations associated with the recorded video can also be stored on database **830**. In one aspect, the annotations made by the user are used to tag the recorded video, and can be used to provide as a means of identifying the subject matter contained in the recorded video. For example, one annotation may describe conditions of a certain disease state. This annotation is used to tag the recorded video. At a later time, a person desiring to view recorded procedures concerning this disease state can locate the video using a key word search.

Retrieval of Stored Video

(43) In some cases, it is desirable for a medical person to be able to view video recordings of past surgical procedures performed on a given patient. In one aspect, a patient who previously underwent a first surgical procedure to treat a medical condition subsequently requires a second surgical procedure to treat recurrence of the same medical condition or to treat anatomy located nearby to the surgical site of the first surgical procedure. In one aspect, the surgical site events of the first surgical procedure were captured in a surgical site video recording, and the video recording was archived in database **830** as part of the patient's electronic medical records. Prior to performing the second surgical procedure on the patient, a medical person can perform a search of database **830** to locate the video recording of the patient's earlier surgical procedure.

(44) In some cases, it is desirable for a medical person planning to perform a surgical procedure on a patient to be able to view video recordings of similar surgical procedures performed on persons having certain characteristics similar to the patient. In one aspect, surgical site video recordings of surgical procedures can be tagged with metadata information such as the patient's age, gender, body mass index, genetic information, type of procedure the patient underwent, etc., before each video recording is archived in database **830**. In one aspect, the metadata information used to tag a video recording is automatically retrieved from a patient's then-existing medical records, and then used to tag the video recording before the video recording is archived in database **830**. Accordingly, prior to performing a medical procedure on a patient, a medical person can search database **830** for video recordings of similar procedures performed on patients sharing certain characteristics in common with the patient. For example, if the medical person is planning to use teleoperated surgical system **850** to perform a prostatectomy on a 65-year-old male patient with an elevated body mass index using, the medical person can search database **830** for surgical site video recordings of prostatectomies performed using teleoperated surgical system **850** on other males of similar age and having similarly elevated body mass index.

(45) In one aspect, a video recording of a surgical procedure is communicated by database **830** to an optional personal computer **820** (as indicated by dashed line), and made available for viewing by a medical person who plans to perform a surgical procedure. Additionally, or in the alternative, the video recording of the earlier surgical procedure can be communicated by database **830** to teleoperated surgical system **850**, and made available for viewing preoperatively or intraoperatively. In one aspect, the video recording is displayed by teleoperated surgical system **850** on a display located on surgeon's console **52**. In another aspect, the video recording of the first surgical procedure is displayed on a display located on electronics cart **56**.

Cloud-Based Video Database

(46) In one aspect, database **830** is implemented on a remote server using a cloud data storage service and is accessible by multiple health care providers. Referring to FIG. **8**, as shown by dashed line, surgical planning tool **800** optionally includes teleoperated surgical system **850** (as indicated by dashed line) and personal computer **840** (as indicated by dashed line). In one aspect,

teleoperated surgical system **850** is similar to teleoperated surgical system **850** and personal computer **840** is similar to personal computer **820**, except that teleoperated surgical system **850** and personal computer **820** are located at a first health care provider and teleoperated surgical system **850** and personal computer **840** are located at a second health care provider. In one aspect, a first patient requires surgical treatment of a medical condition, and undergoes a surgical procedure using teleoperated surgical system **850** at the first health care provider. A video recording of the surgical procedure is archived on database **830**. At a later time, a second patient requires surgical treatment of the same medical condition, and plans to receive surgical treatment using teleoperated surgical system **850** at the second health care provider. Prior to performing the surgical procedure on the second patient, a medical person accesses database **830** through a secure internet connection and searches database **830** for surgical site video recordings of similar procedures. In one aspect, the medical person treating the second patient is able to retrieve from database **830** the video recording of first patient's surgical procedure, without acquiring knowledge of the identity of the first patient. In this manner, the privacy of the first patient is maintained. In one aspect, the video recording of the first patient's surgical procedure includes highlights and/or annotations made by the medical person who treated the first patient.

Computer Based Pattern Matching and Analysis

(47) Surgical planning tool **800** can include a pattern matching and analysis algorithm implemented in the form of computer executable code. In one aspect, the pattern matching and analysis algorithm is stored in a non-volatile memory device of surgical planning tool **800**, and is configured to analyze the video recordings archived in database **830**. As discussed previously, each of the video recordings archived in database **830** can be tagged and/or embedded with certain metadata information. This metadata information can include patient information such as patient age, gender, and other information describing the patient's health or medical history. Additionally, as discussed previously, the metadata information can include highlights or annotations made by a medical person. In one aspect, these highlights and annotations are embedded with the video recording and archived together with the video in database **830**.

(48) In one aspect, pattern matching and analysis algorithm includes an image analysis component that identifies patterns in shapes and colors that are shared amongst multiple video recordings stored on database **830**. The pattern matching and analysis algorithm then reviews the tagged metadata associated with this subset of video recordings to determine whether any words or phrases are frequently associated with videos within this subset. These analyses performed by pattern matching and analysis algorithm can be used to assist medical persons in making determinations about patient anatomy, preferred surgical approaches, disease states, potential complications, etc.

A Method of Using a Surgical Planning Tool

(49) FIG. **9** shows a method **900** of using a surgical planning tool. In one aspect, the surgical planning tool is similar to surgical planning tool **800** at FIG. **8**. At **910**, a fact or characteristic describing a medical patient, e.g., a medical condition suffered by a patient, is received by a medical device. Medical device can receive this fact or circumstance via a user interface located on a teleoperated surgical system (e.g., teleoperated surgical system **10** at FIG. **1** or teleoperated surgical system **50** at FIG. **4**), or alternatively, through a personal computer similar to personal computer **820** at FIG. **2**. At **920**, the medical device uses the fact or characteristic received at **910** to retrieve at least one relevant video recording of a surgical procedure from a medical device database. At **930**, the medical device uses the video recordings to determine surgical planning information. In one aspect, the surgical planning information includes the types of instruments used in the recorded procedure. At **940**, the medical device displays to a user the surgical planning information determined at **930**.

A Method of Using Surgical Skill Level to Guide a Surgical Procedure

(50) Chart **1** identifies several example distinct core set of surgical instrument skills have been identified that are useful during a teleoperated surgical procedure in accordance with Assessment of

Robotic Console Skills (ARCS) criteria.

(51) TABLE-US-00001 CHART 1 Surgical Skill Bimanual wrist manipulation Camera Control Master clutching to manage hand position Use of a third instrument arm Activating an energy source Appropriate depth perception Awareness of forces applied by instruments

(52) In some embodiments, surgical skill level for a category are rated as novice, intermediate and experienced. A surgeon's skill level may vary from one skill category to the next. The skill assessment scale is generally applicable to any multiport robotically assisted surgical procedure, regardless of surgical specialty.

(53) FIG. 10 is an illustrative drawing representing storage atlas in a computer readable storage device **1004** in accordance with some embodiments. The storage atlas **1002** includes first information structures **1006** that indicates instances of previously performed surgical procedures. A second information structures **1008** that indicates teleoperated surgical instrument actuation states during the previously performed surgical procedures. A third information structure **1010** associates a surgical procedure with surgical activities during the surgical procedure. A fourth information structures **1012** associates a surgeon with the surgeon's surgical skill levels. A fifth information structure **1014** associates surgical procedures with surgical instrument actuation states. A sixth information structure **1016** associates surgeon skill levels during different activates with different messages. A seventh information structure **1018** associates surgeon skill levels with during different activates with different surgical instrument safety actuation states. A ninth information structure **1019** associates recorded video information from individual surgeries with corresponding surgical instrument actuator state information and recorded surgeon eye movements during the surgeries in accordance with some embodiments.

(54) In some embodiments, information in the various information structures **1004-1019** are evaluated to identify correlations between surgeon skill levels and surgical procedure results/risks. In some embodiments, information in the various information structures **1004-1019** are evaluated to identify correlations between patient safety concerns/risks and surgical activities during a surgical procedure. In some embodiments, teleoperated surgical procedures are evaluated to identify correlations between patient safety concerns/risks and surgical instrument actuator state during a surgical activity as a function of surgeon skill level. In some embodiments the storage atlas **1002** includes a tenth information structures **1020** to provide a correlation between surgical outcomes/risks and surgical instrument actuator state during a surgical activity as a function of surgeon skill level. These evaluations may involve machine learning (ML) techniques, for example.

(55) The storage atlas **1002** includes data concerning surgeries on prior patients and the prior surgeons who performed the prior surgeries. In some embodiments, the storage atlas **1002** includes video images of surgical scenes from prior surgeries and corresponding annotations such as text and telestration tags **1022**. In some embodiments, the storage atlas **1002** includes recordings **1024** of surgical instrument actuator states during the prior surgeons' performance of surgical activities in the prior surgeries.

(56) FIG. 11 is an illustrative drawing representing an example of the seventh information structure **1018** included within the atlas **1002** in the storage device **1004**, which associates recorded video information from an individual surgery with corresponding surgical instrument actuator state information in accordance with some embodiments. In one aspect, video recording images of patient anatomy during a surgery, surgical instrument actuator states during the surgery, and surgeon eye movement during the surgery are time stamped ($t_1, t_2 \dots t_n$) so as to produce a chronological record of times of occurrence of surgical activities upon patient anatomy, to provide a corresponding chronological record of times of occurrence of surgical instrument actuator states and to provide a corresponding chronological record of surgical eye movement during a surgical procedure. Thus, time stamps recorded during a surgical procedure are used to temporally align video images anatomy, with surgical instrument actuator states and surgeon eye gaze.

(57) During a surgery, a user may annotate the video recording and the surgical instrument

actuation state recording with metadata that indicate corresponding surgical activity such as vessel sealing, suture knot-tying or blunt tissue dissection, for example. The annotation may include one or more of or a combination of written notes tagged to video information and/or surgical instrument actuation state information, coloring or highlighting (e.g., telestration) of images in the video recordings, for example. The annotations may be time stamped for use to temporally align them with corresponding video recording information and corresponding recorded surgical instrument state information.

(58) During a teleoperated surgical procedure, a surgical activity such as neurovascular bundle dissection (nerve sparing), often involves use of multiple surgical instruments such as a prograsper and robotic scissors, each having its own actuator state. Thus, different surgical activities often require combinations of multiple surgical instrument skills. For example, performance of a continuous suturing surgical activity often requires the following combination of surgical skills: instrument wrist manipulation, needle grasping, needle passing and orientation between two instruments, tissue grasping, and needle driving.

(59) FIGS. 12A-12C are illustrative drawings showing an example surgical instrument **1202** and an actuator assembly **1203** in which the surgical instrument is shown in three different example operational states in accordance with some embodiments. The example instrument **1202** includes a jaw end effector **1204** that can transition between open and closed states and a continuum of partially opened/partially closed states in between. The example instrument **1202** also includes a two degree of freedom (2-dof) wrist **1206** that can move between different two-dimensional (x, y) positional states. The example actuator assembly **1203** includes a first actuator **1208**, which in some embodiments includes a jaw motor (JM) used to actuate the jaw end effector **1204**. The example actuator assembly **1203** includes a second actuator **1210**, which in some embodiments includes a wrist motor (WM) used to actuate the wrist **1206**. During a surgery, the surgical instrument **1202** may transition through multiple actuation states corresponding to different activities during a surgical procedure. As represented in FIG. 12A, for example, a surgical procedure may involve a first surgical activity in which the first actuator **1208** (the JM) disposes the jaw end effector **1204** to a fully open state and the second actuator **1210** the (WM) disposes the wrist **1206** to a first positional state (x1, y1). As represented in FIG. 12B, for example, the surgical procedure may involve a second surgical activity in which the first actuator **1208** transitions the jaw end effector **1204** to a fully closed state and the second actuator **1210** transitions the wrist **1206** to a second positional state (x2, y2). As represented in FIG. 12C, for example, the surgical procedure may involve a third surgical activity in which the first actuator **1208** disposes the jaw end effector **1104** in a partially open/partially closed state and the second actuator **1210** transitions the wrist **1206** to a third positional state (x3, y3).

(60) In some embodiments, performance of a teleoperated surgical system in response to a surgeon's input control commands is scaled based upon the surgeon's skill level for surgical activities performed using the system during the surgical procedure. More particularly, rate of movement of a surgical instrument in instrument space in response to user input at a user input command device in user space is scaled based upon at least in part upon user skill level. For example, a record of the surgeon's skill level may indicate a novice skill level in performance of a needle driving surgical activity using a Large Suture Cut Needle Driver surgical instrument. In accordance with some embodiments, during the performance of the needle driving surgical activity, the instrument actuator is operated in a first (novice) mode in which the Large Suture Cut Needle Driver automatically moves very deliberately (1:0.333 scaling) relative to the user intent when near the respective tissue. Thus, the processor **58** is configured for a novice user of the Large Suture Cut Needle Driver surgical instrument in which translation of user input movement to instrument movement is scaled to slow instrument movement. A one-unit movement in user space imparted at control inputs **36**, **38** is kinematically translated to a 0.333 unit movement of the instrument in surgical instrument space. Alternatively, for example, a record of the surgeon's skill level may

indicate an intermediate skill level in performance of the needle driving surgical activity using a Large Needle Driver surgical instrument. In accordance with some embodiments, during the performance of the needle driving surgical activity, the instrument actuator is operated in a second (intermediate) mode in which the Large Needle Driver moves deliberately in a 1:0.5 scale relative to the user intent when near the respective tissue. Thus, the processor **58** is configured for intermediate skill level user of the Large Needle Driver surgical instrument in which translation of user input movement to instrument movement is scaled to slow instrument movement. A one-unit movement in user space imparted at control inputs **36**, **38** is kinematically translated to a 0.5 unit movement of the instrument in surgical instrument space. As yet another alternative, for example, a record of the surgeon's skill level may indicate an experienced skill level in performance of the needle driving surgical activity using the Mega Needle Driver surgical instrument. In accordance with some embodiments, during the performance of the needle driving surgical activity, the instrument actuator is operated in a third (experienced) mode in which the Mega Needle Driver moves in the same speed, 1:1 scale, relative to the user intent when near the respective tissue. Thus, the processor **58** is configured for an experienced skill level user of the Mega Needle Driver surgical instrument in which translation of user input movement to instrument movement is scaled to match instrument movement. A one-unit movement in user space imparted at control inputs **36**, **38** is kinematically translated to a 1.0-unit movement of the instrument in surgical instrument space.

(61) FIG. **13** is an illustrative drawing representing an example tenth information structure **1020** of the atlas **1002** stored in the computer readable storage device **1004** that corresponds to an example surgical procedure to be performed by an example surgeon. The information structure **1020** associates surgical activities during the surgical procedure with surgeon skills. The information structure **1020** associates surgeon skills with a surgeon's skill levels. The information structure **1020** associates surgeon activities with surgical instrument actuator states. The information structure **1020** associates surgical state, surgical skill, surgical skill level, actuator state tuples with surgical actuator safety states.

(62) A first column of the information structure **1020** indicates a list of surgical activities, **A1**, **A2** and **A3** to be performed during the example surgical procedure. A second column of the information structure **1020** indicates lists of surgical skills required during each of the activities and corresponding skill levels of the surgeon performing the surgery for each of the skills. Specifically, in the example, activity **A1** is associated with surgical skill **S1**, skill **S3** and skill **S5**, and the surgeon possess an experienced skill level **L.sub.E** for all three skills **S1**, **S2** and **S5**. Activity **A2** is associated with surgical skills **S1**, **S2**, **S3**, and the surgeon possess an experienced skill level **L.sub.E** for skills **S1** and **S3** and **S5** and possess a novice skill level **L.sub.N** for skill **S2**. Activity **A3** is associated with surgical skills **S1**, **S4**, **S6**, and the surgeon possess an experienced skill level **L.sub.E** for skills **S1** and **S6** and possess an intermediate skill level **L1** for skill **S4**. A third column of the information structure **1020** indicates surgical instrument actuation states indicative of the occurrence of the surgical activities. For example, surgical instrument actuator state **SIA.sub.A1** is indicative of occurrence of surgical state **A1**. Surgical instrument actuator state **SIA.sub.A2** is indicative of occurrence of surgical state **A2**. Surgical instrument actuator state **SIA.sub.A3** is indicative of occurrence of surgical state **A3**. A fourth column of the information structure **1020** indicates messages to be presented to a surgical team at different stages of a surgical procedure, based upon surgical activity states. For example, surgical activity state **A1** is associated with message, **M.sub.A1E**, directed to an experienced skill level surgeon; surgical activity state **A2** is associated with message, **M.sub.A2N**, directed to a novice skill level surgeon; and surgical activity state **A3** is associated with message, **M.sub.A3I**, directed to an intermediate skill level surgeon.

(63) A fifth column of the information structure **1020** indicates surgical instrument actuator safety states to be used during different surgical activities of the surgical procedure. For example, surgical activity **A1** is associated with an instrument actuator safety state **SAI.sub.A1E**, which indicates that

the surgeon has an experienced skill level for surgical activity A1. Surgical activity A2 is associated with an instrument actuator safety state SIA.sub.A2N, which indicates that the surgeon has a novice skill level for surgical activity A2. Surgical activity A3 is associated with an instrument actuator safety state SIA.sub.A3I, which indicates that the surgeon has intermediate skill level for surgical activity A3. It is noted that in this example, the associated instrument actuator safety state is at a level of the lowest corresponding surgeon skill level applicable for the surgical activity. For example, for activity A1, the surgeon's skill level is level L.sub.E (experienced) for all three skills S1, S3, S5, and therefore, the instrument actuator safety state is SAI.sub.A1E, which corresponds to the experienced level. For activity A2, the surgeon's lowest skill level is level L.sub.N (novice) for skill S2, and therefore, the instrument actuator safety state is SAI.sub.A2N, which corresponds to the novice level. For activity A3, the surgeon's lowest skill level is level L.sub.1 (intermediate) for skill S4, and therefore, the instrument actuator safety state is SAI.sub.A3I, which corresponds to the intermediate level.

(64) Referring to the first row of the example information **1020** structure of FIG. **13**, for example, during a surgical procedure involving, activity A1 of the surgery may involve tissue dissection, which requires skill S1=instrument wrist manipulation and orientation, skill S3=tissue grasping and manipulation, and skill S5=cutting. Message MA1.sub.E may indicate “to make small smooth cuts”. Surgical instrument safety actuation state A1.sub.E may involve instrument is set to 1:1 scaling.

(65) Referring to the second row of the example information **1020** structure of FIG. **13**, for example, during the surgical procedure involving, activity A 2 of the surgery may involve tissue suturing, which requires skill S1, skill S2=needle driving and skill S3. Message MA2.sub.N may indicate “to be careful with needle handling to avoid unnecessary tissue needle piercings”. Surgical instrument safety actuation state A2.sub.N may involve instrument is set to 1:0.333 scaling.

(66) Referring to the third row of the example information **1020** structure of FIG. **13**, for example, during the surgical procedure involving, activity A3 of the surgery may involve suture knot-tying, which requires skill S1, skill S4=suture handling and skill S6=knot-tying. Message MA3.sub.1 may indicate “to be careful managing length of suture tail”. Surgical instrument safety actuation state A3.sub.1 may involve instrument is set to 1:0.5 scaling.

(67) FIG. **14** is an illustrative flow diagram **1402** representing configuration of processor **58** to scale kinematic translation of user-to-instrument movement according to a surgical instrument safety actuation state based at least in part upon surgeon skill level information in accordance with some embodiments. Computer program code is used in some embodiments to configure one or more CPUs of the processor **58** to perform the process **1402**. In block **1404**, a surgeon identification is received at an input to a computer processing system associated with the electronics cart **56**. In block **1406**, an identification of a surgical procedure is received at an input of the computer processing system associated with the electronics cart **56**. In block **1408**, information included within the atlas **1002** within information structures **1010**, **1012**, **1014**, **1016** and **1018** is used to produce an instance of the tenth information structure **1020** of FIG. **13** relating to the identified surgeon and to the identified surgical procedure.

(68) During the performance of the identified surgical procedure, block **1410** tracks for each of one or more surgical instruments **26**, which instrument is mounted in at a surgical instrument manipulator **512** and also tracks operational state of a surgical instrument actuator to determine, based upon the surgical instrument actuator state information within the third column of the produced instance of the tenth information structure **1020**, when the surgical procedure is transitioning to an activity identified in the first column of the information structure **1020**. In decision block **1412**, a determination is made as to whether at least one of an instrument **26** mounted at a manipulator **512** a current instrument actuator state matches an actuator state associated with an activity. In response to no match, control loops back to block **1410** and tracking continues. In response to a match, block **1414** uses transitions the surgical instrument actuator to an

instrument actuator safety state identified in the fifth column of the information structure **1020** that is associated with at least one of an instrument **26** mounted at a manipulator **512** and current instrument actuator state and an associated surgeon skill level indicated the second column of the information structure **1020**. Block **1416** configures the display device **32**, **34** and/or **60** to present to a surgical team a safety message associated with the current instrument actuator state and an associated surgeon skill level. In some embodiments, control next flows back to block **1410**, which continues to track surgical instrument actuator state based upon other identified actuator state transition information, for example.

(69) Although illustrative embodiments have been shown and described, a wide range of modification, change and substitution is contemplated in the foregoing disclosure and in some instances, some features of the embodiments may be employed without a corresponding use of other features. For example, in some embodiments, a virtual surgical system comprises a first virtual robotic surgical instrument. The system includes an image generation device to produce images of virtual anatomical tissue and of the first virtual robotic surgical instrument. A user display is coupled to the image generation device so as to show to a user, the generated images of the virtual anatomical tissue and of the first virtual robotic surgical instrument. A user input command device is coupled to receive user input commands to control virtual movement of the first virtual robotic surgical instrument. A virtual movement controller is coupled to receive the user input commands from the input command device and configured to control virtual movement of the first virtual robotic surgical instrument in response to the user input commands and to scale a rate of virtual movement of the first virtual robotic surgical instrument, based at least in part upon a surgical skill level at using the first virtual robotic surgical instrument of the user providing the received user input commands, from a rate of movement indicated by the user input commands received at the user input command device.

(70) Moreover, in some embodiments, a method is provided to operate a virtual surgical system that includes a virtual robotic surgical instrument manipulator. The method includes receiving user input commands from a user to control movement of a virtual robotic surgical instrument mounted at the virtual robotic surgical instrument manipulator. The method further includes determining an identification of a virtual robotic surgical instrument mounted at the virtual robotic surgical instrument manipulator during the receiving the user input commands. The method also includes scaling a rate of movement of the virtual robotic surgical instrument, based at least in part upon a skill level of the user at use of the identified virtual surgical instrument, from a rate of movement indicated by the user input commands. One of ordinary skill in the art would recognize many variations, alternatives, and modifications. Thus, the scope of the disclosure should be limited only by the following claims, and it is appropriate that the claims be construed broadly and in a manner consistent with the scope of the embodiments disclosed herein.

Claims

1. A surgical system comprising: one or more processors, coupled to memory, and configured to: identify a surgical instrument mounted to the surgical system, the surgical instrument moved by operation of a surgical instrument actuator; determine based at least on a state of the surgical instrument actuator, that a surgical procedure is transitioning to a surgical activity of one or more surgical activities; identify a surgical skill level of a surgeon at using the surgical instrument; and match, via one or more information structures, the state of the surgical instrument actuator to an actuator state associated with the surgical activity, a safety state and the surgical skill level; transition, responsive to the match, the state of the surgical instrument actuator to the safety state identified based at least on the surgical skill level of the surgeon.
2. The surgical system of claim 1, wherein the one or more processors are further configured to determine the safety state based at least on the surgical instrument, the state of the surgical

instrument actuator and the surgical skill level of the surgeon for the surgical activity.

3. The surgical system of claim 1, wherein the one or more processors are further configured to transition the state of the surgical instrument actuator to the safety state, among a plurality of safety states, that matches the surgical skill level of the surgeon.

4. The surgical system of claim 1, wherein the one or more processors are further configured to match the state of the surgical instrument actuator to an actuator state associated with the surgical activity.

5. The surgical system of claim 1, wherein the one or more processors are further configured to identify from a record the surgical skill level of the surgeon associated with the surgical activity.

6. The surgical system of claim 1, wherein the one or more processors are further configured to scale kinetic translation of the surgeon to surgical instrument movement according to the safety state and the surgeon skill level.

7. The surgical system of claim 1, wherein the one or more processors are further configured to scale a rate of movement of the surgical instrument relative to a rate of movement of control input from the surgeon, based at least in part upon the surgical skill level of the surgeon.

8. The surgical system of claim 1, wherein the one or more processors are further configured to identify that the surgical instrument is mounted in a surgical instrument manipulator of the surgical system.

9. A surgical system comprising: one or more processors, coupled to memory, and configured to: receive identification of a surgeon and a surgical procedure; identify a surgical instrument being controlled by operation of a surgical instrument actuator; identify, via one or more information structures, a match between a surgical skill level of a surgical skill for a surgical activity of the surgical procedure and a surgical instrument actuator state and a surgical instrument actuator safety state; and transition, responsive to determining the surgical procedure is transitioning to the surgical activity, the surgical instrument actuator state of the surgical instrument actuator to a surgical instrument actuator safety state based at least on the surgical skill level of the surgeon for the surgical skill for the surgical activity.

10. The surgical system of claim 9, wherein the one or more processors are further configured to determine based at least on a state of the surgical instrument actuator, that the surgical procedure is transitioning to the surgical activity of one or more surgical activities.

11. The surgical system of claim 9, wherein the one or more processors are further configured to identify from a record that the surgical instrument is mounted in a surgical instrument manipulator of the surgical system.

12. The surgical system of claim 9, wherein the one or more processors are further configured to transition the surgical instrument actuator state of the surgical instrument actuator to the surgical instrument actuator safety state based at least on the surgical skill level of the surgeon for the surgical skill for the surgical activity and a current state of the surgical instrument actuator.

13. The surgical system of claim 9, wherein the one or more processors are further configured to transition the surgical instrument actuator state of the surgical instrument actuator to the surgical instrument actuator safety state based at least on the surgical skill level of the surgeon for the surgical skill for the surgical activity and the surgical instrument.

14. The surgical system of claim 9, wherein the one or more processors are further configured to identify an information structure in a storage that provides the association.

15. A computer-implement method comprising: identifying, by one or more processors, a surgical instrument mounted to a surgical system and a surgical skill level of a surgeon at using the surgical instrument, the surgical instrument moved by operation of a surgical instrument actuator; determining, by the one or more processors based at least on a state of the surgical instrument actuator, that a surgical procedure is transitioning to a surgical activity of one or more surgical activities; and matching, via one or more information structures, the state of the surgical instrument actuator to an actuator state associated with the surgical activity, a safety state and the surgical skill

level; and transitioning, by the one or more processors responsive to the matching, the state of the surgical instrument actuator to a safety state identified based at least on the state of the surgical instrument actuator and the surgical skill level of the surgeon.

16. The computer-implemented method of claim 15, further comprising scaling, by the one or more processors, a rate of movement of the surgical instrument relative to a rate of movement of control input from the surgeon, based at least in part upon the surgical skill level of the surgeon.

17. The computer-implemented method of claim 15, further comprising determining, by the one or more processors, the safety state based at least on the surgical instrument, the current state of the surgical instrument actuator and the surgical skill level of the surgeon for the surgical activity.

18. The computer-implemented method of claim 15, further comprising scaling, by the one or more processors, kinetic translation of the surgeon to surgical instrument movement according to the safety state and the surgeon skill level.
