

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12417326
B2
September 16, 2025
Asenjo; Juan et al.

Using cloud-based data for industrial simulation

Abstract

A cloud-based simulation generation service collects industrial data from multiple industrial customers for storage and analysis on a cloud platform. The service employs a simulation generator component that analyzes data to facilitate generating a simulation model that simulates an industrial automation system, including simulating or emulating industrial devices, industrial processes, other industrial assets, or network-related assets or devices, and their respective interrelationships with each other. The simulation generator component also analyzes modification data to facilitate generating a modified simulation model that simulates the industrial automation system based on the modification. The simulation generator component performs operation simulations using the simulation model or modified simulation model to facilitate determining whether making the modification is appropriate, determining or predicting performance of a modified industrial automation system, determining compatibility of a modification with an industrial automation system, or determining or predicting performance of the industrial automation system when processing a work order.

Inventors: Asenjo; Juan (Timberlake, OH), Strohmenger; John (Strongsville, OH), Nawalaniec; Stephen (Southlake, TX), Hegrat; Bradford H. (Montville, OH), Harkulich; Joseph A. (Willoughby, OH), Korpela; Jessica Lin (Milwaukee, WI), Wright; Jenifer Rydberg (Renton, WA), Hessmer; Rainer (Rancho Santa Margarita, CA), Dyck; John (Chardon, OH), Hill; Edward Alan (Chagrin Falls, OH), Conti; Sal (Olmsted Township, OH)

Applicant: Rockwell Automation Technologies, Inc. (Mayfield Heights, OH)

Family ID: 1000008818197

Assignee: ROCKWELL AUTOMATION TECHNOLOGIES, INC. (Mayfield Heights, OH)

Appl. No.: 17/649264

Filed: January 28, 2022

Prior Publication Data

Related U.S. Application Data

continuation parent-doc US 16234039 20181227 US 11295047 child-doc US 17649264
continuation parent-doc US 15599921 20170519 US 10204191 20190212 child-doc US 16234039
continuation parent-doc US 14087835 20131122 US 9703902 20170711 child-doc US 15599921
us-provisional-application US 61821639 20130509

Publication Classification

Int. Cl.: G06F30/20 (20200101); G06Q10/06 (20230101)

U.S. Cl.:

CPC G06F30/20 (20200101); G06Q10/06 (20130101); Y02P90/80 (20151101)

Field of Classification Search

CPC: G06F (30/20); G06Q (10/06); Y02P (90/80)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5014317	12/1990	Kita et al.	N/A	N/A
5122948	12/1991	Zapolin	N/A	N/A
5199009	12/1992	Svast	N/A	N/A
5598572	12/1996	Tanikoshi et al.	N/A	N/A
5611059	12/1996	Benton et al.	N/A	N/A
5612869	12/1996	Letzt et al.	N/A	N/A
5682460	12/1996	Hyziak et al.	N/A	N/A
5710885	12/1997	Bondi	N/A	N/A
5844794	12/1997	Keeley	N/A	N/A
5845149	12/1997	Husted et al.	N/A	N/A
5856931	12/1998	McCasland	N/A	N/A
5957985	12/1998	Wong et al.	N/A	N/A
5966301	12/1998	Cook et al.	N/A	N/A
5970430	12/1998	Burns et al.	N/A	N/A
5978568	12/1998	Abraham et al.	N/A	N/A
6167337	12/1999	Haack et al.	N/A	N/A
6175770	12/2000	Bladow	N/A	N/A
6175801	12/2000	Millington	N/A	N/A
6199068	12/2000	Carpenter	N/A	N/A
6279113	12/2000	Vaidya	N/A	N/A
6282455	12/2000	Engdahl	N/A	N/A
6324607	12/2000	Korowitz et al.	N/A	N/A

6381502	12/2001	Rudder et al.	N/A	N/A
6400996	12/2001	Hoffberg et al.	N/A	N/A
6412032	12/2001	Neet et al.	N/A	N/A
6437692	12/2001	Petite et al.	N/A	N/A
6457024	12/2001	Felsentein et al.	N/A	N/A
6463338	12/2001	Neet	N/A	N/A
6466972	12/2001	Paul et al.	N/A	N/A
6529780	12/2002	Soergel et al.	N/A	N/A
6535926	12/2002	Esker	N/A	N/A
6578005	12/2002	Lesaint et al.	N/A	N/A
6611822	12/2002	Beams	N/A	N/A
6624388	12/2002	Blankenship et al.	N/A	N/A
6640145	12/2002	Hoffberg et al.	N/A	N/A
6651062	12/2002	Ghannam et al.	N/A	N/A
6675226	12/2003	Nair et al.	N/A	N/A
6686838	12/2003	Rezvani et al.	N/A	N/A
6691159	12/2003	Grewal et al.	N/A	N/A
6705229	12/2003	Frankenberger	N/A	N/A
6708074	12/2003	Chi et al.	N/A	N/A
6708385	12/2003	Lemelson	N/A	N/A
6714974	12/2003	Machida	N/A	N/A
6728262	12/2003	Woram	N/A	N/A
6732165	12/2003	Jennings, III	N/A	N/A
6732191	12/2003	Baker et al.	N/A	N/A
6757897	12/2003	Shi et al.	N/A	N/A
6774598	12/2003	Kohler et al.	N/A	N/A
6801920	12/2003	Wischinski	N/A	N/A
6819960	12/2003	McKelvey et al.	N/A	N/A
6891850	12/2004	Vandesteeg et al.	N/A	N/A
6895532	12/2004	Raynham	N/A	N/A
6904600	12/2004	James et al.	N/A	N/A
6907302	12/2004	Karbassi	N/A	N/A
6920502	12/2004	Araujo et al.	N/A	N/A
6952680	12/2004	Melby et al.	N/A	N/A
6965802	12/2004	Sexton	N/A	N/A
6968242	12/2004	Hwu et al.	N/A	N/A
6970913	12/2004	Albert et al.	N/A	N/A
6982953	12/2005	Swales	N/A	N/A
7032045	12/2005	Kostadinov	N/A	N/A
7085814	12/2005	Gandhi et al.	N/A	N/A
7103428	12/2005	Varone et al.	N/A	N/A
7133900	12/2005	Szeto	N/A	N/A
7149792	12/2005	Hansen et al.	N/A	N/A
7151966	12/2005	Baier et al.	N/A	N/A
7203560	12/2006	Wylie et al.	N/A	N/A
7210095	12/2006	Mor	N/A	N/A
7233830	12/2006	Callaghan et al.	N/A	N/A
7242009	12/2006	Wilson et al.	N/A	N/A
7275037	12/2006	Lauer	N/A	N/A
7277865	12/2006	Silverstone et al.	N/A	N/A

7289994	12/2006	Nixon et al.	N/A	N/A
7298275	12/2006	Brandt et al.	N/A	N/A
7310344	12/2006	Sue	N/A	N/A
7383155	12/2007	Rosam et al.	N/A	N/A
7412548	12/2007	Sichner	N/A	N/A
7428495	12/2007	Dhar et al.	N/A	N/A
7478010	12/2008	Hashemian	N/A	N/A
7480728	12/2008	Evans	N/A	N/A
7539724	12/2008	Callaghan	N/A	N/A
7734590	12/2009	Chand et al.	N/A	N/A
7827122	12/2009	Campbell, Jr. et al.	N/A	N/A
7831317	12/2009	McGreevy et al.	N/A	N/A
8099661	12/2011	Ritter	N/A	N/A
8150959	12/2011	Bezdicek et al.	N/A	N/A
8266066	12/2011	Wezter et al.	N/A	N/A
8353012	12/2012	Del Real	N/A	N/A
8392845	12/2012	Cahill et al.	N/A	N/A
8451753	12/2012	Vanga et al.	N/A	N/A
8468272	12/2012	Giroti	N/A	N/A
8484250	12/2012	Sujeet et al.	N/A	N/A
8686871	12/2013	Jensen et al.	N/A	N/A
8914300	12/2013	Sustaeta et al.	N/A	N/A
8924328	12/2013	Kozlovsky et al.	N/A	N/A
9024955	12/2014	Ramarao et al.	N/A	N/A
9117076	12/2014	Devost	N/A	N/A
9215264	12/2014	Sokolov	N/A	N/A
9438648	12/2015	Asenjo et al.	N/A	N/A
9507807	12/2015	Florissi et al.	N/A	N/A
9685053	12/2016	Palmeri	N/A	N/A
9690669	12/2016	Bernal et al.	N/A	N/A
9703902	12/2016	Asenjo et al.	N/A	N/A
9709978	12/2016	Asenjo et al.	N/A	N/A
10026049	12/2017	Asenjo et al.	N/A	N/A
10054914	12/2017	Vartiainen et al.	N/A	N/A
11243505	12/2021	Strohmenger	N/A	G05B 23/0237
2001/0035729	12/2000	Graiger et al.	N/A	N/A
2002/0004796	12/2001	Vange et al.	N/A	N/A
2002/0004798	12/2001	Babula et al.	N/A	N/A
2002/0016839	12/2001	Smith et al.	N/A	N/A
2002/0032495	12/2001	Ozaki	N/A	N/A
2002/0042756	12/2001	Kumar et al.	N/A	N/A
2002/0046239	12/2001	Stawikowski et al.	N/A	N/A
2002/0049833	12/2001	Kikinis	N/A	N/A
2002/0065898	12/2001	Leontiev et al.	N/A	N/A
2002/0068983	12/2001	Sexton	N/A	N/A
2002/0068984	12/2001	Alexander et al.	N/A	N/A
2002/0073236	12/2001	Helgeson et al.	N/A	N/A
2002/0077711	12/2001	Nixon et al.	N/A	N/A
2002/0078432	12/2001	Charisius et al.	N/A	N/A

2002/0082966	12/2001	O'Brien et al.	N/A	N/A
2002/0094588	12/2001	Fan et al.	N/A	N/A
2002/0095483	12/2001	Lee et al.	N/A	N/A
2002/0096077	12/2001	Frankenberger	N/A	N/A
2002/0107904	12/2001	Talluri et al.	N/A	N/A
2002/0138378	12/2001	Leskusi	N/A	N/A
2002/0156562	12/2001	Berger et al.	N/A	N/A
2002/0156872	12/2001	Brown	N/A	N/A
2002/0156926	12/2001	Batke et al.	N/A	N/A
2002/0161745	12/2001	Call	N/A	N/A
2002/0169993	12/2001	Woods et al.	N/A	N/A
2003/0004937	12/2002	Salmenkaita et al.	N/A	N/A
2003/0009253	12/2002	McIntyre et al.	N/A	N/A
2003/0009572	12/2002	Turner	N/A	N/A
2003/0011467	12/2002	Suomela	N/A	N/A
2003/0014149	12/2002	Kreidler et al.	N/A	N/A
2003/0023336	12/2002	Kreidler et al.	N/A	N/A
2003/0033179	12/2002	Katz et al.	N/A	N/A
2003/0041089	12/2002	Mauro	N/A	N/A
2003/0051074	12/2002	Edwards	N/A	N/A
2003/0056224	12/2002	Stone	N/A	N/A
2003/0069002	12/2002	Hunter et al.	N/A	N/A
2003/0084016	12/2002	Norgaard et al.	N/A	N/A
2003/0105535	12/2002	Rammler	N/A	N/A
2003/0105585	12/2002	Ukita	N/A	N/A
2003/0109942	12/2002	Yeh et al.	N/A	N/A
2003/0120817	12/2002	Ott et al.	N/A	N/A
2003/0150908	12/2002	Pokorny et al.	N/A	N/A
2003/0156639	12/2002	Liang	N/A	N/A
2003/0167238	12/2002	Zeif	N/A	N/A
2003/0167449	12/2002	Warren et al.	N/A	N/A
2003/0177169	12/2002	Nutt et al.	N/A	N/A
2003/0177201	12/2002	Shen	N/A	N/A
2003/0183456	12/2002	Hatzor	N/A	N/A
2003/0198188	12/2002	Castlebury et al.	N/A	N/A
2003/0200285	12/2002	Hansen et al.	N/A	N/A
2003/0208545	12/2002	Eaton et al.	N/A	N/A
2003/0217100	12/2002	Kronk	N/A	N/A
2003/0224769	12/2002	Solve et al.	N/A	N/A
2003/0236576	12/2002	Resnick et al.	N/A	N/A
2004/0024572	12/2003	Pagnano et al.	N/A	N/A
2004/0025173	12/2003	Levonai et al.	N/A	N/A
2004/0032935	12/2003	Mills et al.	N/A	N/A
2004/0083165	12/2003	Lawrence	N/A	N/A
2004/0111512	12/2003	Barth	N/A	N/A
2004/0148039	12/2003	Farchmin et al.	N/A	N/A
2004/0148187	12/2003	Boettcher et al.	N/A	N/A
2004/0148383	12/2003	Gonsalves et al.	N/A	N/A
2004/0159113	12/2003	Singh et al.	N/A	N/A
2004/0199573	12/2003	Schwartz et al.	N/A	N/A

2004/0203895	12/2003	Balasuriya	N/A	N/A
2004/0214566	12/2003	Suzuki et al.	N/A	N/A
2004/0215551	12/2003	Eder	N/A	N/A
2004/0225629	12/2003	Eder	N/A	N/A
2004/0267729	12/2003	Swaminathan et al.	N/A	N/A
2005/0004789	12/2004	Summers	N/A	N/A
2005/0005093	12/2004	Bartels et al.	N/A	N/A
2005/0021158	12/2004	De Meyer et al.	N/A	N/A
2005/0038528	12/2004	McKelvey et al.	N/A	N/A
2005/0055429	12/2004	Abele et al.	N/A	N/A
2005/0080799	12/2004	Harnden et al.	N/A	N/A
2005/0090911	12/2004	Ingargiola et al.	N/A	N/A
2005/0091410	12/2004	Gibart et al.	N/A	N/A
2005/0120112	12/2004	Wing et al.	N/A	N/A
2005/0125441	12/2004	Clemens et al.	N/A	N/A
2005/0137735	12/2004	Loy et al.	N/A	N/A
2005/0149922	12/2004	Vincent	N/A	N/A
2005/0203869	12/2004	Minamino et al.	N/A	N/A
2005/0203960	12/2004	Suarez et al.	N/A	N/A
2005/0209902	12/2004	Wasaki et al.	N/A	N/A
2005/0257204	12/2004	Bryant et al.	N/A	N/A
2005/0278441	12/2004	Bond et al.	N/A	N/A
2006/0022048	12/2005	Johnson	N/A	N/A
2006/0026193	12/2005	Hood	N/A	N/A
2006/0046712	12/2005	Shamp et al.	N/A	N/A
2006/0067209	12/2005	Sheehan et al.	N/A	N/A
2006/0077095	12/2005	Tucker et al.	N/A	N/A
2006/0078859	12/2005	Mullin	N/A	N/A
2006/0149813	12/2005	Janik	N/A	N/A
2006/0153089	12/2005	Silverman	N/A	N/A
2006/0173873	12/2005	Prompt et al.	N/A	N/A
2006/0190106	12/2005	Kay et al.	N/A	N/A
2006/0190433	12/2005	Chkodrov	N/A	N/A
2006/0236374	12/2005	Hartman	N/A	N/A
2006/0253205	12/2005	Gardiner	N/A	N/A
2006/0259154	12/2005	Hood et al.	N/A	N/A
2006/0259472	12/2005	MacClellan	N/A	N/A
2006/0282432	12/2005	Cassidy et al.	N/A	N/A
2007/0008129	12/2006	Soliman	N/A	N/A
2007/0019641	12/2006	Pai et al.	N/A	N/A
2007/0021968	12/2006	Amir et al.	N/A	N/A
2007/0043674	12/2006	DiFalco et al.	N/A	N/A
2007/0050070	12/2006	Strain	N/A	N/A
2007/0050206	12/2006	Whikehart et al.	N/A	N/A
2007/0061018	12/2006	Callaghan et al.	N/A	N/A
2007/0067145	12/2006	Miller et al.	N/A	N/A
2007/0073850	12/2006	Callaghan et al.	N/A	N/A
2007/0078525	12/2006	Chand	N/A	N/A
2007/0078536	12/2006	Gordon et al.	N/A	N/A
2007/0078537	12/2006	Chand et al.	N/A	N/A

2007/0078736	12/2006	Chand et al.	N/A	N/A
2007/0078862	12/2006	Chand et al.	N/A	N/A
2007/0095907	12/2006	Robinson et al.	N/A	N/A
2007/0112801	12/2006	McGreevy et al.	N/A	N/A
2007/0118560	12/2006	Bornhoevd et al.	N/A	N/A
2007/0130112	12/2006	Lin	N/A	N/A
2007/0132779	12/2006	Gilbert	N/A	N/A
2007/0168057	12/2006	Blevins et al.	N/A	N/A
2007/0192213	12/2006	Wu et al.	N/A	N/A
2007/0194097	12/2006	Jones et al.	N/A	N/A
2007/0198223	12/2006	Ella	N/A	N/A
2007/0213989	12/2006	Cooksy et al.	N/A	N/A
2007/0244892	12/2006	Narancic	N/A	N/A
2007/0245169	12/2006	Farchmin et al.	N/A	N/A
2007/0247789	12/2006	Benson et al.	N/A	N/A
2007/0255431	12/2006	Kinsey	N/A	N/A
2008/0004739	12/2007	Varadhan et al.	N/A	N/A
2008/0027704	12/2007	Kephart et al.	N/A	N/A
2008/0049013	12/2007	Nasle	N/A	N/A
2008/0065243	12/2007	Fallman et al.	N/A	N/A
2008/0077512	12/2007	Grewal	N/A	N/A
2008/0082186	12/2007	Hood et al.	N/A	N/A
2008/0109099	12/2007	Moshier	N/A	N/A
2008/0125887	12/2007	Case	N/A	N/A
2008/0155064	12/2007	Kosuge et al.	N/A	N/A
2008/0162688	12/2007	Reumann et al.	N/A	N/A
2008/0189637	12/2007	Krajewski et al.	N/A	N/A
2008/0208365	12/2007	Grgic et al.	N/A	N/A
2008/0209211	12/2007	Grgic et al.	N/A	N/A
2008/0214104	12/2007	Baumert et al.	N/A	N/A
2008/0229754	12/2007	Goebel et al.	N/A	N/A
2008/0263514	12/2007	DeMesa et al.	N/A	N/A
2008/0303472	12/2007	John et al.	N/A	N/A
2009/0024440	12/2008	Spahn	N/A	N/A
2009/0037378	12/2008	Moor et al.	N/A	N/A
2009/0037872	12/2008	Schnabele et al.	N/A	N/A
2009/0063258	12/2008	Mueller et al.	N/A	N/A
2009/0065578	12/2008	Peterson et al.	N/A	N/A
2009/0070163	12/2008	Angell et al.	N/A	N/A
2009/0083204	12/2008	Baier et al.	N/A	N/A
2009/0086692	12/2008	Chen	N/A	N/A
2009/0088875	12/2008	Baier et al.	N/A	N/A
2009/0089032	12/2008	Sturrock et al.	N/A	N/A
2009/0089233	12/2008	Gach et al.	N/A	N/A
2009/0089359	12/2008	Siorek et al.	N/A	N/A
2009/0089682	12/2008	Baier et al.	N/A	N/A
2009/0109889	12/2008	Budampati et al.	N/A	N/A
2009/0125460	12/2008	Hewison et al.	N/A	N/A
2009/0127325	12/2008	Macurek et al.	N/A	N/A
2009/0132458	12/2008	Edwards et al.	N/A	N/A

2009/0182689	12/2008	Chiles et al.	N/A	N/A
2009/0204234	12/2008	Sustaeta et al.	N/A	N/A
2009/0210071	12/2008	Agrusa et al.	N/A	N/A
2009/0210814	12/2008	Agrusa et al.	N/A	N/A
2009/0216341	12/2008	Enkerud et al.	N/A	N/A
2009/0234689	12/2008	Simon	N/A	N/A
2009/0265157	12/2008	Piepenbrock et al.	N/A	N/A
2009/0300151	12/2008	Friedman et al.	N/A	N/A
2009/0316977	12/2008	Juncker et al.	N/A	N/A
2009/0319831	12/2008	Kruchinin et al.	N/A	N/A
2009/0319848	12/2008	Thaper	N/A	N/A
2010/0010859	12/2009	Ratakonda et al.	N/A	N/A
2010/0023562	12/2009	Kreuch et al.	N/A	N/A
2010/0042704	12/2009	Chakra et al.	N/A	N/A
2010/0057660	12/2009	Kato	N/A	N/A
2010/0076575	12/2009	Vasko et al.	N/A	N/A
2010/0077160	12/2009	Liu et al.	N/A	N/A
2010/0082127	12/2009	Plache et al.	N/A	N/A
2010/0082129	12/2009	McGreevy et al.	N/A	N/A
2010/0082142	12/2009	Usadi et al.	N/A	N/A
2010/0082314	12/2009	Pritchard et al.	N/A	N/A
2010/0082453	12/2009	Speers et al.	N/A	N/A
2010/0082669	12/2009	Obitko et al.	N/A	N/A
2010/0083232	12/2009	Chouinard et al.	N/A	N/A
2010/0083356	12/2009	Steckley et al.	N/A	N/A
2010/0118895	12/2009	Radulescu	N/A	N/A
2010/0146014	12/2009	Ionescu et al.	N/A	N/A
2010/0153487	12/2009	Greven et al.	N/A	N/A
2010/0192144	12/2009	Schmit	N/A	N/A
2010/0210240	12/2009	Mahaffey et al.	N/A	N/A
2010/0211509	12/2009	Jacobs	N/A	N/A
2010/0219950	12/2009	Kong et al.	N/A	N/A
2010/0223212	12/2009	Manolescu et al.	N/A	N/A
2010/0241260	12/2009	Kilibarda et al.	N/A	N/A
2010/0256795	12/2009	McLaughlin et al.	N/A	N/A
2010/0257227	12/2009	McLaughlin et al.	N/A	N/A
2010/0257228	12/2009	Staggs et al.	N/A	N/A
2010/0306377	12/2009	DeHaan et al.	N/A	N/A
2010/0318392	12/2009	Cassels et al.	N/A	N/A
2010/0318837	12/2009	Murphy et al.	N/A	N/A
2010/0324855	12/2009	Parker	N/A	N/A
2010/0332008	12/2009	Knipfer et al.	N/A	N/A
2011/0004446	12/2010	Dorn et al.	N/A	N/A
2011/0016058	12/2010	Pinchuk	N/A	N/A
2011/0035253	12/2010	Mason et al.	N/A	N/A
2011/0040540	12/2010	Yoon	N/A	N/A
2011/0047230	12/2010	McGee	N/A	N/A
2011/0078300	12/2010	Grelewicz et al.	N/A	N/A
2011/0093308	12/2010	Majeed	N/A	N/A
2011/0161378	12/2010	Williamson	N/A	N/A

2011/0173127	12/2010	Ho et al.	N/A	N/A
2011/0257766	12/2010	Sundaram et al.	N/A	N/A
2011/0265020	12/2010	Fields et al.	N/A	N/A
2011/0276498	12/2010	Madhok	N/A	N/A
2011/0288667	12/2010	Noda et al.	N/A	N/A
2011/0295634	12/2010	Bhamidipaty et al.	N/A	N/A
2012/0005242	12/2011	Feng et al.	N/A	N/A
2012/0022700	12/2011	Dress et al.	N/A	N/A
2012/0054246	12/2011	Fischer	N/A	N/A
2012/0072597	12/2011	Teather et al.	N/A	N/A
2012/0079461	12/2011	Copass et al.	N/A	N/A
2012/0083906	12/2011	Weatherhead et al.	N/A	N/A
2012/0084400	12/2011	Almadi et al.	N/A	N/A
2012/0089920	12/2011	Eick	N/A	N/A
2012/0095808	12/2011	Kattapuram et al.	N/A	N/A
2012/0101801	12/2011	Van Dorsselaer	N/A	N/A
2012/0123614	12/2011	Laws	N/A	N/A
2012/0143374	12/2011	Mistry et al.	N/A	N/A
2012/0147894	12/2011	Mulligan et al.	N/A	N/A
2012/0191439	12/2011	Meagher et al.	N/A	N/A
2012/0197911	12/2011	Banka et al.	N/A	N/A
2012/0232876	12/2011	Misra	N/A	N/A
2012/0257544	12/2011	Schein et al.	N/A	N/A
2012/0262069	12/2011	Reed	N/A	N/A
2012/0290104	12/2011	Holt et al.	N/A	N/A
2012/0290266	12/2011	Jain et al.	N/A	N/A
2012/0297249	12/2011	Yang et al.	N/A	N/A
2012/0304007	12/2011	Hanks et al.	N/A	N/A
2012/0306620	12/2011	Karaffa et al.	N/A	N/A
2012/0311387	12/2011	Santhosh et al.	N/A	N/A
2013/0004281	12/2012	Anders et al.	N/A	N/A
2013/0012220	12/2012	Waris et al.	N/A	N/A
2013/0018696	12/2012	Meldrum	N/A	N/A
2013/0024542	12/2012	Keller et al.	N/A	N/A
2013/0031158	12/2012	Salsburg	N/A	N/A
2013/0036198	12/2012	Galm et al.	N/A	N/A
2013/0041705	12/2012	Hampapur et al.	N/A	N/A
2013/0097563	12/2012	Pacheco Rodrigues Velho et al.	N/A	N/A
2013/0097710	12/2012	Basavapatna et al.	N/A	N/A
2013/0104236	12/2012	Ray et al.	N/A	N/A
2013/0107772	12/2012	Splitz et al.	N/A	N/A
2013/0111019	12/2012	Tjew et al.	N/A	N/A
2013/0111034	12/2012	Upadhya	N/A	N/A
2013/0117064	12/2012	Sadeghi et al.	N/A	N/A
2013/0117806	12/2012	Parthasarathy et al.	N/A	N/A
2013/0125233	12/2012	Bush et al.	N/A	N/A
2013/0138812	12/2012	Assuncao et al.	N/A	N/A
2013/0138818	12/2012	Wolf	N/A	N/A
2013/0145033	12/2012	Polla et al.	N/A	N/A

2013/0159500	12/2012	Reus et al.	N/A	N/A
2013/0182107	12/2012	Anderson	N/A	N/A
2013/0191106	12/2012	Kephart et al.	N/A	N/A
2013/0204982	12/2012	Kim et al.	N/A	N/A
2013/0211546	12/2012	Lawson et al.	N/A	N/A
2013/0211547	12/2012	Buchdunger et al.	N/A	N/A
2013/0211555	12/2012	Lawson et al.	N/A	N/A
2013/0211559	12/2012	Lawson et al.	N/A	N/A
2013/0211870	12/2012	Lawson et al.	N/A	N/A
2013/0212420	12/2012	Lawson et al.	N/A	N/A
2013/0212521	12/2012	Fedoseyeva et al.	N/A	N/A
2013/0218971	12/2012	Sasaki et al.	N/A	N/A
2013/0237204	12/2012	Buck et al.	N/A	N/A
2013/0257627	12/2012	Rafael	N/A	N/A
2013/0262654	12/2012	Masli et al.	N/A	N/A
2013/0274899	12/2012	Hamzaoui et al.	N/A	N/A
2013/0282150	12/2012	Panther et al.	N/A	N/A
2013/0283265	12/2012	Acharya et al.	N/A	N/A
2013/0304237	12/2012	Schroeder et al.	N/A	N/A
2013/0311827	12/2012	Drory et al.	N/A	N/A
2013/0325545	12/2012	Mordvinova et al.	N/A	N/A
2013/0347003	12/2012	Whitmore	N/A	N/A
2014/0013100	12/2013	Menzel et al.	N/A	N/A
2014/0046618	12/2013	Arunachalam et al.	N/A	N/A
2014/0046977	12/2013	Gopalakrishnan et al.	N/A	N/A
2014/0047107	12/2013	Maturana et al.	N/A	N/A
2014/0052499	12/2013	Wagner et al.	N/A	N/A
2014/0059056	12/2013	Chaney et al.	N/A	N/A
2014/0067360	12/2013	Bhamidipaty et al.	N/A	N/A
2014/0081691	12/2013	Wendell	N/A	N/A
2014/0095231	12/2013	Cherusseri et al.	N/A	N/A
2014/0095654	12/2013	Finnerty et al.	N/A	N/A
2014/0116341	12/2013	Kopic et al.	N/A	N/A
2014/0121789	12/2013	Brandes et al.	N/A	N/A
2014/0137257	12/2013	Martinez et al.	N/A	N/A
2014/0156032	12/2013	Jenkins et al.	N/A	N/A
2014/0156584	12/2013	Motukuri et al.	N/A	N/A
2014/0215487	12/2013	Cherkasova et al.	N/A	N/A
2014/0250153	12/2013	Nixon et al.	N/A	N/A
2014/0250337	12/2013	Yamaji et al.	N/A	N/A
2014/0278738	12/2013	Feit et al.	N/A	N/A
2014/0279201	12/2013	Iyoob et al.	N/A	N/A
2014/0279641	12/2013	Singh et al.	N/A	N/A
2014/0279948	12/2013	Mahate et al.	N/A	N/A
2014/0282015	12/2013	Nixon et al.	N/A	N/A
2014/0282257	12/2013	Nixon et al.	N/A	N/A
2014/0297354	12/2013	Kogiso et al.	N/A	N/A
2014/0306533	12/2013	Paquin et al.	N/A	N/A
2014/0316794	12/2013	Goll et al.	N/A	N/A

2014/0335480	12/2013	Asenjo et al.	N/A	N/A
2014/0336785	12/2013	Asenjo et al.	N/A	N/A
2014/0336786	12/2013	Asenjo et al.	N/A	N/A
2014/0336791	12/2013	Asenjo et al.	N/A	N/A
2014/0336795	12/2013	Asenjo et al.	N/A	N/A
2014/0337000	12/2013	Asenjo et al.	N/A	N/A
2014/0337086	12/2013	Asenjo et al.	N/A	N/A
2014/0358606	12/2013	Hull	N/A	N/A
2014/0372347	12/2013	Cohen et al.	N/A	N/A
2015/0012763	12/2014	Cohen et al.	N/A	N/A
2015/0019191	12/2014	Maturana et al.	N/A	N/A
2015/0032242	12/2014	Schouwenburg et al.	N/A	N/A
2015/0032886	12/2014	Wang	N/A	N/A
2015/0048952	12/2014	Murphy	N/A	N/A
2015/0235161	12/2014	Azar et al.	N/A	N/A
2015/0278407	12/2014	Vennelakanti et al.	N/A	N/A
2015/0304193	12/2014	Ishii et al.	N/A	N/A
2015/0378356	12/2014	Hefeeda et al.	N/A	N/A
2016/0154693	12/2015	Uhde et al.	N/A	N/A
2016/0188769	12/2015	Aylott et al.	N/A	N/A
2016/0217378	12/2015	Bellala et al.	N/A	N/A
2016/0217410	12/2015	Santos et al.	N/A	N/A
2017/0019483	12/2016	Maturana et al.	N/A	N/A
2017/0236391	12/2016	Palmeri	N/A	N/A
2018/0157995	12/2017	O'Malley	N/A	N/A
2018/0205803	12/2017	Asenjo et al.	N/A	N/A
2019/0130057	12/2018	Asenjo	N/A	G06Q 10/06
2021/0157312	12/2020	Cella	N/A	G01M 13/045
2021/0225201	12/2020	Asenjo	N/A	G09B 19/18
2021/0342836	12/2020	Cella	N/A	H04L 9/3239
2022/0156435	12/2021	Asenjo	703/2	G06F 30/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1232553	12/1998	CN	N/A
1255208	12/1999	CN	N/A
1529837	12/2003	CN	N/A
1605958	12/2004	CN	N/A
1690685	12/2004	CN	N/A
1833424	12/2005	CN	N/A
101086760	12/2006	CN	N/A
101091195	12/2006	CN	N/A
100362442	12/2007	CN	N/A
101114160	12/2007	CN	N/A
101276209	12/2007	CN	N/A
101326471	12/2007	CN	N/A
101536002	12/2008	CN	N/A
101553763	12/2008	CN	N/A

201444256	12/2009	CN	N/A
101739007	12/2009	CN	N/A
101776862	12/2009	CN	N/A
102262401	12/2010	CN	N/A
102435870	12/2011	CN	N/A
102449567	12/2011	CN	N/A
102483837	12/2011	CN	N/A
102640475	12/2011	CN	N/A
102830666	12/2011	CN	N/A
102927937	12/2012	CN	N/A
103019102	12/2012	CN	N/A
103180866	12/2012	CN	N/A
103403753	12/2012	CN	N/A
104142629	12/2013	CN	N/A
104142630	12/2013	CN	N/A
104142662	12/2013	CN	N/A
104142664	12/2013	CN	N/A
104142679	12/2013	CN	N/A
104144204	12/2013	CN	N/A
19834456	12/1999	DE	N/A
19880479	12/2008	DE	N/A
102014102844	12/2013	DE	N/A
1209558	12/2001	EP	N/A
1491977	12/2003	EP	N/A
1531373	12/2004	EP	N/A
1686442	12/2005	EP	N/A
1 868 152	12/2006	EP	N/A
1933214	12/2007	EP	N/A
2189900	12/2009	EP	N/A
2293164	12/2010	EP	N/A
2453326	12/2011	EP	N/A
2469466	12/2011	EP	N/A
2 509 042	12/2011	EP	N/A
2660667	12/2012	EP	N/A
2704401	12/2013	EP	N/A
2778816	12/2013	EP	N/A
2790101	12/2013	EP	N/A
2801935	12/2013	EP	N/A
2801936	12/2013	EP	N/A
2801938	12/2013	EP	N/A
2801940	12/2013	EP	N/A
2801941	12/2013	EP	N/A
3037901	12/2015	EP	N/A
3070550	12/2017	EP	N/A
2001242931	12/2000	JP	N/A
0111586	12/2000	WO	N/A
0169329	12/2000	WO	N/A
0217131	12/2001	WO	N/A
02/057856	12/2001	WO	N/A
03/007097	12/2002	WO	N/A

03058506	12/2002	WO	N/A
2008133715	12/2007	WO	N/A
2009046095	12/2008	WO	N/A
2011050482	12/2010	WO	N/A
2013007866	12/2012	WO	N/A
2014/090310	12/2013	WO	N/A
2016001718	12/2015	WO	N/A

OTHER PUBLICATIONS

Non-Final Office Action received for U.S. Appl. No. 10/234,504 dated Oct. 18, 2006, 15 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/234,504 dated Feb. 7, 2007, 12 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 10/234,504 dated May 1, 2007, 12 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/162,314 dated Dec. 15, 2005, 17 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/162,314 dated Jun. 5, 2006, 23 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/162,314 dated Nov. 16, 2006, 20 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/162,314 dated Apr. 30, 2007, 35 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/162,314 dated Oct. 25, 2007, 28 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/162,314 dated May 5, 2008, 31 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/161,848 dated Nov. 15, 2005, 15 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/161,848 dated Mar. 27, 2006, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/161,848 dated Sep. 5, 2006, 15 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/161,848 dated Feb. 23, 2007, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/161,848 dated May 7, 2007, 14 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/161,848 dated Oct. 17, 2007, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/161,848 dated Feb. 7, 2008, 14 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 10/161,848 dated Sep. 9, 2008, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 12/410,632 dated Feb. 1, 2011, 56 pages.
cited by applicant

Final Office Action received for U.S. Appl. No. 12/410,632 dated May 17, 2011, 17 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 12/410,632 dated Sep. 2, 2011, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/298,366 dated Apr. 20, 2006, 13 pages.

cited by applicant

Final Office Action received for U.S. Appl. No. 10/298,366 dated Sep. 29, 2006, 16 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/298,366 dated Jan. 31, 2007, 12 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 10/298,366 dated Jul. 18, 2007, 14 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/298,366 dated Dec. 17, 2007, 10 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/298,366 dated Jun. 11, 2008, 24 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 10/298,366 dated Nov. 18, 2008, 20 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 10/298,366 dated Feb. 2, 2009, 23 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 13/615,195 dated Aug. 19, 2014, 24 pages. cited by applicant

Communication pursuant to Article 96(2) EPC for EP Application Serial No. 03026339.6 dated Apr. 6, 2006, 6 pages. cited by applicant

Communication pursuant to Article 96(2) EPC for EP Application Serial No. 13166670.3 dated Dec. 14, 2018, 4 pages. cited by applicant

Chinese Third Office Action for Chinese Application No. 201410196114.8 dated Apr. 12, 2017, 25 pages. cited by applicant

Chinese Fourth Office Action for Chinese Application No. 201410196114.8 dated Aug. 15, 2017, 24 pages. cited by applicant

Chinese Second Office Action for Chinese Application No. 201410196198.5 dated Dec. 21, 2016, 10 pages. cited by applicant

Chinese Third Office Action for Chinese Application No. 201410196198.5 dated Mar. 28, 2017, 10 pages. cited by applicant

Chinese Second Office Action for Chinese Application No. 201410196525.7 dated Dec. 21, 2016, 8 pages. cited by applicant

Chinese Second Office Action for Chinese Application No. 201410196775.0 dated Dec. 7, 2016, 8 pages. cited by applicant

Chinese Third Office Action for CN Application Serial No. 201410196150.4, dated Nov. 29, 2017, 10 pages (with English Translation). cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 14167511.6 dated Jan. 23, 2019, 7 pages. cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 14167703.9 dated Jan. 23, 2019, 6 pages. cited by applicant

Anonymous: "Hash function—Wikipedia", Wikipedia, Apr. 19, 2009,

URL:https://en.wikipedia.org/w/index.php?title=Hash_function&oldid=284890279. cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 16160611.6 dated Apr. 5, 2017, 5 pages. cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 16160611.6 dated May 10, 2017, 5 pages. cited by applicant

Second Office Action received for Chinese Patent Application Serial No. 201610151417.7 dated Jan. 22, 2019, 7 pages. cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 16160604.1 dated Jun. 13, 2017, 6 pages. cited by applicant

Summons to attend oral proceedings pursuant to Rule 115(1) EPC received for EP Patent Application Serial No. 14167706.2 dated Dec. 13, 2018, 65 pages. cited by applicant

Second Office Action received for Chinese Patent Application Serial No. 201410196150.4 dated Aug. 3, 2017, 10 pages. cited by applicant

Extended European Search Report received for European Application No. 16160610.8 dated Sep. 8, 2016, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 13/725,543 dated Oct. 9, 2014, 10 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/725,543 dated May 20, 2015, 15 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/615,195 dated Jan. 20, 2015, 22 pages. cited by applicant

Chinese First Office Action for Chinese Application No. 20170339669.7 dated Dec. 11, 2018, 25 pages (Including English Translation). cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/621,206 dated Mar. 22, 2019, 118 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,345 dated May 13, 2019, 78 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,365 dated Jun. 3, 2019, 70 pages. cited by applicant

Third Office Action received for Chinese Patent Application Serial No. 201610149635.7 dated Apr. 26, 2019, 23 pages (including English Translation). cited by applicant

Notice of opposition received for European Patent Application Serial No. 16160611.6 dated Apr. 11, 2019, 789 pages. cited by applicant

Wen et al., "Current Trends and Perspectives in Wireless Virtualization", 2013 International Conference on Selected Topics in Mobile and Wireless Networking (MoWNeT), 2013, 6 pages. cited by applicant

Wang et al., "The Research of Chemical Plant Monitoring Base on the Internet of Things and 3D Visualization Technology", Proceeding of the IEEE International Conference on Information and Automation, Aug. 2013, 5 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/714,333 dated Jul. 17, 2019, 113 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/621,206 dated Aug. 19, 2019, 52 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,394 dated Aug. 19, 2019, 70 pages. cited by applicant

First Office Action received for Chinese Patent Application Serial No. 201710778822.6 dated Jun. 24, 2019, 29 pages (Including English Translation). cited by applicant

Second Office Action received for Chinese Patent Application Serial No. 201710339669.7 dated Jul. 2, 2019, 20 pages (Including English Translation). cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/970,932 dated Nov. 14, 2019, 122 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/714,333 dated Oct. 25, 2019, 36 pages. cited by applicant

Second Office Action received for Chinese Patent Application Serial No. 201710778822.6 dated Sep. 20, 2019, 5 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,345 dated Nov. 26, 2019, 48 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,365 dated Nov. 29, 2019, 48 pages. cited by applicant

Supplementary Search Report received for Chinese Patent Application Serial No. 201710339669.7 dated Sep. 18, 2019, 2 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,394 dated Feb. 20, 2020, 67 pages. cited by applicant

Third Office Action received for Chinese Patent Application Serial No. 201710778822.6 dated Mar. 3, 2020, 43 pages (Including English Translation). cited by applicant

Communication pursuant to Article 94(3) EPC received for EP Patent Application Serial No. 14167627.0 dated Jan. 23, 2020, 6 pages. cited by applicant

Summons to attend oral proceedings pursuant to Rule 115(1) EPC received for EP Patent Application Serial No. 14167703.9 dated Feb. 6, 2020, 8 pages. cited by applicant

Notification of Grant of Patent for Invention received for Chinese Patent Application Serial No. 201710339669.7 dated Dec. 31, 2019, 7 pages (Including English Translation). cited by applicant

Summons to attend oral proceedings pursuant to Rule 115(1) EPC received for EP Patent Application Serial No. 16160611.6 dated Dec. 19, 2019, 26 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/129,116 dated Apr. 1, 2020, 142 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/714,333 dated Apr. 15, 2020, 44 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/970,932 dated Apr. 13, 2020, 37 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,345 dated May 14, 2020, 83 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for EP Patent Application Serial No. 16160602.5 dated May 19, 2020, 07 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for EP Patent Application Serial No. 16160610.8 dated May 27, 2020, 08 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/129,116 dated Jul. 2, 2020, 58 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/714,333 dated Jul. 22, 2020, 40 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,365 dated Jul. 13, 2020, 72 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,394 dated Aug. 5, 2020, 59 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/714,333 dated Dec. 17, 2020, 59 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,345 dated Nov. 4, 2020, 62 pages. cited by applicant

Summons to attend oral proceedings pursuant to Rule 115(1) EPC received for EP Patent Application Serial No. 16160611.6 dated Oct. 30, 2020, 05 pages. cited by applicant

Notification of Reexamination received for Chinese Application No. 201610149635.7, Mailed on Nov. 5, 2020, 17 pages. cited by applicant

Notification of Reexamination received for Chinese Application No. 201610149668.1, Mailed on Oct. 20, 2020, 3 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,365 dated Jan. 21, 2021, 96 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/129,116 dated Nov. 16, 2020, 51 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/658,394 dated Feb. 9, 2021, 92 pages. cited by applicant

Advisory Office Action received for U.S. Appl. No. 14/658,365 dated Mar. 25, 2021, 09 pages. cited by applicant

Summons to attend oral proceedings pursuant to Rule 115(1) EPC received for European Patent Application Serial No. 14167708.8 dated Mar. 18, 2021, 09 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/234,039 dated May 13, 2021, 149 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/900,022 dated May 27, 2021, 146 pages. cited by applicant

Communication Pursuant to Rules 94(3) EPC received for EP Patent Application Serial No. 16160602.5 dated May 11, 2021, 07 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,345 dated Jun. 24, 2021, 73 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for EP Patent Application Serial No. 16160602.5 dated Jul. 20, 2023, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/812,894 dated Sep. 21, 2023, 189 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/648,098 dated Sep. 27, 2023, 168 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/344,118 dated Sep. 6, 2023, 12 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,970 dated Apr. 12, 2017, 59 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,394 dated Apr. 21, 2017, 97 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/388,260 dated Apr. 24, 2017, 101 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,345 dated Mar. 17, 2017, 95 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,327 dated May 1, 2017, 99 pages. cited by applicant

Givvehchi et al., "Control-as-a-Service from the Cloud: A Case Study for using Virtualized PLCs," 2014 10th IEEE Workshop on Factory Communication Systems (WFCS 2014), May 5, 2014 IEEE, 4 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/088,011 dated May 17, 2017, 10 Pages. cited by applicant

Rouse et al. "Definition Industrial Control System (ICS," [whatis.techtarget.com](http://whatis.techtarget.com/definition/industrial-control-system-ICS), ed. Mar. 2016 (accessed from <<<http://whatis.techtarget.com/definition/industrial-control-system-ICS>>> on Jan. 11, 2017). cited by applicant

Examiner Answer to Appeal Brief for U.S. Appl. No. 14/087,977, dated Feb. 1, 2017, 12 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for European Application Serial No. 16160604.1-1802 dated May 17, 2017, 6 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,365 dated Sep. 8, 2017, 59 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/087,821 dated Sep. 7, 2017, 63 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,730 dated Aug. 18, 2017, 72 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/214,583 dated Aug. 28, 2017, 80 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,345 dated Sep. 25, 2017, 52 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/388,260 dated Oct. 18, 2017, 76 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/206,744 dated Nov. 6, 2017, 48 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,327 dated Oct. 30, 2017, 48 pages. cited by applicant

Final Office Action for U.S. Appl. No. 14/658,394 dated Nov. 16, 2017, 49 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/490,076 dated Dec. 20, 2017, 37 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/278,139 dated Jan. 11, 2018, 103 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,821 dated Dec. 14, 2017, 37 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/088,011 dated Nov. 22, 2017, 77 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/087,970 dated Feb. 12, 2018, 69 pages. cited by applicant

Chinese Fifth Office Action received for Chinese Application Serial No. 201410196114.8, Mailed on Dec. 13, 2017, 26 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/143,733 dated Mar. 8, 2018, 141 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/490,076 dated Apr. 2, 2018, 23 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,327 dated Apr. 10, 2018, 43 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,345 dated Mar. 14, 2018, 56 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,365, dated Apr. 5, 2018, 64 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,394, dated Apr. 6, 2018, 40 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/143,733, dated Jun. 18, 2018, 76 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 15/599,921, dated Jun. 29, 2018, 75 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,970, dated Aug. 1, 2018, 68 pages. cited by applicant

Wikipedia; "PID Controller"; Jul. 20, 2018; https://en.wikipedia.org/wiki/PID_controller (Year: 2018). cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 14167714.6 dated Aug. 3, 2018, 5 pages. cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 14167708.8 dated Aug. 3, 2018, 5 pages. cited by applicant

Communication pursuant to Article 94(3) EPC for EP Application Serial No. 14167712.0 dated Aug. 3, 2018, 5 pages. cited by applicant

Search Report received for Chinese Application Serial No. 201610149668.1 dated Apr. 2, 2018, 1 page. cited by applicant

Search Report received for Chinese Application Serial No. 201610149635.7 dated Apr. 2, 2018, 1 page. cited by applicant

Chinese First Office Action received for Chinese Patent Application Serial No. 201610151380.8, Mailed on Jul. 17, 2018, 65 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,345 dated Sep. 13, 2018, 49 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,365 dated Oct. 16, 2018, 42 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/923,127 dated Nov. 21, 2018, 85 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,327 dated Nov. 1, 2018, 58 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,394 dated Nov. 1, 2018, 51 pages. cited by applicant

Chinese Second Office Action received for Chinese Application Serial No. 201610149668.1, Mailed on Oct. 24, 2018, 18 pages. cited by applicant

Chinese Second Office Action received for Chinese Application Serial No. 201610149635.7, Mailed on Oct. 24, 2018, 24 pages. cited by applicant

Chinese First Office Action received for Chinese Application Serial No. 201610151417.7, Mailed on Sep. 18, 2018, 28 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 14/087,730 dated Mar. 11, 2016, 81 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/087,821 dated Mar. 2, 2016, 86 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/087,977 dated Mar. 17, 2016, 83 pages. cited by applicant

'Recursion Software, “SCADA-Aware Mobile”, Frisco, TX, Aug. 29, 2012 (accessed from <<<http://www.emsenergyautomation.com/brochures/scada.pdf> on Feb. 11, 2016)”. cited by applicant

“Ars Technica, ““Windows 7 themes: how to unlock them or create your own””, Nov. 12, 2009 (accessed from <http://arstechnica.com/information-technology/2009/11/unlock-hidden-windows-7-themes/> on Mar. 8, 2016)”. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/088,014 dated Mar. 22, 2016, 98 pages. cited by applicant

“Microsoft,” “Sharing Outlook 2010 Contact\Notes\Field?”, microsoft.com, Jun. 23, 2011 (accessed on Mar. 11, 2016 from http://answers.microsoft.com/en-us/office/forum/office_2010-outlook/sharing-outlook-2010-contactnotes-field/c7e74273-ff60-4da3-a3aa-ccb6cadcd25e?auth=1). cited by applicant

Notice of Allowance received for U.S. Appl. No. 13/608,850 dated Apr. 12, 2016, 37 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/087,873 dated Apr. 18, 2016, 26 pages. cited by applicant

Chinese First Office Action received for Chinese Application No. 201410196198.5, Mailed on Mar. 29, 2016, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/088,011 dated May 12, 2016, 96 pages. cited by applicant

Chinese First Office Action received for Chinese Application No. 201410198289.2, Mailed on Apr. 5, 2016, 18 pages. cited by applicant

Chinese First Office Action received for Chinese Application No. 201410196905.0, Mailed on Apr. 5, 2016, 20 pages. cited by applicant

Chinese First Office Action received for Chinese Application No. 201410196127.5, Mailed on Apr. 7, 2016, 13 pages. cited by applicant

Chinese Office Action for Chinese Application No. 201410196114.8 dated Apr. 25, 2016, 20 pages. cited by applicant

Chinese First Office Action received for Chinese Application No. 201410196775.0, Mailed on May 5, 2016, 14 pages. cited by applicant

Chinese First Office Action received for Chinese Application No. 201410196525.7, Mailed on May 5, 2016, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 13/615,195, dated Jun. 21, 2016, 29 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/725,543, dated Jun. 17, 2016, 19 pages. cited by applicant

Non-final Office Action received for U.S. Appl. No. 14/087,970 dated Jun. 17, 2016, 36 pages. cited by applicant

Chinese First Office Action received for Chinese Application Serial No. 201410195780.X, Mailed on May 26, 2016, 16 pages (Including English Translation). cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,977 dated Jul. 13, 2016, 59 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/088,014 dated Jul. 15, 2016, 65 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/087,922 dated Jul. 19, 2016, 120 pages. cited by applicant

Extended European Search Report received for European Application No. 16160604.1 dated Aug. 17, 2016, 9 pages. cited by applicant

Extended European Search Report received for European Application No. 16160611.6 dated Aug. 24, 2016, 10 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,730 dated Aug. 24, 2016, 113 pages. cited by applicant

Extended European Search Report received for European Application No. 16160602.5 dated Sep. 2, 2016, 9 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/087,835 dated Sep. 23, 2016, 82 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,821 dated Sep. 9, 2016, 97 pages. cited by applicant

Extended European Search Report received for European Application No. 13166670.3 dated Jun. 14, 2016, 10 pages. cited by applicant

"Cloud Computing," Whatis.com, Oct. 27, 2009,
http://searchcloudcomputing.techtarget.com/sDefinition/0,,sid201_gci1287881,00.html, 2 pages. cited by applicant

Mell, P., et al., "The NIST Definition of Cloud Computing," Oct. 7, 2009,
<http://csrc.nist.gov/groups/SNS/cloud/computing/index.html>, 2 pages. cited by applicant

European Office Action for EP Patent Application Serial No. 16160611.6, dated Sep. 26, 2016, 2 pages. cited by applicant

European Office Action for EP Patent Application Serial No. 13166670.3, dated Jul. 18, 2016, 2 pages. cited by applicant

European Office Action for EP Patent Application Serial No. 16160604.1, dated Sep. 26, 2016, 2 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/615,195 dated Oct. 21, 2016, 44 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/088,011 dated Nov. 1, 2016, 79 pages. cited by

applicant

Communication pursuant to Rule 69 EPC received for European Application Serial No. 16160610.8 dated Oct. 17, 2016, 2 pages. cited by applicant

Communication pursuant to Rule 69 EPC received for European Application Serial No. 16160602.5 dated Oct. 10, 2016, 2 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/088,014, dated Nov. 17, 2016, 61 pages. cited by applicant

Chinese second Office Action received for Chinese Application Serial No. 201410196114.8, Mailed on Nov. 9, 2016, 19 pages. cited by applicant

Chinese Second Office Action received for Chinese Application Serial No. 201410196905.0, Mailed on Nov. 18, 2016, 6 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/087,922, dated Nov. 25, 2016, 65 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 14/087,730, dated Feb. 9, 2017, 78 pages. cited by applicant

Chinese Second Office Action received for Chinese Application Serial No. 201410198289.2, Mailed on Dec. 15, 2016, 21 pages. cited by applicant

Chinese Second Office Action received for Chinese Application Serial No. 201410196127.5 Mailed on Nov. 30, 2016, 13 pages. cited by applicant

Chinese Second Office Action received for Chinese Application Serial No. 201410195780.X, Mailed on Feb. 3, 2017, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,365 dated Mar. 23, 2017, 100 pages. cited by applicant

Chinese First Office Action received for Chinese Application Serial No. 201410196150.4, Mailed on Mar. 2, 2017, 37 pages (with English Translation). cited by applicant

Communication pursuant to Article 94(3) EPC received for European Application No. 14167707.0-1955 dated Sep. 22, 2015, 9 pages. cited by applicant

Extended European search report received for European Application No. 14167714.6 dated Aug. 11, 2014, 5 pages. cited by applicant

Extended European search report received for European Application No. 14167706.2 dated Aug. 11, 2014, 7 pages. cited by applicant

Extended European search report received for European Application No. 14167626.2 dated Aug. 11, 2014, 9 pages. cited by applicant

Extended European search report received for European Application No. 14167627.0 dated Aug. 11, 2014, 6 pages. cited by applicant

Extended European search report received for European Application No. 14167703.9 dated Aug. 11, 2014, 7 pages. cited by applicant

Extended European search report received for European Application No. 14167707.0 dated Aug. 11, 2014, 7 pages. cited by applicant

Extended European search report received for European Application No. 14167708.8 dated Aug. 11, 2014, 5 pages. cited by applicant

Extended European search report received for European Application No. 14167712.0 dated Aug. 11, 2014, 5 pages. cited by applicant

Extended European search report received for European Application No. 14167511.6 dated Aug. 11, 2014, 6 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/162,315 dated Dec. 27, 2004, 10 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 10/162,315 dated Jun. 15, 2005, 11 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 10/162,315 dated Sep. 9, 2005, 22 pages.

cited by applicant
Vasudevan Venu., “A Web Services Primer”,
<http://webservices.XML.com/pub/a/ws/2001/04/04/webservices/index.html>, XML.com, Apr. 4, 2001, 10 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 10/162,315 dated Mar. 6, 2006, 10 pages. cited by applicant
W3C, “Web Services Description Language (WSDL) 1.1”, <http://www.w3.org/TR/wsd1>, Mar. 15, 2001, 36 pages. cited by applicant
European Search Report dated Apr. 6, 2004 for European Patent Application Serial No. 03026339, 3 Pages. cited by applicant
Compuquest, Inc., SPM-IM-Instant Messaging Client for SpreadMsg Wireless Messaging Software, <http://www.compuquestinc.com/spmim.html>, Aug. 13, 2002, 4 pages. cited by applicant
Compuquest, Inc., SpreadMsg Lite—Data Capture, Scanning, Extraction & Rule Based Instant Messaging Software, <http://web.archive.org/web/20020813080848/http://www.compuquestinc.com/spmsgl.html>, retrieved Jul. 21, 2006, 6 pages. cited by applicant
International Business Machines Corporation, Cross platform instant messaging using web services, Research Disclosure, Kenneth Mason Publications, Hampshire, GB, vol. 458, No. 156, Jun. 2002. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 13/725,578 dated Jun. 18, 2014, 13 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 13/615,195 dated Aug. 19, 2014, 22 pages. cited by applicant
Final Office Action received for U.S. Appl. No. 13/725,578 dated Dec. 12, 2014, 24 pages. cited by applicant
Third Party Submission under 37 CFR 1.290 received for U.S. Appl. No. 14/087,873 dated Nov. 21, 2014, 26 pages. cited by applicant
Non-final Office Action received for U.S. Appl. No. 13/608,821 dated Jun. 1, 2015, 44 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 13/608,850 dated Jun. 1, 2015, 38 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 13/677,060 dated Apr. 24, 2015, 54 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 13/725,619, dated Jul. 17, 2015, 45 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 13/725,660 dated Aug. 18, 2015, 131 pages. cited by applicant
Colombo, A.W., et al., “Factory of the Future: A Service-Oriented System of Modular, Dynamic Reconfigurable and Collaborative Systems,” Artificial Intelligence Techniques for Networked Manufacturing Enterprises Management, Springer Series in Advanced Manufacturing 2010, pp. 459-481. cited by applicant
Colombo et al., “Towards the Factory of the Future: A Service-Oriented Cross-layer Infrastructure,” ICT Shaping the World: A Scientific View, 2009, pp. 65-81. cited by applicant
Notice of Allowance received for U.S. Appl. No. 13/725,578, dated Apr. 24, 2015, 23 pages. cited by applicant
Final Office Action received for U.S. Appl. No. 13/677,060, dated Oct. 20, 2015, 48 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 13/615,195, dated Sep. 21, 2015, 19 pages. cited by applicant
Final Office Action received for U.S. Appl. No. 13/725,660, dated Oct. 26, 2015, 79 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/087,873 dated Nov. 25, 2015, 57 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/725,619, dated Dec. 4, 2015, 21 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/608,821, dated Dec. 7, 2015, 39 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/615,195, dated Feb. 11, 2016, 19 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 13/725,543, dated Feb. 2, 2016, 15 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 13/725,660, dated Jan. 21, 2016, 72 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 13/608,850, dated Dec. 9, 2015, 25 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for European Application No. 14167706.2-1955 dated Nov. 24, 2015, 8 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for European U.S. Application No. 14167626.2-1955 dated Nov. 24, 2015, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 13/725,619, dated Mar. 31, 2016, 26 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 13/677,060 dated Mar. 10, 2016, 66 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 13/725,660 dated Feb. 3, 2016, 47 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/344,118 dated May 25, 2023, 108 pages. cited by applicant

Non Final Office Action received for U.S. Appl. No. 17/223,385 dated Apr. 29, 2022, 295 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/223,385 dated Jul. 21, 2022, 41pages. cited by applicant

Talha et al., Design for an irrigation and monitoring system of an automated dam, IMECS 2012 Vol II, Mar. 14-16, 2012, Hong Kong, 4 pgs. cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/658,365 dated Jul. 29, 2022, 86 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/658,365 dated Jan. 24, 2022, 38 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/344,118 dated Aug. 31, 2022, 164 pages. cited by applicant

Second Office Action received for Chinese Patent Application Serial No. 201810240055.8 dated Dec. 16, 2021, 8 pages. cited by applicant

Second Office Action received for Chinese Patent Application Serial No. 201610151380.8 dated Jan. 18, 2019, 8 pages. cited by applicant

Third Office Action received for Chinese Patent Application Serial No. 201610149668.1 dated Apr. 26, 2019, 18 pages. cited by applicant

Communication Pursuant to Rules 94(3) EPC received for EP Patent Application Serial No. 16160602.5 dated Sep. 23, 2022, 08 pages. cited by applicant

Communication Pursuant to Article 94(3) EPC received for EP Patent Application Serial No. 16160610.8 dated Sep. 23, 2022, 10 pages. cited by applicant

First Office Action received for Chinese Patent Application Serial No. 201710244682.4 dated Dec. 10, 2018, 14 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/223,385 dated Jan. 30, 2023, 37 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/344,118 dated Feb. 28, 2023, 83 pages. cited by applicant

Summons to attend oral proceedings pursuant to Rule 115(1) EPC received for European Patent Application Serial No. 13166670.3 dated Mar. 17, 2023, 39 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/812,894 dated Dec. 13, 2023, 95 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 14/658,365 dated Jul. 30, 2021, 108 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for European application No. 16160610.8 dated May 27, 2021, 9 pages. cited by applicant

First Office Action received for Chinese application No. 201810240055.8 dated Jun. 25, 2021, 22 pages (Including English Translation). cited by applicant

Search report received for Chinese application No. 201810240055.8 dated Jun. 17, 2021, 2 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/234,039 dated Oct. 25, 2021, 24 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 16/599,276 dated Dec. 3, 2021, 172 pages. cited by applicant

Communication pursuant to Article 94(3) EPC received for European Application Serial No. 11152520.0-1205 dated Nov. 8, 2021, 8 pages. cited by applicant

European Office Action for EP Patent Application Serial No. 14167708.8, dated Oct. 20, 2021, 10 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/900,022 dated Dec. 30, 2021, 66 pages. cited by applicant

U.S. Appl. No. 16/234,039, filed Dec. 27, 2018. cited by applicant

U.S. Appl. No. 15/599,921, filed May 19, 2017. cited by applicant

U.S. Appl. No. 14/087,835, filed Nov. 22, 2013. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/313,001, dated Nov. 8, 2024. cited by applicant

Primary Examiner: Vilakazi; Sizo B

Attorney, Agent or Firm: Amin, Turocy & Watson, LLP

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of, and claims priority to each of, U.S. patent application Ser. No. 16/234,039, filed Dec. 27, 2018, and entitled “USING CLOUD-BASED DATA FOR INDUSTRIAL SIMULATION,” which is a continuation of, and claims priority to each of, U.S. patent application Ser. No. 15/599,921 (now U.S. Pat. No. 10,204,191), filed May 19, 2017, and entitled “USING CLOUD-BASED DATA FOR INDUSTRIAL SIMULATION,” which is a continuation of, and claims priority to each of, U.S. patent application Ser. No. 14/087,835 (now U.S. Pat. No. 9,703,902), filed Nov. 22, 2013, and entitled “USING CLOUD-BASED DATA FOR INDUSTRIAL SIMULATION,” which claims priority to U.S. Provisional Patent Application Ser. No. 61/821,639, filed on May 9, 2013, and entitled “REMOTE SERVICES AND ASSET MANAGEMENT SYSTEMS AND METHODS,” the entireties of which applications are hereby incorporated herein by reference.

TECHNICAL FIELD

(1) The subject application relates generally to industrial automation, and, more particularly, to using cloud-based data to perform industrial simulation of industrial systems.

BACKGROUND

(2) Industrial controllers and their associated input/output (I/O) devices can be useful to the operation of modern automation systems. These industrial controllers can interact with field devices on the plant floor to control automated processes relating to such objectives as product manufacture, material handling, batch processing, supervisory control, and other such applications. Industrial controllers can store and execute user-defined control programs to effect decision-making in connection with the controlled process. Such programs can include, but are not limited to, ladder logic, sequential function charts, function block diagrams, structured text, or other such programming structures. In general, industrial controllers can read input data from sensors and metering devices that can provide discreet and telemetric data regarding one or more states of the controlled system, and can generate control outputs based on these inputs in accordance with the user-defined program.

(3) In addition to industrial controllers and their associated I/O devices, some industrial automation systems also can include low-level control systems, such as vision systems, barcode marking systems, variable frequency drives, industrial robots, and the like, which can perform local control of portions of the industrial process, or which can have their own localized control systems.

(4) The collection of industrial devices, industrial processes, other industrial assets, and network-related assets that makeup a given industrial automation system is typically in flux. As a result of system expansions, maintenance concerns, and device upgrades, industrial devices or other assets frequently can be added, removed, switched, replaced, reconfigured, or updated; industrial processes frequently can be modified; network-related components (e.g., network-related devices or software) frequently can be added, removed, switched, replaced, reconfigured, or updated; etc. Such modifications to the industrial automation system potentially can have positive or negative impacts on the performance of the industrial automation system.

(5) The above-described deficiencies of today's industrial control and business systems are merely intended to provide an overview of some of the problems of conventional systems, and are not intended to be exhaustive. Other problems with conventional systems and corresponding benefits of the various non-limiting embodiments described herein may become further apparent upon review of the following description.

SUMMARY

(6) The following presents a simplified summary in order to provide a basic understanding of some aspects described herein. This summary is not an extensive overview nor is intended to identify key/critical elements or to delineate the scope of the various aspects described herein. Its sole purpose is to present some concepts in a simplified form as a prelude to the more detailed description that is presented later.

(7) Various aspects and embodiments of the disclosed subject matter relate to the use of data analysis in a cloud platform to facilitate simulating operations of industrial automation systems. A cloud-based simulation generation service can collect industrial data (e.g., data relating to industrial automation systems) from industrial automation systems associated with one or more industrial customers for storage and analysis on a cloud platform. The service can employ a simulation generator component that can analyze the industrial data to facilitate generating a simulation model that can simulate or emulate an industrial automation system, including simulating or emulating industrial devices, industrial processes, other industrial assets, or network-related assets or devices, and their respective interrelationships (e.g., functional and/or communicative interrelationships) with each other. The simulation generator component also can analyze modification data (e.g., industrial data relating to a modification to the industrial automation system that is under

consideration) to facilitate generating a modified simulation model that can simulate or emulate the industrial automation system based on the modification.

(8) The simulation generator component can perform operation simulations using the simulation model and/or modified simulation model to facilitate determining the response of the simulation model and/or modified simulation model to a set of operation data (e.g., test data, historical operation data, etc.). The simulation generator component can determine or predict a response (e.g., real-world response) of the corresponding industrial automation system and/or corresponding modified automation system based on the responses (e.g., simulation response data) obtained from the operation simulations performed using the simulation model and/or modified simulation model. The simulation generator component can evaluate the results of the operation simulations to facilitate determining whether making the modification to the industrial automation system is appropriate, determining which, if any, modification or combination of modifications of a set of modification is appropriate, determining or predicting performance of a modified industrial automation system, determining compatibility of a modification or combination of modifications with an industrial automation system, or determining or predicting performance of the industrial automation system when processing a work order.

(9) To the accomplishment of the foregoing and related ends, certain illustrative aspects are described herein in connection with the following description and the annexed drawings. These aspects are indicative of various ways which can be practiced, all of which are intended to be covered herein. Other advantages and novel features may become apparent from the following detailed description when considered in conjunction with the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a block diagram of an example system (e.g., simulation generation system) that can facilitate generation of a simulation model of an industrial automation system associated with an industrial enterprise based on cloud-based data relating to the industrial enterprise, in accordance with various implementations and embodiments of the disclosed subject matter.

(2) FIG. 2 is a diagram of a high-level overview of an example industrial enterprise that can leverage cloud-based services, including simulation generation services, data collection services, and data storage services, in accordance with various aspects and embodiments of the disclosed subject matter.

(3) FIG. 3 presents a block diagram of an exemplary system (e.g., cloud-based, or partially cloud-based, simulation generation system) according to various implementations and embodiments of the disclosed subject matter.

(4) FIG. 4 illustrates a diagram of an example system that can facilitate generation of industrial simulations based at least in part collection of customer-specific industrial data by a cloud-based simulation generation system, in accordance with various aspects and embodiments of the disclosed subject matter.

(5) FIG. 5 illustrates a diagram of an example hierarchical relationship between these example data classes.

(6) FIG. 6 depicts a block diagram of an example system that can be configured to comprise an industrial device that can act or operate as a cloud proxy for other industrial devices of an industrial automation system to facilitate migrating industrial data to the cloud platform for classification and analysis by the simulation generation system, in accordance with various aspects and implementations of the disclosed subject matter.

(7) FIG. 7 illustrates a block diagram of an example system that can employ a firewall box that can serve as a cloud proxy for a set of industrial devices to facilitate migrating industrial data to the

cloud platform for classification and analysis by the simulation generation system, in accordance with various aspects and implementations of the disclosed subject matter.

(8) FIG. 8 illustrates a block diagram of an example device model according to various aspects and implementations of the disclosed subject matter.

(9) FIG. 9 presents a block diagram of an example system that can facilitate collection of data from devices and assets associated with respective industrial automation systems for storage in cloud-based data storage, in accordance with various aspects and implementations of the disclosed subject matter.

(10) FIG. 10 illustrates a block diagram of a cloud-based system that can employ a simulation generation system to facilitate simulation generation services associated with industrial automation systems, in accordance with various aspects and embodiments of the disclosed subject matter.

(11) FIG. 11 illustrates a flow diagram of an example method that can facilitate simulating an industrial automation system based on cloud-based data relating to an industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter.

(12) FIG. 12 depicts a flow diagram of an example method that can facilitate simulating an industrial automation system of a set of industrial automation systems based on cloud-based data relating to the set of industrial automation systems, in accordance with various aspects and embodiments of the disclosed subject matter.

(13) FIG. 13 presents a flow diagram of an example method that can facilitate simulating a modification to an industrial automation system of a set of industrial automation systems based on cloud-based data relating to the set of industrial automation systems, in accordance with various aspects and embodiments of the disclosed subject matter.

(14) FIG. 14 presents a flow diagram of an example method that can facilitate determining whether to modify an industrial automation system based on the modified simulation model associated with the industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter.

(15) FIG. 15 illustrates a flow diagram of another example method that can facilitate determining whether to modify an industrial automation system based on the modified simulation model associated with the industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter.

(16) FIG. 16 depicts a flow diagram of another example method that can facilitate determining whether to modify an industrial automation system, and if so, which modification to implement, based on respective modified simulation models associated with the industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter.

(17) FIG. 17 presents a flow diagram of another example method that can simulate production associated with a work order, based on a simulation model of an industrial automation system, to facilitate determining or predicting a response of the industrial automation system during production associated with the work order, in accordance with various aspects and embodiments of the disclosed subject matter.

(18) FIG. 18 is an example computing and/or operating environment.

(19) FIG. 19 is an example computing and/or networking environment.

DETAILED DESCRIPTION

(20) The subject disclosure is now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding thereof. It may be evident, however, that the subject disclosure can be practiced without these specific details. In other instances, well-known structures and devices are shown in block diagram form in order to facilitate a description thereof.

(21) Industrial automation systems can perform various processes to produce desired products or processed materials. An industrial control system can comprise various industrial devices,

industrial processes, other industrial assets, and network-related assets (e.g., communication network devices and software). The collection of industrial devices, industrial processes, other industrial assets, and network-related assets that makeup a given industrial automation system typically can be in flux. As a result of system expansions, maintenance concerns, and device upgrades, industrial devices or other assets frequently can be added, removed, switched, replaced, reconfigured, or updated; industrial processes frequently can be modified; network-related components (e.g., network-related devices or software) frequently can be added, removed, switched, replaced, reconfigured, or updated; etc. Such modifications to an industrial automation system potentially can have positive or negative impacts on the performance of the industrial automation system.

(22) To that end, presented are various systems, methods, and techniques of the disclosed subject matter that relate to the use of data analysis (e.g., big data analysis) in a cloud platform to facilitate simulating operations of industrial automation systems. A cloud-based simulation generation service (e.g., employing a collection component) can collect industrial data (e.g., data relating to industrial automation systems) from industrial automation systems associated with one or more industrial customers (e.g., industrial enterprises) for storage (e.g., in a cloud-based data store) and analysis on a cloud platform. The simulation generation service can employ a simulation generator component that can analyze the industrial data to facilitate generating a simulation model that can simulate or emulate an industrial automation system, including simulating or emulating industrial devices, industrial processes, other industrial assets, or network-related assets or devices (e.g., network communication or routing devices, network switches, network-related software or operating systems, etc.), and their respective interrelationships (e.g., functional and/or communicative interrelationships) with each other. When a modification to the industrial automation system is under consideration, the simulation generator component can analyze modification data (e.g., industrial data relating to a modification to the industrial automation system that is under consideration), along with the industrial data relating to the industrial automation system, to facilitate generating a modified simulation model that can simulate or emulate the industrial automation system, including simulation or emulation of the modification, based on the modification.

(23) The simulation generator component can perform operation simulations using the simulation model and/or modified simulation model to facilitate determining the response of the simulation model and/or modified simulation model to a set of operation data (e.g., test data, historical operation data, data representative of a work order, etc.). The simulation generator component can determine or predict a response (e.g., a real-world response) of the corresponding industrial automation system and/or corresponding modified automation system based on the responses (e.g., simulation response data) obtained from the operation simulations performed using the simulation model and/or modified simulation model. The simulation generator component can evaluate the results of the operation simulations to facilitate determining whether making the modification to the industrial automation system is appropriate, determining which, if any, modification or combination of modifications of a set of modification is appropriate (e.g., most preferred based on a set of defined operation criteria), determining or predicting performance of a modified industrial automation system, determining compatibility of a modification or combination of modifications with an industrial automation system, or determining or predicting performance of the industrial automation system when processing a work order, among other features or implementations disclosed herein.

(24) As used in this application, the terms “component,” “system,” “platform,” “layer,” “controller,” “terminal,” “station,” “node,” “interface” are intended to refer to a computer-related entity or an entity related to, or that is part of, an operational apparatus with one or more specific functionalities, wherein such entities can be either hardware, a combination of hardware and software, software, or software in execution. For example, a component can be, but is not limited to

being, a process running on a processor, a processor, a hard disk drive, multiple storage drives (of optical or magnetic storage medium) including affixed (e.g., screwed or bolted) or removably affixed solid-state storage drives; an object; an executable; a thread of execution; a computer-executable program, and/or a computer. By way of illustration, both an application running on a server and the server can be a component. One or more components can reside within a process and/or thread of execution, and a component can be localized on one computer and/or distributed between two or more computers. Also, components as described herein can execute from various computer readable storage media having various data structures stored thereon. The components may communicate via local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems via the signal). As another example, a component can be an apparatus with specific functionality provided by mechanical parts operated by electric or electronic circuitry which is operated by a software or a firmware application executed by a processor, wherein the processor can be internal or external to the apparatus and executes at least a part of the software or firmware application. As yet another example, a component can be an apparatus that provides specific functionality through electronic components without mechanical parts, the electronic components can include a processor therein to execute software or firmware that provides at least in part the functionality of the electronic components. As further yet another example, interface(s) can include input/output (I/O) components as well as associated processor, application, or Application Programming Interface (API) components. While the foregoing examples are directed to aspects of a component, the exemplified aspects or features also apply to a system, platform, interface, layer, controller, terminal, and the like.

(25) As used herein, the terms “to infer” and “inference” refer generally to the process of reasoning about or inferring states of the system, environment, and/or user from a set of observations as captured via events and/or data. Inference can be employed to identify a specific context or action, or can generate a probability distribution over states, for example. The inference can be probabilistic—that is, the computation of a probability distribution over states of interest based on a consideration of data and events. Inference can also refer to techniques employed for composing higher-level events from a set of events and/or data. Such inference results in the construction of new events or actions from a set of observed events and/or stored event data, whether or not the events are correlated in close temporal proximity, and whether the events and data come from one or several event and data sources.

(26) In addition, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise, or clear from the context, the phrase “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, the phrase “X employs A or B” is satisfied by any of the following instances: X employs A; X employs B; or X employs both A and B. In addition, the articles “a” and “an” as used in this application and the appended claims should generally be construed to mean “one or more” unless specified otherwise or clear from the context to be directed to a singular form.

(27) Furthermore, the term “set” as employed herein excludes the empty set; e.g., the set with no elements therein. Thus, a “set” in the subject disclosure includes one or more elements or entities. As an illustration, a set of controllers includes one or more controllers; a set of data resources includes one or more data resources; etc. Likewise, the term “group” as utilized herein refers to a collection of one or more entities; e.g., a group of nodes refers to one or more nodes.

(28) Various aspects or features will be presented in terms of systems that may include a number of devices, components, modules, and the like. It is to be understood and appreciated that the various systems may include additional devices, components, modules, etc. and/or may not include all of the devices, components, modules etc. discussed in connection with the figures. A combination of these approaches also can be used.

(29) FIG. 1 illustrates a block diagram of an example system **100** (e.g., simulation generation system) that can facilitate generation of a simulation model of an industrial automation system associated with an industrial enterprise based on cloud-based data relating to the industrial enterprise, in accordance with various implementations and embodiments of the disclosed subject matter. The system **100** can comprise a collection component **102** (e.g., data collection component) that can be associated with an industrial automation system **104** associated with an industrial enterprise. The industrial automation system **104** can comprise one or more industrial devices **106**, industrial processes **108**, or other industrial assets **110** that can be distributed throughout an industrial facility(ies) in accordance with a desired industrial-automation-system configuration. The industrial automation system **104** can perform industrial processes or other actions to facilitate producing desired products, processed materials, etc., as an output.

(30) The industrial automation system **104** also can include a network component **112** that can be associated with (e.g., interfaced with, communicatively connected to) the various industrial devices **106**, processes **108**, and/or other assets **110** of the industrial automation system **104** to facilitate communication of information (e.g., command or control information, status information, production information, etc.) between the various industrial devices **106**, processes **108**, and/or other assets **110** via the network component **112**. The network component **112** can be associated with (e.g., interfaced with, communicatively connected to) the collection component **102** to facilitate the communication of data between the industrial automation system **104** and the collection component **102**.

(31) The collection component **102** can monitor or track the operation of the industrial automation system **104**. The collection component **102** can receive, obtain, detect, or collect data relating to the operation of the industrial automation system **104** and the network component **112**. For example, the collection component **102** can receive data relating to the industrial devices **106** (e.g., operation or status of the industrial devices, properties or characteristics of the industrial devices, maintenance records of the industrial devices, configurations of the industrial devices, etc.), industrial processes **108** (e.g., operation or status of the industrial processes, properties or characteristics of the industrial processes, maintenance records associated with the industrial processes, configurations of the industrial processes, etc.), and the other industrial assets **110** (e.g., operation or status of the industrial assets, properties or characteristics of the industrial assets, maintenance records associated with the industrial assets, configurations of the industrial assets, etc.). The collection component **102** also can receive or collect data relating to operation of the components of the network component **112** (e.g., operation or status of the network devices or assets, communication conditions associated with a communication channel, total bandwidth of a communication channel, available bandwidth of a communication channel, properties or characteristics of the network devices or assets, maintenance records associated with the network devices or assets, configurations of the network devices or assets, etc.).

(32) The system **100** also can comprise a data store **114** that can be associated with (e.g., interfaced with, communicatively connected to) the collection component **102**. The collection component **102** can provide (e.g., communicate, write, etc.) the data received or collected from the industrial automation system **104** and the network component **112** to the data store **114** for storage in the data store **114**.

(33) The system **100** further can include a simulation generator component **116** (e.g., simulation builder component) that can generate a simulation model that can emulate, model, or simulate the operation of the industrial automation system **104** and the associated network component **112**. The simulation generator component **116** can be associated with (e.g., interfaced with, communicatively connected to) the data store **114** to facilitate obtaining data associated with the industrial automation system **104** and network component **112** to facilitate generating a simulation model of the industrial automation system **104**.

(34) In some implementations, the simulation generator component **116**, collection component **102**,

and/or the data store **114** can be located in a cloud platform that can be interfaced with the industrial automation system **104**. In accordance with various other implementations, one or more of the simulation generator component **116**, collection component **102**, and/or the data store **114** can be located at the plant or original equipment manufacturer (OEM) level associated with the industrial automation system **104**, or can be located in a different platform or level.

(35) The simulation generator component **116** can generate simulation models of the industrial automation system **104** for a number of desired purposes. For example, the simulation generator component **116** can generate a simulation model to facilitate determining or predicting whether the industrial automation system **104** will operate desirably (e.g., adequately, properly, optimally, etc.) under a set of defined conditions, in accordance with a set of defined operation criteria. The simulation generator component **116** also can generate a simulation model (e.g., of a modified industrial automation system) to facilitate determining or predicting whether a modification of the industrial automation system that is being considered is desirable (e.g., will improve the system **104**, will not underperform, will not harm the system **104**, etc.), in accordance with the set of defined operation criteria. The simulation generator component **116** also can generate simulation models (e.g., of various modifications to the industrial automation system **104**) to facilitate determining or predicting whether one or more of the modifications under consideration are desirable, in accordance with the set of defined operation criteria.

(36) In still another example, the simulation generator component **116** can generate a simulation model of a modification to the industrial automation system **104**, and can apply a set of historical operation data to the simulation model, to facilitate determining or predicting whether the industrial automation system **104**, with the modification, can desirably respond to the set of historical operation data or to determine what the determined or predicted difference in response there is between the response of the modified simulation model of the modified industrial automation system and the response of the industrial automation system based on the set of historical operation data. In yet another example, in relation to a work order for products or processed materials, the simulation generator component **116** can apply a set of operation data relating to the work order to the simulation model of the industrial automation system **104** to facilitate determining or predicting whether the industrial automation system **104** can desirably process or fulfill the work order, in accordance with the set of defined operation criteria. For instance, the simulation generator component **116** can perform a simulation of the processing of the work order by the industrial automation system **104** to facilitate determining or predicting whether the industrial automation system **104** will be able to satisfy a set of order completion parameters (e.g., time constraints, fiscal constraints, product quality constraints, etc.) associated with the work order, the purchaser, or the manufacturer associated with the industrial enterprise, based on the set of defined operation criteria.

(37) To facilitate generating a simulation model of the industrial automation system **104**, the simulation generator component **116** can access the data store **114** (e.g., cloud-based data store) to obtain a set of data relating to the industrial automation system **104** and/or another industrial automation system (e.g., another system comprising an industrial device(s), process(es), and/or asset(s) that can be the same or similar to an industrial device(s) **106**, process(es) **108**, and/or asset(s) **110** of the industrial automation system **104**). The set of data can comprise information relating to, for example, the respective properties, characteristics, functions, configurations, etc., of respective industrial devices **106**, industrial processes **108**, other industrial assets **110**, or network-related devices of the network component **112**; or the configuration of industrial devices **106**, industrial processes, or other assets in relation to each other. For example, the properties or characteristics for industrial devices **104** or industrial processes **106** can comprise mechanical or process properties or characteristics associated with industrial devices or processes (e.g., mechanical latency, process cycle times, operating schedules, etc., associated with industrial devices). As another example, the properties or characteristics for network-related devices can

comprise communication properties or characteristics (e.g., wireless and/or wireline communication functionality, type(s) of network or communication protocol(s), network or communication specifications, total bandwidth, etc.) of the respective network-related devices.

(38) The set of data also can comprise information relating to, for example, the configuration of the network-related devices in relation to each other, or the configuration of network-related devices in relation to the industrial devices **106**, industrial processes **108**, and/or other industrial assets **110**; software, firmware, and/or operating system utilized by the industrial automation system **104** (e.g., type(s), version(s), revision(s), configuration(s), etc., of the software, firmware, and/or operating system); functional and communicative relationships between industrial devices **106**, industrial processes **108**, industrial assets **110**, network-related devices of the network component **112**, etc. (e.g., communication connections or conditions between industrial devices, types of connections between industrial devices, communication connections between industrial devices and network-related devices, etc.). The set of data further can include information relating to, for example, human behavior or interaction in connection with the industrial automation system **104** (e.g., maintenance schedules, shift-specific or operator-specific behavior or interaction of operators with the industrial automation system); production or process flows of the industrial automation system **104** at particular times or in connection with particular projects; and/or other aspects or features of the industrial automation system **104**.

(39) The simulator generator component **116** can analyze the set of data relating to the industrial automation system **104** and/or the other industrial automation system to facilitate simulating or emulating the industrial automation system **104** and its constituent devices, processes, and other assets. Based at least in part on the results of the analysis of the set of data, the simulation generator component **116** can simulate or emulate (e.g., determine and/or generate a simulation or an emulation for) the industrial automation system **104**, including determining respectively simulating or emulating the respective industrial devices **106**, industrial processes **108**, other assets **110**, and network-related devices of the network component **112**, simulating or emulating the interrelationships (e.g., system configuration, connections, etc.) between the respective industrial devices **106**, industrial processes **108**, other industrial assets **110**, and network-related devices of the network component **112**, and/or simulating or emulating the properties, characteristics, functions, etc., of the respective devices, processes, and/or assets of the industrial automation system **104**, etc.

(40) The simulation generator component **116** can generate a simulation model of the industrial automation system **104** based on the simulation or emulation of the industrial automation system **104**, including the respective simulations or emulations of the respective industrial devices **106**, industrial processes **108**, other assets **110**, and network-related devices of the network component **112**, simulations or emulations of the interrelationships (e.g., system configuration, connections, etc.) between the respective industrial devices **106**, industrial processes **108**, other industrial assets **110**, and network-related devices of the network component **112**, etc.

(41) When a set of operation data is applied to the simulation model, a response or behavior of the simulation model can be generated. The simulation generator component **116** can utilize the response or behavior produced by the simulation model in response to the application of the set of operation data to the simulation model to facilitate determining or predicting how the industrial automation system **104** will respond (or is expected to respond) when the set of operation data is applied to the industrial automation system **104**. The simulation generator component **116** can store the simulation model of the industrial automation system **104**, and/or response information relating to determined or predicted responses based on the simulation model, in the data store **114**.

(42) In some instances, it can be desired to modify the industrial automation system **104** to improve the performance of the industrial automation system **104**, re-configure the industrial automation system **104** in connection with a particular work project, perform updates on portions (e.g., software, firmware, operating system, etc.) of the industrial automation system **104**, etc. The

system **100** (e.g., simulation generation system) can facilitate modeling or simulating the modification(s) to the industrial automation system **104**, for example, prior to implementing the modification(s) to determine or predict the response of the industrial automation system **104** (as modified), determine or predict whether performance of the industrial automation system **104** will be improved by the modification(s), determine or predict which modification or combination of modifications of a set of potential modifications is the most preferred modification(s) of the set, and/or determine or predict a response of the industrial automation system **104** (as modified) based on application of a set of historical operation data to the system **104**, etc.

(43) For instance, if a modification(s) to the industrial automation system **104** is being considered, and/or if a request to generate a modified simulation model of a modified industrial automation system is received by the simulation generator component **116**, the simulation generator component **116** can access the data store **114** to obtain a subset of modification data relating to the modification(s) being considered. The subset of modification data can comprise information relating to the properties, characteristics, functionality, configuration, version, etc., of the device(s), process(es), and/or asset(s) associated with the modification(s).

(44) The simulation generator component **116** can analyze the subset of modification data associated with the modification(s) and the set of data associated with the industrial automation system **104**. Based at least in part on the analysis results, the simulation generator component **116** can simulate or emulate the industrial automation system **104** (e.g., modified industrial automation system **104**), including simulating or emulating the modification(s) to the industrial automation system **104** in relation to (e.g., in connection with) the industrial automation system **104**, based on the set of data associated with the industrial automation system **104** and the subset of modification data associated with the modification(s). The simulation generator component **116** can generate the modified simulation model that can correspond to a modified industrial automation system **104** based on the simulation or emulation of the modified industrial automation system **104**.

(45) In some implementations, the simulation generator component **116** can evaluate the respective responses of the simulation model of the industrial automation system **104** (without modification) and the modified simulation of the modified industrial automation system **104**. For instance, the simulation generator component **116** can apply a set of operation data to each of the simulation model and the modified simulation model to produce respective responses or behaviors (e.g., respective output or response data). The simulation generator component **116** can compare the response or behavior (e.g., response data) of the simulation model to the response or behavior (e.g., response data) of the modified simulation model, and can determine or identify any difference(s) in the respective responses.

(46) Based on the comparison and identified difference(s) between the responses, the simulation generator component **116** can determine or predict whether performance of the industrial automation system **104** will be improved by implementing the modification(s), and/or determine or predict which modification or combination of modifications of a set of potential modifications is the most preferred modification(s) of the set, based on the set of defined operation criteria. For example, if, based on the response of the modified simulation model, the comparison, and/or identified difference(s) between the responses, the simulation generator component **116** determines that the implementation of a modification will improve the performance of the industrial automation system **104** and/or the improvement in the performance satisfies a defined level of improvement over the current (unmodified) industrial automation system **104** or satisfies a defined performance target that justifies the modification (e.g., satisfies fiscal or other constraints (e.g., the benefit (e.g., financial or other benefit) of implementing the modification exceeds the cost of the modification), satisfies performance or production requirements or targets, etc.), based on the set of defined operation criteria, the simulation generator component **116** can determine that the modification is to be implemented to modify the industrial automation system **104**. The set of defined operation criteria also can relate to business-level criteria or factors (e.g., return on

investment or profit associated with the modification, etc.). If, based on the response of the modified simulation model, the comparison, and/or identified difference(s) between the responses, the simulation generator component **116** determines or predicts that the implementation of a modification will not improve the performance of the industrial automation system **104** and/or the improvement in the performance does not satisfy a defined level of improvement over the current (unmodified) industrial automation system **104** or does not satisfy the defined performance target that justifies the modification, based on the set of defined operation criteria, the simulation generator component **116** can determine that the modification is not to be implemented, or at least is not recommended to be implemented, to modify the industrial automation system **104**.

(47) If there are two or more modifications of a set of potential modifications that are being considered, based on the evaluation results of the respective responses of the simulation model and modified simulation model, the simulation generator component **116** can determine or predict which modification, if any, of the two or more modifications is the most preferred, in accordance with the set of defined operation criteria, and/or can determine or predict which combination of modifications, if any, of the set of potential modifications is the most preferred, in accordance with the set of defined operation criteria.

(48) The simulation generator component **116** can employ the simulation model and/or modified simulation model(s) associated with the industrial automation system **104** to facilitate performing various desired types of “what if” analyses. As an example, a set of historical operation data can be applied to a modified simulation model to facilitate determining or predicting how a corresponding modified industrial automation system **104** will respond or behave when subjected to the set of historical data. The simulation generator component **116** can evaluate the response (e.g., the simulation response data). Based on the evaluation, the simulation generator component **116** can facilitate determining whether a modified industrial automation system is predicted to perform differently (e.g., better or worse) than the industrial automation system **104** (or a prior version thereof) performed based on the set of historical operation data, determining or predicting an effect on (e.g., an amount of change in) production output that may result than the historical response (e.g., the historical output) of the industrial automation system **104** (or prior version thereof) in response to the set of historical operation data, and/or determining or predicting whether the modification can satisfy the defined set of operation criteria. The set of defined operation criteria also can comprise or relate to system performance criteria, user preferences or requirements (e.g., preferences or requirements of the industrial enterprise entity, preferences or requirements of a purchaser of the product, etc.), and/or business-level criteria or factors (e.g., return on investment or profit associated with the modification, material costs relating to production, current or predicted demand for a product, etc.)

(49) The simulation generator component **116** also can employ a simulation model of an industrial automation system **104** to perform (e.g., run) work order simulations. The work order simulation can facilitate determining whether the industrial automation system **104** is capable of desirably satisfying the work order, in accordance with the set of defined operation criteria.

(50) A set of operation data relating to the work order can be obtained from the data store **114** and/or received from a user (e.g., operator) via an interface component (e.g., a human machine interface (HMI)). For example, the simulation generator component **116** can facilitate providing a user a set of simulation tools via the interface component that can allow the user to enter all or a portion of the set of operation data relating to the work order. The work-order-related data can indicate various aspects or parameters relating to the work order, such as, for example, the type of product to be produced by the industrial automation system, the amount of product to be produced or number of pieces of the product to be produced, the start date or time for production of the product, the end date or time for completion of the production of the product, properties or characteristics associated with the product, components of the product, etc.

(51) The simulation generator component **116** can apply the set of operation data relating to the

work order to the simulation model to facilitate determining or predicting how the industrial automation system **104** will respond if or when it processes the work order. The simulation generator component **116** can evaluate the response (e.g., simulation response data) of the simulation model to the application of the set of operation data to the simulation model. The simulation generator component **116** can determine or predict a response or behavior of the industrial automation system **104** in connection with processing the work order based on the response of the simulation model to the applying of the operation data relating to the work order.

(52) The simulation generator component **116** can evaluate the determined or predicted response or behavior of the industrial automation system in connection with the information relating to the work order that relates to order completion parameters (e.g., time constraints (e.g., production start date, intermediate order deadline(s), order completion deadline, etc.), fiscal constraints (e.g., production cost constraints, profit constraints, constraints relating to the cost of operating the industrial automation system to process the work order, etc.), product quality constraints (e.g., product or material quality constraints, engineering or error tolerances, etc.), etc.) based on the set of defined operation criteria. Based on the results of this evaluation, the simulation generator component **116** can determine whether the industrial automation system **104** can satisfy the order completion parameters based on the set of defined operation criteria, wherein the criteria can comprise or relate to preferences or requirements of the purchaser and/or preferences or requirements of the industrial enterprise entity associated with the industrial automation system **104**. The set of defined operation criteria also can relate to business-level criteria or factors (e.g., return on investment or profit associated with the work order, material costs of processing the work order, current or predicted demand for the product that is the subject of the work order, etc.)

(53) The simulation generator component **116** can generate a report, which can indicate whether the industrial automation system **104** can process and complete the work order to satisfy the order completion parameters in accordance with the set of defined operation criteria. The simulation generator component **116** can provide (e.g., transmit) the report as an output (e.g., via a communication channel, an HMI, printer, etc.) for review or analysis by another component associated with the industrial enterprise or by an operator or manager. The report also can include information relating to expected turn-around times for processing the work order, predicted overtime costs associated with running additional shifts desired to meet the workload associated with the work order, return on investment associated with the work order, etc.

(54) As disclosed herein, the simulation generation system **100**, or a portion thereof, can be located in a cloud platform. To provide a general context for the cloud-based simulation generation system and services described herein, FIG. 2 illustrates a block diagram of a high-level overview of an example industrial enterprise **200** that can leverage cloud-based services, including simulation generation services, data collection services, and data storage services, in accordance with various aspects and embodiments of the disclosed subject matter. The industrial enterprise **200** can comprise one or more industrial facilities, such as industrial facility.sub.1 **204.sub.1** up through industrial facility.sub.N **204.sub.N**, wherein each industrial facility can include a number of industrial devices in use. For example, industrial facility.sub.1 **204.sub.1** can comprise industrial device.sub.1 **208.sub.1** up through industrial device.sub.N **208.sub.N**, and industrial facility.sub.N **204.sub.N** can comprise industrial device.sub.1 **210.sub.1** up through industrial device.sub.N **210.sub.N**. The industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) can make up one or more automation systems that can operate within the respective industrial facilities (e.g., industrial facility.sub.1 **204.sub.1** up through industrial facility.sub.N **204.sub.N**). Exemplary industrial automation systems can include, but are not limited to, batch control systems (e.g., mixing systems), continuous control systems (e.g., proportional-integral-derivative (PID) control systems), or discrete control systems. Industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) can include such industrial devices as industrial controllers (e.g., programmable logic controllers or other types of programmable automation controllers); field devices such as

sensors and meters; motor drives; HMIs; industrial robots, barcode markers, and readers; vision system devices (e.g., vision cameras); smart welders; or other types of industrial devices.

(55) Exemplary industrial automation systems can include one or more industrial controllers that can facilitate monitoring and controlling of their respective industrial processes. The industrial controllers can exchange data with the field devices using native hardwired input/output (I/O) or via a plant network, such as Ethernet/Internet Protocol (IP), Data Highway Plus, ControlNet, Devicenet, or the like. A given industrial controller typically can receive any combination of digital or analog signals from the field devices that can indicate a current state of the industrial devices and/or their associated industrial processes (e.g., temperature, position, part presence or absence, fluid level, etc.), and can execute a user-defined control program that can perform automated decision-making for the controlled industrial processes based on the received signals. The industrial controller can output appropriate digital and/or analog control signaling to the field devices in accordance with the decisions made by the control program. These outputs can include device actuation signals, temperature or position control signals, operational commands to a machining or material handling robot, mixer control signals, motion control signals, and the like. The control program can comprise any suitable type of code that can be used to process input signals read into the controller and to control output signals generated by the industrial controller, including, but not limited to, ladder logic, sequential function charts, function block diagrams, structured text, or other such platforms.

(56) Although the exemplary overview illustrated in FIG. 2 depicts the industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**) as residing in fixed-location industrial facilities (e.g., industrial facility.sub.1 **204.sub.1** up through industrial facility.sub.N **204.sub.N**, respectively), in some implementations, the industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, and/or **210.sub.N**) also can be part of a mobile control and/or monitoring application, such as a system contained in a truck or other service vehicle.

(57) According to one or more embodiments of the disclosed subject matter, industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) can be coupled to a cloud platform **202** to facilitate leveraging cloud-based applications and services (e.g., data collection services, data storage services, simulation generation services, etc.) associated with the cloud platform **202**. That is, the industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) can be configured to discover and interact with cloud-based computing services **212** that can be hosted by the cloud platform **202**. The cloud platform **202** can be any infrastructure that can allow cloud services **212** (e.g., cloud-based computing services, shared computing services) to be accessed and utilized by cloud-capable devices. The cloud platform **202** can be a public cloud that can be accessible via a public network, such as the Internet, by devices having public network connectivity (e.g., Internet connectivity) and appropriate authorizations to utilize the cloud services **212**. In some scenarios, the cloud platform **202** can be provided by a cloud provider as a platform-as-a-service (PaaS), and the cloud services **212** can reside and execute on the cloud platform **202** as a cloud-based service. In some such configurations, access to the cloud platform **202** and associated cloud services **212** can be provided to customers as a subscription service by an owner of the cloud services **212**. Additionally and/or alternatively, the cloud platform **202** can be a private cloud that can be operated internally by the industrial enterprise **200** or an associated enterprise associated with a third-party entity. An exemplary private cloud platform can comprise a set of servers that can host the cloud services **212** and can reside on a private network (e.g., an intranet, a corporate network, etc.) that can be protected by a firewall.

(58) The cloud services **212** can include, but are not limited to, data collection, data storage, data analysis, control applications (e.g., applications that can generate and deliver control instructions to industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) based on analysis of real-time or near real-time system data or other factors), remote monitoring and support, simulations of industrial automation systems and modifications to industrial automation systems, performance

evaluations of proposed modifications to industrial automation systems, or other applications or services relating to industrial automation. If the cloud platform **202** is a web-based cloud, industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) at the respective industrial facilities **204** can interact with cloud services **212** via the public network (e.g., the Internet). In an exemplary configuration, the industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) can access the cloud services **212** through separate cloud gateways (e.g., cloud gateway **206.sub.1** up through cloud gateway **206.sub.N**) at the respective industrial facilities (e.g., industrial facility.sub.1 **204.sub.1** up through industrial facility.sub.N **204.sub.N**, respectively), wherein the industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) can connect to the respective cloud gateways (e.g., cloud gateway **206.sub.1** up through cloud gateway **206.sub.N**) through a physical (e.g., wireline) or wireless local area network or radio link. In another exemplary configuration, the industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) can access the cloud platform **202** directly using an integrated cloud gateway service. Cloud gateways (e.g., cloud gateway **206.sub.1** up through cloud gateway **206.sub.N**) also can comprise an integrated component of a network infrastructure device, such as a firewall box, router, or switch.

(59) Providing industrial devices with cloud capability via the cloud gateways (e.g., cloud gateway **206.sub.1** up through cloud gateway **206.sub.N**) can offer a number of advantages particular to industrial automation. For instance, cloud-based storage (e.g., cloud-based data store) offered by the cloud platform **202** can be easily scaled to accommodate the large quantities of data that can be generated daily by an industrial enterprise. Further, multiple industrial facilities (e.g., industrial facility.sub.1 **204.sub.1** up through industrial facility.sub.N **204.sub.N**) at different geographical locations can migrate (e.g., communicate) their respective industrial automation data to the cloud platform **202** (e.g., via the collection component) for aggregation, collation, collective big data analysis, and enterprise-level reporting without the need to establish a private network between the respective industrial facilities. Industrial devices (e.g., **208.sub.1**, **208.sub.N**, **210.sub.1**, **210.sub.N**, etc.) and/or cloud gateways (e.g., cloud gateway **206.sub.1** up through cloud gateway **206.sub.N**) having smart configuration capability can be configured to automatically detect and communicate with the cloud platform **202** upon installation at any facility, which can thereby simplify integration with existing cloud-based data storage, analysis, or reporting applications used by the industrial enterprise **200**. In another exemplary application, cloud-based simulation applications (e.g., utilized by the simulation generation system comprising the simulation generator component) can access the data relating to an industrial automation system(s) stored in the cloud-based data store, can generate a simulation model that can simulate the operation of the industrial automation system(s), generate a modified simulation model relating to a proposed modification to the industrial automation system(s), and/or simulate operation of the simulation model and/or modified simulation model based on test operation data or historical operation data to facilitate determining or predicting a response of the corresponding industrial automation system(s) or corresponding modified industrial automation system(s), as more fully disclosed herein. These industrial cloud-computing applications are only intended to be exemplary, and the systems and methods described herein are not limited to these particular applications. As these examples demonstrate, the cloud platform **202**, working with cloud gateways (e.g., cloud gateway **206.sub.1** up through cloud gateway **206.sub.N**), can allow builders of industrial applications to provide scalable solutions as a service, removing the burden of maintenance, upgrading, and backup of the underlying infrastructure and framework.

(60) FIG. 3 presents a block diagram of an exemplary system **300** (e.g., cloud-based, or partially cloud-based, simulation generation system) according to various implementations and embodiments of the disclosed subject matter. Aspects of the systems, apparatuses, or processes explained in this disclosure can constitute machine-executable components embodied within machine(s), e.g., embodied in one or more computer-readable mediums (or media) associated with

one or more machines. Such components, when executed by one or more machines, e.g., computer(s), computing device(s), automation device(s), virtual machine(s), etc., can cause the machine(s) to perform the operations described.

(61) The system **300** can comprise a communicator component **302** that can be used to communicate (e.g., transmit, receive) information between the system **300** and other components (e.g., industrial devices, other types of industrial assets that have communication functionality, other devices with communication functionality that are associated with industrial enterprises, cloud gateways, etc.). The information can include, for example, data relating to industrial automation systems, data relating to specifications, properties, or characteristics of industrial devices or other industrial assets, customer-related data, work-order-related data relating to work orders that will or may be handled by an industrial automation system, etc.

(62) The system **300** can comprise an aggregator component **304** that can aggregate data received (e.g., obtained, collected, detected, etc.) from various entities (e.g., industrial devices, industrial assets, cloud gateways, other devices with communication functionality that are associated with industrial enterprises, processor component(s), user interface(s), data store(s), etc.). The aggregator component **304** can correlate respective items of data based at least in part on type of data, source of the data, time or date the data was generated or received, type of device or asset, identifier associated with a device or asset, customer associated with the data, industrial automation system associated with the data, industrial enterprise associated with the system, etc., to facilitate processing of the data (e.g., analyzing of the data, generating simulation models, etc.).

(63) The system **300** also can include a monitor component **306** that can monitor device data, process data, asset data, system data, customer data, and/or other data in connection with the industrial automation systems. For instance, the monitor component **306** can monitor information (e.g., signals, device or process statuses, network communication of information, process flows, updates, modifications, etc.) associated with industrial automation systems, industrial enterprises, and/or systems or devices of customers associated with the industrial enterprises to facilitate detecting information associated with industrial automation systems that can facilitate simulating industrial automation systems. The monitor component **306** can be associated with sensors, meters, HMIs, communication monitoring components, or other components associated with industrial automation systems, industrial enterprises, and/or systems or devices of the customers to facilitate the monitoring of the industrial automation systems, industrial enterprises, and/or systems or devices of the customers.

(64) The system **300** can comprise a detector component **308** that can detect desired information associated with industrial automation systems that can facilitate simulating industrial automation systems, in accordance with the defined operation criteria. For instance, the detector component **308** can detect desired device data, process data, asset data, system data, and/or customer data in connection with the industrial automation systems that can facilitate simulating industrial automation systems to facilitate collection of the desired data.

(65) The system **300** also can include a collection component **310** that can receive, collect, or obtain data (e.g., desired device data, process data, asset data, system data, and/or customer data) to facilitate simulation industrial automation systems, as more fully disclosed herein. The data collected by the collection component **310** can be stored in the data store **328**, and/or can be made available to other components (e.g., analyzer component **316**, simulation generator component **318**, etc.) to facilitate simulating industrial automation systems, evaluating operation of simulation models of industrial automation systems, and/or performing other desired functions using the data.

(66) The system **300** can comprise an interface component **312** that can be employed to facilitate interfacing the system **300** with industrial automation systems and their constituent components (e.g., industrial devices or assets, network-related devices or assets, etc.) or processes, systems or devices associated with customers, systems or devices associated with device manufacturers, etc. For instance, the interface component **312** can be configured to receive industrial data (e.g., device

data, process data, asset data, system data, configuration data, status data, process variable data, etc.) sent by one or more cloud-capable industrial devices, cloud gateways, or other sources of industrial data. The interface component **312** also can be configured to receive network-related data (e.g., data relating to communication conditions, network-status data, data identifying network-related devices, etc.) communicated by one or more network-related devices of the network component of an industrial automation system. The interface component **312** further can be configured to exchange data with one or more client or customer devices via an Internet connection. For example, the interface component **312** can receive customer profile data, requests for firmware upgrades, customer service selections, information relating to work orders for products, customer preferences or requirements with regard to a work order, or other such information from a client device (e.g., an Internet-capable client device, such as a phone, a computer, an electronic tablet or pad, or other suitable Internet-capable device). The interface component **312** also can deliver upgrade notifications, firmware upgrades, reports or notifications regarding the evaluation of and determinations regarding proposed modifications to an industrial automation system, notifications of impending device failures, identification of asset or system inefficiencies, configuration recommendations, or other such data to the client device.

(67) The system also can contain a controller component **314** can control operations relating to processing data, generating simulation models that can simulate or emulate industrial automation systems, performing simulation operations using simulation models, determining or predicting responses of industrial automation systems based on corresponding simulation models, evaluating modifications to industrial automation systems that are under consideration, and/or other operations. The controller component **314** can facilitate controlling operations being performed by various components of the system **300**, controlling data flow between various components of the system **300**, controlling data flow between the system **300** and other components or systems associated with the system **300**, etc.

(68) The analyzer component **316** can analyze data (e.g., device data, process data, asset data, system data, customer data, and/or other data) to facilitate generating simulation models of industrial automation systems, evaluating modifications being considered for an industrial automation system, determining or predicting a response of an industrial automation system under a set of conditions based on a corresponding simulation model, etc. The analyzer component **316** can parse data to facilitate identifying data that is relevant to performing an operation (e.g., generating a simulation model, evaluating a modification, etc.) by the system **300**. Based at least in part on the analysis of the data, the analyzer component **316** can generate analysis results that can be provided to another component (e.g., simulation generator component **318**, processor component **326**, etc.) to facilitate the performance of various operations by the system **300**.

(69) The system **300** also can comprise a simulation generator component **318** that can generate a simulation model that can simulate or emulate an industrial control system and can simulate operation of the industrial control system under a set of conditions based on the simulation model. The simulation generator component **318** can include an emulator component **320** that can emulate or facilitate simulating the industrial control system, including emulating or facilitating simulating the constituent components (e.g., industrial devices, industrial processes, industrial assets, network-related devices or assets, etc.) of the industrial control system, the interrelationships between respective constituent components, configurations of respective constituent components, etc., in accordance with the set of defined operation criteria, as more fully disclosed herein.

(70) The simulation generator component **318** can comprise a simulation model generator component **322** that can generate a simulation model of the industrial automation system based on the simulation or emulation of the industrial control system, in accordance with the set of defined operation criteria. The simulation model generator component **322** can integrate the respective simulations or emulations of the constituent components of the industrial automation system, the interrelationships between respective constituent components, configurations of respective

constituent components, etc., to facilitate generating the simulation model that can simulate or emulate the industrial automation system. When a modification to an industrial automation system is to be considered or implemented, the emulator component **320** can emulate or facilitate simulating the modification and the interrelationship(s) of the modification with other constituent components of the industrial automation system to facilitate simulating or emulating a modified industrial automation system. The simulation model generator component **322** can generate the modified industrial automation system based on the simulation or emulation of the modification and the interrelationship(s) of the modification with other constituent components of the industrial automation system.

(71) The simulation generator component **318** also can include an evaluator component **324** that can evaluate simulated operation of an industrial automation system (or modified industrial automation system) under a given set of conditions based on a corresponding simulation model (or corresponding modified simulation model) to facilitate determining or predicting a response of the industrial automation system (or modified industrial automation system) under the given set of conditions, determining or predicting whether an industrial automation system can adequately handle a work order for a product or processed materials based on a simulated operation and response of a corresponding simulation model, determining whether a proposed modification to an industrial automation system is suitable for implementation, determining which modification or combination of modifications is most suitable for implementation to modify an industrial automation system, and/or make other determinations or predictions relating to industrial automation systems, in accordance with the set of defined operation criteria.

(72) The system **300** also can comprise a processor component **326** that can operate in conjunction with the other components (e.g., communicator component **302**, aggregator component **304**, monitor component **306**, etc.) to facilitate performing the various functions and operations of the system **300**. The processor component **326** can employ one or more processors (e.g., central processing units (CPUs), graphical processing units (GPUs), field-programmable gate arrays (FPGAs), etc.), microprocessors, or controllers that can process data, such as industrial data (e.g., device data, process data, asset data, system data, etc.) associated with industrial control systems, customer or client related data, data relating to parameters associated with the system **300** and associated components, etc., to facilitate generating simulation models of industrial automation systems, evaluating modifications to an industrial automation system based on simulation models of a modified industrial automation system, simulating operation of simulation models under a set of conditions to facilitate determining or predicting how the corresponding industrial automation system will respond under the set of conditions, etc.; and can control data flow between the system **300** and other components associated with the system **300**.

(73) In yet another aspect, the system **300** can contain a data store **328** that can store data structures (e.g., user data, metadata); code structure(s) (e.g., modules, objects, classes, procedures), commands, or instructions; industrial data or other data associated with industrial automation systems or industrial enterprises; customer or client related information; data relating to generation of simulation models of industrial automation systems; parameter data; algorithms (e.g., algorithm(s) relating to simulating or emulating industrial devices, industrial processes, industrial assets, network-related devices, interrelationships between such devices, processes, or assets, etc.); algorithm(s) relating to evaluating, determining, or predicting operation of an industrial automation system based on a corresponding simulation model or evaluating, determining, or predicting operation of a modified automation system based on a corresponding modified simulation model); a set of defined operation criteria; and so on. In an aspect, the processor component **326** can be functionally coupled (e.g., through a memory bus) to the data store **328** in order to store and retrieve data desired to operate and/or confer functionality, at least in part, to the communicator component **302**, aggregator component **304**, monitor component **306**, etc., of the system **300** and/or substantially any other operational aspects of the system **300**. It is to be appreciated and understood

that the various components of the system **300** can communicate data, instructions, or signals between each other and/or between other components associated with the system **300** as desired to carry out operations of the system **300**. It is to be further appreciated and understood that respective components (e.g., communicator component **302**, aggregator component **304**, monitor component **306**, etc.) of the system **300** each can be a stand-alone unit, can be included within the system **300** (as depicted), can be incorporated within another component of the system **300** (e.g., within the simulator generator component **318**) or a component separate from the system **300**, and/or virtually any suitable combination thereof, as desired.

(74) In accordance with various embodiments, one or more of the various components of the system **300** (e.g., communication component **302**, aggregator component **304**, monitor component **306**, etc.) can be electrically and/or communicatively coupled to one another to perform one or more of the functions of the system **300**. In some implementations, one or more components of the system **300** (e.g., communication component **302**, aggregator component **304**, monitor component **306**, . . . , simulation generator component **318**) can comprise software instructions that can be stored in the data store **328** and executed by the processor component **326**. The system **300** also can interact with other hardware and/or software components not depicted in FIG. 3. For example, the processor component **326** can interact with one or more external user interface devices, such as a keyboard, a mouse, a display monitor, a touchscreen, or other such interface devices.

(75) FIG. 4 illustrates a diagram of an example system **400** that can facilitate generation of industrial simulations based at least in part collection of customer-specific industrial data by a cloud-based simulation generation system, in accordance with various aspects and embodiments of the disclosed subject matter. The system **400** can include a simulation generation system **402** that can execute as a cloud-based service on a cloud platform (e.g., cloud platform **202** of FIG. 2), and can collect data from multiple industrial automation systems, such as industrial automation system.sub.1 **404.sub.1**, industrial automation system.sub.2 **404.sub.2**, and/or (up through) industrial automation system.sub.N **404.sub.N**. The industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**) can comprise different industrial automation systems within a given facility and/or different industrial facilities at diverse geographical locations. Industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**) also can correspond to different business entities (e.g., different industrial enterprises or customers), wherein the simulation generation system **402** can collect and maintain a distinct customer data store **406** for each customer or business entity.

(76) The simulation generation system **402** can organize manufacturing data collected from the industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**) according to various classes. In the illustrated example, manufacturing data can be classified according to device data **408**, process data **410**, asset data **412**, and system data **414**.

(77) Referring briefly to FIG. 5, FIG. 5 illustrates a diagram of an example hierarchical relationship **500** between these example data classes. A given plant or supply chain **502** can comprise one or more industrial automation systems **504**. The industrial automation systems **504** can represent the production lines or productions areas within a given plant facility or across multiple facilities of a supply chain. Each industrial automation system **504** can comprise a number of assets **506** that can represent the machines and equipment that make up the industrial automation system (e.g., the various stages of a production line). In general, each asset **506** can comprise one or more industrial devices **508**, which can include, for example, the programmable controllers, motor drives, HMIs, sensors, meters, etc. comprising the asset **506**. The various data classes depicted in FIGS. 4 and 5 are only intended to be exemplary, and it is to be appreciated that any organization of industrial data classes maintained by the simulation generation system **402** is within the scope of one or more embodiments of the disclosed subject matter.

(78) Returning again to FIG. 4, the simulation generation system **402** can collect and maintain data from the various devices and assets that make up the industrial automation systems **504** and can classify the data according to the aforementioned classes for the purposes of facilitating analysis of

the data, generation of simulation models of the industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**), and/or performing other operations by the simulation generation system **402**. Device data **408** can comprise device-level information relating to the identity, configuration, and status of the respective devices comprising the industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**), including but not limited to device identifiers, device statuses, current firmware versions, health and diagnostic data, device documentation, identification and relationship of neighboring devices that interact with the device, etc.

(79) The process data **410** can comprise information relating to one or more processes or other automation operations carried out by the devices; e.g., device-level and process-level faults and alarms, process variable values (speeds, temperatures, pressures, etc.), and the like.

(80) The asset data **412** can comprise information generated, collected, determined, or inferred based on data that can be aggregated from various (e.g., multiple) industrial devices over time, which can yield higher asset-level views of the industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**). Example asset data **412** can include performance indicators (KPIs) for the respective assets, asset-level process variables, faults, alarms, etc. Since the asset data **412** can yield a relatively longer term view of asset characteristics relative to the device and process data, the simulation generation system **402** can leverage the asset data **412** to facilitate identifying operational patterns and correlations unique to each asset, among other types of analysis, and this can facilitate simulation or emulation of the respective assets and generation of a simulation model of an industrial control system based on the simulation or emulation of the respective assets associated with the industrial control system.

(81) The system data **414** can comprise collected, determined, or inferred information that can be generated based on data that can be aggregated from various (e.g., multiple) assets over time. The system data **414** can characterize system behavior within a large system of assets, yielding a system-level view of each of the industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**). The system data **414** also can document the particular system configurations in use and industrial operations performed at each of the industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**). For example, the system data **414** can document the arrangement of assets, interconnections between devices, the product being manufactured at a given facility, an industrial process performed by the assets, a category of industry of each industrial system (e.g., automotive, oil and gas, food and drug, marine, textiles, etc.), or other relevant information. Among other functions, this data can be accessed by technical support personnel during a support session so that particulars of the customer's unique system and device configurations can be obtained without reliance on the customer to possess complete knowledge of their assets.

(82) As an example, a given industrial facility can include a packaging line (e.g., the system), which in turn can comprise a number of individual assets (e.g., a filler, a labeler, a capper, a palletizer, etc.). Each asset can comprise a number of devices (e.g., controllers, variable frequency drives, HMIs, etc.). Using an architecture similar to that depicted in FIG. 2, the simulation generation system **402** can collect industrial data from the individual devices during operation and can classify the data in the customer data store **406** according to the aforementioned classifications. Note that some data may be duplicated across more than one class. For example, a process variable classified under process data **410** also can be relevant to the asset-level view of the system represented by the asset data **412**. Accordingly, such process variables can be classified under both classes. Moreover, subsets of data in one classification can be derived, determined, or inferred based on data under another classification. For example, subsets of system data **414** that characterize certain system behaviors can be derived, determined, or inferred based on a long-term analysis of data in the lower-level classifications.

(83) In addition to maintaining the data classes (e.g., **408**, **410**, **412**, **414**), each customer data store also can maintain a customer model **416** that can contain data specific to a given industrial entity or customer. The customer model **416** can contain customer-specific information and preferences,

which can be leveraged by (e.g., used by) the simulation generation system **402** to facilitate generating a simulation model (or modified simulation model) that can be representative of an industrial automation system (or a modified simulation model), evaluating the performance or response of a simulation model (or modified simulation model) under a set of conditions, determining or predicting a response of an industrial automation system (or modified industrial automation system) based on the simulation model (or modified simulation model), etc. Example information that can be maintained in the customer model **416** can include a client identifier, client preferences or requirements with regard to production or work orders associated with an industrial automation system, client contact information specifying which plant personnel are to be notified in response to results of an evaluation of a simulation of an industrial automation system or modification thereof, notification preferences that can specify how plant personnel are to be notified (e.g., email, mobile phone, text message, etc.), service contracts that are active between the customer and the technical support entity, and other such information. The simulation generation system **402** can marry (e.g., associate, unite, map, etc.) data collected for each customer with the corresponding customer model **416** for identification and event handling purposes.

(84) As noted above, industrial data can be migrated (e.g., communicated) from industrial devices to the cloud platform (e.g., **102**) using cloud gateways. To this end, some devices can include integrated cloud gateways that can directly interface each device to the cloud platform.

Additionally or alternatively, some configurations can utilize a cloud proxy device that can collect industrial data from multiple devices associated with the industrial automation systems (e.g., **404.sub.1**, **404.sub.2**, **404.sub.N**) and can send (e.g., transmit) the data to the cloud platform. Such a cloud proxy can comprise a dedicated data collection device, such as a proxy server that can share a network (e.g., communication network) with the industrial devices. Additionally or alternatively, the cloud proxy can be a peer industrial device that can collect data from other industrial devices.

(85) FIGS. **6** and **7** depict block diagrams of example systems **600** and **700**, respectively, illustrating respective techniques that can facilitate migrating industrial data to the cloud platform via proxy devices for classification and analysis by the simulation generation system, in accordance with various aspects and implementations of the disclosed subject matter. FIG. **6** depicts the system **600** that can be configured to comprise an industrial device that can act or operate as a cloud proxy for other industrial devices of an industrial automation system. The industrial automation system can comprise a plurality of industrial devices, including industrial devices **606.sub.1**, industrial device.sub.2 **606.sub.2**, industrial device.sub.3 **606.sub.3**, and/or (up through) industrial device.sub.N **606.sub.N**, that collectively can monitor and/or control one or more controlled processes **602**. The industrial devices **606.sub.1**, **606.sub.2**, **606.sub.3**, and/or (up through) **606.sub.N** respectively can generate and/or collect process data relating to control of the controlled process(es) **602**. For industrial controllers such as PLCs or other automation controllers, this can include collecting data from telemetry devices connected to an industrial controller's I/O, generating data internally based on measured process values, etc.

(86) In the configuration depicted in FIG. **6**, industrial device.sub.1 **606.sub.1** can act, operate, or function as a proxy for industrial devices **606.sub.2**, **606.sub.3**, and/or (up through) **606.sub.N**, whereby the data **614** from devices **606.sub.2**, **606.sub.3**, and/or (up through) **606.sub.N** can be sent (e.g., transmitted) to the cloud via proxy industrial device.sub.1 **606.sub.1**. Industrial devices **606.sub.2**, **606.sub.3**, and/or (up through) **606.sub.N** can deliver their respective data **614** to the proxy industrial device.sub.1 **606.sub.1** over the plant network or backplane **612** (e.g., a Common Industrial Protocol (CIP) network or other suitable network protocol). Using such a configuration, it is only necessary to interface one industrial device to the cloud platform (via cloud gateway **608**). In some embodiments, the cloud gateway **608** can perform preprocessing on the gathered data prior to migrating the data to the cloud platform (e.g., time stamping, filtering, formatting, normalizing, summarizing, compressing, etc.). The collected and processed data can be pushed (e.g., transmitted) to the cloud platform as cloud data **604** via cloud gateway **608**. Once migrated to the

cloud platform, the cloud-based simulation generation system can classify the data according to the example classifications described herein and/or can utilize the data to facilitate performing various operation relating to simulating industrial automation systems.

(87) While the proxy device illustrated in FIG. 6 is depicted as an industrial device that itself can perform monitoring and/or control of a portion of controlled process(es) 602, other types of devices also can be configured to serve as cloud proxies for multiple industrial devices according to one or more implementations of the disclosed subject matter. For example, FIG. 7 illustrates an example system 700 that can comprise a firewall box 712 that can serve as a cloud proxy for a set of industrial devices 706.sub.1, 706.sub.2, and/or (up through) 706.sub.N. The firewall box 712 can act as a network infrastructure device that can allow the plant network 716 to access an outside network such as the Internet, while also providing firewall protection that can prevent unauthorized access to the plant network 716 from the Internet. In addition to these firewall functions, the firewall box 712 can include a cloud gateway 708 that can interface the firewall box 712 with one or more cloud-based services (e.g., simulation generation services, data collection services, data storage services, etc.). In a similar manner to the proxy industrial device 606.sub.1 of FIG. 6, the firewall box 712 of FIG. 7 can collect industrial data 714 from including industrial devices 706.sub.1, industrial device.sub.2 706.sub.2, and/or (up through) industrial device.sub.N 706.sub.N, which can monitor and control respective portions of controlled process(es) 702. Firewall box 712 can include a cloud gateway 708 that can apply appropriate pre-processing to the gathered industrial data 714 prior to pushing (e.g., communicating) the data to the cloud-based simulation generation system as cloud data 704. Firewall box 712 can allow industrial devices 706.sub.1, 706.sub.2, and/or (up through) 706.sub.N to interact with the cloud platform without directly exposing the industrial devices to the Internet.

(88) In some embodiments, the cloud gateway 608 of FIG. 6 or cloud gateway 708 of FIG. 7 can tag the collected industrial data (e.g., 614 or 714) with contextual metadata prior to pushing the data as cloud data (e.g., 604 or 704) to the cloud platform. Such contextual metadata can include, for example, a time stamp, a location of the device at the time the data was generated, or other contextual information. In another example, some cloud-aware devices can comprise smart devices capable of determining their own context within the plant or enterprise environment. Such devices can determine their location within a hierarchical plant context or device topology. Data generated by such devices can adhere to a hierarchical plant model that can define multiple hierarchical levels of an industrial enterprise (e.g., a workcell level, a line level, an area level, a site level, an enterprise level, etc.), such that the data can be identified (e.g., by the simulation generation system) in terms of these hierarchical levels. This can allow a common terminology to be used across an entire industrial enterprise to identify devices and their associated data. Cloud-based applications and services that model an enterprise according to such an organizational hierarchy can represent industrial controllers, devices, machines, or processes as data structures (e.g., type instances) within this organizational hierarchy to provide context for data generated by respective devices within the enterprise relative to the enterprise as a whole. Such a convention can replace the flat name structure that is employed by some industrial applications.

(89) In some embodiments, the cloud gateway 608 of FIG. 6 or cloud gateway 708 of FIG. 7 can comprise uni-directional “data only” gateways that can be configured only to move data from the premises (e.g., industrial facility) to the cloud platform. Alternatively, the cloud gateways 608 and 708 can comprise bi-directional “data and configuration” gateways that additionally can be configured to receive configuration or instruction data from services running on the cloud platform. Some cloud gateways can utilize store-and-forward technology that can allow the gathered industrial data (e.g., 614 or 714) to be temporarily stored locally on storage associated with the cloud gateway (e.g., 608 or 708) in the event that communication between a gateway and the cloud platform is disrupted. In such events, the cloud gateway (e.g., 608 or 708) can forward (e.g., communicate) the stored data to the cloud platform when the communication link is re-established.

(90) To ensure a rich and descriptive set of data for analysis purposes, the cloud-based simulation generation system can collect device data in accordance with one or more standardized device models. To this end, a standardized device model can be developed for each industrial device. Device models can profile the device data that is available to be collected and maintained by the simulation generation system.

(91) FIG. 8 illustrates a block diagram of an example device model **800** according to various aspects and implementations of the disclosed subject matter. In the illustrated example model **800**, the device model **806** can be associated with a cloud-aware industrial device **802** (e.g., a programmable logic controller, a variable frequency drive, an HMI, a vision camera, a barcode marking system, etc.). As a cloud-aware device, the industrial device **802** can be configured to automatically detect and communicate with the cloud platform **808** upon installation at a plant facility, simplifying integration with existing cloud-based data storage, analysis, and applications (e.g., as performed by the simulation generation system described herein). When added to an existing industrial automation system, the industrial device **802** can communicate with the cloud platform and can send identification and configuration information in the form of the device model **806** to the cloud platform **808**. The device model **806** can be received by the simulation generation system **810**, which can update the customer's device data **812** based on the device model **806**. In this way, the simulation generation system **810** can leverage the device model **806** to facilitate integrating the new industrial device **802** into the greater system as a whole. This integration can include the simulation generation system **810** updating cloud-based applications or services to recognize the new industrial device **802**, adding the new industrial device **802** to a dynamically updated data model of the customer's industrial enterprise or plant, modifying a simulation model of the industrial automation system to integrate, incorporate, or include a simulation or an emulation of the new industrial device **802** based on the identification and configuration information (or other data), determining or predicting a response of the modified industrial automation system based on a modified simulation model that integrates the new industrial device **802**, making other devices on the plant floor aware of the new industrial device **802**, or other desired integration functions. Once deployed, some data items comprising the device model **806** can be collected and monitored by the simulation generation system **810** on a real-time or near real-time basis.

(92) The device model **806** can comprise such information as a device identifier (e.g., model and serial number) associated with the industrial device **802**, status information for the industrial device **802**, a currently installed firmware version associated with the industrial device **802**, device setup data associated with the industrial device **802**, warranty specifications associated with the industrial device **802**, calculated and/or anticipated KPIs associated with the industrial device **802** (e.g., mean time between failures), health and diagnostic information associated with the industrial device **802**, device documentation, or other such parameters.

(93) In addition to maintaining individual customer-specific data stores for each industrial enterprise, the simulation generation system (e.g., cloud-based simulation generation system) also can feed (e.g., transmit) sets of customer data to a global data storage (referred to herein as cloud-based data store or Big Data for Manufacturing (BDFM) data store) for collective big data analysis in the cloud platform (e.g., by the simulation generation system). FIG. 9 presents a block diagram of an example system **900** that can facilitate collection of data from devices and assets associated with respective industrial automation systems for storage in cloud-based data storage, in accordance with various aspects and implementations of the disclosed subject matter. As illustrated in FIG. 9, the collection component **310** of the simulation generation system (e.g., as facilitated by the interface component **312**) can collect data from devices and assets comprising respective different industrial automation systems, such as industrial automation system.sub.1 **906.sub.1**, industrial automation system.sub.2 **906.sub.2**, and/or (up through) industrial automation system.sub.N **906.sub.N**, for storage in a cloud-based BDFM data store **902**. In some embodiments,

data maintained in the BDFM data store **902** can be collected anonymously with the consent of the respective customers. For example, customers can enter into a service agreement with a technical support entity whereby the customer can agree to have their device and asset data collected by the simulation generation system in exchange for simulation generation services or a credit towards simulation generation services. The data maintained in the BDFM data store **902** can include all or portions of the classified customer-specific data described in connection with FIG. **4**, as well as additional data (e.g., derived, determined, or inferred data). The simulation generator component **318** or another component of the simulation generation system can organize the collected data stored in the BDFM data store **902** according to device type, system type, application type, applicable industry, or other relevant categories. The simulation generator component **318** can analyze data stored in the resulting multi-industry, multi-customer data store (e.g., BDFM data store **902**) to facilitate learn, determine, or identify industry-specific, device-specific, and/or application-specific trends, patterns, thresholds (e.g., device-related thresholds, network-related thresholds, etc.), industrial-automation-system interrelationships between devices or assets, etc., associated with the industrial automation systems associated with the cloud platform. In general, the simulation generator component **318** can perform a data analysis (e.g., big data analysis) on data (e.g., the multi-industrial enterprise data) maintained (e.g., stored in) the BDFM data store **902** to learn, determine, identify, characterize, simulate, and/or emulate operational industrial-automation-system interrelationships, thresholds, trends, or patterns associated with industrial automation systems as a function of industry type, application type, equipment in use, asset configurations, device configuration settings, or other types of variables.

(94) For example, it can be known that a given industrial asset (e.g., a device, a configuration of device, a machine, etc.) can be used across different industries for different types of industrial applications. Accordingly, the simulation generator component **318** can identify a subset of the global data stored in BDFM data storage **902** relating to the asset or asset type, and perform analysis on this subset of data to determine how the asset or asset type performs over time and under various types of operating conditions for each of multiple different industries or types of industrial applications. The simulation generator component **318** also can determine the operational behavior of the asset or asset type over time and under various types of operating conditions for each of different sets of operating constraints or parameters (e.g. different ranges of operating temperatures or pressures, different recipe ingredients or ingredient types, etc.). The simulation generator component **318** can leverage (e.g., use) a large amount of historical data relating to the asset or asset type that has been gathered (e.g., collected and/or aggregated) from many different industrial automation systems to facilitate learning or determining common operating characteristics of many diverse configurations of industrial assets or asset types at a relatively high degree of granularity and under many different operating contexts. The simulation generator component **318** can use the learned or determines operating characteristics relating to the industrial assets or asset types to facilitate simulating or emulating the industrial assets or asset types when employed in an industrial automation system.

(95) FIG. **10** illustrates a block diagram of a cloud-based system **1000** that can employ a simulation generation system to facilitate simulation generation services associated with industrial automation systems, in accordance with various aspects and embodiments of the disclosed subject matter. As disclosed herein, the simulation generation system **1002** can collect, maintain, and monitor customer-specific data (e.g. device data **408**, process data **410**, asset data **412**, and system data **414**) relating to one or more industrial assets **1004** of an industrial enterprise. In addition, the simulation generation system **1002** can collect and organize industrial data anonymously (with customer consent) from multiple industrial enterprises, and can store such industrial data in a BDFM data store **1006** for collective analysis by the simulation generation system **1002**, for example, as described herein.

(96) The simulation generation system **1002** also can collect product resource information and

maintain (e.g., store) the product resource information in the cloud-based product resource data store **1008**. In general, the product resource data store **1008** can maintain up-to-date information relating to specific industrial devices or other vendor products in connection with industrial automation systems. Product data stored in the product resource data store **1008** can be administered by the simulation generation system **1002** and/or one or more product vendors or OEMs. Exemplary device-specific data maintained by the product resource data store **1008** can include product serial numbers, most recent firmware revisions, preferred device configuration settings and/or software for a given type of industrial application, or other such vendor-provided information.

(97) The system depicted in FIG. **10** can provide simulation generation services to subscribing customers (e.g., owners of industrial assets **1004**). For example, customers can enter an agreement with a product vendor or technical support entity to allow their system data to be gathered anonymously and fed into (e.g., communicated to and stored in) the BDFM data store **1006**, and this thereby can expand the store of global data available for collective analysis by the simulation generation system **1002**. In exchange, the vendor or technical support entity can agree to provide customized simulation generation services to the customer (e.g., real-time or near real-time system monitoring, evaluation of proposed modification to an industrial automation system, simulation and evaluation of a performance of an industrial automation system in connection with a work order, etc.). Alternatively, the customer can subscribe to one or more available simulation generation services that can be provided by the simulation generation system **1002**, and optionally can allow their system data to be maintained in the BDFM data store **1006**. In some embodiments, a customer can be given an option to subscribe to simulation generation services without permitting their data to be stored in the BDFM data store **1006** for collective analysis with data from other systems (e.g., industrial automation systems). In such cases, the customer's data will only be maintained as customer data (e.g., in customer data store **406**) for the purposes of generating and evaluating simulations of an industrial automation system(s) relating to that particular customer, and the collected customer data will be analyzed in connection with data stored in the BDFM data store **1006** and the product resource data store **1008** without that customer data being migrated for storage in the BDFM data store **1006** for long-term storage and analysis. In another exemplary agreement, customers can be offered a discount on simulation generation services in exchange for allowing their system data to be anonymously migrated to the BDFM data store **1006** for collective analysis by the simulation generation system **1002**.

(98) In accordance with various aspects, the customer-specific data can include device and/or asset level faults and alarms, process variable values (e.g., temperatures, pressures, product counts, cycle times, etc.), calculated or anticipated key performance indicators for the customer's various assets, indicators of system behavior over time, and other such information. The customer-specific data also can include documentation of firmware versions, configuration settings, and software in use on respective devices of the customer's industrial assets. Moreover, the simulation generation system **1002** can take into consideration customer information encoded in customer model **416**, which can have a bearing on inferences made by the simulation generation system **1002** based on the analysis (e.g., big data analysis) stored in the BDFM data store **1006**. For example, customer model **416** may indicate a type of industry that is the focus of the customer's business (e.g., automotive, food and drug, oil and gas, fibers and textiles, power generation, marine, etc.). Knowledge of the customer's industry can facilitate enabling the simulation generation system **1002** to correlate the customer-specific data with data relating to similar systems and applications in the same industry, as documented by the data stored in the BDFM data storage **1006**.

(99) Taken together, customer-specific data and a customer model (e.g., **416**) can facilitate accurately modeling the customer's industrial enterprise at a highly granular level, from high-level system behavior over time down to the device and software level. The analyzing (e.g., by the simulation generation system **1002**) of this customer-specific data in view of global industry-

specific and application-specific trends learned via analysis of data stored in the BDFM data storage **1006**, as well as vendor-provided device information maintained in the product resource data storage **1008**, can facilitate generation accurate simulation models of industrial automation systems.

(100) The aforementioned systems and/or devices have been described with respect to interaction between several components. It should be appreciated that such systems and components can include those components or sub-components specified therein, some of the specified components or sub-components, and/or additional components. Sub-components could also be implemented as components communicatively coupled to other components rather than included within parent components. Further yet, one or more components and/or sub-components may be combined into a single component providing aggregate functionality. The components may also interact with one or more other components not specifically described herein for the sake of brevity, but known by those of skill in the art.

(101) FIGS. **11-17** illustrate various methods in accordance with one or more embodiments of the subject application. While, for purposes of simplicity of explanation, the one or more methods shown herein are shown and described as a series of acts, it is to be understood and appreciated that the disclosed subject matter is not limited by the order of acts, as some acts may, in accordance therewith, occur in a different order and/or concurrently with other acts from that shown and described herein. For example, those skilled in the art will understand and appreciate that a method could alternatively be represented as a series of interrelated states or events, such as in a state diagram. Moreover, not all illustrated acts may be required to implement a method in accordance with the disclosed subject matter. Furthermore, interaction diagram(s) may represent methods, in accordance with the subject disclosure when disparate entities enact disparate portions of the methods. Further yet, two or more of the disclosed example methods can be implemented in combination with each other, to accomplish one or more features or advantages described herein.

(102) FIG. **11** illustrates a flow diagram of an example method **1100** that can facilitate simulating an industrial automation system based on cloud-based data relating to an industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter. The method **1100** can be implemented by a simulation generation system that can comprise a simulation generator component and/or another component(s) (e.g., a collection component, a cloud-based data store, etc.).

(103) At **1102**, an industrial automation system can be simulated or emulated based on a set of industrial-automation-system-related data stored in a cloud-based data store, wherein a first subset of the set of industrial-automation-system-related data can be received (e.g., collected, obtained, detected, etc.) from the industrial automation system and stored in the cloud-based data store. The set of industrial-automation-system-related data can comprise, for example, device-related data (e.g., industrial device-related data), asset-related data, process-related data (e.g., industrial-automation-process-related data), and/or other industrial-automation-system-related data associated with an industrial enterprise. The industrial-automation-system-related data can be migrated (e.g., communicated) to the cloud platform using one or more cloud gateways (e.g., communication gateway components) that can serve as uni-directional or bi-directional communication interfaces between industrial devices of the industrial automation system and the cloud platform. The device-related data, asset-related data, process-related data, and/or other industrial-automation-system-related data can be stored in the cloud-based data store in association with identification information, such as, for example, a customer identifier and other customer-specific information.

(104) The collection component can facilitate collecting or obtaining the industrial-automation-system-related data, and can store the industrial-automation-system-related data in the cloud-based data store. The simulation generator component can access the cloud-based data store and can receive (e.g., collect, obtain, etc.) the set of industrial-automation-system-related data from the cloud-based data store. The simulation generator component can simulate or emulate the industrial

automation system based on the set of industrial-automation-system-related data. For example, the simulation generator component can simulate or emulate industrial devices, software and/or firmware configurations (including software or firmware revisions or updates) associated with industrial devices and/or other components of the industrial automation system, network-related devices (e.g., communication devices, computers, routers, etc.) associated with the industrial automation system, functional and communicative relationships between industrial devices, industrial processes, network-related devices, etc. (e.g., communication connections or conditions between industrial devices, types of connections between industrial devices, communication connections between industrial devices and network-related devices, etc.), mechanical or process properties or characteristics associated with industrial devices (e.g., mechanical latency, process cycle times, operating schedules, etc., associated with industrial devices), human behavior or interaction in connection with the industrial automation system (e.g., maintenance schedules, shift-specific or operator-specific behavior or interaction of operators with the industrial automation system), production or process flows of the industrial automation system at particular times or in connection with particular projects, and/or other aspects or features of the industrial automation system.

(105) At **1104**, a simulation model that can simulate the industrial automation system can be generated based on the simulation or emulation of the industrial automation system. The simulation generator component can generate a simulation model that can simulate the industrial automation system based on the respective simulations or emulations of the various portions (e.g., industrial devices, software, firmware, etc.) of the industrial automation system. For example, the simulation generator component use the simulation or emulation of the industrial automation system, including the simulations or emulations of the respective industrial devices, software and/or firmware configurations, network devices, functional and communicative relationships between industrial devices or processes, mechanical or process properties or characteristics, human behavior or interaction in connection with the industrial automation system, production or process flows of the industrial automation system at particular times or in connection with particular projects, to facilitate generating the simulation model for the industrial automation system.

(106) FIG. **12** depicts a flow diagram of an example method **1200** that can facilitate simulating an industrial automation system of a set of industrial automation systems based on cloud-based data relating to the set of industrial automation systems, in accordance with various aspects and embodiments of the disclosed subject matter. The method **1200** can be implemented by a simulation generation system that can comprise a simulation generator component and/or another component(s) (e.g., a collection component, a cloud-based data store, etc.).

(107) At **1202**, a set of data relating to a set of industrial automation systems comprising one or more industrial automation systems can be collected. The simulation generation system can comprise a collection component that can collect the set of data relating to the set of industrial automation systems. The set of data can comprise data relating to industrial devices, assets, industrial processes, and network devices, associated with the one or more industrial automation systems of the set of industrial automation systems. The set of industrial automation systems can be associated with one or more industrial enterprises.

(108) In some implementations, all or part of the simulation generation system can be located in a cloud platform. For example, simulation generator component, the collection component, data store (e.g., cloud-based data store), and/or another component(s) of the simulation generation system can be located in the cloud platform. In other implementations, certain components (e.g., simulation generator component or collection component) can be located outside of the cloud platform and can access the cloud platform (e.g., the data store in the cloud platform) to facilitate analyzing the data in the data store to facilitate simulating an industrial automation system of the set of industrial automation systems.

(109) At **1204**, the set of data can be stored in a data store. The collection component can facilitate

storing the set of data in the data store, wherein the data store can be a cloud-based data store located in the cloud platform.

(110) At **1206**, the set of data can be analyzed. The simulation generator component can access the cloud-based data store and can retrieve, obtain, read the set of data from the cloud-based data store. The simulator generator component can analyze the set of data (e.g., perform big data analysis on the set of data) to facilitate simulating the industrial automation system. The simulation generator component can analyze the set of data to facilitate identifying or determining industrial devices, industrial processes, operating systems, software (e.g., software type, software version, software functions, software manufacturer, etc.), firmware (e.g., firmware type, firmware version, firmware functions, firmware manufacturer, etc.), network devices, etc., associated with the industrial automation system; identifying or determining configuration of the industrial devices, industrial processes, operating systems, software, firmware, and network devices, including the functional relationships or connections between respective industrial devices, industrial processes, operating systems, software, firmware, and network devices; respective properties or characteristics associated with the respective industrial devices, industrial processes, operating systems, software, firmware, and network devices; etc.

(111) At **1208**, the industrial automation system, comprising the industrial devices, industrial processes, operating systems, software, firmware, network devices, etc., can be simulated or emulated based on the results of the analysis of the set of data. The simulation generator component can simulate or emulate the industrial automation system, including simulating or emulating the industrial devices, software and/or firmware configurations (including software or firmware revisions or updates) associated with the industrial devices and/or other components of the industrial automation system, network-related devices (e.g., communication devices, computers, routers, etc.) associated with the industrial automation system, functional and communicative relationships between industrial devices, industrial processes, network-related devices, etc. (e.g., communication connections or conditions between industrial devices, types of connections between industrial devices, communication connections between industrial devices and network-related devices, etc.), mechanical or process properties or characteristics associated with industrial devices (e.g., mechanical latency, process cycle times, operating schedules, etc., associated with industrial devices), properties or characteristics associated with the network-related devices (e.g., communication conditions, total bandwidth, available bandwidth, wireless communications, wireline communications, etc., associated with the network-related devices), human behavior or interaction in connection with the industrial automation system (e.g., maintenance schedules, shift-specific or operator-specific behavior or interaction of operators with the industrial automation system), production or process flows of the industrial automation system at particular times or in connection with particular projects, and/or other aspects or features of the industrial automation system.

(112) In some implementations, a subset of the data can relate to operation of a portion (e.g., industrial device, industrial process, software, firmware, network-related device, etc.) of a second industrial automation system of the set of industrial automation systems. The simulation generator component can analyze the subset of the data to facilitate simulating or emulating a same or similar portion of the industrial automation system. For example, the portion of the second industrial automation system can be an industrial device, wherein the industrial automation system can comprise a same or similar industrial device. The simulation generator component can analyze the subset of the data, and/or another subset of the set of data (e.g., data relating to the same or similar industrial device of the industrial automation system), and can simulate or emulate the industrial device based on the analysis of the subset of the data and/or the other subset of the data.

(113) At **1210**, a simulation model that can simulate the industrial automation system can be generated based on the simulation or emulation of the respective portions (e.g., industrial devices, industrial processes, software, firmware, network-related devices, etc.) of the industrial automation

system. The simulation generator component can generate the simulation model, which can simulate the operation of the industrial automation system (e.g., in response to applied input data relating to operation of the industrial automation system) based on the simulation or emulation of the respective portions (e.g., industrial devices, industrial processes, software, firmware, network-related devices, etc.) associated with the industrial automation system.

(114) At this point, the method **1200** can proceed to reference point A, wherein the generated simulation model can be used to facilitate evaluating modifications to the industrial automation system that are being considered, determining whether a modification is to be made to an industrial automation system, and/or other features or aspects of the disclosed subject matter, such as those features and aspects of the disclosed subject matter described herein with regard to method **1300**, method **1400**, method **1500**, method **1600**, and/or method **1700**.

(115) Information relating to the simulation model can be stored in the cloud-based data store or another desired data store, wherein the simulation generator component can access the simulation model from the cloud-based data store or other data store, and can use the simulation model to simulate operation of the associated industrial automation system, for example, in response to application of data, such as operational data relating to the industrial automation system, to the simulation model.

(116) FIG. **13** presents a flow diagram of an example method **1300** that can facilitate simulating a modification to an industrial automation system of a set of industrial automation systems based on cloud-based data relating to the set of industrial automation systems, in accordance with various aspects and embodiments of the disclosed subject matter. The method **1300** can be implemented by a simulation generation system that can comprise a simulation generator component and/or another component(s) (e.g., a collection component, a cloud-based data store, etc.). In some implementations, the method **1300** can proceed from reference point A of method **1200**, wherein a simulation model that can simulate an industrial automation system has been generated, in accordance with the method **1500**.

(117) At **1302**, a request to evaluate a modification to the industrial automation system can be received. The simulation generator component can receive a request to evaluate a modification to the industrial automation system that is being considered. The modification can relate to a change of an industrial device or a change of a configuration of an industrial device, a change of an industrial process, a change or update of software, a change or update of firmware, and/or a change of a network-related device or a change of a configuration of a network-related device, etc., associated with the industrial automation system.

(118) At **1304**, a subset of modification data relating to the modification of the industrial automation system can be obtained from the data store (e.g., cloud-based data store). A subset of modification data relating to the modification can be stored in the cloud-based data store and/or the simulation generator component can generate a subset of modification data relating to the modification. The subset of modification data can comprise, for example, information relating to the functions, features, characteristics, properties, etc., of the object (e.g., industrial device, industrial process, software, firmware, network-related device, etc.) associated with the modification.

(119) At **1306**, the subset of the modification data relating to the modification can be analyzed. The simulation generator component can analyze the subset of the modification data in connection with the simulation model associated with the industrial automation system (e.g., as generated using the method **1200**) to facilitate simulating or emulating the modification in connection with generating a modified simulation model of the industrial automation system as modified based on the modification.

(120) At **1308**, the modification to the industrial automation system can be simulated or emulated in connection with the simulation model based on the results of the analysis of the subset of the modification data relating to the modification. The simulation generator component can simulate or

emulate the modification to the industrial automation system based on the results of the analysis of the subset of the modification data. For instance, the simulation generator component can simulate or emulate the modification to the industrial automation system, including simulating or emulating the interrelationship of the modification with the other portions of the industrial automation system. (121) At **1310**, a modified simulation model of the modified industrial automation system can be generated based on the simulation model of the industrial automation system as modified based on the simulation or emulation of the modification. The simulation generator component can generate the modified simulation model of the industrial automation system as modified based on the simulation or emulation of the modification.

(122) At this point, the method **1300** can proceed to reference point B, wherein, for example, the modified simulation model of the modified industrial automation system can be used to facilitate determining whether the modification is to be made to the industrial automation system (e.g., in accordance with method **1400**, method **1500**, or method **1600**).

(123) FIG. **14** presents a flow diagram of an example method **1400** that can facilitate determining whether to modify an industrial automation system based on the modified simulation model associated with the industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter. The method **1400** can be implemented by a simulation generation system that can comprise a simulation generator component and/or another component(s) (e.g., a collection component, a cloud-based data store, etc.). In some implementations, the method **1400** can proceed from reference point B of method **1300**, wherein a modified simulation model that can simulate a modified industrial automation system can be generated (e.g., based on the subset of modification data relating to the modification, which can be stored in the cloud-based data store), for example, in accordance with the method **1300**.

(124) At **1402**, a response or behavior of the industrial automation system can be determined or predicted based on the simulation model of the industrial automation system. The simulation generator component can determine or predict a response or behavior of the industrial automation system, or a portion thereof, based on the simulation model (e.g., as generated in accordance with the method **1200**). For example, the simulator generator component can apply a set of operation data (e.g., real or simulated operation data) relating to operation of the industrial automation system to the simulation model. The simulator generator component can analyze the simulated operation of the simulation model and can determine or predict the response or behavior of the industrial automation system, or a portion thereof, based on the simulated operation of the simulation model via application of the set of operation data to the simulation model.

(125) At **1404**, a response or behavior of the modified industrial automation system can be determined or predicted based on the modified simulation model of the modified industrial automation system. The simulation generator component can determine or predict the response or behavior of the modified industrial automation system, or a portion thereof, based on the modified simulation model. For example, the simulator generator component can apply the set of operation data relating to operation of the modified industrial automation system to the modified simulation model. The simulator generator component can analyze the simulated operation of the modified simulation model and can determine or predict the response or behavior of the modified industrial automation system, or a portion thereof, based on the simulated operation of the modified simulation model via application of the set of operation data to the modified simulation model.

(126) At **1406**, the determined or predicted response or behavior of the modified industrial automation system can be compared to the determined or predicted response or behavior of the industrial automation system (without modification). The simulator generator component can compare the determined or predicted response or behavior of the modified industrial automation system to the determined or predicted response or behavior of the industrial automation system (without modification).

(127) At **1408**, a difference(s) between the determined or predicted response or behavior of the

modified industrial automation system and the determined or predicted response or behavior of the industrial automation system (without modification) can be determined based on a result of the comparison of the determined or predicted response or behavior of the modified industrial automation system to the determined or predicted response or behavior of the industrial automation system (without modification). The simulator generator component can determine or identify the difference(s) between the determined or predicted response or behavior of the modified industrial automation system and the determined or predicted response or behavior of the industrial automation system (without modification). For example, the simulator generator component can determine or identify an improvement in operation of the industrial automation system based on the modification, a diminution of the performance of the industrial automation system based on the modification as compared to the performance of the industrial automation system without the modification, or another difference(s) between the determined or predicted response or behavior of the modified industrial automation system and the determined or predicted response or behavior of the industrial automation system (without modification).

(128) At **1410**, it can be determined whether the modification is to be made to the industrial automation system based on the difference(s) between the determined or predicted response or behavior of the modified industrial automation system and the determined or predicted response or behavior of the industrial automation system (without modification), in accordance with the set of defined operation criteria. The simulator generator component can determine whether the modification is to be made to the industrial automation system based on the difference(s) between the determined or predicted response or behavior of the modified industrial automation system and the determined or predicted response or behavior of the industrial automation system (without modification), in accordance with the set of defined operation criteria. For example, in response to determining that the modification to the industrial automation system is determined or predicted to result in a defined level of improvement in performance over the unmodified industrial automation system, in accordance with the set of defined operation criteria, the simulation generator component can determine that the modification is to or should be made to the industrial automation system, and can generate a report indicating that the modification to the industrial automation system is appropriate and/or recommended.

(129) FIG. **15** illustrates a flow diagram of another example method **1500** that can facilitate determining whether to modify an industrial automation system based on the modified simulation model associated with the industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter. The method **1500** can be implemented by a simulation generation system that can comprise a simulation generator component and/or another component(s) (e.g., a collection component, a cloud-based data store, etc.). In some implementations, the method **1500** can proceed from reference point B of method **1300**, wherein a modified simulation model that can simulate a modified industrial automation system can be generated, in accordance with the method **1300**.

(130) At **1502**, a set of historical operation data relating to the industrial automation system can be received, for example, from the cloud-based data store. The simulation generator component can access the cloud-based data store, and can obtain, retrieve, or read the set of historical operation data from the cloud-based data store.

(131) At **1504**, the set of historical operation data can be applied to the modified simulation model of the modified industrial automation system to facilitate generating a response by the modified simulation model based on (e.g., in response to application of) the set of historical operation data. The simulation generator component can apply the set of historical operation data to the modified simulation model. The modified simulation model can produce a response based on the applying of the set of historical operation data to the modified simulation model.

(132) At **1506**, the response of the modified industrial automation system to the applying of the set of historical operation data to the modified simulation model can be determined or predicted to

facilitate generating a set of response data. The simulation generator component can determine or predict the response or behavior of the modified industrial automation system, or a portion thereof, based on the applying of the set of historical operation data to the modified simulation model. For example, the simulator generator component can analyze the simulated operation of the modified simulation model in response to the applying of the set of historical operation data to the modified simulation model. Based in part on the results of this analysis, the simulator generator component can determine or predict the response or behavior of the modified industrial automation system, or a portion thereof, based on the simulated operation of the modified simulation model.

(133) At **1508**, a set of historical response data relating to the response of the industrial automation system to the set of historical operation data can be received, for example, from the cloud-based data store. The simulation generator component can access the cloud-based data store, and can obtain, retrieve, or read the set of historical response data from the cloud-based data store. The set of historical response data can be data relating to the response of the industrial automation system or a prior version of the industrial automation system to the set of historical operation data, for example.

(134) At **1510**, the set of response data associated with the simulation of the response of the modified industrial automation system can be compared to the set of historical response data. The simulation generator component can compare the set of response data associated with the simulation of the response of the modified industrial automation system to the set of historical response data to facilitate determining the difference between the responses.

(135) At **1512**, a difference(s) between the set of response data and the set of historical response data can be determined based on a result of the comparison of the set of response data to the set of historical response data. The simulator generator component can determine or identify the difference(s) between the set of response data and the set of historical response data based on the comparison result. For example, the simulator generator component can determine or identify an improvement in operation or response of the industrial automation system in connection with the application of the set of historical operation data based on the modification, a diminution of the performance of the industrial automation system in connection with the application of the set of historical operation data based on the modification as compared to the performance of the industrial automation system (or a prior version thereof) in response to the application of the set of historical operation data, or another difference(s) between the determined or predicted operation or response of the modified industrial automation system and the operation or response of the industrial automation system (or a prior version thereof) in response to the application of the set of historical operation data.

(136) At **1514**, it can be determined whether the modification is to be made to the industrial automation system based on the difference(s) between the set of response data and the set of historical response data can be determined based on the difference(s) between the set of response data and the set of historical response data, in accordance with the set of defined operation criteria. The simulator generator component can determine whether the modification is to be made to the industrial automation system based on the difference(s) between the set of response data and the set of historical response data can be determined based on the difference(s) between the set of response data and the set of historical response data, in accordance with the set of defined operation criteria. For example, in response to determining that the modification to the industrial automation system is determined or predicted to result in a defined level of improvement in performance over the unmodified industrial automation system, in accordance with the set of defined operation criteria, the simulation generator component can determine that the modification is to or should be made to the industrial automation system, and can generate a report indicating that the modification to the industrial automation system is appropriate and/or recommended.

(137) FIG. **16** depicts a flow diagram of another example method **1600** that can facilitate determining whether to modify an industrial automation system, and if so, which modification to

implement, based on respective modified simulation models associated with the industrial automation system, in accordance with various aspects and embodiments of the disclosed subject matter. The method **1600** can be implemented by a simulation generation system that can comprise a simulation generator component and/or another component(s) (e.g., a collection component, a cloud-based data store, etc.). In some implementations, the method **1600** can proceed from reference point B of method **1300**, wherein a modified simulation model that can simulate a modified industrial automation system (e.g., based on a first modification) can be generated, in accordance with the method **1300**. For instance, a first type of modification to the industrial automation system can be simulated or emulated and a first modified simulation model of the industrial automation system, if modified based on the first type of modification, can be generated, for example, in accordance with the method **1300**.

(138) At **1602**, a request to evaluate a second type of modification to the industrial automation system can be received. The simulation generator component can receive a request to evaluate a second type of modification to the industrial automation system that is being considered. The request can be part of the same request as that associated with the first type of modification or can be a separate request. The second type of modification can relate to a change of an industrial device or a change of a configuration of an industrial device, a change of an industrial process, a change or update of software, a change or update of firmware, and/or a change of a network-related device or a change of a configuration of a network-related device, etc., associated with the industrial automation system. The second type of modification can be a different type of modification than that of the first type of modification.

(139) A second subset of modification data relating to the second type of modification can be stored in the cloud-based data store and/or the simulation generator component can generate the second subset of modification data relating to the second type of modification. The second subset of modification data can comprise, for example, information relating to the functions, features, characteristics, properties, etc., of the object (e.g., industrial device, industrial process, software, firmware, network-related device, etc.) associated with the second type of modification.

(140) At **1604**, the second subset of the modification data relating to the second type of modification can be analyzed. The simulation generator component can analyze the second subset of the modification data in connection with the simulation model associated with the industrial automation system (e.g., as generated using the method **1200**) to facilitate simulating or emulating the second type of modification in connection with generating a second modified simulation model of the industrial automation system as modified based on the second type of modification.

(141) At **1606**, the second type of modification to the industrial automation system can be simulated or emulated in connection with the simulation model based on the results of the analysis of the second subset of the modification data relating to the second type of modification. The simulation generator component can simulate or emulate the second type of modification to the industrial automation system based on the results of the analysis of the second subset of the modification data.

(142) At **1608**, a second modified simulation model for the second modified industrial automation system can be generated based on the simulation model of the industrial automation system as modified based on the simulation or emulation of the second type of modification. The simulation generator component can generate the second modified simulation model of the industrial automation system as modified based on the simulation or emulation of the second type of modification.

(143) At **1610**, a response or behavior of the industrial automation system can be determined or predicted based on the simulation model of the industrial automation system. The simulation generator component can determine or predict a response or behavior of the industrial automation system, or a portion thereof, based on the simulation model (e.g., as generated in accordance with the method **1200**). For example, the simulator generator component can apply a set of operation

data (e.g., real or simulated operation data) relating to operation of the industrial automation system to the simulation model. The simulator generator component can analyze the simulated operation of the simulation model and can determine or predict the response or behavior of the industrial automation system, or a portion thereof, based on the simulated operation of the simulation model via application of the set of operation data to the simulation model.

(144) At **1612**, a response or behavior of the first modified industrial automation system can be determined or predicted based on the first modified simulation model for the first modified industrial automation system being considered. The simulation generator component can determine or predict the response or behavior of the first modified industrial automation system, or a portion thereof, based on the first modified simulation model. For example, the simulator generator component can apply the set of operation data relating to operation of the first modified industrial automation system to the first modified simulation model. The simulator generator component can analyze the simulated operation of the first modified simulation model and can determine or predict the response or behavior of the first modified industrial automation system, or a portion thereof, based on the simulated operation of the first modified simulation model via application of the set of operation data to the first modified simulation model.

(145) At **1614**, a response or behavior of the second modified industrial automation system can be determined or predicted based on the second modified simulation model for the second modified industrial automation system being considered. The simulation generator component can determine or predict the response or behavior of the second modified industrial automation system, or a portion thereof, based on the second modified simulation model. For example, the simulator generator component can apply the set of operation data relating to operation of the second modified industrial automation system to the second modified simulation model. The simulator generator component can analyze the simulated operation of the second modified simulation model and can determine or predict the response or behavior of the second modified industrial automation system, or a portion thereof, based on the simulated operation of the second modified simulation model via application of the set of operation data to the second modified simulation model.

(146) At **1616**, the respective responses associated with the simulation model, the first modified simulation model, and the second modified simulation model can be evaluated (e.g., compared against each other). The simulator generator component can evaluate or compare the respective responses in relation to each other to facilitate determining whether any modification is to be made and/or determining which modification is to be made if a modification is to be made.

(147) At **1618**, a determination can be made regarding whether to modify the industrial automation system based on the results of the evaluation of the respective responses associated with the simulation model, the first modified simulation model, and the second modified simulation model, in accordance with the set of defined operation criteria. The simulator generator component can determine whether to modify the industrial automation system based on the results of the evaluation of the respective responses.

(148) If it is determined that the industrial automation system is not to be or should not be modified, at **1620**, a report can be generated, wherein the report can indicate that the industrial automation system is not to be or should not be modified. The simulator generator component can generate the report indicating that the industrial automation system is not to be or should not be modified in response to determining that the industrial automation system is not to be or should not be modified. For example, the simulator generator component can determine that neither the first type of modification or second type of modification satisfy the set of defined operation criteria relating to modifications of the industrial automation system, and, as a result, no modification of the industrial automation system is to be performed. The simulator generator component can generate and provide (e.g., communicate) a report that can indicate that the industrial automation system is not to be or should not be modified.

(149) If, at **1618**, it is determined that the industrial automation system is to be or should be

modified, at **1622**, a determination can be made regarding which of the first type of modification, the second type of modification, or a combination of the first type of modification and the second type of modification, is to be made or should be made to the industrial control system based on the evaluation results and the set of defined operation criteria. The simulator generator component can determine which of the first type of modification, the second type of modification, or the combination of the first type of modification and the second type of modification, is to be made or should be made to the industrial control system based on the evaluation results and the set of defined operation criteria.

(150) At **1624**, a report can be generated, wherein the report can indicate which of the first type of modification, the second type of modification, or the combination of the first type of modification and the second type of modification, is to be made or should be made to the industrial control system. The simulator generator component can generate the report indicating that the industrial automation system is to be or should be modified, and indicating which of the first type of modification, the second type of modification, or a combination of the first type of modification and the second type of modification, is to be made or should be made to the industrial control system. For example, the simulator generator component can determine that the first type of modification satisfies the set of defined operation criteria and the first type of modification is preferred over the second type of modification (e.g., the first type of modification is determined or predicted to result in better performance of the industrial automation system than if the second type of modification were to be made to the industrial automation system). In such instance, the simulator generator component can generate and provide (e.g., communicate) a report that can indicate that the industrial automation system is to be or should be modified based on the first type of modification.

(151) In some implementations, when appropriate, a simulation model of the combination of the first type of modification and the second type of modification to the industrial automation system can be generated and evaluated (e.g., by the simulator generator component) in relation to the other simulation models. The simulator generator component can determine whether there is to be no modification, a modification based on the first type of modification, a modification based on the second type of modification, a modification based on a combination of the first type of modification and the second type of modification, or a modification based on a combination of a different subset of modifications, based on the results of the evaluation, in accordance with the set of defined operation criteria.

(152) FIG. **17** presents a flow diagram of another example method **1700** that can simulate production associated with a work order, based on a simulation model of an industrial automation system, to facilitate determining or predicting a response of the industrial automation system during production associated with the work order, in accordance with various aspects and embodiments of the disclosed subject matter. The method **1700** can be implemented by a simulation generation system that can comprise a simulation generator component and/or another component(s) (e.g., a collection component, a cloud-based data store, etc.). In some implementations, the method **1700** can proceed from reference point A of method **1200**, wherein a simulation model that can simulate the industrial automation system can be generated, in accordance with the method **1200**.

(153) At **1702**, information relating to a work order can be received. The simulation generator component can receive a work order and/or information relating to the work order. The information can indicate various aspects or parameters relating to the work order, such as, for example, the type of product to be produced by the industrial automation system, the amount of product to be produced or number of pieces of the product to be produced, the start date or time for production of the product, the end date or time for completion of the production of the product, properties or characteristics associated with the product, components of the product, etc. If the information relating to the work order is not in condition for use to facilitate simulating operation of the

industrial automation system using the corresponding simulation model, the simulator generator component can analyze and process the information relating to the work order (e.g., normalize or format work-order information, identify work-order parameters, etc.) to generate operation data relating to the work order that can be used with the simulation model to facilitate simulating processing of the work order by the industrial automation system.

(154) At **1704**, the operation data relating to the work order can be applied to the simulation model that can simulate or emulate the industrial automation system. The simulation generator component can apply the operation data relating to the work order to the simulation model to facilitate determining or predicting how the industrial automation system will respond if or when it processes the work order.

(155) At **1706**, a response of the simulation model to the applying of the operation data to the simulation model can be generated. The simulation generator component can generate a response (e.g., simulation response data) of the simulation model of the industrial automation system in response to the applying of the operation data to the simulation model.

(156) At **1708**, a response or behavior of the industrial automation system in connection with processing the work order can be determined or predicted based on the response of the simulation model. The simulation generator component can determine or predict a response or behavior of the industrial automation system in connection with processing the work order based on the response of the simulation model to the applying of the operation data relating to the work order.

(157) At **1710**, the determined or predicted response or behavior of the industrial automation system can be analyzed in connection with the information associated with the work order that relates to order completion parameters (e.g., time constraints (e.g., production start date, intermediate order deadline(s), order completion deadline, etc.), fiscal constraints (e.g., production cost constraints, profit constraints, constraints relating to the cost of operating the industrial automation system to process the work order, etc.), product quality constraints (e.g., product or material quality constraints, engineering or error tolerances, etc.), etc.) based on the set of defined operation criteria. The simulation generator component can analyze the determined or predicted response or behavior of the industrial automation system to facilitate determining whether the industrial automation system can satisfy the order completion parameters based on the set of defined operation criteria, wherein the criteria can comprise or relate to preferences or requirements of the purchaser and/or preferences or requirements of the industrial enterprise entity associated with the industrial automation system.

(158) At **1712**, a determination can be made regarding whether the industrial automation system can process and complete the work order to satisfy the order completion parameters based on the results of the analysis and the set of defined operation criteria. The simulation generator component can determine whether the industrial automation system can process and complete the work order to satisfy the order completion parameters based on the results of the analysis and the set of defined operation criteria. For example, the simulation generator component can determine that the industrial automation system can adequately or acceptably process and complete production relating to the work order if it is determined that the industrial automation system can satisfy the order completion parameters in processing and completing production on the work order in accordance with the set of defined operation criteria. If the simulator generator component determines that the industrial automation system is not able, or is not expected to be able, to satisfy the order completion parameters in processing and completing production on the work order, the simulator generator component can determine that the industrial automation system is not able to, or is not expected to be able to, adequately or acceptably process and complete production relating to the work order in accordance with the set of defined operation criteria.

(159) At **1714**, a report, which can indicate whether the industrial automation system can process and complete the work order to satisfy the order completion parameters in accordance with the set of defined operation criteria, can be generated. The simulation generator component can generate

the report and can provide (e.g., transmit) the report as an output for review or analysis by another component associated with the industrial enterprise or by an operator or manager.

(160) Embodiments, systems, and components described herein, as well as industrial control systems and industrial automation environments in which various aspects set forth in the subject specification can be carried out, can include computer or network components such as servers, clients, programmable logic controllers (PLCs), automation controllers, communications modules, mobile computers, wireless components, control components and so forth which are capable of interacting across a network. Computers and servers include one or more processors—electronic integrated circuits that perform logic operations employing electric signals—configured to execute instructions stored in media such as random access memory (RAM), read only memory (ROM), a hard drives, as well as removable memory devices, which can include memory sticks, memory cards, flash drives, external hard drives, and so on.

(161) Similarly, the term PLC or automation controller as used herein can include functionality that can be shared across multiple components, systems, and/or networks. As an example, one or more PLCs or automation controllers can communicate and cooperate with various network devices across the network. This can include substantially any type of control, communications module, computer, Input/Output (I/O) device, sensor, actuator, and human machine interface (HMI) that communicate via the network, which includes control, automation, and/or public networks. The PLC or automation controller can also communicate to and control various other devices such as I/O modules including analog, digital, programmed/intelligent I/O modules, other programmable controllers, communications modules, sensors, actuators, output devices, and the like.

(162) The network can include public networks such as the internet, intranets, and automation networks such as control and information protocol (CIP) networks including DeviceNet, ControlNet, and Ethernet/IP. Other networks include Ethernet, DH/DH+, Remote I/O, Fieldbus, Modbus, Profibus, CAN, wireless networks, serial protocols, and so forth. In addition, the network devices can include various possibilities (hardware and/or software components). These include components such as switches with virtual local area network (VLAN) capability, LANs, WANs, proxies, gateways, routers, firewalls, virtual private network (VPN) devices, servers, clients, computers, configuration tools, monitoring tools, and/or other devices.

(163) In order to provide a context for the various aspects of the disclosed subject matter, FIGS. **18** and **19** as well as the following discussion are intended to provide a brief, general description of a suitable environment in which the various aspects of the disclosed subject matter can be implemented.

(164) With reference to FIG. **18**, an example environment **1800** for implementing various aspects of the aforementioned subject matter includes a computer **1812**. The computer **1812** includes a processing unit **1814**, a system memory **1816**, and a system bus **1818**. The system bus **1818** couples system components including, but not limited to, the system memory **1816** to the processing unit **1814**. The processing unit **1814** can be any of various available processors. Multi-core microprocessors and other multiprocessor architectures also can be employed as the processing unit **1814**.

(165) The system bus **1818** can be any of several types of bus structure(s) including the memory bus or memory controller, a peripheral bus or external bus, and/or a local bus using any variety of available bus architectures including, but not limited to, 8-bit bus, Industrial Standard Architecture (ISA), Micro-Channel Architecture (MSA), Extended ISA (EISA), Intelligent Drive Electronics (IDE), VESA Local Bus (VLB), Peripheral Component Interconnect (PCI), Universal Serial Bus (USB), Advanced Graphics Port (AGP), Personal Computer Memory Card International Association bus (PCMCIA), and Small Computer Systems Interface (SCSI).

(166) The system memory **1816** includes volatile memory **1820** and nonvolatile memory **1822**. The basic input/output system (BIOS), containing the basic routines to transfer information between elements within the computer **1812**, such as during start-up, is stored in nonvolatile memory **1822**.

By way of illustration, and not limitation, nonvolatile memory **1822** can include read only memory (ROM), programmable ROM (PROM), electrically programmable ROM (EPROM), electrically erasable PROM (EEPROM), or flash memory. Volatile memory **1820** includes random access memory (RAM), which acts as external cache memory. By way of illustration and not limitation, RAM is available in many forms such as synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), and direct Rambus RAM (DRRAM).

(167) Computer **1812** also includes removable/non-removable, volatile/non-volatile computer storage media. FIG. **18** illustrates, for example a disk storage **1824**. Disk storage **1824** includes, but is not limited to, devices like a magnetic disk drive, floppy disk drive, tape drive, Jaz drive, Zip drive, LS-100 drive, flash memory card, or memory stick. In addition, disk storage **1824** can include storage media separately or in combination with other storage media including, but not limited to, an optical disk drive such as a compact disk ROM device (CD-ROM), CD recordable drive (CD-R Drive), CD rewritable drive (CD-RW Drive) or a digital versatile disk ROM drive (DVD-ROM). To facilitate connection of the disk storage **1824** to the system bus **1818**, a removable or non-removable interface is typically used such as interface **1826**.

(168) It is to be appreciated that FIG. **18** describes software that acts as an intermediary between users and the basic computer resources described in suitable operating environment **1800**. Such software includes an operating system **1828**. Operating system **1828**, which can be stored on disk storage **1824**, acts to control and allocate resources of the computer **1812**. System applications **1830** take advantage of the management of resources by operating system **1828** through program modules **1832** and program data **1834** stored either in system memory **1816** or on disk storage **1824**. It is to be appreciated that one or more embodiments of the subject disclosure can be implemented with various operating systems or combinations of operating systems.

(169) A user enters commands or information into the computer **1812** through input device(s) **1836**. Input devices **1836** include, but are not limited to, a pointing device such as a mouse, trackball, stylus, touch pad, keyboard, microphone, joystick, game pad, satellite dish, scanner, TV tuner card, digital camera, digital video camera, web camera, and the like. These and other input devices connect to the processing unit **1814** through the system bus **1818** via interface port(s) **1838**. Interface port(s) **1838** include, for example, a serial port, a parallel port, a game port, and a universal serial bus (USB). Output device(s) **1840** use some of the same type of ports as input device(s) **1836**. Thus, for example, a USB port may be used to provide input to computer **1812**, and to output information from computer **1812** to an output device **1840**. Output adapters **1842** are provided to illustrate that there are some output devices **1840** like monitors, speakers, and printers, among other output devices **1840**, which require special adapters. The output adapters **1842** include, by way of illustration and not limitation, video and sound cards that provide a means of connection between the output device **1840** and the system bus **1818**. It should be noted that other devices and/or systems of devices provide both input and output capabilities such as remote computer(s) **1844**.

(170) Computer **1812** can operate in a networked environment using logical connections to one or more remote computers, such as remote computer(s) **1844**. The remote computer(s) **1844** can be a personal computer, a server, a router, a network PC, a workstation, a microprocessor based appliance, a peer device or other common network node and the like, and typically includes many or all of the elements described relative to computer **1812**. For purposes of brevity, only a memory storage device **1846** is illustrated with remote computer(s) **1844**. Remote computer(s) **1844** is logically connected to computer **1812** through a network interface **1848** and then physically connected via communication connection **1850**. Network interface **1848** encompasses communication networks such as local-area networks (LAN) and wide-area networks (WAN). LAN technologies include Fiber Distributed Data Interface (FDDI), Copper Distributed Data Interface (CDDI), Ethernet/IEEE 802.3, Token Ring/IEEE 802.5 and the like. WAN technologies include,

but are not limited to, point-to-point links, circuit switching networks like Integrated Services Digital Networks (ISDN) and variations thereon, packet switching networks, and Digital Subscriber Lines (DSL).

(171) Communication connection(s) **1850** refers to the hardware/software employed to connect the network interface **1848** to the system bus **1818**. While communication connection **1850** is shown for illustrative clarity inside computer **1812**, it can also be external to computer **1812**. The hardware/software necessary for connection to the network interface **1848** includes, for exemplary purposes only, internal and external technologies such as, modems including regular telephone grade modems, cable modems and DSL modems, ISDN adapters, and Ethernet cards.

(172) FIG. **19** is a schematic block diagram of a sample computing and/or networking environment **1900** with which the disclosed subject matter can interact. The computing and/or networking environment **1900** can include one or more clients **1902**. The client(s) **1902** can be hardware and/or software (e.g., threads, processes, computing devices). The computing and/or networking environment **1900** also can include one or more servers **1904**. The server(s) **1904** can also be hardware and/or software (e.g., threads, processes, computing devices). The servers **1904** can house threads to perform transformations by employing one or more embodiments as described herein, for example. One possible communication between a client **1902** and servers **1904** can be in the form of a data packet adapted to be transmitted between two or more computer processes. The computing and/or networking environment **1900** can include a communication framework **1906** that can be employed to facilitate communications between the client(s) **1902** and the server(s) **1904**. The client(s) **1902** are operably connected to one or more client data stores **1908** that can be employed to store information local to the client(s) **1902**. Similarly, the server(s) **1904** are operably connected to one or more server data stores **1910** that can be employed to store information local to the servers **1904**.

(173) What has been described above includes examples of the disclosed subject matter. It is, of course, not possible to describe every conceivable combination of components or methods for purposes of describing the disclosed subject matter, but one of ordinary skill in the art may recognize that many further combinations and permutations of the disclosed subject matter are possible. Accordingly, the disclosed subject matter is intended to embrace all such alterations, modifications, and variations that fall within the spirit and scope of the appended claims.

(174) In particular and in regard to the various functions performed by the above described components, devices, circuits, systems and the like, the terms (including a reference to a “means”) used to describe such components are intended to correspond, unless otherwise indicated, to any component which performs the specified function of the described component (e.g., a functional equivalent), even though not structurally equivalent to the disclosed structure, which performs the function in the herein illustrated exemplary aspects of the disclosed subject matter. In this regard, it will also be recognized that the disclosed subject matter includes a system as well as a computer-readable medium having computer-executable instructions for performing the acts and/or events of the various methods of the disclosed subject matter.

(175) In addition, while a particular feature of the disclosed subject matter may have been disclosed with respect to only one of several implementations, such feature may be combined with one or more other features of the other implementations as may be desired and advantageous for any given or particular application.

(176) Furthermore, to the extent that the terms “includes,” and “including” and variants thereof are used in either the detailed description or the claims, these terms are intended to be inclusive in a manner similar to the term “comprising.”

(177) In this application, the word “exemplary” is used to mean serving as an example, instance, or illustration. Any aspect or design described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects or designs. Rather, use of the word exemplary is intended to present concepts in a concrete fashion.

(178) Various aspects or features described herein may be implemented as a method, apparatus, or article of manufacture using standard programming and/or engineering techniques. The term “article of manufacture” as used herein is intended to encompass a computer program accessible from any computer-readable device, carrier, or media. For example, computer readable media can include but are not limited to magnetic storage devices (e.g., hard disk, floppy disk, magnetic strips . . .), optical disks [e.g., compact disk (CD), digital versatile disk (DVD) . . .], smart cards, and flash memory devices (e.g., card, stick, key drive . . .).

Claims

1. A system, comprising: a memory that stores computer-executable components; and a processor, operatively coupled to the memory, that executes computer-executable components, the computer-executable components comprising: a simulation generator component that, based on an analysis of a subset of a set of industrial data relating to a set of devices, comprising a first device and a second device, of an industrial automation system, simulates an interrelationship between the first device and the second device to facilitate simulation of the industrial automation system, and generates a simulation model that corresponds to the industrial automation system based on the simulation of the interrelationship between the first device and the second device, wherein the industrial automation system is controlled based on the simulation model.
2. The system of claim 1, wherein the interrelationship between the first device and the second device is a functional or communicative interrelationship between the first device and the second device.
3. The system of claim 1, wherein the computer-executable components comprise a collection component that receives the set of industrial data associated with the set of devices and stores the set of industrial data in a data store, and wherein at least one of the collection component, the simulation generator component, or the data store is part of a cloud platform.
4. The system of claim 3, wherein an industrial device is added to the industrial automation system to generate a modified industrial system, wherein the industrial device comprises a device model that is representative of functions or a configuration of the industrial device, wherein the simulation generator component or the collection component receives the device model from the industrial device or a cloud gateway component associated with the industrial device, and wherein the simulation generator component simulates the industrial device, based on the device model, and modifies the simulation model based on the simulation of the industrial device to generate a modified model that corresponds to the modified industrial system.
5. The system of claim 4, wherein the simulation generator component communicates a message, comprising message data, to the first device to inform the first device that the industrial device has been added to the industrial automation system.
6. The system of claim 4, wherein the device model comprises information relating to a device identifier associated with the industrial device, status information regarding a status of the industrial device, a firmware version of firmware associated with the industrial device, setup data associated with the industrial device, a warranty specification associated with the industrial device, a group of performance indicators associated with the industrial device, or health and diagnostic information associated with the industrial device.
7. The system of claim 3, wherein the computer-executable components comprise an interface component that interfaces the cloud platform with the cloud gateway component, wherein the cloud gateway component obtains the subset of industrial data from the first device or the second device, and wherein the collection component, the simulation generator component, or the data store receive the subset of industrial data from the cloud gateway component via the interface component.
8. The system of claim 7, wherein the first device is an industrial device, and at least one of the

cloud gateway component is integrated with the industrial device or the cloud gateway component is associated with the industrial device and the second device.

9. The system of claim 7, wherein the cloud gateway component determines a first location of the cloud gateway component or a second location of the first device associated with the cloud gateway component within a component topology associated with the industrial automation system, wherein the cloud platform receives, from the cloud gateway component via the interface component, location information that indicates the first location of the cloud gateway component or the second location of the first device within the component topology, and wherein the simulation generator component generates the simulation model based on a portion of the simulation relating to the first location of the cloud gateway component or the second location of the first device within the component topology.

10. The system of claim 1, wherein the first device is a first industrial device that is part of a first portion of the industrial automation system that is contained in a vehicle, and wherein the second device is a second industrial device that is part of a second portion of the industrial automation system that is contained in an industrial facility.

11. The system of claim 1, wherein the simulation generator component evaluates a response of the simulation model to an application of a set of operation data relating to a work order to the simulation model, determines an industrial system response of the industrial automation system based on the response of the simulation model to the application of the set of operation data, and determines whether the industrial automation system is able to satisfy a set of conditions associated with processing or completion of the work order based on a result of an evaluation of the industrial system response of the industrial automation system.

12. The system of claim 1, wherein the simulation generator component simulates a modification to the industrial automation system based on a set of data relating to the modification, generates a modified simulation model that corresponds to a modified industrial automation system that incorporates the modification to the industrial automation system based on the simulation of the modification, and determines whether the modification to the industrial automation system is to be performed based on the modified simulation model.

13. The system of claim 12, wherein the simulation generator component evaluates at least one of first response data relating to a modification response of the modified simulation model or second response data relating to a response of the simulation model, based on an application of a set of operation data to at least one of the modified simulation model or the simulation model, and determines whether the modification to the industrial automation system is to be performed based on a result of the evaluation of at least one of the first response data relating to the modification response of the modified simulation model or the second response data relating to the response of the simulation model.

14. The system of claim 13, wherein the simulation generator component compares the first response data relating to the modification response of the modified simulation model to the second response data relating to the response of the simulation model, determines a difference between the first response data and the second response data based on a comparison result of the comparison of the first response data and the second response data, and determines whether the modification to the industrial automation system is to be performed based on the difference between the first response data and the second response data, and wherein the result comprises the difference.

15. A method, comprising: simulating, by a system comprising a processor, an interrelationship between a first device and a second device of an industrial automation system, based on analyzing at least a portion of a set of industrial data associated with a set of devices, comprising the first device and the second device, of the industrial automation system, to facilitate generating a simulation model that corresponds to the industrial automation system; and controlling, by the system, the industrial automation system based on the simulation model.

16. The method of claim 15, further comprising: interfacing, by the system, a cloud platform with

the industrial automation system via at least one cloud gateway component associated with the set of devices; monitoring, by the system, the industrial automation system via the interfacing; based on the monitoring, receiving, by the system, the set of industrial data from the at least one cloud gateway component; and storing, by the system, the set of industrial data in a data store, wherein at least one of the monitoring, the receiving, the storing, the simulating, or the controlling is performed in the cloud platform.

17. The method of claim 15, further comprising: simulating, by the system, a modification to the industrial automation system based on a set of data relating to the modification to facilitate simulating a modified industrial automation system that comprises the modification; and generating, by the system, a modified simulation model that corresponds to the modified industrial automation system based on the simulating of the modified industrial automation system.

18. The method of claim 17, further comprising: evaluating, by the system, first response data relating to a modification response of the modified simulation model or second response data relating to a response of the simulation model in response to applying operation data to the modified simulation model or the simulation model; and determining, by the system, whether to implement the modification to the industrial automation system based on a result of the evaluating of the first response data relating to the modification response or the second response data relating to the response.

19. A non-transitory machine-readable medium storing computer-executable instructions that, in response to execution, cause a system comprising a processor to perform operations, comprising: simulating an interrelationship between a first device and a second device of an industrial automation system, based on analyzing at least a subset of a set of industrial data associated with a set of devices, comprising the first device and the second device, of the industrial automation system, to facilitate generating a simulation model that simulates the industrial automation system, wherein the subset of industrial data relates to the at least one device; and managing the industrial automation system based on the simulation model.

20. The non-transitory machine-readable medium of claim 19, wherein the operations further comprise: interfacing a cloud platform with the industrial automation system via at least one cloud gateway component associated with the set of devices; and receiving at least the subset of the set of industrial data from the at least one cloud gateway component, wherein at least one of the simulating, the managing, or the receiving is performed in the cloud platform.
