

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417593
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Vaish; Rajan et al.

Generating immersive augmented reality experiences from existing images and videos

Abstract

A two-dimensional element is identified from one or more two-dimensional images. A volumetric content item is generated based on the two-dimensional element identified from the one or more two-dimensional images. A display device presents the volumetric content item overlaid on a real-world environment that is within a field of view of a user of the display device.

Inventors: Vaish; Rajan (Beverly Hills, CA), Kratz; Sven (Mercer Island, WA), Monroy-Hernández; Andrés (Princeton, NJ), Smith; Brian Anthony (New York, NY)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008818289

Assignee: Snap Inc. (Santa Monica, CA)

Appl. No.: 18/170271

Filed: February 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240071008 A1	Feb. 29, 2024

Related U.S. Application Data

us-provisional-application US 63402914 20220831

Publication Classification

Int. Cl.: G06T19/00 (20110101); **G06T15/08** (20110101); **G06V10/26** (20220101); **G06V10/94** (20220101); **G06V20/20** (20220101)

U.S. Cl.:

CPC G06T19/006 (20130101); **G06T15/08** (20130101); **G06V10/26** (20220101); **G06V10/945** (20220101); **G06V20/20** (20220101); G06T2200/24 (20130101); G06V2201/10 (20220101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4807158	12/1988	Blanton et al.	N/A	N/A
6038295	12/1999	Mattes	N/A	N/A
6430997	12/2001	French et al.	N/A	N/A
6819982	12/2003	Doane	N/A	N/A
6980909	12/2004	Root et al.	N/A	N/A
7173651	12/2006	Knowles	N/A	N/A
7190496	12/2006	Klug et al.	N/A	N/A
7411493	12/2007	Smith	N/A	N/A
7535890	12/2008	Rojas	N/A	N/A
7542073	12/2008	Li et al.	N/A	N/A
8046719	12/2010	Skourup et al.	N/A	N/A
8131597	12/2011	Hudetz	N/A	N/A
8174562	12/2011	Hartman	N/A	N/A
8199747	12/2011	Rojas et al.	N/A	N/A
8274550	12/2011	Steuart, III	N/A	N/A
8332475	12/2011	Rosen et al.	N/A	N/A
8608563	12/2012	Miyazaki et al.	N/A	N/A
8646720	12/2013	Shaw	N/A	N/A
8718333	12/2013	Wolf et al.	N/A	N/A
8724622	12/2013	Rojas	N/A	N/A
8812954	12/2013	Shuster et al.	N/A	N/A
8874677	12/2013	Rosen et al.	N/A	N/A
8909679	12/2013	Root et al.	N/A	N/A
8934015	12/2014	Chi et al.	N/A	N/A
8995433	12/2014	Rojas	N/A	N/A
9040574	12/2014	Wang et al.	N/A	N/A
9055416	12/2014	Rosen et al.	N/A	N/A
9100806	12/2014	Rosen et al.	N/A	N/A
9100807	12/2014	Rosen et al.	N/A	N/A
9186548	12/2014	House et al.	N/A	N/A
9191776	12/2014	Root et al.	N/A	N/A
9204252	12/2014	Root	N/A	N/A

9235932	12/2015	Choi et al.	N/A	N/A
9344642	12/2015	Niemi et al.	N/A	N/A
9345711	12/2015	Friedhoff	N/A	N/A
9443227	12/2015	Evans et al.	N/A	N/A
9445081	12/2015	Kouperman et al.	N/A	N/A
9471059	12/2015	Wilkins	N/A	N/A
9489661	12/2015	Evans et al.	N/A	N/A
9489937	12/2015	Beard et al.	N/A	N/A
9491134	12/2015	Rosen et al.	N/A	N/A
9551873	12/2016	Zalewski	N/A	N/A
9576369	12/2016	Venkataraman et al.	N/A	N/A
9582166	12/2016	Vaittinen et al.	N/A	N/A
9586147	12/2016	Bathiche et al.	N/A	N/A
9589448	12/2016	Schneider et al.	N/A	N/A
9681046	12/2016	Adsumilli et al.	N/A	N/A
9703369	12/2016	Mullen	N/A	N/A
9723272	12/2016	Lu et al.	N/A	N/A
9747901	12/2016	Gentry	N/A	N/A
9761057	12/2016	Salter et al.	N/A	N/A
9779538	12/2016	Sanders et al.	N/A	N/A
9794527	12/2016	Balez et al.	N/A	N/A
9818225	12/2016	Wang et al.	N/A	N/A
9916673	12/2017	Castro et al.	N/A	N/A
9922659	12/2017	Bradlow et al.	N/A	N/A
9989965	12/2017	Cuban et al.	N/A	N/A
10061328	12/2017	Canoy et al.	N/A	N/A
10109224	12/2017	Ratti et al.	N/A	N/A
10140987	12/2017	Erickson et al.	N/A	N/A
10168700	12/2018	Gordon et al.	N/A	N/A
10282903	12/2018	Clark et al.	N/A	N/A
10289193	12/2018	Hardy et al.	N/A	N/A
10313481	12/2018	Kada	N/A	N/A
10325410	12/2018	Smith et al.	N/A	N/A
10365784	12/2018	Inomata	N/A	N/A
10370118	12/2018	Nielsen et al.	N/A	N/A
10403050	12/2018	Beall et al.	N/A	N/A
10445925	12/2018	Tokubo	N/A	N/A
10445940	12/2018	Guay et al.	N/A	N/A
10482665	12/2018	Copic et al.	N/A	N/A
10501180	12/2018	Yu	N/A	N/A
10504277	12/2018	Haitani et al.	N/A	N/A
10581940	12/2019	Iyer et al.	N/A	N/A
10599286	12/2019	Inomata	N/A	N/A
10616663	12/2019	Davisson et al.	N/A	N/A
10768639	12/2019	Meisenholder et al.	N/A	N/A
10768776	12/2019	Roche et al.	N/A	N/A
10796489	12/2019	Cordes et al.	N/A	N/A
10819946	12/2019	Tanumihardja et al.	N/A	N/A
10901215	12/2020	Newcombe et al.	N/A	N/A

10921878	12/2020	Noris et al.	N/A	N/A
10937239	12/2020	Huston et al.	N/A	N/A
11006095	12/2020	Holzer et al.	N/A	N/A
11051049	12/2020	Bustamante et al.	N/A	N/A
11062517	12/2020	Crews et al.	N/A	N/A
11094127	12/2020	Mccall	N/A	N/A
11126206	12/2020	Meisenholder et al.	N/A	N/A
11145123	12/2020	Chor	N/A	G06F 3/147
11156830	12/2020	Johnson et al.	N/A	N/A
11163358	12/2020	Marks et al.	N/A	N/A
11194439	12/2020	Laaksonen et al.	N/A	N/A
11200028	12/2020	Newell et al.	N/A	N/A
11200742	12/2020	Post et al.	N/A	N/A
11302077	12/2021	Kang et al.	N/A	N/A
11361473	12/2021	Abdollahian et al.	N/A	N/A
11372474	12/2021	Schweet et al.	N/A	N/A
11413514	12/2021	Marty et al.	N/A	N/A
11436806	12/2021	Katz	N/A	N/A
11468605	12/2021	Corson	N/A	N/A
11481423	12/2021	Singleton	N/A	N/A
11481980	12/2021	Yerli	N/A	N/A
11495004	12/2021	Henry	N/A	N/A
11521359	12/2021	Noorkami et al.	N/A	N/A
11623138	12/2022	Yeh et al.	N/A	N/A
11734905	12/2022	Henry	N/A	N/A
11769299	12/2022	Stehlik et al.	N/A	N/A
11810259	12/2022	Ramani et al.	N/A	N/A
11847749	12/2022	Lebeaupin et al.	N/A	N/A
11941764	12/2023	Harding et al.	N/A	N/A
11972521	12/2023	Vaish et al.	N/A	N/A
12267482	12/2024	Vaish et al.	N/A	N/A
2004/0135890	12/2003	Kaneko et al.	N/A	N/A
2006/0287025	12/2005	French	N/A	N/A
2007/0167689	12/2006	Ramadas et al.	N/A	N/A
2007/0250526	12/2006	Hanna	N/A	N/A
2008/0081676	12/2007	Chakraborty et al.	N/A	N/A
2008/0158256	12/2007	Russell et al.	N/A	N/A
2008/0168411	12/2007	Mang et al.	N/A	N/A
2008/0186255	12/2007	Cohen et al.	N/A	N/A
2008/0211771	12/2007	Richardson	N/A	N/A
2008/0255842	12/2007	Simhi	N/A	N/A
2009/0122133	12/2008	Hartman	N/A	N/A
2009/0171902	12/2008	Maclaurin et al.	N/A	N/A
2009/0187389	12/2008	Dobbins et al.	N/A	N/A
2009/0213114	12/2008	Dobbins et al.	N/A	N/A
2010/0026809	12/2009	Curry	N/A	N/A
2010/0125799	12/2009	Roberts et al.	N/A	N/A
2010/0185984	12/2009	Wright et al.	N/A	N/A
2010/0260422	12/2009	Ito et al.	N/A	N/A
2011/0179313	12/2010	Macdonald et al.	N/A	N/A

2011/0202598	12/2010	Evans et al.	N/A	N/A
2011/0214082	12/2010	Osterhout et al.	N/A	N/A
2011/0242134	12/2010	Miller et al.	N/A	N/A
2011/0261083	12/2010	Wilson	N/A	N/A
2012/0052947	12/2011	Yun	N/A	N/A
2012/0131125	12/2011	Seidel et al.	N/A	N/A
2012/0188452	12/2011	Keiser et al.	N/A	N/A
2012/0194420	12/2011	Osterhout et al.	N/A	N/A
2012/0209924	12/2011	Evans et al.	N/A	N/A
2012/0263154	12/2011	Blanchflower et al.	N/A	N/A
2012/0281885	12/2011	Syrdal et al.	N/A	N/A
2012/0287274	12/2011	Bevirt	N/A	N/A
2012/0320169	12/2011	Bathiche	N/A	N/A
2013/0056581	12/2012	Sparks	N/A	N/A
2013/0072296	12/2012	Miyazaki et al.	N/A	N/A
2013/0083009	12/2012	Geisner et al.	N/A	N/A
2013/0083173	12/2012	Geisner et al.	N/A	N/A
2013/0162632	12/2012	Varga et al.	N/A	N/A
2013/0238168	12/2012	Reyes	N/A	N/A
2014/0013228	12/2013	Hutten	N/A	N/A
2014/0038708	12/2013	Davison et al.	N/A	N/A
2014/0254896	12/2013	Zhou et al.	N/A	N/A
2014/0285522	12/2013	Kim	345/633	G06Q 30/0601
2014/0357366	12/2013	Koganezawa et al.	N/A	N/A
2014/0368542	12/2013	Tawara	345/633	G06T 19/006
2015/0015486	12/2014	Osman et al.	N/A	N/A
2015/0015608	12/2014	Park	345/633	G06F 3/012
2015/0016777	12/2014	Abovitz et al.	N/A	N/A
2015/0022432	12/2014	Stewart et al.	N/A	N/A
2015/0035862	12/2014	Fischer et al.	N/A	N/A
2015/0070272	12/2014	Kim et al.	N/A	N/A
2015/0175263	12/2014	Reyes	N/A	N/A
2015/0193979	12/2014	Grek	N/A	N/A
2015/0199022	12/2014	Gottesman et al.	N/A	N/A
2015/0287246	12/2014	Huston et al.	N/A	N/A
2015/0331490	12/2014	Yamada	N/A	N/A
2015/0355711	12/2014	Rihn	N/A	N/A
2015/0362917	12/2014	Wang et al.	N/A	N/A
2015/0363034	12/2014	Hinckley et al.	N/A	N/A
2016/0004390	12/2015	Laska et al.	N/A	N/A
2016/0027218	12/2015	Salter et al.	N/A	N/A
2016/0049003	12/2015	Shuster et al.	N/A	N/A
2016/0063987	12/2015	Xu et al.	N/A	N/A
2016/0071548	12/2015	House et al.	N/A	N/A
2016/0133230	12/2015	Daniels et al.	N/A	N/A
2016/0161946	12/2015	Wuth Sepulveda et al.	N/A	N/A
2016/0179096	12/2015	Bradlow et al.	N/A	N/A

2016/0217623	12/2015	Singh	N/A	G09G 5/00
2016/0292575	12/2015	Weast et al.	N/A	N/A
2016/0292886	12/2015	Erad et al.	N/A	N/A
2016/0307335	12/2015	Perry et al.	N/A	N/A
2016/0307573	12/2015	Wobrock	N/A	N/A
2016/0330532	12/2015	Bostick et al.	N/A	N/A
2016/0336020	12/2015	Bradlow et al.	N/A	N/A
2016/0350973	12/2015	Shapira et al.	N/A	N/A
2016/0357258	12/2015	Yeom et al.	N/A	N/A
2017/0031369	12/2016	Liu et al.	N/A	N/A
2017/0061700	12/2016	Urbach et al.	N/A	N/A
2017/0084051	12/2016	Weising et al.	N/A	N/A
2017/0094259	12/2016	Kouperman et al.	N/A	N/A
2017/0099424	12/2016	Jones	N/A	N/A
2017/0102699	12/2016	Anderson	N/A	N/A
2017/0177925	12/2016	Volkart	N/A	N/A
2017/0208103	12/2016	Sarmova	N/A	N/A
2017/0225796	12/2016	Sun et al.	N/A	N/A
2017/0228690	12/2016	Kohli	N/A	N/A
2017/0237940	12/2016	Chaney et al.	N/A	N/A
2017/0244937	12/2016	Meier et al.	N/A	N/A
2017/0256040	12/2016	Grauer	N/A	N/A
2017/0266554	12/2016	Marks et al.	N/A	N/A
2017/0269685	12/2016	Marks et al.	N/A	N/A
2017/0320564	12/2016	Kuzikov	N/A	N/A
2017/0323481	12/2016	Tran et al.	N/A	N/A
2017/0324841	12/2016	Clement et al.	N/A	N/A
2017/0337791	12/2016	Gordon-carroll	N/A	N/A
2017/0359624	12/2016	Englert et al.	N/A	N/A
2017/0364153	12/2016	Kazansky et al.	N/A	N/A
2017/0365098	12/2016	Auten et al.	N/A	N/A
2017/0365102	12/2016	Huston et al.	N/A	N/A
2017/0371353	12/2016	Millinger, III	N/A	N/A
2018/0005429	12/2017	Osman et al.	N/A	N/A
2018/0059783	12/2017	Van Hoff et al.	N/A	N/A
2018/0082682	12/2017	Erickson et al.	N/A	N/A
2018/0098059	12/2017	Valdivia et al.	N/A	N/A
2018/0130257	12/2017	Moran	N/A	N/A
2018/0154232	12/2017	Gentil	N/A	N/A
2018/0190033	12/2017	Barnett	N/A	G06N 20/00
2018/0246529	12/2017	Hu et al.	N/A	N/A
2018/0270427	12/2017	Damstra et al.	N/A	N/A
2018/0288364	12/2017	Virhia	N/A	N/A
2018/0311585	12/2017	Osman	N/A	N/A
2018/0329486	12/2017	Williams et al.	N/A	N/A
2019/0005546	12/2018	Chen	N/A	G06Q 30/0267
2019/0005728	12/2018	Leppanen et al.	N/A	N/A
2019/0011921	12/2018	Wang et al.	N/A	N/A
2019/0054379	12/2018	Ackley et al.	N/A	N/A

2019/0073831	12/2018	Kim	N/A	N/A
2019/0073832	12/2018	Kim	N/A	N/A
2019/0130599	12/2018	Gebbie et al.	N/A	N/A
2019/0130631	12/2018	Gebbie et al.	N/A	N/A
2019/0138260	12/2018	Rogers et al.	N/A	N/A
2019/0138463	12/2018	Kurata et al.	N/A	N/A
2019/0172265	12/2018	Cossairt et al.	N/A	N/A
2019/0180509	12/2018	Laaksonen et al.	N/A	N/A
2019/0182471	12/2018	Khalid et al.	N/A	N/A
2019/0188895	12/2018	Miller, IV et al.	N/A	N/A
2019/0199993	12/2018	Babu J D et al.	N/A	N/A
2019/0208189	12/2018	Lau et al.	N/A	N/A
2019/0217189	12/2018	Gutierrez et al.	N/A	N/A
2019/0278369	12/2018	Ballard	N/A	N/A
2019/0325654	12/2018	Stisser et al.	N/A	N/A
2019/0358547	12/2018	Mack et al.	N/A	N/A
2020/0020136	12/2019	Hwang	N/A	G06F 3/013
2020/0042160	12/2019	Gabbi et al.	N/A	N/A
2020/0043235	12/2019	Chapman et al.	N/A	N/A
2020/0051336	12/2019	Ichikawa et al.	N/A	N/A
2020/0066043	12/2019	Graham et al.	N/A	N/A
2020/0097077	12/2019	Nguyen et al.	N/A	N/A
2020/0098179	12/2019	Gough et al.	N/A	N/A
2020/0098191	12/2019	Mccall	N/A	N/A
2020/0101372	12/2019	Drake et al.	N/A	N/A
2020/0126257	12/2019	Tauber	N/A	N/A
2020/0134911	12/2019	Van Hoff et al.	N/A	N/A
2020/0159361	12/2019	Rosenberg et al.	N/A	N/A
2020/0162779	12/2019	Saxena	N/A	N/A
2020/0169715	12/2019	Liu et al.	N/A	N/A
2020/0171394	12/2019	Khan et al.	N/A	N/A
2020/0241575	12/2019	Meisenholder et al.	N/A	N/A
2020/0242840	12/2019	Logan et al.	N/A	N/A
2020/0257367	12/2019	Rihn et al.	N/A	N/A
2020/0260149	12/2019	Ding et al.	N/A	N/A
2020/0273243	12/2019	Duffy et al.	N/A	N/A
2020/0279407	12/2019	Liljeroos et al.	N/A	N/A
2020/0289935	12/2019	Azmandian et al.	N/A	N/A
2020/0289941	12/2019	Khan et al.	N/A	N/A
2020/0314323	12/2019	Van Geel et al.	N/A	N/A
2020/0341541	12/2019	Olah-Reiken et al.	N/A	N/A
2020/0349751	12/2019	Bentovim et al.	N/A	N/A
2020/0371737	12/2019	Leppänen et al.	N/A	N/A
2020/0394012	12/2019	Wright, Jr. et al.	N/A	N/A
2020/0409451	12/2019	Mukherjea et al.	N/A	N/A
2021/0096543	12/2020	Stump et al.	N/A	N/A
2021/0142578	12/2020	Weinheimer et al.	N/A	N/A
2021/0159980	12/2020	Ben-Yehuda et al.	N/A	N/A
2021/0232632	12/2020	Howard	N/A	N/A
2021/0272367	12/2020	Richter	N/A	N/A

2021/0279962	12/2020	Hutten et al.	N/A	N/A
2021/0286179	12/2020	Miller, IV et al.	N/A	N/A
2021/0287452	12/2020	Maruyama	N/A	N/A
2021/0289317	12/2020	Son et al.	N/A	N/A
2021/0312684	12/2020	Zimmermann et al.	N/A	N/A
2021/0327145	12/2020	Noorkami et al.	N/A	N/A
2021/0362848	12/2020	Spencer	N/A	N/A
2021/0374579	12/2020	Dotan-cohen et al.	N/A	N/A
2021/0382503	12/2020	Meisenholder et al.	N/A	N/A
2021/0390953	12/2020	Makker et al.	N/A	N/A
2021/0394046	12/2020	Yen et al.	N/A	N/A
2021/0405772	12/2020	Canberk et al.	N/A	N/A
2021/0407178	12/2020	Zhou et al.	N/A	N/A
2021/0407208	12/2020	Hariton	N/A	N/A
2021/0409502	12/2020	Chepizhenko et al.	N/A	N/A
2022/0014723	12/2021	Pandey et al.	N/A	N/A
2022/0028108	12/2021	Haapoja et al.	N/A	N/A
2022/0028170	12/2021	Haapoja et al.	N/A	N/A
2022/0053219	12/2021	Bathory	N/A	N/A
2022/0101593	12/2021	Rockel et al.	N/A	N/A
2022/0103969	12/2021	Drummond et al.	N/A	N/A
2022/0108539	12/2021	Nussbaum et al.	N/A	N/A
2022/0116581	12/2021	Miyata et al.	N/A	N/A
2022/0124143	12/2021	Rafkind et al.	N/A	N/A
2022/0139055	12/2021	Palmaro	N/A	N/A
2022/0146833	12/2021	Miller, IV et al.	N/A	N/A
2022/0164491	12/2021	Palmaro	N/A	N/A
2022/0189075	12/2021	Lynch et al.	N/A	N/A
2022/0197485	12/2021	Goodrich et al.	N/A	N/A
2022/0198603	12/2021	Goodrich et al.	N/A	N/A
2022/0230663	12/2021	Sun et al.	N/A	N/A
2022/0242450	12/2021	Sokolov et al.	N/A	N/A
2022/0244835	12/2021	Faulkner et al.	N/A	N/A
2022/0247929	12/2021	Yang et al.	N/A	N/A
2022/0269336	12/2021	Lafontaine et al.	N/A	N/A
2022/0274026	12/2021	Steigelfest et al.	N/A	N/A
2022/0362631	12/2021	Hong	N/A	N/A
2022/0382255	12/2021	Lee	N/A	H04L 67/125
2023/0010754	12/2022	Saxena	N/A	N/A
2023/0063505	12/2022	Chastain et al.	N/A	N/A
2023/0097571	12/2022	Mccain et al.	N/A	N/A
2023/0139337	12/2022	Noam et al.	N/A	N/A
2023/0173367	12/2022	Marty et al.	N/A	N/A
2023/0179641	12/2022	Bauer et al.	N/A	N/A
2023/0214005	12/2022	Ohashi	N/A	N/A
2023/0214082	12/2022	Kang	345/633	G06F 3/012
2023/0237192	12/2022	Kahan et al.	N/A	N/A
2023/0316681	12/2022	Dolev et al.	N/A	N/A
2023/0334754	12/2022	Kirchmayer et al.	N/A	N/A

2023/0341928	12/2022	Traynor et al.	N/A	N/A
2023/0342989	12/2022	Lehtiniemi et al.	N/A	N/A
2023/0409114	12/2022	Sun et al.	N/A	N/A
2023/0412480	12/2022	Greyson et al.	N/A	N/A
2024/0005623	12/2023	Cooper et al.	N/A	N/A
2024/0069626	12/2023	Vaish et al.	N/A	N/A
2024/0069627	12/2023	Vaish et al.	N/A	N/A
2024/0069637	12/2023	Vaish et al.	N/A	N/A
2024/0070969	12/2023	Vaish et al.	N/A	N/A
2024/0071004	12/2023	Vaish et al.	N/A	N/A
2024/0071006	12/2023	Kratz et al.	N/A	N/A
2024/0071007	12/2023	Vaish et al.	N/A	N/A
2024/0073402	12/2023	Vaish et al.	N/A	N/A
2024/0073404	12/2023	Vaish et al.	N/A	N/A
2024/0119679	12/2023	Canberk et al.	N/A	N/A
2024/0119682	12/2023	Rudman et al.	N/A	N/A
2024/0233224	12/2023	Fan et al.	N/A	N/A
2024/0273832	12/2023	Newman et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2887596	12/2014	CA	N/A
105912129	12/2015	CN	N/A
2010061452	12/2009	JP	N/A
20200014587	12/2019	KR	N/A
20200109812	12/2019	KR	N/A
20210065423	12/2020	KR	N/A
20210135859	12/2020	KR	N/A
20220064130	12/2021	KR	N/A
WO-2016105839	12/2015	WO	N/A
WO-2021002788	12/2020	WO	N/A
2024049687	12/2023	WO	N/A
WO-2024049700	12/2023	WO	N/A
WO-2024050229	12/2023	WO	N/A
WO-2024050231	12/2023	WO	N/A
WO-2024050232	12/2023	WO	N/A
WO-2024050245	12/2023	WO	N/A
WO-2024050246	12/2023	WO	N/A
WO-2024050259	12/2023	WO	N/A
WO-2024050262	12/2023	WO	N/A
WO-2024050264	12/2023	WO	N/A

OTHER PUBLICATIONS

US 10,656,660 B1, 05/2020, Meisenholder et al. (withdrawn) cited by applicant
 “International Application Serial No. PCT US2023 030926, International Search Report mailed Dec. 12, 2023”, 3 pgs. cited by applicant
 “International Application Serial No. PCT US2023 030926, Written Opinion mailed Dec. 12, 2023”, 4 pgs. cited by applicant
 Laput, Gierad, et al., “PixelTone: A Multimodal Interface for Image Editing”, ACM, Proceedings of

the SIGCHI Conference on Human Factors in Computing Systems, Paris, FR, (2013), 10 pgs. cited by applicant

Leyden, John, "This SMS will self-destruct in 40 seconds", [Online] Retrieved from the Internet: <URL: <http://www.theregister.co.uk/2005/12/12/stealthtext/>>, (Dec. 12, 2005), 1 pg. cited by applicant

Meisenholder, David, et al., "Remoteless Control of Drone Behavior", U.S. Appl. No. 15/640,143, filed Jun. 30, 2017, 108 pgs. cited by applicant

Pourmehr, Shokoofeh, et al., "'You two! Take off!': Creating, Modifying, and Commanding Groups of Robots Using Face Engagement and Indirect Speech in Voice Commands", IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), Tokyo, JP, (2013), 137-142. cited by applicant

Yamada, Wataru, et al., "iSphere: Self-Luminous Spherical Drone Display", Proceedings of the 30th Annual ACM Symposium on User Interface Software and Technology (UIST), Quebec City, CA, (Oct. 22-25, 2017), 635-343. cited by applicant

"U.S. Appl. No. 17/899,935, Non Final Office Action mailed Jun. 6, 2024", 13 pgs. cited by applicant

"U.S. Appl. No. 17/899,935, Response filed Oct. 7, 2024 to Non Final Office Action mailed Jun. 6, 2024", 11 pgs. cited by applicant

"U.S. Appl. No. 17/899,970, Corrected Notice of Allowability mailed Jan. 3, 2024", 5 pgs. cited by applicant

"U.S. Appl. No. 17/899,970, Non Final Office Action mailed Jul. 3, 2023", 22 pgs. cited by applicant

"U.S. Appl. No. 17/899,970, Notice of Allowance mailed Dec. 20, 2023", 9 pgs. cited by applicant

"U.S. Appl. No. 17/899,970, PTO Response to Rule 312 Communication mailed Mar. 27, 2024", 1 page. cited by applicant

"U.S. Appl. No. 17/899,970, Response filed Oct. 3, 2023 to Non Final Office Action mailed Jul. 3, 2023", 11 pgs. cited by applicant

"U.S. Appl. No. 17/899,970, Supplemental Notice of Allowability mailed Mar. 27, 2024", 2 pgs. cited by applicant

"U.S. Appl. No. 17/900,200, Final Office Action mailed May 6, 2024", 32 pgs. cited by applicant

"U.S. Appl. No. 17/900,200, Non Final Office Action mailed Aug. 29, 2024", 35 pgs. cited by applicant

"U.S. Appl. No. 17/900,200, Non Final Office Action mailed Nov. 8, 2023", 26 pgs. cited by applicant

"U.S. Appl. No. 17/900,200, Response filed Jan. 31, 2024 to Non Final Office Action mailed Nov. 8, 2023", 14 pgs. cited by applicant

"U.S. Appl. No. 17/900,200, Response filed Aug. 6, 2024 to Final Office Action mailed May 6, 2024", 13 pgs. cited by applicant

"U.S. Appl. No. 17/900,407, Advisory Action mailed Oct. 30, 2024", 3 pgs. cited by applicant

"U.S. Appl. No. 17/900,407, Examiner Interview Summary mailed Apr. 15, 2024", 2 pgs. cited by applicant

"U.S. Appl. No. 17/900,407, Final Office Action mailed Aug. 21, 2024", 14 pgs. cited by applicant

"U.S. Appl. No. 17/900,407, Non Final Office Action mailed Feb. 9, 2024", 11 pgs. cited by applicant

"U.S. Appl. No. 17/900,407, Response filed Apr. 23, 2024 to Non Final Office Action mailed Feb. 9, 2024", 12 pgs. cited by applicant

"U.S. Appl. No. 17/900,407, Response filed Oct. 18, 2024 to Final Office Action mailed Aug. 21, 2024", 12 pgs. cited by applicant

"U.S. Appl. No. 17/900,436, Non Final Office Action mailed Sep. 23, 2024", 12 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Corrected Notice of Allowability mailed Sep. 4, 2024”, 2 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Examiner Interview Summary mailed Nov. 7, 2023”, 2 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Final Office Action mailed Apr. 8, 2024”, 15 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Non Final Office Action mailed Aug. 7, 2023”, 12 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Notice of Allowance mailed Aug. 16, 2024”, 9 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Notice of Non-Compliant Amendment mailed Nov. 16, 2023”, 2 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Response filed Jan. 3, 2024 to Notice of Non-Compliant Amendment mailed Nov. 16, 2023”, 11 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Response filed Jul. 8, 2024 to Final Office Action mailed Apr. 8, 2024”, 13 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Response filed Nov. 7, 2023 to Non Final Office Action mailed Aug. 7, 2023”, 11 pgs. cited by applicant

“U.S. Appl. No. 18/058,175, Examiner Interview Summary mailed Jun. 7, 2024”, 2 pgs. cited by applicant

“U.S. Appl. No. 18/058,175, Final Office Action mailed Sep. 19, 2024”, 12 pgs. cited by applicant

“U.S. Appl. No. 18/058,175, Non Final Office Action mailed Mar. 11, 2024”, 14 pgs. cited by applicant

“U.S. Appl. No. 18/058,175, Response filed Jun. 11, 2024 to Non Final Office Action mailed Mar. 11, 2024”, 11 pgs. cited by applicant

“U.S. Appl. No. 18/058,175, Response filed Oct. 30, 2024 to Final Office Action mailed Sep. 19, 2024”, 9 pgs. cited by applicant

“U.S. Appl. No. 18/169,631, Non Final Office Action mailed Sep. 17, 2024”, 28 pgs. cited by applicant

“U.S. Appl. No. 17/899,970, 312 Amendment filed Mar. 20, 2024”, 7 pgs. cited by applicant

“International Application Serial No. PCT/US2023/031066, International Search Report mailed Dec. 15, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/031066, Written Opinion mailed Dec. 15, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072274, International Search Report mailed Nov. 28, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072274, Written Opinion mailed Nov. 28, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072277, International Search Report mailed Dec. 8, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072277, Written Opinion mailed Dec. 8, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072282, International Search Report mailed Dec. 1, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072282, Written Opinion mailed Dec. 1, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072557, International Search Report mailed Dec. 12, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072557, Written Opinion mailed Dec. 12, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072568, International Search Report mailed Dec. 5, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072568, Written Opinion mailed Dec. 5, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072701, International Search Report mailed Dec. 1, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072701, Written Opinion mailed Dec. 1, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072718, International Search Report mailed Dec. 1, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072718, Written Opinion mailed Dec. 1, 2023”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072726, International Search Report mailed Dec. 12, 2023”, 3 pgs. cited by applicant

“International Application Serial No. PCT/US2023/072726, Written Opinion mailed Dec. 12, 2023”, 4 pgs. cited by applicant

Ko, Jonggook, et al., “Hybrid Camera Based Real-Time Human Body Segmentation for Virtual Reality E-learning System”, First ACIS JNU International Conference on Computers Networks Systems and Industrial Engineering Jeju Korea South, (2011), 3 pgs. cited by applicant

Langa, Sergi Fernandez, et al., “Multiparty Holomeetings Toward a New Era of Low Cost Volumetric Holographic Meetings in Virtual Reality”, IEEE Access vol. 10, (Aug. 3, 2022), 21 pgs. cited by applicant

S. A., Aseeri, et al., “The Influence of Avatar Representation and Behavior on Communication in Social Immersive Virtual Environments”, IEEE Conference on Virtual Reality and 3D User Interfaces VR Tuebingen Reutlingen Germany, (2018), 2 pgs. cited by applicant

Yanbin, Wang, et al., “Real Time Stereoscopic Rendering of Realistic Avatar for Interactive 3D Telepresence System”, 2nd International Conference on Image Vision and Computing ICIVC Chengdu, (2017), 5 pgs. cited by applicant

“U.S. Appl. No. 17/900,200, Response filed Nov. 27, 2024 to Non Final Office Action mailed Aug. 29, 2024”, 13 pgs. cited by applicant

“U.S. Appl. No. 17/900,354, Non Final Office Action mailed Dec. 12, 2024”, 17 pgs. cited by applicant

“U.S. Appl. No. 17/900,407, Notice of Allowance mailed Nov. 27, 2024”, 8 pgs. cited by applicant

“U.S. Appl. No. 17/900,436, Examiner Interview Summary mailed Jan. 3, 2025”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/900,436, Response filed Dec. 20, 2024 to Non Final Office Action mailed Sep. 23, 2024”, 12 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Notice of Allowability mailed Dec. 31, 2024”, 2 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Notice of Allowance mailed Dec. 11, 2024”, 5 pgs. cited by applicant

“U.S. Appl. No. 18/058,175, Notice of Allowance mailed Nov. 15, 2024”, 8 pgs. cited by applicant

“U.S. Appl. No. 18/169,631, Response filed Dec. 17, 2024 to Non Final Office Action mailed Sep. 17, 2024”, 11 pgs. cited by applicant

“U.S. Appl. No. 17/899,935, Non Final Office Action mailed Apr. 17, 2025”, 14 pgs. cited by applicant

“U.S. Appl. No. 17/899,935, Response filed Apr. 9, 2025 to Final Office Action mailed Jan. 10, 2025”, 10 pgs. cited by applicant

“U.S. Appl. No. 17/900,200, Final Office Action mailed Mar. 3, 2025”, 39 pgs. cited by applicant

“U.S. Appl. No. 17/900,354, Response filed Mar. 12, 2025 to Non Final Office Action mailed Dec. 12, 2024”, 10 pgs. cited by applicant

“U.S. Appl. No. 17/900,436, Final Office Action mailed Apr. 10, 2025”, 14 pgs. cited by applicant

“U.S. Appl. No. 18/056,142, Corrected Notice of Allowability mailed Mar. 12, 2025”, 2 pgs. cited

by applicant

“U.S. Appl. No. 18/056,142, Corrected Notice of Allowability mailed Mar. 26, 2025”, 2 pgs. cited by applicant

“U.S. Appl. No. 18/169,631, Final Office Action mailed Mar. 10, 2025”, 28 pgs. cited by applicant

“International Application Serial No. PCT/US2023/030926, International Preliminary Report on Patentability mailed Mar. 13, 2025”, 6 pgs. cited by applicant

“U.S. Appl. No. 17/899,935, Response filed Jul. 16, 2025 to Non Final Office Action mailed Apr. 17, 2025”, 13 pgs. cited by applicant

“U.S. Appl. No. 17/900,200, Response filed Jul. 30, 2025 to Final Office Action mailed Mar. 3, 2025”, 13 pgs. cited by applicant

“U.S. Appl. No. 17/900,436, Examiner Interview Summary mailed Jul. 16, 2025”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/900,436, Non Final Office Action mailed Jul. 29, 2025”, 13 pgs. cited by applicant

“U.S. Appl. No. 18/169,631, Non Final Office Action mailed Jul. 15, 2025”, 18 pgs. cited by applicant

Primary Examiner: Chu; David H

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This patent application claims the benefit of U.S. Provisional Patent Application No. 63/402,914, filed Aug. 31, 2022, entitled “GENERATING IMMERSIVE AUGMENTED REALITY EXPERIENCES FROM EXISTING IMAGES AND VIDEOS”, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The present disclosure generally relates to mobile and wearable computing technology. In particular, example embodiments of the present disclosure address systems, methods, and user interfaces for creating immersive augmented reality experiences from existing images and videos.

BACKGROUND

(2) An augmented reality (AR) experience includes application of virtual content to a real-world environment whether through presentation of the virtual content by transparent displays through which a real-world environment is visible or through augmenting image data to include the virtual content overlaid on real-world environments depicted therein. The virtual content can comprise one or more AR content items. An AR content item may include audio content, visual content or a visual effect. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. A device that supports AR experiences in any one of these approaches is referred to herein as an “AR device.”

(3) For some example AR devices, audio and visual content or the visual effects are applied to media data such as a live image stream. Other example AR devices include head-worn devices that may be implemented with a transparent or semi-transparent display through which a user of the head-worn device can view the surrounding environment. Such devices enable a user to see through the transparent or semi-transparent display to view the surrounding environment, and to also see objects (e.g., virtual objects such as 3D renderings, images, video, text, and so forth) that are generated for display to appear as a part of, and/or overlaid upon, the surrounding environment. A user of the head-worn device may access and use a computer software application to perform

various tasks or engage in an entertaining activity. To use the computer software application, the user interacts with a 3D user interface provided by the head-worn device.

(4) The so-called “Internet of Things” or “IoT” is a network of physical objects (referred to as “smart devices” or “IoT devices”) that are embedded with sensors, software, and other technologies for enabling connection and exchange of data with other devices via the Internet. For example, IoT devices are used in home automation to control lighting, heating and air conditioning, media and security systems, and camera systems. A number of IoT-enabled devices have been provided that function as smart home hubs to connect different smart home products. IoT devices have been used in a number of other applications as well. Application layer protocols and supporting frameworks have been provided for implementing such IoT applications. Artificial intelligence has also been combined with the IoT infrastructure to achieve more efficient IoT operations, improve human-machine interactions, and enhance data management and analytics.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

- (1) To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.
- (2) FIG. 1 is a diagrammatic representation of a networked environment in which a volumetric content presentation system may be deployed, in accordance with some example embodiments.
- (3) FIG. 2A is a perspective view of a head-worn device, in accordance with some example embodiments.
- (4) FIG. 2B illustrates a further view of the head-worn device of FIG. 2A, in accordance with some example embodiments.
- (5) FIG. 3 is a block diagram illustrating a networked system including details of the head-worn device of FIG. 1, in accordance with some example embodiments.
- (6) FIG. 4 is a diagrammatic representation of the volumetric content presentation system, in accordance with some examples embodiments, that has both client-side and server-side functionality.
- (7) FIG. 5 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some example embodiments.
- (8) FIG. 6 is a conceptual diagram illustrating an embodiment in which the volumetric content presentation system identifies one or more two-dimensional elements from an image data to be presented in augmented reality, in accordance with some example embodiments.
- (9) FIG. 7A is a conceptual diagram that illustrates a field of view of a user before the one or more volumetric content items are overlaid on a real-world environment, in accordance with some example embodiments.
- (10) FIG. 7B is a conceptual diagram that illustrates a fields of view of a user after the one or more volumetric content items are overlaid on a real-world environment, in accordance with some example embodiments.
- (11) FIGS. 8A-8D are flowcharts illustrating operations of the volumetric content presentation system in performing a method for creating an immersive AR experience from existing image data, in accordance with some example embodiments.
- (12) FIG. 9 is a block diagram illustrating a representative software architecture, which may be used in conjunction with various hardware architectures herein described, in accordance with some example embodiments.
- (13) FIG. 10 is a block diagram illustrating components of a machine able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein, in accordance with some example embodiments.

DETAILED DESCRIPTION

(14) The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative embodiments of the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the inventive subject matter. It will be evident, however, to those skilled in the art, that embodiments of the inventive subject matter may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

(15) Volumetric content is an example of an augmented reality (AR) experience. Volumetric content can include volumetric videos and images of three-dimensional spaces captured in three-dimensions (as well as audio signals recorded with volumetric videos and images). Recording of volumetric content includes volumetrically capturing elements of the three-dimensional space such as objects and human beings using a combination of cameras and sensors. Volumetric content includes a volumetric representation of one or more three-dimensional elements (e.g., an object or a person) of a three-dimensional space. A volumetric representation of an element (e.g., an AR content item) refers to a visual representation of the three-dimensional element in three-dimensions. The presentation of the volumetric content may include displaying one or more AR content items overlaid upon a real-world space, which may be the same as the three-dimensional space in which the volumetric video was captured or a different space. The presentation of the volumetric content may include displaying one or more content items in motion, displaying one or more content items performing a movement or other action, displaying one or more content items statically positioned, or combinations thereof. A content item may be displayed for a duration of the presentation of the volumetric content or a portion thereof.

(16) The presentation of the volumetric content may include tracking a location and movement of a user within their physical real-world environment and using the tracked location and movement of the user to allow the user to move around in and interact with the presentation of the volumetric content. As such, the presentation of the volumetric content may include displaying a content item from multiple perspectives depending on a user's movement and change in location. In this manner, the presentation of volumetric content provides an immersive AR experience to users.

(17) Aspects of the present disclosure include systems, methods, techniques, instruction sequences, and computing machine program products to create immersive AR experiences from existing images and videos. Whether from a single video of a single scene or a series of images and videos about a trip, the volumetric content presentation system described herein allows users to create immersive experiences using metadata and visual details.

(18) In an example, an existing image depicts a dog playing with a ball in a park. The volumetric content presentation system **100** segments different components of the image to render them in AR. Grass from the park turns the floor green, background from the picture turns the wall to a similar shade, and the dog and ball are segmented and placed as a “clone” in AR in the physical world. For some embodiments, the system performs segmentation automatically. For some embodiments, segmentation may rely on user input if an image contains too many key elements. Additionally, using metadata such as weather, the system can render AR clouds for a cloudy day or snow if it snowed that day. If it was windy, using AI, the system can create additional effects to blow the dog's hair, as if the dog was experiencing the wind. Although the current example addresses a location-independent scenario, the creation of immersive AR experiences can be location-dependent and perhaps more contextual as well. For some embodiments, the experience can be made more immersive using IoT/smart devices such as by triggering a smart fan to add the wind effect.

(19) FIG. 1 is a block diagram showing an example volumetric content presentation system **100** for presenting volumetric content. The volumetric content presentation system **100** includes of a client device **102**. The client device **102** hosts a number of applications including a presentation client

104. Each presentation client **104** is communicatively coupled to a presentation server system **108** via a network **106** (e.g., the Internet). In an example, the client device **102** is a wearable device (e.g., smart glasses) worn by the user **124** that includes a camera and optical elements that include a transparent display through which the real-world environment is visible to the user **124**.

(20) A presentation client **104** is able to communicate and exchange data with another presentation client **104** and with the presentation server system **108** via the network **106**. The data exchanged between the presentation client **104**, and between another presentation client **104** and the presentation server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

(21) The presentation server system **108** provides server-side functionality via the network **106** to a particular presentation client **104**. While certain functions of the volumetric content presentation system **100** are described herein as being performed by either a presentation client **104** or by the presentation server system **108**, the location of certain functionality either within the presentation client **104** or the presentation server system **108** is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the presentation server system **108**, but to later migrate this technology and functionality to the presentation client **104** where the client device **102** has a sufficient processing capacity.

(22) The presentation server system **108** supports various services and operations that are provided to the presentation client **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the presentation client **104**. This data may include volumetric content (e.g., volumetric videos), message content, device information, geolocation information, media annotation and overlays, message content persistence conditions, social network information, and live event information, as examples. Data exchanges within the volumetric content presentation system **100** are invoked and controlled through functions available via user interfaces (UIs) and of the presentation client **104**.

(23) Turning now specifically to the presentation server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, an application server **112**. The application server **112** is communicatively coupled to a database server **114**, which facilitates access to a database **116** in which is stored data associated with messages processed by the application server **112**.

(24) The Application Program Interface (API) server **110** receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application server **112**. Specifically, the Application Program Interface (API) server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the presentation client **104** in order to invoke functionality of the application server **112**. The API server **110** exposes various functions supported by the application server **112**, including account registration, login functionality, the sending of messages, via the application server **112**, from a particular presentation client **104** to another presentation client **104**, the sending of media files (e.g., volumetric videos) to the presentation client **104**, the setting of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the adding and deletion of friends to a social graph, the location of friends within a social graph, and opening an application event (e.g., relating to the presentation client **104**).

(25) The application server **112** hosts a number of applications and subsystems, including a presentation server **118**, an image processing server **120** and a social networking server **122**. The presentation server **118** is generally responsible for managing volumetric content and facilitating presentation thereof by the client device **102**. The image processing server **120** is dedicated to performing various image processing operations, typically with respect to images or video generated and displayed by the client device **102**. The presentation server **118** and image processing server **120** may work in conjunction to provide one or more AR experiences to the user **124**. For example, the presentation server **118** and image processing server **120** may work in

conjunction to support presentation of volumetric content by the client device **102**. Further details regarding presentation of volumetric content are discussed below.

(26) The social networking server **122** supports various social networking functions and services, and makes these functions and services available to the presentation server **118**. To this end, the social networking server **122** maintains and accesses an entity graph within the database **116**. Examples of functions and services supported by the social networking server **122** include the identification of other users of the volumetric content presentation system **100** with which a particular user has relationships or is “following”, and also the identification of other entities and interests of a particular user.

(27) The application server **112** is communicatively coupled to a database server **114**, which facilitates access to a database **116** in which is stored data associated with content presented by the presentation server **118** and image processing server **120**.

(28) The presentation server system **108** may further communicate and exchange data with one or more network-connected device(s) **126**. For some devices, the presentation server system **108** may communicate and exchange data directly with a network-connected device(s) **126** while in other instances the presentation server system **108** may communicate and exchange data with a network-connected device(s) **126** via a network service(s) **128** (e.g., a third-party application). The network service(s) **128** may, for example, expose one or more APIs for communicating with a network-connected device(s) **126**. Examples of data communicated between the presentation server system **108** and the one or more network-connected devices include device state data and sensor data along with or as part of various requests and commands. As shown in FIG. 1, in some embodiments, the client device **102** (e.g., display device such as glasses **200** in FIG. 2A) is distinct from network-connected device(s) **126**.

(29) The term “network-connected devices” as used herein includes devices known to those skilled in the art as “IoT devices.” As such, a network-connected device(s) **126** may include common household and other devices that a standard end user might encounter such as smart lamps and lightbulbs, thermostats, smart televisions, smart speakers, smart switches, smart appliances (e.g., washers, dryers, ranges, and microwaves), navigation systems, and the like.

(30) FIG. 2A is perspective view of a head-worn display device (e.g., glasses **200**), in accordance with some examples. The glasses **200** are an example of the client device **102** of FIG. 1. The glasses **200** are capable of displaying content and are thus an example of a display device, which is referenced below. In addition, the display capabilities of the glasses **200** support AR experiences and the glasses **200** are thus an example of an AR device. As noted above, AR experiences include application of virtual content to real-world environments whether through presentation of the virtual content by transparent displays through which a real-world environment is visible or through augmenting image data to include the virtual content overlaid on real-world environments depicted therein.

(31) The glasses **200** can include a frame **202** made from any suitable material such as plastic or metal, including any suitable shape memory alloy. In one or more examples, the frame **202** includes a first or left optical element holder **204** (e.g., a display or lens holder) and a second or right optical element holder **206** connected by a bridge **212**. A first or left optical element **208** and a second or right optical element **210** can be provided within respective left optical element holder **204** and right optical element holder **206**. The right optical element **210** and the left optical element **208** can be a lens, a display, a display assembly, or a combination of the foregoing. Any suitable display assembly can be provided in the glasses **200**.

(32) The frame **202** additionally includes a left arm or temple piece **222** and a right arm or temple piece **224**. In some examples the frame **202** can be formed from a single piece of material so as to have a unitary or integral construction.

(33) The glasses **200** can include a computing device, such as a computer **220**, which can be of any suitable type so as to be carried by the frame **202** and, in one or more examples, of a suitable size

and shape, so as to be partially disposed in one of the temple piece **222** or the temple piece **224**. The computer **220** can include one or more processors with memory, wireless communication circuitry, and a power source. As discussed below, the computer **220** comprises low-power circuitry, high-speed circuitry, and a display processor. Various other examples may include these elements in different configurations or integrated together in different ways. Additional details of aspects of computer **220** may be implemented as illustrated by the data processor **302** discussed below.

(34) The computer **220** additionally includes a battery **218** or other suitable portable power supply. In some examples, the battery **218** is disposed in left temple piece **222** and is electrically coupled to the computer **220** disposed in the right temple piece **224**. The glasses **200** can include a connector or port (not shown) suitable for charging the battery **218**, a wireless receiver, transmitter or transceiver (not shown), or a combination of such devices.

(35) The glasses **200** include a first or left camera **214** and a second or right camera **216**. Although two cameras are depicted, other examples contemplate the use of a single or additional (i.e., more than two) cameras. In one or more examples, the glasses **200** include any number of input sensors or other input/output devices in addition to the left camera **214** and the right camera **216**. Such sensors or input/output devices can additionally include biometric sensors, location sensors, motion sensors, and so forth.

(36) In some examples, the left camera **214** and the right camera **216** provide video frame data for use by the glasses **200** to extract 3D information from a real-world scene.

(37) The glasses **200** may also include a touchpad **226** mounted to or integrated with one or both of the left temple piece **222** and right temple piece **224**. The touchpad **226** is generally vertically-arranged, approximately parallel to a user's temple in some examples. As used herein, generally vertically aligned means that the touchpad is more vertical than horizontal, although potentially more vertical than that. Additional user input may be provided by one or more buttons **228**, which in the illustrated examples are provided on the outer upper edges of the left optical element holder **204** and right optical element holder **206**. The one or more touchpads **226** and buttons **228** provide a means whereby the glasses **200** can receive input from a user of the glasses **200**.

(38) FIG. 2B illustrates the glasses **200** from the perspective of a user. For clarity, a number of the elements shown in FIG. 2A have been omitted. As described in FIG. 2A, the glasses **200** shown in FIG. 2B include left optical element **208** and right optical element **210** secured within the left optical element holder **204** and the right optical element holder **206** respectively.

(39) The glasses **200** include forward optical assembly **230** comprising a right projector **232** and a right near eye display **234**, and a forward optical assembly **238** including a left projector **240** and a left near eye display **244**.

(40) In some examples, the near eye displays are waveguides. The waveguides include reflective or diffractive structures (e.g., gratings and/or optical elements such as mirrors, lenses, or prisms). Light **236** emitted by the projector **232** encounters the diffractive structures of the waveguide of the near eye display **234**, which directs the light towards the right eye of a user to provide an image on or in the right optical element **210** that overlays the view of the real world seen by the user. Similarly, light **242** emitted by the projector **240** encounters the diffractive structures of the waveguide of the near eye display **244**, which directs the light towards the left eye of a user to provide an image on or in the left optical element **208** that overlays the view of the real world seen by the user. The combination of a GPU, the forward optical assembly **230**, the left optical element **208**, and the right optical element **210** provide an optical engine of the glasses **200**. The glasses **200** use the optical engine to generate an overlay of the real world view of the user including display of a 3D user interface to the user of the glasses **200**.

(41) It will be appreciated however that other display technologies or configurations may be utilized within an optical engine to display an image to a user in the user's field of view. For example, instead of a projector **232** and a waveguide, an LCD, LED or other display panel or

surface may be provided.

(42) In use, a user of the glasses **200** will be presented with information, content and various 3D user interfaces on the near eye displays. As described in more detail herein, the user can then interact with the glasses **200** using a touchpad **226** and/or the buttons **228**, voice inputs or touch inputs on an associated device (e.g. client device **328** illustrated in FIG. 3), and/or hand movements, locations, and positions detected by the glasses **200**.

(43) FIG. 3 is a block diagram illustrating a networked system **300** including details of the glasses **200**, in accordance with some examples. The networked system **300** includes the glasses **200**, a client device **328**, and a server system **332**. The client device **328** may be a smartphone, tablet, phablet, laptop computer, access point, or any other such device capable of connecting with the glasses **200** using a low-power wireless connection **336** and/or a high-speed wireless connection **334**. The client device **328** is connected to the server system **332** via the network **330**. The network **330** may include any combination of wired and wireless connections. The server system **332** may be one or more computing devices as part of a service or network computing system. The client device **328** and any elements of the server system **332** and network **330** may be implemented using details of the software architecture **920** or the machine **1000** described in FIG. 9 and FIG. 10 respectively.

(44) The glasses **200** include a data processor **302**, displays **310**, one or more cameras **308**, and additional input/output elements **316**. The input/output elements **316** may include microphones, audio speakers, biometric sensors, additional sensors, or additional display elements integrated with the data processor **302**. Examples of the input/output elements **316** are discussed further with respect to FIG. 9 and FIG. 10. For example, the input/output elements **316** may include any of I/O components **1018** including output components **1026**, motion components **1034**, and so forth. Examples of the displays **310** are discussed in FIG. 2B. In the particular examples described herein, the displays **310** include a display for the user's left and right eyes.

(45) The data processor **302** includes an image processor **306** (e.g., a video processor), a GPU & display driver **338**, a tracking module **340**, an interface **312**, low-power circuitry **304**, and high-speed circuitry **320**. The components of the data processor **302** are interconnected by a bus **342**.

(46) The interface **312** refers to any source of a user command that is provided to the data processor **302**. In one or more examples, the interface **312** is a physical button that, when depressed, sends a user input signal from the interface **312** to a low-power processor **314**. A depression of such button followed by an immediate release may be processed by the low-power processor **314** as a request to capture a single image, or vice versa. A depression of such a button for a first period of time may be processed by the low-power processor **314** as a request to capture video data while the button is depressed, and to cease video capture when the button is released, with the video captured while the button was depressed stored as a single video file. Alternatively, depression of a button for an extended period of time may capture a still image. In some examples, the interface **312** may be any mechanical switch or physical interface capable of accepting user inputs associated with a request for data from the cameras **308**. In other examples, the interface **312** may have a software component, or may be associated with a command received wirelessly from another source, such as from the client device **328**.

(47) The image processor **306** includes circuitry to receive signals from the cameras **308** and process those signals from the cameras **308** into a format suitable for storage in the memory **324** or for transmission to the client device **328**. In one or more examples, the image processor **306** (e.g., video processor) comprises a microprocessor integrated circuit (IC) customized for processing sensor data from the cameras **308**, along with volatile memory used by the microprocessor in operation.

(48) The low-power circuitry **304** includes the low-power processor **314** and the low-power wireless circuitry **318**. These elements of the low-power circuitry **304** may be implemented as separate elements or may be implemented on a single IC as part of a system on a single chip. The

low-power processor **314** includes logic for managing the other elements of the glasses **200**. As described above, for example, the low-power processor **314** may accept user input signals from the interface **312**. The low-power processor **314** may also be configured to receive input signals or instruction communications from the client device **328** via the low-power wireless connection **336**. The low-power wireless circuitry **318** includes circuit elements for implementing a low-power wireless communication system. Bluetooth™ Smart, also known as Bluetooth™ low energy, is one standard implementation of a low power wireless communication system that may be used to implement the low-power wireless circuitry **318**. In other examples, other low power communication systems may be used.

(49) The high-speed circuitry **320** includes a high-speed processor **322**, a memory **324**, and a high-speed wireless circuitry **326**. The high-speed processor **322** may be any processor capable of managing high-speed communications and operation of any general computing system used for the data processor **302**. The high-speed processor **322** includes processing resources used for managing high-speed data transfers on the high-speed wireless connection **334** using the high-speed wireless circuitry **326**. In some examples, the high-speed processor **322** executes an operating system such as a LINUX operating system or other such operating system. In addition to any other responsibilities, the high-speed processor **322** executing a software architecture for the data processor **302** is used to manage data transfers with the high-speed wireless circuitry **326**. In some examples, the high-speed wireless circuitry **326** is configured to implement Institute of Electrical and Electronic Engineers (IEEE) 802.11 communication standards, also referred to herein as Wi-Fi. In other examples, other high-speed communications standards may be implemented by the high-speed wireless circuitry **326**.

(50) The memory **324** includes any storage device capable of storing camera data generated by the cameras **308** and the image processor **306**. While the memory **324** is shown as integrated with the high-speed circuitry **320**, in other examples, the memory **324** may be an independent standalone element of the data processor **302**. In some such examples, electrical routing lines may provide a connection through a chip that includes the high-speed processor **322** from image processor **306** or the low-power processor **314** to the memory **324**. In other examples, the high-speed processor **322** may manage addressing of the memory **324** such that the low-power processor **314** will boot the high-speed processor **322** any time that a read or write operation involving the memory **324** is desired.

(51) The tracking module **340** estimates a pose of the glasses **200**. For example, the tracking module **340** uses image data and corresponding inertial data from the cameras **308** and position components, as well as GPS data, to track a location and determine a pose of the glasses **200** relative to a frame of reference (e.g., real-world environment). The tracking module **340** continually gathers and uses updated sensor data describing movements of the glasses **200** to determine updated three-dimensional poses of the glasses **200** that indicate changes in the relative position and orientation relative to physical objects in the real-world environment. The tracking module **340** permits visual placement of virtual content relative to physical objects by the glasses **200** within the field of view of the user via the displays **310**.

(52) The GPU & display driver **338** may use the pose of the glasses **200** to generate frames of virtual content or other content to be presented on the displays **310** when the glasses **200** are functioning in a traditional augmented reality mode. In this mode, the GPU & display driver **338** generates updated frames of virtual content based on updated three-dimensional poses of the glasses **200**, which reflect changes in the position and orientation of the user in relation to physical objects in the user's real-world environment.

(53) One or more functions or operations described herein may also be performed in an application resident on the glasses **200** or on the client device **328**, or on a remote server. The glasses **200** may be a stand-alone client device that is capable of independent operation or may be a companion device that works with a primary device to offload intensive processing and/or exchange data over

the network **106** with the presentation server system **108**. The glasses **200** may also be communicatively coupled with a companion device such as a smart watch and may be configured to exchange data with the companion device. The glasses **200** may further include various components common to mobile electronic devices such as smart glasses or smart phones (for example, including a display controller for controlling display of visual media on a display mechanism incorporated in the device).

(54) FIG. **4** is a block diagram illustrating further details regarding the volumetric content presentation system **100**, according to some examples. Specifically, the volumetric content presentation system **100** is shown to comprise the presentation client **104** and the application servers **112**. The volumetric content presentation system **100** embodies a number of subsystems, which are supported on the client-side by the presentation client **104** and on the sever-side by the application servers **112**. These subsystems include, for example, a collection management system **402**, a presentation control system **404**, an augmentation system **406**, and an immersive experience creation system **408**.

(55) The collection management system **402** is responsible for managing sets or collections of content (e.g., collections of text, image, video, and audio data). A collection of content may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection management system **402** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the presentation client **104**.

(56) The collection management system **402** furthermore includes a curation interface **412** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **412** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **402** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection.

(57) The presentation control system **404** is responsible for facilitating and controlling volumetric content presentation. As such, the presentation control system **404** provides a mechanism that allows users to specify control operations for controlling volumetric content presentation. Control operations may, for example, include: a stop operation to stop the presentation; a pause operation to pause the presentation; a fast-forward operation to advance the presentation at a higher speed; a rewind operation to rewind the presentation; a zoom-in operation to increase a zoom level of the presentation; a zoom-out operation to decrease the zoom level of the presentation; and a playback speed modification operation to change the speed of the presentation (e.g., to produce a slow-motion presentation of the volumetric video).

(58) For some embodiments, a user may specify input indicative of a control operation for controlling presentation of volumetric content by providing one or more inputs via one or more I/O components (examples of which are described in further detail below in reference to FIG. **10**). For some embodiments, the presentation control system **404** may provide an interactive control interface comprising one or more interactive elements (e.g., virtual buttons) to trigger a control operation and the presentation control system **404** monitors interaction with the interactive interface to detect input indicative of a control operation. For some embodiments, a user may trigger a control operation using a gesture such as a hand or head gesture that can be associated with a specific control operation.

(59) The augmentation system **406** provides various functions that enable a user to augment (e.g., annotate or otherwise modify or edit) media content. For example, the augmentation system **406** provides functions related to the generation, publication, and application of augmentation data such as media overlays (e.g., image filters) to volumetric content. A media overlay may include audio

and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo) at the client device **102**. For example, the media overlay may include text or image that can be overlaid on top of a photograph taken by the client device **102**. The augmentation system **406** operatively supplies one or more media overlays to the presentation client **104** based on a geolocation of the client device **102** or based on other information, such as social network information of the user of the client device **102**. The media overlays may be stored in the database **116** and accessed through the database server **114**.

(60) Filters are an example of media overlays that are displayed as overlaid on an image or video during presentation to a user. Filters may be of various types, including user-selected filters from a set of filters presented to a user by the presentation client **104**. Other types of filters include geolocation filters (also known as geo-filters), which may be presented to a user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the presentation client **104**, based on geolocation information determined by a Global Positioning System (GPS) unit of the client device **102**.

(61) Another type of filter is a data filter, which may be selectively presented to a user by the presentation client **104**, based on other inputs or information gathered by the client device **102**. Examples of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a client device **102**, or the current time.

(62) AR content items are another example of media overlays. An AR content item may be a real-time special effect and/or sound that can be added to an image or a video including volumetric images and videos.

(63) Generally, AR content items, overlays, image transformations, images, and similar terms refer to modifications that may be applied to image data (e.g., videos or images) including volumetric content. This includes real-time modifications, which modify an image as it is captured using device sensors (e.g., one or multiple cameras) of a client device **102** and then displayed by a display device of the client device **102** (e.g., an embedded display of the client device) with the modifications. This also includes modifications to stored content, such as volumetric videos in a gallery or collection that may be modified. For example, in a client device **102** with access to multiple AR content items, a user can use a single volumetric video with multiple AR content items to see how the different AR content items will modify the stored content. For example, multiple augmented reality content items that apply different pseudorandom movement models can be applied to the same content by selecting different AR content items for the content. Similarly, real-time video capture may be used with an illustrated modification to show how video images currently being captured by sensors of a client device **102** would modify the captured data. Such data may simply be displayed on the screen and not stored in memory, or the content captured by the device sensors may be recorded and stored in memory with or without the modifications (or both). In some systems, a preview feature can show how different augmented reality content items will look within different windows in a display at the same time. This can, for example, enable multiple windows with different pseudorandom animations to be viewed on a display at the same time.

(64) Data and various systems using augmented reality content items or other such augmentation systems to modify content using augmentation data can thus involve detection of objects (e.g., faces, hands, bodies, cats, dogs, surfaces, objects, etc.), tracking of such objects as they leave, enter, and move around the field of view in video frames, and the modification or transformation of such objects as they are tracked. In various examples, different methods for achieving such transformations may be used. Some examples may involve generating a three-dimensional mesh model of the object or objects, and using transformations and animated textures of the model within the video to achieve the transformation. In other examples, tracking of points on an object

may be used to place an image or texture (which may be two dimensional or three dimensional) at the tracked position. In still further examples, neural network analysis of video frames may be used to place images, models, or textures in content (e.g., images or frames of video). AR content items thus refer both to the images, models, and textures used to create transformations in content, as well as to additional modeling and analysis information needed to achieve such transformations with object detection, tracking, and placement.

(65) Real-time video processing can be performed with any kind of video data (e.g., video streams, video files, volumetric videos, etc.) saved in a memory of a computerized system of any kind. For example, a user can load video files and save them in a memory of a device, or can generate a video stream using sensors of the device. Additionally, any objects can be processed using a computer animation model, such as a human's face and parts of a human body, animals, or non-living things such as chairs, cars, or other objects.

(66) In some examples, when a particular modification is selected along with content to be augmented (e.g., edited), elements to be transformed are identified by the computing device, and then detected and tracked if they are present in the frames of the video. The elements of the object are modified according to the request for modification, thus transforming the frames of the video stream. Transformation of frames of a video stream can be performed by different methods for different kinds of transformation. For example, for transformations of frames mostly referring to changing forms of an object's elements, characteristic points for each element of an object are calculated (e.g., using an Active Shape Model (ASM) or other known methods). Then, a mesh based on the characteristic points is generated for each of the at least one element of the object. This mesh can be used in the following stage of tracking the elements of the object in the video stream. In the process of tracking, the mentioned mesh for each element is aligned with a position of each element. Then, additional points are generated on the mesh. A set of first points is generated for each element based on a request for modification, and a set of second points is generated for each element based on the set of first points and the request for modification. Then, the frames of the video stream can be transformed by modifying the elements of the object on the basis of the sets of first and second points and the mesh. In such method, a background of the modified object can be changed or distorted as well by tracking and modifying the background.

(67) In some examples, transformations changing some areas of an object using its elements can be performed by calculating characteristic points for each element of an object and generating a mesh based on the calculated characteristic points. Points are generated on the mesh, and then various areas based on the points are generated. The elements of the object are then tracked by aligning the area for each element with a position for each of the at least one element, and properties of the areas can be modified based on the request for modification, thus transforming the frames of the video stream. Depending on the specific request for modification, properties of the mentioned areas can be transformed in different ways. Such modifications may involve changing color of areas; removing at least some part of areas from the frames of the video stream; including one or more new objects into areas which are based on a request for modification; and modifying or distorting the elements of an area or object. In various examples, any combination of such modifications or other similar modifications may be used. For certain models to be animated, some characteristic points can be selected as control points to be used in determining the entire state-space of options for the model animation.

(68) In some examples of a computer animation model to transform image data using face detection, the face is detected on an image with use of a specific face detection algorithm (e.g., Viola-Jones). Then, an Active Shape Model (ASM) algorithm is applied to the face region of an image to detect facial feature reference points.

(69) Other methods and algorithms suitable for face detection can be used. For example, in some examples, features are located using a landmark, which represents a distinguishable point present in most of the images under consideration. For facial landmarks, for example, the location of the left

eye pupil may be used. If an initial landmark is not identifiable (e.g., if a person has an eyepatch), secondary landmarks may be used. Such landmark identification procedures may be used for any such objects. In some examples, a set of landmarks forms a shape. Shapes can be represented as vectors using the coordinates of the points in the shape. One shape is aligned to another with a similarity transform (allowing translation, scaling, and rotation) that minimizes the average Euclidean distance between shape points. The mean shape is the mean of the aligned training shapes.

(70) In some examples, a search for landmarks from the mean shape aligned to the position and size of the face determined by a global face detector is started. Such a search then repeats the steps of suggesting a tentative shape by adjusting the locations of shape points by template matching of the image texture around each point and then conforming the tentative shape to a global shape model until convergence occurs. In some systems, individual template matches are unreliable, and the shape model pools the results of the weak template matches to form a stronger overall classifier. The entire search is repeated at each level in an image pyramid, from coarse to fine resolution.

(71) The augmentation system **406** can capture an image or video stream on a client device (e.g., the client device **102**) and perform complex image manipulations locally on the client device **102** while maintaining a suitable user experience, computation time, and power consumption. The complex image manipulations may include size and shape changes, emotion transfers (e.g., changing a face from a frown to a smile), state transfers (e.g., aging a subject, reducing apparent age, changing gender), style transfers, graphical element application, and any other suitable image or video manipulation implemented by a convolutional neural network that has been configured to execute efficiently on the client device **102**.

(72) In some examples, a computer animation model to transform video and image content can be used by the augmentation system **406** where a neural network operates as part of a presentation client **104** operating on the client device **102**. The augmentation system **406** determines the presence of a face within the image or video stream and provides interactive modification elements (e.g., icons) associated with a computer animation model to transform image data, or the computer animation model can be present as associated with an interface described herein. The interactive modification elements include changes that may be the basis for modifying the user's face within the image or video content as part of the modification operation. Once a modification icon is selected, the transform system initiates a process to convert the image of the user to reflect the selected modification icon (e.g., generate a smiling face on the user). Modified image or video content may be presented in a graphical user interface displayed on the client device **102** as soon as the image or video stream is captured, and a specified modification is selected. The augmentation system **406** may implement a complex convolutional neural network on a portion of the image or video content to generate and apply the selected modification. That is, the user may be presented with modified content in real-time or near real-time. Further, the modification may be persistent while the content is being presented. Machine taught neural networks may be used to enable such modifications.

(73) The immersive experience creation system **408** is responsible for creating immersive AR experiences based on existing images and videos. In doing so, the immersive experience creation system **408** may utilize one or more known machine learning or artificial intelligence image processing techniques to segment images and videos to identify key elements. The immersive experience creation system **408** generates volumetric content items for each of the key elements that can be utilized in creating immersive AR experiences. Further details regarding the creation and presentation of the immersive AR experiences are discussed below.

(74) FIG. 5 is a diagrammatic representation of a data structure **500** as maintained in the database **116**, in accordance with some examples. While the content of the database **116** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

(75) An entity table **506** stores entity data, and is linked (e.g., referentially) to an entity graph **508** and profile data **502**. Entities for which records are maintained within the entity table **506** may include individuals, corporate entities, organizations, objects, places, events, and so forth. Regardless of entity type, any entity regarding which the presentation server system **108** stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity type identifier (not shown). The entity table **506** may associate various augmentations from the augmentation table **510** with various images and videos stored in the image table **514** and the video table **512**.

(76) The entity graph **508** stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example.

(77) The profile data **502** stores multiple types of profile data about a particular entity. The profile data **502** may be selectively used and presented to other users of the volumetric content presentation system **100**, based on privacy settings specified by a particular entity. Where the entity is an individual, the profile data **502** includes, for example, a user name, telephone number, address, settings (e.g., notification and privacy settings), as well as a user-selected avatar representation (or collection of such avatar representations).

(78) The database **116** also stores augmentation data, such as overlays including AR content items and filters, in an augmentation table **510**. The augmentation data is associated with and applied to videos (for which data is stored in a video table **512**) and images (for which data is stored in an image table **514**) including volumetric videos and images.

(79) A story table **516** stores data regarding collections of content including associated image, video, or audio data that are compiled into a collection (e.g., a story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **506**). A user may create a “personal story” in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the presentation client **104** may include an icon that is user-selectable to enable a sending user to add specific content to his or her personal story.

(80) As mentioned above, the video table **512** stores video data that includes volumetric videos. Similarly, the image table **514** stores image data that includes volumetric images.

(81) FIG. **6** is a conceptual diagram illustrating an example in which the volumetric content presentation system **100** identifies one or more two-dimensional elements from a two-dimensional image **610** to be presented as part of an augmented reality experience. As shown, the two-dimensional image **610** includes multiple two-dimensional elements: a sun **602**, two birds **604**, a piece of cloud **606**, a dog **608**, a grass field, and trees. To individually identify the elements in the two-dimensional image **610**, the volumetric content presentation system **100** may perform image segmentation on the two-dimensional image **610** using various known segmentation algorithms. In addition, in this example, cloud **606** is identified based on user input.

(82) The volumetric content presentation system **100** generates volumetric content items based on the two-dimensional elements identified in the two-dimensional image **610**. For example, the volumetric content presentation system **100** generates a volumetric content item **612** based on the sun **602** identified in the two-dimensional image **610**. In generating the volumetric content items, the volumetric content presentation system **100** may adjust the dimensions of the volumetric content items either automatically based on image analysis or based on user-inputs. That, the volumetric content presentation system **100** may utilize one or more scaling techniques in generating the volumetric content item **612**.

(83) FIGS. **7A** and **7B** are conceptual diagrams that illustrate an example augmented reality experience provided to a user **702** of a user device **704**. The user device **704** is an example of the client device **102** of FIG. **1**. FIG. **7A** illustrates an example field of view of a user standing in a real-world environment, which in this example is a room. As shown, multiple real-world elements

are in the field of view of the user **124**, including a floor, walls, windows, and a book shelf.

(84) FIG. 7B illustrates an example field of view of the user **702** after the volumetric content presentation system **100** causes the user device **704** to present the volumetric content items overlaid on the real-world environment. The volumetric content item representing a grass field is presented as an overlay on the ground surface, the volumetric content items representing the sun, trees, and the cloud, are presented as overlays on the walls, the volumetric content item representing the dog **608** is placed on the floor as a “clone” in AR in the real-world environment (i.e., the room), providing an AR experience to the user **702**. The dimensions of the volumetric content item **612** has also been adjusted (e.g., scaled) proportionally to fit the real-world environment.

(85) FIG. 8A is a flowchart illustrating operations for the volumetric content presentation system **100** in performing method **800** for providing immersive AR experiences based on existing image data, in accordance with some examples. The method **800** may be embodied in computer-readable instructions for execution by one or more processors such that operations of the method **800** may be performed in part or in whole by the functional components of the volumetric content presentation system **100**; accordingly, the method **800** is described below by way of example with reference thereto. However, it shall be appreciated that at least some of the operations of the method **800** may be deployed on various other hardware configurations than the volumetric content presentation system **100**.

(86) At operation **802**, the volumetric content presentation system **100** accesses image data comprising one or more two-dimensional image. The image data may comprise any one or more of a digital image, a frame of a video, or a physical copy of a photograph. The image data may be stored in and accessed from a database (e.g., database **116**), or a memory of a mobile device or a wearable device (e.g., client device **102**).

(87) In a first example, the image data includes a two-dimensional image that depicts a puppy running in a grassland. The image data is stored in a memory component of the client device **102**. The volumetric content presentation system **100** access the image data from the memory component based on user input.

(88) In a second examples, the image data includes a two-dimensional image based on a physical copy of a photo depicting the puppy running. The two-dimensional image may be generated by capturing a photo of the physical copy of the running-puppy photo in preparation for further operations.

(89) At operation **804**, the volumetric content presentation system **100** identifies a two-dimensional element depicted in the one or more two-dimensional images. The two-dimensional image element may correspond to either virtual or real-world objects. For example, the two-dimensional image element may correspond to an animal, a person, a plant, a landscape, an architecture, the sun, the moon, or the sky.

(90) For some embodiments, to identify the two-dimensional image element, the volumetric content presentation system **100** performs image segmentation on the image data to identify and extract two-dimensional elements. The volumetric content presentation system **100** may utilize any one or more known digital image processing and computer vision techniques in performing image segmentation including known machine-learning and artificial intelligence image segmentation and classification techniques. For some embodiments, to segment or extract two-dimensional image elements from the one or more two-dimensional images, the volumetric content presentation system **100** relies on a user input to delineate at least some of the two-dimensional elements in the image.

(91) At operation **806**, the volumetric content presentation system **100** generates a volumetric content item based on the two-dimensional elements identified from the image data. The volumetric content item comprises a volumetric representation of the two-dimensional element identified from the two-dimensional image. The volumetric content item is of a format compatible to be presented using a client device, such that the volumetric content item appears to the user

using the client device as parts of, and/or overlaid upon, their surrounding environment (e.g., the real-world environment). Returning to the example of the image of the puppy running in the grassland, a puppy, a grassland, and a sky are identified two-dimensional image elements. A volumetric content item is created for each one or more of the puppy, grassland and sky.

(92) Hence, in some instances, a set of two-dimensional elements can be identified from image data and volumetric content items are only generated for a sub-set of the elements. The selection of the particular two-dimensional element or elements from the two-dimensional image elements identified through image segmentation may be performed automatically by the volumetric content presentation system **100**, for some embodiments. Returning again to the example of the image of the puppy running in the grassland, though the puppy, the grassland, and the blue sky may all be identified based on image segmentation, the volumetric content presentation system **100** may select only the puppy for creation of a volumetric content item.

(93) For some embodiments, to select a particular two-dimensional elements multiple identified two-dimensional elements, the volumetric content presentation system **100** provides an interactive interface operable to receive selection of one of multiple two-dimensional image elements for generation of a volumetric content item. The volumetric content presentation system **100** may, for example, cause the display device to present the interactive interface. The volumetric content presentation system **100** may receive input indicative of a selection of the two-dimensional image element for generation of a volumetric content item based on user interaction with the interactive interface. The interactive interface presents a plurality of two-dimensional image elements segmented from the image data and allows the user to select one or more two-dimensional elements for generation of a volumetric content item. In an example, image data includes a two-dimensional image depicting a road full of cars. The volumetric content presentation system **100** may identify each car as a segmented element of the image. In this example, the interactive interface presents the image in a manner such that the user is able to select a subset of the cars on the road as a basis for the generation of one or more volumetric content items.

(94) At operation **808**, the volumetric content presentation system **100** causes a display device to present the volumetric content item overlaid on a real-world environment that is visible within a field of view of a user of the display device. In this manner, the presentation of the volumetric content item makes the volumetric content items appear to be in the real-world environment.

(95) For some embodiments, the presentation of the volumetric content item overlaid on the real-world environment is based on an association between the volumetric content item and an element (or surface) in the real-world environment. Consistent with these embodiments, the causing of the presentation of the volumetric content item comprises identifying or detecting a real-world element in the real-world environment and generating or identifying an association between volumetric content item and the identified real-world element. Based on the association between the volumetric content item and the identified real-world element, the volumetric content presentation system **100** causes presentation of the volumetric content item overlaid on the real-world environment. For some embodiments, the volumetric content presentation system **100** causes the display device to present the volumetric content item overlaid on the real-world environment at a location within the real-world environment based on the association with the real-world element (e.g., at a location of the real-world element in the real-world environment). The real-world element includes an object or person in the real world. Some example real-world elements are a floor, a wall, and a table. By presenting the volumetric content item overlaid on an associated real-world element, the realism and immersive nature of the AR experience is enhanced. For example, a volumetric content item representing a grassland may be associated with a ground surface and presented as an overlay on the ground surface to provide an AR experience in which the user is standing and able to walk on the grassland.

(96) To generate associations between the volumetric content item and the identified real-world element, the volumetric content presentation system **100** may provide an interactive interface

operable to receive the associations between the volumetric content item and the real-world element. The volumetric content presentation system **100** may, for example, cause the display device to present the interactive interface. The volumetric content presentation system **100** receives input indicative of a selection of the associations between the volumetric content item and the real-world element from the interactive interface.

(97) For some embodiments, the presentation of the volumetric content item may be automatically triggered in response to detecting a location of the wearable device being within a threshold distance of a location depicting by the one or more images. For example, the image data may include one or more images depicting a first location. The volumetric content presentation system **100** may determine the first location based, for example, on metadata associated with the image data. The volumetric content presentation system **100** may determine a second location associated with the display device (e.g., based on location data from the display device, a primary device to which the display device is a companion device, or a companion device of the display device). The volumetric content presentation system **100** may cause presentation of the volumetric content item in response to determining the second location is within the threshold distance of the first location.

(98) For some embodiments, the presentation of the volumetric content item may include presentation of a visual effect in conjunction with the volumetric content item. For example, the volumetric content presentation system **100** may obtain metadata included in or associated with the image data and determine a visual effect to present in conjunction with the volumetric content item based on the obtained metadata. The metadata provides information about the image data including information about a real-world environment associated with the image data. The real-world environment associated with the image data may be the same real-world environment in which the volumetric content item is overlaid or a different real-world environment. In some examples, the information may include weather condition, date, time of the day, people, and location. The information corresponds to the time of creation of the image data. In a specific example, a two-dimensional image depicts a dog running in the rain. Metadata associated with the image includes weather data indicating a rain condition at the time of image generation. The metadata may include machine-generated data and/or user input. Metadata may be obtained from multiple sources including the image data, one or more camera devices that generated the image data, and third-party services.

(99) A visual effect is determined and presented in conjunction with the volumetric content item based on the obtained metadata. The visual effect includes one or more augmentations to be applied to the real-world environment. The visual effect may comprise an animation. In an example, a rain animation is presented in conjunction with the presentation of the volumetric content item based on weather data from the metadata indicating a rain condition.

(100) The volumetric content presentation system **100** causes the display device to apply the generated visual effect to the real-world environment in conjunction with the volumetric content item. The presentation of the visual effect causes the real-world environment to appear to the user as if the real-world environment is under a similar condition under which the two-dimensional image is taken. In an example, the real-world environment is an indoor office, and the metadata indicates a rainy weather condition. A visual effect that includes a rain animation is presented in conjunction with a volumetric content item as overlays on the user's field of view of the indoor office.

(101) For some embodiments, the presentation of the volumetric content item includes a presentation of an animated effect associated with the volumetric content item based on a determined visual effect. The animated effect associated with the volumetric content item comprises a visual enhancement of the volumetric content item that makes it appear to be more consistent with the visual effect generated based on the metadata. In an example, presentation of volumetric representations of a dog, a grassland, and a sky are overlaid on a real-world environment in conjunction with a rain animation visual effect. In this example, the volumetric

content presentation system **100** may cause presentation of three animated effects associated with the volumetric representations of the dog, grassland, and sky. The animated effect associated with the volumetric representation of the dog causes the dog to appear to be soaked; the animated effect associated with the volumetric representation of the grassland causes the grassland to appear to be wet and start to form small ponds; and the animated effect associated with the volumetric representation of the sky causes the sky to appear to be darker. As another example, when a windy visual effect is presented based on metadata, an animated effect associated with the volumetric representation of the dog causes animated wind to blow the hair of the dog.

(102) In some embodiments, the presentation of the volumetric content item includes determining a real-world effect and causing a network-connected device (e.g., an IoT device or other smart device) to provide the real-world effect. The real-world effect may be associated with functionality provided by the network-connected device. Example network-connected devices include, for example, smart fans, smart thermostats, and smart light bulbs. A real-life effect can be created by causing the network-connect device in the real-world environment to perform certain functionality to create a condition in the real-world environment, which may be associated with a visual effect. The real-world effect may be determined from metadata associated with the image data. For example, a windy condition may be a real-world effect determined based on a metadata associated with the image data (e.g., weather data included in the metadata). Based on the determined windy condition associated with the image data, the volumetric content presentation system **100** may cause a smart fan in the real-world environment to be activated, causing a wind-like condition in the real-world environment thereby adding a real-life effect to the presentation of the volumetric content item. In another example, sun-drenched condition associated with the image data is determined based on metadata. In response, the volumetric content presentation system **100** may cause a smart thermostat to be activated at a high temperature and cause a smart light in the real-world environment to change color to bright yellow.

(103) In some embodiments, the presentation the volumetric content item includes a presentation of one or more virtual objects in conjunction with the volumetric content item overlaid on the real-world environment. A virtual object is a computer-generated object that is imaginary, fictional, or no longer exists in the real-world. For example, a virtual object may be a dinosaur, a dragon that breathes fire, zombies, or wizards. The volumetric virtual items generated based on virtual objects may be stored in a library of volumetric virtual items (e.g., stored in the database **116**).

(104) At operation **810**, the volumetric content presentation system **100** generates volumetric content based on the presentation of the volumetric content item overlaid on the real-world environment. The volumetric content may further include audio data comprising one or more audio signals and as such, the presentation of the volumetric content can include presenting one or more audio signals. The new volumetric content comprises the volumetric content item, one or more audio signals, and one or more elements of the real-world environment. In some instances, the volumetric content comprises the volumetric content item and a volumetric representation of the one or more elements of the real-world environment. The volumetric content presentation system **100** stores the volumetric content for subsequent presentation, at operation **812**.

(105) As shown in FIG. **8B**, the method **800** may, in some embodiments, further include operation **814**. Consistent with these embodiments, the operation **814** may be performed as part of operation **804** where the volumetric content presentation system **100** identifies a two-dimensional element depicted in the one or more two-dimensional images. As noted above, the two-dimensional image element may correspond to either virtual or real-world objects such as an animal, a persons, a plant, a landscape, a architecture, the sun, the moon, or the sky. At operation **814**, the volumetric content presentation system **100** performs image segmentation on the image data to identify the two-dimensional element. In performing the image segmentation, the volumetric content presentation system **100** may utilize any one or more known digital image processing and computer vision techniques including known machine-learning and artificial intelligence image segmentation and

classification techniques.

(106) As shown in FIG. 8C, the method **800** may, in some embodiments, further include operations **816** and **818**. Consistent with these embodiments, the operations **816** and **818** may be performed as part of the operation **804** where the volumetric content presentation system **100** identifies a two-dimensional element depicted in the one or more two-dimensional images. At operation **816**, the volumetric content presentation system **100** provides an interactive interface that enables a user to identify the two-dimensional element from the image data. Accordingly, the interactive interface may include a presentation of the image data along with one or more interactive elements that allow the user to select and/or specify a two-dimensional element depicted in the image data. In providing the interactive interface, the volumetric content presentation system **100** may cause a user device (e.g., the client device **102**) to present the interactive interface.

(107) At operation **818**, the volumetric content presentation system **100** receives an input indicative of the user identification of the two-dimensional element. In some examples, the input is generated by the user **124** delineating the two-dimensional element in the image using touch, a gesture, or one or more interactive elements.

(108) As shown in FIG. 8D, the method **800** may, in some embodiments, further include operations **820**, **822**, and **824**. Consistent with these embodiments, the operations **820**, **822**, and **824** may be performed as part of the operation **806** where the volumetric content presentation system **100** causes presentation of the volumetric content item. At operation **820**, the volumetric content presentation system **100** identifies a real-world element in the real-world environment. At operation **822**, the volumetric content presentation system **100** associates the volumetric content item with the real-world element. At operation **824**, the volumetric content presentation system **100** causes presentation of the volumetric content item based on the association with the real-world element. In an example, the volumetric content item is presented at a predefined distance from the real-world element based on the association. In another example, the volumetric content item is presented as an overlay on the real-world element based on the association. In presenting the volumetric content item, the volumetric content presentation system **100** may perform one or more scaling operations to adjust the dimension of the volumetric content item. The adjustments may be determined automatically based on characteristics of the real-world environment and the volumetric content item or the adjustments may be determined based on user input. As an example, the size of the volumetric content item may be adjusted (scaled) to match the size of the real-world element.

(109) With returned reference to the examples illustrated in FIG. 6 and FIGS. 7A and 7B, the volumetric content presentation system **100** identifies the wall **708** as a real-world element (at operation **820**), associates the volumetric content item **612** with the wall **708** (at operation **822**), and the volumetric content presentation system **100** causes presentation of the volumetric content item **612** overlaid on the wall **708** (at operation **824**).

(110) FIG. 9 is a block diagram illustrating an example software architecture **920**, which may be used in conjunction with various hardware architectures herein described. FIG. 9 is a non-limiting example of a software architecture, and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture **920** may execute on hardware such as a machine **1000** of FIG. 10 that includes, among other things, processors **1004**, memory/storage **1006**, and I/O components **1018**. A representative hardware layer **928** is illustrated and can represent, for example, the machine **1000** of FIG. 10. The representative hardware layer **928** includes a processing unit **922** having associated executable instructions **930**. The executable instructions **930** represent the executable instructions of the software architecture **920**, including implementation of the methods, components, and so forth described herein. The hardware layer **928** also includes memory and/or storage modules **924**, which also have the executable instructions **932**. The hardware layer **928** may also comprise other hardware **926**.

(111) In the example architecture of FIG. 9, the software architecture **920** may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software

architecture **920** may include layers such as an operation system **940**, libraries **918**, frameworks/middleware **910**, applications **904**, and a presentation layer **902**. Operationally, the applications **904** and/or other components within the layers may invoke API calls **942** through the software stack and receive a response to the API calls **942** as messages **944**. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special-purpose operating systems may not provide a frameworks/middleware **910**, while others may provide such a layer. Other software architectures may include additional or different layers.

(112) The operation system **940** may manage hardware resources and provide common services. The operation system **940** may include, for example, a kernel **934**, services **936**, and drivers **938**. The kernel **934** may act as an abstraction layer between the hardware and the other software layers. For example, the kernel **934** may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services **936** may provide other common services for the other software layers. The drivers **938** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **938** include display drivers, camera drivers, Bluetooth® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), Wi-Fi® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration.

(113) The libraries **918** provide a common infrastructure that is used by the applications **904** and/or other components and/or layers. The libraries **918** provide functionality that allows other software components to perform tasks in an easier fashion than by interfacing directly with the underlying operation system **940** functionality (e.g., kernel **934**, services **936**, and/or drivers **938**). The libraries **918** may include system libraries **912** (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematical functions, and the like. In addition, the libraries **918** may include API libraries **914** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as MPEG4, H.294, MP3, AAC, AMR, JPG, and PNG), graphics libraries (e.g., an OpenGL framework that may be used to render 2D and 3D graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries **918** may also include a wide variety of other libraries **916** to provide many other APIs to the applications **904** and other software components/modules.

(114) The frameworks/middleware **910** provide a higher-level common infrastructure that may be used by the applications **904** and/or other software components/modules. For example, the frameworks/middleware **910** may provide various GUI functions, high-level resource management, high-level location services, and so forth. The frameworks/middleware **910** may provide a broad spectrum of other APIs that may be utilized by the applications **904** and/or other software components/modules, some of which may be specific to a particular operating operation system **940** or platform.

(115) The applications **904** include built-in applications **906** and/or third-party applications **908**. Examples of representative built-in applications **906** may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, and/or a game application. The third-party applications **908** may include an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform and may be mobile software running on a mobile operating system such as IOS™ ANDROID™, WINDOWS® Phone, or other mobile operating systems. The third-party applications **908** may invoke the API calls **942** provided by the mobile operating system (such as the operating operation system **940**) to facilitate functionality described herein.

(116) The applications **904** may use built-in operating system functions (e.g., kernel **934**, services **936**, and/or drivers **938**), libraries **918**, and frameworks/middleware **910** to create user interfaces to

interact with users of the system. Alternatively, or additionally, in some systems interactions with a user may occur through a presentation layer, such as the presentation layer **902**. In these systems, the application/component “logic” can be separated from the aspects of the application/component that interact with a user.

(117) FIG. **10** is a block diagram illustrating components of a machine **1000**, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **10** shows a diagrammatic representation of the machine **1000** in the example form of a computer system, within which instructions **1010** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1000** to perform any one or more of the methodologies discussed herein may be executed. As such, the instructions **1010** may be used to implement modules or components described herein. The instructions **1010** transform the general, non-programmed machine **1000** into a particular machine **1000** programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine **1000** operates as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1000** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1000** may comprise, but not be limited to, a server computer, a client computer, a PC, a tablet computer, a laptop computer, a netbook, a set-top box (STB), a PDA, an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1010**, sequentially or otherwise, that specify actions to be taken by the machine **1000**. Further, while only a single machine **1000** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the method **800** to perform any one or more of the methodologies discussed herein.

(118) The machine **1000** may include processors **1004**, memory/storage **1006**, and I/O components **1018**, which may be configured to communicate with each other such as via a BUS **1002**. In an example embodiment, the processors **1004** (e.g., a CPU, a reduced instruction set computing (RISC) processor, a complex instruction set computing (CISC) processor, a GPU, a digital signal processor (DSP), an ASIC, a radio-frequency integrated circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **1008** and a processor **1016** that may execute the instructions **1010**. Although FIG. **10** shows multiple processors **1004**, the machine **1000** may include a single processor with a single core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiple cores, or any combination thereof.

(119) The memory/storage **1006** may include a memory **1012**, such as a main memory, or other memory storage, and a storage unit **1014**, both accessible to the processors **1004** such as via the BUS **1002**. The storage unit **1014** and memory **1012** store the instructions **1010** embodying any one or more of the methodologies or functions described herein. The instructions **1010** may also reside, completely or partially, within the memory **1012**, within the storage unit **1014**, within at least one of the processors **1004** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1000**. Accordingly, the memory **1012**, the storage unit **1014**, and the memory of the processors **1004** are examples of machine-readable media.

(120) The I/O components **1018** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1018** that are included in a particular machine **1000** will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless

server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1018** may include many other components that are not shown in FIG. **10**. The I/O components **1018** are grouped according to functionality merely for simplifying the following discussion, and the grouping is in no way limiting. In various example embodiments, the I/O components **1018** may include output components **1026** and input components **1028**. The output components **1026** may include visual components (e.g., a display such as a plasma display panel (PDP), a light-emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input component **1028** may include alphanumeric input components (e.g., a keyboard, a touch screen display configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a physical button, a touch screen display that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(121) In further example embodiments, the I/O components **1018** may include biometric components **1030**, motion components **1034**, environment components **1036**, or position components **1038**, among a wide array of other components. For example, the biometric components **1030** may include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion components **1034** may include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environment components **836** may include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas sensors to detect concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position component **1038** may include location sensor components (e.g., a Global Positioning System (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(122) Communication may be implemented using a wide variety of technologies. The I/O components **1018** may include communication components **1040** operable to couple the machine **1000** to a network **1032** or devices **1020** via a coupling **1024** and a coupling **1022**, respectively. For example, the communication components **1040** may include a network interface component or other suitable device to interface with the network **1032**. In further examples, the communication components **1040** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1020** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(123) Moreover, the communication components **1040** may detect identifiers or include components operable to detect identifiers. For example, the communication components **840** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection

components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF4114, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1040**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

Glossary

(124) “CARRIER SIGNAL” in this context refers to any intangible medium that is capable of storing, encoding, or carrying instructions for execution by a machine, and includes digital or analog communications signals or other intangible media to facilitate communication of such instructions. Instructions may be transmitted or received over a network using a transmission medium via a network interface device and using any one of a number of well-known transfer protocols.

(125) “CLIENT DEVICE” in this context refers to any machine that interfaces to a communications network to obtain resources from one or more server systems or other client devices. A client device may be, but is not limited to, a mobile phone, desktop computer, laptop, PDA, smart phone, tablet, ultra book, netbook, laptop, multi-processor system, microprocessor-based or programmable consumer electronics system, game console, set-top box, or any other communication device that a user may use to access a network.

(126) “COMMUNICATIONS NETWORK” in this context refers to one or more portions of a network that may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, a network or a portion of a network may include a wireless or cellular network, and the coupling to the network may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or another type of cellular or wireless coupling. In this example, the coupling may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High-Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long-Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long-range protocols, or other data transfer technology.

(127) “MACHINE-READABLE MEDIUM” in this context refers to a component, device, or other tangible medium able to store instructions and data temporarily or permanently, and may include, but is not limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EPROM)), and/or any suitable combination thereof. The term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions. The term “machine-readable medium” shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., code) for execution by a machine, such that the instructions, when executed by one or more processors of the machine, cause the machine to perform any one or more of the methodologies described herein. Accordingly, a “machine-

readable medium” refers to a single storage apparatus or device, as well as “cloud-based” storage systems or storage networks that include multiple storage apparatus or devices. The term “machine-readable medium” excludes signals per se.

(128) “COMPONENT” in this context refers to a device, a physical entity, or logic having boundaries defined by function or subroutine calls, branch points, APIs, or other technologies that provide for the partitioning or modularization of particular processing or control functions. Components may be combined via their interfaces with other components to carry out a machine process. A component may be a packaged functional hardware unit designed for use with other components and a part of a program that usually performs a particular function of related functions. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components.

(129) A “HARDWARE COMPONENT” is a tangible unit capable of performing certain operations and may be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein. A hardware component may also be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. A hardware component may be a special-purpose processor, such as a field-programmable gate array (FPGA) or an ASIC. A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor.

(130) Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations. Accordingly, the phrase “hardware component” (or “hardware-implemented component”) should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein.

(131) Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time.

(132) Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have

access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information).

(133) The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more processors. Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components.

(134) Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an application programming interface (API)). The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

(135) “PROCESSOR” in this context refers to any circuit or virtual circuit (a physical circuit emulated by logic executing on an actual processor) that manipulates data values according to control signals (e.g., “commands,” “op codes,” “machine code,” etc.) and which produces corresponding output signals that are applied to operate a machine. A processor may, for example, be a CPU, a RISC processor, a CISC processor, a GPU, a DSP, an ASIC, a RFIC, or any combination thereof. A processor may further be a multi-core processor having two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously.

(136) “TIMESTAMP” in this context refers to a sequence of characters or encoded information identifying when a certain event occurred, (for example, giving date and time of day) sometimes accurate to a small fraction of a second.

Claims

1. A method, comprising: identifying a two-dimensional element from one or more two-dimensional images; generating a volumetric content item based on the two-dimensional element identified from the one or more two-dimensional images, the volumetric content item representing the two-dimensional element; identifying a real-world element in a real-world environment; associating the volumetric content item with the real-world element in the real-world environment; presenting an interactive interface operable to receive an association between the volumetric content item and the real-world element; receiving an input indicative of the association between the volumetric content item and the real-world element; and causing presentation, by a display device, of the volumetric content item overlaid on the real-world environment at a location based on the association, the real-world environment being is within a field of view of a user of the

display device.

2. The method of claim 1, wherein the interactive interface is a second interactive interface, and the method further comprises: providing a first interactive interface operable to receive user identification of the two-dimensional element from the one or more two-dimensional images; and receiving an input indicative of the user identification of the two-dimensional element, wherein the identifying of the two-dimensional element is based on the input.

3. The method of claim 1, wherein the identifying of the two-dimensional element from the one or more two-dimensional images comprises performing image segmentation on the one or more two-dimensional images.

4. The method of claim 1, wherein the causing of presentation of the volumetric content item overlaid on the real-world environment comprises: causing presentation of one or more virtual objects in conjunction with the volumetric content item.

5. The method of claim 4, wherein the one or more virtual objects comprise one or more computer-generated objects that are imaginary.

6. The method of claim 1, further comprising: obtaining a metadata associated with the one or more two-dimensional images; generating a visual effect based on the metadata, the visual effect includes one or more augmentations to be applied to the real-world environment; and causing presentation, by the display device, of the visual effect applied to the real-world environment.

7. The method of claim 6, wherein the causing of the presentation of the visual effect applied to the real-world environment comprises causing presentation of an animated effect in conjunction with the volumetric content item.

8. The method of claim 1, further comprising: obtaining a metadata associated with the one or more two-dimensional images; determining a real-world effect based on the metadata, real-world effect being associated with functionality provided by a network-connected device; and causing the network-connected device in the real-world environment to provide the real-world effect.

9. The method of claim 1, further comprising: generating volumetric content based on the presentation of the volumetric content item overlaid on the real-world environment; and storing the volumetric content for subsequent presentation.

10. The method of claim 1, wherein: the one or more images depict a first location; and the method further comprises: determining a second location associated with the display device; determining the second location is within a threshold distance of the first location; and the causing of the presentation of the volumetric content item is in response to determining the second location is within the threshold distance of the first location.

11. A system comprising: one or more hardware processors; and at least one memory storing instructions that cause the one or more hardware processors to perform operations comprising: identifying a two-dimensional element from one or more two-dimensional images; generating a volumetric content item based on the two-dimensional element identified from the one or more two-dimensional images; identifying a real-world element in a real-world environment; associating the volumetric content item with the real-world element in the real-world environment; presenting an interactive interface operable to receive an association between the volumetric content item and the real-world element; receiving an input indicative of the association between the volumetric content item and the real-world element; and causing presentation, by a display device, of the volumetric content item overlaid on the real-world environment at a location based on the association, the real-world environment being within a field of view of a user of the display device.

12. The system of claim 11, wherein the interactive interface is a second interactive interface, and the operations further comprise: providing a first interactive interface operable to receive user identification of the two-dimensional element from the one or more two-dimensional images; and receiving an input indicative of the user identification of the two-dimensional element, wherein the identifying of the two-dimensional element is based on the input.

13. The system of claim 11, wherein the identifying of the two-dimensional element from the one

or more two-dimensional images comprises performing image segmentation on the one or more two-dimensional images.

14. The system of claim 11, wherein the causing of presentation of the volumetric content item overlaid on the real-world environment comprises: causing presentation of one or more virtual objects in conjunction with the volumetric content item.

15. The system of claim 14, wherein the one or more virtual objects comprise one or more computer-generated objects that are imaginary.

16. The system of claim 11, wherein the operations further comprising: obtaining a metadata associated with the one or more two-dimensional images; generating a visual effect based on the metadata, the visual effect includes one or more augmentations to be applied to the real-world environment; and causing presentation, by the display device, of the visual effect applied to the real-world environment.

17. The system of claim 16, wherein the causing of the presentation of the visual effect applied to the real-world environment comprises causing presentation of an animated effect in conjunction with the volumetric content item.

18. The system of claim 11, wherein the operations further comprising: obtaining a metadata associated with the one or more two-dimensional images; determining a real-world effect based on the metadata, the real-world effect being associated with functionality provided by a network-connected device; and causing the network-connected device in the real-world environment to provide the real-world effect.

19. The system of claim 11, wherein the operations further comprising: generating volumetric content based on the presentation of the volumetric content item overlaid on the real-world environment; and storing the volumetric content for subsequent presentation.

20. A machine-readable medium storing instructions that, when executed by a computer system, cause the computer system to perform operations comprising: identifying a two-dimensional element from one or more two-dimensional images; generating a volumetric content item based on the two-dimensional element identified from the one or more two-dimensional images; identifying a real-world element in a real-world environment; associating the volumetric content item with the real-world element in the real-world environment; presenting an interactive interface operable to receive an association between the volumetric content item and the real-world element; receiving an input indicative of the association between the volumetric content item and the real-world element; and causing presentation, by a display device, of the volumetric content item overlaid on the real-world environment at a location based on the association, the real-world environment being within a field of view of a user of the display device.
