



US 20250280807A1

(19) **United States**

(12) **Patent Application Publication**
Taylor

(10) **Pub. No.: US 2025/0280807 A1**

(43) **Pub. Date: Sep. 11, 2025**

(54) **FISHING LURE**

Publication Classification

(71) Applicant: **Suede Taylors**, San Antonio, TX (US)

(51) **Int. Cl.**
A01K 85/01 (2006.01)

(72) Inventor: **Michael Maurice Taylor**, San Antonio, TX (US)

A01K 85/18 (2006.01)

(52) **U.S. Cl.**
CPC **A01K 85/018** (2022.02); **A01K 85/18** (2013.01)

(21) Appl. No.: **18/898,299**


(22) Filed: **Sep. 26, 2024**

Related U.S. Application Data

(63) Continuation-in-part of application No. 29/931,204, filed on Mar. 5, 2024.

(57) **ABSTRACT**

A fishing lure designed with an internal cavity filled with a scented material and an odor release hole. The fishing lure mimics a fish, with a tail and head that move in a swimming motion. As the fishing lure moves through the water, the scent is gradually released, creating a continuous odor trail that attracts fish.






FIG. 1




FIG. 2





FIG. 3



4
G
H
L




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

FISHING LURE

FIELD OF THE INVENTION

[0001] The present invention relates generally to fishing. More specifically, the present invention is an odor releasing fishing lure.

BACKGROUND OF THE INVENTION

[0002] Fishing is an ancient practice that involves the capture of fish using various techniques and tools. Over the centuries, fishing methods have evolved, with modern anglers employing sophisticated equipment to increase the efficiency and success of their efforts. One critical tool in fishing is the lure, which is designed to attract fish and simulate the appearance and movement of prey or bait. Lures come in various forms, including spoons, jigs, spinners, and soft plastics, and their purpose is to mimic the behavior of live bait in the water, enticing fish to strike.

[0003] A fishing lure generally relies on visual stimuli and movement to attract fish. Some modern lures incorporate noise-making features or reflective materials to further enhance their effectiveness. However, one essential aspect of natural bait that remains difficult to replicate in artificial lures is scent. Fish, particularly species like bass, trout, and catfish, often rely on their sense of smell to locate and identify prey. Natural bait, such as worms, minnows, or insects, release odors that fish associate with food, prompting them to strike. Artificial lures, while effective in replicating the appearance and movement of prey, generally lack the ability to release a scent that mimics natural bait. As a result, the absence of scent in artificial lures can reduce their effectiveness, particularly in situations where fish are not actively hunting by sight or sound.

[0004] Several attempts have been made to address the lack of scent in artificial lures. In some prior art, scented attractants are manually applied to the exterior of lures before casting, but these attractants tend to wash off quickly, particularly after repeated casts or exposure to water. This results in the need for frequent reapplication, which is inconvenient for anglers and interrupts the fishing experience. Other artificial lures are constructed from materials infused with scents, which release the odor over time. However, these lures often degrade quickly, losing their scent as the material wears down or becomes less effective after extended use. Additionally, the scent release from these lures is not always controlled or consistent, leading to either too little or too much odor being emitted at different points during use.

[0005] The problems with the prior art can be summarized as follows: First, the manual application of scent to lures is inefficient and temporary, often requiring anglers to pause their fishing activity to reapply attractants. Second, lures infused with scent material degrade over time, losing their effectiveness and requiring replacement. Third, the inconsistent or uncontrollable release of scent from existing solutions limits their overall effectiveness. These issues demonstrate a clear gap in the current state of artificial lure technology, where a controlled and continuous release of scent is highly desired but remains underdeveloped.

[0006] The objectives of the prior art have typically focused on replicating the appearance and movement of natural prey, while scent has been a secondary consideration. Although efforts have been made to incorporate scent into

artificial lures, these attempts have failed to provide a solution that offers both durability and consistency in scent release.

[0007] The present invention addresses the shortcomings of the prior art by providing a fishing lure that not only replicates the appearance and movement of natural bait but also incorporates a controlled and continuous release of scent. The present invention is a fishing lure resembling a fish or other bait animal, equipped with an internal cavity and an odor release hole. In the preferred embodiment, the cavity is filled with a scented material that mimics the odor of natural bait, attracting fish through their sense of smell. As the lure moves through the water, the scent is gradually released through the odor release hole, creating a continuous scent trail that lures fish toward the bait.

[0008] By incorporating an internal cavity and odor release hole, the present invention overcomes the problem of scent washing off quickly, as experienced with manually applied attractants. Unlike lures infused with scent, the present invention allows for a more controlled and prolonged release of the scent, ensuring the lure remains effective for longer periods of time. The design of the present invention also prevents premature degradation of the lure, allowing it to maintain its structural integrity and effectiveness throughout extended fishing sessions.

[0009] In conclusion, the present invention represents a significant advancement in the field of fishing lures by offering a solution that addresses the key issues of durability, scent consistency, and ease of use. The continuous release of scent from the internal cavity provides anglers with a more effective tool for attracting fish, improving their chances of success while reducing the need for constant reapplication of scented attractants.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a perspective view of the present invention.

[0011] FIG. 2 is a side view of the head of the present invention.

[0012] FIG. 3 is a side view of the tail of the present invention.

[0013] FIG. 4 is a right-side view of the present invention.

[0014] FIG. 5 is a right side view of an alternate embodiment of the present invention.

[0015] FIG. 6 is a left-side view of the present invention.

[0016] FIG. 7 is a right-side view of an alternate embodiment of the present invention.

[0017] FIG. 8 is a perspective view of the present invention.

[0018] FIG. 9 is a perspective view of an alternate embodiment of the present invention.

[0019] FIG. 10 is a perspective view of an alternate embodiment of the present invention.

[0020] FIG. 11 is a perspective view of an alternate embodiment of the present invention.

DETAIL DESCRIPTIONS OF THE INVENTION

[0021] All illustrations of the drawings are for the purpose of describing selected versions of the present invention and are not intended to limit the scope of the present invention.

[0022] As a preliminary matter, it will readily be understood by one having ordinary skill in the relevant art that the present disclosure has broad utility and application. As

should be understood, any embodiment may incorporate only one or a plurality of the above-disclosed aspects of the disclosure and may further incorporate only one or a plurality of the above-disclosed features. Furthermore, any embodiment discussed and identified as being “preferred” is considered to be part of a best mode contemplated for carrying out the embodiments of the present disclosure. Other embodiments also may be discussed for additional illustrative purposes in providing a full and enabling disclosure. Moreover, many embodiments, such as adaptations, variations, modifications, and equivalent arrangements, will be implicitly disclosed by the embodiments described herein and fall within the scope of the present disclosure.

[0023] Accordingly, while embodiments are described herein in detail in relation to one or more embodiments, it is to be understood that this disclosure is illustrative and exemplary of the present disclosure, and are made merely for the purposes of providing a full and enabling disclosure. The detailed disclosure herein of one or more embodiments is not intended, nor is to be construed, to limit the scope of patent protection afforded in any claim of a patent issuing here from, which scope is to be defined by the claims and the equivalents thereof. It is not intended that the scope of patent protection be defined by reading into any claim a limitation found herein that does not explicitly appear in the claim itself.

[0024] Additionally, it is important to note that each term used herein refers to that which an ordinary artisan would understand such term to mean based on the contextual use of such term herein. To the extent that the meaning of a term used herein—as understood by the ordinary artisan based on the contextual use of such term—differs in any way from any particular dictionary definition of such term, it is intended that the meaning of the term as understood by the ordinary artisan should prevail.

[0025] Furthermore, it is important to note that, as used herein, “a” and “an” each generally denotes “at least one,” but does not exclude a plurality unless the contextual use dictates otherwise. When used herein to join a list of items, “or” denotes “at least one of the items,” but does not exclude a plurality of items of the list. Finally, when used herein to join a list of items, “and” denotes “all of the items of the list.”

[0026] The following detailed description refers to the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the following description to refer to the same or similar elements. While many embodiments of the disclosure may be described, modifications, adaptations, and other implementations are possible. For example, substitutions, additions, or modifications may be made to the elements illustrated in the drawings, and the methods described herein may be modified by substituting, reordering, or adding stages to the disclosed methods. Accordingly, the following detailed description does not limit the disclosure. Instead, the proper scope of the disclosure is defined by the appended claims. The present disclosure contains headers. It should be understood that these headers are used as references and are not to be construed as limiting upon the subjected matter disclosed under the header.

[0027] Other technical advantages may become readily apparent to one of ordinary skill in the art after review of the following figures and description. It should be understood at the outset that, although exemplary embodiments are illus-

trated in the figures and described below, the principles of the present disclosure may be implemented using any number of techniques, whether currently known or not. The present disclosure should in no way be limited to the exemplary implementations and techniques illustrated in the drawings and described below.

[0028] Unless otherwise indicated, the drawings are intended to be read together with the specification, and are to be considered a portion of the entire written description of this invention. As used in the following description, the terms “horizontal”, “vertical”, “left”, “right”, “up”, “down” and the like, as well as adjectival and adverbial derivatives thereof (e.g., “horizontally”, “rightwardly”, “upwardly”, “radially”, etc.), simply refer to the orientation of the illustrated structure as the particular drawing figure faces the reader. Similarly, the terms “inwardly”, “outwardly” and “radially” generally refer to the orientation of a surface relative to its axis of elongation, or axis of rotation, as appropriate.

[0029] The present disclosure includes many aspects and features. Moreover, while many aspects and features relate to, and are described in the context of a fishing lure **1**, embodiments of the present disclosure are not limited to use only in this context.

[0030] As shown in FIG. 1, the present invention is a fishing lure **1** comprising a packing hole **17** and an at least one odor release hole **18** wherein the packing hole **17** is a cavity extruded into the fishing lure **1**. In the context of the present invention, the at least one odor release hole **18** is a through hole traversing outwardly from the packing hole **17** through the fishing lure **1**.

[0031] Furthermore, as shown in FIG. 1, in the context of the present invention, the fishing lure further comprises a top surface **14**, a bottom surface **15**, and a plurality of lateral surfaces **16**. In the context of the present invention, the top surface **14** is the top-most outwardly facing surface of the fishing lure **1**. Likewise, in the context of the present invention, the bottom surface **15** is the bottom-most outwardly facing surface of the fishing lure **1**. Further, in the context of the present invention, the plurality of lateral sides **16**, in the preferred embodiment comprising two lateral sides (shown in FIG. 4 and FIG. 6), are opposing sides of the fishing lure (left and right sides). Additionally, in the preferred embodiment of the present invention, the top surface **14**, the bottom surface **15**, and the lateral sides **16** are configured in a manner that are depictive of a fish. Furthermore, as shown in FIG. 1, the present invention further comprises a plurality of eyelets **19** wherein said plurality of eyelets **19** are positioned about the fishing lure **1**, enabling the connection of an at least one hook **110** and a fishing line.

[0032] In the preferred embodiment of the present invention, the fishing lure further comprises a head **11**, a trunk **12**, and a tail **13**, as shown in FIG. 1, wherein the head **11** composes a forward-most portion of the fishing lure **1**, the tail **13** composes the rearward-most portion of the fishing lure **1**, and the trunk **12** is interposed between the head **11** and the tail **13**. In some embodiments of the present invention, the trunk **12** is configured to permit differing movement between the head **11** and the tail **13**. In the preferred embodiment of the present invention, the movement is similar to a fish’s swimming motion.

[0033] As shown in FIG. 2, in the preferred embodiment of the present invention, the head **11** of the fishing lure **1** comprises at least one of the plurality of eyelets **19**. In the

preferred embodiment of the present invention, one eyelet is configured at the forward-most portion of the head **1**. In such an embodiment, the fishing line is attached to the forward-most eyelet of the head **11** and used to pull the fishing lure **1** through the water, mimicking a fish swimming through water. Additionally, in the preferred embodiment, an eyelet is attached to the bottom surface **15** of the fishing lure **1**, enabling attachment of the at least one hook **110**. In some embodiments of the present invention, the head **11** comprises a decorative element **111**. In the context of the present invention, a decorative element **111** is an element intended to depict portions of a fish such as an eye, gills, fins, and other ornamental characteristics of a fish.

[0034] As shown in FIG. 3, in the preferred embodiment of the present invention, the tail **13** comprises at least one of the plurality of eyelets **19**, wherein said eyelet is positioned on the bottom surface of the fishing lure **1**. In the preferred embodiment of the present invention, the tail **13** of the present invention is depictive of a fish tail.

[0035] In the preferred embodiment of the present invention, as shown in FIG. 2, FIG. 3, and FIG. 4, is composed of a plurality of interlocking eyelets **19**. In such embodiments as shown in FIG. 2 and FIG. 3, a rear most portion of the head **11** and the front-most portion of the tail **13**, each comprise an eyelet **121**, wherein said eyelets **121** are coupled together, as shown in FIG. 4, to compose the trunk **12**. In the preferred embodiment of the present invention, the eyelets **121** are configured in a manner as to allow unimpeded movement between the head **11** and the tail **13** of the present invention.

[0036] In some embodiments of the present invention, as shown in FIG. 5, the head **11**, the trunk **12**, and the tail **13** are composed of a solid member. In such an embodiment, the trunk **12** is rigid, thereby securing the head **11** and tail **13** together in a manner that moves both members **11,13** simultaneously.

[0037] In the preferred embodiment of the present invention, the packing hole **17** is a cavity traversing from the top surface **14** into the fishing lure **1**. As shown in FIG. 6, in some embodiments of the present invention, the packing hole **17** traverses the head **11** of the present invention from the top surface **14**, wherein the at least one odor release hole **18** traverses a lateral surface **16** of the head **11** into the packing hole **17**. In the preferred embodiment of the present invention, the at least one odor release hole **18**, comprises two odor release holes **18**, wherein each odor release hole **18** traverses into the packing hole **17** from each lateral side (as shown in FIG. 4 and FIG. 6). In some embodiments of the present invention, the packing hole **17** traverses the fishing lure **1** from the top surface **14** through the bottom surface **15**, as shown in FIG. 7. In the context of the present invention, the packing hole **17** provides an upward force to an odorous material **2** thereby preventing the odorous material **2** from falling out. In embodiments wherein the packing hole traverses a portion of the fishing lure **1**, the upward force (reaction force) is provided by a bottom-most portion of the packing hole **17**. In an embodiment of the present invention wherein the packing hole **17** traverses the fishing lure **1** from the top surface **14** to the bottom surface **15**, the packing hole is angled, thereby providing an upward reaction force to the odorous material **2**, preventing the odorous material **2** from falling through the packing hole **17**.

[0038] In the preferred embodiment of the present invention, as shown in FIG. 8, FIG. 9, FIG. 10, and FIG. 11, the

fishing lure **1** further comprises an odorous material **2** wherein said odorous material **2** is interposed into the packing hole **17**. In the context of the present invention, an odorous material **2** is a material that releases a fish attracting scent. In the context of the present invention, a fish attracting scent is an odor resembling worms, fish liver, fish, and other scents possessed by baits known to those within the art. In the preferred embodiment of the present invention, as the fishing lure **1** maneuvers through water, particulate matter of odorous material **2**, and thus an odor, are discarded through the at least one odor release hole **18**. In some embodiments of the present invention, the fishing lure **1** further comprises a fastener wherein said fastener prevents the odorous material **2** from expelling through the packing hole **18**. In some embodiments of the present invention, the fastener **172** is selected from a plug **172a**, a band **172b**, and a pin **172c**. In an embodiment wherein the fastener is a plug **172a**, the plug **172a** is secured into the packing hole **17**, thereby preventing the odorous material **2** from expelling through the packing hole **17**. Likewise, in embodiments wherein the fastener **172** is a band **172b**, the band **172b** is positioned around the fishing lure **1**, traversing the packing hole **17**, thereby securing the odorous material **2** within the packing hole **17**. Lastly, in embodiments wherein the fastener is a pin **172c**, the pin **172c** is inserted through the odor release holes **18**, piercing the odorous material **2**, and securing said odorous material **2** within the packing hole **17**.

[0039] Although the invention has been explained in relation to its preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the spirit and scope of the invention.

What is claimed is:

1. A fishing lure comprising:
 - a top surface;
 - a plurality of lateral sides;
 - a packing hole; and
 - an at least one odor release hole;
 wherein:
 - the top surface is the top-most outwardly surface of the fishing lure;
 - the packing hole traverses at least a portion of the fishing lure from the top surface; and
 - the at least one odor release hole traverses at least one of the lateral sides into the packing hole.
2. The fishing lure, as claimed in claim 1 wherein the packing hole further comprises an odorous material.
3. The fishing lure, as claimed in claim 2 wherein the fishing lure resembles a fish comprising:
 - a head;
 - a trunk; and
 - a tail;
 wherein:
 - the head composes the front-most portion of the fishing lure;
 - the tail composes the rear-most portion of the fishing lure; and
 - the trunk is interposed between the head and the tail.
4. The fishing lure, as claimed in claim 3, wherein the trunk comprises a plurality of eyelets wherein:
 - at least one of the plurality of eyelets are coupled to a rear-most portion of the head;
 - at least one of the plurality of eyelets are coupled to the front-most portion of the tail; and

the at least one eyelet of the head and the at least one eyelet of the tail are interlocked together, thus composing the trunk.

5. The fishing lure, as claimed in claim 2, wherein the packing hole further comprises a plug, wherein said plug is inserted into the packing hole, thereby preventing the odorous material from expelling through the packing hole.

6. The fishing lure, as claimed in claim 2, wherein the packing hole further comprises a band wherein said band is configured around the fishing lure, covering the packing hole, thereby preventing the odorous material from expelling through the packing hole.

7. The fishing lure, as claimed in claim 2, wherein a pin traverses the lateral sides of the fishing lure through the scent release holes and piercing the odorous material, thereby preventing the odorous material from expelling through the packing hole.

8. The fishing lure, as claimed in claim 3, wherein the bottom surface an a front most portion of the head, each comprise an eyelet.

9. The fishing lure, as claimed in claim 8, wherein the eyelet of the bottom surface comprises a hook.

10. The fishing lure, as claimed in claim 2, wherein particulate matter of the odorous material is released through the at least one odor release hole.

11. The fishing lure, as claimed in claim 3, further comprising a bottom surface;

the bottom surface being opposite the top surface; and the packing hole traversing from the top surface through the bottom surface.

12. A fishing lure comprising:

a top surface;

a plurality of lateral sides; and

an at least one odor release hole;

wherein:

the fishing lure resembles a fish comprising a head, a trunk, and a tail;

the head composes the front-most portion of the fishing lure;

the tail composes the rear-most portion of the fishing lure;

the trunk is interposed between the head and the tail;

the top surface is the top-most outwardly surface of the fishing lure;

the at least one odor release hole traverses at least one of the lateral sides.

13. The fishing lure, as claimed in claim 12, wherein the trunk comprises a plurality of eyelets wherein:

at least one of the plurality of eyelets are coupled to a rear-most portion of the head;

at least one of the plurality of eyelets are coupled to the front-most portion of the tail; and

the at least one eyelet of the head and the at least one eyelet of the tail are interlocked together, thus composing the trunk.

14. The fishing lure, as claimed in claim 13, further comprising a packing hole;

wherein the packing hole traverses into a portion of the fishing lure from the top surface;

15. The fishing lure, as claimed in claim 14, wherein the packing hole comprises an odorous material; wherein particulate matter from the odorous material is expelled through the at least one odor release hole.

16. The fishing lure, as claimed in claim 15 wherein the odorous material is prevented from expelling through the packing hole by a fastener selected from the following consisting of: a plug; a band; and a pin.

17. The fishing lure, as claimed in claim 16, further comprising:

a plurality of eyelets; and

an at least one hook;

wherein:

at least one eyelet of the plurality of eyelets is attached to a bottom surface of the fishing lure;

the bottom surface of the fishing lure being opposite the top surface;

the at least one hook coupling to the at least one eyelet on the bottom surface.

18. A fishing lure comprising:

a plurality of lateral sides;

an at least one odor release hole; and

a packing hole;

wherein:

the fishing lure resembles a fish comprising a head, a trunk, and a tail;

the head composes the front-most portion of the fishing lure;

the tail composes the rear-most portion of the fishing lure;

the trunk is interposed between the head and the tail;

the trunk comprises a plurality of eyelets wherein:

at least one of the plurality of eyelets are coupled to a rear-most portion of the head;

at least one of the plurality of eyelets are coupled to the front-most portion of the tail; and

the at least one eyelet of the head and the at least one eyelet of the tail are interlocked together, thus composing the trunk.

the at least one odor release hole traverses at least one of the lateral sides into the packing hole.

19. The fishing lure, as claimed in claim 18 wherein:

the packing hole further comprising an odorous material; the odorous material is prevented from expelling through the packing hole by a fastener selected from the following consisting of: a plug; a band; and a pin.

20. The fishing lure, as claimed in claim 18, wherein particulate matter of the odorous material is expelled from the packing hole through the at least one odor release hole.

* * * * *