

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285406

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Yamada; Tetsushi et al.

METHOD TO EXTRACT COLOR AND TEXTURE INFORMATION FROM ROCK PARTICLE INSTANCE IMAGES

Abstract

Systems and methods are provided to extract features (e.g., colors, textual features) from arbitrary shaped and sized images by implementing global average pooling (GAP) and partial convolution in an autoencoder (AE) for analysis of the images. A global average pooling (GAP) layer may be used at the last layer of the encoder of the AE to make the feature rotation and translation invariant and scale equivariant. In addition, partial convolution may be used in the encoder to logically ignore the invalid pixels (e.g., background, image error, other object) or any pixel (e.g., in any area) in the images.

Inventors: Yamada; Tetsushi (Cambridge, MA), Di Santo; Simone (Dhahran, SA), Bondabou; Karim (Montpellier, FR)

Applicant: Schlumberger Technology Corporation (Sugar Land, TX)

Family ID: 1000008166549

Appl. No.: 18/888739

Filed: September 18, 2024

Related U.S. Application Data

us-provisional-application US 63562275 20240307

Publication Classification

Int. Cl.: G06V10/44 (20220101); G06V10/54 (20220101); G06V10/56 (20220101); G06V10/771 (20220101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims priority to U.S. Provisional Application No. 63/562,275, filed Mar. 7, 2024, which is incorporated by reference herein in its entirety.

BACKGROUND

[0002] The present disclosure generally relates to systems and methods for extracting color and texture information from rock particle instance images, and, more specifically, to the integration of global average pooling (GAP) and partial convolution in an autoencoder (AE) for analysis of the images of the rock particles.

[0003] This section is intended to introduce the reader to various aspects of art that may be related to various aspects of the present techniques, which are described and/or claimed below. This discussion is believed to be helpful in providing the reader with background information to facilitate a better understanding of the various aspects of the present disclosure. Accordingly, it should be understood that these statements are to be read in this light, and not as an admission of any kind.

[0004] Rock particles are usually a fundamental unit of domain-specific post-processing analysis that has been widely used in industry and scientific applications, including, but not limited to, space exploration, mining, civil engineering, geothermal, and oil and gas. Image data of the rock particles typically come from imaging systems that produce digital images or three-dimensional (3D) images from a laser scanner. Once rock particles are detected and segmented, they may be used to compute the rock particle properties such as size, shapes, textures, and other morphological, rock properties and petrophysical properties to answer domain-specific questions.

[0005] In oil and gas, geothermal, as well as scientific exploration applications, rock particles are produced during drilling activities. The rock particles are called rock cuttings (or caving's, depending on their sizes). Rock cuttings are generally used to identify lithology types for the subsurface characterization and are one of the highest available and lowest cost data sources for understanding and characterizing the subsurface rock properties. As such, there is a strong industry need to automatically analyze rock cuttings to extract rock particle properties (e.g., features), thereby reducing human cost, improving the accuracy and efficiency of the analysis process, and shortening the turnaround time of the interpretation. In particular, existing feature extraction techniques may be limited on extracting texture features from rock cutting instance images due to the properties of texture, such as spatial information captured in the features, feature size depending on input size, shape similarity affected by the existence of background, blurry reconstructed image caused by the pixel-based reconstruction loss, and the like. For example, rock cutting instances may have arbitrary shapes and sizes, which may introduce background pixels in the rock cutting instance images during image acquisition, and these background pixels may be excluded from the feature extraction process. Further, some portion of the rock cutting instance images may contain pixels that do not represent any feature of the rock particles (e.g., imaging errors, other objects), and these pixels may be excluded from the feature extraction process. These pixels do not represent any feature of the rock particles and are counted as invalid pixels when extracting features from the rock cutting instance images. Accordingly, it is desirable to automatically analyze rock cuttings to extract color and texture information from arbitrary shaped and sized rock particle instance images containing invalid pixels. It should be noted that, in some embodiments, the system and methods described herein may be used for excluding any pixel (e.g., in any area of the input image) from the

feature extraction process for imaging processing purposes, such as image inpainting, etc.

SUMMARY

[0006] A summary of certain embodiments described herein is set forth below. It should be understood that these aspects are presented merely to provide the reader with a brief summary of these certain embodiments and that these aspects are not intended to limit the scope of this disclosure.

[0007] Implementations herein are directed to systems and methods to extract features (e.g., colors, textual features) from arbitrary shaped and sized images by implementing global average pooling (GAP) and partial convolution in an autoencoder (AE) for analysis of the images. It should be noted that, the feature extraction technique described herein may be applied to other images (e.g., rock core images, borehole images) and/or images in any domain, such as remote sensing and medical imaging. In some embodiments, an autoencoder (AE), which may be data driven and/or unsupervised, may be used to extract texture features from images. In some embodiments, a variational autoencoder (VAE) may be used to control the distribution of the latent space. In some embodiments, a vanilla AE may be used instead of VAE. A global average pooling (GAP) layer may be used at the last layer of the encoder to make the feature rotation and translation invariant and scale equivariant. In addition, partial convolution may be used in the encoder to logically ignore the invalid pixels (e.g., background, image error, other object) in the images. It should be noted that, in some embodiments, the system and methods described herein may be used for excluding any pixel (e.g., in any area of the input image) from the feature extraction process for imaging processing purposes, such as image inpainting, etc.

[0008] Certain embodiments of the present disclosure include a method that includes receiving, via an encoder, an image; generating, via the encoder, a feature map by performing a partial convolution operation using the image and a mask image for the image; generating, via the encoder, an updated mask image based on the mask image and a dimension of the feature map; performing, via the encoder, a global average pooling (GAP) operation on the feature map using the updated mask image to generate a global feature map; and generating, via the encoder, an output feature image for the cutting instance image based on the global feature map.

[0009] Certain embodiments of the present disclosure also include a method of training an autoencoder (AE) that includes generating a set of training images from a plurality of images; generating respective mask images for the set of training images; inputting the set of training images and the respective mask images into an encoder of the AE. And the encoder of the AE is configured to: generating respective feature maps for the set of training images by performing partial convolution operation using the training images and the respective mask images; and generating respective global feature maps by performing a global average pooling (GAP) operation on the respective feature maps. The method of training the AE also includes generating, via a decoder of the AE, respective output images for the set of training images based on the respective global feature maps; and training the AE using the respective output images and the training images based on a loss function.

[0010] Certain embodiments of the present disclosure also include an autoencoder (AE) that includes an encoder. The encoder includes a convolution layer configured to generate a feature map by performing a partial convolution operation using an image and a mask image for the image. The encoder also includes a global average pooling (GAP) layer configured to generate a global feature map by performing a GAP operation on the feature map using an updated mask image generated based on the mask image. The AE also includes a decoder configured to generate an output image based on the global feature map.

[0011] Various refinements of the features noted above may be undertaken in relation to various aspects of the present disclosure. Further features may also be incorporated in these various aspects as well. These refinements and additional features may exist individually or in any combination. For instance, various features discussed below in relation to one or more of the illustrated

embodiments may be incorporated into any of the above-described aspects of the present disclosure alone or in any combination. The brief summary presented above is intended to familiarize the reader with certain aspects and contexts of embodiments of the present disclosure without limitation to the claimed subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] Various aspects of this disclosure may be better understood upon reading the following detailed description and upon reference to the drawings, in which:

[0013] FIG. 1 illustrates a drilling system, in accordance with embodiments of the present disclosure;

[0014] FIG. 2 illustrates a shale shaker removing drill bit cuttings from drilling fluid, in accordance with embodiments of the present disclosure;

[0015] FIG. 3 illustrates a drill bit generating cuttings, in accordance with embodiments of the present disclosure;

[0016] FIG. 4 illustrates a system that includes an analysis and control system to monitor and control the drilling system of FIG. 1, in accordance with embodiments of the present disclosure;

[0017] FIG. 5 illustrates a cuttings collection and image acquisition workflow that may be performed by the analysis and control system of FIG. 4, in accordance with embodiments of the present disclosure;

[0018] FIG. 6 illustrates an example workflow for lithological characterization of cuttings based on analysis of images of the cuttings, in accordance with embodiments of the present disclosure;

[0019] FIG. 7 illustrates a rock sample image and the corresponding segmented individual cutting instance images, in accordance with embodiments of the present disclosure;

[0020] FIG. 8 illustrates other embodiment of the segmented individual cutting instance images of FIG. 7, in accordance with embodiments of the present disclosure;

[0021] FIG. 9 illustrates an example workflow for property estimation process of FIG. 6, in accordance with embodiments of the present disclosure;

[0022] FIG. 10 illustrates a process for implementing an encoder to transform the segmented individual cutting instance images having invalid pixels from the image space to the latent vector space, in accordance with embodiments of the present disclosure;

[0023] FIG. 11 illustrates a process for image analysis using an embodiment of a partial texture VAE including a mask-aware texture encoding layer (TEL) in the encoder and using partial convolution in the encoder of the partial texture VAE, in accordance with embodiments of the present disclosure;

[0024] FIG. 12 illustrates a process for image analysis using another embodiment of a partial texture VAE including a mask-aware global average pooling (GAP) layer in the encoder and using partial convolution in the convolution layers of the encoder of the partial texture VAE, in accordance with embodiments of the present disclosure;

[0025] FIG. 13 is a block diagram illustrating a training process for the partial texture VAE of FIG. 12, in accordance with embodiments of the present disclosure;

[0026] FIG. 14 is a block diagram illustrating a feature extraction process to extract features from analyzing images using the encoder of the trained partial texture VAE of FIG. 13, in accordance with embodiments of the present disclosure; and

[0027] FIG. 15 shows a visualization of the rock cuttings, in accordance with embodiments of the present disclosure.

DETAILED DESCRIPTION

[0028] One or more specific embodiments of the present disclosure will be described below. These

described embodiments are only examples of the presently disclosed techniques. Additionally, in an effort to provide a concise description of these embodiments, all features of an actual implementation may not be described in the specification. It should be appreciated that in the development of any such actual implementation, as in any engineering or design project, numerous implementation-specific decisions must be made to achieve the developers' specific goals, such as compliance with system-related and business-related constraints, which may vary from one implementation to another. Moreover, it should be appreciated that such a development effort might be complex and time consuming, but would nevertheless be a routine undertaking of design, fabrication, and manufacture for those of ordinary skill having the benefit of this disclosure.

[0029] When introducing elements of various embodiments of the present disclosure, the articles “a,” “an,” and “the” are intended to mean that there are one or more of the elements. The terms “comprising,” “including,” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements. Additionally, it should be understood that references to “one embodiment” or “an embodiment” of the present disclosure are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features.

[0030] As used herein, the terms “connect,” “connection,” “connected,” “in connection with,” and “connecting” are used to mean “in direct connection with” or “in connection with via one or more elements”; and the term “set” is used to mean “one element” or “more than one element.” Further, the terms “couple,” “coupling,” “coupled,” “coupled together,” and “coupled with” are used to mean “directly coupled together” or “coupled together via one or more elements.”

[0031] In addition, as used herein, the terms “real time”, “real-time”, or “substantially real time” may be used interchangeably and are intended to describe operations (e.g., computing operations) that are performed without any human-perceivable interruption between operations. For example, as used herein, data relating to the systems described herein may be collected, transmitted, and/or used in control computations in “substantially real time” such that data readings, data transfers, and/or data processing steps occur once every second, once every 0.1 second, once every 0.01 second, or even more frequent, during operations of the systems (e.g., while the systems are operating). In addition, as used herein, the terms “continuous”, “continuously”, or “continually” are intended to describe operations that are performed without any significant interruption. For example, as used herein, control commands may be transmitted to certain equipment every five minutes, every minute, every 30 seconds, every 15 seconds, every 10 seconds, every 5 seconds, or even more often, such that operating parameters of the equipment may be adjusted without any significant interruption to the closed-loop control of the equipment. In addition, as used herein, the terms “automatic”, “automated”, “autonomous”, and so forth, are intended to describe operations that are performed or caused to be performed, for example, by a computing system (i.e., solely by the computing system, without human intervention). Indeed, although certain operations described herein may not be explicitly described as being performed continuously and/or automatically in substantially real time during operation of the computing system and/or equipment controlled by the computing system, it will be appreciated that these operations may, in fact, be performed continuously and/or automatically in substantially real time during operation of the computing system and/or equipment controlled by the computing system to improve the functionality of the computing system (e.g., by not requiring human intervention, thereby facilitating faster operational decision-making, as well as improving the accuracy of the operational decision-making by, for example, eliminating the potential for human error), as described in greater detail herein.

[0032] As described above, whenever a drilling process is involved in an activity, rock cuttings are produced and are generally available at the well site. Cuttings properties may include geological properties observed or measured associated with cuttings. Currently, cuttings are generally under-utilized for the subsurface characterization by geoscientists and reservoir engineers in the oil and gas industry. When these rock cuttings are observed and interpreted by human eyes, it is extremely

interpreter-dependent and relatively time consuming as well as physically labor intensive. Accordingly, a need exists for automating the process of cuttings analysis in the industry. To that end, the embodiments described herein provide a domain-based image analysis workflow that includes multiple computational modules to automatically extract relevant geological information from rock cuttings. As used herein, the terms “image”, “digital image”, “photograph”, and “photo” are intended to be used interchangeably. A digital image may be divided into small geometrical subunits called image pixels having pixel values corresponding to the image content. Depending on the content of the image, the digital image may include different color channels, such as red channel image data indicative of target luminance of a red color, blue channel image data indicative of target luminance of a blue color, green channel image data indicative of target luminance of a green color, or grayscale image data indicative of target luminance of a gray color. The image data corresponding with the image content are indicative of target visual characteristics (e.g., luminance and/or color) at one or more specific points (e.g., image pixels) in the image content, for example, by indicating color channel brightness levels (e.g., gray levels). Gray levels are discrete levels (e.g., 0, 1 . . . 255) corresponding to quantized light brightness (e.g., light brightness of color channels, light brightness of gray color) at the image pixels. For example, the brightness level may be at maximum when the gray level has a value of 255 and minimum when the gray level has a value of 0. For example, a digital image may have three color channels (e.g., red (R), green (G), blue (B)), and an image pixel of the digital image may have a pixel value of (R,G,B) (e.g., (255,255,255)). In some embodiments, a digital image may have more than 3 channels per pixel (e.g., hyperspectral images, multispectral images). In some embodiments, a digital image may be a grayscale image and only have one color channel, and an image pixel of the digital image may have a pixel value of corresponding gray level (e.g., 0, 1 . . . 255). The relationship between the gray level of the image pixels and the corresponding brightness at the image pixels is associated with the imaging system used to take the image. In addition, although described herein as systems and methods for analyzing images of drill bit cuttings, it will be appreciated that the embodiments described herein may be capable of analyzing images of other types of rock particles, such as other types of cuttings, cavings, and so forth as well as non-rock objects in the mud, such as mud additives, metal shavings, and foreign objects.

[0033] FIG. 1 illustrates a drilling system **10** in accordance with the embodiments described herein. As illustrated, in certain embodiments, a drill string **12** may be suspended at an upper end by a kelly and a traveling block **14** and terminated at a lower end by a drill bit **16** (shown in FIG. 3). The drill string **12** and the drill bit **16** are rotated by a rotary table **18** on a driller floor **20**, thereby drilling a borehole **22** into earth formation **24**, where a portion of the borehole **22** may be cased by a casing **26**. As illustrated, in certain embodiments, drilling fluid or drilling “mud” **28** may be pumped by a mud pump **30** into the upper end of the hollow drill string **12** through a connecting mud line **32**. From there, the drilling fluid **28** may be pumped downward through the drill string **12**, exiting the drill string **12** through opening in the drill bit **16**, and returning to the surface by way of an annulus formed between the wall of the borehole **22** and an outer diameter of the drill string **12**. Once at the surface, the drilling fluid **28** may return through a return flow line **34**, for example, via a bell nipple **36**. As illustrated, in certain embodiments, a blowout preventer **38** may be used to prevent blowouts from occurring in the drilling system **10**.

[0034] As illustrated in FIG. 1, drill bit cuttings that are formed by the drill bit **16** crushing rocks in the formation **24** may typically be removed from the returned drilling fluid **28** by a shale shaker **40** in the return flow line **34** such that the drilling fluid **28** may be reused for injection, where the shale shaker **40** includes a shaker pit **42** and a gas trap **44**. The drilling fluid **28** may then be delivered to a mud pit **48** from which the mud pump **30** may draw the drilling fluid **28**. FIG. 2 illustrates drill bit cuttings **46** that have been removed from the drilling fluid **28** in the shaker pit **42** of the shale shaker **40**. In FIG. 2, one or more cameras **52** may be used to capture the drill bit cuttings **46**. In addition, FIG. 3 illustrates how drill bit cuttings **46** may be created by the drill bit **16**, and then flow

back up within the drilling fluid **28** through an annulus formed between the wall of the borehole **22** and an outer diameter of the drill string **12**.

[0035] In addition, as illustrated in FIG. **1**, in certain embodiments, an analysis and control system **50** (e.g., a mud logging unit) may be used to control the drilling system **10**, as well as provide analysis of the drill bit cuttings **46**, as described in greater detail herein. In particular, in certain embodiments, the analysis and control system **50** may be configured to automatically analyze images of the drill bit cuttings **46** that are automatically captured by cameras (e.g., the one or more cameras **52** shown in FIG. **2**) during performance of the drilling system **10** illustrated in FIG. **1**, as described in greater detail herein. As illustrated in FIG. **2**, in certain embodiments, the one or more cameras **52** may be directly associated with (e.g., directly attached to or disposed adjacent to or in close proximity to) the shale shaker **40**. However, in other embodiments, the one or more cameras **52** may be other types of cameras not directly associated with the shale shaker **40**.

[0036] FIG. **4** illustrates a system **54** that includes an analysis and control system **50** to monitor and control the drilling system **10** of FIG. **1**, as described in greater detail herein. In certain embodiments, the analysis and control system **50** may include one or more analysis modules **56** (e.g., tools or instruments) that may be configured to perform various functions of the embodiments described herein including, but not limited to, utilizing certain analysis algorithms to analyze images of drill bit cuttings **46** that are captured by the one or more cameras **52**, as described in greater detail herein. In certain embodiments, to perform these various functions, an analysis module **56** executes instructions on one or more processors **58** of the analysis and control system **50**, which may be connected to one or more storage media **60** of the analysis and control system **50**. Indeed, in certain embodiments, the one or more analysis modules **56** may be stored in the one or more storage media **60**. In certain embodiments, the one or more analysis modules **56** include analysis hardware (e.g., analysis circuitry) and/or software including processor executable instructions and associated data.

[0037] In certain embodiments, the one or more processors **58** may include a microprocessor, a microcontroller, a processor module or subsystem, a programmable integrated circuit, a programmable gate array, a digital signal processor (DSP), or another control or computing device. In certain embodiments, the one or more storage media **60** may be implemented as one or more non-transitory computer-readable or machine-readable storage media. In certain embodiments, the one or more storage media **60** may include one or more different forms of memory including semiconductor memory devices such as dynamic or static random access memories (DRAMs or SRAMs), erasable and programmable read-only memories (EPROMs), electrically erasable and programmable read-only memories (EEPROMs) and flash memories; magnetic disks such as fixed, floppy and removable disks; other magnetic media including tape; optical media such as compact disks (CDs) or digital video disks (DVDs); or other types of storage devices. Note that the processor-executable instructions and associated data of the analysis module(s) **56** may be provided on one computer-readable or machine-readable storage medium of the storage media **60** or, alternatively, may be provided on multiple computer-readable or machine-readable storage media distributed in a large system having possibly plural nodes. Such computer-readable or machine-readable storage medium or media are considered to be part of an article (or article of manufacture), which may refer to any manufactured single component or multiple components. In certain embodiments, the one or more storage media **60** may be located either in the machine running the machine-readable instructions, or may be located at a remote site from which machine-readable instructions may be downloaded over a network for execution.

[0038] In certain embodiments, the processor(s) **58** may be connected to a network interface **62** of the analysis and control system **50** to allow the analysis and control system **50** to communicate with various surface sensors **64** (Internet of Things (IoT) sensors, gauges, and so forth) and/or downhole sensors **66** described herein, as well as communicate with actuators **68** and/or PLCs **70** of surface equipment **72** and/or of downhole equipment **74** for the purpose of monitoring and/or

controlling operation of the drilling system **10**, as described in greater detail herein. In addition, in certain embodiments, the network interface **62** may also facilitate the analysis and control system **50** to communicate with one or more cameras **52**, as described in greater detail herein. In certain embodiments, the network interface **62** may also facilitate the analysis and control system **50** to communicate data to a cloud-based service **76** (or other wired and/or wireless communication network) to, for example, archive the data or to enable external computing systems **78** (e.g., cloud-based computing systems, in certain embodiments) to access the data and/or to remotely interact with the analysis and control system **50**. For example, in certain embodiments, some or all of the analysis modules **56** described in greater detail herein may be executed via cloud and edge deployments.

[0039] In certain embodiments, the analysis and control system **50** may include an electronic display **80** configured to display a graphical user interface to present results on the analysis described herein. In addition, in certain embodiments, the graphical user interface may present other information to operators of the equipment **72**, **74**. For example, the graphical user interface may include a dashboard configured to present visual information to the operators. In certain embodiments, the dashboard may show live (e.g., real-time) data as well as the results of the analysis described herein. In addition, in certain embodiments, the analysis and control system **50** may include one or more input devices **82** configured to enable the operators to, for example, provide commands to the equipment **72**, **74** described herein. In addition, in certain embodiments, the display **80** may include a touch screen interface configured to receive inputs from operators.

[0040] It should be appreciated that the system **54** illustrated in FIG. **4** is only exemplary, and that the system **54** may have more or fewer components than shown, may combine additional components not depicted in the embodiment of FIG. **4**, and/or the system **54** may have a different configuration or arrangement of the components depicted in FIG. **4**. In addition, the various components illustrated in FIG. **4** may be implemented in hardware, software, or a combination of both hardware and software, including one or more signal processing and/or application specific integrated circuits. Furthermore, the operations of the system **54** as described herein may be implemented by running one or more functional modules in an information processing apparatus such as application specific chips, such as application-specific integrated circuits (ASICs), field-programmable gate arrays (FPGAs), programmable logic devices (PLDs), systems on a chip (SOCs), or other appropriate devices. These modules, combinations of these modules, and/or their combination with hardware are all included within the scope of the embodiments described herein.

[0041] In conventional systems, drill bit cuttings **46** are analyzed by mud loggers in a mud logging unit. These conventional systems are generally human-dependent. The embodiments described herein enhance the analysis of such drill bit cuttings **46**. FIG. **5** illustrates a cuttings collection and image acquisition workflow **84** that may be performed by the analysis and control system **50** of FIG. **4**. As illustrated in FIG. **5**, the cuttings collection and image acquisition workflow **84** begins with a drilling system **10** that generates rock particles (e.g., that include the drill bit cuttings **46** described above). Then, the rock particles are collected, for example, from a shale shaker **40**, as described with respect to FIG. **2** (e.g., sample collection **86**).

[0042] Then, in certain embodiments, the rock particles may be prepared for analysis by, for example, drying the rock particles in an oven for analysis (e.g., sample preparation **88**). In addition, in certain embodiments, the sample preparation **88** may include sieving the rock particles using one or more meshes **90** to select cuttings **46** that fall in certain ranges of sizes. In certain embodiments, the sizes of the meshes **90** may be in a range of between 0.25 millimeters (mm) and 3.0 mm and may be approximately 0.25 mm, approximately 0.50 mm, approximately 0.75 mm, approximately 1.0 mm, approximately 1.25 mm, approximately 1.50 mm, approximately 1.75 mm, approximately 2.0 mm, approximately 2.25 mm, approximately 2.50 mm, approximately 2.75 mm, or approximately 3.0 mm. It will be appreciated that consecutive meshes **90** through which the rock particles may be sieved may begin with larger meshes **90** followed by progressively smaller meshes

90 such that larger cuttings **46** are sieved sooner and smaller cuttings **46** are sieved later until such point where the sieved rock particles are so fine that they are no longer considered cuttings **46** per se. It will also be appreciated that the size of a particle cutting **46** is the smallest axis of the cutting **46** when the cutting **46** is approximated as an ellipsoid. In certain embodiments, the sample preparation **88** may include placing the sieved cuttings **46** in a sample tray having a relatively vivid background color (e.g., pure magenta (e.g., with RGB values of 255, 0, 255), pure blue (e.g., with RGB values of 0, 0, 255), pure green (e.g., with RGB values of 0, 255, 0), and so forth). In general, such colors do not exist in nature and, accordingly, help instance segmentation models avoid detecting the background of the sample tray as part of the instance. In certain situations, the sample tray may be prepared by a human or an automated system, so the distribution of the cuttings **46** is often random. For example, the cuttings **46** may be touching or piled in some areas on the sample tray and may be sparsely distributed in other areas.

[0043] In certain embodiments, an image **94** of the cuttings **46** may be taken (e.g., image acquisition **96**) by imaging devices (e.g., the one or more cameras **52**). The examples below are given with cameras detecting visible light spectrum, but the same methods may be applied to an image taken with infrared (IR) or ultraviolet (UV) cameras detecting light in UV or IR domains. As described in greater detail herein, in certain embodiments, during the image acquisition **96**, illumination, color, and resolution of the image **94** may be calibrated and standardized in order to obtain quantitative and reliable measurements of pixel values between images **94**. For example, in certain embodiments, color/illumination calibration may be obtained by using colorimetry algorithms against previously analyzed images **94** and a current image of interest **94**, while resolution calibration may be based on lens focal length, focal distance, and sensor size/resolution for the current image **94** of interest as compared to that of previously analyzed images **94**. All of these parameters may vary, but the final image is “calibrated” and the same objects may be digitalized with reasonably near values. Pixel values (e.g., the images **94** may be digital images) and size are, therefore, treated as effective measurements of the particle rather than mere representation. The embodiments described herein enable the creation of such calibrated and error-assessed input images **94**. Without such calibration, final object classification may vary because of the acquisition rather than because of any real-world difference. In certain embodiments, an optical image of the sample under the visible light may be taken. In certain embodiments, an optical image of the same sample under the UV light, which may cause the fluorescence of some minerals and oil (if oil is trapped in the cuttings), may be taken. This may be a clue for certain rock types or existence of oil in the geological formation which the cutting belonged to. In certain embodiments, the optical images of the same sample taken under different light spectrum (e.g., visible light, UV, IR) may be combined for image analysis of the sample, as described in FIG. 6 and FIG. 8.

[0044] Then, in certain embodiments, the image **94** (e.g., digital image) of the cuttings **46** may be compressed for easier transfer (e.g., image compression **98**). In particular, well sites are quite often in relatively remote locations where the available network bandwidth may be relatively slow. Accordingly, compressing the images **94** of cuttings **46** may facilitate transfer of the images **94**. It will be appreciated that compressing the images **94** of cuttings **46** may not be as beneficial if there is higher bandwidth at the well site (e.g., when the well site has cable internet access). Then, in certain embodiments, the image **94** of the cuttings **46** may be transferred (e.g., image transfer **100**), for example, to the analysis and control system **50** and/or the computing system **78** illustrated in FIG. 4 for analysis, as described in greater detail herein. The analysis and control system **50** may be at the well site or in a remote location. Then, in certain embodiments, analysis of the image **94** of the cuttings **46** (e.g., image analysis **102**) may include extraction of geologically meaningful information relating to the cuttings **46** from the image **94**, as described in greater detail herein.

[0045] The embodiments described herein determine measurements from images **94** of cuttings **46** that relate to lithology of the formation **24** from which the cuttings **46** are generated based on lithology geological scientific definitions. In general, the lithology of a rock unit is a description of

its physical characteristics visible at an outcropping, in hand or core samples, or with low magnification microscopy. Such physical characteristics include, but are not limited to, color, texture, grain size, and composition. Lithology may refer to either a detailed description of these physical characteristics, or a summary of the gross physical character of a rock. Examples of lithology types may include sandstone, slate, basalt, limestone, and so forth. As such, color, texture, and grain size are physical characteristics of a type of lithology, and the workflows described herein illustrate how these physical characteristics may be measured, extracted, and consolidated to obtain automated lithological image recognition.

[0046] The embodiments described herein apply to analysis of calibrated images **94** of prepared cuttings **46**, regardless of the particular methods used to achieve the sample preparation **88**, the image acquisition **96**, the image compression **98**, and the image transfer **100**, described with respect to FIG. 5.

[0047] In certain embodiments, the analysis and control system **50** may be configured to separate pixels of individual rock particles from multiple particles (e.g., cuttings **46**) depicted in an image **94** (e.g., calibrated image). In addition, in certain embodiments, the analysis and control system **50** is configured to determine relevant morphological (e.g., size, shape, and so forth), color, and texture data from one or more individual rock particles (e.g., cuttings **46**) depicted in a calibrated image **94**. In addition, in certain embodiments, the analysis and control system **50** may be configured to utilize extracted information from calibrated images **94** to perform geological/lithological classification at a plurality of different hierarchical levels (e.g., at a single particle/cutting level, at a single sample level of a plurality of cuttings, at a particular depth interval within a borehole **22**, for a particular geological formation **24**, for an entire well, for an entire well field, and so forth). As described in greater detail herein, consolidating the analysis results in a plurality of hierarchical levels enables operators to analyze the cuttings **46** in a much more robust (and automated and more accurate) manner than conventional techniques. In addition, in certain embodiments, the analysis and control system **50** may be configured to utilize the information derived herein based on the calibrated images **94** to create a mud logging report. In addition, in certain embodiments, the analysis and control system **50** may be configured to output from the calibrated images **94** any relevant information that can be integrated with other well-related answer products. In addition, in certain embodiments, the analysis and control system **50** may be configured to utilize a supervised machine learning model (e.g., from another well in the same field or another field with similar geological setting) to infer the lithology type from a calibrated image **94** from the current well. In addition, in certain embodiments, the analysis and control system **50** may be configured to utilize all of this type of information to automatically adjust operating parameters of a drilling system **10** (e.g., drilling fluid composition, drill bit speed, and so forth), as described in greater detail herein.

[0048] While the cuttings collection and image acquisition workflow **84** illustrated in FIG. 5 has been described with particular reference to analyzing cuttings **46** to determine geologically meaningful information relating to the cuttings **46** from images **94**, the embodiments described herein may be extended to the analysis of images **94** to identify features of other types of objects, rather than just cuttings **46**.

[0049] In certain embodiments, object-based image analysis (OBIA) may be used to analyze the images **94** (e.g., calibrated images). OBIA generally involves grouping a number of pixels in a digital image into shapes with a meaningful representation of objects based on either spectral or spatial similarity or an external variable (e.g., soil or geological unit). OBIA may be used to address complex classes that are defined by spatial and hierarchical relationships within and during the classification process. In some embodiments, color and texture analysis may be used to analyze the images **94**. In geology, rocks are characterized by texture and color. Thus, a key step is to extract color and texture features from the images **94** for a variety of downstream image analysis tasks, such as clustering, image retrieval, classification, and manifold representation for visualizing the rock particles distribution to enable the OBIA. Analysis of the images **94** may include image

segmentation, feature extraction, and classification, as illustrated in FIG. 6. As mentioned previously, calibrated images **94** may be used in the image analysis to obtain more reliable results. The embodiments described herein focus on feature extraction and classification analysis of calibrated images **94**. Certain embodiments implement lithological recognition and/or classification from images **94** of cuttings **46** by applying neural network (NN) and machine learning (ML) techniques. It should be noted that, the feature extraction technique described herein may be applied to other images (e.g., rock core images, borehole images) and/or images in any domain, such as remote sensing and medical imaging.

[0050] FIG. 6 illustrates an example workflow **110** of the image analysis for an image **94** (e.g. calibrated image) by the system **54**. The image **94** (e.g., digital image) may be input into a cutting instances segmentation module **112** (e.g., tools or instruments) of the system **54** to obtain segmented individual cutting instance images **114** (shown in FIG. 7). The cutting instances segmentation module **112** may identify and separate individual objects within the calibrated image **94**, for example, by detecting the boundaries of each object and assigning a unique label to each object, as illustrated in FIG. 7 and FIG. 8. FIG. 7 shows an example of a calibrated image **94** and the corresponding segmented individual cutting instance images **114**. In certain embodiments, the cutting instances segmentation module **112** may include analysis hardware (e.g., analysis circuitry) and/or software including processor executable instructions and associated data. In certain embodiments, the cutting instances segmentation module **112** may utilize Mask R-CNN (Region-based Convolutional Neural Networks) to identify various objects in the calibrated image **94**, which has been found to outperform conventional segmentation methods. A Mask R-CNN model is trained in a supervised manner, and it has been found that the same approach may be taken to efficiently build a system to run the instance segmentation using any type of image (e.g., digital image, distance image, etc.) and rock particle scene (e.g., cuttings, mining site, space, etc.) by training the model with relevant datasets.

[0051] The segmented individual cutting instance images **114** may be used in a rock property estimation process **116** and a rock property measurement process **118**. For instance, in the rock property estimation process **116**, the segmented individual cutting instance images **114** may be input into a feature extraction module **120** (e.g., tools or instruments) of the analysis and control system **50**. In certain embodiments, the feature extraction module **120** may include analysis hardware (e.g., analysis circuitry) and/or software including processor executable instructions and associated data. The feature extraction module **120** may analyze the segmented individual cutting instance images **114** using reference data **122** (e.g., baseline cuttings used for reference) and output a set of parameters (features) representing the color and textural properties of the cutting instance, which may be key visual properties to identify rock types, as illustrated in FIG. 8. Thus, cutting features are a set of values that represent or summarize color and texture information of a cutting instance image. FIG. 8 shows an example of the segmented individual cutting instance images **114** with individual cutting instance images (e.g., cutting A and cutting B) indicated with corresponding set of parameters for number D of features (e.g., feature.sub.1, feature.sub.2 . . . feature.sub.D). As illustrated in FIG. 8, the individual cutting instance images (e.g., cutting A, cutting B) in the segmented individual cutting instance images **114** may have arbitrary sizes, shapes (e.g., height (H), width (W)), and colors. The feature extraction module **120** may analyze the segmented individual cutting instance images **114**, and each cutting instance image (I_i) may be transformed from the image space, $I_{sub.i} \in R_{sup.}(H_i \times W_i \times 3)$ (e.g., height (H_i), width (W_i), 3 color channels (e.g., red, green, blue)), to a D-dimensional feature vector space, $\{\vec{V}\}_{sub.i} \in R_{sup.D}$. In some embodiments, the cutting instance image (I_i) may be a grayscale image and have only one color channel. The D-dimensional feature vector space $R_{sup.D}$ may include number D of feature (e.g., feature.sub.1, feature.sub.2 . . . feature.sub.D) axes, and the feature vector $\{\vec{V}\}_{sub.i}$ may have a set of parameters along respective feature axes in the feature vector space $R_{sup.D}$. In certain embodiments, different types of images representing different

physical properties of the same rock particle samples may be obtained without changing the position of the samples in the sample tray. In such cases, we may combine those images and generate a single multi-channel image. Thus, the transformation is from the image space $I_{sub.i} \in R_{sup.}(H_i \times W_i \times C)$, where C is the number of channels (e.g., physical properties of the rock particle samples, such as colors), to a D -dimensional feature vector space $\{\vec{V}\}_{sub.i} \in R_{sup.D}$. For example, in certain embodiments, fluorescence of the minerals in the cuttings may be a clue for certain rock types, and an optical image of the same sample (e.g., cuttings **46**) under the UV light, which may cause the fluorescence of the minerals, may be combined with the calibrated image **94** (e.g., obtained using visible light) to create a 6 channel image (e.g., 3 color channels for the image taken with UV light and 3 color channels for the image taken with visible light). In some embodiments, the calibrated image **94** may include hyperspectral images (e.g., continuous ranges of wavelengths) and/or multispectral images (e.g., discrete targeted wavelengths) of the cuttings taken by using imaging spectroscopy. These hyperspectral images and/or multispectral images may have more than 3 color channels and may include spectral signatures for minerals in the cuttings, which may be used to identify the minerals. In this case, the transformation will be from an image space $I_{sub.i} \in R_{sup.}(H_i \times W_i \times 6)$ to the D -dimensional feature vector space, $\{\vec{V}\}_{sub.i} \in R_{sup.D}$. The feature vectors of the segmented individual cutting instance images **114** may be used by a lithology classification module **124** (e.g., tools or instruments) of the analysis and control system **50** to determine the lithology **126** of the cuttings **46**, as described in greater detail herein. In certain embodiments, the lithology classification module **124** may include analysis hardware (e.g., analysis circuitry) and/or software including processor executable instructions and associated data. For a lithology type of rock (e.g., sandstone), a grain size analysis module **128** (e.g., tools or instruments) of the analysis and control system **50** may be used to analyze each individual cutting **46** to identify a grain size class (e.g., fine, medium, coarse, and so forth) **130** and a grain size distribution **132**, among other grain size-related properties, of each individual cutting **46**. In certain embodiments, the grain size analysis module **128** may include analysis hardware (e.g., analysis circuitry) and/or software including processor executable instructions and associated data.

[0052] The feature vectors of the segmented individual cutting instance images **114** may be used with other properties **134** (e.g., properties not easily extracted from digital images) to estimate rock properties, as described in greater detail herein. For example, other properties **134** may include guided manual property descriptions, associated well log values, or other external data such as, but not limited to, stratigraphic geological sequences, while-drilling logs, 3D model properties, cutting physical analysis (e.g., diffractometry, calcimetry, acid test), or any other information that may be useful to resolve lithology classification ambiguities. In certain embodiments, the other properties **134** may be determined by using instruments/tools (e.g., surface equipment **72**, downhole equipment **74**), analysis hardware (e.g., analysis circuitry), and/or software including processor executable instructions and associated data.

[0053] As illustrated in FIG. **8**, the individual cutting instance images (e.g., cutting A, cutting B) in the segmented individual cutting instance images **114** may have arbitrary sizes, shapes, and colors. The property measurement process **118** may use a shape measurements module **136** (e.g., tools or instruments) of the analysis and control system **50**, and the segmented individual cutting instance images **114** may be analyzed by the shape measurement module **136** based on individual instances to determine the size **138** and shape **140** of the individual instances. The property measurement process **118** may use a texture measurements module **142** (e.g., tools or instruments) of the analysis and control system **50**, and the segmented individual cutting instance images **114** may be analyzed by the texture measurement module **142** based on individual instances to determine the texture **144** of the individual instances, such as homogeneous, heterogeneous, laminated, grainy, and so forth. The property measurement process **118** may also use a color measurements module **146** (e.g., tools or instruments) of the analysis and control system **50**, and the segmented individual cutting

instance images **114** may be analyzed by the color measurement module **146** based on individual instances to determine the color **148** of the individual instances. In certain embodiments, the shape measurements module **136**, the texture measurement module **142**, and the color measurements module **146** may include analysis hardware (e.g., analysis circuitry) and/or software including processor executable instructions and associated data. The outputs of the property estimation process **116** (e.g., the lithology **126**, the grain size class **130**, the grain size distribution **132**) and the outputs of the property measurement process **118** may be combined to obtain consolidated results **150**.

[0054] The property estimation process **116** may include two stages: stage one for reference data description and indexing (e.g., for baseline cuttings used for reference); and stage two for property estimation of a cutting instance image based on the reference data description and indexing obtained in stage one. FIG. **9** shows a workflow **200** of stage one for using the reference data **122** for data description and indexing. In some embodiments, the workflow **200** may include instruments/tools (e.g., surface equipment **72**, downhole equipment **74**), hardware (e.g., analysis circuitry), and/or software including processor executable instructions and associated data. The reference data **122** may include image data for a set of M images (e.g., calibrated images **94**) obtained when analyzing previous wells or previous data of the current well.

[0055] The workflow **200** may include instance segmentation (process **1**), image feature extraction (process **2**), property association (process **3**), and indexing (process **4**). In process **1** of the workflow **200**, each image of the set of M images may be analyzed (e.g., by the cutting instances segmentation module **112**) to obtain respective segmented individual cutting instance images having a number (e.g., N) of individual cutting instance images **202** (e.g., I.sub.1, I.sub.2, . . . I.sub.N). The cuttings in the individual cutting instance images **202** (e.g., I.sub.1, I.sub.2, . . . I.sub.N) may be used as reference cuttings or baseline cuttings. In process **2** of the workflow **200**, the segmented individual cutting instance images may be analyzed (e.g., by the feature extraction module **120**) to obtain corresponding set of parameters for number D of features (e.g., feature.sub.1, feature.sub.2 . . . feature.sub.D) for the individual cutting instance images **202** (e.g., I.sub.1, I.sub.2, . . . I.sub.N). Thus, the individual cutting instance images **202** (e.g., I.sub.1, I.sub.2, . . . I.sub.N) may be transformed from the image space to corresponding feature vectors **204** (e.g., represented by corresponding matrix y.sub.1, y.sub.2, . . . y.sub.N) in the D-dimensional feature vector space R.sup.D.

[0056] In process **3** of the workflow **200**, the individual cutting instance images **202** (e.g., I.sub.1, I.sub.2, . . . I.sub.N) may be manually described by geologists (e.g., 3-1 guided manual property description) who is guided by a cutting description software, which is described in detail in FIGS. **12** and **13**. The cutting description software may include a description wizard having multiple entries, such as lithology type, hardness, visual porosity, etc. Some of the entries of the description wizard may not be easily extracted from digital images. In process **3** of the workflow **200**, well log values may also be used for property description (e.g., 3-2 Well log values association). Well log may include a detailed record for the geologic formation (e.g., the formation **24**). The detailed record may include information regarding the geologic properties (e.g., lithology, layer, depositional environments) and petrophysical characterization (e.g., water saturation, porosity, permeability, volume of shale) of the geologic formation, which may be used to control the drilling device or a drilling plan of the drilling system **10**. Well log may be a function of the borehole depth. For example, cuttings **46** may be collected at a depth of the borehole **22**, and the well log value at the depth may be associated with the cuttings from the same depth of the same well or different wells, as illustrated in FIG. **14**. This approach may be used, for example, when the reference data of stage one includes a well with cuttings and well log measurements, and the cutting instance image in stage two includes another well with cuttings but without well log measurements. A property **206** (e.g., P.sub.1, P.sub.2, . . . P.sub.N) of the corresponding individual cutting instance images **202** (e.g., I.sub.1, I.sub.2, . . . I.sub.N) may be determined by using the

guided manual property description, associated well log values, or other external data such as, but not limited to, stratigraphic geological sequences, while-drilling logs, 3D model properties, cutting physical analysis (e.g., diffractometry, calcimetry, acid test), or any other information that may be useful to resolve lithology classification ambiguities. The property **206** may include properties of the reference cuttings in the individual cutting instance images **202**, such as lithology type, hardness, visual porosity, gamma ray log, porosity log, etc. For example, P.sub.1 may include a description “Lithology type: Limestone; Hardness:0.6, Visual porosity: 1%, Gamma Ray log: 30API; Porosity log: 3% . . .” P.sub.2 may include a description “Lithology type: Sandstone; Hardness:0.6, Visual porosity: 5%, Gamma Ray log: 30API; Porosity log: 3% . . .” P.sub.N may include a description “Lithology type: Sandstone; Hardness:0.7, Visual porosity: 2%, Gamma Ray log: 30API; Porosity log: 3% . . .” The property description of the Nth reference cutting (P.sub.N) may be propagated to other cuttings in the same segmented individual cutting instance images based on the feature similarity, and a view **207** (e.g., two-dimensional (2D) view, three-dimensional (3D) view) of the property description of the cuttings may be displayed on a user interface.

[0057] In process **4** of the workflow **200**, the cutting instance images (e.g., I.sub.1, I.sub.2, . . . I.sub.N), the feature vectors **204** (e.g., represented by corresponding matrix y.sub.1, y.sub.2, . . . y.sub.N), and the corresponding property **206** may be indexed and stored together in an index dataset **208** (e.g., index A). The index dataset **208** may contain the cutting instance images (e.g., I.sub.1, I.sub.2, . . . I.sub.N), the feature vectors **204** (e.g., represented by corresponding matrix y.sub.1, y.sub.2, . . . y.sub.N), and the corresponding property **206** (e.g., P.sub.1, P.sub.2, . . . P.sub.N) for the set of M images in the reference data **122**. In process **4**, a clustering technique may be applied to the index dataset **208** to reduce the data size of the index. The clustering technique may be a data compression technique or redundancy reduction technique. For example, when there are multiple cutting instances that are visually very similar and corresponding feature distances (e.g., the squared Euclidean (L2-squared) distance) in the feature vector space R.sup.D are very close to each other, the cutting instances may be grouped into a cluster and only the representative cutting instance may be retained, wherein the representative cutting instance may be the centroid cutting instance of the cluster. Multiple index databases may be created by using different sets of M images. For example, various index datasets (e.g., index A, index B, index C) may be created from images of specific geographical locations or specific geological formations.

[0058] FIG. **9** also shows a workflow **210** for property estimation (e.g., lithology type, hardness, visual porosity, Gamma ray log, porosity log) of a cutting instance image using the property **206** and the index dataset **208** obtained in the workflow **200**. In some embodiments, the workflow **210** may include instruments/tools (e.g., surface equipment **72**, downhole equipment **74**), hardware (e.g., analysis circuitry), and/or software including processor executable instructions and associated data. The workflow **210** may include instance segmentation (process **1**), image feature extraction (process **2**), query (process **3**), and property propagation (process **4**). In process **1** of the workflow **210**, an image (e.g., a calibrated image **94**) may be analyzed (e.g., by the cutting instances segmentation module **112**) to obtain segmented individual cutting instance images having a number (e.g., J) of unknown individual cutting instance images **212** (e.g., I.sub.1, I.sub.2, . . . I.sub.J) (e.g., unknown lithology type, unknown hardness, unknown visual porosity, unknown Gamma ray log, unknown porosity log). In process **2** of the workflow **210**, the segmented individual cutting instance images may be analyzed (e.g., by the feature extraction module **120**) to obtain a set of parameters for number D of features (e.g., feature.sub.1, feature.sub.2 . . . feature.sub.D) for each of the unknown individual cutting instance images **212** (e.g., I.sub.1, I.sub.2, . . . I.sub.J). Thus, each of the unknown individual cutting instance images **212** (e.g., I.sub.1, I.sub.2, . . . I.sub.J). may be transformed from the image space to corresponding feature vectors **214** (e.g., represented by corresponding matrix xi) in the D-dimensional feature vector space R.sup.D. The process **1** and process **2** of the workflow **210** may be repeated for the new images acquired.

[0059] The process **3** of the workflow **210** may be used to retrieve a number K of most similar

($K \geq 1$) cuttings **216** from the index storage (e.g., index A, index B, index C) for each of the unknown individual cutting instance images **212** (e.g., I.sub.1, I.sub.2, . . . I.sub.J) by comparing the feature vector **214** (e.g., represented by corresponding matrix xi) with feature vectors (e.g., represented by corresponding matrix y.sub.1, y.sub.2, . . . y.sub.N) of the index storage. As described above, the properties (e.g., lithology type, hardness, visual porosity, Gamma ray log, porosity log) of the number K of most similar cuttings **216** may be obtained in the property association of stage one. Distances (e.g., the squared Euclidean (L2-squared) distance) in the feature vector space $R_{sup.D}$ between the feature vector **214** (e.g., represented by corresponding matrix xi) and the feature vectors (e.g., represented by corresponding matrix y.sub.1, y.sub.2, . . . y.sub.N) of the index storage may be calculated, and the nearest neighbor search method may be used to determine the number K of most similar cuttings **216** by finding the number K of smallest distances.

[0060] In the process **4** of the workflow **210**, a corresponding property description **218** (e.g., lithology type, hardness, visual porosity, Gamma ray log, porosity log) may be determined for each of the unknown individual cutting instance images **212** (e.g., I.sub.1, I.sub.2, . . . I.sub.J) by using the K most similar rock particles **216**. For instance, index dataset in the index storage might be selected to have a better accuracy of query and thus the property estimation. For example, in FIG. **9**, the index dataset A may be selected among other options such as index dataset B and index dataset C based on geographical locations, geological formations, well locations, depths in a well, etc. When K equals to 1, the properties of the retrieved cutting **216** may be simply copied to the unknown individual cutting instance image **212** being analyzed, as illustrated in FIG. **9**. For example, when K equals to 1, the most similar rock particle in the index may have the property description as ““Lithology type: Sandstone; Hardness:0.6, Visual porosity: 5%, Gamma Ray log: 30API; Porosity log: 4% . . . ,” and the unknown individual cutting instance image **212** being analyzed may be determined to have the same property description. When K is greater than 1, the properties of the retrieved cuttings **216** may be summarized and copied to the unknown individual cutting instance image **212** being analyzed using various ways. For example, for categorical property (such as Lithology class), the probability may be calculated for each class and the most probable category may be selected.

[0061] In some embodiments, texture features may be extracted from the cutting instance images and used to analyze the rock particles. Texture generally refers to the spatial organization of a set of basic elements or primitives (e.g., textons), which are fundamental microstructures in images and basic units of pre-attentive human visual perception. Extracting texture features from the cutting instance images may be different than extracting other features (e.g., color) from the cutting instance images due to properties of texture. For example, while color may stay invariant during rescaling of images, rescaled version of a cutting instance image may correspond to different texture features, which may be used to distinguish different type of rocks (e.g., fine sandstone and medium sandstone). In addition, texture may stay invariant during rotation and translation of an image (e.g., a cutting instance image), accordingly, rotated or translated versions of the image may be assigned with the same or very similar texture features as the original image.

[0062] Existing feature extraction techniques may be limited on extracting texture features from cutting instance images due to the properties of texture, such as spatial information captured in the features, feature size depending on input size, shape similarity affected by the existence of background, blurry reconstructed image caused by the pixel-based reconstruction loss, and the like. For example, in some embodiments, the segmented individual cutting instance images **212** may contain background pixels of the background (e.g., the sample tray) used during the image acquisition **96**, when taking an image of the cuttings **46**. For example, rock particles in the cuttings **46** may have arbitrary size and shape, accordingly, the images of the rock particles in the segmented individual cutting instance images **212** (e.g., $I_{sub.i} \in R_{sup.(H_i \times W_i \times 3)}$) may have arbitrary sizes and shapes, thereby leaving a portion of the segmented individual cutting instance

images **212** (e.g., corners) filled with background pixels, as illustrated in FIG. **10**. The background pixels do not represent any feature of the rock particles and are counted as invalid pixels when transforming the segmented individual cutting instance images **212** (I_i) from the image space, $I_{sub.i} \in R_{sup.}(H_i \times W_i \times 3)$ (e.g., height (H_i), width (W_i), 3 color channels (e.g., red, green, blue)), to the D-dimensional feature vector space, $\{\vec{V}\}_{sub.i} \in R_{sup.D}$. In some embodiments, the background pixels may be cropped and only the center of the segmented individual cutting instance images may be used for extracting the features of the rock particles. However, some segmented individual cutting instance images may include global texture representations, and using only the center of the segmented individual cutting instance images may miss the global texture representation. In some embodiments, some segmented individual cutting instance images may be resized before inputting into a feature extraction module to make the input image size uniform, however, resizing may deform the geometry and scale of the texture.

[0063] Implementations herein are directed to systems and methods to extract features (e.g., colors, textual features) from arbitrary shaped and sized images containing invalid pixels (e.g., background, image error, other object). It should be noted that, the feature extraction technique described herein may be applied to other images (e.g., rock core images, borehole images) and/or images in any domain, such as remote sensing and medical imaging. In some embodiments, an autoencoder (AE) (e.g., in the feature extraction module **120**), which may be data driven and/or unsupervised, may be used to extract texture features from images. In some embodiments, a variational autoencoder (VAE) (e.g., in the feature extraction module **120**) may be used to control the distribution of the latent space. In some embodiments, a vanilla AE may be used instead of VAE. A global average pooling (GAP) layer may be used at the last layer of the encoder to make the feature rotation and translation invariant and scale equivariant. In addition, partial convolution may be used in the encoder to logically ignore the invalid (e.g., background, image error, other object) pixels in the images.

[0064] Autoencoder is a general framework including two parts. The first part is an encoder, which encodes the input image $I_{sub.i} \in R_{sup.}(H_i \times W_i \times 3)$ to a latent vector $Z_{sub.i} \sim \text{Encoder}(I_{sub.i}) = q(Z_i | I_{sub.i})$, as illustrated in FIG. **10**. The latent vector $Z_{sub.i}$ is also called as feature or encoding. The second part is a decoder, which decodes the latent vector $Z_{sub.i}$ into an image $\hat{I}_{sub.i} = \text{Decoder}(Z_{sub.i}) = p(I_{sub.i} | Z_{sub.i})$. Both encoders and decoders are convolutional neural networks (CNNs), and the network parameters (e.g., weights, biases) may be defined thorough training, as illustrated in FIG. **11**. A convolutional neural network (CNN) may include an input layer, one or more hidden layers, and an output layer. The basic unit of computation in a neural network is the neuron/node. Each neuron/node receives input from some other nodes, or from an external source and computes an output. The input layer may include neurons/nodes to receive external inputs, such as input data to the CNN. Each hidden layer is made up of a set of neurons/nodes that have learnable weights and biases, and each neuron/node in the hidden layers may receive some inputs and perform a dot product. The output layer may include neurons/nodes to receive inputs from the hidden layers and output results of the CNN. A CNN uses a feedforward artificial network of neurons to execute image identification or recognition. It uses a reverse feed system for learning and produces a set of weights to calibrate the execution system. A CNN may include multiple layers in the hidden layers, such as convolution layers, pooling layers, and activation layers. The convolution layer extracts low-level features (e.g., lines or edges within an image) from the input data (e.g., operating in a sliding window manner), and the pooling layer reduces variations (e.g., by maxing or value averaging, pooling common features over a particular region of an image). The result may be passed on to further convolution and pooling layers. The activation layers may apply activation functions (e.g., rectified linear unit (ReLU) function, sigmoid function, tanh function) to the results received (e.g., from the pooling layers).

Autoencoders may be trained in an unsupervised manner (e.g., no labeled data is used to train the model). Once the model is trained, the encoder part may be used to extract features from images.

The encoder and decoder may be created based on residual neural network (ResNet) or similar architecture. The decoder architecture may be symmetrical or non-symmetrical to the encoder architecture.

[0065] FIG. **10** illustrate a process **300** for implementing an encoder to transform the segmented individual cutting instance images having invalid background pixels from the image space to the latent vector space. As illustrated in FIG. **10**, the images of the rock particles in the segmented individual cutting instance images **302** (e.g., $I_{\text{sub},i} \in R_{\text{sup}}(H_i \times W_i \times 3)$) may have arbitrary sizes and shapes, thereby leaving a portion of the segmented individual cutting instance images **302** (e.g., corners) filled with background pixels. The background pixels do not represent any feature of the rock particles and are counted as invalid pixels when transforming the segmented individual cutting instance images **302** from the image space $I_{\text{sub},i} \in R_{\text{sup}}(H_i \times W_i \times 3)$ (e.g., height (H_i), width (W_i), 3 color channels (e.g., red, green, blue)), through an encoder **304**, to the N-dimensional representation space **306** (e.g., $Z_{\text{sub},i} \in R_{\text{sup}}(N)$). The encoder **304** may be an encoder of a partial texture VAE, which may logically ignore the background pixels in the segmented individual cutting instance images **302** so that the extracted features in the N-dimensional representation space **306** may not be affected by the background pixels in the segmented individual cutting instance images **302**. The encoder **304** may include a texture encoding layer (TEL) and use partial convolution in the convolution layers to be agnostic to geometrical arrangement, image size and shape, and background pixels, as illustrated in FIG. **11**.

[0066] FIG. **11** shows a process **400** of image analysis using an embodiment of a partial texture VAE, which includes a mask-aware texture encoding layer (TEL) in the encoder and uses partial convolution in hidden layers (e.g., convolution layers, pooling layers) of the encoder of the partial texture VAE. As illustrated in FIG. **11**, an input image **402** (e.g., $64 \times 64 \times 3$, indicating height (H)=64, width (W)=64, 3 color channels (e.g., red, green, blue)) may be provided to the input layer of the encoder of the VAE together with a corresponding mask image **402M** (e.g., $64 \times 64 \times 1$). The mask image **402M** is a digital image having binary values with masked area having one value and unmasked area having another value (e.g., $\in \{0, 1\}$ sup. $H \times W$ with masked area having value “0” and unmasked area having value “1”). The input image **402** and the mask image **402M** may be used as input and processed using partial convolution through some hidden layers (e.g. convolution layers, pooling layers) of the encoder of the VAE to generate feature maps for the input image **402**. For example, in the illustrated embodiment of FIG. **11**, a feature map **404** (e.g., $32 \times 32 \times 8$) may be generated by conducting partial convolution using the input image **402** and the mask image **402M**, and the mask image **402M** may be updated to an updated mask image **404M** based on the dimension of the feature map **404** (e.g., $32 \times 32 \times 1$). The feature map **404** and the updated mask image **404M** may be further processed (e.g., via pooling layers) to generate a feature map **406** (e.g., $16 \times 16 \times 32$) and corresponding updated mask image **406M**, which may be used to generate a feature map **408** (e.g., $8 \times 8 \times 64$) and corresponding updated mask image **408M** (e.g., $8 \times 8 \times 1$). It should be noted that, although three layers are used to process the input images **402** and the mask image **402M** in the illustrated embodiment of FIG. **11**, other number (e.g., 2, 4, 5) of layers may be used in other embodiments. During the partial convolution, only the unmasked area in the mask image may contribute to the convolution result, as illustrated in Equation [1] below. Equation [1] describe a partial convolution process on one channel of an input image or a feature map $F \in R_{\text{sup}}(H \times W \times C)$ (e.g., H is height, W is width, and C is number of channels) to generate corresponding next level feature map Z (e.g., $H' \times W' \times C'$, and H' , W' , C' may be different from H , W , C depending on the filter function) using a filter function (pooling process may also be taken as convolution using a special filter (e.g., average or max)):

$$[00001] Z_{h',w',c'} = \begin{cases} W^T (X_{h,w,c}^F \odot X_{h,w}^M) \frac{\text{sum}(1)}{\text{sum}(X_{h,w}^M)} + b, & \text{if } \text{sum}(X_{h,w}^M) > 0 \\ 0, & \text{otherwise} \end{cases} \quad [1]$$

where W is a matrix including the convolution filter weights and WT is the transpose of W , b is the bias for the convolution filter, $\times_{\text{sub.h,w,c.sup.F}}$ denotes the sliding convolution window centered at (h, w, c) in F , $X_{\text{sub.h,w.sup.M}}$ denotes the binary mask corresponding to the current sliding convolution window centered at (h, w) in M , $\odot$ denotes element-wise multiplication, and 1 has the same shape as M but with all the elements being 1 . The scaling factor $\text{sum}(1)/\text{sum}(X_{\text{sub.h,w.sup.M}})$ applies appropriate scaling to adjust for the varying amount of valid (unmasked) inputs. After each partial convolution operation, the mask may be updated as follows: if the convolution was able to condition its output on at least one valid input value, then that location is marked valid, which is expressed as:

$$[00002]M'_{h',w'} = \begin{cases} 1, & \text{if } \text{sum}(X_{h,w}^M) > 0 \\ 0, & \text{otherwise} \end{cases}$$

In Equation [1], the mask image M has the same dimension $H \times W$ (e.g., 64×64 , 32×32 , 8×8) as the feature map or the input image F in one channel, with value “0” in masked area and value “1” in unmasked area. As illustrated in Equation [1], the masked area in the mask image M has no contribution to $Z_{\text{sub.h',w',c'}}$ since $M_{\text{sub.h,w}}$ has value “0” in the masked area. Accordingly, the masked area of the mask image M may be selected to cover the invalid pixels (e.g., background, image error, other object) in the input image to make the invalid pixels logically ignored when using the partial texture VAE, as illustrated in FIG. 14.

[0067] The mask-aware texture encoding layer (TEL) **410** in the partial texture VAE may include a learnable residual encoding layer, which may include a codebook **412** (dictionary, e.g., $64 \times 32 \times 1$). The feature map **408** may be reshaped to a feature map **414** (e.g., $64 \times (8 \times 8) \times 1$), which may be used as an input for the residual encoding layer. Residual vector representation **416** (e.g., $32 \times 64 \times (8 \times 8)$) may be calculated by pairwise difference between the feature map **414** and the codes (e.g., 32 codes) of the codebook **412**. Assignment weights **418** (e.g., $32 \times (8 \times 8) \times 1$) may be calculated based on pairwise distance between the feature map **414** and the codes of the codebook **412**. The masked image **408M** may be reshaped to a masked array **420M** (e.g., $1 \times (8 \times 8)$) and used together with the assignment weights **418** to be aggregated with the residual vector representation **416** to generate feature aggregation map **422** (e.g., $32 \times 64 \times (8 \times 8)$). For example, the masked area **421M** in the masked array **420M** may be transformed to a slice **421** (e.g., $32 \times 64 \times 1$) in the feature aggregation map **422**. The feature aggregation map **422** may be used to generate a feature map **424** (e.g., $32 \times 64 \times 1$), which may be reshaped to a fixed-length representation **426** (e.g., $64 \times 32 \times 1$), in which the resulting vectors may be normalized using the L2 normalization. Therefore, the TEL **410** acts as a feature aggregation module. There are several advantages in integrating this module, for example, the TEL **410** may take images with any input sizes and provide the output as a fixed-length representation, which may be spatially orderless representation, making the feature translation invariant and scale equivariant, as well as rotation invariance.

[0068] The fixed-length representation **426** may be fed into a fully connected (FC) layer to generate an updated map **428**. The FC layer may multiply the input by a weight matrix and then add a bias vector. The FC layers may be used for updating weights due to its ability to introduce more connectivity possibilities, as every neuron of the FC is connected to every neuron of the previous layer. The updated map **428** may be used to generate a feature map **430** via reparameterization. The feature map **430** may then be decoded by the decoder of the partial texture VAE to generate a feature map **432** (e.g., $8 \times 8 \times 64$), which may be used to generate a feature map **434** (e.g., $16 \times 16 \times 32$). The feature map **434** may be used to generate a feature map **436** (e.g., $32 \times 32 \times 8$), which may be used to generate an output image **438** (e.g., $64 \times 64 \times 3$). The decoder may integrate up-sampling blocks followed by a convolution layer instead of a deconvolution layer (e.g., to avoid the checkerboard effects in the generated image).

[0069] FIG. 12 illustrates a process **500** for image analysis using another embodiment of a partial texture VAE, which uses a mask-aware global average pooling (GAP) **510** instead of the mask-

aware TEL **410** in the encoder and uses partial convolution in the convolution layers of the encoder of the partial texture VAE. As illustrated in FIG. **12**, the last feature map **408** and the last updated mask image **408M** generated by the encoder of the partial texture VAE may be input into the mask-aware global average pooling (GAP) **510**. During the average pooling operation in the GAP **510**, only the unmasked area in the mask image may contribute to the result, as illustrated in Equation [2] below. Equation [2] describe a mask-aware global average pooling on the last feature map $F \in R.\text{sup.}(H \times W \times C)$ (e.g., the feature map **408**) to generate a global feature tensor **526**:

$$[00003] \ Z_i = [\frac{1}{\text{sum}(M)} \cdot \text{Math}_{h=1}^H \cdot \text{Math}_{w=1}^W F_{h,w,c} M_{h,w}] \quad [2]$$

Where i corresponds to c, M.sub.h,w represents the value at a location on the last mask image $M \in \{0, 1\}.\text{sup.}H \times W$ (e.g., the mask image **408M**) with coordinate (h,w) (e.g., height $h=1, 2 \dots H$, width $w=1, 2 \dots W$), and F.sub.h,w,c represents the value at a location on the last feature map $F \in R.\text{sup.}(H \times W \times C)$ with coordinate (h,w,c). In Equation [2], the mask image M has the same dimension $H \times W$ (e.g., 64×64 , 32×32 , 8×8) as the feature map or the input image F in one channel, with value “0” in masked area and value “1” in unmasked area. As illustrated in Equation [2], the masked area in the mask image M has no contribution to Z.sub.i since M.sub.h,w has value “0” in the masked area. Accordingly, the masked area of the mask image M may be selected to cover the invalid pixels (e.g., background, image error, other object) in the input image to make the invalid pixels logically ignored when using the partial texture VAE, and the pixel values of the invalid pixels may not contribute to the result of the partial texture VAE.

[0070] As illustrated in FIG. **12**, the GAP **510** is used to convert the feature map **408** to an one-dimensional (1D) global feature tensor **526** based on the average response amplitude of each channel of the feature map **408**. Since the mask image **408M** has value “0” in the masked area, the masked area has no contribution to the tensor **526**. In addition, the GAP **510** makes the feature rotation and translation invariant and scale equivariant. These aspects of the feature are important from geological point of view. Accordingly, rotated or translated versions of the image may be assigned with the same or very similar features as the original image, and re-scaled versions of the image may be assigned with different feature values (e.g., to distinguish fine sandstone and medium sandstone).

[0071] The global feature tensor **526** may be fed into a fully connected (FC) layer, which acts as a classifier to generate an updated map **528**. The FC layer may multiply the input by a weight matrix and then add a bias vector. The FC layers may be used for updating weights due to its ability to introduce more connectivity possibilities, as every neuron of the FC is connected to every neuron of the previous layer. The updated map **528** may be used to generate a feature map **530** via reparameterization. The feature map **530** may then be decoded by the decoder of the partial texture VAE. For example, the feature map **530** may be decoded to generate a feature map **532** (e.g., $8 \times 8 \times 64$), which may be used to generate a feature map **534** (e.g., $16 \times 16 \times 32$). The feature map **534** may be used to generate a feature map **536** (e.g., $32 \times 32 \times 8$), which may be used to generate an output image **538** (e.g., $64 \times 64 \times 3$). The decoder may integrate up-sampling blocks followed by a convolution layer instead of a deconvolution layer (e.g., to avoid the checkerboard effects in the generated image).

[0072] FIG. **13** is a block diagram illustrating a training process **600** for a partial texture VAE **602** including a GAP layer, such as the partial texture VAE in FIG. **12**. The training process **600** may be used to update the network parameters based on a loss function using training data. For instance, a set of individual cutting instance images **604** (e.g., $I.\text{sub.i} \in R.\text{sup.}(H_i \times W_i \times 3)$) may be used as training images, which may be cropped to have the same size to be used as the training data for the partial texture VAE **602**. For example the images **604** with $I.\text{sub.i} \in R.\text{sup.}$

$(H.\text{sup.i}.\text{sup.} \times W.\text{sup.i}.\text{sup.} \times 3)$ may be transformed to cropped images **606** with $I.\text{sub.i}.\text{sup.crop} \in R.\text{sup.}(H.\text{sup.crop}.\text{sup.} \times W.\text{sup.crop}.\text{sup.} \times 3)$, with the cropped image dimensions $H.\text{sub.crop}$ and $W.\text{sub.crop}$ fixed to a specific value (e.g., 56, 64, 128). In some embodiments, the cropped images

606 may be the portions of the corresponding images **604** that contain no invalid pixels (e.g., background, image error, other object), and corresponding synthetic mask images **608** (e.g., $M_{\text{sub.i.sup.crop}} \in \{0, 1\} \cdot \text{sup.}(H_{\text{sup.crop.sup.}} \times W_{\text{sup.crop.sup.}})$) may be created randomly (e.g., adding number N randomly selected ellipsoidal spots), as illustrated in FIG. 13.

[0073] The cropped images **606** $I_{\text{sub.i.sup.crop}}$ and the mask images **608** $M_{\text{sub.i.sup.crop}}$ may be used as an input **610** for training the partial texture VAE **602**. The partial texture VAE **602** may include an encoder **612**, which may include hidden layers (e.g., convolution layers, pooling layers) using partial convolution. The encoder **612** may include a GAP layer **614**, and during the average pooling operation in the GAP **612**, only the unmasked area in the mask images **608** may contribute to the result, as illustrated in Equation [2] above. Features may be extracted by the encoder **612** from the cropped images **606** and generate corresponding feature maps **616**, which may be decoded by a decoder **618** of the partial texture VAE **602** to generate corresponding output images **620** $I_{\text{sub.o.sup.crop}}$. The output images **620** $I_{\text{sub.i.sup.crop}}$ may have a relationship with the input **610**, as described in Equation [3]:

$$[00004] \hat{I}_o^{\text{crop}} = \text{autoencoder}(I_i^{\text{crop}}, M_i^{\text{crop}}) \quad [3]$$

[0074] To extract textural information in the latent space, a perceptual loss may be used in the loss function for training the VAE **602** to better capture textual information (e.g., using Mean squared error (MSE) or binary cross entropy (BCE) may cause a blurred version of the input image). For instance, $\emptyset_{\text{sub.j(I)}}$ may be the activation of the j -th layer of the network $\emptyset$ when processing image I . The j -th layer may be a convolutional layer, so $\emptyset_{\text{sub.j(I)}}$ is a feature map of shape $C_{\text{sub.j}} \times H_{\text{sub.j}} \times W_{\text{sub.j}}$, i.e., $\emptyset_{\text{sub.j}}(I) \in R_{\text{sup.}}(C_{\text{sup.j.sup.}} \times H_{\text{sup.j.sup.}} \times W_{\text{sup.j}})$. The network $\emptyset$ may be well-known architecture, such as VGG, AlexNet, and Squeeze Net, and pretrained with a large dataset such as ImageNet. The layer j to be used from the network $\emptyset$ may be a choice of the design. The perceptual loss using j -th layer is defined in Equation [4] as:

$$[00005] L_{\text{recons}}^j(I_i^{\text{crop}}, \hat{I}_o^{\text{crop}}) = f(\emptyset_j(I_i^{\text{crop}}), \emptyset_j(\hat{I}_o^{\text{crop}})) \quad [4]$$

In Equation [4], there may be different ways to define the function f , which is used to compute the loss from two feature maps, such as using the pairwise L2 distance, L2 distance of the Gram matrices, or combination of them with weight parameters. The function f may also integrate cosine similarity or structural similarity (SSIM). The total reconstruction loss is the sum of the reconstruction losses from all the target layers, as illustrated in Equation [5]:

$$[00006] L_{\text{recons}} = \text{Math.j} \quad L_{\text{recons}}^j(I_i^{\text{crop}}, \hat{I}_o^{\text{crop}}) \quad [5]$$

In addition, Kullback-Leibler (KL) divergence loss (e.g., $L_{\text{sub.KLD}} \text{DKL}(q(z|I)||p(z))$) may be used during the training process to control the distribution of the latent vector z , which is independent Gaussian random variables (e.g., random variables with a unit variance and zero mean). The final loss may be expressed as in Equation [6]:

$$[00007] L_{\text{total}} = L_{\text{recons}} + L_{\text{KLD}}, \quad [6]$$

where β is a weighting parameter. The value of β may be selected so that both $L_{\text{sub.recons}}$ and $L_{\text{sub.KLD}}$ smoothly decrease during training.

[0075] FIG. 14 is a block diagram illustrating a feature extraction process **700** to extract features from analyzing images **702** by using the encoder **612** after the partial texture VAE **602** is trained. For instance, an input image **704** $I_{\text{sub.i}} \in R_{\text{sup.}}(H_{\text{sup.i.sup.}} \times W_{\text{sup.i.sup.}} \times 3)$ may be selected from the analyzing images **702**, and corresponding mask image **706** $M_{\text{sub.i}} \in \{0, 1\} H_i \times W_i$ may be used as an input **708** for inputting into the encoder **612** to extract D -dimensional feature vector $v_{\text{sub.i}} \in R_{\text{sup.}}D$ included in the feature map **710**. The mask image **706** may be obtained from instance segmentation computation (e.g., via the cutting instances segmentation module **112**) or generated by checking specific pixel values (e.g., (255, 255, 255)) in the image **704**, which may correspond to the background (e.g., the sample tray) used during the image acquisition **96**, when

taking an image of the cuttings **46**. In some embodiments, The mask image **706** (e.g., dark area corresponding to the foreground and while area corresponding to the background of the images **704**) may be any shape corresponding to a corresponding part of the image **704** (e.g., background, image error, other object, a certain area), and the mask image **706** may be used in the encoder **612** to logically ignore the corresponding part of the images **704** (e.g., for image inpainting) by using the partial convolution operation.

[0076] In the illustrated embodiment in FIG. **14**, the input images may not be cropped since the GAP layer **614** is trained. The invalid pixels (e.g., background, image error, other object) in the input image **704** are logically ignored due to the use of partial convolution as described above. The feature vector $v_{sub.i}$ may be expressed in Equation [7]:

$$[00008] \ v_i = \text{Encocer}(I_i, M_i) \quad [7]$$

[0077] The extracted features may be used in different ways, such as classification, clustering, information retrieval, visualization, etc. The features may be used as input of a lithology classification and similarity-based property extraction. The classification may be parametric (requires training) or non-parametric (does not require training). The extracted features may also be used as inputs of clustering of the cuttings instance images. Most similar cuttings may be retrieved based on the distance between feature vectors. For example, the smaller the distance between two feature vectors of two images, the more similar the two images are. Dimensions of the feature maps may be modified (e.g., reduced) using technique such as PCA and t-SNE, and the feature maps may be plotted in 2D or 3D map. In visualizations, visually similar cuttings may be placed in the same area. The visual distribution helps interpretation of the rock type groups. FIG. **15** shows a visualization **800** of the rock cuttings. The cutting images projected in the 2D or 3D space after reducing the dimension from the original D-dimensional feature space using projection techniques such as t-SNE (t-distributed stochastic neighbor embedding) or PCA (principal component analysis) may be displayed. The color and patterns used in the display **800** may be lithological patterns of the user company's standard or based on the USGS (United States Geological Survey) standard. The property description of the cuttings may show the distributions of the lithology types (e.g., dolostone **806**, limestone **808**, sandstone **810**, mudrock **812**, uncertain category **814**, unknown category **816**).

[0078] The techniques and system disclosed herein relate to analyzing rock cuttings and measure physical lithological features of the rock cuttings. Systems and methods are provided to extract features (e.g., colors, textual features) from arbitrary shaped and sized images containing invalid pixels (e.g., background, image error, other object) by implementing global average pooling (GAP) and partial convolution in an autoencoder (AE) for analysis of the images. It should be noted that, the feature extraction technique described herein may be applied to other images (e.g., rock core images, borehole images) and/or images in any domain, such as remote sensing and medical imaging. In some embodiments, an autoencoder (AE), which may be data driven and/or unsupervised, may be used to extract texture features from images. In some embodiments, a variational autoencoder (VAE) may be used to control the distribution of the latent space. In some embodiments, a vanilla AE may be used instead of VAE. A global average pooling (GAP) layer may be used at the last layer of the encoder to make the feature rotation and translation invariant and scale equivariant. In addition, partial convolution may be used in the encoder to logically ignore the invalid pixels (e.g., background, image error, other object) in the images. It should be noted that, in some embodiments, the system and methods described herein may be used for excluding any pixel (e.g., in any area of the input image) from the feature extraction process for imaging processing purposes, such as image inpainting, etc. An image analysis workflow is provided, which includes multiple computational modules to automatically extract relevant geological information from rock cuttings. Reference data, manual descriptions, and well log values are associated and used to determine rock properties of the rock cuttings. A software is

developed for the image analysis, and results are displayed in various views. The results may be used to control related devices, such as the drilling system **10** and/or drilling plans of the drilling system **10** based on the rock properties (e.g., lithology) of the rock cuttings. For example, the analysis and control system **50** may automatically adjust one or more operating parameters of the drilling system **10** from which the rock cuttings are obtained based at least in part on the determined rock properties of the rock cuttings. The techniques and method disclosed herein may allow the acquisition of high quality logging curves for real-time and/or near real-time geologic formation evaluation and geosteering, which may be used to control the drilling process more efficiently and accurately. Although the examples described above are illustrated for wellbores on the land, similar method may be applied to any acquisition configuration. In addition, in the illustrated embodiments above, the techniques and systems are primarily described in the context of digital images having three color channels (e.g., R, G, B). However, the techniques and systems described above may be applied to other types of digital images, such as grayscale images, hyperspectral images, multispectral images, etc.

[0079] The specific embodiments described above have been illustrated by way of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover all modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

[0080] In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents, but also equivalent structures. Thus, for example, although a nail and a screw may not be structural equivalents in that a nail employs a cylindrical surface to secure wooden parts together, whereas a screw employs a helical surface, in the environment of fastening wooden parts, a nail and a screw may be equivalent structures. It is the express intention of the applicant not to invoke 35 U.S.C. § 112, paragraph 6 for any limitations of any of the claims herein, except for those in which the claim expressly uses the words “means for” together with an associated function.

Claims

1. A method, comprising: receiving, via an encoder, an image; generating, via the encoder, a feature map by performing a partial convolution operation using the image and a mask image for the image; generating, via the encoder, an updated mask image based on the mask image and a dimension of the feature map; performing, via the encoder, a global average pooling (GAP) operation on the feature map using the updated mask image to generate a global feature map; and generating, via the encoder, an output feature vector for the image based on the global feature map.
2. The method of claim 1, wherein the encoder is a part of a variational autoencoder (VAE).
3. The method of claim 1, comprising: generating the mask image for the image by detecting a specific pixel value in the image.
4. The method of claim 1, wherein the mask image comprises a binary image.
5. The method of claim 4, wherein the binary image comprises a first portion corresponding to invalid pixels of the image corresponding to pixel values equal to 0.
6. The method of claim 5, wherein the binary image comprises a second portion corresponding to valid pixels of the image corresponding to pixel values equal to 1.
7. The method of claim 1, wherein the image and the mask image have a same dimension.
8. The method of claim 1, wherein the global feature map comprises a one-dimensional (1D) tensor generated based on an average response amplitude of each channel of the feature map.
9. The method of claim 8, wherein the feature map comprises a plurality of channels, and each value of the 1D tensor is determined based on the updated mask image and a respective channel of the plurality of channels.

- 10.** The method of claim 1, wherein the image comprises a cutting instance image of a cutting of a geological formation, and wherein the output feature vector comprises a rock property of the cutting.
 - 11.** The method of claim 10, wherein the rock property comprises textual information.
 - 12.** The method of claim 10, wherein the rock property comprises color information.
 - 13.** A method of training an autoencoder (AE), comprising: generating a set of training images from a plurality of images; generating respective mask images for the set of training images; inputting the set of training images and the respective mask images into an encoder of the AE, wherein the encoder is configured to: generating respective feature maps for the set of training images by performing partial convolution operation using the training images and the respective mask images; and generating respective global feature maps by performing a global average pooling (GAP) operation on the respective feature maps; generating, via a decoder of the AE, respective output images for the set of training images based on the respective global feature maps; and training the AE using the respective output images and the training images based on a loss function.
 - 14.** The method of claim 13, wherein the set of training images and the respective mask images have a same dimension.
 - 15.** The method of claim 13, comprising: generating the respective mask images for the set of training images randomly.
 - 16.** The method of claim 13, wherein the loss function comprises a perceptual loss function for extracting textual information from the set of training images.
 - 17.** The method of claim 13, wherein the plurality of images comprise cutting instance images of a cutting of a geological formation.
 - 18.** An autoencoder (AE), comprising: an encoder, comprising: a convolution layer configured to generate a feature map by performing a partial convolution operation using an image and a mask image for the image; and a global average pooling (GAP) layer configured to generate a global feature map by performing a GAP operation on the feature map using an updated mask image generated based on the mask image; and a decoder configured to generate an output image based on the global feature map.
 - 19.** The AE of claim 18, wherein the mask image comprises a binary image.
 - 20.** The AE of claim 19, wherein the binary image comprises a first portion corresponding to invalid pixels of the image corresponding to pixel values equal to 0.
 - 21.** The AE of claim 20, wherein the binary image comprises a second portion corresponding to valid pixels of the image corresponding to pixel values equal to 1.
 - 22.** The AE of claim 18, wherein the GAP layer is configured to generate the global feature map with feature rotation and translation invariant and scale equivariant.
 - 23.** The AE of claim 18, wherein the image comprises a cutting instance image of a cutting of a geological formation.
-