

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410032
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Katsumata; Toshiyuki et al.

Sheet binding apparatus, sheet processing apparatus, and image forming system

Abstract

A guide portion guides a binding unit in a first direction and a second direction. The guide portion includes a pair of first wall portions, a pair of second wall portions, a pair of third wall portions, and a restricting portion. A first protrusion is engageable between the pair of first wall portions and between the pair of second wall portions. A second protrusion is disposed upstream of the first protrusion in the first direction, and is engageable with the pair of first wall portions and the pair of third wall portions. The restricting portion restricts entry of the first protrusion from between the pair of first wall portions to between the pair of third wall portions and permits entry of the second protrusion from between the pair of first wall portions to between the pair of third wall portions.

Inventors: Katsumata; Toshiyuki (Yamanashi, JP), Nakajima; Junya (Yamanashi, JP), Takahashi; Masaya (Yamanashi, JP), Kubo; Mamoru (Yamanashi, JP)

Applicant: CANON FINETECH NISCA INC. (Saitama, JP)

Family ID: 89577837

Assignee: Canon Finetech Nisca Inc. (Saitama, JP)

Appl. No.: 18/354036

Filed: July 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240025692 A1	Jan. 25, 2024

Foreign Application Priority Data

JP	2022-117885	Jul. 25, 2022
JP	2023-113320	Jul. 10, 2023

Publication Classification

Int. Cl.: B65H37/04 (20060101); B65H31/02 (20060101)

U.S. Cl.:

CPC B65H37/04 (20130101); B65H31/02 (20130101); B65H2301/4213 (20130101); B65H2301/51611 (20130101); B65H2404/743 (20130101)

Field of Classification Search

CPC: B65H (2301/51611); B65H (2404/743); B65H (31/02); B65H (37/04); B65H (2301/4213); B65H (2801/27)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7654511	12/2009	Nagata et al.	N/A	N/A
2018/0348692	12/2017	Yoshida	N/A	B65H 37/04
2022/0204302	12/2021	Nishi	N/A	B65H 31/34

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2006-248685	12/2005	JP	N/A
2014-061964	12/2013	JP	N/A
WO-2021188175	12/2020	WO	N/A

Primary Examiner: Bahls; Jennifer

Attorney, Agent or Firm: Venable LLP

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to a sheet binding apparatus that performs a binding process on sheets, a sheet processing apparatus including the sheet binding apparatus, and an image forming system including the sheet processing apparatus.

Description of the Related Art

(2) As a sheet processing apparatus, a configuration including a sheet binding apparatus having a binding unit such as a staple unit that performs a binding process on sheets is conventionally known. In addition, as such a sheet binding apparatus, a configuration in which a staple unit is moved along a width direction of a sheet to perform a side stitch binding in which a binding process is performed in parallel to the width direction with respect to an edge portion of the sheet and an oblique binding in which a binding process is performed in a direction inclined in the width direction with respect to a corner portion of the sheet is conventionally known.

(3) As a mechanism for moving the staple unit in the width direction, for example, JP 2014-61964

A discloses a configuration in which a groove is formed in a moving table for moving the staple unit, and two protrusions provided on the staple unit side are engaged with the groove to guide the staple unit. In the case of the configuration described in JP 2014-61964 A, the mechanism includes a main body groove formed along the width direction, a branch groove branched from the main body groove on the end side in the width direction of the main body groove, and an extension groove further formed along the main body groove from a branch point. Further, when the oblique binding is performed on the corner portion of the sheet, the oblique binding can be executed by inclining the staple unit by guiding one protrusion on the downstream side in the moving direction of the staple unit to the branch groove and the other protrusion on the upstream side to the extension groove, of the two protrusions on the staple unit side.

(4) Here, in order to engage the protrusion on the downstream side with the branch groove in order to perform the oblique binding, normally, a turning assisting member serving as a trigger for turning the staple unit with the movement of the staple unit is required. As the turning assisting member, for example, there is a configuration in which the turning assisting member provided outside the groove and the staple unit is turned by being brought into contact with a part of a member moving together with the staple unit.

(5) It is desired to further improve a configuration in which a binding unit such as a staple unit is turned when oblique binding is performed.

SUMMARY OF THE INVENTION

(6) According to a first aspect of the present invention, a sheet binding apparatus includes a binding unit configured to move in a first direction and a second direction opposite to the first direction and perform a binding process on sheets, a guide portion configured to guide the binding unit in the first direction and the second direction, a moving portion configured to move along the guide portion together with the binding unit, a rotation holding portion configured to rotatably hold the binding unit with respect to the moving portion, an engaging portion that is provided to be movable in the first direction and the second direction together with the binding unit and to be rotatable together with the binding unit, the engaging portion including a first protrusion and a second protrusion each engaged with the guide portion, and, a driving unit configured to drive the moving portion to move the moving portion along the guide portion. The guide portion includes a pair of first wall portions formed along the first direction, a pair of second wall portions formed along an inclined direction inclined with respect to the first direction from a downstream end of the first wall portion in the first direction, a pair of third wall portions formed along the first direction from a downstream end of the first wall portion in the first direction, and a restricting portion. The pair of first wall portions is disposed so as to guide the first protrusion and the second protrusion movably along the first direction in a state where the first protrusion and the second protrusion are disposed between the pair of first wall portions. The pair of the second wall portions is disposed so as to guide the first protrusion movably along the inclined direction in a state where the first protrusion is disposed between the pair of second wall portions. The pair of the third wall portions is disposed so as to guide the second protrusion movably along the first direction from the downstream end of the first wall portion in the first direction in a state where the second protrusion is disposed between the pair of third wall portions. The first protrusion is engageable between the pair of first wall portions and between the pair of second wall portions by a first engagement amount in a height direction of the first wall portions and the second wall portions. The second protrusion is disposed upstream of the first protrusion in the first direction, and is engageable between the pair of first wall portions and between the pair of third wall portions by a second engagement amount smaller than the first engagement amount in the height direction of the first wall portions and the third wall portions. The restricting portion is configured to restrict entry of the first protrusion from between the pair of first wall portions to between the pair of third wall portions and permit entry of the second protrusion from between the pair of first wall portions to between the pair of third wall portions.

(7) According to a second aspect of the present invention, a sheet processing apparatus includes a first conveyance portion configured to convey a sheet in a first conveyance direction, a placement portion configured to place the sheet conveyed to a downstream side in the first conveyance direction by the first conveyance portion, a second conveyance portion configured to convey the sheet on the placement portion in a second conveyance direction opposite to the first conveyance direction, an abutment portion against which a downstream end edge in the second conveyance direction of the sheet conveyed in the second conveyance direction by the second conveyance portion abuts, and, a sheet binding apparatus configured to perform a binding process on the sheet which is conveyed in the second conveyance direction by the second conveyance portion and of which the downstream end edge in the second conveyance direction is abutted against the abutment portion. The sheet binding apparatus includes a binding unit configured to move in a first direction and a second direction opposite to the first direction and perform a binding process on sheets, a guide portion configured to guide the binding unit in the first direction and the second direction, a moving portion configured to move along the guide portion together with the binding unit, a rotation holding portion configured to rotatably hold the binding unit with respect to the moving portion, an engaging portion that is provided to be movable in the first direction and the second direction together with the binding unit and to be rotatable together with the binding unit, the engaging portion including a first protrusion and a second protrusion each engaged with the guide portion, and, a driving unit configured to drive the moving portion to move the moving portion along the guide portion. The guide portion includes a pair of first wall portions formed along the first direction, a pair of second wall portions formed along an inclined direction inclined with respect to the first direction from a downstream end of the first wall portion in the first direction, a pair of third wall portions formed along the first direction from a downstream end of the first wall portion in the first direction, and a restricting portion. The pair of first wall portions is disposed so as to guide the first protrusion and the second protrusion movably along the first direction in a state where the first protrusion and the second protrusion are disposed between the pair of first wall portions. The pair of the second wall portions is disposed so as to guide the first protrusion movably along the inclined direction in a state where the first protrusion is disposed between the pair of second wall portions. The pair of the third wall portions is disposed so as to guide the second protrusion movably along the first direction from the downstream end of the first wall portion in the first direction in a state where the second protrusion is disposed between the pair of third wall portions. The first protrusion is engageable between the pair of first wall portions and between the pair of second wall portions by a first engagement amount in a height direction of the first wall portions and the second wall portions. The second protrusion is disposed upstream of the first protrusion in the first direction, and is engageable between the pair of first wall portions and between the pair of third wall portions by a second engagement amount smaller than the first engagement amount in the height direction of the first wall portions and the third wall portions. The restricting portion is configured to restrict entry of the first protrusion from between the pair of first wall portions to between the pair of third wall portions and permit entry of the second protrusion from between the pair of first wall portions to between the pair of third wall portions. By moving along the guide portion by the driving unit, the binding unit is capable of performing a first binding process of binding a downstream edge portion of the sheets in the second conveyance direction in a direction along a width direction of the sheet intersecting the second conveyance direction and a second binding process of binding a corner portion of the downstream edge portion of the sheets in the second conveyance direction on one end side of the sheet in the width direction in a direction inclined with respect to the width direction.

(8) According to a third aspect of the present invention, an image forming system includes an image forming apparatus including an image forming unit configured to form an image on a sheet, and a sheet processing apparatus configured to perform a binding process on a sheet on which an image is formed by the image forming unit. The sheet processing apparatus includes a first

conveyance portion configured to convey a sheet in a first conveyance direction, a placement portion configured to place the sheet conveyed to a downstream side in the first conveyance direction by the first conveyance portion, a second conveyance portion configured to convey the sheet on the placement portion in a second conveyance direction opposite to the first conveyance direction, an abutment portion against which a downstream end edge in the second conveyance direction of the sheet conveyed in the second conveyance direction by the second conveyance portion abuts, and, a sheet binding apparatus configured to perform a binding process on the sheet which is conveyed in the second conveyance direction by the second conveyance portion and of which the downstream end edge in the second conveyance direction is abutted against the abutment portion. The sheet binding apparatus includes a binding unit configured to move in a first direction and a second direction opposite to the first direction and performs a binding process on sheets, a guide portion configured to guide the binding unit in the first direction and the second direction, a moving portion configured to move along the guide portion together with the binding unit, a rotation holding portion configured to rotatably hold the binding unit with respect to the moving portion, an engaging portion that is provided to be movable in the first direction and the second direction together with the binding unit and to be rotatable together with the binding unit, the engaging portion including a first protrusion and a second protrusion engaged with the guide portion, and, a driving unit configured to drive the moving portion to move the moving portion along the guide portion. The guide portion includes a pair of first wall portions formed along the first direction, a pair of second wall portions formed along an inclined direction inclined with respect to the first direction from a downstream end of the first wall portion in the first direction, a pair of third wall portions formed along the first direction from a downstream end of the first wall portion in the first direction, and a restricting portion. The pair of first wall portions is disposed so as to guide the first protrusion and the second protrusion movably along the first direction in a state where the first protrusion and the second protrusion are disposed between the pair of first wall portions. The pair of the second wall portions is disposed so as to guide the first protrusion movably along the inclined direction in a state where the first protrusion is disposed between the pair of second wall portions. The pair of the third wall portions is disposed so as to guide the second protrusion movably along the first direction from the downstream end of the first wall portion in the first direction in a state where the second protrusion is disposed between the pair of third wall portions. The first protrusion is engageable between the pair of first wall portions and between the pair of second wall portions by a first engagement amount in a height direction of the first wall portions and the second wall portions. The second protrusion is disposed upstream of the first protrusion in the first direction, and is engageable between the pair of first wall portions and between the pair of third wall portions by a second engagement amount smaller than the first engagement amount in the height direction of the first wall portions and the third wall portions. The restricting portion is configured to restrict entry of the first protrusion from between the pair of first wall portions to between the pair of third wall portions and permit entry of the second protrusion from between the pair of first wall portions to between the pair of third wall portions. By moving along the guide portion by the driving unit, the binding unit is capable of performing a first binding process of binding a downstream edge portion of the sheets in the second conveyance direction in a direction along a width direction of the sheet intersecting the second conveyance direction and a second binding process of binding a corner portion of the downstream edge portion of the sheets in the second conveyance direction on one end side of the sheet in the width direction in a direction inclined with respect to the width direction.

(9) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic configuration cross-sectional view of an image forming system according to an embodiment.
- (2) FIG. 2 is a schematic configuration cross-sectional view of a sheet processing apparatus according to the embodiment.
- (3) FIG. 3 is a perspective view of the sheet processing apparatus according to the embodiment.
- (4) FIG. 4 is a schematic configuration perspective view of the sheet binding apparatus according to the embodiment.
- (5) FIG. 5 is an exploded perspective view of a base portion of the sheet binding apparatus according to the embodiment.
- (6) FIG. 6 is an exploded perspective view of a stapler moving unit of the sheet binding apparatus according to the embodiment.
- (7) FIG. 7 is a perspective view illustrating a relationship between a cam groove and a stapler holding unit according to the embodiment.
- (8) FIG. 8A is a perspective view of the stapler holding unit according to the embodiment.
- (9) FIG. 8B is a cross-sectional view of the stapler moving unit according to the embodiment.
- (10) FIG. 9 is a perspective view of the stapler moving unit according to an embodiment.
- (11) FIG. 10 is a perspective view of the cam groove according to the embodiment.
- (12) FIG. 11 is a perspective view illustrating a relationship between the cam groove and a moving portion according to the embodiment.
- (13) FIG. 12 is a plan view of the cam groove according to the embodiment.
- (14) FIG. 13A is a plan view illustrating a relationship between the cam groove and the stapler moving unit at a home position.
- (15) FIG. 13B is a plan view illustrating a relationship between the cam groove and the moving portion at the home position.
- (16) FIG. 14A is a plan view illustrating a relationship between the cam groove and the stapler moving unit at an oblique binding position on a front side.
- (17) FIG. 14B is a plan view illustrating a relationship between the cam groove and the moving portion at the oblique binding position on the front side.
- (18) FIG. 15A is a plan view illustrating a relationship between the cam groove and the stapler moving unit at an oblique binding position on a rear side.
- (19) FIG. 15B is a plan view illustrating a relationship between the cam groove and the moving portion at the oblique binding position on the rear side.
- (20) FIG. 16A is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a first state of movement of the stapler moving unit from the home position to a first groove.
- (21) FIG. 16B is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a second state of movement of the stapler moving unit from the home position to the first groove.
- (22) FIG. 16C is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a third state of movement of the stapler moving unit from the home position to the first groove.
- (23) FIG. 16D is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a fourth state of movement of the stapler moving unit from the home position to the first groove.
- (24) FIG. 16E is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a fifth state of movement of the stapler moving unit from the home position to the first groove.
- (25) FIG. 17A is a schematic diagram illustrating a relationship between the cam groove and the

- stapler moving unit, the relationship illustrating a first state of movement of the stapler moving unit from the first groove to the oblique binding position on the front side.
- (26) FIG. 17B is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a second state of movement of the stapler moving unit from the first groove to the oblique binding position on the front side.
- (27) FIG. 17C is a schematic view illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a third state of movement of the stapler moving unit from the first groove to the oblique binding position on the front side.
- (28) FIG. 18A is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a state in which the stapler moving unit is located at a side stitch binding position on the front side.
- (29) FIG. 18B is a schematic view illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a state in which the stapler moving unit is located at a side stitch binding position on the rear side.
- (30) FIG. 19A is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a first state of movement of the stapler moving unit from the first groove to the oblique binding position on the rear side.
- (31) FIG. 19B is a schematic diagram illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a second state of movement of the stapler moving unit from the first groove to the oblique binding position on the rear side.
- (32) FIG. 19C is a schematic view illustrating a relationship between the cam groove and the stapler moving unit, the relationship illustrating a third state of movement of the stapler moving unit from the first groove to the oblique binding position on the rear side.

DESCRIPTION OF THE EMBODIMENTS

(33) An embodiment will be described with reference to FIGS. 1 to 19C. First, a schematic configuration of an image forming system according to the present embodiment will be described with reference to FIG. 1. Note that, in the following description, a front side (F side) is a side on which the user operates the apparatus, that is, a front side of the apparatus, and is, for example, a side on which an operation unit such as a button or an operation panel for operating the image forming system is provided. A rear side (R side) is a side opposite to the front side in the width direction of the sheet to be described below, that is, a back side of the apparatus.

Image Forming System

- (34) FIG. 1 is a cross-sectional view illustrating the schematic configuration of the image forming system according to the present embodiment. An image forming system 1000A includes an image forming apparatus 100, a punch unit 150, and a sheet processing apparatus 200A. The image forming apparatus 100 is a copying machine, a printer, a facsimile, a multifunction peripheral having a plurality of functions thereof, or the like, and forms an image on a sheet such as a sheet of paper or a plastic sheet. In the present embodiment, an electrophotographic system printer is used, and a sheet on which a toner image is formed is discharged from a first discharge portion 101 or a second discharge portion 102. The image forming apparatus 100 may be an inkjet type image forming apparatus.
- (35) In the image forming apparatus of the present embodiment, although not illustrated in detail, a toner image is formed on a sheet in the image forming unit 103. Briefly, a surface of a photosensitive drum is charged and exposed to form an electrostatic latent image on the photosensitive drum. Then, the electrostatic latent image is developed with a developer by a developing unit to form a toner image. The toner image formed on the photosensitive drum is transferred to a sheet, and further heated and pressed by a fixing unit to be fixed to the sheet. The sheet on which the toner image is fixed is sent to the first discharge portion 101 or the second discharge portion 102 through a conveyance path 104.
- (36) The image forming apparatus 100 of the present embodiment includes an image forming

apparatus body **110** including the image forming unit **103**, the conveyance path **104**, the first discharge portion **101**, and the second discharge portion **102**, and an image reading unit **120** disposed above the image forming apparatus body **110**. The image reading unit **120** reads an image on a document and sends a read image signal to the image forming apparatus body **110**. The image forming apparatus body **110** includes a first casing unit **111** in which the image forming unit **103** is disposed, and a second casing unit **112** in which a part of the conveyance path **104**, the first discharge portion **101**, and the second discharge portion **102** are disposed, and the second casing unit **112** is provided above the first casing unit **111**. The image reading unit **120** is provided above the second casing unit **112**. In addition, an operation panel (not illustrated) is provided in the second casing unit, and an instruction (printing condition, mode setting, and the like) from the user can be input to the image forming apparatus **100**, the punch unit **150**, and the sheet processing apparatus **200A**.

(37) In the present embodiment, with such a configuration, an in-body space **130** surrounded by the first casing unit **111**, the second casing unit **112**, and the image reading unit **120** is provided. Then, the sheet is discharged from the first discharge portion **101** or the second discharge portion **102** into the in-body space **130**. The punch unit **150**, the sheet processing apparatus **200A**, and the like are detachable from the in-body space **130**. In the present embodiment, the image forming system **1000A** is configured by attaching the punch unit **150** and the sheet processing apparatus **200A**, but any one of the punch unit **150** and the sheet processing apparatus **200A** or another apparatus that performs sheet processing may be attached.

(38) The punch unit **150** is connected to the first discharge portion **101**, and can receive a sheet discharged from the first discharge portion **101** and perform punch processing on the sheet. The sheet processing apparatus **200A** is connected to a sheet discharge portion of the punch unit **150** and receives the sheet discharged from the punch unit **150**. As will be described in detail below, predetermined processing such as stapling can be performed on the sheet. It is possible to deliver the sheet to the sheet processing apparatus **200A** without performing punch processing by the punch unit **150**, and it is also possible to discharge the sheet without performing predetermined processing in the sheet processing apparatus **200A**. The sheet discharged from the second discharge portion **102** is discharged to a sheet placement surface **160** above the punch unit **150** and the sheet processing apparatus **200A**.

(39) In the in-body space **130**, a rail **131** is disposed along a left-right direction in FIG. **1**, and the punch unit **150** and the sheet processing apparatus **200A** are detachable in directions of arrows $\alpha 1$ and $\alpha 2$ along the rail **131**. The punch unit **150** may be omitted, and the sheet processing apparatus **200A** may be directly connected to the first discharge portion **101**. Further, by making the punch unit **150** and the sheet processing apparatus **200A** detachable in this manner, sheet jam processing can be performed.

(40) For example, when the sheet is jammed in the first discharge portion **101**, the punch unit **150** and the sheet processing apparatus **200A** are pulled out in the direction of the arrow $\alpha 1$ to expose the first discharge portion **101**. When the sheet is jammed in the punch unit **150**, only the sheet processing apparatus **200A** is pulled out in the direction of the arrow $\alpha 1$ to expose the punch unit **150**. When the punch unit **150** and the sheet processing apparatus **200A** are attached to the image forming apparatus **100**, the punch unit **150** and the sheet processing apparatus **200A** are pushed in the direction of the arrow $\alpha 2$. As described above, in the present embodiment, since the sheet processing apparatus **200A** is disposed in the in-body space **130** of the image forming apparatus **100**, it is required to reduce the size of the sheet processing apparatus **200A**.

Sheet Processing Apparatus

(41) A configuration of a sheet processing apparatus **200A** of the present embodiment will be described with reference to FIGS. **2** and **3**. The sheet processing apparatus **200A** includes a conveyance path **210A**, pre-processing rollers **211A** and **212A** serving as a first conveyance portion, a processing tray **220** serving as a placement portion, an upper discharge roller (i.e., nip

member) **230A** and a lower discharge roller **230B** serving as a pair of discharge rotary members (i.e., discharge portions), a reversing paddle **240A** serving as a second conveyance portion, a trailing edge dropping member **250A** serving as a sheet dropping portion, an alignment unit **270A** serving as a shift unit, a return member **280**, a trailing edge regulation member **290** serving as an abutment portion, a stacking tray **300** serving as a stacking portion, a sheet pressing paddle **320A**, and the like. The sheet received from the image forming apparatus **100** or the punch unit **150** is conveyed to the conveyance path **210A**.

(42) The sheet conveyed from the conveyance path **210A** is directly discharged to the stacking tray **300** or placed on the processing tray **220** according to the mode of processing the sheet. The direct discharge to the stacking tray **300** means that the sheet is discharged to the stacking tray **300** without being reversely conveyed to a position where staple processing can be executed with the sheet on the processing tray **220**. In other words, the sheet processing apparatus **200A** has a mode of discharging the sheets on which the staple processing is performed by the staple unit **400** to the stacking tray **300** and a mode of discharging the sheets to the stacking tray **300** without performing the staple processing by the staple unit **400**. In the present embodiment, the sheet can be aligned by the alignment unit **270A** without being placed on the processing tray **220**. Further, the sheet can be also aligned on the processing tray **220**, and the staple unit **400** can staple the sheets placed on the processing tray **220**. Further, the sheet or a sheet bundle placed on the processing tray **220** can be discharged to the stacking tray **300** by the upper discharge roller **230A** and the lower discharge roller **230B** serving as the pair of discharge rotary members, and the like. Hereinafter, a configuration of each unit will be described in detail.

Conveyance Path

(43) The conveyance path **210A** is a path that conveys a sheet in a first conveyance direction (predetermined direction), and includes an upper guide **2101** that guides an upper surface of the conveyed sheet and a lower guide **2102** that guides a lower surface of the sheet. In the conveyance path **210A**, the pre-processing rollers **211A** and **212A** serving as the first conveyance portion (the pair of conveyance rotary members), and upstream rollers (inlet rollers) **213a** and **213b** are disposed. These are disposed in pairs so as to be separated from each other in a width direction of the sheet (direction of arrow γ in FIG. 3) intersecting a conveyance direction of the sheet (first conveyance direction, direction of arrow β in FIG. 2 (left-right direction)), respectively.

(44) The pre-processing rollers **211A** and **212A** are a first conveyance portion and the pair of conveyance rotary members that convey a sheet, and at least one of the pre-processing rollers **211A** and **212A** rotates while nipping the sheet. At least one of the upstream rollers **213a** and **213b** rotates while nipping the sheet. The upstream rollers **213a** and **213b** are disposed at an inlet of the sheet processing apparatus **200A**, and receive a sheet conveyed from upstream of the sheet processing apparatus **200A** and convey the sheet to the conveyance path **210A**. Then, the sheet passing through the conveyance path **210A** reaches the pre-processing rollers **211A** and **212A**.

(45) The pre-processing rollers **211A** and **212A** form a pre-processing nip portion **211a** capable of nipping and conveying a sheet. Then, the sheet is nipped by the pre-processing nip portion **211a** and conveyed in the first conveyance direction, and the sheet is discharged from the conveyance path **210A**. The pre-processing rollers **211A** and **212A** can be brought into contact with or separated from each other, or the nip pressure can be changed.

Processing Tray

(46) The processing tray **220** serving as the placement portion is disposed on a downstream side in a sheet conveyance direction (first conveyance direction) of the conveyance path **210A** and vertically below the conveyance path **210A**. The processing tray **220** is inclined with respect to a horizontal plane such that an upstream side in the first conveyance direction is lower than the downstream side in the first conveyance direction. The processing tray **220** temporarily places the sheet conveyed to the downstream side in the first conveyance direction by the pre-processing rollers **211A** and **212A**. In addition, the processing tray **220** can stack a plurality of sheets in an

overlapping manner, and alignment of the sheets in the width direction and movement of the sheets in the width direction (shift of the sheets) are performed by the alignment unit **270A** with the sheets on the processing tray **220**. The trailing edge regulation member **290** serving as the abutment portion against which an upstream end edge (a downstream end edge in a second conveyance direction opposite to the first conveyance direction, and a trailing edge of the sheet) of the sheet placed on the processing tray **220** in the first conveyance direction abuts is disposed at an upstream end of the processing tray **220** in the first conveyance direction. A part of the processing tray **220** (for example, the downstream side end portion in the first conveyance direction) may protrude vertically above the conveyance path **210A**.

(47) Further, the staple unit **400** serving as a binding unit performing a binding process on the sheets is disposed upstream of the processing tray **220** in the first conveyance direction. The staple unit **400** performs staple processing (binding processing) as predetermined processing on the sheet bundle subjected to the alignment in the width direction and regulation of the trailing edge by the processing tray **220**. The staple unit **400** configures a part of a sheet binding apparatus **410** as described below, is configured to change a staple position with respect to the sheet bundle and to move according to the staple position. The predetermined processing may be other processing such as punching other than stapling. The sheet or the sheet bundle placed on the processing tray **220** are discharged to the stacking tray **300** by the upper discharge roller **230A** and the lower discharge roller **230B** as described below.

Reversing Paddle

(48) The reversing paddle **240A** serving as the second conveyance portion conveys the sheet on the processing tray **220** in the second conveyance direction opposite to the first conveyance direction. The reversing paddle **240A** includes a paddle portion **2401** serving as a rotary member, a paddle arm **2402** serving as a supporting portion that supports the paddle portion **2401**, and a swing fulcrum **2403** that swingably supports the paddle arm **2402**. That is, the paddle arm **2402** is swingable in a vertical direction about the swing fulcrum **2403**, and the paddle portion **2401** is rotatably provided at the distal end of the paddle arm **2402**.

(49) The reversing paddle **240A** is swingable about the swing fulcrum **2403** between a return position where the paddle portion **2401** abuts on the upper surface of the sheet on the processing tray **220** to convey the sheet in the second conveyance direction and an upper retracting position where the paddle portion **2401** is retracted above the return position. The swing fulcrum **2403** is disposed upstream of the pre-processing nip portion **211a**, which is a nip position at which the sheet is nipped by the pre-processing rollers **212A** and **211A**, in the first conveyance direction and vertically above the pre-processing nip portion **211a**. The paddle arm **2402** extends from the swing fulcrum **2403** toward the downstream side in the first conveyance direction, and the paddle portion **2401** is provided at a distal end portion thereof. A pair of the reversing paddles **240A** is disposed on both sides in the width direction of the upper discharge roller **230A** to be described below.

Trailing Edge Dropping Member

(50) A pair of the trailing edge dropping members **250A** serving as the sheet dropping portion is provided on both sides of the pair of reversing paddles **240A**. That is, the pair of the trailing edge dropping members **250A** is disposed on both sides of the reversing paddle **240A** in the width direction, and moves in the vertical direction in conjunction with the reversing paddle **240A** as described below, so that the pair of the trailing edge dropping members **250A** operates to abut on the upper surface of the sheet on the upstream side in the first conveyance direction and to drop the upstream end portion (trailing edge portion) of the sheet toward the processing tray **220**. The trailing edge dropping member **250A** may be operated by a separate drive from the reversing paddle **240A**.

(51) The trailing edge dropping member **250A** includes a pivot shaft **2501** serving as the pivot axis downstream of the pre-processing rollers **211A** and **212A** serving as the pair of conveyance rollers in the first conveyance direction. The trailing edge dropping member **250A** extends to the upstream

side in the first conveyance direction from the pivot shaft **2501**, and is pivotable about the pivot shaft **2501** from an upper position above the pre-processing rollers **211A** and **212A** to a lower position below the pre-processing rollers **211A** and **212A**. The trailing edge dropping member **250A** pivots from the upper position to the lower position, and thus, abuts on the sheet conveyed by the pre-processing rollers **211A** and **212A** from above and drops the sheet onto the processing tray **220** below.

Return Member

(52) The return member **280** conveys the sheet conveyed toward the trailing edge regulation member **290** by the reversing paddle **240A** as described above, further toward the trailing edge regulation member **290**, and brings the trailing edge of the sheet into contact with the trailing edge regulation member **290** to regulate the trailing edge position of the sheet. The return member **280** is configured by a knurled belt **281**, and rotationally drives the knurled belt **281** to further convey the sheet conveyed to the upstream side in the first conveyance direction by the reversing paddle **240A**, thereby bringing the trailing edge into contact with the trailing edge regulation member **290**. The return member **280** is movable to an abutting position where the return member **280** can abut on the sheet and a retracting position where the return member **280** is retracted above the abutting position, and moves to the abutting position when the sheet is conveyed toward the trailing edge regulation member **290** and to the retracting position when the sheet on the processing tray **220** is conveyed toward the stacking tray **300**.

Discharge Roller

(53) The upper discharge roller **230A** and the lower discharge roller **230B** configure the pair of discharge rotary members and the discharge portion, convey the sheet conveyed to the downstream side in the first conveyance direction by the pre-processing rollers **211A** and **212A** to the downstream side in the first conveyance direction with respect to the processing tray **220**, and discharge the sheet. Specifically, the upper discharge roller **230A** and the lower discharge roller **230B** discharge the sheets stapled by the staple unit **400** onto the stacking tray **300**. The upper discharge roller **230A** is movable to a nip position (contact position) where the sheet is nipped between the upper discharge roller **230A** and the lower discharge roller **230B** and a retracting position where the upper discharge roller **230A** is retracted above the nip position, and nips the sheet between the upper discharge roller **230A** and the lower discharge roller **230B** at the nip position. That is, the upper discharge roller **230A** functions as a nip member that nips the sheet between the upper discharge roller **230A** and the lower discharge roller **230B** at the nip position. Two upper discharge rollers **230A** are disposed apart from each other in the width direction of the sheet. Two lower discharge rollers **230B** are disposed apart from each other in the width direction of the sheet. In the present embodiment, the upper discharge rollers **230A** and the lower discharge rollers **230B** are disposed inside the pair of reversing paddles **240A** in the width direction.

(54) The upper discharge roller **230A** and the lower discharge roller **230B** nip the sheet or the sheet bundle at the nip position, and for example, the lower discharge roller **230B** rotates to convey the nipped sheet or sheet bundle. The upper discharge roller **230A** is a driven roller that rotates following the rotation of the lower discharge roller **230B**, but may be configured to drive. That is, in the present embodiment, the upper discharge roller **230A** is the driven rotary member, and the lower discharge roller **230B** is the driving rotary member. Further, the upper discharge roller **230A** functions as a nip member capable of nipping the sheet with the lower discharge roller **230B** at the nip position, but the nip member may be another rotary member such as a belt instead of the roller, or may be an abutting member that abuts on the sheet without rotating like a lever member. Further, the lower discharge roller **230B** may be a rotary member such as a belt in addition to the roller.

(55) The upper discharge roller **230A** is pivotable about the pivot shaft **2301** between the nip position and the retracting position. In other words, the upper discharge roller **230A** is movable up and down between the nip position and the retracting position. The upper discharge roller **230A** is provided at a distal end of the discharge arm **2302** serving as a supporting portion. The pivot shaft

2301 is provided coaxially with the swing fulcrum **2403** described above, and is disposed upstream in the first conveyance direction from the pre-processing nip portion **211a** that nips the sheet with the pre-processing rollers **211A** and **212A**, and vertically above the pre-processing nip portion **211a**. Then, the discharge arm **2302** extends from the pivot shaft **2301** to the downstream side in the first conveyance direction, and the upper discharge roller **230A** is provided at a distal end portion thereof. The pivot shaft **2301** may not be disposed coaxially with the swing fulcrum **2403**, but in the present embodiment, the pivot shafts of the upper discharge roller **230A** and the reversing paddle **240A** are coaxial.

(56) The pivot shaft **2301** is disposed on the upstream side in the first conveyance direction with respect to a discharge nip portion where the upper discharge roller **230A** nips the sheet with the lower discharge roller **230B** at the nip position. Further, the upper discharge roller **230A** is positioned vertically above the pre-processing nip portion **211a** that nips the sheet with the pre-processing rollers **211A** and **212A** in the retracting position, and the pivot shaft **2301** is positioned vertically above the center of the upper discharge roller **230A** in the retracting position.

(57) Since the positional relationship between the pivot shaft **2301** and the pre-processing nip portion **211a** is defined as described above, the upper discharge roller **230A** allows the sheet passing through the pre-processing nip portion **211a** to move toward the stacking tray **300** in the state of being in the retracting position. On the other hand, the upper discharge roller **230A** rotates counterclockwise in FIG. 2 about the pivot shaft **2301**, thereby moving downward from the retracting position toward the nip position. When the upper discharge roller **230A** moves to the nip position, the sheet can be nipped between the upper discharge roller **230A** and the lower discharge roller **230B**.

Alignment Unit

(58) The alignment unit **270A** serving as a shift unit moves in a shift direction (width direction) intersecting the first conveyance direction in a state of being in contact with an end edge along the first conveyance direction of the sheet conveyed to the downstream side in the first conveyance direction by the pre-processing rollers **211A** and **212A**, thereby moving the sheet in the shift direction. Such an alignment unit **270A** includes a pair of aligning plates **271A** disposed to face each other in the shift direction.

(59) The pair of aligning plates **271A** is disposed further downstream of the downstream end portion in the first conveyance direction of the conveyance path **210A**, and moves in the width direction to abut on the end edge in the width direction of the sheet, thereby performing the alignment of the sheet in the width direction. In the present embodiment, the aligning plates **271A** are disposed on both sides in the width direction of the sheet placed on the processing tray **220**, and are movable in the width direction, respectively. The pair of aligning plates **271A** extends from the upstream side to the downstream side in the first conveyance direction with respect to the upper discharge roller **230A** and the lower discharge roller **230B**. The configuration of the pair of aligning plates **271A** is the same. The pair of aligning plates **271A** moves in the shift direction by the driving of a front side (F side) aligning plate moving motor and a rear side (R side) aligning plate moving motor serving as driving units.

(60) The aligning plate **271A** is formed to have a large width in the vertical direction on the downstream side in the first conveyance direction. That is, the aligning plate **271A** includes a first plate portion **2701** on the downstream side in the first conveyance direction and a second plate portion **2702** formed to be continuous with the first plate portion **2701** on the upstream side in the first conveyance direction. The first plate portion **2701** has a larger area in the vertical direction than the second plate portion **2702** so as to be able to abut on the conveyed sheet even if the leading edge side of the sheet is curled upward or downward. On the other hand, the second plate portion **2702** is formed to have a height in the vertical direction lower than that of the first plate portion **2701** so as not to interfere with the trailing edge dropping member **250A** even when the trailing edge dropping member **250A** is located at the lower position. The upper end edge of the second

plate portion **2702** is inclined so as to be lower toward the upstream side in the first conveyance direction.

(61) Further, the first plate portion **2701** is formed so as to extend from the upstream side to the downstream side in the first conveyance direction with respect to the upper discharge roller **230A** and the lower discharge roller **230B**. Accordingly, even when a sheet is discharged by a first shift discharge process described below, at least the first plate portion **2701** can abut on the sheet. Also, the second plate portion **2702** is located on the processing tray **220** and is formed continuously with the first plate portion **2701** in the first conveyance direction. As a result, at least the second plate portion **2702** can abut on the sheet placed on the processing tray **220** by a second shift discharge process described below.

Stacking Tray

(62) As described above, the sheet discharged by the upper discharge roller **230A** and the lower discharge roller **230B** is stacked on the stacking tray **300** serving as the stacking portion. The stacking tray **300** is provided downstream of the processing tray **220** in the first conveyance direction so as to be vertically movable downward. The stacking tray **300** is inclined with respect to the horizontal plane such that the upstream side in the first conveyance direction is lower than the downstream side thereof. Such a stacking tray **300** is supported so as to be movable in the vertical direction along rails disposed in the vertical direction, for example, and moves up and down by the driving of a stacking tray elevating motor serving as an elevating unit.

(63) An upstream end of the stacking tray **300** in the first conveyance direction is provided with a rising surface **310a** serving as a supporting side regulating unit that regulates an upstream end (trailing edge) in a predetermined direction of the sheet or the sheet bundle stacked on the stacking tray **300**, and a trailing edge presser **310b** that presses the trailing edge of the sheet abutting on the rising surface **310a**. The trailing edge presser **310b** is inclined toward the downstream side in the first conveyance direction toward the upper side, and can press the trailing edge of the sheet even if the trailing edge of the sheet is curled upward. Further, a sheet pressing paddle **320A** is provided coaxially with the rotation shaft of the lower discharge roller **230B**.

(64) The stacking tray **300** is movable up and down between a first stacking position and a second stacking position below the first stacking position by a stacking tray elevating motor **MT20**. The second stacking position is a position at which the operation of the stacking tray **300** that has been lowered when the sheets are discharged to the stacking tray **300** is switched to the rising. At the time of sheet discharge, the sheet pressing paddle **320A** rotates as the stacking tray **300** moves up and down, and the sheet or the sheet bundle on the stacking tray **300** is pressed by the sheet pressing paddle **320A**.

Control of Each Mode

(65) Next, control of each mode of the present embodiment will be described. In the present embodiment, there are a straight discharge mode in which the sheets sent to the sheet processing apparatus **200A** are discharged to the stacking tray **300** as they are without being subjected to predetermined processing, a shift mode in which the sheets sent to the sheet processing apparatus **200A** are moved (shifted) in the width direction and discharged to the stacking tray **300**, and a staple mode in which the sheets sent to the sheet processing apparatus **200A** are stapled as predetermined processing and discharged to the stacking tray **300**. Each of these modes is selected by the user.

(66) Further, in the shift mode, there are a case where a shift operation is performed on a sheet (first sheet, small-sized sheet) of which length in the sheet conveyance direction (first conveyance direction) is a first length and a case where a shift operation is performed on a sheet (second sheet, large-sized sheet) of which length in the first conveyance direction is a second length longer than the first length. The small-sized sheet is, for example, a sheet of which length in the first conveyance direction is equal to or less than a predetermined length, and the large-sized sheet is, for example, a sheet of which length in the first conveyance direction is longer than the

predetermined length. The predetermined length is, for example, a so-called A4 vertical size in which an A4 size sheet is sent in the vertical direction (direction in which the longitudinal direction is the conveyance direction). Further, in the shift mode, it is possible to select and execute a productivity priority mode in which productivity is prioritized and an alignment priority mode in which alignment of sheets is prioritized.

(67) The productivity priority mode as a first shift discharge process is a mode in which the sheet conveyed to the downstream side in the first conveyance direction by the pre-processing rollers **211A** and **212A** is shifted in the shift direction by the alignment unit **270A** by driving the F-side aligning plate moving motor and the R-side aligning plate moving motor without being conveyed in a second conveyance direction by the reversing paddle **240A**, and is discharged to the stacking tray **300** by the upper discharge roller **230A** and the lower discharge roller **230B**.

(68) The alignment priority mode as a second shift discharge process is a mode in which the sheet conveyed to the downstream side in the first conveyance direction by the pre-processing rollers **211A** and **212A** is conveyed in the second conveyance direction by the reversing paddle **240A** on the processing tray **220**, a downstream end edge of the sheet in the second conveyance direction is abutted against (regulated) the trailing edge regulation member **290**, then the F-side aligning plate moving motor and the R-side aligning plate moving motor are driven without performing the predetermined process by the staple unit **400**, the sheet is shifted in the shift direction by the alignment unit **270A**, and the sheet is discharged to the stacking tray **300** by the upper discharge roller **230A** and the lower discharge roller **230B**.

Manual Binding

(69) A schematic configuration of an appearance of the sheet processing apparatus **200A** of the present embodiment configured as described above is as illustrated in FIG. **3**. In the sheet processing apparatus **200A** of the present embodiment, a manual insertion portion **204** into which a user can manually insert a sheet or a sheet bundle from the outside is provided on the front side of the apparatus in the width direction. The manual insertion portion **204** is a portion into which a corner portion of the sheet bundle is inserted in a case where a user manually binds the sheet bundle by stapling from outside the apparatus. When the user inserts the sheet bundle into the manual insertion portion **204** and presses an operation button **205**, the staple unit **400** moves to this position and performs staple processing. Note that a detection unit that detects that the sheet bundle has been inserted may be provided in the manual insertion portion **204**, and when the detection unit detects the sheet bundle, the staple unit **400** may be moved to perform the staple process. In this case, the operation button **205** may be omitted.

Sheet Binding Apparatus

(70) Next, the sheet binding apparatus **410** according to the present embodiment will be described with reference to FIGS. **4** to **19**. First, an overall configuration of the sheet binding apparatus **410** will be described with reference to FIGS. **4** to **9**. In FIGS. **4** and **5**, the right front side in the drawings is the front side (F side) of the apparatus, and the left back side is the rear side (R side) of the apparatus. In FIG. **7**, the right front side in the drawing is the rear side (R side) of the apparatus, and the left back side is the front side (F side) of the apparatus.

(71) As illustrated in FIG. **4**, the sheet binding apparatus **410** includes a base portion **420** and a stapler moving unit **450**. As illustrated in FIG. **5**, the base portion **420** includes a base **411**, a cam groove **430** serving as a guide portion, a drive unit **440**, and the like. The cam groove **430** and the drive unit **440** are fixed on the base **411**. An HP sensor **412** that detects the home position (HP) of the staple unit **400** and an abutment member **413** are also fixed on the base **411**.

(72) As illustrated in FIG. **6**, the stapler moving unit **450** includes a staple unit **400**, a stapler holding unit **460**, and the like. The stapler holding unit **460** includes a slide plate **461** serving as a moving portion, a rotation plate **462** serving as a rotation holding portion, and an engaging portion **465**. The engaging portion **465** includes a first roller **463** serving as a first protrusion and a second roller **464** serving as a second protrusion.

Base Portion

(73) In the base portion **420**, the cam groove **430** and the like are fixed on the base **411** as described above. As illustrated in FIG. 7, the cam groove **430** guides movement of the staple unit **400** in a first direction and a second direction opposite to the first direction. Note that FIG. 7 illustrates a relationship between the stapler holding unit **460** and the cam groove **430** by omitting the staple unit **400** in the stapler moving unit **450**.

(74) The first direction and the second direction, which are the moving directions of the staple unit **400**, are the above-described width direction (an arrow γ direction in FIGS. 3, 4, and 7), and the staple unit **400** is guided by the cam groove **430** to reciprocate between the F side and the R side in the width direction. The above-described HP sensor **412** is disposed in the vicinity of the F-side end of the cam groove **430**, and the abutment member **413** is disposed in the vicinity of the R-side end of the cam groove **430**, respectively. A detailed configuration of the cam groove **430** will be described below.

(75) As illustrated in FIGS. 4 and 5, the drive unit **440** serving as a driving unit reciprocates the staple unit **400** in the width direction along the cam groove, and includes a motor **441** serving as a drive source and a belt **442**. The belt **442** is stretched between a driving pulley (not illustrated) to which driving is transmitted from an output shaft of the motor **441** and a driven pulley **443**. In the present embodiment, the motor **441** and the driving pulley are arranged on the R side in the width direction, the driven pulley is arranged on the F side, and the belt **442** is arranged over the width direction. As will be described below, a stapler moving unit **450** is fixed to the belt **442**, and when the belt **442** rotates, the stapler moving unit **450** reciprocates in the width direction along the cam groove **430**.

(76) Note that the driving unit for moving the staple unit **400** may have a configuration other than the above-described belt configuration. For example, a motor and a pinion gear to which drive is transmitted from an output shaft of the motor are provided on the staple unit **400** side, and a rack gear is provided along the width direction on the base **411** side. Then, the pinion gear and the rack gear are engaged with each other. By driving the motor on the staple unit **400** side, the staple unit **400** moves along the rack gear by the engagement between the pinion gear and the rack gear. As described above, the driving unit may be configured to cause the staple unit **400** to self-propel.

Stapler Moving Unit

(77) As illustrated in FIG. 6, the stapler moving unit **450** includes the staple unit **400**, a cable holder **451**, a cover **452**, a belt holder **453**, an inclination regulation member **454**, a contact portion **455**, the stapler holding unit **460**, and the like. The staple unit **400** can perform a binding process on the sheet bundle. The cable holder **451** is a holder that holds a cable connected to an apparatus body of the sheet processing apparatus **200A**. The cover **452** covers a connection portion between the staple unit **400** and the cable disposed via the cable holder **451**. The staple unit **400** is driven by power supplied from the apparatus body via the cable.

(78) The belt holder **453** is connected to the belt **442** of the drive unit **440** described above. The inclination regulation member **454** regulates an inclination angle of the staple unit **400** as described below. The contact portion **455** is a member that abuts on an abutment member **413** provided in the base portion **420** and serves as a trigger for inclining the staple unit **400** when the staple unit **400** performs oblique binding described below on the R side.

(79) As illustrated in FIGS. 6 and 8A, the stapler holding unit **460** is obtained by integrally assembling the slide plate **461**, the rotation plate **462**, the first roller **463**, and the second roller **464**, and moves along the cam groove **430** integrally with the staple unit **400**.

(80) The slide plate **461** moves along the cam groove **430** together with the staple unit **400**. For this purpose, the belt holder **453** is fixed to the slide plate **461**, and the slide plate **461** moves along the cam groove **430** by the rotation of the belt **442**. Further, the slide plate **461** has a guide hole **461a** as a penetrating portion through which the first roller **463** and the second roller **464** penetrate and which allows the first roller **463** and the second roller **464** to move with the rotation of the staple

unit **400**.

(81) The rotation plate **462** rotatably holds the staple unit **400** with respect to the slide plate **461**, and the staple unit **400** is integrally fixed to the upper surface thereof. The rotation plate **462** is disposed on the upper surface of the slide plate **461** so as to be rotatable with respect to the slide plate **461**. Further, the contact portion **455** is fixed to the rotation plate **462**, and when the stapler moving unit **450** moves to the R side and the contact portion **455** abuts the abutment member **413**, the rotation plate **462** and the staple unit **400** rotate with respect to the slide plate **461**. Further, the first roller **463** and the second roller **464** are fixed to the rotation plate **462** at intervals.

(82) The first roller **463** and the second roller **464** are provided to be movable in the width direction together with the staple unit **400** and to be rotatable together with the staple unit **400**, and are engaged with the cam groove **430**. An outer peripheral surface of at least a portion of the first roller **463** and the second roller **464** engaged with the cam groove **430** is formed in a cylindrical shape. The first roller **463** and the second roller **464** are rotatably fixed to a surface of the rotation plate **462** on a side opposite to a side on which the staple unit **400** is fixed, that is, a lower surface. The first roller **463** and the second roller **464** may not rotate.

(83) In addition, the first roller **463** and the second roller **464** are provided so as to protrude downward from the rotation plate **462**, and protrusion amounts of the first roller **463** and the second roller **464** are different from each other. That is, the first roller **463** serving as the first protrusion has a larger protrusion amount from the rotation plate **462** than the second roller **464** serving as the second protrusion. The first roller **463** and the second roller **464** are arranged at a predetermined interval from each other, pass through the guide hole **461a** formed in the slide plate **461** located below the rotation plate **462**, and protrude below the slide plate **461**.

(84) The guide hole **461a** of the slide plate **461** is an opening curved so as to guide the first roller **463** and the second roller **464** in the rotation direction of the staple unit **400**, and at least an inner peripheral edge portion of the guide hole **461a** is formed in a substantially semicircular shape. In the present embodiment, the inner peripheral edge portion of the guide hole **461a** is a semicircle having a diameter slightly larger than the distance between the outer peripheral surface of the first roller **463** and the outer peripheral surface of the second roller **464**. As a result, the first roller **463** and the second roller **464** are movable along the inner peripheral edge portion of the guide hole **461a**. The guide hole **461a** has a width larger than the diameters of the first roller **463** and the second roller **464**, and is formed to smoothly guide the first roller **463** and the second roller **464**. The outer peripheral edge of the guide hole **461a** may be formed in a substantially semicircular shape, and the first roller **463** and the second roller **464** may be movable along the outer peripheral edge of the guide hole **461a**.

(85) Further, a straight line connecting both ends of the semicircle of the guide hole **461a** is substantially parallel to the width direction which is a moving direction of the staple unit **400**. Therefore, in a state where the staple unit **400** is not inclined with respect to the width direction, the first roller **463** and the second roller **464** are positioned so as to be arranged substantially parallel to the width direction, and are positioned at the both ends of the semicircle of the guide hole **461a**. Then, the first roller **463** and the second roller **464** sandwich an arc-shaped plate portion **461b** on the inner side of the guide hole **461a** at this position.

(86) When the slide plate **461** is driven by the drive unit **440** to move in the width direction, the first roller **463** and the second roller **464** are engaged with the cam groove **430**, and the slide plate **461** moves along the cam groove **430**. At this time, the arc-shaped plate portion **461b** of the slide plate **461** is sandwiched between the first roller **463** and the second roller **464**, so that the slide plate **461** and the rotation plate **462** can be integrally and stably moved.

(87) In the above example, the rotation plate **462** is disposed between the staple unit **400** and the slide plate **461**, and the first roller **463** and the second roller **464** provided on the rotation plate **462** are disposed so as to penetrate the slide plate **461**. However, as long as the staple unit **400** is rotatable with respect to the slide plate **461**, the positions of the slide plate **461** and the rotation

plate **462** may be interchanged. For example, the staple unit **400** and the rotation plate **462** may be disposed so as to sandwich the slide plate **461**, and the staple unit **400** and the rotation plate **462** may be fixed via an arm or the like. In short, the stapler holding unit **460** only needs to be configured to be able to move the staple unit **400** along the cam groove **430** and to be able to rotate the staple unit **400** at a position where oblique binding is performed on the F side and the R side to be described below.

(88) The guide hole **461a** is not limited to the semicircular curved configuration as described above. For example, on a straight line connecting the center of the first roller **463** and the center of the second roller **464**, a round hole having a diameter slightly larger than a distance between positions where the outer peripheral surface of the first roller **463** and the outer peripheral surface of the second roller **464** are farthest from each other may be used. In short, the guide hole **461a** may be formed so as to guide the first roller **463** and the second roller **464** so that the first roller **463** and the second roller **464** penetrate and may rotate together with the staple unit **400**.

(89) As illustrated in FIGS. **8B** and **9**, the stapler moving unit **450** is configured by assembling the staple unit **400** to the stapler holding unit **460**. As illustrated in FIG. **8B**, the staple unit **400** is disposed to be inclined in accordance with the inclination of the processing tray **220** described above, and the insertion portion **401** into which the sheet bundle, on which the binding process is performed, is inserted is directed obliquely upward. The inclination regulation member **454** described above is disposed on the back surface of the staple unit **400** on the side opposite to the insertion portion **401**, and the inclination of the staple unit **400** is regulated by the inclination regulation member **454** abutting on the base **411**. As a result, it is possible to prevent the staple unit **400** from being excessively inclined when the staple unit **400** moves in the width direction. The position of the inclination regulation member **454** in the vertical direction can be adjusted.

Cam Groove

(90) Next, the cam groove **430** will be described with reference to FIGS. **10** to **12**. Here, the first direction and the second direction are directions along the above-described width direction, and the first direction is indicated by an arrow $\gamma 1$ and the second direction is indicated by an arrow $\gamma 2$. In the present embodiment, the first direction is a direction toward the F side along the width direction, and the second direction is a direction toward the R side along the width direction. The relationship between the first direction and the second direction may be reversed depending on the configuration of the device. In addition, a direction of an arrow $\beta 1$ illustrated in FIGS. **10** to **12** is the above-described first conveyance direction, and a direction of an arrow $\beta 2$ is the above-described second conveyance direction. The first conveyance direction $\beta 1$ is a direction in which the sheet is conveyed toward the processing tray **220** by the above-described pre-processing rollers **211A** and **212A**, and the second conveyance direction $\beta 2$ is a direction in which the sheet on the processing tray **220** is conveyed toward the trailing edge regulation member **290** by the above-described reversing paddle **240A**.

(91) The cam groove **430** includes a first groove **431**, a second groove **432**, a third groove **433**, a fourth groove **434**, a fifth groove **435**, a sixth groove **436**, and a seventh groove **437**. In the present embodiment, the second groove **432**, the third groove **433**, the sixth groove **436**, and the seventh groove **437** are disposed on the downstream side in the first direction $\gamma 1$ of the first groove **431**, that is, on the F side. On the other hand, the fourth groove **434** and the fifth groove **435** are disposed on the downstream side in the second direction $\gamma 2$ of the first groove **431**, that is, on the R side. Each groove has a width slightly larger than the diameters of the first roller **463** and the second roller **464**, and is formed such that the first roller **463** and the second roller **464** may engage and are guided without rattling. In the present embodiment, the outer diameters of the first roller **463** and the second roller **464** are the same, and the widths of the grooves are also the same. Hereinafter, each groove will be described in detail.

(92) The first groove **431** has a pair of wall portions (first wall portions) **431a** and a bottom portion **431b** and is formed along the first direction $\gamma 1$. The pair of wall portions **431a** is arranged to face

each other so that the first roller **463** and the second roller **464** can enter therebetween. In other words, the pair of wall portions **431a** is disposed so as to guide the first roller **463** and the second roller **464** so as to be movable along the first direction $\gamma 1$ in a state where the first roller **463** and the second roller **464** are located therebetween. The bottom portion **431b** is a bottom portion of the groove between the pair of wall portions **431a**. The first groove **431** is opened on the side opposite to the bottom portion **431b**, and the first roller **463** and the second roller **464** are engaged with the pair of wall portions **431a** through the opening. Note that the bottom portion **431b** can be omitted. That is, the first groove **431** may be a through hole having a pair of wall portions **431a**.

(93) The second groove **432** has a pair of wall portions (second wall portions) **432a** and a bottom portion **432b**, and is formed along a direction inclined with respect to the first direction $\gamma 1$ from a downstream end of the first groove **431** in the first direction $\gamma 1$. That is, the second groove **432** is inclined with respect to the width direction, and an inclination direction is a direction toward the downstream side in the first conveyance direction $\beta 1$ as it goes toward the downstream side in the first direction $\gamma 1$. The pair of wall portions **432a** is arranged to face each other so that the first roller **463** can enter therebetween. In other words, the pair of wall portions **432a** is disposed so as to guide the first roller **463** movably along the inclination direction (a direction toward the downstream side in the first conveyance direction $\beta 1$ as it goes toward the downstream side in the first direction $\gamma 1$) from the downstream end in the first direction $\gamma 1$ of the first groove **431** in a state where the first roller **463** is disposed between the wall portions. The bottom portion **432b** is a bottom portion of the groove between the pair of wall portions **432a**. The second groove **432** is opened on the side opposite to the bottom portion **432b**, and the first roller **463** is engaged with the pair of wall portions **432a** through the opening. Note that the bottom portion **432b** can be omitted. That is, the second groove **432** may be a through hole having the pair of wall portions **432a**.

(94) The third groove **433** has a pair of wall portions (third wall portions) **433a** and a bottom portion **433b**, and is formed along the first direction $\gamma 1$ from the downstream end of the first groove **431** in the first direction $\gamma 1$. That is, the third groove **433** is formed in a similar manner as the first groove **431**, on the downstream side of the first groove **431** in the first direction $\gamma 1$, extending downstream side from the first groove **431**. The pair of wall portions **433a** is arranged to face each other so that the second roller **464** can enter therebetween. In other words, the pair of wall portions **433a** is disposed so as to guide the second roller **464** so as to be movable along the first direction $\gamma 1$ from the downstream end of the first groove **431** in the first direction $\gamma 1$ in a state where the second roller **464** is disposed between the wall portions. The bottom portion **433b** is a bottom portion of the groove between the pair of wall portions **433a**. The third groove **433** is opened on the side opposite to the bottom portion **433b**, and the second roller **464** is engaged with the pair of wall portions **433a** through the opening. Note that the bottom portion **433b** can be omitted. That is, the third groove **433** may be a through hole having a pair of wall portions **433a**.

(95) The fourth groove **434** has a pair of wall portions (fourth wall portions) **434a** and a bottom portion **434b**, and is formed along a direction inclined with respect to the second direction $\gamma 2$ from a downstream end of the first groove **431** in the second direction $\gamma 2$. That is, the fourth groove **434** is inclined with respect to the width direction, and an inclination direction is a direction toward the downstream side in the first conveyance direction $\beta 1$ as it goes toward the downstream side in the second direction $\gamma 2$. The pair of wall portions **434a** is arranged to face each other so that the second roller **464** can enter therebetween. In other words, the pair of wall portions **434a** is disposed so as to guide the second roller **464** so as to be movable along the inclination direction (a direction toward the downstream side in the first conveyance direction $\beta 1$ as it goes toward the downstream side in the second direction $\gamma 2$) from the downstream end of the first groove **431** in the second direction $\gamma 2$ in a state where the second roller **464** is disposed between the wall portions. The bottom portion **434b** is a bottom portion of the groove between the pair of wall portions **434a**. The fourth groove **434** is opened on the side opposite to the bottom portion **434b**, and the second roller **464** is engaged with the pair of wall portions **434a** through the opening. Note that the bottom

portion **434b** can be omitted. That is, the fourth groove **434** may be a through hole having a pair of wall portions **434a**.

(96) The fifth groove **435** has a pair of wall portions (fifth wall portions) **435a** and a bottom portion **435b**, and is formed along the second direction γ_2 from the downstream end of the first groove **431** in the second direction γ_2 . That is, the fifth groove **435** is formed in a similar manner as the first groove **431**, on the downstream side of the first groove **431** in the second direction γ_2 , extending downstream side from the first groove **431**. The pair of wall portions **435a** is arranged to face each other so that the first roller **463** can enter therebetween. In other words, the pair of wall portions **435a** is disposed so as to guide the first roller **463** movably along the second direction γ_2 from the downstream end in the second direction γ_2 of the first groove **431** in a state where the first roller **463** is disposed between the wall portions. The bottom portion **435b** is a bottom portion of the groove between the pair of wall portions **435a**. The fifth groove **435** is opened on the side opposite to the bottom portion **435b**, and the first roller **463** is engaged with the pair of wall portions **435a** through the opening. Note that the bottom portion **435b** can be omitted. That is, the fifth groove **435** may be a through hole having a pair of wall portions **435a**.

(97) The sixth groove **436** has a pair of wall portions (sixth wall portions) **436a** and a bottom portion **436b**, and is formed on the downstream side of the second groove **432** in the first direction γ_1 along a direction inclined in a direction opposite to the second groove **432** with respect to the first direction γ_1 . That is, the sixth groove **436** is inclined with respect to the width direction, and the inclination direction is a direction toward the upstream side in the first conveyance direction β_1 , that is, the downstream side in the second conveyance direction β_2 as it goes toward the downstream side in the first direction γ_1 . Between the second groove **432** and the sixth groove **436**, a switching groove **438** for switching a rotation direction of the first roller **463** with respect to the second roller **464** is provided as described below. The pair of wall portions **436a** is arranged to face each other so that the first roller **463** can enter therebetween. In other words, the pair of wall portions **436a** is disposed so as to guide the first roller **463** so as to be movable along the inclination direction (a direction inclined in the direction opposite to the second groove **432** with respect to the first direction γ_1) from the downstream end in the first direction γ_1 of the second groove **432** in a state where the first roller **463** is disposed between the wall portions. The bottom portion **436b** is a bottom portion of the groove between the pair of wall portions **436a**. The sixth groove **436** is opened on the side opposite to the bottom portion **436b**, and the first roller **463** is engaged with the pair of wall portions **436a** through the opening. Note that the bottom portion **436b** can be omitted. That is, the sixth groove **436** may be a through hole having a pair of wall portions **436a**.

(98) The seventh groove **437** has a pair of wall portions (seventh wall portions) **437a** and a bottom portion **437b**, and is formed along the first direction γ_1 from the downstream end in the first direction γ_1 of the sixth groove **436**. The seventh groove **437** is located at the same position as the first groove **431** and the third groove **433** in the first conveyance direction β_1 , and when the first roller **463** enters the seventh groove **437** as described below, the direction of the stapler moving unit **450** is the same as the case where the first roller **463** and the second roller **464** are located in the first groove **431**. The pair of wall portions **437a** is arranged to face each other so that the first roller **463** can enter therebetween. In other words, the pair of wall portions **437a** is disposed so as to guide the first roller **463** movably along the first direction γ_1 from the downstream end in the first direction γ_1 of the sixth groove **436** in a state where the first roller **463** is disposed between the wall portions. The bottom portion **437b** is a bottom portion of the groove between the pair of wall portions **437a**. The seventh groove **437** is opened on the side opposite to the bottom portion **437b**, and the first roller **463** is engaged with the pair of wall portions **437a** through the opening. Note that the bottom portion **437b** can be omitted. That is, the seventh groove **437** may be a through hole having a pair of wall portions **437a**.

Relationship Between Each Groove and First Roller and Second Roller

(99) Next, a relationship between the grooves and the first roller **463** and the second roller **464** will be described with reference to FIGS. **10** to **15B**. In the following description, the “depth of the groove” in each groove is the same as the “height of the wall portion” in each groove. In the present embodiment, among the grooves described above, the third groove **433** is formed such that the depth of the groove is shallower (the height of the wall portion is lower) than the other grooves. As described above, the first roller **463** and the second roller **464** have different protrusion amounts from the rotation plate **462**. As a result, engagement amounts of the first roller **463** and the second roller **464** with respect to the groove are made different. Here, the “engagement amount” is an amount by which the first roller **463** and the second roller **464** enter the pair of wall portions in the height direction of the wall portion (the length direction of the first roller **463** and the second roller **464**), in other words, a length of a portion in which the first roller **463** and the second roller **464** abut on the pair of wall portions in the height direction of the wall portion. The second roller **464** is disposed upstream side of the first roller **463** in the first direction $\gamma 1$, that is, on the R side.

(100) Note that the first roller **463** and the second roller **464** have different lengths so as to have different protrusion amounts from the rotation plate **462**, but may have the same length as long as the engagement amount with the groove is different. For example, by changing the attachment position in the height direction (a depth direction of the groove) with respect to the rotation plate **462**, the engagement amount of the first roller **463** and the second roller **464** with respect to the groove can be changed even if the lengths are the same.

(101) Here, the stapler moving unit **450** moves in the first direction $\gamma 1$ and the second direction $\gamma 2$, and each of the first roller **463** and the second roller **464** are positioned in any one of the grooves described above, whereby the posture of the staple unit **400** can be changed. Specifically, the staple unit **400** can be changed to a first posture and a second posture inclined with respect to the first posture. In the present embodiment, the drive unit **440** that moves the staple unit **400**, the stapler holding unit **460** that holds the staple unit **400**, and the cam groove **430** constitute a movable turning unit **470** (FIG. **4**) that moves the staple unit **400** in the width direction and further turns the staple unit **400** between the first posture and the second posture inclined with respect to the first posture.

(102) The first posture is a posture in which the staple unit **400** performs the binding process in the direction along the width direction with respect to a downstream edge portion of the sheet in the second conveyance direction $\beta 2$, that is, a side stitch binding posture. The second posture is a posture in which the staple unit **400** performs the binding process in a direction inclined with respect to the width direction with respect to the corner portion on a first end side or a second end side (the F side or the R side in the present embodiment) in the width direction of the downstream edge portion of the sheet in the second conveyance direction $\beta 2$, that is, a posture in which the staple unit performs the oblique binding. Note that the inclination direction with respect to the width direction is opposite between the second posture on the F side and the second posture on the R side.

(103) The sheet binding apparatus **410** according to the present embodiment can execute a first binding process in which the staple unit **400** performs side stitching to a downstream edge portion (trailing edge portion) of the sheet in the second conveyance direction $\beta 2$ in the first posture, a second binding process in which the staple unit **400** performs oblique binding to the first end side (F side) of the downstream edge portion (trailing edge portion) of the sheet in the second conveyance direction $\beta 2$ in the second posture, and a third binding process in which the staple unit **400** performs oblique binding to the second end side (R side) of the downstream edge portion (trailing edge portion) of the sheet in the second conveyance direction $\beta 2$ in the second posture.

(104) FIGS. **13A** and **13B** illustrate a state in which the stapler moving unit **450** is at the home position (HP). At the home position, the staple unit **400** takes the same posture as the first posture, but does not perform the binding process on the sheets. FIGS. **14A** and **14B** illustrate the second posture on the F side, and FIGS. **15A** and **15B** illustrate the second posture on the R side,

respectively.

First Groove and F-Side Groove

(105) First, a relationship between the first groove **431**, the second groove **432**, the third groove **433**, the sixth groove **436**, and the seventh groove **437** on the downstream side in the first direction γ_1 of the first groove **431**, that is, on the F side, and the first roller **463** and the second roller **464** will be described. The first roller **463** can be engaged with the first groove **431** and the second groove **432** by a first engagement amount. On the other hand, the second roller **464** can be engaged with the first groove **431** and the third groove **433** by a second engagement amount smaller than the first engagement amount.

(106) The third groove **433** has a stepped surface **439** serving as a restricting portion that restricts entry of the first roller **463** from the first groove **431** and permits entry of the second roller **464** from the first groove **431**. That is, the first groove **431** and the second groove **432** are formed such that the depth of the groove is deeper than the first engagement amount. That is, the heights of the first wall portion **431a** and the second wall portion **432a** are higher than the first engagement amount. On the other hand, the third groove **433** is formed such that the depth of the groove is shallower than the first engagement amount and deeper than the second engagement amount. That is, the height of the third wall portion **433a** is lower than the first engagement amount and higher than the second engagement amount. The stepped surface **439** between the third groove **433** and the first groove **431** restricts the first roller **463** from entering the third groove **433** (between the pair of third wall portions **433a**) from the first groove **431** (between the pair of first wall portions **431a**), and allows the second roller **464** to enter the third groove **433** from the first groove **431**.

(107) Therefore, when the stapler moving unit **450** moves to the downstream side in the first direction γ_1 toward the third groove **433** along the first groove **431**, the first roller **463** on the downstream side in the first direction γ_1 with respect to the second roller **464** abuts on the stepped surface **439**. The stepped surface **439** is formed in parallel with the inclination direction of the second groove **432**, and is on the same plane as the inner wall surface of the wall portion **433a** on the upstream side in the first conveyance direction β_1 , that is, on the third groove **433** side, of the pair of wall portions **432a** of the second groove **432**. Therefore, when the stapler moving unit **450** further attempts to move downstream side in the first direction γ_1 in a state of being in contact with the stepped surface **439**, the first roller **463** is guided to the second groove **432** along the inclination of the stepped surface **439**.

(108) On the other hand, with the movement of the stapler moving unit **450** to the downstream side in the first direction γ_1 , the second roller **464** located upstream side of the first roller **463** in the first direction γ_1 reaches the position of the stepped surface **439** after the first roller **463** is guided to the second groove **432**. The engagement amount of the second roller **464** with the groove is smaller than the amount of engagement of the first roller **463** with the groove, and the third groove **433** is formed deeper than the engagement of the second roller **464** with the groove. Therefore, when the stapler moving unit **450** moves downstream side in the first direction γ_1 , the second roller **464** is engaged with the third groove **433** without being in contact with the stepped surface **439**.

(109) With such an operation, the first roller **463** is engaged with the second groove **432**, the second roller **464** is engaged with the third groove **433**, and the rotation plate **462** to which the first roller **463** and the second roller **464** are fixed rotates with respect to the slide plate **461**. At this time, the first roller **463** rotates about the second roller **464** along the guide hole **461a** formed in the slide plate **461**, so that the engagement of the first roller **463** with the second groove **432** and rotation of the rotation plate **462** become possible.

(110) Then, when the stapler moving unit **450** further moves to the downstream side in the first direction γ_1 , the first roller **463** reaches the switching groove **438** as illustrated in FIG. 14B. The switching groove **438** has a pair of wall portions and a bottom portion similarly to each groove described above. The same applies to the point that the bottom portion may be omitted. Such a switching groove **438** can be engaged with the first roller **463**, and has the same depth as the

second groove **432** in the present embodiment. Switching groove **438** is formed substantially parallel to the first groove **431**. Therefore, when the first roller **463** is positioned in the switching groove **438**, the position of the first roller **463** with respect to the second roller **464** is stabilized in the first conveyance direction $\beta 1$.

(111) That is, in a state where the first roller **463** enters the second groove **432**, the positional relationship with the second roller **464** changes depending on the position of the first roller **463** on the second groove **432**, and the angle of the staple unit **400** held by the rotation plate **462** also changes. On the other hand, when the first roller **463** is engaged with the switching groove **438**, the angle of the staple unit **400** is stabilized regardless of the position of the first roller **463** on the switching groove **438**. Then, at this position, the staple unit **400** takes the second posture as illustrated in FIG. **14A** for performing oblique binding on the F side as described above. As described above, in the present embodiment, the switching groove **438** functions as a positioning groove of the first roller **463** for causing the staple unit **400** to take the second posture on the F side. Note that the staple unit **400** may take the second posture in a state where the first roller **463** is positioned in the second groove **432**.

(112) The restricting portion that restricts the entry of the first roller **463** from the first groove **431** and permits the entry of the second roller **464** from the first groove **431** is not limited to the stepped surface **439** described above. For example, the restricting portion may be a horizontal bar provided at an upstream end of the third groove **433** in the first direction $\gamma 1$ at a position shallower than the first engagement amount and deeper than the second engagement amount. In this case, the third groove may have the same depth as the first groove.

(113) Next, a relationship between the sixth groove **436** and the seventh groove **437** formed continuously with the switching groove **438** on the downstream side in the first direction $\gamma 1$ of the switching groove **438** and the first roller **463** and the second roller **464** will be described. The sixth groove **436** and the seventh groove **437** have a depth with which the first roller **463** can be engaged, and in the present embodiment, have the same depth as the second groove **432**.

(114) As described above, when the first roller **463** is engaged with the second groove **432** and the stapler moving unit **450** moves to the downstream side in the first direction $\gamma 1$, the first roller **463** passes through the switching groove **438** and is engaged with the sixth groove **436**. At this time, the first roller **463** rotates about the second roller **464** along the guide hole **461a** formed in the slide plate **461**. The rotation direction at this time is opposite to the rotation direction when the first roller **463** is engaged with the second groove **432** from the first groove **431**. As a result, the rotation direction of the first roller **463** with respect to the second roller **464** is switched by the switching groove **438**, and the engagement with the sixth groove **436** and the rotation of the rotation plate **462** become possible.

(115) Next, when the stapler moving unit **450** further moves to the downstream side in the first direction $\gamma 1$, the first roller **463** is engaged with the seventh groove **437** as illustrated in FIG. **13B**. As described above, the seventh groove **437** is formed along the first direction $\gamma 1$, and is located at the same position as the first groove **431** and the third groove **433** with respect to the first conveyance direction $\beta 1$. Therefore, when the first roller **463** is engaged with the seventh groove **437**, the first roller **463** rotates about the second roller **464** along the guide hole **461a** formed in the slide plate **461**, and the rotation plate **462** and the staple unit **400** held by the rotation plate take a posture as illustrated in FIG. **13A**. This posture is the same posture as when the first roller **463** and the second roller **464** are in the first groove **431**. In the present embodiment, the case where the first roller **463** is positioned in the seventh groove **437** is set as the home position (HP) of the stapler moving unit **450**.

(116) In the present embodiment, the above-described manual binding operation can be performed at the home position, that is, the position where the first roller **463** is engaged with the seventh groove **437**. That is, when the stapler moving unit **450** is located at the home position, a portion of the staple unit **400** that performs the binding process is located in the manual insertion portion **204**

(FIG. 3). Therefore, when the user inserts the sheet bundle into the manual insertion portion 204 in this state, the sheet bundle is engaged with the portion where the binding process is performed, and the binding process can be performed.

R-Side Groove

(117) Next, a relationship between the fourth groove 434 and the fifth groove 435 on the downstream side in the second direction $\gamma 2$ of the first groove 431, that is, on the R side, and the first roller 463 and the second roller 464 will be described. The second roller 464 can be engaged with the fourth groove 434, and the first roller 463 can be engaged with the fifth groove 435. In the present embodiment, the fourth groove 434 has the same depth as the third groove 433, and the fifth groove 435 has the same depth as the first groove 431. The fourth groove 434 may have the same depth as the fifth groove 435.

(118) As described above, the abutment member 413 is disposed in the vicinity of the R-side end of the cam groove 430. As illustrated in FIGS. 11 and 12, the abutment member 413 serving as the abutted portion is disposed outside the first groove 431 to the seventh groove 437 (outside the pair of first wall portions 431a to the pair of seventh wall portions 437a). In the present embodiment, the abutment member 413 is disposed at the downstream end portion of the first groove 431 in the second direction $\gamma 2$ and is disposed on the downstream side of the fourth groove 434 in the first conveyance direction $\beta 1$. On the other hand, the rotation plate 462 is provided with the contact portion 455.

(119) When the stapler moving unit 450 moves to the downstream side in the second direction $\gamma 2$ along the first groove 431 and approaches the vicinity of the downstream end portion in the second direction $\gamma 2$ of the first groove 431, the contact portion 455 abuts against the abutment member 413. When the stapler moving unit 450 further moves to the downstream side in the second direction $\gamma 2$, the contact portion 455 and the abutment member 413 abut on each other, so that the rotation plate 462 rotates. At this time, the second roller 464 rotates about the first roller 463 along the guide hole 461a formed in the slide plate 461. As a result, the second roller 464 is engaged with the fourth groove 434 formed along the direction inclined with respect to the second direction $\gamma 2$ from the downstream end of the first groove 431 in the second direction $\gamma 2$. As a result, the staple unit 400 held by the rotation plate 462 rotates in the direction opposite to the rotation direction when the first roller 463 is engaged with the second groove 432.

(120) That is, when the second roller 464 is at a position where the second roller 464 can be engaged with the fourth groove 434 (between the pair of fourth wall portions 434a) from the first groove 431 (between the pair of first wall portions 431a), the contact portion 455 provided on the rotation plate 462 abuts on the abutment member 413. Then, as the staple unit 400 moves from this position in the second direction, the staple unit 400 turns, and the second roller 464 is engaged with the fourth groove 434.

(121) On the downstream side in the second direction $\gamma 2$ of the fourth groove 434, a positioning groove 434c is provided so as to be continuous with the fourth groove 434. The positioning groove 434c has a pair of wall portions and a bottom portion similarly to each groove described above. The same applies to the point that the bottom portion may be omitted. Such a positioning groove 434c has the same depth as the fourth groove 434 and is formed in parallel with the first groove 431. On the downstream side of the first groove 431 in the second direction $\gamma 2$, the fifth groove 435 is formed along the second direction $\gamma 2$ from the downstream end in the second direction $\gamma 2$ of the first groove 431.

(122) As described above, when the second roller 464 is engaged with the fourth groove 434 and the stapler moving unit 450 further moves to the downstream side in the second direction $\gamma 2$, the first roller 463 located at the upstream side in the second direction $\gamma 2$ with respect to the second roller 464 moves in the first groove 431 as it is. Then, as illustrated in FIG. 15B, the second roller 464 is engaged with the positioning groove 434c, and the first roller 463 is engaged with the fifth groove 435. Then, at this position, the staple unit 400 takes the second posture as illustrated in FIG.

15A for performing oblique binding on the R side as described above.

(123) Similarly to the above-described switching groove **438**, the positioning groove **434c** stabilizes the posture of the staple unit **400**. However, the staple unit **400** may take the second posture in a state where the second roller **464** is positioned in the fourth groove **434**, and in this case, the positioning groove **434c** may be omitted. Further, the fifth groove **435** is formed by extending the first groove **431** in order to move the second roller **464** to the positioning groove **434c**, the fifth groove **435** may be omitted as long as the staple unit **400** can be brought into the second posture without moving the first roller **463** to the fifth groove **435**.

Moving Position and Posture of Staple Unit

(124) Next, the position of the staple unit **400** in the cam groove **430** and the posture at that time will be described with reference to FIGS. **16A** to **19C**. FIGS. **16A** to **16E** sequentially illustrate a state in which the stapler moving unit **450** moves from the home position to the first groove **431**. FIGS. **17A** to **17C** sequentially illustrate a state in which the stapler moving unit **450** moves from the first groove **431** to the oblique binding position on the F side. FIGS. **18A** and **18B** illustrate a state in which the stapler moving unit **450** is located at different side stitch binding positions on the first groove **431**. FIGS. **19A** to **19C** sequentially illustrate a state in which the stapler moving unit **450** moves from the first groove **431** to the oblique binding position on the R side.

Movement from Home Position to First Groove **431**

(125) FIG. **16A** illustrates a state in which the stapler moving unit **450** is in a home position. In this state, as described above, the first roller **463** is located in the seventh groove **437**, and the second roller **464** is located in the third groove **433**. When the stapler moving unit **450** moves from this position to the downstream side in the second direction γ_2 , as illustrated in FIG. **16B**, the first roller **463** is engaged with the sixth groove **436**, and the second roller **464** moves along the third groove **433**. At this time, the first roller **463** rotates in the clockwise direction in the drawing around the second roller **464**, whereby the staple unit **400** is inclined.

(126) When the stapler moving unit **450** further moves to the downstream side in the second direction γ_2 , the first roller **463** is engaged with the switching groove **438** and enters the state of FIG. **16C**. The posture of the staple unit **400** in this state is the above-described second posture. Next, when the stapler moving unit **450** further moves to the downstream side in the second direction γ_2 , the first roller **463** is engaged with the second groove **432** as illustrated in FIG. **16D**. Further, when the stapler moving unit **450** further moves to the downstream side in the second direction γ_2 , the first roller **463** is engaged with the first groove **431** as illustrated in FIG. **16E**. In this state, the first roller **463** and the second roller **464** are positioned in the first groove **431**, and the staple unit **400** takes the first posture. An operation of moving from this position to the home position is reversed to that described above.

Movement from First Groove to F Side Oblique Binding Position

(127) FIG. **17A** illustrates a state in which the first roller **463** and the second roller **464** are located in the first groove **431** and the first roller **463** is located near the downstream end portion of the first groove **431** in the first direction γ_1 . When the stapler moving unit **450** moves from this position to the downstream side in the first direction γ_1 , the first roller **463** is guided by the stepped surface **439**, as illustrated in FIG. **17B**, the first roller **463** is engaged with the second groove **432**, and the second roller **464** starts to be engaged with the third groove **433**. At this time, the first roller **463** rotates in the clockwise direction in the drawing around the second roller **464**, whereby the staple unit **400** is inclined.

(128) Next, when the stapler moving unit **450** further moves to the downstream side in the first direction γ_1 , the first roller **463** is engaged with the switching groove **438**, and the second roller **464** moves on the third groove **433**. In this state, the staple unit **400** takes the above-described second posture on the F side. Then, at this position, it is possible to perform oblique binding at the corner portion on the F side of the downstream edge portion (trailing edge portion) of the sheet bundle in the second conveyance direction β_2 .

Side Stitch Binding Position

(129) FIG. 18A illustrates a position where side stitch binding is performed on the F side of the downstream edge portion (trailing edge portion) of the sheet bundle in the second conveyance direction $\beta 2$. At this position, the first roller 463 and the second roller 464 are located in the first groove 431, and the staple unit 400 is in the first posture. Further, FIG. 18B illustrates a position where the side stitch binding is performed on the R side of the downstream edge portion (trailing edge portion) of the sheet bundle in the second conveyance direction $\beta 2$. Also at this position, the first roller 463 and the second roller 464 are located in the first groove 431, and the staple unit 400 is in the first posture.

Movement from First Groove to R Side Oblique Binding Position

(130) FIG. 19A illustrates a state in which the first roller 463 and the second roller 464 are located in the first groove 431 and the second roller 464 is located near the downstream end portion of the first groove 431 in the second direction $\gamma 2$. In this state, the contact portion 455 provided in the stapler moving unit 450 abuts the abutment member 413. When the stapler moving unit 450 moves from this position to the downstream side in the second direction $\gamma 2$, the contact portion 455 and the abutment member 413 abut on each other, so that the rotation plate 462 starts to rotate in the counter-clockwise direction in the drawing together with the staple unit 400. Then, as illustrated in FIG. 19B, the second roller 464 is engaged with the fourth groove 434.

(131) Next, when the stapler moving unit 450 moves from this position to the downstream side in the second direction $\gamma 2$, as illustrated in FIG. 19BC, the second roller 464 is engaged with the positioning groove 434c, and the first roller 463 is engaged with the fifth groove 435. In this state, the staple unit 400 takes the above-described second posture on the R side. Then, at this position, it is possible to perform oblique binding at the corner portion on the R side of the downstream edge portion (trailing edge portion) of the sheet bundle in the second conveyance direction $\beta 2$.

(132) According to the present embodiment as described above, it is possible to provide a new configuration for turning the staple unit 400 at the time of performing oblique binding. In particular, in the present embodiment, in order to turn the staple unit 400 on the F side, the abutment member 413 as on the R side is not used. That is, in the present embodiment, the engagement amount of the first roller 463 and the second roller 464 with respect to the groove is made different, and the entry of the first roller 463 is restricted at the entrance of the third groove 433 to guide the first roller 463 to the second groove 432. Therefore, the staple unit 400 can be turned by moving in the width direction without arranging a member serving as a trigger for turning the staple unit 400 outside each groove like the abutment member 413.

(133) Therefore, in the present embodiment, a member that triggers for turning the staple unit 400 on the F side can be omitted. As a result, it is not necessary to dispose such a member outside the groove on the F side, so that the degree of freedom in design can be improved.

(134) By interchanging the configuration of each groove on the F side and the configuration of the groove on the R side and interchanging the positions of the first roller 463 and the second roller 464, the staple unit 400 can be turned in the same manner as described above even if there is no abutment member on the R side.

(135) In the above-described embodiment, the sheet processing apparatus 200A is disposed in the internal space 130 of the image forming apparatus 100, but the configuration of the sheet processing apparatus of the present technology may be, for example, a configuration to be attached to a side surface of the image forming apparatus. Also, the sheet processing apparatus may be controlled by a control unit included in the image forming apparatus.

(136) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(137) This application claims the benefit of Japanese Patent Application No. 2022-117885, filed on

Claims

1. A sheet binding apparatus comprising: a stapler configured to be capable of performing a binding process on a sheet bundle in a first posture and in a second posture which is different from the first posture; a moving mechanism configured to move the stapler in a moving direction; and a turn mechanism configured to turn the stapler from the first posture to the second posture in accordance with moving the stapler in the moving direction by the moving mechanism, wherein the turn mechanism includes: (1) a first protrusion and a second protrusion configured to move together with the stapler; (2) a first rail configured to guide the first protrusion and the second protrusion in the moving direction; (3) a second rail extending along an inclined direction inclined with respect to the moving direction from a downstream end of the first rail in the moving direction and configured to guide the first protrusion; (4) a third rail extending along the moving direction from the downstream end of the first rail and configured to guide the second protrusion; and (5) an introducing member having a length to introduce the first protrusion from the first rail to the second rail by coming into contact with the first protrusion, and to allow the second protrusion to enter from the first rail to the third rail, wherein when the first protrusion and the second protrusion are guided by the first rail, the stapler is held in the first posture, wherein when (1) the first protrusion is guided by the second rail and (2) the second protrusion is guided by the third rail, the stapler is held in the second posture, and wherein the stapler turns from the first posture to the second posture by (1) the first protrusion being introduced from the first rail to the second rail and (2) the second protrusion being guided from the first rail to the third rail, when the stapler moves in the moving direction.

2. The sheet binding apparatus according to claim 1, further comprising a fourth rail extending along another inclined direction inclined with respect to the inclined direction from a downstream end of the second rail, wherein the stapler turns from the second posture to the first posture by (1) the first protrusion being guided from the second rail to the fourth rail and (2) the second protrusion being guided to a downstream side of the third rail in the moving direction, when the stapler further moves in the moving direction from a position at which (1) the first protrusion is guided by the second rail and (2) the second protrusion is guided by the third rail.

3. An image forming system comprising: an image forming apparatus including an image forming unit configured to form an image on a sheet; and a sheet binding apparatus configured to perform a binding process on a sheet on which an image is formed by the image forming unit, wherein the sheet binding apparatus includes: (A) a stapler configured to be capable of performing a binding process on a sheet bundle in a first posture and in a second posture which is different from the first posture; (B) a moving mechanism configured to move the stapler in a moving direction; and (C) a turn mechanism configured to turn the stapler from the first posture to the second posture in accordance with moving the stapler in the moving direction by the moving mechanism, wherein the turn mechanism includes: (1) a first protrusion and a second protrusion configured to move together with the stapler; (2) a first rail configured to guide the first protrusion and the second protrusion in the moving direction; (3) a second rail extending along an inclined direction inclined with respect to the moving direction from a downstream end of the first rail in the moving direction and configured to guide the first protrusion; (4) a third rail extending along the moving direction from the downstream end of the first rail and configured to guide the second protrusion; and (5) an introducing member having a length to introduce the first protrusion from the first rail to the second rail by coming into contact with the first protrusion, and to allow the second protrusion to enter from the first rail to the third rail, wherein when the first protrusion and the second protrusion are guided by the first rail, the stapler is held in the first posture, wherein when (1) the first

protrusion is guided by the second rail and (2) the second protrusion is guided by the third rail, the stapler is held in the second posture, and wherein the stapler turns from the first posture to the second posture by (1) the first protrusion being introduced from the first rail to the second rail and (2) the second protrusion being guided from the first rail to the third rail, when the stapler moves in the moving direction.
