

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402957
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Schumann; Steffen et al.

Instrument calibration

Abstract

Surgical instrument calibration methods, systems, and devices are provided that allow a virtual representation of a surgical instrument to be modified to adjust for any variations in a distal tip of a surgical instrument. For example, an instrument calibration system is provided that can have a surgical instrument, a calibration instrument, and a monitoring system. The surgical instrument can have a distal tip and an orientation element thereon, and the calibration instrument can have a pivot point thereon and a calibration reference element attached thereto. The monitoring system can be configured to record movement of the surgical instrument with respect to the calibration instrument when the tip of the surgical instrument is inserted into the pivot point of the calibration instrument, and to calculate a deviation of the tip of the surgical instrument from a predefined ideal tip based on the recorded movement.

Inventors:	Schumann; Steffen (Zofingen, CH), Puls; Marc (Thörigen, CH)
Applicant:	DePuy Synthes Products, Inc. (Raynham, MA)
Family ID:	71401813
Assignee:	DePuy Synthes Products, Inc. (Raynham, MA)
Appl. No.:	18/488528
Filed:	October 17, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240041538 A1	Feb. 08, 2024

Related U.S. Application Data

continuation parent-doc US 16453710 20190626 US 11839434 child-doc US 18488528

Publication Classification

Int. Cl.: **A61B34/20** (20160101); **A61B17/16** (20060101); **A61B17/70** (20060101); **A61B34/00** (20160101); **A61B34/30** (20160101); **G16H40/40** (20180101)

U.S. Cl.:

CPC **A61B34/20** (20160201); **A61B17/1671** (20130101); **A61B17/7082** (20130101); **A61B34/25** (20160201); **A61B34/30** (20160201); **G16H40/40** (20180101); A61B2034/2048 (20160201); A61B2034/2051 (20160201); A61B2034/2055 (20160201); A61B2034/2072 (20160201); A61B2034/254 (20160201); A61B2560/0238 (20130101)

Field of Classification Search

CPC: A61B (2560/0238); A61B (2017/00725); A61B (2034/207); A61B (2034/2046); A61B (2034/2068)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6497134	12/2001	Faul	73/1.79	A61B 90/36
6511418	12/2002	Shahidi	73/1.79	A61B 5/064
11839434	12/2022	Schumann et al.	N/A	N/A
2004/0044295	12/2003	Reinert	600/587	G16H 20/40
2004/0158260	12/2003	Blau	606/108	A61B 90/36
2004/0167654	12/2003	Grimm	700/114	A61B 34/20
2005/0267358	12/2004	Tuma et al.	N/A	N/A
2008/0228195	12/2007	von Jako	606/130	A61B 34/20
2009/0163930	12/2008	Aoude	606/130	A61B 34/20
2009/0171197	12/2008	Burger	600/426	A61B 34/20
2009/0202387	12/2008	Dlugos, Jr. et al.	N/A	N/A
2009/0326324	12/2008	Munoz Martinez	901/30	A61B 34/30
2010/0331855	12/2009	Zhao	606/130	A61B 34/30
2015/0182293	12/2014	Yang	600/424	A61B 17/1703
2017/0345177	12/2016	Hladio et al.	N/A	N/A
2018/0140223	12/2017	Kheradpir et al.	N/A	N/A
2019/0029765	12/2018	Crawford et al.	N/A	N/A
2020/0405400	12/2019	Schumann	N/A	A61B 34/20
2024/0041538	12/2023	Schumann	N/A	A61B 17/1671

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1511249	12/2003	CN	N/A
103732165	12/2013	CN	N/A
109171962	12/2018	CN	N/A
2003534035	12/2002	JP	N/A
2009254805	12/2008	JP	N/A
0167979	12/2000	WO	N/A

02061371	12/2001	WO	N/A
2010077008	12/2009	WO	N/A
2017200445	12/2016	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/IB2020/055335, mailed on Aug. 24, 2020, 11 pages. cited by applicant

Koulechov, Kirill (2006) “Leistungssteuerung chirurgischer Instrumente in der Kopf-Chirurgie”, “Performance control of surgical instruments in head surgery”, Technical University of Munich, Munich, Germany, 156 pages. cited by applicant

Primary Examiner: Jacob; Oommen

Attorney, Agent or Firm: Barnes & Thornburg LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 16/453,710, filed Jun. 26, 2019 and entitled “INSTRUMENT CALIBRATION,” which is hereby incorporated by reference herein in its entirety.

FIELD

(1) Surgical devices, systems, and methods are provided for performing instrument calibration on surgical instruments.

BACKGROUND

(2) Computer and/or robotic-assisted surgery has allowed for more successful surgical outcomes by providing a variety of different benefits to a surgeon, such as improved visualization during surgery, guidance, better control over instruments, etc. For computer and/or robotic systems to provide assistance, navigation systems are used for tracking movements of surgical instruments during a procedure and providing a virtual representation of the instrument relative to a scan of the patient. Accurately tracking movements of the instruments and accurately representing the instruments in various virtual representation is important for the safety of the patient. As such prior to use, each instrument must be calibrated to ensure accurate measurements and accurate virtual representations. However, current methods present challenges, such as accurately modeling instruments.

(3) Therefore, improved instrument calibration techniques are needed.

SUMMARY

(4) Methods, devices, and systems are provided herein that allow an instrument to be calibrated such that a virtual representation of the instrument can be updated to accommodate for any distortions or bending that may occur at the distal tip over time, such as in instruments having a curved distal tip. In one aspect, an instrument calibration system is provided with a surgical instrument that has an elongate shaft with a proximal end and a distal end. The distal end has a distal-most tip while the proximal end has an orientation element fixed in an initial position thereon. The system also has a calibration instrument with a point thereon that is configured to receive the distal-most tip of the surgical instrument for pivoting thereabout. The calibration instrument also has a predefined geometric structure and a calibration reference element attached thereto. The system also has a monitoring system that is configured to record movement of the surgical instrument when the distal-most tip of the surgical instrument is positioned at the pivot point of the calibration instrument by recording a relative position of the orientation element to the

calibration reference element. The monitoring system is configured to calculate a deviation of the distal-most tip of the surgical instrument from a predefined ideal distal-most tip based on the recorded movement of the orientation element of the surgical instrument, a predefined ideal instrument axis of the surgical instrument, and the predefined ideal distal-most tip of the surgical instrument, and the monitoring system is configured to modify a virtual representation of the surgical instrument on a display based on the calculated deviation.

(5) The system can have numerous variations. For example, the distal end of the surgical instrument can be a curved tip. In another example, the distal end of the surgical instrument can have a cavity formed therein. In one example, the monitoring system can be configured to determine an initial orientation of the orientation element with respect to the surgical instrument while the orientation element remains in a fixed position relative to the surgical instrument. In another example, the monitoring system can be configured to determine an actual orientation of the surgical instrument in use while the orientation element on the proximal end thereof is moved to one of a plurality of second positions different than the initial position on the surgical instrument without requiring re-recording movement of the surgical instrument with respect to the calibration instrument.

(6) In still another example, the pivot point on the calibration instrument can include a plurality of removable and replaceable pivot points, and each of the plurality of removable and replaceable pivot points can be configured to correspond to one of a plurality of different distal-most tips of a plurality of different surgical instruments. The monitoring system can also be configured to be updated depending on which one of the plurality of removable and replaceable pivot points is used.

(7) In some embodiments, each of the orientation element and the calibration reference element can include one of an array having a plurality of trackable targets thereon, an electro-magnetic sensor, and a gyroscope. The monitoring system can also include at least one camera, at least one sensor, at least one processor, and at least one display. In some embodiments, the monitoring system can be part of a robotic surgery system, and the surgical instrument can be configured to be controlled by the robotic surgery system. Exemplary surgical instruments include, for example, a screwdriver and a discectomy device. In another embodiment, the orientation element can be configured to rotate about the surgical instrument in a plurality of known orientations, and the monitoring system can be configured to update a virtual representation of the surgical instrument on a display based on each of the plurality of known orientations of the orientation element without rerecording the relative position of the orientation element to the calibration reference element in each of the plurality of known orientations.

(8) In another aspect, a method of calibrating a surgical instrument for use during surgical navigation is provided that includes inserting a distal-most tip on a distal end of the surgical instrument onto a pivot point on a calibration instrument while the calibration instrument has a predefined geometric structure and a calibration reference element attached thereto. The method also includes pivoting the surgical instrument about the pivot point such that a proximal end of the surgical instrument moves along an approximately circular path above the calibration instrument while a monitoring system records reference coordinate points of an orientation element fixed at a first position on the surgical instrument relative to reference coordinate points of the calibration reference element on the calibration instrument. The method further includes comparing, by the monitoring system, the recorded reference coordinate points to at least one stored reference coordinate point of an orientation element on a predefined ideal surgical instrument to calculate a deviation of the distal-most tip of the surgical instrument from a predefined ideal distal-most tip based on the comparison. After determining the deviation of the distal-most tip, the monitoring system modifies a virtual representation of the surgical instrument on a display based on the calculated deviation.

(9) The method can have a number of variations. For example, the method can include determining by the monitoring system an initial orientation of the orientation element with respect to the

surgical instrument while the orientation element remains in a fixed position relative to the surgical instrument.

(10) In another embodiment, the pivot point can be formed on a removable portion of the calibration instrument, and the method can include replacing the removable portion of the calibration instrument with a second removable portion having a second pivot point with a different shape configured to match the distal-most tip of the surgical instrument. In some embodiments, the method can include updating the monitoring system based on the second pivot point.

(11) In other aspects, the method can include, after modifying the virtual representation of the surgical instrument based on the calculated deviation, rotating the orientation element of the surgical instrument to a different known orientation and modifying by the monitoring system the virtual representation of the surgical instrument on the display based on the different known orientation of the orientation element.

(12) In another aspect, a method for calibrating a surgical instrument with a distal-most tip is provided that includes recording, by a monitoring system, a movement of an orientation element at an initial position on the surgical instrument with respect to a calibration reference element on a calibration instrument. The method also includes calculating, by a processor operatively coupled to the monitoring system, a deviation of the distal-most tip of the surgical instrument from a predefined virtual representation of the distal-most tip of the surgical instrument by comparing the recorded movement of the orientation element of the surgical instrument to an expected movement of the orientation element. The predefined virtual representation of the distal-most tip of the surgical instrument includes a plurality of data points stored in a memory accessible by the processor that define a representation of the surgical instrument. The method also includes updating, by the processor, one or more first data points stored in the memory among the plurality of data points of the predefined virtual representation of the distal-most tip of the surgical instrument based on the calculated deviation of the distal-most tip.

(13) Multiple variations of the method are possible. For example, the method can include controlling, by the processor, a surgical display so as to display the one or more updated first data points of the predefined virtual representation of the distal-most tip of the surgical instrument. In another example, the method can include, after updating the one or more first data points, determining, by the processor, an orientation of the surgical instrument during use when the orientation element thereon is moved to a second position different than the initial position on the surgical instrument without re-recording the movement of the surgical instrument with respect to the calibration instrument. In such an example, the method can also include updating, by the processor, one or more second data points stored in the memory among the plurality of data points of the predefined virtual representation of the distal-most tip of the surgical instrument based on the second position of the orientation element.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The embodiments described above will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings. The drawings are not intended to be drawn to scale. For purposes of clarity, not every component may be labeled in every drawing. In the drawings:

(2) FIG. 1 is a perspective view of one embodiment of a calibration instrument;

(3) FIG. 2A is a cross-sectional side view of a pivot point in the calibration instrument of FIG. 1;

(4) FIG. 2B is a cross-sectional side view of a pivot point in another embodiment of a calibration instrument similar to the calibration instrument of FIG. 1;

(5) FIG. 3 is a perspective view of one embodiment of a surgical instrument;

- (6) FIG. 4 is a perspective view of the surgical instrument of FIG. 3;
- (7) FIG. 5 is a top-down view of a patient and one embodiment of a monitoring system;
- (8) FIG. 6 is a diagram showing one embodiment of a control system architecture;
- (9) FIG. 7 illustrates a flow diagram of one embodiment of a calibration process of the surgical instrument of FIG. 3 rotating and/or pivoting with respect to the calibration instrument of FIG. 1;
- (10) FIG. 8 illustrates another flow diagram of the calibration process of the instrument of FIG. 3;
- (11) FIG. 9 is a perspective view of the surgical instrument of FIG. 3 interacting with the calibration instrument of FIG. 1;
- (12) FIG. 10 is a perspective view of the calibration process of FIGS. 7 and 8 with the surgical instrument of FIG. 3 rotating with respect to the calibration instrument of FIG. 1;
- (13) FIG. 11 is a perspective view of continued rotation of the surgical instrument and the calibration instrument in FIG. 10;
- (14) FIG. 12 is a perspective view of continued rotation of the surgical instrument and the calibration instrument in FIG. 11;
- (15) FIG. 13A is an image of a graphical interface showing a virtual sphere fit to a predefined or ideal version of the instrument of FIG. 3;
- (16) FIG. 13B is an image of a graphical interface showing virtual tracking points created based on the rotation of FIGS. 10-12;
- (17) FIG. 13C is an image of a graphical interface showing virtual instrument shafts of the instrument of FIG. 3 based on the tracking points of FIG. 13B;
- (18) FIG. 13D is an image of a graphical interface showing a virtual sphere fit to the tracking points of FIG. 13B;
- (19) FIG. 13E is an image of a graphical interface showing the virtual sphere of FIG. 13D mapped or transposed onto the virtual sphere of FIG. 13A;
- (20) FIG. 14 is a perspective view of another embodiment of a surgical instrument;
- (21) FIG. 15 is a perspective view of an orientation arm of the surgical instrument of FIG. 14;
- (22) FIG. 16 is a perspective view of a ring coupling of the surgical instrument of FIG. 14;
- (23) FIG. 17A is a perspective view of the surgical instrument of FIG. 14 in use;
- (24) FIG. 17B is a perspective view of the surgical instrument of FIG. 14 in use;
- (25) FIG. 18 is a side view of another embodiment of a surgical instrument;
- (26) FIG. 19 is a side view of a distal end of the surgical instrument of FIG. 18 with another embodiment of a calibration instrument; and
- (27) FIG. 20 is a side view of the distal end of the surgical instrument of FIG. 18 with the calibration instrument of FIG. 19.

DETAILED DESCRIPTION

(28) Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

(29) Further, in the present disclosure, like-named components of the embodiments generally have similar features, and thus within a particular embodiment each feature of each like-named component is not necessarily fully elaborated upon. Additionally, to the extent that linear or circular dimensions are used in the description of the disclosed systems, devices, and methods, such dimensions are not intended to limit the types of shapes that can be used in conjunction with such systems, devices, and methods. A person skilled in the art will recognize that an equivalent to such

linear and circular dimensions can easily be determined for any geometric shape. Sizes and shapes of the systems and devices, and the components thereof, can depend at least on the anatomy of the subject in which the systems and devices will be used, the size and shape of components with which the systems and devices will be used, and the methods and procedures in which the systems and devices will be used.

(30) Various exemplary methods, devices, and systems are provided for performing instrument calibration on surgical instruments with curved distal tips. During computer and/or robotic-assisted surgery, an accurate virtual representation of any instrument being used during surgery is needed for the computer or robotic system to be able to correctly assess a current location of the instrument and to correctly provide assistance, guidance, etc. to the surgeon. Because virtual representations of instruments with curved distal tips can become inaccurate as a result of an actual distal tip on a corresponding surgical instrument bending or warping over time, updating a virtual representation of an instrument with a curved distal tip so that it accurately reflects a current distal tip geometry of the instrument can allow for better surgical results. For example, the virtual representation used by the computer or robotic system can accurately reflect the instrument used in the surgery rather than the system having to assume a distal tip is in an ideal state. Additionally, it can allow for reduced waste by eliminating the need to discard any surgical instrument that cannot be calibrated only because the curved distal tip is not in a perfect or near-perfect state while the instrument is otherwise surgically acceptable. Thus, instruments with curved tips can be accurately calibrated using the methods, devices, and systems provided herein such that a computer or robotic system can determine accurate distal tip geometry and measurements of the instruments, even after repeated use, and accurately update a virtual representation of the instrument.

(31) Instrument calibration can be performed on a surgical instrument with a curved distal tip using a navigation array fixed on the surgical instrument in a first orientation. In certain embodiments, the navigation array can be rotated and/or moved into one or more different orientations on the surgical instrument during use to ensure the surgical instrument can be continually tracked by the computer or robotic system without requiring the surgical instrument to be recalibrated each time an orientation of the navigation array is changed. This movement allows the surgeon more flexibility in rotating or maneuvering the surgical instrument during use while saving time and still ensuring that the instrument is tracked by the system.

(32) An exemplary instrument calibration system can include a surgical instrument with an elongate shaft that has a curved distal tip and an orientation array thereon. A calibration instrument can also be provided that has a predefined geometric structure and a calibration reference array attached thereto. A pivot point can be formed in the calibration instrument that is configured to receive the curved distal tip of the instrument. A monitoring system can also be provided that is configured to record coordinates of the surgical instrument when the curved distal tip of the surgical instrument is inserted into the pivot point of the calibration instrument and the instrument is rotated thereabout. Based on the recorded coordinates, the monitoring system can be configured to calculate a deviation of the curved distal tip of the surgical instrument from a predefined ideal curved tip and modify a virtual representation of the surgical instrument on a display based on the calculated deviation such that the virtual representation accurately mirrors the actual curved distal tip of the instrument with any bends or deviations reflected therein. Virtual representations can include a variety of different information and/or data representing parts of the instruments and systems discussed herein. For example, virtual representations can include pluralities of data points defining and/or representing shapes, orientations, locations, etc. of the various components of the systems discussed herein.

(33) FIG. 1 illustrates one exemplary embodiment of a calibration instrument **100** with a pivot point **110** formed therein and a calibration reference array **120** attached thereon. The calibration instrument **100** is configured to allow calibration of a surgical instrument **200** with a curved distal tip **210** by a monitoring system **300**, discussed in detail below. The calibration instrument **100** has a

predefined side and shape that is known to the monitoring system **300**, and the pivot point **110** is formed in one side **102** thereof.

(34) The pivot point **110** is configured to receive the curved distal tip **410** of the surgical instrument **200** therein. The pivot point **110** can be sized and shaped to complement the curved distal tip **210** and to provide a relatively secure hold on a distal-most end **212** of the curved distal tip **210** to prevent the distal tip **210** from sliding around in the pivot point **110**. At the same time, the pivot point **210** provides a fixed point about which the surgical instrument **200** can smoothly rotate or pivot, as discussed more below. Thus, the pivot point **110** can be specifically configured to receive distal tips of certain instruments or groups of instruments, and dimensions of the pivot point **110** like depth of the cavity, diameter of the circular opening on the side wall **102**, angles of the sidewalls of the cavity, etc. can all be varied. For example, the pivot point **110** can be a cavity shaped like an inverse cone, as illustrated in FIG. 2A, for receiving a cone-shaped or more rounded tip. However different embodiments can have different shaped pivot points depending on the type of distal end being received therein, such as cavities shaped like inverse cylinders, spheres, pyramids, prisms, etc. While the pivot point **110** is formed in one side **102** of the calibration instrument **100**, it can be formed in various other locations on the calibration instrument **100** in other embodiments. Additionally, in some embodiments, the pivot point **110** can be removable and replaceable to allow different pivot points configured to accept different types of distal tips to be inserted and used during calibration of different types of instruments. For example, FIG. 2B illustrates a removable pivot point mechanism **152** that can be inserted into and removed from a calibration instrument **150** that is similar to the instrument **100**, and the removable pivot point mechanism **152** can be secured in place through a variety of different means, such as through clips, engagements, friction, etc.

(35) The calibration instrument **100** also has a calibration reference array **120** attached thereto that is configured to be tracked by the monitoring system **300**. The calibration reference array **120** has a predefined arrangement known to the monitoring system **300** such that it can provide a predefined 3-dimensional calibration coordinate system **130** to the monitoring system **300** during calibration. For example, as the instrument **200** is calibrated by pivoting the instrument **200** relative to the pivot point **110**, the calibration reference array **120** is configured to allow the monitoring system **300** to take images containing the calibration reference array **120**. Because the dimensional arrangement and orientation of the calibration reference array **120** with respect to itself and the calibration instrument **100** is predefined and known to the monitoring system **300**, the calibration reference array **120** allows the monitoring system **300** to use the calibration reference array **120** in each image as a reference scale to determine various orientation and measurement values of other objects in the images based on the position and visibility of the calibration reference array **120** in each image. This allows the monitoring system **300** to effectively place other objects in the images to scale within the context of the calibration coordinate system **130**.

(36) The illustrated calibration reference array **120** has three targets **122a**, **122b**, **122c** thereon that can be imaged and tracked by the monitoring system **300** to provide a calibration coordinate system **130** to the monitoring system **300** and/or the control system **400**. The targets **122a**, **122b**, **122c** are arranged in a generally triangular configuration in a single plane that extends parallel to and above an upper surface **104** of the calibration instrument **100**. Targets **122a**, **122b** are arranged on wings **124**, **126** that extend laterally away from each other on the upper surface **104** of the calibration instrument **100**. The calibration instrument **100** can be tipped sideways to rest on the wing **126** and maintain the calibration instrument **100** at a defined and consistent angle. During calibration, the pivot point **110** is thus accessible so that a distal tip of the instrument **200** can be inserted therein, as illustrated in FIGS. 10-12. In other embodiments, however, the orientation and placement of the one or more target **122a**, **122b**, **122c** can vary, such as being arranged in planar squares, rectangles, etc., or 3-dimensional cubes, pyramids, etc., and the wings **124**, **126** can be placed elsewhere on or removed entirely from the calibration instrument **100**. The calibration instrument **100** itself can also

have various targets thereon, for example providing reference planes on one or more sides of the instrument **100**, along edges thereof, etc. While the calibration instrument **100** has a specific rectangular wing structure illustrated in FIG. **1**, in other embodiments, the calibration instrument can be any three-dimensional structure with one or more calibration reference elements thereon and one or more pivot points thereon.

(37) While a variety of tracking approaches can be used, the targets **122a**, **122b**, **122c** are configured to be captured in images and to provide orientation, location, and scale information based on their relative positions to each other in the images. For instance, if an image captures the targets **122a**, **122b**, **122c** all in the triangular orientation visible by looking straight down on the calibration instrument **100**, the calibration instrument **100** is oriented such that the calibration reference array **120** is facing directly at the monitoring system **200**. If the targets **122a**, **122b**, **122c** are captured such that all three targets are positioned along a shared line, the calibration instrument **100** is positioned such that the calibration reference array **120** is perpendicular to the monitoring system **200**. Thus, as the calibration instrument **100** moves three-dimensionally while the calibration reference array **120** is within view of the monitoring system **300**, the targets **122a**, **122b**, **122c** allow the location, orientation, and scale within the image of the calibration instrument **100** to be determined by mapping the known and predetermined coordinates of the targets **122a**, **122b**, **122c** relative to each other to the actual coordinates of the targets **122a**, **122b**, **122c** in the captured images. A virtual representation of the calibration instrument **100** can thus be rotated and oriented so that the known and predefined orientations of the targets **122a**, **122b**, **122c** on the virtual representation match up with the actual imaged targets **122a**, **122b**, **122c**. The virtual representation of the calibration instrument can be a plurality of coordinates defining the shape of the calibration instrument **100** and stored in a memory, as discussed below. Because the calibration reference array **120** is attached to the calibration instrument **100** in a known orientation and because the shape and size of the calibration instrument **100** is known, the location and pose of the calibration instrument can be accurately determined. Once the orientation of the calibration reference array **120** is determined, the relative distances between the targets **122a**, **122b**, **122c** in the actual image can be used for scale because the actual distances between the targets are known and predefined.

(38) While FIG. **1** illustrates three targets **122a**, **122b**, **122c** in the form of spheres, any number of targets can be used, and the targets can take various different forms, such as flat images, grids, geometric shapes, patterns, various transmitting elements, lights, etc. The targets **122a**, **122b**, **122c** are configured to be passive targets, however active targets can be used in some embodiments requiring one or more power sources, such as light-emitting diodes (LEDs), or a combination of active and passive tracking can be used. In other embodiments, one or more various different sensors can be used as reference elements instead of or in addition to one or more of the targets **122a**, **122b**, **122c** or instead of the calibration reference array **120** entirely, such as electro-magnetic sensor(s), gyroscope(s), various radio-frequency identification (RFID) tags or various transmitting tags, etc. The calibration reference array **120** and the calibration instrument **100** can be made from a variety of different materials, such as medical grade metals, plastics, polymers, ceramics, etc.

(39) As indicated above, the pivot point **110** of the calibration instrument **100** is configured to receive a tip on a surgical instrument to allow a surgical instrument to be calibrated. FIGS. **3** and **4** illustrate one embodiment of a surgical instrument **200** that has an elongate shaft **204** extending from a handle **202** with a curved distal tip **210** on a distal end thereof. The surgical instrument **200** can be calibrated such that an accurate virtual representation of at least an axis of the elongate shaft **204** and the curved distal tip **210** can be generated by the monitoring system **300**. The virtual representation of the surgical instrument **200** can be a plurality of data points, e.g., coordinates, that aid in defining the shape of the surgical instrument **200**. The data points can be stored in a memory and updated in the memory based on the calculations discussed herein, as discussed in detail below.

(40) The instrument **200** is configured to be calibrated through interaction with the calibration instrument **100** and the monitoring system **300**. Calibration can be achieved by comparing

measured data to predetermined data based on a predefined or ideal instrument axis **250** and a predefined or ideal instrument tip **252**. The predefined instrument axis **250** and the predefined instrument tip **252** may not necessarily reflect a current configuration of the elongate shaft **204** and a distal-most end **212** of the instrument **200**. Rather, they can be calculated based on the design and/or manufacturing parameters for the instrument. For example, the predetermined data can be in the form of one or more coordinates representing ideal locations of one or more reference arrays on an ideal instrument. The coordinates, referred to as predetermined instrument coordinates, represent initial or expected data that can be provided to the monitoring system **300** to generate an initial or expected virtual representation of the instrument **200**. The initial or expected virtual representation can be used to calibrate a newly manufactured instrument and/or a used instrument. The predefined instrument axis **250** and the predefined instrument tip **252** can be specific to the type of instrument, and the values may be different when different instruments are used in other embodiments. While data representing the predefined instrument axis **250** and the predefined instrument tip **252** are provided to the monitoring system, a variety of other data can also be provided in some embodiments, such as instrument type, number of uses, etc.

(41) By way of non-limiting example, the illustrated surgical instrument **200** is the DePuy Synthes Concorde Clear minimally invasive discectomy device, however a variety of instruments can be used, configured both for minimally-invasive or more traditional surgeries. The surgical instrument **200** can be made from a variety of different materials, such as medical grade metals, plastics, polymers, ceramics, etc. While the illustrated instrument **200** has a curved distal tip **210**, an instrument with a straight distal tip can be used in other embodiments, such as instruments with sharp or pointed distal tips, screwdrivers, etc.

(42) Similar to the calibration instrument **100**, the surgical instrument **200** also has an orientation array **220** attached thereto that can be tracked by the monitoring system **300** and that has a predefined arrangement known to the monitoring system **300** such that it can provide predefined instruments coordinates within a predefined 3-dimensional instrument coordinate system **230** to the monitoring system **300** during calibration.

(43) As the instrument **200** is calibrated by pivoting in the pivot point **110**, the orientation array **220** allows the monitoring system **300** to take images containing the orientation array **220**. Because the dimensional arrangement and orientation of the orientation array **220** is predefined and known to the monitoring system **300**, the orientation array **220** allows the monitoring system **300** to use the orientation array **220** in each image as a reference scale to determine various orientation and measurement values of other objects in the images based on the position and visibility of the orientation array **220** in each image, such as the surgical instrument **200**. Thus, the monitoring system **300** can effectively place other objects in the images to scale within the context of the instrument coordinate system **230**.

(44) Similar to the calibration reference array **120**, in the illustrated embodiment the orientation array **220** has three targets **222a**, **222b**, **222c** thereon that can be imaged and tracked by the monitoring system **300** to provide the instrument coordinate system **230** in a similar manner to the targets **122a**, **122b**, **122c** of the calibration instrument **100** discussed above. The targets **222a**, **222b**, **222c** are arranged in a generally triangular arrangement to one another in a single plane that extends parallel to and offset from a longitudinal axis of the surgical instrument **200**. The orientation array **220** is coupled to the surgical instrument **200** in a known and predefined orientation by an orientation arm **224** with a predefined length and an orientation ring **226**, however the orientation array **220** can be coupled to the instrument **200** in a variety of different ways.

(45) Using the same imaging approach as the calibration reference array **120**, the surgical instrument **200** moves three-dimensionally while the orientation array **220** is within view of the monitoring system **300**. The targets **222a**, **222b**, **222c** thus allow the location, orientation, and scale within the image of the surgical instrument **200** to be determined by mapping the actual imaged coordinates of the targets **222a**, **222b**, **222c** in the captured images. The mapped coordinates of the

targets **222a**, **222b**, **222c** on the instrument **200**, referred to herein as the measured instrument coordinates, can be compared to the predetermined instrument coordinates calculated based on an ideal instrument. The system **300** can use these coordinates to generate a virtual representation of the surgical instrument **200** such that the measured instrument coordinates of the targets **222a**, **222b**, **222c** on the virtual representation overlay the predetermined instrument coordinates of actual imaged targets **222a**, **222b**, **222c**. Because the orientation array **220** is attached to the surgical instrument **200** in a known orientation and because the shape and size of the surgical instrument **200** is known, the location and pose of the surgical instrument **200** with the curved distal tip **210** can then be determined. Once the orientation of the orientation array **220** is determined, the distances between the targets **222a**, **222b**, **222c** in the actual image can be used for scale because the actual distances between the targets are known and predefined.

(46) There are three targets **222a**, **222b**, **222c** illustrated in FIGS. **3** and **4**, and the targets **222a**, **222b**, **222c** are in the form of spheres. However, any number of targets can be used, and the targets can take various different forms, such as flat images, grids, geometric shapes, patterns, various transmitting elements, lights, etc. The targets **222a**, **222b**, **222c** can be passive targets, however active targets can be used in some embodiments requiring one or more power sources, such as light-emitting diodes (LEDs), or a combination of active and passive tracking can be used. In other embodiments, one or more various different sensors can be used as orientation elements instead of or in addition to one or more of the targets **222a**, **222b**, **222c** or instead of the orientation array **220** entirely, such as electro-magnetic sensor(s), gyroscope(s), various radio-frequency identification (RFID) tags or various transmitting tags, etc. The orientation array **220** can be made from a variety of different materials, such as medical grade metals, plastics, polymers, ceramics, etc.

(47) As noted, the calibration instrument **100** and/or the surgical instrument **200** can be tracked by a monitoring system, such as the monitoring system **300** illustrated in FIG. **5**. Specifically, the monitoring system **300** is configured to track an orientation and a location of the configuration reference array **120** and the orientation array **220** relative to the monitoring system **300** during calibration of the surgical instrument **200**, and it can be configured to track the surgical instrument **200** during use. For example, it is configured to track the targets **122a**, **122b**, **122c** of the calibration instrument **100** and the targets **222a**, **222b**, **222c** of the surgical instrument **200**, as discussed in detail above, and it can be configured to record movement of the surgical instrument **200** when the curved distal tip **210** of the surgical instrument **200** is inserted into the pivot point **110** of the calibration instrument **100** and rotated thereabout, as discussed in detail below. Based on the recorded movement, e.g., the recorded coordinates, the monitoring system **300** can be configured to calculate a deviation of the curved distal tip **210** of the surgical instrument **200** from the predefined instrument tip **252**. The monitoring system **300** can thus modify a virtual representation of the surgical instrument **200** on a surgical display, such as a virtual representation **275** of the surgical instrument **200** on a display **500** to be used during surgery on a patient **10** in FIG. **5**, based on the calculated deviation such that the virtual representation accurately mirrors the actual curved distal tip **210** of the instrument **200** with any bends or deviations reflected therein. As discussed in detail below, this can be achieved in part by translating the measured instrument coordinates and predetermined instrument coordinates in coordinate system **230** onto coordinate system **130**.

(48) The monitoring system **300** can have a variety of configurations and can include various components, such as a navigation camera used for surgery. Depending on the type of target used, the monitoring system **300** can be configured to directly visualize the operating space through one or more cameras, and the monitoring system **300** can use active tracking, passive tracking, or some combination. It can also be part of a robotic surgical system, part of a computer-assisted surgical system, or a stand-alone device.

(49) The control system or processor **400** is configured to assist in calculating the orientation and location of the arrays **120**, **220** relative to the monitoring system **400** based on data gathered by the

monitoring system **400**. The control system **400** can be configured to calculate results both at a single point in time, periodically, or continuously over a period of time. The control system **400** can either be part of the monitoring system **300**, can be part of a robotic surgical system, can be a separate component, or some combination of the preceding. In some embodiments, it can also communicate with at least one of the monitoring system **400**, the calibration instrument **100** and/or the array **120**, the surgical instrument **200** and/or the array **220**, or some combination of the preceding either directly or indirectly and either wirelessly or through wired connections. FIG. 6 illustrates a diagrammatic view of an exemplary device architecture of the control system **400**.

(50) As shown in FIG. 6, the control system **400** may contain multiple components, including, but not limited to, an internal processor (e.g., central processing unit (CPU) **410**), a memory **420**, a wired or wireless communication unit **430**, one or more input units **440**, and one or more output units **450**. It should be noted that the architecture depicted in FIG. 6 is simplified and provided merely for demonstration purposes. The architecture of the control system **400** can be modified in any suitable manner as would be understood by a person having ordinary skill in the art, in accordance with the present claims. Moreover, the components of the control system **400** themselves may be modified in any suitable manner as would be understood by a person having ordinary skill in the art, in accordance with the present claims. Therefore, the device architecture depicted in FIG. 6 should be treated as exemplary only and should not be treated as limiting the scope of the present disclosure.

(51) The internal processor **410** is capable of controlling operation of the control system **400** and/or the monitoring system **300** depending on whether the control system **400** and the monitor system **300** are combined or separate. More specifically, the processor **410** may be operable to control and interact with multiple components associated with the control system **400**, as shown in FIG. 6. For instance, the memory **420** can store program instructions that are executable by the internal processor **410** and data. The process described herein may be stored in the form of program instructions in the memory **420** for execution by the internal processor **410**. The communication unit **430** can allow the control system **400** to transmit data to and receive data from one or more external devices via a communication network. The input unit **440** can enable the control system **400** to receive input of various types, such as audio/visual input, user input, data input, and the like. To this end, the input unit **440** may be composed of multiple input devices for accepting input of various types, including, for instance, one or more cameras **442** (i.e., an imaging device), touch panel(s) **444**, microphone(s) (not shown), sensors **446**, one or more buttons or switches (not shown), and so forth. The input devices included in the input **440** may be manipulated by a user. Notably, the term image acquisition unit, as used herein, may refer to the camera **442**, but is not limited thereto. For example, the image acquisition unit can be the monitoring system **300** or a part thereof. The output unit **450** can display information on the display screen **452** for a user to view. The display screen **452** can also be configured to accept one or more inputs, such as a user tapping or pressing the screen **452**, through a variety of mechanisms known in the art, and the output unit **450** may further include a light source **454**. In some embodiments, the output unit **450** can be configured to send any processing results to various systems, such as a robotic surgical system or a computer-assisted surgical system. The control system **400** and/or the monitoring system **300** can also be configured to calculate orientations of instruments, distances, translations of coordinate systems, etc. based on information from the arrays **120**, **220**.

(52) As noted above, interaction of the calibration instrument **100**, the surgical instrument **200**, the monitoring system **300**, and the control system **400** can allow the monitoring system **300** and/or the control system **400** to calculate a deviation of the curved distal tip **210** of the surgical instrument **200**, and to modify the virtual representation of the surgical instrument **200** on a surgical display based on the calculated deviation. As illustrated at step **600** in FIGS. 7 and 8, initially, the monitoring system **300** and/or the control system **400** is provided with various known and predefined data as discussed above, such as a virtual representation of the surgical instrument **200**

with the predefined instrument axis **250**, the predefined instrument tip **252**, and information regarding the orientation and arrangement of the orientation array **220** on the surgical instrument **200**, which can all be represented by a plurality of data points (e.g., predetermined instrument coordinates) defining the shape and orientation of the surgical instrument with the predefined shaft and tip; and a virtual representation of the calibration instrument **100** with a known shape and size and information regarding the orientation and arrangement of the calibration reference array **120** on the calibration instrument **100**, which can be represented by a plurality of data points defining the shape and orientation of the calibration instrument. This information can be provided through a variety of means, such as being manually inputted, automatically loaded by, for example, scanning or imaging one or more of the instruments **100**, **200** and/or the arrays **120**, **220** that can have identifying information thereon, downloaded onto the system **300**, etc. The monitoring system **300** is initiated to begin tracking the calibration instrument **100** and the surgical instrument **200** at step **602**, for example each instrument **100**, **200** and/or each array **120**, **220** can be displayed to the monitoring system **300** or the monitoring system **300** can be instructed manually to initiate tracking.

(53) The curved distal tip **210** of the surgical instrument **200** is inserted into the pivot point **110** of the calibration instrument **100** at step **604** and FIG. **9**, for example by tipping the calibration instrument **100** at a defined angle as illustrated in FIGS. **10-12** and inserting the distal-most end **212** into the pivot point **110**. The surgical instrument **200** is rotated in an approximately circular motion above the calibration instrument, as illustrated in FIGS. **10-12**, and the monitoring system **300** records the movement of the orientation array **220** on the surgical instrument **200** relative to the fixed position of the calibration reference array **120** on the calibration instrument **100**. As the surgical instrument **200** moves, the distal-most end **212** of the curved distal tip **210** remains in the cavity of the pivot point **110** because the pivot point **110** is sized and shaped to secure the distal-most end **212** therein while allowing the surgical instrument **200** to smoothly rotate and pivot. The pivot point **110** thus provides a fixed, known point about which the surgical instrument **200** can rotate. The monitoring system **300** thus captures images and records coordinates of the orientation array **220** when the surgical instrument **200** is in a plurality of different poses or positions at step **606**. For example, FIGS. **10-12** illustrate exemplary rotation of the surgical instrument **200** while the monitoring system **300** captures a variety of images of the orientation array **220** in relation to the calibration reference array **120**. As such, the rotation generally defines a circular shape **240** of movement above the pivot point **110** that corresponds to a path of motion of the orientation array **220**.

(54) The monitoring system **300** and/or the control system **400** can use the captured movement of the orientation array **220** (e.g. the measured instrument coordinates) in relation to the fixed pivot point **110** and the calibration reference array **120** to update the virtual representation of the surgical instrument **200**. The system(s) **300/400** can do this by comparing the captured calibration movement (e.g. the measured instrument coordinates) to expected calibration movement (e.g. predetermined instrument coordinates) of a model of the surgical instrument **200** with the predefined instrument axis **250** and the ideal tip **252**, discussed below.

(55) The monitoring system **300** and/or the control system **400** can be initially provided with data representing a model of the surgical instrument **200** with the predefined instrument axis **250** and the ideal tip **252**. The system(s) **300/400** can also be provided with expected calibration movement data (e.g. predetermined instrument coordinates) of the surgical instrument **200** with the predefined instrument axis **250** and the ideal tip **252**. However, in some embodiments, the system(s) **300/400** can also model the expected behavior itself using the predefined instrument axis **250** and the ideal tip **252** data. With a new or ideal instrument, calibration movement data is modeled based on technical diagrams of the instrument. In other embodiments, though, it can be directly measured and recorded on a never-before-used instrument. Expected calibration movement data can be modeled by assuming the ideal instrument is rotated in a manner similar to the instrument **200**

about a fixed point **256**. As such, a circle **257** of movement is defined above the fixed pivot point **256**, as illustrated in FIG. **13A**, that corresponds to a path of motion of an orientation array if the orientation array was fixed to the ideal instrument. For example, a plurality of points **258** can represent a plurality of coordinates of the ideal orientation array during calibration movement. The predefined instrument axis **250** defines a distance away from the fixed pivot point **256** at which the ideal orientation array would move, with each of the points **258** being positioned at the same distance away from the fixed point **256**. Thus, movement of the ideal surgical instrument about the pivot point **256** with the ideal tip **252** inserted therein can define a semi-sphere **254** with the predefined instrument axis **250** acting as a radius of the sphere **254** and the fixed point **256** representing both a center of the semi-sphere **254** and a location of a distal-most tip of the ideal surgical instrument. The semi-sphere **254** can thus represent calibration movement data (e.g. predetermined instrument coordinates) of an ideal surgical instrument with the predefined instrument axis **250** and the ideal tip **252**, and the center **256** of the semi-sphere can represent a location in 3-dimensional space of the distal-most end of the ideal tip **252**. While steps to actually create such a model are discussed above, in some embodiments the calibration movement data (e.g. predetermined instrument coordinates) can be provided initially such that no extensive modeling of an ideal surgical instrument is required.

(56) Returning to the surgical instrument **200**, the circular shape **240** of movement of the surgical instrument **200** above the pivot point **110** represents similar motion to the circle **257** of movement above the fixed pivot point **256** that defines ideal or predefined motion of an ideal version of the surgical instrument. The circular shape **240** of movement of the surgical instrument **200** is defined by data points **260** captured by the monitoring system **300** of movement of the orientation array **220**. The points **260** illustrated in FIG. **13B** represent coordinates of movement of the orientation array **220** (and thus of the surgical instrument **200**) in 3-dimensional space with respect to the pivot point **110** during calibration. The data points **260** thus represent similar coordinates to the points **258** that define ideal orientation array movement during calibration. As such, the points **260** can be used to model virtual representations **262** of the elongate shaft **204** of the surgical instrument **200** in a plurality of poses corresponding to a plurality of poses of the elongate shaft **204** during actual pivoting, as illustrated in FIG. **13C**. The virtual representations **262** can be determined because they extend from the points **260**, which represent movement of the orientation array **220** of the instrument **200**, and they terminate in a common virtual distal tip **264**, which represents the curved distal tip **210** as it pivots in the pivot point **110**. During pivoting, the recorded points **260** are all at a same distance away from the pivot point **110** because an overall length of the elongate shaft **204** of the instrument **200** does not change during calibration. This is similar to the ideal surgical instrument in which the predefined instrument axis **250** defines a distance away from the fixed pivot point **256** at which the points **258** are positioned in the ideal instrument. The monitoring system **300** and/or the control system **400** can then mathematically match a semi-sphere **266** to the recorded points **260**, as illustrated in FIG. **13D** and similar to the semi-sphere **254** of the ideal instrument. Movement of the actual surgical instrument **200** and recorded points **260** may not represent a perfect semi-sphere because measurements are being made in an actual operating setting and the curved distal tip **210** may be warped or bent. The semi-sphere **266** can thus be a best-fit sphere to the points **260**, and the predefined instrument axis **250** can be used as an initial sphere radius to help determine a sphere fit if needed. A center **268** of the semi-sphere **266** represents a location of the distal-most end **212** of the curved distal tip **210** because it was stationary in the pivot point **110** while the instrument **200** pivoted about that point. This is similar to the fixed point **256** representing both the center of the ideal semi-sphere **254** and the location of the distal-most tip of the ideal surgical instrument. The center **268** can thus correspond to the actual curved distal tip **210** with any warping or bending thereon.

(57) The monitoring system **300** and/or the control system **400** can then map or transpose the semi-sphere **266** of the actual curved distal tip **210** onto the ideal semi-sphere **254** of the ideal tip **252**, as

illustrated in FIG. 13E. The system(s) **300, 400** can compare the semi-spheres **254, 266** to one another while placing the centers **268, 256** of the semi-spheres **254, 266** at a same or shared coordinate point. The centers **268, 256** of the semi-spheres **254, 266** can be placed at the same coordinate point because they represent the pivot point **110** and the fixed point **256** about which the surgical instrument **200** and the ideal surgical instrument were pivoted. If the semi-spheres **254, 266** correspond perfectly relative to each other, then the system(s) **300, 400** can determine that there is no warping or bending of the distal tip **210** from the ideal tip **252** because there is no deviation between the semi-spheres **254, 266**. If there is any deviation between the two semi-spheres **254, 266**, the monitoring system **300** and/or the control system **400** can determine that there is bending or warping in the distal tip **210** because calibration motion of the surgical instrument **200** does not correspond exactly to that of an instrument with the ideal tip **252**. Additionally, the amount of deviation can be determined because these spheres **254, 266** are modeled in the same 3-dimensional coordinate system **130**. As such, any deviation of the measured semi-sphere **266** (representing the measured instrument coordinates) from the ideal semi-sphere **254** (representing the predetermined instrument coordinates) thus correlates to any bending or warping of the actual curved distal tip **210** from the ideal distal tip **252**. This correlated deviation can then be used to update the virtual model of the curved distal tip **210** to more accurately represent any bending or warping measured during calibration. As one illustrative example, the ideal semi-sphere **254** has a larger radius than the illustrated measured semi-sphere **266** in FIG. 13E. As such, this deviation indicates that the curved distal tip **210** has been bent toward the orientation array **220**, which reduces a distance between the distal tip **210** and the orientation array **220** and thus causes a shorter or smaller radius of the measured semi-sphere **266**. Based on the amount of deviation between the radius of the ideal semi-sphere **254** and the radius of the measured semi-sphere **266**, the degree or amount by which the curved distal tip **210** has been bent toward the orientation array **220** can be determined. Once any deviation is calculated, the system(s) **300, 400** can update the virtual model of the curved distal tip **210** so that it accurately represents the 3-dimensional location of its distal-most end **212** with any bending or warping at step **608**. The updated virtual model provides a more accurate representation of the surgical instrument **200**, providing better surgical results to a surgeon because the instrument **200** can be accurately represented while also not requiring disposal of a surgically-acceptable instrument because of minor bending. The updated virtual model can also be created through a single-step process of rotating the surgical instrument **200** in the pivot point **110** rather than any multi-stage process involving multiple measurements and calibration instruments.

(58) The monitoring system **300** and/or the control system **400** can provide the updated virtual representation of the surgical instrument **200** with any warping of the curved distal tip **210** in step **610** to the surgeon and/or a surgical system through a variety of means, for example by being displayed on various displays for the surgeon, by being modeled as a virtual 3-dimensional image in real time, by being provided to a computer-assisted surgical system, by being provided to a robotic surgical system, etc. As illustrated in FIG. 5, updating a virtual representation of the surgical instrument **200** with any warping of the curved distal tip **210** can thus include updating the virtual representation **275** of the surgical instrument **200** with the plurality of data points defining the shape and orientation of the surgical instrument **200** and the curved distal tip **210** by saving new values of the plurality of data points based on the calculated deviation to a memory, such as the memory **420** of the control system **400**. As noted above, the monitoring system **300** and/or the control system **400** can be directly incorporated into various computer-assisted surgical systems and/or robotic surgical systems in other embodiments. In some embodiments, the surgeon can then perform an operation, such as a minimally-invasive surgery, on a patient using the updated virtual representation **275** of the surgical instrument **200**. The calibration process discussed herein can be repeated as needed, and the predefined and/or ideal values discussed herein can represent either values from instruments that have not experienced any bending or warping or values from

previously-performed calibration processes that represent some previous bending or warping but may need to be updated for continued accurate use.

(59) FIGS. 14-17B illustrate another embodiment of a surgical instrument **700** similar to the surgical instrument **200** with an elongate shaft **704** extending from a handle **702** and a curved distal tip **710** on a distal end of the elongate shaft **704**. Like surgical instrument **200**, surgical instrument **700** can be calibrated such that an accurate virtual representation of at least an axis of the elongate shaft **704** and the actual curved distal tip **710** can be generated that accurately reflects bends or distortions of the curved distal tip **710** and provided to a computer or robotic surgical system, such as the monitoring system **300**. The instrument **700** can be calibrated through interaction with the calibration instrument **100** and the monitoring system **300**.

(60) The surgical instrument **700** has an orientation array **720** attached thereto, similar to array **220**, that can be tracked by the monitoring system **300**, similar to arrays **120**, **220** discussed in detail above, and to have a predefined arrangement known to the monitoring system **300** such that it can provide a predefined 3-dimensional instrument coordinate system, similar to the coordinate system **230**. However, while the orientation array **220** is configured to remain in one fixed orientation after calibration, the orientation array **720** can be rotated to a predefined plurality of different known orientations during use without requiring recalibration by the monitoring system **300** and the calibration instrument **100**. Because the plurality of different known orientations are provided to the monitoring system **300** during initial calibration, the monitoring system **300** and/or the control system **400** can be configured to determine an orientation and update a virtual representation of the surgical instrument **700** during use when the orientation array **720** is moved into a different one of the plurality of known orientations than the one used during initial calibration. The surgical instrument **700** can therefore be configured for use in a plurality of different orientations with the curved distal tip **710** being rotated as needed during surgery while being able to rotate the orientation array **720** to one of the plurality of different known orientations to ensure the orientation array **720** is still visible to the monitoring system **300** without blocking the view and without having to recalibrate the instrument **700**, as illustrated in FIGS. 17A and 17B. For example, the orientation array **720** has three targets **722a**, **722b**, **722c** thereon that can be imaged in a similar manner to the targets **122a**, **122b**, **122c** and the targets **222a**, **222b**, **222c**. The orientation array **720** is coupled to the surgical instrument **700** in one of four known and predefined orientations by engaging an array interface **725** at one end of an orientation arm **724** with a predefined length that has an orientation ring **726** disposed at an opposite end, as illustrated in FIG. 15. The orientation ring **726** couples onto the instrument **700** through engagement with a ring coupling **728** disposed at a proximal end of the handle **702**, and as illustrated in FIG. 16, the ring coupling **728** has a generally circular engagement surface **730** that is configured to interact with the ring coupling **728** of the orientation array **720** and has four notches **732a**, **732b**, **732c**, **732d** formed therein. The orientation ring **726** interacts with the four notches **732a**, **732b**, **732c**, **732d** such that the orientation ring **726** can engage with each notch in turn and remain in a temporarily-fixed orientation with respect to the surgical instrument **700** with respect to one of the notches **732a**, **732b**, **732c**, **732d**. For example, it can have four corresponding protuberances (not shown) on an inner surface of the orientation ring **726** that are configured to engage the four notches **732a**, **732b**, **732c**, **732d**. The ring **726** can also be opened by an engagement mechanism **726a** and a hinge **726b** such that the orientation ring **726** can be opened, rotated, and reengaged with the notches as desired. In use, the orientation ring **726**, and thus the orientation array **720** extending therefrom, can engage with the notch **732a** during calibration and initial use such that the orientation array **720** is visible to the monitoring system **300**, as illustrated in FIG. 17A. However, during use, the orientation ring **726** can be disengaged from the notch **732a** and rotated 180 degrees about the elongate shaft **704** of the surgical instrument **700** and to reengage the ring coupling **728** at the notch **732c**, thus rotating the orientation array **720** coupled thereto around to an opposite side of the surgical instrument **700** during use, as illustrated in FIG. 17B. Because of this rotation, the curved distal tip **710** of the

surgical instrument **700** can be applied to a different boney structure in a patient while the orientation array **720** can remain visible to the monitoring system **300** to allow continued tracking. While four notches **732a**, **732b**, **732c**, **732d** are illustrated herein, any number and type of engagement point is possible to allow an orientation array to be rotated to a predefined plurality of different known orientations.

(61) Calibration of the instrument **700** is performed through the same process as instrument **200** discussed above, which involves rotation in the pivot point **110** of the calibration instrument **100** and tracking of the monitoring system **300** to generate an accurate virtual representation of the surgical instrument **700** and the curved distal tip **710**. However, monitoring system **300** and/or the control system **400** is provided with the predefined plurality of different known orientations of the orientation array **720**, such as four in the illustrated embodiment, and each orientation is uniquely identified, such as orientations in notches **732a**, **732b**, **732c**, **732d**. As the orientation is changed during use, as illustrated in FIGS. **17A** and **17B** when the instrument **700** is used on vertebra of the patient **10**, the monitoring system **300** and/or the control system **400** is provided with the unique identifier of the new orientation so that the monitoring system **300** and/or the control system **400** can determine a new location and pose of the surgical instrument **700** and its curved distal tip **710** based on the new designated orientation, such as when the orientation array **720** is moved from the orientation in notch **732a** in FIG. **17A** to the orientation in notch **732c** in FIG. **17B**. Because the monitoring system **300** and/or the control system **400** knows the fixed orientations at notches **732a**, **732b**, the monitoring system **300** and/or the control system **400** can update a virtual representation of the overall orientation or pose of the surgical instrument **700** without having to recalibrate the instrument **700**, for example by updating a plurality of data points of the virtual representation defining the surgical instrument **700**. After changing the orientation of the orientation array **720**, the identity of the new designated orientation can be provided to the monitoring system **300** and/or the control system **400** during use in a variety of ways. For example, the instrument **700** can have various markings, flags, sensors, engagements, patterns, etc. on the handle **702**, the shaft **704**, the orientation ring **726**, the ring coupling **728**, etc. that can either electronically or visually indicate to the monitoring system **300** and/or the control system **400** the change. The information can also be input to the monitoring system **300** and/or the control system **400** manually, such as by the surgeon or an assistant.

(62) While instruments with protruding distal-most tips have been illustrated, in other embodiments, instruments having a cavity or void at a distal end thereof can also be calibrated with a calibration instrument having a protuberance, cone, sphere, etc. for using the same method as discussed above. FIGS. **18-20** illustrate a surgical instrument **800** similar to instruments **200**, **700**. The surgical instrument **800** has an elongate shaft **804** extending from a handle **802** and a straight distal tip **810** having a cavity **810a** defined therein on a distal end of the elongate shaft **804**. The cavity **810a** is in the shape of an inverse cone, however a variety of different instruments with different cavities can be used, such as oval, semi-spherical, cylindrical, curved, etc. The surgical instrument **800** has an orientation array **820** attached thereto, similar to arrays **220**, **720**, that can be tracked by the monitoring system **300**. Thus, surgical instrument **800** can be calibrated similar to surgical instruments **200**, **700** such that an accurate virtual representation of at least an axis of the elongate shaft **804** and the actual distal tip **810** can be generated that accurately reflects any bends or distortions of the distal tip **810** and can be provided to a computer or robotic surgical system, such as the monitoring system **300**.

(63) Furthermore, the instrument **800** can be calibrated through interaction with a calibration instrument **900**, similar to calibration instrument **100**. The calibration instrument **900** has a calibration reference array **920** thereon, similar to array **110**, that can be tracked by the monitoring system **300**. The instrument **900** also has a pivot point **910**, similar to pivot point **110**, about which the instrument **800** can be pivoted and rotated for calibration, similar to the calibration process discussed above. The pivot point **910** protrudes from an upper surface of the calibration instrument

900 and is in the shape of a cone that is inserted into the cavity **810a** of the distal tip **810** on the instrument **800**, as illustrated by the arrow in FIG. **19**. However, any protruding shape can be used to correspond to a particular cavity on a surgical instrument to be calibrated, such as semi-spheres, cylinders, prisms, etc. Once the distal tip **810** of the surgical instrument **800** is engaged with the calibration instrument **900**, the instrument **800** is rotated thereabout for calibration, as illustrated by the arrow in FIG. **20** and similar to the process discussed above.

(64) All of the devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the devices can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the devices, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the devices can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the devices can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

(65) It is preferred that devices disclosed herein be sterilized before use. This can be done by any number of ways known to those skilled in the art including beta or gamma radiation, ethylene oxide, steam, and a liquid bath (e.g., cold soak). An exemplary embodiment of sterilizing a device including internal circuitry is described in more detail in U.S. Pat. Pub. No. 2009/0202387 filed Feb. 8, 2008 and entitled "System And Method Of Sterilizing An Implantable Medical Device." It is preferred that device, if implanted, is hermetically sealed. This can be done by any number of ways known to those skilled in the art.

(66) Further, in the present disclosure, like-named components of the embodiments generally have similar features, and thus within a particular embodiment each feature of each like-named component is not necessarily fully elaborated upon. Additionally, to the extent that linear or circular dimensions are used in the description of the disclosed systems, devices, and methods, such dimensions are not intended to limit the types of shapes that can be used in conjunction with such systems, devices, and methods. A person skilled in the art will recognize that an equivalent to such linear and circular dimensions can easily be determined for any geometric shape. Sizes and shapes of the systems and devices, and the components thereof, can depend at least on the anatomy of the subject in which the systems and devices will be used, the size and shape of components with which the systems and devices will be used, and the methods and procedures in which the systems and devices will be used.

(67) Additionally, it is understood that one or more of the systems and methods herein, or aspects thereof, may be executed by at least one processor. The processor may be implemented in various devices, as described herein. A memory configured to store program instructions may also be implemented in the device(s), in which case the processor can be specifically programmed to execute the stored program instructions to perform one or more processes, which are described further herein. Moreover, it is understood that the methods may be executed by a specially designed device, a mobile device, a computing device, etc., comprising the processor, in conjunction with one or more additional components, as described in detail herein.

(68) Furthermore, the systems and methods, or aspects thereof, of the present disclosure may be embodied as non-transitory computer readable media on a computer readable medium containing executable program instructions executed by the processor. Examples of the computer readable mediums include, but are not limited to, ROM, RAM, compact disc (CD)-ROMs, magnetic tapes, floppy disks, flash drives, smart cards, and optical data storage devices. The computer readable recording medium can also be distributed in network-coupled computer systems so that the

computer readable media is stored and executed in a distributed fashion, for example by a cloud-based system, a telematics server, a Controller Area Network (CAN), etc.

(69) One skilled in the art will appreciate further features and advantages of the described devices and methods based on the above-described embodiments. Accordingly, the present disclosure is not to be limited by what has been particularly shown and described, except as indicated by the appended claims. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

Claims

1. An instrument calibration system, comprising: a surgical instrument having an elongate shaft with a proximal end and a distal end, the distal end having a distal tip, the proximal end having an orientation element fixed in an initial position thereon; a calibration instrument having a pivot point thereon configured to receive the distal-most tip of the surgical instrument for pivoting thereabout, the calibration instrument having a predefined geometric structure and a calibration reference element attached thereto; and a monitoring system configured to map coordinates of the orientation element relative to the calibration reference element as the surgical instrument is moved with the distal-most tip of the surgical instrument positioned at the pivot point of the calibration instrument, the monitoring system being configured to calculate a deviation of the mapped coordinates of the orientation element from a plurality of corresponding reference coordinates of a predefined surgical instrument according to manufacturing parameters and having a predefined distal tip, and being configured to modify, based on the calculated deviation, a virtual representation of the predefined surgical instrument on a display to depict a virtual representation of the surgical instrument, wherein the mapped coordinates of the orientation element and the plurality of corresponding reference coordinates are characterized by respective first and second semi-spheres, and wherein the calculated deviation corresponds to a difference in form between the first and second semi-spheres.
2. The instrument calibration system of claim 1, wherein the distal tip is curved.
3. The instrument calibration system of claim 1, wherein the calculated deviation corresponds to a degree of curvature in the distal tip.
4. The instrument calibration system of claim 1, wherein a calculated deviation corresponds to a curve in a distal-most tip of the surgical instrument.
5. The instrument calibration system of claim 1, wherein the monitoring system is configured to determine an initial orientation of the orientation element with respect to the surgical instrument while the orientation element remains in a fixed position relative to the surgical instrument.
6. The instrument calibration system of claim 5, wherein the monitoring system is configured to determine an actual orientation of the surgical instrument while the orientation element on the proximal end thereof is moved to one of a plurality of second positions different than the initial position.
7. The instrument calibration system of claim 1, wherein the pivot point of the calibration element comprises a plurality of removable and replaceable pivot points.
8. The instrument calibration system of claim 7, wherein each of the plurality of removable and replaceable pivot points corresponds to a different type of distal tip usable with the surgical instrument.
9. The instrument calibration system of claim 1, wherein the pivot point protrudes from the calibration element, and wherein the distal tip has a corresponding cavity shaped and sized to receive the protruding pivot point.
10. The instrument calibration system of claim 1, wherein the orientation element can be configured to move to a plurality of secondary positions from the fixed initial position.
11. The instrument calibration system of claim 10, wherein the monitoring system is configured to

identify the plurality of secondary positions of the orientation element.

12. The instrument calibration system of claim 10, wherein the monitoring system is configured to update the virtual representation to correspond to one of the plurality of secondary positions.
