

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12404013
B2
September 02, 2025
Maalioune; Hakim et al.

System for managing the deceleration of an aircraft on a runway on the ground and associated method

Abstract

A system for managing the deceleration of an aircraft enabling the control in real time of the position of the aircraft on a braking axis, includes a braking system; a calculator configured to: calculate, from aircraft data and from external data, a sequence of use of the braking system intended to brake the aircraft over a predetermined braking distance which associates a predetermined position on the braking axis with each braking instant; update in real time the sequence of use as a function of the difference between the position of the aircraft and the predetermined position; and a controller configured to control the braking system as a function of the sequence of use.

Inventors:	Maalioune; Hakim (Moissy-Cramayel, FR), Miralles; Laurent Christian Vincent Roger (Moissy-Cramayel, FR), Bastide; Christophe (Moissy-Cramayel, FR), Fert; Jérémy Edmond (Moissy-Cramayel, FR), Hupin; Vincent (Moissy-Cramayel, FR)
Applicant:	SAFRAN AIRCRAFT ENGINES (Paris, FR); SAFRAN ELECTRONICS & DEFENSE (Boulogne-Billancourt, FR); SAFRAN LANDING SYSTEMS (Velizy-Villacoublay, FR); SAFRAN NACELLES (Gonfreville-l'Orcher, FR)
Family ID:	71662013
Assignee:	SAFRAN AIRCRAFT ENGINES (Paris, FR); SAFRAN ELECTRONICS & DEFENSE (Boulogne-Billancourt, FR); SAFRAN LANDING SYSTEMS (Velizy Villacoublay, FR); SAFRAN NACELLES (Gonfreville-l'Orcher, FR)
Appl. No.:	17/913386
Filed (or PCT Filed):	March 18, 2021
PCT No.:	PCT/FR2021/050446

PCT Pub. No.: WO2021/191530

PCT Pub. Date: September 30, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230137045 A1	May. 04, 2023

Foreign Application Priority Data

FR	2003016	Mar. 27, 2020
----	---------	---------------

Publication Classification

Int. Cl.: B64C25/42 (20060101); B64C19/02 (20060101); G08G5/25 (20250101); G08G5/26 (20250101)

U.S. Cl.:

CPC B64C25/426 (20130101); B64C19/02 (20130101); G08G5/25 (20250101); G08G5/26 (20250101);

Field of Classification Search

CPC: B64C (25/426); B64C (19/02); B64C (19/00); G08G (5/0008); G08G (5/0013); Y02T (50/80)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10049590	12/2017	Thiele	N/A	G08G 5/21
10131442	12/2017	Waltner	N/A	B64C 27/04
10202204	12/2018	Daidzic	N/A	G08G 5/22
11409282	12/2021	Suzuki	N/A	B64D 13/00
11724820	12/2022	Sellmann	701/16	G08G 5/34
2008/0249675	12/2007	Goodman	701/16	B64C 25/426
2009/0043434	12/2008	Deker	701/16	G05D 1/0676
2010/0079308	12/2009	Fabre	340/951	G08G 5/76
2010/0204909	12/2009	Gayraud	701/120	G05D 1/0083
2017/0183086	12/2016	Le-Bouedec	N/A	G08G 5/54
2022/0009651	12/2021	Lampazzi	N/A	B64D 45/00
2023/0137045	12/2022	Maalioune	701/3	B64C 19/00
2023/0368683	12/2022	Maalioune	N/A	G08G 5/21

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0 895 929	12/1998	EP	N/A
2 514 647	12/2011	EP	N/A

OTHER PUBLICATIONS

International Search Report as issued in International Patent Application No. PCT/FR2021/050446, dated May 26, 2021. cited by applicant

Primary Examiner: Brushaber; Frederick M

Attorney, Agent or Firm: Pillsbury Winthrop Shaw Pittman LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is the U.S. National Stage of PCT/FR2021/050446, filed Mar. 18, 2021, which in turn claims priority to French patent application number 2003016 filed Mar. 27, 2020. The content of these applications are incorporated herein by reference in their entireties.

TECHNICAL FIELD OF THE INVENTION

(2) The technical field of the invention is that of aircraft and more particularly that of systems for managing the deceleration of an aircraft on a runway on the ground.

(3) The present invention relates to a system for managing the deceleration of an aircraft on a runway on the ground and in particular a system for managing the deceleration of an aircraft on a runway on the ground enabling the control in real time of the position of the aircraft on a braking axis of the runway. The present invention also relates to a control method implemented by the system.

TECHNOLOGICAL BACKGROUND OF THE INVENTION

(4) Aircraft runway overruns are numerous, of the order of one runway overrun a month in the world, and are due, in around 25% of cases, to a poor piloting choice during a landing in degraded meteorological conditions.

(5) Faced with this, the aeronautical authorities require solutions to be put in place to reduce the number of runway overruns, and in particular the number of longitudinal runway overruns.

(6) Longitudinal runway overruns are linked to poor management of the braking means making it possible to brake the aircraft, when the conditions at the level of the runway are degraded.

(7) At present, the different braking means are managed independently of one another and manually by the pilot, since all the braking means are not automated and since the automated braking means are not automated in a compatible manner.

(8) Thus, it is the pilot who has to manage the configuration of each of the braking means. The risk of longitudinal runway overruns in the case of degraded meteorological conditions is thus high since the management of the braking means is entirely based on the pilot and his experience.

(9) There thus exists a need for a system making it possible to manage the braking means of an aircraft in deceleration phase to limit the risk of a longitudinal runway overrun.

SUMMARY OF THE INVENTION

(10) The invention offers a solution to the aforementioned problems, by proposing a system for managing the deceleration of an aircraft limiting the risk of longitudinal runway overruns.

(11) A first aspect of the invention relates to a system for managing the deceleration of an aircraft on a runway on the ground enabling the control in real time of the position of the aircraft on a braking axis of the runway, comprising: Braking means configured to brake the aircraft; A calculator configured to: Calculate, from aircraft data and from external data comprising data on

the state of the runway and meteorological data on the ground, a sequence of use of the braking means intended to brake the aircraft along the braking axis over a predetermined braking distance associated with a predetermined braking duration comprising a plurality of braking instants each associated with a predetermined position on the braking axis; Update in real time the sequence of use as a function of the difference, along the braking axis, between the position of the aircraft and the predetermined position associated with a given braking instant or the occurrence of a given event; Control means configured to control the braking means as a function of the sequence of use or an instruction sent by a runway overrun alert system of the aircraft.

(12) Thanks to the invention, the calculator calculates a sequence of use of the braking means making it possible to brake the aircraft over a predetermined braking distance along a braking axis of the runway and which takes into account, on the one hand, the data of the aircraft and, on the other hand, the data relative to the state of the runway and to the meteorological conditions on the ground. The sequence of use is next updated when a difference along the braking axis between the position of the aircraft and the predetermined position for a given braking instant is noted, due for example to a difference between the external data used for the calculation and the real external data. This updating is carried out in real time, that is to say at very close instants, so that the difference does not have the time to be accentuated in such a way that it would no longer be possible to correct the position of the aircraft along the braking axis before a longitudinal runway overrun. The braking means are controlled by the control means according to the sequence of use in the nominal case or according to an alert instruction coming from a runway overrun alert system in an emergency.

(13) Apart from the characteristics that have been set out in the preceding paragraph, the system according to a first aspect of the invention may have one or more complementary characteristics among the following, considered individually or according to all technically possible combinations thereof.

(14) According to an alternative embodiment, the braking means comprise a plurality of thrust reversers each equipped on an engine of the aircraft and a plurality of landing gears each comprising at least one wheel.

(15) According to a sub-alternative embodiment compatible with the preceding alternative embodiment, the braking means further comprise a plurality of air brakes each equipped on a wing of the aircraft.

(16) According to a first embodiment compatible with the preceding alternative embodiment, the control means comprise a single central controller.

(17) Thus, the central controller is configured to control each braking means as a function of the sequence of use or an instruction. The number of calculators and thus the mass of the control means is minimised, which notably makes it possible to limit fuel consumption.

(18) According to a second embodiment compatible with the preceding alternative embodiment, the control means comprise a central controller and a controller per braking means or per type of braking means.

(19) Thus, each controller is configured to control a single braking means, for example a given thrust reverser, or a single type of braking means, for example all of the thrust reversers, and the central controller is configured to control each of the controllers as a function of the sequence of use or an instruction. It thus suffices to equip existing aircraft with a central calculator in order that the control system is implemented.

(20) According to an alternative embodiment compatible with the preceding alternatives and embodiments, the aircraft comprises engines and in that the aircraft data comprise the speed of the aircraft and/or data of availability of the braking means and/or data of use of the engines.

(21) Thus, the calculation of the sequence of use takes into account the current speed of the aircraft and the future speed of the aircraft, through information on the braking means which could be used and the use of the engines, and thus the level of deceleration of the aircraft.

(22) According to a sub-alternative embodiment of the preceding alternative embodiment, the data of availability of a braking means comprise data relative to the state of the braking means and/or data relative to the cost of use of the braking means.

(23) Thus, the calculation of the sequence of use takes into account the operating capacity of each braking means and/or its cost of use, for example through the wear that the use causes on the braking means and/or the consumption of fuel brought about by the use of the braking means.

(24) According to an alternative embodiment compatible with the preceding alternatives and embodiments, the system comprises first communication means configured to communicate with a station on the ground.

(25) Thus, the system can obtain external data from the control tower in charge of take offs and landings on the runway, in accordance with regulations.

(26) According to an alternative embodiment compatible with the preceding alternatives and embodiments, the system comprises second communication means configured to communicate with at least one other aircraft.

(27) Thus, the calculator can use sequences of use calculated by other aircraft having previously landed or taken off on the runway and having been transmitted to it to calculate the sequence of use.

(28) A second aspect of the invention relates to a method for controlling in real time the position of an aircraft on a braking axis of a runway on the ground implemented by the system according to the first aspect of the invention, comprising the following steps: Calculating, by the calculator, from aircraft data and from external data comprising data on the state of the runway and meteorological data on the ground, a sequence of use of the braking means intended to brake the aircraft along the braking axis over a predetermined braking distance associated with a predetermined braking duration comprising a plurality of braking instants each associated with a predetermined position on the braking axis; If, at a given braking instant, the difference along the braking axis, between the position of the aircraft and the predetermined position, is above a threshold or if a given event occurs, updating, by the calculator, of the sequence of use; Implementing the sequence of use of the braking means by the control means.

(29) Thus, the sequence of use is updated when the difference between the position of the aircraft and the predetermined position on the braking axis becomes greater than a threshold value at a given braking instant.

(30) According to an alternative embodiment, the sequence of use is implemented automatically or manually.

(31) Thus, the pilot may choose to implement the sequence of use himself.

(32) According to an alternative embodiment compatible with the preceding alternative embodiment, the sequence of use is calculated in flight.

(33) Thus, if the calculator does not manage to calculate a sequence of use corresponding to the predetermined braking distance, for example because the predetermined braking distance is too short given the speed of the aircraft and its braking means, the calculator can trigger an instruction for rejection of landing or take off.

(34) A third aspect of the invention relates to a computer product-programme comprising instructions which, when they are executed by a computer, lead said computer to implement the steps of the method according to the second aspect of the invention.

(35) A fourth aspect of the invention relates to a recording support readable by a computer comprising instructions which, when they are executed by a computer, lead said computer to implement the steps of the method according to the second aspect of the invention.

(36) The invention and the different applications thereof will be better understood on reading the description that follows and by examining the figures that accompany it.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) The figures are presented for indicative purposes and in no way limit the invention.
- (2) FIG. 1 shows a schematic representation of an aircraft.
- (3) FIG. 2 shows a schematic representation of the control system according to the first embodiment.
- (4) FIG. 3 shows a schematic representation of the control system according to the second embodiment.
- (5) FIG. 4 is a block diagram illustrating the steps of the control method.
- (6) FIG. 5 shows a schematic representation of the position at several instants of an aircraft equipped with the control system, on a braking axis of a runway.

DETAILED DESCRIPTION

- (7) Unless stated otherwise, a same element appearing in the different figures has a single reference.
- (8) A first aspect of the invention relates to a system for managing the deceleration of an aircraft on a runway on the ground enabling the control in real time of the position of the aircraft on a braking axis of the runway on the ground.
- (9) The objective of the invention is to avoid an aircraft runway overrun, more particularly during the landing of the aircraft. The control system thus makes it possible to stop the aircraft before it overruns the runway, that is to say to respect a predetermined braking distance along a braking axis comprised in the runway.
- (10) "Braking distance" is taken to mean the distance travelled by the aircraft along a braking axis, between its landing on the runway and its stoppage on the runway, that is to say the distance travelled by the aircraft for a braking duration comprising a plurality of braking instants comprised between the instant at which the aircraft lands on the runway and the instant at which the aircraft stops on the runway.
- (11) The invention may also be implemented in the case of a rejection of take off, for example when the aircraft does not have sufficient speed to take off and has to brake urgently to prevent a runway overrun. The braking distance is then the distance travelled by the aircraft between the instant at which at least one first braking means is activated and the instant at which the aircraft stops on the runway.
- (12) The predetermined braking distance is the distance travelled by the aircraft along a braking axis, for a predetermined braking duration comprising a plurality of instants each associated with a predetermined position on the braking axis corresponding to the position at which the aircraft should be at the given braking instant in order that the aircraft stops at the predetermined braking distance.
- (13) FIG. 5 shows a schematic representation of the position at several braking instants, of an aircraft equipped with the control system, over a braking axis **402** on a runway **400**.
- (14) In FIG. 5, the predetermined braking distance **401** is along a longitudinal braking axis **402** passing through the middle of the runway **400** and is associated with a braking duration comprising 9 braking instants, each corresponding to a predetermined position **X1'**, **X2'**, **X3'**, **X4'**, **X5'**, **X6'**, **X7'**, **X8'**, **X9'** on the braking axis **402**.
- (15) In the case of landing, the predetermined braking distance **401** is for example the distance between the landing point of the aircraft on the runway **400** and the distance corresponding to a given percentage of the runway **400**, such as for example three quarters of the runway **400** or seven eighths of the runway **400**.
- (16) The predetermined braking distance **401** may also depend on the state of the runway **400**, for example zones being able to influence the braking of the aircraft, such as zones having hollows or

bumps liable to slow down the aircraft or instead the coefficient of friction of the runway **400** supplied by a control tower on the ground.

(17) The predetermined braking distance **401** is for example determined from performance abacuses of the aircraft **100** giving a braking distance as a function of the configuration of the braking means.

(18) “Control in real time of the position of the aircraft on a braking axis” is taken to mean that the data relative to the position of the aircraft are processed immediately after their acquisition, and that the duration between the acquisition of the position data and the production of control instructions making it possible to adjust the real position of the aircraft on the predetermined position at a given braking instant is reduced to the minimum. The duration is for example of the order of 2.5 to 20 ms.

(19) FIG. 2 shows a schematic representation of the control system **200** according to a first embodiment.

(20) FIG. 3 shows a schematic representation of the control system **200** according to a second embodiment.

(21) As illustrated in FIG. 2, the control system **200** comprises: Braking means **110**; A calculator **201**; Control means **210** comprising at least one central calculator **211**.

(22) The braking means **110** are configured to brake the aircraft, that is to say to decrease the speed of the aircraft.

(23) FIG. 1 shows a schematic representation of an aircraft **100**.

(24) As illustrated in FIG. 1, the braking means **110** comprise a plurality of thrust reversers **111** and a plurality of landing gears **112**. The aircraft **100** comprises a plurality of engines **1110**. Each thrust reverser is mounted on an engine **1110** but each engine **1110** is not necessarily equipped with a thrust reverser **111**. The landing gear **112** comprises at least one wheel.

(25) The aircraft **100** then comprises a first type of braking means **110** corresponding to the thrust reversers **111** and a second type of braking means **110** corresponding to the landing gears **112**.

(26) The braking means **110** may also comprise a plurality of air brakes **113**, as in FIG. 1, each wing of the aircraft **100** being equipped with at least one air brake **113**.

(27) The aircraft **100** then further comprises a third type of braking means **110** corresponding to the air brakes **113**.

(28) The calculator **201** is configured to calculate a sequence of use of the braking means **110** making it possible to brake the aircraft **100** over the predetermined braking distance **401**.

(29) “Sequence of use of the braking means **110**” is taken to mean an ordered series of use of the braking means **110** comprising the activation/deactivation of the different braking means **110** and their characteristics of use, such as for example the use power for the thrust reversers **111**, the level of deceleration for the landing gears **112** or the angle for the air brakes **113**.

(30) If the example is taken of an aircraft **100** landing at one end of a runway **400** and parking at the other end of the runway **400**, the sequence of use comprises for example, between the landing point of the aircraft **100** and the middle of the runway **400**, the use of thrust reversers **111** with a given first power and air brakes **113** according to a given angle, then, between the middle of the runway and the parking point, the use of the landing gears **112** with a given level of deceleration and the thrust reversers **111** with a given second power.

(31) The sequence of use is for example calculated in flight before landing or at the moment of landing of the aircraft **100**, during the first contact between the runway **400** and the aircraft **100**.

(32) The sequence of use is for example calculated on the ground at the moment of take off.

(33) In the case where the sequence of use is calculated in flight, if the calculator **201** does not manage to calculate a sequence of use which does not lead to a runway overrun of the aircraft **100**, for example because the predetermined braking distance **401** is too short given the speed of the aircraft **100** and/or the braking means **110** of the aircraft **100**, the calculator **201** can generate an alert advising the pilot not to land.

- (34) The sequence of use is calculated from aircraft data, that is to say data relative to the aircraft, and external data, that is to say data relative to conditions external to the aircraft **100**.
- (35) The external data comprise data relative to the state of the runway **400**, for example the coefficient of friction of the runway **400**, and data relative to the meteorological conditions at the level of the runway **400**, for example the force and the direction of the wind.
- (36) The external data are for example obtained from a control tower on the ground in charge of the runway **400**. In this case, the system **200** comprises first communication means **2021** making it possible to communicate with the control tower and generally speaking with a station on the ground.
- (37) The aircraft data comprise for example the speed of the aircraft **100**, data relative to the availability of the braking means **110**, for example if a given braking means **110** is out of order or operational and/or data relative to the use by the aircraft **100** of its engines **1110**, for example the power delivered by each engine **1110**.
- (38) The data relative to the availability of a certain braking means **110** comprise data relative to the state of the braking means **110**, for example if the braking means **110** are operational or are out of order or instead the level of wear of the braking means **110**, and/or data relative to the cost of use of the braking means **110**, for example the consumption of fuel linked to the use of the braking means **110** or instead the cost of replacing the braking means **110**.
- (39) The choice of the aircraft data used to calculate the sequence of use is for example made by the pilot or by the airline company.
- (40) The sequence of use may also be calculated from data coming from other aircraft **100**, for example aircraft **100** having already landed on the runway **400**. In this case, the system **200** comprises second communication means **2022** making it possible to communicate with other aircraft **100**.
- (41) The calculator **201** is also configured to update the sequence of use in real time as a function of the difference between the position of the aircraft **100** and the predetermined position **401** along the braking axis **402** at a given braking instant.
- (42) For example, if the example developed previously is reconsidered, if a wind pushes the aircraft **100** forwards with an intensity above the provided for intensity, that is to say above the intensity that had been used to calculate the sequence of use, the sequence of use is for example updated to compensate for the intensity of the wind, for example by increasing the power of the thrust reversers **111**.
- (43) The calculator **201** is also configured to update the sequence of use as a function of a given event. The event is for example the breakdown of a braking means **110** used in the sequence of use, or instead the breakdown of an engine **1110**.
- (44) The control means **210** are configured to control the braking means **110** as a function of the sequence of use or an instruction coming from a runway overrun alert system.
- (45) The runway overrun alert system is for example a ROAAS (Runway Overrun Alert and Awareness System) equipped on the aircraft **100**.
- (46) The instruction is for example to implement a maximum braking sequence when a danger has been detected.
- (47) According to the first embodiment of the system **200** illustrated in FIG. 2, the control means **210** comprise a single central controller **211** configured to control all of the braking means **110**.
- (48) According to the second embodiment of the system **200**, the control means **210** comprise a central controller **211** and a controller **212** per braking means **110** or per type of braking means **110** configured to control the braking means or the type of braking means on instruction of the central controller **211**.
- (49) In FIG. 3, the control means **210** comprise a central controller **211**, a controller **212-1** configured to control the thrust reversers **111**, a controller **212-2** configured to control the landing gears **112** and a controller **212-3** configured to control the air brakes **113**.

(50) A second aspect of the invention relates to a method for controlling in real time the position of the aircraft on the braking axis **402** implemented by the system **200** according to the first aspect of the invention.

(51) FIG. **4** is a block diagram illustrating the steps of the method **300** according to the second aspect of the invention.

(52) A first step **301** of the method **300** implemented by the calculator **201**, consists in calculating the sequence of use of the braking means **110** as a function of aircraft data and external data.

(53) If, for a braking instant of the predetermined braking duration, a first condition **C1** is realised, that is to say if the difference along the braking axis **402**, between the position **X1**, **X2**, **X3**, **X4**, **X5**, **X6**, **X7**, **X8**, **X9** of the aircraft **100** and the predetermined position **X1'**, **X2'**, **X3'**, **X4'**, **X5'**, **X6'**, **X7'**, **X8'**, **X9'** associated with the braking instant is above a threshold **S1**, a second step **302** of the method **300** is realised.

(54) If the first condition **C1** is not realised, a third step **303** of the method is realised.

(55) The threshold **S1** is chosen in such a way that it is still possible to correct the position of the aircraft **100** on the braking axis **402** before a longitudinal runway overrun.

(56) The threshold **S1** is for example the value zero.

(57) The second step **302** of the method **300** implemented by the calculator **201**, consists in updating the sequence of use. Thus, if for example, at a given braking instant, the position **X1**, **X2**, **X3**, **X4**, **X5**, **X6**, **X7**, **X8**, **X9** of the aircraft **100** is further on the runway than the predetermined position **X1'**, **X2'**, **X3'**, **X4'**, **X5'**, **X6'**, **X7'**, **X8'**, **X9'**, for example because the intensity of the wind pushing the aircraft **100** forwards has been underestimated, the sequence of use is updated to brake the aircraft **100** more.

(58) The second step **302** of the method **300** is followed by the third step **303**.

(59) A third step **303** of the method **300** implemented by the control means **210**, consists in implementing the sequence of use on the braking means **110**.

(60) The implementation of the sequence of use of the braking means **110** may be carried out automatically or manually by the pilot of the aircraft **100**.

(61) In the case where the implementation is manual, indications could be provided to assist the pilot.

(62) An exemplary embodiment is illustrated in FIG. **5**. The position of an aircraft **100** along the braking axis **402** is represented therein at several instants, a point **Xi** corresponding to a position of the aircraft **100** at a given instant.

(63) In FIG. **5**, the aircraft **100** lands at a point **X1** of the runway **400**. The sequence of use of the braking means **100** has been calculated in flight to enable the aircraft **100** to brake over the predetermined braking distance **401**.

(64) At each instant, it is verified if the first condition **C1** is realised. At the instant corresponding to the point **X2**, the difference between the position **X2** of the aircraft **100** and the predetermined position **X2'** along the braking axis **402** is below the threshold **S1**. The sequence of use is thus not updated and the control means **210** thus implement the sequence of use calculated in flight.

(65) At the instant corresponding to the point **X3**, the difference along the braking axis **402** between the position **X3** of the aircraft **100** and the predetermined position **X3'** is above the threshold **S1**. The sequence of use is thus updated. From the instant corresponding to the point **X4**, the control means **210** implement the sequence of use updated at point **X3**.

(66) Up to the instant corresponding to the point **X9**, parking point, the difference along the braking axis **402** between the position **X4**, **X5**, **X6**, **X7**, **X8**, **X9** of the aircraft **100** and the predetermined position **X4'**, **X5'**, **X6'**, **X7'**, **X8'**, **X9'** is below the threshold **S1** and the sequence of use is thus not updated between the instant corresponding to the point **X3** and the parking of the aircraft **100**.

Claims

1. A system for managing a deceleration of an aircraft on a runway on the ground enabling a control in real time of a position of the aircraft on a braking axis of the runway, comprising: a braking system configured to brake the aircraft; a calculator configured to: calculate, from aircraft data and from external data comprising data on a state of the runway and meteorological data on the ground, a sequence of use of the braking system of the aircraft on the ground intended to brake the aircraft along the braking axis, over a predetermined braking distance associated with a predetermined braking duration comprising a plurality of braking instants each associated with a predetermined position on the braking axis, the sequence of use of the braking system being defined as an ordered series of use of the braking system between a landing point and a parking point of the aircraft, comprising activation/deactivation of the braking system and its characteristics of use; update in real time, the sequence of use as a function of the difference, along the braking axis, between the position of the aircraft and the predetermined position associated with a given braking instant, or the occurrence of a given event; a controller configured to control the braking system as a function of the sequence of use or an instruction sent by a runway overrun alert system of the aircraft.
2. The system according to claim 1, wherein the braking system comprises a plurality of thrust reversers each equipped on an engine of the aircraft and a plurality of landing gears each comprising at least one wheel.
3. The system according to claim 2, wherein the braking system further comprises a plurality of air brakes each equipped on a wing of the aircraft.
4. The system according to claim 1, wherein the controller comprises a single central controller.
5. The system according to claim 1, wherein the controller comprises a central controller and a controller per braking system or per type of braking system.
6. The system according to claim 1, wherein the aircraft comprises engines and wherein the aircraft data comprises a speed of the aircraft and/or data of availability of the braking system and/or data of use of the engines.
7. The system according to claim 6, wherein the data of availability of a braking system comprises data relative to the state of the braking system and/or data relative to the cost of use of the braking system.
8. The system according to claim 1, further comprising first communication means configured to communicate with a station on the ground.
9. The system according to claim 1, further comprising second communication means configured to communicate with at least one other aircraft.
10. A method for controlling in real time a position of an aircraft on a braking axis of a runway on the ground implemented by a system for managing a deceleration of the aircraft on the runway enabling a control in real time of said position of the aircraft, the system including a braking system configured to brake the aircraft, a calculator and a controller configured to control the braking system, the method comprising: calculating, by the calculator, from aircraft data and from external data comprising data on the state of the runway and meteorological data on the ground, a sequence of use of the braking system of the aircraft on the ground intended to brake the aircraft along the braking axis, over a predetermined braking distance associated with a predetermined braking duration comprising a plurality of braking instants each associated with a predetermined position on the braking axis, the sequence of use of the braking system being defined as an ordered series of use of the braking system between a landing point and a parking point of the aircraft, comprising activation/deactivation of the braking system and its characteristics of use; when, at a given braking instant, a difference along the braking axis between the position of the aircraft and the predetermined position is above a threshold or when a given event occurs, updating in real time, by the calculator, of the sequence of use; implementing the sequence of use of the braking system by the controller.

11. The method according to claim 10, wherein the sequence of use is implemented automatically.

12. The method according to claim 10, wherein the sequence of use is calculated in flight.

13. A non-transitory computer readable medium readable by a computer comprising instructions which, when executed by a computer, lead said computer to implement a method for controlling in real time a position of an aircraft on a braking axis of a runway on the ground implemented by a system for managing a deceleration of the aircraft on the runway enabling a control in real time of said position of the aircraft, the system including a braking system configured to brake the aircraft, a calculator and a controller configured to control the braking system, the method comprising: calculating, by the calculator, from aircraft data and from external data comprising data on the state of the runway and meteorological data on the ground, a sequence of use of the braking system of the aircraft on the ground intended to brake the aircraft along the braking axis, over a predetermined braking distance associated with a predetermined braking duration comprising a plurality of braking instants each associated with a predetermined position on the braking axis, the sequence of use of the braking system being defined as an ordered series of use of the braking system between a landing point and a parking point of the aircraft, comprising activation/deactivation of the braking system and its characteristics of use; when, at a given braking instant, a difference along the braking axis between the position of the aircraft and the predetermined position is above a threshold or when a given event occurs, updating in real time, by the calculator, of the sequence of use; implementing the sequence of use of the braking system by the controller.
