

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406046
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Gottschalk; Richard et al.

System and method for authentication on a device

Abstract

A method for the authentication on a device includes a step of providing a certificate, the certificate enabling a limited number N of authentication processes. The method further includes a step of carrying out an authentication process on the device, and a step of reducing the number N of authentication processes that are still possible for the certificate.

Inventors:	Gottschalk; Richard (Regensburg, DE), Rehberg; Andreas (Nittendorf, DE)
Applicant:	BSH Hausgeraete GmbH (Munich, DE)
Family ID:	71401799
Assignee:	BSH Hausgeraete GmbH (Munich, DE)
Appl. No.:	17/624443
Filed (or PCT Filed):	June 30, 2020
PCT No.:	PCT/EP2020/068329
PCT Pub. No.:	WO2021/001334
PCT Pub. Date:	January 07, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220350874 A1	Nov. 03, 2022

Foreign Application Priority Data

DE	102019209888.6	Jul. 04, 2019
----	----------------	---------------

Publication Classification

Int. Cl.: G06F21/33 (20130101)

U.S. Cl.:

CPC G06F21/33 (20130101);

Field of Classification Search

CPC: G06F (21/33); H04L (9/0897); H04L (9/3234); H04L (9/3263); H04L (9/3271); H04L (63/0823); H04L (2209/805)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5982898	12/1998	Hsu et al.	N/A	N/A
7278582	12/2006	Siegel	235/487	H04L 9/0897
10382461	12/2018	Sharifi Mehr	N/A	H04L 63/1425
2002/0056747	12/2001	Matsuyama et al.	N/A	N/A
2006/0085848	12/2005	Aissi	726/9	H04L 63/0869
2008/0022412	12/2007	Challener	726/27	G06F 21/62
2012/0297200	12/2011	Thom	713/189	G06F 21/602
2014/0101439	12/2013	Pettigrew	726/7	H04L 9/3268
2014/0173695	12/2013	Valdivia	726/4	G06F 21/33
2019/0268307	12/2018	Lancioni	N/A	H04L 63/0263
2019/0357023	12/2018	Park	N/A	H04W 84/18
2020/0169427	12/2019	Wu	N/A	H04N 21/43615

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101674304	12/2009	CN	N/A
102017211267	12/2018	DE	N/A

OTHER PUBLICATIONS

Sarmenta, Luis FG, et al. “Offline count-limited certificates.” Proceedings of the 2008 ACM symposium on Applied computing. 2008. (Year: 2008). cited by examiner

“Secure access module”. Wikipedia. Published Apr. 2017. Retrieved on May 29, 2024 from: https://web.archive.org/web/20170204190218/https://en.wikipedia.org/wiki/Secure_access_module. (Year: 2017). cited by examiner

“Smart card”. Wikipedia. Published Jan. 2019. Retrieved on May 29, 2024 from: https://web.archive.org/web/20190101113045/https://en.wikipedia.org/wiki/Smart_card (Year: 2019). cited by examiner

“Hardware security module”. Wikipedia. Published Jan. 2019. Retrieved on May 29, 2024 from: https://web.archive.org/web/20190104231248/https://en.wikipedia.org/wiki/Hardware_security_module (Year: 2019). cited by examiner

Yang et al., Information Security Basics, Southwest Jiaotong University Press, Jun. 2019, pp. 65-66, ISBN 978-7-5643-6910-1, Chengdu, China. cited by applicant

Background/Summary

FIELD AND BACKGROUND OF THE INVENTION

(1) The invention relates to a system and a method which enable a reliable authentication of a user on an appliance even if the appliance can not communicate with an authentication server.

(2) An IoT (Internet of Things) appliance is typically connected to a server via the Internet. A user of the IoT appliance (for example, a service engineer) can authenticate themselves on the IoT appliance, with the authenticity check mostly taking place via an authentication server. An authentication can, for example, be required to prevent unauthorized interventions on the IoT appliance.

SUMMARY OF THE INVENTION

(3) If the Internet connection of an IoT appliance is interrupted or is unavailable, a reliable and secure authentication can mostly not be carried out (as it is not possible to access the authentication server). The present document is concerned with the technical object of enabling a secure and reliable authentication on an appliance even when the appliance is not connected to an authentication server via a communication connection.

(4) The object is achieved by the subject matter of the independent claims in each instance. Advantageous embodiments are defined, in particular, in the dependent claims, described in the description below or represented in the accompanying drawings.

(5) According to one aspect of the invention, a method for authentication (of a user and/or a computer unit) on an appliance is described. The appliance, in particular the IoT appliance is preferably a household appliance, in particular a washing machine, a dryer, a food processor, a cooker, an oven, a refrigerator and/or a dishwasher.

(6) The method comprises the provision and/or the receipt of a certificate. Here, the certificate can be provided by a (certificate) server which is responsible for the administration of accesses to the appliance. The server can, for example, be made available by a manufacturer of the appliance. In addition to the certificate, (current) information relating to the appliance can be provided by the server (for example, in relation to the current status of the appliance). The information provided can lead to an increase in the quality of a subsequent access to the appliance.

(7) In order to obtain a certificate, a server authentication process can first of all be carried out on the server to authenticate the unit (for example, a computer unit and/or a user) which wants to obtain the certificate from the server. The certificate can (possibly exclusively) be provided by the server following a successful server authentication process.

(8) The certificate (provided by the server) enables a limited number N of authentication processes. The number N of possible authentication processes for the certificate when providing the certificate via the server preferably lies between 2 and 10. Limiting the authentication processes which can be enabled by a certificate can ensure a high level of security (also in the case of a lost certificate). The certificate can also be limited to a defined period of time.

(9) The method furthermore comprises carrying out an authentication process on the appliance (using the certificate). As part of the authentication process, a challenge (for example, a random number) which was sent by the appliance can be received by the unit which would like to be authenticated on the appliance. Furthermore, a response to the challenge can be generated by the unit, wherein the response depends on the challenge and the certificate. The response can then be sent to the appliance, and the appliance can authenticate the unit or reject the authentication request on the basis of the response.

- (10) The method also comprises reducing the number N of authentication processes that are still possible for the certificate. In particular, after each authentication process with which the certificate is used, the number N can be reduced (by one in each case). An unauthorized authentication on an appliance can therefore be securely prevented (even in cases where no communication connection exists between the appliance and an authentication server).
- (11) The certificate can be embodied to enable a user of the certificate to access the appliance following a successful authentication process. In this context, the certificate can be embodied to limit the access to a subset of access rights from a total set of access rights. The subset of access rights can depend on a user type of the user (for example, a user of the appliance or service personnel for the appliance and/or a developer of the appliance).
- (12) The method can comprise determining a user type from a plurality of different user types. A certificate can thereupon be provided and/or received which enables one or more of the access rights to the appliance depending on the determined user type. The security of access to an appliance can therefore be increased further.
- (13) The method can comprise checking, as part of the authentication process, whether the number N of authentication processes that are still possible is greater than zero. The authentication process on the appliance can be (automatically) rejected if it is determined that the number N of authentication processes that are still possible is not greater than zero. The validity of the certificate can therefore be reliably limited.
- (14) The certificate can be provided on a hardware security module (HSM). This ensures a reliable storage of the certificate.
- (15) In this way, the number N of authentication processes that are still possible can be reduced by means of a counter on the hardware security module to allow a particularly reliable limiting of the validity of the certificate.
- (16) The method can in particular be designed to authenticate a computer unit on the appliance. Access to the certificate (for an authentication process) can then be enabled via a communication interface (for example, via a USB interface) between the computer unit and the hardware security module. The certificate can therefore be made available for use in a reliable and convenient manner.
- (17) According to one aspect of the invention, a system for authentication (of a user or a computer unit) on an appliance is described. The system is embodied to provide a certificate, wherein the certificate enables a limited number N of authentication processes. The system is furthermore embodied to carry out an authentication process on the appliance (using the certificate) and to reduce the number N of authentication processes that are still possible for the certificate.
- (18) It should be noted that any aspects of the system and/or method described in this document can be combined with one another in a wide variety of ways. In particular, the features of the claims can be combined with one another in a variety of ways.
-

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) The invention will now be described in greater detail making reference to the exemplary embodiments illustrated in the drawings. In the drawings:
- (2) FIG. 1 shows a block diagram of a system for authenticating a user on an appliance;
- (3) FIG. 2 shows an exemplary sequence of an authentication process on an appliance; and
- (4) FIG. 3 shows a flow chart of an exemplary method for authentication on an appliance.

DETAILED DESCRIPTION OF THE INVENTION

- (5) As set out in the introduction, the present document concerns the efficient and secure authentication of a user or of the computer unit of a user on an appliance. In this context, FIG. 1

shows a system **100** for authentication on an appliance **105**, in particular on a household appliance. The system **100** comprises a hardware security module (HSM) **103** which is embodied to receive a certificate **102** from an authentication server **101** (step **111** in FIG. **1**). Here, the certificate **102** can enable access to a specific appliance **105** and/or to a specific group of appliances **105**. Furthermore, the certificate **102** can define the scope of activities which can be executed in the context of an access to an appliance **105**.

(6) The certificate **102** comprises a specific (maximum) usage number, wherein the usage number shows how often or how many times the certificate **102** can and/or may be used for authentication on an appliance **105**.

(7) The certificate **102** can be stored in the HSM **103**. The HSM **103** can be connected to a computer unit **104** (for example to a smartphone or a laptop computer) by a user via an interface **108** (for example, via USB). A communication connection **112** (for example, Bluetooth and/or WLAN) can be set up between the computer unit **104** and the appliance **105** to enable access to an appliance **105**.

(8) The appliance **105** can send a challenge **113** to the computer unit **104** via the communication connection **112**. The challenge **113** can comprise, for example, a random number. The computer unit **104** can thereupon complete or sign the challenge **113** using the certificate (for example, by means of one of the passwords included in the certificate). On the basis of the signed challenge **113**, a response **114** can then be sent from the computer unit **104** to the appliance **105**. For example, the signed challenge **113** can be encrypted and/or a hash function of the signed challenge **113** can be created and sent as a response **114**. On the basis of the response **114**, the appliance **105** can authenticate the computer unit **104** or reject an authentication. The computer unit **104** can also be informed of the authentication result **115**. Following successful authentication, the access **117** to the appliance **105** can be enabled.

(9) The appliance **105** can comprise a communication unit **107** via which the communication with the computer unit **104** takes place. Furthermore, the appliance **105** can comprise a control unit **106** which is configured to evaluate the response **114** in order to authenticate a computer unit **104**.

(10) The HSM **103** is embodied to reduce (step **116**) the remaining usage number of the certificate **102** for each authentication process. Furthermore, the HSM **103** can be configured to prevent a further use of the certificate **102** for authentication purposes if the remaining usage number of the certificate **102** is zero. Alternatively or additionally the appliance **105** can be embodied to update the usage number of a certificate **102**. Furthermore, the appliance **105** can be configured to check the remaining usage number as part of an authentication process.

(11) Without loss of generality, a customer service intervention is described below as an example of an access to an appliance **105**. The method described in this document for authentication on an appliance **105**, in particular a household appliance, can however in principle be used by any individual.

(12) The user **202** (see FIG. **2**), who would like to authenticate themselves on the appliance **105** or on the system master SMM **205** of the appliance **105**, uses an HSM (hardware security module) **103**, possibly as the only required hardware. With the aid of a (possibly freely available) web service, the user **202** can, for example, use a PC or a smartphone to authenticate themselves with a backend server **101**. By specifying and evidencing specific information, a distinction can be made, where appropriate, between different user groups (for example, end user, customer service, appliance developer, etc.). The user can request (step **211**) a digital certificate **102** according to their authorization, for example to carry out a customer service intervention on a particular appliance **105** or on a defined group of appliances **105**. Here, the granularity of the access rights can depend on the implementation and/or the properties of the appliance **105**.

(13) A digital certificate **102** can be generated (step **212**) by the backend server **101** depending on the properties of the user **202** and/or the appliance **105** or the appliance group. The digital certificate **102** can be securely stored (step **213**) in the HSM **103** with the aid of one of more

technologies provided by the HSM **103** (for example, “PKI as a Service”, “Device Issuer CA”, “Built-In PKI” and/or Secure Channel). PKI stands for public key infrastructure and CA for certification authority.

(14) Requests for a certificate **102**, which are not considered to be plausible, can be rejected by the backend server **101** (for example, too many access or certificate requests in one day). Where appropriate, requests from known, invalid users can also be rejected, allowing for example an effective revoking of certificates **102**. This functionality can not typically be replicated with an implementation without HSM **103**.

(15) If access to an appliance **105** is to be implemented, the user inserts the HSM **103** into a computer unit **104** (for example in a smartphone with a USB OTG interface). A software APP on the computer unit **104** can enable (step **214**) an end-to-end communication **112** between the HSM **103** and the appliance **105**.

(16) The user then proves their authorization with the certificate **102** by means of a challenge-response method (steps **215**, **216**, **217**, **219**), wherein a random number (for example, in the form of an authentication token) **203** of the appliance **105** is signed (step **218**) by a private key of the certificate **102** in the HSM **103**. Access can be restricted by the HSM features “Key Use Counter” and/or “Key Restriction”. After each use, an internal counter is counted down (step **116**). As soon as the value of the counter reaches 0, no further use is possible with the installed certificate **102**. This means that a loss of the HSM **103** only has a limited impact on security.

(17) Security can also be increased further as an option through the use of PIN management.

(18) The measures described in this document can improve the ease of handling and increase security. Furthermore, as a new certificate **102** has to be obtained from a backend server **101** in a timely manner before each access, current information on an appliance **105** can be provided which improves access to the appliance **105**. For example, information on preceding accesses and/or current software or firmware versions for an appliance **105** can be transmitted. As an alternative to an HSM **103**, a JavaCard-compatible NFC smartcard which has the HSM-relevant features can be used.

(19) FIG. 3 shows a flow diagram of an exemplary method **300** for authentication (of a unit **104** and/or a user **202**) on an appliance **105**. The method **300** can be executed by a system **100** and/or by a computer unit **104**. The method **300** comprises providing **301** a certificate **102**, the certificate **102** enabling a limited number N of authentication processes (for example, $N > 1$ and/or $N < 5$ on delivery of the certificate **102**).

(20) Furthermore, the method **300** comprises carrying out **302** an authentication process on the appliance **105** using the certificate **102**. The method **300** furthermore comprises reducing **303** the number N of authentication processes that are still possible for the certificate **102**. In this way, the number N of authentication processes that are still possible for the certificate **102** can be reduced (by one in each case) after each authentication process. The access to an appliance **105** (or to an appliance group) can therefore be enabled and/or controlled in an efficient and secure manner.

(21) The present invention is not restricted to the exemplary embodiments shown. In particular, it should be noted that the description and the figures are only intended to illustrate the principle of the proposed system and/or the proposed method.

Claims

1. A method for authentication on an appliance, the method comprising: providing a certificate on a hardware security module from an authentication server, the certificate enabling a limited number N of authentication processes; carrying out an authentication process on the appliance to authenticate a user on the appliance; reducing the number N of authentication processes that are still possible for the certificate; connecting the hardware security module to a computer unit by the user via an interface, and reducing the number N of authentication processes that are still possible

- by a counter of the hardware security module; and requesting the certificate by the user and rejecting requests which do not meet a predetermined threshold of plausibility; and authenticating the computer unit on the appliance, and enabling access to the certificate via a communication interface between the computer unit and the hardware security module; and providing information relating to the appliance from the server together with the certificate.
2. The method according to claim 1, wherein the authentication process comprises: checking whether the number N of authentication processes that are still possible is greater than zero; and upon determining that the number N of authentication processes that are still possible is not greater than zero, rejecting the authentication process on the appliance.
 3. The method according to claim 1, wherein the method further comprises: determining a user type from a plurality of different user types; and providing a certificate which enables one or more specific access rights to the appliance depending on the user type.
 4. The method according to claim 1, wherein the authentication process comprises: receiving a challenge from the appliance; determining a response to the challenge, the response depending on the challenge and the certificate; and sending the response to the appliance.
 5. The method according to claim 1, wherein the authentication server is responsible for an administration of accesses to the appliance.
 6. The method according to claim 5, which further comprises: carrying out a server authentication process on the server to authenticate a unit requesting to obtain the certificate from the server; and providing the certificate following a successful server authentication process.
 7. The method according to claim 5, wherein the number N of possible authentication processes for the certificate, when the certificate is provided via the server, lies between 2 and 10.
 8. The method according to claim 1, wherein the number N of possible authentication processes for the certificate, when the certificate is first provided, lies between 2 and 10.
 9. The method according to claim 1, wherein the appliance is a household appliance.
 10. The method according to claim 9, wherein the household appliance is an appliance selected from the group consisting of a washing machine, a dryer, a food processor, a stove, an oven, a refrigerator, and a dishwasher.
 11. The method according to claim 1, wherein: the certificate is configured to enable a user of the certificate to access the appliance following a successful authentication process; and the certificate is configured to limit an access to a subset of access rights from a total set of access rights.
 12. A system for authentication on an appliance, the system, comprising: a hardware security module, an authentication server, a computer unit, and an interface; the system being configured: to provide a certificate on the hardware security module from the authentication server, the certificate enabling a limited number N of authentication processes; to carry out an authentication process on the appliance to authenticate a user on the appliance; and to decrease the number N of authentication processes that are still possible for the certificate; to connect the hardware security module to the computer unit by the user via the interface, and to reduce the number N of authentication processes that are still possible by a counter of the hardware security module; to receive requests for a digital certificate by the user and reject requests which do not meet a predetermined threshold of plausibility; and to authenticate the computer unit on the appliance, and to enable access to the certificate via a communication interface between the computer unit and the hardware security module; and to provide information relating to the appliance from the server together with the certificate.
-