

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408802
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lee; Seungjin et al.

Robot cleaner

Abstract

Disclosed is a robot cleaner including a main body for forming an exterior of the robot cleaner, each wheel cover detachably disposed in the main body, each driving module movably coupled to each wheel cover, and each wheel coupled to each driving module and rotated by receiving a driving force from each driving module, wherein each wheel includes a wheel body coupled to each driving module and forming an appearance of each wheel, a plurality of treads arranged to be spaced apart from each other along a circumferential face of the wheel body, and a plurality of ribs respectively disposed between the treads and protruding radially outward of each wheel.

Inventors:	Lee; Seungjin (Seoul, KR), Lee; Sangik (Seoul, KR)
Applicant:	LG ELECTRONICS INC. (Seoul, KR)
Family ID:	79729215
Assignee:	LG ELECTRONICS INC. (Seoul, KR)
Appl. No.:	18/017338
Filed (or PCT Filed):	December 09, 2020
PCT No.:	PCT/KR2020/017952
PCT Pub. No.:	WO2022/019405
PCT Pub. Date:	January 27, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230320547 A1	Oct. 12, 2023

Foreign Application Priority Data

KR	10-2020-0090970	Jul. 22, 2020
----	-----------------	---------------

Publication Classification

Int. Cl.: **A47L9/00** (20060101); **A47L9/28** (20060101); **B60B19/00** (20060101); **B60C11/13** (20060101); **B60K7/00** (20060101)

U.S. Cl.:

CPC **A47L9/009** (20130101); **A47L9/2852** (20130101); **B60B19/00** (20130101); **B60K7/0007** (20130101); A47L2201/04 (20130101); B60B2200/49 (20130101); B60C2011/1361 (20130101); B60K2007/0092 (20130101)

Field of Classification Search

CPC: A47L (9/009); A47L (9/2852); A47L (2201/04); B60B (19/00); Y10S (901/01)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6176284	12/2000	Takada	152/902	B60C 11/047
6633150	12/2002	Wallach	15/53.4	A47L 9/009
8733796	12/2013	Lee	280/856	B60B 19/12
9597930	12/2016	Dautrey	N/A	B60C 19/002
2006/0260087	12/2005	Im	15/319	A47L 9/009
2017/0209015	12/2016	Liu et al.	N/A	N/A
2018/0184875	12/2017	Youk	N/A	A47L 9/28

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
5-91910	12/1992	JP	N/A
10-2005-0122118	12/2004	KR	N/A
10-0613809	12/2005	KR	N/A
10-0619786	12/2005	KR	N/A
20090007907	12/2008	KR	N/A
10-2009-0013349	12/2008	KR	N/A
20090013349	12/2008	KR	N/A
10-1480639	12/2014	KR	N/A
10-2016-0104056	12/2015	KR	N/A
10-2018-0079068	12/2017	KR	N/A
10-2019-0021294	12/2018	KR	N/A
I582322	12/2016	TW	N/A
I664943	12/2018	TW	N/A

Primary Examiner: Clemmons; Steve

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is the National Phase of PCT International Application No. PCT/KR2020/017952, filed on Dec. 9, 2020, which claims priority under 35 U.S.C. 119(a) to Patent Application No. 10-2020-0090970, filed in the Republic of Korea on Jul. 22, 2020, all of which are hereby expressly incorporated by reference into the present application.

TECHNICAL FIELD

(2) The present disclosure relates to a robot cleaner.

BACKGROUND ART

(3) A person cleans a living space thereof for hygiene and cleanliness. There are many reasons for the cleaning. For example, the cleaning may be done to protect a body from disease or to prevent damage to a bronchus. Further, the cleaning may be done for a quality of life, such as, for using the space thereof in a clean state.

(4) Dust or foreign substances settle on a floor by gravity. Thus, in order to perform the cleaning, people tend to bend their waists or sit down, so that it is easy to put a strain on the waists or joints.

(5) To this end, in recent years, cleaners that help people clean have appeared. The cleaners may be roughly classified into a handy stick cleaner, a bar-type cleaner, a robot cleaner, and the like.

(6) Among these, the robot cleaner cleans the space instead of a user in a specific space such as a home, an office, or the like. The robot cleaner generally performs the cleaning by sucking dust in a region to be cleaned.

(7) A tread pattern may be formed on a wheel of the robot cleaner for stable travel. However, in the region to be cleaned of homes, offices, or the like where the robot cleaner travels, there may be cases in which electric wires for use of home appliances or foreign substances having a large particle diameter are caught between the tread patterns, which may hinder the stable travel.

(8) In particular, Patent Document 1 and Patent Document 2 disclose that each rib is formed between two adjacent tire tread patterns. However, Patent Document 1 is a document on an automobile tire, which has a difference in application range from the tire of the robot cleaner.

(9) Patent Document 3 discloses a driver module that is detachable and is able to alleviate a shock against a floor face, but does not disclose contents for the stable travel because it is not easy to remove the foreign substance when the foreign substance is caught between the treads.

PATENT DOCUMENTS

(10) Patent Document 1: Korean Patent Application Publication No. 10-2013-0117131 (2015.01.02)

(11) Patent Document 2: Korean Patent Application Publication No. 10-2016-7020870 (2016.09.02)

(12) Patent Document 3: Korean Patent Application Publication No. 10-2019-0021294 (2019.03.05)

DISCLOSURE

Technical Problem

(13) The embodiments of the present disclosure are to provide a robot cleaner that may effectively prevent a foreign substance from being caught in a wheel.

(14) In addition, the embodiments of the present disclosure are to provide a robot cleaner that may prevent a foreign substance from being caught and effectively secure a climbing performance at the same time.

Technical Solution

(15) An embodiment of the present disclosure provides a robot cleaner that has changed a shape of treads formed on a wheel of the robot cleaner.

(16) Specifically, provided is a robot cleaner that may prevent degradation of a climbing performance that occurs when preventing a foreign substance from being caught between treads.

(17) In particular, provided is a robot cleaner that may easily climb a stepped terrain, such as a

threshold, as a thin rib is bent.

(18) More specifically, a robot cleaner according to an embodiment of the present disclosure includes a main body, each wheel cover, each driving module, and each wheel. The main body forms an appearance of the robot cleaner, and each wheel cover is detachably disposed in the main body.

(19) Each driving module is movably coupled to each wheel cover, and each wheel is coupled to each driving module and is rotated by receiving a driving force from each driving module.

(20) Each wheel includes a wheel body, a plurality of treads, and a plurality of ribs. Each wheel body is coupled to each driving module and forms an appearance of each wheel. The plurality of treads are arranged to be spaced apart from each other along a circumferential face of the wheel body. The plurality of ribs are respectively disposed between the treads and protrude radially outward of each wheel.

(21) The rib may protrude to have the same height as the tread. The rib may protrude to have a smaller height than the tread.

(22) The rib may have a smaller thickness than the tread. Each tread may be formed such that a center thereof has a greater thickness than both ends thereof in a width direction of the wheel body.

(23) Each tread may have a contact face in contact with a road face in an octagonal shape. The rib may have a smaller width than the tread.

(24) The rib may be made of the same material as the tread. The rib may be made of a material different from a material of the tread.

(25) The plurality of ribs may be arranged in the rest except for some of a plurality of spaced spaces, and each spaced space may be defined between every adjacent two of the plurality of treads. The rib may have elasticity to be bent by being pressed by the ground.

(26) Each driving module may be disposed in each wheel cover to be movable in a vertical direction, and the rib may be constructed to have a height allowing the rib not to be in contact with each wheel cover in a state where each driving module is maximally in close contact with each wheel cover.

(27) Each wheel may include a plurality of bents defined by being recessed inward of each wheel body between the treads, and each rib may be disposed to protrude from each bent radially outward of the wheel body.

(28) Each rib may include a central portion and wing portions positioned on both sides of the central portion based on a width direction of the wheel body. The wing portion may be thicker than the central portion.

Advantageous Effects

(29) The embodiments of the present disclosure may provide the robot cleaner that may travel stably without being disturbed by the foreign substance such as the electric wire.

(30) In addition, the embodiments of the present disclosure may provide the robot cleaner that may effectively perform cleaning because the climbing performance is not degraded even when a member capable of preventing the foreign substance from being caught between the treads is formed.

(31) In addition, the embodiments of the present disclosure may provide the robot cleaner that may prevent the foreign substance from being caught, so that the user does not need to constantly supervise a travel situation of the robot cleaner to determine whether a malfunction resulted from the foreign substance has occurred, thereby maximizing convenience of a user.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a perspective view of a robot cleaner according to an embodiment.

- (2) FIG. 2 is a bottom view of a robot cleaner according to an embodiment.
- (3) FIG. 3 is a view illustrating a driver of a robot cleaner according to an embodiment of the present disclosure.
- (4) FIGS. 4 and 5 are exploded perspective views of a driver of a robot cleaner according to an embodiment of the present disclosure.
- (5) FIG. 6 is a view illustrating an operation of a driver according to an embodiment of the present disclosure.
- (6) FIG. 7 is an exploded perspective view of a driving module according to an embodiment of the present disclosure.
- (7) FIG. 8 is a view illustrating various embodiments of ribs according to an embodiment of the present disclosure.
- (8) FIG. 9 is a view illustrating ribs according to another embodiment of the present disclosure.
- (9) FIG. 10 is a view illustrating an operation of a robot cleaner according to an embodiment of the present disclosure.

BEST MODE

- (10) Hereinafter, an embodiment of the present disclosure will be described in detail with reference to the accompanying drawings such that a person having ordinary knowledge in the technical field to which the present disclosure belongs may easily implement the embodiment.
- (11) However, the present disclosure is able to be implemented in various different forms and is not limited to the embodiment described herein. In addition, in order to clearly describe the present disclosure, components irrelevant to the description are omitted in the drawings. Further, similar reference numerals are assigned to similar components throughout the specification.
- (12) Duplicate descriptions of the same components are omitted herein.
- (13) In addition, it will be understood that when a component is referred to as being 'connected to' or 'coupled to' another component herein, it may be directly connected to or coupled to the other component, or one or more intervening components may be present. On the other hand, it will be understood that when a component is referred to as being 'directly connected to' or 'directly coupled to' another component herein, there are no other intervening components.
- (14) The terminology used in the detailed description is for the purpose of describing the embodiments of the present disclosure only and is not intended to be limiting of the present disclosure.
- (15) As used herein, the singular forms 'a' and 'an' are intended to include the plural forms as well, unless the context clearly indicates otherwise.
- (16) It should be understood that the terms 'comprises', 'comprising', 'includes', and 'including' when used herein, specify the presence of the features, numbers, steps, operations, components, parts, or combinations thereof described herein, but do not preclude the presence or addition of one or more other features, numbers, steps, operations, components, or combinations thereof.
- (17) In addition, in this specification, the term 'and/or' includes a combination of a plurality of listed items or any of the plurality of listed items. In the present specification, 'A or B' may include 'A', 'B', or 'both A and B'.
- (18) FIG. 1 is a perspective view of a robot cleaner according to an embodiment.
- (19) A robot cleaner **100** according to an embodiment may include a main body **1**, a dust collector **2**, and drivers **3**. Further, the robot cleaner **100** may further include a battery (not shown) for providing electric power such that the above-described driver and dust collector may be electrically driven.
- (20) The battery may be provided as a secondary battery and may be repeatedly charged and discharged. Thus, a user may use the robot cleaner by repeatedly charging the battery when a battery power level is low without having to replace or add a battery.
- (21) When the battery is provided as the secondary battery, the robot cleaner may further include a charging device (not shown) that may charge the robot cleaner.

(22) In another example, the battery may be provided as a dry battery rather than the secondary battery. In this case, the dry battery may be required to be replaced when the dry battery is dead.

(23) That is, there is no restriction on how the robot cleaner is provided with the electric power.

(24) The main body **1** may be disposed to form an appearance of the robot cleaner **100**.

(25) The main body **1** may include a first housing **11** and a second housing **12**.

(26) The first housing **11** may form a portion of the main body **1** and may provide a space in which electronic components required for the robot cleaner **100** or parts required for the robot cleaner are mounted.

(27) For example, a controller (not shown) that controls an operation of the robot cleaner **100** may be mounted.

(28) Further, the first housing **11** may be disposed to provide a flow path (not shown) through which air containing dust is guided to the dust collector **2** to be described later. That is, the air sucked through a suction portion **4** to be described later may be guided through an internal space of the first housing **11** to the dust collector **2**.

(29) The second housing **12** may be disposed in a form of a cover that covers the first housing **11**. However, the second housing **12** is not limited thereto.

(30) A display (not shown) may be disposed on one face of the second housing **12**. The display may be formed in a shape of a touch panel, so that the user may simply enter a command through the display.

(31) It is sufficient that the second housing **12** is disposed to be coupled to the first housing **11**. For example, the second housing **12** may be hinged or integrally formed with the first housing **11**.

(32) However, it is preferable that the second housing **12** is separately disposed in consideration of installation convenience of the parts mounted in the first housing **11**. The second housing **12** may prevent the parts mounted in the first housing **11** from being contaminated or damaged by an outside factor.

(33) That is, the robot cleaner according to the present embodiment may be disposed such that the parts mounted in the first housing **11** are covered by the second housing **12** and not exposed to the outside. Thus, when the parts are operating, a user's body may be injured due to user's carelessness, malfunction, or the like. Thus, the main body **1** may cover the internal parts to prevent a safety accident. Further, because the main body **1** is present, a complex interior is not exposed to the outside, thereby creating a sense of beauty. Thus, the main body **1** may be used as a design element.

(34) The sensor unit **121** may be disposed on the main body **1**. The sensor unit **11** may provide image information such that the robot cleaner **100** may travel in a region to be cleaned. The sensor unit **121** may be a camera or a photographing sensor.

(35) Specifically, the sensor unit **121** may collect information necessary for autonomous travel of the robot cleaner **100**.

(36) For example, the sensor unit **121** may include the photographing sensor that creates a travel map by photographing a periphery of the robot cleaner **100**, an obstacle sensor that senses an obstacle, and the like. In another example, additional sensors may be further arranged in addition to the above-described sensors.

(37) For example, the sensor unit **121** may further include a wall sensor (not shown). Thus, information about the region to be cleaned may be input to the robot cleaner **100** through the wall sensor, the photographing sensor, and the like. The robot cleaner **100** may input a shape of a space while traveling, and divide the region to be cleaned through the wall sensor into a plurality of cleaning areas.

(38) The dust collector **2** may be a portion where the dust is collected. The dust collector **2** may include a cyclone (not shown). The dust collector **2** may be in communication with the suction portion **4**.

(39) The air may be introduced into the robot cleaner by the dust collector **2**. When the air is sucked by the dust collector **2** and the air from which the dust has been removed is discharged to

the outside, a negative pressure is generated in the robot cleaner **100**, so that the air containing the dust may be introduced through the suction portion housing **41**.

(40) The dust collector **2** may be formed in a form in which relatively large dust is primarily separated and then relatively small dust is secondarily separated. However, the dust collector **2** is not limited thereto and is sufficient when being able to suck the dust present on the traveling face.

(41) The dust collector **2** may be disposed to be detachable from the main body **1**. Thus, when the robot cleaner completes the cleaning or when excessive dust is accumulated in the dust collector **2**, the user may easily separate the dust collector **2** to remove the dust, thereby ensuring convenience.

(42) The suction portion **4** may be a portion that is coupled to the main body of the robot cleaner **100** to perform the cleaning.

(43) The suction portion **4** may include a suction portion housing **41** and a roller **42**.

(44) The suction portion **4** may be disposed to clean a traveling face. Specifically, the suction portion **4** may be disposed to suck dust present on the traveling face.

(45) The traveling face may be a floor face. When a carpet or the like is disposed, the traveling face may be a top face of the carpet.

(46) The dust may be sucked into a space provided by the first housing **11** through the suction portion housing **41**. The sucked dust may be collected in the dust collector **2** and air from which the dust has been removed may be discharged to the outside of the main body **1**.

(47) The suction portion housing **41** may be disposed to be coupled to the main body **10** to provide a space for accommodating a mop **50** to be described later therein.

(48) Further, the suction portion housing **41** may provide a flow path through which the air containing the dust may be sucked such that the dust present on the traveling face may be removed.

(49) Specifically, the suction portion housing **41** may provide the space for accommodating the roller **42** therein as described above, so that the roller **42** may smoothly clean the traveling face.

(50) There is no restriction on a connection relationship between the suction portion housing **41** and the main body **1**. That is, the suction portion housing **41** and the main body **1** may be integrally formed or may be formed separately. However, it is preferable that the main body **1** and the suction portion housing **41** are separately formed from a viewpoint of convenience when cleaning an interior of the roller or when a failure of a component occurs in the suction portion housing **41** or in the main body **1** and the component is replaced.

(51) FIG. **2** is a bottom view of a robot cleaner according to an embodiment.

(52) The robot cleaner **100** may include the drivers **3**.

(53) The drivers **3** may be arranged to move the main body **1**. The drivers **3** may be arranged to be detachable from the main body **1**.

(54) As shown in FIG. **2**, each driver **3** may have a fastening portion **311**, and the main body **1** may have receiving portions **111** defined therein for respectively receiving the drivers **3** therein. Each coupling portion (not shown) having a shape corresponding to each fastening portion **311** may be defined in each receiving portion **111**. As each fastening portion **311** is connected to each coupling portion, each driver **3** may be coupled to the main body **1**.

(55) Each fastening portion **311** and each coupling portion are connected to each other, so that each driver **3** may be integrally coupled with the main body **1**. Accordingly, the main body **1** may perform the cleaning of the region to be cleaned while moving by the operation of the drivers **3**.

(56) Each receiving portion **111** may be defined in a bottom face of the robot cleaner **100**.

(57) Each driver **3** may include a wheel cover **31**, a driving module **32**, and a wheel **33**.

Specifically, each driver **3** may include the driving module **32** that generates a driving force, the wheel **33** constructed to be rotatable by the driving module **32**, and the wheel cover **31** disposed to cover the driving module **32** and the wheel **33**.

(58) The wheel cover **31** may be a portion that provides a space for receiving the driving module **32** and the wheel **33** to be described later therein. The fact that the wheel cover **31** provides the space for receiving the driving module **32** and the wheel **33** therein may not simply mean that the wheel

cover **31** receives the driving module **32** and the wheel **33** therein by covering an entirety of the driving module **32** and the wheel **33**. That is, the wheel cover **31** is sufficient to provide a space for the wheel **33** and the driving module **32** to be seated.

(59) Each fastening portion **311** described above may be disposed on each wheel cover **31** to connect each driver **3** to the main body **1**.

(60) The driving module **32** is constructed to generate the driving force and transmit the driving force to the wheel **33**, and is coupled to the wheel cover **31** so as to be movable in a vertical direction. The vertical movement of each driving module **32** may be guided by guide bars **3121** of buffers **312** to be described later. A detailed configuration of the driving module **32** will be described in detail later.

(61) The wheels **33** may be constructed to rotate by receiving electric power. The wheels **33** may be disposed on both sides of the main body **1**, respectively.

(62) The wheel **33** disposed on one side and the wheel **33** disposed on the other side may be controlled independently of each other. That is, the wheel **33** disposed on one side and the wheel **33** disposed on the other side may be rotated at different rotational speeds.

(63) Therefore, the robot cleaner **100** may rotate in a left or right direction. In addition, the robot cleaner **100** may change a direction in addition to a forward or backward movement.

(64) That is, a travel speed of the robot cleaner **100** may be determined based on the rotational speed of the wheel **33** and the travel direction may be determined based on a difference in the rotational speeds of the wheels **33**.

(65) For example, when the wheel **33** located on the left side of the robot cleaner is maintained in a stopped state and the wheel **33** located on the right side rotates, the robot cleaner **100** may be rotated in the left direction. When both wheels **33** are in operation, but the wheel **33** on the right rotates faster than the wheel **33** on the left, as the direction is changed to the left direction, the robot cleaner may continue to move forward.

(66) Because the robot cleaner **100** performs the cleaning while essentially moving in the region to be cleaned, the suction portion housing **41** may not move smoothly during the travel. Therefore, an auxiliary wheel **112** may be disposed for the smooth travel. As the auxiliary wheel **112** is disposed, the suction portion housing **41** may move more smoothly during the travel of the robot cleaner **100**.

(67) However, the present disclosure is not limited to the above-described example, and the above-described example is only one embodiment. The photographing sensor and the obstacle sensor may simultaneously perform wall sensing.

(68) The photographing sensor may be disposed not only to sense the region to be cleaned, but also to specify a position of the main body **1** in the region to be cleaned that is previously input. Thus, a position of the space where the robot cleaner **100** performs the cleaning may be specified. As the position of the robot cleaner **100** is specified, a movement to a next cleaning area may be guided.

(69) A type and the number of sensor units **121** are not limited. That is, a plurality of photographing sensors may be arranged, and when the plurality of photographing sensors are arranged, the plurality of photographing sensors may be photographing sensors of the same type or different types.

(70) The robot cleaner **100** may vary a suction strength of the dust collector **2** based on a material of the floor. This is because when the dust collector **2** always sucks the dust at the same strength, it may be difficult to completely perform the cleaning on an unusual floor face such as the carpet and the like.

(71) The robot cleaner **100** may include a floor sensor (not shown) to sense the material of the floor. The floor sensor may be a sensor that senses the material of the floor. The floor sensor may be disposed in the sensor unit **121** described above, or may be disposed at a position different from the sensor unit **121**.

(72) The region to be cleaned in which the robot cleaner **100** is used may vary depending on a case. For example, a floor material of the region to be cleaned may be marble or a floor paper. Further,

the region to be cleaned may be made of a material other than the above example.

(73) Depending on the material of the floor, an intensity at which the dust collector **2** is driven to effectively suck the dust may vary.

(74) Specifically, the dust collector **2** must be driven more strongly in a carpeted region than on a general floor paper to effectively perform cleaning. The controller of the robot cleaner **100** may adjust the driving intensity of the dust collector **2** based on the type of floor material.

(75) The obstacle sensor may determine whether an obstacle exists in the region to be cleaned. The obstacle sensor may be disposed integrally with the sensor unit **121** described above, or may be disposed separately. That is, the photographing sensor may also serve as the obstacle sensor.

(76) As the obstacle sensor senses the obstacle, a travel path of the robot cleaner **100** may be changed. As a moving line becomes complicated, battery consumption may vary. Specifically, when the obstacle is present, the robot cleaner **100** is moved to bypass the obstacle. At this time, the moving line may be lengthened. As the moving line lengthens, a battery consumption for cleaning the corresponding area may increase.

(77) The driver **3** will be described in detail with reference to FIGS. **2** to **5**.

(78) Each driver **3** may include the buffers **312** constructed to allow the driving module **32** and the wheel **33** to move in the vertical direction in the wheel cover **31**.

(79) Each buffer **312** may include a guide bar **3121** and an elastic member **3122**.

(80) The buffers **312** may be respectively inserted into through-holes **312a** defined in each wheel cover **31** to be connected to each driving module **32**.

(81) The guide bars **3121** are constructed to guide the vertical movement of the driving module **32**. The guide bars **3121** are formed to extend in one direction, penetrate the driving module **32**, and extend in the wheel cover **31** in the vertical direction.

(82) It is shown in the present drawing that the guide bars **3121** are formed to penetrate the driving module **32** in the left and right sides of the driving module **32**, respectively.

(83) Both upper and lower ends of the guide bar **3121** may be fixed to the wheel cover **31**. In the present drawing, the upper end of the guide bar **3121** may be fixed at a top of the wheel cover **31** and the lower end of the guide bar **3121** may be fixed to a bottom of the wheel cover **31**.

(84) The elastic member **3122** may be disposed to absorb a shock when the driving module **32** moves in the vertical direction. The elastic member **3122** may be connected to the wheel cover **31** and the driving module **32**.

(85) Specifically, the elastic member **3122** may be formed as a coil spring surrounding the guide bar **3121**. However, a type of elastic member is not limited thereto, and any type of the elastic member is possible as long as the shock may be relieved and the driving module **32** may be moved in the vertical direction.

(86) Buffer spaces **321** may be defined in each driving module **32** to respectively provide spaces in which the buffers **312** may be received, respectively. Each buffer **312** may be received in each buffer space **321**.

(87) The wheel **33** may include a wheel body **331**, treads **332**, bents **333**, and ribs **334**.

(88) The wheel body **331** may be disposed to be coupled to the driving module **32**. The wheel body **331** may form an appearance of the wheel **33**. That is, the wheel body **331** may include a side wall and a bead.

(89) The treads **332** may be formed integrally with the wheel body **331** and may include a plurality of treads along a circumferential face of the wheel body **331**. The treads **332** may form a pattern of the wheel **33**.

(90) A thickness of the tread **332** may not be constant. That is, a thickness of a portion of the tread **332** positioned at a center of the wheel body **331** in a width direction may be greater than portions positioned on both sides of the wheel body **331** in the width direction. For example, a shape of a contact face of the tread **332** to be in contact with a road face may be formed such that a thickness of a portion positioned at a center of the wheel body in a thickness direction is great and a thickness

of portions positioned on both sides of the wheel body **331** in the thickness direction is small.

(91) As the contact face of the tread **332** to be in contact with the road face is formed in an octagonal shape, the travel and climbing may be stably performed. Specifically, a thickness of a portion near the center of the tread **332** may be great and a thickness of a portion near an edge may be smaller than the thickness of the portion near the center of the tread **332**. When traveling in a straight line, the tread **332** may be stably in contact with the traveling face, and when changing the direction, the tread **332** may reduce a resistance caused by the traveling face, so that smooth direction change may be achieved.

(92) That is, the tread **332** may have the contact face in contact with the road face in the octagonal shape or a shape similar to the octagonal shape.

(93) A contact force or a frictional force with the road face may vary based on the pattern shape of the tread **332**, so that travel stability may vary.

(94) The treads **332** may be arranged on the circumferential face of the wheel body **331** to be spaced apart from each other.

(95) The bents **333** may mean portions between the treads **332**. Each bent **333** may be defined in a form recessed inward of the wheel body **331** between the two adjacent treads **332**.

(96) The ribs **334** may be integrally formed with the wheel body **331**, and each rib **334** may be formed between the two adjacent treads **332** to protrude outward in a radial direction of the wheel **33**. That is, each rib **334** may be located in each bent **333** between the two adjacent treads **332**.

(97) The rib **334** may be formed to protrude to have a height equal to or similar to a height of the tread **332**. When the rib **334** protrudes more than the tread **332**, the travel stability may be deteriorated when the robot cleaner travels.

(98) For example, when the rib **334** is disposed to protrude more than the tread **332**, rattling may occur when the robot cleaner performs the cleaning. In addition to the deterioration of the travel stability, connection between interior electric components may be weakened or the electric components may be deviated from original positions thereof when the robot cleaner is constantly shaken.

(99) Therefore, it is not preferable that the rib **334** has a height greater than that of the tread **332**.

(100) As the rib **334** is disposed, a foreign substance may be prevented from being caught in the bent **333**. Specifically, the foreign substance such as an electric wire may be prevented from being caught in the bent **333** defined between the two adjacent treads **332**. When the wire gets caught when the robot cleaner travels, home appliances may not operate smoothly, or a failure of the robot cleaner may be caused.

(101) The rib **334** may have a thickness smaller than that of the tread **332**. Unlike the tread **332**, the rib **334** is not disposed to increase the contact force with the road face or secure the friction force with the road face, so that the rib **334** does not need to be thick.

(102) In addition, the rib **334** may have a width smaller than that of the tread **332**. In other words, the width of the rib **334** may be smaller than the width of the tread **332**.

(103) Because the rib **334** is disposed to prevent the foreign substance from being caught, the rib **334** is not necessary to be larger than the tread **332**. That is, the width of the rib **334** may be equal to or smaller than the width of the tread **332**.

(104) FIGS. **3** to **5** show that each of all the ribs **334** is disposed between every adjacent two of all the treads **332**, but it is not necessary for the ribs **334** to be respectively disposed in all of the bents **333**. Because the rib **334** plays a role of preventing the foreign matter from being caught, it is sufficient when an appropriate number of the ribs **334** are arranged in consideration of the travel speed of the robot cleaner, a size of the wheel, and the like.

(105) Accordingly, the ribs **334** may be respectively formed in some of the spaces defined by the plurality of treads **332**. However, the present disclosure may not be limited thereto, and each rib **334** may be disposed between every adjacent two of all the treads **332**.

(106) FIG. **6** is a view illustrating various states of a driver of a robot cleaner according to an

embodiment.

(107) (a) in FIG. 6 is a view illustrating a state in which the wheel is inserted into an innermost side of the wheel cover, and (b) in FIG. 6 is a view illustrating a state in which the wheel protrudes to an outermost side of the wheel cover.

(108) Hereinafter, for convenience of description, a state as shown in (a) in FIG. 6 is described as a first state, and a state as shown in (b) in FIG. 6 is described as a second state.

(109) The first state may be a state in which the wheel of the robot cleaner is in contact with the road face and a self-load of the robot cleaner is transmitted to the wheel 33. In other words, it represents a state in which the wheel 33 is in contact with the floor and supports the main body 1 of the robot cleaner.

(110) In other words, in the first state, the robot cleaner may travel normally.

(111) In the second state, the self-load of the robot cleaner may not be transmitted to the road face. In other words, it represents a state in which the wheel 33 has lost contact with the floor. That is, it may be difficult for the robot cleaner to travel normally despite the rotation of the wheel 33 as in a case in which a portion of the robot cleaner is caught in a stepped terrain.

(112) The robot cleaner according to an embodiment may control the rotation of the wheel 33 by determining whether the wheel 33 is in contact with the floor.

(113) Specifically, when the wheel 33 loses contact with the floor and the robot cleaner becomes in the second state, the driving of a driving motor is stopped, thereby preventing the wheel 33 from idling unnecessarily.

(114) When the wheel 33 contacts the floor again, the driving motor may be driven again to rotate the wheel 33. Thus, the wheel may be controlled properly based on the state of the robot cleaner.

(115) Hereinafter, the driving module 32 will be described with reference to FIG. 7.

(116) The driving module 32 may be coupled to the wheel body 331 and the wheel cover 31. Specifically, the driving module 32 may be coupled to the wheel cover 31 so as to be movable in the vertical direction.

(117) Each buffer space 321 through which each guide bar 3121 passes is defined in the casing 322. The buffer spaces 321 may be defined on both left and right sides of the casing 322, respectively. The casing 322 is constructed to be movable in the vertical direction along the guide bar 3121.

(118) The driving motor (not shown) is mounted on one side of the casing 322.

(119) A sun and planet gear assembly connects the driving motor and the wheel 33 with each other, decelerates the rotation of the driving motor, and transmits the decelerated rotation of the driving motor to the wheel 33. The sun and planet gear assembly is disposed on the other side of the casing 322. The sun and planet gear assembly may be composed of one or more stages. In the present drawing, the sun and planet gear assembly is composed of two stages, but is not limited thereto.

(120) A sun gear is mounted on a rotation shaft of the driving motor, and the wheel 33 is mounted on a cage that rotatably supports a spinning shaft of each of a plurality of planet gears. With the above structure, the rotation shaft of the driving motor and the rotation axis of the wheel 33 are placed on the same axis.

(121) A space capable of receiving at least a portion of the driving module 32 is defined inside the wheel 33. The sun and planet gear assembly is completely received in the space, so that a circumference of the sun and planet gear assembly may be surrounded by the wheel 33. Therefore, the sun and planet gear assembly are not visible from the outside.

(122) As such, the gearing that decelerates the rotation of the driving motor and transmits the decelerated rotation to the wheel 33 is formed as the sun and planet gear assembly, so that the rotation shaft of the driving motor and the rotation axis of the wheel 33 are placed on the same axis, and the sun and planet gear assembly is received inside the wheel 33, thereby miniaturizing the structure related to the driving of the wheel 33. This may contribute to miniaturization of the cleaner 100 or increase in a volume of another component.

(123) In order to obtain an appropriate deceleration ratio, the sun and planet gear assembly may be

composed of a combination of a first sun and planet gear **323** and a second sun and planet gear **324**, that is, two stages. The first sun and planet gear **323** is linked with the rotation shaft of the driving motor. The second sun and planet gear **324** is linked with the first sun and planet gear **323** and is connected with the wheel **33**.

(124) In a detailed structure thereof, the casing **322** includes a main casing **3221**, a middle casing **3222**, and a front casing **3223**.

(125) The main casing **3221** has each buffer space **321** through which each guide bar **3121** passes. The driving motor is mounted in one side of the main casing **3221**, and the first sun and planet gear **323** is received in the other side of the main casing **3221**. The rotation shaft of the driving motor is formed to penetrate the main casing **3221**.

(126) The first sun and planet gear **323** includes a first sun gear **3231**, a first ring gear **3232**, a plurality of first planet gears **3233**, and a first cage **3234**.

(127) The first sun gear **3231** is coupled to the rotation shaft of the driving motor and exposed to the other side of the main casing **3221**. The first sun gear **3231** may be constructed to rotate in both directions in response to a driving signal applied from the controller.

(128) The first ring gear **3232** is formed to surround the first sun gear **3231** on the other side of the main casing **3221**. The first sun gear **3231** is placed at a center of the first ring gear **3232**. As shown, the first ring gear **3232** may be formed on the main casing **3221** itself.

(129) The plurality of first planet gears **3233** are constructed to be engaged with the first sun gear **3231** and the first ring gear **3232** to spin and revolve around the first sun gear **3231** at the same time. In the present structure in which the first ring gear **3232** is fixed, a spinning direction of each of the plurality of first planet gears **3233** is a direction opposite to a rotation direction of the first sun gear **3231**, and a revolution direction thereof is the same as the rotation direction of the first sun gear **3231**.

(130) The first cage **3234** rotatably supports the spinning shaft of each of the plurality of first planet gears **3233**. The first cage **3234** is disposed to cover a portion of each of the plurality of first planet gears **3233**. The first cage **3234** may be disposed to cover the first sun gear **3231**. In this case, the first cage **3234** may be constructed to rotatably support the rotation shaft of the first sun gear **3231**.

(131) The middle casing **3222** is coupled to the main casing **3221**. One side of the middle casing **3222** is disposed to cover the first sun and planet gear **323**, and the other side of the middle casing **3222** receives the second sun and planet gear **324** therein. In the middle casing **3222**, a hole for connection between the first sun and planet gear **323** and the second sun and planet gear **324** is defined.

(132) The second sun and planet gear **324** includes a second sun gear **3241**, a second ring gear **3242**, a plurality of second planet gears **3243**, and a second cage **3244**.

(133) The second sun gear **3241** protrudes from the first cage **3234** and exposed to the other side of the middle casing **3222** through the hole.

(134) The second ring gear **3242** is formed on the other side of the middle casing **3222** to surround the second sun gear **3241**. The second sun gear **3241** is placed at a center of the second ring gear **3242**. As shown, the second ring gear **3242** may be formed on the middle casing **3222** itself.

(135) The plurality of second planet gears **3243** are constructed to be engaged with the second sun gear **3241** and the second ring gear **3242** to spin and revolve around the second sun gear **3241** at the same time. In the present structure in which the second ring gear **3242** is fixed, a spinning direction of each of the plurality of second planet gears **3243** is a direction opposite to a rotation direction of the second sun gear **3241**, and a revolution direction thereof is the same as the rotation direction of the second sun gear **3241**.

(136) The second cage **3244** rotatably supports the spinning shaft of each of the plurality of second planet gears **3243**. The second cage **3244** is disposed to cover a portion of each of the plurality of second planet gears **3243**. The second cage **3244** may be disposed to cover the second sun gear

3241. In this case, the second cage **3244** may be constructed to rotatably support the rotation shaft of the second sun gear **3241**.

(137) The front casing **3223** is disposed to be coupled to the middle casing **3222** and cover the second sun and planet gear **324**. In the front casing **3223**, a hole for connection between the second sun and planet gear **324** and the wheel **33** is defined.

(138) The second cage **3244** has a protrusion inserted into the hole, and the protrusion has a coupling protrusion that is engaged with a coupling groove of the wheel **33**. The coupling protrusion is engaged with a coupling groove **123b** to prevent the wheel **33** from idling during the rotation by receiving the driving force through the sun and planet gear assembly.

(139) FIG. **8** is a view illustrating various embodiments of a robot cleaner.

(140) (a) in FIG. **8** is a view illustrating that the rib is made of the same material as the wheel, and (b) in FIG. **8** is a view illustrating that the rib is made of a material different from that of the wheel.

(141) There is no restriction on the material of the wheel **33**, but in general, the wheel **33** may be made of a material having excellent elasticity such as rubber, urethane, and the like.

(142) There is no restriction on a type of the rib **334**. That is, the rib **334** may be made of the same material as the tread **332** as shown in (a) in FIG. **8**, or may be made of a material different from that of the tread **332** as shown in (b) in FIG. **8**.

(143) When tread **332** and the rib **334** are made of the same material, manufacturing may be facilitated. Even when the tread **332** and the rib **334** are made of the same material, the tread **332** and the rib **334** may have different thicknesses or shapes.

(144) The tread **332** is a portion disposed for the stable travel of the robot cleaner **100** through the contact with the road face, and the rib **334** is a portion disposed to prevent the foreign substance from being caught between the two adjacent treads **332**, so that it is not preferable that the tread **332** and the rib **334** are formed in the same shape.

(145) As shown in (b) in FIG. **8**, the tread **332** and the rib **334** may be made of different materials. As described above, because the roles of the tread **332** and the rib **334** are different, the rib **334** is not necessarily made of the same material as the tread **332**.

(146) That is, the tread **332** and the rib **334** may be made of materials having different hardnesses. Specifically, a hardness of the tread **332** may be greater than that of the rib **334**.

(147) Because the rib **334** is disposed to prevent the foreign substance from being caught, it is preferable that the rib **334** is bent with a little force to easily remove the foreign substance when the foreign substance such as the electric wire is caught between the rib **334** and the tread **332**. On the other hand, it is preferable that the tread **332** is not bent easily for the stable travel of the robot cleaner.

(148) Specifically, it is preferable that the tread **332** is not bent by the self-load of the robot cleaner.

(149) In one example, even when the rib **334** is made of the same material as the tread **332**, because the thicknesses of the tread **332** and the rib **334** are different from each other, the tread **332** may not be bent by the self-load of the robot cleaner and the rib **334** may be easily bent by a hand of the user, as described above.

(150) However, when the tread **332** and the rib **334** are made of the same material, through the adjustment of the thicknesses and the shapes of the tread **332** and the rib **334**, the tread **332** should be formed so as not to be bent even by the self-load of the robot cleaner and the rib **334** should be formed such that the user may easily remove the foreign substance, so that a choice of a manufacturer may be narrowed.

(151) Therefore, a size and a shape of the wheel **33** may be freely selected by selecting different materials for the tread **332** and the rib **334**.

(152) FIG. **9** is a view illustrating ribs of a robot cleaner according to another embodiment.

(153) Referring to FIG. **9**, the rib **334** may include a central portion **3341** and wing portions **3342**.

(154) The central portion **3341** may be a portion positioned adjacent to the center of the tread **332**, and the wing portions **3342** may be portions respectively positioned on both sides of the central

portion **3341**. The central portion **3341** and the wing portions **3342** may be integrally formed.

(155) In a description focusing on the wheel body **331**, the wing portions **3342** are portions located on both sides of the wheel body **331** in the width direction, and the central portion **3341** is a portion containing a center of the wheel body **331** in the width direction.

(156) A thickness of the wing portion **3342** may be greater than that of the central portion **3341**. In general, the electric wire or the like starts to be caught at a position of the wing portion **3342** when being caught between the two adjacent treads **332** during the travel of the robot cleaner.

(157) Therefore, when the thickness of the wing portion **3342** is greater than that of the central portion **3341**, the wing portion **3342** may perform a function of preventing the foreign substance from being caught to some extent.

(158) In addition, when the wing portion **3342** is thicker than the central portion **3341**, and when the robot cleaner moves a threshold or the stepped terrain diagonally, the wing portion **3342** of the robot cleaner touches the stepped terrain first. In this case, because a great load is applied to one of the wing portions **3342**, it is preferable that the wing portion **3342** is thick.

(159) In addition, as described above, the edges of the tread **332** may be thinner than the portion of the tread **332** located at the center of the width direction of the wheel body **331**. That is, a distance between the two adjacent treads **332** is greater at the edge of the wheel body **331** than at the center of the width direction. In other words, a spacing between the respective edges of the two adjacent treads **332** is greater than that between the respective portions of the two adjacent treads **332** located at the center of the width direction of the wheel body **331**. Therefore, even when the great load is applied to the wing portion **3342**, a space in which the wing portion **3342** may be sufficiently bent is defined, so that the climbing may be performed easily.

(160) The central portion **3341** may be bent when the robot cleaner passes the stepped terrain while moving forward. In addition, even when only the wing portion **3342** is bent, the central portion **3341** may play a role of providing a restoring force for returning the wing portion **3342** to an original position thereof.

(161) FIG. **10** is a view illustrating a state when a robot cleaner is climbing according to an embodiment.

(162) Referring to FIG. **10**, the rib **334** of the robot cleaner according to an embodiment may be constructed to be bent when passing the stepped terrain.

(163) As the ribs **334** are arranged, the foreign substance may be prevented from being caught between the treads **332**, but a climbing performance may be lowered by the ribs **334**. In general, when the robot cleaner passes the stepped terrain, as the stepped terrain gets caught in the bent **333** defined between the two adjacent treads **332** and the tread **332** pushes the terrain, the robot cleaner climbs the stepped terrain.

(164) When the ribs **334** are arranged, it is difficult for the stepped terrain to be settled in the bent **333**. Therefore, the rib **334** may be constructed to be bent when the stepped terrain gets caught, as shown in the drawing.

(165) When the rib **334** is constructed to be bent in a case where the load of the robot cleaner is transmitted to one face of the rib **334**, the rib **334** may exhibit the effect of preventing the foreign substance from being caught and the effect of preventing degradation in the climbing performance at the same time.

(166) In this connection, the one face of the rib **334** means a face pressed by the stepped terrain when the wheel **33** rotates. In other words, the one face of the rib **334** refers to a face neighboring a face in contact with the road face when traveling on the flat road face rather than a face in contact with the road face when traveling on the flat road face.

(167) Although the exemplary embodiment of the present disclosure has been described above in detail, those of ordinary skill in the art to which the present disclosure pertains will appreciate that various modifications are possible within the limits without departing from the scope of the present disclosure provided by the claims to be described later.

Claims

1. A robot cleaner comprising: a main body for forming an exterior of the robot cleaner; a wheel cover detachably provided on the main body; a driving module movably coupled to the wheel cover; and a wheel coupled to the driving module and rotated by receiving a driving force from the driving module, wherein the wheel includes: a wheel body coupled to the driving module and forming an appearance of the wheel; a plurality of treads arranged along a circumferential face of the wheel body and spaced apart from each other; and a plurality of ribs respectively disposed between the treads and protruding radially outward of the wheel, wherein a rib of the plurality of ribs includes a central portion and wing portions positioned on both sides of the central portion in a width direction of the wheel body, wherein a wing portion of the wing portions is thicker than the central portion, and wherein, with respect to the width direction of the wheel body, a first spacing between an edge portion of an adjacent one of the plurality of treads and one of the wing portions is greater than a second spacing between a center of the adjacent one of the plurality of treads and the central portion.
 2. The robot cleaner of claim 1, wherein the rib protrudes to have the same height as a tread of the plurality of treads.
 3. The robot cleaner of claim 1, wherein the rib protrudes to have a smaller height than a tread of the plurality of treads.
 4. The robot cleaner of claim 1, wherein the rib has a smaller thickness than a tread of the plurality of treads.
 5. The robot cleaner of claim 4, wherein the tread is formed such that a center thereof has a greater thickness than both ends thereof in the width direction of the wheel body.
 6. The robot cleaner of claim 5, wherein the tread has a contact face in contact with a ground in an octagonal shape.
 7. The robot cleaner of claim 1, wherein the rib has a smaller width than a tread of the plurality of treads.
 8. The robot cleaner of claim 1, wherein the rib is made of the same material as a tread of the plurality of treads.
 9. The robot cleaner of claim 1, wherein the rib is made of a material different from a material of a tread of the plurality of treads.
 10. The robot cleaner of claim 1, wherein an inter-tread space of a plurality of spaces are defined inter-tread spaces is respectively located between every adjacent two treads of the plurality of treads, and wherein the plurality of ribs are arranged in a remaining subset of said plurality of inter-tread spaces excluding at least one of the plurality of inter-tread spaces.
 11. The robot cleaner of claim 1, wherein the rib has elasticity to be bent by being pressed by a ground.
 12. The robot cleaner of claim 1, wherein the driving module is provided in the wheel cover to be movable in a vertical direction, wherein the rib has a height allowing the rib not to be in contact with each wheel cover in a state where the driving module is maximally in close contact with the wheel cover.
 13. The robot cleaner of claim 1, wherein the wheel further includes a plurality of bent portions defined by being recessed inward of the wheel body between the treads, wherein the rib protrudes from a portion of the plurality of bent portions radially outward of the wheel body.
 14. The robot cleaner of claim 1, wherein the central portion is positioned adjacent to a center of an adjacent one of the plurality of treads, and the wing portions are positioned on both sides of the central portion.
-