

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411392
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Shabtay; Gal et al.

Slim pop-out cameras and lenses for such cameras

Abstract

Digital cameras comprising a lens assembly comprising N lens elements L.sub.1-L.sub.N starting with L.sub.1 on an object side, wherein N is ≥ 4 , an image sensor having a sensor diagonal S.sub.D, and a pop-out mechanism that controls a largest air-gap d between two consecutive lens elements within lens elements L.sub.1 and L.sub.N to bring the camera to an operative pop-out state and a collapsed state, wherein the lens assembly has a total track length TTL in the operative pop-out state and a collapsed total track length cTTL in the collapsed state, wherein S.sub.D is in the range of 7-20 mm and wherein $cTTL/S.sub.D < 0.6$.

Inventors: Shabtay; Gal (Tel Aviv, IL), Yedid; Itay (Tel Aviv, IL), Goldenberg; Ephraim (Tel Aviv, IL), Korman; Tal (Tel Aviv, IL), Rudnick; Roy (Tel Aviv, IL), Goldstein; Kobi (Tel Aviv, IL), Kowal; Yiftah (Tel Aviv, IL), Dror; Michael (Tel Aviv, IL), Scherer; Michael (Tel Aviv, IL)

Applicant: Corephotonics Ltd. (Tel Aviv, IL)

Family ID: 79023434

Assignee: Corephotonics LTD. (Tel Aviv, IL)

Appl. No.: 19/010050

Filed: January 05, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250138396 A1	May. 01, 2025

Related U.S. Application Data

continuation parent-doc US 18768244 20240710 US 12292671 child-doc US 19010050
continuation parent-doc US 17567417 20220103 US 12066747 20240820 child-doc US 18768244
continuation parent-doc US 17460231 20210829 US 12072609 20240827 child-doc US 17567417

continuation-in-part parent-doc US 17291475 ABANDONED WO PCT/IB2020/058697 20200918
child-doc US 17460231
us-provisional-application US 63037836 20200611
us-provisional-application US 63026317 20200518
us-provisional-application US 62904913 20190924

Publication Classification

Int. Cl.: **G03B17/04** (20210101); **G02B7/02** (20210101); **G02B13/02** (20060101); **G02B13/06** (20060101); **G03B17/12** (20210101); **G03B30/00** (20210101); **H04N23/54** (20230101); **H04N23/55** (20230101); **H04N23/57** (20230101)

U.S. Cl.:

CPC **G03B17/04** (20130101); **G02B7/021** (20130101); **G02B7/026** (20130101); **G02B13/02** (20130101); **G02B13/06** (20130101); **G03B30/00** (20210101); **H04N23/54** (20230101); **H04N23/55** (20230101); **H04N23/57** (20230101); G03B17/12 (20130101)

Field of Classification Search

CPC: H04N (23/54); H04N (23/55); H04N (23/57); G02B (7/021); G02B (7/026); G02B (13/02); G02B (13/06); G03B (30/00); G03B (17/04); G03B (17/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2106752	12/1937	Land	N/A	N/A
2354503	12/1943	Cox	N/A	N/A
2378170	12/1944	Aklin	N/A	N/A
2441093	12/1947	Aklin	N/A	N/A
3388956	12/1967	Eggert et al.	N/A	N/A
3524700	12/1969	Eggert et al.	N/A	N/A
3558218	12/1970	Grey	N/A	N/A
3864027	12/1974	Harada	N/A	N/A
3942876	12/1975	Betensky	N/A	N/A
4134645	12/1978	Sugiyama et al.	N/A	N/A
4338001	12/1981	Matsui	N/A	N/A
4465345	12/1983	Yazawa	N/A	N/A
4792822	12/1987	Akiyama et al.	N/A	N/A
5000551	12/1990	Shibayama	N/A	N/A
5327291	12/1993	Baker et al.	N/A	N/A
5331465	12/1993	Miyano	N/A	N/A
5600488	12/1996	Minefuji et al.	N/A	N/A
5969869	12/1998	Hirai et al.	N/A	N/A
6014266	12/1999	Obama et al.	N/A	N/A
6035136	12/1999	Hayashi et al.	N/A	N/A
6038087	12/1999	Suzuki et al.	N/A	N/A
6147702	12/1999	Smith	N/A	N/A

6169636	12/2000	Kreitzer	N/A	N/A
6654180	12/2002	Ori	N/A	N/A
7187504	12/2006	Horiuchi	N/A	N/A
7206136	12/2006	Labaziewicz et al.	N/A	N/A
7274516	12/2006	Kushida et al.	N/A	N/A
7515351	12/2008	Chen et al.	N/A	N/A
7564635	12/2008	Tang	N/A	N/A
7643225	12/2009	Tsai	N/A	N/A
7660049	12/2009	Tang	N/A	N/A
7684128	12/2009	Tang	N/A	N/A
7688523	12/2009	Sano	N/A	N/A
7692877	12/2009	Tang et al.	N/A	N/A
7697220	12/2009	Iyama	N/A	N/A
7738186	12/2009	Chen et al.	N/A	N/A
7777972	12/2009	Chen et al.	N/A	N/A
7813057	12/2009	Lin	N/A	N/A
7821724	12/2009	Tang et al.	N/A	N/A
7826149	12/2009	Tang et al.	N/A	N/A
7826151	12/2009	Tsai	N/A	N/A
7869142	12/2010	Chen et al.	N/A	N/A
7898747	12/2010	Tang	N/A	N/A
7916401	12/2010	Chen et al.	N/A	N/A
7918398	12/2010	Li et al.	N/A	N/A
7957075	12/2010	Tang	N/A	N/A
7957076	12/2010	Tang	N/A	N/A
7957079	12/2010	Tang	N/A	N/A
7961406	12/2010	Tang et al.	N/A	N/A
8000031	12/2010	Tsai	N/A	N/A
8004777	12/2010	Sano et al.	N/A	N/A
8077400	12/2010	Tang	N/A	N/A
8149523	12/2011	Ozaki	N/A	N/A
8218253	12/2011	Tang	N/A	N/A
8228622	12/2011	Tang	N/A	N/A
8233224	12/2011	Chen	N/A	N/A
8253843	12/2011	Lin	N/A	N/A
8279537	12/2011	Sato	N/A	N/A
8363337	12/2012	Tang et al.	N/A	N/A
8395851	12/2012	Tang et al.	N/A	N/A
8400717	12/2012	Chen et al.	N/A	N/A
8451549	12/2012	Yamanaka et al.	N/A	N/A
8503107	12/2012	Chen et al.	N/A	N/A
8514502	12/2012	Chen	N/A	N/A
8570668	12/2012	Takakubo et al.	N/A	N/A
8718458	12/2013	Okuda	N/A	N/A
8780465	12/2013	Chae	N/A	N/A
8810923	12/2013	Shinohara	N/A	N/A
8854745	12/2013	Chen	N/A	N/A
8958164	12/2014	Kwon et al.	N/A	N/A
9185291	12/2014	Shabtay et al.	N/A	N/A

9201223	12/2014	Ohashi	N/A	N/A
9229194	12/2015	Yoneyama et al.	N/A	N/A
9235036	12/2015	Kato et al.	N/A	N/A
9279957	12/2015	Kanda et al.	N/A	N/A
9299510	12/2015	Cheong	N/A	H01H 13/86
9438792	12/2015	Nakada et al.	N/A	N/A
9488802	12/2015	Chen et al.	N/A	N/A
9568712	12/2016	Dror et al.	N/A	N/A
9678310	12/2016	Iwasaki et al.	N/A	N/A
9817213	12/2016	Mercado	N/A	N/A
9835834	12/2016	Li et al.	N/A	N/A
9869846	12/2017	Bone et al.	N/A	N/A
10330892	12/2018	Hashimoto	N/A	N/A
10948696	12/2020	Shabtay et al.	N/A	N/A
11340425	12/2021	Yamazaki	N/A	N/A
11347016	12/2021	Shabtay et al.	N/A	N/A
12066747	12/2023	Shabtay	N/A	H04N 23/54
12069371	12/2023	Shabtay et al.	N/A	N/A
12292671	12/2024	Shabtay	N/A	G02B 13/02
2002/0118471	12/2001	Imoto	N/A	N/A
2003/0048542	12/2002	Enomoto	N/A	N/A
2004/0095503	12/2003	Iwasawa et al.	N/A	N/A
2005/0041300	12/2004	Oshima et al.	N/A	N/A
2005/0062346	12/2004	Sasaki	N/A	N/A
2005/0128604	12/2004	Kuba	N/A	N/A
2005/0141103	12/2004	Nishina	N/A	N/A
2005/0168840	12/2004	Kobayashi et al.	N/A	N/A
2005/0270667	12/2004	Gurevich et al.	N/A	N/A
2006/0092524	12/2005	Konno	N/A	N/A
2006/0238902	12/2005	Nakashima et al.	N/A	N/A
2006/0262420	12/2005	Matsumoto et al.	N/A	N/A
2006/0275025	12/2005	Labaziewicz et al.	N/A	N/A
2007/0114990	12/2006	Godkin	N/A	N/A
2007/0183058	12/2006	Bito et al.	N/A	N/A
2007/0188884	12/2006	Yoshitsugu et al.	N/A	N/A
2007/0229983	12/2006	Saori	N/A	N/A
2007/0247726	12/2006	Sudoh	N/A	N/A
2007/0253689	12/2006	Nagai et al.	N/A	N/A
2008/0056698	12/2007	Lee et al.	N/A	N/A
2008/0094730	12/2007	Toma et al.	N/A	N/A
2008/0094738	12/2007	Lee	N/A	N/A
2008/0117527	12/2007	Nuno et al.	N/A	N/A
2008/0273250	12/2007	Nishio	N/A	N/A
2008/0291531	12/2007	Heimer	N/A	N/A
2008/0304161	12/2007	Souma	N/A	N/A
2009/0002839	12/2008	Sato	N/A	N/A
2009/0067063	12/2008	Asami et al.	N/A	N/A
2009/0122423	12/2008	Park et al.	N/A	N/A
2009/0135245	12/2008	Luo et al.	N/A	N/A

2009/0141365	12/2008	Jannard et al.	N/A	N/A
2009/0147368	12/2008	Oh et al.	N/A	N/A
2009/0161228	12/2008	Lee	N/A	N/A
2009/0225438	12/2008	Kubota	N/A	N/A
2009/0279191	12/2008	Yu	N/A	N/A
2009/0303620	12/2008	Abe et al.	N/A	N/A
2010/0007967	12/2009	Ohashi	N/A	N/A
2010/0026878	12/2009	Seo	N/A	N/A
2010/0033844	12/2009	Katano	N/A	N/A
2010/0060995	12/2009	Yumiki et al.	N/A	N/A
2010/0165476	12/2009	Eguchi	N/A	N/A
2010/0214664	12/2009	Chia	N/A	N/A
2010/0277813	12/2009	Ito	N/A	N/A
2011/0001838	12/2010	Lee	N/A	N/A
2011/0032409	12/2010	Rossi et al.	N/A	N/A
2011/0080655	12/2010	Mori	N/A	N/A
2011/0102667	12/2010	Chua et al.	N/A	N/A
2011/0102911	12/2010	Iwasaki	N/A	N/A
2011/0115965	12/2010	Engelhardt et al.	N/A	N/A
2011/0149119	12/2010	Matsui	N/A	N/A
2011/0157430	12/2010	Hosoya et al.	N/A	N/A
2011/0157721	12/2010	Ohtake	N/A	N/A
2011/0188121	12/2010	Goring et al.	N/A	N/A
2011/0249347	12/2010	Kubota	N/A	N/A
2012/0062783	12/2011	Tang et al.	N/A	N/A
2012/0069455	12/2011	Lin et al.	N/A	N/A
2012/0092777	12/2011	Tochigi et al.	N/A	N/A
2012/0105708	12/2011	Hagiwara	N/A	N/A
2012/0147489	12/2011	Matsuoka	N/A	N/A
2012/0154929	12/2011	Tsai et al.	N/A	N/A
2012/0194923	12/2011	Um	N/A	N/A
2012/0229920	12/2011	Otsu et al.	N/A	N/A
2012/0262806	12/2011	Lin et al.	N/A	N/A
2012/0314299	12/2011	Tashiro et al.	N/A	N/A
2013/0002933	12/2012	Topliss et al.	N/A	N/A
2013/0057971	12/2012	Zhao et al.	N/A	N/A
2013/0088788	12/2012	You	N/A	N/A
2013/0176479	12/2012	Wada	N/A	N/A
2013/0208178	12/2012	Park	N/A	N/A
2013/0271852	12/2012	Schuster	N/A	N/A
2013/0279032	12/2012	Suigetsu et al.	N/A	N/A
2013/0286488	12/2012	Chae	N/A	N/A
2014/0022436	12/2013	Kim et al.	N/A	N/A
2014/0028898	12/2013	Pavithran et al.	N/A	N/A
2014/0036112	12/2013	Scarff	N/A	N/A
2014/0063616	12/2013	Okano et al.	N/A	N/A
2014/0092487	12/2013	Chen et al.	N/A	N/A
2014/0139719	12/2013	Fukaya et al.	N/A	N/A
2014/0146216	12/2013	Okumura	N/A	N/A
2014/0160581	12/2013	Cho et al.	N/A	N/A

2014/0204480	12/2013	Jo et al.	N/A	N/A
2014/0240853	12/2013	Kubota et al.	N/A	N/A
2014/0285907	12/2013	Tang et al.	N/A	N/A
2014/0293453	12/2013	Ogino et al.	N/A	N/A
2014/0362274	12/2013	Christie et al.	N/A	N/A
2015/0022896	12/2014	Cho et al.	N/A	N/A
2015/0029601	12/2014	Dror et al.	N/A	N/A
2015/0116569	12/2014	Mercado	N/A	N/A
2015/0138431	12/2014	Shin et al.	N/A	N/A
2015/0153548	12/2014	Kim et al.	N/A	N/A
2015/0160438	12/2014	Okuda	N/A	N/A
2015/0168667	12/2014	Kudoh	N/A	N/A
2015/0177496	12/2014	Marks et al.	N/A	N/A
2015/0205068	12/2014	Sasaki	N/A	N/A
2015/0244942	12/2014	Shabtay et al.	N/A	N/A
2015/0253532	12/2014	Lin	N/A	N/A
2015/0253543	12/2014	Mercado	N/A	N/A
2015/0253647	12/2014	Mercado	N/A	N/A
2015/0323757	12/2014	Bone	N/A	N/A
2015/0373252	12/2014	Georgiev	N/A	N/A
2015/0373263	12/2014	Georgiev et al.	N/A	N/A
2016/0007008	12/2015	Molgaard et al.	N/A	N/A
2016/0033742	12/2015	Huang	N/A	N/A
2016/0044250	12/2015	Shabtay et al.	N/A	N/A
2016/0062084	12/2015	Chen et al.	N/A	N/A
2016/0062136	12/2015	Nomura et al.	N/A	N/A
2016/0070088	12/2015	Koguchi	N/A	N/A
2016/0085089	12/2015	Mercado	N/A	N/A
2016/0105616	12/2015	Shabtay et al.	N/A	N/A
2016/0187631	12/2015	Choi et al.	N/A	N/A
2016/0195691	12/2015	Bito et al.	N/A	N/A
2016/0202455	12/2015	Aschwanden et al.	N/A	N/A
2016/0212333	12/2015	Liege et al.	N/A	N/A
2016/0241756	12/2015	Chen	N/A	N/A
2016/0291295	12/2015	Shabtay et al.	N/A	N/A
2016/0306161	12/2015	Harada et al.	N/A	N/A
2016/0313537	12/2015	Mercado	N/A	N/A
2016/0341931	12/2015	Liu et al.	N/A	N/A
2016/0349504	12/2015	Kim et al.	N/A	N/A
2016/0353008	12/2015	Osborne	N/A	N/A
2017/0023778	12/2016	Inoue	N/A	N/A
2017/0052350	12/2016	Chen	N/A	N/A
2017/0094187	12/2016	Sharma et al.	N/A	N/A
2017/0102522	12/2016	Jo	N/A	N/A
2017/0115471	12/2016	Shinohara	N/A	N/A
2017/0153422	12/2016	Tang et al.	N/A	N/A
2017/0160511	12/2016	Kim et al.	N/A	N/A
2017/0199360	12/2016	Chang	N/A	N/A
2017/0276911	12/2016	Huang	N/A	N/A

2017/0276914	12/2016	Yao et al.	N/A	N/A
2017/0310952	12/2016	Adomat et al.	N/A	N/A
2017/0329108	12/2016	Hashimoto et al.	N/A	N/A
2017/0337703	12/2016	Wu et al.	N/A	N/A
2018/0024319	12/2017	Lai et al.	N/A	N/A
2018/0048825	12/2017	Wang	N/A	N/A
2018/0059365	12/2017	Bone et al.	N/A	N/A
2018/0059376	12/2017	Lin et al.	N/A	N/A
2018/0081149	12/2017	Bae et al.	N/A	N/A
2018/0120674	12/2017	Avivi et al.	N/A	N/A
2018/0149835	12/2017	Park	N/A	N/A
2018/0196236	12/2017	Ohashi et al.	N/A	N/A
2018/0196238	12/2017	Goldenberg et al.	N/A	N/A
2018/0217475	12/2017	Goldenberg et al.	N/A	N/A
2018/0218224	12/2017	Olmstead et al.	N/A	N/A
2018/0224630	12/2017	Lee et al.	N/A	N/A
2018/0253877	12/2017	Kozub et al.	N/A	N/A
2018/0268226	12/2017	Shashua et al.	N/A	N/A
2019/0025549	12/2018	Hsueh et al.	N/A	N/A
2019/0025554	12/2018	Son	N/A	N/A
2019/0049687	12/2018	Bachar et al.	N/A	N/A
2019/0075284	12/2018	Ono	N/A	N/A
2019/0086638	12/2018	Lee	N/A	N/A
2019/0094500	12/2018	Tseng et al.	N/A	N/A
2019/0107651	12/2018	Sade	N/A	N/A
2019/0121216	12/2018	Shabtay et al.	N/A	N/A
2019/0155002	12/2018	Shabtay et al.	N/A	N/A
2019/0170965	12/2018	Shabtay et al.	N/A	N/A
2019/0187443	12/2018	Jia et al.	N/A	N/A
2019/0187486	12/2018	Goldenberg et al.	N/A	N/A
2019/0196148	12/2018	Yao et al.	N/A	N/A
2019/0215440	12/2018	Rivard et al.	N/A	N/A
2019/0222758	12/2018	Goldenberg et al.	N/A	N/A
2019/0235202	12/2018	Smyth et al.	N/A	N/A
2019/0305403	12/2018	Wang	N/A	H01Q 1/243
2019/0353874	12/2018	Yeh et al.	N/A	N/A
2019/0363498	12/2018	Cox	N/A	B25J 19/0029
2020/0057240	12/2019	Yu et al.	N/A	N/A
2020/0064597	12/2019	Shabtay et al.	N/A	N/A
2020/0084358	12/2019	Nadamoto	N/A	N/A
2020/0192069	12/2019	Makeev et al.	N/A	N/A
2020/0221026	12/2019	Fridman et al.	N/A	N/A
2020/0241233	12/2019	Shabtay et al.	N/A	N/A
2020/0333691	12/2019	Shabtay et al.	N/A	N/A
2020/0400926	12/2019	Bachar	N/A	N/A
2021/0026117	12/2020	Yao	N/A	N/A
2021/0048628	12/2020	Shabtay et al.	N/A	N/A
2021/0048649	12/2020	Goldenberg et al.	N/A	N/A
2021/0165192	12/2020	Goldenberg et al.	N/A	N/A

2021/0263276	12/2020	Huang et al.	N/A	N/A
2021/0364746	12/2020	Chen	N/A	N/A
2021/0396974	12/2020	Kuo	N/A	N/A
2022/0004085	12/2021	Shabtay et al.	N/A	N/A
2022/0046151	12/2021	Shabtay et al.	N/A	N/A
2022/0066168	12/2021	Shi	N/A	N/A
2022/0113511	12/2021	Chen	N/A	N/A
2022/0128886	12/2021	Shabtay	N/A	H04N 23/55
2022/0206264	12/2021	Rudnick et al.	N/A	N/A
2022/0232167	12/2021	Shabtay et al.	N/A	N/A
2023/0080199	12/2022	Eromaki et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101025470	12/2006	CN	N/A
101634738	12/2009	CN	N/A
102147519	12/2010	CN	N/A
102193162	12/2010	CN	N/A
102466865	12/2011	CN	N/A
102466867	12/2011	CN	N/A
102147519	12/2012	CN	N/A
103576290	12/2013	CN	N/A
103698876	12/2013	CN	N/A
104297906	12/2014	CN	N/A
104407432	12/2014	CN	N/A
105467563	12/2015	CN	N/A
105657290	12/2015	CN	N/A
106680974	12/2016	CN	N/A
104570280	12/2016	CN	N/A
105467563	12/2018	CN	N/A
112764200	12/2020	CN	N/A
S54157620	12/1978	JP	N/A
S59121015	12/1983	JP	N/A
6165212	12/1985	JP	N/A
S6370211	12/1987	JP	N/A
H0233117	12/1989	JP	N/A
406059195	12/1993	JP	N/A
H06258702	12/1993	JP	N/A
H06347687	12/1993	JP	N/A
H07120673	12/1994	JP	N/A
H07325246	12/1994	JP	N/A
H07333505	12/1994	JP	N/A
H08179215	12/1995	JP	N/A
H09211326	12/1996	JP	N/A
H11223771	12/1998	JP	N/A
2000131610	12/1999	JP	N/A
2000292848	12/1999	JP	N/A
3210242	12/2000	JP	N/A
2002365549	12/2001	JP	N/A

2003329932	12/2002	JP	N/A
2004226563	12/2003	JP	N/A
2004247887	12/2003	JP	N/A
2004334185	12/2003	JP	N/A
2006195139	12/2005	JP	N/A
2007133096	12/2006	JP	N/A
2007164065	12/2006	JP	N/A
2007219199	12/2006	JP	N/A
2007306282	12/2006	JP	N/A
2008111876	12/2007	JP	N/A
2008191423	12/2007	JP	N/A
2010032936	12/2009	JP	N/A
2010164841	12/2009	JP	N/A
2011145315	12/2010	JP	N/A
2011151448	12/2010	JP	N/A
2012203234	12/2011	JP	N/A
2012230323	12/2011	JP	N/A
2013003317	12/2012	JP	N/A
2013003754	12/2012	JP	N/A
2013101213	12/2012	JP	N/A
2013105049	12/2012	JP	N/A
2013106289	12/2012	JP	N/A
2013148823	12/2012	JP	N/A
2014142542	12/2013	JP	N/A
2017116679	12/2016	JP	N/A
2018059969	12/2017	JP	N/A
2019028249	12/2018	JP	N/A
2019113878	12/2018	JP	N/A
20080088477	12/2007	KR	N/A
20090019525	12/2008	KR	N/A
20090131805	12/2008	KR	N/A
20110058094	12/2010	KR	N/A
20110115391	12/2010	KR	N/A
20120068177	12/2011	KR	N/A
20140135909	12/2012	KR	N/A
20140023552	12/2013	KR	N/A
20160000759	12/2015	KR	N/A
101632168	12/2015	KR	N/A
20160115359	12/2015	KR	N/A
M602642	12/2019	TW	N/A
2013058111	12/2012	WO	N/A
2013063097	12/2012	WO	N/A
2018130898	12/2017	WO	N/A
WO-2021059097	12/2020	WO	G02B 13/0015

OTHER PUBLICATIONS

A compact and cost effective design for cell phone zoom lens, Chang et al., Sep. 2007, 8 pages.

cited by applicant

Consumer Electronic Optics: How small a lens can be? The case of panomorph lenses, Thibault et

al., Sep. 2014, 7 pages. cited by applicant

Optical design of camera optics for mobile phones, Steinich et al., 2012, pp. 51-58 (8 pages). cited by applicant

The Optics of Miniature Digital Camera Modules, Bareau et al., 2006, 11 pages. cited by applicant

Modeling and measuring liquid crystal tunable lenses, Peter P. Clark, 2014, 7 pages. cited by applicant

Mobile Platform Optical Design, Peter P. Clark, 2014, 7 pages. cited by applicant

Boye et al., "Ultrathin Optics for Low-Profile Innocuous Imager", Sandia Report, 2009, pp. 56-56. cited by applicant

"Cheat sheet: how to understand f-stops", Internet article, Digital Camera World, 2017. cited by applicant

Husain Sumra: "Security Camera Field Of View Tips—How To Position Your Camera I Ooma", Aug. 2, 2019 (Aug. 2, 2019), Internet article, Ooma. cited by applicant

Search Report in related EP patent application 24213123.3, dated Feb. 28, 2025. cited by applicant

Primary Examiner: Haskins; Twyler L

Assistant Examiner: Morehead, III; John H

Attorney, Agent or Firm: Nathan & Associates

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This is a continuation of U.S. patent application Ser. No. 18/768,244 filed Jul. 10, 2024 (now allowed), which was a continuation of U.S. patent application Ser. No. 17/567,417 filed Jan. 3, 2022 (now U.S. Pat. No. 12,066,747), which was a continuation of U.S. patent application Ser. No. 17/460,231 filed Aug. 29, 2021 (now U.S. Pat. No. 12,072,609), which was a continuation in part (CIP) of U.S. patent application Ser. No. 17/291,475 filed May 5, 2021, which was a 371 from international application PCT/IB2020/058697 filed Sep. 18, 2020, and is related to and claims priority from U.S. Provisional Patent Applications No. 62/904,913 filed Sep. 24, 2019, 63/026,317 filed May 18, 2020 and 63/037,836 filed Jun. 11, 2020, all of which are incorporated herein by reference in their entirety.

FIELD

(1) The present disclosure relates in general to digital cameras, and more particularly, to digital cameras with pop-out mechanisms and lenses.

BACKGROUND

(2) Compact multi-aperture digital cameras (also referred to as "multi-lens cameras" or "multi-cameras") and in particular dual-aperture (or "dual-camera") and triple-aperture (or "triple-camera") digital cameras are known. Miniaturization technologies allow incorporation of such cameras in compact portable electronic devices such as tablets and mobile phones (the latter referred to hereinafter generically as "smartphones"), where they provide advanced imaging capabilities such as zoom, see e.g. co-owned PCT patent application No. PCT/IB2063/060356, which is incorporated herein by reference in its entirety. A typical triple-camera system (exemplarily including an ultra-wide-angle (or "Ultra-Wide" or "UW") camera, wide-angle (or "Wide") camera and a telephoto (or "Tele") camera.

(3) A challenge with dual-aperture zoom cameras relates to camera height and size of image sensor ("Sensor Diagonal" or S.sub.D). There is a large difference in the height (and also of the total track length or "TTL") of the Tele and Wide cameras. FIG. 1A illustrates schematically the definition of

various entities such as TTL, effective focal length (EFL) and back focal length (BFL). The TTL is defined as the maximal distance between the object-side surface of a first lens element and a camera image sensor plane. The BFL is defined as the minimal distance between the image-side surface of a last lens element and a camera image sensor plane. In the following, “W” and “T” subscripts refer respectively to Wide and Tele cameras. The EFL has a meaning well known in the art. In most miniature lenses, the TTL is larger than the EFL, as in FIG. 1A.

(4) FIG. 1B shows an exemplary camera system having a lens with a field of view (FOV), an EFL and an image sensor with a sensor width S. For fixed width/height ratios of a (normally rectangular) image sensor, the sensor diagonal is proportional to the sensor width and height. The horizontal FOV relates to EFL and sensor width as follows:

$$(5) \tan\left(\frac{\text{FOV}}{2}\right) = \frac{S}{2} / \text{EFL}$$

This shows that for realizing a camera with a larger image sensor width (i.e. larger sensor diagonal) but same FOV, a larger EFL is required.

(6) In mobile devices, typical Wide cameras have 35 mm equivalent focal lengths (“35 eqFL”), ranging from 22 mm to 28 mm. Image sensors embedded in mobile cameras are smaller than full frame sensors and actual focal lengths in Wide cameras range from 3.2 mm to 7 mm, depending on the sensor size and FOV. In most lenses designed for such cameras, the TTL/EFL ratio is larger than 1.0 and is typically between 1.0 and 1.3. Another characteristic of these lenses is that their TTL-to-sensor diagonal ratio TTL/SD is typically in the range of 0.6 to 0.7. Embedding larger sensors in Wide cameras is desirable, but require larger EFL for maintaining the same FOV, resulting in larger TTL, which is undesirable.

(7) Many mobile devices include now both Tele and Wide cameras. The Tele camera enables optical zoom and other computational photography features such as digital Bokeh. Depending on the Wide camera characteristics and permissible module height, the 35 eqFL of mobile device Tele cameras ranges from 45 mm to 100 mm. The TTL of lenses designed for Tele cameras is smaller than the EFL of such lenses, typically satisfying $0.7 < \text{TTL}/\text{EFL} < 1.0$. Typical Tele EFL values range from 6 mm to 10 mm (without applying 35 mm equivalence conversion) in vertical (non-folded) Tele cameras and from 10 mm to 30 mm in folded Tele cameras. Larger EFL is desirable for enhancing the optical zoom effect but it results in larger TTL, which is undesirable.

(8) In a continuous attempt to improve the obtained image quality, there is a need to incorporate larger image sensors into the Wide and Tele cameras. Larger sensors allow for improved low-light performance and larger number of pixels, hence improving the spatial resolution as well. Other image quality characteristics, such as noise characteristics, dynamic range and color fidelity may also improve as the sensor size increases.

(9) As the Wide camera sensor becomes larger, the required EFL is larger (for the same 35 mm equivalent focal length), the lens TTL increases and the camera module height becomes larger, resulting in a limit on the permissible sensor size when considering the allowed mobile device thickness or other industrial design constraints. In Wide cameras of most mobile devices, the sensor pixel array size full diagonal ranges from about 4.5 mm (typically referred to as 1/4" sensor) to 16 mm (typically referred to 1" sensor).

(10) It would be beneficial to have Wide and/or Tele lens designs that support large EFLs for large sensor diagonals (optical zoom) while still having small TTL for slim design. The latter is presented for example in co-owned U.S. provisional patent application No. 62/904,913.

SUMMARY

(11) In various examples, there are provided digital cameras comprising: an optics module comprising a lens assembly that includes N lens elements $L_{\text{sub}.1}$ - $L_{\text{sub}.N}$ starting with $L_{\text{sub}.1}$ on an object side, wherein $N \geq 4$; an image sensor having a sensor diagonal $S_{\text{sub}.D}$ in the range of 5-20 mm; and a pop-out mechanism configured to control at least one air-gap between lens elements or between a lens element and the image sensor to bring the camera to an operative pop-out state and to a collapsed state, wherein the lens assembly has a total track length TTL in the operative pop-out

state and a collapsed total track length $cTTL$ in the collapsed state, and wherein $cTTL/S_{sub.D} < 0.6$.

(12) For simplicity, in the description below, “lens” may be used instead of “lens assembly”.

(13) Henceforth and for simplicity, the use of the term “pop-out” before various components may be skipped, with the understanding that if defined the first time as being a “pop-out” component, that component is such throughout this description.

(14) In various examples of cameras above and below, the window pop-up mechanism includes a window frame engageable with the optics module, wherein the window frame does not touch the optics module in the pop-out state and wherein the window frame is operable to press on the optics module to bring the camera to the collapsed state. The window frame includes a window that is not in direct contact with the lens.

(15) In some examples, the largest air-gap d is between $L_{sub.N-1}$ and $L_{sub.N}$.

(16) In some examples, the largest air-gap d is between $L_{sub.N-2}$ and $L_{sub.N-1}$ or between $L_{sub.N-1}$ and $L_{sub.N}$, and the lens assembly has a 35 mm equivalent focal length 35 eqFL between 40 mm and 150 mm. In such an example, d may be larger than $TTL/5$.

(17) In some examples, $cTTL/S_{sub.D} < 0.55$.

(18) In some examples, $S_{sub.D}$ is in the range of 10 mm to 15 mm.

(19) In some examples, a camera as above or below is included in a multi-camera together with a second camera having a second total track length $TTL_{sub.2}$ in the range of $0.9 \times TTL$ to $1.1 \times TTL$.

(20) In some examples, the lens assembly has a 35 mm equivalent focal length 35 eqFL larger than 24 mm.

(21) In some examples, the lens assembly has an effective focal length EFL and ratio TTL/EFL is smaller than 1.4 and larger than 1.0.

(22) In various examples, there are provided digital cameras comprising: an optics module comprising a lens assembly that includes N lens elements $L_{sub.1}$ - $L_{sub.N}$ starting with $L_{sub.1}$ on an object side, wherein $N \geq 4$ and wherein the lens assembly has a back focal length BFL that is larger than any air-gap between lens elements and has an effective focal length EFL in the range of 7 mm to 18 mm; a pop-out mechanism configured to actuate the lens assembly to an operative pop-out state and to a collapsed state, wherein the lens assembly has a total track length TTL in the operative pop-out state and a collapsed total track length $cTTL$ in the collapsed state, and wherein the pop-out mechanism is configured to control the BFL such that $cTTL/EFL < 0.55$; and an image sensor having sensor diagonal $S_{sub.D}$.

(23) In some examples, a pop-out mechanism includes a window pop-out mechanism based on a pin-groove assembly, and one or more of the pins slide in vertically oriented grooves and one or more pins slide in angled grooves that have an angle of 20-80 degrees, 30-70 degrees or 40-60 degrees with respect to the vertical.

(24) In some examples, a pop-out mechanism includes a barrel pop-out mechanism that comprises springs and a guiding and positioning mechanism that enables sufficient z-decenter and xy-decenter accuracy between lens elements in the operative pop-out state and enables repeatability in switching between operative and collapsed states, wherein the sufficient decenter accuracy is less than 0.1 mm decenter and wherein the repeatability is less than 0.05 mm decenter. In other examples, the sufficient decenter accuracy is less than 0.8 mm decenter and the repeatability is less than 0.04 mm decenter. In yet other examples, the sufficient decenter accuracy is less than 0.6 mm decenter and the repeatability is less than 0.03 mm decenter. The guiding and positioning mechanism may be based on a pin and groove assembly, on a stopper or on a kinematic coupling mechanism. In some examples, a guiding mechanism may be based on a pin-groove assembly and a positioning mechanism based on a magnetic force.

(25) In some examples, $S_{sub.D}$ is in the range of 4.5 mm to 10 mm and the lens assembly has a 35 eqFL larger than 45 mm and smaller than 180 mm.

(26) In some examples, $S_{sub.D}$ is in the range of 10 mm to 20 mm and the lens assembly has a 35 eqFL larger than 40 mm and smaller than 180 mm.

- (27) In some examples, ratio TTL/EFL is smaller than 1.0 and larger than 0.7.
- (28) In some examples, BFL is larger than $TTL/3$ and smaller than $TTL/1.5$.
- (29) In some examples of cameras as above or below, the lens has a lens element with a largest lens diameter $d_{sub.L}$, wherein a penalty between a largest diameter $d_{sub.module}$ of the optics module and the largest lens diameter $d_{sub.L}$ is smaller than 4 mm, than 2 mm or even than 1 mm.
- (30) In various examples, there are provided multi-cameras comprising: a first camera that includes a first lens assembly with a first field of view $FOV_{sub.1}$ and N lens elements $L_{sub.1}$ - $L_{sub.N}$ starting with $L_{sub.1}$ on an object side wherein $N \geq 4$, a first image sensor having a sensor diagonal $S_{sub.D1}$, and a pop-out mechanism that controls a largest air-gap d between two consecutive lens elements to bring the first camera to an operative pop-out state and a collapsed state, wherein the first lens assembly has a first 35 mm equivalent focal length $35\ eqFL_{sub.1}$, a total track length $TTL_{sub.1}$ in the operative state and a collapsed total track length $cTTL_{sub.1}$ in the collapsed state, wherein $S_{sub.D1}$ is in the range 7-20 mm and wherein $cTTL_{sub.1}/S_{sub.D1} < 0.6$; and a second camera having a second camera effective focal length $EFL_{sub.2}$ of 7-18 mm and including a second lens assembly with a second field of view $FOV_{sub.2}$ smaller than $FOV_{sub.1}$, the second lens assembly comprising M lens elements $L_{sub.1}$ - $L_{sub.M}$ starting with $L_{sub.1}$ on an object side wherein $M \geq 4$, and a pop-out mechanism configured to actuate the second camera to an operative state and a collapsed state, wherein the second lens assembly has a second 35 mm equivalent focal length $35\ eqFL_{sub.2}$, a total track length $TTL_{sub.2}$ in the operative state and a collapsed total track length $cTTL_{sub.2}$ in the collapsed state, and wherein $cTTL/EFL < 0.55$.
- (31) In some examples, $cTTL_{sub.1} = cTTL_{sub.2} \pm 10\%$.
- (32) In some examples, $35\ eqFL_{sub.2} \geq 1.5 \times 35\ eqFL_{sub.1}$.
- (33) In some examples, $35\ eqFL_{sub.1}$ is larger than 24 mm.
- (34) In some examples, $35\ eqFL_{sub.2}$ is larger than 45 mm.
- (35) In various examples, there are provided multi-cameras comprising: a Wide camera comprising a lens barrel carrying a Wide lens assembly comprising $N \geq 4$ lens elements $L_{sub.1}$ - $L_{sub.N}$ starting with $L_{sub.1}$ on an object side, an image sensor having a Wide sensor diagonal $S_{sub.DW}$, and a first pop-out mechanism that controls an air-gap $d_{sub.N-1}$ between lens elements $L_{sub.N}$ and $L_{sub.N-1}$ to bring the camera to an operative state and a collapsed state, wherein the Wide lens assembly has a field of view $FOV_{sub.W}$, a total track length $TTL_{sub.W}$ in the operative state and a collapsed total track length $cTTL_{sub.W}$ in the collapsed state, wherein if $S_{sub.DW}$ is in the range 10-16 mm then $cTTL_{sub.W}/S_{sub.DW} < 0.6$; and a Tele camera comprising a lens barrel carrying a Tele lens assembly comprising N is ≥ 4 lens elements $L_{sub.1}$ - $L_{sub.N}$ starting with $L_{sub.1}$ on an object side, a Tele image sensor having a sensor diagonal $S_{sub.DT}$ and a second pop-out mechanism that controls an air-gap between lens element $L_{sub.N}$ and the Tele image sensor to bring the camera to an operative state and a collapsed state, wherein the Tele lens assembly has a field of view $FOV_{sub.T}$ smaller than $FOV_{sub.W}$, a $TTL_{sub.T}$ in the operative state and a $cTTL_{sub.T}$ in the collapsed state, wherein if $S_{sub.DT}$ is in the range 4.5-10 mm then $cTTL_{sub.T} < EFL_{sub.T} < 0.55$, and wherein $cTTL_{sub.W} = cTTL_{sub.T} \pm 10\%$.
- (36) In some examples, the multi-camera is embedded in a device having a device exterior surface, and in an operative state the camera extends beyond the device exterior surface by 2 mm-7 mm and in a non-operative state the cameras extends beyond the device exterior surface by less than 2 mm.
- (37) In some examples, $7\ mm < TTL_{sub.W} < 13\ mm$, $1.0 < TTL_{sub.W}/EFL_{sub.W} < 1.3$ and $d_{sub.N-1}$ is greater than $TTL/4$.
- (38) In some examples, there is provided a camera comprising: a lens assembly comprising N lens elements $L_{sub.1}$ - $L_{sub.N}$ starting with $L_{sub.1}$ on an object side wherein $N \geq 4$; a curved image sensor having a sensor diagonal $S_{sub.D}$ in the range of 7-20 mm; and a pop-out mechanism that controls an air-gap d between $L_{sub.N}$ and the image sensor to bring the camera to an operative pop-out state and a collapsed state, wherein the lens assembly has a total track length TTL in the operative pop-out state and a collapsed total track length $cTTL$ in the collapsed state, wherein

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Non-limiting examples of embodiments disclosed herein are described below with reference to figures attached hereto that are listed following this paragraph. Identical structures, elements or parts that appear in more than one figure are generally labeled with a same numeral in all the figures in which they appear. If identical elements are shown but numbered in only one figure, it is assumed that they have the same number in all figures in which they appear. The drawings and descriptions are meant to illuminate and clarify embodiments disclosed herein and should not be considered limiting in any way. In the drawings:
- (2) FIG. 1A illustrates schematically the definition of various entities such as TTL and EFL;
- (3) FIG. 1B shows definitions of FOV, EFL and S for a thin lens approximation or equivalence;
- (4) FIG. 2A shows a cross sectional view of a pop-out camera disclosed herein in an in a pop-out state and incorporated in a host device;
- (5) FIG. 2B shows a cross sectional view of a pop-out frame of the camera of FIG. 2A;
- (6) FIG. 2C shows a cross sectional view of the camera of FIG. 2A in a collapsed state;
- (7) FIG. 2D shows a cross sectional view of the frame shown in FIG. 2B in a collapsed state;
- (8) FIG. 3A shows a perspective view of the camera of FIG. 2A in the pop-out state;
- (9) FIG. 3B shows a perspective view of the camera of FIG. 2A in the collapsed state;
- (10) FIG. 4A shows in cross section a lens module in the camera of FIG. 2A;
- (11) FIG. 4B shows the same as FIG. 4A in a perspective view;
- (12) FIG. 4C shows an example of an optical lens system that may be used in a pop-out camera disclosed herein;
- (13) FIG. 5A shows in cross section a lens module in the camera of FIG. 2A in the collapsed state;
- (14) FIG. 5B shows the same as FIG. 5A in a perspective view;
- (15) FIG. 6A shows in cross section another example of a lens module in a pop-out state;
- (16) FIG. 6B shows in cross section the pop-out lens module of FIG. 6A in a collapsed state;
- (17) FIGS. 6C and 6D shows other examples of an optical lens system that may be used in a pop-out camera disclosed herein;
- (18) FIG. 7 shows a perspective view of the lens module of FIG. 6A;
- (19) FIG. 8 shows a perspective view of the lens module of FIG. 6B;
- (20) FIG. 9A shows a perspective view of an actuator of the pop-out mechanism in a pop-out state;
- (21) FIG. 9B shows a perspective view of the actuator of FIG. 9A in a collapsed state;
- (22) FIG. 10 shows yet another example of an optical lens system that may be used in a pop-out camera disclosed herein;
- (23) FIG. 11A shows an example of a smartphone with a dual-camera that includes a regular folded Tele camera and an upright pop-out Wide camera;
- (24) FIG. 11B shows details of the cameras of FIG. 11A with the Wide pop-out camera being in a pop out state;
- (25) FIG. 11C shows the smartphone of FIG. 11A with the Wide pop-out camera in a collapsed state;
- (26) FIG. 11D shows details of the cameras of FIG. 11A, with the Wide pop-out camera being in a collapsed state;
- (27) FIG. 12A shows another example of a smartphone with a dual-camera comprising an upright Tele camera and an upright Wide camera, with both cameras in a pop-out state;
- (28) FIG. 12B shows details of the cameras of the smartphone in FIG. 12A in a pop-out state;

(29) FIG. 12C shows the smartphone of FIG. 12A with both cameras in a collapsed state;

(30) FIG. 12D shows details of the cameras of the smartphone in FIG. 12A in a collapsed state;

(31) FIG. 13 shows yet another example of an optical lens system can be included in a pop-out camera disclosed herein;

(32) FIG. 14A shows in cross sectional view another example of a pop-out camera disclosed herein in a pop-out state and incorporated in a host device;

(33) FIG. 14B shows a perspective view of a frame in the pop-out camera of FIG. 14A;

(34) FIG. 14C shows in cross section the camera of FIG. 14A in a collapsed state;

(35) FIG. 14D shows a perspective view of the frame of FIG. 14B in a collapsed state;

(36) FIG. 15A shows in cross-section a pop-out mechanism in the camera of FIG. 14A;

(37) FIG. 15B shows the mechanism of FIG. 15A in a collapsed state;

(38) FIG. 16A shows a cross sectional view of another example of a pop-out optics module in a pop-out state;

(39) FIG. 16B shows a perspective view of the pop-out optics module of FIG. 16A;

(40) FIG. 17A shows in perspective view the pop-out optics module of FIG. 16A in a pop-out state;

(41) FIG. 17B shows in perspective view the pop-out optics module of FIG. 16A in a collapsed state;

(42) FIG. 18A shows a perspective view of an optics frame in the optics module of FIG. 16A a pop-out state;

(43) FIG. 18B shows a perspective view of the optics frame of FIG. 18A in a collapsed state;

(44) FIG. 18C shows a section of the optics frame of FIG. 18A in more detail;

(45) FIG. 18D shows a section of optics frame of FIG. 18B in more detail;

(46) FIG. 18E shows the optics frame of FIG. 18A in a top view;

(47) FIG. 18F shows the optics frame of FIG. 18A in an exploded view;

(48) FIG. 19A shows a perspective view of yet another example of an optics module in a pop-out state;

(49) FIG. 19B shows the optics module of FIG. 19A in a top view;

(50) FIG. 19C shows the optics module of FIG. 19A in a pop-out state in a cross-sectional view;

(51) FIG. 19D shows the optics module of FIG. 19A in a collapsed state in a cross-sectional view;

(52) FIG. 19E shows a top cover and a magnet of the optics module of FIG. 19A in a perspective view;

(53) FIG. 19F shows the top cover and magnet of the optics module of FIG. 19E in a top view;

(54) FIG. 20A shows a magnet part of window position measurement mechanism in a side view;

(55) FIG. 20B shows the window position measurement mechanism of FIG. 20A in a perspective view;

(56) FIG. 20C shows a side view of 3 magnets and a Hall sensor of the window position measurement mechanism of FIG. 20A in a collapsed state;

(57) FIG. 20D shows a side view of the 3 magnets and the Hall sensor of the window position measurement mechanism of FIG. 20A in a pop-out state;

(58) FIG. 20E shows an example of a design and magnetic field of the window position measurement mechanism of FIG. 20A;

(59) FIG. 20F shows an example of a magnet configuration that may be included in the position measurement mechanism;

(60) FIG. 20G shows another example of another magnet configuration that may be included in a position measurement mechanism.

DETAILED DESCRIPTION

(61) FIG. 2A shows in cross sectional view (through cross section marked 2A-2A in FIG. 3A) an example numbered **200** of a pop-out camera disclosed herein incorporated in a “host” device **250** (e.g. a smartphone, tablet, etc.). In FIG. 2A, camera **200** is shown in an operative or “pop-out” state (and thus referred to as a “camera in pop-out state”). Camera **200** has also a collapsed (“c” or “non-

operative”) state, shown in FIG. 2C. In this state, the camera is not operative as a camera in pop-out state. FIG. 3A shows camera **200** in the pop-out state and FIG. 3B shows camera **200** in the collapsed state, both in perspective views.

(62) Camera **200** comprises a general pop-out mechanism **210** and a pop-out optics module **240**. Optics module **240** comprises a lens barrel holder **202** carrying a pop-out lens barrel **204** with a pop-out lens assembly **206**, and in some cases (“examples”) an image sensor **208**. In some examples, the image sensor may be separate from the optics module. Lens barrel **204** and window **216** are separated by an air-gap **222** of, for example, 0.15-3 mm. Air-gap **222** allows for a movement of the lens barrel by 0.1-3 mm for performing auto-focus (AF) and optical image stabilization (OIS) by moving the lens as known in the art. Optics module **240** is covered by a cover **232**. In some examples, the pop-out lens barrel (e.g. a lens barrel **602**) may be divided into two or more sections, e.g. in a fixed lens barrel section and a collapsible barrel section.

(63) General pop-out mechanism **210** comprises a “window” pop-out mechanism (external to the optics module) and a “barrel” pop-out mechanism with some parts external to and some parts internal to the optics module. The window pop-out mechanism raises and lowers the window. The barrel pop-out mechanism enables the pop-out and collapsed lens barrel states.

(64) The window pop-out mechanism includes parts shown in detail for example in FIG. 9A-B, FIG. 14B, FIG. 14D, FIGS. 15A-B, FIGS. 20A-F. Specifically, the window pop-out mechanism comprises an actuator like **212** or **212'**, a pop-out frame **220** (see e.g. FIG. 2B) that includes a window frame **214** carrying a window **216** that covers an aperture **218** of the camera, and an external module seal **224**. External module seal **224** prevents particles and fluids from entering the camera and host device **250**. In some embodiments (e.g. in a frame **220'** described with reference to FIGS. 14A-D), a pop-out frame may include additional parts such as a cam follower (e.g. **1402** in FIG. 14A), a side limiter (e.g. **1406** in FIG. 14A) and a window position measurement mechanism (e.g. **1420** in FIG. 14B).

(65) The barrel pop-out mechanism includes parts shown in detail for example in FIGS. 4A, 5A, 6A-B, 14A, 14C, 16A, 17A-B, 18A-F and 19A-F. Specifically, the barrel pop-out mechanism may include one or more springs **230**, pop-out lens barrel **204** with pop-out lens assembly **206**, one or more springs **230** and a guiding and positioning mechanism (see e.g. FIGS. 19A-19B and description below). The one or more springs push optics module **240** towards frame **220**, i.e. when frame **220** moves upwards for switching from a collapsed state to a pop-out state, no further actuation mechanism within the optics module is required.

(66) The guiding and positioning mechanism positions the lens groups and optical components in fixed distance and orientation. In an example, the guiding and positioning mechanism comprises a pin **242** and a groove **244** (see FIG. 2C, FIG. 4A and FIG. 5A). In some examples, the guiding and positioning mechanism may include a stopper **618** (see FIG. 6A-B), a kinematic coupling mechanism (see FIG. 18A-D) or a magnet-yoke assembly (see FIGS. 19A-F). In some examples, the guiding and positioning mechanism works by means of an interplay between an optics module and another component of a camera such as camera **200** (see e.g. FIGS. 6A-B and FIGS. 19A-F). Pin **242** and groove **244** provide a first example of a pin-groove assembly. Groove **244** may comprise a v-shaped groove or another groove, with groove **244** having legs at an angle of e.g. 30-150 degrees. Other pin-groove assemblies are described below. In some examples, the guiding and positioning mechanism is included in an optics module in its entirety (see e.g. FIG. 4A and FIG. 5A and FIG. 18A-D).

(67) The pin-groove assembly with pin **242** and groove **244** provides mechanical stability and repeatability in the X-Z plane and in the Y plane of the coordinate system shown. Stopper **618** provides mechanical stability and repeatability in Y plane. In some examples, other pins such as pins **1206** (see FIG. 12B and FIG. 12D) may be used for providing mechanical stability and repeatability in the X-Z plane.

(68) The lens, the image sensor and (optionally) an optical window or “filter” (e.g. IR filter) **234**

form a pop-out optical lens system **260** (see e.g. FIG. 4C). The image sensor may have a sensor diagonal S.sub.D in the range 3.5-30 mm. For a lens having an EFL of 5 mm to 25 mm, this typically represents a 35 eqFL in the range 10-300 mm. Sensor diagonal S.sub.D connects to a sensor width W and a height H via $S_{sub.D} = \sqrt{(W_{sup.2} + H_{sup.2})}$. In other examples EFL may be 8 mm to 28 mm.

(69) To switch between pop-out and collapsed states, pop-out mechanism **210** causes the following movements in frame **220** (where all movements are defined relative to the host device and the coordinate systems shown): a horizontal (i.e. in the X-Z plane) movement of the cam follower and a vertical (i.e. in the Y direction) movement of the window frame. The movement in frame **220** causes a vertical (Y direction) movement of the lens barrel (for a single group or “1G” lens) or of a collapsible section of the lens barrel (in a two group or “2G” lens) in optics module **240**. The image sensor and the side limiter do not move. Importantly, the barrel pop-out mechanism does not include an actuator.

(70) In the pop-out state shown in FIG. 2B, camera **200** forms a significant pop-out bump **226** with respect to an exterior surface **228** of host device **250**. Here, “significant” may be for example 1.5 mm-8 mm. In the pop-out state, camera **200** increases the height of host device **250** to a “height in a pop-out state”.

(71) The pop-out lens may be a Tele lens, for example as in FIG. 4C or FIG. 10 or FIG. 6D, or a Wide lens as in FIG. 6C or FIG. 13. Depending on the type of lens, a pop-out camera operates as a pop-out Tele camera or as a pop-out Wide camera. A pop-out Tele camera may have a FOV.sub.T of 20-50 deg. A pop-out Wide camera may have a FOV.sub.W of 50-120 deg. The TTL of the lens, measured from the first surface of the first lens element in the lens to the image sensor may be for example 6 mm-18 mm.

(72) FIG. 2D shows a cross sectional view of frame **220** in the collapsed state. Actuator **212** brings the camera to a collapsed state by performing work against the spring. In the collapsed state, the spring is in a compressed state, see also FIG. 4B. To switch camera **200** to the collapsed state, actuator **212** moves window frame **214** to apply pressure on lens barrel **204**. This translates into a movement of lens barrel **204** towards the image sensor. In the collapsed state, the TTL is a collapsed TTL (cTTL) and may be for example 5-12 mm. cTTL is always measured between a first surface of lens element L1 on the image side (marked S2) and an imaging surface of the image sensor along the optical axis marked S16. The difference between cTTL and TTL stems from a modified BFL with respect to the pop-out state. Camera **200** is designed such that there is a large BFL in the operative state. This large BFL can be collapsed to bring the camera to a collapsed state, achieving a slim camera design. In the collapsed state, the camera forms a collapsed bump (c-bump) **236** with respect to device exterior surface **228**. The c-bump may have for example a size (height) of 0-3 mm. In the collapsed state, the height of host device **250** is a “height in the collapsed state” that is much smaller than the height in the pop-out state but still larger than the host device height by the c-bump **236**.

(73) Camera **200** may be designed to support, in some examples, accuracy tolerances for decenter of e.g. $\pm 20 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 10 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.5^\circ$. The planes and directions are as in the coordinate systems shown in the figures. Repeatability tolerances for decenter may be e.g. $\pm 10 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 5 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.25^\circ$. In other examples, accuracy tolerances for decenter may be e.g. $\pm 10 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 5 \mu\text{m}$ in the Y direction, as well as e.g. $\pm 0.15^\circ$. Repeatability tolerances for decenter may be e.g. $\pm 5 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 2.5 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.08^\circ$. In yet other examples, accuracy tolerances for decenter may be e.g. $\pm 5 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 2.5 \mu\text{m}$ in the Y direction, as well as e.g. $\pm 0.1^\circ$. Repeatability tolerances for decenter may be e.g. $\pm 1.5 \mu\text{m}$ in the X-Z plane and of e.g. $\pm 0.8 \mu\text{m}$ in the Y direction, as well as for a tilt of $\pm 0.05^\circ$.

(74) Similar accuracy tolerances and repeatability tolerances hold for optics frame **1650** (see e.g.

FIG. 16A) and optics module 600" (see e.g. FIG. 19A).

(75) "Accuracy tolerances" refer here to a maximum variation of the distances between optical elements and between mechanical elements. "Repeatability tolerances" refer here to a maximum variation of the distances between optical elements and between mechanical elements in different pop-out cycles, i.e. the capability of the mechanical and optical elements to return to their prior positions after one or many pop-out (or collapse) events.

(76) Tolerances in the Y direction may be less important, as variations in Y can be compensated by optical feedback and moving the lens for auto-focus.

(77) FIG. 4A shows in cross section optics module 240 in the pop-out state. FIG. 4B shows optics module 240 in the same state in perspective. The diameter of the smallest circle that entirely surrounds the optics module defines a "largest diameter" "d.sub.module" of the optics module. That is "d.sub.module" marks the largest diagonal of an optics module (here and in e.g. FIGS. 7, 17B, 18A, 18B, 18E and 19A) except when stated otherwise (e.g. as re. FIG. 16A).

(78) FIG. 4C shows details of a first exemplary lens system 400 that can be used in camera 200 in a pop-out state. Lens system 400 comprises a lens 420 that includes, in order from an object side to an image side, a first lens element L1 with object-side surface S2 and image-side surface S3; a second lens element L2 with object-side surface S4, with an image side surface marked S5; a third lens element L3 with object-side surface S6 with image-side surface S7; a fourth lens element L4 object-side surface marked S8 and an image-side surface marked S9; a fifth lens element L5 with object-side surface marked S10 and an image-side surface marked S11; and a sixth lens element L6 with object-side surface marked S12 and an image-side surface marked S13. S1 marks a stop. Lens system 400 further comprises optical window 234 disposed between surface S13 and image sensor 208. Distances between lens elements and other elements are given in tables below along an optical axis of the lens and lens system.

(79) In lens system 400, TTL=11.55 mm, BFL=5.96 mm, EFL=13 mm, F number=2.20 and the FOV=29.7 deg. A ratio of TTL/EFL=0.89. The optical properties of lens 420 do not change when switching between a pop-out state and a collapsed state (i. e. gaps between lens elements are constant).

(80) In the collapsed state (see FIG. 5A), cTTL may be 5.64-8.09 mm. The difference between cTTL and TTL stems from a modified BFL which is now a collapsed BFL, "c-BFL" (see FIG. 5A). c-BFL may be 0.051-2.5 mm. All distances between lens elements L1-L6 and lens surfaces S2-S13 remain unchanged.

(81) Detailed optical data of lens system 400 is given in Table 1, and the aspheric surface data is given in Table 2 and Table 3, wherein the units of the radius of curvature (R), lens element thickness and/or distances between elements along the optical axis and diameter are expressed in mm. "Index" is the refraction index. The equation of the aspheric surface profiles is expressed by:

$$z(r) = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + D_{\text{con}}(u)$$

$$D_{\text{con}}(u) = u^4 \cdot \text{Math}_{n=0}^N A_n Q_n^{\text{con}}(u^2)$$

$$u = \frac{r}{r_{\text{norm}}}, x = u^2$$

$$(82) \quad Q_0^{\text{con}}(x) = 1, Q_1^{\text{con}} = -(5 - 6x), Q_2^{\text{con}} = 15 - 14x(3 - 2x)$$

$$Q_3^{\text{con}} = -\{35 - 12x[14 - x(21 - 10x)]\}$$

$$Q_4^{\text{con}} = 70 - 3x\{168 - 5x[84 - 11x(8 - 3x)]\}$$

$$Q_5^{\text{con}} = -[126 - x(1260 - 11x\{420 - x[720 - 13x(45 - 14x)]\})]$$

where {z, r} are the standard cylindrical polar coordinates, c=1/R is the paraxial curvature of the surface, k is the conic parameter, and r.sub.norm is generally one half of the surface's clear aperture. An are the polynomial coefficients shown in lens data Table 2 and Table 3 (as well as in

Table 5 and Table 6, and in Table 10 and Table 11). The Z-axis is defined to be positive towards the image. Also note that in Table 1 (as well as in Table 4 and Table 9), the distances between various elements (and/or surfaces) refer to the element thickness and are measured on the optical axis Z, wherein the stop is at $z=0$. Each number is measured from the previous surface. Thus, the first distance -1.197 mm is measured from the stop to surface S2. The reference wavelength is 555.0 nm. Units are in mm (except for refractive index “Index” and Abbe #). The largest lens diameter d.sub.L of a lens such as lens **240** is given by the largest diameter present among all the lens elements of a lens such as lens **240**.

(83) TABLE-US-00001 TABLE 1 Lens system 400 EFL = 13.00 mm, F number = 2.20, FOV = 29.7 deg. Aperture Curvature Radius Focal Surface # Comment Type Radius Thickness (D/2) Material Index Abbe # Length 1 A.S Plano Infinity -1.197 2.940 2 Lens 1 QT1 3.453 0.927 2.940 Plastic 1.54 56.18 14.80 3 5.463 0.008 2.895 4 Lens 2 QT1 4.054 1.545 2.811 Plastic 1.54 56.18 8.78 5 22.988 0.025 2.620 6 Lens 3 QT1 6.508 0.218 2.346 Plastic 1.67 19.4 -9.67 7 3.215 1.134 2.003 8 Lens 4 QT1 -9.074 0.206 1.774 Plastic 1.64 23.53 -17.62 9 -45.557 0.902 1.648 10 Lens 5 QT1 66.987 0.417 1.665 Plastic 1.67 19.44 9.93 11 -7.435 0.009 1.788 12 Lens 6 QT1 -19.713 0.197 1.845 Plastic 1.54 56.18 -10.85 13 8.487 5.450 1.984 14 Filter Plano Infinity 0.210 — Glass 1.52 64.2 15 Infinity 0.300 — 16 Image Plano Infinity — —

(84) TABLE-US-00002 TABLE 2 Aspheric Coefficients Surface # R.sub.norm A0 A1 A2 A3 2 2.385 $-6.99E-02$ $-1.08E-02$ $-1.52E-03$ $-4.14E-04$ 3 2.385 $-6.86E-02$ $-1.05E-02$ $2.44E-03$ $-3.81E-04$ 4 2.385 $9.39E-03$ $-1.24E-02$ $2.84E-03$ $8.52E-04$ 5 2.385 $1.26E-03$ $-2.19E-02$ $1.12E-03$ $8.76E-04$ 6 1.692 $-5.76E-02$ $2.59E-02$ $-4.13E-03$ $-2.03E-05$ 7 1.692 $-2.94E-02$ $3.95E-02$ $-5.32E-03$ $-6.02E-04$ 8 1.648 $3.50E-01$ $8.82E-03$ $-2.47E-03$ $6.30E-04$ 9 1.648 $4.12E-01$ $2.61E-02$ $2.43E-03$ $2.06E-03$ 10 1.587 $-2.16E-01$ $-3.53E-02$ $-8.04E-03$ $4.41E-04$ 11 1.587 $-1.36E-01$ $-2.45E-02$ $-2.51E-03$ $1.25E-03$ 12 1.609 $-2.58E-01$ $2.37E-02$ $-1.19E-03$ $2.12E-04$ 13 1.609 $-2.99E-01$ $2.60E-02$ $-4.30E-03$ $-2.04E-04$

(85) TABLE-US-00003 TABLE 3 Surface # A4 A5 A6 2 $-4.91E-05$ $6.04E-06$ $-7.27E-07$ 3 $8.15E-05$ $-5.60E-05$ $6.51E-06$ 4 $1.04E-04$ $-1.60E-04$ $1.22E-05$ 5 $-4.30E-04$ $9.99E-05$ $-1.20E-05$ 6 $6.30E-05$ $-4.83E-06$ $1.65E-07$ 7 $2.23E-05$ $2.33E-05$ $2.32E-07$ 8 $-2.32E-04$ $-1.73E-05$ $-4.47E-05$ 9 $-4.98E-05$ $-1.12E-04$ $-7.34E-05$ 10 $1.23E-04$ $1.53E-04$ $7.13E-05$ 11 $-6.11E-04$ $1.56E-04$ $1.39E-05$ 12 $-5.99E-04$ $1.37E-04$ $7.47E-06$ 13 $5.73E-05$ $-1.33E-05$ $1.30E-06$

(86) FIG. 5A shows a pop-out optics module **240** in a collapsed state in a cross sectional view. FIG. 5B shows a perspective view of the same.

(87) FIG. 6A shows a cross sectional view (through cross section marked 6A-6A in FIG. 7) of another example numbered **600** of a pop-out optics module in a pop-out state. Optics module **600** may be integrated into a pop-out mechanism such as **210** (not shown here). Optics module **600** includes a lens barrel **602** with a collapsible lens barrel section (first barrel section) **604** carrying a first lens group **606**, and a fixed lens barrel section (second barrel section) **608** carrying a second lens group **610**. The two lens groups form a lens **620** that includes altogether N lens elements L1-LN, arranged with a first lens element L1 on an object side and a last lens element LN on an image side. Optics module **600** is covered by cover **232**. Lens **620**, and optional optical window **234** and an image sensor **208** form a lens system **630**.

(88) In general, $N \geq 4$. In other examples, the lens barrel may comprise more than two barrel sections with more lens groups each, e.g. 3, 4, 5 lens barrel sections with each barrel section carrying a lens group. The lens barrel sections may be divided into fixed barrel sections and movable barrel sections. Air-gaps may be formed between lens groups according to their relative movement. In examples with more than two barrel sections, some or all barrel sections may be movable and have respective air-gaps formed between the lens groups. The air-gaps between lens groups may collapse in a non-operative camera state. The sum of such air-gaps may be 1-8.5 mm. The largest air-gaps present between two consecutive lens elements may be used to define lens

(93) In the collapsed state (see FIG. 6B or FIG. 14C), cTTL may be 6.44-7.24 mm. The difference between cTTL and TTL stems from a modified air-gap between L6 and L7, which is a collapsed air-gap c-d.sub.N-1 and which may be 0.05-0.85 mm. The BFL did not change with respect to the pop-out state.

(94) The optical properties of lens 620' change when switching between a pop-out state and the collapsed state. The optical properties presented here refer to the lens elements in a "maximal" pop-out state, i.e. when the lens has the largest TTL.

(95) TABLE-US-00005 TABLE 5 Aspheric Coefficients Surface # R.sub.norm A0 A1 A2 A3 A4 2
2.03E+00 8.98E-02 1.91E-02 4.39E-03 8.23E-04 1.41E-04 3 1.88E+00 1.36E-02
1.31E-02 1.21E-03 2.44E-04 8.58E-05 4 1.87E+00 -6.37E-02 3.51E-02 1.73E-03
6.81E-04 1.38E-04 5 1.85E+00 -1.16E-02 5.94E-02 1.65E-02 6.10E-03 1.62E-03 6
1.85E+00 -1.04E-01 1.94E-02 1.51E-02 4.62E-03 9.45E-04 7 1.78E+00 -1.51E-01
-4.96E-03 3.05E-03 1.05E-03 2.14E-04 8 1.78E+00 -5.18E-01 -1.59E-02 5.30E-03
2.48E-03 8.04E-04 9 2.10E+00 -5.53E-01 7.15E-02 3.81E-02 1.81E-02 6.25E-03 10
2.30E+00 -3.60E-01 2.33E-01 1.57E-01 1.29E-01 5.32E-02 11 2.42E+00 -1.68E+00
1.98E-01 -4.68E-03 5.58E-02 2.62E-02 12 2.59E+00 -1.52E+00 8.24E-02 -8.59E-03
1.18E-02 2.67E-04 13 2.86E+00 4.37E-01 2.30E-03 4.67E-02 -1.08E-02 -3.33E-03 14
5.06E+00 1.44E+00 5.66E-01 -2.72E-01 1.01E-01 -2.51E-02 15 5.55E+00 -5.28E+00
5.59E-01 -2.71E-01 4.18E-02 -4.23E-02

(96) TABLE-US-00006 TABLE 6 Aspheric Coefficients Surface # A5 A6 A7 A8 A9 2 0.00E+00
0.00E+00 0.00E+00 0.00E+00 0.00E+00 3 -2.45E-05 0.00E+00 0.00E+00 0.00E+00
0.00E+00 4 -7.03E-05 0.00E+00 0.00E+00 0.00E+00 0.00E+00 5 2.33E-04 0.00E+00
0.00E+00 0.00E+00 0.00E+00 6 5.32E-05 0.00E+00 0.00E+00 0.00E+00 7
3.84E-05 0.00E+00 0.00E+00 0.00E+00 0.00E+00 8 3.66E-04 0.00E+00 0.00E+00
0.00E+00 0.00E+00 9 1.49E-03 -2.63E-04 0.00E+00 0.00E+00 0.00E+00 10 1.64E-02
1.44E-03 0.00E+00 0.00E+00 0.00E+00 11 1.59E-02 3.54E-03 1.08E-03 0.00E+00
0.00E+00 12 3.18E-03 -5.00E-04 -3.15E-04 0.00E+00 0.00E+00 13 2.65E-03 2.67E-05
-4.87E-04 1.84E-04 0.00E+00 14 -2.21E-04 -1.68E-05 6.75E-04 -6.40E-04 2.77E-04 15
5.53E-03 -7.30E-03 -2.11E-04 -1.38E-03 2.11E-04

(97) FIG. 6D shows an example of yet another lens system 660 that may be used in optics module 600 or 600'. Lens system 660' is shown in a pop-out state. The design data is given in Tables 7-9. Lens system 660 includes a lens 620" with six lens elements L1-L6 arranged as shown, optical window 234 and image sensor 208. Lens elements L1-L3 form the first lens group 606, and lens elements L4-L6 form the second lens group 610. The TTL is 13.5 mm and the BFL is 5.49 mm. Focal length is EFL=15.15 mm, F number=2.0 and the FOV=32.56 deg. Air-gap d.sub.607 is 1.78 mm. A ratio of TTL/EFL=0.89.

(98) In the collapsed state (see FIG. 6B), cTTL may be 5-11 mm. The difference between cTTL and TTL stems from a modified air-gap between L3 and L4, which is a collapsed air-gap c-d.sub.607 and which may be 0.05-1.0 mm and a modified BFL which is a c-BFL and may be 0.1-1.5 mm. The optical properties of lens 620" change when switching between a pop-out state and the collapsed state. For lens system 660, a ratio TTL/EFL is 0.89, i.e. EFL>TTL. The ratio cTTL/EFL may be 0.35-0.75.

(99) TABLE-US-00007 TABLE 7 Lens system 660 EFL = 15.15 mm, F number = 2.0, FOV = 32.56 deg. Aperture Curvature Radius Focal Surface # Comment Type Radius Thickness (D/2) Material Index Abbe # Length 1 A.S Plano Infinity -1.823 3.731 2 Lens 1 ASP 4.314 1.837 3.731 Plastic 1.54 55.91 9.50 3 21.571 0.048 3.560 4 Lens 2 ASP 4.978 0.265 3.419 Plastic 1.67 19.44 -17.41 5 3.422 0.113 3.139 6 Lens 3 ASP 5.764 1.473 3.113 Plastic 1.67 19.44 20.20 7 11.201 1.780 2.909 8 Lens 4 ASP -6.075 0.260 2.143 Plastic 1.67 19.44 -14.33 9 -17.446 1.230 2.008 10 Lens 5 ASP -18.298 0.688 2.264 Plastic 1.54 55.91 184.98 11 -16.202 0.040 2.468 12 Lens 6 ASP 10.235 0.273 2.679 Plastic 1.54 55.91 -93.97 13 8.454 4.783 2.848 14 Filter Plano

Infinity 0.210 — Glass 1.52 64.17 15 Infinity 0.500 — 16 Image Plano Infinity — —

(100) TABLE-US-00008 TABLE 8 Aspheric Coefficients Surface # Conic A4 A6 A8 A10 2 0
-4.57E-04 -5.55E-05 2.46E-05 -4.65E-06 3 0 8.55E-04 7.37E-04 -1.07E-04 9.78E-06
4 0 -1.51E-02 3.43E-03 -6.33E-04 8.54E-05 5 0 -2.21E-02 5.71E-03 -1.50E-03
2.85E-04 6 0 -3.61E-03 3.56E-03 -1.08E-03 2.29E-04 7 0 -1.74E-04 2.47E-04
5.66E-05 -3.21E-05 8 0 1.75E-02 2.27E-03 -2.24E-03 7.99E-04 9 0 1.79E-02
5.45E-03 -3.71E-03 1.37E-03 10 0 -4.37E-03 -1.59E-02 1.33E-02 -6.54E-03 11 0
-7.77E-02 4.02E-02 -1.21E-02 1.65E-03 12 0 -1.39E-01 7.50E-02 -2.44E-02 4.78E-03
13 0 -5.32E-02 1.90E-02 -4.73E-03 6.11E-04

(101) TABLE-US-00009 TABLE 9 Aspheric Coefficients Surface # A12 A14 A16 2 4.92E-07
-2.88E-08 5.71E-10 3 -6.44E-07 1.90E-08 -1.21E-10 4 -6.96E-06 3.18E-07 -6.61E-09
5 -3.28E-05 2.13E-06 -6.25E-08 6 -2.83E-05 1.87E-06 -5.35E-08 7 5.30E-06
-4.54E-07 1.54E-08 8 -1.70E-04 1.94E-05 -9.28E-07 9 -2.64E-04 2.29E-05 -1.78E-07
10 1.83E-03 -2.76E-04 1.73E-05 11 -8.43E-06 -2.54E-05 2.18E-06 12 -5.86E-04
4.30E-05 -1.42E-06 13 -2.86E-05 -1.51E-06 1.53E-07

(102) FIG. 7 shows a perspective view of optics module **600** in a pop-out state. FIG. 8 shows a perspective view of optics module **600** in a collapsed state.

(103) FIG. 9A shows a perspective view of actuator **212** in a pop-out state. FIG. 9B shows a perspective view of actuator **212** in a collapsed state. Cross sections 2B-2B and 2D-2D refer to respectively FIGS. 2B and 2D. Actuator **212** comprises a pop-out actuator **902** with moving parts for actuation. A pop-out actuator—window frame coupling **904** with a switch **906** translates the pop-out actuation to a movement of the window frame. Switch **906** couples actuator **902** with window frame **214**. As indicated above, the window frame movement is used to switch the camera to the collapsed state. In FIG. 9A, switch **906** is “down” to provide the pop-out state. In FIG. 9B, switch **906** is “up” to provide the collapsed state.

(104) FIG. 10 shows another lens system numbered **1000** that can be included in a pop-out Tele camera in a maximal pop-out state. Lens system **1000** includes a lens **1020** with five lens elements as shown, optical window **234** and image sensor **208**. The Tele pop-out camera with lens system **1000** may be incorporated in a host device (e.g. a smartphone, tablet, etc., not shown here). Similar to the shown in FIG. 6A and FIG. 6B, in lens system **1000** switching between the pop-out and the collapsed states is obtained by modifying an air-gap **d1006** between a first lens group **1016** and a second lens group **1018**.

(105) In lens system **1000**, a first lens group **1016** includes lens elements **1002**, **1004** and **1006** and a second lens group **1018** includes lens elements **1008** and **1010**. In the pop-out state, air-gap **d1006** between surface **1008a** of lens element **1008** and surface **1006b** of the immediately preceding lens element **1006** is 2.020 mm (see Table 10). The TTL of the lens system is 5.904 mm. The division into a first lens group and a second lens group is done according to the largest air-gap between two consecutive lens elements.

(106) Lens system **1000** may provide a FOV of 25-50 degrees, and EFL=6.9 mm, a F number=2.80 and a TTL=5.904 mm. The ratio TTL/EFL is 0.86, i.e. EFL>TTL. The ratio cTTL/EFL may be 0.58-0.69. For air-gap **d1006**=TTL/2.95, so **d1006**>TTL/3. In other examples, for a largest air-gap that divides the lens elements into first and a second lens groups the air-gap may fulfill air-gap>TTL/5 and EFL>TTL.

(107) The optical properties of lens system **1000** change when switching to the collapsed state (not shown). In the collapsed state, cTTL may be 3.97-10 mm and collapsed air-gap c-d**1006** may be 0.05-0.85 mm. The difference between cTTL and TTL stems from a modified distance between first lens group **1016** and second lens group **1018**. The distance between first lens group **1016** and image sensor **208** changed with respect to the pop-out state, but distance between second lens group **1016** and the image sensor **1014** did not change.

(108) In lens system **1000**, all lens element surfaces are aspheric. Detailed optical data is given in

Table 10, and the aspheric surface data is given in Table 11, wherein the units of the radius of curvature (R), lens element thickness and/or distances between elements along the optical axis and diameter are expressed in mm. “Nd” is the refraction index. The equation of the aspheric surface profiles is expressed by:

$$(109) z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + \alpha_1 r^2 + \alpha_2 r^4 + \alpha_3 r^6 + \alpha_4 r^8 + \alpha_5 r^{10} + \alpha_6 r^{12} + \alpha_7 r^{14}$$

where r is distance from (and perpendicular to) the optical axis, k is the conic coefficient, c=1/R where R is the radius of curvature, and α are coefficients given in Table 2. In the equation above as applied to examples of a lens assembly disclosed herein, coefficients $\alpha_{\text{sub.1}}$ and $\alpha_{\text{sub.7}}$ are zero. Note that the maximum value of r “max r”=Diameter/2. Also note that Table 1 the distances between various elements (and/or surfaces) are marked “Lmn” (where m refers to the lens element number, n=1 refers to the element thickness and n=2 refers to the air-gap to the next element) and are measured on the optical axis z, wherein the stop is at z=0. Each number is measured from the previous surface. Thus, the first distance −0.466 mm is measured from the stop to surface **1002a**, the distance L11 from surface **1002a** to surface **1002b** (i.e. the thickness of first lens element **1002**) is 0.894 mm, the gap L12 between surfaces **1002b** and **1004a** is 0.020 mm, the distance L21 between surfaces **1004a** and **1004b** (i.e. thickness d2 of second lens element **1004**) is 0.246 mm, etc. Also, L21=d.sub.2 and L51=d.sub.5.

(110) TABLE-US-00010 TABLE 10 Lens system 1000 EFL = 6.9 mm, F number = 2.80, FOV = 44 degrees Radius R Distances Diameter # Comment [mm] [mm] Nd/Vd [mm] 1 Stop Infinite −0.466 2.4 2 L11 1.5800 0.894 1.5345/57.095 2.5 3 L12 −11.2003 0.020 2.4 4 L21 33.8670 0.246 1.63549/23.91 2.2 5 L22 3.2281 0.449 1.9 6 L31 −12.2843 0.290 1.5345/57.095 1.9 7 L32 7.7138 2.020 1.8 8 L41 −2.3755 0.597 1.63549/23.91 3.3 9 L42 −1.8801 0.068 3.6 10 L51 −1.8100 0.293 1.5345/57.095 3.9 11 L52 −5.2768 0.617 4.3 12 Infinite 0.410 3.0

(111) TABLE-US-00011 TABLE 11 Conic coefficient # k $\alpha_{\text{sub.2}}$ $\alpha_{\text{sub.3}}$ $\alpha_{\text{sub.4}}$ $\alpha_{\text{sub.5}}$ $\alpha_{\text{sub.6}}$ 2 −0.4668 7.9218E−03 2.3146E−02 −3.3436E−02 2.3650E−02 −9.2437E−03 3 −9.8525 2.0102E−02 2.0647E−04 7.4394E−03 −1.7529E−02 4.5206E−03 4 10.7569 −1.9248E−03 8.6003E−02 1.1676E−02 −4.0607E−02 1.3545E−02 5 1.4395 5.1029E−03 2.4578E−01 −1.7734E−01 2.9848E−01 −1.3320E−01 6 0.0000 2.1629E−01 4.0134E−02 1.3615E−02 2.5914E−03 −1.2292E−02 7 −9.8953 2.3297E−01 8.2917E−02 −1.2725E−01 1.5691E−01 −5.9624E−02 8 0.9938 −1.3522E−02 −7.0395E−03 1.4569E−02 −1.5336E−02 4.3707E−03 9 −6.8097 −1.0654E−01 1.2933E−02 2.9548E−04 −1.8317E−03 5.0111E−04 10 −7.3161 −1.8636E−01 8.3105E−02 −1.8632E−02 2.4012E−03 −1.2816E−04 11 0.0000 −1.1927E−01 7.0245E−02 −2.0735E−02 2.6418E−03 −1.1576E−04

(112) Advantageously, the Abbe number of the first, third and fifth lens element is 57.095. Advantageously, the first air-gap between lens elements **1002** and **1004** (the gap between surfaces **1002b** and **1004a**) has a thickness (0.020 mm) which is less than a tenth of thickness d.sub.2 (0.246 mm). Advantageously, the Abbe number of the second and fourth lens elements is 23.91. Advantageously, the third air-gap between lens elements **1006** and **1008** has a thickness (2.020 mm) greater than TTL/5 (5.904/5 mm). Advantageously, the fourth air-gap between lens elements **108** and **110** has a thickness (0.068 mm) which is smaller than d.sub.5/2 (0.293/2 mm).

(113) The focal length (in mm) of each lens element in lens system **1000** is as follows: f1=2.645, f2=−5.578, f3=−8.784, f4=9.550 and f5=−5.290. The condition $1.2 \times |f3| > |f2| < 1.5 \times f1$ is clearly satisfied, as $1.2 \times 8.787 > 5.578 > 1.5 \times 2.645$. f1 also fulfills the condition $f1 < \text{TTL}/2$, as $2.645 < 2.952$.

(114) FIG. 11A shows an example of a host device **1100** such as a smartphone with a dual-camera comprising a regular (non pop-up) folded Tele camera **1102** and a Wide pop-out camera **1104**. The Wide camera **1104** is in an operative pop-out state and extends the device's exterior surface **228**. Bump **226** is visible. A large image sensor such as **208** (not visible here) and a pop-out frame such as frame **220** (not fully visible here) required for switching between a collapsed and a pop-out camera state define a minimum area of the device's exterior surface **228** that is covered by the pop-

out camera (in X-Z). The minimum pop-out camera area may be larger than that of folded Tele cameras or that of regular (i.e. non pop-out) upright Wide cameras that are typically included in a device.

(115) FIG. 11B shows details of folded Tele camera 1102 and the upright Wide camera 1104 in a pop out state. The folded Tele camera comprises a prism 1108 and a folded Tele lens and sensor module 1112. In FIG. 11A and FIG. 11B only prism 1108 is visible.

(116) FIG. 11C shows host device 1100 with Wide camera 1104 in a collapsed state, illustrating the small height of the c-bump.

(117) FIG. 11D shows details of the folded Tele camera and the upright Wide camera in a collapsed state.

(118) FIG. 12A shows another example of a host device 1200 such as a smartphone with a dual-camera comprising a Tele pop-out camera 1202 as disclosed herein and a Wide pop-out camera 1204 in an operative pop-out state. Pop-out bump 226 is visible. A pop-out mechanism cover 1206 covers both the Tele and the Wide camera. A frame like 220 (not shown) switches the Tele and the Wide camera between a pop-out state and a collapsed state together and simultaneously. Pins 1208 may provide mechanical stability and repeatability in the X-Z plane. In some examples, 2 pins may be included. In other examples, 3 or more pins may be used.

(119) FIG. 12B shows details of upright Tele camera 1202 and upright Wide camera 1204, with both cameras in the pop-out state.

(120) FIG. 12C shows host device 1200 with the cameras in a collapsed state. A c-bump 236 is shown. FIG. 12E shows details of upright Tele camera 1202 and upright Wide camera 1204, with both cameras in the collapsed state.

(121) FIG. 13 shows yet another example of a lens system numbered 1300 comprising a lens 1320 including seven lens elements L1-L7, optionally optical window 234, and an image sensor 208. Here, image sensor 208 is a curved image sensor, meaning that its light collecting surface is curved with a radius of curvature $R = -19.026$ mm wherein the “-” sign refers to a curvature with center at the object side of the image sensor. Use of a curved image sensor may be beneficial as undesired effects such as field curvature and shading toward the sensor edges may be less than for a planar image sensor. Lens system 1300 may be used in a camera such camera 200 in a pop-out state. The design data is given in Tables 12-14.

(122) In lens system 1300, TTL=8.28 mm, BFL=3.24 mm, EFL=6.95 mm, F number=1.85 and the FOV=80.52 deg.

(123) In the collapsed state (see FIG. 2C), cTTL may be 6.54-10 mm. The difference between cTTL and TTL stems from a modified BFL which is now a collapsed “c-BFL” (see FIG. 5A). c-BFL may be 1.494-2.5 mm. The optical properties of lens 1320 do not change when switching between a pop-out state and a collapsed state (i. e. all distances between the lens elements L1-L7 and the lens surfaces S2-S15 did not change).

(124) TABLE-US-00012 TABLE 12 Lens system 1300 EFL = 6.95 mm, F number = 1.85, FOV = 80.52 deg. Aperture Curvature Radius Abbe Focal Surface # Comment Type Radius Thickness (D/2) Material Index # Length A.S Plano Infinity -0.681 1.879 Lens 1 QT1 2.791 0.577 1.879 Plastic 1.54 55.9 11.01 4.824 0.426 1.824 Lens 2 QT1 5.964 0.244 1.824 Plastic 1.67 19.4 -12.73 3.463 0.005 1.795 Lens 3 QT1 3.871 0.959 1.814 Plastic 1.54 55.9 7.85 35.947 0.452 1.783 Lens 4 QT1 -134.398 0.458 1.812 Plastic 1.66 20.37 63.02 -32.072 0.342 2.004 Lens 5 QT1 -4.466 0.252 2.096 Plastic 1.57 37.4 -10.23 -19.576 0.286 2.280 Lens 6 QT1 7.072 0.364 2.336 Plastic 1.54 55.9 3.95 -3.047 0.203 2.714 Lens 7 QT1 -7.929 0.478 3.717 Plastic 1.54 55.9 -5.59 5.074 1.744 4.108 Filter Plano Infinity 0.2100 — Glass 1.52 64.2 Infinity 1.284 — Image Plano -19.026 — —

(125) TABLE-US-00013 TABLE 13 Aspheric Coefficients Surface # R.sub.norm A0 A1 A2 A3 2 2.170 6.97E-02 6.81E-02 4.19E-02 1.88E-02 3 2.170 1.92E-01 1.54E-01 7.45E-02 2.62E-02 4 1.891 -1.23E-01 2.32E-02 -4.13E-04 -3.43E-04 5 1.891 -1.59E-01 2.59E-02

-6.88E-03 -1.68E-03 6 1.891 -3.55E-03 3.14E-02 3.10E-03 1.53E-03 7 1.891 -4.64E-02
2.24E-02 1.31E-02 5.48E-03 8 2.225 -5.98E-01 1.18E-01 8.64E-02 1.98E-02 9 2.225
-4.13E-01 9.40E-02 1.01E-01 5.25E-02 10 2.670 -3.70E-01 -1.57E-01 -7.49E-02
3.70E-02 11 2.670 -6.73E-01 2.51E-01 -1.90E-01 -1.12E-02 12 3.671 -3.40E+00 9.02E-01
-4.45E-01 5.39E-02 13 3.671 3.45E+00 5.97E-02 -2.00E-01 -2.88E-02 14 5.340 2.76E+00
7.29E-02 5.26E-04 -1.83E-01 15 5.340 -6.08E+00 7.69E-02 -7.67E-01 -1.27E-01

(126) TABLE-US-00014 TABLE 14 Aspheric Coefficients Surface # A4 A5 A6 A7 A8 2

6.08E-03 1.29E-03 1.49E-04 0.00E+00 0.00E+00 3 6.42E-03 1.10E-03 1.85E-04
0.00E+00 0.00E+00 4 -6.39E-04 -2.45E-04 -7.91E-05 0.00E+00 0.00E+00 5 -1.32E-03
-9.94E-06 1.50E-04 0.00E+00 0.00E+00 6 -4.90E-05 3.53E-04 2.69E-04 0.00E+00
0.00E+00 7 2.07E-03 6.57E-04 1.36E-04 0.00E+00 0.00E+00 8 3.42E-04 -1.45E-03
-8.99E-04 0.00E+00 0.00E+00 9 1.74E-02 5.33E-03 4.89E-04 0.00E+00 0.00E+00 10
-3.53E-02 -1.64E-02 -1.34E-02 0.00E+00 0.00E+00 11 -4.40E-02 -4.87E-03 -1.09E-02
0.00E+00 0.00E+00 12 -1.00E-02 -3.74E-02 -5.14E-02 9.87E-03 1.02E-02 13 -2.41E-02
5.41E-02 4.32E-02 1.11E-02 7.56E-03 14 -2.94E-01 -1.73E-01 -8.86E-02 -1.66E-02
-2.06E-03 15 -1.78E-01 -7.01E-02 -5.97E-02 -2.09E-02 -8.43E-03

(127) In other examples, optical window **234** may be curved. A radius of curvature $R_{sub.W}$ of the optical window may be of same sign as the radius of curvature R of curved image sensor **208** (i.e. with a center at the object side of the optical window) and may be curved in a similar way, so $R_{sub.W}$ may e.g. be $R_{sub.W} = -15$ to -25 mm. In another example may be $R_{sub.W} = R$, with R being radius of curvature of the curved image sensor. This may allow for a smaller cTTL. cTTL may be 5.64-7.54 mm and c-BFL may be 0.594-2.5 mm.

(128) FIG. **14A** shows in cross sectional view another example numbered **1400** of a pop-out camera disclosed herein in a pop-out state and incorporated in a “host” device **250** (e.g. a smartphone, tablet, etc.). Camera **1400** comprises a pop-out frame **220'** and an optics module **600'** that includes a lens **620**. As shown in FIG. **14B**, frame **220'** comprises a window frame **214'**, a cam follower **1402** and a side limiter **1406**. Cam follower **1402** is coupled via springs **1408** to a pop-out actuator **1408**. Optics module **600'** includes a lens barrel **602** with a collapsible lens barrel section (first barrel section) **604** carrying a first lens group **606**, and a fixed lens barrel section (second barrel section) **608** carrying a second lens group **610**. The two lens groups form a lens **620** that includes altogether N lens elements $L1-LN$, arranged with a first lens element $L1$ on an object side and a last lens element LN on an image side. Lens **620**, an optional optical window **234** and image sensor **208** form a lens system **630**.

(129) Camera **1400** comprises an external module seal **224** and an internal module seal **1404**. External seal **224** prevents particles and fluids from entering device **250**. Seal **224** may support a IP68 class ranking of device **250**. Internal seal **1404** prevents particles from entering optics module **600'**.

(130) “External” and “internal” refer to the fact that seal **224** prevents contamination of the camera from outside the host device, while seal **1404** prevents contamination of the camera from inside the host device.

(131) Optics module **600'** and window frame **214** form an air-gap **222'** between the lens barrel and window **216**, which may be for example 0.1 mm-3 mm. Air-gap **222'** allows for a movement of the lens barrel by 0.1-3 mm for performing auto-focus (AF) and optical image stabilization (OIS) by moving lens **620** or parts of lens **620** or optics module **600'** or sensor **208** as known in the art.

(132) Camera **1400** forms a significant pop-out bump **226** with respect to an exterior surface **228** of device **250**. Here, “significant” may be for example 1.5 mm-12 mm. In the pop-out state, camera **1400** increases the height of host device **250** to a height in a pop-out state.

(133) Lens **620** may have $N \geq 4$ lens elements, and, as mentioned, comprises a barrel with two lens barrel sections. In other examples, the lens barrel may comprise more than two barrel sections with more lens groups, e.g. 3, 4, 5 lens barrel sections with each barrel section carrying a lens group.

The lens barrel sections may be divided into fixed barrel sections and movable barrel sections. In the example shown, first lens group **606** includes lenses L1-LN-1 and second lens group **610** includes lens LN (see FIG. **14A**). Air-gaps may be formed between lens groups according to their relative movement. In examples with more than two barrel sections, some or all barrel sections may be movable and have respective air-gaps formed between the lens groups. The air-gaps between lens groups may collapse in a non-operative camera state. The sum of such air-gaps may be 1-12 mm. In the pop-out state, air-gap d.sub.N-1 may be 1-5.5 mm. Three springs **614** (not all visible here) push first lens barrel section **604** towards a mechanical stop. The mechanical stop may be provided by a kinematic coupling mechanism as shown in FIGS. **18A-B** and FIGS. **19A-B**. In other examples and as shown in FIG. **20C**, the mechanical stop may be provided by a top cover **1606'**. In some examples, the camera in pop-out state may be designed to support tolerances for decenter of e.g. $\pm 20\text{ }\mu\text{m}$ in the X-Z plane and of e.g. $\pm 10\text{ }\mu\text{m}$ in the Y direction, as well as a tilt of $\pm 0.2^\circ$ of the lens barrel with respect to image sensor **208**. In other examples, tolerances for decenter may be e.g. $\pm 2\text{-}10\text{ }\mu\text{m}$ in the X-Z plane and of e.g. $\pm 2\text{-}10\text{ }\mu\text{m}$ in the Y direction, as well as e.g. $\pm 0.05^\circ\text{-}0.15^\circ$ for a tilt of lens barrel with respect to the image sensor Y.

(134) The TTL of the lens may be 5-22 mm. The image sensor diagonal may be $6\text{ mm} < \text{sensor diagonal} < 30\text{ mm}$. The 35 eqFL may be $15\text{ mm} < \text{equivalent focal length} < 200\text{ mm}$. The TTL/EFL ratio may vary in the range $0.7 < \text{TTL/EFL} < 1.5$.

(135) A window position measurement mechanism **1420** shown in FIG. **14B** comprises one or more magnets and one or more Hall sensors shown in FIGS. **20C-E**. The magnets are fixedly coupled to a cam follower **1402**, and the Hall sensor(s) is (are) fixedly coupled to a side limiter **1406**. Mechanism **1420** senses the position of the cam follower relative to side limiter **1406** and host device **250**. The camera is mechanically coupled to the host device and the side limiter is mechanically coupled to the camera.

(136) FIG. **14B** shows a perspective view of frame **220'** in a pop-out state. A pop-out camera such as **1400** is formed when optics module **600'** is inserted into frame **220'**. Window frame **214'**, cam follower **1402** and side limiter **1406** move with respect to each other. Window frame **214'** and cam follower **1402** also move with respect to host device **250**, but side limiter **1406** does not move with respect to host device **250**. Camera **1400** is switched from a pop-out state to a collapsed state by moving window frame **214'** in a positive X direction with respect of host device **250** and side limiter **1406**. Window frame **214'** is moved by actuator **212'** via cam follower **1402**. The movement of cam follower **1402** is substantially parallel to the X axis, and this movement is translated in a movement of window frame **214'** substantially parallel to the Y axis. This translation of movements in X direction and in Y direction is described in FIG. **15A-B**. As for the movement along Y, window frame **214'** applies pressure to the lens barrel that translates into a movement of the collapsible lens barrel section towards the image sensor. Cam follower **1402** is coupled via springs **1408** to a pop-out actuator **1412**. Actuator **1412** moves cam follower **1402** e.g. via a screw stepper motor or another actuation method. The movement is mediated by the springs **1408**. Springs **1408** may act as shock absorber for camera **1400**. E.g. when host device **250** is dropped and hits another object, a large force may act on window frame **214'**. By means of springs **1408**, this large force may be translated into a collapse of the pop-out camera, thereby mediating a large portion of the large force. Internal module seal **1404** may act as an additional shock absorber.

(137) FIG. **14C** shows a cross sectional view of camera **1400** in a collapsed ("c") or non-operative state. FIG. **14D** shows a perspective view of frame **220'** in a collapsed state. To switch optics module **600'** to the collapsed state, actuator **212'** decreases air-gap d.sub.N-1 by moving the window frame **214'** to apply pressure to the lens barrel that translates into a movement of the collapsible lens barrel section towards the image sensor. In the collapsed state, cTTL may be 5-12 mm. and collapsed air-gap c-d.sub.N-1 may be 0.05-1.5 mm.

(138) FIG. **15A** shows the frame **220'** of example **1400** in a cross sectional view via X-Y plane in a pop-out state. A switching pin **1502** and a switching pin **1504** are rigidly coupled to cam follower

1402. A side limiter pin **1512** is fixedly coupled to side limiter **1406** and slides within a vertically oriented limiter groove **1514**. Switching pin **1502** and **1504** slide within switching grooves **1506** and **1508**. Switching pins **1502** and **1504** have a diamond shape which is superposed by a curvature having a large radius of curvature for minimizing contact stress acting between the pins and window frame **214'**. Side limiter pin **1512** has a rectangular shape superposed by a curvature having a large radius of curvature for minimizing contact stress.

(139) When cam follower **1402** is moved in a negative X direction, the inclination of switching grooves **1506** and **1508** leads to a downward movement (in a negative Y direction) of window frame **214'**. This downward movement is used to switch the camera to the collapsed state. The downward movement is limited and guided by side limiter pin **1512**. The inclination of switching grooves **1506** and **1508** may e.g. be between 20-80 degrees with respect to a vertical Y axis.

(140) FIG. **15B** shows the frame **220'** of FIG. **15A** in a collapsed state. To switch the camera from the collapsed state to a pop-out state, cam follower **1402** is moved in a positive X direction and the inclination of switching grooves **1506** and **1508** leads to an upward movement (in a positive Y direction) of window frame **214'**.

(141) FIG. **16A** shows a cross sectional view and FIG. **16B** show a perspective view of optics module **600'** in a pop-out state. Module **600'** comprises an optics frame **1650**, first collapsible lens barrel section **604** (lens elements not shown here), second fixed lens barrel section **608**, three springs **614** (not all visible here), a side cover **1604**, a top cover **1606** and three stoppers **1608** (not all visible here). Each spring sits on one of three spring holders **1612** (not all visible here). Optics frame **1650** holds all components of optics module **600'** except the lens elements that are included in the first and the second lens barrel sections. Stoppers **1608** are rigidly coupled to top cover **1606** and ensure that the collapsible lens barrel section (**604**) is not in direct contact with window frame **214**.

(142) A “penalty” p for a diameter of an optics module is defined as the difference between the diameter of the optics module and the largest diameter of a lens included in the optics module. For optics module **600'**, $d_{sub.module}$ is slightly larger than the largest diameter of lens **620**, represented by the diameter of $L_{sub.N}$. Therefore, for optics module **600'**, penalty p is $p = p_{sub.1} + p_{sub.2}$ and may be 0.5 mm-8 mm.

(143) FIG. **17A** shows optics module **600'** in cross-section and FIG. **17B** shows the module in perspective in a collapsed state. In the collapsed state, springs **614** are compressed.

(144) FIGS. **18A-18F** shows optics frame **1650** in various positions and with various details of its components. FIG. **18A** shows optics frame **1650** in a pop-out state and FIG. **18B** shows optics frame **1650** in a collapsed state, both in a perspective view. Collapsible lens barrel section **604** is coupled to optics frame **1650** via a “Maxwell kinematic coupling” mechanism. The Maxwell kinematic coupling mechanism comprises three v-groove/pin pairs **1810** that act as a guiding and positioning mechanism that ensures that collapsible lens barrel section **604** is kept in a fixed position relative to the other optical elements such as image sensor **208** with high accuracy. Each v-groove/pin pair **1810** is identical and includes a hemispherical pin **1812** and a v-groove **1814**. More details of a v-groove/pin pair **1810** are given in FIG. **18C** (for the pop-out state) and FIG. **18D** (for the collapsed state). In other examples, the pins may be round or diamond-shaped or canoe-shaped. The v-grooves shown in FIG. **18A-18D** have an angle of about 90 degrees. In other examples, the angle of the v-grooves may vary between 30 to 150 degrees.

(145) Pairs **1810** are distributed at equal distance from each other. By means of the three v-groove/pin pairs **1810**, optics frame **1650** supports narrow tolerances in terms of accuracy as well as repeatability for decenter in X-Z and Y as well as for tilt. Here and in the description of FIGS. **19A** and **19B**, “tolerances” refer to tolerances between collapsible lens barrel section **604** the fixed lens barrel section **608**.

(146) Optics frame **1650** as well as optics module **600'** below may be designed to support accuracy tolerances for decenter and reliability tolerances like those of camera **200**.

(147) FIG. 18E shows optics frame **1650** in a top view. FIG. 18F shows optics frame **1650** in an exploded view showing the single parts that **1650** may be assembled from. Three spring holders **1612** keep the three respective springs **614** in a fixed position. One may assemble optics frame **1650** from the bottom to the top. One may start an assembly process with inserting L.sub.N into fixed lens barrel section **608**, then insert springs **614** into spring holders **1612**, then put top cover **1606**, then put side cover **1604** and then insert the collapsible lens barrel **604** on top. In some examples such as shown in FIGS. 2A-D and FIGS. 4A-B, a lens such as lens **420** may be included in an optics frame such as **1650**. Lens **420** includes a single group of lens elements only and may be included entirely in a collapsible lens barrel such as **604**. In some examples, collapsible lens barrel **604** and top cover **1606** may be one single unit.

(148) FIG. 19A and FIG. 19B show (in perspective and cross section respectively) another optics module numbered **600''**. Optics module numbered **600''** comprises a guiding and positioning mechanism for keeping collapsible lens barrel section **604** in a fixed position with high accuracy. The guiding and positioning mechanism is based on a yoke-magnet pair. A yoke **2002** is fixedly coupled to top cover **1606'**, and a permanent magnet **2004** is fixedly coupled to the side cover **1604'**. Through the use of yoke **2002** and magnet **2004**, top cover **1606** and the side cover **1604** are attracted to each other, keeping a constant distance and orientation to each other. Optics module **1650'** thus supports narrow tolerances in terms of accuracy as well as repeatability for decenter in X-Z and Y and for tilt.

(149) FIG. 19C shows optics module **600''** in a pop-out state in a cross-sectional view. A side cover **1604'** acts also as a second and fixed lens barrel section carrying a second group of lens elements, i.e. no additional component acting as second lens barrel section is required. FIG. 19D shows optics module **600''** in a collapsed state in a cross-sectional view.

(150) FIG. 19E shows a perspective view and FIG. 19F shows a top view of top cover **1606'** and magnet **2004**.

(151) FIG. 20A shows a side view and FIG. 20B shows a perspective view of a magnet part of window position measurement mechanism **1420** in a collapsed state. Two side magnets **2102a** and **2102b** are located on both sides of an inner (auxiliary) magnet **2104**. All magnets are fixedly coupled to cam follower **1402**. Magnets **2102a**, **2102b** and **2104** create a magnetic field that is sensed by Hall sensor **2106**. Hall sensor **2106** is fixedly coupled to side limiter **1406** (not shown here). The magnetic field sensed by Hall sensor **2106** depends on the relative position of cam follower **1402** and side limiter **1406**. That is, mechanism **1420** allows sensing of the relative position of cam follower **1402** and side limiter **1406** continuously along a stroke that may be in a range 1-10 mm.

(152) FIG. 20C shows a side view of magnets **2102a**, **2102b**, **2104** and Hall sensor **2106**, with camera **1400** shown in a collapsed state. FIG. 20D shows a side view of magnets **2102a**, **2102b**, **2104** and Hall sensor **2106**, with camera **1400** shown in a pop-out state. The stroke extends between the extreme positions shown here, i.e. between the collapsed state and the pop-out state. In some examples, mechanism **1420** may measure the relative position of **1402** and **1406** with the same accuracy along the entire stroke. In other examples and beneficially, mechanism **1420** may measure the relative position of **1402** and **1406** with a higher accuracy close to the extreme positions shown here, and with a lower accuracy in other positions.

(153) FIG. 20E shows an example of (a) a design and (b) the magnetic field of mechanism **1420**, with magnetization of magnets **2102a**, **2102b** and **2104** shown.

(154) FIG. 20F shows an example of a magnet configuration **2110** that may be included in a position measurement mechanism such as **1420**. A configuration of magnets **2102a**, **2102b** and **2104** is shown in (a), and magnetic flux density versus a position X as created by the magnet configuration of (a) is shown in (b). A large and substantially identical slope $\Delta B/\Delta X$ may be achieved along a linear range. The linear range of **2110** may extend between 1-10 mm.

(155) FIG. 20G shows another example of a magnet configuration **2120** that may be included in a

position measurement mechanism such as **1420**. A configuration of magnets **2102a**, **2102b** and **2104** is shown in (a), and magnetic flux density versus a position X as created by the magnet configuration of (a) is shown in (b). The linear range is divided into three sub-ranges A1, B and A2. In the sub-ranges A1 and A2, slope $\Delta B/\Delta X$ is larger than the slope in sub-range B. For example, a slope in the sub-ranges A1 and A2, $\Delta B/\Delta X(A)$, may be 5 times, 10 times or 25 times larger than a slope in the sub-range B, $\Delta B/\Delta X(B)$. For example, $\Delta B/\Delta X(A) \sim 500$ mT/mm, and $\Delta B/\Delta X(B) \sim 50$ mT/mm, so that a ratio of $[\Delta B/\Delta X(A)]/[\Delta B/\Delta X(B)] = 10$. The division in of the linear range in sub ranges with different slopes may be beneficial for a position measurement mechanism such as **1420**, as a higher accuracy may be required in the extreme regions close to the positions of the pop-out state and the collapsed state.

(156) In summary, disclosed herein are digital cameras with a pop-out mechanisms that allow for large EFLs and large image sensor sizes and low camera heights in a collapsed mode.

(157) While this disclosure has been described in terms of certain examples and generally associated methods, alterations and permutations of the examples and methods will be apparent to those skilled in the art. The disclosure is to be understood as not limited by the specific examples described herein, but only by the scope of the appended claims.

(158) It is appreciated that certain features of the presently disclosed subject matter, which are, for clarity, described in the context of separate examples, may also be provided in combination in a single example. Conversely, various features of the presently disclosed subject matter, which are, for brevity, described in the context of a single example, may also be provided separately or in any suitable sub-combination.

(159) Furthermore, for the sake of clarity the term “substantially” is used herein to imply the possibility of variations in values within an acceptable range. According to one example, the term “substantially” used herein should be interpreted to imply possible variation of up to 10% over or under any specified value. According to another example, the term “substantially” used herein should be interpreted to imply possible variation of up to 5% over or under any specified value. According to a further example, the term “substantially” used herein should be interpreted to imply possible variation of up to 2.5% over or under any specified value.

(160) Unless otherwise stated, the use of the expression “and/or” between the last two members of a list of options for selection indicates that a selection of one or more of the listed options is appropriate and may be made.

(161) It should be understood that where the claims or specification refer to “a” or “an” element, such reference is not to be construed as there being only one of that element.

(162) All patents and patent applications mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual patent or patent application was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present disclosure.

Claims

1. A camera integrated in a mobile device, comprising: a lens assembly that includes N lens elements L1-LN starting with L.sub.1 on an object side, wherein $N \geq 6$; an image sensor having a sensor diagonal SD in the range of 11-22 mm; and a pop-out mechanism configured to control an air-gap between a lens element and the image sensor to bring the camera to an operative pop-out state and to a collapsed state, wherein the pop-out mechanism is configured to raise and lower a moving window element relative to a stationary surface of the mobile device and comprises an external module seal configured to prevent liquids and particles from penetrating the mobile device, wherein the external module seal is coupled to the moving window element and to the stationary surface so as to adapt to a motion of the moving window element, wherein the lens

- assembly has a total track length TTL in the operative pop-out state and a collapsed total track length cTTL in the collapsed state, and wherein $cTTL/SD < 0.65$.
2. The camera of claim 1, wherein the external module seal has a collapsible structure, an inner edge and an outer edge, and wherein the external module seal collapses into a peripheral bulge formed between its inner and outer edges in response to the pop-out mechanism lowering the moving window element.
 3. The camera of claim 2, wherein the peripheral bulge of the external module seal unfolds in response to the pop-out mechanism raising the moving window element.
 4. The camera of claim 3, wherein in the pop-out state, the external module seal extends to form a crown with a tubular shape.
 5. The camera of claim 3, wherein in the collapsed state, the peripheral bulge extends inwards into the mobile device.
 6. The camera of claim 1, wherein the external module seal facilitates completely preventing ingress of dust into the mobile device and enabling the mobile device to be continuously immersed in water under predefined pressure conditions.
 7. The camera of claim 6, wherein the external module seal supports an ingress protection ranking IP68 of the mobile device.
 8. The camera of claim 1, wherein the pop-out mechanism includes a stepper motor.
 9. The camera of claim 1, wherein $cTTL/SD < 0.625$.
 10. The camera of claim 1, wherein $N \geq 6$ includes $N=6$ or 7.
 11. The camera of claim 1, wherein the lens has a f number $f/\#$ in the range 1.7-2.5.
 12. The camera of claim 1, wherein the lens has a f number $f/\#$ in the range 1.5-1.7.
 13. The camera of claim 1, wherein the camera includes an optics module comprising the lens, wherein the pop-up mechanism includes a window frame engageable with the optics module, wherein the window frame does not touch the optics module in the operative pop-out state, and wherein the window frame is operable to press on the optics module to bring the camera to the collapsed state.
 14. The camera of claim 13, wherein the moving window element is the window frame.
 15. The camera of claim 13, wherein the optics module has an optics module diameter dO , wherein the lens assembly has a maximum lens diameter dL , and wherein $dO < dL + 8$ mm.
 16. The camera of claim 15, wherein $dO < dL + 4$ mm.
 17. The camera of claim 15, wherein $dO < dL + 2$ mm.
 18. The camera of claim 15, wherein $dO < dL + 1$ mm.
 19. The camera of claim 1, wherein the pop-out mechanism comprises a guiding and positioning mechanism based on a kinematic coupling mechanism.
 20. The camera of claim 1, wherein the mobile device is a smartphone.
-