

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                      |
|----------------------|----------------------|
| United States Patent | 12411645             |
| Kind Code            | B2                   |
| Date of Patent       | September 09, 2025   |
| Inventor(s)          | Jin; Seoyoung et al. |

---

### Foldable electronic device for controlling screen rotation, and operating method therefor

---

#### Abstract

An electronic device includes a hinge structure, a first housing, second housing foldably connected to the hinge structure and configured to be foldable with respect to the first housing, a first display disposed from at least a part of a first surface to at least a part of a third surface, a second display, a first sensor configured to collect sensor data related to movement of the first housing, a second sensor configured to collect sensor data related to movement of the second housing, and a processor operatively connected with the first display, the second display, the first sensor, and the second sensor. The processor is configured to identify a folding angle between the first housing and the second housing by using the first sensor and the second sensor.

---

**Inventors:** Jin; Seoyoung (Suwon-si, KR), Kwon; Oheon (Suwon-si, KR), Sung; Changhuyn (Suwon-si, KR), Kang; Seongsig (Suwon-si, KR), Lee; Wonhee (Suwon-si, KR), Park; Jeongmin (Suwon-si, KR)

**Applicant:** SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

**Family ID:** 80117368

**Assignee:** SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

**Appl. No.:** 18/745465

**Filed:** June 17, 2024

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240338164 A1          | Oct. 10, 2024           |

#### Foreign Application Priority Data

|    |                 |               |
|----|-----------------|---------------|
| KR | 10-2020-0097145 | Aug. 04, 2020 |
|----|-----------------|---------------|

## Related U.S. Application Data

continuation parent-doc US 18105084 20230202 US 12014104 child-doc US 18745465  
continuation parent-doc WO PCT/KR2021/009244 20210719 PENDING child-doc US 18105084

---

## Publication Classification

**Int. Cl.:** **G06F3/14** (20060101); **G06F3/0346** (20130101); **H04M1/02** (20060101); H04M1/72454 (20210101)

**U.S. Cl.:**

**CPC** **G06F3/1446** (20130101); **G06F3/0346** (20130101); **H04M1/0216** (20130101); **H04M1/0268** (20130101); H04M1/72454 (20210101); H04M2250/12 (20130101)

## Field of Classification Search

**CPC:** G06F (1/1618); G06F (1/1641); G06F (1/1647); G06F (1/1652); G06F (1/1677); G06F (1/1681); G06F (1/3206); G06F (1/325); G06F (1/3265); G06F (3/0346); G06F (3/038); G06F (3/0484); G06F (3/0488); G06F (3/1431); G06F (3/1446); G06F (3/147); G06F (2200/1614); G06F (2200/1637); G09G (3/035); G09G (5/00); G09G (2340/14); G09G (2380/02); H04M (1/0214); H04M (1/0216); H04M (1/0243); H04M (1/0268); H04M (1/72454); H04M (2250/12)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name         | U.S. Cl. | CPC         |
|--------------|-------------|-----------------------|----------|-------------|
| 9348504      | 12/2015     | Kwak et al.           | N/A      | N/A         |
| 9412341      | 12/2015     | Lin                   | N/A      | N/A         |
| 9430184      | 12/2015     | Cho et al.            | N/A      | N/A         |
| 9558709      | 12/2016     | Zhou                  | N/A      | N/A         |
| 10394371     | 12/2018     | Kim et al.            | N/A      | N/A         |
| 10403241     | 12/2018     | Kim et al.            | N/A      | N/A         |
| 2004/0084578 | 12/2003     | Cho et al.            | N/A      | N/A         |
| 2008/0253073 | 12/2007     | Kee et al.            | N/A      | N/A         |
| 2010/0060664 | 12/2009     | Kilpatrick, II et al. | N/A      | N/A         |
| 2013/0321340 | 12/2012     | Seo                   | 345/174  | G06F 3/0486 |
| 2016/0026381 | 12/2015     | Kim et al.            | N/A      | N/A         |
| 2016/0132074 | 12/2015     | Kim et al.            | N/A      | N/A         |
| 2017/0075640 | 12/2016     | Chun et al.           | N/A      | N/A         |
| 2017/0206049 | 12/2016     | Choi et al.           | N/A      | N/A         |
| 2017/0221456 | 12/2016     | Kim                   | N/A      | G06F 1/1641 |
| 2019/0018454 | 12/2018     | Jung et al.           | N/A      | N/A         |
| 2019/0138179 | 12/2018     | Xia                   | N/A      | N/A         |
| 2020/0225706 | 12/2019     | Jung et al.           | N/A      | N/A         |
| 2020/0249898 | 12/2019     | Ko et al.             | N/A      | N/A         |

|              |         |            |     |            |
|--------------|---------|------------|-----|------------|
| 2021/0398465 | 12/2020 | Kim et al. | N/A | N/A        |
| 2022/0269314 | 12/2021 | Chen       | N/A | G09G 3/035 |

## FOREIGN PATENT DOCUMENTS

| Patent No.      | Application Date | Country | CPC |
|-----------------|------------------|---------|-----|
| 108027650       | 12/2017          | CN      | N/A |
| 10-2004-0040000 | 12/2003          | KR      | N/A |
| 10-2007-0041224 | 12/2006          | KR      | N/A |
| 10-2008-0093340 | 12/2007          | KR      | N/A |
| 10-2011-0066165 | 12/2010          | KR      | N/A |
| 10-2016-0012779 | 12/2015          | KR      | N/A |
| 10-2016-0055646 | 12/2015          | KR      | N/A |
| 10-2017-0085317 | 12/2016          | KR      | N/A |
| 10-2018-0089229 | 12/2017          | KR      | N/A |
| 10-2018-0132847 | 12/2017          | KR      | N/A |
| 10-2020-0026654 | 12/2019          | KR      | N/A |
| 10-2020-0045241 | 12/2019          | KR      | N/A |
| 10-2020-0086830 | 12/2019          | KR      | N/A |

## OTHER PUBLICATIONS

Communication dated Sep. 11, 2024, issued by the Korean Intellectual Property Office in Korean Application No. 10-2020-0097145. cited by applicant

Communication issued Nov. 10, 2023 by the European Patent Office in European Patent Application No. 201854226.4. cited by applicant

Communication dated Oct. 22, 2021, issued by the International Searching Authority in counterpart International Application No. PCT/KR2021/009244 (PCT/ISA/210). cited by applicant

Communication dated Oct. 22, 2021, issued by the International Searching Authority in counterpart International Application No. PCT/KR2021/009244 (PCT/ISA/237). cited by applicant

Office Action issued in U.S. Appl. No. 18/105,084 dated Oct. 12, 2023. cited by applicant

Notice of Allowance received in U.S. Appl. No. 18/105,084 dated Feb. 29, 2024. cited by applicant

Communication issued Feb. 7, 2025 by the Korean Intellectual Property Office in Korean Patent Application No. 10-2020-0097145. cited by applicant

Communication dated Jul. 29, 2025 issued by the State Intellectual Property Office of People's Republic of China in Chinese Patent Application No. 202180057974.1. cited by applicant

---

*Primary Examiner:* Rosario; Nelson M

*Attorney, Agent or Firm:* Sughrue Mion, PLLC

---

## Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. patent application Ser. No. 18/105,084, filed Feb. 2, 2023, in the US Patent and Trademark Office, which application is a continuation of International Application No. PCT/KR2021/009244, filed Jul. 19, 2021, which is based on and claims priority to Korean Patent Application No. 10-2020-0097145, filed on Aug. 4, 2020, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein in their entireties.

## BACKGROUND

### 1. Field

(1) The disclosure relates to a device and a method for controlling screen rotation in a foldable electronic device.

## 2. Description of Related Art

(2) Electronic devices are gradually becoming slimmer and are being improved to enhance design aspects and differentiate functional elements thereof. These electronic devices are gradually being transformed into various shapes apart from a uniform rectangular shape. For example, an electronic device may have a transformable structure capable of adjusting the size of a display to satisfy portability and usability of the electronic device. An electronic device having a transformable structure may include a foldable electronic device that operates in a manner in which at least two housings are folded or unfolded with respect to each other.

(3) A foldable electronic device may operate in an in-folding, out-folding, in/out-folding, sliding, and/or rolling manner through rotation of a first housing and a second housing with respect to each other via a hinge module.

(4) In the foldable electronic device, since the first housing and the second housing rotate via the hinge module, a structure of a display disposed to cross the first housing and the second housing may be transformed into various shapes. A user of the foldable electronic device may view a content displayed on the display in a different direction according to various shapes of the display.

(5) The foldable electronic device requires a method for controlling screen rotation based on various shapes of a display.

## SUMMARY

(6) Provided are a device and a method for controlling screen rotation in a foldable electronic device.

(7) According to an aspect of the disclosure, an electronic device includes: a first housing including a first surface, a second surface opposite to the first surface, and a first lateral surface surrounding a first space between the first surface and the second surface; a second housing including a third surface, a fourth surface opposite to the third surface, and a second lateral surface surrounding a second space between the third surface and the fourth surface; a hinge structure foldably connecting the first housing and the second housing to each other such that the first surface and the third surface face a same direction when the first housing and the second housing are in an unfolded state; a first display disposed from at least a part of the first surface to at least a part of the third surface; a second display disposed in the second space so as to be visible from an outside through at least a part of the fourth surface; a first sensor disposed at least partly in the first space and configured to obtain sensor data related to movement of the first housing; a second sensor disposed at least partly in the second space and configured to obtain sensor data related to movement of the second housing; and a processor operatively connected with the first display, the second display, the first sensor, and the second sensor, wherein the processor is configured to: identify a folding angle between the first housing and the second housing by using the first sensor and the second sensor, select the second display based on the folding angle between the first housing and the second housing being in a first range, determine a display direction of a content, based on the sensor data obtained by the second sensor, and control the second display to display the content, based on the display direction of the content.

(8) The electronic device may further include a magnetic detection sensor disposed in the first space or the second space, and the processor may be further configured to: based on at least one of the first display and the second display being in an active state, identify the folding angle between the first housing and the second housing by using the first sensor, the second sensor, and the magnetic detection sensor; and based on the first display and the second display being in an inactive state, identify the folding angle between the first housing and the second housing by using at least one of a part of the first sensor and a part of the second sensor.

(9) At least one of the first sensor and the second sensor may include an acceleration sensor and a gyro sensor, and the at least one of the part of the first sensor or the part of the second sensor

includes the acceleration sensor.

(10) The processor may be further configured to: based on the first housing and the second housing being in a folded state, select the second display; determine the display direction of the content, based on the sensor data obtained by the first sensor; and control the second display to display the content, based on the display direction of the content.

(11) The processor may be further configured to: the first housing and the second housing are in the unfolded state, select the first display; determine the display direction of the content, based on at least one the sensor data obtained by the first sensor and the sensor data obtained by the second sensor; and control the first display to display the content, based on the display direction of the content.

(12) The processor may be further configured to: based on the first display being in an active state and the first housing and the second housing being in the unfolded state, determine the display direction of the content based on the sensor data obtained by the first sensor and the sensor data obtained by the second sensor; and based on the first display being in an inactive state and the first housing and the second housing being in the unfolded state, determine the display direction of the content based on at least one the sensor data obtained by the first sensor and the sensor data obtained by the second sensor.

(13) The processor may be further configured to: select the first display based on the folding angle between the first housing and the second housing being in a second range different from the first range; determine the display direction of the content, based on at least one of the sensor data obtained by the first sensor and the sensor data obtained by the second sensor; and control the first display to display the content, based on the display direction of the content.

(14) The processor may be further configured to: based on the sensor data obtained by the first sensor satisfying a first condition, determine the display direction of the content based on the sensor data obtained by the second sensor; and based on the sensor data obtained by the second sensor satisfying the first condition, determine the display direction of the content based on the sensor data obtained by the first sensor.

(15) The processor may be further configured to, based on the sensor data obtained by the first sensor and the sensor data obtained by the second sensor not satisfying the first condition, determine the display direction of the content, based on the sensor data obtained by the first sensor and the sensor data obtained by the second sensor.

(16) According to an aspect of the disclosure, an operation method of an electronic device including a first housing, a second housing, and a hinge structure foldably connecting the first housing and the second housing, includes: identifying, by a first sensor and a second sensor, a folding angle between the first housing and the second housing, the first sensor being disposed in a first space of the first housing which includes a first surface, a second surface facing a direction opposite to the first surface, and a first lateral surface surrounding the first space between the first surface and the second surface, the second sensor being disposed in a second space of the second housing which includes a third surface facing a same direction as the first surface when the first housing and the second housing are in an unfolded state, a fourth surface opposite to the third surface, and a second lateral surface surrounding the second space between the third surface and the fourth surface; based on the folding angle between the first housing and the second housing satisfying a first range, selecting a second display from among a first display disposed from at least a part of the first surface to at least a part of the third surface, and the second display disposed in the second space so as to be visible from an outside through at least a part of the fourth surface; determining a display direction of a content, based on sensor data obtained by the second sensor; and displaying the content on the second display, based on the display direction of the content.

(17) The identifying the folding angle may include: based on at least one of the first display and the second display being in an active state, identifying the folding angle between the first housing and the second housing by using the first sensor, the second sensor, and a magnetic detection sensor;

and based on the first display and the second being are in an inactive state, identifying the folding angle between the first housing and the second housing through at least one of a part of the first sensor and a part of the second sensor.

(18) At least one of the first sensor and the second sensor may include an acceleration sensor and a gyro sensor, and at least one of the part of the first sensor or the part of the second sensor includes the acceleration sensor.

(19) The operation method may further include: based on the first housing and the second housing being in a folded state, selecting the second display; determining the display direction of the content, based on sensor data on the sensor data obtained by the first sensor; and displaying the content on the second display, based on the display direction of the content.

(20) The operation method may further include: based on the first housing and the second housing being in the unfolded state, selecting the first; determining the display direction of the content, based on sensor data on the sensor data obtained by at least one of the first sensor and the second sensor; and displaying the content on the first display, based on the display direction of the content.

(21) The operation method may further include: selecting the first display when the folding angle between the first housing and the second housing is in a second range different from the first range; determining the display direction of the content, based on sensor data obtained by at least one of the first sensor and the second sensor; and displaying the content on the first display, based on the display direction of the content.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

(1) The above and other aspects, features, and advantages of the present disclosure will be more apparent from the following detailed description of embodiments, taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a block diagram of an electronic device, according to various embodiments;

(3) FIG. 2A illustrates an unfolded state of an electronic device according to various embodiments;

(4) FIG. 2B illustrates a folded state of an electronic device according to various embodiments;

(5) FIG. 2C illustrates an intermediate state of an electronic device according to various embodiments;

(6) FIG. 2D is an exploded perspective view of an electronic device according to various embodiments;

(7) FIG. 3 is a block diagram of an electronic device for controlling screen rotation according to various embodiments;

(8) FIG. 4 is a flowchart of configuring a display direction of a second display in an electronic device in an intermediate state according to various embodiments;

(9) FIGS. 5A, 5B, and 5C illustrate an example of switching a display direction of a second display in an electronic device in an intermediate state according to various embodiments;

(10) FIGS. 6A and 6B illustrate another example of switching a display direction of a second display in an electronic device in an intermediate state according to various embodiments;

(11) FIG. 7 is a flowchart of detecting a folding angle in an electronic device according to various embodiments;

(12) FIG. 8 is a flowchart of configuring a display direction of a first display in an electronic device in an intermediate state according to various embodiments;

(13) FIGS. 9A and 9B illustrate an example of switching a display direction of a first display in an electronic device in an intermediate state according to various embodiments;

(14) FIGS. 10A and 10B illustrate another example of switching a display direction of a first display in an electronic device in an intermediate state according to various embodiments;

- (15) FIG. 11 illustrates an example of configuring a display direction of a first display in an electronic device in an intermediate state according to various embodiments;
- (16) FIG. 12 is a flowchart of configuring a display direction of a first display in an electronic device in an unfolded state according to various embodiments;
- (17) FIGS. 13A and 13B illustrate an example of switching a display direction of a first display in an electronic device in an unfolded state according to various embodiments;
- (18) FIG. 14 is a flowchart of configuring a display direction of a second display in an electronic device in a folded state according to various embodiments; and
- (19) FIGS. 15A and 15B illustrate an example of switching a display direction of a second display in an electronic device in a folded state according to various embodiments.

#### DETAILED DESCRIPTION

- (20) Hereinafter, various embodiments will be described in detail with reference to the accompanying drawings.
- (21) FIG. 1 is a block diagram illustrating an example electronic device **101** in a network environment **100** according to various embodiments. Referring to FIG. 1, the electronic device **101** in the network environment **100** may communicate with an electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **101** may communicate with the electronic device **104** via the server **108**. According to an embodiment, the electronic device **101** may include a processor **120**, memory **130**, an input module **150**, a sound output module **155**, a display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In various embodiments, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In various embodiments, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).
- (22) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation. According to an embodiment, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in non-volatile memory **134**. According to an embodiment, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.
- (23) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application).

According to an embodiment, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(24) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(25) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(26) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(27) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(28) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(29) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., an electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(30) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(31) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **177** may include,



for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(32) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the electronic device **102**).

According to an embodiment, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(33) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **179** may include, for example, a motor, a piezoelectric element, or an electric stimulator.

(34) The camera module **180** may capture a still image or moving images. According to an embodiment, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(35) The power management module **188** may manage power supplied to the electronic device **101**. According to an embodiment, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(36) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(37) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the electronic device **102**, the electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5G network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(38) The wireless communication module **192** may support a 5G network, after a 4G network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional

MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC. According to an embodiment, the subscriber identification module **196** may include a plurality of subscriber identification modules. For example, the plurality of subscriber identification modules may store different subscriber information.

(39) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(40) According to various embodiments, the antenna module **197** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(41) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(42) According to an embodiment, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing

or mobile edge computing. In an embodiment, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(43) The electronic device according to various embodiments may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, a home appliance, or the like. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(44) It should be appreciated that various embodiments of the present disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(45) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, or any combination thereof, and may interchangeably be used with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(46) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., internal memory **136** or external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the “non-transitory” storage medium is a tangible device, and may not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(47) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only

memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as memory of the manufacturer's server, a server of the application store, or a relay server.

(48) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(49) FIG. 2A illustrates an unfolded state of an electronic device **200** according to various embodiments. FIG. 2B illustrates a folded state of the electronic device **200** according to various embodiments. FIG. 2C illustrates an intermediate state of the electronic device **200** according to various embodiments. The electronic device **200** of FIGS. 2A, 2B, and 2C may be, for example, at least partially similar to the electronic device **101** of FIG. 1, may include features of the electronic device **101**, may be used in conjunction with other features and systems similar to the electronic device **101** shown in FIG. 1 or may include other embodiments of the electronic device.

(50) Referring to FIGS. 2A, 2B, and 2C, the electronic device **200** may include a pair of housings **210** and **220** (e.g., a foldable housing) rotatably or foldably coupled through a hinge structure or hinge module (e.g., a hinge module **264** of FIG. 2D) so that they can be folded with respect to each other. The electronic device **200** may include a first display **230** (e.g., a flexible display, a foldable display, or a main display) and a second display **235** (e.g., a sub display) which are disposed through the pair of housings **210** and **220**. According to an embodiment, the hinge module (e.g., the hinge module **264** of FIG. 2D) may be disposed to be visible from the outside through a first housing **210** and a second housing **220**, in a folded state, and may be disposed to be invisible from the outside through a hinge cover **265** which protects the hinge module **264** and covers a foldable part, in an unfolded state. A surface on which the first display **230** is disposed may be defined as a front surface of the electronic device **200**, and an opposite surface of the front surface may be defined as a rear surface of the electronic device **200**. In addition, a surface surrounding the space between the front surface and the rear surface may be defined as a lateral surface of the electronic device **200**.

(51) According to various embodiments, the pair of housings **210** and **220** may include the first housing **210** and the second housing **220** configured to be foldable with respect to each other through the hinge module (e.g., the hinge module **264** of FIG. 2D). According to an embodiment, the pair of housings **210** and **220** are not limited to the shape and coupling shown in FIGS. 2A, 2B, and 2C and may be implemented by a combination and/or coupling of other shapes or components. According to an embodiment, the first housing **210** and the second housing **220** may be disposed on opposite sides with respect to a folding axis (A axis), and may have an overall symmetrical shape with respect to the folding axis (A axis). According to an embodiment, the first housing **210** and the second housing **220** may be folded asymmetrically with reference to the folding axis. According to an embodiment, an angle or distance between the first housing **210** and the second housing **220** may be changed depending on whether the electronic device **200** is in an unfolded state, a folded state, or an intermediate state.

(52) According to an embodiment, the first housing **210** may be connected to the hinge module (e.g., the hinge module **264** of FIG. 2D) in the unfolded state of the electronic device **200**, and include a first surface **211** disposed to face the front surface of the electronic device **200**, a second surface **212** facing a direction opposite to the first surface **211**, and a first lateral member **213** surrounding at least a part of a first space between the first surface **211** and the second surface **212**. According to an embodiment, the second housing **220** may be connected to the hinge module (e.g., the hinge module **264** of FIG. 2D) in an unfolded state of the electronic device **200**, and include a third surface **221** disposed to face the front surface of the electronic device **200**, a fourth surface **222** facing a direction opposite to the third surface **221**, and a second lateral member **223** surrounding at least a part of a second space between the third surface **221** and the fourth surface **222**. According to an embodiment, the first surface **211** may face the same direction as the third surface **221** in the unfolded state, and face the third surface **221** in the folded state. Although not shown, according to another embodiment, the first surface **211** may be disposed to face the opposite direction of the third surface **221** in the folded state. According to an embodiment, the electronic device **200** may include a recess **201** formed to receive the first display **230** via structural coupling of the first housing **210** and the second housing **220**. According to an embodiment, the recess **201** may have substantially the same size as the first display **230**.

(53) According to various embodiments, the hinge cover **265** may be disposed between the first housing **210** and the second housing **220** to cover the hinge module (e.g., the hinge module **264** of FIG. 2D). According to an embodiment, the hinge cover **265** may be covered by parts of the first housing **210** and the second housing **220** or exposed to the outside depending on whether the electronic device is in an unfolded state, a folded state, or an intermediate state. For example, when the electronic device **200** is in the unfolded state, the hinge cover **265** may be not exposed since the hinge cover is covered by the first housing **210** and the second housing **220**. According to an embodiment, when the electronic device **200** is in the folded state such that the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** face each other, the hinge cover **265** may be exposed to the outside between the first housing **210** and the second housing **220**. According to an embodiment, when the electronic device is in the intermediate state in which the first housing **210** and the second housing **220** are folded with a certain angle, the hinge cover **265** may be at least partially exposed to the outside of the electronic device **200** between the first housing **210** and the second housing **220**. For example, an area where the hinge cover **265** is exposed to the outside may be smaller than an area of the hinge cover **265** that is exposed when the electronic device **200** is in a completely folded state. Although not shown, according to another embodiment, when the electronic device **200** is in the folded state such that the second surface **212** of the first housing **210** and the fourth surface **222** of the second housing **220** face each other, the hinge cover **265** may be not exposed to the outside between the first housing **210** and the second housing **220**. In an embodiment, the hinge cover **265** may include a curved surface.

(54) According to various embodiments, when the electronic device **200** is in the unfolded state (e.g., the state of FIG. 2A), the first housing **210** and the second housing **220** form an angle of 180 degrees, and a first area **230a**, a folding area **230c**, and a second area **230b** of the first display **230** may be on the same plane and may be disposed to face the same direction.

(55) In an embodiment, when the electronic device **200** is in the folded state (e.g., the state of FIG. 2B), the first surface **211** of the first housing **210** and the third surface **221** of the second housing **220** may be disposed to face each other (an in-folding manner). In an embodiment, the first area **230a** and the second area **230b** of the first display **230** may form a narrow angle (e.g., a range of from about 0 degrees to about 10 degrees) through the folding area **230c**, and may be disposed to face each other. According to an embodiment, at least a part of the folding area **230c** may be configured to have a curved surface having a predetermined curvature. In another embodiment, when the electronic device **200** is in the folded state, the first housing **210** and the second housing **220** may rotate with respect to each other by an angle of 360 degrees to be reversely folded so that

the second surface **212** and the fourth surface **222** face each other (an out-folding manner).

(56) According to an embodiment, when the electronic device **200** is in the intermediate state (e.g., the state of FIG. **2C**), the first housing **210** and the second housing **220** may be disposed at a certain angle to each other. In this case, the first area **230a** and the second area **230b** of the first display **230** may form an angle greater than that in the folded state and smaller than that in the unfolded state, and the curvature of the folding area **230c** may be smaller than that in the folded state. In an embodiment, the first housing **210** and the second housing **220** may be configured to be capable of stopping at a designated folding angle between the folded state and the unfolded state, through the hinge module (e.g., the hinge module **264** of FIG. **2D**) (a free stop function). In an embodiment, the first housing **210** and the second housing **220** may operate while being pressed in an unfolding direction or a folding direction with reference to a designated inflection angle, through the hinge module (e.g., the hinge module **264** of FIG. **2D**).

(57) According to various embodiments, the electronic device **200** may include at least one of at least one display **230** and **235** disposed in the first housing **210** and/or the second housing **220**, an input device **215**, sound output device **227** and **228**, sensor modules **217a**, **217b**, and **226**, camera modules **216a**, **216b**, and **225**, a key input device **219**, an indicator (not shown), or a connector port **229**. In an embodiment, the electronic device **200** may omit at least one of the components or may additionally include at least one other component.

(58) According to various embodiments, the at least one display **230** and **235** may include the first display **230** (e.g., a flexible display) disposed to be supported by the third surface **221** of the second housing **220** from the first surface **211** of the first housing **210** through the hinge module (e.g., the hinge module **264** of FIG. **2D**), and the second display **235** disposed to be visible from the outside through the fourth surface **222** in an inner space of the second housing **220**. According to an embodiment, the first display **230** may be mainly used in the unfolded state of the electronic device **200**, and the second display **235** may be mainly used in the folded state of the electronic device **200**. According to an embodiment, in the case of the intermediate state, the electronic device **200** may use the first display **230** or the second display **235**, based on a folding angle between the first housing **210** and the second housing **220**.

(59) According to various embodiments, the first display **230** may be disposed in a space formed by the pair of housings **210** and **220**. For example, the first display **230** may be seated in the recess **201** formed by the pair of housings **210** and **220**, and may be disposed to occupy substantially most of the front surface of the electronic device **200**. According to an embodiment, the first display **230** may include a flexible display in which at least a partial area thereof may be transformed into a flat or curved surface. According to an embodiment, the first display **230** may include the first area **230a** facing the first housing **210**, the second area **230b** facing the second housing **220**, and the folding area **230c** which connects the first area **230a** and the second area **230b** and faces the hinge module (e.g., the hinge module **264** of FIG. **2D**). According to an embodiment, the area division of the first display **230** is only an exemplary physical division by the pair of housings **210** and **220** and the hinge module (e.g., the hinge module **264** of FIG. **2D**), and substantially, the first display **230** may be seamlessly displayed as one entire screen through the pair of housings **210** and **220** and the hinge module (e.g., the hinge module **264** of FIG. **2D**). According to an embodiment, the first area **230a** and the second area **230b** may have a generally symmetrical shape or a partially asymmetrical shape with reference to the folding area **230c**.

(60) According to various embodiments, the electronic device **200** may include a first rear cover **240** disposed on the second surface **212** of the first housing **210**, and a second rear cover **250** disposed on the fourth surface **222** of the second housing **220**. In an embodiment, at least a part of the first rear cover **240** may be integrally configured with the first lateral member **213**. In an embodiment, at least a part of the second rear cover **250** may be integrally configured with the second lateral member **223**. According to an embodiment, at least one of the first rear cover **240** and the second rear cover **250** may be configured through a substantially transparent plate (e.g., a

polymer plate or a glass plate including various coating layers) or an opaque plate. According to an embodiment, the first rear cover **240** may be formed of, for example, an opaque plate such as coated or colored glass, ceramic, a polymer, a metal (e.g., aluminum, stainless steel (STS), or magnesium), or a combination of at least two of the materials. According to an embodiment, the second rear cover **250** may be formed through, for example, a substantially transparent plate such as glass or polymer. Accordingly, the second display **235** may be disposed to be visible from the outside through the second rear cover **250** in the inner space of the second housing **220**.

(61) According to various embodiments, the input device **215** may include a microphone **215**. In an embodiment, the input device **215** may include a plurality of microphones **215** disposed to detect the direction of sound. According to an embodiment, the sound output devices **227** and **228** may include speakers **227** and **228**. According to an embodiment, the speakers **227** and **228** may include a call receiver **227** disposed through the fourth surface **222** of the second housing **220**, and an external speaker **228** disposed through the lateral member of the second housing **220**. In an embodiment, the microphone **215**, the speakers **227** and **228**, and the connector port **229** may be disposed in spaces of the first housing **210** and/or the second housing **220**, and may be exposed to an external environment through at least one hole formed in the first housing **210** and/or the second housing **220**. In an embodiment, holes formed in the first housing **210** and/or the second housing **220** may be commonly used for the microphone **215** and the speakers **227** and **228**. In an embodiment, the sound output devices **227** and **228** may include a speaker (e.g., a piezo speaker) which operates while excluding the hole formed in the first housing **210** and/or the second housing **220**.

(62) According to various embodiments, the camera modules **216a**, **216b**, and **225** may include a first camera device **216a** disposed on the first surface **211** of the first housing **210**, a second camera device **216b** disposed on the second surface **212** of the first housing **210**, and/or a third camera device **225** disposed on the fourth surface **222** of the second housing **220**. According to an embodiment, the electronic device **200** may include a flash **218** disposed near the second camera device **216b**. According to an embodiment, the flash **218** may include, for example, a light-emitting diode or a xenon lamp. According to an embodiment, the camera devices **216a**, **216b**, and **225** may include one or a plurality of lenses, an image sensor, and/or an image signal processor. In an embodiment, at least one of the camera devices **216a**, **216b**, and **225** may include two or more lenses (wide-angle and telephoto lenses) and image sensors, and may be disposed together on either surface of the first housing **210** and/or the second housing **220**.

(63) According to various embodiments, the sensor modules **217a**, **217b**, and **226** may generate an electrical signal or data value corresponding to an internal operation state of the electronic device **200** or an external environment state thereof. According to an embodiment, the sensor modules **217a**, **217b**, and **226** may include a first sensor module **217a** disposed on the first surface **211** of the first housing **210**, a second sensor module **217b** disposed on the second surface **212** of the first housing **210**, and/or a third sensor module **226** disposed on the fourth surface **222** of the second housing **220**. In an embodiment, the sensor modules **217a**, **217b**, and **226** may include at least one of a gesture sensor, a grip sensor, a color sensor, an infrared (IR) sensor, an illuminance sensor, an ultrasonic sensor, an iris recognition sensor, or a distance detection sensor (a TOF sensor or LiDAR scanner).

(64) According to various embodiments, the electronic device **200** may include a first inertial sensor **283a** disposed in the first housing **210**, and a second inertial sensor **283b** disposed in the second housing **220**. According to an embodiment, the first inertial sensor **283a** may be disposed in an inner space of the first housing **210** to generate an electrical signal or data value related to movement of the first housing **210**. According to an embodiment, the second inertial sensor **283b** may be disposed in the inner space of the second housing **220** to generate an electrical signal or data value related to movement of the second housing **220**. For example, the first inertial sensor **283a** and/or the second inertial sensor **283b** may include a 6-axis sensor, a motion sensor, a gyro

sensor, and/or an acceleration sensor.

(65) According to various embodiments, the electronic device **200** may further include at least one or more various other sensors, for example, an air pressure sensor, a magnetic sensor, a biometric sensor, a temperature sensor, a humidity sensor, or a fingerprint recognition sensor. In an embodiment, the fingerprint recognition sensor may be disposed through at least one of the first lateral member **213** of the first housing **210** and/or the second lateral member **223** of the second housing **220**.

(66) According to various embodiments, the key input device **219** may be disposed to be exposed to the outside through the first lateral member **213** of the first housing **210**. In an embodiment, the key input device **219** may be disposed to be exposed to the outside through the second lateral member **223** of the second housing **220**. In an embodiment, the electronic device **200** may not include a part or all of the above-mentioned key input device **219**, and a key input device **219**, which is not included, may be implemented in another form, such as a soft key, on the at least one display **230** and **235**. In another embodiment, the key input device **219** may be implemented using a pressure sensor included in the at least one display **230** and **235**.

(67) According to various embodiments, the connector port **229** may receive a connector (for example, a USB connector or an interface connector port module (IF module)) for transmitting or receiving power and/or data to or from an external electronic device. In an embodiment, the connector port **229** may perform a function for transmitting or receiving an audio signal to or from an external electronic device together or further include a separate connector port (e.g., an ear jack hole) for performing a function for transmitting or receiving an audio signal.

(68) According to various embodiments, at least one camera device **216a** and **225** among the camera devices **216a**, **216b**, and **225** and at least one sensor module **217a** and **226** among the sensor modules **217a**, **217b**, and **226**, and/or the indicator may be disposed to be exposed through the at least one display **230** and **235**. For example, the at least one camera device **216a** and **225**, the at least one sensor module **217a** and **226**, and/or the indicator may be disposed under active areas (display areas) of the displays **230** and **235** in the inner spaces of the at least one housing **210** and **220**, and disposed to be in contact with an external environment through an opening perforated up to a cover member (e.g., a window layer (not shown) of the first display **230** and/or the second rear cover **250**). In another embodiment, some camera devices **216a** and/or **225** or sensor modules **217a** and/or **226** may be disposed to perform their functions without being visually exposed through the display **230** and/or **235**. For example, an area of the display **230** and/or **235** (e.g., a display panel) facing the camera device **216a** and/or **225** and/or the sensor module **217a** and/or **226** may not require a perforated opening.

(69) Referring to FIG. 2C, the electronic device **200** may operate to maintain the intermediate state through the hinge module (e.g., the hinge module **264** of FIG. 2D). According to an embodiment, the intermediate state may be an operation state corresponding to the first housing **210** and the second housing **220** being between an unfolded state and a folded state. The intermediate state may include an operation state in which a folding angle between the first housing **210** and the second housing **220** is included in a third reference range of, for example, from about 20 degrees to about 170 degrees. According to an embodiment, in the intermediate state, the electronic device **200** may operate such that the first housing **210** and the second housing **220** are maintained in the unfolded state at various angles through the hinge module (e.g., the hinge module **264** of FIG. 2D). For example, the unfolded state of the first housing **210** and the second housing **220** may include an operation state in which the folding angle between the first housing **210** and the second housing **220** is included in a first reference range of, for example, from about 170 degrees to about 180 degrees. For example, the folded state of the first housing **210** and the second housing **220** may include an operation state in which the folding angle between the first housing **210** and the second housing **220** is included in a second reference range of, for example, from about 0 degrees to about 20 degrees.



(70) According to an embodiment, the electronic device **200** may use the first display **230** or the second display **235**, based on the folding angle between the first housing **210** and the second housing **220**. For example, when the folding angle between the first housing **210** and the second housing **220** is included in a designated first range (e.g., from about 20 degrees to about 75 degrees), the electronic device **200** may use the second display **235**. For example, when the folding angle between the first housing **210** and the second housing **220** is included in a designated second range (e.g., from about 75 degrees to about 170 degrees), the electronic device **200** may use the first display **230**. In an embodiment, the electronic device **200** may control the first display **230** to display different contents in a first area (e.g., a first area **231a** of FIG. 2D) of the first display **230** corresponding to the first surface **211** and a second area (e.g., a second area **231b** of FIG. 2D) of the first display **230** corresponding to the third surface **221**. For example, the designated first range and/or the designated second range may be included in the third reference range for determining the intermediate state.

(71) FIG. 2D is an exploded perspective view of the electronic device **200** according to various embodiments.

(72) Referring to FIG. 2D, in an embodiment, the electronic device **200** may include the first display **230**, the second display **235**, a support member assembly **260**, at least one printed circuit board **270**, the first housing **210**, the second housing **220**, the first rear cover **240**, and the second rear cover **250**.

(73) According to various embodiments, the first display **230** may include a display panel **231** (e.g., a flexible display panel) and one or more plates **232** or layers on which the display panel **231** (e.g., a flexible display panel) is seated. In an embodiment, the one or more plates **232** may include a conductive plate (e.g., a Cu sheet or an SUS sheet) disposed between the display panel **231** and the support member assembly **260**. According to an embodiment, the one or more plates **232** may be configured to have substantially the same area as the first display **230**, and may be configured such that an area thereof facing the folding area **230c** of the first display **230** is bendable. According to an embodiment, the one or more plates **232** may include at least one sub-material layer (e.g., a graphite member) disposed on a rear surface of the display panel **231**. In an embodiment, the one or more plates **232** may be configured to have a shape corresponding to the display panel **231**.

(74) According to various embodiments, the second display **235** may be disposed in the space between the second housing **220** and the second rear cover **250**. According to an embodiment, the second display **235** may be disposed to be visible from the outside through substantially the entire area of the second rear cover **250**, in the space between the second housing **220** and the second rear cover **250**.

(75) According to various embodiments, the support member assembly **260** may include a first support member **261** (e.g., a first support plate), a second support member **262** (e.g., a second support plate), the hinge module **264** disposed between the first support member **261** and the second support member **262**, the hinge cover **265** which covers the hinge module **264** when viewed from the outside, and at least one wiring member **263** (e.g., a flexible printed circuit board (FPCB)) crossing the first support member **261** and the second support member **262**. According to an embodiment, the support member assembly **260** may be disposed between the one or more plates **232** and the at least one printed circuit board **270**. According to an embodiment, the first support member **261** may be disposed between the first area **231a** of the first display **230** and a first printed circuit board **271**. According to an embodiment, the second support member **262** may be disposed between the second area **231b** of the first display **230** and a second printed circuit board **272**.

According to an embodiment, at least a part of the hinge module **264** and the at least one wiring member **263** may be disposed inside the support member assembly **260**. The at least one wiring member **263** may be disposed in a direction (e.g., the x-axis direction) crossing the first support member **261** and the second support member **262**. According to an embodiment, the at least one wiring member **263** may be disposed in a direction (e.g., the x-axis direction) perpendicular to a

folding axis (e.g., the y-axis or the folding axis A of FIG. 2A) of the folding area 230c.

(76) According to various embodiments, the at least one printed circuit board 270 may include the first printed circuit board 271 disposed to face the first support member 261, and the second printed circuit board 272 disposed to face the second support member 262. According to an embodiment, the first printed circuit board 271 and the second printed circuit board 272 may be disposed in an inner space formed by the support member assembly 260, the first housing 210, the second housing 220, the first rear cover 240, and/or the second rear cover 250. According to an embodiment, the first printed circuit board 271 and the second printed circuit board 272 may include a plurality of electronic components arranged to implement various functions of the electronic device 200.

(77) According to various embodiments, the electronic device may include, in the first space of the first housing 210, the first printed circuit board 271 disposed in a space formed through the first support member 261, a first battery 291 disposed at a position facing a first swelling hole 2611 of the first support member 261, at least one camera device 282 (e.g., the first camera device 216a and/or the second camera device 216b of FIG. 2A), or at least one sensor module 281 (e.g., the first sensor module 217a and/or the second sensor module 217b of FIG. 2A). According to an embodiment, the second space of the second housing 220 may include the second printed circuit board 272 disposed in a second space formed through the second support member 262, and a second battery 292 disposed at a position facing a second swelling hole 2621 of the second support member 262. According to an embodiment, the first housing 210 and the first support member 261 may be integrally configured. According to an embodiment, the second housing 220 and the second support member 262 may also be integrally configured.

(78) According to various embodiments, the first housing 210 may include a first rotation support surface 214, and the second housing 220 may include a second rotation support surface 224 corresponding to the first rotation support surface 214. According to an embodiment example, the first rotation support surface 214 and the second rotation support surface 224 may include a curved surface corresponding to (naturally connected to) a curved surface included in the hinge cover 265. According to an embodiment, when the electronic device 200 is in the unfolded state, the first rotation support surface 214 and the second rotation support surface 224 may cover the hinge cover 265 so that the hinge cover 265 is not exposed to the rear surface of the electronic device 200 or is minimally exposed. In an embodiment, when the electronic device 200 is in the folded state, the first rotation support surface 214 and the second rotation support surface 224 may rotate along the curved surface included in the hinge cover 265 to maximally expose the hinge cover 265 to the rear surface of the electronic device 200.

(79) FIG. 3 is a block diagram of an electronic device for controlling screen rotation according to various embodiments. According to an embodiment, an electronic device 300 of FIG. 3 may be at least partially similar to the electronic device 101 of FIG. 1 or the electronic device 200 of FIG. 2A, or may further include other embodiments of the electronic device.

(80) Referring to FIG. 3, according to various embodiments, the electronic device 300 may include a processor 310, a first display 320, a second display 330, a first sensor 340, a second sensor 350, and/or a memory 360. According to an embodiment, the processor 310 may be substantially the same as the processor 120 of FIG. 1 or included in the processor 120. The first display 320 and/or the second display 330 may be substantially the same as the display module 160 of FIG. 1 or included in the display module 160. The first sensor 340 and/or the second sensor 350 may be substantially the same as the sensor module 176 of FIG. 1 or included in the sensor module 176. The memory 360 may be substantially the same as the memory 130 of FIG. 1 or included in the memory 130.

(81) According to an embodiment, the first display 320 may be substantially the same as the first display 230 of FIG. 2A or included in the first display 230. The second display 330 may be substantially the same as the second display 235 of FIG. 2A or included in the second display 235. The first sensor 340 may be substantially the same as the first inertial sensor 283a of FIG. 2A or

included in the first inertial sensor **283a**. The second sensor **350** may be substantially the same as the second inertial sensor **283b** of FIG. 2A or included in the second inertial sensor **283b**.

(82) According to various embodiments, the first display **320** may be disposed from at least a part of a first surface (e.g., the first surface **211** of FIG. 2A) of a first housing (e.g., the first housing **210** of FIG. 2A) of the electronic device **300** to at least a part of a third surface (e.g., the third surface **221** of FIG. 2A) of a second housing (e.g., the second housing **220** of FIG. 2A). According to an embodiment, the first display **320** may include a flexible display in which at least a partial area thereof can be changed to a flat or curved surface based on a folding angle between the first housing (e.g., the first housing **210** of FIG. 2A) and the second housing (e.g., the second housing **220** of FIG. 2A).

(83) According to various embodiments, the second display **330** may be disposed to be visible from the outside through at least a part of a fourth surface (e.g., the fourth surface **222** of FIG. 2A) in an inner space of the second housing (e.g., the second housing **220** of FIG. 2A) of the electronic device **300**.

(84) According to various embodiments, the first display **320** and/or the second display **330** may display information processed by the electronic device **300**. According to an embodiment, the first display **320** and/or the second display **330** may display a content related to an application program executed by the processor **310**. According to an embodiment, when the electronic device **300** operates in a sleep mode, the first display **320** and/or the second display **330** may display a content related to a low power display mode (e.g., may be an always on display (AOD)). For example, the sleep mode of the electronic device **300** may include a state in which driving of the processor **310** (e.g., an application processor) is restricted.

(85) According to various embodiments, the first sensor **340** may be disposed in at least a part of an inner space of the first housing (e.g., the first housing **210** of FIG. 2A) of the electronic device **300**. According to an embodiment, the first sensor **340** may collect information such as, for example, posture, angular velocity, and/or acceleration, information related to movement of the first housing (e.g., the first housing **210** of FIG. 2A) to provide the collected information to the processor **310**. For example, the first sensor **340** may include an inertial sensor, a motion sensor, a 6-axis sensor, a first gyro sensor, and/or a first acceleration sensor.

(86) According to various embodiments, the second sensor **350** may be disposed in at least a part of the inner space of the second housing (e.g., the second housing **220** of FIG. 2A) of the electronic device **300**. According to an embodiment, the second sensor **350** may collect information such as, for example, posture, angular velocity, and/or acceleration information related to movement of the second housing (e.g., the second housing **220** of FIG. 2A) to provide the collected information to the processor **310**. For example, the second sensor **350** may include an inertial sensor, a motion sensor, a 6-axis sensor, a second gyro sensor, and/or a second acceleration sensor.

(87) According to various embodiments, the processor **310** may control the first display **320**, the second display **330**, and the first sensor **340** and/or the second sensor **350** which are operatively connected. For example, the processor **310** may include an application processor or a sensor hub processor.

(88) According to various embodiments, the processor **310** may detect a folding angle of the electronic device **300**. According to an embodiment, when the first display **320** and/or the second display **330** is in an active state, the processor **310** may detect the folding angle between the first housing (e.g., the first housing **210** of FIG. 2A) and the second housing (e.g., the second housing **220** of FIG. 2A), based on sensor data collected through the first sensor **340** and the second sensor **350**. For example, when the first display **320** and/or the second display **330** is in the active state, the processor **310** may detect the folding angle between the first housing (e.g., the first housing **210** of FIG. 2A) and the second housing (e.g., the second housing **220** of FIG. 2A) by using the first sensor **340**, the second sensor **350**, and a magnetic detection sensor such as, for example, a Hall IC. For example, the magnetic detection sensor may be disposed in the first housing (or the second

housing) to detect a magnetic force generated from a magnetic material disposed in the second housing (or the first housing). For example, the active state of the first display **320** and/or the second display **330** may include a state in which all pixels of a display (e.g., the first display **320** and/or the second display **330**) are activated. For example, the processor **310** (e.g., the application processor) may be activated when the first display **320** and/or the second display **330** is in the active state. In this case, the first sensor **340** and/or the second sensor **350** may be controlled by the application processor and/or the sensor hub processor.

(89) According to an embodiment, when the first display **320** and the second display **330** are in an inactive state, the processor **310** may detect a folding angle between the first housing (e.g., the first housing **210** of FIG. 2A) and the second housing (e.g., the second housing **220** of FIG. 2A), based on sensor data collected through a part (e.g., the first acceleration sensor) of the first sensor **340** and/or a part (e.g., the second acceleration sensor) of the second sensor **350**. For example, the inactive state of the first display **320** and/or the second display **330** may include a state in which at least one pixel of the display (e.g., the first display **320** and/or the second display **330**) is activated or a state in which all pixels of the display are inactivated. For example, when the first display **320** and/or the second display **330** is in the inactive state, the application processor of the processor **310** may be inactivated, and the sensor hub processor may control the first sensor **340** and/or the second sensor **350**.

(90) According to various embodiments, the processor **310** may select the first display **320** and/or the second display **330** as a display for displaying a content, based on the folding angle of the electronic device **300**. For example, the content may include a content related to an application program executed by the processor **310** or a content related to a low power display mode (e.g., an always on display AOD). According to an embodiment, when the processor **310** determines that the electronic device **300** is in an unfolded state (e.g., the state of FIG. 2A), based on the folding angle of the electronic device **300**, the processor may select the first display **320** to display a content. For example, the unfolded state of the electronic device **300** may include a state in which the folding angle of the electronic device **300** is included in the first reference range (e.g., from about 170 degrees to about 180 degrees). According to an embodiment, when the processor **310** determines that the electronic device **300** is in a folded state (e.g., the state of FIG. 2B), based on the folding angle of the electronic device **300**, the processor **310** may select the second display **330** to display a content. For example, the folded state of the electronic device **300** may include a state in which the folding angle of the electronic device **300** is included in the second reference range (e.g., from about 0 degrees to about 20 degrees).

(91) According to an embodiment, when the folding angle of the electronic device **300** is included in the designated first range (e.g., from about 20 degrees to about 75 degrees), the processor **310** may select the second display **330** to display a content. For example, when the folding angle of the electronic device **300** is included in the designated first range (e.g., from about 20 degrees to about 75 degrees), the electronic device **300** may operate in a first sub-mode or a second sub-mode, based on an area which is placed on (or in contact with) a horizontal plane. For example, the horizontal plane may refer to a plane substantially perpendicular to the direction of gravity. Accordingly, the processor **310** may select the second display **330** to display a content in the first sub-mode and the second-sub mode. For example, the first sub-mode may include a state in which a second surface (e.g., the second surface **212** of FIG. 2A) of the first housing (e.g., the first housing **210** of FIG. 2A) is placed on (or in contact with) the horizontal plane. For example, the second sub-mode may include a state in which a lateral surface (e.g., the first lateral member **213** of FIG. 2A) of the first housing (e.g., the first housing **210** of FIG. 2A) and a lateral surface (e.g., the second lateral member **223** of FIG. 2A) of the second housing (e.g., the second housing **220** of FIG. 2A) are placed on (or in contact with) the horizontal plane. For example, when the folding angle of the electronic device is included in a designated third range of the vertical axis (e.g., the Z-axis in FIG. 2A), the transverse axis (e.g., the X-axis in FIG. 2A), and the longitudinal axis (e.g., the Y-axis in

FIG. 2A) of the first sensor **340**, the processor **310** may determine that the second surface of the first housing is in a state of being placed on (or in contact with) the horizontal plane. For example, the designated third range may include a range from about -25 degrees to about 25 degrees about the transverse axis, a range from about -12 degrees to about 12 degrees about the longitudinal axis, and a range from about 65 degrees to about 90 degrees about the vertical axis.

(92) According to an embodiment, when the folding angle of the electronic device **300** is included in the designated second range (e.g., from about 75 degrees to about 170 degrees), the processor **310** may select the first display **320** to display a content. For example, when the folding angle of the electronic device **300** is included in the designated first range or the designated second range, the processor **310** may determine that the electronic device **300** is in an intermediate state (e.g., the state of FIG. 2C).

(93) According to various embodiments, the processor **310** may select the first sensor **340** and/or the second sensor **350** as a sensor to be used to detect rotation of the electronic device **300**, based on the folding angle of the electronic device **300**. According to an embodiment, when the processor **310** determines that the electronic device **300** is in the unfolded state (e.g., the state of FIG. 2A), based on the folding angle of the electronic device **300**, the processor may select the first sensor **340** and/or the second sensor **350** as the sensor to be used to detect rotation of the electronic device **300**. For example, the processor **310** may indicate that all axis directions of the first sensor **340** and the second sensor **350** are the same while the electronic device **300** is in the unfolded state.

Accordingly, while the electronic device **300** is in the unfolded state, the processor **310** may select the first sensor **340** (e.g., the first acceleration sensor) or the second sensor **350** (e.g., the second acceleration sensor) as a sensor for detecting rotation of the electronic device **300**. For example, when the first display **320** is in the inactive state while the electronic device **300** is in the unfolded state, the processor **310** may select the first sensor **340** (e.g., the first acceleration sensor) or the second sensor **350** (e.g., the second acceleration sensor) as a sensor for detecting rotation of the electronic device **300**, in order to reduce power consumption.

(94) According to an embodiment, when the processor **310** determines that the electronic device **300** is in the folded state (e.g., the state of FIG. 2B), based on the folding angle of the electronic device **300**, the processor may select the first sensor **340** as the sensor to be used to detect rotation of the electronic device **300**. For example, since the second display **330** selected to display a content while the electronic device **300** is in the folded state corresponds to the direction (e.g., the Z-axis) of the vertical axis of the first sensor **340**, the processor **310** may select the first sensor **340** as the sensor to be used to detect rotation of the electronic device **300**.

(95) According to an embodiment, when the folding angle of the electronic device **300** is included in the designated first range (e.g., from about 20 degrees to about 75 degrees), the processor **310** may select the second sensor **350** as the sensor to be used to detect rotation of the electronic device **300**.

(96) According to an embodiment, when the folding angle of the electronic device **300** is included in the designated second range (e.g., from about 75 degrees to about 170 degrees), the processor **310** may select the first sensor **340** and/or the second sensor **350** as the sensor to be used to detect rotation of the electronic device **300**. For example, when the second surface (e.g., the second surface **212** of FIG. 2A) of the first housing (e.g., the first housing **210** of FIG. 2A) is placed on (or in contact with) the horizontal plane in a state where the folding angle of the electronic device **300** is included in the designated second range (e.g., from about 75 degrees to about 170 degrees), the processor **310** may select the second sensor **350** as the sensor to be used to detect rotation of the electronic device **300**. For example, when the fourth surface (e.g., the fourth surface **222** of FIG. 2A) of the second housing (e.g., the second housing **220** of FIG. 2A) is placed on (or in contact with) the horizontal plane in a state where the folding angle of the electronic device **300** is included in the designated second range (e.g., from about 75 degrees to about 170 degrees), the processor **310** may select the first sensor **340** as the sensor to be used to detect rotation of the electronic

device **300**. For example, when the second surface (e.g., the second surface **212** of FIG. 2A) of the first housing (e.g., the first housing **210** of FIG. 2A) and the fourth surface (e.g., the fourth surface **222** of FIG. 2A) of the second housing (e.g., the second housing **220** of FIG. 2A) are not placed on (or in contact with) the horizontal plane in a state where the folding angle of the electronic device **300** is included in the designated second range (e.g., from about 75 degrees to about 170 degrees), the processor **310** may select the first sensor **340** and the second sensor **350** as the sensor to be used to detect rotation of the electronic device **300**. For example, when the folding angle of the electronic device is included in a designated third range of the vertical axis (e.g., the Z-axis in FIG. 2A), the transverse axis (e.g., the X-axis in FIG. 2A), and the longitudinal axis (e.g., the Y-axis in FIG. 2A) of the second sensor **350**, the processor **310** may determine that the fourth surface of the second housing is in a state of being placed on the horizontal plane.

(97) According to various embodiments, the processor **310** may configure a display direction of a content, based on the first sensor **340** and/or the second sensor **350** selected based on the folding angle of the electronic device **300**. According to an embodiment, the processor **310** may detect an orientation angle of the electronic device **300**, based on the first sensor **340** (e.g., the first acceleration sensor) and/or the second sensor **350** (e.g., the second acceleration sensor). The processor **310** may configure the display direction of the content, based on the orientation angle of the electronic device **300**. For example, the orientation angle of the electronic device **300** may refer to an angle between the transverse axis (e.g., the X-axis in FIG. 2A) and the longitudinal axis (e.g., the Y-axis in FIG. 2A), the angle corresponding to one surface of the electronic device **300** viewed by a user. The processor **310** may configure the display direction of the content, based on the orientation angle corresponding to the one surface of the electronic device **300** viewed by the user. The user may refer to, for example, a user who owns and/or operates the electronic device **300**. The display direction of the content may refer to, for example, a direction in which a user's gaze is directed.

(98) According to various embodiments, the processor **310** may generate information related to the content to be displayed on the first display **320** or the second display **330** selected to display the content, based on the display direction of the content. According to an embodiment, the processor **310** may generate the information related to the content, based on the size of a display area (e.g., screen) for displaying the content, a start position of the content, and/or a display direction of the content. For example, when the first display **320** is selected, the processor **310** may draw the information related to the content in a buffer of the first display **320**. In this case, the first display **320** may output the information related to the content drawn in the buffer to the display panel. For example, when the second display **330** is selected, the processor **310** may draw the information related to the content in a buffer of the second display **330**. In this case, the second display **330** may output the information related to the content drawn in the buffer to the display panel.

(99) According to various embodiments, the memory **360** may store various data used by at least one component (e.g., the processor **310**, the first display **320**, the second display **330**, the first sensor **340**, or the second sensor **350**) of the electronic device **300**. For example, the data may include information related to a reference range and/or a designated range for classifying an operation state of the electronic device **300**. As another example, the data may include sensor data collected by the first sensor **340** and/or the second sensor **350**.

(100) According to various embodiments of the disclosure, an electronic device (e.g., the electronic device **101** of FIG. 1, the electronic device **200** of FIG. 2A, or the electronic device **300** of FIG. 3) may include a hinge module (e.g., the hinge module of FIG. 2D), a first housing (e.g., the first housing **210** of FIG. 2A) connected to the hinge module and including a first surface (e.g., the first surface **211** of FIG. 2A), a second surface (e.g., the second surface **212** of FIG. 2A) facing a direction opposite to the first surface, and a first lateral surface (e.g., the first lateral member **213** of FIG. 2A) surrounding a first space between the first surface and the second surface, a second housing (e.g., the second housing **220** of FIG. 2A) connected to the hinge module so as to be

foldable with respect to the first housing and, in an unfolded state, including a third surface (e.g., the third surface **221** of FIG. 2A) facing the same direction as the first surface, a fourth surface (e.g., the fourth surface **222** of FIG. 2A) facing a direction opposite to the third surface, and a second lateral surface (e.g., the second lateral surface **223** of FIG. 2A) surrounding a second space between the third surface and the fourth surface, a first display (e.g., the display module **160** of FIG. 1, the first display **230** of FIG. 2A, or the first display **320** of FIG. 3) disposed from at least a part of the first surface to at least a part of the third surface, a second display (e.g., the display module **160** of FIG. 1, the second display **235** of FIG. 2A, or the second display **330** of FIG. 3) disposed in the second space so as to be visible from the outside through at least a part of the fourth surface, a first sensor (e.g., the sensor module **176** of FIG. 1, the first inertial sensor **283a** of FIG. 2A, or the first sensor **340** of FIG. 3) disposed in at least a part of the first space and configured to collect sensor data related to movement of the first housing, a second sensor (e.g., the sensor module **176** of FIG. 1, the second inertial sensor **283b** of FIG. 2A, or the second sensor **350** of FIG. 3) disposed in at least a part of the second space and configured to collect sensor data related to movement of the second housing, and a processor (e.g., the processor **120** of FIG. 1 or the processor **310** of FIG. 3) operatively connected with the first display, the second display, the first sensor, and the second sensor, wherein the processor is configured to identify a folding angle between the first housing and the second housing through the first sensor and the second sensor, select the second display when the folding angle between the first housing and the second housing satisfies a designated first range, determine a display direction of a content, based on sensor data collected through the second sensor, and control the second display to display the content, based on the display direction of the content.

(101) According to various embodiments, the electronic device may further include a magnetic detection sensor disposed in the first space or the second space, wherein the processor is configured to, when the first display and/or the second display is in an active state, identify the folding angle between the first housing and the second housing by using the first sensor, the second sensor, and the magnetic detection sensor, and when the first display and the second display are in an inactive state, identify the folding angle between the first housing and the second housing through a part of the first sensor and a part of the second sensor.

(102) According to various embodiments, the first sensor and/or the second sensor may include an acceleration sensor and a gyro sensor, and the part of the first sensor and/or the second sensor may include the acceleration sensor.

(103) According to various embodiments, the processor may be configured to select the second display when the first housing and the second housing are determined as being in a folded state, based on the folding angle between the first housing and the second housing, determine the display direction of the content, based on sensor data collected through the first sensor, and control the second display to display the content, based on the display direction of the content.

(104) According to various embodiments, the processor may be configured to select the first display when the first housing and the second housing are determined as being in the unfolded state, based on the folding angle between the first housing and the second housing, determine the display direction of the content, based on sensor data collected through the first sensor and/or the second sensor, and control the first display to display the content, based on the display direction of the content.

(105) According to various embodiments, the processor may be configured to, when the first display is in an active state in a state where the first housing and the second housing are in the unfolded state, determine the display direction of the content, based on the sensor data collected through the first sensor and the second sensor, and when the first display is in an inactive state in a state where the first housing and the second housing are in the unfolded state, determine the display direction of the content, based on the sensor data collected through the first sensor or the second sensor.

(106) According to various embodiments, the processor may be configured to select the first display when the folding angle between the first housing and the second housing satisfies a designated second range different from the designated first range, determine the display direction of the content, based on sensor data collected through the first sensor and/or the second sensor, and control the first display to display the content, based on the display direction of the content.

(107) According to various embodiments, the processor may be configured to, when the sensor data collected through the first sensor satisfies a designated first condition, determine the display direction of the content, based on the sensor data collected through the second sensor, and when the sensor data collected through the second sensor satisfies the designated first condition, determine the display direction of the content, based on the sensor data collected through the first sensor.

(108) According to various embodiments, the processor may be configured to, when the sensor data collected through the first sensor and the second sensor does not satisfy the designated first condition, determine the display direction of the content, based on the sensor data collected through the first sensor and the second sensor.

(109) According to various embodiments, the content may include a content related to an application program or a content related to a low power display mode.

(110) FIG. 4 is a flowchart 400 related to configuring a display direction of a second display in an electronic device in an intermediate state according to various embodiments. In the following embodiments, operations may be performed sequentially, but are not necessarily performed sequentially. For example, the order of the operations may be changed, and multiple operations such as at least two operations may be performed in parallel. For example, an electronic device of FIG. 4 may be the electronic device 101 of FIG. 1, the electronic device 200 of FIG. 2A, the electronic device 300 of FIG. 3 or another embodiment of an electronic device. At least some configurations of FIG. 4 will be described with reference to FIGS. 5A, 5B, 5C, 6A, and 6B. FIGS. 5A, 5B, and 5C illustrate an example of switching a display direction of a second display in an electronic device in an intermediate state according to various embodiments. FIGS. 6A and 6B illustrate another example of switching a display direction of a second display in an electronic device in an intermediate state according to various embodiments.

(111) Referring to FIG. 4, according to various embodiments, in operation 401, an electronic device (e.g., the processor 120 of FIG. 1 or the processor 310 of FIG. 3) may identify a folding angle of the electronic device. According to an embodiment, the processor 310 may identify the folding angle of the electronic device, based on the first sensor 340 disposed in a first housing (e.g., the first housing 210 of FIG. 2A), the second sensor 350 disposed in a second housing (e.g., the second housing 220 of FIG. 2A), and/or a magnetic detection sensor (e.g., a Hall IC). For example, when the first display 320 and/or the second display 330 is in an active state, the processor 310 may detect the folding angle of the electronic device by using the first sensor 340, the second sensor 350, and the magnetic detection sensor. For example, when the first display 320 and the second display 330 are in an inactive state, the processor 310 may detect the folding angle of the electronic device by using a part (e.g., the first acceleration sensor) of the first sensor 340 and a part (e.g., the second acceleration sensor) of the second sensor 350. For example, the folding angle of the electronic device may include an angle between the first housing (e.g., the first housing 210 of FIG. 2A) and the second housing (e.g., the second housing 220 of FIG. 2A).

(112) According to various embodiments, in operation 403, the electronic device (e.g., the processor 120 or 310) may identify whether the folding angle of the electronic device satisfies a designated first range (e.g., from about 20 degrees to about 75 degrees). According to an embodiment, as shown in FIG. 5A, when a folding angle 500 between the first housing 210 and the second housing 220 is included in the designated first range, the processor 310 may determine that the folding angle satisfies the designated first range. According to an embodiment, as shown in FIG. 6A, when a folding angle 600 between the first housing 210 and the second housing 220 is included in the designated first range, the processor 310 may determine that the folding angle



satisfies the designated first range.

(113) According to various embodiments, when the folding angle of the electronic device satisfies the designated first range (e.g., “Yes” in operation **403**), in operation **405**, the electronic device (e.g., the processor **120** or **310**) may select a second display (e.g., the second display **235** of FIG. 2A or the second display **330** of FIG. 3) as a display for displaying a content. According to an embodiment, when the second display **330** is selected as the display for displaying a content, power may be supplied to the second display. In this case, power supply to the first display **320** may be cut off. For example, the content may include a content related to an application program executed by the processor **310** or a content related to a low power display mode (e.g., an always on display AOD).

(114) According to various embodiments, in operation **407**, the electronic device (e.g., the processor **120** or **310**) may configure a display direction of the content, based on a second sensor (e.g., the second inertial sensor **283b** of FIG. 2A or the second sensor **350** of FIG. 3).

(115) According to an embodiment, as shown in FIG. 5A, when the folding angle **500** between the first housing **210** and the second housing **220** is included in the designated first range and the electronic device operates in a second sub-mode, the processor **310** may detect an orientation angle of the electronic device **300**, based on sensor data collected through the second sensor **350** (e.g., the second acceleration sensor). For example, as shown in FIG. 5B, since the vertical axis (e.g., the Z-axis in FIG. 2A) of the second sensor **350** is disposed to face the first display **320**, the processor **310** may detect the orientation angle of the electronic device **300** by inverting (e.g., rotating 180 degrees) the vertical axis (e.g., the Z-axis in FIG. 2A) and the transverse axis (e.g., the X-axis in FIG. 2A) of the second sensor **350** with reference to the longitudinal axis thereof (e.g., the Y-axis in FIG. 2A). For example, the processor **310** may configure a direction (e.g., the transformed direction of the X-axis in FIG. 5B) facing an upper end of a virtual plane obtained by extending the transverse axis (e.g., the X-axis in FIG. 2A) and the longitudinal axis (e.g., the Y-axis in FIG. 2A) forming the orientation angle of the electronic device **300** as the display direction of the content, based on the orientation angle of the electronic device **300**. For example, the processor **310** may configure a first direction (e.g., direction {circle around (1)} in FIG. 5C) oriented from the second housing **220** toward the folding area **230c** (e.g., the hinge module **264** of FIG. 2D) as the display direction of the content, based on the orientation angle of the electronic device **300**. For example, the second sub-mode may include a state in which a lateral surface (e.g., the first lateral member **213** of FIG. 2A) of the first housing **210** and a lateral surface (e.g., the second lateral member **223** of FIG. 2A) of the second housing **220** are placed on (or in contact with) a horizontal plane as shown in FIG. 5A.

(116) According to an embodiment, as shown in FIG. 6A, when the folding angle **600** between the first housing **210** and the second housing **220** is included in the designated first range and the electronic device operates in a first sub-mode, the processor **310** may detect the orientation angle of the electronic device **300**, based on sensor data collected through the second sensor **350**. For example, the processor **310** may detect the orientation angle of the electronic device **300**, based on a change in the longitudinal axis (e.g., the Y-axis in FIG. 2A) and the transverse axis (e.g., the X-axis in FIG. 2A) of the second sensor **350** (e.g., the second acceleration sensor). For example, the processor **310** may configure a second direction (e.g., direction {circle around (2)} in FIG. 6B) oriented from the folding area **230c** (e.g., the hinge module **264** of FIG. 2D) toward the second housing **220** as the display direction of the content, based on the orientation angle of the electronic device **300**. For example, the first sub-mode may include a state in which a second surface (e.g., the second surface **212** of FIG. 2A) of the first housing **210** is placed on (or in contact with) the horizontal plane as shown in FIG. 6A.

(117) According to various embodiments, in operation **409**, the electronic device (e.g., the processor **120** or **310**) may display the content on the second display (e.g., the second display **235** of FIG. 2A or the second display **330** of FIG. 3), based on the display direction of the content.

According to an embodiment, the processor **310** may generate information related to the content to be displayed on the second display **330**, based on the display direction of the content. For example, as shown in FIG. 5C, the processor **310** may draw the information related to the content in the buffer of the second display **330** such that the content starts from a first point **505**, based on the first direction (e.g., direction {circle around (1)} in FIG. 5C) which is the display direction of the content. For example, as shown in FIG. 6B, the processor **310** may draw the information related to the content in the buffer of the second display **330** such that the content starts from a second point **605**, based on the second direction (e.g., direction {circle around (2)} in FIG. 6B) which is the display direction of the content. For example, the information related to the content may be generated based on the size of a display area (e.g., screen) for displaying the content, a start position of the content, and/or a display direction of the content. According to an embodiment, as shown in FIG. 5C, in the case of operating in the second sub-mode, the second display **330** may display a content **510**, based on the first direction (e.g., direction {circle around (1)}) facing the folding area **230c** (e.g., the hinge module **264** of FIG. 2D). For example, the second display **330** may output, to the display panel, the information related to the content drawn in the buffer of the second display **330** by the processor **310** based on the first direction. For example, the second display **330** may output the information related to the content to the display panel from the first point **505**.

(118) According to an embodiment, as shown in FIG. 6B, in the case of operating in the first sub-mode, the second display **330** may display a content **610**, based on the second direction (e.g., direction {circle around (2)} oriented from the folding area **230c** (e.g., the hinge module **264** of FIG. 2D) toward the second housing **220**. For example, the second display **330** may output, to the display panel, the information related to the content drawn in the buffer of the second display **330** by the processor **310** based on the second direction. For example, the second display **330** may output the information related to the content to the display panel from the second point **605**.

(119) According to various embodiments, when the second display **330** is in the active state in a state where the folding angle between the first housing **210** and the second housing **220** is included in the designated first range, the electronic device **300** may display, on the second display **330**, a content (e.g., a game, a video, a website, and/or a still image) related to an application program executed in the electronic device **300**. In this case, power supply to the first display **320** may be cut off.

(120) According to various embodiments, when the second display **330** is in the inactive state and the electronic device **300** is in a state where the folding angle between the first housing **210** and the second housing **220** is included in the designated first range, the electronic device **300** may display, on the second display **330**, a content (e.g., time, weather, date, calendar, and/or notification information) related to a low power display mode (e.g., always on display AOD). In this case, a power supply to the first display **320** may be cut off.

(121) According to various embodiments, when the electronic device **300** changes from the second sub-mode as shown in FIG. 5A to the first sub-mode as shown in FIG. 6A, the electronic device **300** may switch the display direction of the content from a state in which the content **510** is displayed to correspond to the first direction (e.g., direction {circle around (1)}) as shown in FIG. 5C to a state in which the content **610** is displayed to correspond to the second direction (e.g., direction {circle around (2)}) as shown in FIG. 6B. According to an embodiment, when changing from the first sub-mode as shown in FIG. 6A to the second sub-mode as shown in FIG. 5A, the electronic device **300** may switch the display direction of the content from a state in which the content **610** is displayed to correspond to the second direction (e.g., direction {circle around (2)}) as shown in FIG. 6B to a state in which the content **510** is displayed to correspond to the first direction (e.g., direction {circle around (1)}) as shown in FIG. 5C. According to an embodiment, the processor **310** may generate the information related to the content to be displayed on the second display **330**, based on the display direction switch of the content. The processor **310** may draw the

information related to the content in the buffer of the second display **330**. For example, the second display **330** may output the information related to the content drawn in the buffer to the display panel.

(122) FIG. **7** is a flowchart **700** related to detecting a folding angle in an electronic device according to various embodiments. According to an embodiment, the operations of FIG. **7** may be detailed operations of operation **401** of FIG. **4**. In the following embodiments, the operations may be performed sequentially, but are not necessarily performed sequentially. For example, the order of the operations may be changed, and multiple operations such as at least two operations may be performed in parallel. An electronic device of FIG. **7** may be, for example, the electronic device **101** of FIG. **1**, the electronic device **200** of FIG. **2A**, the electronic device **300** of FIG. **3**, or another embodiment of an electronic device.

(123) Referring to FIG. **7**, according to various embodiments, in operation **701**, an electronic device (e.g., the processor **120** of FIG. **1** or the processor **310** of FIG. **3**) may identify whether a first display (e.g., the first display **230** or **320**) and/or a second display (e.g., the second display **235** or **330**) is in an active state. According to an embodiment, the processor **310** may control the first display **320** or the second display **330** to be switched into the active state, based on an active event. For example, the active event may be generated based on an input of a power button, fingerprint image acquisition of a fingerprint sensor, a touch input associated with the active event, and/or movement of the electronic device associated with the active event. For example, the active state of the first display **320** and/or the second display **330** may include a state in which power is applied to a display (e.g., the first display **320** and/or the second display **330**) and all pixels of the display (e.g., the first display **320** and/or the second display **330**) are activated. For example, when the first display **320** and/or the second display **330** is in the active state, the processor **310** (e.g., the application processor) may be activated so as to control the display (e.g., the first display **320** and/or the second display **330**).

(124) According to various embodiments, when the first display (e.g., the first display **230** or **320**) and/or the second display (e.g., the second display **235** or **330**) is in the active state (e.g., “Yes” in operation **701**), in operation **703**, the electronic device (e.g., the processor **120** or **310**) may identify a folding angle of the electronic device by using a sensor (e.g., the first sensor **340** or the second sensor **350**) of the electronic device. According to an embodiment, when the first display **320** and/or the second display **330** is in the active state, the processor **310** (e.g., the application processor and/or the sensor hub processor) may detect the folding angle of the electronic device by using the first sensor **340**, the second sensor **350**, and/or the magnetic detection sensor (e.g., a Hall IC).

(125) According to various embodiments, when the first display (e.g., the first display **230** or **320**) and the second display (e.g., the second display **235** or **330**) are in an inactive state (e.g., “No” in operation **701**), in operation **705**, the electronic device (e.g., the processor **120** or **310**) may identify a folding angle of the electronic device by using a part (e.g., the first acceleration sensor and the second acceleration sensor) of the sensor (e.g., the first sensor **340** and the second sensor **350**) of the electronic device. According to an embodiment, when the first display **320** and the second display **330** are in the inactive state, the processor **310** (e.g., the sensor hub processor) may detect the folding angle of the electronic device by using the first acceleration sensor of the first sensor **340** and the second acceleration sensor of the second sensor **350**. For example, the inactive state of the first display **320** and/or the second display **330** may include a state in which at least one pixel of the display (e.g., the first display **320** and/or the second display **330**) is activated or a state in which all pixels of the display are inactivated. For example, the state in which at least one pixel of the display (e.g., the first display **320** and the second display **330**) is activated may include a state in which power is applied to the display (e.g., the first display **320** and the second display **330**), but only at least one pixel is activated and a scan rate is relatively low. For example, when the first display **320** and the second display **330** are in the inactive state, the application processor of the

processor **310** may be inactivated, and the sensor hub processor may control the first sensor **340** and/or the second sensor **350**.

(126) FIG. **8** is a flowchart **800** related to configuring a display direction of a first display in an electronic device in an intermediate state according to various embodiments. In the following embodiments, operations may be performed sequentially, but are not necessarily performed sequentially. For example, the order of the operations may be changed, and multiple operations such as at least two operations may be performed in parallel. An electronic device of FIG. **8** may be, for example, the electronic device **101** of FIG. **1**, the electronic device **200** of FIG. **2A**, the electronic device **300** of FIG. **3**, or another embodiment of an electronic device. For example, at least some configurations of FIG. **8** will be described with reference to FIGS. **9A**, **9B**, **10A**, **10B**, and **11**. FIGS. **9A** and **9B** illustrate an example of switching a display direction of a first display in an electronic device in an intermediate state according to various embodiments. FIGS. **10A** and **10B** illustrate another example of switching a display direction of a first display in an electronic device in an intermediate state according to various embodiments. FIG. **11** illustrates an example of configuring a display direction of a first display in an electronic device in an intermediate state according to various embodiments.

(127) Referring to FIG. **8**, according to various embodiments, in operation **801**, an electronic device (e.g., the processor **120** of FIG. **1** or the processor **310** of FIG. **3**) may identify a folding angle of the electronic device. According to an embodiment, when the first display **320** and/or the second display **330** is in an active state, the processor **310** may detect the folding angle of the electronic device by using the first sensor **340**, the second sensor **350**, and the magnetic detection sensor. According to an embodiment, when the first display **320** and the second display **330** are in an inactive state, the processor **310** may detect the folding angle of the electronic device by using a part (e.g., the first acceleration sensor) of the first sensor **340** and a part (e.g., the second acceleration sensor) of the second sensor **350**.

(128) According to various embodiments, in operation **803**, the electronic device (e.g., the processor **120** or **310**) may identify whether the folding angle of the electronic device satisfies a designated second range (e.g., from about 75 degrees to about 170 degrees). According to an embodiment, as shown in FIG. **9A**, when a folding angle **900** between the first housing **210** and the second housing **220** is included in the designated second range, the processor **310** may determine that the folding angle satisfies the designated second range. According to an embodiment, as shown in FIG. **10A**, when a folding angle **1000** between the first housing **210** and the second housing **220** is included in the designated second range, the processor **310** may determine that the folding angle satisfies the designated second range. According to an embodiment, as shown in FIG. **11**, when a folding angle **1100** between the first housing **210** and the second housing **220** is included in the designated second range, the processor **310** may determine that the folding angle satisfies the designated second range.

(129) According to various embodiments, when the folding angle of the electronic device satisfies the designated second range (e.g., “Yes” in operation **803**), in operation **805**, the electronic device (e.g., the processor **120** or **310**) may select a first display (e.g., the first display **230** of FIG. **2A** or the first display **320** of FIG. **3**) as a display for displaying a content. According to an embodiment, when the first display **320** is selected as the display for displaying a content, power may be supplied to the first display. In this case, a power supply to the second display **330** may be cut off.

(130) According to various embodiments, in operation **807**, the electronic device (e.g., the processor **120** or **310**) may select a sensor to be used to detect rotation of the electronic device. According to an embodiment, the processor **310** may select a sensor included in a housing which is not placed on (or in contact with) a horizontal plane. For example, as shown in FIG. **9A**, when the folding angle **900** between the first housing **210** and the second housing **220** is included in the designated second range and a second surface (e.g., the second surface **212** of FIG. **2A**) of the first housing **210** is placed on (or in contact with) the horizontal plane, the processor **310** may select the

second sensor **350** as the sensor to be used to detect rotation of the electronic device **300**. For example, when the folding angle of the electronic device is included in a designated third range of the vertical axis (e.g., the Z-axis in FIG. 2A), the transverse axis (e.g., the X-axis in FIG. 2A), and the longitudinal axis (e.g., the Y-axis in FIG. 2A) of the first sensor **340**, the processor **310** may determine that the second surface of the first housing is in a state of being placed on (or in contact with) the horizontal plane. For example, as shown in FIG. 10A, when the folding angle **1000** between the first housing **210** and the second housing **220** is included in the designated second range and a fourth surface (e.g., the fourth surface **222** of FIG. 2A) of the second housing **220** is placed on (or in contact with) the horizontal plane, the processor **310** may select the first sensor **340** as the sensor to be used to detect rotation of the electronic device **300**. For example, when the folding angle of the electronic device is included in a designated third range of the vertical axis (e.g., the Z-axis in FIG. 2A), the transverse axis (e.g., the X-axis in FIG. 2A), and the longitudinal axis (e.g., the Y-axis in FIG. 2A) of the second sensor **350**, the processor **310** may determine that the fourth surface of the second housing is in a state of being placed on (or in contact with) the horizontal plane. For example, as shown in FIG. 11, when the folding angle **1100** between the first housing **210** and the second housing **220** is included in the designated second range and one surface of the first housing **210** and the second housing **220** is not placed on (or in contact with) the horizontal plane, the processor **310** may select the first sensor **340** and the second sensor **350** as the sensor to be used to detect rotation of the electronic device **300**. For example, the designated third range may include a range from about -25 degrees to about 25 degrees about the transverse axis (e.g., the X-axis in FIG. 2A), a range from about -12 degrees to about 12 degrees about the longitudinal axis (e.g., the Y-axis in FIG. 2A), and a range from about 65 degrees to about 90 degrees about the vertical axis (e.g., the Z-axis in FIG. 2A).

(131) According to various embodiments, in operation **809**, the electronic device (e.g., the processor **120** or **310**) may configure a display direction of a content, based on a first sensor (e.g., the first inertial sensor **283a** of FIG. 2A or the first sensor **340** of FIG. 3) and/or a second sensor (e.g., the second inertial sensor **283b** of FIG. 2A or the second sensor **350** of FIG. 3) selected to detect rotation of the electronic device.

(132) According to an embodiment, as shown in FIG. 9A, when the second sensor **350** disposed in the second housing **220** is selected to detect rotation of the electronic device **300**, the processor **310** may detect an orientation angle of the electronic device **300**, based on sensor data collected through the second sensor **350**. For example, the processor **310** may configure a second direction (e.g., direction {circle around (2)} in FIG. 9B) oriented from the folding area **230c** (e.g., the hinge module **264** of FIG. 2D) toward the second housing **220** as the display direction of the content, based on the orientation angle of the electronic device **300**.

(133) According to an embodiment, as shown in FIG. 10A, when the first sensor **340** disposed in the first housing **210** is selected to detect rotation of the electronic device **300**, the processor **310** may detect an orientation angle of the electronic device **300** based on sensor data collected through the first sensor **340**. For example, the processor **310** may configure a third direction (e.g., direction {circle around (3)} in FIG. 10B) oriented from the folding area **230c** (e.g., the hinge module **264** of FIG. 2D) toward the first housing **210** as the display direction of the content, based on the orientation angle of the electronic device **300**.

(134) According to an embodiment, as shown in FIG. 11, when the first sensor **340** and the second sensor **350** are selected to detect rotation of the electronic device **300**, the processor **310** may detect an orientation angle of the electronic device **300**, based on sensor data collected through the first sensor **340** and the second sensor **350**. For example, the processor **310** may generate a virtual plane **1110** by rotating data from the first sensor **340** (e.g., the first acceleration sensor) in a fourth direction (e.g., the - direction or clockwise) with reference to the longitudinal axis (e.g., the Y-axis in FIG. 2A) by a correction angle, and rotating data from the second sensor **350** (e.g., the second acceleration sensor) in a fifth direction (e.g., the + direction or anticlockwise) with reference to the

longitudinal axis (e.g., the Y-axis in FIG. 2A) by the correction angle. The processor **310** may detect the orientation angle of the electronic device **300** with reference to the virtual plane **1110**. For example, the processor **310** may detect the orientation angle of the electronic device **300**, based on a change in the transverse axis (e.g., the X-axis in FIG. 2A) and the longitudinal axis (e.g., the Y-axis in FIG. 2A) with reference to the virtual plane **1110**. For example, the correction angle may include half of the folding angle of the electronic device **300**. For example, the processor **310** may rotate data from the first acceleration sensor and/or the second acceleration sensor by using a rotation matrix. For example, the processor **310** may configure the display direction of the content, based on the orientation angle of the electronic device **300**.

(135) According to various embodiments, in operation **811**, the electronic device (e.g., the processor **120** or **310**) may display the content on the first display (e.g., the first display **230** of FIG. 2A or the first display **320** of FIG. 3), based on the display direction of the content. According to an embodiment, the processor **310** may generate information related to the content to be displayed on the first display **320**, based on the display direction of the content. For example, as shown in FIG. 9B, the processor **310** may draw the information related to the content in the buffer of the first display **320** such that the content starts from a third point **905**, based on the second direction (e.g., direction {circle around (2)} in FIG. 9B) which is the display direction of the content. For example, as shown in FIG. 10B, the processor **310** may draw the information related to the content in the buffer of the first display **320** such that the content starts from a fourth point **1005**, based on the third direction (e.g., direction {circle around (3)} in FIG. 10B) which is the display direction of the content. For example, the information related to the content may be generated based on the size of a display area (e.g., screen) for displaying the content, a start position of the content, and/or a display direction of the content. According to an embodiment, as shown in FIG. 9B, the first display **320** may display a content **910**, based on the second direction (e.g., direction {circle around (2)} oriented from the folding area **230c** (e.g., the hinge module **264** of FIG. 2D) toward the second housing **220**. For example, the first display **320** may output, to the display panel, the information related to the content drawn in the buffer of the first display **320** by the processor **310** based on the second direction {circle around (2)}. For example, the first display **320** may output the information related to the content to the display panel from the third point **905**. For example, the processor **310** may control the first display **320** such that a video content is displayed to be oriented in the second direction (e.g., direction {circle around (2)} in a second area (e.g., the second area **231b** of FIG. 2D) of the first display **320**. For example, the processor **310** may control the first display **320** to display another content (e.g., a control menu related to a video content) in a first area (e.g., the first area **231a** of FIG. 2D) of the first display **320**.

(136) According to an embodiment, as shown in FIG. 10B, the first display **320** may display a content **1010**, based on the third direction (e.g., direction {circle around (3)} oriented from the folding area **230c** (e.g., the hinge module **264** of FIG. 2D) toward the first housing **210**. For example, the first display **320** may output, to the display panel, information related to the content drawn in the buffer of the first display **320** by the processor **310** based on the third direction {circle around (3)}. For example, the first display **320** may output the information related to the content to the display panel from the fourth point **1005**. For example, the processor **310** may control the first display **320** such that a video content is displayed to be oriented in the third direction (e.g., direction {circle around (3)} in the first area (e.g., the first area **231a** of FIG. 2D) of the first display **320**. For example, the processor **310** may control the first display **320** to display another content (e.g., a control menu related to a video content) in the second area (e.g., the second area **231b** of FIG. 2D) of the first display **320**.

(137) According to various embodiments, the electronic device **300** may be changed from a state where the second surface (e.g., the second surface **212** of FIG. 2A) of the first housing **210** is placed on the horizontal plane as shown in FIG. 9A to a state where the fourth surface (e.g., the fourth surface **222** of FIG. 2A) of the second housing **220** is placed on the horizontal plane as

shown in FIG. 10A. In this case, the electronic device 300 may switch the display direction of the video content from a state in which the content is displayed to be oriented in the second direction in the second area (e.g., the second area 231b of FIG. 2D) of the first display 320 as shown in FIG. 9B to a state in which the content is displayed to be oriented in the third direction in the first area (e.g., the first area 231a of FIG. 2D) of the first display 320 as shown in FIG. 10B. According to an embodiment, when the electronic device 300 is switched from a state where the fourth surface (e.g., the fourth surface 222 of FIG. 2A) of the second housing 220 is placed on the horizontal plane as shown in FIG. 10A to a state where the second surface (e.g., the second surface 212 of FIG. 2A) of the first housing 210 is placed on the horizontal plane as shown in FIG. 9A, the electronic device 300 may switch the display direction of the video content from a state in which the content is displayed to be oriented in the third direction {circle around (3)} in the first area (e.g., the first area 231a of FIG. 2D) of the first display 320 as shown in FIG. 10B to a state in which the content is displayed to be oriented in the second direction {circle around (2)} in the second area (e.g., the second area 231b of FIG. 2D) of the first display 320 as shown in FIG. 9B.

(138) FIG. 12 is a flowchart 1200 related to configuring a display direction of a first display in an electronic device in an unfolded state according to various embodiments. In the following embodiments, operations may be performed sequentially, but are not necessarily performed sequentially. For example, the order of the operations may be changed, and multiple operations such as at least two operations may be performed in parallel. An electronic device of FIG. 12 may be, for example, the electronic device 101 of FIG. 1, the electronic device 200 of FIG. 2A, the electronic device 300 of FIG. 3, or another embodiment of an electronic device. At least some configurations of FIG. 12 will be described with reference to FIGS. 13A and 13B. FIGS. 13A and 13B illustrate an example of switching a display direction of a first display in an electronic device in an unfolded state according to various embodiments.

(139) Referring to FIG. 12, according to various embodiments, in operation 1201, an electronic device (e.g., the processor 120 of FIG. 1 or the processor 310 of FIG. 3) may identify an unfolded state of the electronic device. According to an embodiment, when a folding angle between the first housing 210 and the second housing 220 is included in a first reference range (e.g., from about 170 degrees to about 180 degrees), the processor 310 may determine that the electronic device 300 is in the unfolded state. For example, as in operations 701 to 703 of FIG. 7, when the first display 320 and/or the second display 330 is in an active state, the processor 310 (e.g., the application processor and/or the sensor hub processor) may detect a folding angle of the electronic device by using the first sensor 340, the second sensor 350, and/or the magnetic detection sensor (e.g., a Hall IC). For example, as in operations 701 and 705 of FIG. 7, when the first display 320 and the second display 330 are in an inactive state, the processor 310 (e.g., the sensor hub processor) may detect the folding angle of the electronic device by using the first acceleration sensor of the first sensor 340 and the second acceleration sensor of the second sensor 350.

(140) According to various embodiments, in operation 1203, the electronic device (e.g., the processor 120 or 310) may select a first display (e.g., the first display 230 of FIG. 2A or the first display 320 of FIG. 3) as a display for displaying a content, based on the unfolded state of the electronic device.

(141) According to various embodiments, in operation 1205, the electronic device (e.g., the processor 120 or 310) may configure a display direction of a content by using on a first sensor (e.g., the first inertial sensor 283a of FIG. 2A or the first sensor 340 of FIG. 3) or a second sensor (e.g., the second inertial sensor 283b of FIG. 2A or the second sensor 350 of FIG. 3). According to an embodiment, all axis directions of the first sensor 340 and the second sensor 350 may be the same when the electronic device 300 is in the unfolded state. Accordingly, when the electronic device 300 is in the unfolded state, the processor 310 may detect an orientation angle of the electronic device 300, based on sensor data collected through the first sensor 340 (e.g., the first acceleration sensor) or the second sensor 350 (e.g., the second acceleration sensor). For example,

the processor **310** may configure the display direction of the content, based on the orientation angle of the electronic device **300**. For example, the sensor data may include data related to a change in the longitudinal axis (e.g., the Y-axis in FIG. 2A) and the transverse axis (e.g., the X-axis in FIG. 2A) of the first acceleration sensor or the second acceleration sensor.

(142) According to various embodiments, in operation **1207**, the electronic device (e.g., the processor **120** or **310**) may display the content on the first display (e.g., the first display **230** of FIG. 2A or the first display **320** of FIG. 3), based on the display direction of the content. According to an embodiment, as shown in FIG. 13A, when the orientation angle of the electronic device **300** is landscape, the processor **310** may control the first display **320** to display a content **1300**, based on the display direction of the content. According to an embodiment, as shown in FIG. 13B, when the orientation angle of the electronic device **300** is portrait, the processor **310** may control the first display **320** to display a content **1310**, based on the display direction of the content.

(143) According to various embodiments, in the case of changing from the landscape direction as shown in FIG. 13A to the portrait direction as shown in FIG. 13B, the electronic device may switch the display direction of the content from a state in which the content **1300** is displayed to correspond to the landscape direction as shown in FIG. 13A to a state in which the content **1310** is displayed to correspond to the portrait direction as shown in FIG. 13B.

(144) FIG. 14 is a flowchart **1400** related to configuring a display direction of a second display in an electronic device in a folded state according to various embodiments. In the following embodiments, operations may be performed sequentially, but are not necessarily performed sequentially. For example, the order of the operations may be changed, and multiple operations such as at least two operations may be performed in parallel. For example, an electronic device of FIG. 14 may be the electronic device **101** of FIG. 1, the electronic device **200** of FIG. 2A, the electronic device **300** of FIG. 3, or another embodiment of an electronic device. For example, at least some configurations of FIG. 14 will be described with reference to FIGS. 15A and 15B. FIGS. 15A and 15B illustrate an example of switching a display direction of a second display in an electronic device in a folded state according to various embodiments.

(145) Referring to FIG. 14, according to various embodiments, in operation **1401**, an electronic device (e.g., the processor **120** of FIG. 1 or the processor **310** of FIG. 3) may identify a folded state of the electronic device. According to an embodiment, when a folding angle between the first housing **210** and the second housing **220** is included in a second reference range (e.g., from about 0 degrees to about 20 degrees), the processor **310** may determine that the electronic device **300** is in the folded state. For example, as in operations **701** to **703** of FIG. 7, when the first display **320** and/or the second display **330** is in an active state, the processor **310** (e.g., the application processor and/or the sensor hub processor) may detect a folding angle of the electronic device by using the first sensor **340**, the second sensor **350**, and the magnetic detection sensor (e.g., a Hall IC). For example, as in operations **701** and **705** of FIG. 7, when the first display **320** and the second display **330** are in an inactive state, the processor **310** (e.g., the sensor hub processor) may detect the folding angle of the electronic device by using the first acceleration sensor of the first sensor **340** and the second acceleration sensor of the second sensor **350**.

(146) According to various embodiments, in operation **1403**, the electronic device (e.g., the processor **120** or **310**) may select a second display (e.g., the second display **235** of FIG. 2A or the second display **330** of FIG. 3) as a display for displaying a content, based on the folded state of the electronic device.

(147) According to various embodiments, in operation **1405**, the electronic device (e.g., the processor **120** or **310**) may configure a display direction of a content by using a first sensor (e.g., the first inertial sensor **283a** of FIG. 2A or the first sensor **340** of FIG. 3). According to an embodiment, since the second display **330** selected to display a content while the electronic device **300** is in the folded state corresponds to the direction (e.g., the Z-axis) of the vertical axis of the first sensor **340**, the processor **310** may select the first sensor **340** as a sensor to be used to detect



rotation of the electronic device **300**. According to an embodiment, the processor **310** may detect an orientation angle of the electronic device **300**, based on sensor data collected through the first sensor **340** (e.g., the first acceleration sensor). For example, the processor **310** may configure the display direction of the content, based on the orientation angle of the electronic device **300**. For example, the sensor data may include data related to a change in the longitudinal axis (e.g., the Y-axis in FIG. 2A) and the transverse axis (e.g., the X-axis in FIG. 2A) of the first acceleration sensor.

(148) According to various embodiments, in operation **1407**, the electronic device (e.g., the processor **120** or **310**) may display the content on the second display (e.g., the second display **235** of FIG. 2A or the second display **330** of FIG. 3), based on the display direction of the content. According to an embodiment, as shown in FIG. 15A, when the orientation angle of the electronic device **300** is landscape, the processor **310** may control the second display **330** (e.g., the second display **235** of FIG. 2A) to display a content **1500**, based on the display direction of the content. According to an embodiment, as shown in FIG. 15B, when the orientation angle of the electronic device **300** is portrait, the processor **310** may control the second display **330** to display a content **1510**, based on the display direction of the content.

(149) According to an embodiment, when changing from the portrait direction as shown in FIG. 15B to the landscape direction as shown in FIG. 15A, the electronic device **300** may switch the display direction of the content from a state in which the content **1510** is displayed to correspond to the portrait direction as shown in FIG. 15B to a state in which the content **1500** is displayed to correspond to the landscape direction as shown in FIG. 15A.

(150) According to various embodiments of the disclosure, an operation method of an electronic device (e.g., the electronic device **101** of FIG. 1, the electronic device **200** of FIG. 2A, or the electronic device **300** of FIG. 3) may include identifying, by a first sensor (e.g., the sensor module **176** of FIG. 1, the first inertial sensor **283a** of FIG. 2A, or the first sensor **340** of FIG. 3) and a second sensor (e.g., the sensor module **176** of FIG. 1, the second inertial sensor **283b** of FIG. 2A, or the second sensor **350** of FIG. 3), a folding angle between a first housing (e.g., the first housing **210** of FIG. 2A) and a second housing (e.g., the second housing **220** of FIG. 2A), the first sensor being disposed in a first space of the first housing which is connected to a hinge module (e.g., the hinge module **264** of FIG. 2D) and includes a first surface (e.g., the first surface **211** of FIG. 2A), a second surface (e.g., the second surface **212** of FIG. 2A) facing a direction opposite to the first surface, and a first lateral surface (e.g., the first lateral member **213** of FIG. 2A) surrounding the first space between the first surface and the second surface, the second sensor being disposed in a second space of the second housing which is connected to the hinge module so as to be foldable with respect to the first housing and, in an unfolded state, includes a third surface (e.g., the third surface **221** of FIG. 2A) facing the same direction as the first surface, a fourth surface (e.g., the fourth surface **222** of FIG. 2A) facing a direction opposite to the third surface, and a second lateral surface (e.g., the second lateral surface **223** of FIG. 2A) surrounding the second space between the third surface and the fourth surface, when the folding angle between the first housing and the second housing satisfies a designated first range, from among a first display (e.g., the display module **160** of FIG. 1, the first display **230** of FIG. 2A, or the first display **320** of FIG. 3) disposed from at least a part of the first surface to at least a part of the third surface, and a second display (e.g., the display module **160** of FIG. 1, the second display **235** of FIG. 2A, or the second display **330** of FIG. 3) disposed in the second space so as to be visible from the outside through at least a part of the fourth surface, selecting the second display, determining a display direction of a content, based on sensor data collected through the second sensor, and displaying the content on the second display, based on the display direction of the content.

(151) According to various embodiments, the identifying of the folding angle may include identifying the folding angle between the first housing and the second housing by using the first sensor, the second sensor, and a magnetic detection sensor when the first display and/or the second

display is in an active state, or identifying the folding angle between the first housing and the second housing through a part of the first sensor and a part of the second sensor when the first display and the second display are in an inactive state.

(152) According to various embodiments, the first sensor and/or the second sensor may include an acceleration sensor and a gyro sensor, and the part of the first sensor and/or the second sensor may include the acceleration sensor.

(153) According to various embodiments, the method may further include selecting the second display when the first housing and the second housing are determined as being in a folded state, based on the folding angle between the first housing and the second housing, determining the display direction of the content, based on sensor data collected through the first sensor, and displaying the content on the second display, based on the display direction of the content.

(154) According to various embodiments, the method may further include selecting the first display when the first housing and the second housing are determined as being in the unfolded state, based on the folding angle between the first housing and the second housing, determining the display direction of the content, based on sensor data collected through the first sensor and/or the second sensor, and displaying the content on the first display, based on the display direction of the content.

(155) According to various embodiments, the determining of the display direction may include, when the first display is in an active state in a state where the first housing and the second housing are in the unfolded state, determining the display direction of the content, based on the sensor data collected through the first sensor and the second sensor, or when the first display is in an inactive state in a state where the first housing and the second housing are in the unfolded state, determining the display direction of the content, based on the sensor data collected through the first sensor or the second sensor.

(156) According to various embodiments, the method may include selecting the first display when the folding angle between the first housing and the second housing satisfies a designated second range different from the designated first range, determining the display direction of the content, based on sensor data collected through the first sensor and/or the second sensor, and displaying the content on the first display, based on the display direction of the content.

(157) According to various embodiments, the determining of the display direction of the content may include, when the sensor data collected through the first sensor satisfies a designated first condition, determining the display direction of the content, based on the sensor data collected through the second sensor, or when the sensor data collected through the second sensor satisfies the designated first condition, determining the display direction of the content, based on the sensor data collected through the first sensor.

(158) According to various embodiments, the determining of the display direction of the content may include, when the sensor data collected through the first sensor and the second sensor does not satisfy the designated first condition, determining the display direction of the content, based on the sensor data collected through the first sensor and the second sensor.

(159) According to various embodiments, the displaying of the content on the second display may include displaying a content related to an application program when the second display is in an active state, or displaying a content related to a low power display mode when the second display is in an inactive state.

(160) While embodiments have been particularly shown and described above, it will be understood that various changes in form and details may be made therein without departing from the spirit and scope of the following claims.

## Claims

1. A portable communication device comprising: a first housing comprising a first surface and a second surface opposite to each other; a second housing comprising a third surface and a fourth

surface opposite to each other; a hinge structure foldably connected to the first housing and the second housing such that the first surface and the third surface face a same direction when the portable communication device is unfolded; a flexible display accommodated in the first housing and the second housing, and capable of bending when the portable communication device is at least partially folded; one or more sensors configured to obtain sensor data corresponding to a movement of at least one of the first housing or the second housing; a processor operatively coupled with the flexible display and the one or more sensors, and memory storing instructions which, when executed by the processor, cause the portable communication device to: while the portable communication device is in an unfolded state, display, via the flexible display, content in a first display direction; and based on the portable communication device being partially folded from the unfolded state: identify, based at least in part on the sensor data, an angle between the first housing and the second housing while the content is displayed; display, via the flexible display, the content in a second display direction different from the first display direction based on the portable communication device being in a first configuration in which the angle is within a first range and the first housing is in a plane that is substantially perpendicular to a direction of gravity; and display, via the flexible display, the content in a third display direction different from each of the first display direction and the second display direction based on the portable communication device being rotated to a second configuration from the first configuration in which the angle remains in the first range and the second housing is in the plane that is substantially perpendicular to the direction of gravity.

2. The portable communication device of claim 1, wherein the flexible display comprises a first portion corresponding to the first surface of the first housing and a second portion corresponding to the third surface of the second housing, and wherein the instructions which, when executed by the processor, cause the portable communication device to: perform the displaying of the content in the second display direction such that at least portion of the content is displayed via the second portion of the flexible display.

3. The portable communication device of claim 2, wherein the memory stores instructions which, when executed by the processor, cause the portable communication device to: display, via the first portion of the flexible display, a control interface corresponding to the content.

4. The portable communication device of claim 1, wherein the flexible display comprises a first portion corresponding to the first surface of the first housing and a second portion corresponding to the third surface of the second housing, and wherein the instructions which, when executed by the processor, cause the portable communication device to: perform the displaying of the content in the third display direction such that at least portion of the content is displayed via the first portion of the flexible display.

5. The portable communication device of claim 4, wherein the memory stores instructions which, when executed by the processor, cause the portable communication device to: display, via the second portion of the flexible display, a control interface corresponding to the content.

6. The portable communication device of claim 1, wherein the flexible display comprises a first edge and a second edge each substantially parallel with a length direction of the hinge structure, and accommodated in the first housing and the second housing, respectively, and wherein the instructions which, when executed by the processor, cause the portable communication device to: perform the displaying of the content in the second display direction such that a upper side of the content is aligned with the second edge of the flexible display.

7. The portable communication device of claim 1, wherein the flexible display comprises a first edge and a second edge each substantially parallel with a length direction of the hinge structure, and accommodated in the first housing and the second housing, respectively, and wherein the instructions which, when executed by the processor, cause the portable communication device to: perform the displaying of the content in the third display direction such that the upper side of the content is aligned with the first edge of the flexible display.

8. The portable communication device of claim 1, wherein the one or more sensors comprises a first sensor disposed in the first housing and a second sensor disposed in the second housing, and wherein the memory stores instructions which, when executed by the processor, cause the portable communication device to: determine the second display direction using the second sensor; and determine the third display direction using the first sensor.
9. The portable communication device of claim 1, wherein the one or more sensors comprises at least one of an acceleration sensor or a gyro sensor.
10. An operation method of a portable communication device comprising a first housing, a second housing, and a hinge structure foldably connecting the first housing and the second housing, the operation method comprising: while the portable communication device is in an unfolded state, displaying, via a flexible display of the portable communication device, content in a first display direction; and based on the portable communication device being partially folded from the unfolded state: identifying an angle between the first housing and the second housing while the content is displayed; displaying, via the flexible display, the content in a second display direction different from the first display direction based on the portable communication device being in a first configuration in which the angle is within a first range and the first housing is in a plane that is substantial perpendicular to a direction of gravity; and displaying, via the flexible display, the content in a third display direction different from each of the first display direction and the second display direction based on the portable communication device being rotated to a second configuration from the first configuration in which the angle remains in the first range and the second housing is in the plane that is substantially perpendicular to the direction of gravity.
11. The operation method of claim 10, wherein the flexible display comprises a first portion corresponding to a first surface of the first housing and a second portion corresponding to a third surface of the second housing, and wherein the displaying of the content in the second display direction comprises displaying, via the second portion of the flexible display, at least portion of the content.
12. The operation method of claim 11, further comprising; displaying, via the first portion of the flexible display, a control interface corresponding to the content.
13. The operation method of claim 10, wherein the flexible display comprises a first portion corresponding to a first surface of the first housing and a second portion corresponding to a third surface of the second housing, and wherein the displaying of the content in the third display direction comprises displaying, via the first portion of the flexible display, at least portion of the content.
14. The operation method of claim 13, further comprising; displaying, via the second portion of the flexible display, a control interface corresponding to the content.
15. The operation method of claim 10, wherein the flexible display comprises a first edge and a second edge each substantially parallel with a length direction of the hinge structure, and accommodated in the first housing and the second housing, respectively, and wherein the displaying of the content in the second display direction comprises displaying the content in the second display direction such that a upper side of the content is aligned with the second edge of the flexible display.
16. The operation method of claim 10 wherein the flexible display comprises a first edge and a second edge each substantially parallel with a length direction of the hinge structure, and accommodated in the first housing and the second housing, respectively, and wherein the displaying of the content in the third display direction comprises displaying the content in the third display direction such that the upper side of the content is aligned with the first edge of the flexible display.
17. The operation method of claim 10, further comprising; determining the second display direction using a second sensor among a first sensor disposed in the first housing and the second sensor disposed in the second housing.

18. The operation method of claim 10, further comprising; determining the third display direction using a first sensor among the first sensor disposed in the first housing and a second sensor disposed in the second housing.

19. The portable communication device of claim 1, wherein the one or more sensors comprise a first sensor disposed in the first housing and a second sensor disposed in the second housing, and wherein the memory stores instructions which, when executed by the processor, further cause the portable communication device to: determine whether the first housing is in the plane substantially perpendicular to the direction of gravity using the first sensor, and determine whether the second housing is in the plane substantially perpendicular to the direction of gravity using the second sensor.

20. The operation method of claim 10, further comprising; determining whether the first housing is in the plane substantially perpendicular to the direction of gravity using a first sensor among the first sensor disposed in the first housing and a second sensor disposed in the second housing, and determining whether the second housing is in the plane substantially perpendicular to the direction of gravity using the second sensor.

---