








FIG 1.

**FIG 2.**



**FIG 4.**

**FIG 5.**







FIG. 6.

**FIG 7.**

**FIG 8.**

**FIG 9.**

1002

Enter Geological Entities: Green Formation

Rank	Name	Country	Similarity	Reliability (Entropy Based)				Feedback
				Mention	Docs	Author	Reliability SCORE	
1	Blue Fm	Egypt	82.3%	34	3	3	306	
2	Orange Fm	Bolivia	76.5%	12	1	1	12	X
3	Black Mbr	UK	75%	10	5	2	100	
4	Grey Gp	USA	71.04 %	6	2	2	24	
5	Purple Fm	Yemen	69.87 %	123	27	13	43,173	
More								

1004 1006 1008 1010 1012 1014 1016 1018 1020

FIG 10.

1102

Enter Geological Entities: injectites , basin floor

Rank	Name	Country	Similarity	Reliability (Entropy Based)				Feedback
				Mention	Docs	Author	Reliability SCORE	
1	<u>Red Fm</u>	<u>Egypt</u>	<u>82.3%</u>	34	3	3	306	
2	<u>Amber Fm</u>	<u>Bolivia</u>	<u>76.5%</u>	12	1	1	12	X
3	<u>Ruby Fm</u>	<u>UK</u>	<u>75%</u>	10	5	2	100	
4	<u>Topaz Fm</u>	<u>USA</u>	<u>71.04%</u>	6	2	2	24	
5	<u>Pearl Fm</u>	<u>Yemen</u>	<u>69.87%</u>	123	27	13	43,173	
<u>More</u>								

FIG 11.

THE NAMES OF THE PARTIES TO A JOINT
RESEARCH AGREEMENT

Not applicable

INCORPORATION-BY-REFERENCE OF
MATERIAL SUBMITTED ON A COMPACT
DISC OR AS A TEXT FILE VIA THE OFFICE
ELECTRONIC FILING SYSTEM (EFS-WEB)

Not applicable

STATEMENT REGARDING PRIOR
DISCLOSURES BY THE INVENTOR OR A
JOINT INVENTOR

The method of applying space-time aware Lithostratigraphic analogue suggestion from geoscience text using theory-guided machine learning has not been disclosed (outside this United States patent application). A conference presentation in May 2016 at the Digital Energy Conference in Aberdeen, UK (Cleverley 2016) did introduce the notion of using unsupervised machine learning through word co-occurrence to Lithostratigraphic entity names for analogue suggestion. The method of suppressing associated local geographical and successional lithostratigraphy as dimensions for analogue computation along with an entropy reliability score and active (reinforcement) learning mechanism has not been disclosed anywhere outside this United States patent application.

BACKGROUND OF THE INVENTION

(1) Field of the Invention

The present invention relates generally to geoscience, more specifically to the field of entity similarity at the intersection of information retrieval, natural language processing and artificial intelligence.

(2) Description of Related Art

It has been reported that over 60% of petroleum geoscientists believe that the identification of global analogues reduces exploration risk and improves field development decisions (Sun and Wan 2002). Analogues are important to geoscientists in numerous industry sectors such as petroleum, economic mining, geo-health, construction and space exploration (Baker 2014). Nearly all oil and gas companies use geoscience analogues extensively, particularly in data sparse new ventures areas and for peer review processes. Analogues uncover subtle opportunities that may not be apparent from any other technique or technology. The ability to make global comparisons ‘casting a wider net than just what is close by’ was identified as being particularly useful.

Traditional Information Retrieval (IR) systems are not well suited to answer questions such as ‘*Have we handled such a case before?*’ (Mukherjee et al 2013) or show geoscientists analogues given a specific geological context (Cleverley and Burnett 2015).

Manually created geoscience analogue databases exist and are useful, but as they are manually curated, also potentially blind geoscientists to new discoveries. There is also evidence of significant cognitive bias (Rose 2016), with tendencies for petroleum geoscientists to show overconfidence that uncertainties are known.

In the current data driven environment of ‘big data’—exponentially growing information volumes in published literature and reports—it is not possible for scientists to read all that is relevant due to human cognitive processing limitations. Dark data, hidden latent patterns in text may exist in literature (Zheng et al 2015). Whilst most subject matter experts may know the ‘big patterns’ in their specialties, it is the ‘small patterns’ within and across the boundaries of these areas that may present the most unexpected, insightful and valuable information.

Text and data mining (TDM) is the use of automated analytical techniques to analyse text and data for patterns, trends and other useful information. These techniques can be used to summarize, synthesize and compare (Manning et al. 2008), supporting higher level thinking processes rather than simply retrieving (remembering) information (Bloom et al. 1956).

Detecting geographical terms in text through geoparsers has been conducted extensively for documents, entities, topics and sentiment (Hu 2018). The geosciences have several unique challenges requiring novel methodologies in machine learning. Geoscience information has high dimensionality, geoscience bodies are not as clear cut as objects in other domains, rare events are of interest and geoscience processes can show long-memory characteristics in time (Karpatne et al 2017). Significant potential exists using data driven approaches that can scan through vast amounts of text to discover interesting patterns representing geoscience relationships.

The method of using unsupervised machine learning based on the co-occurrence patterns of words in high dimensional space (word embeddings) has been used in the biomedical field. This included the classification of cancer, as cancer profiles can be characterized by a series of co-occurring mutations (Kim et al 2018). Dai and Prout (2016) weighted the input terms of such techniques using Part of Speech (POS) tagging, finding that when verbs were weighted higher, accuracy for sentiment analysis was improved.

Entity similarity techniques have been studied extensively (Tan 2010; Roettger and Ziegler 2012; Yu 2012; Gomaa and Fahmy 2013; Mikolov et al 2013; Pennington et al 2014; Aparicio 2015; Malik et al 2016) but not their use for discovering geoscience analogues in text. Machine learning techniques (Chan 2016; Kumar et al 2013) have been applied to geoscientific texts however, methods focus on using these techniques to disambiguate entities. In addition, Nooralahzadeh et al (2006) applied word embeddings to oil and gas literature with a narrow focus largely on identification of synonyms.

Methods applying text analytics in the geosciences often use deductive extraction using linguistics (dictionaries and taxonomies) and rules (Zhu et al 2017) from text to detect associations to other extractions with results stored in a Knowledge Graph. Whilst this can target specific concepts (e.g. Geological Time, Paleontological Species) a drawback is that any concept which is not modelled a priori, is discarded in any computation. Greenberg (2011) contends that knowledge representations (such as taxonomies) enhance information systems, whilst also blinding us to new knowledge discoveries if used as the only lens when automatically parsing unstructured text.

This argument is taken up specifically in the geosciences (Karpatne et al 2017), suggesting a hybrid model; learning patterns and models from data but without ignoring the wealth of knowledge gathered from geoscientists. This is effectively a critical realist philosophy towards data science.

Anchoring machine learning frameworks with knowledge of what geoscientists deem most useful and interesting for analogues, learned models may have a better chance against overfitting. Methods which are inherently transparent are also deemed to be preferable for geoscientists (Karpatne et al 2017).

Cleverley (2016) was the first to apply numerical representations of words in high-dimensional space, to surface Lithostratigraphic analogues in geoscience text. In this method the system uses the latent structure in text through word co-occurrence patterns to 'learn' similarity in an unsupervised way from named Lithostratigraphic entities. A drawback of using a fixed text 'window' for detecting associations to entities is the large number of false negatives (associated concepts) that are likely to be missed. This may lead to inaccurate similarity computation. In addition, no account was made for hierarchical relations between the entities, where each entity (such as a Formation, Member, Bed) were treated as a flat list. This would also likely lead to inaccurate similarity computation as word co-occurrences to the 'child' Lithostratigraphic entity would not be included when comparing the similarity with the 'parent' Lithostratigraphic entity.

In detail, for this method a static window was applied (10 words) around each Lithostratigraphic entity detected, in order to create an aggregated word co-occurrence based text vector. This encompasses the surrounding words from all mentions of said entity, from which cosine similarity is computed to estimate how similar one entity vector is to another.

From unpublished information science research with geoscientists (Cleverley 2017) the method outlined (Cleverley 2016) appears capable of surfacing unexpected, insightful and valuable suggestions. However, the unpublished research showed that when suggested analogues were scored similar because they were associated with similar local geographical terms or other Lithostratigraphical entities, they were not deemed as interesting or useful. For example, the 'Grey Formation' may often be mentioned near the 'Black Formation' in text, related to local succession (it was deposited before or after), which is not so interesting or useful for analogue purposes as it is unlikely it will tell the geoscientist something they don't already know.

There are precedents for patents awarded to petroleum data processing methods (Piovesan and Kozman 2009).

BRIEF SUMMARY OF THE INVENTION

The present invention is a theory-guided data science method and system for computing geological Lithostratigraphic analogues from the latent patterns in unstructured text.

Five underlying theories inform the invention design specifically for geoscience:

Theory	Description
1 Geological Actualism	Processes in the past are the same as the present. Therefore a meaning of a word is the same regardless of its age context.
2 Geological Succession (Time)	Lithostratigraphic entities occurring locally with the Lithostratigraphic entity (in time), are not useful to be included in the word associations for similarity scores for analogues.

-continued

Theory	Description
3 Geological Succession (Geography)	Geographical names occurring with the Lithostratigraphic entity (in geography), are not useful to be included in the word associations for similarity scores for analogues.
4 Lithostratigraphic entities in text General-to-Specific	Where Lithostratigraphic entities follow each other in text, using a class hierarchy (Super-group > Group > Formation > Member > Bed); if a more specific class is preceded by (subsumed by) a more general class, the word associations for the specific class are also associated to the more general class.
5 Focus on nouns, adjectives and verbs in geoscience text	Due to the nature of Lithostratigraphic analogues and geological concepts, priority (weighting) is given to nouns first, then adjectives, then verbs in the word associations to detected Lithostratigraphic entities for vector similarity computation.

Theory #1 is based on the principle of geological actualism; past geological action is like all present geological action. So for text mining similarity purposes, the mention in text of the diagenetic process karstification in context to a geological time period 350 Million years ago is the same as a mention of karstification in context to a geological time period 20 Million years ago. This cannot be said for all human actions, for example farming in context to the 19th century is a quite different process to a mention of farming in context to the 21st century.

Theory #2 is a computation that takes into consideration geological succession (Lithostratigraphic units deposited above or below) which are deemed (as stated earlier from unpublished research) not interesting or useful for global analogue suggestion.

For example, consider the text ".the organic rich Blue Formation is of Jurassic age, overlies the Green Formation . . .". In traditional published unsupervised text machine learning techniques, the 'Green Formation' will have a disproportionately high similarity to the 'Blue Formation' because these actual entity names co-occur in close proximity to one another in the same text window. This is a form of similarity which has been shown to be not so useful when looking for global Lithostratigraphic analogues.

Theory #3 is a computation that takes into consideration local geographical elements (Lithostratigraphic units in the same proximal location) which are generally not seen as interesting or useful for global analogue suggestion.

For example, consider the two sentences in different documents, "... west of Spring Mountain is an exposure of the Yellow Formation" and "The Brown Unit can be seen at the base of the Spring Mountain . . .". In traditional unsupervised text machine learning techniques, the 'Yellow Formation' will have a disproportionately high similarity to the 'Brown Unit' because the same geographical entity (in this case Spring Mountain) co-occurs in proximity to both entity names. Similarity is biased by local geography which has been shown to be not so useful or interesting when suggesting global Lithostratigraphic analogues.

Theory #4 contends that geoscience literature tends to follow from the general to the specific. So a more specific Lithostratigraphic entity (by class) discussed in text occurring after a more general Lithostratigraphic entity (by class) is likely to be a sub-division subsumed (a child entity) to the more general 'parent' entity.

For example, taking a hierarchy rule that in terms of Lithostratigraphic units (classes) Formations contain Members, for the following text, "the Grey Formation the Silver Member" it can be inferred that the Silver Member is 'parent

of the Grey Formation and therefore it follows that all of the surrounding text for the Silver Member is also valid by inference for the Grey Formation as part of an amalgamated vector.

Theory #5 is based on geoscience being the study of earth features, history and the processes that act upon the earth. The theory contends that for properties and provenance of a rock, one would expect nouns to be more important (e.g. colour, texture, porosity, age) for analogue suggestion. Therefore, nouns, adjectives and verbs (weighted in decreasing order of importance) are deemed the most important word associations to Lithostratigraphic entities to exploit for geoscience analogues.

The present invention computes a similarity score from resulting vectors of Lithostratigraphic entity names. A reliability (entropy based) score is computed which incorporates the total number of mentions found of the Lithostratigraphic entity (in a given corpus) along with the diversity of documents and authors from which those mentions are distributed. The resulting display of potential global analogues ranked by similarity scores includes a feedback loop allowing the geoscientist to indicate if a suggested analogue is 'good' or 'bad' which can be used to modify weighting of the similarity score, thereby incorporating user feedback in an active learning component.

It would therefore be desirable to have a data processing system and method to suggest global Lithostratigraphic analogues from unstructured text which are not unduly influenced by local time (succession) and space (geography). It would therefore be desirable to have a method and system to compute a similarity score using the processed text vectors of Lithostratigraphic entities which is deemed to give a greater propensity for suggesting useful and interesting global analogues from unstructured text.

This would be useful because there is too much potentially relevant information available for geoscientists to read and it is difficult to search on analogues because they are not always known. Geoscientists may be limited by their own knowledge of keywords for search terms from discovering what is new to science using traditional IR systems.

Accordingly, in one aspect, a computer process as implemented, involves receiving sentences from a plurality of sentences, rules and topic lexicons from a plurality of lexicons in a computer memory. These data in the computer memory are processed with a computer processor to process the text to remove key areas of potential bias and identify entities (Lithostratigraphic entity names). A similarity classification for each entity is computed. A preferred embodiment is a Natural Language Processing (NLP), dictionary (lexicon) and an unsupervised machine learning method. This is achieved by applying a filter to the text removing geographical entities and containing an NLP rule to identify Lithostratigraphic entities; associating the text nearby to said entity until a different entity of the same type is encountered. Subsumed entities are amalgamated. A similarity score is computed by comparing vectors computed from the aggregated text associated with each Lithostratigraphic entity. A reliability score is computed for the entity similarity, based on the entropy of mentions and diversity of documents and authors from which they are derived. The greater the diversity of mentions, documents and authors, the more reliable the similarity measure.

In another aspect, a computer program utilizes computer disk (storage) in which instruction code resides. These instructions when processed by a computer, instruct the computer to compute the similarity of Lithostratigraphic entities, a reliability score and automatic updates to the

similarity model based on user feedback. The techniques could be implemented in digital circuitry, hardware, firmware or software. The techniques can be implemented in a computer program written in any form of programming language and on any operating system. Additional embodiments could include one or more computer devices configured to carry out the instructions.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

The figures attached form part of the specification, further explain the invention and supported by the detailed description, serve to explain the principles of the present invention.

FIG. 1—Example applied to a paragraphs of text.

FIG. 2—Diagram illustrating the system architecture.

FIG. 3—Schematic illustrating the software system, modules, operating system and user interface.

FIG. 4—High level flowchart of operations summarizing the detection of Lithostratigraphic entities in text and computation of similarity, in accordance with a preferred embodiment.

FIG. 5—Flow chart for preparing text (geoparsing and removing geographical entity names).

FIG. 6—Flow chart for detecting Lithostratigraphic entities and associating surrounding text.

FIG. 7—Flow chart for computing entity similarity and reliability scores.

FIG. 8—Flow chart for ranking Lithostratigraphic Units by similarity for a given input.

FIG. 9—Flow chart for receiving user feedback and updating similarity model.

FIG. 10—Schematic showing display for similarity for Lithostratigraphic entities with reliability score and user feedback mechanism.

FIG. 11—Schematic showing display for similarity for Lithostratigraphic entities to a combination of search terms rather than a query for a Lithostratigraphic entity.

DETAILED DESCRIPTION OF THE INVENTION

The various values and configuration discussed in the following sections can be varied and are listed just to illustrate one embodiment. The invention may be embodied in several different forms and should not be taken as limited to the embodiments disclosed. The disclosed embodiments address theory-guided global analogue suggestion for Lithostratigraphic entity names through machine learning from unstructured text. The disclosed embodiments are provided by way of illustration to ensure thorough disclosure and the nature of the inventions to people skilled in the art.

In this document the following definitions are used. Theory-driven data science is the integration of scientific knowledge in learnt machine models. A Lithostratigraphic unit is a geological layer which has a distinct lithology classification and has an areal extent which can be mapped spatially. An information container is any collection of data in computer readable form such as natural language text. This may include a collection of information, an individual document, paragraph, snippet or sentence of information. A named entity is a named noun or noun phrase explicitly mentioned in information containers that uniquely identifies something that exists, such as a geographical place name or geological Lithostratigraphic names.

An example set of sentences and paragraphs within an information container being processed by the method is

of Lithostratigraphic entity (except for the lowest leaf of 'Bed') there are two potential vectors; one which only refers to the explicit word associations to the mention of that Lithostratigraphic entity name and one that also includes implicit word associations brought in from its inferred subsumed (child) Lithostratigraphic entity classes. If there are more sentences **616** the process is repeated. If no further entities are detected in the document and the last sentence has been processed, the co-occurrence window for the last detected entity is truncated **618** at the end of the paragraph in which it was detected. The process is repeated and a new document processed one sentence at a time, until all documents in the corpus have been processed.

FIG. 7 shows the workflow for reliability and similarity score computation. When all sentences in the corpus have been processed, the co-occurrence window text for each unique Lithostratigraphic entity name is aggregated **702** forming a new information container (document) for that Lithostratigraphic entity **704**. A reliability score computed **706**, an entropy based measure including sample size (number of detections of said Lithostratigraphic entity name), information container diversity (number of documents generating those mentions) and provenance diversity (number of unique authors/sources who have generated the documents). These are multiplied together to form an overall entropy score, the higher the number, the greater the reliability of the similarity score.

Using distributional semantics (counting) or text embedding (prediction) methods (or other such technique), a vector is computed for each Lithostratigraphic entity information container (document) **708**. Word vectors are weighted giving priority to nouns, followed by adjectives followed by verbs **710** to create an overall aggregated vector for each Lithostratigraphic entity.

A similarity score is computed for each Lithostratigraphic entity to every other Lithostratigraphic entity **712** using such method as cosine similarity (measures the angle between vectors in n-dimensional space). This may be pre-computed and stored in an array structure or performed in real time against the statistical model.

A preferred embodiment for vector creation goes beyond computing one vector per word (Mikolov et al 2013; Pennington et al 2014, Le and Mikolov 2014). Using characters/word pieces to handle unseen words (Bojanowski et al 2016), more than one vector per word to cater for polysemy (Peters et al 2018) and use of transfer learning and flexible context windows (not fixed) to capture longer term dependency (Devlin et al 2018).

FIG. 8 shows the method of ranking for similarity given an initial user input. A user interface allowing a user to input query terms **802** can display **804** these similarities and reliability scores ranked in order of closest similarity (the more similar the vectors representing each Lithostratigraphic entity name, the closer the cosine will be to 1) to the input context **806**. The Lithostratigraphic entity name closest to 1 would be ranked first, the Lithostratigraphic entity name furthest from 1 would be displayed last.

FIG. 9 shows the method for incorporating feedback given user input, after ranked Lithostratigraphic entity names have been displayed. Through the user interface this can receive user feedback based on the rankings **902** as to whether the analogue suggestions are deemed useful or not by the geoscientist. This positive and negative user feedback can be incorporated in the statistical ranking model in a number of ways **904**. This includes (but is not limited to) modification of input text/co-occurrence prior to similarity

computation (such as addition/removal of certain terms) or adjustment (increase/decrease) of the overall computed paired similarity score.

FIG. 10 shows one embodiment of a user interface. Given user input **1002**, Lithostratigraphic Entity Names **1006** are ranked **1004** by their cosine similarity **1010** allowing filtering by geographical entities **1008**. An entropy (reliability score) allows the user to view the number of mentions of the detected Lithostratigraphic Entity Name **1012**, the number of unique documents from which those mentions are derived **1014** and number of unique authors from which all of those are derived **1016**. An overall reliability score could be colour coded to indicate where the similarity score may be potentially suspect **1018**. Post query user feedback could be collected **1020** as positive or negative to the suggested Lithostratigraphic entity names. This could be used to adjust similarity calculations. FIG. 11 illustrates how the input context could be a combination of terms from the text corpus as well as an 'exemplar' Lithostratigraphic entity name used as an input query. In this example the vectors of the terms entered would be summed (which could include a weighting (such as TF-IDF) biasing towards the more specific term(s) which has a stronger signal) in order to generate a similarity score to Lithostratigraphic entity names.

The invention claimed is:

1. A computer implemented process for suggesting space-time aware geological Lithostratigraphic analogues from text using theory-guided machine learning, the process comprising:

receiving into a computer memory: sentences of text, geographical lexicons, negation/negative terms, geological time lexicons and Natural Language Processing (NLP) rules, processing a data in the computer memory with a processor to detect geological Lithostratigraphic entity names,

processing the data in the computer memory with a processor to compute similarity between Lithostratigraphic entities through word associations,

applying a filter around the detected geological Lithostratigraphic entities, the filter having a dynamic width defined by a window length comprising a first mention of a Lithostratigraphic entity and a subsequent mention of a different Lithostratigraphic entity, removing all geographical terms from these text and combining the texts as it relates to each Lithostratigraphic entity, the filter output providing an input to a learned statistical model where the positive and negative user feedback can be incorporated in the statistical ranking model, weighting from high to low nouns, adjectives, and verbs, from which a Lithostratigraphic entity-entity similarity is determined; and outputting the Lithostratigraphic entity-entity similarity through cosine similarity.

2. The computer-implemented process of claim 1 further comprising:

computing an entropy reliability function for each entity using the number of mentions of a Lithostratigraphic entity multiplied by a number of documents and further multiplied by a number of unique authors/sources for documents.

3. The computer-implemented process of claim 2 further comprising: receiving into the computer memory, human feedback from judgments of geologists on the suitability of Lithostratigraphic entity display ranking based on similarity score ranking;

processing the data in computer memory using a computer processor to incorporate a user feedback into the Lithostratigraphic entity similarity calculation, by: altering the learned statistical model for the Lithostratigraphic entities, through reduction or increase of at least one of an original input text and overall pairwise similarity score.

* * * * *