

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412872
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kim; Il-Soo et al.

Display device and manufacturing method of display device with the plurality of light emitting nanorods

Abstract

According to an aspect of the present disclosure, a display device having a plurality of pixels each including a plurality of sub-pixels, includes a first substrate; a plurality of first pads disposed on the first substrate in the plurality of sub-pixels; a common pad disposed on the first substrate and shared by the plurality of sub-pixels; a second substrate disposed to face the first substrate; a plurality of first electrodes disposed on the second substrate and connected to the plurality of first pads; a second electrode disposed on the second substrate and connected to the common pad; and a plurality of light emitting nanorods having one ends and the other ends respectively connected to the plurality of first electrodes and the second electrode. Therefore, self-aligning of the light emitting nanorods can be easily achieved.

Inventors: Kim; Il-Soo (Goyang-si, KR), Jung; Taeil (Paju-si, KR), Park; Seongkyong (Gimpo-si, KR)

Applicant: LG Display Co., Ltd. (Seoul, KR)

Family ID: 79293641

Assignee: LG DISPLAY CO., LTD. (Seoul, KR)

Appl. No.: 17/377108

Filed: July 15, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220020906 A1	Jan. 20, 2022

Foreign Application Priority Data

KR	10-2020-0087747	Jul. 15, 2020
----	-----------------	---------------

Publication Classification

Int. Cl.: **H01L25/075** (20060101); **H10H20/01** (20250101); **H10H20/831** (20250101);
H10H20/857 (20250101); **H10H29/14** (20250101); **H10K59/80** (20230101)

U.S. Cl.:

CPC **H01L25/0753** (20130101); **H10H20/01** (20250101); **H10H20/831** (20250101);
H10H20/857 (20250101); **H10H29/142** (20250101); **H10K59/805** (20230201);
H10H20/032 (20250101); H10H20/0364 (20250101)

Field of Classification Search

CPC: H01L (33/62); H01L (27/156); H01L (33/005); H01L (33/38); H01L (2933/0016); H01L
(2933/0066); H01L (25/0753); H10K (59/805); H10H (29/142); H10H (20/01); H10H
(20/831); H10H (20/857); H10H (20/0364); H10H (20/032)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2017/0357344	12/2016	Hong	N/A	G06F 3/0447
2018/0012876	12/2017	Kim et al.	N/A	N/A
2018/0090061	12/2017	Kim	N/A	H10K 50/805
2021/0288033	12/2020	Lim	N/A	H01L 33/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
108598251	12/2017	CN	N/A
110400819	12/2018	CN	N/A
3 787 027	12/2020	EP	N/A
10-2013-0127389	12/2012	KR	N/A
10-2017-0010132	12/2016	KR	N/A
10-2018-0007025	12/2017	KR	N/A
10-2019-0124359	12/2018	KR	N/A
201946270	12/2018	TW	N/A
202013025	12/2019	TW	N/A
WO-2020013386	12/2019	WO	H01L 25/0753

Primary Examiner: Richards; Norman D

Assistant Examiner: Winters; Sean Ayers

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of and priority to Korean Patent Application No. 10-2020-0087747 filed on Jul. 15, 2020 in the Republic of Korea, the entire contents of which are hereby expressly incorporated by reference into the present application.

BACKGROUND

Technical Field

(2) The present disclosure relates to a display device, and more particularly, to a display device capable of easily self-aligning light emitting nanorods and a method of manufacturing the display device.

Discussion of the Related Art

(3) Recently, as our society advances toward an information-oriented society, the field of display devices for visually expressing an electrical information signal has rapidly advanced. Various display devices having excellent performance in terms of thinness, lightness, and low power consumption, are being continually developed correspondingly.

(4) Specifically, flat panel display devices such as a liquid crystal display device using a light emitting diode (LED) as a light source and an organic light emitting diode (OLED) display device using a self-emission type OLED, are attracting attention as the next-generation display devices due to their small thicknesses and low power consumption.

(5) The inventors of the present disclosure have recognized that in the case of a display device using light emitting nanorods as light emitting elements among display devices using LEDs as described above, a process time increases and a decrease in yield can be caused. Specifically, since red light emitting nanorods, green light emitting nanorods, and blue light emitting nanorods are individually grown and transferred to a display panel individually, the process time can increase, leading to a decrease in yield. In addition, since the light emitting nanorods are individually transferred, there can be a limit to a reduction in the size of the light emitting nanorods.

SUMMARY OF THE INVENTION

(6) Accordingly, the inventors of the present disclosure have invented a display device and a method of manufacturing the display device, capable of reducing a process time and costs by self-aligning light emitting nanorods in a manufacturing process.

(7) An object of the present disclosure is to provide a display device capable of self-aligning light emitting nanorods through first and second electrodes electrically respectively connected to one ends and the other ends of the light emitting nanorods and a method of manufacturing the display device.

(8) Another object of the present disclosure is to provide a display device and a method of manufacturing the display device, in which the self-alignment can be more easily achieved by forming protrusions on the first electrode and/or the second electrode connected to the light emitting nanorods.

(9) Objects of the present disclosure are not limited to the above-mentioned objects, and other objects, which are not mentioned above, can be clearly understood by those skilled in the art from the following descriptions.

(10) In order to solve the above problems, according to an aspect of the present disclosure, a display device having a plurality of pixels each of which includes a plurality of sub-pixels, includes a first substrate; a plurality of first pads disposed on the first substrate in the plurality of sub-pixels; a common pad disposed on the first substrate and shared by the plurality of sub-pixels; a second substrate disposed to face the first substrate; a plurality of first electrodes disposed on the second substrate and connected to the plurality of first pads; a second electrode disposed on the second substrate and connected to the common pad; and a plurality of light emitting nanorods having one ends and the other ends respectively connected to the plurality of first electrodes and the second electrode. The plurality of first electrodes and/or the second electrode includes a plurality of

protrusions connected to the plurality of light emitting nanorods.

(11) According to another aspect of the present disclosure, a display device having a plurality of pixels each of which includes a plurality of sub-pixels, includes a first substrate and a second substrate facing each other; a plurality of first pads disposed on the first substrate in the plurality of sub-pixels; a common pad disposed on the first substrate and shared by the plurality of sub-pixels; a plurality of first electrodes disposed on the second substrate in the plurality of sub-pixels; a second electrode disposed on the second substrate and shared by the plurality of sub-pixels; a plurality of light emitting nanorods disposed on the second substrate in the plurality of sub-pixels and in contact with the plurality of first electrodes and the second electrode; and adhesive patterns connecting the plurality of first pads and the plurality of first electrodes and connecting the common pad and the second electrode. The plurality of first electrodes and/or the second electrode includes a plurality of protrusions connected to the plurality of light emitting nanorods.

(12) According to yet another aspect of the present disclosure, a method of manufacturing a display device having a plurality of pixels each of which includes a plurality of sub-pixels, includes preparing a first substrate on which a plurality of first pads disposed in the plurality of sub-pixels and a common pad shared by the plurality of sub-pixels are disposed; forming a first electrode layer and a second electrode layer spaced apart from each other on a second substrate; self-aligning a plurality of light emitting nanorods by applying a direct current to the first electrode layer and the second electrode layer; separating the first electrode layer and the second electrode layer into a plurality of first electrodes and a second electrode, respectively, corresponding to the plurality of sub-pixels; and bonding the first substrate and the second substrate by connecting the plurality of first pads and the plurality of first electrodes and connecting the common pad and the second electrode. The plurality of light emitting nanorods are connected to a plurality of protrusions of the first electrode layer and/or the second electrode layer and are self-aligned.

(13) Other detailed matters of the exemplary embodiments are included in the detailed description and the drawings.

(14) According to the present disclosure, light emitting nanorods are self-aligned by applying a current to a first electrode and a second electrode of a substrate, so that a process can be simplified and costs can be reduced.

(15) According to the present disclosure, alignment accuracy of the light emitting nanorods can be improved by concentrating a current on protrusions formed on the first electrode and/or the second electrode.

(16) The effects according to the present disclosure are not limited to the contents exemplified above, and more various effects are included in the present specification.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present disclosure.

(2) FIG. 1 is an exploded perspective view of a display device according to an exemplary embodiment of the present disclosure.

(3) FIG. 2 is an enlarged plan view of a first substrate of the display device according to an exemplary embodiment of the present disclosure.

(4) FIG. 3A is an enlarged plan view of a second substrate of the display device according to an exemplary embodiment of the present disclosure.

(5) FIG. 3B is an enlarged view of region A of FIG. 3A.

(6) FIG. 4 is a cross-sectional view of the display device taken along line IV-IV' of FIG. 3B.

(7) FIG. 5 is a perspective view of a light emitting nanorod of the display device according to an exemplary embodiment of the present disclosure.

(8) FIG. 6A to FIG. 6C are plan views for explaining a method of manufacturing a second substrate according to an exemplary embodiment of the present disclosure.

(9) FIG. 7 to FIG. 10 are partial enlarged plan views of the second substrate according to various embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(10) Advantages and characteristics of the present disclosure and a method of achieving the advantages and characteristics will be clear by referring to exemplary embodiments described below in detail together with the accompanying drawings. However, the present disclosure is not limited to the exemplary embodiments disclosed herein but will be implemented in various forms. The exemplary embodiments are provided by way of example only so that those skilled in the art can fully understand the disclosures of the present disclosure and the scope of the present disclosure. Therefore, the present disclosure will be defined only by the scope of the appended claims.

(11) The shapes, sizes, ratios, angles, numbers, and the like illustrated in the accompanying drawings for describing the exemplary embodiments of the present disclosure are merely examples, and the present disclosure is not limited thereto. Like reference numerals generally denote like elements throughout the specification. Further, in the following description of the present disclosure, a detailed explanation of known related technologies can be omitted to avoid unnecessarily obscuring the subject matter of the present disclosure. The terms such as “including,” “having,” and “consist of” used herein are generally intended to allow other components to be added unless the terms are used with the term “only”. Any references to singular can include plural unless expressly stated otherwise.

(12) Components are interpreted to include an ordinary error range even if not expressly stated.

(13) When the position relation between two parts is described using the terms such as “on”, “above”, “below”, and “next”, one or more parts can be positioned between the two parts unless the terms are used with the term “immediately” or “directly”.

(14) When an element or layer is disposed “on” another element or layer, another layer or another element can be interposed directly on the other element or therebetween.

(15) Although the terms “first”, “second”, and the like are used for describing various components, these components are not confined by these terms. These terms are merely used for distinguishing one component from the other components and may not define order. Therefore, a first component to be mentioned below can be a second component in a technical concept of the present disclosure.

(16) Like reference numerals generally denote like elements throughout the specification.

(17) A size and a thickness of each component illustrated in the drawing are illustrated for convenience of description, and the present disclosure is not limited to the size and the thickness of the component illustrated.

(18) The features of various embodiments of the present disclosure can be partially or entirely adhered to or combined with each other and can be interlocked and operated in technically various ways, and the embodiments can be carried out independently of or in association with each other.

(19) Hereinafter, the present disclosure will be described in detail with reference to accompanying drawings. All the components of each display device according to all embodiments of the present disclosure are operatively coupled and configured.

(20) FIG. 1 is an exploded perspective view of a display device according to an exemplary embodiment of the present disclosure. FIG. 2 is an enlarged plan view of a first substrate of the display device according to an exemplary embodiment of the present disclosure. FIG. 3A is an enlarged plan view of a second substrate of the display device according to an exemplary embodiment of the present disclosure. FIG. 3B is an enlarged view of region A of FIG. 3A.

(21) In FIG. 1 to FIG. 3B, for convenience of explanation, in a display device **100**, a first substrate

110, first pads **141**, common pads **142**, a second substrate **150**, first electrodes **161**, second electrodes **162**, first and second dummy electrodes **165** and **166**, light emitting nanorods **170**, and adhesive patterns **180** among various components of the display device **100**, are shown. FIG. 3A can be a view of the second substrate **150** shown in FIG. 1 as viewed from the bottom.

(22) Hereinafter, with reference to FIG. 1 to FIG. 3B, arrangement structures of a plurality of first pads **141**, a plurality of common pads **142**, a plurality of first electrodes **161**, a plurality of second electrodes **162**, first and second dummy electrodes **165** and **166**, and light emitting nanorods **170** on a plane will be mainly described.

(23) Referring to FIG. 1 to FIG. 3B, the display device **100** according to an exemplary embodiment of the present disclosure includes the first substrate **110** and the second substrate **150**. The first substrate **110** and the second substrate **150** can face each other and can be electrically connected to each other by the adhesive patterns **180**.

(24) The display device has a plurality of pixels PX each of which includes a plurality of sub-pixels. The first substrate **110** and the second substrate **150** each carry various components constituting the plurality of pixels PX. Each of the plurality of pixels PX can include a first sub-pixel SP1, a second sub-pixel SP2, and a third sub-pixel SP3 that emit light of different wavelengths. The plurality of pixels PX are minimum units constituting a screen, and each of the plurality of sub-pixels SP1, SP2, and SP3 can include the light emitting nanorods **170** and a pixel circuit for driving the light emitting nanorods **170**. The first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3 can be a blue sub-pixel, a green sub-pixel, and a red sub-pixel, respectively, but are not limited thereto, and any other number of sub-pixels can be provided in each pixel PX.

(25) The plurality of first pads **141** and the plurality of common pads **142** are disposed on the first substrate **110**. The plurality of first pads **141** and the plurality of common pads **142** can be spaced apart from each other and disposed on a planarization layer **115** to be described later above the first substrate **110**.

(26) The plurality of first pads **141** can be disposed to correspond to the plurality of respective sub-pixels SP1, SP2, and SP3. The plurality of first pads **141** can be disposed on one sides of the plurality of sub-pixels SP1, SP2, and SP3, i.e., one side of the plurality of pixels PX. The plurality of first pads **141** can be electrically connected to transistors **120** to be described later disposed in the plurality of sub-pixels SP1, SP2, and SP3. Also, the plurality of first pads **141** can be electrically connected to the plurality of first electrodes **161** by the adhesive patterns **180**.

(27) The plurality of common pads **142** can be disposed to correspond to each of the plurality of pixels PX. Specifically, the first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3 of one pixel PX can share one common pad **142** in common. The common pad **142** can be disposed on the other side of the pixel PX. In the present disclosure, although it is illustrated that the common pad **142** is disposed on the other side of the second sub-pixel SP2, the present disclosure is not limited thereto. The common pad **142** can be electrically connected to a common electrode **130** to be described later connected to the first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3 in common. Also, the common pad **142** can be electrically connected to the second electrode **162** by the adhesive pattern **180**.

(28) The plurality of first electrodes **161**, the plurality of second electrodes **162**, the first and second dummy electrodes **165** and **166**, and a plurality of the light emitting nanorods **170** are disposed on the second substrate **150**. The plurality of first electrodes **161**, the plurality of second electrodes **162**, and the first and second dummy electrodes **165** and **166** can be disposed to be spaced apart from each other on the same plane.

(29) The plurality of first electrodes **161** can be disposed to correspond to the plurality of respective sub-pixels SP1, SP2, and SP3 on the second substrate **150**. The plurality of first electrodes **161** can be disposed to overlap the plurality of first pads **141**. The plurality of first electrodes **161** can include first portions **161a** overlapping the plurality of first pads **141** and pairs of second portions

161b extending from one ends and the other ends of the first portions **161a** or from one sides and the other sides of the first portions **161a**. The pair of second portions **161b** can be disposed to be parallel to each other.

(30) The plurality of second electrodes **162** can be disposed to correspond to each of the plurality of pixels PX on the second substrate **150**. Specifically, the first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3 of one pixel PX can share one second electrode **162** in common. The second electrodes **162** can be disposed to be opposite to the plurality of first electrodes **161** in the pixels PX. Also, the plurality of second electrodes **162** can be disposed to overlap the plurality of common pads **142**.

(31) The plurality of second electrodes **162** can include line electrodes **162a** overlapping the plurality of common pads **142** and a plurality of branch electrodes **162b** extending from the line electrodes **162a** toward the plurality of first electrodes **161**. The line electrode **162a** can be parallel to the first portions **161a** of the first electrodes **161** and can be disposed in common in the first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3. The plurality of branch electrodes **162b** can be surrounded by the plurality of first electrodes **161**. The branch electrode **162b** can extend to be parallel to the pair of second portions **161b** in each of the plurality of sub-pixels SP1, SP2, and SP3. In the plurality of sub-pixels SP1, SP2, and SP3, the branch electrode **162b** can be disposed between the pair of second portions **161b**.

(32) The plurality of second electrodes **162** can further include a plurality of second protrusions **162c** protruding from the branch electrodes **162b** toward the pairs of second portions **161b**. The plurality of second protrusions **162c** can be formed to be narrower in width from the branch electrode **162b** toward the second portion **161b**. In addition, ends of the plurality of second protrusions **162c** can have a sharp shape. For example, the plurality of second protrusions **162c** can have a triangular shape, but is not limited thereto.

(33) The plurality of light emitting nanorods **170** can be connected to the plurality of second protrusions **162c**. The plurality of light emitting nanorods **170** can be easily aligned by the plurality of second protrusions **162c**. Specifically, when the plurality of light emitting nanorods **170** are self-aligned, a current is concentrated on the plurality of second protrusions **162c**, so that the plurality of light emitting nanorods **170** can be easily aligned. This will be described later with reference to FIG. 6A to FIG. 6C.

(34) Meanwhile, although FIG. 1 to FIG. 3B illustrate that the plurality of second protrusions **162c** are formed on the second electrode **162**, a plurality of first protrusions can be formed on the first electrode **161**. In this case, the plurality of first protrusions can protrude from the pair of second portions **161b** toward the branch electrodes **162b**. Also, although FIG. 1 to FIG. 3B illustrate that ten second protrusions **162c** are disposed in one sub-pixel SP1, SP2, or SP3, the present disclosure is not limited thereto.

(35) The first and second dummy electrodes **165** and **166** are disposed outside the plurality of pixels PX to be adjacent to portions of the plurality of pixels PX. The first and second dummy electrodes **165** and **166** can be connected to the plurality of first electrodes **161** and the plurality of second electrodes **162** before the light emitting nanorods **170** are aligned. The first and second dummy electrodes **165** and **166** can be separated from the plurality of first electrodes **161** and the plurality of second electrodes **162** after the light emitting nanorods **170** are aligned. The first dummy electrode **165** can include first dummy protrusions **165a** that are separated from the first electrodes **161**, and the second dummy electrode **166** can include second dummy protrusions **166a** that are separated from the second electrodes **162**. The first dummy protrusions **165a** can be disposed on the same lines as the first portions **161a** of the plurality of first electrodes **161**. The second dummy protrusions **166a** can be disposed on the same lines as the line electrodes **162a** of the plurality of second electrodes **162**. The dummy electrodes **165** and **166** will be described later with reference to FIG. 6A to FIG. 6C.

(36) Meanwhile, although it is illustrated that the first dummy electrode **165** and the second

dummy electrode **166** are disposed on an upper side and a lower side of the second substrate **150**, respectively, the present disclosure is not limited thereto. For example, the number and arrangement of the first and second dummy electrodes **165** and **166** can be variously changed according to the number and arrangement of pixels PX connected to the first and second dummy electrodes **165** and **166** during a manufacturing process.

(37) The plurality of light emitting nanorods **170** are disposed between the first electrode **161** and the second electrode **162**. One ends of the plurality of light emitting nanorods **170** can be electrically connected to the first electrode **161**, and the other ends of the plurality of light emitting nanorods **170** can be electrically connected to the second electrode **162**. Specifically, one ends of the plurality of light emitting nanorods **170** can be connected to the second portion **161b**, and the other ends of the plurality of light emitting nanorods **170** can be connected to the second protrusions **162c** of the branch electrode **162b**.

(38) The plurality of light emitting nanorods **170** can be connected to the first electrode **161** and the second electrode **162** to emit light having a wavelength corresponding to each of the sub-pixels SP1, SP2, and SP3. For example, the plurality of light emitting nanorods **170** disposed in the first sub-pixel SP1 can emit blue light, the plurality of light emitting nanorods **170** disposed in the second sub-pixel SP2 can emit green light, and the plurality of light emitting nanorods **170** disposed in the third sub-pixel SP3 can emit red light, but the present disclosure is not limited thereto.

(39) The adhesive patterns **180** are disposed on the first portions **161a** of the first electrodes **161** and the line electrodes **162a** of the second electrodes **162**. The adhesive patterns **180** are disposed to overlap the plurality of first pads **141** and the plurality of common pads **142**. The adhesive patterns **180** can electrically connect the first pads **141** of the first substrate **110** and the first electrodes **161** of the second substrate **150**. In addition, the adhesive patterns **180** can electrically connect the common pads **142** of the first substrate **110** and the second electrodes **162** of the second substrate **150**.

(40) Hereinafter, one sub-pixel SP2 of the display device **100** will be described in more detail with reference to FIG. 4. The cross-sectional view illustrated in FIG. 4 can be a cross-sectional view of the second sub-pixel SP2. However, a structure of FIG. 4 except for the common pad **142** can be equally applied to the first sub-pixel SP1 and the third sub-pixel SP3.

(41) Particularly, FIG. 4 is a cross-sectional view of the display device taken along line IV-IV' of FIG. 3B.

(42) Referring to FIG. 4, the first substrate **110** is a support member for supporting other components of the display device **100**, and can be formed of an insulating material. For example, the first substrate **110** can be formed of glass or resin. In addition, the first substrate **110** can be formed to include a polymer or plastic such as polyimide (PI), or can be formed of a material having flexibility.

(43) A buffer layer **111** is disposed on the first substrate **110**. The buffer layer **111** can reduce penetration of moisture or impurities through the first substrate **110**. The buffer layer **111** can be composed of, for example, a single layer or multilayers of silicon oxide (SiOx) or silicon nitride (SiNx), but is not limited thereto. However, the buffer layer **111** can be omitted depending on a type of the first substrate **110** or a type of the transistor **120**, but is not limited thereto.

(44) The transistor **120** is disposed on the buffer layer **111**. The transistor **120** includes an active layer **121**, a gate electrode **122**, a source electrode **123**, and a drain electrode **124**.

(45) The active layer **121** is disposed on the buffer layer **111**. The active layer **121** can be formed of a semiconductor material such as an oxide semiconductor, amorphous silicon, or polysilicon, but is not limited thereto. For example, when the active layer **121** is formed of an oxide semiconductor, the active layer **121** includes a channel region, a source region, and a drain region, and the source region and the drain region can be conductive regions, but are not limited thereto.

(46) A gate insulating layer **112** is disposed on the active layer **121**. The gate insulating layer **112** is

an insulating layer for insulating the active layer **121** and the gate electrode **122** and can be composed of a single layer or multilayers of silicon oxide (SiOx) or silicon nitride (SiNx), but is not limited thereto.

(47) The gate electrode **122** is disposed on the gate insulating layer **112**. The gate electrode **122** can be formed of a conductive material, for example, copper (Cu), aluminum (Al), molybdenum (Mo), nickel (Ni), titanium (Ti), chromium (Cr), or an alloy thereof, but is not limited thereto.

(48) An interlayer insulating layer **113** is disposed on the gate electrode **122**. Contact holes for connecting the source electrode **123** and the drain electrode **124** to the active layer **121** are formed in the interlayer insulating layer **113** and the gate insulating layer **112**. The interlayer insulating layer **113** can be composed of a single layer or multilayers of silicon oxide (SiOx) or silicon nitride (SiNx), but is not limited thereto.

(49) The source electrode **123** and the drain electrode **124** are disposed on the interlayer insulating layer **113**. The source electrode **123** and the drain electrode **124** can be spaced apart from each other and electrically connected to the active layer **121**. The source electrode **123** and the drain electrode **124** can be formed of a conductive material, for example, copper (Cu), aluminum (Al), molybdenum (Mo), nickel (Ni), titanium (Ti), chromium (Cr), or an alloy thereof, but is not limited thereto.

(50) The common electrode **130** is disposed on the interlayer insulating layer **113**. The common electrode **130** can be an electrode that is disposed not only in the second sub-pixel SP2, but also in the first sub-pixel SP1 and the third sub-pixel SP3 in common. The common electrode **130** can be electrically connected to a common voltage line and receive a common voltage. The common electrode **130** can be formed of copper (Cu), aluminum (Al), molybdenum (Mo), nickel (Ni), titanium (Ti), chromium (Cr) or an alloy thereof, but is not limited thereto.

(51) A passivation layer **114** is disposed on the source electrode **123**, the drain electrode **124**, and the common electrode **130**. The passivation layer **114** can protect the source electrode **123**, the drain electrode **124**, and the common electrode **130**. The passivation layer **114** can be composed of a single layer or multilayers of silicon oxide (SiOx) or silicon nitride (SiNx), but is not limited thereto.

(52) A planarization layer **115** is disposed on the passivation layer **114**. The planarization layer **115** is an insulating layer that planarizes an upper portion of the first substrate **110**. Contact holes for connecting the drain electrode **124** and the common electrode **130** to the first pad **141** and the common pad **142**, respectively, are formed in the planarization layer **115** and the passivation layer **114**. The planarization layer **115** can be composed of an organic material, for example, a single layer or multilayers of polyimide or photo acryl, but is not limited thereto.

(53) The first pad **141** and the common pad **142** are disposed on the planarization layer **115**. The first pad **141** can be electrically connected to the drain electrode **124** of the transistor **120**, but is not limited thereto, and can be connected to the source electrode **123**. The common pad **142** can be electrically connected to the common electrode **130**. The first pad **141** and the common pad **142** can be formed of molybdenum (Mo), aluminum (Al), chromium (Cr), gold (Au), silver (Ag), titanium (Ti), nickel (Ni), neodymium (Nd), and copper (Cu) or an alloy thereof, but is not limited thereto.

(54) The second substrate **150** is disposed to face the first substrate **110**. The second substrate **150** is a support member for supporting other components of the display device **100**, and can be formed of an insulating material. For example, the second substrate **150** can be formed of glass or resin. In addition, the second substrate **150** can be formed to include a polymer or plastic such as polyimide (PI), or can be formed of a material having flexibility.

(55) The first electrode **161** is disposed on the second substrate **150** to correspond to the first pad **141**. Specifically, based on FIG. 4, the first electrode **161** can be disposed on a lower surface of the second substrate **150** to face the first pad **141**. The first electrode **161** can include the first portion **161a** overlapping the first pad **141** and the second portion **161b** extending from the first portion

161a. The first portion **161a** can be electrically connected to the first pad **141** by the adhesive pattern **180**. Accordingly, the first electrode **161** can be connected to the transistor **120** and receive a data voltage.

(56) The second electrode **162** is disposed on the second substrate **150** to correspond to the common pad **142**. Specifically, based on FIG. 4, the second electrode **162** can be disposed on the lower surface of the second substrate **150** to face the common pad **142**. The second electrode **162** can include the line electrode **162a** overlapping the common pad **142**, the branch electrode **162b** extending from the line electrode **162a**, and the second protrusions **162c** extending from the branch electrode **162b**. The line electrode **162a** can be electrically connected to the common pad **142** by the adhesive pattern **180**. Accordingly, the second electrode **162** can be connected to the common electrode **130** and receive a common voltage.

(57) The first electrode **161** and the second electrode **162** can be formed of a conductive material, for example, copper (Cu), aluminum (Al), molybdenum (Mo), nickel (Ni), titanium (Ti), chromium (Cr), or an alloy thereof, but is not limited thereto.

(58) The light emitting nanorod **170** is disposed between the first electrode **161** and the second electrode **162**. The light emitting nanorod **170** can include a first nanorod electrode **171**, a first conductive semiconductor layer **172**, an active layer **173**, a second conductive semiconductor layer **174**, and a second nanorod electrode **175**. The first nanorod electrode **171** can contact the second portion **161b** of the first electrode **161**, and the second nanorod electrode **175** can contact the second protrusion **162c** of the second electrode **162**. Accordingly, a data voltage and a common voltage can be applied to the light emitting nanorod **170** so that light can be emitted from the active layer **173**. Although it is illustrated that the light emitting nanorod **170** is disposed on the second substrate **150** and contacts ends of the first electrode **161** and the second electrode **162**, the present disclosure is not limited thereto. For example, the first nanorod electrode **171** and the second nanorod electrode **175** of the light emitting nanorod **170** are disposed on the second portion **161b** and the second protrusion **162c**, respectively, and can be in contact with the first electrode **161** and the second electrode **162**, respectively. A specific structure of the light emitting nanorod **170** will be described later.

(59) The adhesive pattern **180** can electrically connect the first pad **141** and the first portion **161a** of the first electrode **161**. Also, the adhesive pattern **180** can electrically connect the common pad **142** and the line electrode **162a** of the second electrode **162**. The adhesive pattern **180** can be formed of a conductive material, for example, copper (Cu), aluminum (Al), molybdenum (Mo), nickel (Ni), titanium (Ti), chromium (Cr) or an alloy thereof, but is not limited thereto. In addition, bonding of the first pad **141** and the first portion **161a** and bonding of the common pad **142** and the line electrode **162a** can be performed by eutectic or anisotropic conductive film (ACF) bonding, but the present disclosure is not limited thereto.

(60) FIG. 5 is a perspective view of a light emitting nanorod of the display device according to an exemplary embodiment of the present disclosure.

(61) Referring to FIG. 5, the light emitting nanorod **170** includes the first nanorod electrode **171**, the first conductive semiconductor layer **172**, the active layer **173**, the second conductive semiconductor layer **174**, and the second nanorod electrode **175** sequentially stacked one on top of another. The light emitting nanorod **170** can be formed in a cylindrical shape, but is not limited thereto.

(62) The first nanorod electrode **171** can supply holes to the active layer **173**. The first nanorod electrode **171** can be formed of molybdenum (Mo), aluminum (Al), chromium (Cr), gold (Au), silver (Ag), titanium (Ti), nickel (Ni), neodymium (Nd), and copper (Cu) or an alloy thereof. Alternatively, the first nanorod electrode **171** can be formed of a transparent conductive material such as indium tin oxide (ITO) or indium zinc oxide (IZO), but is not limited thereto.

(63) The first conductive semiconductor layer **172** is disposed on the first nanorod electrode **171**. The first conductive semiconductor layer **172** can be a p-type semiconductor layer including a

group III-V semiconductor material. Specifically, the first conductive semiconductor layer **172** can include a semiconductor material having a composition formula of $\text{In}_{0.5}\text{Al}_{0.5}\text{Ga}_{0.5}\text{N}_{0.5}$ ($0 \leq x \leq 1$, $0 \leq y \leq 1$, $0 \leq x+y \leq 1$). For example, the first conductive semiconductor layer **172** can include any one of InAlGa_N, Ga_N, AlGa_N, InGa_N, Al_N, and In_N, and can be doped with a first conductive dopant, for example, magnesium (Mg) or the like.

(64) The active layer **173** is disposed on the first conductive semiconductor layer **172**. The active layer **173** is a layer for emitting light of a specific color, and can include one of a red active layer, a green active layer, and a blue active layer. When an electric field is applied, the active layer **173** can emit light by electron-hole pair bonding. The active layer **173** can have a single or multiple quantum well structure. The active layer **173** can include a group III-V semiconductor material.

(65) The second conductive semiconductor layer **174** is disposed on the active layer **173**. The second conductive semiconductor layer **174** can be an n-type semiconductor layer including a group III-V semiconductor material. Specifically, the second conductive semiconductor layer **174** can include a semiconductor material having a composition formula of $\text{In}_{0.5}\text{Al}_{0.5}\text{Ga}_{0.5}\text{N}_{0.5}$ ($0 \leq x \leq 1$, $0 \leq y \leq 1$, $0 \leq x+y \leq 1$). For example, the second conductive semiconductor layer **174** can include any one of InAlGa_N, Ga_N, AlGa_N, InGa_N, Al_N, and In_N, and can be doped with a second conductive dopant, for example, silicon (Si), germanium (Ge), tin (Sn) or the like.

(66) The second nanorod electrode **175** can supply electrons to the active layer **173**. The second nanorod electrode **175** can be formed of molybdenum (Mo), aluminum (Al), chromium (Cr), gold (Au), silver (Ag), titanium (Ti), nickel (Ni), neodymium (Nd), and copper (Cu) or an alloy thereof. Alternatively, the second nanorod electrode **175** can be formed of a transparent conductive material such as indium tin oxide (ITO) or indium zinc oxide (IZO), but is not limited thereto.

(67) FIG. **6A** to FIG. **6C** are plan views for explaining a method of manufacturing a display device according to an exemplary embodiment of the present disclosure. Specifically, FIG. **6A** to FIG. **6C** are plan views for explaining a method of manufacturing the first electrodes **161**, the second electrodes **162**, the first and second dummy electrodes **165** and **166**, the light emitting nanorods **170**, and the adhesive patterns **180** that are disposed on the second substrate **150** of the display device **100** according to an exemplary embodiment of the present disclosure.

(68) First, referring to FIG. **6A**, a step of forming a first electrode layer **610** and a second electrode layer **620** that are spaced apart from each other is performed on the second substrate **150**. The first electrode layer **610** and the second electrode layer **620** can be formed by depositing an electrode material on the second substrate **150** using a mask. The electrode material can be composed of a conductive material, for example, copper (Cu), aluminum (Al), molybdenum (Mo), nickel (Ni), titanium (Ti), chromium (Cr), or an alloy thereof, but is not limited thereto.

(69) The first electrode layer **610** includes a dummy portion **611**, first portions **612**, and second portions **613**. The second electrode layer **620** includes a dummy portion **621**, first portions **622**, and second portions **623**. Shapes of the dummy portions **611** and **621**, the first portions **612** and **622**, and the second portions **613** and **623** are not limited to those shown in FIG. **6A** to FIG. **6C**, and can be variously changed according to the number and arrangement of the pixels PX.

(70) The dummy portion **611** of the first electrode layer **610** and the dummy portion **621** of the second electrode layer **620** are disposed to be parallel to each other on the first substrate **150**. The dummy portions **611** and **621** can be disposed to correspond to an outside of the plurality of pixels PX. The dummy portions **611** and **621** can be regions that are separated from the first portions **612** and **622** after self-alignment of the light emitting nanorods **170** is completed.

(71) The first portion **612** of the first electrode layer **610** extends from the dummy portion **611** of the first electrode layer **610** toward the dummy portion **621** of the second electrode layer **620**. Also, the first portion **622** of the second electrode layer **620** extends from the dummy portion **621** of the second electrode layer **620** toward the dummy portion **611** of the first electrode layer **610**. The first portion **612** of the first electrode layer **610** and the first portion **622** of the second electrode layer **620** can be disposed to face each other while being parallel to each other. For example, the first

portion **612** of the first electrode layer **610** and the first portion **622** of the second electrode layer **620** can be disposed to respectively correspond to one side and the other side of the pixel PX or the sub-pixels SP1, SP2, and SP3.

(72) The second portions **613** of the first electrode layer **610** extend from the first portion **612** of the first electrode layer **610** toward the first portion **622** of the second electrode layer **620**. In this case, the second portions **613** of the first electrode layer **610** include thin second portions and thick second portions. For example, the thin second portions **613** can be disposed to correspond to upper and lower sides of the pixel PX. The thick second portions **613** can be disposed to correspond to a boundary between the first sub-pixel SP1 and the second sub-pixel SP2 adjacent to each other and a boundary between the second sub-pixel SP2 and the third sub-pixel SP3 adjacent to each other. After the self-alignment of the light emitting nanorods **170** is completed, the thick second portion **613** can be separated into two parts and disposed one by one on an upper side or a lower side of the sub-pixel SP1, SP2 or SP3.

(73) The second portions **623** of the second electrode layer **620** extend from the first portion **622** of the second electrode layer **620** toward the first portion **612** of the first electrode layer **610**. The second portions **623** of the second electrode layer **620** can be disposed to be parallel to the second portions **613** of the first electrode layer **610**. Also, the second portion **623** of the second electrode layer **620** can be disposed between the two adjacent second portions **613** of the first electrode layer **610**. In this case, the second portion **623** of the second electrode layer **620** can be disposed to correspond to each of the sub-pixels SP1, SP2, and SP3.

(74) The second portion **623** of the second electrode layer **620** includes protrusions **623c** protruding toward the second portions **613** of the first electrode layer **610**. In FIG. 6A, it is illustrated that the protrusions **623c** are formed on the second portions **623** of the second electrode layer **620**, but the present disclosure is not limited thereto. For example, protrusions can be formed from the second portions **613** of the first electrode layer **610** toward the second portions **623** of the second electrode layer **620**.

(75) Referring to FIG. 6B, a step of self-aligning the plurality of light emitting nanorods **170** between the first electrode layer **610** and the second electrode layer **620** is performed. The plurality of light emitting nanorods **170** include first light emitting nanorods emitting blue light, second light emitting nanorods emitting green light, and third light emitting nanorods emitting red light. The first light emitting nanorods can be disposed to correspond to the first sub-pixel SP1. The second light emitting nanorods can be disposed to correspond to the second sub-pixel SP2. The third light emitting nanorods can be disposed to correspond to the third sub-pixel SP3.

(76) The step of self-aligning the plurality of light emitting nanorods **170** can include a step of self-aligning the first light emitting nanorods, a step of self-aligning the second light emitting nanorods, and a step of self-aligning the third light emitting nanorods.

(77) Specifically, a photoresist is disposed on the second substrate **150** on which the first electrode layer **610** and the second electrode layer **620** are formed, and only a region corresponding to the first sub-pixel SP1 is etched. The first electrode layer **610** and the second electrode layer **620** corresponding to the first sub-pixel SP1 can be exposed in the region opened by the etching. In addition, a first light emitting nanorod solution can be injected into the open region. In this case, the first light emitting nanorod solution can be prepared by mixing the plurality of first light emitting nanorods in a solvent. The solvent can include any one of acetone, water, alcohol, and toluene, but is not limited thereto.

(78) After the injection of the light emitting nanorod solution, a direct current (DC) is applied to the first electrode layer **610** and the second electrode layer **620**. For example, a negative current can be applied to the first electrode layer **610** and a positive current can be applied to the second electrode layer **620**, but the present disclosure is not limited thereto. When a direct current is applied to the first electrode layer **610** and the second electrode layer **620**, the first nanorod electrodes **171** of the first light emitting nanorods can be aligned toward the first electrode layer **610** and the second

nanorod electrodes **172** of the first light emitting nanorods can be aligned toward the second electrode layer **620**. For example, as a direct current is applied to the first electrode layer **610** and the second electrode layer **620**, the first light emitting nanorods can be easily self-aligned.

(79) Next, the photoresist is completely removed, and the same process as in the first sub-pixel SP1 is performed on a region corresponding to the second sub-pixel SP2 and a region corresponding to the third sub-pixel SP3. From this, the light emitting nanorods **170** can be self-aligned in the plurality of sub-pixels SP1, SP2, and SP3.

(80) In particular, the second nanorod electrode **175** of the light emitting nanorod **170** can be connected to the protrusion **623c** of the second electrode layer **620**. Specifically, when a direct current is applied to the second electrode layer **620**, a current can be concentrated on the protrusions **623c**. Accordingly, the second nanorod electrode **175** can be aligned by being drawn toward the protrusion **623c** in which the current is concentrated. Accordingly, manufacture efficiency of the display device **100** can be improved by more effectively aligning the plurality of light emitting nanorods **170**.

(81) Referring to FIG. **6C**, steps of separating the plurality of sub-pixels SP1, SP2, and SP3 and forming the adhesive patterns **180** are performed.

(82) First, in order to dispose a photoresist and separate the plurality of sub-pixels SP1, SP2, and SP3, regions from which portions of the electrode layers **610** and **620** are to be removed can be opened. In addition, by removing portions of the electrode layers **610** and **620**, the plurality of sub-pixels SP1, SP2, and SP3 can be separated from each other.

(83) Specifically, the dummy portion **611** and the first portion **612** of the first electrode layer **610** are separated, a part of the first portion **612** is separated, and the thick second portion **613** can be divided into two parts. The separated dummy portion **611** can become the first dummy electrode **165**, the separated first portion **612** can become the first portion **161a** of the first electrode **161**, and the separated second portion **613** can become the second portion **161b** of the first electrode **161**. On a portion of the first dummy electrode **165**, the first dummy protrusion **165a** remaining after being separated from the first portion **161a** can be present.

(84) Also, the dummy portion **621** and the first portion **622** of the second electrode layer **620** can be separated, and a part of the first portion **622** can be separated. The separated dummy portion **621** can become the second dummy electrode **166**, the separated first portion **622** can become the line electrode **162a** of the second electrode **162**, the second portion **623** can become the branch electrode **162b** of the second electrode **162**, and the protrusion **623c** can become the second protrusion **162c** of the second electrode **162**. On a portion of the second dummy electrode **166**, the second dummy protrusion **166a** remaining after being separated from the line electrode **162a** can be present.

(85) After the plurality of sub-pixels SP1, SP2, and SP3 are separated, the adhesive patterns **180** are formed. The adhesive patterns **180** can be disposed on a plurality of the first portions **161a** and a plurality of the line electrodes **162a**. Also, the adhesive patterns **180** can be disposed in regions corresponding to the first pad **141** and the common pad **142** of the first substrate **110**.

(86) Meanwhile, a manufacturing process of the display device **100** can be completed by bonding the second substrate **150** according to the above-described manufacturing method to the first substrate **110**. The first substrate **110** and the second substrate **150** can be electrically connected to each other by the adhesive patterns **180**.

(87) In the case of a display device including general light emitting nanorods, red light emitting nanorods, green light emitting nanorods, and blue light emitting nanorods were directly individually transferred to regions corresponding to a red sub-pixel, a green sub-pixel, and a blue sub-pixel. Accordingly, there are disadvantages in that a process time and costs increase, and a decrease in yield is caused.

(88) Accordingly, in the display device **100** according to an exemplary embodiment of the present disclosure, the first electrode layer **610** and the second electrode layer **620** for self-aligning the light

emitting nanorods **170** can be disposed on the second substrate **150**. For example, by injecting a solution including the light emitting nanorods **170** into the first electrode layer **610** and the second electrode layer **620** and applying a direct current thereto, the light emitting nanorods **170** can be self-aligned. In other words, the first nanorod electrodes **171** of the light emitting nanorods **170** can be aligned toward the first electrode layer **610** to which a negative current is applied, and the second nanorod electrodes **175** of the light emitting nanorods **170** can be aligned toward the second electrode layer **620** to which a positive current is applied. Accordingly, the plurality of light emitting nanorods **170** can be easily disposed in the plurality of sub-pixels SP1, SP2, and SP3.

(89) In addition, the self-alignment of the plurality of light emitting nanorods **170** can be simultaneously performed in each of the sub-pixels SP1, SP2, and SP3. Specifically, when the first light emitting nanorods are self-aligned, a process can be proceeded by opening an entirety of regions corresponding to the first sub-pixels SP1. Accordingly, the self-alignment of the plurality of first light emitting nanorods can be simultaneously performed in all of the plurality of first sub-pixels SP1. In addition, the self-alignment of the plurality of second light emitting nanorods can be simultaneously performed in all of the plurality of second sub-pixels SP2. In addition, the self-alignment of the plurality of third light emitting nanorods can be simultaneously performed in all of the plurality of third sub-pixels SP3. In other words, a process of self-aligning the light emitting nanorods **170** can be performed once for each of the plurality of sub-pixels SP1, SP2, and SP3. Accordingly, since individual transfers of the light emitting nanorods **170** are unnecessary, the process can be simplified. Accordingly, a process time can be shortened, costs can be reduced, and a yield can be improved.

(90) In addition, the second portion **623** of the second electrode layer **620** can include a plurality of the protrusions **623c**. When a direct current is applied to the second electrode layer **620**, the current can be concentrated on the plurality of protrusions **623c** of the second electrode layer **620**. The plurality of light emitting nanorods **170** can be aligned by being drawn to the plurality of protrusions **623c** in which the current is concentrated. Accordingly, the plurality of light emitting nanorods **170** can be uniformly aligned at accurate positions. Accordingly, an alignment defect can be minimized and reliability of the display device **100** can be improved.

(91) FIG. 7 is a partial enlarged plan view of the second substrate according to another exemplary embodiment of the present disclosure. In FIG. 7, one sub-pixel SP2 among the plurality of sub-pixels SP1, SP2, and SP3 is illustrated for convenience of explanation. Since other configurations of the second substrate **150** of FIG. 7 are substantially the same as those of the second substrate **150** of FIG. 1 except that both a first electrode **161** and the second electrode **162** respectively include first and second protrusions **161c** and **162c**, a redundant description will be omitted or may be provided briefly.

(92) Referring to FIG. 7, the first electrode **161** includes the first portion **161a**, the pair of second portions **161b**, and a plurality of first protrusions **161c**, and the second electrode **162** includes the line electrode **162a**, the branch electrode **162b**, and the plurality of second protrusions **162c**.

(93) The plurality of first protrusions **161c** can protrude from the pair of second portions **161b** toward the branch electrode **162b**. The plurality of second protrusions **162c** can protrude from the branch electrode **162b** toward the pair of second portions **161b**. The plurality of first protrusions **161c** and the plurality of second protrusions **162c** can be disposed to face each other. Accordingly, the plurality of first protrusions **161c** and the plurality of second protrusions **162c** can be disposed to be symmetrical with each other based on an imaginary straight line that is parallel to the pair of second portions **161b** or the branch electrode **162b**. The plurality of first protrusions **161c** can be formed to be narrower in width from the second portion **161b** toward the branch electrode **162b**. Also, the plurality of second protrusions **162c** can be formed to be narrower in width from the branch electrode **162b** toward the second portion **161b**. Ends of the plurality of first and second protrusions **161c** and **162c** can have a pointed shape. For example, the plurality of first and second protrusions **161c** and **162c** can have a triangular shape, but is not limited thereto.

(94) In the second substrate **150** of the display device according to another exemplary embodiment of the present disclosure, both the first electrode **161** and the second electrode **162** can include the plurality of protrusions. For example, the first electrode **161** can include the plurality of first protrusions **161c** protruding from the pair of second portions **162b**, and the second electrode **162** can include the plurality of second protrusions **162c** protruding from the branch electrode **162b**. In this case, the plurality of first protrusions **161c** and the plurality of second protrusions **162c** can be symmetrical to each other and disposed to face each other. Accordingly, the self-alignment of the plurality of light emitting nanorods **170** can be made more easily.

(95) Specifically, when a direct current is applied to the first electrode **761** and the second electrode **162** for self-alignment of the plurality of light emitting nanorods **170**, the current can be concentrated on the plurality of first protrusions **161c** and the plurality of second protrusions **162c**. Accordingly, the first nanorod electrodes **171** and the second nanorod electrodes **175** of the plurality of light emitting nanorods **170** can be aligned by being drawn to the plurality of first protrusions **161c** and the plurality of second protrusions **162c**. Accordingly, the plurality of light emitting nanorods **170** can be uniformly aligned at more accurate positions, thereby improving alignment accuracy.

(96) FIG. **8** is a partial enlarged plan view of the second substrate according to another exemplary embodiment of the present disclosure. In FIG. **8**, one sub-pixel SP2 among the plurality of sub-pixels SP1, SP2, and SP3 is illustrated for convenience of explanation. Since other configurations of the second substrate **150** of FIG. **8** are substantially the same as those of the second substrate **150** of FIG. **7** except for arrangement structures of first and second protrusions **161c** and **162c**, a redundant description will be omitted or may be provided briefly.

(97) Referring to FIG. **8**, each of a plurality of first electrodes **161** includes the first portion **161a**, the pair of second portions **161b**, and a plurality of first protrusions **161c**, and each of a plurality of second electrodes **162** includes the line electrode **162a**, the plurality of branch electrodes **162b**, and a plurality of second protrusions **162c**.

(98) The plurality of first protrusions **161c** can protrude from the pair of second portions **161b** toward the branch electrode **162b**. The plurality of second protrusions **162c** can protrude from the branch electrode **162b** toward the pair of second portions **161b**. The plurality of first protrusions **161c** and the plurality of second protrusions **162c** can be disposed to be offset from each other based on an imaginary straight line that is parallel to the pair of second portions **161b** or the branch electrode **162b**. Also, the plurality of second protrusions **162c** disposed at an upper portion of the branch electrode **162b** and the plurality of second protrusions **162c** disposed at a lower portion of the branch electrode **162b** can be disposed to be offset from each other.

(99) One ends and the other ends of the plurality of light emitting nanorods **170** are connected to the plurality of first protrusions **161c** and the plurality of second protrusions **162c**, respectively. Since the plurality of first protrusions **161c** and the plurality of second protrusions **162c** are disposed to be offset from each other, the plurality of light emitting nanorods **170** can be arranged in an oblique line. Accordingly, during the self-alignment of the plurality of light emitting nanorods **170**, alignment defects of the plurality of light emitting nanorods **170** can be reduced, and thus the reliability of the display device **100** can be improved.

(100) FIG. **9** is a partial enlarged plan view of the second substrate according to still another exemplary embodiment of the present disclosure. FIG. **9** shows one sub-pixel SP2 among the plurality of sub-pixels SP1, SP2, and SP3 for convenience of explanation, and an illustration of the light emitting nanorods **170** is omitted in FIG. **9**. Since other configurations of the second substrate **150** of FIG. **9** are substantially the same as those of the second substrate **150** of FIG. **7** except for a shape of the first and second protrusions **161c** and **162c**, a redundant description will be omitted or may be provided briefly.

(101) Referring to FIG. **9**, each of a plurality of first electrodes **161** includes the first portion **161a**, the pair of second portions **161b**, and a plurality of first protrusions **161c**, and each of a plurality of

second electrodes **162a** includes the line electrode **162a**, the plurality of branch electrode **162b**, and a plurality of second protrusions **162c**.

(102) The plurality of first protrusions **161c** can protrude from the pair of second portions **161b** toward the branch electrode **162b**. The plurality of second protrusions **162c** can protrude from the branch electrode **162b** toward the pair of second portions **161b**. The plurality of first protrusions **161c** and the plurality of second protrusions **162c** can be symmetrical to each other and disposed to face each other. The plurality of first protrusions **161c** can be formed to be narrower in width from the second portion **161b** toward the branch electrode **162b**. Also, the plurality of second protrusions **162c** can be formed to be narrower in width from the branch electrode **162b** toward the second portion **161b**.

(103) Ends of the plurality of first and second protrusions **161c** and **162c** can have a rounded shape. Accordingly, a contact area of the plurality of first and second protrusions **161c** and **162c** and the plurality of light emitting nanorods **170** can increase. Thus, resistance between the plurality of first and second protrusions **161c** and **162c** and the plurality of light emitting nanorods **170** can be reduced, and luminous efficiency of the display device **100** can be increased.

(104) FIG. **10** is a partial enlarged plan view of the second substrate according to another exemplary embodiment of the present disclosure. In FIG. **10**, one pixel PX among a plurality of pixels PX is illustrated for convenience of description. Since other configurations of a display device of FIG. **10** are substantially the same as those of the display device **100** of FIG. **1** except for arrangement structures of a first electrode **161** and a second electrode **162** in the plurality of sub-pixels SP1, SP2, and SP3, a redundant description will be omitted or may be provided briefly.

(105) Referring to FIG. **10**, the pixel PX includes a first sub-pixel SP1, a second sub-pixel SP2, and a third sub-pixel SP3. The first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3 can be a blue sub-pixel, a green sub-pixel, and a red sub-pixel, respectively. The first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3 can respectively have different areas. For example, the first sub-pixel SP1 and the second sub-pixel SP2 can have the same area, and the third sub-pixel SP3 can have an area greater than those of the first sub-pixel SP1 and the second sub-pixel SP2.

(106) The second substrate **150** includes the first electrode **161**, the second electrode **162**, the plurality of light emitting nanorods **170**, and the plurality of adhesive patterns **180**. The first electrode **161** and the second electrode **162** can be disposed in different structures in the plurality of sub-pixels SP1, SP2, and SP3. In addition, the number of light emitting nanorods **170** disposed in each of the sub-pixels SP1, SP2, and SP3 can be different.

(107) The first electrode **161** disposed in each of the plurality of sub-pixels includes a first portion **161a**, a pair of second portions **161b**, and a plurality of first protrusions **161c**.

(108) In the first sub-pixel SP1, the first portion **161a** can overlap the first pad **141** of the first substrate **110** and can be disposed on a lateral portion of the first sub-pixel SP1. The pair of second portions **161b** can extend from one end and the other end of the first portion **161a**. The pair of second portions **161b** can be disposed to be parallel to each other. The plurality of first protrusions **161c** can protrude from the pair of second portions **161b** toward a branch electrode **162b** of the second electrode to be described later.

(109) In the second sub-pixel SP2, the first portion **161a** can overlap the first pad **141** of the first substrate **110** and can be disposed on a lateral portion of the second sub-pixel SP2. The pair of second portions **161b** can extend from one end and the other end of the first portion **161a**. The pair of second portions **161b** can be disposed to be parallel to each other. The plurality of first protrusions **161c** can protrude from the pair of second portions **161b** toward a branch electrode **162b** of the second electrode to be described later.

(110) In the third sub-pixel SP3, the first portion **161a** can overlap the first pad **141** of the first substrate **110** and can have a shape in which it is bent along a periphery of the third sub-pixel SP3 at a lateral portion of the third sub-pixel SP3. The pair of second portions **161b** can extend from

one end and the other end of the first portion **161a**. In this case, an upper second portion of the pair of second portions **161b** can have a bent shape, and a lower second portion thereof can have a straight shape. For example, the first portion **161a** and the pair of second portions **161b** of the first electrode **161** disposed in the third sub-pixel SP3 can be disposed along a periphery of a region in the third sub-pixel SP3 where a line electrode **162a** of the second electrode to be described later is not disposed. The plurality of first protrusions **161c** can protrude from the pair of second portions **161b** toward a branch electrode **162b** of the second electrode to be described later.

(111) The second electrode **162** includes the line electrode **162a**, the branch electrodes **162b**, and a plurality of second protrusions **162c**. The line electrode **162a** can be disposed in the first sub-pixel SP1, the second sub-pixel SP2, and the third sub-pixel SP3 in common. The line electrode **162a** can overlap the common pad **142** of the first substrate **110** and can be disposed on lateral portions of the first sub-pixel SP1, the second sub-pixel SP2 and the third sub-pixel SP3 in common. The branch electrodes can extend from the line electrode **162a** toward the first electrode **161** in the plurality of respective sub-pixels SP1, SP2, and SP3. The branch electrodes **162b** can include a branch electrode disposed in the first sub-pixel SP1, a branch electrode disposed in the second sub-pixel SP2, and a branch electrode disposed in a third sub-pixel SP3. The branch electrodes **162b** can be disposed between the pairs of second portions **161b** in the respective sub-pixels SP1, SP2, and SP3. The plurality of second protrusions **162c** can protrude from the branch electrodes **162b** toward the pairs of second portions **161b**.

(112) The plurality of first and second protrusions **161c** and **162c** can be formed in different numbers in each of the sub-pixels SP1, SP2, and SP3. For example, the numbers of the plurality of first and second protrusions **161c** and **162c** can decrease in the order of the third sub-pixel SP3, the first sub-pixel SP1, and the second sub-pixel SP2. Since the numbers of the plurality of first and second protrusions **161c** and **162c** are different in each of the sub-pixels SP1, SP2, and SP3, the number of the plurality of light emitting nanorods **170** connected thereto can also be different in each of the sub-pixels SP1, SP2, and SP3. For example, the number of the plurality of light emitting nanorods **170** can decrease in the order of the third sub-pixel SP3, the first sub-pixel SP1, and the second sub-pixel SP2.

(113) Specifically, Table 1 shows needed quantities according to efficiency of the light emitting nanorods disposed in the respective sub-pixels SP1, SP2, and SP3 of the pixel PX.

(114) TABLE-US-00001 TABLE 1 Light SP1/ Light Panel Light Emitting SP2/ Emitting Required
Emitting Nanorod SP3 Nanorod Lumi- Nanorod Required Lumi- Required Required nance
Efficiency Current nance Quantity Current (nit) (Cd/A) (uA) Ratio Ratio Ratio First 16.2 4.7 0.49 1
2 1 sub- pixel SP1 Second 218.3 110 0.28 13 1 0.6 sub- pixel SP2 Third 68.1 3.3 2.93 4 10 6.0 sub-
pixel SP3

(115) Referring to Table 1, it could be confirmed that the efficiency of the light emitting nanorods is good in the order of the light emitting nanorods of the third sub-pixel SP3, the light emitting nanorods of the first sub-pixel SP1, and the light emitting nanorods of the second sub-pixel SP2. In addition, luminance and current required for each of the sub-pixels SP1, SP2, and SP3 can be entirely different. Accordingly, it could be confirmed that a ratio of the light emitting nanorods of the first sub-pixel SP1, the light emitting nanorods of the second sub-pixel SP2, and the light emitting nanorods of the third sub-pixel SP3 is appropriate when it is 2:1:10.

(116) In the second substrate **150** according to another exemplary embodiment of the present disclosure, the number of light emitting nanorods **170** can be configured differently in each of the sub-pixels SP1, SP2, and SP3 according to the efficiency of the light emitting nanorods **170** disposed in each of the sub-pixels SP1, SP2, and SP3. For example, since luminous efficiency of the light emitting nanorods of the third sub-pixel SP3 is the lowest, a size of the third sub-pixel SP3 in the pixel PX, the numbers of the plurality of first and second protrusions **161c** and **162c**, and the number of the plurality of light emitting nanorods **170** can be more increased compared to the other sub-pixels SP1 and SP2. In addition, since luminous efficiency of the light emitting nanorods of the

second sub-pixel SP2 is the best, the numbers of the plurality of first and second protrusions **161c** and **162c** of the second sub-pixel SP2 in the pixel PX and the number of the plurality of light emitting nanorods **170** can be more increased compared to the other sub-pixels SP1 and SP3.

(117) For example, the numbers of the plurality of first and second protrusions **161C** and **162c** and the number of the plurality of light emitting nanorods **170** can be adjusted so that the efficiency of each of the sub-pixels SP1, SP2, and SP3 is uniform in one pixel PX. Accordingly, the efficiency and quality of the display device **100** can be improved.

(118) The exemplary embodiments of the present disclosure can also be described as follows:

(119) According to an aspect of the present disclosure, a display device having a plurality of pixels each of which includes a plurality of sub-pixels, includes a first substrate; a plurality of first pads disposed on the first substrate in the plurality of sub-pixels; a common pad disposed on the first substrate and shared by the plurality of sub-pixels; a second substrate disposed to face the first substrate; a plurality of first electrodes disposed on the second substrate and connected to the plurality of first pads; a second electrode disposed on the second substrate and connected to the common pad; and a plurality of light emitting nanorods having one ends and the other ends respectively connected to the plurality of first electrodes and the second electrode. The plurality of first electrodes and/or the second electrode includes a plurality of protrusions connected to the plurality of light emitting nanorods.

(120) Each of the plurality of first electrodes can include a first portion and a pair of second portions extending from one end and the other end of the first portion. The second electrode can include a line electrode and a plurality of branch electrodes extending from the line electrode toward the plurality of first electrodes. Each of the plurality of branch electrodes can be disposed between the pair of second portions.

(121) The plurality of first electrodes can include the plurality of protrusions. The plurality of protrusions can protrude from the pair of second portions toward the plurality of branch electrodes. The plurality of protrusions can be formed to be narrower in width from the pair of second portions toward the plurality of branch electrodes.

(122) The second electrode can include the plurality of protrusions. The plurality of protrusions can protrude from the plurality of branch electrodes toward the pair of second portions. The plurality of protrusions can be formed to be narrower in width from the plurality of branch electrodes toward the pair of second portions.

(123) The plurality of protrusions can include a plurality of first protrusions protruding from the pair of second portions toward the plurality of branch electrodes; and a plurality of second protrusions protruding from the plurality of branch electrodes toward the pair of second portions.

(124) The plurality of first protrusions and the plurality of second protrusions can be disposed to be symmetrical to each other with respect to an imaginary straight line that is parallel to the plurality of branch electrodes or the pair of second portions.

(125) The plurality of first protrusions and the plurality of second protrusions can be disposed to be offset from each other based on an imaginary straight line that is parallel to the plurality of branch electrodes or the pair of second portions.

(126) Ends of the plurality of protrusions connected to the plurality of light emitting nanorods can have a pointed shape or a rounded shape.

(127) The plurality of sub-pixels can include a blue sub-pixel, a green sub-pixel, and a red sub-pixel. The number of the plurality of light emitting nanorods disposed in the red sub-pixel can be greater than the numbers of the plurality of light emitting nanorods disposed in the blue sub-pixel and the green sub-pixel.

(128) The display device can further include a plurality of dummy electrodes disposed on the second substrate to correspond to an outside of the plurality of pixels and spaced apart from the plurality of first electrodes and the second electrode.

(129) According to another aspect of the present disclosure, a display device having a plurality of

pixels each of which includes a plurality of sub-pixels, includes a first substrate and a second substrate facing each other; a plurality of first pads disposed on the first substrate in the plurality of sub-pixels; a common pad disposed on the first substrate and shared by the plurality of sub-pixels; a plurality of first electrodes disposed on the second substrate in the plurality of sub-pixels; a second electrode disposed on the second substrate and shared by the plurality of sub-pixels; a plurality of light emitting nanorods disposed on the second substrate in the plurality of sub-pixels and in contact with the plurality of first electrodes and the second electrode; and adhesive patterns connecting the plurality of first pads and the plurality of first electrodes and connecting the common pad and the second electrode. The plurality of first electrodes and/or the second electrode includes a plurality of protrusions connected to the plurality of light emitting nanorods.

(130) Each of the plurality of first electrodes can include a first portion and a pair of second portions extending from both ends of the first portion. The second electrode can include a line electrode and a plurality of branch electrodes extending from the line electrode toward the plurality of first electrodes. The plurality of branch electrodes can be surrounded by the plurality of first electrodes.

(131) The plurality of protrusions can include a plurality of first protrusions protruding from the pair of second portions toward the plurality of branch electrodes; and a plurality of second protrusions protruding from the plurality of branch electrodes toward the pair of second portions.

(132) The plurality of sub-pixels can include a blue sub-pixel, a green sub-pixel, and a red sub-pixel. The number of the plurality of light emitting nanorods disposed in the red sub-pixel can be greater than the numbers of the plurality of light emitting nanorods disposed in the blue sub-pixel and the green sub-pixel.

(133) According to yet another aspect of the present disclosure, a method of manufacturing a display device having a plurality of pixels each of which includes a plurality of sub-pixels, includes preparing a first substrate on which a plurality of first pads disposed in the plurality of sub-pixels and a common pad shared by the plurality of sub-pixels are disposed; forming a first electrode layer and a second electrode layer spaced apart from each other on a second substrate; self-aligning a plurality of light emitting nanorods by applying a direct current to the first electrode layer and the second electrode layer; separating the first electrode layer and the second electrode layer into a plurality of first electrodes and a second electrode, respectively, corresponding to the plurality of sub-pixels; and bonding the first substrate and the second substrate by connecting the plurality of first pads and the plurality of first electrodes and connecting the common pad and the second electrode. The plurality of light emitting nanorods are connected to a plurality of protrusions of the first electrode layer and/or the second electrode layer and are self-aligned.

(134) The plurality of sub-pixels can include a first sub-pixel, a second sub-pixel, and a third sub-pixel. The plurality of light emitting nanorods can include first light emitting nanorods, second light emitting nanorods, and third light emitting nanorods. The self-aligning of the plurality of light emitting nanorods can include self-aligning the first light emitting nanorods by injecting a first light emitting nanorod solution into an opening region on the first electrode layer and the second electrode layer corresponding to the first sub-pixel; self-aligning the second light emitting nanorods by injecting a second light emitting nanorod solution into an opening region on the first electrode layer and the second electrode layer corresponding to the second sub-pixel; and self-aligning the third light emitting nanorods by injecting a third light emitting nanorod solution into an opening region on the first electrode layer and the second electrode layer corresponding to the third sub-pixel. The first light emitting nanorod solution, the second light emitting nanorod solution and the third light emitting nanorod solution can be prepared by respectively mixing the plurality of first light emitting nanorods, the plurality of second light emitting nanorods and the plurality of third light emitting nanorods in a solvent, and the solvent can include any one of acetone, water, alcohol, and toluene.

(135) Each of the plurality of first electrodes can include a first portion and a pair of second

portions respectively extending from one side and the other side of the first portion. The second electrode can include a line electrode and a plurality of branch electrodes extending from the line electrode toward the plurality of first electrodes. Each of the plurality of branch electrodes can be disposed between the pair of second portions.

(136) The plurality of protrusions include a plurality of first protrusions protruding from the pair of second portions toward the plurality of branch electrodes; and a plurality of second protrusions protruding from the plurality of branch electrodes toward the pair of second portions.

(137) The plurality of sub-pixels can include a blue sub-pixel, a green sub-pixel, and a red sub-pixel. The number of the plurality of light emitting nanorods disposed in the red sub-pixel can be greater than the numbers of the plurality of light emitting nanorods disposed in the blue sub-pixel and the green sub-pixel.

(138) Although the exemplary embodiments of the present disclosure have been described in detail with reference to the accompanying drawings, the present disclosure is not limited thereto and can be embodied in many different forms without departing from the technical concept of the present disclosure. Therefore, the exemplary embodiments of the present disclosure are provided for illustrative purposes only but not intended to limit the technical concept of the present disclosure. The scope of the technical concept of the present disclosure is not limited thereto. Therefore, it should be understood that the above-described exemplary embodiments are illustrative in all aspects and do not limit the present disclosure. The protective scope of the present disclosure should be construed based on the following claims, and all the technical concepts in the equivalent scope thereof should be construed as falling within the scope of the present disclosure.

Claims

1. A display device having a plurality of pixels each including a plurality of sub-pixels, the display device comprising: a first substrate; a plurality of first pads disposed on the first substrate in the plurality of sub-pixels; a common pad disposed on the first substrate and shared by the plurality of sub-pixels; a second substrate disposed to face the first substrate; a plurality of first electrodes disposed under the second substrate and connected to the plurality of first pads; a second electrode disposed under the second substrate and connected to the common pad; and a plurality of light emitting nanorods having one ends and the other ends respectively and directly connected to the plurality of first electrodes and the second electrode, wherein the plurality of first electrodes and/or the second electrode includes a plurality of protrusions directly connected to the plurality of light emitting nanorods, and wherein uppermost surfaces of the plurality of first electrodes, the second electrode, and the plurality of light emitting nanorods are coplanar in a cross-section view of the display device.

2. The display device of claim 1, wherein each of the plurality of first electrodes includes a first portion and a pair of second portions extending from one end and the other end of the first portion, wherein the second electrode includes a line electrode and a plurality of branch electrodes extending from the line electrode toward the plurality of first electrodes, and wherein each of the plurality of branch electrodes is disposed between the pair of second portions.

3. The display device of claim 2, wherein the plurality of first electrodes include the plurality of protrusions, and wherein the plurality of protrusions protrude from the pair of second portions toward the plurality of branch electrodes.

4. The display device of claim 3, wherein the plurality of protrusions are formed to be narrower in width from the pair of second portions toward the plurality of branch electrodes.

5. The display device of claim 2, wherein the second electrode includes the plurality of protrusions, and wherein the plurality of protrusions protrude from the plurality of branch electrodes toward the pair of second portions.

6. The display device of claim 5, wherein the plurality of protrusions are formed to be narrower in

width from the plurality of branch electrodes toward the pair of second portions.

7. The display device of claim 2, wherein the plurality of protrusions include: a plurality of first protrusions protruding from the pair of second portions toward the plurality of branch electrodes; and a plurality of second protrusions protruding from the plurality of branch electrodes toward the pair of second portions.

8. The display device of claim 7, wherein the plurality of first protrusions and the plurality of second protrusions are disposed to be symmetrical to each other with respect to an imaginary straight line that is parallel to the plurality of branch electrodes or the pair of second portions.

9. The display device of claim 7, wherein the plurality of first protrusions and the plurality of second protrusions are disposed to be offset from each other based on an imaginary straight line that is parallel to the plurality of branch electrodes or the pair of second portions.

10. The display device of claim 1, wherein ends of the plurality of protrusions directly connected to the plurality of light emitting nanorods have a pointed shape or a rounded shape.

11. The display device of claim 1, wherein the plurality of sub-pixels include a blue sub-pixel, a green sub-pixel, and a red sub-pixel, and wherein the number of the plurality of light emitting nanorods disposed in the red sub-pixel is greater than the numbers of the plurality of light emitting nanorods disposed in the blue sub-pixel and the green sub-pixel.

12. The display device of claim 1, further comprising: a plurality of dummy electrodes disposed under the second substrate to correspond to an outside of the plurality of pixels and spaced apart from the plurality of first electrodes and the second electrode.

13. The display device of claim 1, wherein the plurality of protrusions have a shape that becomes narrower in going from the plurality of first electrodes and/or the second electrode towards the plurality of light emitting nanorods, respectively.

14. The display device of claim 1, wherein the plurality of protrusions have a triangular shape having vertices that contact the plurality of light emitting nanorods, respectively.

15. A display device having a plurality of pixels each including a plurality of sub-pixels, the display device comprising: a first substrate and a second substrate facing each other; a plurality of first pads disposed on the first substrate in the plurality of sub-pixels; a common pad disposed on the first substrate and shared by the plurality of sub-pixels; a plurality of first electrodes disposed under the second substrate in the plurality of sub-pixels; a second electrode disposed under the second substrate and shared by the plurality of sub-pixels; a plurality of light emitting nanorods disposed under the second substrate in the plurality of sub-pixels and in contact with the plurality of first electrodes and the second electrode; and a plurality of adhesive patterns connecting the plurality of first pads and the plurality of first electrodes and connecting the common pad and the second electrode, wherein the plurality of first electrodes and/or the second electrode includes a plurality of protrusions directly connected to the plurality of light emitting nanorods, and wherein uppermost surfaces of the plurality of first electrodes, the second electrode, and the plurality of light emitting nanorods are coplanar in a cross-section view of the display device.

16. The display device of claim 15, wherein each of the plurality of first electrodes include a first portion and a pair of second portions extending from both ends of the first portion, wherein the second electrode includes a line electrode and a plurality of branch electrodes extending from the line electrode toward the plurality of first electrodes, and wherein the plurality of branch electrodes are surrounded by the plurality of first electrodes.

17. The display device of claim 16, wherein the plurality of protrusions include: a plurality of first protrusions protruding from the pair of second portions toward the plurality of branch electrodes; and a plurality of second protrusions protruding from the plurality of branch electrodes toward the pair of second portions.

18. The display device of claim 15, wherein the plurality of sub-pixels include a blue sub-pixel, a green sub-pixel, and a red sub-pixel, and wherein the number of the plurality of light emitting nanorods disposed in the red sub-pixel is greater than the numbers of the plurality of light emitting

nanorods disposed in the blue sub-pixel and the green sub-pixel.

19. The display device of claim 15, wherein the plurality of protrusions have a shape that becomes narrower in going from the plurality of first electrodes and/or the second electrode towards the plurality of light emitting nanorods, respectively.

20. The display device of claim 15, wherein the plurality of protrusions have a triangular shape having vertices that contact the plurality of light emitting nanorods, respectively.
