

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413570
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Chen; Weigang et al.

Digital certificate obtaining method and apparatus

Abstract

A digital certificate obtaining method and apparatus. The method includes: a routing device receives a network access request sent by a terminal on the basis of a first virtual local area network, wherein the first virtual local area network is associated with a uniform resource locator (URL) of a server, so that the terminal obtains, by means of the server, a digital certificate used for accessing a second virtual local area network; and in response to the network access request sent by the terminal on the basis of the first virtual local area network, the routing device sends the URL of the server to the terminal, so that the terminal obtains the digital certificate from the server according to the URL.

Inventors:	Chen; Weigang (Shaanxi, CN), Li; Peng (Shaanxi, CN), Chen; Geng (Shaanxi, CN), Yan; Xiang (Shaanxi, CN), Zhang; Guoqiang (Shaanxi, CN)
Applicant:	CHINA IWNCOMM CO., LTD. (Shaanxi, CN)
Family ID:	79552728
Assignee:	CHINA IWNCOMM CO., LTD. (Shaanxi, CN)
Appl. No.:	18/011591
Filed (or PCT Filed):	May 20, 2021
PCT No.:	PCT/CN2021/094913
PCT Pub. No.:	WO2022/007510
PCT Pub. Date:	January 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230164135 A1	May. 25, 2023

Foreign Application Priority Data

CN

202010640522.3

Jul. 06, 2020

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC H04L63/0823 (20130101); H04L63/0272 (20130101);

Field of Classification Search

CPC: H04L (63/0272); H04L (63/0823); H04L (63/0281); H04L (63/20); H04L (67/02)

USPC: 726/12; 726/10; 726/2; 713/156

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6081900	12/1999	Subramaniam	713/153	H04L 63/0807
6360254	12/2001	Linden	707/E17.112	G06F 16/955
6640302	12/2002	Subramaniam	713/169	H04L 63/162
8166141	12/2011	Van Horne, III	709/225	H04L 67/02
8341717	12/2011	Delker et al.	N/A	N/A
9871722	12/2017	Ou	N/A	H04L 61/4511
2003/0074555	12/2002	Fahn	713/156	H04L 9/3263
2004/0117493	12/2003	Bazot	709/229	H04L 63/0884
2006/0036850	12/2005	Enokida	713/156	H04L 63/0869
2006/0271707	12/2005	Cheline	709/245	H04L 63/0823
2010/0242105	12/2009	Harris	709/229	H04L 63/105
2015/0334110	12/2014	Bishop	713/156	H04L 63/0272
2017/0012780	12/2016	Kaliski, Jr.	N/A	H04L 9/3247
2017/0012941	12/2016	Subbarayan	N/A	H04L 67/10
2017/0244577	12/2016	Patrick	N/A	H04L 12/2801
2017/0353496	12/2016	Pai	N/A	H04L 63/10
2017/0366636	12/2016	Wang	N/A	H04L 63/166
2018/0048624	12/2017	Fok	N/A	H04L 63/0272
2021/0319868	12/2020	Whitaker	N/A	G16H 10/60

OTHER PUBLICATIONS

NPL Search Terms (Year: 2024). cited by examiner

NPL Search Terms (Year: 2025). cited by examiner

ISR dated Aug. 4, 2021 for PCT/CN2021/094913. cited by applicant

Primary Examiner: Zaidi; Syed A

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) The present disclosure is a National Stage of International Application No. PCT/CN2021/094913, filed on May 20, 2021, which claims priority to Chinese Patent Application No. 202010640522.3 filed on Jul. 6, 2020 and entitled “DIGITAL CERTIFICATE OBTAINING METHOD AND APPARATUS”, the entire contents of which are incorporated herein by reference.

FIELD

(2) The present disclosure relates to the technical field of communication, in particular to a digital certificate obtaining method and apparatus.

BACKGROUND

(3) A digital certificate refers to a digital authentication that marks the identity information of parties communicating in an Internet communication to identify the identity of the other party. The digital certificate is also referred to as a digital identification. The digital certificate supports the integrity and security of information and data of network users in computer network communication.

(4) Currently, network access based on wireless LAN authentication and privacy infrastructure (WAPI) and WiFi has employed the digital certificate to ensure the security of network access (commonly referred to as “surfing the internet”), which is referred to as a certificate model. The certificate mode is a mode with the highest level of security currently available for smart devices to opt when wireless network access is performed.

SUMMARY

(5) In a first aspect, an embodiment of the present disclosure provides a digital certificate obtaining method, including: receiving, by a routing device, a network access request sent by a terminal based on a first virtual local area network, wherein the first virtual local area network is associated with a Uniform Resource Locator (URL) of a server such that the terminal obtains a digital certificate for accessing a second virtual local area network by the server; and sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network such that the terminal obtains the digital certificate from the server according to the URL.

(6) In an embodiment of the present disclosure, the method further includes: receiving, by the routing device, a network access request sent by the terminal based on the second virtual local area network; and performing, by the routing device, digital certificate authentication with the terminal according to the network access request sent by the terminal based on the second virtual local area network, and establishing a network connection with the terminal after the authentication passes.

(7) In the embodiment of the present disclosure, sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, includes: sending a DNS resolution response to the terminal after a proxy Domain Name System (DNS) service in the routing device receives a DNS resolution request sent by the terminal based on the first virtual local area network, the DNS resolution response carrying an IP address of a proxy WEB service in the routing device; and receiving, by the proxy WEB service in the routing device, a network access request sent by the terminal according to the IP address of the proxy WEB service and based on the first virtual local area network, and sending redirection information carrying the URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

(8) In an embodiment of the present disclosure, sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, includes: sending the redirection information carrying the URL of the server to the terminal after the proxy DNS service in the routing device receives the DNS resolution request sent by the terminal based on the first virtual local area network, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

(9) In an embodiment of the present disclosure, the routing device is configured with a first service set identification and a second service set identification, wherein the first service set identification is configured to identify the first virtual local area network and the second service set identification is configured to identify the second virtual local area network.

(10) In a second aspect, an embodiment of the present disclosure provides a routing device including: a receiving module, configured to receive a network access request sent by a terminal based on a first virtual local area network, wherein the first virtual local area network is associated with a URL of a server such that the terminal obtains a digital certificate for accessing a second virtual local area network by the server; and a processing module, configured to send the URL of the server to the terminal in response to the network access request initiated based on the first virtual local area network such that the terminal obtains the digital certificate from the server according to the URL.

(11) In an embodiment of the present disclosure, the receiving module is further configured to receive a network access request sent by the terminal based on the second virtual local area network; and the processing module is further configured to perform digital certificate authentication with the terminal according to the network access request sent by the terminal based on the second virtual local area network, and establish a network connection with the terminal after the authentication passes.

(12) In an embodiment of the present disclosure, the processing module includes a proxy DNS service module and a proxy WEB service module; the proxy DNS service module is configured to, after receiving a DNS resolution request sent by the terminal based on the first virtual local area network, send a DNS resolution response to the terminal, the DNS resolution response carrying an IP address of the proxy WEB service module; and the proxy WEB service module is configured to receive a network access request sent by the terminal according to the IP address of the proxy WEB service and based on the first virtual local area network, and send redirection information carrying the URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

(13) In an embodiment of the present disclosure, the processing module includes a proxy DNS service module; and the proxy DNS service module is configured to, after receiving a DNS resolution request sent by the terminal based on the first virtual local area network, send the redirection information carrying the URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

(14) In an embodiment of the present disclosure, the routing device is configured with a first service set identification and a second service set identification, wherein the first service set identification is configured to identify the first virtual local area network and the second service set identification is configured to identify the second virtual local area network.

(15) In a third aspect, an embodiment of the present disclosure provides a routing device including a processor, a memory, and a communication interface; the communication interface receives and sends data under the control of the processor; the memory stores computer instructions; and the processor is configured to read the computer instructions to perform the method in the first aspect.

(16) In a fourth aspect, the present disclosure provides a computer-readable storage medium storing computer-executable instructions, wherein the computer-executable instructions are configured to enable a computer to perform any method in the first aspect.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order to more clearly illustrate the embodiments of the present disclosure or the technical solutions in the related art, the drawings required for the embodiments or the description of the prior art are simply introduced, and it will be apparent that the drawings in the following description are some embodiments of the present disclosure and that those of ordinary skill in the art can obtain other drawings according to these drawings without inventive effort.
- (2) FIG. 1 exemplarily shows a schematic diagram of an application scenario provided by an embodiment of the present disclosure;
- (3) FIG. 2 exemplarily shows a schematic structural diagram of a routing device provided by an embodiment of the present disclosure;
- (4) FIG. 3 exemplarily shows a flow chart of a network access method provided by an embodiment of the present disclosure;
- (5) FIG. 4 exemplarily shows a flow chart of obtaining a digital certificate provided by an embodiment of the present disclosure;
- (6) FIG. 5 exemplarily shows a flow chart of obtaining a digital certificate provided by an embodiment of the present disclosure;
- (7) FIG. 6 exemplarily shows a schematic structural diagram of a routing device provided by an embodiment of the present disclosure; and
- (8) FIG. 7 exemplarily shows a schematic structural diagram of a routing device provided by an embodiment of the present disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (9) In order to make the objectives, technical solutions and advantages of the present disclosure will become more apparent, the present disclosure will be further described in detail below with reference to the drawings, and it will be apparent that the described embodiments are only some, but not all, embodiments of the present disclosure. Based on the embodiments in the present disclosure, all other embodiments obtained by those of ordinary skill in the art without making inventive effort fall within the scope of protection of the present disclosure.
- (10) Hereafter, the terms “first” and “second” are only used for differential description and cannot be understood as implying relative importance or implicitly indicating the number of the indicated technical feature. Thus, features defined as “first” and “second” may either explicitly or implicitly include one or more such features, and in the description of the embodiments of the present disclosure, “at least one” means one or more than one, unless otherwise stated.
- (11) When a digital certificate-based security mechanism is applied, a digital certificate needs to be installed for a terminal.
- (12) In the civilian field, the general digital certificate obtaining and installing processes are as follows: a user accesses the Internet by the terminal (e.g., by a wired local area network (LAN) or by dialing, or other manners) to log in a server, various pieces of information required to apply the digital certificate are input to a digital certificate application interface provided by the server, and a digital certificate file is downloaded and stored for manual installation. The above digital certificate application method requires the user to know a domain name or an IP address of the server in advance and to be familiar with the application flow of the digital certificate, which is cumbersome to operate.
- (13) In the field of industry/enterprise users, a digital certificate is generally configured by a network administrator via a certificate server for an industry/enterprise user or employee, and then is issued to the industry/enterprise user or employee for certificate installation via email, short messages, or the copy of a mobile memory (e.g., USB), resulting in tedious and error-prone process, and low efficiency.

(14) To address the above problems, an embodiment of the present disclosure provides a digital certificate obtaining method. In the method, a first virtual local area network is arranged in a routing device in advance, and is associated with a URL pointing to a server for providing a digital certificate. When a user initiates a network access request by a first virtual local area network, the request is redirected to a server corresponding to the URL, so that the terminal can download and is equipped with a digital certificate for accessing a second virtual local area network by the server, thereby performing network access by the second virtual local area network. In the above process, a user does not need to memorize or obtain a domain name or an address of a server, so as to eliminate manual operation by a network administrator or the like, thereby simplifying and facilitating the obtaining and use operations of the digital certificate, and improving the user experience.

(15) Embodiments of the present disclosure are described in detail below in conjunction with the drawings.

(16) FIG. 1 exemplarily shows a schematic diagram of an application scenario provided by an embodiment of the present disclosure. As shown in FIG. 1, the scenario includes a terminal **100a** and a terminal **100b**, and the terminals (**100a**, **100b**) are connected with a routing device **200** in a wireless or wired manner. The routing device **200** is connected with a server **300** by a network **400**.

(17) The terminals (**100a**, **100b**) may be various forms of user devices, such as a mobile station (MS for short) and a terminal device. Some terminals are, for example, a mobile phone, a tablet computer, a laptop, a palmtop, a mobile internet device (MID), a wearable device, a wireless terminal in self-driving, a wireless terminal in a smart grid, a wireless terminal in a smart home, etc.

(18) The routing device **200** is primarily configured to provide network access, and specifically may be an access router, an enterprise class router, a home router, or other network devices having a routing function.

(19) The server **300** may be an enterprise class server, a public network server, or the like, and is configured to provide a digital certificate service for a user to obtain a digital certificate.

(20) The network **400** may be the Internet, and correspondingly, the server **300** is a server of a digital certificate authority, which may provide a digital certificate application service for public users. The network **400** may also be a local area network, such as an enterprise local area network, and correspondingly, the server **300** may be an enterprise class server (for example, an IP address of the enterprise class server is <http://192.168.1.1>), which may provide a digital certificate application service for users within the enterprise local area network. The applied digital certificate is a digital certificate within the enterprise, and may correspond to an identity for identifying a network user within the enterprise.

(21) In some embodiments, the server **300** may also be directly connected with or integrated in the routing device **200**.

(22) In an embodiment of the present disclosure, a first virtual local area network is set in the routing device **200** in advance, and is associated with a URL pointing to the server **300**, which redirects the access request to the server **300** to guide the user to complete the digital certificate obtaining operation when the terminals (**100a**, **100b**) perform network access based on the first virtual local area network.

(23) FIG. 2 exemplarily shows a schematic diagram of configuration of a virtual local area network in a routing device **200** provided by an embodiment of the present disclosure. As shown in FIG. 2, VLAN1 (first virtual local area network), VLAN2 (second virtual local area network), service set identification SSID1, and service set identification SSID2 are configured on the routing device **200**. SSID1 is configured to identify VLAN1, and the network of SSID1 is VLAN1. SSID2 is configured to identify VLAN2, and the network of SSID2 is VLAN2.

(24) VLAN1 is configured as an access method without digital certificate authentication, for example, an access method of clicking on SSID and then entering passwords, or an access method

of no entry of passwords after clicking on SSID, which is generally used when a smartphone accesses a wireless local area network; and VLAN2 is configured as an access method with digital certificate authentication.

(25) VLAN1 is associated with a URL of the server 300 for providing the digital certificate to redirect network access initiated based on VLAN1 to the server 300, so that the terminal can download the digital certificate by the server 300. The digital certificate is a certificate that enables the terminals (100a, 100b) to access VLAN2.

(26) After the digital certificate is installed, the terminals (100a, 100b) may access VLAN2 by the digital certificate to perform normal network access.

(27) FIG. 3 exemplarily shows a flow chart of a network access method provided by an embodiment of the present disclosure according to a schematic structural diagram of the routing device 200 as shown in FIG. 2. As shown in FIG. 3, the process mainly includes the following steps.

(28) S301: The routing device 200 receives a network access request initiated by a terminal based on VLAN1.

(29) VLAN1 is associated with the URL of the server such that the terminal obtains a digital certificate for accessing VLAN2 by the server.

(30) In this step, at the terminal side, the terminal obtains an SSID list of the routing device, in which SSID1 and SSID2 are included, wherein SSID1 is an identity of VLAN1 and SSID2 is an identity of VLAN2. SSID1 in the SSID list is triggered to select corresponding VLAN1 (e.g., the user clicks on SSID1 in the SSID list by a touch screen of the terminal, or a SSID1 is automatically selected by an application (APP) on the terminal) such that the terminal accesses to VLAN1 corresponding to SSID1.

(31) In some application scenarios, a browser on a terminal is opened actively (e.g., a terminal program is automatically opened) or opened passively (e.g., a user opens the browser), and the browser actively or passively sends a network access request to the routing device 200. Currently, most smartphones automatically submit network access requests to routing devices by means of browsers, that is, the so-called active submission of network access requests. Other terminal devices may still need to manually enter a string (e.g., xxx.com, yyy.org, etc.) that conforms to a domain name format in the browser to trigger the terminal to send a network access request by the browser to the routing device 200, that is, the so-called passive submission of network access requests.

(32) S302: the routing device 200 sends the URL of the server 300 to the terminal in response to the network access request sent by the terminal based on VLAN1, such that the terminal obtains a digital certificate from the server 300 according to the URL.

(33) In this step, the routing device 200 may confirm that the network access request is sent based on VLAN1 according to identification of SSID1. In response to the network access request, the routing device 200 feeds back a URL of the server 300 associated with VLAN1 to the terminal, such that the terminal accesses the server 300 corresponding to the URL by the browser.

(34) In the embodiment, for the network access request for any domain name (a string conforming to the domain name format) sent by the terminal, the routing device may feed back the URL of the server 300 associated with VLAN1 to the terminal for response, such that the terminal accesses the server 300 corresponding to the URL.

(35) S303: the terminal performs an application operation for the digital certificate by the server 300.

(36) In this step, at the terminal side, the user may click on a “download” function option based on a prompt from a digital certificate application interface provided by the server 300, and select a local storage path for the digital certificate based on the prompt. After downloading is completed, the user clicks on an “install” function option and selects a local installation path for the digital certificate to install the digital certificate at the terminal.

(37) In other embodiments, for example, a digital certificate download page may provide a method for downloading and installing the digital certificate, for example, may provide an instruction document containing a download address and an installation process of the digital certificate, and at the terminal side, the user downloads and installs the digital certificate according to the instruction document.

(38) The terminal may, after obtaining the digital certificate, initiate a network access process based on VLAN2 using the digital certificate when network access is required, which specifically includes the following steps.

(39) **S304**: the routing device **200** receives a network access request initiated by the terminal based on VLAN2.

(40) In this step, SSID2 in the SSID list of the terminal is triggered (e.g., the user clicks on SSID2, or an APP on the terminal automatically selects SSID2), such that the terminal accesses VLAN2. The terminal is able to access VLAN2 because the digital certificate installed at the terminal is the certificate to access VLAN2.

(41) The routing device **200** performs digital certificate authentication with the terminal and establishes a network connection with the terminal after the authentication passes, thereby achieving general network access.

(42) The digital certificate generally has a validity period during which the terminal may not repeat the downloading and installing process of the **S301-S303**, and directly performs the network access process of the **S304**. When the user performs network access by the terminal within a preset number of days before expiration of the validity period of the digital certificate, an APP user interface on the terminal may provide prompt information to update the digital certificate, such that the user updates the digital certificate according to the prompt information. If the digital certificate is not updated before expiration, the terminal cannot perform network access, and performs the digital certificate obtaining process of the **S301-S303** again.

(43) The above steps **S301** to **S303** are the digital certificate obtaining process, the routing device **200** redirects the access request sent by the terminal to the server **300** based on VLAN1, such that the user can download and install the digital certificate without needing to memorize the IP address of the server, thereby simplifying the operation of obtaining the digital certificate by the user.

(44) In some embodiments, the routing device **200** and the server **300** may be integrated in an apparatus having the same function as the routing device **200** and the server **300** deployed independently.

(45) In some embodiments, the routing device may include a proxy DNS service and a proxy WEB service, and the network access request of the terminal may be redirected to the server by the proxy DNS service and the proxy WEB service. The process may be as shown in FIG. 4.

(46) FIG. 4 exemplarily shows a flow chart of redirection of a network access request provided by an embodiment of the present disclosure. As shown in FIG. 4, the process includes the following several steps: **S401**: the terminal selects SSID1 to access VLAN1 according to the SSID list provided by the routing device **200**, and receives a domain name address entered by the user or automatically generated by a terminal program; **S402**: the terminal sends a DNS resolution request based on VLAN1 to the routing device **200**, wherein the request is submitted to the proxy DNS service for processing; **S403**: the proxy DNS service in the routing device **200** may, after receiving the DNS resolution request, send a DNS resolution response to the terminal, the DNS resolution response carrying an IP address of the proxy WEB service; **S404**: the terminal sends a hypertext transfer protocol (HTTP) access request to the routing device **200** according to the IP address of the proxy WEB service, wherein the HTTP access request is submitted to the proxy WEB service for processing; **S405**: the proxy WEB service in the routing device **200**, in response to the HTTP access request, sends redirection information carrying the URL of the server **300** to the terminal, wherein the server **300** is configured to cause the terminal to obtain a digital certificate for accessing VLAN2; and **S406**: the terminal sends the HTTP access request to the corresponding

server **300** according to the URL, to complete the digital certificate obtaining operation by accessing the server **300**.

(47) In some embodiments, when the server **300** is a server that provides a digital certificate of a public network, the server **300** may be accessed by translating a source IP address of the terminal to an IP address of the public network by source network address translation (SNAT); and when server **300** is a server that provides an internal network digital certificate, no SNAT is required.

(48) In the above embodiments of the present disclosure, in the **S402**, the DNS resolution request sent by the terminal may include a domain name entered by the user and some other parameters; in the **S403**, these parameters may be included in the DNS resolution response returned to the terminal by the proxy DNS access; in the **S404**, the proxy WEB service can normalize the domain name address entered by the user and remove unnecessary parameters, so that the server can ensure a correct response to the received request (in most cases, servers in the market can handle unnecessary parameters in the domain name to make a correct response to received access requests; however, in a few cases, there are servers that cannot handle unnecessary parameters in the domain name, resulting in the received access request being considered as an erroneous request, thereby feeding back the error to the terminal, e.g., **404** error, etc.).

(49) In further embodiments of the present disclosure, the routing device may include the proxy DNS service by which the network access request of the terminal is redirected to the server **300**. The process may be as shown in FIG. 5.

(50) FIG. 5 exemplarily shows a flow chart of obtaining a digital certificate provided by an embodiment of the present disclosure. As shown in FIG. 5, the process includes the following steps: **S501**: the terminal selects SSID1 to access VLAN1 according to the SSID list provided by the routing device **200**, and receives a domain name address entered by the user or automatically generated by a terminal program; **S502**: the terminal sends a DNS resolution request based on VLAN1 to the routing device **200**, wherein the request is submitted to the proxy DNS service for processing; **S503**: the proxy DNS service in the routing device **200** may, after receiving the DNS resolution request, send redirection information of a URL carrying the server **300** to the terminal, wherein the server **300** is configured to cause the terminal to obtain a digital certificate for accessing VLAN2; and **S504**: the terminal sends a HTTP access request to the corresponding server **300** according to the URL, thereby completing the digital certificate obtaining operation by the server **300**.

(51) In embodiments of the present disclosure, the routing device is internally configured with VLAN1 and VLAN2, wherein VLAN1 is associated with the URL of the server configured to provide the digital certificate that enables the terminal to access VLAN2. When the terminal accesses VLAN1, the browser of the terminal submits the network access request to the routing device **200** which redirects the network access request to the server associated with VLAN1, such that the terminal obtains the digital certificate from the server. When the user needs network access, the network access request may be initiated based on VLAN2 for normal network access. The user does not need to memorize or obtain the domain name or address of the server, so that the difficulty of obtaining the digital certificate is reduced, the digital certificate obtaining operation is simplified, and the user experience is improved.

(52) Based on the same technical concept, an embodiment of the present disclosure also provides a routing device that can realize the functions of the routing device in the foregoing embodiments.

(53) FIG. 6 exemplarily shows a structure of a routing device in an embodiment of the present disclosure. As shown FIG. 6, the routing device may include a receiving module **601**, and a processing module **602**.

(54) The receiving module **601** is configured to receive a network access request sent by a terminal based on a first virtual local area network, wherein the first virtual local area network is associated with a URL of a server such that the terminal obtains a digital certificate for accessing a second virtual local area network by the server.

(55) The processing module **602** is configured to send the URL of the server to the terminal in response to the network access request initiated by the terminal based on the first virtual local area network such that the terminal obtains the digital certificate from the server according to the URL.

(56) In some embodiments of the present disclosure, the receiving module **601** is further configured to receive a network access request initiated by the terminal based on the second virtual local area network; and the processing module **602** is further configured to perform digital certificate authentication with the terminal according to the network access request sent by the terminal based on the second virtual local area network, and establish a network connection with the terminal after the authentication passes.

(57) In some embodiments of the present disclosure, the processing module includes a proxy DNS service module **6021** and a proxy WEB service module **6022**.

(58) The proxy DNS service module **6021** is configured to, after receiving a DNS resolution request sent by the terminal based on the first virtual local area network, send a DNS resolution response to the terminal, the DNS resolution response carrying an IP address of the proxy WEB service module; and the proxy WEB service module **6022** is configured to receive a network access request sent by the terminal according to the IP address of the proxy WEB service and based on the first virtual local area network, and send redirection information carrying the URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

(59) In some embodiments of the present disclosure, the processing module includes a proxy DNS service module **6021**; and the proxy DNS service module **6021** is further configured to, after receiving the DNS resolution request sent by the terminal based on the first virtual local area network, send redirection information carrying a URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

(60) In some embodiments of the present disclosure, the routing device is configured with a first service set identification and a second service set identification, wherein the first service set identification is configured to identify the first virtual local area network and the second service set identification is configured to identify the second virtual local area network.

(61) It should be noted that the above routing device provided by embodiments of the present disclosure can implement all the method steps implemented by the embodiments of the above method and achieve the same technical effects. Parts and advantages of the embodiment, which are same as those of the method embodiments are not described in detail here.

(62) Based on the same technical concept, an embodiment of the present disclosure also provides a routing device that can realize the functions of the routing device in the foregoing embodiments.

(63) FIG. 7 exemplarily shows a schematic structural diagram of a routing device in an embodiment of the present disclosure. As shown in FIG. 7, the routing device may include a processor **701**, a memory **702**, a communication interface **703**, and a bus interface **704**.

(64) The processor **701** is responsible for managing a bus architecture and processing generally, and the memory **702** can store data used by the processor **701** in performing operations. The communication interface **703** is configured to receive and send data under the control of the processor **701**.

(65) The bus architecture may include any quantity of interconnecting buses and bridges, specifically, various circuits of one or more processors, represented by the processor **701**, and a memory represented by the memory **702** are linked together. The bus architecture may also link various other circuits such as peripherals, voltage regulators and power management circuits, which are well known in the art, and therefore, will not be further described herein. The bus interface provides an interface. The processor **701** is responsible for managing the bus architecture and processing generally, and the memory **702** can store data used by the processor **701** in performing operations.

(66) The processes disclosed in embodiments of the present disclosure may be applied to or implemented by the processor **701**. In the implementation process, the various steps of the signal processing flow may be completed by integrated logic circuitry of hardware or instructions in the form software in the processor **701**. The processor **701** may be a general purpose processor, a digital signal processor, an application specific integrated circuit, a field programmable gate array or other programmable logic device, a discrete gate or a transistor logic device, a discrete hardware component, which may implement or perform the methods, steps, and logical block diagrams disclosed in the embodiments of the present disclosure. The general purpose processor may be a microprocessor or any conventional processor or the like. The steps of the method disclosed in connection with the embodiments of the present disclosure may be embodied directly as a hardware processor, or performed by a combination of hardware and software modules in the processor. The software module may be located in a storage medium in the art, such as a random access memory, a flash memory, a read-only memory, a programmable read-only memory, or an electrically erasable programmable memory and a register. The storage medium is located in the memory **702**, and the processor **701** reads information from the memory **702**, and in conjunction with its hardware, completes the steps of the signal processing flow. In some embodiments, the processor **701** is configured to read computer instructions in the memory **702** and execute the functions implemented at the terminal side in the flows as shown in FIG. 3.

(67) In some embodiments, the processor **701** may read computer instructions in the memory **702** to perform the following operations: receiving, by a routing device, a network access request sent by the terminal based on the first virtual local area network, wherein the first virtual local area network is associated with a URL of a server such that the terminal can obtain a digital certificate for accessing a second virtual local area network by the server; and sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network such that the terminal obtains the digital certificate from the server according to the URL.

(68) In an embodiment of the present disclosure, the operations performed by the processor further include: receiving a network access request sent by the terminal based on the second virtual local area network; performing, according to the network access request initiated by the terminal based on the second virtual local area network, digital certificate authentication by the routing device with the terminal, and establishing a network connection with the terminal after the authentication passes.

(69) It should be noted that the above routing device provided by embodiments of the present disclosure can implement all the method steps implemented by embodiments of the above method and achieve the same technical effects. Parts and advantages of the embodiment, which are same as those of the method embodiments are not described in detail here.

(70) An embodiment of the present disclosure also provides a non-transitory computer-readable storage medium storing computer-executable instructions, wherein the computer-executable instructions are configured to enable a computer to perform the method performed by the routing device in the above embodiments.

(71) Those skilled in the art should understand that the embodiments of the present disclosure may be provided as a method, system, or computer program product. Accordingly, the present disclosure may take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment combining software and hardware aspects. Furthermore, the present disclosure may take the form of a computer program product implemented on one or more computer available storage media (including but not limited to disc storage, CD-ROM, optical memory, etc.) including computer available program codes.

(72) The present disclosure is described with reference to flow charts and/or block diagrams of the method, device (system) and computer program products according to the present disclosure. It should be understood that each flow and/or block in the flow chart and/or block diagrams, and

combinations of the flows and/or blocks in the flow chart and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a general purpose computer, a special purpose computer, an embedded processing machine, or a processor of other programmable data processing device to produce a machine, such that the instructions executed by the processor of the computer or other programmable data processing device produce an apparatus for implementing the functions specified in one or more flows of the flow charts and/or one or more blocks of the block diagrams.

(73) These computer program instructions may also be stored in a computer-readable memory that can guide the computer or other programmable data processing device to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article of manufacture including an instruction apparatus which implements the functions specified in one or more flows of the flow chart and/or one or more blocks of the block diagrams.

(74) These computer program instructions may also be loaded onto a computer or other programmable data processing device, a series of operation steps are caused performed on the computer or other programmable device to produce a computer-implemented process such that the instructions which are executed on the computer or other programmable device provide steps for implementing the functions specified in one or more flows of the flow chart and/or one or more blocks of the block diagrams.

Claims

1. A digital certificate obtaining method, comprising: receiving, by a routing device, a network access request sent by a terminal based on a first virtual local area network, wherein the first virtual local area network is associated with a Uniform Resource Locator (URL) of a server such that the terminal obtains a digital certificate for accessing a second virtual local area network by the server; sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network such that the terminal obtains the digital certificate from the server according to the URL.
2. The method according to claim 1, further comprising: receiving, by the routing device, a network access request sent by the terminal based on the second virtual local area network; performing, by the routing device, a digital certificate authentication with the terminal according to the network access request sent by the terminal based on the second virtual local area network, and establishing a network connection with the terminal after the authentication passes.
3. The method according to claim 2, wherein the routing device is configured with a first service set identification and a second service set identification, the first service set identification being configured to identify the first virtual local area network and the second service set identification being configured to identify the second virtual local area network.
4. The method according to claim 1, wherein the sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, comprises: sending a DNS resolution response to the terminal after a proxy domain name system (DNS) service in the routing device receives a DNS resolution request sent by the terminal based on the first virtual local area network, the DNS resolution response carrying an IP address of a proxy WEB service in the routing device; and receiving, by the proxy WEB service, a network access request sent by the terminal according to the IP address of the proxy WEB service and based on the first virtual local area network, and sending redirection information carrying the URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.
5. The method according to claim 4, wherein the routing device is configured with a first service set identification and a second service set identification, the first service set identification being configured to identify the first virtual local area network and the second service set identification

being configured to identify the second virtual local area network.

6. The method according to claim 1, wherein the sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, comprises: sending the redirection information carrying the URL of the server to the terminal after the proxy DNS service in the routing device receives the DNS resolution request sent by the terminal based on the first virtual local area network, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

7. The method according to claim 6, wherein the routing device is configured with a first service set identification and a second service set identification, the first service set identification being configured to identify the first virtual local area network and the second service set identification being configured to identify the second virtual local area network.

8. The method according to claim 1, wherein the routing device is configured with a first service set identification and a second service set identification, the first service set identification being configured to identify the first virtual local area network and the second service set identification being configured to identify the second virtual local area network.

9. A routing device, comprising a processor, a memory, and a communication interface; wherein the communication interface receives and sends data under control of the processor; the memory stores computer instructions; and the processor is configured to read the computer instructions to perform followings: receiving a network access request sent by a terminal based on a first virtual local area network, wherein the first virtual local area network is associated with a Uniform Resource Locator (URL) of a server such that the terminal obtains a digital certificate for accessing a second virtual local area network by the server; sending the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network such that the terminal obtains the digital certificate from the server according to the URL.

10. The routing device according to claim 9, wherein the processor is further configured to read the computer instructions to perform followings: receiving a network access request sent by the terminal based on the second virtual local area network; performing a digital certificate authentication with the terminal according to the network access request sent by the terminal based on the second virtual local area network, and establishing a network connection with the terminal after the authentication passes.

11. The routing device according to claim 9, wherein the processor is configured to read the computer instructions to send the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, by: sending a DNS resolution response to the terminal after a proxy domain name system (DNS) service in the routing device receives a DNS resolution request sent by the terminal based on the first virtual local area network, the DNS resolution response carrying an IP address of a proxy WEB service in the routing device; and receiving, by the proxy WEB service, a network access request sent by the terminal according to the IP address of the proxy WEB service and based on the first virtual local area network, and sending redirection information carrying the URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

12. The routing device according to claim 9, wherein the processor is configured to read the computer instructions to send the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, by: sending the redirection information carrying the URL of the server to the terminal after the proxy DNS service in the routing device receives the DNS resolution request sent by the terminal based on the first virtual local area network, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

13. The routing device according to claim 9, wherein the routing device is configured with a first

service set identification and a second service set identification, the first service set identification being configured to identify the first virtual local area network and the second service set identification being configured to identify the second virtual local area network.

14. A non-transitory computer-readable storage medium storing computer-executable instructions, wherein the computer-executable instructions are configured to enable a computer to perform a digital certificate obtaining method, wherein the digital certificate obtaining method comprises: receiving, by a routing device, a network access request sent by a terminal based on a first virtual local area network, wherein the first virtual local area network is associated with a Uniform Resource Locator (URL) of a server such that the terminal obtains a digital certificate for accessing a second virtual local area network by the server; sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network such that the terminal obtains the digital certificate from the server according to the URL.

15. The non-transitory computer-readable storage medium storing computer-executable instructions according to claim 14, wherein the computer-executable instructions are configured to enable a computer to perform followings: receiving, by the routing device, a network access request sent by the terminal based on the second virtual local area network; performing, by the routing device, a digital certificate authentication with the terminal according to the network access request sent by the terminal based on the second virtual local area network, and establishing a network connection with the terminal after the authentication passes.

16. The non-transitory computer-readable storage medium storing computer-executable instructions according to claim 14, wherein the sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, comprises: sending a DNS resolution response to the terminal after a proxy domain name system (DNS) service in the routing device receives a DNS resolution request sent by the terminal based on the first virtual local area network, the DNS resolution response carrying an IP address of a proxy WEB service in the routing device; and receiving, by the proxy WEB service, a network access request sent by the terminal according to the IP address of the proxy WEB service and based on the first virtual local area network, and sending redirection information carrying the URL of the server to the terminal, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

17. The non-transitory computer-readable storage medium storing computer-executable instructions according to 14, wherein the sending, by the routing device, the URL of the server to the terminal in response to the network access request sent by the terminal based on the first virtual local area network, comprises: sending the redirection information carrying the URL of the server to the terminal after the proxy DNS service in the routing device receives the DNS resolution request sent by the terminal based on the first virtual local area network, wherein the server enables the terminal to obtain a digital certificate for accessing the second virtual local area network.

18. The non-transitory computer-readable storage medium storing computer-executable instructions according to claim 14, wherein the routing device is configured with a first service set identification and a second service set identification, the first service set identification being configured to identify the first virtual local area network and the second service set identification being configured to identify the second virtual local area network.
