

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414437
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Wang; Lei et al.

Display module, display, and terminal

Abstract

A display system includes a substrate, a plurality of first signal lines and a plurality of second signal lines. The second signal lines and the first signal lines are extended in a same direction and are insulated from each other. At least one first subpixel array is also disposed on the substrate. A first signal line group is disposed between adjacent rows of subpixels in the first subpixel array, and the first signal line group includes one first signal line and one second signal line. The first signal line and the second signal line in at least one first signal line group on the substrate overlap in a region having a transparent subpixel.

Inventors:	Wang; Lei (Dongguan, CN), Pan; Liangyu (Dongguan, CN), Dong; Yujie (Dongguan, CN), Zhang; Rui (Wuhan, CN), Yan; Yuan (Shenzhen, CN), Li; Haiyan (Shenzhen, CN)
Applicant:	Huawei Technologies Co., Ltd. (Shenzhen, CN)
Family ID:	79272941
Assignee:	HUAWEI TECHNOLOGIES CO., LTD. (Shenzhen, CN)
Appl. No.:	18/003632
Filed (or PCT Filed):	March 19, 2021
PCT No.:	PCT/CN2021/081850
PCT Pub. No.:	WO2022/001208
PCT Pub. Date:	January 06, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230263021 A1	Aug. 17, 2023

Foreign Application Priority Data

CN

202010605443.9

Jun. 29, 2020

Publication Classification

Int. Cl.: H10K59/121 (20230101); H04M1/02 (20060101); H10K59/131 (20230101); H10K59/35 (20230101); H10K59/65 (20230101); H10K59/80 (20230101)

U.S. Cl.:

CPC H10K59/121 (20230201); H04M1/0264 (20130101); H10K59/353 (20230201); H10K59/65 (20230201); H10K59/875 (20230201); H10K59/131 (20230201)

Field of Classification Search

CPC: H10K (59/121); H10K (59/353); H10K (59/65); H10K (59/875); H10K (59/131); H10K (59/122); H04M (1/0264); G09G (3/3208); G09G (3/3275); G09G (2300/0426)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0196536	12/2017	Li	N/A	H10K 59/40
2021/0408200	12/2020	Zhao et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
109994536	12/2018	CN	N/A
110444125	12/2018	CN	N/A
110491918	12/2018	CN	N/A

Primary Examiner: Greece; James R

Assistant Examiner: Diaz; Jose M

Attorney, Agent or Firm: Conley Rose, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This is a U.S. National Stage of International Patent Application No. PCT/CN2021/081850 filed on Mar. 19, 2021, which claims priority to Chinese Patent application Ser. No. 202010605443.9 filed on Jun. 29, 2020. Both of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(2) This application relates to the field of display technologies, and in particular, to a display module, a display, and a terminal.

BACKGROUND

(3) With development of display technologies, a terminal device with a high screen-to-body ratio becomes a more popular product type for consumers. An optical component needs to occupy a specific region on a display surface of the terminal device, to collect light on a side on which the display surface of the terminal device is located. Therefore, the optical component becomes a main factor that limits full-screen display of the terminal device.

(4) For a terminal device including an organic light-emitting diode (organic light-emitting diode, OLED) display, because the OLED display is not completely opaque, to simplify a structure, a commonly used design is that an optical component is disposed on the back of the OLED display, and a light-receiving surface of the optical component faces the back of the OLED display. However, because transmittance of the OLED display is only approximately 3% to 5%, when the optical component is disposed on the back of the OLED display, performance of the optical component is affected because an amount of light emitted into the optical component is small.

(5) Therefore, how to improve transmittance of the OLED display when the optical component is disposed on the back of the OLED display, to increase the amount of light received by the optical component becomes a technical problem that needs to be resolved by a person skilled in the art.

SUMMARY

(6) Embodiments of this application provide a display module, a display, and a terminal, to resolve a problem of how to improve transmittance of an OLED display.

(7) To achieve the foregoing objective, the following technical solutions are used in embodiments.

(8) According to a first aspect, a display module is provided, and includes: a substrate; a plurality of first signal lines, disposed on the substrate and insulated from each other; a plurality of second signal lines, disposed on the substrate and insulated from each other, where the plurality of second signal lines and the plurality of first signal lines extend in a same direction, are insulated from each other, and are alternately disposed; and at least one first subpixel array, disposed on the substrate, where the first subpixel array includes a plurality of first light-emitting subpixels and a plurality of transparent subpixels, and the plurality of first light-emitting subpixels and the plurality of transparent subpixels are arranged in a mixed manner; a first signal line group is disposed between adjacent rows of subpixels in the first subpixel array, and the first signal line group includes one first signal line and one second signal line; and orthographic projections of the first signal line and the second signal line in at least one first signal line group on the substrate overlap in a region in which the transparent subpixel is located. In this embodiment of this application, structures of the first signal line and the second signal line are adjusted, so that the orthographic projections of the first signal line and the second signal line on the substrate overlap in the region in which the transparent subpixel is located, and an overlapping part of the orthographic projections of the first signal line and the second signal line does not form a diffraction grating. Therefore, based on the structures of the first signal line and the second signal line provided in this embodiment of this application, a quantity of diffraction gratings formed between the first signal line and the second signal line can be reduced, to reduce impact of the first signal line and the second signal line on light emitted into a display, and improve transmittance of the display. In addition, after the orthographic projections of the first signal line and the second signal line on the substrate overlap in the region in which the transparent subpixel is located, an area of the region in which the transparent subpixel is located may be increased, blocking of the region in which the transparent subpixel is located by the first signal line and the second signal line is reduced, and transmittance of the region in which the transparent subpixel is located is improved. Therefore, a daylighting effect of an optical component can be further improved.

(9) Optionally, the first signal line includes at least one first sub-signal line and at least one second sub-signal line, the first sub-signal line and the second sub-signal line are disposed in parallel, and the first sub-signal line and the second sub-signal line are alternately connected along an extension direction of the first signal line; and in a same first signal line group, an orthographic projection of

the second sub-signal line on the substrate overlaps an orthographic projection of the second signal line on the substrate, where the second sub-signal line is located in the region in which the transparent subpixel is located, and the second sub-signal line and the second signal line are disposed at different layers. Therefore, a short circuit between the second sub-signal line and the second signal line is avoided.

(10) Optionally, the second sub-signal line and the first sub-signal line are disposed at different layers. Therefore, the second sub-signal line may be jumpered to another film layer, to improve performance of insulating the second sub-signal line from the second signal line.

(11) Optionally, the first sub-signal line and the second signal line are disposed at a same layer or at different layers. Therefore, the line is more flexible.

(12) Optionally, the second sub-signal line and the first sub-signal line are disposed at a same layer; and in the same first signal line group, an orthographic projection of the first sub-signal line on the substrate and the orthographic projection of the second signal line on the substrate are disposed side by side. Therefore, the second sub-signal line and the first sub-signal line may be disposed at a same layer, and do not need to be jumpered to another film layer, to improve line flexibility.

(13) Optionally, the display further includes a plurality of third signal lines that are insulated from each other and a plurality of fourth signal lines that are insulated from each other; the plurality of third signal lines and the plurality of fourth signal lines are parallel, are insulated from each other, and are alternately disposed on the substrate; and the second sub-signal line is disposed at a same layer as the third signal line and/or the fourth signal line, where the first signal line intersects the third signal line. Therefore, when the second sub-signal line is prepared, the third sub-signal line and the fourth signal line may be prepared in a same process, to simply a preparation process. In addition, the third sub-signal line and the fourth signal line are disposed at the same layer as the second sub-signal line, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display is lightened and thin.

(14) Optionally, the display further includes a plurality of third signal lines that are insulated from each other and a plurality of fourth signal lines that are insulated from each other; the plurality of third signal lines and the plurality of fourth signal lines extend in a same direction, are insulated from each other, and are alternately disposed on the substrate; a second signal line group is disposed between adjacent rows of subpixels in the first subpixel array, and the second signal line group includes one third signal line and one fourth signal line; and orthographic projections of the third signal line and the fourth signal line in at least one second signal line group on the substrate overlap in the region in which the transparent subpixel is located, where the first signal line intersects the third signal line. Therefore, transmittance of the display is further improved.

(15) Optionally, the third signal line includes at least one third sub-signal line and at least one fourth sub-signal line, the third sub-signal line and the fourth sub-signal line are disposed in parallel, and the third sub-signal line and the fourth sub-signal line are alternately connected along an extension direction of the third signal line; and in a same second signal line group, an orthographic projection of the fourth sub-signal line on the substrate overlaps an orthographic projection of the fourth signal line on the substrate, where the fourth sub-signal line is located in the region in which the transparent subpixel is located, and the fourth sub-signal line and the fourth signal line are disposed at different layers. Therefore, performance of insulating the fourth sub-signal line from the fourth signal line is improved.

(16) Optionally, the fourth sub-signal line and the third sub-signal line are disposed at different layers. Therefore, performance of insulating the fourth sub-signal line from the third sub-signal line is improved.

(17) Optionally, the third sub-signal line and the fourth signal line are disposed at a same layer or at different layers. Therefore, line layout flexibility is improved.

(18) Optionally, the fourth sub-signal line and the third sub-signal line are disposed at a same layer; and in the same second signal line group, an orthographic projection of the third sub-signal line on

the substrate and the orthographic projection of the fourth signal line on the substrate are disposed side by side. Therefore, the fourth sub-signal line and the third sub-signal line do not need to be jumpered to another film layer, to improve line flexibility.

(19) Optionally, each fourth sub-signal line is located in the region in which the transparent subpixel is located, and adjacent fourth sub-signal lines are connected through the third sub-signal line; and an orthographic projection of the first signal line on the substrate does not overlap the orthographic projection of the fourth sub-signal line on the substrate, and crosses an orthographic projection of the third sub-signal line on the substrate. Therefore, one fourth sub-signal line is located in a region in which the transparent subpixel is located, and does not cross a signal line (for example, the first signal line) located at a boundary between two adjacent transparent subpixels.

(20) Optionally, the fourth sub-signal line and the second signal line are disposed at a same layer. Therefore, when the second sub-signal line is prepared, the fourth sub-signal line may be prepared in a same process, to simplify a preparation process. In addition, the fourth sub-signal line and the second sub-signal line are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display is lightened and thin.

(21) Optionally, the fourth sub-signal line is disposed at a different layer from the first signal line and the second signal line; and the fourth sub-signal line penetrates, along an extension direction of the fourth sub-signal line, at least one region in which the transparent subpixel is located.

Therefore, a quantity of fourth sub-signal lines can be reduced, to reduce complexity of the third signal line.

(22) Optionally, each second sub-signal line is located in the region in which the transparent subpixel is located, and the first sub-signal line crosses a boundary between two adjacent transparent subpixels; and the orthographic projection of the third signal line on the substrate and/or the orthographic projection of the fourth signal line on the substrate do/does not overlap the orthographic projection of the second sub-signal line on the substrate, and cross/crosses the orthographic projection of the first sub-signal line on the substrate. Therefore, one second sub-signal line is located in a region in which the transparent subpixel is located, and does not cross signal lines (for example, the third signal line and the fourth signal line) located at a boundary between two adjacent transparent subpixels.

(23) Optionally, when the first signal line includes at least one first sub-signal line and at least one second sub-signal line, the second sub-signal line is disposed at a same layer as the third signal line or the fourth signal line. Therefore, cabling flexibility is improved.

(24) Optionally, when the first signal line includes at least one first sub-signal line and at least one second sub-signal line, the second sub-signal line is disposed at a different layer from the third signal line and the fourth signal line; and the second sub-signal line penetrates, along an extension direction of the second sub-signal line, at least one region in which the transparent subpixel is located. Therefore, a quantity of second sub-signal lines is reduced, to reduce complexity of the first signal line.

(25) Optionally, the first signal line and the third signal line are mutually a grid line and a data line. Therefore, cabling flexibility is improved.

(26) Optionally, the plurality of first light-emitting subpixels are grouped into a plurality of light-emitting pixels, and each light-emitting pixel includes at least three first light-emitting subpixels that are adjacent to each other and that are respectively used to display three primary colors; the plurality of transparent subpixels are grouped into a plurality of transparent pixels, where a quantity of transparent subpixels included in each transparent pixel is equal to a quantity of first light-emitting subpixels included in the light-emitting pixel, and a plurality of transparent subpixels in a same transparent pixel are adjacent to each other; and in the first subpixel array, the light-emitting pixels and the transparent pixels are arranged in a mixed manner. Therefore, a daylighting effect of the optical component can be improved.

(27) Optionally, a same row of first light-emitting subpixels arranged along the extension direction

of the first signal line is connected to a same first signal line and a same second signal line; and/or a same row of first light-emitting subpixels arranged along the extension direction of the third signal line is connected to a same third signal line and a same fourth signal line. Therefore, a drive signal may be transmitted from one side of the display to the first signal line and the second signal line, and/or the third signal line and the fourth signal line, that is, unilateral driving is implemented, and a structure is simple.

(28) Optionally, the first light-emitting subpixel includes a drive circuit and a light-emitting component, and the drive circuit is connected to the first signal line, the second signal line, and the light-emitting component; and the light-emitting component includes a first cathode, a first anode, and an electroluminescent layer located between the first cathode and the first anode; and the transparent subpixel includes a second cathode, and the second cathode and the first cathode are of an integrated structure. Therefore, the first cathode and the second cathode are of an entire-layer structure, and patterning can be reduced.

(29) Optionally, the first signal line and the second signal line each are a data line DL or a power voltage line ELVDD.

(30) Optionally, if a pixel drive circuit of the display module is of a 7T1C structure, the first signal line and the second signal line are any two different signal lines in an enabling signal line EM, a first grid scanning signal line N-1, a second grid scanning signal line N, an initial signal line Vint, and a reverse power voltage line ELVSS.

(31) Optionally, a pixel drive circuit of the display module is of a 2T1C structure, the first signal line and the second signal line each are any signal line in a second grid scanning signal line N, an initial signal line Vint, and a reverse power voltage line ELVSS.

(32) Optionally, the third signal line and the fourth signal line are mutually a data line DL and a power voltage line ELVDD.

(33) Optionally, if a pixel drive circuit of the display module is of a 7T1C structure, the third signal line and the fourth signal line are any two different signal lines in an enabling signal line EM, a first grid scanning signal line N-1, a second grid scanning signal line N, an initial signal line Vint, and a reverse power voltage line ELVSS.

(34) Optionally, if a pixel drive circuit of the display module is of a 2T1C structure, the third signal line and the fourth signal line each are any signal line in a second grid scanning signal line N, an initial signal line Vint, and a reverse power voltage line ELVSS.

(35) According to a second aspect of this application, a display is provided, and includes the display module described above.

(36) According to a third aspect of this application, a terminal is provided, and includes the display described above. The terminal further includes an optical component. The optical component is disposed on the back of the display, a light-receiving surface of the optical component faces the display, and an orthographic projection of the optical component on the display is located in a region in which a first subpixel array is located. Therefore, the terminal uses the foregoing display, so that a daylighting effect of the optical component can be improved.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1a is a schematic diagram of a disassembly structure of a terminal according to an embodiment of this application;

(2) FIG. 1b is a schematic diagram of a structure of a display having an optical component according to an embodiment of this application;

(3) FIG. 2a is a schematic diagram of a structure of a display according to an embodiment of this application;

- (4) FIG. 2b is a schematic diagram of a structure of another display according to an embodiment of this application;
- (5) FIG. 2c is a circuit diagram of a light-emitting subpixel in FIG. 2b;
- (6) FIG. 2d is another circuit diagram of a light-emitting subpixel in FIG. 2b;
- (7) FIG. 2e is a schematic diagram of a partial structure of a display having an optical component according to an embodiment of this application;
- (8) FIG. 2f is a schematic diagram of a structure of a pixel delimiting layer FIG. 2e;
- (9) FIG. 3 is a schematic diagram of a structure of another display according to an embodiment of this application;
- (10) FIG. 4a to FIG. 4d each are a schematic diagram of a structure in which a first display region of a display is disposed on a side of a second display region according to an embodiment of this application;
- (11) FIG. 5a to FIG. 5f each are a schematic diagram of a structure in which a second display region of a display surrounds a first display region according to an embodiment of this application;
- (12) FIG. 6a is a schematic diagram of a structure of another display according to an embodiment of this application;
- (13) FIG. 6b is a schematic diagram of a structure of another display according to an embodiment of this application;
- (14) FIG. 6c is a schematic diagram of a structure of another display according to an embodiment of this application;
- (15) FIG. 6d is a schematic diagram of a structure of another display according to an embodiment of this application;
- (16) FIG. 6e is a schematic diagram of a structure of another display according to an embodiment of this application;
- (17) FIG. 6f is a schematic diagram of a structure of another display having an optical component according to an embodiment of this application;
- (18) FIG. 7a is a schematic diagram of a structure of another display according to an embodiment of this application;
- (19) FIG. 7b is a schematic diagram of a structure of another display according to an embodiment of this application;
- (20) FIG. 7c is a schematic diagram of a structure of another display according to an embodiment of this application;
- (21) FIG. 7d is a schematic diagram of a structure of another display according to an embodiment of this application;
- (22) FIG. 7e is a schematic diagram of a structure of another display according to an embodiment of this application;
- (23) FIG. 8a is a schematic diagram of a structure of another display according to an embodiment of this application;
- (24) FIG. 8b is a section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (25) FIG. 8c is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (26) FIG. 8d is a schematic diagram of a structure of another display according to an embodiment of this application;
- (27) FIG. 8e is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (28) FIG. 8f is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (29) FIG. 8g is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;

- (30) FIG. 9a is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (31) FIG. 9b is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (32) FIG. 9c is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (33) FIG. 9d is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (34) FIG. 9e is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (35) FIG. 10a is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (36) FIG. 10b is another section view along a direction A1-A2 in FIG. 8a according to an embodiment of this application;
- (37) FIG. 11 is a schematic diagram of a structure of another display according to an embodiment of this application;
- (38) FIG. 12a is a schematic diagram of a structure of another display according to an embodiment of this application;
- (39) FIG. 12b is a schematic diagram of a structure of another display according to an embodiment of this application;
- (40) FIG. 12c is a schematic diagram of a structure of another display according to an embodiment of this application;
- (41) FIG. 12d is a schematic diagram of a structure of another display according to an embodiment of this application;
- (42) FIG. 12e is a schematic diagram of a structure of another display according to an embodiment of this application;
- (43) FIG. 13a is a schematic diagram of a structure of another display according to an embodiment of this application;
- (44) FIG. 13b is a schematic diagram of a structure of another display according to an embodiment of this application;
- (45) FIG. 13c is a schematic diagram of a structure of another display according to an embodiment of this application;
- (46) FIG. 13d is a schematic diagram of a structure of another display according to an embodiment of this application;
- (47) FIG. 14a is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (48) FIG. 14b is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (49) FIG. 14c is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (50) FIG. 14d is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (51) FIG. 14e is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (52) FIG. 14f is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (53) FIG. 14g is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (54) FIG. 14h is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;

- (55) FIG. 14i is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (56) FIG. 15a is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (57) FIG. 15b is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (58) FIG. 15c is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (59) FIG. 15d is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (60) FIG. 15e is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (61) FIG. 15f is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (62) FIG. 15g is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (63) FIG. 15h is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (64) FIG. 15i is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (65) FIG. 15j is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (66) FIG. 15k is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (67) FIG. 16a is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (68) FIG. 16b is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (69) FIG. 16c is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (70) FIG. 16d is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (71) FIG. 16e is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application;
- (72) FIG. 16f is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application; and
- (73) FIG. 16g is a section view along a direction B1-B2 in FIG. 13a according to an embodiment of this application.

REFERENCE NUMERALS

(74) **1**: Terminal; **2**: Display; **3**: Middle frame; **4**: Housing; **5**: Cover; **6**: Optical component; **10**: First signal line; **20**: Second signal line; **100**: First signal line group; **23**: Substrate; **25**: Pixel delimiting layer; **251**: Retaining wall; **252**: First opening.

DESCRIPTION OF EMBODIMENTS

(75) The following describes technical solutions in embodiments of this application with reference to accompanying drawings in embodiments of this application. It is clear that the described embodiments are merely a part rather than all of embodiments of this application.

(76) Terms such as “first” and “second” mentioned below are merely intended for a purpose of description, and shall not be understood as an indication or implication of relative importance or implicit indication of a quantity of indicated technical features. Therefore, a feature limited by “first” or “second” may explicitly or implicitly include one or more features. In the descriptions of

this application, unless otherwise stated, “a plurality of” means two or more.

(77) In addition, in this application, position terms such as “top” and “bottom” are defined relative to positions of components in the accompanying drawings. It should be understood that these position terms are relative concepts used for relative description and clarification, and may correspondingly change based on changes in the positions of the components in the accompanying drawings.

(78) In this application, it should be noted that a term “connection” should be understood in a broad sense unless otherwise expressly specified and limited. For example, the “connection” may be a fixed connection, may be a detachable connection, may be an integral connection; may be a direct connection, or may be an indirect connection implemented by using a medium.

(79) An embodiment of this application provides a terminal. The terminal may be a product having a display interface, such as a tablet computer, a mobile phone, an e-reader, a remote control, a personal computer (personal computer, PC), a notebook computer, a personal digital assistant (personal digital assistant, PDA), a vehicle-mounted device, a web television, a wearable device, or a television, and smart display wearable products such as a smart watch and a smart band. A specific form of the terminal is not specially limited in this embodiment of this application. For ease of description, an example in which the terminal is a mobile phone is used for description in the following embodiments.

(80) As shown in FIG. 1a, a terminal 1 mainly includes a display 2, a middle frame 3, a housing (or referred to as a battery cover or a rear housing) 4, and a cover 5.

(81) The display 2 has a light-emitting surface a1 on which a display picture can be seen and a back surface a2 disposed opposite to the light-emitting surface a1, the back surface a2 of the display 2 is close to the middle frame 3, and the cover 5 is disposed on the light-emitting surface a1 of the display 2.

(82) In a possible embodiment of this application, the display 2 is an organic light-emitting diode (organic light-emitting diode, OLED) display. Because an electroluminescent layer is disposed in each light-emitting subpixel of the OLED display, the OLED display can implement self-luminescence after receiving an operating voltage.

(83) The cover 5 is located on a side on which the display 2 is away from the middle frame 3. For example, the cover 5 may be cover glass (cover glass, CG), and the cover glass may have specific resilience.

(84) The middle frame 3 is located between the display 2 and the housing 4. A surface of the middle frame 3 that is away from the display 2 is used to install internal components, for example, a battery, a printed circuit board (printed circuit board, PCB), a camera (camera), and an antenna. After the housing 4 and the middle frame 3 are closed, the internal components are located between the housing 4 and the middle frame 3.

(85) On this basis, as shown in FIG. 1b, the terminal 1 further includes an optical component 6. The optical component 6 is disposed on a side of the back surface a2 that is of the display 2 and that is opposite to the light-emitting surface a1, a light-receiving surface of the optical component 6 faces the display 2, and the optical component 6 may be electrically connected to the PCB.

(86) The optical component 6 is a component including a photosensor, and there may be one or more optical components 6. The optical component 6 may include, for example, one or more of a front-facing camera, a fingerprint sensor, an optical proximity sensor, a time of flight (time of flight, TOF) sensor, an iris recognition sensor, or a facial recognition sensor. Herein, the front-facing camera is a camera configured to collect an image on a side on which a display surface of the terminal 1 is located.

(87) For a region in which the optical component 6 is disposed, as shown in FIG. 2a, the display 2 is divided into a display region A.

(88) In a possible embodiment, the display 2 further includes a surrounding region B located around the display region A. In another possible embodiment, the display 2 does not have a

surrounding region B.

(89) A relative location relationship and shapes of the display region A and the surrounding region B are not limited. In this embodiment of this application, an example in which the surrounding region B surrounds the display region A for one circle is used for description.

(90) It may be understood that the optical component 6 included in the terminal 1 implements a specific function by collecting light emitted to the optical component 6 through the display 2. However, the display 2 transmits light only through the display region A. Therefore, as shown in FIG. 2a, an orthographic projection of the optical component 6 on the display 2 is located in the display region A of the display 2.

(91) In a possible embodiment, as shown in FIG. 2b, the display region A includes a plurality of light-emitting subpixels (subpixel) P, and each light-emitting pixel includes at least three light-emitting subpixels P that are respectively used to display three primary colors. For example, each light-emitting pixel includes a red subpixel, a green subpixel, and a blue subpixel. Alternatively, for example, each light-emitting pixel includes a red subpixel, two green subpixels, and a blue subpixel.

(92) For ease of description, in this application, an example in which the plurality of light-emitting subpixels P are arranged in a matrix form is used for description. It may be understood that a shape and an arrangement manner of the light-emitting subpixel P shown in this application are merely for description, and are not limited.

(93) In addition, a drive circuit Q and an OLED (light-emitting component) electrically connected to the drive circuit Q are disposed in each light-emitting subpixel P, and the drive circuit Q is configured to control the OLED to perform displaying.

(94) For example, in a possible embodiment, as shown in FIG. 2c, the drive circuit Q includes a capacitor Cst, a plurality of switch transistors (M1, M2, M3, M5, M6 and M7), and a drive transistor M4. That is, a 7T1C structure is used.

(95) In another possible embodiment, as shown in FIG. 2d, the drive circuit Q includes a capacitor Cst, a switch transistor M1, and a drive transistor M2. That is, a 2T1C structure is used.

(96) Certainly, the drive circuit Q may alternatively be of another structure. The drive circuit Q shown in FIG. 2c and FIG. 2d in this embodiment of this application is merely for description.

(97) For a manner in which the drive circuit Q and the OLED are disposed in the display 2 in a stacked manner, as shown in FIG. 2e, the display 2 includes a substrate 23 and the light-emitting subpixel P disposed on the substrate 23. FIG. 2e shows that two light-emitting subpixels P are disposed on the substrate 23.

(98) The drive circuit Q in the light-emitting subpixel P includes the drive transistor M4 shown in FIG. 2e. Another transistor in the drive circuit Q and the drive transistor M4 are synchronously formed and disposed at a same layer.

(99) As shown in FIG. 2e, the OLED in the light-emitting subpixel P is disposed on a side on which the drive transistor M4 is away from the substrate 23. The OLED includes an anode a, an electroluminescent layer (emitting material layer, EML), and a cathode c that are sequentially, disposed in a direction away from the substrate 23.

(100) The anode a is electrically connected to a second electrode of the drive transistor M4, and receives a drive current $I_{sub.sd}$ generated by the drive transistor M4. The electroluminescent layer EML emits light under driving of the drive current $I_{sub.sd}$. A pixel delimiting layer 25 is disposed between adjacent light-emitting subpixels P, and the pixel delimiting layer 25 is configured to prevent light emitted by the adjacent light-emitting subpixels P from being mixed.

(101) As shown in FIG. 2f, the pixel delimiting layer 25 includes a plurality of horizontal and vertical crossing retaining walls 251 and a plurality of first openings 252 enclosed by the plurality of horizontal and vertical crossing retaining walls 251, and one first opening 252 corresponds to one light-emitting subpixel P.

(102) As shown in FIG. 2e, the drive circuit Q is located on a side on which the retaining wall 251

is close to the substrate 23, and the OLED is located in the first opening 252.

(103) As shown in FIG. 2e, the optical component 6 included in the terminal 1 is disposed on a side on which the backlight surface a2 of the display 2 is located, and implements the specific function by collecting light emitted to the optical component 6 through the display 2. However, because the retaining wall 251 has a light absorption effect, the light cannot pass through the retaining wall 251 and be emitted to the optical component 6, which affects a daylighting effect of the optical component 6.

(104) Based on this, to improve a daylighting effect of the optical component 6 and improve detection precision of the optical component 6, the light-emitting subpixels P in the display 2 are re-arranged, and an area of the retaining wall 251 is reduced by reducing a quantity of drive circuits Q, to reduce a light absorption effect of the retaining wall 251.

(105) In another possible embodiment, as shown in FIG. 3, the display 2 includes at least one first subpixel array (low-density subpixel array) D1 and at least one second subpixel array (high-density subpixel array) D2 that are disposed on the substrate 23.

(106) The first subpixel array D1 includes a plurality of first light-emitting subpixels P1 and a plurality of transparent subpixels T, and the plurality of first light-emitting subpixels P1 and the plurality of transparent subpixels T are arranged in a mixed manner.

(107) An arrangement manner of the plurality of first light-emitting subpixels P1 and the plurality of transparent subpixels T is not limited. For example, three first light-emitting subpixels P1 used to respectively display the three primary colors may be a light-emitting pixel, and at least one transparent subpixel T is disposed between adjacent light-emitting pixels.

(108) Alternatively, three first light-emitting subpixels P1 used to respectively display the three primary colors may be a light-emitting pixel, three transparent subpixels T may be a transparent pixel, and at least one transparent pixel is disposed between adjacent light-emitting pixels. A quantity of transparent subpixels T included in each transparent pixel is equal to a quantity of first light-emitting subpixels P1 included in the light-emitting pixel, and a plurality of transparent subpixels T in a same transparent pixel are adjacent to each other.

(109) In this way, the light-emitting pixels and the transparent pixels in the first subpixel array D1 are arranged in a mixed manner.

(110) The second subpixel array D2 includes a plurality of second light-emitting subpixels 2. In a possible embodiment, the second subpixel array 172 includes only the second light-emitting subpixel P2.

(111) In another possible embodiment, the second subpixel array D2 may further include the transparent subpixel T, but a ratio of the transparent subpixel T to the second light-emitting subpixel P2 in the second subpixel array D2 is less than a ratio of the transparent subpixel T to the first light-emitting subpixel P1 in the first subpixel array D1. That is, a proportion of the transparent subpixel T in the second subpixel array D2 is less than a proportion of the transparent subpixel T in the first subpixel array D1, that is, transmittance of a region in which the second subpixel array D2 is located is poorer than transmittance of a region in which the first subpixel array D1 is located.

(112) It should be noted that structures of the first light-emitting subpixel P1 and the second light-emitting subpixel P2 displaying light of a same color may be the same or different, and both the first light-emitting subpixel P1 and the second light-emitting subpixel P2 are used to display the three primary colors.

(113) For a relative location relationship between subpixels in the first subpixel array D1 and the second subpixel array D2, as shown in FIG. 3, subpixels arranged in a row along a horizontal direction X are referred to as subpixels in a same row. Subpixels arranged in a row along a vertical direction Y are referred to as subpixels in a same column.

(114) In some embodiments, as shown in FIG. 3, along the horizontal direction X, a row of subpixels in the first subpixel array D1 and a row of subpixels in the second subpixel array D2 are

located in a same row. FIG. 3 is used as an example. A third row of second light-emitting subpixel P2 in the second subpixel array D2 and a first row of subpixels in the first subpixel array D1 are located in a same row, and form a third row of subpixels from top to bottom in the display 2.

(115) Along the vertical direction Y, a column of subpixels in the first subpixel array D1 and a column of subpixels in the second subpixel array D2 are located in a same column. FIG. 3 is used as an example. A seventh column of second light-emitting subpixels P2 in the second subpixel array D2 and a first column of subpixels in the first subpixel array D1 are located in a same column, to form a seventh column of subpixels from left to right in the display 2.

(116) That is, subpixels in the first subpixel array D1 and subpixels in the second subpixel array D2 in the display 2 are arranged in an array.

(117) For a distribution manner of the first subpixel array D1 and the second subpixel array D2, in this embodiment of this application, the display region A may include a first display region and a second display region, and the region in which the first subpixel array D1 is located is the first display region, and the region in which the second subpixel array D2 is located is the second display region. A relative location relationship between and shapes of the first display region and the second display region are not limited.

(118) In some embodiments, as shown in FIG. 4a to FIG. 4d, a first display region A1 is located on a side of a second display region A2.

(119) In some embodiments, as shown in FIG. 5a to FIG. 5f, the second display region A2 surrounds the first display region A1.

(120) The first display region A1 may be one region shown in FIG. 5a to FIG. 5d, or may be a plurality of regions shown in FIG. 5e and FIG. 5f. When the first display region A1 is the plurality of regions, a first subpixel array D1 is disposed in each region.

(121) For a structure of subpixels in the first subpixel array D1, as shown in FIG. 6a, each first light-emitting subpixel P1 includes a drive circuit Q and an OLED electrically connected to the drive circuit Q, and the drive circuit Q is configured to drive the OLED to emit light of the three primary colors. The transparent subpixel T is of a transparent structure and does not emit light.

(122) In some embodiments, the transparent subpixel T does not include the drive circuit Q or the OLED.

(123) In some other embodiments, the light-emitting component OLED includes a first cathode, a first anode, and an electroluminescent layer located between the first cathode and the first anode. The transparent subpixel T does not include the drive circuit Q, but the transparent subpixel T includes a second cathode, and the second cathode and the first cathode are of an integrated structure. Therefore, the first cathode and the second cathode are of an entire-layer structure, and patterning can be reduced.

(124) For a structure of subpixels in the second subpixel array D2, as shown in FIG. 6a, each second light-emitting subpixel P2 includes a drive circuit Q and an OLED electrically connected to the drive circuit Q, and the drive circuit Q is configured to drive the OLED to emit light of the three primary colors.

(125) Transmittance of light in a region in which the first subpixel array D1 is located, that is, the first display region A1 is greater than transmittance of light in a region in which the second subpixel array D2 is located, that is, the second display region A2, the orthographic projection of the optical component 6 on the display 2 is located in the region in which the first subpixel array D1 is located (the first display region A1).

(126) A structure of the drive circuit Q is not limited. In some embodiments, the drive circuit Q may be, for example, the same as the drive circuit Q shown in FIG. 2c. For example, the drive circuit Q is the 7T1C structure.

(127) In some embodiments, the drive circuit Q may be, for example, the same as the drive circuit Q shown in FIG. 2d. For example, the drive circuit Q is the 2T1C structure.

(128) Based on this, as shown in FIG. 6b, the display 2 further includes a plurality of first signal

lines **10** and a plurality of second signal lines **20**. The first signal line **10** and the second signal line **20** are electrically connected to the drive circuit Q, and are configured to transmit an electrical signal to the drive circuit Q.

(129) As shown in FIG. **6b**, the plurality of first signal lines **10** are all disposed on the substrate **23**, and the plurality of first signal lines **10** are parallel to each other and insulated from each other. The plurality of second signal lines **20** are also disposed on the substrate **23** and the plurality of second signal lines **20** are parallel to each other and insulated from each other. In addition, the first signal line **10** and the second signal line **20** are parallel to each other (with a same extension direction), insulated from each other, and alternately arranged.

(130) In the first subpixel array **D1**, a first signal line group **100** is disposed between adjacent rows of subpixels arranged along the extension direction of the first signal line **10**, and the first signal line group **100** includes one first signal line **10** and one second signal line **20**.

(131) It should be noted that, first, as shown in FIG. **6b**, a row of subpixels in the first subpixel array **D1** may include both the first light-emitting subpixel **P1** and the transparent subpixel **T**, for example, a first row of subpixels from top to bottom in the first subpixel array **D1** shown in FIG. **6b**. Alternatively, a row of subpixels in the first subpixel array **D1** may include only the first light-emitting subpixel **P1**, for example, a second row of subpixels from top to bottom in the first subpixel array **D1** shown in FIG. **6b**. Alternatively, a row of subpixels in the first subpixel array **D1** may include only the transparent subpixel **T**, for example, a third row of subpixels from top to bottom in the first subpixel array **D1** shown in FIG. **6b**.

(132) Second, a same row of first light-emitting subpixels **P1** arranged along the extension direction of the first signal line **10** is connected to a same first signal line **10** and a same second signal line **20**.

(133) That is, the first signal line **10** and the second signal line **20** in a same first signal line group **100** may be electrically connected to the same row of first light-emitting subpixels **P1** in the first subpixel array **D1**.

(134) It may be understood that the first signal line **10** and the second signal line **20** are connected to the first light-emitting subpixel **P1**, and are essentially connected to the drive circuit Q in the first light-emitting subpixel **P1**.

(135) In a possible embodiment, as shown in FIG. **6b**, the first signal line **10** and the second signal line **20** that are connected to the same row of first light-emitting subpixels **P1** belong to the same first signal line group **100**.

(136) In another possible embodiment, as shown in FIG. **6c**, the first signal line **10** and the second signal line **20** that are connected to the same row of first light-emitting subpixels **P1** belong to different first signal line groups **100**.

(137) That is, the first signal line **10** and the second signal line **20** in the same first signal line group **100** may be electrically connected to different rows of first light-emitting subpixels **P1** in the first subpixel array **D1**.

(138) In this embodiment of this application, for ease of description, an example in which the first signal line **10** and the second signal line **20** that are connected to the same row of first light-emitting subpixels **P1** belong to the same first signal line group **100** is used for description.

(139) Third, in a possible embodiment, as shown in FIG. **6b**, in the first subpixel array **D1**, the same row of first light-emitting subpixels **P1** arranged along the extension direction of the first signal line **10** is connected to the same first signal line **10** and the same second signal line **20**. Therefore, a drive signal may be transmitted from one side of the display **2** to the first signal line **10** and the second signal line **20**, that is, unilateral driving is implemented, and a structure is simple.

(140) In another possible embodiment, as shown in FIG. **6d**, it may be considered that the display **2** includes two adjacent first subpixel arrays **D1**, and the first light-emitting subpixels **P1** connecting the first signal line **10** and the second signal line **20** in the same first signal line group **100** belong

to a same first subpixel array D1. In this way, drive signals may be transmitted to the first signal line 10 and the second signal line 20 from two opposite sides of the display 2, that bilateral driving is implemented.

(141) When a quantity of a same row of first light-emitting subpixels P1 that are arranged along the extension direction of the first signal line 10 is large, a length of the required first signal line 10 is long. Due to existence of a voltage drop on the first signal line 10, the drive signal on the first signal line 10 along the extension direction of the first signal line 10 gradually weakens. The bilateral driving may shorten the length of the first signal line 10, so that the drive signal received by each first light-emitting subpixel P1 is approximately equal, which ensures display quality.

(142) In FIG. 6b, an example in which the extension direction of the first signal line 10 is a horizontal direction X is used for description, and the extension direction of the first signal line 10 may also be a vertical direction Y.

(143) Fourth, the first signal line 10 and the second signal line 20 are not limited in this embodiment of this application provided that extension directions of the first signal line 10 and the second signal line 20 are the same and the first signal line 10 and the second signal line 20 are insulated.

(144) In a possible embodiment, the first signal line 10 and the second signal line 20 belong to signal lines that provide different types of signals to a same row (as shown in FIG. 6b) or different rows (as shown in FIG. 6c) of first light-emitting subpixels P1.

(145) For example, the drive circuit Q in the first light-emitting subpixel P1 is the 7T1C structure shown in FIG. 2c. The first signal line 10 and the second signal line 20 may be any two different signal lines in an enabling signal line EM, a first grid scanning signal line N-1, a second grid scanning signal line N, an initial signal line Vint, and a reverse power voltage line ELVSS.

Alternatively, the first signal line 10 and the second signal line 20 may be mutually a data line DL or a power voltage line ELVDD.

(146) In another possible embodiment, as shown in FIG. 6e, the first signal line 10 and the second signal line 20 belong to signal lines that provide a same type of signal to different rows of first light-emitting subpixels P1.

(147) For example, the drive circuit Q in the first light-emitting subpixel P1 is the 2T1C structure shown in FIG. 2d. The first signal line 10 and the second signal line 20 each may be any signal line in a second grid scanning signal line N, an initial signal line Vint, and a reverse power voltage line ELVSS. Alternatively, the first signal line 10 and the second signal line 20 each may be a data line DL or a power voltage line ELVDD.

(148) Fifth, the first signal line 10 and the second signal line 20 may be disposed at a same layer, or may be disposed at different layers (that is, an insulation layer is disposed between the first signal line 10 and the second signal line 20 along a stacking direction of the first signal line 10 and the second signal line 20).

(149) Sixth, the first signal line group 100 may also be disposed between adjacent rows of subpixels in the second subpixel array D2 in the display 2. In this way, based on a difference in the relative location of the first display region A1 in which the first subpixel array D1 is located and the second display region A2 in which the second subpixel array D2 is located, in a row of subpixels connected to the first signal line 10 and the second signal line 20, both of the first light-emitting subpixel P1 and the second light-emitting subpixel P2 may be included. Alternatively, only the first light-emitting subpixel P1 is included. Alternatively, only the second light-emitting subpixel P2 is included.

(150) Seventh, for differentiation, as shown in FIG. 6b to FIG. 6d, when signals transmitted on the first signal line 10 and the second signal line 20 are different, in this embodiment of this application, an example in which the first signal line 10 and the second signal line 20 have different widths in a direction perpendicular to the extension direction is used for description. However, there is no limitation that the widths of the first signal line 10 and the second signal line 20 are

different, and the widths of the first signal line **10** and the second signal line **20** may also be the same.

(151) In the first subpixel array **D1**, a second signal line group **200** is disposed between adjacent rows of subpixels arranged along an extension direction of a third signal line **30**, and the second signal line group **200** includes one third signal line **30** and one fourth signal line **40**.

(152) It should be noted that, first, a same row of first light-emitting subpixels **P1** arranged along the extension direction of the third signal line **30** is connected to a same third signal line **30** and a same fourth signal line **40**.

(153) It may be understood that the third signal line **30** and the fourth signal line **40** are connected to the first light-emitting subpixel **P1**, and are essentially connected to the drive circuit **Q** in the first light-emitting subpixel **P1**.

(154) In a possible embodiment, as shown in FIG. **6b**, the third signal line **30** and the fourth signal line **40** that are connected to the same row of first light-emitting subpixels **P1** belong to a same second signal line group **200**.

(155) That is, the third signal line **30** and the fourth signal line **40** in the same second signal line group **200** may be electrically connected to the same row of first light-emitting subpixels **P1** in the first subpixel array **D1**.

(156) In another possible embodiment, as shown in FIG. **6c**, the third signal line **30** and the fourth signal line **40** that are connected to the same row of first light-emitting subpixels **P1** belong to different second signal line groups **200**.

(157) That is, the third signal line **30** and the fourth signal line **40** in the same second signal line group **200** may be electrically connected to different rows of first light-emitting subpixels **P1** in the first subpixel array **D1**.

(158) In this embodiment of this application, for ease of description, an example in which the third signal line **30** and the fourth signal line **40** that are connected to the same row of first light-emitting subpixels **P1** belong to the same second signal line group **200** is used for description.

(159) Second, the third signal line **30** and the fourth signal line **40** are not limited in this embodiment of this application provided that extension directions of the third signal line **30** and the fourth signal line **40** are the same and the third signal line **30** and the fourth signal line **40** are insulated.

(160) In a possible embodiment, the third signal line **30** and the fourth signal line **40** belong to signal lines that provide different types of signals to a same row (as shown in FIG. **6b**) or different rows (as shown in FIG. **6c**) of first light-emitting subpixels **P1**.

(161) For example, the drive circuit **Q** in the first light-emitting subpixel **P1** is the 7T1C structure shown in FIG. **2c**. The third signal line **30** and the fourth signal line **40** may mutually be a data line **DL** and a power voltage line **ELVDD**. The third signal line **30** and the fourth signal line **40** may alternatively be any two different signal lines in an enabling signal line **EM**, a first grid scanning signal line **N-1**, a second grid scanning signal line **N**, an initial signal line **Vint**, and a reverse power voltage line **ELVSS**.

(162) In another possible embodiment, as shown in FIG. **6e**, the third signal line **30** and the fourth signal line **40** belong to signal lines that provide a same type of signal to the different rows of first light-emitting subpixels **P1**.

(163) For example, the drive circuit **Q** in the first light-emitting subpixel **P1** is the 2T1C structure shown in FIG. **2d**. The third signal line **30** and the fourth signal line **40** each may be a data line **DL** and a power voltage line **ELVDD**. Alternatively, the third signal line **30** and the fourth signal line **40** each may be any signal line in a second grid scanning signal line **N**, an initial signal line **Vint**, and a reverse power voltage line **ELVSS**.

(164) Third, in a possible embodiment, as shown in FIG. **6c**, in the extension direction of the third signal line **30**, the first light-emitting subpixels **P1** and the second light-emitting subpixels **P2** that are located in a same row are connected to a same third signal line **30** and a same fourth signal line

40.

(165) The second signal line group **200** may also be disposed between adjacent rows of subpixels in the second subpixel array **D2** in the display **2**.

(166) In this way, based on a difference in the relative location of the first display region **A1** in which the first subpixel array **D1** is located and the second display region **A2** in which the second subpixel array **D2** is located, in a row of subpixels connected to the third signal line **30** and the fourth signal line **40**, both of the first light-emitting subpixel **P1** and the second light-emitting subpixel **P2** may be included. Alternatively, only the first light-emitting subpixel **P1** is included. Alternatively, only the second light-emitting subpixel **P2** is included.

(167) In FIG. **6c**, an example in which the extension direction of the third signal line **10** is a vertical direction **Y** is used for description, and the extension direction of the third signal line **30** may also be a horizontal direction **X** provided that the extension direction of the first signal line **10** intersects the extension direction of the third signal line **30**, for example, the first signal line **10** and the third signal line **30** are mutually a grid scanning signal line **N** and a data line **DL**.

(168) For ease of description, in this embodiment of this application, an example in which the extension direction of the first signal line **10** is the horizontal direction **X**, and the extension direction of the third signal line **10** is the vertical direction **Y** is used for description.

(169) Fourth, the third signal line **30** and the fourth signal line **40** may be disposed at a same layer, or may be disposed at different layers (that is, an insulation layer is disposed between the third signal line **30** and the fourth signal line **40** along a stacking direction of the third signal line **30** and the fourth signal line **40**).

(170) Fifth, for differentiation, as shown in FIG. **6b** to FIG. **6d**, when signals transmitted on the third signal line **30** and the fourth signal line **40** are different, in this embodiment of this application, an example in which the third signal line **30** and the fourth signal line **40** have different widths in a direction perpendicular to the extension direction is used for description. However, there is no limitation that the widths of the third signal line **30** and the fourth signal line **40** are different, and the widths of the third signal line **30** and the fourth signal line **40** may also be the same.

(171) In this embodiment of this application, a proportion of the transparent subpixel **T** in the first display region **A1** in which the first subpixel array **D1** is located is greater than a proportion of the transparent subpixel **T** in the second display region **A2** in which the second subpixel array **D2** is located (there may be no transparent subpixel **T** in the second subpixel array **D2**), and the transparent subpixel **T** does not include the drive circuit **Q**. Therefore, as shown in FIG. **6f**, density of the drive circuit **Q** in the first display region **A1** is less than density of the drive circuit **Q** in the second display region **A2**, so that a quantity of transistors in the first display region **A1** is less than a quantity of transistors in the second display region **A2**.

(172) As shown in FIG. **6f**, the optical component **6** is located on the back surface **a2** of the display **2**. Because the transistor in the drive circuit **Q** is a light shielding material, after light is emitted to the drive circuit **Q**, the light is blocked. As a result, the light cannot pass through, and therefore cannot be emitted to the optical component **6**. Because there is a blank region in which no drive circuit **Q** is disposed in the first display region **A1**, the light transmittance of the first display region **A1** is greater than the light transmittance of the second display region **A2**. When the optical component **6** is disposed in the first display region **A1**, a light receiving rate of the optical component **6** may be further increased, to improve performance of the optical component **6**.

(173) However, regardless of whether the first signal line **10** and the second signal line **20** are disposed at a same layer, because an orthographic projection of the first signal line **10** on the substrate **23** and an orthographic projection of the second signal line **20** on the substrate **23** are disposed side by side, a diffraction grating is formed between the first signal line **10** and the second signal line **20**. Therefore, the light is diffracted, and the light receiving rate of the optical component **6** is affected. Similarly, a diffraction grating is also formed between the third signal line

30 and the fourth signal line **40**, which affects the light receiving rate of the optical component **6**.
(174) Based on this, to further increase the light receiving rate of the optical component **6** and improve the performance of the optical component **6** in the terminal **1**, the display **2** is further improved based on the display **2** provided in this embodiment of this application.

Example 1

(175) As shown in FIG. **7a**, the display **2** includes at least one first subpixel array (low-density subpixel array) **D1** and at least one second subpixel array (high-density subpixel array) **D2** that are disposed on the substrate **23**. The first subpixel array **D1** includes a plurality of first light-emitting subpixels **P1** and a plurality of transparent subpixels and the plurality of first light-emitting subpixels **P1** and the plurality of transparent subpixels **T** are arranged in a mixed manner.

(176) The display **2** further includes a plurality of first signal lines **10** and a plurality of second signal lines **20**. The first signal line **10** and the second signal line **20** are electrically connected to the drive circuit **Q** of the first light-emitting subpixel **P1** in the first subpixel array **D1** and the drive circuit **Q** of second light-emitting subpixel **P2** in the second subpixel array **D2**, and are configured to transmit electrical signals to the drive circuit **Q**.

(177) As shown in FIG. **7a**, the plurality of first signal lines **10** are disposed on the substrate **23**, and the plurality of first signal lines **10** are insulated from each other. The plurality of second signal lines **20** are also disposed on the substrate **23** and the plurality of second signal lines **20** are insulated from each other. In addition, the plurality of first signal line **10** and the plurality of second signal line **20** extend in a same direction, are insulated from each other, and are alternately arranged.

(178) For locations at which the first signal line **10** and the second signal line **20** in the display **10** are disposed and signals transmitted on the first signal line **10** and the second signal line **20**, refer to the foregoing related descriptions of FIG. **6a** to FIG. **6e**. Details are not described herein again.

(179) In the first subpixel array **D1**, a first signal line group **100** is disposed between adjacent rows of subpixels arranged along the extension direction of the first signal line **10**, and the first signal line group **100** includes one first signal line **10** and one second signal line **20**.

(180) Based on a difference in a structure of the first subpixel array **D1**, the display **2** may include one first signal line group **100**, or may include a plurality of first signal line groups **100**.

(181) As shown in FIG. **7a**, orthographic projections of the first signal line **10** and the second signal line **20** in at least one first signal line group **100** on the substrate **23** overlap in some regions in which the transparent subpixels **T** are located.

(182) That is, in a possible embodiment, the display **2** includes one first signal line group **100**, and the orthographic projections of the first signal line **10** and the second signal line **20** in the first signal line group **100** on the substrate **23** overlap in some regions in which the transparent subpixels **T** are located.

(183) In another possible embodiment, as shown in FIG. **7a**, the display **2** includes a plurality of first signal line groups **100**, and orthographic projections of the first signal line **10** and the second signal line **20** included in some of the plurality of first signal line groups **100** on the substrate **23** overlap in some regions in which the transparent subpixels **T** are located.

(184) In another possible embodiment, as shown in FIG. **7b**, the display **2** includes a plurality of first signal line groups **100**, orthographic projections of the first signal line **10** and the second signal line **20** included in each of the plurality of first signal line groups **100** on the substrate **23** overlap in regions in which the transparent subpixels **T** are located.

(185) That the orthographic projection of the first signal line **10** on the substrate **23** and the orthographic projection of the second signal line **20** on the substrate **23** overlap in the regions in which the transparent subpixels **T** are located may be understood that along a thickness direction of the display **2**, a part of the first signal line **10** is located right above or right below the second signal line **20**.

(186) In a possible embodiment, as shown in FIG. **7b**, the orthographic projection of the first signal

line **10** on the substrate **23** and the orthographic projection of the second signal line **20** on the substrate **23** overlap in regions in which each transparent subpixel T is located.

(187) In another possible embodiment, as shown in FIG. 7c, the orthographic projection of the first signal line **10** on the substrate **23** and the orthographic projection of the second signal line **20** on the substrate **23** overlap in regions in which some of the plurality of transparent subpixels T are located.

(188) In addition, to reduce changes to a preparation process, so as to reduce process complexity, in a possible embodiment, as shown in FIG. 7a to FIG. 7c, only a structure of a same signal line is changed, so that the first signal line **10** and the second signal line **20** that are originally parallel overlap.

(189) To unify the preparation process, structures of all first signal lines **10** are the same. In another possible embodiment, as shown in FIG. 7d, each first signal line **10** connected to the subpixels in the first subpixel array D1 has a same structure.

(190) To reduce blocked areas of the first signal line **10** and the second signal line **20**, and maximize an area of the regions in which the transparent subpixels T are located, so as to improve transmittance, in another possible embodiment, as shown in FIG. 7e, when one side of the first signal line group **100** is the transparent subpixels T, and the other side is the first light-emitting subpixels P1, a signal line that is in the first signal line group **100** and that is close to the transparent subpixels T bends toward a signal line that is far away from the transparent subpixels T (as shown in regions drawn by elliptical dotted lines in FIG. 7e).

(191) For example, as shown in FIG. 7e, in the first signal line group **100** located above the transparent subpixels T in the first subpixel array D1, the first signal line **10** is close to the transparent subpixels T. Therefore, the first signal line **10** bends toward the second signal line **20** in the regions in which the transparent subpixels T are located, so that the first signal line **10** overlaps the second sub-signal line **20**.

(192) In the first signal line group **100** located below the transparent subpixels T in the first subpixel array D1, the second sub-signal line **20** is close to the transparent subpixels T. Therefore, the second sub-signal line **20** bends toward the first signal line **10** in the regions in which the transparent subpixels T are located, so that the first signal line **10** overlaps the second sub-signal line **20**.

(193) It should be noted that, as shown in FIG. 7a to FIG. 7e, although the orthographic projection of the first signal line **10** on the substrate **23** and the orthographic projection of the second signal line **20** on the substrate **23** overlap, the first signal line **10** and the second signal line **20** are insulated from each other.

(194) In this embodiment of this application, the structures of the first signal line **10** and the second signal line **20** are adjusted, so that the orthographic projections of the first signal line **10** and the second signal line **20** on the substrate **23** overlap in the regions in which the transparent subpixels T are located, and overlapping parts of the orthographic projections of the first signal line **10** and the second signal line **20** do not form a diffraction grating. Therefore, the structures of the first signal line **10** and the second signal line **20** provided in this embodiment of this application can reduce diffraction gratings formed between the first signal line **10** and the second signal line **20**, to reduce impact of the first signal line **10** and the second signal line **20** on light emitted into the display **2**, and improve transmittance of light in the first display region A1 in which the first subpixel array D1 is located. The optical component **6** in the terminal is disposed on the back of the display **2**, and corresponds to the first display region A1. Therefore, a daylighting effect of the optical component **6** can be improved.

(195) In addition, after the orthographic projections of the first signal line **10** and the second signal line **20** on the substrate **23** overlap in the regions in which the transparent subpixels T are located, the area of the regions in which the transparent subpixels T are located may be increased, blocking of the regions in which the transparent subpixels T are located by the first signal line **10** and the

second signal line **20** is reduced, and transmittance of the regions in which the transparent subpixels T are located is improved. Therefore, a daylighting effect of the optical component **6** can be further improved.

(196) For the structures of the first signal line **10** and the second signal line **20**, in a possible embodiment, as shown in FIG. **8a**, the first signal line **10** includes at least one first sub-signal line **11** and at least one second sub-signal line **12**.

(197) The first sub-signal line **11** and the second sub-signal line **12** are disposed in parallel, that is, the first sub-signal line **11** and the second sub-signal line **12** are arranged in a staggered manner, and the first sub-signal line **11** and the second sub-signal line **12** are not on a same extension line.

(198) The first sub-signal line **11** and the second sub-signal line **12** are alternately connected along the extension direction of the first signal line **10**.

(199) A connection manner between the first sub-signal line **11** and the second sub-signal line **12** is not limited. For example, as shown in FIG. **8a**, the first sub-signal line **11** is connected to the second sub-signal line **12** through a first connection line **13**.

(200) When the first sub-signal line **11** and the second sub-signal line **12** are at a same layer, the first connection line **13** and the first sub-signal line **11** may be at a same layer, and two ends of the first connection line **13** are directly connected to the first sub-signal line **11** and the second sub-signal line **12**. In this case, the first sub-signal line **11**, the second sub-signal line **12**, and the first connection line **13** may be of an integrated structure.

(201) When the first sub-signal line **11** and the second sub-signal line **12** are at different layers, the first connection line **13** and the first sub-signal line **11** may be at a same layer, or the first connection line **13** and the first sub-signal line **11** may be of an integrated structure. The first connection line **13** is connected to the second sub-signal line **12** through a via, to implement the connection between the first sub-signal line **11** and the second sub-signal line **12**. Alternatively, the first connection line **13** and the second sub-signal line **12** may be at a same layer, and the first connection line **13** and the second sub-signal line **12** may be of an integrated structure. The first connection line **13** is connected to the first sub-signal line **11** through a via, to implement the connection between the first sub-signal line **11** and the second sub-signal line **12**.

(202) Certainly, regardless of the structure, the first connection line **13** is not connected to the second signal line **20**, to avoid a short circuit.

(203) The second sub-signal line **12** is located in the regions in which the transparent subpixels T are located, and the second sub-signal line **12** and the second signal line **20** are disposed at different layers.

(204) In a same first signal line group **100**, an orthographic projection of the second sub-signal line **12** on the substrate **23** overlaps the orthographic projection of the second signal line **20** on the substrate **23**.

(205) That is, in the first signal line **10**, the second sub-signal line **12** is located in the regions in which the transparent subpixels T are located, and the second sub-signal line **12** is located right above or right below the second signal line **20**.

(206) The following describes a location relationship between the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20**.

(207) In a first possible embodiment, details are as follows:

(208) As shown in FIG. **8b** (a section view along a direction A1-A2 in FIG. **8a**), the second sub-signal line **12** and the first sub-signal line **11** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(209) That is, the first sub-signal line **11** in the first signal line **10** and the second signal line **20** are disposed at the same layer, and the second sub-signal line **12** in the first signal line **10** is jumpered to another film layer, so that the second sub-signal line **12** is located right above or right below the second signal line **20**.

(210) As shown in FIG. **8b**, to avoid a short circuit of signal lines between adjacent film layers, an

inter layer dielectric (inter layer dielectric, ILD) layer is disposed between signal lines of adjacent layers. A quantity of ILD layers between the adjacent signal lines is not limited. In FIG. 8b, only one ILD layer is used as an example for description. A material of the ILD layer is not limited, and materials that can perform an insulation function may all be applicable to the ILD layer.

(211) To avoid the short circuit between the first connection line 13 and the second signal line 20, as shown in FIG. 8b), the first connection line 13 and the second sub-signal line 12 are disposed at the same layer, and the first connection line 13 is connected to the first sub-signal line 11 through the via located at an ILD layer between the first sub-signal line 11 and the second sub-signal line 12, to implement the connection between the first sub-signal line 11 and the second sub-signal line 12.

(212) For a location relationship between the third signal line 30, the fourth signal line 40, and the first signal line 10, optionally, as shown in FIG. 8b, the third signal line 30 and the fourth signal line 40 are disposed at a same layer, and the third signal line 30 and the fourth signal line 40 are disposed at a different layer from the first sub-signal line 11 and the second sub-signal line 12.

(213) Alternatively, for a location relationship between the third signal line 30, the fourth signal line 40, and the first signal line 10, optionally, as shown in FIG. 8c (a section view along the direction A1-A2 in FIG. 8a), the third signal line 30 and the fourth signal line 40 are disposed at different layers, and the third signal line 30 and the fourth signal line 40 are disposed at different layers from the first sub-signal line 11 and the second sub-signal line 12.

(214) Certainly, the third signal line 30 may be located above the fourth signal line 40, or the fourth signal line 40 may be located above the third signal line 30.

(215) When the third signal line 30 and the fourth signal line 40 are disposed at different layers from the first sub-signal line 11 and the second sub-signal line 12, in some embodiments, as shown in FIG. 8a, a second sub-signal line 12 is located in a region in which the transparent subpixel T is located and does not penetrate the region, and the first sub-signal line 11 crosses a boundary between two adjacent transparent subpixels T. Orthographic projections of the third signal line 30 and the fourth signal line 40 on the substrate 23 do not overlap the orthographic projection of the second sub-signal line 1 on the substrate 23. In addition, the orthographic projection of the third signal line 30 on the substrate 23 and the orthographic projection of the fourth signal line 40 on the substrate 23 cross an orthographic projection of the first sub-signal line 11 on the substrate 23.

(216) That is, a second sub-signal line 12 is located in a region in which the transparent subpixel T is located, and does not cross signal lines (for example, the third signal line 30 and the fourth signal line 40) located at a boundary between two adjacent transparent subpixels T.

(217) When the third signal line 30 and the fourth signal line 40 are disposed at different layers from the first sub-signal line 11 and the second sub-signal line 12, in some other embodiments, to reduce a quantity of second sub-signal lines 12, so as to reduce complexity of the first signal line 10, as shown in FIG. 8d, the second sub-signal line 12 penetrates, along an extension direction of the second sub-signal line 12, at least one region in which the transparent subpixel T is located.

(218) Alternatively, for a location relationship between the third signal line 30, the fourth signal line 40, and the first signal line 10, optionally, as shown in FIG. 8e (a section view along the direction A1-A2 in FIG. 8a), the third signal line 30 and the fourth signal line 40 are disposed at a same layer, and the second sub-signal line 12 is disposed at a same layer as the third signal line 30 and the fourth signal line 40.

(219) Therefore, when the third signal line 30 and the fourth signal line 40 are prepared, the second sub-signal line 12 may be prepared in a same process, to simply a preparation process. In addition, the second sub-signal line 12 is disposed at the same layer as the third signal line 30 and the fourth signal line 40, so that a quantity of insulation layers between layers can be reduced, and the display 2 is lightened and thin.

(220) Alternatively, for a location relationship between the third signal line 30, the fourth signal line 40, and the first signal line 10, optionally, as shown in FIG. 8f (a section view along the

direction A1-A2 in FIG. 8a), the third signal line 30 and the fourth signal line 40 are disposed at different layers, and the second sub-signal line 12 and the third signal line 30 are disposed at a same layer.

(221) Therefore, when the third signal line 30 is prepared, the second sub-signal line 12 may be prepared in a same process, to simply a preparation process. In addition, the second sub-signal line 12 and the third signal line 30 are disposed at the same layer, so that a quantity of insulation layers between layers can be reduced, and the display 2 is lightened and thin.

(222) Alternatively, for a location relationship between the third signal line 30, the fourth signal line 40, and the first signal line 10, optionally, as shown in FIG. 8g (a section view along the direction A1-A2 in FIG. 8a), the third signal line 30 and the fourth signal line 40 are disposed at different layers, and the second sub-signal line 12 and the fourth signal line 40 are disposed at a same layer.

(223) Therefore, when the fourth signal line 40 is prepared, the second sub-signal line 12 may be prepared in a same process, to simply a preparation process. In addition, the second sub-signal line 12 and the fourth signal line 40 are disposed at the same layer, so that a quantity of insulation layers between layers can be reduced, and the display 2 is lightened and thin.

(224) When the third signal line 30 and/or the fourth signal line 40 are/is disposed at a same layer as the second sub-signal line 12, in some embodiments, as shown in FIG. 8a, a second sub-signal line 12 is located in a region in which the transparent subpixel T is located and does not penetrate the region, and the first sub-signal line 11 crosses a boundary between two adjacent transparent subpixels T. Orthographic projections/an orthographic projection of the third signal line 30 and/or the fourth signal line 40 on the substrate 23 do/does not overlap the orthographic projection of the second sub-signal line 12 on the substrate 23. In addition, the orthographic projection of the third signal line 30 on the substrate 23 and the orthographic projection of the fourth signal line 40 on the substrate 23 cross an orthographic projection of the first sub-signal line 11 on the substrate 23.

(225) That is, when the third signal line 30 and the second sub-signal line 12 are disposed at the same layer, the third signal line 30 and the second sub-signal line 12 are not crossed, and the third signal line 30 and the first sub-signal line 11 are crossed. When the fourth signal line 40 and the second sub-signal line 12 are disposed at the same layer, the fourth signal line 40 and the second sub-signal line 12 are not crossed, and the fourth signal line 40 and the first sub-signal line 11 are crossed.

(226) It should be noted that a location relationship between the first sub-signal line 11 and the second sub-signal line 12 shown in FIG. 8b and FIG. 8c and FIG. 8e to FIG. 8g is merely an example, and constitutes no limitation provided that the first sub-signal line 11 and the second sub-signal line 12 are disposed at different layers.

(227) In a second possible embodiment, details are as follows:

(228) A difference between the second possible embodiment and the first possible embodiment lies in that the first sub-signal line 11 and the second signal line 20 are disposed at different layers.

(229) As shown in FIG. 9a (a section view along a direction A1-A2 in FIG. 8a), the second sub-signal line 12 and the first sub-signal line 11 are disposed at different layers, and the first sub-signal line 11 and the second signal line 20 are disposed at different layers.

(230) That is, the first sub-signal line 11 in the first signal line 10 and the second signal line 20 are disposed at the different layers, and the second sub-signal line 12 in the first signal line 10 and the second signal line 20 are disposed at different layers, and the first sub-signal line 11 and the second sub-signal line 12 in the first signal line 10 are also disposed at different layers.

(231) The first sub-signal line 11 and the second signal line 20 are disposed at different layers, and the first sub-signal line 11 may be located above the second signal line 20. In this case, the first connection line 13 and the first sub-signal line 11 may be at a same layer, or the first connection line 13 and the second sub-signal line 12 may be at a same layer, to avoid a short circuit between the first connection line 13 and the second signal line 20. The first sub-signal line 11 may

alternatively be located below the second signal line **20**. In this case, the first connection line **13** and the second sub-signal line **12** are at a same layer, to avoid a short circuit between the first connection line **13** and the second signal line **20**. In this example, an example in which the first sub-signal line **11** is located above the second signal line **20**, and the first connection line **13** and the second sub-signal line **12** are disposed at a same layer is used for description.

(232) Similarly, for a location relationship between the third signal line **30**, the fourth signal line **40**, and the first signal line **10**, optionally, as shown in FIG. **9a**, the third signal line **30** and the fourth signal line **40** are disposed at a same layer, and the third signal line **30** and the fourth signal line **40** are disposed at a different layer from the first sub-signal line **11** and the second sub-signal line **12**.

(233) Alternatively, for a location relationship between the third signal line **30**, the fourth signal line **40**, and the first signal line **10**, optionally, as shown in FIG. **9b** (a section view along a direction A1-A2 in FIG. **8a**), the third signal line **30** and the fourth signal line **40** are disposed at different layers, and the third signal line **30** and the fourth signal line **40** are disposed at different layers from the first sub-signal line **11** and the second sub-signal line **12**.

(234) Certainly, the third signal line **30** may be located above the fourth signal line **40**, or the fourth signal line **40** may be located above the third signal line **30**.

(235) When the third signal line **30** and the fourth signal line **40** are disposed at different layers from the first sub-signal line **11** and the second sub-signal line **12**, in some embodiments, as shown in FIG. **8a**, a second sub-signal line **12** is located in a region in which the transparent subpixel T is located and does not penetrate the region, and the first sub-signal line **11** crosses a boundary between two adjacent transparent subpixels T. Orthographic projections of the third signal line **30** and the fourth signal line **40** on the substrate **23** do not overlap the orthographic projection of the second sub-signal line **12** on the substrate **23**. In addition, the orthographic projection of the third signal line **30** on the substrate **23** and the orthographic projection of the fourth signal line **40** on the substrate **23** cross an orthographic projection of the first sub-signal line **11** on the substrate **23**.

(236) That is, a second sub-signal line **12** is located in a region in which the transparent subpixel T is located, and does not cross signal lines (for example, the third signal line **30** and the fourth signal line **40**) located at a boundary between two adjacent transparent subpixels T.

(237) When the third signal line **30** and the fourth signal line **40** are disposed at different layers from the first sub-signal line **11** and the second sub-signal line **12**, in some other embodiments, to reduce a quantity of second sub-signal lines **12**, so as to reduce complexity of the first signal line **10**, as shown in FIG. **8d**, the second sub-signal line **12** penetrates, along an extension direction of the second sub-signal line **12**, at least one region in which the transparent subpixel T is located.

(238) Alternatively, for a location relationship between the third signal line **30**, the fourth signal line **40**, and the first signal line **10**, optionally, as shown in FIG. **9c** (a section view along the direction A1-A2 in FIG. **8a**), the third signal line **30** and the fourth signal line **40** are disposed at a same layer, and the second sub-signal line **12** is disposed at a same layer as the third signal line **30** and the fourth signal line **40**.

(239) Therefore, when the third signal line **30** and the fourth signal line **40** are prepared, the second sub-signal line **12** may be prepared in a same process, to simply a preparation process. In addition, the second sub-signal line **12** is disposed at the same layer as the third signal line **30** and the fourth signal line **40**, so that a quantity of insulation layers between layers can be reduced, and the display **2** is lightened and thin.

(240) Alternatively, for a location relationship between the third signal line **30**, the fourth signal line **40**, and the first signal line **10**, optionally, as shown in FIG. **9d** (a section view along the direction A1-A2 in FIG. **8a**), the third signal line **30** and the fourth signal line **40** are disposed at different layers, and the second sub-signal line **12** and the third signal line **30** are disposed at a same layer.

(241) Therefore, when the third signal line **30** is prepared, the second sub-signal line **12** may be

prepared in a same process, to simply a preparation process. In addition, the second sub-signal line **12** and the third signal line **30** are disposed at the same layer, so that a quantity of insulation layers between layers can be reduced, and the display **2** is lightened and thin.

(242) Alternatively, for a location relationship between the third signal line **30**, the fourth signal line **40**, and the first signal line **10**, optionally, as shown in FIG. **9e** (a section view along the direction A1-A2 in FIG. **8a**), the third signal line **30** and the fourth signal line **40** are disposed at different layers, and the second sub-signal line **12** and the fourth signal line **40** are disposed at a same layer.

(243) Therefore, when the fourth signal line **40** is prepared, the second sub-signal line **12** may be prepared in a same process, to simply a preparation process. In addition, the second sub-signal line **12** and the fourth signal line **40** are disposed at the same layer, so that a quantity of insulation layers between layers can be reduced, and the display **2** is lightened and thin.

(244) When the third signal line **30** and/or the fourth signal line **40** are/is disposed at a same layer as the second sub-signal line **12**, in sonic embodiments, as shown in FIG. **8a**, a second sub-signal line **12** is located in a region in which the transparent subpixel T is located and does not penetrate the region, and the first sub-signal line **11** crosses a boundary between two adjacent transparent subpixels T. Orthographic projections/an orthographic projection of the third signal line **30** and/or the fourth signal line **40** on the substrate **23** do/does not overlap the orthographic projection of the second sub-signal line **12** on the substrate **23**. In addition, the orthographic projection of the third signal line **30** on the substrate **23** and the orthographic projection of the fourth signal line **40** on the substrate **23** cross an orthographic projection of the first sub-signal line **11** on the substrate **23**.

(245) That is, when the third signal line **30** and the second sub-signal line **12** are disposed at the same layer, the third signal line **30** and the second sub-signal line **12** are not crossed, and the third signal line **30** and the first sub-signal line **11** are crossed. When the fourth signal line **40** and the second sub-signal line **12** are disposed at the same layer, the fourth signal line **40** and the second sub-signal line **12** are not crossed, and the fourth signal line **40** and the first sub-signal line **11** are crossed.

(246) It should be noted that a location relationship between the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** shown in FIG. **9a** to FIG. **9e** is merely an example, and constitutes no limitation provided that two of the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers.

(247) In a third possible embodiment, details are as follows:

(248) A difference between the third possible embodiment and the first and second possible embodiments lies in that the second sub-signal line **12** and the first sub-signal line **11** are disposed at a same layer.

(249) As shown in FIG. **10a** (a section view along a direction A1-A2 in FIG. **8a**), the second sub-signal line **12** and the first sub-signal line **11** are disposed at a same layer. As shown in FIG. **8a**, in a same first signal line group **100**, an orthographic projection of the first sub-signal line **11** on the substrate **23** and the orthographic projection of the second signal line **20** on the substrate **23** are disposed side by side.

(250) That is, the first sub-signal line **11** and the second sub-signal line **12** in the first signal line **10** are disposed at the same layer, and the first signal line **10** and the second signal line **20** are disposed at different layers. The orthographic projection of the first sub-signal line **11** in the first signal line **10** on the substrate **23** and the orthographic projection of the second signal line **20** on the substrate **23** are disposed side by side, and the second sub-signal line **12** in the first signal line **10** is located right above or right below the second signal line **20**.

(251) Similarly, for a location relationship between the third signal line **30**, the fourth signal line **40**, and the first signal line **10**, optionally, as shown in FIG. **10a**, the third signal line **30** and the fourth signal line **40** are disposed at a same layer, and the third signal line **30** and the fourth signal line **40** are disposed at a different layer from the first sub-signal line **11** and the second sub-signal

line **12**.

(252) Alternatively, for a location relationship between the third signal line **30**, the fourth signal line **40**, and the first signal line **10**, optionally, as shown in FIG. **10b** (a section view along a direction **A1-A2** in FIG. **8a**), the third signal line **30** and the fourth signal line **40** are disposed at different layers, and the third signal line **30** and the fourth signal line **40** are disposed at different layers from the first sub-signal line **11** and the second sub-signal line **12**.

(253) Certainly, the third signal line **30** may be located above the fourth signal line **40**, or the fourth signal line **40** may be located above the third signal line **30**.

(254) When the third signal line **30** and the fourth signal line **40** are disposed at different layers from the first sub-signal line **11** and the second sub-signal line **12**, in some embodiments, as shown in FIG. **8a**, a second sub-signal line **12** is located in a region in which the transparent subpixel **T** is located and does not penetrate the region, and the first sub-signal line **11** crosses a boundary between two adjacent transparent subpixels **T**. Orthographic projections of the third signal line **30** and the fourth signal line **40** on the substrate **23** do not overlap the orthographic projection of the second sub-signal line **12** on the substrate **23**. In addition, the orthographic projection of the third signal line **30** on the substrate **23** and the orthographic projection of the fourth signal line **40** on the substrate **23** cross the orthographic projection of the first sub-signal line **11** on the substrate **23**.

(255) That is, a second sub-signal line **12** is located in a region in which the transparent subpixel **T** is located, and does not cross signal lines (for example, the third signal line **30** and the fourth signal line **40**) located at a boundary between two adjacent transparent subpixels

(256) When the third signal line **30** and the fourth signal line **40** are disposed at different layers from the first sub-signal line **11** and the second sub-signal line **12**, in some other embodiments, to reduce a quantity of second sub-signal lines **12**, so as to reduce complexity of the first signal line **10**, as shown in FIG. **8d**, the second sub-signal line **12** penetrates, along an extension direction of the second sub-signal line **12**, at least one region in which the transparent subpixel **T** is located.

(257) It may be understood that, in the schematic diagrams provided in this example, from a perspective of the figures, an example in which the first signal line **10** and the second signal line **20** extend along the horizontal direction **X** is used for description. Certainly, as shown in FIG. **11**, the first signal line **10** and the second signal line **20** may also extend along the vertical direction **Y**. A structure in which the first signal line **10** and the second signal line **20** extend along the vertical direction **Y** is the same as the structure in which the first signal line **10** and the second signal line **20** extend along the horizontal direction **X**. Details are not described herein again.

Example 2

(258) A difference between Example 2 and Example 1 lies in that structures of the third signal line **30** and the fourth signal line **40** in the display **2** are different.

(259) As shown in FIG. **12a**, the display **2** includes a plurality of third signal lines **30** that are insulated from each other and a plurality of fourth signal lines **40** that are insulated from each other, and the plurality of third signal lines **30** and the plurality of fourth signal lines **40** extend in a same direction, are insulated from each other, and are alternately disposed on the substrate **23**.

(260) Orthographic projections of the third signal line **30** and the fourth signal line **40** in at least one second signal line group **200** on the substrate **23** overlap in some regions in which the transparent subpixels **T** are located.

(261) That is, in a possible embodiment, the display **2** includes one second signal line group **200**, and the orthographic projections of the third signal line **30** and the fourth signal line **40** in the second signal line group **200** on the substrate **23** overlap in some regions in which the transparent subpixels **T** are located.

(262) In another possible embodiment, as shown in FIG. **12a**, the display **2** includes a plurality of second signal line groups **200**, and orthographic projections of the third signal line **30** and the fourth signal line **40** included in some of the plurality of second signal line groups **200** on the substrate **23** overlap in some regions in which the transparent subpixels **T** are located.

(263) In another possible embodiment, as shown in FIG. 12b, the display 2 includes a plurality of second signal line groups 200, orthographic projections of the third signal line 30 and the fourth signal line 40 included in each of the plurality of second signal line groups 200 on the substrate 23 overlap in regions in which the transparent subpixels T are located.

(264) That the orthographic projection of the third signal line 30 on the substrate 23 and the orthographic projection of the fourth signal line 40 on the substrate 23 overlap in the regions in which the transparent subpixels T are located may be understood that along a thickness direction of the display 2, a part of the third signal line 30 is located right above or right below the fourth signal line 40.

(265) In a possible embodiment, as shown in FIG. 12b, the orthographic projection of the third signal line 30 on the substrate 23 and the orthographic projection of the fourth signal line 40 on the substrate 23 overlap in regions in which each transparent subpixel T is located.

(266) In another possible embodiment, as shown in FIG. 12c, the orthographic projection of the third signal line 30 on the substrate 23 and the orthographic projection of the fourth signal line 40 on the substrate 23 overlap in regions in which some of the plurality of transparent subpixels T are located.

(267) In addition, to reduce changes to a production process, so as to reduce process complexity, in a possible embodiment, as shown in FIG. 12a to FIG. 12c, only a structure of a same signal line is changed, so that the third signal line 30 and the fourth signal line 40 that are originally parallel overlap.

(268) To unify the production process, structures of all third signal lines 30 are the same. In another possible embodiment, as shown in FIG. 12d, each third signal line 30 connected to the subpixels in the first subpixel array D1 has a same structure.

(269) To reduce blocked areas of the third signal line 30 and the fourth signal line 40, and maximize an area of the regions in which the transparent subpixels T are located, so as to improve transmittance, in another possible embodiment, as shown in FIG. 12e, when one side of the second signal line group 200 is the transparent subpixels T, and the other side is the first light-emitting subpixels P1, a signal line that is in the second signal line group 200 and that is close to the transparent subpixels T bends toward a signal line that is far away from the transparent subpixels T (as shown in regions drawn by elliptical dotted lines in FIG. 12e).

(270) For example, as shown in FIG. 12e, in the two regions drawn by the elliptical dotted lines, in the region that is located above and that is drawn by the elliptical dotted lines, the third signal line 30 is close to the transparent subpixel relative to the fourth signal line 40. Therefore, the third signal line 30 bends toward the fourth signal line 40, so that the third signal line 30 overlaps the fourth sub-signal line 40.

(271) In the two regions drawn by the elliptical dotted lines, in the region that is located below and that is drawn by the elliptical dotted lines, the fourth signal line 40 is close to the transparent subpixel T relative to the third signal line 30. Therefore, the fourth signal line 40 bends toward the third signal line 30, so that the third signal line 30 overlaps the fourth sub-signal line 40.

(272) It should be noted that, as shown in FIG. 12a to FIG. 12e, although the orthographic projection of the third signal line 30 on the substrate 23 and the orthographic projection of the fourth signal line 40 on the substrate 23 overlap, the third signal line 30 and the fourth sub-signal line 40 are insulated from each other.

(273) In this embodiment of this application, the structures of the third signal line 30 and the fourth sub-signal line 40 are adjusted, so that the orthographic projections of the third signal line 30 and the fourth sub-signal line 40 on the substrate 23 overlap in the regions in which the transparent subpixels T are located, and overlapping parts of the orthographic projections of the third signal line 30 and the fourth sub-signal line 40 do not form a diffraction grating. Therefore, the structures of the third signal line 30 and the fourth sub-signal line 40 provided in this embodiment of this application can reduce diffraction gratings formed between the third signal line 30 and the fourth

sub-signal line **40**, to reduce impact of the third signal line **30** and the fourth sub-signal line **40** on light emitted into the display **2**, and improve transmittance of light in the first display region **A1** in which the first subpixel array **D1** is located. The optical component **6** in the terminal is disposed on the back of the display **2**, and corresponds to the first display region **A1**. Therefore, a daylighting effect of the optical component **6** can be improved.

(274) In addition, after the orthographic projections of the third signal line **30** and the fourth sub-signal line **40** on the substrate **23** overlap in the regions in which the transparent subpixels **T** are located, the area of the regions in which the transparent subpixels **T** are located may be increased, blocking of the regions in which the transparent subpixels **T** are located by the third signal line **30** and the fourth sub-signal line **40** is reduced, and transmittance of the regions in which the transparent subpixels **T** are located is improved. Therefore, a daylighting effect of the optical component **6** can be further improved.

(275) For the structures of the third signal line **30** and the fourth sub-signal line **40**, in a possible embodiment, as shown in FIG. **13a**, the third signal line **30** includes at least one third sub-signal line **31** and at least one fourth sub-signal line **32**, and the third sub-signal line **31** and the fourth sub-signal line **32** are disposed in parallel, and the third sub-signal line **31** and the fourth sub-signal line **32** are alternately connected along the extension direction of the third signal line **30**.

(276) The third sub-signal line **31** and the fourth sub-signal line **32** are disposed in parallel, that is, the third sub-signal line **31** and the fourth sub-signal line **32** are arranged in a staggered manner, and the third sub-signal line **31** and the fourth sub-signal line **32** are not on a same extension line.

(277) The third sub-signal line **31** and the fourth sub-signal line **32** are alternately connected along the extension direction of the third signal line **30**, and a connection manner between the first sub-signal line **11** and the second sub-signal line **12** is not limited. For example, as shown in FIG. **13a**, the third sub-signal line **31** is connected to the fourth sub-signal line **32** through a second connection line **33**.

(278) When the third sub-signal line **31** and the fourth sub-signal line **32** are at a same layer, the second connection line **33** may be at a same layer as the third sub-signal line **31**, and two ends of the second connection line **33** are directly connected to the third sub-signal line **31** and the fourth sub-signal line **32**. In this case, the third sub-signal line **31**, the fourth sub-signal line **32**, and the second connection line **33** may be of an integrated structure.

(279) When the third sub-signal line **31** and the fourth sub-signal line **32** are at different layers, the second connection line **33** may be at a same layer as the third sub-signal line **31**, or the second connection line **33** and the third sub-signal line **31** may be of an integrated structure. The second connection line **33** is connected to the fourth sub-signal line **32** through a via, to implement the connection between the third sub-signal line **31** and the fourth sub-signal line **32**. Alternatively, the second connection line **33** may be at a same layer as the fourth sub-signal line **32**, and the second connection line **33** and the fourth sub-signal line **32** may be of an integrated structure. The second connection line **33** is connected to the third sub-signal line **31** through a via, to implement the connection between the third sub-signal line **31** and the fourth sub-signal line **32**.

(280) Certainly, regardless of the structure, the second connection line **33** is not connected to the fourth signal line **40**, to avoid a short circuit.

(281) The fourth sub-signal line **32** is located in the regions in which the transparent subpixels **T** are located.

(282) In a same second signal line group **200**, an orthographic projection of the fourth sub-signal line **32** on the substrate **23** overlaps the orthographic projection of the fourth signal line **40** on the substrate **23**, but the fourth sub-signal line **32** and the fourth signal line **40** are disposed at different layers, and are insulated.

(283) That is, in the third signal line **30**, the fourth sub-signal line **32** is located in the regions in which the transparent subpixels **T** are located, and the fourth sub-signal line **32** is located right above or right below the fourth signal line **40**.

(284) For a structure of the fourth sub-signal line **32**, in some embodiments, as shown in FIG. **13a** and FIG. **13b**, a fourth sub-signal line **32** is located in a region in which the transparent subpixel **T** is located and does not penetrate the region, and the third sub-signal line **31** crosses a boundary between two adjacent transparent subpixels **T**. Orthographic projections of the first signal line **10** and the second signal line **20** on the substrate **23** do not overlap the orthographic projection of the fourth sub-signal line **32** on the substrate **23**. In addition, the orthographic projection of the first signal line **10** on the substrate **23** and the orthographic projection of the second signal line **20** on the substrate **23** cross an orthographic projection of the third sub-signal line **31** on the substrate **23**.

(285) That is, a fourth sub-signal line **32** is located in a region in which the transparent subpixel **T** is located, and does not cross signal lines (for example, the first signal line **10** and the second signal line **20**) located at a boundary between two adjacent transparent subpixels **T**.

(286) In this case, for a structure of the second sub-signal line **12**, as shown in FIG. **13a**, a second sub-signal line **12** is located in a region in which the transparent subpixel **T** is located, and does not cross signal lines (for example, the third signal line **30** and the fourth signal line **40**) located at a boundary between two adjacent transparent subpixels **T**. Alternatively, as shown in FIG. **13b**, the second sub-signal line **12** penetrates, along an extension direction of the second sub-signal line **12**, at least one region in which the transparent subpixel **T** is located.

(287) For the structure of the fourth sub-signal line **32**, in some other embodiments, as shown in FIG. **13c** and FIG. **13d**, to reduce a quantity of fourth sub-signal lines **32**, so as to reduce complexity of the third signal line **30**, the fourth sub-signal line **32** penetrates, along the extension direction of the fourth sub-signal line **32**, at least one region in which the transparent subpixel **T** is located.

(288) In this case, for the structure of the second sub-signal line **12**, as shown in FIG. **13c**, a second sub-signal line **12** is located in a region in which the transparent subpixel **T** is located, and does not cross signal lines (for example, the third signal line **30** and the fourth signal line **40**) located at a boundary between two adjacent transparent subpixels **T**. Alternatively, as shown in FIG. **13d**, the second sub-signal line **12** penetrates, along the extension direction of the second sub-signal line **12**, at least one region in which the transparent subpixel **T** is located.

(289) The following describes a location relationship between the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40**.

(290) In a first possible embodiment, details are as follows:

(291) As shown in FIG. **14a** (a section view along a direction **B1-B2** in FIG. **13a**), the fourth sub-signal line **32** and the third sub-signal line **31** are disposed at different layers, and the third sub-signal line **31** and the fourth signal line **40** are disposed at a same layer.

(292) That is, the third sub-signal line **31** in the third signal line **30** and the fourth signal line **40** are disposed at the same layer, and the fourth sub-signal line **32** in the third signal line **30** is jumpered to another film layer, so that the fourth sub-signal line **32** is located right above or right below the fourth signal line **40**.

(293) It may be understood that, as shown in FIG. **14a**, to avoid a short circuit of signal lines between adjacent film layers, an ILD layer is disposed between signal lines of adjacent layers. A quantity of ILD layers between the adjacent signal lines is not limited, and FIG. **14a** is merely an example. A material of the ILD layer is not limited, and materials that can perform an insulation function may all be applicable to the ILD layer.

(294) To avoid the short circuit between the second connection line **33** and the fourth signal line **40**, as shown in FIG. **14a**, the second connection line **33** and the fourth sub-signal line **32** are disposed at a same layer, and the second connection line **33** is connected to the third sub-signal line **31** through the via located at an ILD layer between the third sub-signal line **31** and the fourth sub-signal line **32**, to implement the connection between the third sub-signal line **31** and the fourth sub-signal line **32**.

(295) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the

second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(296) Optionally, as shown in FIG. **14a**, the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(297) That is, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(298) In this case, structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(299) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(300) Alternatively, optionally, as shown in FIG. **14b** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(301) In addition, the third sub-signal line **31** and the fourth signal line **40** are disposed at a same layer as the second sub-signal line **12**, and the fourth sub-signal line **32** and the first sub-signal line **11** are disposed at different layers, and the second sub-signal line **12** and the second signal line **20** are disposed at different layers.

(302) Therefore, when the second sub-signal line **12** is prepared, the third sub-signal line **31** and the fourth signal line **40** may be prepared in a same process, to simply a preparation process. In addition, the third sub-signal line **31** and the fourth signal line **40** are disposed at the same layer as the second sub-signal line **12**, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(303) In this case, structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13c**.

(304) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(305) Alternatively, optionally, as shown in FIG. **14c** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(306) In addition, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at a same layer, the fourth sub-signal line **32** is disposed at a different layer from the first sub-signal line **11** and the second signal line **20**, and the third sub-signal line **31** and the fourth signal line **40** are disposed at a different layer from the second sub-signal line **12**.

(307) Therefore, when the second sub-signal line **12** is prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(308) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13c**.

(309) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(310) Alternatively, optionally, as shown in FIG. **14d**, the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(311) In addition, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(312) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(313) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(314) Alternatively, optionally, as shown in FIG. **14e** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(315) In addition, the third sub-signal line **31** and the fourth signal line **40** are disposed at a same layer as the second sub-signal line **12**, and the fourth sub-signal line **32** and the first sub-signal line **11** are disposed at different layers, and the second sub-signal line **12** and the second signal line **20** are disposed at different layers.

(316) Therefore, when the second sub-signal line **12** is prepared, the third sub-signal line **31** and the fourth signal line **40** may be prepared in a same process, to simply a preparation process. In addition, the third sub-signal line **31** and the fourth signal line **40** are disposed at the same layer as the second sub-signal line **12**, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(317) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13c**.

(318) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(319) Alternatively, optionally, as shown in FIG. **14f** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(320) In addition, the third sub-signal line **31** and the fourth signal line **40** are disposed at a different layer from the second sub-signal line **12**, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at a same layer, and the fourth sub-signal line **32**, the first sub-signal line **11**, and the second signal line **20** are disposed at different layers.

(321) Therefore, when the second sub-signal line **12** is prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(322) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(323) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(324) Alternatively, optionally, as shown in FIG. **14g** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(325) In addition, the third sub-signal line **31** and the fourth signal line **40** are disposed at a different layer from the second sub-signal line **12**, and the fourth sub-signal line **32** and the first sub-signal line **11** are disposed at a same layer.

(326) Therefore, when the first sub-signal line **11** is prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line

32 and the first sub-signal line **11** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(327) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13b**.

(328) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(329) Alternatively, optionally, the second sub-signal line **12** and the first sub-signal line **11** are disposed at a same layer.

(330) When the second sub-signal line **12** and the first sub-signal line **11** are disposed at the same layer, the first connection line **13**, the second sub-signal line **12**, and the first sub-signal line **11** are disposed at a same layer. That is, as shown in FIG. **14h** (a section view along the direction B1-B2 in FIG. **13a**), a film layer location at which the first connection line **13** and the second sub-signal line **12** are located is a film layer location at which the first sub-signal line **11** is located.

(331) In addition, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(332) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(333) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(334) Alternatively, optionally, the second sub-signal line **12** and the first sub-signal line **11** are disposed at a same layer.

(335) When the second sub-signal line **12** and the first sub-signal line **11** are disposed at the same layer, the first connection line **13**, the second sub-signal line **12**, and the first sub-signal line **11** are disposed at a same layer. That is, as shown in FIG. **14i** (a section view along the direction B1-B2 in FIG. **13a**), a film layer location at which the first connection line **13** and the second sub-signal line **12** are located is a film layer location at which the first sub-signal line **11** is located.

(336) In addition, the fourth sub-signal line **32** is disposed at a same layer as the first sub-signal line **11** and the second sub-signal line **12**.

(337) Therefore, when the first sub-signal line **11** and the second sub-signal line **12** are prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line **32** is disposed at the same layer as the first sub-signal line **11** and the second sub-signal line **12**, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(338) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13b**.

(339) In a second possible embodiment, details are as follows:

(340) A difference between the second possible embodiment and the first possible embodiment lies in that the third sub-signal line **31** and the fourth signal line **40** are disposed at different layers.

(341) As shown in FIG. **15a** (a section view along a direction B1-B2 in FIG. **13a**), the fourth sub-signal line **32** and the third sub-signal line **31** are disposed at different layers, and the third sub-signal line **31** and the fourth signal line **40** are disposed at different layers.

(342) That is, the third sub-signal line **31** and the fourth sub-signal line **32** in the third signal line **30** are disposed at different layers from the fourth signal line **40**, so that the fourth sub-signal line **32** is located right above or right below the fourth signal line **40**.

(343) The third sub-signal line **31** and the fourth signal line **40** are disposed at different layers, and the third sub-signal line **31** may be located above the fourth signal line **40**. In this case, the second

connection line **33** may be at a same layer as the third sub-signal line **31**, or the second connection line **33** may be at a same layer as the fourth sub-signal line **32**, to avoid a short circuit between the second connection line **33** and the fourth signal line **40**. The third sub-signal line **31** may alternatively be located below the fourth signal line **40**. In this case, the second connection line **33** is at a same layer as the fourth sub-signal line **32**, to avoid the short circuit between the second connection line **33** and the fourth signal line **40**. In this example, an example in which the third sub-signal line **31** is located above the fourth signal line **40**, and the second connection line **33** and the fourth sub-signal line **32** are disposed at a same layer is used for description.

(344) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(345) Optionally, as shown in FIG. **15a**, the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(346) In addition, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(347) In this case, structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(348) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(349) Alternatively, optionally, as shown in FIG. **15b** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(350) In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at a same layer.

(351) Therefore, when the second sub-signal line **12** is prepared, the fourth signal line **40** may be prepared in a same process, to simply a preparation process. In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(352) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13c**.

(353) Alternatively, optionally, as shown in FIG. **15c** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(354) In addition, the third sub-signal line **31** and the second sub-signal line **12** are disposed at a same layer.

(355) Therefore, when the second sub-signal line **12** is prepared, the third sub-signal line **31** may be prepared in a same process, to simply a preparation process. In addition, the third sub-signal line **31** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(356) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13c**.

(357) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(358) Alternatively, optionally, as shown in FIG. **15d** (a section view along the direction B1-B2 in

FIG. 13a), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer. (359) In addition, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at a same layer.

(360) Therefore, when the second sub-signal line **12** is prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(361) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. 13a to FIG. 13c.

(362) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(363) Alternatively, optionally, as shown in FIG. 15e, the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(364) In addition, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(365) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. 13a to FIG. 13d.

(366) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(367) Alternatively, optionally, as shown in FIG. 15f (a section view along the direction B1-B2 in FIG. 13a), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(368) In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at a same layer.

(369) Therefore, when the second sub-signal line **12** is prepared, the fourth signal line **40** may be prepared in a same process, to simply a preparation process. In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(370) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. 13a or FIG. 13c.

(371) Alternatively, optionally, as shown in FIG. 15g (a section view along the direction B1-B2 in FIG. 13a), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(372) In addition, the third sub-signal line **31** and the second sub-signal line **12** are disposed at a same layer.

(373) Therefore, when the second sub-signal line **12** is prepared, the third sub-signal line **31** may be prepared in a same process, to simply a preparation process. In addition, the third sub-signal line **31** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(374) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. 13a or FIG. 13c.

(375) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the

second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(376) Alternatively, optionally, as shown in FIG. **15h** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers. (377) In addition, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at a same layer.

(378) Therefore, when the second sub-signal line **12** is prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line **32** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(379) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13c**.

(380) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(381) Alternatively, optionally, as shown in FIG. **15i** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(382) In addition, the fourth sub-signal line **32** and the first sub-signal line **11** are disposed at a same layer.

(383) Therefore, when the first sub-signal line **11** is prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line **32** and the first sub-signal line **11** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(384) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13b**.

(385) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(386) Alternatively, optionally, the second sub-signal line **12** and the first sub-signal line **11** are disposed at a same layer.

(387) When the second sub-signal line **12** and the first sub-signal line **11** are disposed at the same layer, the first connection line **13**, the second sub-signal line **12**, and the first sub-signal line **11** are disposed at a same layer. That is, as shown in FIG. **15j** (a section view along the direction B1-B2 in FIG. **13a**), a film layer location at which the first connection line **13** and the second sub-signal line **12** are located is a film layer location at which the first sub-signal line **11** is located.

(388) In addition, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(389) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(390) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(391) Alternatively, optionally, the second sub-signal line **12** and the first sub-signal line **11** are disposed at a same layer.

(392) When the second sub-signal line **12** and the first sub-signal line **11** are disposed at the same

layer, the first connection line **13**, the second sub-signal line **12**, and the first sub-signal line **11** are disposed at a same layer. That is, as shown in FIG. **15k** (a section view along the direction B1-B2 in FIG. **13a**), a film layer location at which the first connection line **13** and the second sub-signal line **12** are located is a film layer location at which the first sub-signal line **11** is located.

(393) In addition, the fourth sub-signal line **32** is disposed at a same layer as the first sub-signal line **11** and the second sub-signal line **12**.

(394) Therefore, when the first sub-signal line **11** and the second sub-signal line **12** are prepared, the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the fourth sub-signal line **32** is disposed at the same layer as the first sub-signal line **11** and the second sub-signal line **12**, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(395) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13b**.

(396) In a third possible embodiment, details are as follows:

(397) A difference between the third possible embodiment and the first possible embodiment lies in that the third sub-signal line **31** and the fourth sub-signal line **32** are disposed at a same layer.

(398) As shown FIG. **16a** (a section view along a direction B1-B2 in FIG. **13a**), the third sub-signal line **31** and the fourth sub-signal line **32** are disposed at a same layer, and in a same second signal line group **200**, the orthographic projection of the third sub-signal line **31** on the substrate **23** and the orthographic projection of the fourth signal line **40** on the substrate **23** are disposed side by side.

(399) That is, the third sub-signal line **31** and the fourth sub-signal line **32** in the third signal line **30** are disposed at the same layer, and the third signal line **30** and the fourth signal line **40** are disposed at different layers. The orthographic projection of the third sub-signal line **31** in the third signal line **30** on the substrate **23** and the orthographic projection of the fourth signal line **40** on the substrate **23** are disposed side by side, and the fourth sub-signal line **32** in the third signal line **30** is located right above or right below the fourth signal line **40**.

(400) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(401) Optionally, as shown in FIG. **16a**, the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(402) In addition, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(403) In this case, structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(404) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(405) Alternatively, optionally, as shown in FIG. **16b** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(406) In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at a same layer.

(407) Therefore, when the second sub-signal line **12** is prepared, the fourth signal line **40** may be prepared in a same process, to simply a preparation process. In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is

lightened and thin.

(408) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13c**.

(409) Alternatively, optionally, as shown in FIG. **16c** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at a same layer.

(410) In addition, the third sub-signal line **31** and the fourth sub-signal line **32** are disposed at a same layer as the second sub-signal line **12**.

(411) Therefore, when the second sub-signal line **12** is prepared, the third sub-signal line **31** and the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the third sub-signal line **31** and the fourth sub-signal line **32** are disposed at the same layer as the second sub-signal line **12**, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(412) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13c**.

(413) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(414) Alternatively, optionally, as shown in FIG. **16d** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(415) In addition, the first sub-signal line **11**, the second sub-signal line **12**, and the second signal line **20** are disposed at different layers from the third sub-signal line **31** and the fourth sub-signal line **32**.

(416) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** to FIG. **13d**.

(417) Alternatively, optionally, as shown in FIG. **16e** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(418) In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at a same layer.

(419) Therefore, when the second sub-signal line **12** is prepared, the fourth signal line **40** may be prepared in a same process, to simply a preparation process. In addition, the fourth signal line **40** and the second sub-signal line **12** are disposed at the same layer, so that a quantity of insulation layers and a quantity of conducting layers between layers can be reduced, and the display **2** is lightened and thin.

(420) In this case, the structures of the second sub-signal line **12** and the fourth sub-signal line **32** may be shown in FIG. **13a** or FIG. **13c**.

(421) A location relationship between the first sub-signal line **11**, the second sub-signal line **12**, the second signal line **20**, the third sub-signal line **31**, the fourth sub-signal line **32**, and the fourth signal line **40** is as follows:

(422) Alternatively, optionally, as shown in FIG. **16f** (a section view along the direction B1-B2 in FIG. **13a**), the first sub-signal line **11** and the second sub-signal line **12** are disposed at different layers, and the first sub-signal line **11** and the second signal line **20** are disposed at different layers.

(423) In addition, the third sub-signal line **31** and the fourth sub-signal line **32** are disposed at a same layer as the second sub-signal line **12**.

(424) Therefore, when the second sub-signal line **12** is prepared, the third sub-signal line **31** and the fourth sub-signal line **32** may be prepared in a same process, to simply a preparation process. In addition, the third sub-signal line **31** and the fourth sub-signal line **32** are disposed at the same layer as the second sub-signal line **12**, so that a quantity of insulation layers and a quantity of

conducting layers between layers can be reduced, and the display 2 is lightened and thin.

(425) In this case, the structures of the second sub-signal line 12 and the fourth sub-signal line 32 may be shown in FIG. 13a or FIG. 13c.

(426) A location relationship between the first sub-signal line 11, the second sub-signal line 12, the second signal line 20, the third sub-signal line 31, the fourth sub-signal line 32, and the fourth signal line 40 is as follows:

(427) Alternatively, optionally, the second sub-signal line 12 and the first sub-signal line 11 are disposed at a same layer.

(428) When the second sub-signal line 12 and the first sub-signal line 11 are disposed at the same layer, the first connection line 13 is disposed at a same layer as the second sub-signal line 12 and the first sub-signal line 11. That is, as shown in FIG. 16g (a section view along the direction B1-B2 in FIG. 13a), a film layer location at which the first connection line 13 and the second sub-signal line 12 are located is a film layer location at which the first sub-signal line 11 is located.

(429) In addition, the first sub-signal line 11, the second sub-signal line 12, and the second signal line 20 are disposed at different layers from the third sub-signal line 31 and the fourth sub-signal line 32.

(430) In this case, the structures of the second sub-signal line 12 and the fourth sub-signal line 32 may be shown in FIG. 13a to FIG. 13d.

(431) The descriptions are merely specific implementations of this application, but are not intended to limit the protection scope of this application. Any variation or replacement readily figured out by a person skilled in the art within the technical scope disclosed in this application shall fall within the protection scope of this application. Therefore, the protection scope of this application shall be subject to the protection scope of the claims.

Claims

1. A display, system comprising: a layered structure comprising a substrate; at least one first subpixel array disposed on the substrate and comprising: a plurality of first light-emitting subpixels; and a plurality of transparent subpixels, wherein the first light-emitting subpixels and the transparent subpixels are arranged in a mixed manner; a plurality of first signal lines disposed on the substrate, wherein the first signal lines are insulated from each other; and a plurality of second signal lines disposed on the substrate, wherein the second signal lines are insulated from each other, wherein the second signal lines and the first signal lines are extended in a same direction, insulated from each other, and alternately disposed, wherein a first signal line group comprises one first signal line and one second signal line disposed between adjacent rows of subpixels in the at least one first subpixel array, and wherein portions of the one first signal line and the one second signal line overlap in a region in which a corresponding transparent subpixel is located.
2. The display system of claim 1, wherein the one first signal line comprises: at least one first sub-signal line; and at least one second sub-signal line, wherein the at least one first sub-signal line and the at least one second sub-signal line are disposed in parallel and are alternately coupled along an extension direction of the one first signal line, wherein, in a same first signal line group, a portion of the at least one second sub-signal line on the substrate overlaps an overlaps a portion of the one second signal line on the substrate, wherein the at least one second sub-signal line is located in the region, and wherein the at least one second sub-signal line and the one second signal line are disposed at first different layers.
3. The display system of claim 2, wherein the at least one second sub-signal line and the at least one first sub-signal line are disposed at second different layers.
4. The display system of claim 3, wherein the at least one first sub-signal line and the one second signal line are disposed at a same layer or at third different layers.
5. The display system of claim 2, wherein the at least one second sub-signal line and the at least

one first sub-signal line are disposed at a same layer, and wherein, in the same first signal line group, a portion of the at least one first sub-signal line on the substrate and a portion of the second signal line on the substrate are disposed side by side.

6. The display system of claim 2 further comprising: a plurality of third signal lines insulated from each other; and a plurality of fourth signal lines insulated from each other, wherein the third signal lines and the fourth signal lines are disposed in parallel, insulated from each other, and alternately disposed on the substrate, wherein the at least one second sub-signal line is disposed at a same layer as the third signal lines or the fourth signal lines, and wherein the one first signal line intersects the third signal lines.

7. The display system of claim 2 further comprises comprising: a plurality of third signal lines insulated from each other; and a plurality of fourth signal lines insulated from each other, wherein the third signal lines and the fourth signal lines are extended in a same direction, insulated from each other, and alternately disposed on the substrate, wherein a second signal line group is disposed between the adjacent rows and comprises one third signal line and one fourth signal line, wherein portions of the one third signal line and the one fourth signal line on the substrate overlap in the region, and wherein the one first signal line intersects the one third signal line.

8. The display system of claim 7, wherein the one third signal line comprises: at least one third sub-signal line; and at least one fourth sub-signal line, wherein the at least one third sub-signal line and the at least one fourth sub-signal line are disposed in parallel and alternately coupled along an extension direction of the one third signal line, wherein, in a same second signal line group, a portion of the at least one fourth sub-signal line on the substrate overlaps a portion of the one fourth signal line on the substrate, wherein the at least one fourth sub-signal line is located in the region, and wherein the at least one fourth sub-signal line and the one fourth signal line are disposed at second different layers.

9. The display system of claim 8, wherein the at least one fourth sub-signal line and the at least one third sub-signal line are disposed at third different layers.

10. The display system of claim 9, wherein the at least one third sub-signal line and the one fourth signal line are disposed at a same layer or at fourth different layers.

11. The display system of claim 8, wherein the at least one fourth sub-signal line and the at least one third sub-signal line are disposed at a same layer, and wherein, in the same second signal line group, a portion of the at least one third sub-signal line on the substrate and a portion of the fourth signal line on the substrate are disposed side by side.

12. The display system of claim 8, wherein each of the at least one fourth sub-signal line is located in the region, wherein adjacent fourth sub-signal lines of the at least one fourth sub-signal line are coupled through the at least one third sub-signal line, and wherein a portion of the one first signal line on the substrate does not overlap the fourth sub-signal line on the substrate and crosses a portion of the at least one third sub-signal line on the substrate.

13. The display system of claim 12, wherein the at least one fourth sub-signal line and the one second signal line are disposed at a same layer.

14. The display system of claim 8, wherein the at least one fourth sub-signal line is disposed at a different layer from the one first signal line and the one second signal line, and wherein the at least one fourth sub-signal line penetrates, along an extension direction of the at least one fourth sub-signal line, the region.

15. The display system of claim 8, wherein each of the at least one second sub-signal line is located in the region, wherein the at least one first sub-signal line crosses a boundary between two adjacent transparent subpixels, and wherein portion of the one third signal line on the substrate or a portion of the fourth signal line on the substrate does not overlap the second sub-signal line on the substrate and crosses the at least one first sub-signal line on the substrate.

16. The display system of claim 15, wherein the at least one second sub-signal line is disposed at a same layer as the one third signal line or the one fourth signal line when the one first signal line

comprises the at least one first sub-signal line and the at least one second sub-signal line.

17. The display system of claim 7, wherein the at least one second sub-signal line is disposed at a different layer from the one third signal line and the one fourth signal line when the one first signal line comprises the at least one first sub-signal line and the at least one second sub-signal line, and wherein the at least one second sub-signal line penetrates, along an extension direction of the at least one second sub-signal line, the region.

18. The display system of claim 7, wherein the one first signal line and the one third signal line are mutually a grid line and a data line.

19. The display system of claim 1, wherein the first light-emitting subpixels are grouped into a plurality of light-emitting pixels, wherein each of the light-emitting pixels comprises at least three first light-emitting subpixels that are adjacent to each other and that are respectively used to display three primary colors, wherein the transparent subpixels are grouped into a plurality of transparent pixels, wherein a quantity of transparent subpixels comprised in each of the transparent pixels is equal to a quantity of first light-emitting subpixels comprised in one light-emitting pixel, wherein a plurality of transparent subpixels in a same transparent pixel are adjacent to each other, and wherein in the at least one first subpixel array, the light-emitting pixels and the transparent pixels are arranged in a mixed manner.

20. A terminal comprising: a display comprising: a back; a layered structure comprising a substrate; at least one first subpixel array disposed on the substrate and comprising: a plurality of first light-emitting subpixels; and a plurality of transparent subpixels, wherein the first light-emitting subpixels and the transparent subpixels are arranged in a mixed manner; a plurality of first signal lines disposed on the substrate, wherein the first signal lines are insulated from each other; and a plurality of second signal lines disposed on the substrate, wherein the second signal lines are insulated from each other, wherein the second signal lines and the first signal lines are extended in a same direction, insulated from each other, and alternately disposed, wherein a first signal line group comprising one first signal line and one second signal line is disposed between adjacent rows of subpixels in the at least one first subpixel array, and wherein a portion of the one first signal line and the one second signal line on the substrate overlap in a first region in which a corresponding transparent subpixel is located; and an optical component disposed on the back, and comprising: a light-receiving surface facing the display, wherein a portion of the optical component on the display is located in a second region in which the at least one first subpixel array is located.
