

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414788
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lee; Jung Joo et al.

End tool of surgical instrument and surgical instrument including the same

Abstract

According to the present disclosure, provided is a surgical instrument in which an actual motion of bending an end tool or performing a surgical treatment intuitively matches a motion of a manipulation portion corresponding thereto. In detail, to this end, provided are an end tool having various degrees of freedom, a manipulation portion having a structure to enable intuitive manipulation of a motion of the end tool, and a driving force transmission portion for transmitting a driving force of the manipulation portion to the end tool so that the end tool operates as manipulated by the manipulation portion.

Inventors: Lee; Jung Joo (Yongin-si, KR), Kim; Hee Jin (Seoul, KR), Jang; Dong Kyu (Seoul, KR)

Applicant: LIVSMED INC. (Seongnam-si, KR)

Family ID: 1000008821040

Assignee: LIVSMED INC. (Seongnam-si, KR)

Appl. No.: 17/553127

Filed: December 16, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220104841 A1	Apr. 07, 2022

Related U.S. Application Data

continuation parent-doc US 17059418 US 11278302 WO PCT/KR2019/014557 20191031 child-doc US 17553127

Publication Classification

Int. Cl.: A61B17/29 (20060101); A61B17/00 (20060101)

U.S. Cl.:

CPC A61B17/29 (20130101); A61B2017/00424 (20130101); A61B2017/2903 (20130101); A61B2017/2912 (20130101); A61B2017/2938 (20130101)

Field of Classification Search

CPC: A61B (17/2912); A61B (17/2915); A61B (17/32); A61B (34/71); A61B (2017/2927); A61B (2034/305); A61B (2017/2912); A61B (2017/2915); A61B (2017/32); A61B (17/29)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6394998	12/2001	Wallace et al.	N/A	N/A
10631886	12/2019	Lee et al.	N/A	N/A
10709467	12/2019	Lee et al.	N/A	N/A
10722315	12/2019	Lee et al.	N/A	N/A
11141181	12/2020	Scheldes	N/A	N/A
2007/0088340	12/2006	Brock et al.	N/A	N/A
2007/0208375	12/2006	Nishizawa et al.	N/A	N/A
2010/0011901	12/2009	Burbank	N/A	N/A
2010/0016852	12/2009	Manzo et al.	N/A	N/A
2011/0106145	12/2010	Jeong	N/A	N/A
2015/0150635	12/2014	Kilroy et al.	N/A	N/A
2017/0042560	12/2016	Lee et al.	N/A	N/A
2020/0323601	12/2019	Lee	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102015118914	12/2016	DE	N/A
1984-102587	12/1983	JP	N/A
1984-102587	12/1983	JP	N/A
2010-220786	12/2009	JP	N/A
2016-518160	12/2015	JP	N/A
2017-513678	12/2016	JP	N/A
2018-505001	12/2017	JP	N/A
2018-149299	12/2017	JP	N/A
2018-527094	12/2017	JP	N/A
10-2010-0099818	12/2009	KR	N/A
10-2011-0028613	12/2010	KR	N/A
10-2013-0057250	12/2012	KR	N/A
10-1772805	12/2016	KR	N/A
2014/151952	12/2013	WO	N/A

OTHER PUBLICATIONS

Office Action for EU Application No. 19950802.9, Jun. 2, 2023, Extended European Search Report. cited by applicant

Notice of Reasons for Refusal, Japanese Patent Application No. 2021-572472, Jul. 6, 2023, Ikimura, Tatsuto 3616 3I00. cited by applicant

Notice of Reason for Refusal for Japanese application No. 2021-572472 issued on Dec. 22, 2022. cited by applicant

Primary Examiner: Aleman; Sarah W

Attorney, Agent or Firm: Bridgeway IP Law Group, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation application of U.S. patent application Ser. No. 17/059,418 filed on Nov. 27, 2020, which is a national-stage under 35 USC 371 of PCT international application No. PCT/KR2019/014557 filed on Oct. 31, 2019, the entire disclosure of which is hereby incorporated by reference.

TECHNICAL FIELD

(1) The present disclosure relates to an end tool of a surgical instrument and a surgical instrument having the same, and more particularly, to an end tool of a surgical instrument which may be manually operated in a laparoscopic surgery or other various surgeries and a surgical instrument having the same.

BACKGROUND ART

(2) Medically, surgery refers to the treatment of a disease by using medical devices to cut, slit, or manipulate skin, mucous membrane, or other tissue. In particular, open surgery of cutting and opening the skin of a surgical site to treat, reshape, or remove organs therein causes bleeding, side effects, pain to the patient, and scars. Accordingly, recently, surgery using a robot or surgery performed by inserting only a medical device, for example, a laparoscope, a surgical instrument, a microsurgical microscope, or the like, in the body by forming a predetermined hole in the skin, has been spotlighted as an alternative.

(3) A surgical instrument is a tool for performing surgery at a surgical site by manipulating an end tool provided at one end of a shaft passing through a hole drilled in the skin by a medical doctor using a predetermined driving unit or a robot arm. The end tool provided at the surgical instrument performs a rotation operation, a gripping operation, a cutting operation, or the like through a predetermined structure.

(4) However, a surgical instrument according to the related art has a problem in that accessing a surgical site and performing various surgical motions are not easy because an end tool portion of the surgical instrument according to the related art is not bent. To address the above problem, surgical instruments having a bendable end tool portion have been developed. However, as a motion of a manipulating portion for bending an end tool or performing a surgical operation does not intuitively match with an actual motion of bending an end tool or performing a surgical treatment, from an operator's point of view, there is a problem in that an intuitive operation is not easy and it takes a long time to master a use method.

(5) The above-mentioned background technology is technical information acquired by the inventor to derive the present invention or during the derivation process of the present invention, and is not

necessarily a known technology disclosed to the general public before filing the present invention.

DESCRIPTION OF EMBODIMENTS

Technical Problem

(6) Provided is a surgical instrument in which an actual motion of bending an end tool or performing a surgical treatment intuitively matches a motion of a manipulation portion corresponding thereto. In detail, to this end, provided are an end tool having various degrees of freedom, a manipulation portion having a structure to enable intuitive manipulation of a motion of the end tool, and a driving force transmission portion for transmitting a driving force of the manipulation portion to the end tool so that the end tool operates as manipulated by the manipulation portion.

Solution to Problem

(7) According to an embodiment of the present disclosure, an end tool of a surgical instrument includes a first jaw and a second jaw capable of rotating independently of each other, a J11 pulley coupled to the first jaw and formed to be capable of rotating around a first axis, a J21 pulley coupled to the second jaw and formed to be capable of rotating around an axis that is substantially the same as or parallel to the first axis, an end tool hub including a pair of jaw pulley coupling portions formed to face each other and a guide portion connecting the pair of jaw pulley coupling portions, wherein at least parts of the J11 pulley and the J21 pulley are accommodated in a space formed by the pair of jaw pulley coupling portion and the guide portion, and a region adjacent to the J11 pulley and the J21 pulleys in the guide portion has a section that is curved with a certain radius of curvature, a J12 pulley and a J14 pulley formed at one side of the end tool hub to be capable of rotating around a second axis forming an angle with respect to the first axis, and a J22 pulley and a J24 pulley formed at one side of the end tool hub to be capable of rotating around an axis that is substantially the same as or parallel to the second axis.

(8) According to another embodiment of the present disclosure, a surgical instrument includes an end tool formed to be capable of rotating in two or more directions and including a first jaw and a second jaw, each being formed to be rotatable, a manipulation portion configured to control a rotation of the end tool in the two or more directions, a driving force transmission portion including a first jaw wire connected to the manipulation portion and transmitting a rotation of the manipulation portion to the first jaw and a second jaw wire connected to the manipulation portion and transmitting a rotation of the manipulation portion to the second jaw, and a connection portion extending in a first direction (an X-axis), having one end portion to which the end tool is coupled and another end portion to which the manipulation portion is coupled to connect the manipulation portion and the end tool, and including a bent portion that is bent one or more times while connecting the end tool to the manipulation portion, wherein the end tool further includes a pair of jaw pulley coupling portions formed to face each other, and an end tool hub including a guide portion connecting the pair of jaw pulley coupling portions, and at least parts of the J11 pulley and the J21 pulley are accommodated in a space formed by the pair of jaw pulley coupling portion and the guide portion, and a region adjacent to the J11 pulley and the J21 pulleys in the guide portion has a section that is curved with a certain radius of curvature.

(9) Other aspects, features, and advantages than those described above will become apparent from the following drawings, claims, and detailed description of the disclosure.

Advantageous Effects of Disclosure

(10) According to the present disclosure, as a manipulating direction of a manipulation portion by a surgical operator and an operating direction of an end tool are intuitively the same direction, convenience of a surgical operator may be improved and accuracy, reliability, and rapidity of surgery may be improved.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1A is a conceptual view of a pitch motion of a surgical instrument according to the related art, and FIG. 1B is a conceptual view of a yaw motion thereof.
- (2) FIG. 1C is a conceptual view of a pitch motion of a surgical instrument according to another related art, FIG. 1D is a conceptual view of a yaw motion thereof.
- (3) FIG. 1E is a conceptual view of a pitch motion of a surgical instrument according to the present disclosure, and FIG. 1F is a conceptual view of a yaw motion thereof.
- (4) FIG. 2 is a perspective view of a surgical instrument according to an embodiment of the disclosure.
- (5) FIG. 3 is a side view of the surgical instrument of FIG. 2
- (6) FIGS. 4 and 5 are perspective views of an end tool of the surgical instrument of FIG. 2.
- (7) FIG. 6 illustrates an end tool hub of the surgical instrument of FIG. 4.
- (8) FIGS. 7 and 8 are plan views of an end tool of a surgical instrument according to the related art.
- (9) FIG. 9 is a plan view of the end tool of the surgical instrument of FIG. 2.
- (10) FIG. 10 illustrates a comparison between the end tool of the surgical instrument of FIG. 8 according to the related art and the end tool of the surgical instrument of FIG. 4 according to an embodiment of the disclosure.
- (11) FIG. 11 illustrates a modified example of the end tool of FIG. 4.
- (12) FIGS. 12 and 13 are perspective views of the manipulation portion of the surgical instrument of FIG. 2.
- (13) FIG. 14 schematically illustrates only a configuration of pulleys and wires forming a joint of the surgical instrument of FIG. 12 according to an embodiment of the disclosure.
- (14) FIGS. 15A and 15B schematically illustrate a configuration of pulleys and wires related to an actuation motion and a yaw motion of the surgical instrument of FIG. 12 according to an embodiment of the disclosure, for a first jaw and a second jaw.
- (15) FIG. 16 is a perspective view of a yaw motion of the surgical instrument of FIG. 12.
- (16) FIGS. 17A and 17B schematically illustrate a configuration of pulleys and wires related to a pitch motion of the surgical instrument of FIG. 12 according to an embodiment of the disclosure, for a first jaw and a second jaw.
- (17) FIG. 18 is a perspective view of the pitch motion of the surgical instrument of FIG. 12.

BEST MODE

- (18) As the disclosure allows for various changes and numerous embodiments, embodiments will be illustrated in the drawings and described in detail in the written description. However, this is not intended to limit the disclosure to particular modes of practice, and it is to be appreciated that all changes, equivalents, and substitutes that do not depart from the spirit and technical scope of the disclosure are encompassed in the disclosure. In the description of the disclosure, certain detailed explanations of the related art are omitted when it is deemed that they may unnecessarily obscure the essence of the disclosure.
- (19) While such terms as “first,” “second,” etc., may be used to describe various components, such components must not be limited to the above terms. The above terms are used only to distinguish one component from another.
- (20) The terms used in the specification are merely used to describe embodiments, and are not intended to limit the disclosure. An expression used in the singular encompasses the expression of the plural, unless it has a clearly different meaning in the context. In the specification, it is to be understood that the terms such as “including,” “having,” and “comprising” are intended to indicate the existence of the features, numbers, steps, actions, components, parts, or combinations thereof disclosed in the specification, and are not intended to preclude the possibility that one or more other features, numbers, steps, actions, components, parts, or combinations thereof may exist or may be added.

(21) Hereinafter, exemplary embodiments will be described in detail with reference to the accompanying drawings, and in the description with reference to the drawings, the same or corresponding constituents are indicated by the same reference numerals and redundant descriptions thereof are omitted.

(22) Furthermore, in the description of various embodiments of the disclosure, it is not necessary to independently interpreted or worked each embodiment, and technical concepts described in the respective embodiments should be understood to be interpreted or worked by being combined to another embodiment that is individually described.

Surgical Instrument According to an Embodiment

(23) A surgical instrument according to the present disclosure is characteristic in that, when a manipulation portion is rotated in any one direction with respect to at least one of pitch, yaw, and actuation motions, an end tool is rotated in the intuitively same direction as a manipulating direction of the manipulation portion.

(24) FIG. 1A is a concept view of a pitch motion of a surgical instrument according to the related art, and FIG. 1B is a concept view of a yaw motion thereof.

(25) Referring to FIG. 1A, in performing a pitch motion of a surgical instrument according to the related art, in a state in which an end tool **120a** is formed in front of a rotation center **121a** of the end tool **120a**, and a manipulation portion **110a** is formed at the rear of a rotation center **111a** of the manipulation portion **110a**, when the manipulation portion **110a** is rotated clockwise, the end tool **120a** is also rotated clockwise, and when the manipulation portion **110a** is rotated counterclockwise, the end tool **120a** is also rotated counterclockwise. Referring to FIG. 1B, in performing a yaw motion of the surgical instrument according to the related art, in a state in which the end tool **120a** is formed in front of the rotation center **121a** of the end tool **120a**, and the manipulation portion **110a** is formed at the rear of the rotation center **111a** of the manipulation portion **110a**, when the manipulation portion **110a** is rotated clockwise, the end tool **120a** is also rotated clockwise, and when the manipulation portion **110a** is rotated counterclockwise, the end tool **120a** is also rotated counterclockwise. In this case, in view of the left and right directions of a user, when the user moves the manipulation portion **110a** to the left, the end tool **120a** moves to the right, and when the user moves the manipulation portion **110a** to the right, the end tool **120a** moves to the left. Consequently, as the user's manipulating direction and the end tool's operating direction are opposite to each other, the user may make an error and user's manipulation may not be easy.

(26) FIG. 1C is a concept view of a pitch motion of a surgical instrument according to another related art, FIG. 1D is a concept view of a yaw motion thereof.

(27) Referring to FIG. 1C, in a surgical instrument according to the related art, which is partially formed in a mirror symmetry, in performing a pitch motion, in a state in which an end tool **120b** is formed in front of a rotation center **121b** of the end tool **120b**, and a manipulation portion **110b** is formed at the rear of a rotation center **111b** of the manipulation portion **110b**, when the manipulation portion **110b** is rotated clockwise, the end tool **120b** is rotated counterclockwise, and when the manipulation portion **110b** is rotated counterclockwise, the end tool **120b** is rotated clockwise. In this case, in view of rotating directions of the manipulation portion **110b** and the end tool **120b**, a rotating direction in which the user rotates the manipulation portion **110b** and a rotating direction of the end tool **120b** according thereto are opposite to each other. Consequently, the user may be confused with the manipulating direction, and as the operation of a joint is not intuitive, the user may make an error. Furthermore, referring to FIG. 1D, in performing a yaw motion, in a state in which the end tool **120b** is formed in front of the rotation center **121b** of the end tool **120b**, and the manipulation portion **110b** is formed at the rear of the rotation center **111b** of the manipulation portion **110b**, when the manipulation portion **110b** is rotated clockwise, the end tool **120b** is rotated counterclockwise, and when the manipulation portion **110b** is rotated counterclockwise, the end tool **120b** is rotated clockwise. In this case, in view of rotating directions of the manipulation portion **110b** and the end tool **120b**, a rotating direction in which the user

rotates the manipulation portion **110b** and a rotating direction of the end tool **120b** according thereto are opposite to each other. Consequently, the user may be confused with the manipulating direction, and as the operation of a joint is not intuitive, the user may make an error. In the user's pitch or yaw manipulation of the surgical instrument according to the related art, the user's manipulating direction and the end tool's operating direction do not match each other in view of one of the rotating direction and the left and right directions. This is because the configurations of the end tool and the manipulation portion are different from each other in the joint configuration of the surgical instrument according to the related art. In other words, while the end tool is formed in front of the rotation center of the end tool, the manipulation portion is formed at the rear of the rotation center of the manipulation portion. To address the above problem, a surgical instrument of FIGS. **1E** and **1F** according to an embodiment of the disclosure is characteristic in that an end tool **120c** is formed in front of a rotation center **121c** of the end tool **120c** and a manipulation portion **110c** is also formed in front of a rotation center **111c** of the manipulation portion **110c** so that the operations of the manipulation portion **110c** and the end tool **120c** are intuitively matched with each other. When the characteristics are expressed in a different way, unlike an existing example in which the manipulation portion **110c** is close to the user with respect to a joint thereof (that is, away from the end tool **120c**), as illustrated in FIGS. **1A**, **1B**, **1C**, and **1D**, the surgical instrument of FIGS. **1E** and **1F** according to an embodiment of the disclosure is formed such that at least a part of the manipulation portion **110c** is closer to the end tool **120c** with respect to a joint thereof (than the joint thereof) end tool at any one moment or more in a manipulation process.

(28) In other words, in the surgical instrument according to the related art as illustrated in FIGS. **1A**, **1B**, **1C**, and **1D**, while the end tool is located in front of a rotation center thereof, the manipulation portion is formed at the rear of a rotation center thereof, and as the end tool is moved at a front side thereof with a rear side fixed through a motion of the manipulation portion that moves at a rear side thereof with a front side thereof fixed, it is not an intuitively matching structure. Accordingly, a mismatch occurs between the manipulation of the manipulation portion and the motion of the end tool in view of the left and right directions or in view of the rotating direction, which may confuse the user, and also as it is difficult to intuitively quickly perform the manipulation of the manipulation portion, an error may be made. In contrast, in the surgical instrument according to an embodiment of the disclosure, as both of the end tool and the manipulation portion are moved with respect to the rotation center formed at the rear side thereof, it may be said that the motions are intuitively matched with each other in terms of structure. In other words, as a moving part of the end tool is moved with respect to the rotation center formed at the rear side thereof, a moving part of the manipulation portion is also moved with respect to the rotation center formed at the rear side thereof, and thus it may be said that the motions are intuitively matched with each other in terms of structure. Accordingly, the user may intuitively quickly perform a control in a direction toward the end tool, and a possibility of making an error may be remarkably reduced. In the following description, a detailed mechanism enabling the above-described function is described below.

(29) FIG. **2** is a perspective view of a surgical instrument according to an embodiment of the disclosure, and FIG. **3** is a side view of the surgical instrument of FIG. **2**.

(30) Referring to FIGS. **2** and **3**, a surgical instrument **100** according to an embodiment of the disclosure may include a manipulation portion **110**, an end tool **120**, a driving force transmission portion **130**, and a connection portion **140**. The connection portion **140** has a hollow shaft shape for accommodating therein one or more wires that are described below, one end portion to which the manipulation portion **110** is coupled, and the other end portion to which the end tool **120** is coupled, and may connect the manipulation portion **110** to the end tool **120**. The connection portion **140** of the surgical instrument **100** according to an embodiment of the disclosure may characteristically include a bent portion **141** formed at the side of the manipulation portion **110**. As such, as the end portion the connection portion **140** at the side of the manipulation portion **110** is

formed to be bent, a pitch manipulation portion **111**, a yaw manipulation portion **112**, and an actuation manipulation portion **113** may be formed along an extension line of the end tool **120** or adjacent to the extension line. In other words, it may be said that the pitch manipulation portion **111** and the yaw manipulation portion **112** are at least partially accommodated in a concave portion formed by the bent portion **141**. Due to the above-described shape of the bent portion **141**, the shapes and motions of the manipulation portion **110** and the end tool **120** may be further intuitively matched with each other.

(31) A plane on which the bent portion **141** is formed may be substantially the same plane as a pitch plane, that is, an X-Z plane of FIG. 2. As such, as the bent portion **141** is formed on substantially the same plane as the X-Z plane, interference with the manipulation portion **110** may be reduced. For intuitive motions of the end tool **120** and the manipulation portion **110**, any form other than the X-Z plane may be possible.

(32) The manipulation portion **110** is formed at the one end portion of the connection portion **140** and provided as an interface to be directly controlled by a medical doctor, for example, a tongs shape, a stick shape, a lever shape, or the like. When the medical doctor controls the manipulation portion **110**, the end tool **120** that is connected to the interface and inserted into the body of a patient performs a certain motion, thereby performing surgery. Although FIG. 2 illustrates that the manipulation portion **110** is formed in a handle shape that is rotatable with fingered inserted therein, the concept of the present disclosure is not limited thereto, and various types of manipulation portions that are connected to the end tool **120** to manipulate the end tool **120** may be possible.

(33) The end tool **120** is formed on the other end portion of the connection portion **140**, and performs necessary motions for surgery by being inserted into a surgical site. As an example of the end tool **120**, as illustrated in FIG. 2, a pair of jaws **121** and **122** for performing a grip motion may be used. However, the concept of the present disclosure is not limited thereto, and various devices for surgery may be used as the end tool **120**. For example, a configuration of a cantilever cautery may be used as the end tool **120**. The end tool **120** configured as above is connected to the manipulation portion **110** by the driving force transmission portion **130**, and receives a driving force of the manipulation portion **110** through the driving force transmission portion **130** to perform a motion necessary for surgery, such as gripping, cutting, suturing, or the like.

(34) The end tool **120** of the surgical instrument **100** according to an embodiment of the disclosure is formed to be capable of rotating in at least two directions, for example, the end tool **120** may perform a pitch motion around the Y-axis of FIG. 2 and simultaneously perform a yaw motion and an actuation motion around the Z-axis of FIG. 2.

(35) The pitch, yaw, and actuation motions used in the present disclosure each are defined as follows.

(36) First, the pitch motion means a motion of the end tool **120** rotating in a vertical direction with respect to the extension direction of the connection portion **140** (the X-axis direction of FIG. 2), that is, a rotating motion around the Y-axis of FIG. 2. In other words, the pitch motion means a motion of the end tool **120**, which extends from the connection portion **140** in the extension direction of the connection portion **140** (the X-axis direction of FIG. 2), rotating vertically around the Y-axis with respect to the connection portion **140**. Next, the yaw motion means a motion of the end tool **120** rotating in the left and right directions, that is, the Z-axis of FIG. 2, with respect to the extension direction of the connection portion **140** (the X-axis direction of FIG. 2). In other words, the yaw motion means a motion of the end tool **120**, which extends from the connection portion **140** in the extension direction of the connection portion **140** (the X-axis direction of FIG. 2), rotating horizontally around the Z-axis with respect to the connection portion **140**. In other words, the yaw motion means a motion of the two jaws **121** and **122** formed on the end tool **120** rotating around the Z-axis in the same direction. The actuation motion may mean a motion of the end tool **120** rotating around the same rotation axis as that of the yaw motion, while the two jaws **121** and

122 rotating in the opposite directions so as to be closed or opened. In other words, the actuation motion means a rotating motion of the two jaws **121** and **122** formed on the end tool **120** in the opposite directions around the Z-axis.

(37) The driving force transmission portion **130** may connect the manipulation portion **110** to the end tool **120**, transmit the driving force of the manipulation portion **110** to the end tool **120**, and include a plurality of wires, pulleys, links, sections, gears, or the like. In the surgical instrument **100** according to an embodiment of the disclosure, the driving force transmission portion **130** may include a pitch wire **130P**, a first jaw wire **130J1**, and a second jaw wire **130J2**.

(38) In the following description, the manipulation portion **110**, the end tool **120**, the driving force transmission portion **130**, and the like of the surgical instrument **100** of FIG. 2 are described in detail.

(39) (End Tool)

(40) FIGS. 4 and 5 are perspective views of an end tool of the surgical instrument of FIG. 2, and FIG. 6 illustrates an end tool hub of the surgical instrument of FIG. 4. FIGS. 7 and 8 are plan views of an end tool of a surgical instrument according to the related art, and FIG. 9 is a plan view of the end tool of the surgical instrument of FIG. 2. FIG. 10 illustrates a comparison between the end tool of the surgical instrument of FIG. 8 according to the related art and the end tool of the surgical instrument of FIG. 4 according to an embodiment of the disclosure, and FIG. 11 illustrates a modified example of the end tool of FIG. 4.

(41) First, Referring to FIGS. 4, 5, 6, and 9, the end tool **120** according to an embodiment of the present disclosure may include the jaws **121** and **122** for performing a grip motion, that is, the first jaw **121** and the second jaw **122**. Furthermore, the end tool **120** may include a J11 pulley **123J11**, a J12 pulley **123J12**, a J13 pulley **123J13**, a J14 pulley **123J14**, and a J15 pulley **123J15**, which are related to a rotating motion of the first jaw **121**, and a J21 pulley **123J21**, a J22 pulley **123J22**, a J23 pulley **123J23**, a J24 pulley **123J24**, and a J25 pulley **123J25**, which are related to a rotating motion of the second jaw **122**. The first jaw **121**, the J11 pulley **123J11**, the J12 pulley **123J12**, the J14 pulley **123J14**, the second jaw **122**, the J21 pulley **123J21**, the J22 pulley **123J22**, and the J24 pulley **123J24** all may be formed to rotate together around an end tool pitch rotation shaft **123PA**.

(42) A connection portion hub **142** is formed on the one end portion of the connection portion **140** that is coupled to the end tool **120**. The J12 pulley **123J12**, the J13 pulley **123J13**, the J14 pulley **123J14**, and the J15 pulley **123J15**, and the J22 pulley **123J22**, the J23 pulley **123J23**, the J24 pulley **123J24**, and the J25 pulley **123J25**, are all coupled to the connection portion hub **142**.

(43) Although the pulleys facing each other are illustrated in the drawings formed parallel to each other, the concept of the present disclosure is not limited thereto, each of the pulleys may be variously formed at positions and in sizes suitable for a configuration of the end tool.

(44) The J11 pulley **123J11** and the J21 pulley **123J21** are formed to face each other and independently rotate around a jaw rotation shaft **123JA**. While the first jaw **121** is fixedly coupled to the J11 pulley **123J11** to rotate together with the J11 pulley **123J11**, the second jaw **122** is fixedly coupled to the J21 pulley **123J21** to rotate together with the J21 pulley **123J21**. The yaw motion and the actuation motion of the end tool **120** are performed according to the rotations of the J11 pulley **123J11** and the J21 pulley **123J21**. In other words, when the J11 pulley **123J11** and the J21 pulley **123J21** rotate in the same direction, a yaw motion is performed, and when the J11 pulley **123J11** and the J21 pulley **123J21** rotate in the opposite direction, an actuation motion is performed.

(45) The end tool **120** may further include a pitch pulley **123P** around which the pitch wire **130P** is wound. Furthermore, the end tool **120** may further include an end tool hub **125** that forms a base of the end tool **120** so that the J11 pulley **123J11**, the J21 pulley **123J21**, the pitch pulley **123P**, or the like are coupled thereto.

(46) An embodiment of the present disclosure has a feature that a guide portion **125c** for performing a function as an auxiliary pulley is formed as the end tool hub **125**. In other words, the

guide portion **125c** for guiding paths of the first jaw wire **130J1** and the second jaw wire **130J2** are formed on the end tool hub **125**. The guide portion **125c** may be disposed between the J11 pulley **123J11** and the J12 pulley **123J12**/the J14 pulley **123J14**. Furthermore, the guide portion **125c** may be disposed between the J21 pulley **123J21** and the J22 pulley **123J22**/the J24 pulley **123J24**. The guide portion **125c** of the end tool hub **125** may perform a function of a kind of auxiliary pulley to change a path of a wire. The guide portion **125c** of the end tool hub **125**, which performs a function of an auxiliary pulley, is described below in detail.

(47) In the following description, constituent elements related to the rotation of the J11 pulley **123J11** are described.

(48) The J12 pulley **123J12** and the J14 pulley **123J14** are disposed at one side of the J11 pulley **123J11** to face each other. The J12 pulley **123J12** and the J14 pulley **123J14** are formed to independently rotate around the end tool pitch rotation shaft **123PA**. Furthermore, the J13 pulley **123J13** and the J15 pulley **123J15** are disposed respectively at one side of the J12 pulley **123J12** and the J14 pulley **123J14** (in the X-axis direction) to face each other. The J13 pulley **123J13** and the J15 pulley **123J15** are formed to independently rotate around the Y-axis direction. Although the J12 pulley **123J12**, the J13 pulley **123J13**, the J14 pulley **123J14**, and the J15 pulley **123J15** are all illustrated to be rotatable around the Y-axis direction, the concept of the present disclosure is not limited thereto, and rotation-axes of the respective pulleys may be formed various directions suitable for a configuration thereof.

(49) The J12 pulley **123J12** and the J14 pulley **123J14** are disposed at a first side (the right side of the pitch pulley **123P** in FIG. 9) with respect to a plane perpendicular to the Y-axis and passing through a center-axis (X-axis) of the connection portion **140**. This is because the guide portion **125c** of the end tool hub **125** changes an arrangement path of the first jaw wire **130J1** by performing a function of an auxiliary pulley. Likewise, the J13 pulley **123J13** and the J15 pulley **123J15** are also disposed at the same side (first side) as the J12 pulley **123J12** and the J14 pulley **123J14**.

(50) Likewise, the J22 pulley **123J22** and the J24 pulley **123J24** are disposed at a second side (the left side of the pitch pulley **123P** in FIG. 9) with respect to the plane perpendicular to the Y-axis and passing through the center-axis (X-axis) of the connection portion **140**. This is because the guide portion **125c** of the end tool hub **125** changes an arrangement path of the second jaw wire **130J2** by performing a function of an auxiliary pulley. Likewise, the J23 pulley **123J23** and the J25 pulley **123J25** are also disposed at the same side (second side) as the J22 pulley **123J22** and the J24 pulley **123J24**.

(51) The first jaw wire **130J1** is sequentially wound around the J13 pulley **123J13**, the J12 pulley **123J12**, the J11 pulley **123J11**, the guide portion **125c** of the end tool hub **125**, the J14 pulley **123J14**, and the J15 pulley **123J15** by at least partially contacting the same, and the first jaw wire **130J1** moves along the pulleys while rotating the pulleys.

(52) In detail, the first jaw wire **130J1** extending from the connection portion **140** is first wound around the J13 pulley **123J13** in an arrow A direction of FIG. 5 (counterclockwise when viewed on the X-Z plane), and then wound around the J12 pulley **123J12** in an arrow B direction of FIG. 5 (clockwise when viewed on the X-Z plane). Then, the first jaw wire **130J1** is wound around the J11 pulley **123J11** in an arrow C direction of FIG. 5 (counterclockwise when viewed on the X-Y plane), and then wound around the guide portion **125c** of the end tool hub **125** in an arrow D direction of FIG. 5 (clockwise when viewed on the X-Y plane). Then, the first jaw wire **130J1** is first wound around the J14 pulley **123J14** in a direction opposite to the arrow B direction of FIG. 5 (counterclockwise when viewed on the X-Z plane), and then wound around the J15 pulley **123J15** in a direction opposite to the arrow A direction of FIG. 5 (clockwise when viewed on the X-Z plane) and drawn into the connection portion **140**.

(53) Accordingly, when the first jaw wire **130J1** is pulled in a direction indicated by an arrow J1R of FIG. 9, the first jaw wire **130J1** rotates the J15 pulley **123J15**, the J14 pulley **123J14**, the J11

pulley **123J11**, the J12 pulley **123J12**, and the J13 pulley **123J13**. In this state, the J11 pulley **123J11** is rotated in an arrow R direction of FIG. **9** to rotate the first jaw **121** together.

(54) Reversely, when the first jaw wire **130J1** is pulled in a direction indicated by an arrow **J1L** of FIG. **9**, the first jaw wire **130J1** rotates the J13 pulley **123J13**, the J12 pulley **123J12**, the J11 pulley **123J11**, the J14 pulley **123J14**, and the J15 pulley **123J15**. In this state, the J11 pulley **123J11** is rotated in an arrow L direction of FIG. **9** to rotate the first jaw **121** together.

(55) Next, constituent elements related to the rotation of the J21 pulley **123J21** are described.

(56) The J22 pulley **123J22** and the J24 pulley **123J24** are disposed at one side of the J21 pulley **123J21** to face each other. The J22 pulley **123J22** and the J24 pulley **123J24** are formed to independently rotate around the end tool pitch rotation shaft **123PA**. Furthermore, the J23 pulley **123J23** and the J25 pulley **123J25** are disposed respectively at one side of the J22 pulley **123J22** and the J24 pulley **123J24** (in the X-axis direction) to face each other. The J23 pulley **123J23** and the J25 pulley **123J25** are formed to independently rotate around the Y-axis direction. Although the J22 pulley **123J22**, the J23 pulley **123J23**, the J24 pulley **123J24**, and the J25 pulley **123J25** are all illustrated to be rotatable around the Y-axis direction, the concept of the present disclosure is not limited thereto, and rotation-axes of the respective pulleys may be formed in various directions suitable for a configuration thereof.

(57) A second jaw wire **130J2** is sequentially wound around the J23 pulley **123J23**, the J22 pulley **123J22**, the J21 pulley **123J21**, the guide portion **125c** of the end tool hub **125**, the J24 pulley **123J24**, and the J25 pulley **123J25** by at least partially contacting the same, and the second jaw wire **130J2** moves along the pulleys while rotating the pulleys.

(58) Accordingly, when the second jaw wire **130J2** is pulled in a direction indicated by an arrow **J2R** of FIG. **9**, the second jaw wire **130J2** rotates the J23 pulley **123J23**, the J22 pulley **123J22**, the J21 pulley **123J21**, the J24 pulley **123J24**, and the J25 pulley **123J25**. In this state, the J21 pulley **123J21** is rotated in the arrow R direction of FIG. **9** to rotate the second jaw **122** together.

(59) Reversely, when the second jaw wire **130J2** is pulled in a direction indicated by an arrow **J2L** of FIG. **9**, the second jaw wire **130J2** rotates the J25 pulley **123J25**, the J24 pulley **123J24**, the J21 pulley **123J21**, the J22 pulley **123J22**, and the J23 pulley **123J23**. In this state, the J21 pulley **123J21** is rotated in the arrow L direction of FIG. **9** to rotate the second jaw **122** together.

(60) When the one end portion of the first jaw wire **130J1** is pulled in a direction indicated by the arrow **J1R** of FIG. **9** and simultaneously the other end portion of the first jaw wire **130J1** is pulled in a direction indicated by the arrow **J1L** of FIG. **9** (that is, when both end portions of the first jaw wire **130J1** are pulled), as the first jaw wire **130J1** is wound around lower sides of the J12 pulley **123J12** and the J14 pulley **123J14** to be capable of rotating around the end tool pitch rotation shaft **123PA**, as illustrated in FIG. **5**, the J11 pulley **123J11** to which the first jaw wire **130J1** is fixedly coupled, the first jaw **121**, the jaw rotation shaft **123JA**, the end tool hub **125**, and the second jaw **122** connected thereto are rotated counterclockwise together around the end tool pitch rotation shaft **123PA**. Consequently, the end tool **120** is rotated downward, thereby performing a pitch motion. At this time, as the second jaw **122** and the second jaw wire **130J2** fixedly coupled thereto are wound around upper sides of the J22 pulley **123J22** and the J24 pulley **123J24** to be capable of rotating around the end tool pitch rotation shaft **123PA**, both end portions of the second jaw wire **130J2** are moved in the opposite directions of the arrows **J2L** and **J2R**.

(61) Reversely, when the one end portion of the second jaw wire **130J2** is pulled in a direction toward the arrow **J2R** of FIG. **9** and simultaneously the other end portion of the second jaw wire **130J2** is pulled in a direction toward the arrow **J2L** of FIG. **9**, the second jaw wire **130J2** is wound around the upper sides of the J22 pulley **123J22** and the J24 pulley **123J24** to be capable of rotating around the end tool pitch rotation shaft **123PA**, as illustrated in FIG. **5**, the J21 pulley **123J21** to which the second jaw wire **130J2** is fixedly coupled, the second jaw **122**, the jaw rotation shaft **123JA**, the end tool hub **125**, and the first jaw **121** connected thereto are rotated clockwise together around the end tool pitch rotation shaft **123PA**. Consequently, the end tool **120** is rotated upward,

thereby performing a pitch motion. At this time, as the first jaw wire **130J1** fixedly coupled to the first jaw **121** is wound around the lower sides of the J12 pulley **123J12** and the J14 pulley **123J14** to be capable of rotating around the end tool pitch rotation shaft **123PA**, both end portions of the first jaw wire **130J1** are moved in a direction opposite to the arrows **J1L** and **J1R**.

(62) In a surgical instrument **100** of the present disclosure, the end tool **120** may further include the pitch pulley **123P**, the manipulation portion **110** may further include a pitch wire end pulley **115P**, and the driving force transmission portion **130** may further include the pitch wire **130P**. In detail, the pitch pulley **123P** of the end tool **120** is rotatable around the end tool pitch rotation shaft **123PA** and may be fixedly coupled to the end tool hub **125**. A pitch wire end pulley **115P** of the manipulation portion **110** is rotatable around a pitch rotation shaft (**1111**) and may be fixedly coupled to a pitch manipulation portion (not shown). Furthermore, the pitch wire **130P** may connect the pitch pulley **123P** of the end tool **120** to the pitch wire end pulley **115P** of the manipulation portion **110**.

(63) Accordingly, while a user grips a first handle **114** of the manipulation portion **110** with a hand, when the first handle **114** is rotated around a pitch rotation shaft **1111**, the pitch pulley coupled to the first handle **114** rotates around the pitch rotation shaft **1111**, the rotation of the pitch pulley is transmitted to the pitch pulley **123P** of the end tool **120** via the pitch wire **130P** so that the pitch pulley **123P** is rotated together. Consequently, the end tool **120** is rotated, thereby performing a pitch motion.

(64) In other words, the surgical instrument **100** according to an embodiment of the disclosure, which includes the pitch pulley **123P** of the end tool **120**, the pitch wire end pulley **115P** of the manipulation portion **110**, and the pitch wire **130P** of the driving force transmission portion **130**, may more completely transmit a driving force of the pitch motion of the pitch manipulation portion **111** to the end tool **120**, thereby improving motion reliability.

(65) In the following description, the end tool hub **125** is described in detail, particularly the guide portion **125c** of the end tool hub **125** performing a function of an auxiliary pulley, is mainly described.

(66) The end tool hub **125** may include a pair of jaw pulley coupling portions **125a** and **125b**, the guide portion **125c**, a guide groove **125d**, and a pitch pulley coupling portion **125e**.

(67) In detail, the jaw pulley coupling portions **125a** and **125b** are formed to face each other, and the J11 pulley **123J11** and the J21 pulley **123J21** are accommodated therein. Furthermore, as a through hole is formed in each of the jaw pulley coupling portions **125a** and **125b**, the jaw rotation shaft **123JA** penetrates the jaw pulley coupling portions **125a** and **125b**, the J11 pulley **123J11**, and the J21 pulley **123J21** so as to couple the same.

(68) The jaw pulley coupling portions **125a** and **125b** are connected by the guide portion **125c**. In other words, the jaw pulley coupling portions **125a** and **125b** that are parallel to each other are coupled by the guide portion **125c** that is roughly formed in a perpendicular direction, the jaw pulley coupling portions **125a** and **125b** and the guide portion **125c** forms about a “ π ” shape, and the J11 pulley **123J11** and the J21 pulley **123J21** are accommodated therein.

(69) In other words, it may be seen that the jaw pulley coupling portions **125a** and **125b** extends, in the X-axis direction, from both end portions of the guide portion **125c** that is formed long in Z-axis direction.

(70) The guide portion **125c** may have a cylindrical shape having a roughly semi-circular section. The semi-circular portion may be disposed to protrude toward the J11 pulley **123J11** and the J21 pulley **123J21**. In other words, it may be said that the guide portion **125c** protrudes toward a space formed by the jaw pulley coupling portions **125a** and **125b** and the guide portion **125c**. In other words, in the guide portion **125c**, a region adjacent to the jaw pulley coupling portions **125a** and **125b** has a section that is curved with a certain radius of curvature.

(71) Alternatively, in other words, the guide portion **125c**, which is wound with the first jaw wire **130J1** and the second jaw wire **130J2**, may guide the paths of the first jaw wire **130J1** and the

second jaw wire **130J2**, performing a function as a kind of pulley member. However, the guide portion **125c**, which is not a member rotating around a certain axis like a pulley in a sense, may be fixedly formed as a part of the end tool hub **125**, and may partially similarly perform a function of a pulley around which a wire is wound.

(72) In the drawings, the guide portion **125c** is illustrated to have a cylindrical shape with a section that is roughly semi-circular. In other words, at least a part of the section of the guide portion **125c** on the X-Y plane forms a certain arc shape. However, the concept of the present disclosure is not limited thereto, and the section may have a certain radius of curvature like an oval or a parabola, or a corner of a polygonal column is rounded to a certain degree, so that the section may have various shapes and sizes suitable for guiding the paths of the first jaw wire **130J1** and the second jaw wire **130J2**.

(73) The guide groove **125d** for guiding the paths of the first jaw wire **130J1** and the second jaw wire **130J2** well may be further formed in a portion of the guide portion **125c** contacting the first jaw wire **130J1** and the second jaw wire **130J2**. The guide groove **125d** may have a groove shape recessed to a degree from a protruding surface of the guide portion **125c**.

(74) Although the guide groove **125d** is illustrated in the drawings as being formed in the entire arc surface of the guide portion **125c**, the concept of the present disclosure is not limited thereto, and the guide groove **125d** may be formed only in a part of the arc surface of the guide portion **125c**, as necessary.

(75) As such, by further forming the guide groove **125d** in the guide portion **125c**, unnecessary friction between the first jaw wire **130J1** and the second jaw wire **130J2** is reduced so that durability of the wires may be improved.

(76) The pitch pulley coupling portion **125e** may be further formed on the guide portion **125c** in a direction opposite to the direction in which the jaw pulley coupling portions **125a** and **125b** are formed. The pitch pulley coupling portion **125e** may be formed in a direction parallel to the pitch pulley **123P**, that is, on the X-Z plane. A through hole into which the end tool pitch rotation shaft **123PA** is penetrated and inserted may be formed in the pitch pulley coupling portion **125e**, and the end tool pitch rotation shaft **123PA** penetrates the pitch pulley coupling portion **125e** and the pitch pulley **123P** so that the two members may be coupled to each other. The pitch pulley coupling portion **125e** is formed deviated to a certain degree toward one side than the center thereof, when viewed on the X-Y plane, thereby forming balance overall when the pitch pulley **123P** is coupled thereto.

(77) In the following description, the role and function of the guide portion **125c** are described in detail.

(78) The guide portion **125c** contacts the first jaw wire **130J1** and the second jaw wire **130J2** and changes the arrangement path of the first jaw wire **130J1** and the second jaw wire **130J2** to a certain degree, thereby increasing the rotational radius of each of the first jaw **121** and the second jaw **122**.

(79) In other words, when no auxiliary pulley is disposed as illustrated in FIG. 7, each of a first jaw **121'** and a second jaw **122'** may be rotated to a right angle only. In an embodiment of the disclosure, as the end tool hub **125** is further provided with the guide portion **125c**, an effect of increasing the maximum rotation angle by θ as shown in FIG. 9 may be obtained. This enables a motion of the two jaws of the end tool **120** being opened for an actuation motion while the two jaws are yaw-rotated by 90° in the arrow L direction. This is because the second jaw **122** is rotated by an additional angle θ as illustrated in FIG. 9. Likewise, an actuation motion is possible even when the two jaws are yaw-rotated in the arrow R direction. In other words, a feature of increasing the range of yaw rotation in which an actuation motion is possible may be obtained through the configuration of the guide portion **125c** of the end tool hub **125**. Furthermore, by forming the guide portion **125c** on the end tool hub **125** that already exists, without adding a separate structure such as an auxiliary pulley, a feature of increasing the range of rotation without adding a component and

a manufacturing process may be obtained.

(80) Furthermore, when a separate auxiliary pulley is disposed as illustrated in FIG. 8, a separate structure, that is, a J16 pulley (not shown) and a J26 pulley **123J26**, is additionally disposed to change the arrangement path of the first jaw wire **130J1** and the second jaw wire **130J2**.

Accordingly, the number of components is increased and the manufacturing process becomes complicated, and also the length of an end tool is increased as much as the size of the auxiliary pulley. However, in an embodiment of the disclosure, as the guide portion **125c** is formed in the end tool hub **125**, an effect of increasing the maximum rotation angle of an end tool without a separate additional structure may be obtained. Furthermore, as there is no need to additionally dispose a separate structure, the number of components is decreased and the manufacturing process is simplified, and also the length of an end tool is decreased as much as the size of an auxiliary pulley end tool so that the length of an end tool is decreased during a pitch motion. Accordingly, an effect of facilitating a surgical motion in a narrow space may be obtained.

(81) The above effects are described below in detail.

(82) Referring to FIG. 7, which illustrates a case in which no auxiliary pulley exists, as a first jaw wire **130J1'** is fixedly coupled to a J11 pulley (not shown) and a second jaw wire **130J2'** is fixedly coupled to a J21 pulley **123J21'**, when no auxiliary pulley is disposed, each of the J11 pulley and the J21 pulley **123J21'** may be rotated by a line M of FIG. 7 in the arrow L direction. In other words, the J11 pulley (not shown) and the J21 pulley **123J21'** are rotatable by only about a right angle where a fixing coupling portion **124'** of the second jaw wire **130J2'** and a J21 pulley **123J21'** and the second jaw wire **130J2'** are not separated. In this case, when an actuation motion is performed while the first jaw **121'** and the second jaw **122'** are located on the line M of FIG. 7, the first jaw **121'** may be opened in the R direction, but the second jaw **122'** may not be rotated beyond the line M in the L direction. Accordingly, when the first jaw **121'** and the second jaw **122'** perform a yaw motion over a certain angle, it is a problem that an actuation motion is not smoothly performed.

(83) To address the above problem, in the surgical instrument **200** according to the related art in FIG. 8, a J16 pulley (not shown) and a J26 pulley **123J26''**, which are auxiliary pulleys, are additionally disposed at one side of the J11 pulley and a J21 pulley **123J21''**, respectively. As such, as the arrangement path of a first jaw wire **130J1''** and a second jaw wire **130J2''** is changed to a certain degree by disposing the J16 pulley and the J26 pulley **123J26''**, a tangential direction of the first jaw wire **130J1''** and the second jaw wire **130J2''** is changed. Accordingly, a fixing coupling portion **124''** of the second jaw wire **130J2''** and the J21 pulley **123J21''** may be rotated by a line N of FIG. 8. However, in this case, in order to change the arrangement path of the first jaw wire **130J1''** and the second jaw wire **130J2''**, a separate structure of the J16 pulley and the J26 pulley **123J26''** are additionally disposed, and thus the number of components is increased and the manufacturing process becomes complicated, and also the length of an end tool is increased as much as the size of an auxiliary pulley. Accordingly, it is difficult to perform a motion in a narrow space.

(84) To address the above problems, in the surgical instrument **100** according to an embodiment of the disclosure, as the guide portion **125c** for changing the path of a wire is formed on an inner wall of the end tool hub **125**, a feature of changing the arrangement path of a wire without a separate structure may be obtained. As such, as the arrangement path of the first jaw wire **130J1** and the second jaw wire **130J2** is changed to a certain degree by forming the guide portion **125c** in the end tool hub **125**, the tangential direction of the first jaw wire **130J1** and the second jaw wire **130J2** is changed. Accordingly, a fixing coupling portion **124** of the second jaw wire **130J2** and the J21 pulley **123J21** may be rotated by a line N of FIG. 9. In other words, the fixing coupling portion **124** of the second jaw wire **130J2** and the J21 pulley **123J21** is rotatable until the fixing coupling portion **124** is located on a common inner tangent line of the J21 pulley **123J21** and the J26 pulley **123J26**. Likewise, a coupling portion of the first jaw wire **130J1** and the J11 pulley **123J11** is

rotatable until the coupling portion is located on the common inner tangent line of the J11 pulley **123J11** and the J16 pulley **123J16**, and thus the range of rotation may be increased in the R direction.

(85) In other words, two stands of the first jaw wire **130J1** wound around the J11 pulley **123J11** by the guide portion **125c** are disposed at one side with respect to the plane perpendicular to the Y-axis and passes through the X-axis. Simultaneously, two strands of the second jaw wire **130J2** wound around the J21 pulley **123J21** by the guide portion **125c** are disposed at the other side with respect to the plane perpendicular to the Y-axis and passing through the X-axis

(86) In other words, the J12 pulley **123J12** and the J14 pulley **123J14** are disposed at one side with respect to the plane perpendicular to the Y-axis and passing through the X-axis, and the J22 pulley **123J22** and the J24 pulley **123J24** are disposed at the other side with respect to the plane perpendicular to the Y-axis and passing through the X-axis.

(87) In other words, the first jaw wire **130J1** is located on the inner tangent line of the J11 pulley **123J11** and the guide portion **125c**, and the rotation angle of the J11 pulley **123J11** is increased by the guide portion **125c**. Furthermore, the second jaw wire **130J2** is located on the inner tangent line of the J21 pulley **123J21** and the guide portion **125c**, and the rotation angle of the J21 pulley **123J21** is increased by the guide portion **125c**.

(88) In FIG. **10**, (a) showing the end tool of the surgical instrument of FIG. **8** according to the related art and (b) showing the end tool of the surgical instrument of FIG. **4** according to an embodiment of the disclosure are compared with each other.

(89) In comparison of (a) and (b) of FIG. **10**, compared with the surgical instrument according to the related art of (a) of FIG. **10** where a separate auxiliary pulley **123J26'** is formed, the end tool of the surgical instrument of the present disclosure of (b) of FIG. **10** where the guide portion **125c** for changing the path of a wire is formed on the inner wall of the end tool hub **125**, without forming an auxiliary pulley, has a length that is short by d. As such, as the length of an end tool is decreased, particularly when a pitch motion is performed, the length of an end tool is quite distinguished from the related art. Accordingly, when surgery is performed in a narrow surgery space in the human body, a surgical operator may easily manipulate a surgical instrument and a side effect of surgery may be reduced.

(90) According to the present disclosure as above, as the rotation radii of the first jaw **121** and the second jaw **122** increase, a yaw motion range in which a normal opening/closing actuation motion is performed may be increased.

(91) FIG. **11** illustrates a modified example of the end tool of FIG. **4**.

(92) A surgical instrument according to the present modified example is characteristically different from the above-described surgical instrument according to the embodiment of the present disclosure in that the separate guide groove (see **125d** of FIG. **6**) is not formed in the guide portion **125c** of the end tool hub **125**. As such, as the separate guide groove (see **125d** of FIG. **6**) is not formed, the manufacturing process may be further simplified and manufacturing costs may be reduced.

(93) (Manipulation Portion)

(94) FIG. **12** is a perspective view of the manipulation portion of the surgical instrument of FIG. **2**, and FIG. **13** is a perspective view of FIG. **12** viewed from the rear side.

(95) Referring to FIGS. **2** to **13**, the manipulation portion **110** of the surgical instrument **100** according to an embodiment of the disclosure may include the first handle **114** that a user may grip, the actuation manipulation portion **113** for controlling the actuation motion of the end tool **120**, the yaw manipulation portion **112** for controlling the yaw motion of the end tool **120**, and the pitch manipulation portion **111** for controlling the pitch motion of the end tool **120**.

(96) First, in an example of a use stage of the surgical instrument **100** of FIG. **2**, while a user grips the first handle **114** in the palm, the first handle **114** is rotated around the Y-axis, that is, the pitch rotation shaft **1111**, to perform a pitch motion, and the first handle **114** is rotated around the Z-axis,

that is, a yaw rotation shaft **1121**, to perform a yaw motion. Furthermore, the user may perform an actuation motion by rotating the actuation manipulation portion **113** with a thumb and an index finger inserted into the actuation manipulation portion **113**.

(97) In the surgical instrument **100** according to an embodiment of the disclosure, when the manipulation portion **110** is rotated in one direction with respect to the connection portion **140**, the end tool **120** is characteristically rotated in the intuitively same direction as the manipulating direction of the manipulation portion **110**. In other words, when the first handle **114** of the manipulation portion **110** is rotated in any one direction, the end tool **120** is also rotated in the intuitively same direction as the one direction, thereby performing a pitch motion or a yaw motion. The intuitively same direction may mean that a direction in which the finger of a user gripping the manipulation portion **110** moves and a direction in which an end portion of the end tool **120** moves form substantially the same direction. The same direction may not be a perfectly matching direction in 3 dimension coordinates, and may be understood to be sameness to a degree that, for example, when a user's finger moves to the left, the end portion of the end tool **120** also moves to the left, and when the user's finger moves downwards, the end portion of the end tool **120** also moves downwards.

(98) To this end, in the surgical instrument **100** according to an embodiment of the disclosure, the manipulation portion **110** and the end tool **120** is characteristically formed in the same direction with respect to a plane perpendicular to an extension-axis of the connection portion **140**. In other words, when viewed based on the Y-Z plane of FIG. 2, the manipulation portion **110** extends in a +X-axis direction, and simultaneously the end tool **120** also extends in the +X-axis direction. In other words, a direction in which the end tool **120** is formed in the one end portion of the connection portion **140** and a direction in which the manipulation portion **110** is formed the other end portion of the connection portion **140** may be the same direction with respect to the Y-Z plane. Alternatively, in other words, it may be said that the manipulation portion **110** is formed in a direction away from a body of a user who grips the manipulation portion **110**, that is, toward a direction in which the end tool **120** is formed. In other words, the first handle **114**, actuation rotating portions **1132a** and **1132b**, and the like, which are moved by being gripped by a user for an actuation motion, a yaw motion, and a pitch motion, are formed such that a portion moving for performing each motion is formed to extend in the +X-axis direction than a rotation center of each joint for the motion. Accordingly, as the manipulation portion **110** may be configured in the same manner in which a moving portion of the end tool **120** is formed to extend in the +X-axis direction than the rotation center of each joint for the motion, as described in FIG. 1, the user's manipulating direction and the end tool's motion direction are matched with each other both in view of the rotating direction and in view of the left and right directions. Consequently, the intuitively same manipulation may be possible.

(99) In detail, for the surgical instrument according to the related art, as a direction in which a user manipulates a manipulation portion and the end tool's actual manipulation direction are different from each other and are not intuitively matched with each other, the intuitive operation is not easy in view of a surgical operator, and it takes long to be skilled to move the end tool in a desired direction. In some cases, malfunction may be generated so that a patient is damaged.

(100) To address the above problem, in the surgical instrument **100** according to an embodiment of the disclosure, the manipulating direction of the manipulation portion **110** and the manipulation direction of the end tool **120** are intuitively the same direction. To this end, the manipulation portion **110**, like the end tool **120**, is characteristic in that an actually moving portion for an actuation motion, a yaw motion, and a pitch motion is formed to extend in the +X-axis direction than the rotation center of the joint of each motion, which is described below in detail.

(101) The first handle **114** may be formed to be gripped by a user with a hand, particularly by wrapping the first handle **114** with his/her palm. The actuation manipulation portion **113** and the yaw manipulation portion **112** may be formed on the first handle **114**, and the pitch manipulation

portion **111** may be formed at one side of the yaw manipulation portion **112**. The other end portion of the pitch manipulation portion **111** may be connected to the bent portion **141** of the connection portion **140**.

(102) The actuation manipulation portion **113** may include a first actuation manipulation portion **113a** and a second actuation manipulation portion **113b**. The first actuation manipulation portion **113a** may include a first actuation rotation shaft **1131a**, a first actuation rotating portion **1132a**, a first actuation pulley **113P1**, and a first actuation gear **1134a**. The second actuation manipulation portion **113b** may include a second actuation rotation shaft **1131b**, a second actuation rotating portion **1132b**, a second actuation pulley **113P2**, and a second actuation gear **1134b**. The first actuation rotating portion **1132a** and the second actuation rotating portion **1132b** may be operated by means of a second handle.

(103) The actuation rotation shafts **1131a** and **1131b** may be formed at a certain angle with respect to the X-Y plane where the connection portion **140** is formed. For example, the actuation rotation shafts **1131a** and **1131b** may be formed in a direction parallel to the Z-axis, and in this state, when the pitch manipulation portion **111** or the yaw manipulation portion **112** is rotated, the coordinate system of the actuation manipulation portion **113** may be changed relative thereto. The concept of the present disclosure is not limited thereto, and the actuation rotation shafts **1131a** and **1131b** may be formed in various directions suitable for the structure of a hand of a user gripping the actuation manipulation portion **113** according to an ergonomic design.

(104) The first actuation rotating portion **1132a**, the first actuation pulley **113P1**, and the first actuation gear **1134a** are fixedly coupled to one another to be rotatable together around the first actuation rotation shaft **1131a**. The first actuation pulley **113P1** may be configured to be a single pulley or two pulleys fixedly coupled to each other.

(105) Likewise, the second actuation rotating portion **1132b**, the second actuation pulley **113P2**, and the second actuation gear **1134b** are fixedly coupled to one another to be rotatable together around the second actuation rotation shaft **1131b**. The second actuation pulley **113P2** may be configured to be a single pulley or two pulleys fixedly coupled to each other.

(106) The first actuation gear **1134a** and the second actuation gear **1134b** may be formed to be engaged with each other such that, when any one gear rotates, the other rotates in the opposite direction.

(107) The yaw manipulation portion **112** may include the yaw rotation shaft **1121**, a first jaw yaw pulley **112P1**, a second jaw yaw pulley **112P2**, and a yaw frame **1123**. Furthermore, the yaw manipulation portion **112** may further include a first jaw yaw auxiliary pulley **112S1** formed at one side of the first jaw yaw pulley **112P1**, and a second jaw yaw auxiliary pulley **112S2** formed at one side of the second jaw yaw pulley **112P2**. The first jaw yaw auxiliary pulley **112S1** and the second jaw yaw auxiliary pulley **112S2** may be coupled to a pitch frame **1113** that is described below.

(108) Although the drawings illustrate that the yaw manipulation portion **112** includes the first jaw yaw pulley **112P1** and the second jaw yaw pulley **112P2**, and that the first jaw yaw pulley **112P1** and the second jaw yaw pulley **112P2** each includes two pulleys formed to face each other and capable of independently rotating, the concept of the present disclosure is not limited thereto. In other words, one or more pulleys having the same or different diameters may be provided according to the configuration of the yaw manipulation portion **112**.

(109) In detail, the yaw rotation shaft **1121** is formed at one side of the actuation manipulation portion **113** on the first handle **114**. In this state, the first handle **114** may be formed to be capable of rotating around the yaw rotation shaft **1121**.

(110) The yaw rotation shaft **1121** may be formed at an angle with respect to the X-Y plane where the connection portion **140** is formed. For example, the yaw rotation shaft **1121** may be formed in a direction parallel to the Z-axis, and in this state, when the pitch manipulation portion **111** rotates, the coordinate system of the yaw rotation shaft **1121** may be changed relative thereto as described above. The concept of the present disclosure is not limited thereto, and the yaw rotation shaft **1121**

may be formed in various directions suitable for the structure of a hand of a user gripping the manipulation portion **110** according to an ergonomic design.

(111) The first jaw yaw pulley **112P1** and the second jaw yaw pulley **112P2** are coupled to the yaw rotation shaft **1121** to be capable of rotating around the yaw rotation shaft **1121**. The first jaw wire **130J1** may be wound around the first jaw yaw pulley **112P1**, and the second jaw wire **130J2** may be wound around the second jaw yaw pulley **112P2**. In this state, the first jaw yaw pulley **112P1** and the second jaw yaw pulley **112P2** each may be formed, as two pulleys, to face each other and to be capable of independently rotating. Accordingly, a wire being wound and a wire being released may be wound around separate pulleys so that the wires perform motions without interference with each other.

(112) The yaw frame **1123** may connect the first handle **114**, the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b**, to allow the first handle **114**, the yaw manipulation portion **112**, and the actuation manipulation portion **113** to be integrally rotated around the yaw rotation shaft **1121**.

(113) The pitch manipulation portion **111** may include the pitch rotation shaft **1111**, a first jaw pitch pulley-a **111P1a**, a first jaw pitch pulley-b **111P1b** (not shown), a second jaw pitch pulley-a **111P2a** (not shown), a second jaw pitch pulley-b **111P2b** (not shown), and a pitch frame **1113**. Furthermore, the pitch manipulation portion **111** may further include a first jaw pitch auxiliary pulley-a **111S1a** formed at one side of the first jaw pitch pulley-a **111P1a**, a first jaw pitch auxiliary pulley-b **111S1b** (not shown) formed at one side of the first jaw pitch pulley-b **111P1b**, a second jaw pitch auxiliary pulley-a **111S2a** (not shown) formed at one side of the second jaw pitch pulley-a **111P2a**, and a second jaw pitch auxiliary pulley-b **111S2b** (not shown) formed at one side of the second jaw pitch pulley-b **111P2b**. The pitch manipulation portion **111** is connected to the bent portion **141** of the connection portion **140** via the pitch rotation shaft **1111**.

(114) In detail, the pitch frame **1113** is a base frame of the pitch manipulation portion **111**, and the yaw rotation shaft **1121** is rotatably coupled to one end portion thereof. In other words, the yaw frame **1123** is rotatable around the yaw rotation shaft **1121** with respect to the pitch frame **1113**.

(115) As described above, the yaw frame **1123** connects the first handle **114**, the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b**, and also, as the yaw frame **1123** is connected to the pitch frame **1113**, when the pitch frame **1113** rotates around the pitch rotation shaft **1111**, the yaw frame **1123** connected to the pitch frame **1113**, the first handle **114**, the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b** are rotated together. In other words, when the pitch manipulation portion **111** is rotated around the pitch rotation shaft **1111**, the actuation manipulation portion **113** and the yaw manipulation portion **112** are rotated together with the pitch manipulation portion **111**. In other words, when a user pitch-rotates the first handle **114** around the pitch rotation shaft **1111**, the actuation manipulation portion **113**, the yaw manipulation portion **112**, and the pitch manipulation portion **111** are moved together.

(116) The pitch rotation shaft **1111**, the first jaw pitch pulley-a **111P1a**, the first jaw pitch pulley-b **111P1b**, the second jaw pitch pulley-a **111P2a**, and the second jaw pitch pulley-b **111P2b** are coupled to the pitch frame **1113**. In this state, the first jaw pitch pulley-a **111P1a**, the first jaw pitch pulley-b **111P1b**, the second jaw pitch pulley-a **111P2a**, and the second jaw pitch pulley-b **111P2b** are coupled to the pitch rotation shaft **1111** to be capable of rotating around the pitch rotation shaft **1111**.

(117) The first jaw pitch pulley-a **111P1a** and the first jaw pitch pulley-b **111P1b** may be formed to face each other and to be capable of independently rotating. Accordingly, a wire being wound and a wire being released may be wound around separate pulleys so that the wires perform motions without interference with each other. Likewise, the second jaw pitch pulley-a **111P2a** and the second jaw pitch pulley-b **111P2b** may also be formed to face each other and to be capable of independently rotating. Accordingly, a wire being wound and a wire being released may be wound

around separate pulleys so that the wires perform motions without interference with each other.

(118) Referring to FIG. 13, the pitch wire end pulley **115P** is fixedly coupled to the pitch frame **1113** to be rotatable together. The pitch wire **130P** is fixedly coupled to the pitch frame **1113** via a pitch wire auxiliary pulley **115S** and the pitch wire end pulley **115P**. Consequently, the pitch frame **1113** and the pitch wire end pulley **115P** may be rotated together around the pitch rotation shaft **1111** according to the pitch rotation.

(119) A motion of the pitch wire **130P** is described below.

(120) The pitch pulley **123P** is fixedly coupled to the end tool hub **125** in the end tool **120**, the pitch wire end pulley **115P** is formed in the manipulation portion **110**, and the pitch pulley **123P** and the pitch wire end pulley **115P** are connected to each other by the pitch wire **130P**, so that the pitch motion of the end tool **120** is easily performed according to the pitch manipulation of the manipulation portion **110**. Both end portions of the pitch wire **130P** are fixedly coupled to the pitch frame **1113** respectively via the pitch wire auxiliary pulley **115S** and the pitch wire end pulley **115P**, and the pitch wire end pulley **115P** is fixedly coupled to the pitch frame **1113**. In other words, the pitch frame **1113** and the pitch wire end pulley **115P** are rotated together around the pitch rotation shaft **1111** by the pitch rotation of the manipulation portion **110**. Consequently, both end portions of the pitch wire **130P** are moved in the opposite directions, and thus a driving force of additional pitch rotation separate from the pitch motion of the end tool **120** by the first jaw wire **130J1** and the second jaw wire **130J2** may be transmitted.

(121) A relationship between the first handle **114** and each of the pitch manipulation portion **111**, the yaw manipulation portion **112**, and the actuation manipulation portion **113** is summarized as follows. The actuation rotation shafts **1131a** and **1131b**, the yaw rotation shaft **1121**, and the pitch rotation shaft **1111** may be formed on the first handle **114**. In this state, as the actuation rotation shafts **1131a** and **1131b** are directly formed on the first handle **114**, the first handle **114** and the actuation manipulation portion **113** may be directly connected to each other. As the yaw rotation shaft **1121** is directly formed on the first handle **114**, the first handle **114** and the yaw manipulation portion **112** may be directly connected to each other. In contrast, as the pitch manipulation portion **111** is formed at one side of the yaw manipulation portion **112** to be connected to the yaw manipulation portion **112**, the pitch manipulation portion **111** is not directly connected to the first handle **114**, and the pitch manipulation portion **111** and the first handle **114** may be indirectly connected to each other via the yaw manipulation portion **112**.

(122) Referring back to the drawing, in the surgical instrument **100** according to an embodiment of the disclosure, the pitch manipulation portion **111** and the end tool **120** may be formed on the same or parallel axis (X-axis). In other words, the pitch rotation shaft **1111** of the pitch manipulation portion **111** is formed on one end portion of the bent portion **141** of the connection portion **140**, and the end tool **120** is formed on the other end portion of the connection portion **140**.

(123) One or more intermediate pulleys MP for changing or guiding paths of wires may be disposed at some places along the connection portion **140**, particularly in the bent portion **141**. As the wires are at least partially wound around the intermediate pulleys MP to guide the paths of the wires, the wires may be disposed along a bent shape of the bent portion **141**.

(124) Although the connection portion **140** is illustrated to have the bent portion **141** to be curved with a certain radius of curvature, the concept of the present disclosure is not limited thereto, and the connection portion **140** may be formed linearly or to be bent one or more times, as necessary. Even in this case, it may be said that the pitch manipulation portion **111** and the end tool **120** are formed on substantially the same or parallel axis. Furthermore, although FIG. 3 illustrates that the pitch manipulation portion **111** and the end tool **120** each are formed on an axis parallel to the X-axis, the concept of the present disclosure is not limited thereto, and the pitch manipulation portion **111** and the end tool **120** may be formed on different axes.

(125) The actuation motion, the yaw motion, and the pitch motion according to the present embodiment are described below.

(126) First, the actuation motion is described as follows.

(127) When a user inserts an index finger into the first actuation rotating portion **1132a** and a thumb into the second actuation rotating portion **1132b** and rotates the first and second actuation rotating portions **1132a** and **1132b** by using any one finger or both fingers, the first actuation pulley **113P1** fixedly coupled to the first actuation rotating portion **1132a** and the first actuation gear **1134a** are rotated around the first actuation rotation shaft **1131a**, and the second actuation pulley **113P2** fixedly coupled to the second actuation rotating portion **1132b** and the second actuation gear **1134b** are rotated around the second actuation rotation shaft **1131b**. In this state, the first actuation pulley **113P1** and the second actuation pulley **113P2** are rotated in the opposite directions.

Accordingly, the first jaw wire **130J1** wound around the first actuation pulley **113P1** with one end portion thereof fixedly coupled thereto and the second jaw wire **130J2** wound around the second actuation pulley **113P2** with one end portion thereof fixedly coupled thereto are also moved in the opposite directions. As the above rotation force is transmitted to the end tool **120** via the driving force transmission portion **130**, the two jaws **121** and **122** of the end tool **120** perform an actuation motion. The actuation motion may mean a motion of the two jaws **121** and **122** rotating in the opposite directions being opened or closed, as described above. In other words, when the first and second actuation rotating portions **1132a** and **1132b** of the actuation manipulation portion **113** are rotated in directions close to each other, the first jaw **121** is rotated counterclockwise and the second jaw **122** is rotated clockwise so that the end tool **120** is closed, and when the first and second actuation rotating portions **1132a** and **1132b** of the actuation manipulation portion **113** are rotated in directions away from each other, the first jaw **121** is rotated clockwise and the second jaw **122** is rotated counterclockwise so that the end tool **120** is opened. In the present embodiment, as the first actuation rotating portion **1132a** and the second actuation rotating portion **1132b**, forming the second handle, are provided for the above-described actuation manipulation, the actuation manipulation may be performed by using two fingers. However, the configuration of the actuation manipulation portion **113** for the actuation manipulation of opening or closing the two jaws of the end tool **120** may be sufficiently modified such that, for example, two actuation pulleys (the first actuation pulley **113P1** and the second actuation pulley **113P2**) may be reversely rotated by using one actuation rotation portion, unlike the above description.

(128) Next, the yaw motion is described as follows.

(129) When a user grips the first handle **114** and rotates the first handle **114** around the yaw rotation shaft **1121**, the actuation manipulation portion **113** and the yaw manipulation portion **112** perform a yaw rotation around the yaw rotation shaft **1121**. In other words, when the first actuation pulley **113P1** of the first actuation manipulation portion **113a** to which the first jaw wire **130J1** is fixedly coupled is rotated around the yaw rotation shaft **1121**, the first jaw wire **130J1** wound around the first jaw yaw pulley **112P1** is moved. Likewise, when the second actuation pulley **113P2** of the second actuation manipulation portion **113b** to which the second jaw wire **130J2** is fixedly coupled is rotated around the yaw rotation shaft **1121**, the second jaw wire **130J2** wound around the second jaw yaw pulley **112P2** is moved. In this state, the first jaw wire **130J1** connected to the first jaw **121** and the second jaw wire **130J2** connected to the second jaw **122** are respectively wound around the first jaw yaw pulley **112P1** and the second jaw yaw pulley **112P2** so that, during a yaw rotation, the first jaw **121** and the second jaw **122** are rotated in the same direction. As the rotation force is transmitted to the end tool **120** via the driving force transmission portion **130**, the two jaws **121** and **122** of the end tool **120** perform a yaw motion rotating in the same direction.

(130) In this state, as the yaw frame **1123** connects the first handle **114**, the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b** to one another, the first handle **114**, the yaw manipulation portion **112**, and the actuation manipulation portion **113** are rotated around the yaw rotation shaft **1121** together.

(131) Next, the pitch motion is described as follows.

(132) When a user grips the first handle **114** and rotates the first handle **114** around the pitch

rotation shaft **1111**, the actuation manipulation portion **113**, the yaw manipulation portion **112**, and the pitch manipulation portion **111** perform a pitch rotation around the pitch rotation shaft **1111**. In other words, the first actuation pulley **113P1** of the first actuation manipulation portion **113a** to which the first jaw wire **130J1** is fixedly coupled is rotated around the pitch rotation shaft **1111**, the first jaw wire **130J1** wound around the first jaw pitch pulley-a **111P1a** and the first jaw pitch pulley-b **111P1b** is moved. Likewise, when the second actuation pulley **113P2** of the second actuation manipulation portion **113b** to which the second jaw wire **130J2** is fixedly coupled is rotated around the pitch rotation shaft **1111**, the second jaw wire **130J2** wound around the second jaw pitch pulley-a **111P2a** and the second jaw pitch pulley-b **111P2b** is moved. In this state, as described above in FIG. 9, as both strands of the first jaw wire **130J1** are moved in the same direction and both strands of the second jaw wire **130J2** are moved in the same direction, the first jaw wire **130J1** and the second jaw wire **130J2** are wound around the first jaw pitch pulleys **111P1a** and **111P1b** and the second jaw pitch pulleys **111P2a** and **111P2b** so that the first jaw **121** and the second jaw **122** may perform a pitch rotation. As the rotation force is transmitted to the end tool **120** via the driving force transmission portion **130**, the two jaws **121** and **122** of the end tool **120** perform a pitch motion.

(133) In this state, as the pitch frame **1113** is connected to the yaw frame **1123** and the yaw frame **1123** connects the first handle **114**, the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b** to one another, when the pitch frame **1113** is rotated around the pitch rotation shaft **1111**, the yaw frame **1123** connected to the pitch frame **1113**, the first handle **114**, the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b** are rotated together. In other words, when the pitch manipulation portion **111** is rotated around the pitch rotation shaft **1111**, the actuation manipulation portion **113** and the yaw manipulation portion **112** are rotated together with the pitch manipulation portion **111**.

(134) In summary, it is the characteristics of the surgical instrument **100** according to an embodiment of the disclosure that a pulley is provided at each joint point (actuation joint, yaw joint, or pitch joint), a wire (first jaw wire or second jaw wire) is wound around the pulley, a rotation manipulation (actuation rotation, yaw rotation, or pitch rotation) of a manipulation portion causes a movement of each wire, and thus a desired motion of the end tool **120** is induced. Furthermore, as auxiliary pulleys may be provided at one side of each pulley, the auxiliary pulleys may prevent the wire from being wound around one pulley multiple times.

(135) FIG. 14 schematically illustrates only a configuration of pulleys and wires forming a joint of the surgical instrument **100** of FIG. 12 according to an embodiment of the disclosure. In FIG. 14, the intermediate pulleys for changing the paths of the wires are omitted regardless of the joint motion.

(136) Referring to FIG. 14, the manipulation portion **110** may include the first actuation pulley **113P1**, the first jaw yaw pulley **112P1**, the first jaw yaw auxiliary pulley **112S1**, the first jaw pitch pulley-a **111P1a**, the first jaw pitch pulley-b **111P1b**, the first jaw pitch auxiliary pulley-a **111S1a**, and the first jaw pitch auxiliary pulley-b **111S1b**, which are related to the rotating motion of the first jaw **121**.

(137) Furthermore, the manipulation portion **110** may include the second actuation pulley **113P2**, the second jaw yaw pulley **112P2**, the second jaw yaw auxiliary pulley **112S2**, the second jaw pitch pulley-a **111P2a**, the second jaw pitch pulley-b **111P2b**, the second jaw pitch auxiliary pulley-a **111S2a**, and the second jaw pitch auxiliary pulley-b **111S2b**, which are related to the rotating motion of the second jaw **122**. (As the arrangement and configuration of the respective pulleys in the manipulation portion **110** are the same in principle as those of the respective pulleys in the end tool **120**, detailed indications of reference numerals on the drawing are partially omitted.)

(138) The first jaw yaw pulley **112P1** and the second jaw yaw pulley **112P2** may be formed to be capable of independently rotating around the yaw rotation shaft **1121** that is the same axis. In this

state, the first jaw yaw pulley **112P1** and the second jaw yaw pulley **112P2** may be formed, as two pulleys, to face each other and to be capable of independently rotating.

(139) The first jaw yaw auxiliary pulley **112S1** and the second jaw yaw auxiliary pulley **112S2** may be formed to be capable of independently rotating around the same axis. In this state, the first jaw yaw auxiliary pulley **112S1** may be formed, as two pulleys, to face each other and to be capable of independently rotating, and in this state, the two pulleys may have different diameters. Likewise, the second jaw yaw auxiliary pulley **112S2** may be formed, as two pulleys, to face each other and to be capable of independently rotating, and in this state, the two pulleys may have different diameters.

(140) The first jaw pitch auxiliary pulley-a **111S1a**, the first jaw pitch auxiliary pulley-b **111S1b**, the second jaw pitch auxiliary pulley-a **111S2a**, and the second jaw pitch auxiliary pulley-b **111S2b** may be formed to be capable of independently rotating around the same axis. In this state, the first jaw pitch auxiliary pulley-a **111S1a** and the first jaw pitch auxiliary pulley-b **111S1b** may have different diameters. Furthermore, the second jaw pitch auxiliary pulley-a **111S2a** and the second jaw pitch auxiliary pulley-b **111S2b** may have different diameters.

(141) The first jaw pitch pulley-a **111P1a**, the first jaw pitch pulley-b **111P1b**, the second jaw pitch pulley-a **111P2a**, and the second jaw pitch pulley-b **111P2b** may be formed to be capable of independently rotating around the pitch rotation shaft **1111** that is the same axis.

(142) The first jaw wire **130J1** is formed to sequentially pass the first jaw pitch pulley-a **111P1a**, the first jaw pitch auxiliary pulley-a **111S1a**, the first jaw yaw auxiliary pulley **112S1**, and the first jaw yaw pulley **112P1** of the manipulation portion **110** to be wound around the first actuation pulley **113P1**, and then sequentially pass again the first jaw yaw pulley **112P1**, the first jaw yaw auxiliary pulley **112S1**, the first jaw pitch auxiliary pulley-b **111S1b**, and the first jaw pitch pulley-b **111P1b**, and to move along the pulleys while the first jaw wire **130J1** rotates the pulleys. In this state, the first jaw wire **130J1** may be fixedly coupled to one point of the first actuation pulley **113P1**.

(143) The second jaw wire **130J2** is formed to sequentially pass the second jaw pitch pulley-a **111P2a**, the second jaw pitch auxiliary pulley-a **111S2a**, the second jaw yaw auxiliary pulley **112S2**, and the second jaw yaw pulley **112P2** of the manipulation portion **110** to be wound around the second actuation pulley **113P2**, and then sequentially pass again the second jaw yaw pulley **112P2**, the second jaw yaw auxiliary pulley **112S2**, the second jaw pitch auxiliary pulley-b **111S2b**, and the second jaw pitch pulley-b **111P2b**, and to move along the pulleys while the second jaw wire **130J2** rotates the pulleys. In this state, the second jaw wire **130J2** may be fixedly coupled to one point of the second actuation pulley **113P2**.

(144) FIGS. **15A-15B** schematically illustrate a configuration of pulleys and wires related to an actuation motion and a yaw motion of the surgical instrument **100** of FIG. **12** according to an embodiment of the disclosure, for a first jaw and a second jaw. FIG. **15A** illustrates pulleys and wires only for the second jaw, and FIG. **15B** illustrates pulleys and wires only for the first jaw. FIG. **16** is a perspective view of a yaw motion of the surgical instrument of FIG. **12**.

(145) First, a wire motion of the actuation motion is described below.

(146) Referring to FIG. **15B**, when the first actuation rotating portion **1132a** is rotated around the first actuation rotation shaft **1131a** in an arrow **OPA1** direction, the first actuation pulley **113P1** connected to the first actuation rotating portion **1132a** is rotated, and thus both strands of the first jaw wire **130J1** wound around the first actuation pulley **113P1** are moved in directions **W1a** and **W1b**. Consequently, the first jaw **121** of the manipulation portion **110** is rotated in an arrow **EPA1** direction.

(147) Referring to FIG. **15A**, when the second actuation rotating portion **1132b** is rotated around the second actuation rotation shaft **1131b** in an arrow **OPA2** direction, the second actuation pulley **113P2** connected to the second actuation rotating portion **1132b** is rotated, and thus both strands of the second jaw wire **130J2** wound around the second actuation pulley **113P2** are moved in

directions **W2a** and **W2b**. Consequently, the second jaw **122** of the manipulation portion **110** is rotated in an arrow **EPA2** direction. Accordingly, when a user manipulates the first actuation rotating portion **1132a** and the second actuation rotating portion **1132b** in directions close to each other, a motion of the first jaw **121** and the second jaw **122** of the end tool **120** being close to each other is performed.

(148) Next, a wire motion of the yaw motion is described below.

(149) First, as the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b** are connected to by the yaw frame (see **1123** of FIG. **12**), the yaw rotation shaft **1121**, the first actuation rotation shaft **1131a**, and the second actuation rotation shaft **1131b** are integrally rotated together.

(150) Referring to FIG. **15B**, when the first handle **114** is rotated around the yaw rotation shaft **1121** in an arrow **OPY1** direction, the first actuation pulley **113P1** and the first jaw yaw pulley **112P1**, and the first jaw wire **130J1** wound therearound, are rotated as a whole around the yaw rotation shaft **1121**. Consequently, both strands of the first jaw wire **130J1** wound around the first jaw yaw pulley **112P1** are moved in the directions **W1a** and **W1b**, respectively. As a result, the first jaw **121** of the end tool **120** is rotated in an arrow **EPY1** direction.

(151) Referring to FIG. **15A**, when the first handle **114** is rotated around the yaw rotation shaft **1121** in an arrow **OPY2** direction, the second actuation pulley **113P2** and the second jaw yaw pulley **112P2**, and the second jaw wire **130J2** wound therearound, are rotated as a whole around the yaw rotation shaft **1121**. Consequently, both strands of the second jaw wire **130J2** wound around the second jaw yaw pulley **112P2** are respectively moved in a direction opposite to the direction **W1a** and a direction opposite to the direction **W1b**. As a result, the first jaw **121** of the end tool **120** is rotated in an arrow **EPY2** direction.

(152) FIGS. **17A-17B** schematically illustrate a configuration of pulleys and wires related to a pitch motion of the surgical instrument **100** of FIG. **12** according to an embodiment of the disclosure, for a first jaw and a second jaw. FIG. **17A** illustrates pulleys and wires only for the second jaw, and FIG. **17B** illustrates pulleys and wires only for the first jaw. As illustrated in FIG. **14**, two pulleys for each wire are related to the pitch motion and both strands of each wire are wound in the same path, and thus both strands are expressed by a single line in FIGS. **17A** and **17B**. FIG. **18** is a perspective view of the pitch motion of the surgical instrument of FIG. **12**.

(153) Referring to FIG. **17B**, when the first handle **114** is rotated around the pitch rotation shaft **1111** in an arrow **OPP1** direction, the first actuation pulley **113P1**, the first jaw pitch auxiliary pulleys **111S1a** and **111S1b**, and the first jaw pitch pulleys **111P1a** and **111P1b**, and the first jaw wire **130J1** wound therearound, are rotated as a whole around the pitch rotation shaft **1111**. At this time, as illustrated in FIG. **14**, as both strands of the first jaw wire **130J1** are wound around the upper sides of the first jaw pitch pulleys **111P1a** and **111P1b**, both strands are moved in a direction toward an arrow **W1**. Consequently, as described in FIG. **5**, the first jaw **121** of the end tool **120** is rotated in an arrow **EPP1** direction.

(154) Referring to FIG. **17A**, when the first handle **114** is rotated around the pitch rotation shaft **1111** in an arrow **OPP2** direction, the second actuation pulley **113P2**, the second jaw pitch auxiliary pulleys **111S2a** and **111S2b**, and the second jaw pitch pulleys **111P2a** and **111P2b**, and the second jaw wire **130J2** wound therearound, are rotated as a whole around the pitch rotation shaft **1111**. In this state, as described in FIG. **14**, both strands of the second jaw wire **130J2** are wound around the lower sides of the second jaw pitch pulleys **111P2a** and **111P2b**, both strands are moved in a direction toward an arrow **W2**. Consequently, as described in FIG. **5**, the second jaw **122** of the end tool **120** is rotated in an arrow **EPP2** direction.

(155) Accordingly, FIGS. **12** and **13** illustrating an embodiment may describe the motion principle through FIGS. **14**, **15A-15B**, **16**, **17A-17B**, and **18**, and the actuation motion, the yaw motion, and the pitch motion may be independently manipulated.

(156) As described in FIG. **1**, as the rotation shafts of each of the actuation manipulation portion

113, the yaw manipulation portion **112**, and the pitch manipulation portion **111** are located at the rear of each manipulation portion, the manipulation portion **110** is configured to have the same joint configured of the end tool, so that a user may perform intuitively matching manipulations. (157) In particular, in the surgical instrument **100** according to an embodiment of the disclosure, a pulley is provided at each joint point (actuation joint, yaw joint, or pitch joint), a wire (first jaw wire or second jaw wire) is wound around the pulley, a rotation manipulation (actuation rotation, yaw rotation, or pitch rotation) of a manipulation portion causes a movement of each wire, and thus a desired motion of the end tool **120** is induced. Furthermore, as auxiliary pulleys may be provided at one side of each pulley, the auxiliary pulleys may prevent the wire from being wound around one pulley multiple times. Accordingly, the wires wound around the pulleys do not contact each other, and the paths of the wire being wound around the pulley and the wire being released from the pulley are safely formed so that safety and efficiency in the transmission of a driving force of a wire may be improved.

(158) As described above, the yaw manipulation portion **112** and the actuation manipulation portion **113** are directly formed on the first handle **114**. Accordingly, when the first handle **114** is rotated around the pitch rotation shaft **1111**, the yaw manipulation portion **112** and the actuation manipulation portion **113** are also rotated together with the first handle **114**. Accordingly, the coordinate systems of the yaw manipulation portion **112** and the actuation manipulation portion **113** are not fixed, but are continuously changed relative to the rotation of the first handle **114**. In other words, FIG. 2 illustrates that the yaw manipulation portion **112** and the actuation manipulation portion **113** are parallel to the Z-axis. However, when the first handle **114** is rotated, the yaw manipulation portion **112** and the actuation manipulation portion **113** are not parallel to the Z-axis any longer. In other words, the coordinate systems of the yaw manipulation portion **112** and the actuation manipulation portion **113** are changed according to the rotation of the first handle **114**. However, in the present specification, for convenience of explanation, unless described otherwise, the coordinate systems of the yaw manipulation portion **112** and the actuation manipulation portion **113** are described on the basis of a state in which the first handle **114** is located perpendicularly to the connection portion **140** as illustrated in FIG. 2.

(159) As such, While the disclosure has been particularly shown and described with reference to preferred embodiments using specific terminologies, the embodiments and terminologies should be considered in descriptive sense only and not for purposes of limitation. Therefore, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the following claims.

INDUSTRIAL APPLICABILITY

(160) The present disclosure provides an end tool of a surgical instrument and a surgical instrument having the same. Furthermore, the embodiments of the present disclosure may be applied to manually operated surgical instruments for use in industrially used laparoscopic surgery or various surgical procedures.

Claims

1. An end tool of a surgical instrument, the end tool comprising: a first jaw and a second jaw capable of rotating independently of each other; a J11 pulley coupled to the first jaw and formed to be capable of rotating around a first axis; a J21 pulley coupled to the second jaw and formed to be capable of rotating around an axis that is substantially the same as or parallel to the first axis; an end tool hub comprising a pair of jaw pulley coupling portions formed to face each other and a guide portion connecting the pair of jaw pulley coupling portions, wherein at least parts of the J11 pulley and the J21 pulley are accommodated in a space formed by the pair of jaw pulley coupling portion and the guide portion, and a region adjacent to the J11 pulley and the J21 pulleys in the

guide portion has a section that is curved with a certain radius of curvature, the section being on a plane perpendicular to the first axis; a J12 pulley and a J14 pulley formed at one side of the end tool hub to be capable of rotating around a second axis forming an angle with respect to the first axis; a J22 pulley and a J24 pulley formed at one side of the end tool hub to be capable of rotating around an axis that is substantially the same as or parallel to the second axis; and the guide portion is integrally formed with the pair of jaw pulley coupling portions as one body, wherein a first jaw wire sequentially contacts the J12 pulley, the J11 pulley, the guide portion, and the J14 pulley, and a second jaw wire sequentially contacts the J22 pulley, the J21 pulley, the guide portion, and the J24 pulley, wherein two strands of the first jaw wire wound around the J11 pulley are disposed by the guide portion at one side with respect to a plane perpendicular to the second axis and passing through the first axis, and wherein two strands of the second jaw wire wound around the J21 pulley are disposed by the guide portion at another side with respect to the plane perpendicular to the second axis and passing through the first axis.

2. The end tool of claim 1, wherein the first jaw wire is wound around the J11 pulley in a first direction and then wound around the guide portion in a second direction that is opposite to the first direction, and the second jaw wire is wound around the J21 pulley in the second direction and then wound around the guide portion in the first direction.

3. The end tool of claim 2, wherein a connection portion hub capable of rotating around the second axis with respect to the end tool hub is formed at one side of the end tool hub, and in the connection portion hub, a J13 pulley and a J15 pulley are formed to be capable of rotating around an axis that is substantially parallel to the second axis, and a J23 pulley and a J25 pulley are formed to be capable of rotating around the axis that is substantially parallel to the second axis.

4. The end tool of claim 3, wherein the first jaw wire is wound around the J13 pulley in a third direction and then wound around the J12 pulley in a fourth direction that is opposite to the third direction, and the second jaw wire is wound around the J23 pulley in the fourth direction and then wound around the J22 pulley in the third direction.

5. The end tool of claim 4, wherein the first direction and the third direction are substantially perpendicular to each other.

6. The end tool of claim 1, wherein the first jaw wire is located on an inner tangent line of the J11 pulley and the guide portion, and a rotation angle of the J11 pulley is increased by the guide portion, and the second jaw wire is located on an inner tangent line of the J21 pulley and the guide portion, and a rotation angle of the J21 pulley is increased by the guide portion.

7. The end tool of claim 1, wherein the first jaw wire is fixedly coupled to the J11 pulley by a fixing coupling portion, and the second jaw wire is fixedly coupled to the J21 pulley by another fixing coupling portion.

8. The end tool of claim 1, wherein the first jaw wire passes inwardly through the J11 pulley and the guide portion, and the second jaw wire passes inwardly through the J21 pulley and the guide portion.

9. The end tool of claim 1, wherein one or more guide grooves are further formed in the guide portion as a surface of the guide portion is recessed to accommodate at least a part of each of the first jaw wire or the second jaw wire.

10. The end tool of claim 9, wherein the guide groove is formed only in a part of the guide portion.

11. The end tool of claim 1, wherein the guide portion is disposed at a side opposite to the first jaw and second jaw with respect to the J11 pulley and the J21 pulley.

12. The end tool of claim 1, wherein the pair of jaw pulley coupling portions and the guide portion connecting the pair of jaw pulley coupling portions have a "Π" shape.

13. The end tool of claim 1, wherein the guide portion is formed in a direction of the first axis, and wherein the pair of jaw pulley coupling portions extend from both end portions of the guide portion in a third axis direction that is different from each of the first axis and the second axis.

14. The end tool of claim 13, wherein at least a part of a section of the guide portion has an arc

shape in a direction perpendicular to the first axis.

15. The end tool of claim 1, wherein in the guide portion, surfaces facing the J11 pulley and the J21 pulley protrude toward the J11 pulley and the J21 pulley to a predetermined degree.

16. The end tool of claim 1, wherein the J12 pulley and J14 pulley are disposed at one side with respect to a plane perpendicular to the second axis and passing through the first axis, and the J22 pulley and J24 pulley are disposed at another side with respect to the plane perpendicular to the second axis and passing through the first axis.

17. The end tool of claim 1, wherein a first jaw wire and a second jaw wire contact at least a part of the guide portion.
