

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12416387
B1
September 16, 2025
Howard; Kenneth A. et al.

Flexible neon LED nightlight

Abstract

A nightlight including a base and an electrical prong secured to the base and adapted to be inserted into an electrical outlet is disclosed. A main circuit is coupled to the electrical prong and contained within the base. A flexible neon LED strip is coupled to the main circuit for receiving an electrical current. A support frame is configured in the shape of an image wherein the support frame has an arcuate shaped cross-section or a C-shaped cross-section sized to receive the flexible neon LED strip. The flexible neon LED strip is positioned along the support frame whereby the flexible neon LED strip when energized emits light corresponding to the image and illuminates an area adjacent the night light. A sound transducer may produce an electrical signal as a function of an ambient sound. The flexible neon LED strip may comprise an RGB LED, an RGB IC, or a solid color LED to produce different colors of light. The main circuit may vary the color of the emitted light that is produced by the flexible neon LED strip as a function of a switch, a remote control, or the ambient sound. The support frame may comprise a back wall and a plurality of side walls where the back wall is translucent or transparent and where the flexible neon LED strip may emit light out of a front surface and a back surface of the flexible neon LED strip. Alternatively, the support frame may comprise an arcuate cross-section where the back wall is translucent or transparent and where the flexible neon LED strip is cylindrical and may emit light out of a front surface and a back surface or all surfaces of the flexible neon LED strip.

Inventors: Howard; Kenneth A. (Creve Coeur, MO), Smith; Matthew S. (St. Charles, MO)

Applicant: Mary Elle Fashions, Inc. (St. Louis, MO)

Family ID: 1000008821103

Assignee: Mary Elle Fashions, Inc. (St. Louis, MO)

Appl. No.: 18/779267

Filed: July 22, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: F21S4/26 (20160101); F21V23/04 (20060101); F21Y103/10 (20160101); F21Y113/00 (20160101); F21Y115/10 (20160101)

U.S. Cl.:

CPC F21S4/26 (20160101); F21V23/0435 (20130101); F21Y2103/10 (20160801); F21Y2113/00 (20130101); F21Y2115/10 (20160801)

Field of Classification Search

CPC: F21S (4/26); F21S (4/22); F21V (23/0435); F21Y (2103/10); F21Y (2115/10); F21Y (2113/00); F21Y (2103/37)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10655804	12/2019	Yuan	N/A	F21S 4/22
2007/0109782	12/2006	Wolf	362/253	A61L 9/037
2011/0163683	12/2010	Steele	315/192	F21V 23/06
2014/0028210	12/2013	Maxik	362/640	F21S 9/024
2015/0159843	12/2014	Chien	362/190	F21V 17/02

Primary Examiner: Truong; Bao Q
Attorney, Agent or Firm: Lewis Rice LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims the benefit of U.S. Provisional Application Nos. 63/661,301, filed Jun. 18, 2024, and 63/562,877, filed Mar. 8, 2024. The entire disclosure of all of the above documents is herein incorporated by reference.

FIELD OF THE INVENTION

(1) The present disclosure relates to a nightlight for illuminating an area adjacent thereto using an illuminated image formed from a flexible neon LED positioned in a C-channel and configured in the shape of the image.

BACKGROUND OF THE INVENTION

(2) Traditional nightlights have used low power incandescent bulbs or LEDs to provide a low level of typically yellow or white light adjacent thereto. Some nightlights have incorporated images or cut-outs to display a pattern on an adjacent wall. Other nightlights have incorporated colored lights to display or illuminate with various selected colors. Nightlights may be activated with a manual switch or a light sensitive switch that is activated when the ambient light level falls below a preset

level.

SUMMARY

(3) As described more fully below, embodiments may include a nightlight with a base and an electrical prong secured to the base and adapted to be inserted into an electrical outlet. A main circuit may be coupled to the electrical prong and contained within the base. A flexible neon LED strip may be coupled to the main circuit for receiving an electrical current. A support frame may be configured in the shape of an image wherein the support frame has a C-shaped cross-section or an arcuate cross-section sized to receive the flexible neon LED strip. The flexible neon LED strip may be positioned along the support frame whereby the flexible neon LED strip when energized emits light corresponding to the image and illuminates an area adjacent the night light. A sound transducer may produce an electrical signal as a function of an ambient sound. The flexible neon LED strip may comprise an RGB LED, an RGB integrated circuit ("IC"), or a solid color LED to produce different colors of light. The main circuit may vary the color of the emitted light that is produced by the flexible neon LED strip as a function of a switch, a remote control, or the ambient sound. The support frame may comprise a back wall and a plurality of side walls where the back wall is translucent or transparent and where the flexible neon LED strip may emit light out of a front surface and a back surface or all surfaces of the flexible neon LED strip. The support frame may comprise an arcuate cross-section where the back wall is translucent or transparent and where the flexible neon LED strip is cylindrical and may emit light out of a front surface and a back surface or all surfaces of the flexible neon LED strip.

(4) In one embodiment, a nightlight includes a base and an electrical prong adapted to be inserted into an electrical outlet, wherein the electrical prong is secured to and projects from the base. A main circuit is coupled to the electrical prong and contained within the base. A flexible neon LED strip is coupled to the main circuit for receiving an electrical current from the main circuit. A support frame is configured in the shape of an image and the support frame has a C-shaped cross-section or an arcuate cross-section sized to receive the flexible neon LED strip. The flexible neon LED strip is positioned along the support frame and, when energized by the main circuit, the flexible neon LED strip emits light corresponding to the image and illuminates an area adjacent the night light. Alternatively, the support frame may comprise an arcuate cross-section where the back wall is translucent or transparent and where the flexible neon LED strip is cylindrical and may emit light out of a front surface and a back surface or all surfaces of the flexible neon LED strip.

(5) The night light may comprise a sound transducer to produce an electrical signal as a function of an ambient sound. The flexible neon LED strip may comprise an RGB LED, an RGB IC, or a solid color LED to produce different colors of light. The main circuit may be coupled to the sound transducer and the flexible neon LED strip for varying the color of the emitted light that is produced by the flexible neon LED strip as a function of a switch, a remote control, or the ambient sound. The support frame may comprise a back wall and a plurality of side walls, where the back wall is translucent and the flexible neon LED strip emits light out of a front surface and a back surface of the flexible neon LED strip. Alternatively, the back wall of the support frame may be transparent. The main circuit may be adapted to vary the color of the emitted light and the intensity of the emitted light that is produced by the flexible neon LED strip as a function of the switch, the remote control, or the ambient sound.

(6) The night light may comprise a plurality of flexible neon LED strips that are electrically coupled to each other and where the plurality of flexible neon LED strips emit light at the same time. The night light may comprise a plurality of flexible neon LED strips that are electrically coupled to the main circuit and where the plurality of flexible neon LED strips are controlled by the main circuit to emit light independently of each other. The night light may comprise a plurality of flexible neon LED strips that are electrically coupled to the main circuit and where the plurality of flexible neon LED strips are controlled by the main circuit to emit light independently of each other

as a function of a switch, a remote control, or an ambient sound.
(7) Other features will be in part apparent and in part pointed out hereinafter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows a nightlight comprising a flexible neon LED.
- (2) FIG. 2 shows a schematic diagram of circuitry to control a light source.
- (3) FIG. 3 shows a cross-section through a channel shaped support for securing a flexible neon LED.
- (4) FIG. 4 shows a cross-section through an arcuate support for securing a flexible neon LED.
- (5) Corresponding reference characters indicate corresponding parts throughout the drawings.

DETAILED DESCRIPTION

(6) FIG. 1 shows a nightlight **100** that includes a plurality of colorful light sources, such as Flexible neon LEDs A and B, formed into a preferred image such as the star shown there. LEDs A and B may be any color of LED or a preferred mix of red, green and blue LEDs. LEDs A and B may be sized and structured to provide any preferred color and intensity of light. For example, as is known in the art, multiple LEDs may be located adjacent each other to provide light mixing to thereby provide many of the colors in the visible spectrum. The LEDs may comprise an RGB LED, an RGB IC, or a solid color LED. More than two LEDs for each formed image in FIG. 1 may be used within the scope of the invention depending on the preferences of the designer and the size of the desired image. For example, nightlight **100** may include at least 5 LEDs, at least 10 LEDs, or at least 50 LEDs but likely not more than 1,000 LEDs or not more than 500 LEDs or not more than 100 LEDs.

(7) Nightlight **100** includes a base **102** that supports conventional electrical prongs **104** sized for insertion into a standard electrical outlet that provides nominal 120 volt AC electricity. A conductor **105** provides the electrical power to a main circuit **106**. The main circuit **106** includes conductors **108** and **110** for selectively energizing LEDs A and B. Nightlight **100** also includes a sound transducer or microphone **114** that creates an electrical signal in response to ambient sound. This electrical signal is provided to main circuit **106** via conductor **116**.

(8) In use, the main circuit **106** may receive a signal from sound transducer **114** and, in response thereto, vary the electricity provided to LEDs A and B to vary the color of the light output by the nightlight **100** as a function of a switch, a remote control, or the ambient sound. In use, the main circuit **106** may receive a signal from sound transducer **114** and, in response thereto, vary the electricity provided to LEDs A and B to vary the intensity of the light or the intensity of the color of the light output by the nightlight **100** as a function of a switch, a remote control, or the ambient sound. In use, the main circuit **106** may receive a signal from sound transducer **114** and, in response thereto, vary the electricity provided to LEDs A and B to vary the color and intensity of the light output by the nightlight **100** as a function of a switch, a remote control, or the ambient sound.

(9) FIG. 2 is a schematic diagram for the main circuit **106**. As seen, main circuit **106** is connected to conventional electrical prongs **104** sized for insertion into a standard electrical outlet that provides nominal 120 volt AC electricity. A rectifier bridge **150** provides a DC voltage. The rectifier bridge **150** may be a full bridge or a partial bridge, as known to those skilled in the art. The DC voltage is carried by a conductor **152** to a DC power supply **154** that supplies a light control circuit **158** with an appropriate level of DC voltage. DC power supply may preferably include a capacitor (not shown) to smooth out the DC wave form. The light control circuit **158** is connected to the sound transducer or microphone **114** via conductor **116**. The light control circuit **158** controls LEDs A and B, respectively, via conductors **108** and **110**.

(10) In use, the light control circuit **158** may receive a signal from sound transducer **114** and, in response thereto, vary the electricity provided to LEDs A and B to vary the color of the light output by the nightlight **100** as a function of a switch, a remote control, or the ambient sound. In use, the light control circuit **158** may receive a signal from sound transducer **114** and, in response thereto, vary the electricity provided to LEDs A and B to vary the intensity of the light or the intensity of the color of the light output by the nightlight **100** as a function of the switch, the remote control, or the ambient sound. In use, the light control circuit **158** may receive a signal from sound transducer **114** and, in response thereto, vary the electricity provided to LEDs A and B to vary the color and intensity of the light output by the nightlight **100** as a function of the switch, the remote control, or the ambient sound.

(11) LEDs A and B in FIG. 2 may be red, green and blue LEDs, respectively, or may be sized and structured to provide any preferred color and intensity of light. For example, as is known in the art, multiple LEDs may be located adjacent each other to provide light mixing to thereby provide many of the colors in the visible spectrum. The LEDs may comprise an RGB LED, an RGB IC, or a solid color LED. Many more than two LEDs may be used within the scope of the invention depending on the preferences of the designer. For example, each of the images formed from the flexible neon LED nightlight **100** may contain at least 5 LEDs, at least 10 LEDs, or at least 50 LEDs but likely not more than 1,000 LEDs or not more than 500 LEDs or not more than 100 LEDs.

(12) FIG. 3 shows a cross-section through a support frame **300** configured in the shape of an image, such as the star-shaped image shown in FIG. 1. The support frame **300** preferably has a C-shaped cross-section sized to receive a flexible neon LED strip **302**. The flexible neon LED strip **302** is positioned along the support frame **300** to illuminate the shape of the image such as the star-shaped image in FIG. 1 and to illuminate an area adjacent to the night light **100**. When it is necessary to bend the flexible neon LED strip **302** through sharper angles such as the point on the star image shown in FIG. 1, then the diameter of the flexible neon LED strip **302** preferably has a smaller diameter or thickness such as 8 mm, 7 mm, 6 mm, 5 mm or even 4 mm. It may also be preferable to form the flexible neon LED strip **302** with flat side walls and round ends so that the flexible neon LED strip **302** may be bent through its flat sides when forming an image. As seen, the support frame has a back wall **306** and a plurality of sidewalls **308**. The back wall **306** may be translucent and the flexible neon LED strip **302** may emit light out of a front surface **310** and a back surface **312** of the flexible neon LED strip **302**. The back wall **306** may be transparent and the flexible neon LED strip **302** may emit light out of a front surface **310** and a back surface **312** of the flexible neon LED strip **302**. Alternatively, the entire support frame **300** may be transparent and the flexible neon LED strip **302** may emit light out through the entirety of its external surface including the surface attached to support frame **300**. In this way, light emanating from the flexible neon LED strip **302** may be emitted through the support frame **300** to provide overall greater illumination and to provide an additional aspect in the design of the image, such as the star in FIG. 1.

(13) Nightlight **100** can be made using multiple flexible neon LED strips **302** that are electrically coupled to each other for emitting light at the same time, at different times or at independent times. Nightlight **100** can be made using multiple flexible neon LED strips **302** that are electrically coupled to each other for emitting light at the same time, at different times or at independent times all as a function of a switch, a remote control, or the ambient sound and the signal from sound transducer **114**.

(14) FIG. 4 shows a cross-section through a support frame **400** configured in the shape of an image, such as the star-shaped image shown in FIG. 1. The support frame **400** preferably has an arcuate cross-section sized to receive a flexible neon LED strip **402**. In this embodiment, the flexible neon LED strip **402** preferably has a round cross-section and an overall shape that is substantially cylindrical. The flexible neon LED strip **402** is positioned along the support frame **400** to illuminate the shape of the image such as the star-shaped image in FIG. 1 and to illuminate an area adjacent to the night light **100**. When it is necessary to bend the flexible neon LED strip **402**

through sharper angles such as the point on the star image shown in FIG. 1, then the diameter of the flexible neon LED strip **402** preferably has a smaller diameter or thickness such as 8 mm, 7 mm, 6 mm, 5 mm or even 4 mm. For images that do not require such sharp angles, the flexible neon LED strip **402** may have a larger diameter or thickness such as 9 mm, 10 mm, 11 mm, 12 mm, 13 mm, 14 mm, or even 15 mm. The diameter of the flexible neon LED strip **402** preferably falls within the range from 4 mm to 15 mm, from 6 mm to 13 mm, or from 8 mm to 13 mm. It may also be preferable to form the flexible neon LED strip **402** with a flat side wall for attachment to a support frame such as support frame **300** or **400**. The support frame **400** may be translucent and the flexible neon LED strip **402** may have a relatively opaque region for attachment to the support frame. Alternatively, the support frame **400** may be transparent and the flexible neon LED strip **402** may emit light out through the entirety of its external surface including the surface attached to support frame **400**. In this way, light emanating from the flexible neon LED strip **402** may be emitted through the support frame **400** to provide overall greater illumination and to provide an additional aspect in the design of the image, such as the star in FIG. 1.

(15) Nightlight **100** can be made using multiple flexible neon LED strips **402** that are electrically coupled to each other for emitting light at the same time, at different times or at independent times. Nightlight **100** can be made using multiple flexible neon LED strips **402** that are electrically coupled to each other for emitting light at the same time, at different times or at independent times all as a function of a switch, a remote control, or the ambient sound and the signal from sound transducer **114**.

(16) Having described the invention in detail, it will be apparent that modifications and variations are possible without departing from the scope of the invention defined in the appended claims.

(17) When introducing elements of the present invention or the preferred embodiments thereof, the articles “a”, “an”, “the” and “said” are intended to mean that there are one or more of the elements. The terms “comprising”, “including” and “having” are intended to be inclusive and mean that there may be additional elements other than the listed elements.

(18) As various changes could be made in the above constructions, products, and methods without departing from the scope of the invention, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

Claims

1. A nightlight comprising: a base; an electrical prong adapted to be inserted into an electrical outlet, wherein the electrical prong is secured to and projects from the base; a main circuit coupled to the electrical prong and contained within the base; a flexible neon LED strip coupled to the main circuit for receiving an electrical current from the main circuit; a support frame configured in the shape of an outline of an image; wherein the support frame has a C-shaped cross-section or an arcuate cross-section sized to receive the flexible neon LED strip; wherein the flexible neon LED strip is positioned along the support frame in the shape of the outline of the image; whereby the flexible neon LED strip when energized by the main circuit emits light to illuminate the shape of the outline of the image and illuminates an area adjacent the night light.

2. The nightlight of claim 1 further comprising: a sound transducer for producing an electrical signal as a function of an ambient sound; and wherein the flexible neon LED strip includes an RGB LED, an RGB IC, or a solid color LED to produce different colors of light; and wherein the main circuit is coupled to the sound transducer and the flexible neon LED strip for varying the color of the emitted light that is produced by the flexible neon LED strip as a function of a switch, a remote control, or the ambient sound.

3. The nightlight of claim 1 wherein the support frame further comprises a back wall and a plurality of side walls; wherein the back wall is translucent; and wherein the flexible neon LED strip emits

light out of a front surface and a back surface of the flexible neon LED strip.

4. The nightlight of claim 1 wherein the support frame further comprises a back wall and a plurality of side walls; wherein the back wall is transparent; and wherein the flexible neon LED strip emits light out of a front surface and a back surface of the flexible neon LED strip.

5. The nightlight of claim 1 wherein the support frame further comprises a back wall and a plurality of side walls; wherein the support frame is transparent; and wherein the flexible neon LED strip emits light out of the entirety of an external surface of the flexible neon LED strip.

6. The nightlight of claim 1 wherein the main circuit is adapted to vary the color of the emitted light and an intensity of the emitted light that is produced by the flexible neon LED strip as a function of a switch, a remote control, or the ambient sound.

7. The nightlight of claim 1 wherein the flexible neon LED strip comprises a plurality of flexible neon LED strips that are electrically coupled to each other; and wherein the plurality of flexible neon LED strips emit light at the same time.

8. The nightlight of claim 1 wherein the flexible neon LED strip comprises a plurality of flexible neon LED strips that are electrically coupled to the main circuit; and wherein the plurality of flexible neon LED strips are controlled by the main circuit to emit light independently of each other.

9. The nightlight of claim 1 wherein the flexible neon LED strip comprises a plurality of flexible neon LED strips that are electrically coupled to the main circuit; and wherein the plurality of flexible neon LED strips are controlled by the main circuit to emit light independently of each other as a function of a switch, a remote control, or the ambient sound.

10. The nightlight of claim 1 wherein the support frame further comprises an arcuate shape; wherein the support frame is translucent; and wherein the flexible neon LED strip emits light out of a front surface of the flexible neon LED strip and does not emit light out of a surface that is attached to the support frame.

11. The nightlight of claim 1 wherein the support frame further comprises an arcuate shape; wherein the flexible neon LED strip comprises a cylindrical shape; wherein the support frame is transparent; and wherein the flexible neon LED strip may emit light out through the entirety of an external surface including the surface attached to the support frame.

12. The nightlight of claim 1 wherein the support frame further comprises an arcuate shape; wherein the flexible neon LED strip comprises a cylindrical shape; wherein the support frame is translucent; and wherein the flexible neon LED strip may emit light out through the entirety of an external surface including the surface attached to the support frame.

13. The nightlight of claim 2 wherein the support frame further comprises a back wall and a plurality of side walls; wherein the back wall is translucent; and wherein the flexible neon LED strip emits light out of a front surface and a back surface of the flexible neon LED strip.

14. The nightlight of claim 2 wherein the support frame further comprises a back wall and a plurality of side walls; wherein the back wall is transparent; and wherein the flexible neon LED strip emits light out of a front surface and a back surface of the flexible neon LED strip.

15. The nightlight of claim 2 wherein the support frame further comprises a back wall and a plurality of side walls; wherein the support frame is transparent; and wherein the flexible neon LED strip emits light out of the entirety of an external surface of the flexible neon LED strip.

16. The nightlight of claim 2 wherein the main circuit is adapted to vary the color of the emitted light and an intensity of the emitted light that is produced by the flexible neon LED strip as a function of a switch, a remote control, or the ambient sound.

17. The nightlight of claim 2 wherein the flexible neon LED strip comprises a plurality of flexible neon LED strips that are electrically coupled to each other; and wherein the plurality of flexible neon LED strips emit light at the same time.

18. The nightlight of claim 2 wherein the flexible neon LED strip comprises a plurality of flexible neon LED strips that are electrically coupled to the main circuit; and wherein the plurality of

flexible neon LED strips are controlled by the main circuit to emit light independently of each other.

19. The nightlight of claim 2 wherein the flexible neon LED strip comprises a plurality of flexible neon LED strips that are electrically coupled to the main circuit; and wherein the plurality of flexible neon LED strips are controlled by the main circuit to emit light independently of each other as a function of a switch, a remote control, or the ambient sound.

20. The nightlight of claim 2 wherein the support frame further comprises an arcuate shape; wherein the support frame is translucent; and wherein the flexible neon LED strip emits light out of a front surface of the flexible neon LED strip and does not emit light out of a surface that is attached to the support frame.

21. The nightlight of claim 2 wherein the support frame further comprises an arcuate shape; wherein the flexible neon LED strip comprises a cylindrical shape; wherein the support frame is transparent; and wherein the flexible neon LED strip may emit light out through the entirety of an external surface including the surface attached to the support frame.

22. The nightlight of claim 2 wherein the support frame further comprises an arcuate shape; wherein the flexible neon LED strip comprises a cylindrical shape; wherein the support frame is translucent; and wherein the flexible neon LED strip may emit light out through the entirety of an external surface including the surface attached to the support frame.
