

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12417997
B2
September 16, 2025
Yoshino; Hiroaki et al.

Wire bonding apparatus, method for manufacture of semiconductor device, and semiconductor device

Abstract

This wire bonding apparatus has a capillary, a movement mechanism moving the capillary, and a control unit controlling driving of the movement mechanism. The control unit at least causes execution of: a first process (trajectory a) of lowering the capillary, after a FAB is formed, to pressure bonding height at a first bonding point to form a pressure bonded ball and a column part at the first bonding point; a second process (trajectory b) of moving the capillary horizontally at the pressure bonding height after execution of the first process to scarp off the column part by the capillary; and a third process (trajectory c-k) of repeating a pressing operation at least once after execution of the second process, the pressing operation involving moving the capillary forward and lowering the capillary temporarily during movement so that the capillary presses down on a wire portion positioned over the pressure bonded ball.

Inventors:	Yoshino; Hiroaki (Tokyo, JP), Tei; Shinsuke (Tokyo, JP)
Applicant:	SHINKAWA LTD. (Tokyo, JP)
Family ID:	1000008821114
Assignee:	SHINKAWA LTD. (Tokyo, JP)
Appl. No.:	17/610445
Filed (or PCT Filed):	May 27, 2019
PCT No.:	PCT/JP2019/020960
PCT Pub. No.:	WO2020/240674
PCT Pub. Date:	December 03, 2020

Prior Publication Data

Document Identifier

US 20220208721 A1

Publication Date

Jun. 30, 2022

Publication Classification

Int. Cl.: H01L23/00 (20060101)

U.S. Cl.:

CPC H01L24/78 (20130101); H01L24/48 (20130101); H01L24/85 (20130101); H01L2224/4807 (20130101); H01L2224/48096 (20130101); H01L2224/48245 (20130101); H01L2224/48453 (20130101); H01L2224/48465 (20130101); H01L2224/78303 (20130101); H01L2224/78353 (20130101); H01L2224/786 (20130101); H01L2224/78824 (20130101); H01L2224/85091 (20130101); H01L2224/85986 (20130101)

Field of Classification Search

CPC: H01L (2224/4807); H01L (2224/48096); H01L (2224/48245); H01L (2224/48453); H01L (2224/48465); H01L (2224/78303); H01L (2224/78353); H01L (2224/786); H01L (2224/78824); H01L (2224/85091); H01L (2224/85986); H01L (2224/45015); H01L (2224/45144); H01L (2224/4809); H01L (2224/48451); H01L (2224/78301); H01L (2224/85045); H01L (2224/85181); H01L (2224/85205); H01L (24/45); H01L (24/78); H01L (24/48); H01L (24/85); H01L (2924/00014); H01L (2924/20751); H01L (2924/20752); H01L (2224/05599)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6001724	12/1998	Stansbury	257/784	H01L 24/11
6180891	12/2000	Murdeswar	361/776	H01L 24/85
6207549	12/2000	Higashi	438/615	H01L 24/11
6260753	12/2000	Renard	228/180.5	H01L 24/13
7748599	12/2009	Arahata et al.	N/A	N/A
8042725	12/2010	Arahata et al.	N/A	N/A
2006/0054662	12/2005	Nishimaki	228/103	H01L 24/78
2006/0175383	12/2005	Mii	228/180.5	B23K 20/007
2007/0187467	12/2006	Toyama	228/101	H01L 24/11
2010/0059574	12/2009	Arahata	228/110.1	H01L 24/48

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
04024934	12/1991	JP	H01L 24/78
H04184947	12/1991	JP	N/A
05235002	12/1992	JP	H01L 24/11

2010103542	12/2009	JP	N/A
4625858	12/2010	JP	N/A
2014140074	12/2013	JP	N/A
6067951	12/2016	JP	B23K 1/0016

OTHER PUBLICATIONS

“International Search Report (Form PCT/ISA/210) of PCT/JP2019/020960,” mailed on Jul. 2, 2021, with English translation thereof, pp. 1-3. cited by applicant

“Office Action of Taiwan Counterpart Application”, issued on Mar. 9, 2020, with English translation thereof, p. 1-p. 9. cited by applicant

“Office Action of China Counterpart Application”, issued on May 29, 2024, with partial English translation thereof, pp. 1-10. cited by applicant

Primary Examiner: Arroyo; Teresa M.

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is a 371 application of the International PCT application serial no. PCT/JP2019/020960, filed on May 27, 2019. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

TECHNICAL FIELD

(2) The present specification discloses a wire bonding apparatus for connecting a first bonding point and a second bonding point provided on a mounted body to each other with a wire, a method for manufacture of a semiconductor device, and a semiconductor device.

BACKGROUND ART

(3) In recent years, in accordance with increase in the level of functionality of portable information terminals, digital AV instruments, IC cards, and the like, mounted semiconductor chips have been required to be smaller and thinner and have a higher level of integration. Particularly, in laminated memory devices or the like, memory capacities thereof are determined depending on the number of chips which can be laminated. For this reason, it is important to be able to laminate a larger number of semiconductor chips within a prescribed package height. In order to satisfy such a demand, it is necessary to restrict the heights of wire loops formed through wire bonding. Hence, in the related art, many low looping technologies for restricting the loop height have been proposed.

(4) Here, a pressure bonded ball having a flat disk shape and a column part overlapping the pressure bonded ball are present at one end of a wire connecting a first bonding point and a second bonding point to each other. In many low looping technologies in the related art, since looping is performed in a state in which a column part remains on a pressure bonded ball as it stands, it is difficult to sufficiently reduce the loop height.

(5) Here, Patent Literature 1 discloses a wire bonding method in which low looping can be formed. Specifically, in Patent Literature 1, a first step in which a side surface of an upper part (column part) of a pressure bonded ball is pressurized and a head top part of the pressure bonded ball is formed by raising a capillary and then moving the capillary to a second bonding point side after a pressure bonded ball having a desired pressure bonding thickness is formed by pressure-bonding a free air ball at a tip of the capillary at a first bonding point, and a second step in which a wire is pressurized from obliquely above by raising the capillary and causing it to descend while moving

the capillary to a second bonding point side after the first step are executed. According to this technology of Patent Literature 1, since a portion of the upper part (column part) of the pressure bonded ball is crushed using a capillary, the loop height can be reduced to a certain extent.

CITATION LIST

Patent Literature

(6) [Patent Literature 1] Japanese Patent No. 4625858

SUMMARY OF INVENTION

Technical Problem

(7) However, in the technology of Patent Literature 1, since only a portion of a column part can be crushed, it is difficult to sufficiently reduce the loop height. Hence, the present specification discloses a wire bonding apparatus with which the loop height can be further reduced, a method for manufacture of a semiconductor device, and a semiconductor device.

Solution to Problem

(8) A wire bonding apparatus disclosed in the present specification is a wire bonding apparatus for connecting a first bonding point and a second bonding point provided on a mounted body to each other with a wire. The wire bonding apparatus includes a capillary which holds the wire, a movement mechanism which moves the capillary with respect to the mounted body, and a control unit which controls driving of the movement mechanism. The control unit executes at least a first process in which a pressure bonded ball and a column part positioned over the pressure bonded ball are formed at the first bonding point by causing the capillary to descend to a prescribed pressure bonding height toward the first bonding point after a free air ball is formed at a tip of the wire; a second process in which the column part is scraped off using the capillary by horizontally moving the capillary at the pressure bonding height after execution of the first process; and a third process in which the capillary is moved in a forward direction that is a direction of approaching the second bonding point at a movement height higher than the pressure bonding height, and a pressing operation of causing the capillary to temporarily descend such that a wire portion overlapping the pressure bonded ball is pressed down using the capillary is repeated at least once during movement after execution of the second process.

(9) In the case of the constitution, the column part is scraped using the capillary, and the wire portion overlapping the pressure bonded ball is pressed down using the capillary. Therefore, the loop height can be further reduced.

(10) In this case, in the second process, the control unit may cause the capillary to horizontally move in a reverse direction that is a direction of separating from the second bonding point.

(11) In addition, in the second process, the control unit may cause the capillary to horizontally move by a distance which is at least a diameter of the column part or longer.

(12) According to the constitution, the column part can substantially certainly be scraped.

(13) In addition, in the third process, the control unit may cause the pressing operation to be performed twice or more while a horizontal position of the capillary is changed such that the wire portion overlapping the pressure bonded ball is thoroughly pressurized using the capillary.

(14) According to the constitution, not only the thickness of a first bonded part but also the loop height can be further reduced.

(15) In addition, the control unit may generate a movement sequence of the capillary based on shape information of the capillary, target shape information of the pressure bonded ball, and information of the wire.

(16) According to the constitution, trouble of an operator can be reduced.

(17) A method for manufacture of a semiconductor device according to another aspect of the present invention is a method for manufacture of a semiconductor device in which a semiconductor device is manufactured by connecting a first bonding point and a second bonding point to each other with a wire using a capillary. The method includes a first step in which a pressure bonded ball and a column part positioned over the pressure bonded ball are formed at the first bonding point by

causing the capillary to descend to a prescribed pressure bonding height toward the first bonding point after a free air ball is formed at a tip of the wire inserted through the capillary; a second step in which the column part is scraped off using the capillary by horizontally moving the capillary at the pressure bonding height after execution of the first step; and a third step in which the capillary is moved in a forward direction that is a direction of approaching the second bonding point at a movement height higher than the pressure bonding height, and a pressing operation for causing the capillary to ascend and descend such that a wire portion overlapping the pressure bonded ball is pressed down using the capillary is repeated at least once during movement after execution of the second step.

(18) In the case of the constitution, the column part is scraped using the capillary, and the wire portion overlapping the pressure bonded ball is pressed down using the capillary. Therefore, the loop height can be further reduced.

(19) A semiconductor device according to another aspect of the present invention is a semiconductor device in which a first bonding point on a semiconductor chip and a second bonding point on a lead frame having the semiconductor chip mounted thereon are connected to each other with a wire loop. The wire loop has a first bonded part which is formed at the first bonding point, and a second bonded part which is formed at the second bonding point and is connected to the first bonded part via the wire. The first bonded part has a shape in which a portion of the wire crushed toward a pressure bonded ball having a flat disk shape is placed at a predetermined interval on the pressure bonded ball. The wire is substantially horizontally drawn out from an end part of the first bonded part.

(20) A portion of the crushed wire is directly placed on the pressure bonded ball. Therefore, not only the thickness of the first bonded part but also the loop height can be reduced, and the thickness of the semiconductor device can be further reduced.

(21) In this case, a loop height that is a distance from an upper surface of the semiconductor chip to a highest point of the wire loop may be smaller than a total value of a thickness of the pressure bonded ball and a diameter of the wire or may be the same as the total value.

(22) According to the constitution, not only the thickness of the first bonded part but also the loop height can be reduced, and the thickness of the semiconductor device can be further reduced.

Advantageous Effects of Invention

(23) According to the wire bonding apparatus, the method for manufacture of a semiconductor device, and the semiconductor device disclosed in the present specification, the column part is scraped using the capillary, and the wire portion overlapping the pressure bonded ball is pressed down using the capillary. Therefore, the loop height can be further reduced.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a view illustrating a constitution of a wire bonding apparatus.

(2) FIG. 2 is a view illustrating a shape of a tip of a capillary.

(3) FIG. 3 is a view illustrating an example of a shape of a wire loop.

(4) FIG. 4 is a view illustrating a movement trajectory of the capillary.

(5) FIG. 5 is a view illustrating a situation at the time of forming a first bonded part.

(6) FIG. 6 is a view illustrating another situation at the time of forming the first bonded part.

(7) FIG. 7 is a table showing experimental results.

(8) FIG. 8 is a photograph showing an example of the first bonded part formed by the technology disclosed in the present specification.

(9) FIG. 9 is a view illustrating a situation in which a first bonded part in the related art is formed.

(10) FIG. 10 is a view illustrating another situation in which the first bonded part in the related art

is formed.

DESCRIPTION OF EMBODIMENT

(11) Hereinafter, a constitution of a wire bonding apparatus **10** will be described with reference to the drawings. FIG. **1** is a view illustrating a constitution of the wire bonding apparatus **10**. This wire bonding apparatus **10** is a device connecting a first bonding point **P1** and a second bonding point **P2** to each other with a wire **50**. Generally, the first bonding point **P1** is set on a pad **112** of a semiconductor chip **110**, and the second bonding point **P2** is set on a lead **122** of a lead frame **120** having the semiconductor chip **110** mounted thereon.

(12) The wire bonding apparatus **10** includes a bonding head **16** and a stage **20** on which the lead frame **120** having the semiconductor chip **110** mounted thereon (both will hereinafter be collectively referred to as “a mounted body”) is placed. The bonding head **16** further includes a bonding arm **14** which functions as an ultrasonic horn and a capillary **12** which is attached to a tip of the said bonding arm **14**. The bonding arm **14** is an arm protruding from the bonding head **16** in a horizontal direction, and an ultrasonic vibrator is embedded thereinto. Ultrasonic vibration can be applied to the capillary **12** positioned at the tip of the bonding arm **14** by applying a voltage to this ultrasonic vibrator using an ultrasonic wave oscillator (not illustrated) provided in the wire bonding apparatus **10**.

(13) The capillary **12** is attached to the tip of the bonding arm **14** such that it vertically faces the stage **20**. A penetration hole (which will hereinafter be referred to as “a hole **40**” and is not illustrated in FIG. **1**) penetrating the capillary **12** in an axial direction is formed therein, and the wire **50** such as a gold wire is inserted through this hole **40**. The capillary **12** is suitably replaced in accordance with the kind of the used wire **50**, the shape of a required pressure bonded ball **60**, or the like.

(14) A discharge electrode **22** is disposed in the vicinity of the capillary **12**. The discharge electrode **22** is provided at a tip of the wire **50** to form a free air ball (which will hereinafter be referred to as “a FAB **52**”) which is realized when the said wire **50** melts. When a high voltage is applied between this discharge electrode **22** and the tip of the wire to generate a discharge, the tip part of the wire **50** melts due to the discharge energy thereof. Further, the FAB **52** is formed at the tip of the wire **50** due to this melting.

(15) A clamper **21** is arranged above the capillary **12**. The clamper **21** has a pair of grip members arranged on both sides of the wire **50** and sandwiches or releases the wire **50** by causing these grip members to become closer to or separate from each other.

(16) The bonding arm **14** is attached to the bonding head **16** via an ascending/descending mechanism (not illustrated). In addition, the bonding head **16** is installed in an XY table **18** and can move in the horizontal direction. Further, the capillary **12** can relatively move in the horizontal direction and a vertical direction with respect to a mounted body in accordance with horizontal movement of the bonding head **16** and vertical movement of the bonding arm **14**. Namely, the ascending/descending mechanism and the XY table **18** function as a movement mechanism for relatively moving the capillary **12** with respect to the mounted body. In the present example, the capillary **12** is moved, but a constitution in which the stage **20** is moved instead of the capillary **12** may be adopted.

(17) A mounted body that is the lead frame **120** having the semiconductor chip **110** mounted thereon is placed on the stage **20**. A heater (not illustrated) for heating the lead frame **120** is built into this stage **20**. When wire bonding is executed, the lead frame **120** is heated by this heater.

(18) A control unit **24** controls driving of each part of the wire bonding apparatus **10**. For example, the control unit **24** includes a memory which stores various kinds of data and a CPU which performs various kinds of computation. Data stored in the memory of the control unit **24** includes a control program for executing a bonding process and data and the like necessary to generate a movement sequence of the capillary **12**, which will be described below.

(19) Specifically, the control unit **24** controls the position of the capillary **12** with respect to the

mounted body by controlling driving of the XY table **18** and the ascending/descending mechanism. In addition, the control unit **24** also performs opening/closing control of the clasper **21**, applying control of a discharge voltage, and driving control of the heater of the stage **20** in accordance with the state of progress of the bonding process. In addition, the control unit **24** also functions as a generation part which generates a movement sequence of the capillary **12** (a driving sequence of the XY table **18** and the ascending/descending mechanism). In order to generate a movement sequence, information related to the shape of the capillary **12**, target shape information related to the pressure bonded ball **60** (which will be described below), and the like are stored in the memory of the control unit **24**, and this will be described below.

(20) FIG. **2** is a view illustrating an example of the tip part of the capillary **12**. The hole **40** that is a penetration hole penetrating the capillary **12** in its axial direction is formed therein. The wire **50** is inserted through the inside of the hole **40**. Therefore, a diameter of the hole **40** (hole diameter H) is larger than the diameter of the wire **50** (wire diameter ϕ) ($H > \phi$). A lower end of the hole **40** expands in a conical shape. A tapered surface expanding in this conical shape will be referred to as a chamfered surface **42**. In addition, the largest diameter (that is, the diameter at the lowermost end) in a space of this conical shape will be referred to as a chamfer diameter CD .

(21) A lower end surface of the capillary **12** becomes a facing surface **44** which pressurizes the FAB **52**. This facing surface **44** may be a flat horizontal surface or may be an inclined surface advancing upward going closer to the outward side. The width of the facing surface **44**, that is, a distance from an inner circumferential edge at the lower end of the hole **40** to an outer circumferential edge at the lower end of the capillary **12** will hereinafter be referred to as “a facing width W ”. When the outer diameter of the capillary **12** is T , the facing width W is expressed by $W = (T - CD)/2$.

(22) FIG. **3** is an image view of a wire loop formed by the wire bonding apparatus **10**. A plurality of pads **112** is arranged in the semiconductor chip **110**, and a plurality of leads **122** is arranged in the lead frame **120**. The wire bonding apparatus **10** connects the first bonding point **P1** positioned over this pad **112** and the second bonding point **P2** positioned over the lead **122** to each other with the wire **50**.

(23) A first bonded part **54** which is formed by pressing one end of the wire **50** to the pad **112** is formed at the first bonding point **P1**, and the wire **50** drawn out from this first bonded part **54** extends to the second bonding point **P2**. A second bonded part **58** which is formed by pressing the other end of the wire **50** to the lead **122** is formed at the second bonding point **P2**. Here, normally, the second bonded part **58** is a stitch bond realized by pressing and crushing the wire **50** against the lead **122**.

(24) In order to reduce the thickness of a semiconductor device, there is a need to reduce the height of this wire loop, particularly a distance from an upper surface of the pad **112** to the uppermost point of the wire loop in the vertical direction, that is, a loop height HL . In the present specification, in order to reduce this loop height HL , the first bonded part **54** is formed through a special step. This will be described in comparison with a technology in the related art. In the following description, when viewed from the first bonding point **P1**, a direction of approaching the second bonding point **P2** will be referred to as “a forward direction”, and a direction of separating from the second bonding point **P2** will be referred to as “a reverse direction”.

(25) First, formation of the first bonded part **54** in the related art will be simply described. FIG. **9** is an image view illustrating a flow of formation of the first bonded part **54** in the related art. When the first bonded part **54** is formed, first, the pressure bonded ball **60** is formed at the first bonding point **P1** positioned over the pad **112** of the semiconductor chip **110**. Specifically, first, as illustrated in FIG. **9(a)**, the FAB **52** is formed at the tip of the wire **50**. Subsequently, as illustrated in FIG. **9(b)**, the capillary **12** is caused to descend toward the first bonding point **P1**, and the FAB **52** is pressurized to the first bonding point **P1** by the facing surface **44** of the capillary **12**. At the time of this pressurization, vibration may be applied to the capillary **12** via the bonding arm **14**. In

accordance with this pressurization, the FAB 52 is deformed flat, and the pressure bonded ball 60 having a flat disk shape is formed on the pad 112. In addition, a portion of a material constituting the FAB 52 fills the inside of the hole 40 of the capillary 12. The material filling the inside of this hole 40 constitutes a column part 62 having a smaller diameter than the pressure bonded ball 60 and a larger diameter than the wire 50. Further, due to this pressurization, the first bonded part 54 in which the column part 62 is placed on the pressure bonded ball 60 having a flat disk shape is formed at the first bonding point P1.

(26) If the first bonded part 54 is formed, the control unit 24 causes the capillary 12 to move such that the wire 50 loops toward the second bonding point P2. Specifically, as indicated by the arrows in FIG. 9(b), the control unit 24 causes the capillary 12 to move in the upward direction, the reverse direction, and the upward direction, imparts a bending habit to the wire 50, and then causes the capillary 12 to move to the second bonding point P2. Further, at the second bonding point P2, the second bonded part 58 (stitch bond) of the crushed wire 50 is formed by pressing the capillary 12 to the lead 122. If the second bonded part 58 is formed, the control unit 24 causes the capillary 12 to move upward, and then causes the capillary 12 to further move in the upward direction in a state in which the clasper 21 is closed such that the wire 50 is torn off.

(27) As in FIG. 9(c), around the first bonded part 54 formed by the foregoing procedure, the wire 50 has a shape extending upward from an upper end of the first bonded part 54, and then extending in an obliquely downward direction while forming a gentle arc. In this case, the loop height HL is the total of the thickness of the pressure bonded ball 60, the thickness of the column part 62, and the height of the wire 50 drawn out substantially in a U-shape from the column part 62. This loop height HL has been comparatively high, which is twice to four times the wire diameter ϕ . Such a large loop height HL has hindered not only thickness reduction of semiconductor devices but also size reduction, thickness reduction, and high integration of semiconductor devices.

(28) Hence, in the related art, a low looping technology in which the loop height HL can be further reduced has been examined. For example, as illustrated in FIG. 10, a technology in which the pressure bonded ball 60 is formed at the first bonding point P1, the wire 50 is thereafter folded back on the said pressure bonded ball 60, and then this folded back wire is pressurized using the capillary 12 has been proposed in the related art. Specifically, if the pressure bonded ball 60 and the column part 62 are formed, as indicated by the arrows in FIG. 10(a), the control unit 24 causes the capillary 12 to move in the upward direction, the reverse direction, the downward direction, and the upward direction. Thereafter, the capillary 12 is moved in the forward direction again. At that spot, once again it is moved in the downward direction. Accordingly, the wire 50 is folded back on the pressure bonded ball 60. Further, thereafter, similar to a normal looping operation, the capillary 12 is moved in the upward direction, the reverse direction, and the upward direction. After a bending habit is imparted thereto, the capillary 12 is moved to the second bonding point P2.

(29) According to the technology, the wire 50 extends substantially in a horizontal direction without vertically rising from the first bonded part 54. Therefore, compared to the technology illustrated in FIG. 9, the loop height HL can be reduced. However, in this technology, the column part 62 lies on its side, and the wire 50 is placed on this lying column part 62. Although this column part 62 and the wire 50 are pressurized by the capillary 12, it is difficult to sufficiently reduce the height thereof by simply pressurizing these. Particularly, the column part 62 is harder than other portions due to work hardening caused when the pressure bonded ball 60 is formed. It is difficult to sufficiently reduce the thickness of the column part 62 by simply pressurizing it using the capillary 12. As a result, the loop height HL according to the technology in FIG. 10 is often approximately the total of a thickness Bt of the pressure bonded ball 60 and the wire diameter ϕ . For example, when the wire diameter is 18 μm and the thickness Bt of the pressure bonded ball 60 is 7 μm , the loop height HL according to the technology in FIG. 10 is approximately 25 μm .

(30) In the wire bonding apparatus 10 disclosed in the present specification, the loop height HL is further reduced. Specifically, in this device, after the pressure bonded ball 60 and the column part

62 are formed, the column part 62 is scraped using the capillary 12 by horizontally moving the capillary 12 as it stands without moving it upward. Accordingly, low looping is achieved. This will be described with reference to FIGS. 4 to 6. FIG. 4 is a view illustrating a movement trajectory of the capillary 12 at the time of forming the first bonded part 54. In addition, FIGS. 5 and 6 are views illustrating movement of the capillary 12 and the wire 50 when the first bonded part 54 is formed. The alphabets a to l applied in each diagram of FIGS. 5 and 6 correspond to trajectories a to m indicated in FIG. 4.

(31) When the first bonded part 54 is formed, the control unit 24 first releases the clasper 21. In this state, driving control of the XY table 18 and the ascending/descending mechanism is performed, and the capillary 12 is moved to a place immediately above the first bonding point P1. Subsequently, the control unit 24 causes a high voltage to be applied between the discharge electrode 22 and the tip of the wire 50 to generate a discharge, and the FAB 52 is formed at the tip of the wire 50.

(32) If the FAB 52 is formed, the control unit 24 causes the capillary 12 to descend toward the first bonding point P1. At this time, a distance from the upper surface of the pad 112 to the lower end of the capillary 12 (which will hereinafter be referred to as “a pressure bonding height H1”) is determined based on a target value of the thickness Bt of the pressure bonded ball 60.

(33) The trajectory a in FIG. 4 indicates a trajectory when this capillary 12 is caused to descend to the pressure bonding height H1. In addition, the diagram at the left end in the upper stage in FIG. 5 illustrates a situation of the capillary 12 and the wire 50 in this trajectory a. In addition, at the time of this descending, ultrasonic vibration may be applied to the capillary 12 via the bonding arm 14.

(34) In accordance with descending of the capillary 12, the FAB 52 is pressurized and becomes flat by the facing surface 44 of the capillary 12. In addition, a portion of a material constituting the FAB 52 fills the inside of the hole 40 of the capillary 12. As a result, as illustrated at the left end in the upper stage in FIG. 5, the pressure bonded ball 60 having a flat disk shape and the column part 62 placed on the said pressure bonded ball 60 are formed at the first bonding point P1. The step and the process of forming this pressure bonded ball 60 and the column part 62 are a first step and a first process.

(35) If the pressure bonded ball 60 is formed, subsequently, the control unit 24 causes the capillary 12 to horizontally move at the pressure bonding height H1 such that the column part 62 is scraped off using the capillary 12. Specifically, as indicated by the trajectory b in FIG. 4, the control unit 24 causes the capillary 12 to horizontally move in the reverse direction without raising the capillary 12, in other words, while maintaining a state in which the column part 62 is present inside the hole 40 of the capillary 12. The diagram at the center in the upper stage in FIG. 5 is a view illustrating a situation at this time. In this case, naturally, an inner circumferential surface of the hole 40 and the column part 62 interfere with each other. When the capillary 12 horizontally moves while interfering with the column part 62, the column part 62 is scraped by the capillary 12. As indicated by darker hatching at the center in the upper stage in FIG. 5, a portion of the material of the scraped column part 62 escapes in a lateral direction, and other portions escape into the hole 40. In any case, when the capillary 12 horizontally moves without rising after the pressure bonded ball 60 is formed, the column part 62 is scraped off. The step and the process of scraping off this column part 62 correspond to a second step and a second process.

(36) Here, a distance of horizontal movement of this capillary 12 (movement distance of the trajectory b) is not particularly limited. However, an objective of this second step (trajectory b) is to scrape the column part 62. Therefore, in the said second step, it is desirable that the capillary 12 be horizontally moved by a distance which is the diameter of the column part 62 or longer. In addition, the direction of horizontal movement of the capillary 12 may be the reverse direction or may be the forward direction as long as the column part 62 can be scraped off. In addition, the capillary 12 may move forward and rearward at least once in the reverse direction and the forward direction as long as the column part 62 can be scraped off. In addition, in order to smoothly perform this

scraping-off operation, ultrasonic vibration may be applied to the capillary **12** during movement in the trajectory **b**.

(37) If the second step ends, the control unit **24** subsequently executes a third step (third process) in which the capillary **12** is moved in the forward direction at a movement height **H2** higher than the pressure bonding height **H1** and a pressing operation of causing the capillary **12** to ascend and descend during the movement is repeated at least once. The trajectory **c** to the trajectory **k** indicate movement trajectories of the capillary **12** in this third step. In addition, the diagrams from the right end in the upper stage in FIG. 5 to the center in the lower stage in FIG. 6 indicate situations of this third step.

(38) Specifically, if the column part **62** is scraped off, the control unit **24** causes the capillary **12** to move upward (trajectory **c**) and then to move to the forward side by a predetermined distance (trajectory **d**). Accordingly, as illustrated at the right end in the upper stage and the left end in the lower stage in FIG. 5, the wire **50** is folded back to the forward side and is placed on the pressure bonded ball **60**. In this state, the control unit **24** causes the capillary **12** to move downward (trajectory **e**), and as illustrated at the center in the lower stage in FIG. 5, causes the wire **50** on the pressure bonded ball **60** to be pressed down by the facing surface **44** of the capillary **12**.

Accordingly, a portion of the material of the trampled wire **50** escapes to the outward side of the capillary **12**, and other portions escape into the hole **40** of the capillary **12**. On the other hand, the thickness of the first bonded part **54** immediately below the facing surface **44** is drastically reduced.

(39) Here, this folded back wire portion includes the material constituting the column part **62** (darker hatching spot). As described above, the column part **62** is harder than those at other spots. For this reason, the original column part **62** is not easily deformed and the thickness thereof is also not easily reduced by simply pressing down the column part **62** using the capillary **12**. However, at this time, the column part **62** has been scraped and destroyed by the capillary **12**. For this reason, it is easily deformed and the thickness thereof is also reduced by pressing down the column part **62** using the capillary **12**.

(40) When the wire **50** is pressed down by the facing surface **44**, ultrasonic vibration may be applied to the capillary **12**. In any case, an operation of causing the capillary **12** to temporarily descend (an operation in the trajectory **e**, **h**, or **k**) in this manner will hereinafter be referred to as “a pressing operation”.

(41) The control unit **24** repeats this pressing operation a plurality of times while a horizontal position is changed until the wire **50** arrives at a forward side end part of the pressure bonded ball **60**. In the present example, the control unit **24** performs the pressing operation three times. The trajectory **e** in FIG. 4 and the diagram at the center in the lower stage in FIG. 5 illustrate a first pressing operation. In addition, the trajectory **h** in FIG. 4 and the diagram at the center in the upper stage in FIG. 6 illustrate a second pressing operation, and the trajectory **k** in FIG. 4 and the diagram at the center in the lower stage in FIG. 6 illustrate a third pressing operation. As is obvious in FIGS. 5 and 6, the wire **50** can be drawn out from the forward side end part of the pressure bonded ball **60** while the thickness of the first bonded part **54** is maintained thin by repeating the pressing operation until the wire **50** arrives at the forward side end part of the pressure bonded ball **60**.

(42) Here, it is desirable that the number of times of performing this pressing operation and horizontal intervals (distances of the trajectories **d**, **g**, and **j**) be set such that the entire wire **50** placed on the pressure bonded ball **60** is thoroughly pressed down by the facing surface **44** on the reverse side of the hole **40**.

(43) In addition, the movement height **H2** is set within a range in which the wire **50** can be folded back. That is, if the movement height **H2** is excessively smaller than the wire diameter **9**, the wire **50** is unlikely to lie, and thus the wire **50** cannot be folded back. On the other hand, if the movement height **H2** is larger than necessary, it takes extra time for the increased portion. Hence, it is desirable that an appropriate value for the movement height **H2** corresponding to the diameter or the material of the used wire **50** be obtained in advance through an experiment or the like and be

stored in the control unit **24**.

(44) It is desirable that the height of the capillary **12** at the time of pressing down, that is, a pressing height **H3** be substantially the same as the pressure bonding height **H1**. However, actually, it is difficult to realize $H3=H1$ due to a resistance or the like from the wire **50** pressed down by the capillary **12**. Actually, $H3<H1$ is realized. A difference ΔH between the pressing height **H3** and the pressure bonding height **H1** significantly affects the thickness of the first bonded part **54**. For this reason, it is desirable that an appropriate value for the difference ΔH be obtained in advance through an experiment or the like and be stored in the control unit **24** for each of the diameter or the material of the used wire **50**.

(45) If the third step is completed, the control unit **24** executes a looping operation in which the wire **50** is drawn out to the second bonding point **P2**. Specifically, if the last pressing operation is completed, the control unit **24** causes the capillary **12** to move in the forward direction at the pressing height **H3** (trajectory **1** in FIG. **4**) and then to move upward (trajectory **m** in FIG. **4**), and a bending habit is imparted to the wire **50**. Thereafter, the control unit **24** causes the capillary **12** to move in an obliquely downward direction toward the second bonding point **P2**.

(46) If the capillary **12** arrives at the second bonding point **P2**, the control unit **24** causes the capillary **12** to descend toward the second bonding point **P2** and causes the wire **50** to be pressed to the lead **122**. At this time, as necessary, ultrasonic vibration is applied to the capillary **12**. Due to this pressing, a stitch bond which becomes the second bonded part **58** is formed at the second bonding point **P2** (lead **122**). In this state, the control unit **24** causes the capillary **12** to slightly rise and then causes the clasper **21** to be closed. Further, the capillary **12** is laterally moved in a state in which the clasper **21** is closed such that the wire **50** is torn off.

(47) As is obvious in the foregoing description, in the wire bonding apparatus **10** disclosed in the present specification, after the pressure bonded ball **60** and the column part **62** is formed, the column part **62** positioned over the pressure bonded ball **60** is scraped off by causing the capillary **12** to horizontally move at the pressure bonding height **H1**. Moreover, after the column part **62** is scraped off, the wire **50** folded over the pressure bonded ball **60** is pressed down using the capillary **12**. Accordingly, not only the thickness of the first bonded part **54** can be drastically reduced, but also the loop height **HL** of the wire loop can be drastically reduced.

(48) FIG. **7** is a table showing experimental results of wire bonding performed by the wire bonding apparatus **10** disclosed in the present specification. In the experiment, 30 wire loops were formed using a gold wire ($\phi=18\text{ }\mu\text{m}$), and the thickness **Bt**, the loop height **HL**, and the pull strength of the pressure bonded ball **60** were measured for each wire loop.

(49) As illustrated in FIG. **7**, according to the technology disclosed in the present specification, the thickness **Bt** of the pressure bonded ball **60** is within a range of $6.6\text{ }\mu\text{m}$ to $7.2\text{ }\mu\text{m}$ (average thickness of $6.9\text{ }\mu\text{m}$), and the loop height **HL** is within a range of $19.8\text{ }\mu\text{m}$ to $21.5\text{ }\mu\text{m}$ (average thickness of $20.5\text{ }\mu\text{m}$). On the other hand, as described above, the loop height **HL** in the technology in the related art illustrated in FIG. **10** approximately corresponds to the total value of the thickness of the pressure bonded ball **60** and the wire diameter. In the case of $\phi=18\text{ }\mu\text{m}$, it is approximately $25\text{ }\mu\text{m}$. Namely, according to the technology disclosed in the present specification, compared to the technology in the related art illustrated in FIG. **10**, the loop height **HL** can be reduced approximately 20%. In addition, as illustrated in FIG. **7**, it can be ascertained that the pull strengths of the wire loops are within a range of 2.0 gf to 2.4 gf and the wire loops are low loops and have sufficient strengths.

(50) FIG. **8** is an image showing an example of the first bonded part **54** formed by the technology disclosed in the present specification. As illustrated in FIG. **8**, in the first bonded part **54** of the present example, a portion of the wire **50** crushed toward the pressure bonded ball **60** at a predetermined interval is placed on the pressure bonded ball **60** having a flat disk shape. In addition, it can be ascertained that the wire **50** is substantially horizontally drawn out from the forward side end part of the pressure bonded ball **60** and the loop height **HL** is restricted to

approximately 1.1 to 1.2 times the wire diameter ϕ .

(51) Next, a flow in which a movement sequence of the capillary **12** is automatically generated by the control unit **24** will be described. As described above, the control unit **24** automatically generates a movement sequence of the capillary **12**. In order to automatically generate this movement sequence, an operator inputs at least size information of the capillary **12**, wire information, and size information of the pressure bonded ball **60** in advance. Here, the size information of the capillary **12** includes dimension values of respective parts at the tip part of the capillary **12**, that is, the hole diameter H, the chamfer diameter CD, an outer diameter T, the facing width W, and the like. In addition, in place of such dimension values of respective parts, an operator may input only identification information (for example, a model number) of the capillary **12**. In this case, the control unit **24** stores a plurality of kinds of dimension values of the capillary **12** in association with the identification information in advance and identifies the dimension values of the actually using capillary **12** based on the identification information input from an operator.

(52) The wire information includes the diameter, the material, and the like of a used wire. In addition, the size information of the pressure bonded ball **60** includes target values for a diameter D and the thickness Bt of the pressure bonded ball **60** to be formed. The control unit **24** may automatically calculate the target values for the diameter D and the thickness Bt of the pressure bonded ball **60** based on other information. For example, the control unit **24** may store the diameter D and the thickness Bt of the pressure bonded ball **60**, which can be formed, for each of the shape of the using capillary **12** and the diameter of the wire, and the control unit **24** may automatically identify the diameter D and the thickness Bt of the pressure bonded ball **60** from the size information of the capillary **12** and the wire information input from an operator.

(53) In addition, before a sequence is generated, the control unit **24** also acquires positional information of the first bonding point P1 and the second bonding point P2, that is, positional information of the pad **112** of the semiconductor chip **110** and the lead of the lead frame **120**. Such positional information may be input by an operator or may be automatically acquired by the control unit **24**. That is, for example, a camera moving together with the said bonding arm **14** may be provided in the vicinity of the bonding arm **14**, and the control unit **24** may calculate the positions the first bonding point P1 and the second bonding point P2 based on an image captured by the said camera.

(54) If these pieces of information can be acquired, the control unit **24** calculates a movement position of the capillary **12** for each movement trajectory. Here, particularly, calculation of the movement positions in the trajectories b to k for forming the first bonded part **54** will be described. The control unit **24** calculates the heights H1 to H3, horizontal movement amount Lb and L1 to L3, and the like for calculating the movement positions of the capillary **12**.

(55) Specifically, the control unit **24** calculates the pressure bonding height H1 that is a distance from the upper surface of the pad **112** to the lower end of the capillary **12** in the first step (at the time of forming the pressure bonded ball **60** and the column part **62**) from the thickness Bt of the pressure bonded ball **60**. In addition, in the third step, the control unit **24** determines the movement height H2 that is a height when the capillary **12** is horizontally moved based on the kind (the diameter, the material, or the like) of the wire **50**. Moreover, in the third step, the control unit **24** determines the pressing height H3 that is a height when the wire **50** is pressed down using the capillary **12** based on the kinds (the diameters or the materials) of the pressure bonding height H1 and the wire **50**. That is, the pressing height H3 has a value obtained by adding the margin ΔH determined based on the kind of the wire **50** to the pressure bonding height H1.

(56) Moreover, the control unit **24** determines the horizontal movement distance Lb in the second step based on the largest diameter (that is, the chamfer diameter CD) of the column part **62**. In addition, the control unit **24** calculates the number N of times of a pressing operation in the third step and the horizontal intervals L1 to LN of a pressing operation based on the shape of the capillary **12** and the shape of the pressure bonded ball **60**. These values N and L1 to LN are set

such that the wire **50** placed on the pressure bonded ball **60** can be thoroughly pressed down by the facing surface **44** of the capillary **12**.

(57) If the heights **H1** to **H3** of the respective trajectories and the horizontal movement amounts **Lb** and **L1** to **LN** can be calculated, the control unit **24** combines these values, positional information of the first bonding point **P1** and the second bonding point **P2**, and the like, and generates a movement sequence of the capillary **12**.

(58) As is obvious in the foregoing description, according to the wire bonding apparatus **10** disclosed in the present specification, wire loops in which the loop height **HL** is reduced can be formed. In addition, according to the wire bonding apparatus **10** disclosed in the present specification, a movement sequence of the capillary **12** capable of realizing such low loops can be automatically generated based on the shape information of the capillary **12**, the wire information, and the shape information of the pressure bonded ball **60**. Accordingly, trouble of an operator can be reduced.

(59) The constitutions which have been described up to now are examples. As long as the control unit **24** executing at least the first process (first step) in which the pressure bonded ball **60** and the column part **62** are formed, the second process (second step) in which the capillary **12** is horizontally moved to scrape the column part **62**, and the third process (third step) in which a pressing operation is performed at least once during movement of the capillary **12** in the forward direction is provided, other constitutions may be suitably changed.

Claims

1. A method for manufacture of a semiconductor device by connecting a first bonding point and a second bonding point to each other with a wire using a capillary, the method comprising: a first step in which, after a free air ball is formed at a tip of the wire inserted through the capillary, the capillary descends to a prescribed pressure bonding height toward the first bonding point to deform the free air ball formed at a tip of the wire into a pressure bonded ball and a column part positioned over the pressure bonded ball at the first bonding point, wherein the prescribed pressure bonding height is determined based on a thickness of the pressure bonded ball; a second step in which the column part is scraped off using the capillary by making the capillary move horizontally without rising at the pressure bonding height after execution of the first step; and a third step in which the capillary is moved in a forward direction that is a direction of approaching the second bonding point at a movement height higher than the pressure bonding height and the wire is folded back without being cut, and a pressing operation for causing the capillary to ascend and descend such that a wire portion overlapping the pressure bonded ball is pressed down using the capillary is repeated at least once during movement after execution of the second step.
