



US012418577B2

(12) **United States Patent**
Rahman et al.

(10) **Patent No.:** **US 12,418,577 B2**

(45) **Date of Patent:** **Sep. 16, 2025**

(54) **DATA DISRUPTION TRACKING FOR WIRELESS NETWORKS, SUCH AS IMS NETWORKS**

(71) Applicant: **T-Mobile USA, Inc.**, Bellevue, WA (US)

(72) Inventors: **Muhammad Tawhidur Rahman**, Bellevue, WA (US); **Hsin Fu Henry Chiang**, Bellevue, WA (US)

(73) Assignee: **T-Mobile USA, Inc.**, Bellevue, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 641 days.

(21) Appl. No.: **17/684,303**

(22) Filed: **Mar. 1, 2022**

(65) **Prior Publication Data**

US 2022/0191266 A1 Jun. 16, 2022

Related U.S. Application Data

(62) Division of application No. 17/081,905, filed on Oct. 27, 2020, now Pat. No. 11,330,034.

(51) **Int. Cl.**
H04L 65/80 (2022.01)
H04B 7/06 (2006.01)
H04B 17/318 (2015.01)
H04L 65/10 (2022.01)
H04L 65/1016 (2022.01)
H04L 65/1069 (2022.01)
H04L 65/1104 (2022.01)
H04L 65/65 (2022.01)

(52) **U.S. Cl.**

CPC **H04L 65/80** (2013.01); **H04B 7/0632** (2013.01); **H04B 17/318** (2015.01); **H04L 65/10** (2013.01); **H04L 65/1016** (2013.01); **H04L 65/1069** (2013.01); **H04L 65/1104** (2022.05); **H04L 65/65** (2022.05)

(58) **Field of Classification Search**

CPC . H04B 17/318; H04B 7/0632; H04L 65/1104; H04L 65/65; H04L 65/10; H04L 65/1016; H04L 65/1069

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,836,797 B2	12/2004	Givoly et al.	
6,957,255 B1	10/2005	Schweitzer et al.	
7,020,130 B2	3/2006	Krause et al.	
7,366,136 B1	4/2008	Kalbag et al.	
7,609,646 B1 *	10/2009	Qi	H04L 12/66 370/252
7,751,316 B2	7/2010	Yarlagadda et al.	
7,773,584 B2	8/2010	Gorti et al.	
8,077,675 B2	12/2011	Stephenson et al.	
8,139,604 B2	3/2012	Yeom	
8,750,839 B1 *	6/2014	Paczkowski	H04L 65/1016 455/414.3
9,178,778 B2	11/2015	Meloche et al.	
10,440,179 B2 *	10/2019	Thomson	H04M 3/5175

(Continued)


Primary Examiner — Syed Ali

(74) *Attorney, Agent, or Firm* — Perkins Coie LLP

(57) **ABSTRACT**

Systems and methods for tracking and logging mute events that occur during communication sessions are disclosed. The method includes generating a disruption report that includes one or more aspects of a mute event detected during a communication session. The disruption report is communicated to a network for further analysis.

17 Claims, 4 Drawing Sheets



US 12,418,577 B2

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

10,972,516	B1 *	4/2021	Venkataraman		H04L 65/1083
2004/0204020	A1	10/2004	Kuramitsu		
2004/0213150	A1	10/2004	Krause et al.		
2005/0175032	A1	8/2005	Yeom		
2005/0233777	A1 *	10/2005	Twerdahl		H04M 1/72451 455/567
2005/0255811	A1	11/2005	Allen et al.		
2006/0193460	A1 *	8/2006	Cadiz		H04M 3/54 379/211.02
2006/0256721	A1	11/2006	Yarlagadda et al.		
2007/0143858	A1	6/2007	Hearty		
2007/0270104	A1	11/2007	Allen et al.		
2007/0286160	A1	12/2007	Gorti et al.		
2008/0137529	A1	6/2008	Sheikh et al.		
2008/0146290	A1 *	6/2008	Sreeram		H04M 1/6066 455/575.2
2009/0073959	A1 *	3/2009	Xu		H04L 65/765 370/352
2009/0135731	A1	5/2009	Secades et al.		
2009/0225670	A1	9/2009	Leung et al.		
2009/0316870	A1	12/2009	Wise et al.		
2010/0014509	A1	1/2010	Kouchri		
2010/0115111	A1	5/2010	Varga et al.		
2010/0226339	A1	9/2010	Stephenson et al.		
2010/0255831	A1	10/2010	Shuman et al.		
2011/0075653	A1	3/2011	Potts et al.		
2011/0110363	A1	5/2011	Anandani		
2011/0167172	A1	7/2011	Roach et al.		
2012/0081501	A1	4/2012	Benzaia et al.		
2012/0195242	A1 *	8/2012	Pyles		H04W 52/0251 370/329
2012/0224678	A1 *	9/2012	Walters		H04M 3/2281 379/189
2012/0294159	A1 *	11/2012	Sridhar		H04L 43/55 370/252
2013/0250779	A1	9/2013	Meloche et al.		
2015/0215346	A1 *	7/2015	Kotecha		H04L 67/141 709/227
2015/0270936	A1 *	9/2015	Han		H04L 5/0035 370/329
2016/0150455	A1 *	5/2016	Suryavanshi		H04W 76/45 455/436
2016/0205518	A1 *	7/2016	Patel		G06F 9/45558 455/518
2017/0078922	A1 *	3/2017	Raleigh		H04L 69/18
2017/0085711	A1 *	3/2017	Thomson		H04M 3/5175
2017/0230908	A1 *	8/2017	Agarwal		H04W 4/80
2017/0251031	A1 *	8/2017	Lehesaari		H04L 65/80
2017/0353598	A1 *	12/2017	Cho		H04M 3/2236
2018/0124238	A1	5/2018	Shah et al.		
2018/0293978	A1 *	10/2018	Sinha		G06F 40/232
2018/0317196	A1 *	11/2018	Do		H04W 24/08
2019/0149442	A1 *	5/2019	Kelley, Jr.		H04L 43/04 709/224
2019/0149445	A1 *	5/2019	Kelley, Jr.		H04L 43/026 709/224
2019/0200175	A1	6/2019	Ylönen et al.		
2019/0239032	A1 *	8/2019	Balasubramanian		H04L 65/611
2019/0278865	A1 *	9/2019	Hurwitz		G06F 16/358
2019/0289047	A1	9/2019	Bai et al.		
2020/0195536	A1 *	6/2020	Beattie, Jr.		H04B 17/318
2020/0296554	A1	9/2020	Chiang et al.		
2021/0021494	A1 *	1/2021	Yao		H04L 41/0631
2023/0289127	A1 *	9/2023	Gupta		G06F 3/04817

* cited by examiner




FIG. 1




FIG. 2





FIG. 3

**FIG. 4**




FIG. 5

1

DATA DISRUPTION TRACKING FOR WIRELESS NETWORKS, SUCH AS IMS NETWORKS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a division of U.S. patent application Ser. No. 17/081,905, filed on Oct. 27, 2020, entitled DATA DISRUPTION TRACKING FOR WIRELESS NETWORKS, SUCH AS IMS NETWORKS, which is hereby incorporated by reference in its entirety.

BACKGROUND

Rapid growth in computing technology is creating greater demand for data communication. As an example, some mobile devices and applications allow users to watch streaming content in ultra-high definition. Also, increasing number of new devices (e.g., Internet of Things (IoT) devices, and/or wearable devices) or devices that previously provided limited functionalities (e.g., appliances) are now communicating data. However, the amount of available network resources may be limited in supporting the growing demand.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a communication network in which some implementations of the present technology can be utilized.

FIG. 2 illustrates a block diagram of an example mobile device in accordance with one or more implementations of the present technology.

FIG. 3 illustrates a block diagram of an example message in accordance with one or more implementations of the present technology.

FIG. 4 is a flow diagram illustrating an example method for tracking disruptions in accordance with one or more implementations of the present technology.

FIG. 5 is a diagrammatic representation of a machine in the example form of a computer system within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, can be executed.

In the drawings, some components and/or operations can be separated into different blocks or combined into a single block for discussion of some of the implementations of the present technology. Moreover, while the technology is amenable to various modifications and alternative forms, specific implementations have been shown by way of example in the drawings and are described in detail below. The intention, however, is not to limit the technology to the particular implementations described. On the contrary, the technology is intended to cover all modifications, equivalents, and alternatives falling within the scope of the technology as defined by the appended claims.

DETAILED DESCRIPTION

Some traditional mobile devices include internal mechanisms that detect network-related mutes, e.g., when voice-related signals are lost or dropped due to an error, during voice communications. When a duration of a mute event reaches a predetermined threshold, traditional mobile devices automatically terminate the session without user input to end the session (e.g., hanging up or terminating the

2

call). Generally, these devices send Session Initiation Protocol (SIP) BYE messages to the core network to signal terminations. For such mute-based automatic terminations, the mobile device can use special headers to notify the core network of the mute event. However, users often terminate the session (e.g., hang up the call) in response to the mute event before the predetermined duration threshold. Accordingly, the mobile devices do not send the mute-related information, and the core network fails to obtain any information regarding the mute event and thus does not know if, e.g., the user terminated the call because of a poor-quality connection.

In contrast, implementations of the present technology seek to provide quality reports for mute events, even for events that do not persist until the threshold duration and/or even when the user terminates the session. In some implementations, mobile devices are configured to determine the mute-related information (via, e.g., the existing internal mechanisms) that represent network-related mutes (e.g., absence of Real-time Transfer Protocol (RTP) packets) during voice communications. The mobile devices track the mute-related information (via, e.g., an Internet Protocol (IP) Media Subsystem (IMS) protocol stack) and report the tracked information to the mobile communication network. For example, the mobile devices can be reconfigured such that the RTP packet loss is periodically reported to the IMS stack. The IMS stack in the mobile device can track the RTP loss information (e.g., duration, loss rate, direction, channel conditions, etc.) during the session. When the session ends, regardless of the source of termination, the IMS stack can include the tracked information in the SIP BYE message according to a predetermined process. Also, the mobile devices can also be configured to determine and report a duration, a direction, a packet drop rate, a radio connection indicator, and/or a geographic location associated with, or at the time of, the mute event.

The network receives the quality information from the mobile devices, such as through the SIP BYE messages. Accordingly, the core network obtains the crowd-sourced information related to the mute events. In some implementations, the core network uses the crowd-sourced information to identify patterns and/or causes for the mute events. For example, the core-network can generate a histogram and/or implement a pattern recognition algorithm to identify certain conditions, scenarios, locations, and/or device combinations associated with the mute events.

Using the reported information, the network can obtain more accurate information of mute events, thereby identifying and fixing potential root-causes for the mutes (e.g., erroneous conditions). Accordingly, by communicating the quality information for mute events, the network can improve network performances and reduce mute events.

Various examples of the invention will now be described. The following description provides certain specific details for a thorough understanding and enabling description of these examples. One skilled in the relevant technology will understand, however, that the invention can be practiced without many of these details. Likewise, one skilled in the relevant technology will also understand that the invention can include many other obvious features not described in detail herein. Additionally, some well-known structures or functions may not be shown or described in detail below, to avoid unnecessarily obscuring the relevant descriptions of the various examples. Further, the examples in this application of prior or related systems and their associated limitations are intended to be illustrative and not exclusive. Other limitations of existing or prior systems will become

apparent to persons of ordinary skill in the art upon reading the following description. The terminology used below is to be interpreted in its broadest reasonable manner, even though it is being used in conjunction with a detailed description of certain specific examples of the invention. Indeed, certain terms may even be emphasized below; however, any terminology intended to be interpreted in any restricted manner will be overtly and specifically defined as such in this Detailed Description section.

The techniques introduced here can be implemented as special-purpose hardware (for example, circuitry), as programmable circuitry appropriately programmed with software and/or firmware, or as a combination of special-purpose and programmable circuitry. Hence, implementations can include a machine-readable medium having stored thereon instructions which can be used to program a computer (or other electronic devices) to perform a process. The machine-readable medium can include, but is not limited to, floppy diskettes, optical disks, compact disc read-only memories (CD-ROMs), magneto-optical disks, ROMs, random access memories (RAMs), erasable programmable read-only memories (EPROMs), electrically erasable programmable read-only memories (EEPROMs), magnetic or optical cards, flash memory, or other types of media/machine-readable medium suitable for storing electronic instructions.

The phrases “in some implementations,” “according to some implementations,” “in the implementations shown,” “in other implementations,” and the like, generally mean the particular feature, structure, or characteristic following the phrase is included in at least one implementation of the present technology and can be included in more than one implementation. In addition, such phrases do not necessarily refer to the same implementations or different implementations.

Suitable Environment

FIG. 1 illustrates a communication network **100** (also referred to herein as network **100**) in accordance with various implementations or embodiments. The communication network **100** can communicatively couple devices, including a mobile device **102** (e.g., User Equipment (UE)). The mobile device **102** can include wireless and/or mobile end-user devices. Some examples of the mobile device **102** can include a mobile phone (e.g., a smart phone), a laptop, a wearable device (e.g., a smart watch, augmented-reality (AR) glasses, etc.), an IoT device, a smart vehicle, an autonomous vehicle, and the like.

The network **100** can include access nodes **104** configured to serve as hubs that function as gateways for the network **100**. Some examples of the access node **104** can include a Radio Access Network (RAN) Node (e.g., an Evolved-Universal Terrestrial Radio Access Network (E-UTRAN) Node B (eNode B or eNB), a Radio Network Controller (RNC) in an E-UTRAN, and/or a next generation Node B (gNB)). The access node **104** may also include a base station, a Wireless Fidelity (WiFi) router, a modem, and/or other network gateway devices. The access nodes **104** can be configured to communicate with the mobile devices **102** according to one or more communication protocols or standards. Some examples of the communication protocols or standards can include: Global System for Mobile Communications (GSM), Internet Protocol (IP) Multimedia Subsystem (IMS), Time Division Multiple Access (TDMA), Universal Mobile Telecommunications System (UMTS), Evolution-Data Optimized (EVDO), Long Term Evolution (LTE), Generic Access Network (GAN), Unlicensed Mobile Access (UMA), Code Division Multiple Access (CDMA)

protocols (e.g., IS-95, IS-2000, and IS-856 protocols), Advanced LTE or LTE+, Orthogonal Frequency Division Multiple Access (OFDM), General Packet Radio Service (GPRS), Enhanced Data GSM Environment (EDGE), Advanced Mobile Phone System (AMPS), WiMAX protocols (e.g., IEEE 802.16e-2005 and IEEE 802.16m protocols), any of the various IEEE 802.11 standards, High Speed Packet Access (HSPA), (including High Speed Downlink Packet Access (HSDPA) and High Speed Uplink Packet Access (HSUPA)), Ultra Mobile Broadband (UMB), 5G NR (New Radio), and/or other communication technologies.

In general, the network **100** can include multiple cells, with each cell including one or more BSs (macro cell), 5G transceivers (including small cell devices), or a combination of both macro and small cells (HetNets), though many other cell types are possible, including cells having one or more femtocells, picocells, IEEE 802.11 access points (WiFi APs), and the like. Depending on the configuration and size, the network **100** can represent and serve various regional areas, for example, one or more rooms, one or more blocks, a city, a state, an entire nation, the whole world, etc. The network **100** may be operated by a service/network provider. End users may sign up as subscribers of the provider and one or more networks thereof.

The network **100** can include network nodes communicatively coupled to the access nodes **104**. The network nodes can be configured to process and/or route information to/from the mobile devices **102** to counterpart communication endpoints (e.g., service providers, content/service servers, and/or other end-user devices). The access nodes **104** can be communicatively coupled (e.g., using a backhaul connection) to backhaul equipment, for example, an operation support subsystem (OSS) server, a radio network controller (RNC), etc. Some examples of the network nodes can include a mobility management entity (MME), a serving gateway (SGW), and/or a package data network (PDN) gateway (PGW). The MME can be a control node for an access network. The MME can control an idle mode UE paging and tagging. The MME can select the serving gateway SGW for the mobile device **102**. The SGW can be a component configured to route and forward user data packets to/from the UEs (e.g., via the access node **104**). The SGW can function as a reference for a user plane during handovers for connecting a UE to a different connection node. The PGW can include network components configured to provide connectivity between the UEs and external packet data networks. In other words, the PGW can function as an exit/entry point of traffic for the UEs. Additionally or alternatively, the network nodes can include Network Functions (NFs).

The network **100** can include a core network **101** configured to function as a backbone portion of the network **100**. For example, the core network **101** can include components (e.g., a set of the network nodes) configured to implement wireless communications, such as cellular communication networks and/or wireless fidelity networks. The core network **101** can be connected to different parts of the network **100**, such as the Internet and/or telephone networks. Accordingly, the core network **101** can establish/facilitate communication sessions **118** for exchanging data between communication endpoints (e.g., end-user devices and/or service provider servers). The core network **101** can include an IP Multimedia Core Network Subsystem (IMS).

As an illustrative example, the core network **101** can include one or more core gateway nodes **106** (e.g., Proxy-Call Session Control Functions (P-CSCF)). The gateway nodes **106** can each include hardware (e.g., circuitry), soft-

ware, and/or firmware configured to function as a Session Initiation Protocol (SIP) proxy. The gateway nodes **106** can each include a Session Border Controller (SBC). The gateway node **106** can serve as a first point of contact for the core network **101**. Accordingly, the gateway node **106** can be configured to facilitate registration of the mobile device **102** for the core network **101**, such as for providing/allowing access to the core network **101**. Also, the gateway node **106** can facilitate termination of the communication session **118**, such as for hanging up voice calls.

The core network **101** can function at a layer above the radio access protocol used to link the mobile device **102** to the access node **104**. For example, the mobile device **102** to the access node **104** can communicate link quality measures **108** that describe a characteristic or a condition of the wireless communication, such as for signal transmission, reception, detection, decoding, etc. As examples, the link quality measure **108** can include a Channel Quality Indicator (CQI), a Channel State Information (CSI), a Received Signal Strength Indication (RSSI), a Reference Signal Received Power (RSRP), a Reference Signal Received Quality, and the like. The link quality measures **108** can be processed by the access node **104** to improve the wireless link between the access node **104** and the mobile device **102**, normally without providing the link quality measures **108** to the core network **101**. However, in some implementations of the present technology, the core network **101** can obtain the link quality measures **108** associated with certain targeted conditions, such as when the mobile device **102** detects mute events (e.g., absence of RTP packets).

Using the wireless link, the mobile device **102** and the network **100** (e.g., the core network **101**) can exchange core messages **110**. In other words, the payload communicated over the wireless link and through the access node **104** can include the core message **110** processed by the core network **101**. In some implementations, the core messages **110** can be formatted according to the SIP. For example, the core messages **110** can include a connection message **112** configured to request connection by the mobile device **102** to the core network **101**. The connection message **112** can correspond to an authentication request from the mobile device **102** for accessing the core network **101**. The connection message **112** can essentially establish the communication session **118**. With the communication session **118** established, the mobile device **102** and the core network **101** can exchange targeted/requested content, such as audio and/or visual data (e.g., web pages, images, texts, sound signals, streaming content, search results, etc.) using content packets **114**. In some implementations, the content packets **114** in the core messages **110** can include RTP packets. For voice communications (e.g., via Voice over Internet Protocol (VoIP), Voice over LTE (VoLTE) and/or Voice over IMS), the RTP packets can carry the audio signals used to recreate the sounds/voice on the receiving device. To end the communication session **118**, the core message **110** can include a termination-based message **116**. For example, the termination-based message **116** can include a SIP BYE message used to end a voice communication.

The communication sessions **118** can experience unintended content disruptions **122**. For voice communications, the content disruptions **122** can correspond to mute events when the content packets **114** are absent. For example, the content disruptions **122** can correspond to absence of the RTP packets. The content disruptions **122** can be separate or different from silences; the RTP packets can represent background noise or inserted values that correspond to silences. The content disruptions **122** can be caused by one or more

errors or failures at the access node **104** (e.g., degradation in the wireless link) and/or at one or more network nodes.

The mobile devices **102** can be configured to detect the content disruptions **122**. For example, the mobile device **102** can include an internal mechanism configured to detect absences in the RTP packets during voice calls. The mobile device **102** can include a media timer **124** configured to track a duration of the content disruption **122**. For example, the mobile device **102** can count/increment clock pulses while the RTP packets are not present in the core messages **110**. The mobile device **102** can be configured to autonomously initiate termination of the communication session **118** when the tracked duration of the content disruption **122** satisfies an autonomous termination threshold **126** (e.g., a predetermined duration, such as 5 seconds or greater). When the tracked duration of the mute event reaches the autonomous termination threshold **126**, the mobile device **102** can autonomously/automatically terminate the communication session **118** (e.g., send the termination-based message **116**, such as the SIP BYE message) without user input for the termination. The mobile device **102** can indicate the autonomous termination in the termination-based message **116**. For example, the mobile device **102** can generate and send an autonomous termination message **128** (e.g., a specific type of the termination-based message **116**) to terminate the communication session and to indicate the autonomous termination event and the corresponding mute event. In some implementations, the autonomous termination message **128** can be an instance of the termination-based message **116** with predetermined values/text in a header thereof.

The mobile device **102** can further include a disruption tracker **130** configured to track the content disruption **122** (e.g., the mute event) and/or determine associated information. For example, the disruption tracker **130** can include a circuit, a software module/routine, and the like configured to store the tracked duration(s) from the media timer **124** even when the duration(s) do not satisfy the autonomous termination threshold **126**. In some implementations, the disruption tracker **130** can have a stack/layer (e.g., an RTP stack) that tracks or processes the RTP periodically to provide information related to the mute event (e.g., the tracked value of the media timer **124**) to a reporting or a messaging stack/layer (e.g., an IMS stack). Also, the disruption tracker **130** can be configured to determine other related aspects of the content disruption **122**, such as by calculating/measuring a packet loss rate, a direction of the mute (e.g., whether the packets are absent in an uplink direction and/or a downlink direction), and the like. In some implementations, the disruption tracker **130** can be configured to obtain the link quality measures **108** at the time of the content disruption **122**.

The mobile device **102** (via, e.g., the disruption tracker **130** and/or the messaging stack/layer) can be configured to generate and send a disruption report **132** to the core network **101**. The mobile device **102** can generate and send the disruption report **132** when the content disruption **122** is detected during the communication session **118** and/or when the communication session **118** ends, such as according to the corresponding user input. The disruption report **132** can include the information determined by the disruption tracker **130**, such as an indication that the content disruption **122** occurred. The disruption report **132** can further include information associated with the content disruption **122**, such as a duration, a packet loss rate, a communication direction, the link quality measure **108**, or a combination thereof. In some implementations, the disruption report **132** can be included in the termination-based message **116** (e.g., the SIP

BYE message). For example, the disruption report **132** can be included as numbers, symbols, letters, and/or other characters included in a header portion of the disruption report **132**. Additionally or alternatively, the disruption report **132** can be included in a payload portion thereof and/or a dedicated bit slot thereof.

The network **100** (via, e.g., the core network **101**) can track and record details of the communications in a Call Detail Record (CDR) **120**. For example, the CDR **120** can include details for voice communications (e.g., telephone calls), such as originating party identifier (e.g., phone number), corresponding party identifier (e.g., call recipient phone number), starting/end time of the session, session duration, utilized nodes, routing path, etc. The CDR **120** may not include any information associated with the content disruption **122**.

Architecture

FIG. 2 illustrates a block diagram of an example mobile device (e.g., the mobile device **102**) in accordance with one or more implementations of the present technology. The mobile device **102** can include circuitry and/or software configured to implement a radio protocol stack **202**. The radio protocol stack **202** can be configured to receive and process the core message **110** of FIG. 1, such as the content packets **114** of FIG. 1. In some implementations, the radio protocol stack **202** can include the RTP layer configured to process the RTP packets.

The radio protocol stack **202** can include a disruption detector **212** (e.g., an internal circuit and/or software mechanism) configured to determine disruptions (e.g., absences) in the content packets **114**. For example, the disruption detector **212** can be configured to determine absences of the RTP packets during the communication session **118** of FIG. 1. The disruption detector **212** can be associated or integral with the media timer **124** of FIG. 1, the disruption tracker **130** of FIG. 1, or a combination thereof. For example, the disruption detector **212** can report the absence of the RTP packet(s) to the media timer **124** via an internal content report **214**, and the media timer **124** can track the duration of the corresponding mute event using the internal content report **214**. When the duration of the mute event satisfies the autonomous termination threshold **126**, the mobile device **102** can autonomously (e.g., without corresponding user input) terminate the communication session as described above.

The mobile device **102** can further include circuitry and/or software configured to implement a reporting stack **204**. The reporting stack **204** can be configured to provide and/or format content reported or sent to the communication network **100** of FIG. 1. For example, the reporting stack **204** can include the IMS stack or the SIP stack configured to generate and/or format the core messages **110** of FIG. 1 to the core network **101** of FIG. 1. Accordingly, the reporting stack **204** can be configured to generate and communicate termination-based message **116** of FIG. 1, the disruption report **132**, or a combination thereof.

As an illustrative example, the radio protocol stack **202** and/or the disruption detector **212** can be configured to provide the internal content report **214** to the reporting stack **204** according to a predetermined interval or frequency (e.g., once per a predetermined number of seconds/minute). The reporting stack **204** can identify a beginning of a mute event when the RTP packet is first reported as being absent during a session (e.g., subsequent to having received one or more RTP packets). The reporting stack **204** can track a duration of the mute event based on counting a number of subsequent sequential set of reports showing the absence of the RTP

packets. The reporting stack **204** can determine other related aspects of the content disruption **122**, such as a status **222**, a measure **224**, and/or a direction **226** associated with the mute event. For example, the reporting stack **204** can determine the status **222** to represent an ongoing or a detected mute event based on the absence of the RTP packet(s). Also, the reporting stack **204** can calculate the measure **224** as the duration and/or the packet loss rate. The packet loss rate can be calculated based on a number of mute events, lengths of the mute events, durations between the mute events, or a combination thereof, for the communication session. Further, the reporting stack **204** can interact with the disruption tracker **130** to determine the direction **226** of the mute (e.g., whether the packets are absent in an uplink direction and/or a downlink direction). Additionally or alternatively, the reporting stack **204** can interact with the disruption tracker **130** to obtain the link quality measures **108** at the time of the content disruption **122**. The reporting stack **204** can aggregate and track information regarding the mute events for each communication session.

When the status **222** and/or other tracked information for the communication session indicates the existence of at least one mute event, the reporting stack **204** can provide the disruption report **132** that includes information regarding the mute event(s). The reporting stack **204** can provide the disruption report **132** regardless of whether the communication session is terminated autonomously by the mobile device **102** or according to a termination input provided by the user. The reporting stack **204** can include the disruption report **132** having the status **222**, the measure **224**, the direction **226**, and/or other descriptions regarding the mute event(s) occurring during a communication session in the termination-based message (e.g., the SIP BYE message) for the corresponding session.

Reporting Format

FIG. 3 illustrates a block diagram of an example message (e.g., the core message **110** of FIG. 1, such as the termination-based message **116**) in accordance with one or more implementations of the present technology. The example message can include the disruption report **132** in one or more locations therein according to a corresponding format.

The core message **110** can include a header **302**, a payload **304**, and/or one or more slots **306** (e.g., bit locations) designated according to a predetermined format/standard. The header **302** can identify a type, a title, an identifier, and/or other general descriptions for the core message **110**. For example, the header **302** can include a predetermined text **312** that provides the type, the title, etc., describing the core message **110**. As an illustrative example, the predetermined text **312** can specify that the core message **110** is the termination-based message **116** and/or an indication that the corresponding session was terminated by the user. The payload **304** can include content information targeted for communication by the core message **110**. The slots **306** can be used to communicate information and/or values corresponding to the designated type or category of information.

The disruption report **132** can be included in the header **302**, the payload **304**, and/or the designated slots **306**. For example, the reporting stack **204** can include the mute-related information as a notifier **314** and/or a text report in the header **302**. The notifier **314** can include a predetermined set of characters that indicates the presence of the disruption report **132** within the termination-based message **116**. The corresponding text report can describe the status **222**, the measure **224**, the direction **226**, and/or other descriptions regarding the mute event(s). The core network **101** of FIG. 1 can search for the notifier **314** within the header **302** (e.g.,

with or without standardization) to identify the presence of the disruption report **132**. Upon detecting the notifier, the core network **101** can obtain and analyze the remaining text report to receive and determine the disruption report **132** or a portion thereof. Also, the reporting stack **204** can include the disruption report **132** in the payload **304** and/or corresponding predetermined slots **306** according to a predetermined content/format (e.g., according to standardized formats).

Control Flow

FIG. **4** is a flow diagram illustrating an example method **400** for tracking disruptions in accordance with one or more implementations of the present technology. The method **400** can be implemented using the communication network **100** of FIG. **1**, the core network **101** of FIG. **1**, and/or the mobile device **102** of FIG. **1**.

At block **402**, the mobile device **102** establishes a communication session based on interacting with the communication network **100**. For example, the mobile device **102** (e.g., the IMS layer) and the communication network **100** can interact with each other and execute a connection sequence for establishing a wireless radio link. Accordingly, the mobile device **102** can establish a wireless radio link with a radio access node **104** of FIG. **1** of the communication network **100**. Once the radio link is established, the mobile device **102** can interact with the core network **101** of FIG. **1** and execute an authentication sequence that includes sending one or more authenticated registration requests. The mobile device **102** can access the core network **101** based on the authenticated registration request.

Once the mobile device **102** is authenticated and registered for the core network **101**, the mobile device **102** can establish a communication session for exchanging data (e.g., sound data corresponding to voice communications) with one or more end point devices. The communication session can be facilitated by the core network **101**. To establish the communication session, the mobile device **102** and the core network **101** can exchange requests and responses associated with SIP INVITE. Accordingly, the mobile device **102** and the core network **101** can implement a voice-communication session for communicating voice data to a counterpart device over the wireless radio link and through the core network **101**.

At block **404**, the mobile device **102** and the communication network **100** exchange content during the communication session. For example, the mobile device **102**, the core network **101**, and the counterpart device can communicate voice data (via, e.g., RTP packets) for the voice-communication session. The radio protocol stack **202** of FIG. **2** can implement the content communication.

At block **422**, the mobile device **102** monitors content continuity while exchanging content. For example, as illustrated at block **424**, the radio protocol stack **202** and/or the disruption tracker **130** of FIG. **1** detects packet disruptions. The radio protocol stack **202** can detect any disruptions/discontinuities in the RTP packets.

At block **426**, the mobile device **102** tracks mute events based on the detected packet disruptions. For example, the radio protocol stack **202** can provide to the reporting stack **204** of FIG. **2** a status (e.g., the internal content report **214** of FIG. **2**) with information regarding the disruptions/discontinuities in the RTP packets. The reporting stack **204** can detect mute events based on the internal content report **214** during the voice-communication session. The reporting stack **204** can detect mute events in response to an initial detection of the RTP discontinuity. The reporting stack **204** can further derive/analyze information regarding the mute

events, such as a duration of the mute event, a packet drop rate during the voice-communication session, a mute direction (e.g., uplink/downlink), a radio condition indicator, etc., as described above.

As an illustrative example, the reporting stack **204** can receive the internal content report **214** according to a predetermined frequency. Accordingly, the reporting stack **204** can derive the disruption measure **224** of FIG. **2** based on calculating the mute duration using a number of sequentially (e.g., back to back) reported absences in the RTP packets and the corresponding durations/periods associated with the reporting frequency. Also, the reporting stack **204** can calculate the packet drop rate based on a total number of reported absences in the RTP packets in comparison to a total number of communicated packets and/or a total duration for the session. The reporting stack **204** can determine the mute direction based on details of the RTP packet detection included in the internal content report **214**. The reporting stack **204** can further determine the radio condition indicator representative of one or more conditions associated with a wireless link between the wireless communications device and the communication network during the voice-communication session. The reporting stack **204** can use the packet drop rate as the radio condition or quality indicator. Alternatively or additionally, the reporting stack **204** can interact with the baseband modem or a corresponding layer mechanism to access the link quality measures **108** of FIG. **1** (e.g., CQI, RSSI, RSRP, RSRQ, etc.) reported/obtained during the voice-communication session. The reporting stack **204** can use the link quality measures **108** to derive the radio condition indicator.

At decision block **406**, the mobile device **102** determines whether the mute duration exceeds a threshold (e.g., the autonomous termination threshold **126** of FIG. **1**). At block **408**, the mobile device **102** initiates autonomous termination when the mute duration exceeds the threshold. In other words, the mobile device **102** can terminate the voice-communication session without any corresponding user input.

Otherwise (e.g., when the mute duration is less than the threshold) at decision block **410**, the mobile device **102** determines whether the user terminated the communication session (via, e.g., a call hang up input). The mobile device **102** can continue to exchange the content without user input to terminate the voice-communication session.

At block **412**, the mobile device **102** terminates the communication session. The mobile device **102** can terminate according to the autonomous termination process and/or the user input. As part of the termination process, the mobile device **102** generates a termination message (e.g., the termination-based message **116** of FIG. **1**) as illustrated at block **432**. For example, the mobile device **102** can generate an SIP BYE message in terminating the communication session.

At block **434**, the mobile device **102** generates a disruption report (e.g., the disruption report **132** of FIG. **1**). For example, the reporting stack **204** can generate the disruption report **132** (e.g., the mute report) based on the detected mute event(s) for providing information regarding the mute event(s) to a network component (e.g., the IMS component) in the communication network **100**. The reporting stack **204** can generate the disruption report **132**, including various aspects of the mute event(s), such as the indication, the duration, the direction, the rate, etc., of the mute event(s). Also, the reporting stack **204** can include the radio condition indicator for the mute event(s) in the disruption report **132**, as well as

11

other useful data (if available), such as location, timestamp, radio type, wireless protocol, and/or mobile/base station ID.

The reporting stack **204** can generate the disruption report **132** according to a predetermined format and/or standard. For example, the reporting stack **204** can generate the SIP BYE message with the disruption report **132** included in the payload **304** of FIG. 3 and/or the designated slot **306** of FIG. 3 for the disruption report **132**. Alternatively or additionally, the reporting stack **204** can generate the SIP BYE message with the disruption report **132** included in the header **302** of FIG. 3. The reporting stack **204** can include the notifier **314** of FIG. 3 to indicate the presence of the disruption report **132**, such as for a user-prompted termination. The reporting stack **204** can include the disruption report **132** using predetermined characters and/or sequences thereof (e.g., a text string) in the header **302** after the notifier **314**. The disruption report **132** can be separate from a CDR associated with the call and separate from the link quality measures **108** associated with the wireless connection management.

At block **436**, the mobile device **102** sends the termination message (e.g., the termination-based message **116**, such as the SIP BYE) to the core network **101**. The mobile device **102** can send the termination message and the disruption report **132** therein via the reporting stack **204** to the communication network **100**. Accordingly, the mobile device **102** can notify the communication network **100** of the mute event(s) when the voice-communication session is terminated in response to the user input and before satisfying the autonomous termination threshold **126** predetermined for the mobile device **102**.

At block **452**, the communication network **100** receives/aggregates the termination message (e.g., the termination-based message **116**, such as the SIP BYE) from multiple mobile devices. Accordingly, the communication network **100** can obtain and aggregate the disruption reports **132** representative of mute events across multiple mobile devices and/or multiple voice-communication sessions.

At block **454**, the communication network **100** analyzes the termination messages from the multiple devices. In other words, the communication network **100** can analyze the crowd-sourced data regarding the mute events across the multiple mobile devices and/or the multiple voice-communication sessions. For example, the communication network **100** can extract the disruption reports **132** and/or components thereof from the termination-based messages **116** based on a predetermined format that designates values and/or bit locations within the session-end message for the mute report. The communication network **100** can analyze the extracted disruption reports **132** and/or components thereof to determine estimated causes, such as patterns associated with a design (as represented by, e.g., a manufacture brand/model) of the mobile device, a type of the mobile device (e.g., a smart phone, a wearable device, an IoT device, etc.), a geographical location, a network condition, or a combination thereof, associated with the set of obtained mute reports. The communication network **100** can utilize a machine learning mechanism, a pattern-recognition mechanism, and/or other artificial-intelligence mechanism to derive patterns, clusters, models, etc., from the mute event status, the duration, the direction, the radio condition indicator, a corresponding delimiter, a geographic location associated thereto, or a combination thereof.

At block **456**, the communication network **100** recommends or takes remedial measures. For example, the communication network **100** can update, adjust, add, and/or remove network functions/components according to the detected issues or make recommendations to take such

12

measures. Alternatively or additionally, the communication network **100** can implement the remedial measures using procedural changes and/or software adjustments.

As described above, the disruption report **132** provides information regarding the mute event(s) even when the communication session is terminated by the user. The communication network **100** can use the provided information to determine any issues and corresponding improvements as described above. Thus, the communication network **100** can obtain increased amount of mute-related data and improve the connectivity and the quality of subsequent communications. Further, the disruption report **132** can be implemented as text strings and/or the notifier **314** within the header **302**, thereby allowing the communication network **100** and the mobile devices to communicate the disruption reports **132** even without standardized format/protocol.

Computer

FIG. 5 is a diagrammatic representation of a machine in the example form of a computer system **500**, within which a set of instructions for causing the machine to perform any one or more of the methodologies or modules discussed herein, can be executed.

In the example of FIG. 5, the computer system **500** includes a processor **502**, a memory **506**, a drive unit **520** (e.g., a machine-readable storage medium, such as a non-volatile memory), and an interface device **510**. Various common components (e.g., cache memory) are omitted for illustrative simplicity. The computer system **500** is intended to illustrate a hardware device on which any of the components described in the example of FIGS. 1-4 (and any other components described in this specification) can be implemented. The computer system **500** can be of any applicable known or convenient type. The components of the computer system **500** can be coupled together via a bus or through some other known or convenient device.

This disclosure contemplates the computer system **500** taking any suitable physical form. As an example, and not by way of limitation, computer system **500** can be an embedded computer system, a system-on-chip (SOC), a single-board computer system (SBC) (such as, e.g., a computer-on-module (COM) or system-on-module (SOM)), a desktop computer system, a laptop or notebook computer system, an interactive kiosk, a mainframe, a mesh of computer systems, a mobile telephone, a personal digital assistant (PDA), a server, or a combination of two or more of these. Where appropriate, computer system **500** can include one or more computer systems **500**; be unitary or distributed; span multiple locations; span multiple machines; or reside in a cloud, which can include one or more cloud components in one or more networks. Where appropriate, one or more computer systems **500** can perform without substantial spatial or temporal limitation one or more steps of one or more methods described or illustrated herein. As an example, and not by way of limitation, one or more computer systems **500** can perform in real time or in batch mode one or more steps of one or more methods described or illustrated herein. One or more computer systems **500** can perform at different times or at different locations one or more steps of one or more methods described or illustrated herein, where appropriate.

The processor **502** can be, for example, a conventional microprocessor, such as an Intel Pentium microprocessor or Motorola power PC microprocessor. One of skill in the relevant art will recognize that the terms “machine-readable (storage) medium” or “computer-readable (storage) medium” include any type of device that is accessible by the processor **502**.

13

The memory 506 is coupled to the processor by, for example, a bus 524. The memory 506 can include, by way of example but not limitation, random access memory (RAM), such as dynamic RAM (DRAM) and static RAM (SRAM). The memory 506 can be local, remote, or distributed.

The bus 524 also couples the processor 502 to the drive unit 520. The drive unit 520 can include a non-volatile memory that is often a magnetic floppy or hard disk, a magnetic-optical disk, an optical disk, a read-only memory (ROM), such as a CD-ROM, EPROM, or EEPROM, a magnetic or optical card, or another form of storage for large amounts of data. Some of this data is often written, by a direct memory access process, into memory during execution of software in the computer 500. The non-volatile storage can be local, remote, or distributed. The non-volatile memory is optional because systems can be created with all applicable data available in memory. A typical computer system will usually include at least a processor, memory, and a device (e.g., a bus) coupling the memory to the processor.

Software is typically stored in the drive unit 520. It should be understood that for software to run, if necessary, it is moved to a computer readable location appropriate for processing, and for illustrative purposes, that location is referred to as the memory in this paper. Even when software is moved to the memory for execution, the processor will typically make use of hardware registers to store values associated with the software, and local cache that, ideally, serves to speed up execution. As used herein, a software program is assumed to be stored at any known or convenient location (from non-volatile storage to hardware registers) when the software program is referred to as “implemented in a computer-readable medium.” A processor is considered to be “configured to execute a program” when at least one value associated with the program is stored in a register readable by the processor.

The bus 524 also couples the processor 502 to the network interface device 510. The network interface device 510 can include one or more of a modem or network interface. It will be appreciated that a modem or network interface can be considered to be part of the computer system 500. The network interface device 510 can include an analog modem, ISDN modem, cable modem, token ring interface, satellite transmission interface (e.g., “direct PC”), or other interfaces for coupling a computer system to other computer systems.

The system 500 can include one or more input and/or output devices, such as a video display 514 and/or an alpha-numeric input device 516. The I/O devices can include, by way of example but not limitation, a keyboard, a mouse or other pointing device, disk drives, printers, a scanner, and other input and/or output devices, including a display device. The video display 514 can include, by way of example but not limitation, a cathode ray tube (CRT), liquid crystal display (LCD), or some other applicable known or convenient display device. For simplicity, it is assumed that controllers of any devices not depicted in the example of FIG. 5 reside in the interface.

In operation, the computer system 500 can be controlled by operating system software that includes a file management system, such as a disk operating system. One example of operating system software with associated file management system software is the family of operating systems known as Windows® from Microsoft Corporation of Redmond, Washington, and their associated file management systems. Another example of operating system software with its associated file management system software is the Linux™ operating system and its associated file manage-

14

ment system. The file management system is typically stored in the non-volatile memory and/or drive unit and causes the processor to execute the various acts required by the operating system to input and output data and to store data in the memory, including storing files on the non-volatile memory and/or drive unit.

Some portions of the detailed description can be presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of operations leading to a desired result. The operations are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or “generating” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission, or display devices.

The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general purpose systems can be used with programs in accordance with the teachings herein, or it can prove convenient to construct more specialized apparatus to perform the methods of some implementations. The required structure for a variety of these systems will appear from the description below. In addition, the techniques are not described with reference to any particular programming language, and various implementations can thus be implemented using a variety of programming languages.

In alternative implementations, the machine operates as a standalone device or can be connected (e.g., networked) to other machines. In a networked deployment, the machine can operate in the capacity of a server or a client machine in a client-server network environment, or as a peer machine in a peer-to-peer (or distributed) network environment.

The machine can be a server computer, a client computer, a personal computer (PC), a tablet PC, a laptop computer, a set-top box (STB), a personal digital assistant (PDA), a cellular telephone, an iPhone, a Blackberry, a processor, a telephone, a web appliance, a network router, switch, or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine.

While the machine-readable medium or machine-readable storage medium is shown in an exemplary embodiment to be a single medium, the term “machine-readable medium” and “machine-readable storage medium” should be taken to include a single medium or multiple media (e.g., a central-

15

ized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term “machine-readable medium” and “machine-readable storage medium” shall also be taken to include any medium that is capable of storing, encoding, or carrying a set of instructions for execution by the machine and that cause the machine to perform any one or more of the methodologies or modules of the presently disclosed technique and innovation.

In general, the routines executed for the implementations, can be implemented as part of an operating system or a specific application, component, program, object, module, or sequence of instructions referred to as “computer programs.” The computer programs typically comprise one or more instructions set at various times in various memory and storage devices in a computer, and that, when read and executed by one or more processing units or processors in a computer, cause the computer to perform operations to execute elements involving the various aspects of the disclosure.

Moreover, while implementations have been described in the context of fully functioning computers and computer systems, those skilled in the art will appreciate that the various implementations are capable of being distributed as a program product in a variety of forms, and that the disclosure applies equally regardless of the particular type of machine or computer-readable media used to actually effect the distribution.

Further examples of machine-readable storage media, machine-readable media, or computer-readable (storage) media include, but are not limited to, recordable type media, such as volatile and non-volatile memory devices, floppy and other removable disks, hard disk drives, optical disks (e.g., Compact Disk Read-Only Memory (CD-ROMS), Digital Versatile Disks, (DVDs), etc.), among others, and transmission type media, such as digital and analog communication links.

In some circumstances, operation of a memory device, such as a change in state from a binary one to a binary zero or vice versa, for example, can comprise a transformation, such as a physical transformation. With particular types of memory devices, such a physical transformation can comprise a physical transformation of an article to a different state or thing. For example, but without limitation, for some types of memory devices, a change in state can involve an accumulation and storage of charge or a release of stored charge. Likewise, in other memory devices, a change of state can comprise a physical change or transformation in magnetic orientation or a physical change or transformation in molecular structure, such as from crystalline to amorphous or vice versa. The foregoing is not intended to be an exhaustive list in which a change in state for a binary one to a binary zero or vice-versa in a memory device can comprise a transformation, such as a physical transformation. Rather, the foregoing is intended as illustrative examples.

A storage medium typically can be non-transitory or comprise a non-transitory device. In this context, a non-transitory storage medium can include a device that is tangible, meaning that the device has a concrete physical form, although the device can change its physical state. Thus, for example, non-transitory refers to a device remaining tangible despite this change in state.

Remarks

Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise,” “comprising,” and the like, are to be construed in an inclusive sense, as opposed to an exclusive or exhaustive sense; that

16

is to say, in the sense of “including, but not limited to.” As used herein, the terms “connected,” “coupled,” or any variant thereof means any connection or coupling, either direct or indirect, between two or more elements; the coupling or connection between the elements can be physical, logical, or a combination thereof. Additionally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, refer to this application as a whole and not to any particular portions of this application. Where the context permits, words in the above Detailed Description using the singular or plural number may also include the plural or singular number, respectively. The word “or,” in reference to a list of two or more items, covers all of the following interpretations of the word: any of the items in the list, all of the items in the list, and any combination of the items in the list.

The above Detailed Description of examples of the invention is not intended to be exhaustive or to limit the invention to the precise form disclosed above. While specific examples for the invention are described above for illustrative purposes, various equivalent modifications are possible within the scope of the invention, as those skilled in the relevant art will recognize. For example, while processes or blocks are presented in a given order, alternative implementations may perform routines having steps, or employ systems having blocks, in a different order, and some processes or blocks may be deleted, moved, added, subdivided, combined, and/or modified to provide alternative or sub-combinations. Each of these processes or blocks may be implemented in a variety of different ways. Also, while processes or blocks are at times shown as being performed in series, these processes or blocks may instead be performed or implemented in parallel, or may be performed at different times. Further any specific numbers noted herein are only examples: alternative implementations may employ differing values or ranges.

The teachings of the invention provided herein can be applied to other systems, not necessarily the system described above. The elements and acts of the various examples described above can be combined to provide further implementations of the invention. Some alternative implementations of the invention may include not only additional elements to those implementations noted above, but also may include fewer elements.

Any patents and applications and other references noted above, and any that may be listed in accompanying filing papers, are incorporated herein by reference in the entirety, except for any subject matter disclaimers or disavowals, and except to the extent that the incorporated material is inconsistent with the express disclosure herein, in which case the language in this disclosure controls. Aspects of the invention can be modified to employ the systems, functions, and concepts of the various references described above to provide yet further implementations of the invention.

These and other changes can be made to the invention in light of the above Detailed Description. While the above description describes certain examples of the invention, and describes the best mode contemplated, no matter how detailed the above appears in text, the invention can be practiced in many ways. Details of the system may vary considerably in its specific implementation, while still being encompassed by the invention disclosed herein. As noted above, particular terminology used when describing certain features or aspects of the invention should not be taken to imply that the terminology is being redefined herein to be restricted to any specific characteristics, features, or aspects of the invention with which that terminology is associated. In general, the terms used in the following claims should not

17

be construed to limit the invention to the specific examples disclosed in the specification, unless the above Detailed Description section explicitly defines such terms. Accordingly, the actual scope of the invention encompasses not only the disclosed examples, but also all equivalent ways of practicing or implementing the invention under the claims. 5

To reduce the number of claims, certain aspects of the invention are presented below in certain claim forms, but the applicant contemplates the various aspects of the invention in any number of claim forms. For example, while only one aspect of the invention is recited as a means-plus-function claim under 35 U.S.C. § 112(f), other aspects may likewise be embodied as a means-plus-function claim, or in other forms, such as being embodied in a computer-readable medium. (Any claims intended to be treated under 35 U.S.C. § 112(f) will begin with the words “means for,” but use of the term “for” in any other context is not intended to invoke treatment under 35 U.S.C. § 112(f).) Accordingly, the applicant reserves the right to pursue additional claims after filing this application to pursue such additional claim forms, in either this application or in a continuing application. 15 20

We claim:

1. A wireless communications system comprising:
 - an access device configured to provide a wireless link between the wireless communications system and a mobile device; and
 - an Internet Protocol (IP) Multimedia Core Network Subsystem (IMS) network coupled to the access device, the IMS network including one or more network components configured to:
 - implement a voice-communication session for communicating voice data between the mobile device and at least one end-point device;
 - receive a session-end message, including a mute report, wherein the session-end message is for signaling an end of the voice-communication session according to an input from a user of the mobile device;
 - determine, at the mobile device, a packet drop rate using a total number of reported absences in packets during the voice-communication session and a total number of communicated packets or a total session duration;
 - generate, at the mobile device, a radio condition indicator that represents one or more conditions associated with the wireless link during the voice-communication session, wherein the radio condition indicator includes the determined packet drop rate;
 - determine a mute report based on the session-end message, wherein the mute report represents a mute event detected by the mobile device during the voice-communication session, and wherein the mute report includes, for the mute event, the radio condition indicator and at least two of:
 - a duration of the mute event,
 - a direction of the mute event,
 - a geographic location associated with of the mute event, or
 - a time of the mute event, and
 - wherein the mute report is determined according to a predetermined format that designates values and/or bit locations within the session-end message for the mute report.
2. The wireless communications system of claim 1, further comprising a network analyzer coupled to or included in the IMS network, the network analyzer configured to: 65

18

crowd-sourcing a set of mute reports representative of mute events across a set of corresponding voice-communication sessions,

wherein the set of mute reports includes the determined mute report; and

identifying an estimated cause associated with the determined mute report based on analyzing the set of mute reports,

wherein the estimated cause represents a geographic location, the access device, a manufacturer, or a device type corresponding to the mobile device, a network condition, or a combination thereof associated with the set of mute reports.

3. The wireless communications system of claim 1, wherein the mute report represents the mute event occurring at a beginning portion of the voice-communication session and/or occurring intermittently during the voice-communication session.

4. The wireless communications system of claim 1, wherein the mute report is determined based on parsing a text header to identify one or more text strings that represent a mute event status, a duration, a direction, a radio condition indicator, a corresponding delimiter, or a combination thereof.

5. The wireless communications system of claim 1, wherein the mute report is separate from a Call Detail Record (CDR) and a link quality data configured to describe the wireless radio link to the access device.

6. An apparatus for use in a wireless communications system, the apparatus comprising:

at least one hardware data processor, wherein the at least one hardware processor is coupled to an Internet Protocol (IP) Multimedia Core Network Subsystem (IMS) network, and

wherein the IMS network is coupled to an access device configured to provide a wireless link with a mobile device; and

at least one memory device coupled to the at least one hardware data processor and storing instructions, which when executed by the at least one hardware data processor performs operations to:

implement a voice-communication session for communicating voice data between the mobile device and at least one end-point device;

receive a session-end message, wherein the session-end message is for signaling an end of the voice-communication session according to an input from a user of the mobile device;

determine, at the mobile device, a packet drop rate using a total number of reported absences in packets during the voice-communication session and a total number of communicated packets or a total session duration;

generate, at the mobile device, a radio condition indicator that represents one or more conditions associated with the wireless link, wherein the radio condition indicator includes the determined packet drop rate;

determine a mute report based on the session-end message, wherein the mute report represents a mute event detected by the mobile device during the voice-communication session, and

wherein the mute report includes, for the mute event, the radio condition indicator and at least one of: a duration of the mute event, a direction of the mute event,

19

a geographic location associated with of the mute event, or
 a time of the mute event, and
 wherein the mute report is determined according to a predetermined format that designates values and/or bit locations within the session-end message for the mute report.

7. The apparatus of claim 6, further comprising a network analyzer coupled to the at least one hardware data processor, the network analyzer configured to:

crowd-sourcing a set of mute reports representative of mute events across a set of corresponding voice-communication sessions,

wherein the set of mute reports includes the determined mute report; and

identifying an estimated cause associated with the determined mute report based on analyzing the set of mute reports,

wherein the estimated cause represents the geographic location, the access device, a manufacturer, or a device type corresponding to the mobile device, a network condition, or a combination thereof associated with the set of mute reports.

8. The apparatus of claim 6, wherein the mute report represents the mute event occurring at a beginning portion of the voice-communication session and/or occurring intermittently during the voice-communication session.

9. The apparatus of claim 6, wherein the mute report is determined based on parsing a text header to identify one or more text strings that represent a mute event status, the duration, the direction, a radio condition indicator, a corresponding delimiter, or a combination thereof.

10. The apparatus of claim 6, wherein the mute report is determined according to a predetermined format that designates values and/or bit locations within the session-end message for the mute report.

11. The apparatus of claim 6, wherein the IMS network is further configured to determine a radio condition indicator representative of one or more conditions associated with a wireless link between the wireless device and the access device during the voice-communication session, wherein the mute report includes the radio condition indicator for the mute event.

12. The apparatus of claim 6 wherein the mute report is separate from a Call Detail Record (CDR) and a link quality data configured to describe the wireless link to the access device.

13. A method comprising:

implementing a voice-communication session for communicating voice data between a mobile device and at least one end-point device;

receiving a session-end message, including a mute report, wherein the session-end message is for signaling an end of the voice-communication session according to an input from a user of the mobile device;

20

determining, at the mobile device, a packet drop rate using a total number of reported absences in packets during the voice-communication session and a total number of communicated packets or a total session duration;

generating, at the mobile device, a radio condition indicator that represents one or more conditions associated with a wireless radio link during the voice-communication session,

wherein the radio condition indicator includes the determined packet drop rate;

determining the mute report based on the session-end message, wherein the mute report represents a mute event detected by the mobile device during the voice-communication session, and

wherein the mute report includes, for the mute event, the radio condition indicator and at least two of:

a duration of the mute event,

a direction of the mute event,

a geographic location associated with of the mute event, or

a time of the mute event, and

wherein the mute report is determined according to a predetermined format that designates values and/or bit locations within the session-end message for the mute report.

14. The method of claim 13, further comprising:

crowd-sourcing a set of mute reports representative of mute events across a set of corresponding voice-communication sessions,

wherein the set of mute reports includes the determined mute report; and

identifying an estimated cause associated with the determined mute report based on analyzing the set of mute reports,

wherein the estimated cause represents a geographic location, an access device, a manufacturer, or a device type corresponding to the mobile device, a network condition, or a combination thereof associated with the set of mute reports.

15. The method of claim 13, wherein the mute report represents the mute event occurring at a beginning portion of the voice-communication session and/or occurring intermittently during the voice-communication session.

16. The method of claim 13, wherein the mute report is determined based on parsing a text header to identify one or more text strings that represent a mute event status, a duration, a direction, a radio condition indicator, a corresponding delimiter, or a combination thereof.

17. The method of claim 13, wherein the mute report is separate from a Call Detail Record (CDR) and a link quality data configured to describe the wireless radio link to an access device.

* * * * *