

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12418813
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Bai; Tianyang et al.

Unified transmission configuration indicator state indication for cross-link interference measurement

Abstract

Methods, systems, and devices for wireless communications are described. A user equipment (UE) may receive control signaling (e.g., from a network entity) indicating a CLI measurement resource and an associated transmission configuration indicator (TCI) state. The UE may generate and transmit a CLI report to the network entity using the CLI measurement resource and the beam associated with the indicated TCI state. In some cases, the control signaling may indicate to use the same TCI state as another dedicated downlink channel configured for the UE. In some cases, the control signaling may indicate a unified TCI state to apply for the CLI measurement. In some cases, a UE may be configured to communicate with multiple transmission and reception points (TRPs). The TCI state to apply to the CLI measurement may be based on the TRP scheduling the CLI measurement.

Inventors: Bai; Tianyang (Somerville, NJ), Zhou; Yan (San Diego, CA), Zhang; Qian (Basking Ridge, NJ), Li; Junyi (Fairless Hills, PA), Luo; Tao (San Diego, CA)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 1000008821177

Appl. No.: 17/715655

Filed: April 07, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230328557 A1	Oct. 12, 2023

Publication Classification

Int. Cl.: H04W24/08 (20090101); H04W72/23 (20230101)

U.S. Cl.:

CPC **H04W24/08** (20130101); **H04W72/23** (20230101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0250797	12/2020	Karjalainen	N/A	H04L 1/0026
2021/0258964	12/2020	Khoshnevisan et al.	N/A	N/A
2021/0328692	12/2020	Zhang et al.	N/A	N/A
2022/0086843	12/2021	Ying et al.	N/A	N/A
2023/0100135	12/2022	Liu	370/252	H04B 7/0695
2023/0327787	12/2022	Bai et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2021248397	12/2020	WO	N/A
WO-2022147755	12/2021	WO	H04B 7/0456
WO-2023055264	12/2022	WO	N/A

OTHER PUBLICATIONS

Partial International Search Report—PCT/US2023/015694—ISA/EPO—Jun. 15, 2023 (2202519WO). cited by applicant
International Search Report and Written Opinion—PCT/US2023/015694—ISA/EPO—Sep. 4, 2023 (2202519WO). cited by applicant

Primary Examiner: Anwar; Mohammad S

Background/Summary

FIELD OF TECHNOLOGY

(1) The following relates to wireless communications, including unified transmission configuration indicator state indication for cross-link interference measurement.

BACKGROUND

(2) Wireless communications systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. These systems may be capable of supporting communication with multiple users by sharing the available

system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include fourth generation (4G) systems such as Long Term Evolution (LTE) systems, LTE-Advanced (LTE-A) systems, or LTE-A Pro systems, and fifth generation (5G) systems which may be referred to as New Radio (NR) systems. These systems may employ technologies such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal FDMA (OFDMA), or discrete Fourier transform spread orthogonal frequency division multiplexing (DFT-S-OFDM). A wireless multiple-access communications system may include one or more base stations, each supporting wireless communication for communication devices, which may be known as user equipment (UE).

SUMMARY

(3) The described techniques relate to improved methods, systems, devices, and apparatuses that support unified transmission configuration indicator state indication for cross-link interference (CLI) measurement. For example, the described techniques provide for indicating a specific transmission configuration indicator (TCI) state associated with a CLI measurement. A user equipment (UE) may receive control signaling (e.g., from a network entity) indicating a CLI measurement resource and an associated TCI state. The UE may generate and transmit a CLI report to the network entity using the CLI measurement resource and the receive beam associated with the indicated TCI state. In some cases, the control signaling may indicate to use the same TCI state as another dedicated downlink channel configured for the UE, for example a physical downlink control channel or a physical downlink shared channel. In some cases, the control signaling may indicate a unified TCI state for the CLI measurement. In some cases, a UE may be configured to communicate with multiple transmission and reception points (TRPs), which may be each be associated with a respective control resource set (CORESET) pool. The UE may receive one or more control messages indicating an association between each CORESET pool and a respective TCI state. When a TRP schedules a CLI measurement for a UE, the UE may apply the beam associated with the TCI state associated with the CORESET pool associated with the scheduling TRP to the scheduled CLI measurement.

(4) A method for wireless communications at a user equipment (UE) is described. The method may include receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource, generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state, and transmitting, to the network entity, a message indicating the CLI measurement.

(5) An apparatus for wireless communications at a UE is described. The apparatus may include a processor, memory coupled with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to receive, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource, generate a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state, and transmit, to the network entity, a message indicating the CLI measurement.

(6) Another apparatus for wireless communications at a UE is described. The apparatus may include means for receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource, means for generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state, and means for transmitting, to the network entity, a message indicating the CLI measurement.

(7) A non-transitory computer-readable medium storing code for wireless communications at a UE is described. The code may include instructions executable by a processor to receive, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource, generate a CLI measurement of

the CLI measurement resource using a receive beam associated with the TCI state, and transmit, to the network entity, a message indicating the CLI measurement.

(8) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, receiving the control signaling may include operations, features, means, or instructions for receiving an indication that the TCI state may be associated with a downlink channel for the UE.

(9) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, receiving the indication that the TCI state may be associated with the downlink channel for the UE may include operations, features, means, or instructions for receiving an indication of a unified TCI state.

(10) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving a downlink control information message indicating the TCI state.

(11) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving a control message indicating a set of TCI states associated with a set of CORESET pools, where each CORESET pool of the set of CORESET pools corresponds to one or more CORESETs and receiving, with the control signaling, an indication of a CORESET pool of the set of CORESET pools, where the TCI state may be based on the indication of the CORESET pool.

(12) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, receiving the indication of the CORESET pool of the set of CORESET pools may include operations, features, means, or instructions for receiving the control signaling from a TRP associated with the CORESET pool, where each CORESET pool of the set of CORESET pools may be associated with a respective TRP.

(13) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, receiving the control signaling may include operations, features, means, or instructions for receiving a first control message indicating the CLI measurement resource and a first CORESET pool of the set of CORESET pools, receiving a second control message indicating the CLI measurement resource and a second CORESET pool of the set of CORESET pools; and may further include operations, features, means, or instructions for generating a first CLI measurement of the CLI measurement resource using a first receive beam associated with a first TCI state associated with the first CORESET pool and generating a second CLI measurement of the CLI measurement resource using a second receive beam associated with a second TCI state associated with the second CORESET pool, where the message indicates the first CLI measurement and the second CLI measurement.

(14) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving a control message indicating a second TCI state associated with a set of CLI measurement resources including the CLI measurement resource, where the CLI measurement resource includes an aperiodic or a semi-periodic CLI measurement resource and receiving, with the control signaling, an indication to overwrite the second TCI state with the TCI state for the CLI measurement resource.

(15) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, receiving the control signaling may include operations, features, means, or instructions for receiving a radio resource control message configuring the CLI measurement resource and the TCI state, where the CLI measurement resource includes a periodic CLI measurement resource.

(16) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the CLI measurement resource includes a layer one sounding reference signal resource or a layer one received signal strength indicator resource.

- (17) A method is described. The method may include transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource and receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.
- (18) An apparatus is described. The apparatus may include a processor, memory coupled with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to transmit, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource and receive, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.
- (19) Another apparatus is described. The apparatus may include means for transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource and means for receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.
- (20) A non-transitory computer-readable medium storing code is described. The code may include instructions executable by a processor to transmit, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource and receive, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.
- (21) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the control signaling may include operations, features, means, or instructions for transmitting an indication that the TCI state may be associated with a downlink channel for the UE.
- (22) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the indication that the TCI state may be associated with the downlink channel for the UE may include operations, features, means, or instructions for transmitting an indication of a unified TCI state.
- (23) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the UE, a downlink control information message indicating the TCI state.
- (24) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the UE, a control message indicating a set of TCI states associated with a set of CORESET pools, where each CORESET pool of the set of CORESET pools corresponds to one or more CORESETs and transmitting, with the control signaling, an indication of a CORESET pool of the set of CORESET pools, where the TCI state may be based on the indication of the CORESET pool.
- (25) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the indication of the CORESET pool of the set of CORESET pools may include operations, features, means, or instructions for transmitting the control signaling from a TRP associated with the CORESET pool, where each CORESET pool of the set of CORESET pools may be associated with a respective TRP.
- (26) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the indication of the CORESET pool of the set of CORESET pools may include operations, features, means, or instructions for transmitting a first control message indicating the CLI measurement resource and a first CORESET pool of the set of CORESET pools and transmitting a second control message indicating the CLI measurement resource and a second CORESET pool of the set of CORESET pools, where the message indicates a first CLI measurement measured at the UE using a first beam associated with a first TCI state associated with the first CORESET pool and a second CLI measurement measured at the UE using a second

beam associated with a second TCI state associated with the second CORESET pool.

(27) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for transmitting, to the UE, a control message indicating a second TCI state associated with a set of CLI measurement resources including the CLI measurement resource, where the CLI measurement resource includes an aperiodic or a semi-periodic CLI measurement resource and transmitting, with the control signaling, an indication to overwrite the second TCI state with the TCI state for the CLI measurement resource.

(28) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, transmitting the control signaling may include operations, features, means, or instructions for transmitting a radio resource control message configuring the CLI measurement resource and the TCI state, where the CLI measurement resource includes a periodic CLI measurement resource.

(29) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the CLI measurement resource includes a layer one sounding reference signal resource and a layer one received signal strength indicator resource.

(30) The foregoing has outlined rather broadly the features and technical advantages of examples according to the disclosure in order that the detailed description that follows may be better understood. Additional features and advantages will be described hereinafter. The conception and specific examples disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present disclosure. Such equivalent constructions do not depart from the scope of the appended claims. Characteristics of the concepts disclosed herein, both their organization and method of operation, together with associated advantages will be better understood from the following description when considered in connection with the accompanying figures. Each of the figures is provided for the purposes of illustration and description, and not as a definition of the limits of the claims.

(31) While aspects and embodiments are described in this application by illustration to some examples, those skilled in the art will understand that additional implementations and use cases may come about in many different arrangements and scenarios. Innovations described herein may be implemented across many differing platform types, devices, systems, shapes, sizes, packaging arrangements. For example, embodiments and/or uses may come about via integrated chip embodiments and other non-module-component based devices (e.g., end-user devices, vehicles, communication devices, computing devices, industrial equipment, retail/purchasing devices, medical devices, artificial intelligence (AI)-enabled devices, etc.). While some examples may or may not be specifically directed to use cases or applications, a wide assortment of applicability of described innovations may occur. Implementations may range in spectrum from chip-level or modular components to non-modular, non-chip-level implementations and further to aggregate, distributed, or original equipment manufacturer (OEM) devices or systems incorporating one or more aspects of the described innovations. In some practical settings, devices incorporating described aspects and features may also necessarily include additional components and features for implementation and practice of claimed and described embodiments. For example, transmission and reception of wireless signals necessarily includes a number of components for analog and digital purposes (e.g., hardware components including antenna, radio frequency (RF)-chains, power amplifiers, modulators, buffer, processor(s), interleaver, adders/summers, etc.). It is intended that innovations described herein may be practiced in a wide variety of devices, chip-level components, systems, distributed arrangements, end-user devices, etc. of varying sizes, shapes, and constitution.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates an example of a wireless communications system that supports unified transmission configuration indicator (TCI) state indication for cross-link interference (CLI) measurement in accordance with one or more aspects of the present disclosure.
- (2) FIG. 2 illustrates an example of a wireless communications system that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (3) FIG. 3 illustrates an example of a process flow that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (4) FIGS. 4 and 5 show block diagrams of devices that support unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (5) FIG. 6 shows a block diagram of a communications manager that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (6) FIG. 7 shows a diagram of a system including a device that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (7) FIGS. 8 and 9 show block diagrams of devices that support unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (8) FIG. 10 shows a block diagram of a communications manager that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (9) FIG. 11 shows a diagram of a system including a device that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.
- (10) FIGS. 12 through 17 show flowcharts illustrating methods that support unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure.

DETAILED DESCRIPTION

(11) A user equipment (UE) may experience cross-link interference (CLI) attributable to signals transmitted by other UEs. For example, a “victim” UE may experience CLI from signals transmitted by an “aggressor” UE in cases where downlink resources of the victim UE overlap with uplink resources of the aggressor UE, thereby resulting in CLI. In some wireless communications systems, UEs may be configured to perform CLI measurements (e.g., reference signal received power (RSRP) measurements or received signal strength indicator (RSSI) measurements) on signals transmitted by other UEs, and report measured CLI to the network so that the network may adjust resources allocated to the respective UEs to reduce CLI. A UE may receive an indication of a unified transmission configuration indicator (TCI) state for one or more signals. For example, a unified TCI type may indicate a common beam for more than one downlink transmissions. If the network does not indicate a specific receive beam to use when measuring CLI, the network may be unaware of which receive beam was used to measure the reported CLI. The network, however, may be most interested in CLI on specific receive beams for a UE as the CLI causes interference with signals received at the UE from the network for a specific receive beam.

(12) Described techniques relate to indicating a specific TCI state associated with a CLI measurement. A UE may receive control signaling (e.g., from a network entity) indicating a CLI measurement resource and an associated TCI state. The UE may generate and transmit a CLI report to the network entity using the CLI measurement resource and the beam associated with the indicated TCI state. For example, the indicated TCI state may indicate which receive beam of a set of receive beams the UE is to use for generating the CLI measure of the indicated CLI measurement resource. In some cases, the control signaling may indicate to use the same TCI state as another dedicated downlink channel configured for the UE, for example a physical downlink control channel (PDCCH) or a physical downlink shared channel (PDSCH). In some cases, the control signaling may indicate a unified TCI state for the CLI measurement. In some cases, a UE may be configured to communicate with multiple transmission and reception points (TRPs), which

may be each be associated with a respective control resource set (CORESET) pool. The UE may receive one or more control messages indicating an association between each CORESET pool and a respective TCI state. When a TRP schedules a CLI measurement for a UE, the UE may apply the beam associated with the TCI state associated with the CORESET pool associated with the scheduling TRP to the scheduled CLI measurement.

(13) Aspects of the disclosure are initially described in the context of wireless communications systems. Aspects of the disclosure are further illustrated by and described with reference to process flows. Aspects of the disclosure are further illustrated by and described with reference to apparatus diagrams, system diagrams, and flowcharts that relate to unified TCI state indication for CLI measurement.

(14) FIG. 1 illustrates an example of a wireless communications system **100** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The wireless communications system **100** may include one or more network entities **105**, one or more UEs **115**, and a core network **130**. In some examples, the wireless communications system **100** may be a Long Term Evolution (LTE) network, an LTE-Advanced (LTE-A) network, an LTE-A Pro network, a New Radio (NR) network, or a network operating in accordance with other systems and radio technologies, including future systems and radio technologies not explicitly mentioned herein.

(15) The network entities **105** may be dispersed throughout a geographic area to form the wireless communications system **100** and may include devices in different forms or having different capabilities. In various examples, a network entity **105** may be referred to as a network element, a mobility element, a radio access network (RAN) node, or network equipment, among other nomenclature. In some examples, network entities **105** and UEs **115** may wirelessly communicate via one or more communication links **125** (e.g., a radio frequency (RF) access link). For example, a network entity **105** may support a coverage area **110** (e.g., a geographic coverage area) over which the UEs **115** and the network entity **105** may establish one or more communication links **125**. The coverage area **110** may be an example of a geographic area over which a network entity **105** and a UE **115** may support the communication of signals according to one or more radio access technologies (RATs).

(16) The UEs **115** may be dispersed throughout a coverage area **110** of the wireless communications system **100**, and each UE **115** may be stationary, or mobile, or both at different times. The UEs **115** may be devices in different forms or having different capabilities. Some example UEs **115** are illustrated in FIG. 1. The UEs **115** described herein may be able to communicate with various types of devices, such as other UEs **115** or network entities **105**, as shown in FIG. 1.

(17) As described herein, a node of the wireless communications system **100**, which may be referred to as a network node, or a wireless node, may be a network entity **105** (e.g., any network entity described herein), a UE **115** (e.g., any UE described herein), a network controller, an apparatus, a device, a computing system, one or more components, or another suitable processing entity configured to perform any of the techniques described herein. For example, a node may be a UE **115**. As another example, a node may be a network entity **105**. As another example, a first node may be configured to communicate with a second node or a third node. In one aspect of this example, the first node may be a UE **115**, the second node may be a network entity **105**, and the third node may be a UE **115**. In another aspect of this example, the first node may be a UE **115**, the second node may be a network entity **105**, and the third node may be a network entity **105**. In yet other aspects of this example, the first, second, and third nodes may be different relative to these examples. Similarly, reference to a UE **115**, network entity **105**, apparatus, device, computing system, or the like may include disclosure of the UE **115**, network entity **105**, apparatus, device, computing system, or the like being a node. For example, disclosure that a UE **115** is configured to receive information from a network entity **105** also discloses that a first node is configured to

receive information from a second node.

(18) In some examples, network entities **105** may communicate with the core network **130**, or with one another, or both. For example, network entities **105** may communicate with the core network **130** via one or more backhaul communication links **120** (e.g., in accordance with an S1, N2, N3, or other interface protocol). In some examples, network entities **105** may communicate with one another over a backhaul communication link **120** (e.g., in accordance with an X2, Xn, or other interface protocol) either directly (e.g., directly between network entities **105**) or indirectly (e.g., via a core network **130**). In some examples, network entities **105** may communicate with one another via a midhaul communication link **162** (e.g., in accordance with a midhaul interface protocol) or a fronthaul communication link **168** (e.g., in accordance with a fronthaul interface protocol), or any combination thereof. The backhaul communication links **120**, midhaul communication links **162**, or fronthaul communication links **168** may be or include one or more wired links (e.g., an electrical link, an optical fiber link), one or more wireless links (e.g., a radio link, a wireless optical link), among other examples or various combinations thereof. A UE **115** may communicate with the core network **130** through a communication link **155**.

(19) One or more of the network entities **105** described herein may include or may be referred to as a base station **140** (e.g., a base transceiver station, a radio base station, an NR base station, an access point, a radio transceiver, a NodeB, an eNodeB (eNB), a next-generation NodeB or a giga-NodeB (either of which may be referred to as a gNB), a 5G NB, a next-generation eNB (ng-eNB), a Home NodeB, a Home eNodeB, or other suitable terminology). In some examples, a network entity **105** (e.g., a base station **140**) may be implemented in an aggregated (e.g., monolithic, standalone) base station architecture, which may be configured to utilize a protocol stack that is physically or logically integrated within a single network entity **105** (e.g., a single RAN node, such as a base station **140**).

(20) In some examples, a network entity **105** may be implemented in a disaggregated architecture (e.g., a disaggregated base station architecture, a disaggregated RAN architecture), which may be configured to utilize a protocol stack that is physically or logically distributed among two or more network entities **105**, such as an integrated access backhaul (IAB) network, an open RAN (O-RAN) (e.g., a network configuration sponsored by the O-RAN Alliance), or a virtualized RAN (vRAN) (e.g., a cloud RAN (C-RAN)). For example, a network entity **105** may include one or more of a central unit (CU) **160**, a distributed unit (DU) **165**, a radio unit (RU) **170**, a RAN Intelligent Controller (RIC) **175** (e.g., a Near-Real Time RIC (Near-RT RIC), a Non-Real Time RIC (Non-RT RIC)), a Service Management and Orchestration (SMO) **180** system, or any combination thereof. An RU **170** may also be referred to as a radio head, a smart radio head, a remote radio head (RRH), a remote radio unit (RRU), or a TRP. One or more components of the network entities **105** in a disaggregated RAN architecture may be co-located, or one or more components of the network entities **105** may be located in distributed locations (e.g., separate physical locations). In some examples, one or more network entities **105** of a disaggregated RAN architecture may be implemented as virtual units (e.g., a virtual CU (VCU), a virtual DU (VDU), a virtual RU (VRU)).

(21) The split of functionality between a CU **160**, a DU **165**, and an RU **175** is flexible and may support different functionalities depending upon which functions (e.g., network layer functions, protocol layer functions, baseband functions, RF functions, and any combinations thereof) are performed at a CU **160**, a DU **165**, or an RU **175**. For example, a functional split of a protocol stack may be employed between a CU **160** and a DU **165** such that the CU **160** may support one or more layers of the protocol stack and the DU **165** may support one or more different layers of the protocol stack. In some examples, the CU **160** may host upper protocol layer (e.g., layer 3 (L3), layer 2 (L2)) functionality and signaling (e.g., Radio Resource Control (RRC), service data adaptation protocol (SDAP), Packet Data Convergence Protocol (PDCP)). The CU **160** may be connected to one or more DUs **165** or RUs **170**, and the one or more DUs **165** or RUs **170** may host lower protocol layers, such as layer 1 (L1) (e.g., physical (PHY) layer) or L2 (e.g., radio link

control (RLC) layer, medium access control (MAC) layer) functionality and signaling, and may each be at least partially controlled by the CU **160**. Additionally, or alternatively, a functional split of the protocol stack may be employed between a DU **165** and an RU **170** such that the DU **165** may support one or more layers of the protocol stack and the RU **170** may support one or more different layers of the protocol stack. The DU **165** may support one or multiple different cells (e.g., via one or more RUs **170**). In some cases, a functional split between a CU **160** and a DU **165**, or between a DU **165** and an RU **170** may be within a protocol layer (e.g., some functions for a protocol layer may be performed by one of a CU **160**, a DU **165**, or an RU **170**, while other functions of the protocol layer are performed by a different one of the CU **160**, the DU **165**, or the RU **170**). A CU **160** may be functionally split further into CU control plane (CU-CP) and CU user plane (CU-UP) functions. A CU **160** may be connected to one or more DUs **165** via a midhaul communication link **162** (e.g., F1, F1-c, F1-u), and a DU **165** may be connected to one or more RUs **170** via a fronthaul communication link **168** (e.g., open fronthaul (FH) interface). In some examples, a midhaul communication link **162** or a fronthaul communication link **168** may be implemented in accordance with an interface (e.g., a channel) between layers of a protocol stack supported by respective network entities **105** that are in communication over such communication links.

(22) In wireless communications systems (e.g., wireless communications system **100**), infrastructure and spectral resources for radio access may support wireless backhaul link capabilities to supplement wired backhaul connections, providing an IAB network architecture (e.g., to a core network **130**). In some cases, in an IAB network, one or more network entities **105** (e.g., IAB nodes **104**) may be partially controlled by each other. One or more IAB nodes **104** may be referred to as a donor entity or an IAB donor. One or more DUs **165** or one or more RUs **170** may be partially controlled by one or more CUs **160** associated with a donor network entity **105** (e.g., a donor base station **140**). The one or more donor network entities **105** (e.g., IAB donors) may be in communication with one or more additional network entities **105** (e.g., IAB nodes **104**) via supported access and backhaul links (e.g., backhaul communication links **120**). IAB nodes **104** may include an IAB mobile termination (IAB-MT) controlled (e.g., scheduled) by DUs **165** of a coupled IAB donor. An IAB-MT may include an independent set of antennas for relay of communications with UEs **115**, or may share the same antennas (e.g., of an RU **170**) of an IAB node **104** used for access via the DU **165** of the IAB node **104** (e.g., referred to as virtual IAB-MT (vIAB-MT)). In some examples, the IAB nodes **104** may include DUs **165** that support communication links with additional entities (e.g., IAB nodes **104**, UEs **115**) within the relay chain or configuration of the access network (e.g., downstream). In such cases, one or more components of the disaggregated RAN architecture (e.g., one or more IAB nodes **104** or components of IAB nodes **104**) may be configured to operate according to the techniques described herein.

(23) For instance, an access network (AN) or RAN may include communications between access nodes (e.g., an IAB donor), IAB nodes **104**, and one or more UEs **115**. The IAB donor may facilitate connection between the core network **130** and the AN (e.g., via a wired or wireless connection to the core network **130**). That is, an IAB donor may refer to a RAN node with a wired or wireless connection to core network **130**. The IAB donor may include a CU **160** and at least one DU **165** (e.g., and RU **170**), in which case the CU **160** may communicate with the core network **130** over an interface (e.g., a backhaul link). IAB donor and IAB nodes **104** may communicate over an F1 interface according to a protocol that defines signaling messages (e.g., an F1 AP protocol). Additionally, or alternatively, the CU **160** may communicate with the core network over an interface, which may be an example of a portion of backhaul link, and may communicate with other CUs **160** (e.g., a CU **160** associated with an alternative IAB donor) over an Xn-C interface, which may be an example of a portion of a backhaul link.

(24) An IAB node **104** may refer to a RAN node that provides IAB functionality (e.g., access for UEs **115**, wireless self-backhauling capabilities). A DU **165** may act as a distributed scheduling

node towards child nodes associated with the IAB node **104**, and the IAB-MT may act as a scheduled node towards parent nodes associated with the IAB node **104**. That is, an IAB donor may be referred to as a parent node in communication with one or more child nodes (e.g., an IAB donor may relay transmissions for UEs through one or more other IAB nodes **104**). Additionally, or alternatively, an IAB node **104** may also be referred to as a parent node or a child node to other IAB nodes **104**, depending on the relay chain or configuration of the AN. Therefore, the IAB-MT entity of IAB nodes **104** may provide a Uu interface for a child IAB node **104** to receive signaling from a parent IAB node **104**, and the DU interface (e.g., DUs **165**) may provide a Uu interface for a parent IAB node **104** to signal to a child IAB node **104** or UE **115**.

(25) For example, IAB node **104** may be referred to as a parent node that supports communications for a child IAB node, and referred to as a child IAB node associated with an IAB donor. The IAB donor may include a CU **160** with a wired or wireless connection (e.g., a backhaul communication link **120**) to the core network **130** and may act as parent node to IAB nodes **104**. For example, the DU **165** of IAB donor may relay transmissions to UEs **115** through IAB nodes **104**, and may directly signal transmissions to a UE **115**. The CU **160** of IAB donor may signal communication link establishment via an F1 interface to IAB nodes **104**, and the IAB nodes **104** may schedule transmissions (e.g., transmissions to the UEs **115** relayed from the IAB donor) through the DUs **165**. That is, data may be relayed to and from IAB nodes **104** via signaling over an NR Uu interface to MT of the IAB node **104**. Communications with IAB node **104** may be scheduled by a DU **165** of IAB donor and communications with IAB node **104** may be scheduled by DU **165** of IAB node **104**.

(26) In the case of the techniques described herein applied in the context of a disaggregated RAN architecture, one or more components of the disaggregated RAN architecture may be configured to support unified TCI state indication for CLI measurement as described herein. For example, some operations described as being performed by a UE **115** or a network entity **105** (e.g., a base station **140**) may additionally, or alternatively, be performed by one or more components of the disaggregated RAN architecture (e.g., IAB nodes **104**, DUs **165**, CUs **160**, RUs **170**, MC **175**, SMO **180**).

(27) A UE **115** may include or may be referred to as a mobile device, a wireless device, a remote device, a handheld device, or a subscriber device, or some other suitable terminology, where the “device” may also be referred to as a unit, a station, a terminal, or a client, among other examples. A UE **115** may also include or may be referred to as a personal electronic device such as a cellular phone, a personal digital assistant (PDA), a tablet computer, a laptop computer, or a personal computer. In some examples, a UE **115** may include or be referred to as a wireless local loop (WLL) station, an Internet of Things (IoT) device, an Internet of Everything (IoE) device, or a machine type communications (MTC) device, among other examples, which may be implemented in various objects such as appliances, or vehicles, meters, among other examples.

(28) The UEs **115** described herein may be able to communicate with various types of devices, such as other UEs **115** that may sometimes act as relays as well as the network entities **105** and the network equipment including macro eNBs or gNBs, small cell eNBs or gNBs, or relay base stations, among other examples, as shown in FIG. 1.

(29) The UEs **115** and the network entities **105** may wirelessly communicate with one another via one or more communication links **125** (e.g., an access link) over one or more carriers. The term “carrier” may refer to a set of RF spectrum resources having a defined physical layer structure for supporting the communication links **125**. For example, a carrier used for a communication link **125** may include a portion of a RF spectrum band (e.g., a bandwidth part (BWP)) that is operated according to one or more physical layer channels for a given radio access technology (e.g., LTE, LTE-A, LTE-A Pro, NR). Each physical layer channel may carry acquisition signaling (e.g., synchronization signals, system information), control signaling that coordinates operation for the carrier, user data, or other signaling. The wireless communications system **100** may support

communication with a UE **115** using carrier aggregation or multi-carrier operation. A UE **115** may be configured with multiple downlink component carriers and one or more uplink component carriers according to a carrier aggregation configuration. Carrier aggregation may be used with both frequency division duplexing (FDD) and time division duplexing (TDD) component carriers. Communication between a network entity **105** and other devices may refer to communication between the devices and any portion (e.g., entity, sub-entity) of a network entity **105**. For example, the terms “transmitting,” “receiving,” or “communicating,” when referring to a network entity **105**, may refer to any portion of a network entity **105** (e.g., a base station **140**, a CU **160**, a DU **165**, a RU **170**) of a RAN communicating with another device (e.g., directly or via one or more other network entities **105**).

(30) In some examples, such as in a carrier aggregation configuration, a carrier may also have acquisition signaling or control signaling that coordinates operations for other carriers. A carrier may be associated with a frequency channel (e.g., an evolved universal mobile telecommunication system terrestrial radio access (E-UTRA) absolute RF channel number (EARFCN)) and may be positioned according to a channel raster for discovery by the UEs **115**. A carrier may be operated in a standalone mode, in which case initial acquisition and connection may be conducted by the UEs **115** via the carrier, or the carrier may be operated in a non-standalone mode, in which case a connection is anchored using a different carrier (e.g., of the same or a different radio access technology).

(31) The communication links **125** shown in the wireless communications system **100** may include downlink transmissions (e.g., forward link transmissions) from a network entity **105** to a UE **115**, uplink transmissions (e.g., return link transmissions) from a UE **115** to a network entity **105**, or both, among other configurations of transmissions. Carriers may carry downlink or uplink communications (e.g., in an FDD mode) or may be configured to carry downlink and uplink communications (e.g., in a TDD mode).

(32) A carrier may be associated with a particular bandwidth of the RF spectrum and, in some examples, the carrier bandwidth may be referred to as a “system bandwidth” of the carrier or the wireless communications system **100**. For example, the carrier bandwidth may be one of a set of bandwidths for carriers of a particular radio access technology (e.g., 1.4, 3, 5, 10, 15, 20, 40, or 80 megahertz (MHz)). Devices of the wireless communications system **100** (e.g., the network entities **105**, the UEs **115**, or both) may have hardware configurations that support communications over a particular carrier bandwidth or may be configurable to support communications over one of a set of carrier bandwidths. In some examples, the wireless communications system **100** may include network entities **105** or UEs **115** that support concurrent communications via carriers associated with multiple carrier bandwidths. In some examples, each served UE **115** may be configured for operating over portions (e.g., a sub-band, a BWP) or all of a carrier bandwidth.

(33) Signal waveforms transmitted over a carrier may be made up of multiple subcarriers (e.g., using multi-carrier modulation (MCM) techniques such as orthogonal frequency division multiplexing (OFDM) or discrete Fourier transform spread OFDM (DFT-S-OFDM)). In a system employing MCM techniques, a resource element may refer to resources of one symbol period (e.g., a duration of one modulation symbol) and one subcarrier, in which case the symbol period and subcarrier spacing may be inversely related. The quantity of bits carried by each resource element may depend on the modulation scheme (e.g., the order of the modulation scheme, the coding rate of the modulation scheme, or both) such that the more resource elements that a device receives and the higher the order of the modulation scheme, the higher the data rate may be for the device. A wireless communications resource may refer to a combination of an RF spectrum resource, a time resource, and a spatial resource (e.g., a spatial layer, a beam), and the use of multiple spatial resources may increase the data rate or data integrity for communications with a UE **115**.

(34) One or more numerologies for a carrier may be supported, where a numerology may include a subcarrier spacing (Δf) and a cyclic prefix. A carrier may be divided into one or more BWPs having

the same or different numerologies. In some examples, a UE **115** may be configured with multiple BWPs. In some examples, a single BWP for a carrier may be active at a given time and communications for the UE **115** may be restricted to one or more active BWPs.

(35) The time intervals for the network entities **105** or the UEs **115** may be expressed in multiples of a basic time unit which may, for example, refer to a sampling period of $T_{\text{sub.s}} = 1/(\Delta f_{\text{sub.max}} \cdot N_{\text{sub.f}})$ seconds, where $\Delta f_{\text{sub.max}}$ may represent the maximum supported subcarrier spacing, and $N_{\text{sub.f}}$ may represent the maximum supported discrete Fourier transform (DFT) size. Time intervals of a communications resource may be organized according to radio frames each having a specified duration (e.g., 10 milliseconds (ms)). Each radio frame may be identified by a system frame number (SFN) (e.g., ranging from 0 to 1023).

(36) Each frame may include multiple consecutively numbered subframes or slots, and each subframe or slot may have the same duration. In some examples, a frame may be divided (e.g., in the time domain) into subframes, and each subframe may be further divided into a quantity of slots. Alternatively, each frame may include a variable quantity of slots, and the quantity of slots may depend on subcarrier spacing. Each slot may include a quantity of symbol periods (e.g., depending on the length of the cyclic prefix prepended to each symbol period). In some wireless communications systems **100**, a slot may further be divided into multiple mini-slots containing one or more symbols. Excluding the cyclic prefix, each symbol period may contain one or more (e.g., $N_{\text{sub.f}}$) sampling periods. The duration of a symbol period may depend on the subcarrier spacing or frequency band of operation.

(37) A subframe, a slot, a mini-slot, or a symbol may be the smallest scheduling unit (e.g., in the time domain) of the wireless communications system **100** and may be referred to as a transmission time interval (TTI). In some examples, the TTI duration (e.g., a quantity of symbol periods in a TTI) may be variable. Additionally, or alternatively, the smallest scheduling unit of the wireless communications system **100** may be dynamically selected (e.g., in bursts of shortened TTIs (sTTIs)).

(38) Physical channels may be multiplexed on a carrier according to various techniques. A physical control channel and a physical data channel may be multiplexed on a downlink carrier, for example, using one or more of time division multiplexing (TDM) techniques, frequency division multiplexing (FDM) techniques, or hybrid TDM-FDM techniques. A control region (e.g., a CORESET) for a physical control channel may be defined by a set of symbol periods and may extend across the system bandwidth or a subset of the system bandwidth of the carrier. One or more control regions (e.g., CORESETs) may be configured for a set of the UEs **115**. For example, one or more of the UEs **115** may monitor or search control regions for control information according to one or more search space sets, and each search space set may include one or multiple control channel candidates in one or more aggregation levels arranged in a cascaded manner. An aggregation level for a control channel candidate may refer to an amount of control channel resources (e.g., control channel elements (CCEs)) associated with encoded information for a control information format having a given payload size. Search space sets may include common search space sets configured for sending control information to multiple UEs **115** and UE-specific search space sets for sending control information to a specific UE **115**.

(39) A network entity **105** may provide communication coverage via one or more cells, for example a macro cell, a small cell, a hot spot, or other types of cells, or any combination thereof. The term “cell” may refer to a logical communication entity used for communication with a network entity **105** (e.g., over a carrier) and may be associated with an identifier for distinguishing neighboring cells (e.g., a physical cell identifier (PCID), a virtual cell identifier (VCID), or others). In some examples, a cell may also refer to a coverage area **110** or a portion of a coverage area **110** (e.g., a sector) over which the logical communication entity operates. Such cells may range from smaller areas (e.g., a structure, a subset of structure) to larger areas depending on various factors such as the capabilities of the network entity **105**. For example, a cell may be or include a building, a

subset of a building, or exterior spaces between or overlapping with coverage areas **110**, among other examples.

(40) A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by the UEs **115** with service subscriptions with the network provider supporting the macro cell. A small cell may be associated with a lower-powered network entity **105** (e.g., a lower-powered base station **140**), as compared with a macro cell, and a small cell may operate in the same or different (e.g., licensed, unlicensed) frequency bands as macro cells. Small cells may provide unrestricted access to the UEs **115** with service subscriptions with the network provider or may provide restricted access to the UEs **115** having an association with the small cell (e.g., the UEs **115** in a closed subscriber group (CSG), the UEs **115** associated with users in a home or office). A network entity **105** may support one or multiple cells and may also support communications over the one or more cells using one or multiple component carriers.

(41) In some examples, a carrier may support multiple cells, and different cells may be configured according to different protocol types (e.g., MTC, narrowband IoT (NB-IoT), enhanced mobile broadband (eMBB)) that may provide access for different types of devices.

(42) In some examples, a network entity **105** (e.g., a base station **140**, an RU **170**) may be movable and therefore provide communication coverage for a moving coverage area **110**. In some examples, different coverage areas **110** associated with different technologies may overlap, but the different coverage areas **110** may be supported by the same network entity **105**. In some other examples, the overlapping coverage areas **110** associated with different technologies may be supported by different network entities **105**. The wireless communications system **100** may include, for example, a heterogeneous network in which different types of the network entities **105** provide coverage for various coverage areas **110** using the same or different radio access technologies.

(43) The wireless communications system **100** may support synchronous or asynchronous operation. For synchronous operation, network entities **105** (e.g., base stations **140**) may have similar frame timings, and transmissions from different network entities **105** may be approximately aligned in time. For asynchronous operation, network entities **105** may have different frame timings, and transmissions from different network entities **105** may, in some examples, not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

(44) Some UEs **115**, such as MTC or IoT devices, may be low cost or low complexity devices and may provide for automated communication between machines (e.g., via Machine-to-Machine (M2M) communication). M2M communication or MTC may refer to data communication technologies that allow devices to communicate with one another or a network entity **105** (e.g., a base station **140**) without human intervention. In some examples, M2M communication or MTC may include communications from devices that integrate sensors or meters to measure or capture information and relay such information to a central server or application program that makes use of the information or presents the information to humans interacting with the application program. Some UEs **115** may be designed to collect information or enable automated behavior of machines or other devices. Examples of applications for MTC devices include smart metering, inventory monitoring, water level monitoring, equipment monitoring, healthcare monitoring, wildlife monitoring, weather and geological event monitoring, fleet management and tracking, remote security sensing, physical access control, and transaction-based business charging.

(45) Some UEs **115** may be configured to employ operating modes that reduce power consumption, such as half-duplex communications (e.g., a mode that supports one-way communication via transmission or reception, but not transmission and reception concurrently). In some examples, half-duplex communications may be performed at a reduced peak rate. Other power conservation techniques for the UEs **115** include entering a power saving deep sleep mode when not engaging in active communications, operating over a limited bandwidth (e.g., according to narrowband communications), or a combination of these techniques. For example, some UEs **115** may be

configured for operation using a narrowband protocol type that is associated with a defined portion or range (e.g., set of subcarriers or resource blocks (RBs)) within a carrier, within a guard-band of a carrier, or outside of a carrier.

(46) The wireless communications system **100** may be configured to support ultra-reliable communications or low-latency communications, or various combinations thereof. For example, the wireless communications system **100** may be configured to support ultra-reliable low-latency communications (URLLC). The UEs **115** may be designed to support ultra-reliable, low-latency, or critical functions. Ultra-reliable communications may include private communication or group communication and may be supported by one or more services such as push-to-talk, video, or data. Support for ultra-reliable, low-latency functions may include prioritization of services, and such services may be used for public safety or general commercial applications. The terms ultra-reliable, low-latency, and ultra-reliable low-latency may be used interchangeably herein.

(47) In some examples, a UE **115** may be able to communicate directly with other UEs **115** over a device-to-device (D2D) communication link **135** (e.g., in accordance with a peer-to-peer (P2P), D2D, or sidelink protocol). In some examples, one or more UEs **115** of a group that are performing D2D communications may be within the coverage area **110** of a network entity **105** (e.g., a base station **140**, an RU **170**), which may support aspects of such D2D communications being configured by or scheduled by the network entity **105**. In some examples, one or more UEs **115** in such a group may be outside the coverage area **110** of a network entity **105** or may be otherwise unable to or not configured to receive transmissions from a network entity **105**. In some examples, groups of the UEs **115** communicating via D2D communications may support a one-to-many (1:M) system in which each UE **115** transmits to each of the other UEs **115** in the group. In some examples, a network entity **105** may facilitate the scheduling of resources for D2D communications. In some other examples, D2D communications may be carried out between the UEs **115** without the involvement of a network entity **105**.

(48) In some systems, a D2D communication link **135** may be an example of a communication channel, such as a sidelink communication channel, between vehicles (e.g., UEs **115**). In some examples, vehicles may communicate using vehicle-to-everything (V2X) communications, vehicle-to-vehicle (V2V) communications, or some combination of these. A vehicle may signal information related to traffic conditions, signal scheduling, weather, safety, emergencies, or any other information relevant to a V2X system. In some examples, vehicles in a V2X system may communicate with roadside infrastructure, such as roadside units, or with the network via one or more network nodes (e.g., network entities **105**, base stations **140**, RUs **170**) using vehicle-to-network (V2N) communications, or with both.

(49) The core network **130** may provide user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The core network **130** may be an evolved packet core (EPC) or 5G core (5GC), which may include at least one control plane entity that manages access and mobility (e.g., a mobility management entity (MME), an access and mobility management function (AMF)) and at least one user plane entity that routes packets or interconnects to external networks (e.g., a serving gateway (S-GW), a Packet Data Network (PDN) gateway (P-GW), or a user plane function (UPF)). The control plane entity may manage non-access stratum (NAS) functions such as mobility, authentication, and bearer management for the UEs **115** served by the network entities **105** (e.g., base stations **140**) associated with the core network **130**. User IP packets may be transferred through the user plane entity, which may provide IP address allocation as well as other functions. The user plane entity may be connected to IP services **150** for one or more network operators. The IP services **150** may include access to the Internet, Intranet(s), an IP Multimedia Subsystem (IMS), or a Packet-Switched Streaming Service.

(50) The wireless communications system **100** may operate using one or more frequency bands, which may be in the range of 300 megahertz (MHz) to 300 gigahertz (GHz). Generally, the region

from 300 MHz to 3 GHz is known as the ultra-high frequency (UHF) region or decimeter band because the wavelengths range from approximately one decimeter to one meter in length. The UHF waves may be blocked or redirected by buildings and environmental features, which may be referred to as clusters, but the waves may penetrate structures sufficiently for a macro cell to provide service to the UEs **115** located indoors. The transmission of UHF waves may be associated with smaller antennas and shorter ranges (e.g., less than 100 kilometers) compared to transmission using the smaller frequencies and longer waves of the high frequency (HF) or very high frequency (VHF) portion of the spectrum below 300 MHz.

(51) The wireless communications system **100** may also operate in a super high frequency (SHF) region using frequency bands from 3 GHz to 30 GHz, also known as the centimeter band, or in an extremely high frequency (EHF) region of the spectrum (e.g., from 30 GHz to 300 GHz), also known as the millimeter band. In some examples, the wireless communications system **100** may support millimeter wave (mmW) communications between the UEs **115** and the network entities **105** (e.g., base stations **140**, RUs **170**), and EHF antennas of the respective devices may be smaller and more closely spaced than UHF antennas. In some examples, this may facilitate use of antenna arrays within a device. The propagation of EHF transmissions, however, may be subject to even greater atmospheric attenuation and shorter range than SHF or UHF transmissions. The techniques disclosed herein may be employed across transmissions that use one or more different frequency regions, and designated use of bands across these frequency regions may differ by country or regulating body.

(52) The wireless communications system **100** may utilize both licensed and unlicensed RF spectrum bands. For example, the wireless communications system **100** may employ License Assisted Access (LAA), LTE-Unlicensed (LTE-U) radio access technology, or NR technology in an unlicensed band such as the 5 GHz industrial, scientific, and medical (ISM) band. While operating in unlicensed RF spectrum bands, devices such as the network entities **105** and the UEs **115** may employ carrier sensing for collision detection and avoidance. In some examples, operations in unlicensed bands may be based on a carrier aggregation configuration in conjunction with component carriers operating in a licensed band (e.g., LAA). Operations in unlicensed spectrum may include downlink transmissions, uplink transmissions, P2P transmissions, or D2D transmissions, among other examples.

(53) A network entity **105** (e.g., a base station **140**, an RU **170**) or a UE **115** may be equipped with multiple antennas, which may be used to employ techniques such as transmit diversity, receive diversity, multiple-input multiple-output (MIMO) communications, or beamforming. The antennas of a network entity **105** or a UE **115** may be located within one or more antenna arrays or antenna panels, which may support MIMO operations or transmit or receive beamforming. For example, one or more base station antennas or antenna arrays may be co-located at an antenna assembly, such as an antenna tower. In some examples, antennas or antenna arrays associated with a network entity **105** may be located in diverse geographic locations. A network entity **105** may have an antenna array with a set of rows and columns of antenna ports that the network entity **105** may use to support beamforming of communications with a UE **115**. Likewise, a UE **115** may have one or more antenna arrays that may support various MIMO or beamforming operations. Additionally, or alternatively, an antenna panel may support RF beamforming for a signal transmitted via an antenna port.

(54) The network entities **105** or the UEs **115** may use MIMO communications to exploit multipath signal propagation and increase the spectral efficiency by transmitting or receiving multiple signals via different spatial layers. Such techniques may be referred to as spatial multiplexing. The multiple signals may, for example, be transmitted by the transmitting device via different antennas or different combinations of antennas. Likewise, the multiple signals may be received by the receiving device via different antennas or different combinations of antennas. Each of the multiple signals may be referred to as a separate spatial stream and may carry information associated with

the same data stream (e.g., the same codeword) or different data streams (e.g., different codewords). Different spatial layers may be associated with different antenna ports used for channel measurement and reporting. MIMO techniques include single-user MIMO (SU-MIMO), where multiple spatial layers are transmitted to the same receiving device, and multiple-user MIMO (MU-MIMO), where multiple spatial layers are transmitted to multiple devices.

(55) Beamforming, which may also be referred to as spatial filtering, directional transmission, or directional reception, is a signal processing technique that may be used at a transmitting device or a receiving device (e.g., a network entity **105**, a UE **115**) to shape or steer an antenna beam (e.g., a transmit beam, a receive beam) along a spatial path between the transmitting device and the receiving device. Beamforming may be achieved by combining the signals communicated via antenna elements of an antenna array such that some signals propagating at particular orientations with respect to an antenna array experience constructive interference while others experience destructive interference. The adjustment of signals communicated via the antenna elements may include a transmitting device or a receiving device applying amplitude offsets, phase offsets, or both to signals carried via the antenna elements associated with the device. The adjustments associated with each of the antenna elements may be defined by a beamforming weight set associated with a particular orientation (e.g., with respect to the antenna array of the transmitting device or receiving device, or with respect to some other orientation).

(56) A network entity **105** or a UE **115** may use beam sweeping techniques as part of beamforming operations. For example, a network entity **105** (e.g., a base station **140**, an RU **170**) may use multiple antennas or antenna arrays (e.g., antenna panels) to conduct beamforming operations for directional communications with a UE **115**. Some signals (e.g., synchronization signals, reference signals, beam selection signals, or other control signals) may be transmitted by a network entity **105** multiple times along different directions. For example, the network entity **105** may transmit a signal according to different beamforming weight sets associated with different directions of transmission. Transmissions along different beam directions may be used to identify (e.g., by a transmitting device, such as a network entity **105**, or by a receiving device, such as a UE **115**) a beam direction for later transmission or reception by the network entity **105**.

(57) Some signals, such as data signals associated with a particular receiving device, may be transmitted by transmitting device (e.g., a transmitting network entity **105**, a transmitting UE **115**) along a single beam direction (e.g., a direction associated with the receiving device, such as a receiving network entity **105** or a receiving UE **115**). In some examples, the beam direction associated with transmissions along a single beam direction may be determined based on a signal that was transmitted along one or more beam directions. For example, a UE **115** may receive one or more of the signals transmitted by the network entity **105** along different directions and may report to the network entity **105** an indication of the signal that the UE **115** received with a highest signal quality or an otherwise acceptable signal quality.

(58) In some examples, transmissions by a device (e.g., by a network entity **105** or a UE **115**) may be performed using multiple beam directions, and the device may use a combination of digital precoding or beamforming to generate a combined beam for transmission (e.g., from a network entity **105** to a UE **115**). The UE **115** may report feedback that indicates precoding weights for one or more beam directions, and the feedback may correspond to a configured set of beams across a system bandwidth or one or more sub-bands. The network entity **105** may transmit a reference signal (e.g., a cell-specific reference signal (CRS), a channel state information reference signal (CSI-RS)), which may be precoded or unprecoded. The UE **115** may provide feedback for beam selection, which may be a precoding matrix indicator (PMI) or codebook-based feedback (e.g., a multi-panel type codebook, a linear combination type codebook, a port selection type codebook). Although these techniques are described with reference to signals transmitted along one or more directions by a network entity **105** (e.g., a base station **140**, an RU **170**), a UE **115** may employ similar techniques for transmitting signals multiple times along different directions (e.g., for

identifying a beam direction for subsequent transmission or reception by the UE **115**) or for transmitting a signal along a single direction (e.g., for transmitting data to a receiving device).

(59) A receiving device (e.g., a UE **115**) may perform reception operations in accordance with multiple receive configurations (e.g., directional listening) when receiving various signals from a receiving device (e.g., a network entity **105**), such as synchronization signals, reference signals, beam selection signals, or other control signals. For example, a receiving device may perform reception in accordance with multiple receive directions by receiving via different antenna subarrays, by processing received signals according to different antenna subarrays, by receiving according to different receive beamforming weight sets (e.g., different directional listening weight sets) applied to signals received at multiple antenna elements of an antenna array, or by processing received signals according to different receive beamforming weight sets applied to signals received at multiple antenna elements of an antenna array, any of which may be referred to as “listening” according to different receive configurations or receive directions. In some examples, a receiving device may use a single receive configuration to receive along a single beam direction (e.g., when receiving a data signal). The single receive configuration may be aligned along a beam direction determined based on listening according to different receive configuration directions (e.g., a beam direction determined to have a highest signal strength, highest signal-to-noise ratio (SNR), or otherwise acceptable signal quality based on listening according to multiple beam directions).

(60) The wireless communications system **100** may be a packet-based network that operates according to a layered protocol stack. In the user plane, communications at the bearer or PDCP layer may be IP-based. An RLC layer may perform packet segmentation and reassembly to communicate over logical channels. A MAC layer may perform priority handling and multiplexing of logical channels into transport channels. The MAC layer may also use error detection techniques, error correction techniques, or both to support retransmissions at the MAC layer to improve link efficiency. In the control plane, the RRC protocol layer may provide establishment, configuration, and maintenance of an RRC connection between a UE **115** and a network entity **105** or a core network **130** supporting radio bearers for user plane data. At the PHY layer, transport channels may be mapped to physical channels.

(61) The UEs **115** and the network entities **105** may support retransmissions of data to increase the likelihood that data is received successfully. Hybrid automatic repeat request (HARQ) feedback is one technique for increasing the likelihood that data is received correctly over a communication link (e.g., a communication link **125**, a D2D communication link **135**). HARQ may include a combination of error detection (e.g., using a cyclic redundancy check (CRC)), forward error correction (FEC), and retransmission (e.g., automatic repeat request (ARQ)). HARQ may improve throughput at the MAC layer in poor radio conditions (e.g., low signal-to-noise conditions). In some examples, a device may support same-slot HARQ feedback, where the device may provide HARQ feedback in a specific slot for data received in a previous symbol in the slot. In some other examples, the device may provide HARQ feedback in a subsequent slot, or according to some other time interval.

(62) A UE **115** may experience CLI attributable to signals transmitted by other UEs **115**. For example, a “victim” UE **115** may experience CLI from signals transmitted by an “aggressor” UE **115** in cases where downlink resources of the victim UE **115** overlap with uplink resources of the aggressor UE **115**, thereby resulting in CLI. In some wireless communications systems, UEs **115** may be configured to perform CLI measurements (e.g., RSRP measurements or RSSI measurements) on signals transmitted by other UEs **115**, and report measured CLI to the network so that the network may adjust resources allocated to the respective UEs **115** to reduce CLI.

(63) A UE **115** may receive an indication of a unified TCI state for one or more signals. For example, a unified TCI type **1** may indicate a common beam for at least one downlink transmission and at least one uplink transmission, a unified TCI type **2** may indicate a common beam for more than one downlink transmissions, and a unified TCI type **3** may indicate a common beam for more

than one uplink transmissions. If the network does not indicate a specific receive beam to use when measuring CLI, the network may be unaware of which receive beam was used to measure the reported CLI. The network, however, may be most interested in CLI on specific receive beams for a UE as the CLI causes interference with signals received at the UE from the network for a specific receive beam.

(64) A UE **115** may receive control signaling (e.g., from a network entity **105**) indicating a CLI measurement resource and an associated TCI state. The UE **115** may generate and transmit a CLI report to the network entity **105** using the CLI measurement resource and the beam associated with the indicated TCI state. In some cases, the control signaling may indicate to use the same TCI state as another dedicated downlink channel configured for the UE **115**, for example a PDCCH or a PDSCH. In some cases, the control signaling may indicate a unified TCI state to apply for the CLI measurement. In some cases, a UE **115** may be configured to communicate with TRPs, which may be each be associated with a respective CORESET pool. The UE **115** may receive one or more control messages indicating an association between each CORESET pool and a respective TCI state. When a TRP schedules a CLI measurement for a UE **115**, the UE **115** may apply the beam associated with the TCI state associated with the CORESET pool associated with the scheduling TRP to the scheduled CLI measurement. Accordingly, the network may allocate resources to reduce CLI based on the measured CLI in accordance with the indicated receive beam.

(65) FIG. 2 illustrates an example of a wireless communications system **200** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. In some examples, the wireless communications system **200** may implement aspects of wireless communications system **100**. The wireless communications system **200** may include a UE **115-a** and a UE **115-b**, which may be examples of UEs **115** as described herein. The wireless communications system **200** may include a network entity **105-a**, which may be an example of a network entity **105** as described herein.

(66) The UE **115-a** may operate in a multiple TRP mode with TRP **205-a** and TRP **205-b**. In some cases, TRP **205-a** and TRP **205-b** may be located at a same network entity **105-a**. In some cases, TRP **205-a** and TRP **205-b** may be located at different network entities.

(67) UE **115-a** may be capable of performing simultaneous communication with TRP **205-a** and TRP **205-b**. The UE **115-a** may communicate with the TRP **205-a** using a communication link **125-a**. The UE **115-a** may communicate with the TRP **205-b** using a communication link **125-b**. The UE **115-b** may communicate with TRP **205-a** using a communication link **125-c**. The communication link **125-a**, the communication link **125-b**, and the communication link **125-c** may include bi-directional links that enable both uplink and downlink communication. For example, the UE **115-a** may transmit uplink signals, such as uplink control signals or uplink data signals, to the TRP **205-a** using the communication link **125-a** and the TRP **205-a** may transmit downlink transmissions, such as downlink control signals or downlink data signals, to the UE **115-a** using the communication link **125-a**. The UE **115-a** may transmit uplink signals, such as uplink control signals or uplink data signals, to the TRP **205-b** using the communication link **125-b** and the TRP **205-b** may transmit downlink transmissions, such as downlink control signals or downlink data signals, to the UE **115-a** using the communication link **125-b**. By way of another example, the UE **115-b** may transmit uplink signals, such as uplink control signals or uplink data signals, to the TRP **205-a** using the communication link **125-c** and the TRP **205-a** may transmit downlink transmissions, such as downlink control signals or downlink data signals, to the UE **115-b** using the communication link **125-c**. In some examples, different TRPs (e.g., TRP **205-a** and TRP **205-b**) may have different TRP identifiers (IDs). In some examples, different TRPs may be identified through an association with other IDs, such as a CORESET pool index, close loop index, TCI ID, TCI group ID, or a sounding reference signal resource set ID.

(68) In some examples, the UE **115-a** (e.g., the victim UE) may experience CLI **230** when receiving downlink transmissions from the TRP **205-a** via the communication link **125-a** caused by

uplink signals transmitted by the UE **115-b** via the communication link **125-c** if the uplink signals and downlink transmissions overlap (e.g., if the uplink and downlink transmissions have overlapping symbols).

(69) CLI **230** may occur when the network configures multiple nearby UEs **115** with different TDD uplink and downlink slot formats. In particular, when an aggressor UE **115-b** is transmitting uplink signals, a nearby victim UE **115-a** may receive the uplink signals as CLI **230** within the configured downlink symbols of the victim UE **115-a** if uplink symbols of the aggressor UE **115-b** collide with (e.g., overlap with) at least one downlink symbol of the victim UE **115-a**. The uplink signals transmitted by the aggressor UE **115-b** may or may not be intended for the victim UE **115-a**, such that the victim UE **115-a** inadvertently “intercepts” the uplink signals intended for another wireless device (e.g., the network entity **105-a**). In some cases, the network entity **105-a** may operate in a full duplex mode (e.g., the network entity **105-a** may serve downlink and uplink UEs **115** at the same time) which may result in increased CLI occurrences.

(70) The victim UE **115-a** may be configured to measure CLI **230** and report the measured CLI **230** to the network entity **105-a** so that the network may allocate resources to reduce CLI **230**. For example, the network may schedule uplink and downlink communications for the aggressor UE **115-b** and the victim UE **115-a**, respectively, in different time or frequency resources to avoid a strong CLI **230**.

(71) For example, the TRP **205-a** may transmit control signaling **210** to the victim UE **115-a** scheduling one or more CLI measurement resources (e.g., CLI measurement occasions). The TRP **205-a** may also transmit control signaling to the aggressor UE **115-b** scheduling one or more sounding reference signal (SRS) corresponding to the CLI measurement resources. The victim UE **115-a** may receive and measure the SRS to determine the CLI strength. For example, the victim UE **115-a** may transmit a message **215** to the TRP **205-a** that includes CLI measurement results in terms of SRS RSRP or CLI RSSI. In some cases, the victim UE **115-a** may transmit the CLI measurement message **215** periodically or based on defined triggering conditions.

(72) In some cases, CLI measurement reports may be triggered by layer 3 signaling. CLI measurement reports triggered by layer 3 signaling may be collected by a CU, and may be associated with additional latency as compared to CLI measurement reports configured by layer 1 signaling, which may be collected by a DU. Filtering results of layer 3 scheduled CLI measurement reports over given beams **235** or time may be unsuitable for a fast layer 1 beam selection in response to interference variation. A CLI measurement report configuration update for layer 3 scheduled CLI measurement reports may involve RRC reconfiguration, which may be inefficient for latency and flexibility purposes. Layer 3 scheduled CLI measurement reports may not define which receive beam **235** to use to measure CLI. In some cases, which beam **235** to use to measure CLI may be determined by a UE implementation. In some cases, CLI in layer 3 scheduled CLI measurement reports may be averaged over different receive beams **235**.

(73) Layer 1 scheduled CLI measurement reports may provide enhanced flexibility and reduced latency. Layer 1 scheduled beams may also not define which receive beam **235** to use to measure CLI. For layer 1 beams, it may be beneficial for the network to know the CLI **230** on a particular victim UE **115-a** receive beam **235** on which the victim UE **115-a** will receive downlink transmissions (e.g., PDSCH or PDCCH messages) so that the network may schedule resources in order to mitigate CLI **230** on the particular beam **235**.

(74) In some cases, three types of unified TCI states may be defined. For example, a first type unified TCI state may include a separate downlink TCI state. A second type of unified TCI state may include a separate uplink TCI state. A third type of TCI state may include a joint uplink and downlink TCI state. In some cases, a unified TCI state may be shared by more than one channel. A separate downlink or a joint downlink and uplink TCI state may be activated by a downlink control information (DCI) message, and the activated TCI state may be used by the victim UE **115-a** for reception of a dedicated PDSCH and/or PDCCH for the victim UE **115-a**. In some cases, other

channels or reference signals may be optionally configured in RRC whether to follow the same activated TCI state as the dedicated PDSCH and/or PDCCH for the victim UE **115-a**.

(75) In some cases, for a separate downlink TCI state, mandatory channels may include UE dedicated PDCCH and PDSCH and optional channels (e.g., which may be configured in RRC) may include non-UE dedicated PDCCH and PDSCH, aperiodic channel state information (CSI) reference signal (CSI-RS) for CSI, and aperiodic CSI-RS for beam management.

(76) In some cases, for a separate uplink TCI state, mandatory channels may include UE dedicated physical uplink shared channel (PUSCH) for both dynamic grant and configured grant and physical uplink control channel (PUCCH). For a separate uplink TCI state, optional channels may include SRS for codebook, SRS for non-codebook, SRS for antenna switching, and SRS for beam management.

(77) In some cases, for a joint downlink and uplink TCI state, mandatory channels may include UE dedicated PDCCH, PDSCH, PUSCH (for dynamic grant and configured grant) and PUCCH. For a joint downlink and uplink TCI state, optional channels may include non-UE dedicated PDCCH and PDSCH, aperiodic CSI-RS, aperiodic CSI-RS for beam management, SRS for codebook, SRS for non-codebook, SRS for antenna switching, and SRS for beam management.

(78) In some cases, if other channels or reference signals are configured to follow the same TCI state of victim UE **115-a** as the dedicated PDCCH and/or PDSCH, the TCI state for the other channels or reference signals will also be autonomously updated by the DCI that updates the TCI state for the dedicated PDCCH and/or PDSCH. In some cases, if other channels or reference signals are configured not to follow the same TCI state of the victim UE **115-a** as the dedicated PDCCH and/or PDSCH, a separate signaling will be used to configure the TCI state for the other channels or reference signals (e.g., via an RRC message or a MAC-CE). For example, if a CSI-RS or a tracking reference signal (TRS) is used to track the channel in the serving PDCCH and/or PDSCH beam, then the CSI-RS or TRS may be configured to share the same TCI state as the PDCCH and/or PDSCH, such that whenever the serving beam changes, the CSI-RS or TRS beam also follow the changed beam. As another example, if a CSI-RS is used to track certain beamforming direction (which need not be the serving beam), then the CSI-RS may be configured not to share the same TCI state as the PDCCH and/or PDSCH for the victim UE **115-a**. In such cases, the TCI state of the CSI-RS may be separately configured by MAC-CE in RRC.

(79) In some cases, a TCI state (e.g., a unified TCI state) may be indicated in control signaling **210** per CLI measurement resource. By indicating a TCI state per CLI resource, the network may configure the receive beam **235** corresponding to the reported CLI. Accordingly, the victim UE **115-a** may generate a CLI measurement using the indicated receive beam **235** and may transmit a message **215** indicating the CLI measurement. For example, in the case of a single TRP **205** (e.g., if the victim UE **115-a** is communicating with TRP **205-a**), each CLI measurement resource or measurement resource set may be indicated whether to share the same unified TCI state as the dedicated PDCCH and PDSCH for the victim UE **115-a**. In some cases (in a single TRP case), a DCI message **220** (e.g., DCI format 1_1 or DCI format 1_2) may update the UE dedicated PDCCH and PDSCH, which may also update the TCI state for the CLI measurement resource, measurement resource set, or both. In some cases, only aperiodic CLI measurement resources may be configured to follow the same TCI state as the dedicated PDSCH and PDCCH for the victim UE **115-a**.

(80) In some cases (in a single TRP case), if the victim UE **115-a** is not configured to share the same unified TCI state as the dedicated PDCCH and PDSCH for the victim UE **115-a**, the TCI state for the CLI measurement resource or measurement resource set may be indicated in RRC. In some cases, the TCI state for the CLI measurement resource or measurement resource set may be updated by a MAC-CE. In some cases, the quasi co-location (QCL) type D source reference signal of the indicated TCI state may be a synchronization signal block (SSB) or a periodic or semi-periodic CSI-RS, where the SSB may be from a non-serving PCID.

(81) In some cases, the victim UE **115-a** may communicate with multiple TRPs **205**. For example,

the victim UE **115-a** may communicate with the TRP **205-a** and the TRP **205-b**. In the case of multiple TRPs **205**, multiple TCI states may be activated for dedicated PDCCH and PDSCH reception for the victim UE **115-a** (e.g., each TCI state may be associated with reception from a particular TRP **205**). For multiple DCI cases, each TRP **205** may be associated with a CORESET pool identifier. In multiple DCI cases, a CLI measurement resource, resource set, or both, may be associated with a CORESET pool identifier, for example in a control message **225** (e.g., in RRC). In some cases, if the CLI resource or resource set is indicated to share the same TCI state as the dedicated PDCCH and PDSCH for the victim UE **115-a**, then the CLI measurement resource may follow the TCI state of the associated TRP **205**. In some cases, the CLI measurement resource may be activated or triggered by the PDCCH or PDSCH from the same TRP **205** (e.g., control signaling **210** received from a TRP **205**).

(82) In some cases, a CLI measurement resource may be configured with multiple TCI state configurations, each associated with a CORESET pool identifier. The CLI measurement resource may be configured with multiple TCI state configurations, each associated with a CORESET pool identifier (e.g., via a control message **225**). The CLI measurement resource may be scheduled or activated by multiple TRPs **205** (e.g., the victim UE **115-a** may receive control signaling **210** from scheduling CLI measurement resources from multiple TRPs), but different receive beams **235** will be used for the CLI measurement resources depending on which TRP **205** transmitted the control signaling **210** activating or scheduling the CLI measurement resource. For example, beam **235-a** may be used if the TRP **205-a** transmitted the control signaling **210**, and beam **235-b** may be used if the TRP **205-b** transmitted the control signaling **210**.

(83) In some cases, a DCI message **220** or MAC-CE activating an aperiodic or semi-periodic CLI measurement may also indicate a TCI state for the aperiodic or semi-periodic CLI measurement. In some examples, the indicated TCI state may overwrite the original TCI configuration associated with the aperiodic or semi-periodic CLI measurement (e.g., which may be configured in RRC). In some cases, where multiple configurations may be pre-configured for multiple CORESET pool identifiers, only the configuration corresponding to the same CORESET pool identifier as the activation signaling (DCI message **220** or MAC-CE) may be overwritten.

(84) As described herein, a layer 1 scheduled CLI measurement report may better reflect current CLI as compared to a layer 3 scheduled CLI measurement report and may request a CLI measurement for an intended receive beam **235** with a low latency as dictated by traffic conditions. A layer 1 CLI measurement resource may include both a layer 1 SRS resource and a layer 1 RSSI resource. For a periodic CLI measurement resource, a corresponding TCI state may be RRC configured. For a semi-periodic CLI measurement resource, a corresponding TCI state may be dynamically updated via a MAC-CE (de)activating the resource or resource set or list. For an aperiodic CLI measurement resource, a corresponding TCI state may be RRC configured with each resource or resource set or list associated with a trigger state, which may be further dynamically indicated in a DCI message.

(85) For example, a first CLI measurement resource is configured with TCI state X for CORESET pool X. In the aperiodic CLI measurement resource case, the first CLI measurement resource may be associated with an aperiodic CLI measurement trigger state for an aperiodic CLI measurement report. When the aperiodic CLI measurement report is triggered (e.g., via control signaling **210**), a different TCI state may be applied for the first CLI measurement, based on which CORESET pool the triggering control signaling **210** (e.g., which may be a DCI message) was received from. In the periodic or semi-periodic CLI measurement resource case, the first CLI measurement resource may be associated with a periodic or semi-periodic report configuration. Based on which CORESET pool the control signaling **210** (e.g., the activation RRC or MAC-CE) is received from, a different TCI state may be applied for the first CLI measurement. For example, both TRP **205-a** and TRP **205-b** may transmit activation commands (e.g., control signaling **210**) for a first CLI measurement resource. The victim UE **115-a** may measure the CLI using receive filters for each of TRP **205-a**

and TRP **205-b** using the first CLI measurement resource. The victim UE **115-a** may transmit indications of CLI measurements using the different receive filters for each of TRP **205-a** and TRP **205-b** in a CLI measurement report message **215**.

(86) FIG. **3** illustrates an example of a process flow **300** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The process flow **300** may include a UE **115-c**, which may be an example of a UE **115** as described herein. The process flow **300** may include a network entity **105-b**, which may be an example of a network entity **105** as described herein. In the following description of the process flow **300**, the operations between the network entity **105-b** and the UE **115-c** may be transmitted in a different order than the example order shown, or the operations performed by the network entity **105-b** and the UE **115-c** may be performed in different orders or at different times. Some operations may also be omitted from the process flow **300**, and other operations may be added to the process flow **300**.

(87) At **305**, the UE **115-c** may receive, from the network entity **105-b**, control signaling indicating a CLI measurement resource and a TCI state the UE **115-c** is to apply for CLI measurement in the CLI measurement resource.

(88) At **310**, the UE **115-c** may determine a receive beam to apply during the CLI measurement resource based on the indicated TCI state.

(89) At **315**, the UE **115-c** may generate a CLI measurement of the CLI measurement resource using the determined receive beam associated with the indicated TCI state.

(90) At **320**, the UE **115-c** may transmit, to the network entity **105-b**, a message indicating the CLI measurement.

(91) In some cases, the UE **115-c** may receive, with the control signaling at **305**, an indication that the TCI state is associated with a downlink channel for the UE **115-c**. For example, the downlink channel may be the dedicated PDSCH and PUCCH for the UE **115-c**. In some cases, receiving the indication that the TCI state is associated with the downlink channel for the UE **115-c** includes receiving an indication of a unified TCI state.

(92) In some cases, the UE **115-c** may receive, from the network entity **105-b**, a DCI message indicating the TCI state.

(93) In some cases, the UE **115-c** may receive, from the network entity **105-b**, a control message indicating a set of TCI states associated with a set of CORESET pools. The UE **115-c** may receive, with the control signaling at **305**, an indication of a CORESET pool of the set of CORESET pools, where the TCI state is based on the indication of the CORESET pool. In some cases, the indication of the CORESET pool of the set of CORESET pools may include a CORESET pool identifier. In some cases, receiving the indication of the CORESET pool of the set of CORESET pools includes receiving the control signaling at **305** from a TRP associated with the CORESET pool, wherein each CORESET pool of the set of CORESET pools is associated with a respective TRP.

(94) In some cases, the UE **115-c** may receive, from the network entity **105-b**, a control message indicating a second TCI state associated with a set of CLI measurement resources including the CLI measurement resource, where the CLI measurement resource is an aperiodic or a semi-periodic CLI measurement resource. The UE **115-c** may receive, with the control signaling at **305**, an indication to overwrite the second TCI state with the TCI state for the CLI measurement resource. In some cases, receiving the control signaling at **305** includes receiving a first control message indicating the CLI measurement resource and a first CORESET pool of the set of CORESET pools; receiving a second control message indicating the CLI measurement resource and a second CORESET pool of the set of CORESET pools. The UE **115-c** may generate may a first CLI measurement of the CLI measurement resource using a first receive beam associated with a first TCI state associated with the first CORESET pool and may generate a second CLI measurement of the CLI measurement resource using a second receive beam associated with a second TCI state associated with the second CORESET pool. The message at **320** may indicate the first CLI measurement and the second CLI measurement.

(95) In some cases, receiving the control signaling at **305** includes, receiving an RRC message configuring the CLI measurement resource and the TCI state, and the CLI measurement resource is a periodic CLI measurement resource.

(96) In some cases, the CLI measurement resource is a layer one sounding reference signal resource or a layer one received signal strength indicator resource.

(97) FIG. 4 shows a block diagram **400** of a device **405** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The device **405** may be an example of aspects of a UE **115** as described herein. The device **405** may include a receiver **410**, a transmitter **415**, and a communications manager **420**. The device **405** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(98) The receiver **410** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to unified TCI state indication for CLI measurement). Information may be passed on to other components of the device **405**. The receiver **410** may utilize a single antenna or a set of multiple antennas.

(99) The transmitter **415** may provide a means for transmitting signals generated by other components of the device **405**. For example, the transmitter **415** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to unified TCI state indication for CLI measurement). In some examples, the transmitter **415** may be co-located with a receiver **410** in a transceiver module. The transmitter **415** may utilize a single antenna or a set of multiple antennas.

(100) The communications manager **420**, the receiver **410**, the transmitter **415**, or various combinations thereof or various components thereof may be examples of means for performing various aspects of unified TCI state indication for CLI measurement as described herein. For example, the communications manager **420**, the receiver **410**, the transmitter **415**, or various combinations or components thereof may support a method for performing one or more of the functions described herein.

(101) In some examples, the communications manager **420**, the receiver **410**, the transmitter **415**, or various combinations or components thereof may be implemented in hardware (e.g., in communications management circuitry). The hardware may include a processor, a digital signal processor (DSP), a central processing unit (CPU), an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA) or other programmable logic device, a microcontroller, discrete gate or transistor logic, discrete hardware components, or any combination thereof configured as or otherwise supporting a means for performing the functions described in the present disclosure. In some examples, a processor and memory coupled with the processor may be configured to perform one or more of the functions described herein (e.g., by executing, by the processor, instructions stored in the memory).

(102) Additionally, or alternatively, in some examples, the communications manager **420**, the receiver **410**, the transmitter **415**, or various combinations or components thereof may be implemented in code (e.g., as communications management software or firmware) executed by a processor. If implemented in code executed by a processor, the functions of the communications manager **420**, the receiver **410**, the transmitter **415**, or various combinations or components thereof may be performed by a general-purpose processor, a DSP, a CPU, an ASIC, an FPGA, a microcontroller, or any combination of these or other programmable logic devices (e.g., configured as or otherwise supporting a means for performing the functions described in the present disclosure).

(103) In some examples, the communications manager **420** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in

cooperation with the receiver **410**, the transmitter **415**, or both. For example, the communications manager **420** may receive information from the receiver **410**, send information to the transmitter **415**, or be integrated in combination with the receiver **410**, the transmitter **415**, or both to obtain information, output information, or perform various other operations as described herein.

(104) The communications manager **420** may support wireless communications at a UE in accordance with examples as disclosed herein. For example, the communications manager **420** may be configured as or otherwise support a means for receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource. The communications manager **420** may be configured as or otherwise support a means for generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state. The communications manager **420** may be configured as or otherwise support a means for transmitting, to the network entity, a message indicating the CLI measurement.

(105) By including or configuring the communications manager **420** in accordance with examples as described herein, the device **405** (e.g., a processor controlling or otherwise coupled with the receiver **410**, the transmitter **415**, the communications manager **420**, or a combination thereof) may support techniques for more efficient utilization of communication resources by enabling enhanced CLI reporting.

(106) FIG. 5 shows a block diagram **500** of a device **505** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The device **505** may be an example of aspects of a device **405** or a UE **115** as described herein. The device **505** may include a receiver **510**, a transmitter **515**, and a communications manager **520**. The device **505** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(107) The receiver **510** may provide a means for receiving information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to unified TCI state indication for CLI measurement). Information may be passed on to other components of the device **505**. The receiver **510** may utilize a single antenna or a set of multiple antennas.

(108) The transmitter **515** may provide a means for transmitting signals generated by other components of the device **505**. For example, the transmitter **515** may transmit information such as packets, user data, control information, or any combination thereof associated with various information channels (e.g., control channels, data channels, information channels related to unified TCI state indication for CLI measurement). In some examples, the transmitter **515** may be co-located with a receiver **510** in a transceiver module. The transmitter **515** may utilize a single antenna or a set of multiple antennas.

(109) The device **505**, or various components thereof, may be an example of means for performing various aspects of unified TCI state indication for CLI measurement as described herein. For example, the communications manager **520** may include a CLI measurement configuration manager **525**, a CLI measurement generation manager **530**, a CLI measurement manager **535**, or any combination thereof. The communications manager **520** may be an example of aspects of a communications manager **420** as described herein. In some examples, the communications manager **520**, or various components thereof, may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **510**, the transmitter **515**, or both. For example, the communications manager **520** may receive information from the receiver **510**, send information to the transmitter **515**, or be integrated in combination with the receiver **510**, the transmitter **515**, or both to obtain information, output information, or perform various other operations as described herein.

(110) The communications manager **520** may support wireless communications at a UE in accordance with examples as disclosed herein. The CLI measurement configuration manager **525**

may be configured as or otherwise support a means for receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource. The CLI measurement generation manager **530** may be configured as or otherwise support a means for generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state. The CLI measurement manager **535** may be configured as or otherwise support a means for transmitting, to the network entity, a message indicating the CLI measurement.

(111) FIG. **6** shows a block diagram **600** of a communications manager **620** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The communications manager **620** may be an example of aspects of a communications manager **420**, a communications manager **520**, or both, as described herein. The communications manager **620**, or various components thereof, may be an example of means for performing various aspects of unified TCI state indication for CLI measurement as described herein. For example, the communications manager **620** may include a CLI measurement configuration manager **625**, a CLI measurement generation manager **630**, a CLI measurement manager **635**, a TCI state association manager **640**, a DCI manager **645**, a CORESET TCI manager **650**, an RRC manager **655**, a unified TCI state manager **660**, a CORESET TCI state manager **665**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(112) The communications manager **620** may support wireless communications at a UE in accordance with examples as disclosed herein. The CLI measurement configuration manager **625** may be configured as or otherwise support a means for receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource. The CLI measurement generation manager **630** may be configured as or otherwise support a means for generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state. The CLI measurement manager **635** may be configured as or otherwise support a means for transmitting, to the network entity, a message indicating the CLI measurement.

(113) In some examples, to support receiving the control signaling, the TCI state association manager **640** may be configured as or otherwise support a means for receiving an indication that the TCI state is associated with a downlink channel for the UE.

(114) In some examples, to support receiving the indication that the TCI state is associated with the downlink channel for the UE, the unified TCI state manager **660** may be configured as or otherwise support a means for receiving an indication of a unified TCI state.

(115) In some examples, the DCI manager **645** may be configured as or otherwise support a means for receiving a downlink control information message indicating the TCI state.

(116) In some examples, the CORESET TCI manager **650** may be configured as or otherwise support a means for receiving a control message indicating a set of TCI states associated with a set of CORESET pools, where each CORESET pool of the set of CORESET pools corresponds to one or more CORESETS. In some examples, the TCI state association manager **640** may be configured as or otherwise support a means for receiving, with the control signaling, an indication of a CORESET pool of the set of CORESET pool, where the TCI state is based on the indication of the CORESET.

(117) In some examples, to support receiving the indication of the CORESET pool of the set of CORESET pools, the CORESET TCI state manager **665** may be configured as or otherwise support a means for receiving the control signaling from a TRP associated with the CORESET pool, where each CORESET pool of the set of CORESET pools is associated with a respective TRP.

(118) In some examples, to support receiving the control signaling, the TCI state association manager **640** may be configured as or otherwise support a means for receiving a first control message indicating the CLI measurement resource and a first CORESET pool of the set of

CORESET pools and a second control message indicating the CLI measurement resource and a second CORESET pool of the set of CORESET pools. The CLI measurement generation manager **630** may be configured as or otherwise support a means for generating a first CLI measurement of the CLI measurement resource using a first receive beam associated with a first TCI state associated with the first CORESET pool and generating a second CLI measurement of the CLI measurement resource using a second receive beam associated with a second TCI state associated with the second CORESET pool, and the message indicates the first CLI measurement and the second CLI measurement.

(119) In some examples, the CLI measurement configuration manager **625** may be configured as or otherwise support a means for receiving a control message indicating a second TCI state associated with a set of CLI measurement resources including the CLI measurement resource, where the CLI measurement resource includes an aperiodic or a semi-periodic CLI measurement resource. In some examples, the CLI measurement configuration manager **625** may be configured as or otherwise support a means for receiving, with the control signaling, an indication to overwrite the second TCI state with the TCI state for the CLI measurement resource.

(120) In some examples, to support receiving the control signaling, the RRC manager **655** may be configured as or otherwise support a means for receiving a radio resource control message configuring the CLI measurement resource and the TCI state, where the CLI measurement resource includes a periodic CLI measurement resource.

(121) In some examples, the CLI measurement resource includes a layer one sounding reference signal resource or a layer one received signal strength indicator resource.

(122) FIG. 7 shows a diagram of a system **700** including a device **705** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The device **705** may be an example of or include the components of a device **405**, a device **505**, or a UE **115** as described herein. The device **705** may communicate (e.g., wirelessly) with one or more network entities **105**, one or more UEs **115**, or any combination thereof. The device **705** may include components for bi-directional voice and data communications including components for transmitting and receiving communications, such as a communications manager **720**, an input/output (I/O) controller **710**, a transceiver **715**, an antenna **725**, a memory **730**, code **735**, and a processor **740**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **745**).

(123) The I/O controller **710** may manage input and output signals for the device **705**. The I/O controller **710** may also manage peripherals not integrated into the device **705**. In some cases, the I/O controller **710** may represent a physical connection or port to an external peripheral. In some cases, the I/O controller **710** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. Additionally, or alternatively, the I/O controller **710** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, the I/O controller **710** may be implemented as part of a processor, such as the processor **740**. In some cases, a user may interact with the device **705** via the I/O controller **710** or via hardware components controlled by the I/O controller **710**.

(124) In some cases, the device **705** may include a single antenna **725**. However, in some other cases, the device **705** may have more than one antenna **725**, which may be capable of concurrently transmitting or receiving multiple wireless transmissions. The transceiver **715** may communicate bi-directionally, via the one or more antennas **725**, wired, or wireless links as described herein. For example, the transceiver **715** may represent a wireless transceiver and may communicate bi-directionally with another wireless transceiver. The transceiver **715** may also include a modem to modulate the packets, to provide the modulated packets to one or more antennas **725** for transmission, and to demodulate packets received from the one or more antennas **725**. The

transceiver **715**, or the transceiver **715** and one or more antennas **725**, may be an example of a transmitter **415**, a transmitter **515**, a receiver **410**, a receiver **510**, or any combination thereof or component thereof, as described herein.

(125) The memory **730** may include random access memory (RAM) and read-only memory (ROM). The memory **730** may store computer-readable, computer-executable code **735** including instructions that, when executed by the processor **740**, cause the device **705** to perform various functions described herein. The code **735** may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. In some cases, the code **735** may not be directly executable by the processor **740** but may cause a computer (e.g., when compiled and executed) to perform functions described herein. In some cases, the memory **730** may contain, among other things, a basic I/O system (BIOS) which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(126) The processor **740** may include an intelligent hardware device (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **740** may be configured to operate a memory array using a memory controller. In some other cases, a memory controller may be integrated into the processor **740**. The processor **740** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **730**) to cause the device **705** to perform various functions (e.g., functions or tasks supporting unified TCI state indication for CLI measurement). For example, the device **705** or a component of the device **705** may include a processor **740** and memory **730** coupled with or to the processor **740**, the processor **740** and memory **730** configured to perform various functions described herein.

(127) The communications manager **720** may support wireless communications at a UE in accordance with examples as disclosed herein. For example, the communications manager **720** may be configured as or otherwise support a means for receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource. The communications manager **720** may be configured as or otherwise support a means for generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state. The communications manager **720** may be configured as or otherwise support a means for transmitting, to the network entity, a message indicating the CLI measurement.

(128) By including or configuring the communications manager **720** in accordance with examples as described herein, the device **705** may support techniques for improved communication reliability and more efficient utilization of communication resources by enabling enhanced CLI reporting.

(129) In some examples, the communications manager **720** may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the transceiver **715**, the one or more antennas **725**, or any combination thereof. Although the communications manager **720** is illustrated as a separate component, in some examples, one or more functions described with reference to the communications manager **720** may be supported by or performed by the processor **740**, the memory **730**, the code **735**, or any combination thereof. For example, the code **735** may include instructions executable by the processor **740** to cause the device **705** to perform various aspects of unified TCI state indication for CLI measurement as described herein, or the processor **740** and the memory **730** may be otherwise configured to perform or support such operations.

(130) FIG. **8** shows a block diagram **800** of a device **805** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The device **805** may be an example of aspects of a network entity **105** as described herein. The device **805** may include a receiver **810**, a transmitter **815**, and a communications manager **820**. The device **805** may also include a processor. Each of these components may be in communication with one another

(e.g., via one or more buses).

(131) The receiver **810** may provide a means for obtaining (e.g., receiving, determining, identifying) information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). Information may be passed on to other components of the device **805**. In some examples, the receiver **810** may support obtaining information by receiving signals via one or more antennas. Additionally, or alternatively, the receiver **810** may support obtaining information by receiving signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof.

(132) The transmitter **815** may provide a means for outputting (e.g., transmitting, providing, conveying, sending) information generated by other components of the device **805**. For example, the transmitter **815** may output information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). In some examples, the transmitter **815** may support outputting information by transmitting signals via one or more antennas. Additionally, or alternatively, the transmitter **815** may support outputting information by transmitting signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof. In some examples, the transmitter **815** and the receiver **810** may be co-located in a transceiver, which may include or be coupled with a modem.

(133) The communications manager **820**, the receiver **810**, the transmitter **815**, or various combinations thereof or various components thereof may be examples of means for performing various aspects of unified TCI state indication for CLI measurement as described herein. For example, the communications manager **820**, the receiver **810**, the transmitter **815**, or various combinations or components thereof may support a method for performing one or more of the functions described herein.

(134) In some examples, the communications manager **820**, the receiver **810**, the transmitter **815**, or various combinations or components thereof may be implemented in hardware (e.g., in communications management circuitry). The hardware may include a processor, a DSP, a CPU, an ASIC, an FPGA or other programmable logic device, a microcontroller, discrete gate or transistor logic, discrete hardware components, or any combination thereof configured as or otherwise supporting a means for performing the functions described in the present disclosure. In some examples, a processor and memory coupled with the processor may be configured to perform one or more of the functions described herein (e.g., by executing, by the processor, instructions stored in the memory).

(135) Additionally, or alternatively, in some examples, the communications manager **820**, the receiver **810**, the transmitter **815**, or various combinations or components thereof may be implemented in code (e.g., as communications management software or firmware) executed by a processor. If implemented in code executed by a processor, the functions of the communications manager **820**, the receiver **810**, the transmitter **815**, or various combinations or components thereof may be performed by a general-purpose processor, a DSP, a CPU, an ASIC, an FPGA, a microcontroller, or any combination of these or other programmable logic devices (e.g., configured as or otherwise supporting a means for performing the functions described in the present disclosure).

(136) In some examples, the communications manager **820** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **810**, the transmitter **815**, or both. For example, the communications manager **820** may receive information from the receiver **810**, send information to the transmitter **815**, or be integrated in combination with the receiver **810**, the transmitter **815**, or both to obtain

information, output information, or perform various other operations as described herein.

(137) For example, the communications manager **820** may be configured as or otherwise support a means for transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource. The communications manager **820** may be configured as or otherwise support a means for receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.

(138) By including or configuring the communications manager **820** in accordance with examples as described herein, the device **805** (e.g., a processor controlling or otherwise coupled with the receiver **810**, the transmitter **815**, the communications manager **820**, or a combination thereof) may support techniques for more efficient utilization of communication resources by enabling enhanced CLI reporting.

(139) FIG. **9** shows a block diagram **900** of a device **905** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The device **905** may be an example of aspects of a device **805** or a network entity **105** as described herein. The device **905** may include a receiver **910**, a transmitter **915**, and a communications manager **920**. The device **905** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(140) The receiver **910** may provide a means for obtaining (e.g., receiving, determining, identifying) information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). Information may be passed on to other components of the device **905**. In some examples, the receiver **910** may support obtaining information by receiving signals via one or more antennas. Additionally, or alternatively, the receiver **910** may support obtaining information by receiving signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof.

(141) The transmitter **915** may provide a means for outputting (e.g., transmitting, providing, conveying, sending) information generated by other components of the device **905**. For example, the transmitter **915** may output information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). In some examples, the transmitter **915** may support outputting information by transmitting signals via one or more antennas. Additionally, or alternatively, the transmitter **915** may support outputting information by transmitting signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof. In some examples, the transmitter **915** and the receiver **910** may be co-located in a transceiver, which may include or be coupled with a modem.

(142) The device **905**, or various components thereof, may be an example of means for performing various aspects of unified TCI state indication for CLI measurement as described herein. For example, the communications manager **920** may include a CLI measurement configuration manager **925**, a CLI measurement manager **930**, or any combination thereof. The communications manager **920** may be an example of aspects of a communications manager **820** as described herein. In some examples, the communications manager **920**, or various components thereof, may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **910**, the transmitter **915**, or both. For example, the communications manager **920** may receive information from the receiver **910**, send information to the transmitter **915**, or be integrated in combination with the receiver **910**, the transmitter **915**, or both to obtain information, output information, or perform various other operations as described herein.

(143) The CLI measurement configuration manager **925** may be configured as or otherwise support a means for transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource. The CLI measurement manager **930** may be configured as or otherwise support a means for receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.

(144) FIG. **10** shows a block diagram **1000** of a communications manager **1020** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The communications manager **1020** may be an example of aspects of a communications manager **820**, a communications manager **920**, or both, as described herein. The communications manager **1020**, or various components thereof, may be an example of means for performing various aspects of unified TCI state indication for CLI measurement as described herein. For example, the communications manager **1020** may include a CLI measurement configuration manager **1025**, a CLI measurement manager **1030**, a TCI state association manager **1035**, a DCI manager **1040**, a CORESET TCI manager **1045**, an RRC manager **1050**, a unified TCI state manager **1055**, a CORESET TCI state manager **1060**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses) which may include communications within a protocol layer of a protocol stack, communications associated with a logical channel of a protocol stack (e.g., between protocol layers of a protocol stack, within a device, component, or virtualized component associated with a network entity **105**, between devices, components, or virtualized components associated with a network entity **105**), or any combination thereof.

(145) The CLI measurement configuration manager **1025** may be configured as or otherwise support a means for transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource. The CLI measurement manager **1030** may be configured as or otherwise support a means for receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.

(146) In some examples, to support transmitting the control signaling, the TCI state association manager **1035** may be configured as or otherwise support a means for transmitting an indication that the TCI state is associated with a downlink channel for the UE.

(147) In some examples, to support transmitting the indication that the TCI state is associated with the downlink channel for the UE, the unified TCI state manager **1055** may be configured as or otherwise support a means for transmitting an indication of a unified TCI state.

(148) In some examples, the DCI manager **1040** may be configured as or otherwise support a means for transmitting, to the UE, a downlink control information message indicating the TCI state.

(149) In some examples, the CORESET TCI manager **1045** may be configured as or otherwise support a means for transmitting, to the UE, a control message indicating a set of TCI states associated with a set of CORESETs pools, where each CORESET pool of the set of CORESET pools corresponds to one or more CORESETs. In some examples, the TCI state association manager **1035** may be configured as or otherwise support a means for transmitting, with the control signaling, an indication of a CORESET pool of the set of CORESET pools, where the TCI state is based on the indication of the CORESET pool.

(150) In some examples, to support transmitting the indication of the CORESET pool of the set of CORESET pools, the CORESET TCI state manager **1060** may be configured as or otherwise support a means for transmitting the control signaling from a TRP associated with the CORESET pool, where each CORESET pool of the set of CORESET pools is associated with a respective TRP.

(151) In some examples, to support transmitting the control signaling, the TCI state association

manager **1035** may be configured as or otherwise support a means for transmitting a first control message indicating the CLI measurement resource and a first CORESET pool of the set of CORESET pools and a second control message indicating the CLI measurement resource and a second CORESET pool of the set of CORESET pools, and the message indicates a first CLI measurement measured at the UE using a first beam associated with a first TCI state associated with the first CORESET pool and a second CLI measurement measured at the UE using a second beam associated with a second TCI state associated with the second CORESET pool.

(152) In some examples, the CLI measurement configuration manager **1025** may be configured as or otherwise support a means for transmitting, to the UE, a control message indicating a second TCI state associated with a set of CLI measurement resources including the CLI measurement resource, where the CLI measurement resource includes an aperiodic or a semi-periodic CLI measurement resource. In some examples, the CLI measurement configuration manager **1025** may be configured as or otherwise support a means for transmitting, with the control signaling, an indication to overwrite the second TCI state with the TCI state for the CLI measurement resource.

(153) In some examples, to support transmitting the control signaling, the RRC manager **1050** may be configured as or otherwise support a means for transmitting a radio resource control message configuring the CLI measurement resource and the TCI state, where the CLI measurement resource includes a periodic CLI measurement resource.

(154) In some examples, the CLI measurement resource includes a layer one sounding reference signal resource or a layer one received signal strength indicator resource.

(155) FIG. **11** shows a diagram of a system **1100** including a device **1105** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The device **1105** may be an example of or include the components of a device **805**, a device **905**, or a network entity **105** as described herein. The device **1105** may communicate with one or more network entities **105**, one or more UEs **115**, or any combination thereof, which may include communications over one or more wired interfaces, over one or more wireless interfaces, or any combination thereof. The device **1105** may include components that support outputting and obtaining communications, such as a communications manager **1120**, a transceiver **1110**, an antenna **1115**, a memory **1125**, code **1130**, and a processor **1135**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **1140**).

(156) The transceiver **1110** may support bi-directional communications via wired links, wireless links, or both as described herein. In some examples, the transceiver **1110** may include a wired transceiver and may communicate bi-directionally with another wired transceiver. Additionally, or alternatively, in some examples, the transceiver **1110** may include a wireless transceiver and may communicate bi-directionally with another wireless transceiver. In some examples, the device **1105** may include one or more antennas **1115**, which may be capable of transmitting or receiving wireless transmissions (e.g., concurrently). The transceiver **1110** may also include a modem to modulate signals, to provide the modulated signals for transmission (e.g., by one or more antennas **1115**, by a wired transmitter), to receive modulated signals (e.g., from one or more antennas **1115**, from a wired receiver), and to demodulate signals. The transceiver **1110**, or the transceiver **1110** and one or more antennas **1115** or wired interfaces, where applicable, may be an example of a transmitter **815**, a transmitter **915**, a receiver **810**, a receiver **910**, or any combination thereof or component thereof, as described herein. In some examples, the transceiver may be operable to support communications via one or more communications links (e.g., a communication link **125**, a backhaul communication link **120**, a midhaul communication link **162**, a fronthaul communication link **168**).

(157) The memory **1125** may include RAM and ROM. The memory **1125** may store computer-readable, computer-executable code **1130** including instructions that, when executed by the processor **1135**, cause the device **1105** to perform various functions described herein. The code

1130 may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. In some cases, the code **1130** may not be directly executable by the processor **1135** but may cause a computer (e.g., when compiled and executed) to perform functions described herein. In some cases, the memory **1125** may contain, among other things, a BIOS which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(158) The processor **1135** may include an intelligent hardware device (e.g., a general-purpose processor, a DSP, an ASIC, a CPU, an FPGA, a microcontroller, a programmable logic device, discrete gate or transistor logic, a discrete hardware component, or any combination thereof). In some cases, the processor **1135** may be configured to operate a memory array using a memory controller. In some other cases, a memory controller may be integrated into the processor **1135**. The processor **1135** may be configured to execute computer-readable instructions stored in a memory (e.g., the memory **1125**) to cause the device **1105** to perform various functions (e.g., functions or tasks supporting unified TCI state indication for CLI measurement). For example, the device **1105** or a component of the device **1105** may include a processor **1135** and memory **1125** coupled with the processor **1135**, the processor **1135** and memory **1125** configured to perform various functions described herein. The processor **1135** may be an example of a cloud-computing platform (e.g., one or more physical nodes and supporting software such as operating systems, virtual machines, or container instances) that may host the functions (e.g., by executing code **1130**) to perform the functions of the device **1105**.

(159) In some examples, a bus **1140** may support communications of (e.g., within) a protocol layer of a protocol stack. In some examples, a bus **1140** may support communications associated with a logical channel of a protocol stack (e.g., between protocol layers of a protocol stack), which may include communications performed within a component of the device **1105**, or between different components of the device **1105** that may be co-located or located in different locations (e.g., where the device **1105** may refer to a system in which one or more of the communications manager **1120**, the transceiver **1110**, the memory **1125**, the code **1130**, and the processor **1135** may be located in one of the different components or divided between different components).

(160) In some examples, the communications manager **1120** may manage aspects of communications with a core network **130** (e.g., via one or more wired or wireless backhaul links). For example, the communications manager **1120** may manage the transfer of data communications for client devices, such as one or more UEs **115**. In some examples, the communications manager **1120** may manage communications with other network entities **105**, and may include a controller or scheduler for controlling communications with UEs **115** in cooperation with other network entities **105**. In some examples, the communications manager **1120** may support an X2 interface within an LTE/LTE-A wireless communications network technology to provide communication between network entities **105**.

(161) For example, the communications manager **1120** may be configured as or otherwise support a means for transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource. The communications manager **1120** may be configured as or otherwise support a means for receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.

(162) By including or configuring the communications manager **1120** in accordance with examples as described herein, the device **1105** may support techniques for improved communication reliability and more efficient utilization of communication resources by enabling enhanced CLI reporting.

(163) In some examples, the communications manager **1120** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the transceiver **1110**, the one or more antennas **1115** (e.g., where applicable), or

any combination thereof. Although the communications manager **1120** is illustrated as a separate component, in some examples, one or more functions described with reference to the communications manager **1120** may be supported by or performed by the processor **1135**, the memory **1125**, the code **1130**, the transceiver **1110**, or any combination thereof. For example, the code **1130** may include instructions executable by the processor **1135** to cause the device **1105** to perform various aspects of unified TCI state indication for CLI measurement as described herein, or the processor **1135** and the memory **1125** may be otherwise configured to perform or support such operations.

(164) FIG. **12** shows a flowchart illustrating a method **1200** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The operations of the method **1200** may be implemented by a UE or its components as described herein. For example, the operations of the method **1200** may be performed by a UE **115** as described with reference to FIGS. **1** through **7**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the described functions. Additionally, or alternatively, the UE may perform aspects of the described functions using special-purpose hardware.

(165) At **1205**, the method may include receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource. The operations of **1205** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1205** may be performed by a CLI measurement configuration manager **625** as described with reference to FIG. **6**.

(166) At **1210**, the method may include generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state. The operations of **1210** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1210** may be performed by a CLI measurement generation manager **630** as described with reference to FIG. **6**.

(167) At **1215**, the method may include transmitting, to the network entity, a message indicating the CLI measurement. The operations of **1215** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1215** may be performed by a CLI measurement manager **635** as described with reference to FIG. **6**.

(168) FIG. **13** shows a flowchart illustrating a method **1300** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The operations of the method **1300** may be implemented by a UE or its components as described herein. For example, the operations of the method **1300** may be performed by a UE **115** as described with reference to FIGS. **1** through **7**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the described functions. Additionally, or alternatively, the UE may perform aspects of the described functions using special-purpose hardware.

(169) At **1305**, the method may include receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource. The operations of **1305** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1305** may be performed by a CLI measurement configuration manager **625** as described with reference to FIG. **6**.

(170) At **1310**, the method may include receiving an indication that the TCI state is associated with a downlink channel for the UE. The operations of **1310** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1310** may be performed by a TCI state association manager **640** as described with reference to FIG. **6**.

(171) At **1315**, the method may include generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state. The operations of **1315** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the

operations of **1315** may be performed by a CLI measurement generation manager **630** as described with reference to FIG. **6**.

(172) At **1320**, the method may include transmitting, to the network entity, a message indicating the CLI measurement. The operations of **1320** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1320** may be performed by a CLI measurement manager **635** as described with reference to FIG. **6**.

(173) FIG. **14** shows a flowchart illustrating a method **1400** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The operations of the method **1400** may be implemented by a UE or its components as described herein. For example, the operations of the method **1400** may be performed by a UE **115** as described with reference to FIGS. **1** through **7**. In some examples, a UE may execute a set of instructions to control the functional elements of the UE to perform the described functions. Additionally, or alternatively, the UE may perform aspects of the described functions using special-purpose hardware.

(174) At **1405**, the method may include receiving a control message indicating a set of TCI states associated with a set of CORESET pools. The operations of **1405** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1405** may be performed by a CORESET TCI manager **650** as described with reference to FIG. **6**.

(175) At **1410**, the method may include receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource. The operations of **1410** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1410** may be performed by a CLI measurement configuration manager **625** as described with reference to FIG. **6**.

(176) At **1415**, the method may include receiving, with the control signaling, an indication of a CORESET pool of the set of CORESET pools, where the TCI state is based on the indication of the CORESET pool. The operations of **1415** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1415** may be performed by a TCI state association manager **640** as described with reference to FIG. **6**.

(177) At **1420**, the method may include generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state. The operations of **1420** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1420** may be performed by a CLI measurement generation manager **630** as described with reference to FIG. **6**.

(178) At **1425**, the method may include transmitting, to the network entity, a message indicating the CLI measurement. The operations of **1425** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1425** may be performed by a CLI measurement manager **635** as described with reference to FIG. **6**.

(179) FIG. **15** shows a flowchart illustrating a method **1500** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The operations of the method **1500** may be implemented by a network entity or its components as described herein. For example, the operations of the method **1500** may be performed by a network entity as described with reference to FIGS. **1** through **3** and **8** through **11**. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

(180) At **1505**, the method may include transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource. The operations of **1505** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1505** may be performed by a CLI measurement configuration manager **1025** as described with reference to FIG. **10**.

(181) At **1510**, the method may include receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state. The operations of **1510** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1510** may be performed by a CLI measurement manager **1030** as described with reference to FIG. **10**.

(182) FIG. **16** shows a flowchart illustrating a method **1600** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The operations of the method **1600** may be implemented by a network entity or its components as described herein. For example, the operations of the method **1600** may be performed by a network entity as described with reference to FIGS. **1** through **3** and **8** through **11**. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

(183) At **1605**, the method may include transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource. The operations of **1605** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1605** may be performed by a CLI measurement configuration manager **1025** as described with reference to FIG. **10**.

(184) At **1610**, the method may include transmitting an indication that the TCI state is associated with a downlink channel for the UE. The operations of **1610** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1610** may be performed by a TCI state association manager **1035** as described with reference to FIG. **10**.

(185) At **1615**, the method may include receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state. The operations of **1615** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1615** may be performed by a CLI measurement manager **1030** as described with reference to FIG. **10**.

(186) FIG. **17** shows a flowchart illustrating a method **1700** that supports unified TCI state indication for CLI measurement in accordance with one or more aspects of the present disclosure. The operations of the method **1700** may be implemented by a network entity or its components as described herein. For example, the operations of the method **1700** may be performed by a network entity as described with reference to FIGS. **1** through **3** and **8** through **11**. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

(187) At **1705**, the method may include transmitting, to the UE, a control message indicating a set of TCI states associated with a set of CORESET pools. The operations of **1705** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1705** may be performed by a CORESET TCI manager **1045** as described with reference to FIG. **10**.

(188) At **1710**, the method may include transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to apply for CLI measurement in the CLI measurement resource. The operations of **1710** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1710** may be performed by a CLI measurement configuration manager **1025** as described with reference to FIG. **10**.

(189) At **1715**, the method may include transmitting, with the control signaling, an indication of a CORESET pool of the set of CORESET pools, where the TCI state is based on the indication of the CORESET pool. The operations of **1715** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1715** may be performed by a TCI state association manager **1035** as described with reference to FIG. **10**.

(190) At **1720**, the method may include receiving, from the UE, a message indicating a CLI

measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state. The operations of **1720** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1720** may be performed by a CLI measurement manager **1030** as described with reference to FIG. **10**.

(191) The following provides an overview of aspects of the present disclosure:

(192) Aspect 1: A method for wireless communications at a UE, comprising: receiving, from a network entity, control signaling indicating a CLI measurement resource and a TCI state the UE is to apply for CLI measurement in the CLI measurement resource; generating a CLI measurement of the CLI measurement resource using a receive beam associated with the TCI state; and transmitting, to the network entity, a message indicating the CLI measurement.

(193) Aspect 2: The method of aspect 1, wherein receiving the control signaling comprises: receiving an indication that the TCI state is associated with a downlink channel for the UE.

(194) Aspect 3: The method of aspect 2, wherein receiving the indication that the TCI state is associated with the downlink channel for the UE comprises: receiving an indication of a unified TCI state.

(195) Aspect 4: The method of any of aspects 1 through 3, further comprising: receiving a downlink control information message indicating the TCI state.

(196) Aspect 5: The method of any of aspects 1 through 4, further comprising: receiving a control message indicating a set of TCI states associated with a set of CORESET pools, wherein each CORESET pool of the set of CORESET pools corresponds to one or more CORESETs; and receiving, with the control signaling, an indication of a CORESET pool of the set of CORESET pools, wherein the TCI state is based at least in part on the indication of the CORESET pool.

(197) Aspect 6: The method of aspect 5, wherein receiving the indication of the CORESET pool of the set of CORESET pools comprises: receiving the control signaling from a TRP associated with the CORESET pool, wherein each CORESET pool of the set of CORESET pools is associated with a respective TRP.

(198) Aspect 7: The method of any of aspects 5 through 6, wherein receiving the control signaling comprises: receiving a first control message indicating the CLI measurement resource and a first CORESET pool of the set of CORESET pools; and receiving a second control message indicating the CLI measurement resource and a second CORESET pool of the set of CORESET pools; and further comprising: generating a first CLI measurement of the CLI measurement resource using a first receive beam associated with a first TCI state associated with the first CORESET pool and generating a second CLI measurement of the CLI measurement resource using a second receive beam associated with a second TCI state associated with the second CORESET pool, wherein the message indicates the first CLI measurement and the second CLI measurement.

(199) Aspect 8: The method of any of aspects 1 through 7, further comprising: receiving a control message indicating a second TCI state associated with a set of CLI measurement resources comprising the CLI measurement resource, wherein the CLI measurement resource comprises an aperiodic or a semi-periodic CLI measurement resource; and receiving, with the control signaling, an indication to overwrite the second TCI state with the TCI state for the CLI measurement resource.

(200) Aspect 9: The method of any of aspects 1 through 8, wherein receiving the control signaling comprises: receiving a radio resource control message configuring the CLI measurement resource and the TCI state, wherein the CLI measurement resource comprises a periodic CLI measurement resource.

(201) Aspect 10: The method of any of aspects 1 through 9, wherein the CLI measurement resource comprises a layer one sounding reference signal resource or a layer one received signal strength indicator resource.

(202) Aspect 11: A method for wireless communications at a network entity comprising: transmitting, to a UE, control signaling indicating a CLI measurement resource and a TCI state to

apply for CLI measurement in the CLI measurement resource; and receiving, from the UE, a message indicating a CLI measurement of the CLI measurement resource measured at the UE using a beam associated with the TCI state.

(203) Aspect 12: The method of aspect 11, wherein transmitting the control signaling comprises: transmitting an indication that the TCI state is associated with a downlink channel for the UE.

(204) Aspect 13: The method of aspect 12, wherein transmitting the indication that the TCI state is associated with the downlink channel for the UE comprises: transmitting an indication of a unified TCI state.

(205) Aspect 14: The method of any of aspects 11 through 13, further comprising: transmitting, to the UE, a downlink control information message indicating the TCI state.

(206) Aspect 15: The method of any of aspects 11 through 14, further comprising: transmitting, to the UE, a control message indicating a set of TCI states associated with a set of CORESET pools, wherein each CORESET pool of the set of CORESET pools corresponds to one or more CORESETs; and transmitting, with the control signaling, an indication of a CORESET pool of the set of CORESET pools, wherein the TCI state is based at least in part on the indication of the CORESET pool.

(207) Aspect 16: The method of aspect 15, wherein transmitting the indication of the CORESET pool of the set of CORESET pools comprises: transmitting the control signaling from a TRP associated with the CORESET pool, wherein each CORESET pool of the set of CORESET pools is associated with a respective TRP.

(208) Aspect 17: The method of any of aspects 15 through 16, wherein transmitting the indication of the CORESET pool of the set of CORESET pools comprises: transmitting a first control message indicating the CLI measurement resource and a first CORESET pool of the set of CORESET pools; and transmitting a second control message indicating the CLI measurement resource and a second CORESET pool of the set of CORESET pools, wherein the message indicates a first CLI measurement measured at the UE using a first beam associated with a first TCI state associated with the first CORESET pool and a second CLI measurement measured at the UE using a second beam associated with a second TCI state associated with the second CORESET pool.

(209) Aspect 18: The method of any of aspects 11 through 17, further comprising: transmitting, to the UE, a control message indicating a second TCI state associated with a set of CLI measurement resources comprising the CLI measurement resource, wherein the CLI measurement resource comprises an aperiodic or a semi-periodic CLI measurement resource; and transmitting, with the control signaling, an indication to overwrite the second TCI state with the TCI state for the CLI measurement resource.

(210) Aspect 19: The method of any of aspects 11 through 18, wherein transmitting the control signaling comprises: transmitting a radio resource control message configuring the CLI measurement resource and the TCI state, wherein the CLI measurement resource comprises a periodic CLI measurement resource.

(211) Aspect 20: The method of any of aspects 11 through 19, wherein the CLI measurement resource comprises a layer one sounding reference signal resource and a layer one received signal strength indicator resource.

(212) Aspect 21: An apparatus for wireless communications at a UE, comprising a processor; memory coupled with the processor; and instructions stored in the memory and executable by the processor to cause the apparatus to perform a method of any of aspects 1 through 10.

(213) Aspect 22: An apparatus for wireless communications at a UE, comprising at least one means for performing a method of any of aspects 1 through 10.

(214) Aspect 23: A non-transitory computer-readable medium storing code for wireless communications at a UE, the code comprising instructions executable by a processor to perform a method of any of aspects 1 through 10.

(215) Aspect 24: An apparatus comprising a processor; memory coupled with the processor; and instructions stored in the memory and executable by the processor to cause the apparatus to perform a method of any of aspects 11 through 20.

(216) Aspect 25: An apparatus comprising at least one means for performing a method of any of aspects 11 through 20.

(217) Aspect 26: A non-transitory computer-readable medium storing code the code comprising instructions executable by a processor to perform a method of any of aspects 11 through 20.

(218) It should be noted that the methods described herein describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Further, aspects from two or more of the methods may be combined.

(219) Although aspects of an LTE, LTE-A, LTE-A Pro, or NR system may be described for purposes of example, and LTE, LTE-A, LTE-A Pro, or NR terminology may be used in much of the description, the techniques described herein are applicable beyond LTE, LTE-A, LTE-A Pro, or NR networks. For example, the described techniques may be applicable to various other wireless communications systems such as Ultra Mobile Broadband (UMB), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, as well as other systems and radio technologies not explicitly mentioned herein.

(220) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(221) The various illustrative blocks and components described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, a CPU, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(222) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described herein may be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

(223) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that may be accessed by a general-purpose or special-purpose computer. By way of example, and not limitation, non-transitory computer-readable media may include RAM, ROM, electrically erasable programmable ROM (EEPROM), flash memory, compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that may be used to carry or store desired program code means in the form of instructions or data structures and that may be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-

readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of computer-readable medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers.

Combinations of the above are also included within the scope of computer-readable media.

(224) As used herein, including in the claims, “or” as used in a list of items (e.g., a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an example step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(225) The term “determine” or “determining” encompasses a variety of actions and, therefore, “determining” can include calculating, computing, processing, deriving, investigating, looking up (such as via looking up in a table, a database or another data structure), ascertaining and the like. Also, “determining” can include receiving (such as receiving information), accessing (such as accessing data in a memory) and the like. Also, “determining” can include resolving, obtaining, selecting, choosing, establishing and other such similar actions.

(226) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label, or other subsequent reference label.

(227) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “example” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(228) The description herein is provided to enable a person having ordinary skill in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to a person having ordinary skill in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. An apparatus for wireless communications at a user equipment (UE), comprising: one or more processors; one or more memories coupled with the one or more processors; and instructions stored in the one or more memories and executable by the one or more processors to cause the apparatus to: receive, from a network entity, a control message that indicates a cross-link interference measurement resource, wherein the control message further indicates a transmission configuration

indicator state the UE is to apply for cross-link interference measurement in the cross-link interference measurement resource, wherein the transmission configuration indicator state is a unified transmission configuration indicator state indicative of a common beam for a first downlink channel and at least one of a second downlink channel or an uplink channel; generate a cross-link interference measurement of the cross-link interference measurement resource using a receive beam associated with the transmission configuration indicator state; and transmit, to the network entity, a message indicating the cross-link interference measurement.

2. The apparatus of claim 1, wherein the instructions to receive the control message are executable by the one or more processors to cause the apparatus to: receive an indication that the transmission configuration indicator state is associated with a downlink channel for the UE.

3. The apparatus of claim 1, wherein the control message comprises a downlink control information message.

4. The apparatus of claim 1, wherein the instructions are further executable by the one or more processors to cause the apparatus to: receive a second control message indicating a set of transmission configuration indicator states associated with a set of control resource set pools, wherein each control resource set pool of the set of control resource set pools corresponds to one or more control resource sets; and receive, with the control message, an indication of a control resource set pool of the set of control resource set pools, wherein the transmission configuration indicator state is based at least in part on the indication of the control resource set pool.

5. The apparatus of claim 4, wherein the instructions to receive the indication of the control resource set pool of the set of control resource set pools are executable by the one or more processors to cause the apparatus to: receive the control message from a transmission and reception point associated with the control resource set pool, wherein each control resource set pool of the set of control resource set pools is associated with a respective transmission and reception point.

6. The apparatus of claim 4, wherein the instructions to receive the control message are executable by the one or more processors to cause the apparatus to: receive the control message indicating the cross-link interference measurement resource and a first control resource set pool of the set of control resource set pools; and wherein the instructions are further executable by the one or more processors to cause the apparatus to: receive a third control message indicating the cross-link interference measurement resource and a second control resource set pool of the set of control resource set pools; and generate a first cross-link interference measurement of the cross-link interference measurement resource using a first receive beam associated with a first transmission configuration indicator state associated with the first control resource set pool and generate a second cross-link interference measurement of the cross-link interference measurement resource using a second receive beam associated with a second transmission configuration indicator state associated with the second control resource set pool, wherein the message indicates the first cross-link interference measurement and the second cross-link interference measurement.

7. The apparatus of claim 1, wherein the instructions are further executable by the one or more processors to cause the apparatus to: receive a second control message indicating a second transmission configuration indicator state associated with a set of cross-link interference measurement resources comprising the cross-link interference measurement resource, wherein the cross-link interference measurement resource comprises an aperiodic or a semi-periodic cross-link interference measurement resource; and receive, with the control message, an indication to overwrite the second transmission configuration indicator state with the transmission configuration indicator state for the cross-link interference measurement resource.

8. The apparatus of claim 1, wherein the control message comprises a radio resource control message, and wherein the cross-link interference measurement resource comprises a periodic cross-link interference measurement resource.

9. The apparatus of claim 1, wherein the cross-link interference measurement resource comprises a layer one sounding reference signal resource or a layer one received signal strength indicator

resource.

10. The apparatus of claim 1, wherein the first downlink channel comprises a physical downlink control channel, and wherein the second downlink channel comprises a channel state information reference signal.

11. The apparatus of claim 10, wherein the instructions to receive the control message are executable by the one or more processors to cause the apparatus to: receive an indication to update a serving beam associated with the physical downlink control channel to the receive beam associated with the transmission configuration indicator state, wherein the control message further indicates the transmission configuration indicator state the UE is to apply via indication of the update to the serving beam.

12. The apparatus of claim 1, wherein the transmission configuration indicator state is different from a second unified transmission configuration indicator state configured for a physical downlink control channel and a physical downlink shared channel for the UE.

13. An apparatus, comprising: one or more processors; one or more memories coupled with the one or more processors; and instructions stored in the one or more memories and executable by the one or more processors to cause the apparatus to: transmit, to a user equipment (UE), a control message that indicates a cross-link interference measurement resource, wherein the control message further indicates a transmission configuration indicator state the UE is to apply for cross-link interference measurement in the cross-link interference measurement resource, wherein the transmission configuration indicator state is a unified transmission configuration indicator state indicative of a common beam for a first downlink channel and at least one of a second downlink channel or an uplink channel; and receive, from the UE, a message indicating a cross-link interference measurement of the cross-link interference measurement resource measured at the UE using a beam associated with the transmission configuration indicator state.

14. The apparatus of claim 13, wherein the instructions to transmit the control message are executable by the one or more processors to cause the apparatus to: transmit an indication that the transmission configuration indicator state is associated with a downlink channel for the UE.

15. The apparatus of claim 13, wherein the control message comprises a downlink control information message indicating the transmission configuration indicator state.

16. The apparatus of claim 13, wherein the instructions are further executable by the one or more processors to cause the apparatus to: transmit, to the UE, a second control message indicating a set of transmission configuration indicator states associated with a set of control resource set pools, wherein each control resource set pool of the set of control resource set pools corresponds to one or more control resource sets; and transmit, with the control message, an indication of a control resource set pool of the set of control resource set pools, wherein the transmission configuration indicator state is based at least in part on the indication of the control resource set pool.

17. The apparatus of claim 16, wherein the instructions to transmit the indication of the control resource set pool of the set of control resource set pools are executable by the one or more processors to cause the apparatus to: transmit the control message from a transmission and reception point associated with the control resource set pool, wherein each control resource set pool of the set of control resource set pools is associated with a respective transmission and reception point.

18. The apparatus of claim 16, wherein the instructions to transmit the indication of the control resource set pool of the set of control resource set pools are executable by the one or more processors to cause the apparatus to: transmit the control message indicating the cross-link interference measurement resource and a first control resource set pool of the set of control resource set pools; and wherein the instructions are further executable to cause the apparatus to: transmit a third control message indicating the cross-link interference measurement resource and a second control resource set pool of the set of control resource set pools, wherein the message indicates a first cross-link interference measurement measured at the UE using a first beam

associated with a first transmission configuration indicator state associated with the first control resource set pool and a second cross-link interference measurement measured at the UE using a second beam associated with a second transmission configuration indicator state associated with the second control resource set pool.

19. The apparatus of claim 13, wherein the instructions are further executable by the one or more processors to cause the apparatus to: transmit, to the UE, a second control message indicating a second transmission configuration indicator state associated with a set of cross-link interference measurement resources comprising the cross-link interference measurement resource, wherein the cross-link interference measurement resource comprises an aperiodic or a semi-periodic cross-link interference measurement resource; and transmit, with the control message, an indication to overwrite the second transmission configuration indicator state with the transmission configuration indicator state for the cross-link interference measurement resource.

20. The apparatus of claim 13, wherein the control message comprises a radio resource control message, wherein the cross-link interference measurement resource comprises a periodic cross-link interference measurement resource.

21. The apparatus of claim 13, wherein the cross-link interference measurement resource comprises a layer one sounding reference signal resource and a layer one received signal strength indicator resource.

22. A method for wireless communications at a user equipment (UE), comprising: receiving, from a network entity, a control message that indicates a cross-link interference measurement resource, wherein the control message further indicates a transmission configuration indicator state the UE is to apply for cross-link interference measurement in the cross-link interference measurement resource, wherein the transmission configuration indicator state is a unified transmission configuration indicator state indicative of a common beam for a first downlink channel and at least one of a second downlink channel or an uplink channel; generating a cross-link interference measurement of the cross-link interference measurement resource using a receive beam associated with the transmission configuration indicator state; and transmitting, to the network entity, a message indicating the cross-link interference measurement.

23. The method of claim 22, wherein receiving the control message comprises: receiving an indication that the transmission configuration indicator state is associated with a downlink channel for the UE.

24. The method of claim 22, wherein the control message comprises a downlink control information message.

25. The method of claim 22, further comprising: receiving a second control message indicating a set of transmission configuration indicator states associated with a set of control resource set pools, wherein each control resource set pool of the set of control resource set pools corresponds to one or more control resource sets; and receiving, with the control message, an indication of a control resource set pool of the set of control resource set pools, wherein the transmission configuration indicator state is based at least in part on the indication of the control resource set pool.

26. The method of claim 25, wherein receiving the indication of the control resource set pool of the set of control resource set pools comprises: receiving the control message from a transmission and reception point associated with the control resource set pool, wherein each control resource set pool of the set of control resource set pools is associated with a respective transmission and reception point.

27. The method of claim 25, wherein receiving the control message comprises: receiving the control message indicating the cross-link interference measurement resource and a first control resource set pool of the set of control resource set pools; and further comprising: receiving a third control message indicating the cross-link interference measurement resource and a second control resource set pool of the set of control resource set pools; and generating a first cross-link interference measurement of the cross-link interference measurement resource using a first receive

beam associated with a first transmission configuration indicator state associated with the first control resource set pool and generating a second cross-link interference measurement of the cross-link interference measurement resource using a second receive beam associated with a second transmission configuration indicator state associated with the second control resource set pool, wherein the message indicates the first cross-link interference measurement and the second cross-link interference measurement.

28. The method of claim 22, further comprising: receiving a second control message indicating a second transmission configuration indicator state associated with a set of cross-link interference measurement resources comprising the cross-link interference measurement resource, wherein the cross-link interference measurement resource comprises an aperiodic or a semi-periodic cross-link interference measurement resource; and receiving, with the control message, an indication to overwrite the second transmission configuration indicator state with the transmission configuration indicator state for the cross-link interference measurement resource.

29. The method of claim 22, wherein the control message comprises a radio resource control message, wherein the cross-link interference measurement resource comprises a periodic cross-link interference measurement resource.

30. A method for wireless communications at a network entity comprising: transmitting, to a user equipment (UE), a control message that indicates a cross-link interference measurement resource, wherein the control message further indicates a transmission configuration indicator state the UE is to apply for cross-link interference measurement in the cross-link interference measurement resource, wherein the transmission configuration indicator state is a unified transmission configuration indicator state indicative of a common beam for a first downlink channel and at least one of a second downlink channel or an uplink channel; and receiving, from the UE, a message indicating a cross-link interference measurement of the cross-link interference measurement resource measured at the UE using a beam associated with the transmission configuration indicator state.
