

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403468
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Azersky; Vladimir et al.

Fluid connector

Abstract

Disclosed herein are cell processing systems, devices, and methods thereof. A system for cell processing may comprise a plurality of instruments each independently configured to perform one or more cell processing operations upon a cartridge, and a robot capable of moving the cartridge between each of the plurality of instruments.

Inventors: Azersky; Vladimir (San Jose, CA), Gerlinghaus; Fabian (South San Francisco, CA), Malleo; Daniele (Menlo Park, CA), Pesch; Brian Alexander (San Francisco, CA), Thakkar; Bharat S. (Campbell, CA), Toy; Wilson Wai (San Francisco, CA)

Applicant: Cellares Corporation (South San Francisco, CA)

Family ID: 75278405

Assignee: Cellares Corporation (South San Francisco, CA)

Appl. No.: 18/487884

Filed: October 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240165613 A1	May. 23, 2024

Related U.S. Application Data

continuation parent-doc US 18141329 20230428 US 11826756 child-doc US 18487884
continuation parent-doc US 17992784 20221122 US 11701654 20230718 child-doc US 18141329
continuation parent-doc US 17849422 20220624 US 11786896 20231017 child-doc US 17992784
continuation parent-doc US 17198134 20210310 US 12157119 child-doc US 17331556
division parent-doc US 17331556 20210526 US 11376587 20220705 child-doc US 17849422

Publication Classification

Int. Cl.: **B01L3/00** (20060101); **A61L2/04** (20060101); **A61L2/20** (20060101); **B01J19/00** (20060101); **C12M1/00** (20060101); **C12M1/36** (20060101); **C12M3/00** (20060101); **C12N5/00** (20060101); A61L2/08 (20060101)

U.S. Cl.:

CPC **B01L3/502715** (20130101); **A61L2/04** (20130101); **A61L2/20** (20130101); **A61L2/206** (20130101); **A61L2/208** (20130101); **B01J19/004** (20130101); **B01L13/00** (20190801); **C12M23/44** (20130101); **C12M23/50** (20130101); **C12M41/48** (20130101); **C12N5/00** (20130101); **C12N5/0081** (20130101); A61L2/08 (20130101); A61L2202/11 (20130101); A61L2202/122 (20130101); A61L2202/123 (20130101); A61L2202/14 (20130101); B01J2219/0002 (20130101); B01J2219/0074 (20130101); B01L2200/027 (20130101); B01L2300/049 (20130101)

Field of Classification Search

CPC: B01L (3/502715); B01L (13/00); B01L (2200/027); B01L (2300/027); A61L (2/04); A61L (2/20); A61L (2/206); A61L (2/208); A61L (2/08); A61L (2202/11); A61L (2202/122); A61L (2202/123)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3728227	12/1972	Elson et al.	N/A	N/A
4234023	12/1979	Sogi et al.	N/A	N/A
4696902	12/1986	Bisconte	N/A	N/A
4751184	12/1987	Higo et al.	N/A	N/A
4839292	12/1988	Cremonese	N/A	N/A
4911833	12/1989	Schoendorfer et al.	N/A	N/A
5058619	12/1990	Zheng	N/A	N/A
5656491	12/1996	Cassani et al.	N/A	N/A
6102678	12/1999	Peclat	N/A	N/A
6267559	12/2000	Mossman et al.	N/A	N/A
6649419	12/2002	Anderson	N/A	N/A
6891182	12/2004	Watari et al.	N/A	N/A
7521224	12/2008	Johnson et al.	N/A	N/A
7550287	12/2008	Hibino et al.	N/A	N/A
7745209	12/2009	Martin et al.	N/A	N/A
7816128	12/2009	Nakashima et al.	N/A	N/A
8158426	12/2011	Wilson et al.	N/A	N/A
8158427	12/2011	Wilson et al.	N/A	N/A
8168432	12/2011	Wilson et al.	N/A	N/A
8273572	12/2011	Martin et al.	N/A	N/A

8415144	12/2012	Wilson et al.	N/A	N/A
8440458	12/2012	Zijlstra et al.	N/A	N/A
8470589	12/2012	Martin et al.	N/A	N/A
8492140	12/2012	Smith et al.	N/A	N/A
8546142	12/2012	Martin et al.	N/A	N/A
8697443	12/2013	Wilson et al.	N/A	N/A
8727132	12/2013	Miltenyi et al.	N/A	N/A
8809044	12/2013	Wilson	N/A	N/A
8846399	12/2013	Martin et al.	N/A	N/A
8956860	12/2014	Vera et al.	N/A	N/A
9040290	12/2014	Martin et al.	N/A	N/A
9045721	12/2014	Martin et al.	N/A	N/A
9080149	12/2014	Bosio et al.	N/A	N/A
9255243	12/2015	Wilson et al.	N/A	N/A
9279099	12/2015	Okano et al.	N/A	N/A
9290730	12/2015	Martin et al.	N/A	N/A
9410114	12/2015	Wilson et al.	N/A	N/A
9441192	12/2015	Wilson et al.	N/A	N/A
9499780	12/2015	Smith et al.	N/A	N/A
9534195	12/2016	Smith et al.	N/A	N/A
9556485	12/2016	Lin et al.	N/A	N/A
9567565	12/2016	Vera et al.	N/A	N/A
9597355	12/2016	Magnant	N/A	N/A
9625463	12/2016	Miltenyi et al.	N/A	N/A
9701932	12/2016	Smith et al.	N/A	N/A
9732317	12/2016	Wilson	N/A	N/A
9783768	12/2016	Larcher et al.	N/A	N/A
9845451	12/2016	Martin et al.	N/A	N/A
10047342	12/2017	Eibl et al.	N/A	N/A
10053663	12/2017	Kabaha et al.	N/A	N/A
10119970	12/2017	Miltenyi et al.	N/A	N/A
10131876	12/2017	Kaiser et al.	N/A	N/A
10253316	12/2018	Masquelier et al.	N/A	N/A
10294658	12/2018	Scannon et al.	N/A	N/A
10323258	12/2018	Bernate et al.	N/A	N/A
10329559	12/2018	Masquelier et al.	N/A	N/A
10385307	12/2018	Rowley et al.	N/A	N/A
10421959	12/2018	Masquelier et al.	N/A	N/A
10508288	12/2018	Bernate et al.	N/A	N/A
10519437	12/2018	Masquelier et al.	N/A	N/A
10533156	12/2019	Vera et al.	N/A	N/A
10584333	12/2019	Masquelier et al.	N/A	N/A
10584334	12/2019	Masquelier et al.	N/A	N/A
10588994	12/2019	Kawamura et al.	N/A	N/A
10620212	12/2019	Miltenyi et al.	N/A	N/A
10689669	12/2019	Feldman et al.	N/A	N/A
10705090	12/2019	Miltenyi et al.	N/A	N/A
10705091	12/2019	Miltenyi et al.	N/A	N/A
10723986	12/2019	Smith et al.	N/A	N/A
10724043	12/2019	Sixto et al.	N/A	N/A

10844338	12/2019	Smith et al.	N/A	N/A
11161111	12/2020	Kabaha et al.	N/A	N/A
11198845	12/2020	Parietti et al.	N/A	N/A
11371018	12/2021	Shi et al.	N/A	N/A
11376587	12/2021	Thakkar et al.	N/A	N/A
11447745	12/2021	Shi et al.	N/A	N/A
11701654	12/2022	Azersky et al.	N/A	N/A
11786896	12/2022	Thakkar et al.	N/A	N/A
11826756	12/2022	Azersky et al.	N/A	N/A
11872557	12/2023	Biz et al.	N/A	N/A
12157119	12/2023	Gerlinghaus et al.	N/A	N/A
12180453	12/2023	Chang et al.	N/A	N/A
2002/0146817	12/2001	Cannon et al.	N/A	N/A
2003/0030272	12/2002	Johnson et al.	N/A	N/A
2003/0031542	12/2002	Hamel et al.	N/A	N/A
2004/0121454	12/2003	Jury et al.	N/A	N/A
2005/0070018	12/2004	Johnson et al.	N/A	N/A
2005/0186671	12/2004	Cannon et al.	N/A	N/A
2005/0260743	12/2004	Drake et al.	N/A	N/A
2006/0194193	12/2005	Tsuruta et al.	N/A	N/A
2006/0257999	12/2005	Chang et al.	N/A	N/A
2007/0185472	12/2006	Baumfalk et al.	N/A	N/A
2008/0057568	12/2007	Kan et al.	N/A	N/A
2008/0176318	12/2007	Wilson et al.	N/A	N/A
2009/0042281	12/2008	Chang et al.	N/A	N/A
2009/0053799	12/2008	Chang-Yen et al.	N/A	N/A
2009/0247417	12/2008	Haas et al.	N/A	N/A
2010/0130732	12/2009	Chung et al.	N/A	N/A
2010/0151571	12/2009	Vukasinovic et al.	N/A	N/A
2010/0301071	12/2009	Alstad et al.	N/A	N/A
2011/0003380	12/2010	Miltenyi et al.	N/A	N/A
2011/0223064	12/2010	Katsumi et al.	N/A	N/A
2011/0229927	12/2010	Larsen et al.	N/A	N/A
2011/0262896	12/2010	Blecka et al.	N/A	N/A
2012/0138156	12/2011	Hofman et al.	N/A	N/A
2012/0148415	12/2011	Brueckner	N/A	N/A
2012/0283867	12/2011	Gelbman et al.	N/A	N/A
2012/0293338	12/2011	Chaffey et al.	N/A	N/A
2013/0078624	12/2012	Holmes et al.	N/A	N/A
2013/0115617	12/2012	Wilson	N/A	N/A
2013/0132006	12/2012	Gwynn et al.	N/A	N/A
2013/0189120	12/2012	Nelson et al.	N/A	N/A
2014/0309795	12/2013	Norton et al.	N/A	N/A
2015/0037803	12/2014	Park et al.	N/A	N/A
2015/0307829	12/2014	Dedry et al.	N/A	N/A
2015/0336096	12/2014	Smith et al.	N/A	N/A
2016/0060680	12/2015	Buse et al.	N/A	N/A
2016/0161516	12/2015	Fritchie et al.	N/A	N/A
2016/0208216	12/2015	Vera et al.	N/A	N/A
2016/0244714	12/2015	Spuhler et al.	N/A	N/A

2016/0303563	12/2015	Granier et al.	N/A	N/A
2016/0320381	12/2015	Holmes et al.	N/A	N/A
2016/0320422	12/2015	Fritchie et al.	N/A	N/A
2017/0058527	12/2016	Williams et al.	N/A	N/A
2017/0239420	12/2016	Wells	N/A	N/A
2017/0307502	12/2016	Mason et al.	N/A	N/A
2017/0313977	12/2016	Wilson	N/A	N/A
2017/0321226	12/2016	Gill et al.	N/A	N/A
2017/0348525	12/2016	Sano et al.	N/A	N/A
2017/0362554	12/2016	Martin et al.	N/A	N/A
2018/0031592	12/2017	Dority	N/A	N/A
2018/0051243	12/2017	Hogan et al.	N/A	N/A
2018/0078935	12/2017	Hung et al.	N/A	N/A
2018/0185849	12/2017	Kaplan et al.	N/A	N/A
2018/0196918	12/2017	Sadowski et al.	N/A	N/A
2019/0212233	12/2018	Jovanovich et al.	N/A	N/A
2019/0275519	12/2018	Castillo et al.	N/A	N/A
2019/0292510	12/2018	Tandon et al.	N/A	N/A
2019/0293673	12/2018	Wescott et al.	N/A	N/A
2019/0316120	12/2018	Masquelier et al.	N/A	N/A
2019/0330579	12/2018	Guenat et al.	N/A	N/A
2020/0009557	12/2019	Frigard et al.	N/A	N/A
2020/0025782	12/2019	Ahlfors	N/A	G01N 35/00
2020/0048599	12/2019	Firouzi et al.	N/A	N/A
2020/0095550	12/2019	Vera et al.	N/A	N/A
2020/0159198	12/2019	Kapre et al.	N/A	N/A
2020/0224147	12/2019	Rogers et al.	N/A	N/A
2020/0283713	12/2019	Ball et al.	N/A	N/A
2020/0292552	12/2019	Miltenyi et al.	N/A	N/A
2020/0353004	12/2019	Nowak et al.	N/A	N/A
2020/0368411	12/2019	Camisani et al.	N/A	N/A
2020/0399578	12/2019	Corso et al.	N/A	N/A
2020/0406221	12/2019	Dabrowski et al.	N/A	N/A
2021/0001339	12/2020	Liu et al.	N/A	N/A
2021/0032583	12/2020	Smith et al.	N/A	N/A
2021/0035655	12/2020	Tanouchi et al.	N/A	N/A
2021/0047668	12/2020	Dabrowski et al.	N/A	N/A
2021/0079344	12/2020	Bosio et al.	N/A	N/A
2021/0147807	12/2020	Lickert et al.	N/A	N/A
2021/0253997	12/2020	Wilson	N/A	N/A
2021/0269755	12/2020	Smith et al.	N/A	N/A
2021/0283565	12/2020	Gerlinghaus et al.	N/A	N/A
2021/0284948	12/2020	Hauwaerts et al.	N/A	N/A
2021/0301239	12/2020	Natsume et al.	N/A	N/A
2021/0324318	12/2020	Parietti et al.	N/A	N/A
2021/0354104	12/2020	Pesch et al.	N/A	N/A
2022/0002652	12/2021	Patrick et al.	N/A	N/A
2022/0003796	12/2021	Ahlfors	N/A	N/A
2022/0047862	12/2021	Chang et al.	N/A	N/A

2022/0121181	12/2021	Sobalvarro et al.	N/A	N/A
2022/0143610	12/2021	Biz et al.	N/A	N/A
2022/0150650	12/2021	Rucker	N/A	N/A
2022/0163438	12/2021	Klas et al.	N/A	N/A
2022/0259546	12/2021	Blanchard	N/A	N/A
2022/0282199	12/2021	Vann	N/A	N/A
2022/0325219	12/2021	Parietti et al.	N/A	N/A
2022/0325240	12/2021	Mcfarland et al.	N/A	N/A
2022/0347683	12/2021	Thakkar et al.	N/A	N/A
2023/0051840	12/2022	Kelso et al.	N/A	N/A
2023/0149922	12/2022	Thakkar et al.	N/A	N/A
2023/0321650	12/2022	Azersky et al.	N/A	N/A
2023/0415154	12/2022	Pesch et al.	N/A	N/A
2023/0415155	12/2022	Biz et al.	N/A	N/A
2024/0018955	12/2023	Hannah et al.	N/A	N/A
2024/0167466	12/2023	Paraluppi	N/A	N/A
2024/0254426	12/2023	Elpel et al.	N/A	N/A
2024/0255537	12/2023	Malleo et al.	N/A	N/A
2024/0279585	12/2023	Griffin et al.	N/A	N/A
2024/0279588	12/2023	Malleo et al.	N/A	N/A
2024/0318116	12/2023	Chang et al.	N/A	N/A
2024/0326043	12/2023	Gerlinghaus et al.	N/A	N/A
2024/0369586	12/2023	Tian et al.	N/A	N/A
2024/0377420	12/2023	Cesarek	N/A	N/A
2024/0390897	12/2023	Azersky et al.	N/A	N/A
2024/0390898	12/2023	Azersky et al.	N/A	N/A
2024/0399365	12/2023	Biz et al.	N/A	N/A
2024/0402206	12/2023	Boppart et al.	N/A	N/A
2025/0002837	12/2024	Bharat	N/A	N/A
2025/0059492	12/2024	Beban et al.	N/A	N/A
2025/0065331	12/2024	Malleo et al.	N/A	N/A
2025/0066708	12/2024	Burkeen et al.	N/A	N/A
2025/0066709	12/2024	Grout et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
104203333	12/2013	CN	N/A
108660060	12/2017	CN	N/A
0246912	12/1986	EP	N/A
0991389	12/1999	EP	N/A
0824380	12/2001	EP	N/A
3134512	12/2018	EP	N/A
2809449	12/2018	EP	N/A
3359294	12/2019	EP	N/A
3928867	12/2020	EP	N/A
2268187	12/1993	GB	N/A
2007325586	12/2006	JP	N/A
20130018286	12/2012	KR	N/A
20220131302	12/2021	KR	N/A
WO-9320440	12/1992	WO	N/A

WO-2006102416	12/2005	WO	N/A
WO-2006112870	12/2005	WO	N/A
WO-2006118282	12/2005	WO	N/A
WO-2007139742	12/2006	WO	N/A
WO-2009072003	12/2008	WO	N/A
WO-2017041051	12/2016	WO	N/A
WO-2017123663	12/2016	WO	N/A
WO-2018015561	12/2017	WO	N/A
WO-2018102471	12/2017	WO	N/A
WO-2020009700	12/2019	WO	N/A
WO-2020014264	12/2019	WO	N/A
WO-2021168368	12/2020	WO	N/A
WO-2021183687	12/2020	WO	N/A
WO-2021212124	12/2020	WO	N/A
WO-2024102996	12/2023	WO	N/A
WO-2024112702	12/2023	WO	N/A
WO-2024152008	12/2023	WO	N/A
WO-2024197093	12/2023	WO	N/A
WO-2024206703	12/2023	WO	N/A
WO-2024233080	12/2023	WO	N/A
WO-2024249904	12/2023	WO	N/A
WO-2025007051	12/2024	WO	N/A
WO-2025038974	12/2024	WO	N/A
WO-2025041046	12/2024	WO	N/A
WO-2025041047	12/2024	WO	N/A
WO-2025041064	12/2024	WO	N/A

OTHER PUBLICATIONS

ChargePoint (2021). Aseptic split butterfly valve 10-6 sterility assurance, located at <https://www.thechargepoint.com/products/aseptic-split-butterfly-valve-10-6-sterility-assurance/>, 2 total pages. cited by applicant

CPC (2014). "6 traits of non-spill: How quick disconnect couplings evolved for low-pressure fluid handling," White Paper 8004, 4 total pages. cited by applicant

CPC (2014). "How single-use connections advance aseptic processing: Increased process flexibility and reliability, reduced costs," White Paper 7004, 6 total pages. cited by applicant

CPC (2018). Comparison Guide: Tube Welders and Aseptic Connectors, Technical Guide 7009, 3 total pages. cited by applicant

EMD Millipore (2015). "Lynx® S2S Connector—Low temperature compatibility (-80°C)," 4 total pages. cited by applicant

Final Office Action mailed on Apr. 28, 2022, for U.S. Appl. No. 17/198,134, filed Mar. 10, 2021, 11 pages. cited by applicant

Final Office Action mailed on Apr. 28, 2022, for U.S. Appl. No. 17/331,554, filed May 26, 2021, 16 pages. cited by applicant

Final Office Action mailed on Jul. 31, 2023, for U.S. Appl. No. 17/331,554, filed May 26, 2021, 19 pages. cited by applicant

Final Office Action mailed on Mar. 31, 2023, for U.S. Appl. No. 17/579,478, filed Jan. 19, 2022, 8 pages. cited by applicant

Garcia, P.A. et al. (2016). "Microfluidic screening of electric fields for electroporation," Sci. Rep. 6:21238, 11 pages. cited by applicant

Genetic Engineering & Biotechnology News (2006). "Thermal welding for sterile connections,"

located at <https://www.genengnews.com/magazine/47/thermal-welding-for-sterile-connections/>, 5 total pages. cited by applicant

International Search Report mailed on Oct. 13, 2021, for PCT Application No. PCT/US2021/021773, filed on Mar. 10, 2021, 13 pages. cited by applicant

Jain, S. et al. (2011). "The complete automation of cell culture: improvements for high-throughput and high-content screening," J. Biomol. Screen 16:932-939. cited by applicant

Kato, R. et al. (2010). "A Compact, Automated Cell Culture System for Clinical Scale Cell Expansion from Primary Tissues," Tissue Engineering: Part C 16:947-956. cited by applicant

Kempner, M.E. and Felder, R.A., "A review of cell culture automation". JALA: Journal of the Association for Laboratory Automation (Apr. 2002); 7(2): 56-62. cited by applicant

Kino-Oka, M. et al. (2005). "Bioreactor Design for Successive Culture of Anchorage-Dependent Cells Operated in an Automated Manner," Tissue Engineering 11:535-545. cited by applicant

Knoll, A. et al. (2004). "Flexible automation of cell culture and tissue engineering tasks," Biotechnol. Prog. 20:1825-1835. cited by applicant

Lutkemeyer, D. et al. (2000). "First steps in robot automation of sampling and sample management during cultivation of mammalian cells in pilot scale," Biotechnol. Prog. 16:822-828. cited by applicant

MEDInstill (2021). INTACT™ Connectors, located at <https://www.medinstill.com/intactconnectors.php>, 1 total page. cited by applicant

Millipore® (2020). "Technical Brief—Choosing the right sterile connector based on design and sterility test results," 4 total pages. cited by applicant

Millipore Sigma (2020). "Lynx® CDR Connectors," Datasheet, 4 total pages. cited by applicant

Millipore Sigma (2021). Lynx® CDR Connectors, located at https://www.emdmillipore.com/US/en/product/Lynx-CDR-Connectors,MM_NF-C188801, 2 total pages. cited by applicant

Non-Final Office Action mailed on Dec. 22, 2022, for U.S. Appl. No. 17/579,478, filed Jan. 19, 2022, 8 pages. cited by applicant

Non-Final Office Action mailed on Jun. 26, 2023, for U.S. Appl. No. 17/198,134, filed Mar. 10, 2021, 15 pages. cited by applicant

Non-Final Office Action mailed on Dec. 3, 2021, for U.S. Appl. No. 17/331,556, filed May 26, 2021, 9 pages. cited by applicant

Non-Final Office Action mailed on Feb. 3, 2022, for U.S. Appl. No. 17/198,134, filed Mar. 10, 2021, 5 pages. cited by applicant

Non-Final Office Action mailed on Mar. 16, 2023, for U.S. Appl. No. 17/331,554, filed May 26, 2021, 16 pages. cited by applicant

Non-Final Office Action mailed on Oct. 28, 2021, for U.S. Appl. No. 17/331,554, filed May 26, 2021, 11 pages. cited by applicant

Non-Final Office Action mailed on Oct. 6, 2021, for U.S. Appl. No. 17/198,134, filed Mar. 10, 2021, 7 pages. cited by applicant

Non-Final Office Action mailed on Sep. 13, 2023, for U.S. Appl. No. 18/141,329, filed Apr. 28, 2023, 7 pages. cited by applicant

Notice of Allowance mailed on Mar. 22, 2023, for U.S. Appl. No. 17/992,784, filed Nov. 22, 2022, 8 pages. cited by applicant

Notice of Allowance mailed on Jul. 18, 2023, for U.S. Appl. No. 17/849,422, filed Jun. 24, 2022, 8 pages. cited by applicant

Notice of Allowance mailed on Jul. 25, 2023, for U.S. Appl. No. 17/579,478, filed Jan. 19, 2022, 8 pages. cited by applicant

Notice of Allowance mailed on Jun. 8, 2023, for U.S. Appl. No. 17/849,422, filed Jun. 24, 2022, 8 pages. cited by applicant

Notice of Allowance mailed on Mar. 1, 2022, for U.S. Appl. No. 17/331,556, filed May 26, 2021, 8

pages. cited by applicant
Notice of Allowance mailed on Oct. 4, 2023, for U.S. Appl. No. 18/141,329, filed Apr. 28, 2023, 8 pages. cited by applicant
Qu, B., et al., “Droplet Electroporation in Microfluidics for Efficient Cell Transformation with or without Cell Wall Removal,” Lab Chip, 2012, vol. 12, pp. 4483-4488. cited by applicant
Saint Gobain (2017). “Pure-Fit® SC—Secure aseptic connections,” Brochure, 5 total pages. cited by applicant
Sartorius Stedim Biotech (2011). “Opta® SFT,” 4 total pages. cited by applicant
Schwartz C, “Optimizing Cell Separation with Beckman Coulter's Centrifugal Elutriation System,” Beckmann Coulter Life Sciences, 2014, 6 total pages. cited by applicant
SeriesLock™ (2021). Features and Specifications, located at <https://serieslock.com/>, 5 total pages. cited by applicant
Shi, Y. et al. (1992). “Performance of Mammalian Cell Culture Bioreactor with a New Impeller Design,” Biotechnology and Bioengineering 40:260-270. cited by applicant
Steris (2018). “A compilation of material compatibilities with vaporized hydrogen peroxide,” 2 total pages. cited by applicant
Steris (2018). “Sterility assurance levels (SALS): Irradiation,” 3 total pages. cited by applicant
Steris (2020). “Overview of sterilization technology comparison,” 1 total page. cited by applicant
Strahlendorf, K.A. et al. (2009). “Bio Pharm International—A review of sterile connectors,” vol. 2009 Supplement, Issue 8, located at <https://www.biopharminternational.com/view/review-sterile-connectors>, 9 total pages. cited by applicant
Written Opinion of the International Searching Authority mailed on Oct. 13, 2021, for PCT Application No. PCT/US2021/021773, filed on Mar. 10, 2021, 20 pages. cited by applicant
Final Office Action for U.S. Appl. No. 17/331,554 mailed Aug. 29, 2024, 18 pages. cited by applicant
International Search Report and Written Opinion for Application No. PCT/US2024/025064 mailed Sep. 6, 2024, 17 pages. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2023/080593 dated Mar. 21, 2024, 12 pages. cited by applicant
International Search Report and Written Opinion for PCT Application No. PCT/US2024/011486 dated May 24, 2024, 12 pages. cited by applicant
Invitation to Pay Additional Fees for International Application No. PCT/US2024/022079 dated Jul. 17, 2024, 19 pages. cited by applicant
Invitation to Pay Additional fees for International Application No. PCT/US2024/025064, mailed Jul. 16, 2024, 12 pages. cited by applicant
Non-Final Office Action for U.S. Appl. No. 18/652,602 mailed Jul. 17, 2024, 30 pages. cited by applicant
Non-Final Office Action for U.S. Appl. No. 18/731,095 mailed Aug. 8, 2024, 24 pages. cited by applicant
Non-Final Office Action mailed on Apr. 24, 2024, for U.S. Appl. No. 17/331,554, filed May 26, 2021, 17 pages. cited by applicant
Non-Final Office Action mailed on May 14, 2024, for U.S. Appl. No. 18/611,632, filed Mar. 20, 2024, 13 pages. cited by applicant
Notice of Allowance (Corrected) mailed on Sep. 5, 2024, for U.S. Appl. No. 18/611,632, filed Mar. 20, 2024, 6 pages. cited by applicant
Notice of Allowance for U.S. Appl. No. 18/611,632 mailed Aug. 26, 2024, 9 pages. cited by applicant
Notice of Allowance mailed on Apr. 11, 2024, for U.S. Appl. No. 17/198,134, filed Mar. 10, 2021, 9 pages. cited by applicant
Pharma Japan, “Astellas Set to Cut Development Time with Cell Culture Robot, Eyes 4 Billion Yen

Profit per Product” Aug. 9, 2023, 3 pages. cited by applicant

Final Office Action for U.S. Appl. No. 18/652,602 mailed Nov. 1, 2024, 29 pages. cited by applicant

Final Office Action for U.S. Appl. No. 18/731,095 mailed Nov. 26, 2024, 31 pages. cited by applicant

Final Office Action for U.S. Appl. No. 18/799,963 mailed Jan. 30, 2025, 10 pages. cited by applicant

International Search Report and Written Opinion for International Application No. PCT/IB2024/058106 mailed Jan. 21, 2025, 13 pages. cited by applicant

International Search Report and Written Opinion for International Application No. PCT/IB2024/058148 mailed Mar. 3, 2025, 21 pages. cited by applicant

International Search Report and Written Opinion for PCT Application No. PCT/IB2024/058105 mailed Dec. 16, 2024, 12 pages. cited by applicant

International Search Report and Written Opinion for PCT Application No. PCT/US2024/022079 mailed Sep. 12, 2024, 25 pages. cited by applicant

International Search Report and Written Opinion for PCT Application No. PCT/US2024/032062 mailed Sep. 6, 2024, 15 pages. cited by applicant

International Search Report and Written Opinion for PCT Application No. PCT/US2024/042795 mailed Dec. 16, 2024, 11 pages. cited by applicant

Invitation to Pay Additional fees for International Application No. PCT/IB2024/058148, mailed Jan. 2, 2025, 13 pages. cited by applicant

Invitation to Pay Additional fees for International Application No. PCT/US2024/020809, mailed Jan. 27, 2025, 17 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/244,051 mailed Oct. 9, 2024, 10 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/638,658 mailed on Nov. 22, 2024, 13 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/731,095 mailed Mar. 6, 2025, 34 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/759,602 mailed Feb. 20, 2025, 15 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/759,602 mailed Nov. 8, 2024, 10 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/792,358 mailed on Nov. 6, 2024, 5 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/799,963 mailed Sep. 30, 2024, 9 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/810,386 mailed Nov. 18, 2024, 8 pages. cited by applicant

Non-Final Office action for U.S. Appl. No. 18/920,607 mailed Feb. 28, 2025, 10 pages. cited by applicant

Non-Final Office Action for U.S. Appl. No. 18/988,628 mailed Mar. 3, 2025, 19 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/331,554 mailed Mar. 5, 2025, 8 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 18/792,358 mailed on Mar. 3, 2025, 8 pages. cited by applicant

Notice of allowance for U.S. Appl. No. 18/792,360 mailed Mar. 4, 2025, 9 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 18/792,360 mailed on Jan. 29, 2025, 9 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 18/810,388 mailed Jan. 21, 2025, 8 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 18/810,388 mailed on Oct. 9, 2024, 9 pages. cited by applicant

Notice of allowance for U.S. Appl. No. 18/811,490 mailed Feb. 26, 2025, 8 pages. cited by applicant

Notice of Allowance for U.S. Appl. No. 18/811,490 mailed on Dec. 12, 2024, 8 pages. cited by applicant

U.S. Appl. No. 29/898,923, filed Aug. 2, 2023, by Gerlinghaus et al. cited by applicant

Primary Examiner: Conley; Sean E

Attorney, Agent or Firm: Cooley LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/141,329, filed Apr. 28, 2023, now U.S. Pat. No. 11,826,756, which is a continuation of U.S. patent application Ser. No. 17/992,784, filed Nov. 22, 2022, now U.S. Pat. No. 11,701,654, which is a continuation of U.S. patent application Ser. No. 17/849,422, filed Jun. 24, 2022, now U.S. Pat. No. 11,786,896, which is a divisional of U.S. patent application Ser. No. 17/331,556, filed May 26, 2021, now U.S. Pat. No. 11,376,587, which is a continuation of U.S. patent application Ser. No. 17/198,134, filed Mar. 10, 2021, which claims the benefit of U.S. Provisional Patent Application No. 62/987,745, filed Mar. 10, 2020, and U.S. Provisional Patent Application No. 63/093,038, filed Oct. 16, 2020, the content of each of which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(1) Devices, systems, and methods herein relate to manufacturing cell products for biomedical applications using automated systems.

BACKGROUND

(2) Cellular therapies based on hematopoietic stem cells (HSCs), chimeric antigen receptor (CAR) T cells, NK cells, tumor infiltrating lymphocytes (TILs), T-cell receptors (TCRs), regulatory T cells (T regs), gamma delta ($\gamma\delta$) T cells, and others rely on manufacturing of cell products.

Manufacturing of such cell products typically involves multiple cell processing steps. Conventional solutions for manufacture of cell products rely on cumbersome manual operations performed in expensive biosafety cabinets and/or clean rooms. Skilled laboratory technicians, adequate sterile enclosures such as cleanroom facilities, and associated protocols and procedures for regulated (GMP) manufacturing are expensive. Many current manufacturing processes employ numerous manual reagent preparation and instrument manipulation steps during a manufacturing protocol, and the processes may require several days or even weeks. Even platforms described as automated cell processing in a closed system generally rely on pre-configured instrumentation and tubing sets that limit operational flexibility and do not reliably prevent process failure due to accidental operator/human error.

(3) Most efforts to automate cell product manufacturing have been directed to automating individual processing steps of a cell therapy manufacturing workflow. Even systems that automate several steps lack end-to-end process flexibility, process robustness, and process scalability. These and other limitations of the previous attempts at automation of cell processing are addressed in various embodiments disclosed here.

SUMMARY

(4) The present disclosure relates generally to methods and systems for processing cell products. By processing a cell product in a cartridge moved between instruments, some variations may achieve one or more advantages over prior cell manufacturing systems, including, for example, improved sterility, automation, lower cost of goods, lower labor costs, higher repeatability, higher reliability, lower risk of operator error, lower risk of contamination, higher process flexibility, higher capacity, higher instrument throughput, higher degree of process scalability, and shorter process duration. Variations of the disclosure may comprise a sterile enclosure, thereby reducing the costs of providing a clean room environment, and/or utilize a workcell having a smaller footprint than current manufacturing facilities. Furthermore, variations of the methods disclosed herein may, in some cases, be performed more quickly and with less risk of cell product loss.

(5) In some variations, the disclosure provides a system for cell processing, comprising a plurality of instruments each independently configured to perform one or more cell processing operation upon a cartridge, and a robot capable of moving the cartridge between each of the plurality of instruments.

(6) In some variations, the system may be enclosed in a workcell. In some variations, the workcell may be automated. In some variations, the plurality of instruments may be configured to interface with the cartridge to perform cell processing operations upon the cartridge. In some variations, the system may comprise a processor. The processor may be configured to control the robot and the plurality of instruments.

(7) In some variations, the system may be configured to receive two or more cartridges. In some variations, the system may comprise the cartridge. In some variations, the cartridge may comprise a plurality of modules. In some variations, the cartridge may comprise a bioreactor module. In some variations, the cartridge may comprise a cell selection module. In some variations, the cell selection module may comprise a magnetic-activated cell selection module. In some variations, the cartridge may comprise a sorting module. In some variations, the sorting module may comprise a fluorescence activated cell sorting (FACS) module. In some variations, the cartridge may comprise an electroporation module. In some variations, the cartridge may comprise a counterflow centrifugal elutriation (CCE) module.

(8) In some variations, the cartridge may comprise one or more sterile liquid transfer ports. In some variations, the cartridge may comprise a liquid transfer bus fluidically coupled to each module. In some variations, the cartridge may comprise a pump fluidically coupled to the liquid transfer bus.

(9) In some variations, the system may comprise a pump actuator configured to interface with the pump. In some variations, the system may comprise a bioreactor instrument. In some variations, the bioreactor instrument may comprise multiple slots for cartridges. In some variations, the system may comprise a cell selection instrument. In some variations, the cell selection instrument may comprise a magnetic-activated cell selection instrument.

(10) In some variations, the system may comprise a sorting instrument. In some variations, the sorting instrument may comprise a fluorescence activated cell sorting (FACS) instrument. In some variations, the system may comprise an electroporation instrument. In some variations, the system may comprise a counterflow centrifugal elutriation (CCE) instrument. In some variations, the system may comprise a reagent vault.

(11) In some variations, the cartridge may comprise a bioreactor module and a selection module. In some variations, the cartridge may comprise a bioreactor module and a CCE module. In some variations, the cartridge may comprise a bioreactor module, selection module, and a CCE module. In some variations, the cartridge may comprise a bioreactor module, selection module, and an electroporation module. In some variations, the cartridge may comprise a bioreactor module, selection module, a CCE module, and an electroporation module. In some variations, the cartridge may comprise a second bioreactor module having an internal volume two or more, five or more, or ten or more times larger than the internal volume of the first bioreactor.

- (12) In some variations, the system may comprise an enclosure. In some variations, the enclosure may comprise an ISO7 cleanroom. In some variations, the enclosure may comprise an ISO6 cleanroom. In some variations, the enclosure may comprise an ISO5 cleanroom. In some variations, the enclosure may comprise a feedthrough. In some variations, the system may perform automated manufacturing of cell products.
- (13) In some variations, the disclosure provides a cartridge for cell processing, comprising a liquid transfer bus and a plurality of modules, each module fluidically coupled to the liquid transfer bus.
- (14) In some variations, the cartridge may comprise one or more sterile liquid transfer ports. In some variations, the cartridge may comprise a bioreactor module. In some variations, the cartridge may comprise a cell selection module. In some variations, the cell selection module may comprise a magnetic-activated cell selection module. In some variations, the cartridge may comprise a sorting module. In some variations, the sorting module may comprise a fluorescence activated cell sorting (FACS) module. In some variations, the cartridge may comprise an electroporation module. In some variations, the cartridge may comprise a counterflow centrifugal elutriation (CCE) module.
- (15) In some variations, the cartridge may comprise a mechanoporation module. In some variations, the cartridge may comprise a second bioreactor module having an internal volume two or more, five or more, or ten or more times larger than the internal volume of the first bioreactor. In some variations, the cartridge may comprise a bioreactor module, selection module, and a CCE module. In some variations, the cartridge may comprise a bioreactor module, selection module, and an electroporation module. In some variations, the cartridge may comprise a bioreactor module, selection module, a CCE module, and an electroporation module.
- (16) In some variations, the disclosure provides a method for processing cells, comprising moving a cartridge containing a cell product between a plurality of instruments inside an enclosed and automated workcell. The instruments may interface with the cartridge to perform cell processing steps on the cell product.
- (17) In some variations, cell processing steps may be performed on the cell product. In some variations, for each cell product, all cell processing steps in the method are performed in a single cartridge.
- (18) In some variations, the cell product may be split into a plurality of cell product portions. In some variations, the cell processing steps may be performed on the plurality of cell product portions in parallel. In some variations, at least two cell product portions of the plurality of cell product portions may be combined.
- (19) In some variations, the workcell may comprise a robot configured to move cartridges. In some variations, the workcell may comprise a processor. The processor may be configured to control the robot and the plurality of instruments. In some variations, the workcell may be configured to receive two or more cartridges.
- (20) In some variations, the cartridge may comprise a plurality of modules. In some variations, the cartridge may comprise a bioreactor module. In some variations, the cartridge may comprise a cell selection module. In some variations, the cell selection module may comprise a magnetic-activated cell selection module.
- (21) In some variations, the cartridge may comprise a sorting module. In some variations, the sorting module may comprise a fluorescence activated cell sorting (FACS) module. In some variations, the cartridge may comprise an electroporation module. In some variations, the cartridge may comprise a counterflow centrifugal elutriation (CCE) module. In some variations, the cartridge may comprise one or more sterile liquid transfer ports. In some variations, the cartridge may comprise a liquid transfer bus fluidically coupled to each module. In some variations, the cartridge may comprise a pump fluidically coupled to the liquid transfer bus.
- (22) In some variations, the workcell may comprise a pump actuator configured to interface with the pump. In some variations, the workcell may comprise a bioreactor instrument. In some variations, the bioreactor instrument may comprise multiple slots for cartridges. In some variations,

the method may comprise performing the cell processing steps on two or more cartridges in parallel.

(23) In some variations, the workcell may comprise a cell selection instrument. In some variations, the cell selection instrument may comprise a magnetic-activated cell selection instrument.

(24) In some variations, the workcell may comprise a sorting instrument. In some variations, the sorting instrument may comprise a fluorescence activated cell sorting (FACS) instrument. In some variations, the workcell may comprise an electroporation instrument. In some variations, the workcell may comprise a counterflow centrifugal elutriation (CCE) instrument. In some variations, the workcell may comprise a reagent vault.

(25) In some variations, the cartridge may comprise a bioreactor module and a selection module. In some variations, the cartridge may comprise a bioreactor module and a CCE module. In some variations, the cartridge may comprise a bioreactor module, selection module, and a CCE module. In some variations, the cartridge may comprise a bioreactor module, selection module, and an electroporation module. In some variations, the cartridge may comprise a bioreactor module, selection module, a CCE module, and an electroporation module.

(26) In some variations, the workcell may comprise an enclosure. In some variations, the enclosure may comprise an ISO7 cleanroom. In some variations, the enclosure may comprise an ISO6 cleanroom. In some variations, the enclosure may comprise an ISO5 cleanroom. In some variations, the enclosure may comprise a feedthrough.

(27) In some variations, the method may perform automated manufacturing of a cell product. In some variations, the cell product may comprise a chimeric antigen receptor (CAR) T cell product. In some variations, the cell product may comprise a natural killer (NK) cell product. In some variations, the cell product may comprise a hematopoietic stem cell (HSC) cell product. In some variations, the cell product may comprise a tumor infiltrating lymphocyte (TIL) cell product. In some variations, the cell product may comprise a regulatory T (Treg) cell product.

(28) In some variations, the disclosure provides a method for processing a solution containing a cell product, performed in an automated system, the method comprising one or more cell processing steps, performed serially in any order, selected from: an enrichment step, a concentration step, a buffer exchange step, a formulation step, a washing step, a selection step, a resting step, an expansion step, a tissue-digestion step, an activation step, a transduction step, a transfection step, and a harvesting step.

(29) In some variations, an enrichment step may comprise enriching a selected population of cells in the solution by conveying the solution to a CCE module of the cartridge via a liquid transfer bus, operating the robot to move the cartridge to a CCE instrument so that the CCE module interfaces with the CCE instrument, and operating the CCE instrument to cause the CCE module to enrich the selected population of cells.

(30) In some variations, a washing step may comprise washing a selected population of cells in the solution by conveying the solution to the CCE module of the cartridge via the liquid transfer bus, operating the robot to move the cartridge to the CCE instrument so that the CCE module interfaces with the CCE instrument, and operating the CCE instrument to cause the CCE module to remove media from the solution, introduce media into the solution, and/or replace media in the solution.

(31) In some variations, a selection step may comprise selecting a selected population of cells in the solution by conveying the solution to a selection module of the cartridge via the liquid transfer bus, operating the robot to move the cartridge to a selection instrument so that the selection module interfaces with the selection instrument, and operating the selection instrument to cause the selection module to select the selected population of cells.

(32) In some variations, a sorting step may comprise sorting a population of cells in the solution by conveying the solution to a sorting module of the cartridge via the liquid transfer bus, operating the robot to move the cartridge to a sorting instrument so that the sorting module interfaces with the sorting instrument, and operating the sorting instrument to cause the sorting module to sort the

population of cells.

(33) In some variations, a resting step may comprise conveying the solution to a bioreactor module of the cartridge via the liquid transfer bus, operating the robot to move the cartridge to the bioreactor instrument so that the bioreactor module interfaces with the bioreactor instrument, and operating the bioreactor instrument to cause the bioreactor module to maintain the cells.

(34) In some variations, an expansion step may comprise expanding the cells in the solution by conveying the solution to the bioreactor module of the cartridge via the liquid transfer bus, operating the robot to move the cartridge to the bioreactor instrument so that the bioreactor module interfaces with the bioreactor instrument, and operating the bioreactor instrument to cause the bioreactor module to allow the cells to expand by cellular replication.

(35) In some variations, a tissue-digestion step may comprise conveying an enzyme reagent via the liquid transfer bus to a module containing a solution containing a tissue such that the enzyme reagent causes digestion of the tissue to release a select cell population into the solution.

(36) In some variations, an activating step may comprise activating a selected population of cells in the solution by conveying an activating reagent via the liquid transfer bus to a module containing the solution containing the cell product.

(37) In some variations, an electroporation step may comprise conveying the solution to an electroporation module of the cartridge via the liquid transfer bus, operating the robot to move the cartridge to an electroporation instrument so that the electroporation module interfaces with the electroporation instrument, and operating the electroporation instrument to cause the electroporation module to electroporate the selected population of cells in the presence of the vector.

(38) In some variations, a transduction step may comprise conveying an effective amount of a vector via the liquid transfer bus to a module containing the solution containing the cell product, thereby transducing a selected population of cells in the solution. In some variations, a fill/finishing step may comprise conveying a formulation solution via the liquid transfer bus to a module containing the cell product to generate a finished cell product and conveying the finished cell product to one or more product collection bags.

(39) In some variations, the method may comprise sterilizing, either manually or automatically, the cartridge in a feedthrough port. In some variations, the method may comprise introducing, either manually or automatically, one or more of a fluid and the cell product into the cartridge via a sterile liquid transfer port. In some variations, the method may comprise a harvesting step comprising removing, either manually or automatically, the cell product from the cartridge. In some variations, the cell product may comprise an immune cell. In some variations, in order, the enrichment step, the selection step, the activation step, the transduction step, the expansion step, and the harvesting step.

(40) In some variations, the immune cell may comprise a genetically engineered chimeric antigen receptor T cell. In some variations, the immune cell may comprise a genetically engineered T cell receptor (TCR) cell. In some variations, the immune cell may comprise is a natural-killer (NK) cell. In some variations, the cell product may comprise a hematopoietic stem cell (HSC). In some variations, the method may comprise, in order, the enrichment step, the selection step, the resting step, the transduction step, and the harvesting step. In some variations, the cell product may comprise a tumor infiltrating lymphocyte (TIL). In some variations, the method may comprise, in order, the tissue-digestion step, the washing step, the activation step, the expansion step, and the harvesting step.

(41) Also described here is a counterflow centrifugal elutriation (CCE) module, comprising a conical element having an internal surface and an external surface fixedly attached to a distal end of a linear member having an internal surface and an external surface, the proximal end of the linear member rotationally attached to a fulcrum to permit extension, retraction, and rotation of the linear member.

(42) Also described here is a workcell comprising an enclosure, a plurality of instruments each independently configured to perform one or more cell processing operation upon a cartridge, and a robot capable of moving the cartridge between each of the plurality of instruments.

(43) In some variations, the enclosure may comprise an air filtration inlet configured to maintain ISO 7 or better air quality within an interior zone of the workcell. In some variations, the workcell may be automated. In some variations, the instruments may interface with the cartridge to perform cell processing operations upon the cartridge. In some variations, the workcell may comprise a processor. The processor may be configured to control the robot and the plurality of instruments.

(44) In some variations, the workcell may be configured to receive two or more cartridges. In some variations, the workcell may comprise the cartridge. In some variations, the cartridge may comprise a plurality of modules. In some variations, the cartridge may comprise a bioreactor module. In some variations, the cartridge may comprise a cell selection module. In some variations, the cell selection module may comprise a magnetic-activated cell selection module. In some variations, the cartridge may comprise a sorting module.

(45) In some variations, the sorting module may comprise a fluorescence activated cell sorting (FACS) module. In some variations, the cartridge may comprise an electroporation module. In some variations, the cartridge may comprise a counterflow centrifugal elutriation (CCE) module. In some variations, the cartridge may comprise one or more sterile liquid transfer ports. In some variations, the cartridge may comprise a liquid transfer bus fluidically coupled to each module. In some variations, the cartridge may comprise a pump fluidically coupled to the liquid transfer bus.

(46) In some variations, the workcell may comprise a pump actuator configured to interface with the pump. In some variations, the workcell may comprise a bioreactor instrument. In some variations, the bioreactor instrument may comprise multiple slots for cartridges. In some variations, the workcell may comprise a cell selection instrument. In some variations, the cell selection instrument may comprise a magnetic-activated cell selection instrument. In some variations, the workcell may comprise a sorting instrument. In some variations, the sorting instrument may comprise a fluorescence activated cell sorting (FACS) instrument. In some variations, the workcell may comprise an electroporation instrument.

(47) In some variations, the workcell may comprise a counterflow centrifugal elutriation (CCE) instrument. In some variations, the workcell may comprise a reagent vault. In some variations, the cartridge may comprise a bioreactor module and a selection module. In some variations, the cartridge may comprise a bioreactor module and a CCE module. In some variations, the cartridge may comprise a bioreactor module, selection module, and a CCE module. In some variations, the cartridge may comprise a bioreactor module, selection module, and an electroporation module. In some variations, the cartridge may comprise a bioreactor module, selection module, a CCE module, and an electroporation module. In some variations, the cartridge may comprise a second bioreactor module having an internal volume two or more, five or more, or ten or more times larger than the internal volume of the first bioreactor. In some variations, the enclosure may comprise a feedthrough. In some variations, the workcell may perform automated manufacturing of cell products. In some variations, the system may comprise a plurality of bioreactor instruments. Each bioreactor instrument may be configured to receive a single cartridge.

(48) Also described here is a rotor comprising a first side comprising a first fluid conduit, a second side comprising a second fluid conduit, the second side opposite the first side, and a cone coupled between the first fluid conduit and the second fluid conduit.

(49) In some variations, the cone may comprise a bicone. In some variations, the bicone may comprise a first cone including a first base and a second cone including a second base. The first base may face the second base. In some variations, the rotor may comprise a magnetic portion. In some variations, the rotor may define a rotation axis. In some variations, at least a portion of the first fluid conduit and at least a portion of the second fluid conduit may extend parallel to the rotation axis. In some variations, at least a portion of the first fluid conduit and at least a portion of

the second fluid conduit may be co-axial.

(50) In some variations, the cone may comprise a volume of between about 10 ml and about 40 ml. In some variations, the cone may comprise a cone angle of between about 30 degrees and about 60 degrees. In some variations, at least a portion of the rotor may be optically transparent. In some variations, the rotor may comprise an asymmetric shape. In some variations, a first portion may comprise the cone and a second portion comprising a paddle shape.

(51) In some variations, a cartridge for cell processing may comprise a liquid transfer bus and a plurality of modules. Each module may be fluidically linked to the liquid transfer bus. The cartridge may comprise a counterflow centrifugal elutriation (CCE) module comprising the rotors described herein.

(52) Also described here is a rotor comprising a first fluid conduit, a first fluid conduit, a first cone coupled to the first fluid conduit. The first cone may comprise a first volume. A second fluid conduit may be coupled to the first cone. A second cone may be coupled to the second conduit. The second cone may comprise a second volume larger than the first volume. A third fluid conduit may be coupled to the second cone.

(53) In some variations, the first cone may comprise a first bicone and the second cone may comprise a second bicone. In some variations, the first bicone may comprise a third cone including a first base and a fourth cone including a second base. The first base may face the second base. The second bicone may comprise a fifth cone including a third base and a sixth cone including a fourth base. The third base may face the fourth base.

(54) In some variations, the rotor may comprise a magnetic portion. In some variations, at least a portion of the rotor may be optically transparent. In some variations, the first fluid conduit may comprise an inlet and the third fluid conduit comprises an outlet.

(55) Also described here is a system for cell processing comprising a cartridge comprising a housing comprising a rotor configured to separate cells from a fluid, and an instrument comprising a magnet configured to interface with the cartridge to magnetically rotate the rotor.

(56) In some variations, the cartridge may be configured to move between a plurality of instruments. In some variations, an air gap may be between the housing and the magnet. In some variations, the housing may enclose the rotor. In some variations, the housing may comprise a consumable component and the magnet comprises a durable component.

(57) In some variations, the magnet may be releasably coupled to the housing. In some variations, the magnet may be configured to be moved relative to the housing. In some variations, the separated cells may comprise a first size and a first density and non-separated cells of the fluid comprise a second size and a second density different from the first size and the first density. Also described here is a cartridge for cell processing, comprising a liquid transfer bus and a plurality of modules. Each module may be fluidically linked to the liquid transfer bus. The cartridge may comprise a counterflow centrifugal elutriation (CCE) module comprising the rotor described here.

(58) Also described here is a method of counterflow centrifugal elutriation (CCE) comprising moving a rotor towards a magnet, the rotor defining a rotational axis, flowing the fluid through the rotor, magnetically rotating the rotor about the rotational axis using the magnet while flowing the fluid through the rotor.

(59) In some variations, image data of one or more of the fluid and particles in the rotor may be generated using an optical sensor. One or more of a rotation rate of the rotor and a flow rate of the fluid may be selected based at least in part on the image data.

(60) In some variations, one or more of the fluid and the cells may be illuminated using an illumination source. In some variations, the method may comprise moving the rotor away from the magnet. In some variations, the method may comprising moving the rotor towards an illumination source and an optical sensor, and moving the rotor away from the illumination source and the optical sensor.

(61) In some variations, moving the rotor comprises advancing and withdrawing the magnet

relative to the rotor using a robot. In some variations, rotating the rotor comprises a rotation rate of up to 6,000 RPM. In some variations, flowing the fluid comprises a flow rate of up to about 150 ml/min while rotating the rotor.

(62) Also described here is a method of magnetic-activated cell selection comprising flowing the fluid comprising input cells into a flow cell. A set of the cells may be labeled with magnetic-activated cell selection (MACS) reagent. The set of cells may be magnetically attracted towards a magnet array for a dwell time. The set of cells may flow out of the flow cell after the dwell time.

(63) In some variations, the method may comprise incubating the MACS reagent with the input cells to label the set of cells with the MACS reagent. In some variations, the method may comprise incubating the MACS reagent may comprise a temperature between about 1° ° C. and about 10° C. In some variations, the method may comprise flowing the set of cells out of the flow cell may comprise flowing a gas through the flow cell. In some variations, the method may comprise flowing the fluid without the set of cells out of the flow cell after the dwell time. In some variations, the dwell time may be at least about one minute. In some variations, the magnet array may be disposed external to the flow cell. In some variations, the method may comprise moving the magnet array relative to the flow cell. In some variations, moving the magnet array may comprise moving the magnet array away from the flow cell to facilitate flowing the set of cells out of the flow cell. In some variations, a longitudinal axis of the flow cell may be perpendicular to ground. In some variations, the flow cell may be absent beads.

(64) Also described here is a magnetic-activated cell selection (MACS) module comprising a flow cell comprising an elongate cavity having a cavity height, a magnet array may comprise a plurality of magnets. Each of the magnets may be spaced apart by a spacing distance. A ratio of the cavity height to the spacing distance may be between about 20:1 and about 1:20.

(65) In some variations, the flow cell may comprise a set of linear channels comprising a first channel parallel to a second channel, and a third channel in fluid communication with each of the first channel and the second channel. In some variations, the first channel may comprise a first cavity height and the second channel may comprise a second cavity height. A ratio of the first cavity height to a second cavity height may be between about 1:1 to about 3:7. In some variations, the third channel may comprise a ratio of a length of the third channel to a diameter of the third channel of between about 2:1 to about 6:1.

(66) In some variations, a first fluid conduit may be coupled to an inlet of the flow cell and an outlet of the flow cell. The first fluid conduit may be configured to receive the set of cells from the flow cell. A second fluid conduit may be coupled to the inlet of the flow cell and the outlet of the flow cell. The second fluid conduit may be configured to receive a fluid without the set of cells from the flow cell.

(67) In some variations, a cartridge for cell processing may comprise a liquid transfer bus and a plurality of modules. Each module may be fluidically linked to the liquid transfer bus. The cartridge may comprise a magnetic-activated cell selection (MACS) module as described herein.

(68) Also described here is a system for cell processing comprising a cartridge comprising a rotor configured for counterflow centrifugal elutriation of cells in a fluid. A first magnet may be configured to magnetically rotate the rotor and separate the cells from the fluid in the rotor. The cartridge may further comprise a flow cell in fluid communication with the rotor and configured to receive the cells from the rotor. A second magnet may be configured to magnetically separate the cells in the flow cell.

(69) In some variations, an illumination source may be configured to illuminate the cells. An optical sensor may be configured to generate image data corresponding to the cells. In some variations, the system may comprise one or more of an oxygen depletion sensor, leak sensor, inertial sensor, pressure sensor, and bubble sensor. In some variations, the system may comprise one or more valves and pumps.

(70) In some variations, the separated cells may comprise a first size and a first density and non-

separated cells of the fluid comprise a second size and a second density different from the first size and the first density.

(71) Also described here is an electroporation module comprising a fluid conduit configured to receive a first fluid comprising cells and a second fluid, a set of electrodes coupled to the fluid conduit, a pump coupled to the fluid conduit, and a controller comprising a processor and memory. The controller may be configured to generate a first signal to introduce the first fluid into the fluid conduit using the pump, generate a second signal to introduce the second fluid into the fluid conduit such that the second fluid separates the first fluid from a third fluid, and generate an electroporation signal to electroporate the cells in the fluid conduit using the set of electrodes.

(72) In some variations, the second fluid may comprise a gas or oil. In some variations, the controller may be configured to generate a third signal to introduce the third fluid into the fluid conduit, the third fluid separated from the first fluid by the second fluid.

(73) In some variations, a cartridge for cell processing may comprise a liquid transfer bus and a plurality of modules. Each module may be fluidically linked to the liquid transfer bus. The cartridge may comprise an electroporation module as described here.

(74) Also described here is a method of electroporating cells comprising receiving a first fluid comprising cells in a fluid conduit, receiving a second fluid in the fluid conduit to separate the first fluid from a third fluid, and applying an electroporation signal to the first fluid to electroporate the cells.

(75) In some variations, the method may comprise receiving the third fluid in the fluid conduit separated from the first fluid by the second fluid. In some variations, the first fluid substantially static when applying the electroporation signal.

(76) Also described here is a method of electroporating cells comprising receiving a first fluid comprising cells in a fluid conduit, applying a resistance measurement signal to the first fluid using a set of electrodes, measuring a resistance between the first fluid and the set of electrodes, and applying an electroporation signal to the first fluid based on the measured resistance.

(77) In some variations, the method may comprise receiving a second fluid comprising a gas in the fluid conduit before applying the electroporation signal to the fluid, the first fluid separated from a third fluid by the second fluid.

(78) Also described here is a bioreactor comprising an enclosure comprising a base, a top, and at least one sidewall. A gas-permeable membrane may be coupled to one or more of the base and the sidewall of the enclosure.

(79) In some variations, the enclosure may comprise one or more nested surfaces curved around a longitudinal axis of the enclosure. In some variations, the one more nested surfaces may comprise a set of concentric toroids. In some variations, the enclosure may comprise a toroid shape. In some variations, the enclosure may comprise a first chamber having a first volume and a second chamber having a second volume, the first chamber separated from the second chamber, and the first volume smaller than the second volume. In some variations, the enclosure may comprise a column extending along a longitudinal axis of the enclosure. In some variations, a cavity may be between the enclosure and the gas-permeable membrane. In some variations, the gas-permeable membrane may extend along the base and the sidewall of the enclosure. In some variations, an outer surface of the gas-permeable membrane may comprise one or more projections.

(80) In some variations, a base of the gas-permeable membrane may comprise an angle between about 3 degrees and about 10 degrees relative to the base of the enclosure. In some variations, the gas-permeable membrane may comprise a curved surface. In some variations, the gas-permeable membrane may comprise a set of patterned curved surfaces. In some variations, the set of patterned curved surfaces may comprise a radius of curvature of between about 50 mm and about 500 mm.

(81) In some variations, a cartridge for cell processing may comprise a liquid transfer bus and a plurality of modules. Each module may be fluidically linked to the liquid transfer bus. The cartridge may comprise a bioreactor module as described here. In some variations, a system for cell

processing may comprising the cartridge described here and may further comprise a bioreactor instrument configured to interface with the cartridge. The bioreactor instrument may comprise an agitator configured to couple to the bioreactor. The agitator may be configured to agitate cell culture media comprising cells. In some variations, a fluid connector may be configured to couple the bioreactor to a liquid transfer bus. The fluid connector may comprise foldable sidewalls. In some variations, the system may comprise a temperature regulator coupled to the bioreactor. In some variations, the system may comprise a gas regulator coupled to the bioreactor.

(82) Also described here is a fluid connector comprising a first connector comprising a first proximal end configured to couple to a first fluid device, and a first distal end comprising a first port. A second connector may comprise a second proximal end configured to couple to a second fluid device, and a second distal end comprising a second port configured to couple to the first port. The first distal end may comprise a first lumen and the second distal end may comprise a second lumen. One of the first valve and the second valve may be configured to translate within the first lumen and the second lumen.

(83) In some variations, the first valve and the second valve may be configured to transition from a closed configuration to an open configuration only when the first valve couples to the second valve. In some variations, the first port and the second port may be configured to transition between an open configuration and a closed configuration. In some variations, the first connector may comprise a first port actuator and/or the second connector comprises a second port actuator. In some variations, the second port may be coupled to the first port defines a chamber.

(84) In some variations, one or more of the first connector and the second connector may comprise a sterilant port configured to couple to a sterilant source. The sterilant port may be configured to be in fluid communication with the first distal end and the second distal end when the second port is coupled to the first port.

(85) In some variations, the chamber may be configured to receive one or more of a fluid and a sterilant from the sterilant port. In some variations, the sterilant port may be configured to receive a sterilant such that the sterilant sterilizes the first connector and the second connector.

(86) In some variations, the first connector may comprise a first valve, and the second connector may comprise a second valve configured to couple to the first valve. In some variations, a first seal may comprise the first port coupled to the second port, and a second seal may comprise the first valve coupled to the second valve. In some variations, the sterilant may comprise one or more of vaporized hydrogen peroxide and ethylene oxide.

(87) In some variations, the fluid connector may comprise one or more robot engagement features. In some variations, the first connector may comprise a first alignment feature and the second connector may comprise a second alignment feature configured to couple to the first alignment feature in a predetermined axial and rotational configuration. In some variations, one or more of the first fluid device and the second fluid device may comprise an instrument.

(88) In some variations, a system may further comprise a robot configured to operate the fluid connector, and a controller comprising a memory and processor. The controller may be coupled to the robot. The controller may be configured to generate a first port signal to couple the first port to the second port using the robotic arm. In some variations, the controller may be configured to generate a first valve signal to translate the first valve relative to the second valve using the robotic arm, and generate a second valve signal to transition the first valve and the second valve to the open configuration. In some variations, the controller may be configured to generate a second port signal to decouple the first port from the second port. A sterility of the fluid connector may be maintained before coupling the first port to the second port and after decoupling the first port from the second port.

(89) In some variations, a fluid pump may be coupled to the sterilant source. The controller may be configured to generate a first fluid pump signal to circulate a fluid into the chamber through the sterilant port. In some variations, the controller may be configured to generate a second fluid pump

signal to circulate the sterilant into the chamber through the sterilant port to sterilize at least the chamber.

(90) In some variations, the controller may be configured to generate a third fluid pump signal to remove the sterilant from the chamber. In some variations, the controller may be configured to generate a thermal sterilization signal to thermally sterilize the fluid connector. In some variations, the controller may be configured to generate a radiation sterilization signal to sterilize the fluid connector using radiation. In some variations, the robot may be configured to couple a fluid connector between at least two of the plurality of instruments and the cartridge.

(91) In some variations, the fluid connector may further comprise a controller comprising a memory and processor, the controller coupled to the robot. The controller may be configured to generate a port signal to couple the first port to the second port using the robotic arm, generate a first valve signal to translate the first valve relative to the second valve using the robotic arm, and generate a second valve signal to transition the first valve and the second valve to the open configuration.

(92) Also described here is a non-transitory computer-readable medium for transforming user-defined cell processing operations into cell processing steps to be executed by an automated cell processing system. The non-transitory computer-readable medium may comprise instructions stored thereon that when executed on a processor perform the steps of receiving an ordered input list of cell processing operations, and executing a transformation model on the ordered input list to create an ordered output list of cell processing steps capable of being performed by the system.

(93) In some variations, the ordered output list may be capable of being performed by the system to control a robot to move one or more cartridges each containing a cell product between the instruments, and control the instruments to perform cell processing steps on each cell product.

(94) In some variations, the method may comprise receiving one or more sets of cell processing parameters, each set associated with one of the cell processing operations, and each set of cell processing parameters specifying characteristics of the cell processing step to be performed by the instrument at that cell processing step. In some variations, the transformation model may comprise constraints on the ordered output list determined by configuration of the automated cell processing system. In some variations, the constraints may comprise information on the configuration of the automated cell processing system. In some variations, the constraints may comprise one or more of a type and/or a number of instruments, a type and/or a number of modules on the cartridge, a type and a number of reservoirs on the cartridge, a type and/or a number of sterile liquid transfer ports on the cartridge, and a number and a position of fluid paths between the modules, reservoirs, and sterile liquid transfer ports on the cartridge.

(95) In some variations, the steps may further comprise receiving a set of more than one ordered input lists of cell processing operations to be performed on more than one cartridge on the automated cell processing system, and executing the transformation model on the sets of ordered input lists to create the ordered output list of cell processing steps. The ordered output list may be capable of being executed by the system to control the robot to move the more than one cartridges, each comprising its cell product, between the instruments, and control the instruments to perform cell processing steps on each cell product of each cartridge.

(96) In some variations, an automated cell processing system may comprise the non-transitory computer-readable medium of any preceding claim.

(97) In some variations, a computer-implemented method for transforming user-defined cell processing operations into cell processing steps to be executed by a processor of an automated cell processing system may comprise receiving an ordered input list of cell processing operations, and executing a transformation model on the ordered input list to create an ordered output list of cell processing steps capable of being performed by the system.

(98) In some variations, the method may include controlling a robot to move one or more cartridges each containing a cell product between the instruments, and controlling the instruments to perform

cell processing steps on each cell product.

(99) In some variations, the method may comprise receiving one or more sets of cell processing parameters, each set associated with one of the cell processing operations, and each set of cell processing parameters specifying characteristics of the cell processing step to be performed by the instrument at that cell processing step. In some variations, the transformation model may comprise constraints on the ordered output list determined by configuration of the automated cell processing system. In some variations, the constraints may comprise information on the configuration of the automated cell processing system.

(100) In some variations, the constraints may comprise one or more of a type and/or number of instruments, a type and/or number of modules on the cartridge, a type and number of reservoirs on the cartridge, a type and/or number of sterile liquid transfer ports on the cartridge, and a number and position of fluid paths between the modules, reservoirs, and sterile liquid transfer ports on the cartridge.

(101) In some variations, the method may comprise receiving a set of more than one ordered input lists of cell processing operations to be performed on more than one cartridge on the automated cell processing system, executing the transformation model on the sets of ordered input lists to create the ordered output list of cell processing steps, controlling the robot to move the more than one cartridges, each comprising its cell product, between the instruments, and controlling the instruments to perform cell processing steps on each cell product of each cartridge.

(102) Additional variations, features, and advantages of the invention will be apparent from the following detailed description and through practice of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a block diagram of an illustrative variation of a cell processing system.

(2) FIG. 1B is a block diagram of an illustrative variation of a cartridge.

(3) FIG. 2A is a block diagram of an illustrative variation of a cell processing system. FIG. 2B is a perspective view of an illustrative variation of a workcell of a cell processing system. FIG. 2C is a perspective view of an illustrative variation of a workcell and cartridge of a cell processing system. FIG. 2D is a block diagram of an illustrative variation of a cell processing system. FIG. 2E is a block diagram of another illustrative variation of a cell processing system.

(4) FIG. 3 is a block diagram of another illustrative variation of a cell processing system.

(5) FIG. 4A is a perspective view of another illustrative variation of a cell processing system.

(6) FIG. 4B is another perspective view of another illustrative variation of a cell processing system.

(7) FIG. 5 is a perspective view of another illustrative variation of a cell processing system.

(8) FIG. 6 is a schematic diagram of an illustrative variation of a cartridge.

(9) FIG. 7 is a schematic diagram of another illustrative variation of a cartridge.

(10) FIG. 8A is a side view of an illustrative variation of a cartridge. FIG. 8B is a top view of an illustrative variation of a cartridge. FIG. 8C is a side view of an illustrative variation of a cartridge. FIG. 8D is a perspective view of an illustrative variation of a cartridge.

(11) FIG. 9 shows a cross-sectional side view of an illustrative variation of a cartridge.

(12) FIG. 10A shows an illustrative variation of a rotary valve and an actuator. FIG. 10B shows an illustrative variation of a rotary valve docked with an actuator.

(13) FIG. 11A is a perspective view of an illustrative variation of a cartridge comprising a CCE module in an extended configuration. FIG. 11B is a cross-sectional side view of illustrative variation of a CCE module in a retracted configuration. FIG. 11C is a cross-sectional side view of an illustrative variation of a CCE module in an extended configuration.

(14) FIG. 12A is a perspective view of an illustrative variation of a magnetic-activated cell sorting

(MACS) instrument comprising a magnet in an ON configuration. FIG. 12B is a perspective view of an illustrative variation of a MACS instrument comprising a magnet in an OFF configuration.

(15) FIG. 13A is a perspective view of an illustrative variation of a cartridge and a bioreactor instrument. FIG. 13B is a perspective view of an illustrative variation of a cartridge coupled to a bioreactor instrument.

(16) FIG. 14 is a perspective view of an illustrative variation of a bioreactor instrument comprising a set of cartridges and cavities configured to receive cartridges.

(17) FIG. 15 is a block diagram of an illustrative variation of a fluid connector system.

(18) FIG. 16A is a schematic diagram of an illustrative variation of a fluid connector. FIG. 16B is a detailed schematic diagram of the fluid connector depicted in FIG. 16A. FIG. 16C is a schematic diagram of the fluid connector depicted in FIG. 16A in a coupled configuration. FIG. 16D is a schematic diagram of the fluid connector depicted in FIG. 16A in an open port configuration. FIG. 16E is a schematic diagram of the fluid connector depicted in FIG. 16A receiving a gas. FIG. 16F is a schematic diagram of the fluid connector depicted in FIG. 16A receiving a sterilant. FIG. 16G is a schematic diagram of the fluid connector depicted in FIG. 16A in an open valve configuration. FIG. 16H is a schematic diagram of the fluid connector depicted in FIG. 16A transferring fluid between fluid devices coupled to the fluid connector. FIG. 16I is a schematic diagram of the fluid connector depicted in FIG. 16A in a closed valve configuration. FIG. 16J is a schematic diagram of the fluid connector depicted in FIG. 16A in a closed port configuration. FIG. 16K is a schematic diagram of the fluid connector depicted in FIG. 16A in an uncoupled configuration. FIG. 16L is a schematic diagram of the fluid connector depicted in FIG. 16A uncoupled from a sterilant source.

(19) FIG. 17A is a front perspective view of a fluid connector in a closed port configuration. FIG. 17B is a rear perspective view of the fluid connector depicted in FIG. 17A in the closed port configuration. FIG. 17C is a rear view of the fluid connector depicted in FIG. 17B in the closed port configuration. FIG. 17D is a front perspective view of a fluid connector in an open port configuration. FIG. 17E is a rear perspective view of the fluid connector depicted in FIG. 17D in the open port configuration. FIG. 17F is a rear view of the fluid connector depicted in FIG. 17E in the open port configuration.

(20) FIG. 18A is a side view of a fluid connector in an uncoupled configuration. FIG. 18B is a cross-sectional side view of a fluid connector in an uncoupled configuration. FIG. 18C is a side view of a fluid connector in a coupled configuration. FIG. 18D is a cross-sectional side view of a fluid connector in a coupled configuration. FIG. 18E is a side view of a fluid connector in an open port configuration. FIG. 18F is a cross-sectional side view of a fluid connector in an open port configuration. FIG. 18G is a side view of a fluid connector in an open valve configuration. FIG. 18H is a cross-sectional side view of a fluid connector in an open valve configuration.

(21) FIG. 19 is a schematic diagram of an illustrative variation of a fluid connector system.

(22) FIG. 20A is a schematic diagram of an illustrative variation of a fluid connector system.

(23) FIGS. 20B and 20C are schematic diagrams of an illustrative variation of a fluid connector connection process.

(24) FIG. 21 is a block diagram of an illustrative variation of a fluid connector system.

(25) FIG. 22 is a block diagram of an illustrative variation of a fluid connector system.

(26) FIG. 23 is a block diagram of an illustrative variation of a fluid connector system.

(27) FIG. 24A is a block diagram of an illustrative variation of a fluid connector system. FIG. 24B is a schematic diagram of an illustrative variation of a fluid connector connection process. FIG. 24C is a schematic diagram of an illustrative variation of a valve.

(28) FIG. 25A is a block diagram of an illustrative variation of a fluid connector system. FIG. 25B is a schematic diagram of an illustrative variation of a fluid connector connection process. FIG. 25C is a schematic diagram of an illustrative variation of a valve.

(29) FIG. 26A is a side view of an illustrative variation of a pump actuator and pump. FIG. 26B is a side view of an illustrative variation of a pump actuator coupled to a pump.

- (30) FIG. 27 is a flowchart of an illustrative variation of a method of transferring fluid using a fluid connector.
- (31) FIG. 28 is a flowchart of an illustrative variation of a method of cell processing.
- (32) FIG. 29 is a flowchart of an illustrative variation of a method of cell processing.
- (33) FIG. 30A is a flowchart of an illustrative variation of a method of cell processing for autologous CAR T cells or engineered TCR cells. FIG. 30B is a flowchart of an illustrative variation of a method of cell processing for allogeneic CAR T cells or engineered TCR cells.
- (34) FIG. 31 is a flowchart of an illustrative variation of a method of cell processing for HSC cells.
- (35) FIG. 32 is a flowchart of an illustrative variation of a method of cell processing for TIL cells.
- (36) FIG. 33 is a flowchart of an illustrative variation of a method of cell processing for NK-CAR cells.
- (37) FIGS. 34A-34C are flowcharts of illustrative variations of methods of cell processing for Treg cells.
- (38) FIG. 35 is a flowchart of an illustrative variation of a method of cell processing.
- (39) FIG. 36 is a flowchart of an illustrative variation of a method of executing a transformation model.
- (40) FIG. 37 is an illustrative variation of a graphical user interface relating to an initial process design interface.
- (41) FIG. 38 is an illustrative variation of a graphical user interface relating to creating a process.
- (42) FIG. 39 is an illustrative variation of a graphical user interface relating to an empty process.
- (43) FIG. 40 is an illustrative variation of a graphical user interface relating to adding a reagent and a consumable container.
- (44) FIG. 41 is an illustrative variation of a graphical user interface relating to a process parameter.
- (45) FIG. 42 is an illustrative variation of a graphical user interface relating to a patient weight process parameter.
- (46) FIG. 43 is an illustrative variation of a graphical user interface relating to a preprocess analytic.
- (47) FIG. 44 is an illustrative variation of a graphical user interface relating to a white blood cell count preprocess analytic.
- (48) FIG. 45 is an illustrative variation of a graphical user interface relating to process parameter calculation.
- (49) FIG. 46 is an illustrative variation of a graphical user interface relating to a completed process setup.
- (50) FIG. 47 is an illustrative variation of a graphical user interface relating to process operations activation settings.
- (51) FIG. 48 is an illustrative variation of a graphical user interface relating to a filled process operations activation settings.
- (52) FIG. 49 is an illustrative variation of a graphical user interface relating to an initial process operations.
- (53) FIG. 50 is an illustrative variation of a graphical user interface relating to dragging in process operations.
- (54) FIG. 51 is another illustrative variation of a graphical user interface relating to dragging in process operations.
- (55) FIG. 52 is an illustrative variation of a graphical user interface relating to a filled process operations.
- (56) FIG. 53 is an illustrative variation of a graphical user interface relating to product monitoring.
- (57) FIG. 54 is another illustrative variation of a graphical user interface relating to product monitoring.
- (58) FIG. 55 is a block diagram of an illustrative variation of a manufacturing workflow.
- (59) FIG. 56 is a block diagram of an illustrative variation of a cell separation system.

(60) FIG. 57 is a cross-sectional side view of an illustrative variation of a counterflow centrifugal elutriation (CCE) module.

(61) FIG. 58 is a cross-sectional side view of an illustrative variation of a magnetic-activated cell selection (MACS) module.

(62) FIGS. 59A-59C are perspective views of an illustrative variation of a CCE system. FIG. 59D is a side cross-sectional view of an illustrative variation of a CCE system. FIGS. 59E-59G are side cross-sectional views of an illustrative variation of a rotor of a CCE module.

(63) FIG. 60A is a plan view of an illustrative variation of a rotor of a CCE module. FIGS. 60B and 60C are perspective views of an illustrative variation of a rotor of a CCE module. FIG. 60D is a side view of an illustrative variation of a rotor of a CCE module. FIG. 60E is a perspective view of an illustrative variation of a rotor in a housing. FIGS. 60F and 60G are plan schematic views of illustrative variations of a rotor of a CCE module. FIG. 60H is a side view of an illustrative variation of a rotor of a CCE module. FIG. 60I is a perspective view of another illustrative variation of a rotor of a CCE module. FIG. 60J is a perspective view of yet another illustrative variation of a rotor of a CCE module. FIG. 60K is a schematic plan view of another illustrative variation of rotor dimensions of a CCE module. FIG. 60L is an image of a set of illustrative variations of rotors of a CCE module.

(64) FIGS. 61A-61C are schematic views of an illustrative variation of a cell separation process.

(65) FIG. 62A is a perspective view of an illustrative variation of a MACS system in a first configuration. FIG. 62B is a perspective view of an illustrative variation of a MACS system in a second configuration. FIG. 62C is a cross-sectional side view of an illustrative variation of a MACS system. FIG. 62D is a perspective view of an illustrative variation of a MACS system in the second configuration. FIG. 62E is a plan view of an illustrative variation of a flow cell and magnet array of a MACS system. FIG. 62F is a plan view of an illustrative variation of a flow cell of a MACS system. FIG. 62G is a schematic diagram of an illustrative variation of a flow cell and magnet array.

(66) FIGS. 63A-63E are perspective views of illustrative variations of a magnet array.

(67) FIG. 64A is a perspective view of an illustrative variation of a flow cell. FIG. 64B is a cross-sectional side view of an illustrative variation of a flow cell. FIG. 64C is a schematic diagram of an illustrative variation of a MACS system.

(68) FIGS. 65A-65C are schematic diagrams of an illustrative variation of a flow cell.

(69) FIGS. 66A-66C are schematic diagrams of an illustrative variation of a cell separation process.

(70) FIGS. 67A-67D are schematic diagrams of an illustrative variation of a cell processing system.

(71) FIG. 68A is a cross-sectional perspective view of an illustrative variation of a bioreactor.

(72) FIG. 68B is a cross-sectional side view of an illustrative variation of a bioreactor. FIG. 68C is a perspective view of an illustrative variation of an enclosure of a bioreactor. FIG. 68D is a plan view of an illustrative variation of an enclosure of a bioreactor.

(73) FIG. 68E is a perspective view of an illustrative variation of a membrane of a bioreactor.

(74) FIG. 68F is a side view of an illustrative variation of a membrane of a bioreactor. FIG. 68G is a perspective view of an illustrative variation of a membrane of a bioreactor. FIG. 68H is a bottom view of an illustrative variation of a membrane of a bioreactor.

(75) FIG. 69A is a cross-sectional side view of an illustrative variation of an enclosure of a bioreactor. FIG. 69B is a cross-sectional perspective view of an illustrative variation of an enclosure of a bioreactor.

(76) FIG. 70 is an exploded perspective view of an illustrative variation of a bioreactor.

(77) FIG. 71A is a plan view of an illustrative variation of a bioreactor. FIG. 71B is a cross-sectional side view of an illustrative variation of a bioreactor.

(78) FIG. 72 is a schematic diagram of an illustrative variation of an electroporation system.

(79) FIG. 73 is an exploded perspective view of an illustrative variation of an electroporation module.

(80) FIGS. **74A-74B** are schematic diagrams of illustrative variation of an electroporation process.

(81) FIG. **75** is a circuit diagram of an illustrative variation of an electroporation process.

(82) FIGS. **76A-76D** are plots of illustrative variations of an electroporation process.

(83) FIG. **77A** is a flowchart of an illustrative variation of a method of separating cells. FIG. **77B** is a flowchart of an illustrative variation of a method of concentrating cells. FIG. **77C** is a flowchart of an illustrative variation of a method of buffer exchange.

(84) FIG. **78** is a flowchart of another illustrative variation of a method of separating cells.

(85) FIG. **79A** is a flowchart of an illustrative variation of a closed-loop method of separating cells **7900**. FIG. **79B** is a flowchart of an illustrative variation of a closed-loop method of elutriating cells **7910**. FIG. **79C** is a flowchart of an illustrative variation of a closed-loop method of harvesting cells **7920**.

(86) FIG. **80A** is a flowchart of an illustrative variation of a method of separating cells. FIG. **80B** is a flowchart of an illustrative variation of a method of selecting cells.

(87) FIG. **81** is a flowchart of another illustrative variation of a method of separating cells.

(88) FIG. **82A** is a flowchart of an illustrative variation of a method of preparing a bioreactor.

(89) FIG. **82B** is a flowchart of an illustrative variation of a method of loading a bioreactor. FIG. **82C** is a flowchart of an illustrative variation of a method of preparing a bioreactor. FIG. **82D** is a flowchart of an illustrative variation of a method of calibration for a bioreactor. FIG. **82E** is a flowchart of an illustrative variation of a method of mixing reagents. FIG. **82F** is a flowchart of an illustrative variation of a method of mixing reagents. FIG. **82G** is a flowchart of an illustrative variation of a method of culturing cells. FIG. **82H** is a flowchart of an illustrative variation of a method of refrigerating cells. FIG. **82I** is a flowchart of an illustrative variation of a method of taking a sample. FIG. **82J** is a flowchart of an illustrative variation of a method of culturing cells.

(90) FIG. **82K** is a flowchart of an illustrative variation of a method of media exchange. FIG. **82L** is a flowchart of an illustrative variation of a method of controlling gas. FIG. **82M** is a flowchart of an illustrative variation of a method of controlling pH.

(91) FIG. **83** is a flowchart of an illustrative variation of a method of electroporating cells.

(92) FIG. **84** is a flowchart of another illustrative variation of a method of electroporating cells.

(93) FIG. **85** are schematic diagrams of an illustrative variation of a fluid connector.

(94) FIG. **86** are schematic diagrams of an illustrative variation of a fluid connector port.

(95) FIG. **87** is a schematic diagram of an illustrative variation of a fluid connector connection process.

(96) FIG. **88** is a schematic diagram of an illustrative variation of a fluid connector connection process.

(97) FIG. **89** is a schematic diagram of an illustrative variation of a fluid connector.

(98) FIG. **90A** is a side view of an illustrative variation of a fluid connector. FIG. **90B** is a perspective view of the fluid connector depicted in FIG. **90A**. FIG. **90C** is a cross-sectional side view of the fluid connector depicted in FIG. **90A**.

(99) FIG. **91A** is a side view of an illustrative variation of a fluid connector. FIG. **91B** is a perspective view of the fluid connector depicted in FIG. **91A**. FIG. **91C** is a cross-sectional side view of the fluid connector depicted in FIG. **91A**.

(100) FIG. **91D** is a side view of an illustrative variation of a fluid connector. FIG. **91E** is a perspective view of the fluid connector depicted in FIG. **91D**. FIG. **91F** is a cross-sectional side view of the fluid connector depicted in FIG. **91D**.

(101) FIG. **92A** is a side view of an illustrative variation of a fluid connector. FIG. **92B** is a transparent side view of the fluid connector depicted in FIG. **92A**. FIG. **92C** is a perspective view of the fluid connector depicted in FIG. **92A**. FIG. **92D** is a cross-sectional side view of the fluid connector depicted in FIG. **92A**.

(102) FIG. **93A** is a perspective view of an illustrative variation of a fluid connector. FIG. **93B** is a transparent perspective view of the fluid connector depicted in FIG. **93A**.

(103) FIG. **94A** is a perspective view of an illustrative variation of a fluid connector. FIG. **94B** is a transparent perspective view of the fluid connector depicted in FIG. **94A**.

(104) FIG. **95A** is a perspective view of an illustrative variation of a fluid connector. FIG. **95B** is a transparent perspective view of the fluid connector depicted in FIG. **95A**. FIG. **95C** is a detailed side view of a port in an open port configuration. FIG. **95D** is a detailed side view of a port in a closed port configuration.

(105) FIG. **96A** is a plan view of an illustrative variation of a fluid device. FIG. **96B** is a side view of an illustrative variation of a fluid device coupled to a robot. FIG. **96C** is a perspective view of an illustrative variation of a fluid device held by a robot.

(106) FIG. **97A** is a perspective view of an illustrative variation of a MACS module. FIG. **97B** is a cross-sectional perspective view of an illustrative variation of a MACS module. FIG. **97C** is a cross-sectional side view of an illustrative variation of a MACS module.

(107) FIG. **98** is a flowchart of an illustrative variation of a method of cell processing.

(108) FIG. **99** is a flowchart of an illustrative variation of a method of cell processing.

(109) FIG. **100** is a flowchart of an illustrative variation of a method of cell processing.

(110) FIG. **101** is a flowchart of an illustrative variation of a method of cell processing.

(111) FIG. **102** is a schematic diagram of an illustrative variation of a cell processing system.

(112) FIGS. **103A** and **103B** are perspective views of an illustrative variation of a sterile liquid transfer device.

DETAILED DESCRIPTION

(113) Systems and methods for processing and manufacturing cell products for biomedical applications are described herein. Cell processing methods and systems may comprise moving a cartridge containing a cell product between a plurality of instruments inside a workcell. One or more instruments may be configured to interface with the cartridge to perform cell processing steps on the cell product, such that the system (e.g., workcell) performs cell processing steps on the cell product. In some variations, a plurality of cell processing steps may be performed within a single cartridge. For example, a robotic arm may be configured to move a cartridge between instruments for different cell processing steps. The cartridge may comprise a plurality of cell processing devices (e.g., modules) such as a bioreactor, a counterflow centrifugal elutriation (CCE) module, a magnetic cell sorter (e.g., magnetic-activated cell selection module), an electroporation device (e.g., electroporation module), a sorting module (e.g. fluorescence activated cell sorting (FACS) module), an acoustic flowcell module, a centrifugation module, a microfluidic enrichment module, combinations thereof, and the like. In some variations, the system may process two or more cartridges in parallel. For example, the bioreactor may comprise a plurality of slots configured to interface with a plurality of cartridges concurrently, as one process step (e.g., cell culturing in a bioreactor) may typically be the rate limiting step for the operation of the cell processing system. The cell processing systems described herein may reduce operator intervention and increase throughput by automating cartridge (and cell product) movement between instruments using a robot. However, in some variations, the cartridge may be moved between instruments manually. Furthermore, throughput of the system may be increased by using a plurality of bioreactors, thereby allowing the system to simultaneously process a plurality of cartridges for a plurality of patients. Moreover, the automated cell processing system may facilitate sterile liquid transfers between the cartridge and instruments or other components of the system such as a fluid connector (e.g., sterile liquid transfer port), reagent vault, a second cartridge, a sampling vessel (e.g., sterile liquid transfer device, combinations thereof, and the like.

(114) Workcell

(115) In some variations, a system for cell processing (e.g., workcell) may comprise a plurality of instruments each independently configured to perform one or more cell processing operations upon a cartridge. A robot may be configured to move the cartridge between each of the plurality of instruments. The instruments may comprise one or more of a bioreactor instrument, a cell selection

instrument (e.g., a magnetic-activated cell selection instrument), a sorting instrument (e.g., a fluorescence activated cell sorting (FACS) instrument), an electroporation instrument, a counterflow centrifugal elutriation (CCE) instrument, a reagent vault, and the like. The system may perform automated manufacturing of cell products.

(116) A cartridge may be configured to be portable and facilitate automated and sterile cell processing using a workcell and robot. For example, the cartridge may be configured to move relative to one or more instruments of the workcell to perform different cell processing steps. In some variations, an instrument may be configured to move relative to a cartridge. In some variations, the cartridge may comprise a plurality of modules including one or more of a bioreactor module, a cell selection module (e.g., magnetic-activated cell selection module), a sorting module (e.g., fluorescence activated cell sorting (FACS) module), an electroporation module, and a counterflow centrifugal elutriation (CCE) module. The cartridge may further comprise one or more of a sterile liquid transfer port, a liquid transfer bus fluidically coupled to each module, and a pump fluidically coupled to the liquid transfer bus.

(117) In some variations, a method of processing a solution containing a cell product may include the cell processing steps of digesting tissue using an enzyme reagent to release a select cell population into solution, enriching cells using a CCE instrument, washing cells using the CCE instrument, selecting cells in the solution using a selection instrument, sorting cells in the solution using a sorting instrument, differentiating or expanding the cells in a bioreactor, activating cells using an activating reagent, electroporating cells, transducing cells using a vector, and finishing a cell product.

(118) Cell Selection System

(119) The cell processing systems described herein may comprise a cell selection system configured to separate cells based on predetermined criteria. For example, cells may be separated based on physical characteristics such as size and/or density using, for example, a counterflow centrifugation elutriation instrument. Cells may also be separated based on the presence of predetermined antigens of a cell using, for example, a magnetic-activated cell selection instrument. In some variations, a cell selection system comprising modules for these separation methods may facilitate one or more cell processing steps including, but not limited to, cell concentration, cell dilution, cell washing, buffer replacement, and magnetic separation. The cell selection systems described herein may increase throughput and cell yields output, in a compact and portable structure. For example, prior to magnetically separating cells, a suspension of cells may be mixed with magnetic reagents in excess or at a predetermined concentration (e.g., cells/ml). Likewise, after magnetically separating cells, the cells may be washed in a solution (e.g., suitable buffered solution).

(120) In some variations, a cell separation system may comprise a rotor configured for counterflow centrifugation elutriation of cells in a fluid, a first magnet configured to magnetically rotate the rotor and separate the cells from the fluid in the rotor, a flow cell in fluid communication with the rotor and configured to receive the cells from the rotor, and a second magnet configured to magnetically separate the cells in the flow cell.

(121) In some variations, a CCE module may be integrated into a cartridge to enable a cell processing system to separate cells based on cell size and/or density. In some variations, a cell separation system may comprise a housing comprising a rotor configured to separate cells from a fluid (e.g., separate cells of different size and/or density from cells that remain in the fluid), and a magnet configured to magnetically rotate the rotor. The housing may be configured to move relative to the magnet or vice versa (e.g., move the magnet relative to the housing). The CCE modules described herein may provide cell separation within a compact and portable housing where the magnet may be disposed external to the housing (e.g., magnet disposed within a CCE instrument).

(122) In some variations, a compact rotor that may aid cartridge integration may comprise input

and output fluid conduits extending from the rotor towards opposing sides of a rotor housing. For example, a rotor may comprise a first side comprising a first fluid conduit and a second side comprising a second fluid conduit where the second side is opposite the first side. An elutriation chamber (e.g., cone) may be coupled between the first fluid conduit and the second fluid conduit. (123) In some variations, a method of separating cells from a fluid may comprise moving a rotor towards a magnet, the rotor defining a rotational axis, flowing the fluid through the rotor, rotating the rotor (e.g., magnetically) about the rotational axis using the magnet while flowing the fluid through the rotor, and moving the rotor away from the magnet.

(124) In some variations, a method of separating cells from a fluid may comprise flowing the fluid comprising the cells into a flow cell. A set of the cells may be labeled with magnetic particles. The set of cells may be magnetically attracted towards a magnet array for a dwell time, and the set of cells may flow out of the flow cell after the dwell time.

(125) In some variations, a flow cell may comprise an elongate cavity having a cavity height and a magnet array comprising a plurality of magnets, each of the magnets spaced apart by a spacing distance. A predetermined ratio between the cavity height to the spacing distance may optimize magnetic separation of the cells in the flow cell.

(126) Electroporation

(127) In some variations, an electroporation module as described herein may be configured to facilitate one or more of transduction and transfection of cells. As described in more detail herein, a volume of fluid (e.g., first batch) comprising cells may be physically separated from a subsequent volume of fluid (e.g., second batch, third batch) comprising cells by a gas (e.g., air gap). Applying an electroporation signal (e.g., voltage pulse, waveform) separately to each discrete batch of fluid may improve electroporation efficiency and thus increase throughput. In some variations, active electric field compensation may similarly improve electroporation efficiency and throughput.

(128) In some variations, a cell processor may comprise a fluid conduit configured to receive a first fluid comprising cells and a second fluid (e.g., gas, oil), a set of electrodes coupled to the fluid conduit, a pump coupled to the fluid conduit, and a controller comprising a processor and memory. The controller may be configured to generate a first signal to introduce the first fluid into the fluid conduit using the pump, generate a second signal to introduce the second fluid into the fluid conduit such that the second fluid separates the first fluid from a third fluid, and generate an electroporation signal to electroporate the cells in the fluid conduit using the set of electrodes.

(129) In some variations, a method of electroporating cells may comprise receiving a first fluid comprising cells in a fluid conduit, receiving a second fluid comprising a gas in the fluid conduit to separate the first fluid from a third fluid, and applying an electroporation signal to the first fluid to electroporate the cells.

(130) In some variations, a method of electroporating cells may comprise receiving a first fluid comprising cells in a fluid conduit, applying a resistance measurement signal to the first fluid using a set of electrodes, measuring a resistance between the first fluid and the set of electrodes, and applying an electroporation signal to the first fluid based on the measured resistance.

(131) Bioreactor

(132) In some variations, a bioreactor may comprise an enclosure comprising a base and a sidewall, and a gas-permeable membrane coupled to one or more of the base and the sidewall of the enclosure. The gas-permeable membrane may aid cell culture. In some variations, a cell processing system may comprise the bioreactor and an agitator coupled to the bioreactor. The agitator may be configured to agitate the bioreactor based on orbital motion.

(133) Fluid Connector

(134) Currently, there is no automated, multi-use sterile fluid connector solution for cell therapy production where a set of sterile fluid connectors are capable of multiple connection and disconnection cycles with a system. For example, conventional sterile fluid connectors are typically single-use devices and are thus expensive and labor intensive. Generally, the fluid connectors

described herein include a plurality of sealed enclosures between a sterile portion (e.g., fluid connector lumen or cavity) and an external (e.g., non-sterile) ambient environment, thereby facilitating aseptic control of a fluid connector and devices coupled thereto. The fluid connectors described herein may be a durable component that may be reused for multiple cycles while maintaining sterility and/or bioburden control. For example, the fluid connector may be sterilized using a sterilant without harming the cell product or other biological material.

(135) In some variations, a sterile manufacturing system as described herein may utilize one or more sterile fluid connectors and have a configuration suitable to be manipulated by a robot such as a robotic arm. The sterile fluid connectors described herein enable the transfer of fluids in an automated, sterile, and metered manner for automating cell therapy manufacturing. Automating cell therapy manufacturing may in turn provide lower per patient manufacturing costs, a lower risk of process failure, and the ability to meet commercial scale patient demand for cell therapies. In some variations, sterile fluid connectors may increase one or more of sterility, efficiency, and speed by removing a human operator from the manufacturing process. An automated and integrated sterilization process as described herein may be applied to the fluid connector to maintain sterility of the system. For example, the fluid connector may maintain sterility through multiple connection/disconnection cycles between separate sterile closed volume fluid devices (e.g., enclosure, container, vessel, cartridge, instrument, bioreactor, enclosed vessel, sealed chamber). Accordingly, the systems, devices, and methods described herein may reduce the complexity of a sterilization process, reduce energy usage, and increase sterilization efficiency.

(136) In some variations, a fluid connector may comprise a first connector configured to mate with a second connector (e.g., male connector and female connector). Respective proximal ends of the connectors may be configured to connect (e.g., be in fluid communication, form a fluid pathway) with respective fluid devices in order to transfer one or more of fluid (e.g., liquid and/or gas) and biological material (e.g., cell product) between the fluid devices. The distal ends of the connectors may comprise ports configured to mate with each other. The fluid connector may also comprise a sterilant port configured to facilitate sterilization of a chamber within the distal ends of the first and second connectors. The fluid connector may be sterilized before or after connection as desired to ensure sterility. In this manner, the fluid connector may be reused for multiple connection and disconnection cycles.

(137) In some variations, a system (e.g., workcell) utilizing the fluid connectors described herein may comprise a robot configured to operate the fluid connector and a controller configured to control the robot to manipulate (e.g., move, connect, open, close, disconnect) the first and second connectors together (without human interaction) while maintaining sterility of the fluid connector and a plurality of fluid devices, thereby further reducing the risk of contamination. The fluid devices may be one or more of an instrument, cartridge, and the like.

(138) Cell Processing Control

(139) Systems and methods for manufacturing cell products for biomedical applications using automated systems are described herein. Conventional semi-automated solutions for cell processing do not allow users to define biological processes. Instead, users select from a limited set of predefined machine processes and process-control parameters. Currently, there is no scalable manufacturing solution for cell therapy production. For example, cell therapy manufacturing is conventionally executed batchwise (i.e. one product will be manufactured in a single room/suite, with required processing tools located inside). This can either be guided by a technician following a standard operating procedure (SOP), or in some cases, processing tools (e.g., Miltenyi Prodigy, Lonza Cocoon) can carry out a series of processing steps for a single patient product on a single multi-functional processing tool. However, existing solutions (e.g., Miltenyi Prodigy) do not allow users to define biological processes. Furthermore, the manual labor required of conventional solutions increases the risk of product contamination and human error.

(140) In some variations, a set of cell therapy biological manufacturing processes may be

transformed into a set of machine instructions suitable for automated execution using the systems described herein. For example, a method of transforming user-defined cell processing operations into cell processing steps to be executed by a processor of an automated cell processing system may comprise receiving an ordered input list of cell processing operations, and executing a transformation model on the ordered input list to create an ordered output list of cell processing steps capable of being performed by the system. As used herein, a transform model may refer to an algorithm, process, or transformation configured to translate a set of cell processing steps into a set of machine or hardware instructions for the system. In some variations, a robot may be controlled to move one or more cartridges each containing a cell product between the instruments, and the instruments may be controlled to perform cell processing steps on each cell product. In this manner, the systems and methods enable biologists to define manufacturing processes in biological terms and have the system transform this biological model (e.g., process definition) into a set of machine-executed instructions.

(141) The end-to-end closed system automation described herein may reduce process failure rates and cost. For example, end-to-end automation may reduce manufacturing time (e.g., dwell times) and increase throughput as compared to conventional manual methods. For example, a plurality of processes (e.g., 10 or more) may be executed simultaneously. The methods described herein may further reduce opportunities for contamination and user error. Thus, the systems, apparatuses, and methods described herein may increase one or more of cell processing automation, repeatability, reliability, process flexibility, instrument throughput, process scalability, and reduce one or more of labor costs, and process duration.

I. System

(142) Described here are systems and apparatuses configured to perform cell processing steps to manufacture a cell product (e.g., cell therapy product). In some variations, a cell processing system may comprise a plurality of instruments each independently configured to perform one or more cell processing operations upon a cartridge (e.g., fluid device), and a robot capable of moving the cartridge between each of the plurality of instruments. The use of a robot and controller may facilitate one or more of automation, efficiency, and sterility of a cell processing system.

(143) In some variations, a system for cell processing may comprise a plurality of instruments each independently configured to perform one or more cell processing operation upon a cartridge. A robot may be capable of moving the cartridge between each of the plurality of instruments. In some variations, the system may be a workcell comprising an enclosure.

(144) FIG. 1A is a block diagram of a cell processing system **100** comprising a workcell **110** and controller **120**. In some variations, the workcell **110** may comprise one or more of an instrument **112**, a cartridge **114** (e.g., consumable, fluid device), a robot **116** (e.g., robotic arm), a reagent vault **118**, a fluid connector **132**, a sterilant source **134**, a fluid source **136**, a pump **138**, a sensor **140**, and a sterile liquid transfer device **142**. In some variations, the controller **120** may comprise one or more of a processor **122**, a memory **124**, a communication device **126**, an input device **128**, and a display **130**.

(145) In some variations, a workcell may comprise a fully, or at least partially, enclosed housing inside which one or more cell processing steps are performed in a fully, or at least partially, automated process. In some variations, the workcell may be an open system lacking an enclosure, which may be configured for use in clean room, biosafety cabinet, or other sterile location. In some variations, the cartridge **114** may be moved using the robot **116** to reduce manual labor in the cell processing steps. In some variations, the workcell may be configured to perform sterile liquid transfers into and out of the cartridge in a fully or partially automated process. For example, one or more fluids may be stored in a sterile liquid transfer device **142**. In some variations, the sterile liquid transfer device may be a portable consumable that may be moved within the system **100**. The sterile liquid transfer devices and fluid connectors described herein enable the transfer of fluids in an automated, sterile, and metered manner for automating cell therapy manufacturing. In some

variations, the enclosure of the workcell may be configured to meet International Organization for Standardization (ISO) standard ISO7 or better (e.g., ISO6 or ISO5). An advantage of meeting ISO7 or better standards is that the system may be used in a facility that does not meet ISO7 standards (i.e. that lack a clean room or other sufficiently filtered air space). Optionally, the facility may be an ISO8 or ISO9 facility. In some variations, a workcell may comprise a volume of less than about 800 m.sup.3, less than about 700 m.sup.3, less than about 600 m.sup.3, less than about 500 m.sup.3, less than about 300 m.sup.3, less than about 250 m.sup.3, less than about 200 m.sup.3, less than about 150 m.sup.3, less than about 100 m.sup.3, less than about 50 m.sup.3, less than about 25 m.sup.3, less than about 10 m.sup.3, and less than about 5 m.sup.3, including all ranges and sub-values in-between.

(146) In some variations, a robot **116** may be configured to manipulate consumable cartridges **114** and fluid connectors **132** between different instruments to perform a predetermined sequence of cell processing steps. In some variations, the same consumable cartridge **114** may be received by different instruments **112** and/or multiple cartridges **114** may be processed in parallel.

(147) In some variations, a cartridge **114** may contain cell product from different donors or contain cell product intended for different recipients. The cell product from a single donor may be split between multiple cartridges **114** if necessary to generate enough product for therapeutic use, or when a donor is providing product for several recipients (e.g., for allogeneic transplant). The cell product for a single recipient may be split between multiple cartridges **114** if necessary to generate enough product for therapeutic use in that recipient. The cell product for a single recipient may be split between multiple cartridges **114** if necessary to generate several cell products with unique genetic modifications, and then optionally recombined in certain ratios for therapeutic use in that recipient. For example, a fluid connector **132** may be coupled between two or more cartridges **114** to transfer a cell product and/or fluid between the cartridges **114**. Furthermore, a fluid connector **132** may be coupled between any set of fluid-carrying components of the system **100** (e.g., cartridge **114**, reagent vault **118**, fluid source **136**, sterile liquid transfer device **142**, fluid conduit, container, vessel, etc.). For example, a first fluid connector may be coupled between a first cartridge and a sterile liquid transfer device, and a second fluid connector may be coupled between the sterile liquid transfer device and a second cartridge.

(148) As illustrated in FIG. 1B, a cartridge **114** may comprise one or more of a bioreactor **150**, cell separation system **152**, electroporation module **160**, liquid transfer bus **162**, sensor **164**, and fluid connector **166**, as described in more detail herein. A cell separation system **152** may comprise one or more of a rotor **154**, flow cell **156**, and magnet **158**. In some variations, the magnet **158** may comprise one or more magnets and/or magnet arrays. For example, the cell separation system **152** may comprise a first magnet configured to magnetically rotate a rotor **154** and a second magnet (e.g., magnet array) configured to magnetically separate cells in flow cell **156**.

(149) Workcell

(150) In some variations, a workcell **110** may comprise at least a partially enclosed enclosure (e.g., housing) in which one or more automated cell processing steps are performed. For example, the workcell **110** may be configured to transfer sterile liquid into and out of a cartridge **114** in a fully or partially automated process. In some variations, a workcell **110** may not have an enclosure and be configured for use in a clean room, a biosafety cabinet, or other suitably clean or sterile location. In some variations, the workcell **100** may comprise a feedthrough access biosafety cabinet, quality control instrumentation, pump, consumable (e.g., fluid device), fluid connector, consumable feedthrough, and sterilization system (e.g., sterilant source and/or generator, fluid source, heater/dessicator, aerator).

(151) FIG. 2A is a block diagram of a cell processing system including a workcell **203**. Workcell **203** may comprise an enclosure **202** having four walls, a base, and a roof. The workcell may be divided into an interior zone **204** with a feedthrough **206** access, and quality control (QC) instrumentation **212**. An air filtration inlet (not shown) may provide high-efficiency particulate air

(HEPA) filtration to provide ISO7 or better air quality in the interior zone **204**. This air filtration may maintain sterile cell processing in an ISO8 or ISO9 manufacturing environment. The workcell **203** may also have an air filter on the air outlet to preserve the ISO rating of the room. In some variations, the workcell **203** may further comprise, inside the interior zone **104**, a bioreactor instrument **214**, a cell selection instrument **216** (e.g., MACS), an electroporation instrument (EP) **220**, a counterflow centrifugation elutriation (CCE) instrument **222**, a sterile liquid transfer instrument **224** (e.g., fluid connector), a reagent vault **226**, and a sterilization system **260**. The reagent vault **226** may be accessible by a user through a sample pickup port **228**. A robot **230** (e.g., support arm, robotic arm) may be configured to move one or more cartridges **250** (e.g., consumables) from any instrument to any other instrument and/or move one or more cartridges **250** to and from a reagent vault. In some variations, the workcell **203** may comprise one or more moveable barrier **213** (e.g., access, door) configured to facilitate access to one or more of the instruments in the workcell **203**.

(152) In some variations of methods according to the disclosure, a human operator may load one or more empty cartridges **250** into the feedthrough **206** via cartridge port **207**. The cartridges **250** may be pre-sterilized, or the feedthrough **206** may sterilize the cartridge **250** using ultraviolet radiation (UV), or chemical sterilizing agents provided as a vapor, spray, or wash. The feedthrough **206** chamber may optionally be configured to automatically spray, wash, irradiate, or otherwise treat cartridges (e.g. with ethanol and/or isopropyl alcohol solutions, vaporized hydrogen peroxide (VHP)) to maintain sterility of the interior zone **204** (e.g., ISO 7 or better). The cartridge **250** may be passed to the biosafety cabinet **206**, where input cell product is provided and loaded to the cartridge through a sterile liquid transfer port into the cartridge **250**. The user (via robot **230**) may then move the cartridge **250** back to the feedthrough **206** and initiate automated processing using a computer processor in the computer server rack (e.g., controller **120**). The robot **230** may be configured to move the cartridge **250** in a predefined sequence to a plurality of instruments and stations, with the components of the workcell **200**. At the end of cell processing, the cartridge **250**, now containing the processed cell product, may be returned to the feedthrough **206** for retrieval by the user. In some variations, an outer surface of the enclosure **202** may comprise an input/output device **208** (e.g., display, touchscreen).

(153) FIG. 2B is a perspective view of a workcell **205** of a cell processing system. FIG. 2C is a perspective view of a cell processing system depicting a cartridge **250** (e.g., any of the cartridges described herein) introduced into a workcell **205** (e.g., any of the workcells described herein). A plurality of cartridges may be inserted into the workcell **205** simultaneously and undergo one or more cell processing operations in parallel.

(154) In some variations, the workcell **205** may comprise a height of more than about a meter, between about 1 m and about 3 m, between about 1 m and about 5 m, between about 3, and about 10 m, between about 5 m and about 20 m, between about 10 m and about 30 m, between about 20 m and 100 m, and more than about 100 m, including all values and ranges in-between. In some variations, the workcell **205** may comprise one or more of a length and width of more than about 1 meter, between about 1 m and about 5 m, between about 3, and about 10 m, between about 5 m and about 20 m, between about 10 m and about 30 m, between about 20 m and 100 m, and more than about 100 m, including all values and ranges in-between.

(155) FIG. 2D is a schematic illustration of a variation of a workcell **200**. Workcell **200** may comprise an enclosure **202** having four walls, a base, and a roof. The workcell may be divided into an interior zone **204** with a feedthrough **206** access, a biosafety cabinet (BSC) **208**, compute server rack **210** (e.g., controller **120**), and quality control (QC) instrumentation **212**. An air filtration inlet (not shown) may provide high-efficiency particulate air (HEPA) filtration to provide ISO7 or better air quality in the interior zone **204**. This air filtration may maintain sterile cell processing in an ISO8 or ISO9 manufacturing environment. The workcell may also have an air filter on the air outlet to preserve the ISO rating of the room. In some variations, the workcell **200** may further

comprise, inside the interior zone **204**, an instrument **211** (e.g., disposed in a universal instrument bay), a bioreactor instrument **214**, a cell selection instrument **216** (e.g., MACS, cell selection system), a cell sorting instrument **218** (e.g., FACS), an electroporation instrument (EP) **220**, and a counterflow centrifugation elutriation (CCE) instrument **222**, a sterile liquid transfer instrument **224** (e.g., fluid connector), a reagent vault **226**, and a sterilization system **260** comprising one or more of a sterilant source, fluid source, and a pump. The reagent vault **226** may be accessible by a user through a sample pickup port **228**. A robot **230** (e.g., support arm, robotic arm) may be configured to move one or more cartridges **250** (e.g., consumables) from any instrument to any other instrument or reagent vault.

(156) In some variations, a human operator may load one or more cartridges **250** into the feedthrough **206**. The cartridges **250** may be pre-sterilized, or the feedthrough **206** may sterilize the cartridge **250** using ultraviolet radiation (UV), or chemical sterilizing agents provided as a spray or wash. The feedthrough **206** chamber may optionally be configured to automatically spray, wash, irradiate, or otherwise treat cartridges (e.g. with ethanol and/or isopropyl alcohol solutions) to maintain sterility of the interior zone **204** (e.g., ISO 7 or better) or the biosafety cabinet **208** (e.g., ISO 5 or better). The cartridge **250** may be passed to the biosafety cabinet **206**, where input cell product is provided and loaded to the cartridge using a sterile liquid transfer instrument **224** (e.g., fluid connector) into the cartridge **250**. The user may then move the cartridge **250** back to the feedthrough **206** and initiate automated processing using a computer processor in the computer server rack **210** (e.g., controller **120**). The robot **230** may be configured to move the cartridge **250** in a predefined sequence to a plurality of instruments and stations, with the components of the workcell **200** being controlled by the computer processor of the computer server rack **210**. Additionally or alternatively, the sequence that the cartridge **250** moves within the workcell **200** may not be predefined. For example, cartridge **250** movement may not be dependent on one or more of the result of a previous step, sensor value, predetermined threshold (e.g., based on a quality control system), and the like. At the end of cell processing, the cartridge **250**, now containing the processed cell product, may be returned to the feedthrough **206** for retrieval by the user. Additionally or alternatively, the cell product **250** containing the processed cell product may be transferred (via a fluid connector) to a second cartridge (e.g., single-use cartridge) and stored in the reagent vault **226** for retrieval by the user.

(157) In some variations, cells from a patient and starting reagents may be loaded into a cartridge (e.g., single-use cartridge) by a human operator in a biosafety cabinet located separate from the workcell or integrated into the workcell. In some variations, the cartridges described herein comprising a cell product and reagent may move through a non-sterile field without contamination since the cartridge is closed. The cartridge may further undergo an automated decontamination routine. For example, the cartridge may be placed within a feedthrough capable of facilitating decontamination of the cartridge before entering the ISO 7 environment in the workcell.

(158) FIG. 2E is a plan schematic illustration of another variation of a workcell **201**. Workcells **200**, **201**, and **203** may comprise an enclosure **202** having four walls, a base, and a roof. The workcell may be divided into an interior zone **204** with a feedthrough **206** access, a biosafety cabinet (BSC) **208**, compute server rack **210** (e.g., controller **120**), and quality control (QC) instrumentation **212**. An air filtration inlet (not shown) may provide high-efficiency particulate air (HEPA) filtration to provide ISO7 or better air quality in the interior zone **204**. This air filtration may maintain sterile cell processing in an ISO8 or ISO9 manufacturing environment. The workcell may also have an air filter on the air outlet to preserve the ISO rating of the room. In some variations, the workcell **200** may further comprise, inside the interior zone **104**, an instrument **211** (e.g., disposed in a universal instrument bay), a bioreactor instrument **214**, a cell selection instrument **216** (e.g., MACS), a cell sorting instrument **218** (e.g., FACS), an electroporation instrument (EP) **220**, and a counterflow centrifugation elutriation (CCE) instrument **222**, a sterile liquid transfer instrument **224**, and a reagent vault **226**. The reagent vault **226** may be accessible by

a user through a sample pickup port **228** (e.g., a door which may facilitate bulk loading of sterile liquid transfer instruments **224**). A robot **230** (e.g., support arm, robotic arm) may be configured to move one or more cartridges **250** (e.g., consumables) from any instrument to any other instrument or reagent vault.

(159) In some variations of methods according to the disclosure, a human operator may load one or more empty cartridges **250** into the feedthrough **206**. Additionally or alternatively, pre-filled cartridges may be loaded into the feedthrough **206**. The cartridges **250** may be pre-sterilized, or the feedthrough **206** may sterilize the cartridge **250** using ultraviolet radiation (UV), or chemical sterilizing agents provided as a spray or wash. The feedthrough **206** chamber may optionally be configured to automatically spray, wash, irradiate, or otherwise treat cartridges (e.g. with ethanol and/or isopropyl alcohol solutions) to maintain sterility of the interior zone **204** (e.g., ISO 7 or better) or the biosafety cabinet **208** (e.g., ISO 5 or better). The cartridge **250** may be passed to the biosafety cabinet **106**, where input cell product is provided and loaded to the cartridge through a sterile liquid transfer port into the cartridge **250**. The user may then move the cartridge **250** back to the feedthrough **206** and initiate automated processing using a computer processor in the computer server rack **210** (e.g., controller **120**). The robot **230** may be configured to move the cartridge **250** in a predefined sequence to a plurality of instruments and stations, with the components of the workcell **200** being controlled by the computer processor of the computer server rack **210**. At the end of cell processing, the cartridge **250**, now containing the processed cell product, may be returned to the feedthrough **206** for retrieval by the user.

(160) In some variations, one or more components of a sterilization system (e.g., sterilant source, pump) may be coupled to a workcell. For example, FIG. **3** is a block diagram of a cell processing system **300** comprising a workcell **310**, sterilization system **320**, fluid connector **330** and fluid devices **340**. In some variations, the fluid devices **340** may comprise a main (e.g., consumable) feedthrough and a fluid device (e.g., reagent) feedthrough. The sterilization system **320** may comprise a sterilant source **322**, pump **324**, and heater (e.g., desiccant/dryer) **326**. For example, the heater **326** may be configured to aerate at a predetermined set of conditions. The sterilization system **320** may be coupled and in fluid communication with one or more of the workcell **310**, fluid connector **330**, and fluid device **340**. In some variations, a robot (not shown) may be configured to manipulate and operate the cell processing system **300**. For example, the fluid connector **330** may be coupled to one or more of the fluid devices **340** and instruments (not shown). One or more of the workcell **310**, fluid connector **330**, and fluid devices **340** may be sterilized and/or aerated by circulating one or more of a sterilant and fluid (e.g., heated air, vaporized hydrogen peroxide (VHP)) using the sterilization system **320**. In some variations, the sterilization system **320** may comprise one or more of vaporized hydrogen peroxide (VHP), electron-beam (e-beam) sterilization, dry thermal decontamination, and steam-in-place. In some variations, the sterilization system **320** may provide a sterility assurance level (SAL) of at least 10⁻³ SAL.

(161) FIGS. **4A** and **4B** illustrate perspective views of a cell processing system **400** comprising a cartridge **400**, **402**, feedthrough **410**, **412**, and fluid connector **420**, **422** (e.g., sterile liquid transfer instrument). For example, cartridge **400** is shown in the feedthrough **410** in FIG. **16A** while a robot (not shown) has moved cartridge **400** to fluid connector **420**.

(162) Robot

(163) Generally, a robot may comprise any mechanical device capable of moving a cartridge from one location to another location. For example, the robot may comprise a mechanical manipulator (e.g., an arm) in a fixed location, or attached to a linear rail, or a 2- or 3-dimensional rail system. In a variation, the robot comprises a robotic shuffle system. In a further variation, the robot comprises a wheeled device. In some variations, the system comprises two or more robots of the same or different type (e.g., two robotic arms each independently configured for moving cartridges between instruments). The robot may also comprise an end effector for precise handling of different

cartridges or barcode scanning or radio-frequency identification tag (RFID) reading.

(164) FIG. 5 is a perspective view of a cell processing system 500 in which a robot arm moves consumable cartridges between slots in various instruments each configured to perform a different cell processing step. In some variations, the same consumable cartridge can be received by different instruments. The system 500 may comprise a modular design to accommodate different instrument configurations. In some variations, a plurality of cartridges may be processed in parallel. Each cartridge may contain a cell product from different donors or contain a cell product intended for different recipients. For example, a cell product from a single donor may be split between a plurality of cartridges to generate a predetermined quantity of cell product for therapeutic use such as when a donor is providing product for several recipients (e.g., for allogeneic transplant). In some variations, the cell product for a single recipient may be split between a plurality of cartridges to generate a predetermined quantity of product for therapeutic use in that recipient. In some variations, the cell product for a single recipient may be split between a plurality of cartridges to generate a predetermined quantity of several cell products with unique genetic modifications, which may be recombined in certain ratios for therapeutic use in that recipient.

(165) Cartridge

(166) Generally, the cell processing systems described herein may comprise one or more cartridges including one or more modules configured to interface with an instrument or instruments. A robot (e.g., robotic arm) may be configured to move a cartridge and/or instrument to perform one or more cell processing steps. For example, a cartridge may comprise a bioreactor module and/or fluid connector (e.g., sterile liquid transfer port) coupled by the robot to a bioreactor instrument of a workcell. Once a predetermined processing step has been completed, the cartridge may be moved by the robot to another instrument of the workcell, and another cartridge may be coupled to the bioreactor instrument. Thus, a portable cartridge and shareable instruments may increase the efficiency, throughput, and flexibility of a cell manufacturing process.

(167) In some variations, the cartridge may optionally provide a self-contained device capable of performing one or more cell processing steps. The modules may be integrated into a fixed configuration within the cartridge. Additionally or alternatively, the modules may be configurable or moveable within the cartridge, permitting various cartridges to be assembled from shared modules. Similarly stated, the cartridge can be a single, closed unit with fixed components for each module; or the cartridge may contain configurable modules coupled by configurable fluidic, mechanical, optical, and electrical connections. In some variations, one or more sub-cartridges, each containing a set of modules, may be configured to be assembled to perform various cell processing workflows. The modules may each be provided in a distinct housing or may be integrated into a cartridge or sub-cartridge with other modules. The disclosure generally shows modules as distinct groups of components for the sake of simplicity, but may be arranged in any suitable configuration. For example, the components for different modules may be interspersed with each other such that each module is defined by the set of connected components that collectively perform a predetermined function. However, the components of each module may or may not be physically grouped within the cartridge. In some variations, multiple cartridges may be used to process a single cell product through transfer of the cell product from one cartridge to another cartridge of the same or different type and/or by splitting cell product into more cartridges and/or pooling multiple cell products into fewer cartridges.

(168) Generally, each of the instruments of the system interfaces with its respective module or modules on the cartridge e.g., an electroporation module on the cartridge (if present) is moved by the system to an electroporation instrument and interfaces with the electroporation instrument to perform an electroporation step on the cell product—and may also interface with common components, such as components of a fluidic bus line (e.g., pumps, valves, sensors, etc.). An advantage of such split module/instrument designs is that expensive components (e.g., motors, sensors, heaters, lasers, etc.) may be retained in the instruments of the system while multiple

cartridges are processed. The use of disposable cartridges may eliminate the need, in such variations, to sterilize cartridges between use. Furthermore, the utilization of shared instruments (e.g. electroporation instrument, CCE instrument, MACS instrument, sterile liquid transfer instrument, FACS instrument, and the like) may be increased since a plurality of the instruments may be utilized simultaneously in parallel by a plurality of cell manufacturing processes. In contrast, conventional semi-automated instruments (e.g., Miltenyi Prodigy) have instrument components that sit idle and are incapable of simultaneous parallel use.

(169) FIG. 6 is a schematic illustration of a cartridge **600** that may be a consumable produced from materials at a cost that make recycling or limited use practical. The cartridge **600** may comprise a liquid transfer bus **624** fluidically coupled to a small bioreactor module **614a**, a large bioreactor module **614b**, a cell selection module **616**, a cell sorting module **618**, an electroporation module **620**, and a counterflow centrifugation elutriation (CCE) module **622**. In some variations, the cell selection module **616** may be a magnetic-activated cell selection (MACS) module. The cell sorting module **618** may comprise a fluorescence activated cell sorting (FACS) module. The cartridge **600** may comprise a housing **602** that renders the cartridge self-contained, and optionally protects the contents from contamination. Sterile liquid transfer ports (SLTPs) **606a-606k** may be fluidically coupled to reservoirs **607a-607k**, and each independently be a flexible bag or a rigid container. In some variations, flexible bags may be configured to hold large volumes and to permit transfer of fluid without replacing transferred fluid with liquid or gas to maintain the pressure in the reservoir, as the bag may collapse when fluid is transferred out and expand when fluid is transferred in.

(170) In some variations, the liquid transfer bus **624** may comprise valves V1 to V28 and corresponding tubing that fluidically links the valves to one another and to each of the modules. Valves shown coupled to four fluidic lines are 4/2 (4 port 2 position) valves and valves shown coupled to three fluidic lines are 3/2 (3 port 2 position) valves. Internal flow paths of the valves are indicated in the legend. The cartridge may further comprise a first pump **632a** and a second pump **632b**, each of which expose tubing on the exterior of the housing **602** to permit each pump to interface with pump actuators (e.g., rotors) in some instruments in the system (e.g., workcell). The liquid transfer bus **624** may be fluidically coupled to reservoir **607d** and a product bag which is fluidically coupled to SLTP **606d** and to product input tubing lines **627a-627b**. An operator may input a cell product into reservoir **607d** by connecting product input tubing line **627a** or **627b** to an external source of cells (e.g., a bag of cells collected from a donor). SLTP **606d** may be configured to permit a system according to the disclosure (e.g., workcell **110**) to add fluid to the reservoir **607d** in an automated fashion. For example, one or more fluid-carrying containers such as reservoirs **607a-607k**, bags, etc. may receive fluid using an SLTP. Additionally or alternatively, the SLTP may be configured to periodically sample one or more of the fluid-carrying containers. The cartridge may further comprise collection bags **626a-626c**, fluidically coupled to the liquid transfer bus **624** via valves V17-V19. The cartridge **600** may be configured to permit an operator to remove the collection bags **626a-626c** after completion of cell processing by the system.

(171) FIG. 7 is a schematic diagram of another variation of a cartridge **700**. For example, cartridge **700** may comprise a reduced feature set compared to cartridge **600**. The cartridge **700** may comprise a liquid transfer bus **724** fluidically coupled to a bioreactor module **714**, a counterflow centrifugation elutriation (CCE) module **722**, and a module **716** selected from cell selection module, a cell sorting module, an electroporation module, or any other cell processing module. The cartridge **700** may comprise a housing **702** and sterile liquid transfer ports (SLTPs) **706a-706f** (e.g., fluid connector) fluidically coupled to reservoirs **707a-707f**, which may be each independently be a flexible bag or a rigid container. SLTP **706g** is fluidically coupled to the bioreactor module **714** to permit direct access by a system or an operator to the bioreactor. Reservoir **707c** may be fluidically coupled to SLTP **707c** and product input tubing line **727**. In some variations, the liquid transfer bus **724** may comprise 14 valves V1-V3, V9, V11-V12, V17-V23 and V28 and tubing that fluidically couples the valves to one another and/or each of the modules. The cartridge may further comprise

collection bags **726a-726c** fluidically coupled to the liquid transfer bus **724** via valves **V17-V19**. The cartridge may further comprise a pump **732** which exposes the tubing on the exterior of the housing **702** to permit each pump to interface with a pump actuator in the system (e.g., workcell). (172) A side and top view of another variation of a cartridge is shown in respective FIGS. **8A** and **8B**. In some variations, a cartridge **800** may comprise a bioreactor **814**, a pump **816**, and a counterflow centrifugation elutriation (CCE) module **822**. The cartridge **800** may comprise blanks **818**, **819**, and **820** configured to house additional module(s) such as a cell selection module, cell sorting module, an electroporation module, a small bioreactor module, and the like. In some variations, a blank may define an empty volume of the cartridge reserved to house a module at another time. In some variations, the cartridge **800** may comprise two or more additional bioreactors and/or reservoirs in blanks **818**, **819**, **820**. Along the near surface of the cartridge **800** may be fluid connectors **806a-806j** (e.g., SLTP) fluidically connected to reservoirs **807a-807f**. Reservoirs **807b** and **807e** may comprise fluid (e.g., buffer or media). Along the top surface are product input tubing lines **827a-827d**, which may be fluidically connected to reservoirs **807a**, **807b**, **807e**, and **807f**, respectively. A liquid transfer bus **824** may fluidically connect the STLPs, reservoirs, and product input tubing lines to the modules via tubing.

(173) In some variations, the housing **802** may have external dimensions of about 225 mm×about 280 mm×385 mm, about 225 mm×about 295 mm×385 mm, and about 450 mm×about 300 mm×about 250 mm, including all values and sub-ranges in-between. In some variations, the cartridge **800** may be about 10%, about 20%, about 30% or more smaller in volume, including all ranges and sub-values in-between. In some variations, the cartridge **800** may be about 10%, about 20%, about 30%, about 50%, about 100%, about 200%, or more in volume, including all ranges and sub-values in-between.

(174) In some variations, a cartridge **800** as shown in the side view of FIG. **8C** and perspective view of FIG. **8D** may comprise a MACS module **818**. For example, the bioreactor module **814** may comprise ports **815a-815f** including a pH and dissolved oxygen (DO) sensors (ports **815a** and **815b**), a gas input line **815c**, an output line **815d** each having a sterile filter behind the connector, and a coolant input line **815e** and output line **815f** from the bioreactor instrument interface when it interfaces with bioreactor module **814** (for heat exchange). For example, the gas input line **815c** may be configured for gas transfer into a fluid (e.g., through headspace gas control or a gas-permeable membrane).

(175) FIG. **9** shows a cross-sectional side view of a cartridge **900**. In some variations, a cartridge **900** may comprise an enclosure (e.g., housing), a bioreactor **914**, one or more pumps **916**, valve **930**, cell selection module **917**, and a counterflow centrifugation elutriation (CCE) module **922**. In some variations, the cell selection module **616** may be a magnetic-activated cell selection (MACS) module **917**. The cartridge may further comprise collection bags **926**. The cartridge **900** may optionally comprise blanks configured to house additional module(s) such as a cell selection module, a cell sorting module, an electroporation module **918**, and the like. In some variations, the cartridge **900** may comprise one or more bioreactors and/or reservoirs in the blanks.

(176) In some variations, a cartridge may comprise one or more valves. In some variations, the valve **1000** on the cartridge may be configured to receive an actuator **1010** provided by an instrument (as shown in FIG. **10A**). As the cartridge is inserted into the instrument, the valve **1000** may be configured to dock with the actuator **1010** (as shown in FIG. **10B**), such that rotation of the actuator **1010** may cause switching of the valve **1000** from one position to another position. In some variations, the valves may be constructed to pinch a section of soft tubing. The pinch valves may comprise a closed configuration, and an external actuator may be configured to interface with the pinch valve (e.g., utilizing a solenoid with linear motion) to open or close the valve. The valves themselves may be configured to be disposable whereas the actuators may be integrated into an instrument configured to process cartridges repeatedly.

(177) Reagent Vault

(178) In some variations, the system comprises a reagent vault (or reagent vaults) where reagents are stored including but not limited to cell culture media, buffer, cytokines, proteins, enzymes, polynucleotides, transfection reagents, non-viral vectors, viral vectors, antibiotics, nutrients, cryoprotectants, solvents, cellular materials, and pharmaceutically acceptable excipients. Additionally or alternatively, waste may be stored in the reagent vault. In some variations, in-process samples extracted from one or more cartridges may be stored in the reagent vault. The reagent vault may comprise one or more controlled temperature compartments (e.g., freezers, coolers, water baths, warming chambers, or others, at e.g. about -80°C ., about -20°C ., about 4°C ., about 25°C ., about 30°C ., about 37°C ., and about 42°C .). Temperatures in these compartments may be varied during the cell manufacturing process to heat or cool reagents. In variations of the methods of the disclosure, a cartridge may be moved by the robot (or manually by an operator) to the reagent vault. The reagent vault interfaces with one or more sterile liquid transfer ports on the cartridge, and the reagent or material is dispensed into the cartridge. Optionally, fluid is added or removed from the cartridge before, during, or after reagent addition or removal. In some variations, the system comprises a sterile liquid transfer instrument, similarly configured to transfer fluid into or out of the cartridge in an automated, manual, or semi-automated fashion. An operator may stock the sterile liquid transfer station with reagents manually, or they may be supplied by a robot (e.g. from a feedthrough or other location). In some cases, a robot moves a reagent or reagents from the reagent vault to the sterile liquid transfer station. The reagent vault may have automated doors to permit access by the robot for sterile liquid transfer devices and/or other reagent vessels, optionally each under independent closed loop temperature control. The devices and vessels may be configured for pick-and-place movement by the robot. In some variations, the reagent vault may comprise one or more sample pickup areas. For example, a robot may be configured to move one or more reagents to and from one or more of the sample pickup areas.

(179) Various materials can be used to construct the cartridge and the cartridge housing, including metal, plastic, rubber, and/or glass, or combinations thereof. The cartridge, its components, and its housing may be molded, machined, extruded, 3D printed, or any combination thereof. The cartridge may contain components that are commercially available (e.g., tubing, valves, fittings); these components may be attached or integrated with custom components or devices. The housing of the cartridge may constitute an additional layer of enclosure that further protects the sterility of the cell product. The operator may perform loading or unloading of the cartridge in an ISO 5 or better environment, utilizing aseptic technique to ensure that sterility of the contents of the cartridge is maintained when the cartridge is opened. In some variations, the operator may perform loading or unloading of the cartridge using manual aseptic connections (e.g., sterile tube welding). The robotic system may also perform sterile loading or unloading of liquids into and out of the cartridge through the use of the sterile liquid transfer instrument and sterile liquid transfer ports on the cartridge.

(180) Counterflow Centrifugal Elutriation

(181) Counterflow centrifugal elutriation (CCE) is a technique used to separate cells based on characteristics such as size and/or density. Counterflow centrifugal elutriation combines centrifugation with counterflow elutriation where centrifugation corresponds to the process of sedimentation under the influence of a centrifugal force field and counterflow elutriation corresponds to the process of separation by washing. Separation takes place in a cone (e.g., bicone, funnel) shaped elutriation chamber. Particles (e.g., cells) conveyed in a fluid into the elutriation chamber are acted upon by two opposing forces: centrifugal force driving the fluid away from an axis of rotation; and fluid velocity driving the fluid towards the axis of rotation (e.g., counterflow). By varying the flow rate and the centrifugal force, the separation of particles (e.g., cells) may be achieved. For example, as described in more detail herein, particles may be separated based on properties such as size and density.

(182) Counterflow centrifugal elutriation may perform multiple operations useful for cell therapy manufacturing workflows including, but not limited to, cell washing, cell concentration, media/buffer replacement, transduction, and separation of white blood cells from other blood components (e.g., platelets, and red blood cells). In some variations, a fluid source (e.g., apheresis bag) for a cell separation process may comprise a suspension of white blood cells, red blood cells, platelets, and plasma. In order to separate immune cells of interest, white blood cells may be isolated and subsequently magnetically tagged for magnetic separation. A white blood cell separation step may be performed in a CCE module to separate cells based on size and density, while magnetic separation may be performed in a MACS module. In some variations, a CCE module may be integrated into a cartridge to enable a cell processing system to separate cells based on one or more of a progression through a cell cycle (e.g., G.sub.1/M phase cells being larger than G.sub.0, S, or G2 phase cells) and cell type (e.g., white blood cells from red blood cells and/or platelets).

(183) Generally, a rotor configured to spin may comprise an elutriation chamber (e.g., cone, bicone). A fluid comprising a suspension of cells may be pumped under continuous flow into the rotor. As cells are introduced into the cone (e.g., bicone), the cells migrate according to their sedimentation rates to positions in the gradient where the effects of the two forces upon them are balanced. Smaller cells having low sedimentation rates (e.g., platelets) may be quickly washed toward the axis of rotation with increased flow velocity. Such smaller cells may be output (e.g., washed out) of the cone. Relatively larger (or denser) cells (e.g., red blood cells) flow through the cone relatively more slowly and reach equilibrium at an elutriation boundary where the centrifugal force and the drag force are in balance, and the fluid velocity is relatively low because the cone has widened. The largest or densest cells (e.g., white blood cells) remain near the inlet to the chamber where centrifugal force and fluid velocity are high. By increasing the flow rate in gradual steps, successive fractions of increasingly large or dense cells (e.g., platelets.fwdarw.red blood cells.fwdarw.white blood cells) may be output from the rotor. Continued incremental increases in fluid flow rate will eventually elutriate all cells from the cone.

(184) FIG. 56 is a block diagram of a cell separation system 5600 comprising a workcell 5610 and at least one cartridge 5620. In some variations, the workcell 5610 may comprise one or more of a counterflow centrifugal elutriation (CCE) instrument 5632 (e.g., first magnet), a magnetic-activated cell selection (MACS) instrument 5642 (e.g., magnet array, second magnet), a fluid connector 5652, a pump 5654, an imaging system comprising an optical sensor 5660 and an illumination source 5662, a sensor 5664, and a processor 5670. In some variations, the cartridge 5620 may comprise one or more of a CCE module 5630 (e.g., rotor), a MACS module 5640 (e.g., flow cell), and a fluid connector 5650 (e.g., sterile liquid transfer port, liquid transfer bus). For example, a cartridge for cell processing may comprise a liquid transfer bus and a plurality of modules, each module fluidically linked to the liquid transfer bus. The modules may include any of the CCE modules or MACS modules described herein. In some variations, a robot (not shown) may be configured to move the cartridge 5620 between different locations within the workcell 5610 to perform different cell processing steps.

(185) In some variations, the imaging system (e.g., optical sensor 5660, illumination source 5662) may be configured to generate image data corresponding to one or more of the CCE module 5630 and MACS module 5640. For example, image data of fluid flow through a rotor of a CCE module 5630 may be analyzed and used to control a flow rate of fluid and/or rotation rate of the rotor, as described in more detail herein. In some variations, the optical sensor 5660 may be a CMOS/CCD sensor having, for example a resolution of about 100 μm , a working distance of between about 40 mm and about 100 mm, and a focal length of less than about 8 mm. The optical sensor 5660 may be configured to operate synchronously with the illumination source 5662. In some variations, the optical sensor 5660 may comprise one or more of a colorimeter, turbidity sensor, and optical density sensor. In some variations, the illumination source 5662 may operate as a strobe light

configured to output light pulses synchronized to a rotation rate of a rotor of the CCE module **5630**. (186) In some variations, the sensor **5664** may comprise one or more of an optical density sensor configured to measure an intensity of fluid, a leak detector configured to detect moisture and/or leaks, an inertial sensor configured to measure vibration, a pressure sensor configured to measure pressure in a fluidic line (e.g., photoelectric sensor), a bubble sensor configured to detect the presence of a bubble in a fluid conduit, colorimetric sensor, vibration sensor, and the like.

(187) In some variations, the fluid connector **5652** may comprise one or more valves, configured to control fluid flow between the workcell and the cartridge **5620**. The processor **5670** may correspond to the controller (e.g., processor and memory) described in more detail herein. The processor **5670** may be configured to control one or more of the CCE instrument **5632**, the MACS instrument **5642**, the pump **5654**, fluid connector **5652** (e.g., valves), the optical sensor **5660**, the illumination source **5662**, and the sensors **5664**.

(188) In some variations, a system **5600** for cell processing may comprise a cartridge **5600** comprising a rotor of a CCE module **5630** configured for counterflow centrifugation elutriation of cells in a fluid. A first magnet of a CCE instrument **5632** may be configured to magnetically rotate the rotor and separate the cells from the fluid in the rotor. The cartridge may further comprise a flow cell of a MACS module **5640** coupled to the rotor and configured to receive the cells from the rotor. A second magnet of a MACS instrument **5642** may be configured to magnetically separate the cells in the flow cell.

(189) In some variations, an illumination source **5662** may be configured to illuminate the cells. An optical sensor **5660** may be configured to generate image data corresponding to the cells. In some variations, the system **5600** may comprise one or more of an oxygen depletion sensor, leak sensor, inertial sensor, pressure sensor, and bubble sensor. In some variations, the system **5600** may comprise one or more valves and pumps.

(190) FIG. **57** is a cross-sectional side view of a counterflow centrifugal elutriation (CCE) module **5700** comprising a housing **5710** (e.g., enclosure), a rotor **5720** configured to rotate within and relative to the housing **5710**, and one or more fluid ports **5730** (e.g., fluid inlet, fluid outlet). In some variations, the CCE module **5700** may be portable and configured to move within a workcell **5610** and cartridge **5620**. For example, a robot may move the CCE module **5700** between different instruments of a workcell **5610**.

(191) FIG. **58** is a cross-sectional side view of a magnetic-activated cell selection (MACS) module comprising a housing **5810** (e.g., enclosure), a first fluid port **5820** (e.g., fluid inlet), a second fluid port **5830** (e.g., fluid outlet), and a flow cell **5810** coupled in between the first fluid port **5820** and the second fluid port **5830**. As described in more detail herein, the flow cell **5810** may comprise a cavity (e.g., chamber) comprising one or more channels (e.g., linear channels, laminar fluid flow channel). In some variations, the cavity of the flow cell **5810** may be substantially empty. For example, the flow cell **5810** may be absent a mesh, beads, tortuous channels, and the like. In some variations, the flow cell **5810** may have a longitudinal axis aligned perpendicular to ground. That is, the flow cell **5810** may be oriented vertically where the first fluid port **5820** is disposed at a higher elevation than the second fluid port **5830** such that gravity may aid fluid flow through the flow cell **5810**. In some variations, the MACS module **5800** may be portable and configured to move within a workcell **5610** and cartridge **5620**. For example, a robot may move the MACS module **5630** between different instruments of a workcell **5610**.

(192) FIGS. **59A** and **59B** are perspective views of a system **5900** for cell processing (e.g., CCE system) comprising a CCE module **5930** (e.g., cartridge) including a housing **5931** and a rotor **5910**, a CCE instrument **5932**, an optical sensor **5960**, and an illumination source **5962**. In some variations, the CCE instrument **5932** may comprise a magnet configured to magnetically rotate the rotor **5910** within the CCE module **5930**. One or more portions of the housing **5931** and rotor **5910** may be optically transparent to facilitate illumination by the illumination source **5962** and image data generation by the optical sensor **5960**.

(193) In some variations, the system **5900** for cell processing may comprise a cartridge **5930** comprising a housing **5931** comprising a rotor **5910** configured to separate cells from a fluid. An instrument **5932** comprising a magnet may be configured to interface with the cartridge **5930** to magnetically rotate the rotor **5910**. The cartridge **5930** may be configured to move a cell product between a plurality of instruments. In some variations, the housing **5931** may enclose the rotor **5910**. In some variations, the housing **5931** may comprise one or more apertures **5937** configured to facilitate visualization (e.g., imaging) of the rotor **5910**. FIGS. **59A** and **59B** depict a magnet **5932** in proximity, but not attached, to housing **5931**. FIG. **59C** is a perspective view of the rotor **5910** and housing **5931** without the magnet **5932**, optical sensor **5960**, and illumination source **5962**.

(194) In some variations, the cartridge **5930** (e.g., housing **5931**, **5910**) may comprise a consumable component such as a disposable component, limited use component, single use component, and the like. In some variations, the magnet **5932** may comprise a durable component that may be re-used a plurality of times. In some variations, the magnet **5932** may be releasably coupled to the housing **5931**. For example, the housing **5931** may be moved relative to the magnet **5932** to facilitate magnetic coupling between the magnet **5932** and a plurality of cartridges **5930**. Additionally or alternatively, the magnet **5932** may be configured to be moved relative to the housing **5931**.

(195) FIG. **59D** is a side cross-sectional view of a CCE module **5930**. In some variations, the housing **5931** of the rotor **5910** may comprise a first side **5933** comprising the first fluid port **5912** (e.g., first fluid conduit) and a second side **5935** comprising the second fluid port **5914** where the second side **5935** is opposite the first side **5933**. The rotor **5910** (including a cone or bicone as described in more detail herein) may be coupled between the first fluid port **5912** and the second fluid port **5914**. In some variations, the CCE module **5930** may comprise an air gap **5902** between the housing **5931** and a magnet **5932**. That is, the cartridge **5930** and magnet **5932** may couple in a non-contact manner. Consequently, the cartridge need not mechanically couple to the magnet **5932** to perform counterflow centrifugal elutriation. Therefore, the rotor **5910** may have a low alignment sensitivity with the magnet **5932**, as well as low vibration between the rotor **5910** and the magnet **5932**. Furthermore, the space between the rotor **5910** and magnet **5932** enables the second fluid port **5914** to extend toward the second side **5935** of the housing **5931**, thus allowing for fluid to flow on each side of the rotor **5910**.

(196) In some variations, counterflow centrifugal elutriation may be performed by the system **5900** by moving a magnet **5932** towards a rotor **5910** (or vice versa). The rotor may define a rotational axis (e.g., coaxial with the first fluid port **5912** and the second fluid port **5914**). Fluid may flow through the rotor via the first fluid port **5912** and the second fluid port **5914**. The magnet **5932** may magnetically rotate the rotor about the rotational axis while flowing the fluid through the rotor **5910**. The rotor may move away from the magnet. For example, moving the rotor **5910** may include advancing and withdrawing the rotor **5910** relative to the magnet **5932** using a robot (not shown).

(197) In some variations, fluid may flow through first fluid port **5912** along the first side **5933** of the rotor **5910** and into the rotor **5910**. After counterflow centrifugal elutriation through the rotor **5910**, the fluid may flow out of the rotor **5910** through second fluid port **5914** along the second side **5935** of the rotor **5910**.

(198) In some variations, counterflow centrifugal elutriation may be visualized by optical sensor **5960** and illumination source **5962** in order to monitor and modify cell separation in real-time based on predetermined criteria in a closed loop manner in order to maximize elutriation efficiency. In some variations, an optical sensor **5960** may be configured to image any portion of the rotor through which fluid flows (e.g., first fluid conduit, second fluid conduit, third fluid conduit, first bicone, second bicone). For example, image data of one or more of the fluid and the cells in the rotor **5910** may be generated using the optical sensor **5960**. In some variations, one or more of the

fluid and the cells may be illuminated using the illumination source **5962**. For example, an output of a cone may be imaged by an optical sensor to identify non-target cells being elutriated.

(199) In some variations, one or more of a rotation rate of the rotor and a flow rate of the fluid may be selected based at least in part on the image data. For example, the rotor may comprise a rotation rate of up to 6,000 RPM. For example, the fluid may comprise a flow rate of up to about 150 ml/min while rotating the rotor. In some variations, the rotor may be moved towards the illumination source **5962** and the optical sensor **5960**. Additionally or alternatively, the rotor **5910** may be moved away from the illumination source **5962** and the optical sensor **5960**.

(200) FIG. **59E** is a side cross-sectional view of a rotor **5910** including a first fluid port **5912** (e.g., fluid conduit, inlet) and a second fluid port **5914** (e.g., fluid conduit, outlet). In some variations, the first fluid port **5912** and the second fluid port **5914** may extend in parallel with each other and/or a rotational axis of the rotor **5910**. In some variations, the first fluid port **5912** and the second fluid port **5914** may be disposed on opposite sides of the rotor **5910**, which may simplify fluid routing, cartridge design, and also reduce manufacturing costs. For example, the fluidic seals may be simplified since they contain only a single lumen each. Conventionally, a complicated fluid flow path (including inlet and outlet) is formed on a first side of a rotor due to a fixed mechanical coupling of a drive motor to a second side of the rotor. FIGS. **59F** and **59G** are cross-sectional side views of a rotor **5910** disposed within housing **5931**.

(201) FIG. **60A** is a plan view of a rotor **6000** that may be used with any of the CCE systems, CCE modules, cartridges, housings, combinations thereof, and the like described herein. The rotor **6000** may comprise a first fluid conduit **6010**, a cone **6020** (e.g., bicone), a second fluid conduit **6030**, a magnetic portion **6040** (e.g., magnet), and housing **6050**. Fluid may flow sequentially through the first fluid conduit **6010**, the cone **6020**, and the second fluid conduit **6030**. In some variations, the magnetic portion **6040** may comprise one or more magnets. In some variations, the rotor **6000** may define a rotation axis **6060**. In some variations, at least a portion of the first fluid conduit **6010** and at least a portion of the second fluid conduit **6030** may extend parallel to the rotation axis (e.g., into and out of the page with respect to FIG. **60A**). In some variations, at least a portion of the first fluid conduit **6010** and at least a portion of the second fluid conduit **6030** may be co-axial.

(202) In some variations, the cone **6020** may comprise a bicone having a first cone including a first base and a second cone including a second base such that the first base faces the second base. In some variations, a bicone may comprise a cylinder (or some other shape) between and/or in fluid communication with the first cone and the second cone. For example, one or more cones of a rotor may comprise a generally stepped shape. For example, one or more cones may comprise stacked circular steps. In some variations, a cone of a rotor may comprise a single cone.

(203) In some variations, at least a portion of the rotor may be optically transparent to facilitate visualization and/or imaging of the rotor **6000** and/or fluid (e.g., cells) in the rotor **6000**. For example, the cone **6020** may be transparent, as well as portions of the first fluid conduit **6010** and the second fluid conduit **6030**.

(204) In some variations, the cone may comprise a volume of between about 10 ml and about 40 ml. In some variations, the cone may comprise a cone angle of between about 40 degrees and about 60 degrees.

(205) In some variations, a cone may comprise a first cone (e.g., distal cone) and a second cone (e.g., proximal cone) where the first cone is larger than the second cone. In some variations, a first cone length may be between about 60 mm and about 90 mm. In some variations, a proximal cone length may be between about 15 mm and about 40 mm. In some variations, a cone diameter (e.g., maximum diameter of the cone) may be between about 15 mm and about 40 mm.

(206) In some variations, the rotor **6000** may comprise an asymmetric shape. In some variations, a first portion (e.g., first end) of the rotor **6000** may comprise the cone **6020** and a second portion (e.g., second end) may comprise a paddle shape.

(207) In some variations, the cone may comprise a length of at least about 4 cm (e.g., between

about 9 cm and about 12 cm), a cone diameter of about 5 cm or less (e.g., between about 3 cm and about 5 cm), a fluid flow rate of up to about 100 ml/min (e.g., between about 60 ml/min and about 100 ml/min), and a rotation rate of less than about 3000 RPM. The shape of the first cone and the second cone may be generally linear (as opposed to convex or concave).

(208) FIGS. **60B** and **60C** are perspective views, and FIG. **60D** is a side view of a rotor **6002** comprising a first fluid conduit **6012**, a cone **6022**, a second fluid conduit **6032**, and a housing **6052**. FIG. **60E** is a perspective view of the rotor **6002** disposed in a housing **6090**.

(209) FIG. **60F** is a plan view of a rotor **6004** having two cones (e.g., two bicones) configured to elutriate cells (e.g., red blood cells, leukapheresis product) in a second cone in order to recirculate a buffer for reuse. The rotor **6004** may comprise a housing **6052**, a first fluid conduit **6012**, a first cone **6022** coupled to the first fluid conduit **6012**, a second fluid conduit **6023** coupled to the first cone **6022**, and a second cone **6024** coupled to the second conduit **6023**, and a third fluid conduit **6032** coupled to the second cone **6024**. The first cone **6022** may comprise a first volume, and the second cone **6024** may comprise a second volume larger than the first volume. In some variations, a ratio of a second volume to a first volume may be between about 2:1 to about 5:1. Fluid may flow sequentially through the first fluid conduit **6012**, the first cone **6022**, the second fluid conduit **6023**, the second cone **6024**, and the third fluid conduit **6032**. In some variations, the rotor **6004** may comprise a magnetic portion **6042**.

(210) In some variations, the first cone **6022** may comprise a first bicone and the second cone **6024** may comprise a second bicone. In some variations, the first bicone may comprise a third cone including a first base and a fourth cone including a second base such that the first base faces the second base. In some variations, the second bicone may comprise a fifth cone including a third base and a sixth cone including a fourth base such that the third base faces the fourth base.

(211) In some variations, a portion of the rotor **6004** may be optically transparent, such as first cone **6022**, second cone **6024**, and at least a portion of first fluid conduit **6012**, second fluid conduit **6023**, and third fluid conduit **6032**. In some variations, the first fluid conduit **6012** may comprise an inlet and the third fluid conduit **6032** may comprise an outlet.

(212) In some variations, cells may enter the first cone **6022** and red blood cells (RBCs) **6030** may be elutriated into the second cone **6024**. Since the second cone **6024** is further out from an axis of rotation (center of housing **6052**), the RBCs **6030** may be concentrated at an inlet **6025** of the second cone **6024** due to centrifugation. The larger volume of the second cone **6024** may further reduce the velocity of fluid (e.g., buffer), thereby reducing the force on RBCs **6030** within the second cone **6024**. By recirculating the fluid (e.g., buffer), a higher concentration of RBCs may be elutriated with less fluid (e.g., buffer). In some variations, white blood cells **6040** may be harvested from the first cone **6022**. An optical sensor may be configured to image the first cone **6022** to generate imaging data used to identify a boundary between the WBCs **6040** and RBCs **6030**. In some variations, the recirculating fluid may be passed through a filter to remove small particles (e.g., platelets) with less fluid (e.g., buffer).

(213) FIG. **60G** is a plan view and FIG. **60H** is a side view of a rotor **6005** having two cones (e.g., two bicones) configured to elutriate cells (e.g., red blood cells) in a second cone. A rotor having two cones may facilitate recirculation of buffer for reuse. The rotor **6006** may comprise a housing **6052**, a first fluid conduit **6012**, a first cone **6022** coupled to the first fluid conduit **6012**, a second cone **6024** coupled to the first cone **6022**, and a fluid conduit **6032** (e.g., outlet) coupled to the second cone **6024**.

(214) FIG. **60I** is a perspective view of a rotor **6006** comprising a cone **6024** and housing **6054**. FIG. **60J** is a perspective view of a rotor **6007** comprising a cone **6026** and housing **6056**. FIG. **60K** is a schematic plan view of rotor **6008** and corresponding dimensions. FIG. **60L** is an image of a set of rotors having varying dimensions.

(215) FIGS. **11A-11C** depict another variation of the counterflow centrifugal elutriation (CCE) module **1100**. FIG. **11A** is a perspective view of a cartridge **1110** comprising a CCE module **1100** in

an extended configuration configured to receive a CCE instrument. FIGS. **11B** and **11C** are cross-sectional side views of a CCE module **1100** in respective retracted and extended configurations. In some variations, a CCE module may comprise a conical element having an internal surface and an external surface fixedly attached to a distal end of a linear member having an internal surface and an external surface. The proximal end of the linear member may be rotationally attached to a fulcrum in order to enable extension, retraction, and/or rotation of the linear member. For example, FIG. **11C** depicts a linear member extended outside the housing of the cartridge and then rotated to generate a centrifugal force. A cell product may be conveyed between the internal surface and external surface of the linear member (optionally in tubing) to the conical element and fed into an opening at the distal end of the internal surface of the conical element, such that the flow of the cell product may run counter to the centrifugal force generated by rotation of the linear member. Cells in the cell product may be separated based on the ratio of their hydrodynamic cross section to their mass, due to the counterflow of the solution and sedimentation of cells subject to centrifugal force. The flow rate may then be increased and/or the rotation of the linear member may be decreased to permit cells to selectively return through the void in the interior surface of the linear member to the proximal end of the linear member. The selected cells may be directed into a tube that returns the selected cells to the cartridge. After an enrichment/washing step is performed, the linear member may be retracted into the housing to the retracted configuration as shown in FIG. **11B**.

(216) Magnetic Cell Selection

(217) Generally, the systems and methods described herein may select cells on the basis of magnetically labeled cells corresponding to cells having a predetermined antigen. For example, a cell suspension of interest may be immunologically labeled with magnetic particles (e.g., magnetic beads) configured to selectively bind to the surface of the cells of interest. The labeled cells may generate a large magnetic moment when the cell suspension is flowed through a flow cell. The flow cell may be disposed in proximity to a magnet array (e.g., permanent magnets, electromagnet) generating a magnetic field having a gradient across the flow cell to attract the labeled cells for separation, capture, recovery, and/or purification. The magnet array may be configured to generate non-uniform magnetic fields at the edges and the interfaces of the individual magnets so as to cover the full volume of the flow cell such that a magnetophoretic force equals a drag force exerted by the fluid flowing through the flow cell.

(218) FIG. **61A-61C** are schematic views of a magnetic cell separation (e.g., magnetic-activated cell selection) system and process. A magnetic cell separation system may comprise a flow cell **6110** comprising an inlet **6130** and an outlet **6132**, a magnet array **6120**, a first fluid source **6140** (e.g., input sample source), a second fluid source **6142** (e.g., buffer source), a third fluid source **6150** (e.g., target cell reservoir), a fourth fluid source **6152** (e.g., waste reservoir), and a set of valves **6134**. As shown in step **6100**, a set of cells **6160**, **6170** may comprise labeled cells **6160** (e.g., magnetically labeled cells) and non-labeled cells **6170** may flow into the flow cell **6110**. For example, a set of the cells **6160** may be labeled with a magnetic-activated cell selection (MACS) reagent. A MACS reagent may be incubated with the set of cells to label (e.g., attach, couple) the cells to the MACS reagent. As described in more detail herein, the magnet array **6120** may be disposed external to the flow cell **6110** such that the magnet array **6120** may be moveable relative to the flow cell **6110**. For example, the magnet array **6120** may move away from the flow cell **6110** to facilitate flowing the set of cells **6160** out of the flow cell **6110**. Conventional flow cells comprise tortuous paths including meshes and/or beads to capture cells. However, recovery of labeled cells from conventional flow cell configurations is difficult. By contrast, the flow cells **6110** described herein may lack tortuous paths such as beads, meshes, and the like, and therefore enable serial separations to be performed efficiently using either positive selection or negative selection. In some variations, the flow cells may comprise generally laminar channels as described in more detail herein.

(219) At step **6102**, the magnet array **6120** may magnetically attract the set of cells **6160** towards

the magnet array **6120** for a predetermined dwell time and/or based on a measured quantity of magnetically separated cells. In some variations, the dwell time may be at least one minute (e.g., at least two minutes, at least three minutes, at least five minutes). The non-labeled cells **6170** are not magnetically attracted to the magnet array **6120** and may flow out of the outlet **6132** of the flow cell **6110** and into the fourth fluid source **6152**. In some variations, the fluid (e.g., cells **6160**, **6170**) within the flow cell may be held statically within the flow cell **6110** for a dwell time before the fluid (e.g., cells **6170**) flow from outlet **6132**. In some variations, a longitudinal axis of the flow cell **6110** may be oriented substantially perpendicular to ground in order for fluid flow through the flow cell **6110** to be aided by gravity. At step **6104**, the magnetic coupling between the magnet array **6120** and the cells **6160** may be released after the dwell time, and the cells **6160** may flow into the third reservoir **6150**.

(220) In some variations, stiction may cause cells to remain attached to a surface of a flow cell even after removal of a magnet array **6120**. Therefore, a gas may be flowed through the flow cell **6110** to aid cell collection into the third reservoir **6150**. Gas flow through the flow cell may provide improved cell recovery over liquid flushing through the flow cell. An interface generated by a gas (e.g., bubble, air gap) may be maintained by gravity, thereby enabling implementation of a relatively wide flowcell that further improves cell recovery relative to a horizontally oriented flow cell. The MACS modules described herein may be configured for positive selection and/or negative selection by modifying the sequence of steps.

(221) Additionally or alternatively, an optical sensor may be configured to image a flow cell to generate imaging data used to identify a quantity of cells magnetically attracted to the magnet array. Fluid containing labeled cells may be flowed out of the flow cell when a predetermined quantity of cells have been measured by the optical sensor.

(222) FIG. **62A** is a perspective view of a MACS module **6200** in a first configuration. The MACS module **6200** (as well as any of the MACS modules described herein) may be a component of any of the cartridges described herein. For example, a cartridge for cell processing may comprise a liquid transfer bus and a plurality of modules with each module fluidically linked to the liquid transfer bus. The MACS module **6200** may comprise a flow cell **6210** comprising an elongate cavity having a cavity height, an inlet **6230**, and an outlet **6232**. The MACS module **6200** may further comprise a magnet array **6220** comprising a plurality of magnets. Each of the magnets may be spaced apart by a spacing distance, such as illustrated in FIGS. **62G**, **63D**, and **63E**, although FIGS. **62A-62E** illustrate a magnet array **6220** with magnets in contact with adjacent magnets.

(223) FIG. **62G** is a schematic diagram of the flow cell **6210** and magnet array **6220**. In some variations, the flow cell **6210** may comprise a cavity height **6202** and a cavity width **6204**. Fluid may be configured to flow through the flow cell **6210** in a first direction **6206**. The magnet array **6220** may comprise a plurality of magnets with each magnet comprising a respective width **6222**. In some variations, adjacent magnets may be separated by a predetermined spacing distance **6224**. Each magnet pair may have the same or different spacing distance **6224**. As shown in FIG. **62G**, an orientation (e.g., poles) of the magnets in the magnet array **6220** may comprise a predetermined pattern.

(224) In some variations, a ratio of the cavity height **6202** to the spacing distance **6224** is between about 20:1 and about 1:20, between about 10:1 and about 1:10, between about 5:1 and about 1:5, and between about 3:1 and about 1:3, including all values and sub-ranges in-between. In some variations, an actuator **6240** (e.g., linear, rotary) may be configured to move the magnet array **6220** relative to the flow cell **6210**. In some variations, an orientation (e.g., poles) of the magnets in the magnet array **6220** may comprise a predetermined pattern (e.g., Halbach array).

(225) In some variations, the magnet array **6220** may move relative to the flow cell **6210** or vice versa. FIG. **62A** illustrates the MACS module **6200** in an open configuration and FIG. **62B** illustrates the MACS module **6200** in a closed configuration. FIG. **62B** is a perspective view of the MACS system **6200** in a second configuration where labeled cells may be magnetically attracted

towards the magnet array **6220**. In the second configuration, the magnetic field lines generated by the magnet array traverse the flow channel exerting a magnetophoretic force on magnetically tagged cells that are injected into the channel. FIG. **62C** is a cross-sectional side view of the MACS system **6200** including the magnet array **6220**. FIG. **62D** is a perspective view of a MACS system **6200** in the second configuration. FIG. **62E** is a plan view of a flow cell **6210** and magnet array **6220** of a MACS system. FIG. **62F** is a plan view of a flow cell **6210** of a MACS system.

(226) FIG. **63A-63E** are perspective views of a set of magnet arrays **6300**, **6310**, **6320**, **6330**, **6340**. One or more of the size, strength, shape, spacing, and orientation of the magnets in a magnet array may be set to generate a magnetic field to attract magnetically-labeled cells. Additionally or alternatively, a magnet array may comprise a high-magnetic permeability material configured to enhance or reduce the field strength and field gradients within the flow cell. The material may be disposed between a magnet and flowcell. Additionally or alternatively, the material may be disposed within the flowcell and/or on one or more sides of the flowcell.

(227) FIGS. **64A** and **64B** are respective perspective and cross-sectional side views of a MACS module **6400** comprising a flow cell **6410** and a magnet array **6420**. The flow cell **6410** may comprise a set of linear channels **6412**, **6414**, **6416** comprising a first channel **6412** parallel to a second channel **6414**, and a third channel **6416** in fluid communication with each of the first channel **6412** and the second channel **6414**. As shown in FIG. **64B**, the third channel **6416** may be disposed between the first channel **6412** and the second channel **6414** and define a volume where fluid from the first channel **6412** and the second channel **6414** interact (e.g., mix). In some variations, the flow cell **6410** may comprise a first inlet **6430** coupled to the first channel **6412** and configured to receive a first fluid **6460** (e.g., cells). A second inlet **6431** may be coupled to the second channel **6414** and configured to receive a second fluid **6470** (e.g., buffer). The flow cell **6410** may comprise a first outlet **6432** coupled to the first channel **6412** and a second outlet **6433** coupled to the second channel **6414**.

(228) The magnet array **6420** may be disposed external to the flow cell **6400** and may be moved relative to the flow cell **6400** as described herein. In some variations, a longitudinal axis of the flow cell **6410** may be perpendicular to ground such that fluid flows in a generally vertical direction.

(229) In some variations, the first channel **6412** may have different dimensions from the second channel **6414**. For example, a first cavity height of the first channel **6412** may be larger than a second cavity height of the second channel **6414**. For example, a ratio of the first cavity height to a second cavity height may be between about 1:1 to about 3:7, between about 1:1 to about 2:3, and between about 2:3 to about 3:7, including all values and sub-ranges in-between. Fluid flowing through the first channel **6412** may have a slower flow rate relative to the second channel **6414** due to the larger cavity height of the first channel **6412** relative to the second channel **6414**. In some variations, the third channel **6416** may comprise a ratio of a length of the third channel **6416** to a diameter of the third channel **6416** of between about 2:1 to about 6:1, between about 2:1 to about 3:1, between about 3:1 to about 4:1, between about 4:1 to about 5:1, between about 5:1 to about 6:1, and between about 3:1 to about 5:1, including all values and sub-ranges in-between.

(230) As shown in FIG. **64B**, a first fluid **6462** may flow through the flow cell **6410** generally following a first direction. The magnetically-labeled cells **6416** within the first fluid **6462** may separate from the rest of the first fluid **6462** within the third channel **6416** as the magnetic attractive forces generated by magnet array **6420** pulls the cells **6416** away from the first channel **6412** and towards the second channel **6414** (e.g., towards the magnet array **6420**). Similarly, a second fluid **6470** (e.g., buffer) may flow through the second channel **6414**. As the cells **6416** flow towards the magnet array **6420**, they displace the second fluid **6470** flowing through the third channel **6416** such that a portion of the second fluid **6470** may flow into the first channel **6412**. In this manner, magnetically-labeled cells **6416** may be magnetically separated from a first fluid **6462** and the second fluid **6470** may aid removal of the first fluid **642** not including the cells **6416**.

(231) In some variations, a set of fluidic loops may be coupled to the flow cell to enable a plurality

of cell separation cycles. FIG. 64C is a schematic diagram of a MACS module comprising a flow cell **6410**, a first fluid conduit **6480** coupled to an inlet **6430** of the flow cell **6410** and an outlet **6432** of the flow cell **6410**. The first fluid conduit may **6480** may be configured to receive the set of cells from an outlet **6432** of the flow cell **6410** for recovery and/or recirculation through the inlet **6430** of the flow cell **6410**. A second fluid conduit **6490** may be coupled to the inlet **6431** of the flow cell **6410** and the outlet **6433** of the flow cell **6410** to recirculate fluid such as buffer and unrecovered magnetically-labeled cells. The second fluid conduit **6490** may be configured to receive a fluid without the set of cells from the flow cell **6410**. Higher purities of labeled cells may be recovered based on a number of cycles performed. For example, a single cell separation cycle may yield about 80% cell purity, a second cell separation cycle may yield about 96% cell purity, a third cell separation cycle may yield about 99.2% cell purity, and a fourth cell separation cycle may yield about 99.84% cell purity.

(232) In some variations, applying a centrifugal force to a magnetic cell separation process may further attract labeled cells toward a magnetic array independently of fluid flow rate so as to maintain throughput. FIGS. 65A-65C are schematic diagrams of a MACS module **6500** utilizing centrifugal force to aid a cell separation process. FIG. 65A depicts a flattened flow cell **6510** configured to be wrapped to form a generally cylindrical shape **6512**. The flow cell **6510** may comprise a curved flow path **6520**.

(233) FIG. 65B illustrates a cylindrical flow cell **6510** concentrically surrounded by (e.g., nested within) a cylindrical magnet array **6530**. In FIG. 65B, only a cross-section of the magnet array **6530** is shown for the sake of clarity. The flow cell **6510** may be spaced apart from the magnet array **6530** by a predetermined spacing distance. Accordingly, the flow cell **6510** may be configured to rotate **6550** about a longitudinal axis to generate a centrifugal force on the fluid **6540** within the flow path **6520** in an outward direction towards the magnet array **6530**. During a cell separation process, the fluid may be subject to set of forces depicted in FIG. 65C including a bulk fluidic force **6560** in an axial (e.g., bulk flow) direction, a centrifugal force **6570** in a radially outward direction from a center of rotation (e.g., proportional to a net particle system buoyancy), and a magnetic force **6580** extending radially outward from a center of rotation (e.g., proportional to net particle system magnetic attractiveness). In some variations, labeled cells may comprise a higher density than non-labeled cells. Therefore, centrifugal force may preferentially push the labeled cells towards the magnet **6530**, further increasing the specificity and efficiency of cell separation.

(234) FIGS. 66A-66C are schematic diagrams of a cell separation system and process. A magnetic cell separation system may comprise a flow cell **6610** comprising a flow path **6620** (shown schematically flattened for sake of clarity), and a magnet array **6630**. As shown in step **6600**, a set of cells **6640**, **6642** may comprise labeled cells **6640** (e.g., magnetically labeled cells) and non-labeled cells **6642** may flow into the flow path **6620** of flow cell **6610**. For example, a set of the cells **6640** may be labeled with a magnetic-activated cell selection (MACS) reagent. The magnet array **6630** may be disposed external to the flow cell **6610** such that the magnet array **6630** may be moveable relative to the flow cell **6610**. For example, the magnet array **6630** may move away from the flow cell **6610** to facilitate flowing the set of cells **6640** out of the flow cell **6610**.

(235) At step **6602**, the flow cell **6650** may be rotated to generate centrifugal force to push the cells **6640**, **6642** toward the magnet array **6630**. In some variations, a longitudinal axis of the flow cell **6610** may be oriented substantially perpendicular to ground in order for fluid flow through the flow cell **6610** to be aided by gravity. At step **6604**, the magnet array **6630** may magnetically attract the set of cells **6640** towards the magnet array **6630** for a predetermined dwell time as described herein. The non-labeled cells **6642** are not magnetically attracted to the magnet array **6630** and may flow out of the flow cell **6610** into, for example, a waste vessel. In some variations, the fluid (e.g., cells **6160**, **6170**) within the flow cell may be held statically within the flow cell **6110** for a dwell time before the fluid (e.g., cells **6170**) flow from outlet **6132**. In some variations, the magnetic

coupling between the magnet array **6630** and the cells **6640** may be released after the dwell time, and the cells **6640** may be recovered.

(236) FIGS. **12A** and **12B** illustrate the magnet of the MACS instrument **1200** comprising a magnet and a MACS module **1210**. The magnet is shown in FIG. **12A** in an ON configuration and shown in FIG. **12B** in an OFF configuration.

(237) Bioreactor

(238) The bioreactors described herein may comprise a vessel configured to culture mammalian cells. Generally, cell and gene therapy products may be grown in a bioreactor to produce a clinical dose which may subsequently be administered to a patient. A number of biological and environmental factors may be controlled to optimize the proliferation speed and success of cell growth. The bioreactor modules described herein enable one or more of monitoring, adjusting, and/or controlling of cell growth (e.g., to facilitate consistent and efficient cellular proliferation).

(239) FIG. **67A** is a schematic diagram of a cell processing system **6700** (e.g., bioreactor module) comprising one or more of a bioreactor **6710**, one or more sensors **6720**, an agitator **6730**, a temperature regulator **6740**, and a gas regulator **6750**. In some variations, the sensor **6720** may be configured to monitor (e.g., measure, sense, determine) one or more characteristics of the bioreactor module **6700** and cells in the bioreactor **6710**. For example, the sensor **6720** may comprise one or more of a pH sensor, a dissolved oxygen (DO) sensor, a temperature sensor, a glucose sensor, a lactose sensor, a cell density sensor, a humidity sensor, combinations thereof, and the like. One or more of the sensors may be a non-invasive optical sensor.

(240) FIGS. **67B-67D** are schematic diagrams of a cell processing system comprising a workcell **6760**, a bioreactor system **6700** (e.g., bioreactor instrument), a cartridge **6770**, an agitator **6730**, and a fluid connector **6780**. In some variations, a cartridge **6770** for cell processing may comprise a liquid transfer bus and a plurality of modules (e.g., bioreactor module, CCE module, MACS module, EP module). Each module may be fluidically linked to the liquid transfer bus. The bioreactor module may comprise at least one bioreactor.

(241) The bioreactor instrument **6700** may be configured to interface with the cartridge **6770**. In some variations, the bioreactor instrument **6700** may comprise the agitator **6730** configured to couple to the bioreactor. The agitator may be configured to agitate cell culture media comprising cells. In some variations, the fluid connector **6780** may be configured to couple the bioreactor system **6700** and workcell **6760**.

(242) FIG. **67B** depicts a cartridge **6770** comprising a bioreactor disposed within a workcell **6760**. The bioreactor **6700** may be uncoupled from the workcell **6760**. Once the fluid connector **6780** couples (e.g., to create a sterile flow path) the workcell **6760** to the bioreactor **6700**, the cartridge **6770** may be moved into the bioreactor **6700**, as shown in FIG. **67C**. For example, the cartridge **6770** may be coupled to (e.g., disposed on) an agitator **6730** and then agitated, as shown in FIG. **67D**. In some variations, the fluid connector **6780** may comprise a set of foldable sidewalls (e.g., like an accordion) configured to receive and dissipate the agitation of the agitator **6730** without transmitting such motion to the workcell **6760**. That is, the fluid connector **6780** may function as a bellows to maintain the connection between the workcell **6760** and bioreactor **6700** without agitating the workcell **6760**. In some variations, the fluid connector **6780** may couple the bioreactor (e.g., of cartridge **6770**) to a liquid transfer bus.

(243) In some variations, an agitator may be configured to generate motion (e.g., orbital, rotary, linear) to the bioreactor in order to mix the culture in instances where it is required to encourage interactions with a reagent and cells. For example, orbital motion may be used to create a homogenous culture volume such that a small sample taken from the culture may be representative of the culture at large. In some variations, the agitator **6730** may comprise one or more impellers. The agitator **6730** may be configured to provide variable-intensity mixing during culture at defined periods.

(244) In some variations, orbital motion may encourage increased interactions within the cell

culture, such as in the toroidal bioreactors described herein that comprise a geometry that may encourage the continuous and gentle flow of fluid around the bioreactor, thereby aiding homogenous mixing with minimal shear stress transferred to the cells.

(245) In some variations, the temperature regulator **6740** may be configured to control a temperature of a bioreactor and corresponding processes. The temperature regulator **6740** may be coupled to the bioreactor. For example, the temperature regulator **6740** may control a temperature of a cell culture to be between about 2° C. and about 40° C. and thereby ensure that a culture is heated to physiological conditions and cooled to slow metabolic processes (e.g., to keep cells in a dormant state) as desired. For example, the thermal regulator **6740** may comprise a circulating coolant coupled to a heat exchanger coupled to a thermal interface (e.g., heating/cooling plate).

(246) In some variations, the gas regulator **6750** may be coupled to the bioreactor and configured to control a gas composition of a bioreactor and corresponding processes using one or more of Clean Dry Air (CDA), carbon dioxide, and nitrogen. The gas regulator **6750** may be coupled to the bioreactor. For example, the sensors **6720** and gas regulator **6750** may provide closed-loop gas control of the bioreactor module **6700**. In some variations, CDA may comprise oxygen such as pure oxygen. In some variations, the gas regulator may comprise a manifold coupled to one or more gas sources. The manifold may include a solenoid coupled to a valve (e.g., restrictive orifice) configured to control gas flow through the bioreactor **6710**. The solenoid may be configured to pulse to control a quantity and composition of gas received through the manifold. Additionally or alternatively, one or more of a proportional valve and Mass Flow Controller (MFC) may be configured to meter and control the flow of gas to a manifold. In some variations, the gas regulator **6750** may comprise one or more sensors to measure the gas mixture and/or flow rate. Additionally or alternatively, the sensors may be configured for closed-loop control of gas flow through the gas regulator.

(247) In some variations, measured pH from a pH sensor may be used to control a pH of the bioreactor **6710** using the gas regulator **6750**. For example, in response to the measured pH, gas regulator **6750** may control a CO₂ concentration of the gas contacting the cell culture to control the free hydrogen ions and pH of the culture. In some variations, a pH of the bioreactor **6710** may be between about 5.5 and about 8.5. One or more of CO₂ composition of the gas in the bioreactor **6710**, buffer, and reagents (e.g., acid, base) may be used to regulate pH. In some variations, a dissolved oxygen concentration of the bioreactor **6710** may be between about 0% and about 21%. Nitrogen composition of the gas in the bioreactor **6710** may be used to regulate the dissolved oxygen concentration. For example, control of both the agitator in the bioreactor and the flow rate and composition of the gas contacting the cell culture may regulate the dissolved carbon dioxide concentration.

(248) In some variations, measured dissolved oxygen from a dissolved oxygen sensor may be used to control an oxygen concentration (e.g., below atmospheric levels) of the bioreactor **6710** using the gas regulator **6750**. For example, gas regulator **6750** may control a nitrogen concentration of the gas contacting the cell culture to create hypoxic conditions.

(249) FIGS. **68A** and **68B** are cross-sectional perspective views of a bioreactor **6800** comprising an enclosure **6810** comprising a base **6812**, a sidewall **6814**, and a top **6816**. A gas-permeable membrane **6820** may be coupled to one or more of the base **6812** and the sidewall **6814** of the enclosure **6810**. In some variations, the enclosure **6810** may comprise a first chamber **6830** having a first volume and a second chamber **6832** having a second volume, the first chamber **6830** separated from the second chamber **6832**, and the first volume smaller than the second volume. In some variations, the first chamber **6830** may be concentrically nested within the second chamber **6832**. For example, nesting the chambers may enable larger overall working volume ranges (e.g., **100:1**). The first chamber **6830** may comprise a well shape with an angled base surface to promote fluid pooling at a center of the first chamber **6830** during aspiration. In some variations, the base **6812** may be disposed on a thermal regulator (not shown) such as a thermoelectric element. In

some variations, the enclosure **6810** may be composed of a thermally conductive material such as a metal (e.g., aluminum).

(250) In some variations, the bioreactor **6800** may be coupled to a gas regulator (not shown) to facilitate gas transfer through the gas-permeable membrane **6820** (e.g., into and out of the culture). The gas-permeable membrane **6820** may be configured to hold a cell culture. Gas may diffuse through the surfaces of the culture that contact the gas-permeable membrane to enable increased oxygenation of the cell culture and removal of gaseous metabolic byproducts of the cell culture, and thus increase the potential for metabolic activity. For example, the gas-permeable membrane **6820** enables dissolved oxygen to diffuse into the culture in close proximity to a cell bed where the oxygen may be consumed. In some variations, the bioreactor may be coupled to both a first gas regulator to facilitate gas transfer through the gas-permeable membrane and a second gas regulator to facilitate control of headspace gas composition.

(251) In addition to gas transfer, the bioreactors described herein may be configured to efficiently control a temperature of a cell culture using a conductive thermal interface (e.g., gas-permeable membrane **6820**, enclosure **6810**) along both a base and sidewall of the bioreactor.

(252) In some variations, the first chamber **6830** may comprise a working volume of between about 10 ml and about 100 ml. In some variations, the first chamber **6830** may comprise a total volume of between about 10 ml and about 130 ml. In some variations, the second chamber **6832** may comprise a working volume of between about 100 ml and about 1000 ml. In some variations, the second chamber **6832** may comprise a total volume of between about 100 ml and about 1400 ml. In some variations, the first chamber **6830** may comprise a diameter of between about 10 mm and about 100 mm, and a height of between about 10 mm and about 100 mm. In some variations, the second chamber **6832** may comprise a diameter of between about 100 mm and about 250 mm, and a height of between about 10 mm and about 100 mm.

(253) As shown in FIG. **68B**, a base **6822** of the gas-permeable membrane **6820** may comprise an angle between about 3 degrees and about 10 degrees relative to the base **6812** of the enclosure **6810**. Similarly, FIGS. **69A** and **69B** depict a sloped base. For example, due to a slope of the base **6822**, the chambers **6830**, **6832** are deeper towards a center of the bioreactor **6800**. This may encourage cell growth towards a center of the bioreactor **6800**, which may aid one or more of cell sampling, cell transfer, cell recovery, and the like. In some variations, orbital motion of the bioreactor **6800** may promote cell congregation toward a center of the bioreactor **6800**, thereby increasing interaction between the cells.

(254) In some variations, the gas-permeable membrane **680** may comprise a curved surface. In some variations, the gas-permeable membrane may comprise a set of patterned curved surfaces. For example, the set of patterned curved surfaces may comprise a radius of curvature of between about 50 mm and about 500 mm.

(255) In some variations, the bioreactor may be configured to facilitate monitoring (e.g., temperature, pH, dissolved oxygen) and fluid flow (e.g., gas composition, fluid transfer) between the chambers. As shown in FIG. **68C**, the enclosure **6810** may comprise one or more nested surfaces curved around a longitudinal axis (e.g., center) of the enclosure **6810**. For example, the nested surfaces may comprise a set of concentric toroids. The enclosure **6810** may comprise a toroid shape. FIG. **68C** is a perspective view and FIG. **68D** is a bottom view of enclosure **6810** comprising a set of apertures **6818** (e.g., holes, openings, slits, slots). In some variations, the apertures **6818** may enable gas and/or heat transfer between the components and chambers of the bioreactor **6800**. Additionally or alternatively, one or more sensors may be coupled to the apertures **6818**. For example, the apertures **6818** may be coupled to a non-contact sensor (e.g., pH, DO) such as an optical sensor (not shown) configured to determine a fluorescent spot disposed on a surface of the bioreactor. In some variations, one or more of a sensor and fluid connector may be introduced through the apertures **6818**.

(256) In some variations, the gas-permeable membrane extends along the base **6812** and the

sidewall **6814** of the enclosure **6810**, as shown in FIG. **68B**. In some variations, the gas-permeable membrane extends only along the base **6812** of the enclosure **6810**. FIG. **68E** is a perspective view and FIG. **68F** is a side view of the gas-permeable membrane **6820** where an outer surface of the gas-permeable membrane **6820** comprises one or more projections **6824** (e.g., projections, spacers, ribs). The projections **6824** are also depicted in the perspective view of FIG. **68G** and bottom view of FIG. **68H**. The projections **6824** contact the enclosure **6810** and define a cavity between the enclosure **6810** and the gas-permeable membrane **6820**. That is, the projections **6824** may be configured to mechanically space away the enclosure **6810** from a portion of the gas-permeable membrane **6820** to facilitate thermal transfer from the enclosure **6810** to the cell culture. In some variations the gas-permeable membrane may comprise polydimethylsiloxane (PDMS) (e.g., silicone), fluorinated ethylene propylene (FEP), polyolefin (PO), polystyrene (PS), ethyl vinyl acetate (EVA) and have a thickness of between about 0.1 mm and about 0.4 mm, between about 0.2 mm and about 0.3 mm, and about 0.25 mm, including all ranges and sub-values in-between.

(257) FIG. **69A** is a cross-sectional side view of an enclosure **6910** of a bioreactor comprising a first chamber **6912**, a second chamber **6914**, and a column **6916** extending along a longitudinal axis of the enclosure **6910**. FIG. **69B** is a cross-sectional perspective view of the enclosure **6910** showing the nested curves of the enclosure **6910**. The column **6916** may be configured to promote cell culture in combination with agitation such as orbital motion.

(258) FIG. **70** is an exploded perspective view of a bioreactor **7000** comprising an enclosure **7010**, a gas-permeable membrane **7020**, and a top **7030**. The top **7030** may be composed of a material such as polyethylene.

(259) FIG. **71A** is a plan view of a bioreactor **7100** comprising a first chamber **7110** and a second chamber **7120**. FIG. **71B** is a cross-sectional side view of the bioreactor **7100**.

(260) FIGS. **13A** and **13B** are perspective views of a cartridge **1300** and bioreactor instrument interface **1310**. The bioreactor instrument interface **1310** is coupled to the cartridge **1300** in FIG. **13B**.

(261) FIG. **14** is a perspective view of a bioreactor instrument **1410** comprising a set of cartridges **1400**, **1402**, **1404** and cavities **1420**, **1422**, **1424** configured to receive a respective cartridge. In some variations, each cartridge may be docked to enable simultaneous expansion, culturing, or resting steps.

(262) Electroporation Module

(263) In some variations, an electroporation module may be configured to facilitate intracellular delivery of macromolecules (i.e., transfection by electroporation). An electroporation module may contain a continuous flow or batch mode chamber and one or more sets of electrodes for applying direct or alternating current to the chamber. An electrical discharge from one or more capacitors, or current sources, may generate sufficient current in the chamber to promote transfer of a polynucleotide, protein, nucleoprotein complex, or other macromolecule into the cells in the cell product. As with other modules described herein, one or more components used for the process step (here, electroporation) may be provided on the cartridge or in the instrument to which the cartridge interfaces. For example, the capacitor(s) and/or batteries may be provided in the module on the cartridge or in the instrument. The electroporation module may, in some variations, be configured to apply an electric field to a cell suspension under continuous flow in a microfluidic device, e.g., as described in Garcia et al. Sci. Rep. 6:21238 (2016).

(264) Additionally or alternatively, intracellular delivery of macromolecules may also be achieved by other methods, such as mechanoporation. It should be understood that throughout the disclosure variations comprising an electroporation module may instead or in addition comprise a mechanoporation module, or another module configured to perform any suitable method of delivering macromolecules into cells. Mechanoporation can be achieved by, for example, applying transient, fluidic pressure to a solution containing cells, or by applying physical pressure to the cells (e.g., by microneedles). Illustrative methods of mechanoporation by passing a cell suspension

through a constriction are provided, e.g., in International Patent Publication No. WO 2017/041051 and WO 2017/123663, and are incorporated by reference herein. Mechanoporation can also be achieved by applying a vortex to a cell suspension in a microfluidic device.

(265) FIG. 72 is a schematic diagram of an electroporation module **7200** (e.g., electroporation system) comprising an electroporation chamber **7210** (which may comprise a fluid conduit), a pump **7220**, an inlet **7230**, an outlet **7232**, a set of pinch valves **7234**, a first fluid source **7240** (e.g., fluid reservoir, cell reservoir), a second fluid source **7242** (e.g., vent, gas source), a set of sensors **7250** (e.g., bubble sensors), and a controller (e.g., processor and memory) configured to control the module **7200**, and a signal generator **7270** configured to deliver an electroporation signal (e.g., voltage pulse) to the electroporation chamber **7210**.

(266) In some variations, the fluid conduit **7210** may be configured to receive a first fluid comprising cells and a second fluid. A set of electrodes may be coupled to the fluid conduit **7210**. A pump may be coupled to the fluid conduit **7210**. The controller **7260** may be configured to generate a first signal to introduce the first fluid into the fluid conduit **7210** using the pump **7220**, generate a second signal to introduce the second fluid into the fluid conduit **7210** such that the second fluid separates the first fluid from a third fluid, and generate an electroporation signal to electroporate the cells in the fluid conduit **7210** using the set of electrodes.

(267) In some variations, the second fluid may comprise a gas or oil. In some variations, the controller may be configured to generate a third signal to introduce the third fluid into the fluid conduit **7210**. The third fluid may be separated from the first fluid by the second fluid. In some variations, a cartridge for cell processing may comprise a liquid transfer bus and a plurality of modules such as the electroporation module **7200**. Each module may be fluidically linked to the liquid transfer bus.

(268) The set of sensors **7250** may be configured to measure fluid changes in a fluid conduit such as a change from a first fluid to a second fluid (e.g., liquid to air) in the fluid conduit. The module **7200** may further comprise a set of valves configured to ensure fluid does not backflow into the electroporation chamber **7210** and/or fluid source **7240**. The electroporation chamber **7210** may comprise a cavity configured to hold a fluid to be electroporated and a set of electrodes to apply an electroporation signal to the fluid. For example, the signal generator **7270** may generate a square wave pulse as described in more detail herein.

(269) In some variations, the electroporation module **7200** (e.g., valves **7234**, pump **7220**, sensors **7250**, and controller **7260**) may be configured to control fluid flow through the electroporation chamber **7210** in a discontinuous (e.g., batch process) manner. For example, a first batch of cells may undergo electroporation and be physically separated from a second batch of cells by an intermediate fluid such as air or fluid such as oil. Separating cell batches may reduce mixing of transfected and non-transfected cells, and further ensure fixed batch volume. That is, a fluid gap may form a visually verifiable boundary between cell batches to reduce diffusion and mixing between electroporated and non-electroporated cells. Separating cell batches may reduce the duration of time that cells are exposed to certain cytotoxic reagents (e.g., electroporation buffer), thereby increasing performance.

(270) In some variations, a batch of cells may be electroporated when substantially static (e.g., substantially no fluid flow state). By contrast, conventional continuous flow electroporation has an upper fluid flow rate limit correlated to a transfection efficiency. In the batch processing described herein, cell batches may be transferred into and out of the electroporation chamber **7210** at a predetermined rate to increase the overall throughput of the system **7200** without a decrease in electroporation efficiency. Furthermore, the electroporation system **7200** does not utilize a precisely controlled flow rate/pulse rate such as those needed for continuous flow electroporation systems.

(271) FIG. 73 is an exploded perspective view of an electroporation module **7300** may comprise an electrode **7310**, a fluid conduit **7320** (e.g., electroporation chamber), a substrate **7330** (e.g., alloy busbar), a housing **7340**, and a fastener **7350**. In some variations, the fluid conduit **7320** may be

configured to hold a volume of fluid between about 0.4 ml and about 3.5 ml. The electroporation module **7300** is a parallel-plate design. In some variations, the electrodes may comprise stainless steel and may be separated by an insulating gasket. In some variations, the electrodes may be polished and/or coated with nonreactive materials (e.g., gold, platinum) to reduce gradual buildup of biological matter (e.g., charged molecules, DNA, proteins) on the electrode surface.

(272) Generally, a method of electroporating cells may comprise receiving a first fluid comprising cells in a fluid conduit, receiving a second fluid in the fluid conduit to separate the first fluid from a third fluid, applying an electroporation signal to the first fluid to electroporate the cells. In some variations, the third fluid may be received in the fluid conduit separated from the first fluid by the second fluid. In some variations, the first fluid may be substantially static when applying the electroporation signal.

(273) FIGS. **74A-74B** are schematic diagrams of variations of an electroporation process **7400**, **7402**. A method **7400** may include loading cells **7410** into an electroporation chamber **7450**. For example, at step **7412**, a first fluid may be pumped into the electroporation by opening valve v1 and the pump generating negative pressure (valves v2 and v3 are closed). At step **7414**, a second fluid (e.g., gas, oil) may separate the first fluid from a third fluid to create a first batch of cells to electroporate. For example, valves v1 and v3 may be closed with valve v2 open and the pump generating negative pressure. In some variations, a loading volume may be between about 1 ml and about 3 ml with a pumping time of between about 8 seconds and about 15 seconds (at a rate of about 20 ml/min). At step **7420**, the cells of the first fluid may be electroporated with each of the valves closed and the pump off. At step **7430**, the cells of the first fluid may be flowed out of the electroporation chamber **7450** to output where valves v1 and v2 are closed, valve v3 is open, and the pump generates positive pressure.

(274) FIG. **74B** depicts another configuration where a pump is disposed between an input and the electroporation chamber such that the pump may be configured to pump in a single direction. A method **7402** may include loading cells **7411** into an electroporation chamber **7450**. For example, at step **7416**, a first fluid may be pumped into the electroporation by opening valve v1 and v4, and the pump generating positive pressure (valves v2 and v3 are closed). At step **7418**, a second fluid (e.g., gas, oil) may separate the first fluid from a third fluid to create a first batch of cells to electroporate. For example, valves v1 and v3 may be closed with valves v2 and v4 open, and the pump generating positive pressure. At step **7422**, the cells of the first fluid may be electroporated with each of the valves closed and the pump off. At step **7432**, the cells of the first fluid may be flowed out of the electroporation chamber **7450** to output where valves v1 and v4 are closed, valves v2 and v3 are open, and the pump generates positive pressure.

(275) In some variations, an impedance/resistance across electrodes of an electroporation system may increase over time due to electrode passivation/degradation due to charged biological matter (e.g., charged molecules, DNA, proteins) attaching to the electrode surface. Active electrical field compensation may be applied to ensure a consistent electrical field strength applied to cells over multiple batches of cells. This may reduce the need for electrode surface modification to reduce passivation.

(276) FIG. **75** is a circuit diagram of a resistor divider network for an electroporation process **7500**. For example, a set of cells may be introduced into an electroporation chamber **7510** to which a voltage $V_{\text{sub.chip}}$ may be applied. Fluid resistance $R_{\text{sub.b}}$ corresponds to a fluid (e.g., cell mixture) resistance. Assuming a uniform cell distribution, the fluid resistance $R_{\text{sub.b}}$ should be consistent, also assuming the same volume of each fluid batch being electroporated. $R_{\text{sub.i}}$ corresponds to a resistance between fluid and electrode, which increases over time through the electroporation process. In a conventional electroporation process, voltage $V_{\text{sub.ps}}$ is constant. However, due to the increasing $R_{\text{sub.i}}$ over time, the voltage applied to the fluid will decrease over time, leading to lower electrical field strength.

(277) Due to variations in fluid resistance $R_{\text{sub.b}}$ and the low number of pulses that may be

applied, interpolation to compensate for reduced electrical field strength may not accurately compensate for electrode passivation.

(278) In some variations, a method of electroporating cells may comprise receiving a first fluid comprising cells in a fluid conduit, applying a resistance measurement signal to the first fluid using a set of electrodes, measuring a resistance between the first fluid and the set of electrodes, and applying an electroporation signal to the first fluid based on the measured resistance. In some variations, a second fluid comprising a gas may be received in the fluid conduit before applying the electroporation signal to the fluid. The first fluid may be separated from a third fluid by the second fluid.

(279) FIGS. **76A-76D** are plots **7600, 7602, 7604, 7606** of measurement waveforms and electroporation waveforms. FIG. **76A** depicts a first resistance measurement pulse **7620** with a low voltage and a wide pulse width. FIG. **76B** depicts a second resistance measurement pulse **7622** with a high voltage and a short pulse width. FIG. **76C** depicts a third resistance measurement pulse **7624** with a continuous low voltage waveform to monitor an impedance change continuously over time. FIG. **76D** depicts a fourth resistance measurement pulse **7626** with a low AC voltage waveform to monitor an impedance change continuously over time. Each of the resistance measurement pulses avoid inducing electroporation in the cells by reducing voltage and/or pulse width. By monitoring the voltage current of the applied resistance measurement pulse, a change in resistance may be measured and the electroporation pulse applied to a cell batch may be compensated accordingly.

(280) In some variations, an electroporation signal may comprise between about 1 pulse and about 50 pulses, a voltage of between about 100 V and about 700 V, a pulse width of between about 100 s and about 1 ms, a pulse spacing between about 5 second to about 30 seconds, a resistance pulse voltage of between about 10 V and about 40 V, and a resistance pulse width of between about 10 μ s and about 50 μ s.

(281) For example, an eight-batch electroporation run may receive one electroporation pulse per batch. Each electroporation pulse may have an electrical field strength between about 0.5 kV/cm and about 2.0 kV/cm. The resistance measurement pulse applied before each batch may have an electrical field strength less than about 0.2 kV/cm such that electroporation is not induced by the resistance measurement pulse.

(282) Sterile Liquid Transfer Device

(283) Generally, the sterile liquid transfer devices described herein may be configured to store fluid for transfer to another component of a cell processing system such as a cartridge, bioreactor, and the like. In some variations, the sterile liquid transfer device may comprise a portable consumable configured to be moved using a robot. For example, a robot may be configured to move a sterile liquid transfer device from a reagent vault to an ISO 7 space to a sterile liquid transfer instrument within a cell processing system. The sterile liquid transfer device enables the transfer of fluids in an automated, sterile, and metered manner for automating cell therapy manufacturing.

(284) FIGS. **103A** and **103B** are perspective views of a sterile liquid transfer device **10300** comprising a fluid cavity **10310** (e.g., container, vessel), fluid connector **10320** (e.g., fluid connector), and pump **10330**. Fluid stored within fluid cavity **10310** may be transferred in and out of the sterile liquid transfer device **10300** through the fluid connector **10320** using the pump **10330**. In some variations, the sterile liquid transfer device **10300** may comprise an engagement feature **10340** (e.g., robot mount) to facilitate robotic arm control.

(285) Fluid Connector

(286) Generally, the aseptic fluid connectors described herein may form a sterile fluid pathway between at least two fluid devices to enable fluid transfer that may be one or more of sterile, fully automated, and precisely metered (e.g., precise control of a transferred fluid volume). In some variations, the robot may be configured to couple a fluid connector between at least two of the plurality of instruments and one or more cartridge. In some variations, the robot may be configured to operate the fluid controller to open and close a set of ports and valves of the fluid connector. The

use of a robot and controller to operate the fluid connector may facilitate automation and sterility of a cell processing system.

(287) In some variations, a system may comprise a robot configured to operate a fluid connector as described herein, and a controller comprising a memory and processor. The controller may be coupled to the robot. The controller may be configured to generate a port signal to couple the first port to the second port using the robotic arm, generate a first valve signal to translate the first valve relative to the second valve using the robotic arm, and generate a second valve signal to transition the first valve and the second valve to the open configuration.

(288) In some variations, a fluid pump may be coupled to the sterilant source, and the controller may be configured to generate a first fluid signal to circulate a fluid into the chamber through the sterilant port. The controller may be configured to generate a second fluid signal to circulate the sterilant into the chamber through the sterilant port to sterilize at least the chamber. The controller may be configured to generate a third fluid signal to remove the sterilant from the chamber.

(289) In some variations, the controller may be configured to generate a port signal to couple the first port to the second port using the robotic arm, generate a first valve signal to translate the first valve relative to the second valve using the robotic arm, and generate a second valve signal to transition the first valve and the second valve to the open configuration.

(290) The fluid connector may further allow for a plurality of connection cycles in a sterile system and may be controlled without human intervention. For example, the fluid connector may comprise one or more of engagement features to facilitate robotic arm control and alignment features to ensure proper connection between connector components. FIG. 15 is a block diagram of an illustrative variation of a fluid connector system **1500** comprising a fluid connector **1510**, first fluid device **1520**, second fluid device **1522**, sterilant source **1530**, fluid source **1532**, robot (e.g., robotic arm) **1540**, and controller **1550**. The fluid connector **1510** may be removably coupled (e.g., connected/disconnected, attached/detached) to each of the first fluid device **1520**, second fluid device **1522**, sterilant source **1532**, fluid source **1532**, and robot **1540**. In some variations, a fluid device may comprise one or more of a cartridge and sterile liquid transfer device. For example, a sterile liquid transfer device may be in fluid communication with a cartridge via the fluid connector. As described in more detail herein, separate portions (e.g., male connector, female connector) of the fluid connector **1510** may be removably coupled to each other. The robot **1540** may be configured to physically manipulate (e.g., removably couple) one or more of the fluid connector **1510**, first fluid device **1520**, second fluid device **1522**, sterilant source **1530**, and fluid source **1532** in a predetermined manner. For example, the robot **1540** may connect the fluid connector **1510** between the first fluid device **1520** and the second fluid device **1522**. The robot **1540** may also connect the sterilant source **1530** and/or fluid source **1532** to a sterilant port of the fluid connector **1510**. In some variations, the robot **1540** may control one or more valves and/or ports of the fluid connector **1510**, and thereby initiate a sterilization process for one or more portions of the fluid connector **1510** using, for example, sterilant from the sterilant source **1530**. The controller **1550** may be coupled to one or more of the robot **1540**, sterilant source **1530**, and fluid source **1532** to control one or more of fluid transfer and sterilization.

(291) FIG. 16A is a schematic diagram of an illustrative variation of a fluid connector **1600**. The fluid connector **1600** may comprise a lumen extending along its length and be disposed between a first fluid device **1630** and a second fluid device **1640** to enable fluid flow through the fluid connector **1600**. In some variations, the first fluid device **1630** and second fluid device **1640** may be aseptically connected and disconnected using the fluid connector **1600**. The fluid devices **1630**, **1640** may comprise a closed sterile device, and may be the same or different types of fluid devices. For example, the fluid devices **1630**, **1640** may comprise one or more of a sterile liquid transfer device and consumable. In some variations, the fluid connector **1600** may comprise a first connector **1610** including a first proximal end **1612** and a first distal end **1614**. The first proximal end **1612** may be configured to couple to the first fluid device **1630**. The first distal end **1614** may

include a first port **1616**, first housing **1617**, and a first valve **1618**. The first housing **1617** may be configured to receive the first port **1616** in a closed configuration as described in more detail herein.

(292) The fluid connector **1600** may further comprise a second connector **1620** including a second proximal end **1622** and a second distal end **1624**. The second proximal end **1622** may be configured to couple to the second fluid device **1640**. The second distal end **1624** may include a second port **1626**, second housing **1627**, and a second valve **1628**. The second housing **1627** may be configured to receive the second port **1626** in a closed configuration. In FIG. **16A**, the first connector **1610** comprises a sterilant port **1650** configured to couple to a sterilant source (not shown). Additionally or alternatively, the second connector **1620** may comprise the sterilant port **1650**. The sterilant port **1650** may be configured to be in fluid communication with the first distal end **1614** and the second distal end **1624** when the second port **1626** is coupled to the first port **1616** as described in more detail herein.

(293) In some variations, a fluid device **1630**, **1640** may comprise a sterilant chamber and a sterilant port configured to receive a sterilant. The sterilant chamber may enclose a fluid device connector (not shown) configured to couple to a proximal end of a first connector **1610** or second connector **1620**. The fluid device **1630**, **1640** may receive a sterilant in a similar manner as the fluid connector **1600**.

(294) FIG. **16B** is a detailed schematic diagram of the first connector **1610** including a first port housing **1617** and a chamber **1615**. The chamber **1615** may be defined by the cavity enclosed by one or more of the distal ends **1614**, **1624**. For example, the chamber **1615** in FIG. **16B** may comprise the portion of the first connector **1610** between the first valve **1618** and the first port **1616** in the closed configuration (e.g., the first distal end **1614**). In some variations, the first chamber **1615** may comprise a volume of between about 1 cm.³ and about 5 cm.³. When the first connector **1610** is coupled to the second connector **1620** and the ports **1616**, **1626** are in an open configuration (as shown in FIG. **16D**), the chamber **1616** may comprise the portion of the fluid connector **1600** between the first valve **1618** and the second valve **1628** (e.g., the first distal end **1614** and second distal end **1624**). The chamber **1615** may comprise an enclosed volume configured to receive a fluid such as a sterilant from the sterilant port **1650**. In some variations, the sterilant port **1650** may comprise an inlet **1652** and outlet **1654**. Methods of using a fluid connector are described in more detail with respect to FIGS. **16C-16L** and **27**.

(295) In some variations, the fluid connector **1600** may comprise one or more alignment features and robot engagement features configured to facilitate robotic manipulation, as described in more detail herein. In some variations, the fluid connector **1600** may be coupled to one or more sensors, pumps, and valves to facilitate fluid transfer and monitoring.

(296) In some variations, the components of the fluid connector in contact with fluid may be USP Class V1 compatible for cell processing and/or GMP applications. In some variations, the components of the fluid connector may be composed of a material including, but not limited to, one or more of cyclic olefin copolymer (COC), polychlorotrifluoroethylene, polyetherimide, polysulfone, polystyrene, polycarbonate, polypropylene, silicone, polyetheretherketone, polymethylmethacrylate, nylon, acrylic, polyvinylchloride, vinyl, phenolic resin, petroleum-derived polymers, glass, polyethylene, terephthalate, metal, stainless steel, titanium, aluminum, cobalt-chromium, chrome, silicates, glass, alloys, ceramics, carbohydrate polymer, mineraloid matter, and combinations or composites thereof.

(297) FIGS. **17A-18D** depict external and internal views of variations of a fluid connector. FIG. **17A** is a front perspective view of a fluid connector **1700** in a closed port configuration. FIG. **17B** is a rear perspective view and FIG. **17C** is a rear view of the fluid connector **1700**. Generally, the fluid connector may comprise a plurality of internal seals to reduce contamination and aid sterilization, as well as alignment features to aid proper registration of the fluid connector components.

(298) The fluid connector **1700** may comprise a lumen extending along its length. In some variations, the fluid connector **1700** may comprise a first connector **1710** including a first proximal end **1712** and a first distal end **1714**. The first proximal end **1712** may be configured to couple to a first fluid device (not shown for the sake of clarity). The first proximal end **1712** may comprise a Luer connector or any other suitable connector. The first distal end **1714** may include a first port **1716** and first housing **1717**. The first housing **1717** is shown in FIG. 17A holding the first port **1716** in a closed configuration. The first connector **1710** further comprises a sterilant port **1750**, **1752** configured to couple to a sterilant source (not shown for the sake of clarity). In some variations, the sterilant port may comprise an inlet and outlet. In some variations, the sterilant port may optionally comprise one or more of a check valve and particle filter configured to reduce contamination into the sterilant port when not connected to a robot or actuator. The first connector **1710** may comprise a first alignment feature **1760** such as a set of protrusions on the first distal end **1714** of the first connector **1710**. The alignment features may ensure that small positioning errors due to robotic manipulation do not impact the operation of the fluid connector.

(299) The fluid connector **1700** may further comprise a second connector **1720** including a second proximal end **1722** and a second distal end **1724**. The second proximal end **1722** may be configured to couple to the second fluid device (not shown for the sake of clarity). The second proximal end **1722** may comprise a Luer connector or any other suitable connector. The second distal end **1724** may include a second port **1726** and second housing **1727**. The second housing **1727** is shown in FIG. 17A holding the second port **1726** in the closed configuration. The second connector **1720** may comprise a second alignment feature **1762** such as a set of holes on the second distal end **1724** of the second connector **1720**. The second alignment feature **1762** may be configured to couple to the first alignment feature **1760** in a predetermined axial and rotational configuration to aid mating of the first connector **1710** and the second connector **1720**.

(300) The first port **1716** and the second port **1726** retained within respective first housing **1717** of the first distal end **1714** and second housing **1727** of the second distal end **1724** facilitates robotic control as the ports **1716**, **1726** are not separable from the fluid connector **1700**, and therefore reduces the risk of failure of automated handling by a robot.

(301) In some variations, the first connector **1710** may comprise a first robot engagement feature **1770** and the second connector **1720** may comprise a second robot engagement feature **1772**. The robot engagement features **1770**, **1772** may be configured to be manipulated by a robot (e.g., robot **1540**) such a robotic arm. In some variations, the robot engagement features **1770**, **1772** may be operatively coupled to a respective first port **1716** and second port **1726** and configured to actuate the ports **1716**, **1726** between a closed port configuration and an open port configuration, as shown in FIGS. 17A-17F. Additionally or alternatively, a user may manually actuate the robot engagement features **1770**, **1772** to actuate respective ports **1716**, **1726**.

(302) FIG. 17D is a front perspective view of the fluid connector **1700** in an open port configuration. FIG. 17E is a rear perspective view and FIG. 17F is a rear view of the fluid connector **1700** in the open port configuration. In the open port configuration, the first valve **1718** of the first connector **1710** and the second valve **1728** of the second connector **1720** are shown in FIG. 17D.

(303) FIG. 18A is a side view and FIG. 18B is a cross-sectional side view of a fluid connector **1800** in an uncoupled configuration. In some variations, the fluid connector **1800** may comprise a first connector **1810** including a first housing **1817** comprising a first port **1816**, a sterilant port **1850** configured to couple to a sterilant source (not shown), a first alignment feature **1860** configured to couple to a corresponding alignment feature (not shown) of the second connector **1820**. The fluid connector **1800** may comprise a second connector **1820** including a second housing **1827** comprising a second port **1826**. The first connector **1810** and second connector **1820** may be axially aligned and alignment features may aid rotational alignment of the first connector **1810** to the second connector **1820**. The first valve **1818** may comprise a first valve stem **1819** and the

second valve **1828** may comprise a second valve stem **1829**.

(304) FIG. **18C** is a side view and FIG. **18D** is a cross-sectional side view of the fluid connector **1800** in a coupled configuration where the first housing **1817** and the second housing **527** are brought together but where the first connector **1810** and the second connector **1820** are not in fluid communication since the first port **1816** and the second port **1826** are both in the closed configuration. The first alignment features on each connector **1810**, **1820** may be configured to ensure axial and/or rotational alignment between the first connector **1810** and the second connector **1820**.

(305) FIG. **18E** is a side view and FIG. **18F** is a cross-sectional side view of the fluid connector **1800** in an open port configuration. Each of the first port **1817** and the second port **1827** are transitioned from the closed configuration to an open configuration. This creates a closed internal volume within respective distal ends of each connector **1810**, **1820**. Each of first valve **1818** and second valve **1828** is in a closed configuration such that fluid flow is inhibited between the first connector **1810** and the second connector **1820**. still restricted on each half on account of the auto-shutoff valves in both sides.

(306) FIG. **18G** is a side view and FIG. **18H** is a cross-sectional side view of the fluid connector **1800** in an open valve configuration where the first valve **1818** is coupled to the second valve **1828**. For example, the second valve **1828** may be translated along a longitudinal axis of the second connector **1820** towards the first valve **1818**. As shown in FIGS. **18G** and **18H**, the second connector **1820** may be axially compressed to translate the second valve **1828** towards the first valve **1818**. The first valve **1818** coupled to the second valve **1828** may form a radial seal, and the first valve stem **1819** and the second valve stem **1829** may be in contact to enable fluid communication between the first connector **1810** and the second connector **1820**.

(307) FIGS. **19-26B** are schematic diagrams of variations of fluid connector systems for coupling fluid devices. In some variations, a fluid connector may comprise a first connector configured to couple to any one of a plurality of second connectors. FIG. **19** is a schematic diagram of an illustrative variation of a fluid connector system **1900** comprising a first connector **1910**, a plurality of second connectors **1920**, **1921**, **1922**, a first fluid device **1930** (e.g., sterile liquid transfer device), a second fluid device **1940** (e.g., consumable), and a robot **1960** (e.g., robotic arm, 3DOF robot). The first connector **1910** may be coupled in fluid communication with the first fluid device **1930**, and the second connectors **1920**, **1921**, **1922** may be coupled in fluid communication with the second fluid device **1940**. The first connector **1910** and the second connectors **1920**, **1921**, **1922** may each comprise a port **1916** configured to couple to a corresponding port as described in more detail herein. The robot **1960** may comprise one or more end effectors **1962**, **1964** configured to manipulate and/or couple to one or more of the first fluid device **1930** and first connector **1910**. For example, the first connector **1910** may comprise one or more sterilization ports **1950** configured to couple to an end effector **1962** (e.g., gripper). Similarly, the first fluid device **1930** may comprise one or more fluid ports **1952** configured to couple to an end effector **1964**.

(308) In some variations, the robot **1960** may be configured to couple to one or more of a sterilant source, fluid source, and pump in order to facilitate efficient and shared fluidic connections between the fluid device, fluid connector, and a sterilization system. For example, FIG. **96A** is a plan view of a fluid device **9600** (e.g., sterile liquid transfer device) comprising a fluid port **9610** configured to couple to a fluid source (not shown) and a sterilization port **9620** configured to couple to a sterilant source (not shown). The FIGS. **96B** and **96C** are respective side and perspective views of a fluid device **9600** coupled to a robot **9650**. In some variations, the robot **9650** may comprise one or more fluid conduits **9660** configured to couple to one or more of the fluid port **9610** and sterilization port **9620** of the fluid device **9600**.

(309) In some variations, a fluid connector may comprise a third connector disposed between a first connector and a second connector. FIG. **20A** is a schematic diagram of an illustrative variation of a fluid connector system **2000** comprising a first connector **2010**, a plurality of second connectors

2020, 2021, 2022, a third connector **2070** (e.g., instrument, sterilization enclosure), a first fluid device **2030** (e.g., sterile liquid transfer device), a second fluid device **2040** (e.g., consumable), and a robot **2060** (e.g., robotic arm, 3 DOF robot, 1 DOF robot). The first connector **2010** may be coupled in fluid communication with the first fluid device **2030**, and the second connectors **2020, 2021, 2022** may be coupled in fluid communication with the second fluid device **2040**. The third connector **2070** may be coupled between the first connector **2010** and one of the second connectors **2020, 2021, 2022**. The third connector **2070** may comprise a lumen configured to receive and circulate a sterilant through one or more portions of the first connector **2010**, second connector **2020, 2021, 2022**, and third connector **2070**. In some variations, the sterilization port **2052** may be non-removably coupled to a sterilant source and/or fluid source, thereby simplifying one or more of the first fluid device **2030** and first connector **2010**.

(310) The robot **2060** may comprise one or more end effectors **2062, 2064, 2066** configured to manipulate and/or couple to one or more of the first fluid device **2030**, first connector **2010**, and third connector **2070**. For example, the first fluid device **2030** may comprise one or more fluid ports **2050** configured to couple to an end effector **2062**. Similarly, the third connector **2070** may comprise one or more sterilization ports **2052** configured to couple to robot **2060** (e.g., end effector **2064**). In some variations, the robot **2060** may be configured to couple to one or more of a sterilant source, fluid source, and pump in order to facilitate efficient and shared fluidic connections between the fluid device, fluid connector, and a sterilization system.

(311) FIGS. **20B** and **20C** are schematic diagrams of a fluid connector connection process. In FIG. **20B**, a third connector **2070** may be coupled to a distal end of a first connector **2010**, at **2002**. A distal end of the second connector **2020** may be coupled to the third connector **2070**, at **2004**. The second connector **2020** may be translated through the third connector **2070** to directly couple the second connector **2020** to the first connector **2010**, at **2006**.

(312) In FIG. **20C**, a third connector **2070** may be coupled to a distal end of the first connector **2010** and a distal end of the second connector **2020**, at **2002**. Each of the first connector **2010** and the second connector **2020** may be translated toward each other through the third connector **2070**, at **2005**. The second connector **2020** may be further translated towards the first connector **2010** to directly couple the first connector **2010** to the second connector **2010**, at **2007**. FIG. **20C** further illustrates a first port **2090** and a second port **2092** that may transition between a closed port configuration and an open port configuration.

(313) In some variations, a fluid connector may comprise a third connector disposed between a first connector and a second connector. The third connector may be coupled to a second robot different from a first robot coupled to the first connector. FIG. **21** is a block diagram of an illustrative variation of a fluid connector system **2100** comprising a first connector **2110**, a plurality of second connectors **2120, 2121, 2122**, a third connector **2170** (e.g., instrument, sterilization enclosure), a first fluid device **2130** (e.g., sterile liquid transfer device), a second fluid device **2140** (e.g., consumable), a first robot **2160**, and a second robot **2166**. The first connector **2110** may be coupled in fluid communication with the first fluid device **2130**, and the second connectors **2120, 2121, 2122** may be coupled in fluid communication with the second fluid device **2140**. The third connector **2170** may be coupled between the first connector **2110** and one of the second connectors **2120, 2121, 2122**. The third connector **2170** may comprise a lumen configured to receive and circulate a sterilant through one or more portions of the first connector **2110**, second connector **2120, 2121, 2122**, and third connector **2170**. In some variations, the third connector **2170** may be non-removably coupled to a sterilant source and/or fluid source, thereby simplifying one or more of the first fluid device **2130** and first connector **2110**.

(314) The first robot **2160** may comprise one or more end effectors **2162, 2164** configured to manipulate and/or couple to one or more of the first fluid device **2130** and first connector **2110**. For example, the first fluid device **2130** may comprise one or more fluid ports **2150** configured to couple to an end effector **2162**. The third connector **2170** may be coupled to a second robot **2166**

(e.g., 3 DOF robot). In some variations, the robot **2160**, **2166** may be configured to couple to one or more of a sterilant source, fluid source, and pump in order to facilitate efficient and shared fluidic connections between the fluid device, fluid connector, and a sterilization system.

(315) In some variations, a fluid connector may comprise a sterilant source coupled to a plurality of second connectors. FIG. **22** is a block diagram of an illustrative variation of a fluid connector system **2200** comprising a first connector **2210**, a plurality of second connectors **2220**, **2221**, **2222**, a first fluid device **2230** (e.g., sterile liquid transfer device), a second fluid device **2240** (e.g., consumable), a robot **2260**, a sterilant source **2290** comprising one or more valves, and a sterilant switch **2292**. The first connector **2210** may be coupled in fluid communication with the first fluid device **2230**, and the second connectors **2220**, **2221**, **2222** may be coupled in fluid communication with the second fluid device **2240**. The robot **2260** may comprise one or more end effectors **2262**, **2264** configured to manipulate and/or couple to one or more of the first fluid device **2230** and first connector **2210**. For example, the first fluid device **2230** may comprise one or more fluid ports **2250** configured to couple to an end effector **2262**. In some variations, the sterilant source **2290** may be coupled to the switch **2292**. The switch **2292** may be coupled to each of the second connectors **2220**, **2221**, **2222** in order to facilitate efficient and shared fluidic connections between the fluid device, fluid connector, and sterilization system. In some variations, a sterilant conduit may be routed from the switch **2292** through the second fluid device **2240** to a respective second connector **2220**, **2221**, **2222**.

(316) In some variations, a fluid device may comprise one or more sterilant valves coupled to a plurality of second connectors. FIG. **23** is a block diagram of an illustrative variation of a fluid connector system **2300** comprising a first connector **2310**, a plurality of second connectors **2320**, **2321**, **2322**, a first fluid device **2330** (e.g., sterile liquid transfer device), a second fluid device **2340** (e.g., consumable), a robot **2360**, a set of sterilant valves **2390** disposed within a housing of the second fluid device **2340**, and a sterilant switch **2392**. The first connector **2310** may be coupled in fluid communication with the first fluid device **2330**, and the second connectors **2320**, **2321**, **2322** may be coupled in fluid communication with the second fluid device **2340**. The robot **2360** may comprise one or more end effectors **2362**, **2364** configured to manipulate and/or couple to one or more of the first fluid device **2330** and first connector **2310**. For example, the first fluid device **2330** may comprise one or more fluid ports **2350** configured to couple to an end effector **2362**. In some variations, the sterilant valves **2390** may be coupled to the switch **2392**. The switch **2392** may be coupled to each of the second connectors **2320**, **2321**, **2322** via the sterilant valves **2390** in order to facilitate efficient and shared fluidic connections between the fluid device, fluid connector, and sterilization system. In some variations, a sterilant conduit may be routed from the switch **2392** through the second fluid device **2340** to a respective second connector **2320**, **2321**, **2322**.

(317) In some variations, a fluid connector may comprise a sterilant source coupled to a plurality of second connectors each having a sterilant port (e.g., sterilant valve) and a sterilant conduit through a fluid device. FIG. **24A** is a block diagram of an illustrative variation of a fluid connector system **2400** comprising a first connector **2410**, a plurality of second connectors **2420**, **2421**, **2422**, a first fluid device **2430** (e.g., sterile liquid transfer device), a second fluid device **2440** (e.g., consumable), a robot **2460**, and a sterilant switch **2492** coupled to a sterilant source (not shown). The first connector **2410** may be coupled in fluid communication with the first fluid device **2430**, and the second connectors **2420**, **2421**, **2422** may be coupled in fluid communication with the second fluid device **2440**. The robot **2460** may comprise one or more end effectors **2462**, **2464** configured to manipulate and/or couple to one or more of the first fluid device **2430** and first connector **2410**. For example, the first fluid device **2430** may comprise one or more fluid ports **2450** configured to couple to an end effector **2462**.

(318) In some variations, each of the second connectors **2420**, **2421**, **2422**, may comprise a respective sterilant port **2494**, **2496**, **2498** comprising a valve coupled to a distal end of the second

connector **2420**, **2421**, **2422**. In some variations, a sterilant conduit may be routed from the switch **2492** through the second fluid device **2440** to a respective sterilant port **2494**, **2496**, **2498**. In some variations, a sterilant source (not shown) may be coupled to the switch **2492**. The switch **2492** may be coupled to each of the second connectors **2420**, **2421**, **2422** via the sterilant ports **2494**, **2496**, **2498** in order to facilitate efficient and shared fluidic connections between the fluid device, fluid connector, and sterilization system.

(319) FIG. **24B** are schematic diagrams of a fluid connector connection process **2402**, **2404**, **2406** where a first connector **2410** is coupled to a second connector **2420**. For example, the sterilant port **2494** is in a closed valve configuration when the first connector **2410** and the second connector **2420** are separated and uncoupled **2402**. FIG. **24C** is a detailed schematic diagram of the sterilant valve **2494**. In some variations, the valve **2494** may transition to an open valve configuration when the first connector **2410** is coupled to the second connector **2420**, at **2404** and **2406**.

(320) In some variations, a plurality of second connectors may comprise one or more pneumatic sterilant valves and a sterilant path through a fluid device. FIG. **25A** is a block diagram of an illustrative variation of a fluid connector system **2500** comprising a first connector **2510**, a plurality of second connectors **2520**, **2521**, **2522**, a first fluid device **2530** (e.g., sterile liquid transfer device), a second fluid device **2540** (e.g., consumable), a robot **2560**, and a sterilant switch **2592** coupled to a sterilant source (not shown). The first connector **2510** may be coupled in fluid communication with the first fluid device **2530**, and the second connectors **2520**, **2521**, **2522** may be coupled in fluid communication with the second fluid device **2540**.

(321) In some variations, each of the second connectors **2520**, **2521**, **2522**, may comprise a respective pneumatic sterilant port **2594**, **2596**, **2598** comprising a valve coupled to a distal end of the second connector **2520**, **2521**, **2522**. In some variations, a sterilant conduit may be routed from the switch **2592** through the second fluid device **2540** to a respective sterilant port **2594**, **2596**, **2598**. In some variations, a sterilant source (not shown) may be coupled to the switch **2592**. The switch **2592** may be coupled to each of the second connectors **2520**, **2521**, **2522** via the sterilant ports **2594**, **2596**, **2598** in order to facilitate efficient and shared fluidic connections between the fluid device, fluid connector, and sterilization system.

(322) The robot **2560** may comprise one or more end effectors **2562**, **2564** configured to manipulate and/or couple to one or more of the first fluid device **2530**, first connector **2510**, and sterilant ports **2594**, **2596**, **2598**. For example, the first fluid device **2530** may comprise one or more fluid ports **2550** configured to couple to an end effector **2562**. Similarly, sterilant ports **2594**, **2596**, **2598** may be configured to couple to the end effector **2562** to pneumatically actuate the sterilant ports **2594**, **2596**, **2598**. A pneumatically actuated sterilant port may enable the sterilant conduit to be formed with a fewer number of check valves between the sterilant ports **2594**, **2596**, **2598** and switch **2592**.

(323) FIG. **25B** are schematic diagrams of a fluid connector connection process **2502** and **2504**, where a first connector **2510** is coupled to a second connector **2520**. For example, the sterilant port **2594** is in a closed valve configuration when the first connector **2510** and the second connector **2520** are separated and uncoupled **2502**. FIG. **25C** is a detailed schematic diagram of the sterilant valve **2594**. In some variations, the valve **2594** may transition to an open valve configuration when the first connector **2510** is coupled to the second connector **2520** and the valve **2594** is pneumatically actuated, at **2504**.

(324) Liquid Transfer Bus

(325) Generally, to permit transfer of one or more of a cell product (that is, solution(s) containing cell product), fluids, and reagents between the modules, the modules of the cartridge may be fluidically coupled to one another either directly or via one or more liquid transfer buses. In some variations, a liquid transfer bus may comprise a portion of the cartridge configured to control the flow and distribution of the cell product between modules and reservoirs. A liquid transfer bus may comprise one or more of a fluid manifold, fluid conduit (e.g., tubing), and one or more valves

(including but not limited to 2/2 valves, 3/2 valves, 3/3 valves, 4/2 valves, and rotary selector valves).

(326) Transfer of the cell product, reagents, or fluids within the cartridge may be achieved by any pump or other structure that generates a pressure differential between fluid in one portion of the cartridge and fluid in another portion of the cartridge. For example, the cartridge may comprise one or more pump; the cartridge may be pre-loaded with pressurized fluid contained behind a valve; the cartridge may be connected to a fluid source or a fluid sink. The cartridge may contain one or more mechanical pumps (e.g., linear pump, peristaltic pump, gear pump, screw pump, plunger pump) or portions of a pump (i.e. the pump may interface with a pump actuator). External pressure may be applied to the cartridge, to tubing within the cartridge, or to a bag within the cartridge (that is, applying pressure either to the liquid in the bag or to headspace gas of the bag). In some variations, an arrangement of the components of the cartridge may facilitate gravity-based fluid transfer within the cartridge (e.g., gravity-fed pumping). Although one advantage of the disclosed variations may be reduced operator intervention, the systems and methods of the disclosure may use manual operation in the designed workflow or as an adjunct to automated operation in case of imperfect automated system operation. For example, a process step may include manual intervention, such as fluid input or output. An operator may intervene in an automated process to correct device operation, (e.g. manually compressing a bag to flush remaining fluid into the system). Fluid may comprise liquid and/or gas, as compressed gases supplied externally or provided in pressurized chambers may be used to generate liquid flow, e.g., transfer of solution containing a cell product from one module to another.

(327) In some variations, the liquid transfer bus may be configured to deliver the cell product(s) to each of a series of modules in an order set by the design of the cartridge, or in an order determined by operation of the system by the processor or processors. Similarly stated, some variations of the cartridge may have the advantage that the order of cell processing steps as well as the process parameters for any of the cell therapy processing steps may not be set by the cartridge but rather are controlled by the controller. In some variations, the liquid transfer bus may be controlled to deliver the cell product to the modules in any of various sequences, or to bypass one or more modules (e.g., by configuring the state of the valve(s) attached to the fluidic bus). In some variations, a module may be used more than once in a method of cell processing. Optionally, the method may comprise performing one or more wash steps. For example, a counterflow centrifugal elutriation (CCE) module may be used more than once. In an illustrative method, the method comprises culturing the cell product in a first bioreactor module, transferring the cell product to the CCE module to enrich for a desired cell type, transferring the cell product to a second bioreactor module for a second culturing step, washing the CCE module using a wash solution, and transferring the cell product to the CCE module for a second enrichment step.

(328) In some variations, the liquid transfer bus or the liquid transfer buses may be fluidically coupled to multiple bags or reservoirs used to provide solutions or reagents, store cell products, or to collect waste solutions or reagents.

(329) In some variations, the cartridge may comprise one or more pumps, which may be fluidically coupled to the liquid transfer bus and/or one or more modules. The pump(s) may include a motor operatively coupled to control circuits and a power source (e.g. a battery or electrical connectors for an off-cartridge power source). In some variations, the pump may be divided into a pump on the cartridge and pump actuators on one or more instruments of the system. The pump may be an opening in the cartridge with tubing arranged around the circumference of the opening and configured to receive a pump actuator (e.g., a peristaltic rotor). By dividing components of the pump that contact the cell product (i.e. tubing) from components of the pump that perform operations of the cell product, (i.e. the pump actuator, e.g., peristaltic rotor), the cartridge may be compact and simplified. For example, FIG. 26A and FIG. 26B illustrate a pump head **2610** and a pump **2610** of a cartridge in an uncoupled configuration (FIG. 13A) and a coupled configuration.

(330) In some variations, one or more pumps **146** (e.g., fluid pump) may generate a predetermined fluid flow rate to circulate a sterilant and/or fluid. In some variations, a pump may comprise one or more of a positive displacement pump (e.g., peristaltic pump, diaphragm pump, syringe pump), centrifugal pump, combinations thereof, and the like. One or more fluid sources may be coupled to the pump.

(331) In some variations, the pump may be configured to receive a pump signal (generated by a controller) configured to circulate a sterilant for a dwell time sufficient to sterilize at least a portion of a fluid connector. For example, the pump may be configured to circulate the sterilant for at least 10 seconds. In some variations, the pump may be configured to receive a pump signal configured to circulate a non-sterilant gas (e.g., inert gas, air) to remove the sterilant.

(332) In some variations, a discontinuous flow pump (e.g., peristaltic pump) may generate pulsatile flow as, for example, a tube contracts and relaxes between rollers. In some variations, closed loop feedback from a flow sensor may be used to compensate for pulsatile flow to generate a substantially continuous flow rate. For example, a flow sensor may be coupled to a fluid conduit to measure the flow rate. A controller may receive the measured flow rate and generate a pump signal to the pump based on a proportional correction function configured to reduce the “ripples” measured by the flow sensor. Additionally or alternatively, a controller may apply periodic error correction to a pump signal to reduce periodic error that may be unique to each pump. For example, a flow sensor may measure and determine a periodic error of a pump. A pump signal comprising the periodic error correction may correspond to a waveform comprising an inverse shape of the error. The resulting pump flow may correct for fluctuations in flow rate.

(333) Controller

(334) In some variations, a system **100** may comprise a controller **120** (e.g., computing device) comprising one or more of a processor **122**, memory **124**, communication device, **126**, input device **128**, and display **130**. The controller **120** may be configured to control (e.g., operate) the workcell **110**. The controller **120** may comprise a plurality of devices. For example, the workcell **110** may enclose one or more components of the controller **120** (e.g., processor **122**, memory **124**, communication device **126**) while one or more components of the controller **120** may be provided remotely to the workcell **110** (e.g., input device **128**, display **130**).

(335) Processor

(336) The processor (e.g., processor **122**) described here may process data and/or other signals to control one or more components of the system (e.g., workcell **110**, controller **120**). The processor may be configured to receive, process, compile, compute, store, access, read, write, and/or transmit data and/or other signals. Additionally, or alternatively, the processor may be configured to control one or more components of a device and/or one or more components of controller (e.g., console, touchscreen, personal computer, laptop, tablet, server).

(337) In some variations, the processor may be configured to access or receive data and/or other signals from one or more of workcell **110**, server, controller **120**, and a storage medium (e.g., memory, flash drive, memory card, database). In some variations, the processor may be any suitable processing device configured to run and/or execute a set of instructions or code and may include one or more data processors, image processors, graphics processing units (GPU), physics processing units, digital signal processors (DSP), analog signal processors, mixed-signal processors, machine learning processors, deep learning processors, finite state machines (FSM), compression processors (e.g., data compression to reduce data rate and/or memory requirements), encryption processors (e.g., for secure wireless data transfer), and/or central processing units (CPU). The processor may be, for example, a general purpose processor, Field Programmable Gate Array (FPGA), an Application Specific Integrated Circuit (ASIC), a processor board, and/or the like. The processor may be configured to run and/or execute application processes and/or other modules, processes and/or functions associated with the system. The underlying device technologies may be provided in a variety of component types (e.g., metal-oxide semiconductor

field-effect transistor (MOSFET) technologies like complementary metal-oxide semiconductor (CMOS), bipolar technologies like emitter-coupled logic (ECL), polymer technologies (e.g., silicon-conjugated polymer and metal-conjugated polymer-metal structures), mixed analog and digital, and the like.

(338) The systems, devices, and/or methods described herein may be performed by software (executed on hardware), hardware, or a combination thereof. Hardware modules may include, for example, a general-purpose processor (or microprocessor or microcontroller), a field programmable gate array (FPGA), and/or an application specific integrated circuit (ASIC). Software modules (executed on hardware) may be expressed in a variety of software languages (e.g., computer code), including structured text, typescript, C, C++, C#, Java®, Python, Ruby, Visual Basic®, and/or other object-oriented, procedural, or other programming language and development tools. Examples of computer code include, but are not limited to, micro-code or micro-instructions, machine instructions, such as produced by a compiler, code used to produce a web service, and files containing higher-level instructions that are executed by a computer using an interpreter. Additional examples of computer code include, but are not limited to, control signals, encrypted code, and compressed code

(339) Memory

(340) The cell processing systems and devices described here may include a memory (e.g., memory **124**) configured to store data and/or information. In some variations, the memory may include one or more of a random access memory (RAM), static RAM (SRAM), dynamic RAM (DRAM), a memory buffer, an erasable programmable read-only memory (EPROM), an electrically erasable read-only memory (EEPROM), a read-only memory (ROM), flash memory, volatile memory, non-volatile memory, combinations thereof, and the like. In some variations, the memory may store instructions to cause the processor to execute modules, processes, and/or functions associated with the device, such as image processing, image display, sensor data, data and/or signal transmission, data and/or signal reception, and/or communication. Some variations described herein may relate to a computer storage product with a non-transitory computer-readable medium (also may be referred to as a non-transitory processor-readable medium) having instructions or computer code thereon for performing various computer-implemented operations. The computer-readable medium (or processor-readable medium) is non-transitory in the sense that it does not include transitory propagating signals per se (e.g., a propagating electromagnetic wave carrying information on a transmission medium such as space or a cable). The computer code (also may be referred to as code or algorithm) may be those designed and constructed for the specific purpose or purposes. In some variations, the memory may be configured to store any received data and/or data generated by the controller and/or workcell. In some variations, the memory may be configured to store data temporarily or permanently

(341) Input Device

(342) In some variations, the display may include and/or be operatively coupled to an input device **128** (e.g., touch screen) configured to receive input data from a user. For example, user input to an input device **128** (e.g., keyboard, buttons, touch screen) may be received and processed by a processor (e.g., processor **122**) and memory (e.g., memory **124**) of the system **100**. The input device may include at least one switch configured to generate a user input. For example, an input device may include a touch surface for a user to provide input (e.g., finger contact to the touch surface) corresponding to a user input. An input device including a touch surface may be configured to detect contact and movement on the touch surface using any of a plurality of touch sensitivity technologies including capacitive, resistive, infrared, optical imaging, dispersive signal, acoustic pulse recognition, and surface acoustic wave technologies. In variations of an input device including at least one switch, a switch may have, for example, at least one of a button (e.g., hard key, soft key), touch surface, keyboard, analog stick (e.g., joystick), directional pad, mouse, trackball, jog dial, step switch, rocker switch, pointer device (e.g., stylus), motion sensor, image

sensor, and microphone. A motion sensor may receive user movement data from an optical sensor and classify a user gesture as a user input. A microphone may receive audio data and recognize a user voice as a user input.

(343) In some variations, the cell processing system may optionally include one more output devices in addition to the display, such as, for example, an audio device and haptic device. An audio device may audibly output any system data, alarms, and/or notifications. For example, the audio device may output an audible alarm when a malfunction is detected. In some variations, an audio device may include at least one of a speaker, piezoelectric audio device, magnetostrictive speaker, and/or digital speaker. In some variations, a user may communicate with other users using the audio device and a communication channel. For example, a user may form an audio communication channel (e.g., VoIP call).

(344) Additionally or alternatively, the system may include a haptic device configured to provide additional sensory output (e.g., force feedback) to the user. For example, a haptic device may generate a tactile response (e.g., vibration) to confirm user input to an input device (e.g., touch surface). As another example, haptic feedback may notify that user input is overridden by the processor.

(345) Communication Device

(346) In some variations, the controller may include a communication device (e.g., communication device **126**) configured to communicate with another controller and one or more databases. The communication device may be configured to connect the controller to another system (e.g., Internet, remote server, database, workcell) by wired or wireless connection. In some variations, the system may be in communication with other devices via one or more wired and/or wireless networks. In some variations, the communication device may include a radiofrequency receiver, transmitter, and/or optical (e.g., infrared) receiver and transmitter configured to communicate with one or more devices and/or networks. The communication device may communicate by wires and/or wirelessly.

(347) The communication device may include RF circuitry configured to receive and send RF signals. The RF circuitry may convert electrical signals to/from electromagnetic signals and communicate with communications networks and other communications devices via the electromagnetic signals. The RF circuitry may include well-known circuitry for performing these functions, including but not limited to an antenna system, an RF transceiver, one or more amplifiers, a tuner, one or more oscillators, a digital signal processor, a CODEC chipset, a subscriber identity module (SIM) card, memory, and so forth.

(348) Wireless communication through any of the devices may use any of plurality of communication standards, protocols and technologies, including but not limited to, Global System for Mobile Communications (GSM), Enhanced Data GSM Environment (EDGE), high-speed downlink packet access (HSDPA), high-speed uplink packet access (HSUPA), Evolution, Data-Only (EV-DO), HSPA, HSPA+, Dual-Cell HSPA (DC-HSPDA), long term evolution (LTE), near field communication (NFC), wideband code division multiple access (W-CDMA), code division multiple access (CDMA), time division multiple access (TDMA), Bluetooth, Wireless Fidelity (WiFi) (e.g., IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, and the like), voice over Internet Protocol (VOIP), Wi-MAX, a protocol for e-mail (e.g., Internet message access protocol (IMAP) and/or post office protocol (POP)), instant messaging (e.g., extensible messaging and presence protocol (XMPP), Session Initiation Protocol for Instant Messaging and Presence Leveraging Extensions (SIMPLE), Instant Messaging and Presence Service (IMPS)), and/or Short Message Service (SMS), EtherCAT, OPC Unified Architecture, or any other suitable communication protocol. In some variations, the devices herein may directly communicate with each other without transmitting data through a network (e.g., through NFC, Bluetooth, WiFi, RFID, and the like).

(349) In some variations, the systems, devices, and methods described herein may be in

communication with other wireless devices via, for example, one or more networks, each of which may be any type of network (e.g., wired network, wireless network). The communication may or may not be encrypted. A wireless network may refer to any type of digital network that is not connected by cables of any kind. Examples of wireless communication in a wireless network include, but are not limited to cellular, radio, satellite, and microwave communication. However, a wireless network may connect to a wired network in order to interface with the Internet, other carrier voice and data networks, business networks, and personal networks. A wired network is typically carried over copper twisted pair, coaxial cable and/or fiber optic cables. There are many different types of wired networks including wide area networks (WAN), metropolitan area networks (MAN), local area networks (LAN), Internet area networks (IAN), campus area networks (CAN), global area networks (GAN), like the Internet, and virtual private networks (VPN). Hereinafter, network refers to any combination of wireless, wired, public and private data networks that are typically interconnected through the Internet, to provide a unified networking and information access system.

(350) Cellular communication may encompass technologies such as GSM, PCS, CDMA or GPRS, W-CDMA, EDGE or CDMA2000, LTE, WiMAX, and 5G networking standards. Some wireless network deployments combine networks from multiple cellular networks or use a mix of cellular, Wi-Fi, and satellite communication.

(351) Display

(352) Image data may be output on a display e.g., display **130**) of a cell processing system. In some variations, a display may include at least one of a light emitting diode (LED), liquid crystal display (LCD), electroluminescent display (ELD), plasma display panel (PDP), thin film transistor (TFT), organic light emitting diodes (OLED), electronic paper/e-ink display, laser display, and/or holographic display.

II. Methods

(353) Generally, the systems and devices described herein may perform one or more cell processing steps to manufacture a cell product. FIG. **28** is a flowchart of a method of cell processing **2800**. The method **2800** may include enriching a selected population of cells in a solution (e.g., fluid) **2802**. For example, the solution may be conveyed to a CCE module of a cartridge via a liquid transfer bus. A robot may be operated to move the cartridge to a CCE instrument so that the CCE module interfaces with the CCE instrument. The CCE instrument may be operated to cause the CCE module to enrich the selected population of cells. Additionally or alternatively, the cell product may be introduced into and out of the cartridge via a sterile liquid transfer port (either manually or automatically) for any of the steps described herein. In some variations, the cartridge may be sterilized in a feedthrough port (either manually or automatically).

(354) In some variations, a selected population of cells in the solution may be washed **2804**. For example, the solution may be conveyed to the CCE module of the cartridge via the liquid transfer bus. A robot may be operated to move the cartridge to the CCE instrument so that the CCE module interfaces with the CCE instrument. The CCE instrument may be operated to cause the CCE module to remove media from the solution, introduce media into the solution, and/or replace media in the solution.

(355) In some variations, a population of cells in the solution may be selected **2806**. For example, the solution may be conveyed to a selection module of the cartridge via the liquid transfer bus. The robot may be operated to move the cartridge to a selection instrument so that the selection module interfaces with the selection instrument. The selection instrument may be operated to cause the selection module to select the selected population of cells.

(356) In some variations, a population of cells in the solution may be sorted **2808**. For example, the solution may be conveyed to a sorting module of the cartridge via the liquid transfer bus. The robot may be operated to move the cartridge to a sorting instrument so that the sorting module interfaces with the sorting instrument. The sorting instrument may be operated to cause the sorting module to

sort the population of cells.

(357) In some variations, the solution may be conveyed to a bioreactor module of the cartridge via the liquid transfer bus to rest **2810**. For example, the robot may be operated to move the cartridge to a bioreactor instrument so that a bioreactor module interfaces with the bioreactor instrument. The bioreactor instrument may be operated to cause the bioreactor module to maintain the cells at a set of predetermined conditions.

(358) In some variations, the cells may be expanded in the solution **2812**. For example, the solution may be conveyed to the bioreactor module of the cartridge via the liquid transfer bus. The robot may be operated to move the cartridge to the bioreactor instrument so that the bioreactor module interfaces with the bioreactor instrument. The bioreactor instrument may be operated to cause the bioreactor module to expand the cells by cellular replication.

(359) In some variations, tissue may be digested by conveying an enzyme reagent via the liquid transfer bus to a module containing a solution containing a tissue such that the tissue releases a select cell population into the solution **2814**.

(360) In some variations, a selected population of cells in the solution may be activated by conveying an activating reagent via the liquid transfer bus to a module containing the solution containing the cell product **2816**.

(361) In some variations, the solution may be conveyed to an electroporation module of the cartridge via the liquid transfer bus and receive an electroporation signal to electroporate the cells in the solution **2818**. For example, the robot may be operated to move the cartridge to an electroporation instrument so that the electroporation module interfaces with the electroporation instrument. The electroporation instrument may be operated to cause the electroporation module to electroporate the selected population of cells in the presence of genetic material.

(362) In some variations, an effective amount of a vector may be conveyed via the liquid transfer bus to a module containing the solution containing the cell product, thereby transducing a selected population of cells in the solution **2820**.

(363) In some variations, a formulation solution may be conveyed via the liquid transfer bus to a module containing the cell product to generate a finished cell product **2822**. For example, the finished cell product may be conveyed to one or more product collection bags. In some variations, finishing a cell product may comprise one or more steps of washing cells, concentrating cells, exchanging a buffer of the cells with a formulation buffer, and dosing cells in the formulation buffer in predetermined quantities into one or more product collection bags and/or vessels.

(364) In some variations, the cell product may be removed, either manually or automatically, from the cartridge to harvest the cells **2824**.

(365) In some variations, the cell product may comprise one or more of an immune cell genetically engineered chimeric antigen receptor T cell, a genetically engineered T cell receptor (TCR) cell, a hematopoietic stem cell (HSC), and a tumor infiltrating lymphocyte (TIL). In some variations, the immune cell may comprise a natural-killer (NK) cell.

(366) Methods of cell processing may include a subset of cell processing steps in any suitable order. For example, the method of cell processing may include, in order, the enrichment step **2802**, the selection step **2806**, the activation step **2816**, the transduction step **2820**, the expansion step **2812**, and the harvesting step **2824**. In some variations, the method of cell processing may include, in order, the enrichment step **2802**, the selection step **2806**, the resting step **2810**, the transduction step **2820**, and the harvesting step **2824**. In some variations, the method of cell processing may include, in order, the tissue-digestion step **2820**, the washing step **2804**, the activation step **2816**, the expansion step **2812**, and the harvesting step **2824**.

(367) Generally, the methods described herein may offload the complex steps performed in cell processing operation to a set of instruments, thereby reducing the cost of the cartridge (which may be a consumable). In some variations, the cartridge may contain the cell product (e.g., solution containing cells) throughout a manufacturing process, with different instruments interfacing with

the cartridge at appropriate times to perform one or more cell processing steps. For example, a cell processing step may comprise conveying cells and reagents to each of the modules within the cartridge. A set of instruments interfacing with a cartridge facilitates process flexibility where a workcell may be customized with a predetermined set of instruments for a predetermined cell therapy product. For example, the order of cell processing steps may be customized for each cell product as described in more detail herein with respect to FIGS. 35-55.

(368) In some variations, a cell product may be retained within the cartridge throughout a manufacturing process (e.g., workflow). Additionally or alternatively, the cell product may be removed from the cartridge for one or more cell processing steps, either manually by an operator, or automatically through a fluid connector (e.g., SLTP) or other access ports on the cartridge. The cell product may then be returned to the same cartridge, transferred to another cartridge, or split among several cartridges. In some variations, one or more cell processing steps may be performed outside the cartridge. In some variations, processing within the workcell may facilitate sterile cell processing within the cartridge.

(369) FIG. 29 is a flowchart of a method of cell processing and illustrates cell processing steps performed on a cartridge (e.g., consumable) within a workcell including a CCE instrument module, a sterile liquid transfer (SLT) instrument module, and a bioreactor instrument module. The consumable may be configured to interface with any of the CCE instrument module, SLT instrument module, and bioreactor instrument module to perform one or more cell processing steps. For example, a robot (or operator) may be configured to move a cartridge between any of the modules of the workcell. A pump head in an instrument may engage the consumable cartridge in order to convey fluids between the modules of the cartridge, into or out of various reservoirs in the cartridge, and/or through ports that permit reagents to be added or removed from the cartridge.

(370) In some variations, the CCE instrument module may comprise a pump and centrifuge configured to interface with a cartridge (e.g., consumable). The SLT instrument module may comprise one or more fluid connectors be configured to interface with one or more of a bag and bioreactor of a cartridge. The bioreactor instrument module may comprise one or more sensors, temperature regulators, pumps, agitators, and the like, and be configured to interface with the cartridge. In some variations, the cell product may be contained within the cartridge throughout cell processing.

(371) A method of cell processing depicted in FIG. 29 may include moving a fluid (e.g., cells in solution) in a product bag to a CCE module (e.g., rotor) of a cartridge (e.g., consumable) using a pump 2910. In some variations, the fluid may be enriched using the CCE module 2912. For example, blood constituents may be collected in a waste bag 2913. In some variations, the fluid may be washed using the CCE module 2914. For example, buffer may be collected in a waste bag 2915. In some variations, media may be exchanged using the CCE module 2916. For example, one or more of buffer (e.g., formulation buffer) and media may be collected in a waste bag 2917. In some variations, fluid may be moved to a bioreactor of the cartridge 2918.

(372) In some variations, a fluid connector may fill a bag with a reagent 2920. In some variations, a reagent (e.g., bead, vector) may be added to a bioreactor of a cartridge 2922. In some variations, a fluid connector removes waste from a bag 2924. In some variations, a fluid connector may optionally remove a sample from a bioreactor.

(373) In some variations, cells may be moved to a bioreactor 2930. In some variations, the cells may undergo activation or genetic modification 2932. In some variations, the cells may undergo incubation 2934. In some variations, the cells may undergo perfusion using a pump 2936. For example, spent media may be collected in a waste bag 2937. In some variations, cells may undergo expansion 2938. In some variations, cells may be harvested after media exchange 2940.

(374) FIG. 30A is a flowchart of a method of cell processing for autologous CAR T cells or engineered TCR cells. The method 3000 may comprise the steps of enrichment, selection, activation, genetic modification, expansion, harvest/formulation, and cryopreservation. FIG. 30B is

a flowchart of a method of cell processing for allogeneic CAR T cells or engineered TCR cells. The method **3010** may comprise the steps of enrichment, activation, genetic modification (e.g., transduction, transfection), alpha/beta T cell depletion, expansion, harvest/pool/formulation, and cryopreservation.

(375) FIG. **31** is a flowchart of a method of cell processing for hematopoietic stem cell (HSC) cells. The method **3100** may comprise the steps of enrichment, selection, rest, genetic modification, harvest/formulation, and cryopreservation.

(376) FIG. **32** is a flowchart of a method of cell processing for tumor infiltrating lymphocyte (TIL) cells. The method **3200** may comprise the steps of tissue digestion, washing, selection, activation, expansion, harvest/formulation, and cryopreservation.

(377) FIG. **33** is a flowchart of a method of cell processing for natural killing (NK) CAR cells. The method **3300** may comprise the steps of enrichment, selection, activation, genetic modification, expansion, harvest/formulation, and cryopreservation.

(378) FIGS. **34A-34C** are flowcharts of methods of cell processing for regulatory T (Treg) cells. The method **3400** may comprise the steps of enrichment, selection, harvest/formulation, cryopreservation. The method **3402** may comprise the steps of enrichment, selection, activation, genetic modification, expansion, selection (optionally), harvest/formulation, and cryopreservation. The method **3404** may comprise the steps of introducing feeder cell culture for enrichment, selection, activation/expansion, and harvest/irradiation. Another set of cells may undergo enrichment, selection, co-culture with the processed feeder cells, harvest, and cryopreservation.

(379) FIGS. **98-101** are flowcharts of methods of cell processing for cell therapy workflows comprising split (e.g., parallel) processing. The method **9800** may comprise the steps of enrichment, selection, activation, genetic modification, expansion, formulation, and cryopreservation. For example, a cell processing method **9800** (e.g., workflow) may comprise splitting a cell product into two or more portions after an enrichment step. The split portions may be processed in parallel within a single cartridge. In some variations, one or more split portions may be transferred to two or more cartridges and processed in parallel. One or more cell processing parameters (e.g., timing of process steps, types of reagents added, transfection constructs, and the like) may be configured independently for each split portion of the cell product. In some variations, the split portions may be pooled after the expansion step.

(380) The method **9900** may comprise the steps of enrichment, selection, activation, genetic modification, expansion, formulation, and cryopreservation. For example, a cell processing method **9900** (e.g., workflow) may comprise splitting a cell product into two or more portions after an activation step. The split portions may be processed in parallel within a single cartridge. In some variations, one or more split portions may be transferred to two or more cartridges and processed in parallel. One or more cell processing parameters (e.g., timing of process steps, types of reagents added, transfection constructs, and the like) may be configured independently for each split portion of the cell product. In some variations, the split portions may be pooled after the expansion step and/or the genetic modification step.

(381) The method **10000** may comprise the steps of enrichment, selection, activation, genetic modification, expansion, formulation, and cryopreservation. For example, a cell processing method **10000** (e.g., workflow) may comprise splitting a cell product into two or more portions after a selection step. The split portions may be processed in parallel within a single cartridge. In some variations, one or more split portions may be transferred to two or more cartridges and processed in parallel. One or more cell processing parameters (e.g., timing of process steps, types of reagents added, transfection constructs, and the like) may be configured independently for each split portion of the cell product. In some variations, the split portions may not be pooled.

(382) The method **10100** may comprise the steps of enrichment, selection, activation, genetic modification, expansion, formulation, and cryopreservation. For example, a cell processing method **10100** (e.g., workflow) may comprise splitting a cell product into two or more portions as starting

materials. The separate products may remain segregated and processed in parallel as split portions within a single cartridge or a plurality of cartridges. One or more cell processing parameters (e.g., timing of process steps, types of reagents added, transfection constructs, and the like) may be configured independently for each split portion. In some variations, the split portions may be pooled after the expansion step.

(383) FIG. **102** is a schematic diagram of a cell processing system **10200** configured for split processing within a single cartridge. For example, the methods **9800-10100** described with respect to FIGS. **98-101** may be performed within the cartridge **10210**. In some variations, the system **10200** may comprise a sterile liquid transfer device **10220** comprising a reagent **10222**, and a cartridge **10210** comprising a plurality of bioreactor modules **10230**, a pump module **10240**, a thermal module **10245**, a pressure driven flow module **10250**, a MACS module **10255**, an electroporation module **10260**, a FACS module **10265**, a CCE module **10270**, and a blank module **10280**. The cartridge **10210** may further comprise a reagent storage **10285**, a plurality of product bags **10290**, and a liquid transfer bus **10295**. The liquid transfer bus **10295** may be configured to couple the components of the cartridge **10210** for fluid communication.

(384) In some variations, loading and removing of cell product into and out of the cartridge may be performed in the system or outside the system. In some variations, the cartridge is loaded bedside to the patient or donor and then delivered to a cell processing system in or near the hospital, or shipped to a facility where the cell processing system is installed. Likewise, the cell product may be removed from the cartridge after processing either at a facility or closer to the intended recipient of the cell product (the patient). Optionally the cell product is frozen before, during, or after the methods of the disclosure—optionally after addition of one or more cryoprotectants to the cell product. In some variations, the system comprises a freezer and/or a liquid nitrogen source. In some variations, the system comprises a water bath or a warming chamber containing gas of controlled temperature to permit controlled thawing of the cell product, e.g. a water bath set to between about 20° C. and about 40° C. In some variations, the cartridge is made of materials that resistant mechanical damage when frozen.

(385) Automated Cell Processing

(386) Described here are methods of transforming user-defined cell processing operations into cell processing steps using the automated cell processing systems and devices described herein. In some variations, cell processing operations are received and transformed into cell processing steps to be performed by the system given a set of predetermined constraints. For example, a user may input a set of biologic process steps and corresponding biologic process parameters to be executed by a cell processing system. Optionally, process parameters may be customized for each cartridge or sets of cartridges.

(387) FIG. **35** is a flowchart that generally describes a variation of a method of automated cell processing. The method **3500** may include receiving an ordered input list of cell processing operations **3502**. For example, a set of more than one ordered input list of cell processing operations may be received to be performed on more than one cartridge on an automated cell processing system. For example, as shown in the GUI **4900** of FIG. **49** and described in more detail herein, one or more biologic process inputs (e.g., available operations) such as enrichment, MACS selection, activation, transduction, transfection, expansion, and inline analysis may be selected as an ordered input list of cell processing operations. Furthermore, GUI **5200** of FIG. **52** illustrates a complete ordered input list of cell processing operations (e.g., set of selected operations) **5220** selected by a user.

(388) In some variations, one or more sets of cell processing parameters may be received **3504**. Each set of cell processing parameters may be associated with one of the cell processing operations. Each set of cell processing parameters may specify characteristics of the cell processing step to be performed by the instrument at that cell processing step. For example, the GUI **4000** of FIG. **40** illustrates reagent and container parameters, the GUI **4200** of FIG. **42** illustrates an

example of a process parameter, the GUI **4400** of FIG. **44** illustrates an example of a preprocess analytic, and the GUI **4800** of FIG. **48** illustrates an example of a set of activation settings.

(389) In some variations, a transformation model may be executed on the ordered input list **3506**. In some variations, the transformation model may comprise constraints on the ordered output list determined by a predetermined configuration of the automated cell processing system. For example, the constraints may comprise information on the configuration of the automated cell processing system.

(390) In some variations, the constraints may comprise one or more of a type and/or number and/or state of instruments, a type and/or number and/or state of modules on the cartridge, a type and/or number of reservoirs on the cartridge, a type and/or number of sterile liquid transfer ports on the cartridge, and number and position of fluid paths between the modules, reservoirs, and sterile liquid transfer ports on the cartridge.

(391) In some variations, a set of predetermined constraints may be placed on a set of the process control parameters. For example, the volume and/or the type of reagents used may be constrained based on the size of the system and/or products manufactured. Other process parameter constraints may include, but is not limited to, one or more of temperature, volume, time, pH, cell size, cell number, cell density, cell viability, dissolved oxygen, glucose levels, volumes of onboard reagent storage and waste, combinations thereof, and the like. For example, the GUI **4000** of FIG. **40** depicts that a reagent has a volume per unit of 30 ml and a required volume of 54 ml, and a consumable container has a volume per unit of 75 ml. The GUI **4800** of FIG. **48** depicts that an activation concentration is 12 mg/L, an activation culture time is 1600 seconds, activation temperature is 18° C., and a gas mix includes 21% oxygen, 78.06% nitrogen, and 0.04% of carbon dioxide. These constraints may be applied by a transformation model to generate an ordered output list of cell processing steps that affect how one or more of the robot, instrument, and cartridge are operated and the cell product manufactured.

(392) In some variations, the order of operations may be constrained based on hardware constraints. For example, the robot may be limited to moving one cartridge at a time. Similarly, an instrument may be constrained to operating on a predetermined number of cartridges at once.

(393) In some variations, as illustrated in the GUI **4900** of FIG. **49**, a load product operation must be the first operation performed, and may be performed once for each process. A fill and finish operation may always be the last operation performed before product completion, and may be performed once for each process.

(394) In some variation, the system may prevent the user from executing a set of operations in an order that cannot be performed by the system.

(395) In some variations, a notification (e.g., warning, alert) may be output if a user orders a set of operations in a “non-standard” manner. For example, a notification may be output if the same type of operation is repeated sequentially (e.g., enrichment immediately followed by enrichment). Similarly, a notification may be output if an operation (e.g., selection, activation) is used two times or more within a given process when such an operation is typically used just once in a given process.

(396) In some variations, an output of the transformation model may correspond to an ordered output list of cell processing steps capable of being performed by the system **3508**. For example, the transformation model may be executed on the sets of ordered input lists to create the ordered output list of cell processing steps. The output list of cell processing steps may control a robot, cartridge, and one or more instruments.

(397) In some variations, the ordered output list is performed by the system to control a robot to move one or more cartridges each containing a cell product between the instruments **3510**. For example, the MACS selection process selected by the user may correspond to the robot **230** of FIG. **2** moving the cartridge **250** to the cell selection instrument **216** from, for example, another instrument. In some variations, the ordered output list may comprise instructions for a robot to load

a cartridge (e.g., single use consumable) into the cell processing system (e.g., workcell). Furthermore, the robot may be configured to move the cartridge to a first instrument position.

(398) In some variations, the ordered output list is further performed by the system to control one or more of the instruments to perform one or more cell processing steps on one or more cell products **3512** of a respective cartridge. For example, the compute server rack **210** (e.g., controller **120**) may be configured to control an electroporation module **220** configured to apply a pulsed electric field to a cell suspension of a cartridge **250**. In some variations, the ordered output list may comprise instructions for an instrument (e.g., bioreactor) to process the product (e.g., transfer the cell product from a small bioreactor module to a large bioreactor module). Furthermore, the instrument may be further configured to operate under a set of process parameters (e.g., 9 hour duration, pH of 6.7, temperature between 37.3° C. and 37.8° C., mixing mode 3). As another example, the ordered output list may comprise instructions to operate a sterile liquid transfer module to perform one or more of removing waste from a cartridge, adding media to the cartridge, and adding a MACS reagent to the cartridge.

(399) In some variations, one or more electronic batch records may be generated **3514** based on the process parameters and data collected from sensors during process execution. Batch records generated by the system may include process parameters, time logging, sensor measurements from the instruments, QC parameters determined by QC instrumentation, and other records.

(400) FIG. **36** is a flowchart that generally describes a variation of a method of executing a transformation model **3600**. In some variations, one or more biological functions may be generated and output to a user. For example, a set of configurable biological function blocks may be displayed on a graphical user interface for user selection. The GUI may enable a user to select and order the biological function blocks and define biological control parameters. One or more control parameters of the biologic function blocks may be modified by a user if desired. In some variations, one or more biologic function templates may be generated comprising a predefined sequence of biological function blocks. One or more biological control parameters of the biologic function templates may be modified by a user if desired.

(401) In some variations, a cell processing system may be configured to receive and/or store one or more biologic function (e.g., process) inputs from the user **3604**. For example, a user may select one or more predefined biological function templates.

(402) In some variations, a biologic process model (e.g., process definition) may be generated based on the biologic process inputs **3606**. In some variations, a biologic process model may include one or more of enrichment, isolation, MACS selection, FACS selection, activation, genetic modification, gene transfer, transduction, transfection, expansion, formulation (e.g., harvest, pool), cryopreservation, T cell depletion, rest, tissue digestion, washing, irradiation, co-culture, combinations thereof, and the like.

(403) In some variations, the biologic process model may be transformed into an instrument execution process model **3608**. For example, each biological function block in the biological process model may correspond to an ordered list of cell processing system operations with corresponding hardware control parameters. The instrument execution process model may comprise the sequence of hardware operations corresponding to the biologic process model. As described herein, the transformation model may comprise one or more constraints.

(404) Optionally, in some variations, a cell processing system may be configured to receive and/or store one or more instrument execution process inputs from the user **3610**. For example, a user may modify the transformed instrument execution process model if desired. The user may select specific hardware components to perform certain steps, modify timing parameters, and the like.

(405) In some variations, the instrument execution process may be executed to generate the cell product **3612**. For example, the cell processing system at run-time may process the cell product through the system as defined by the instrument execution process model.

(406) In some variations, an instrument execution process may be executed **3612**. In some

variations, an instrument execution process model may be transformed back into a biologic process model **3614**. This progress of the biologic process model may be output (e.g., displayed) to a user for monitoring. For example, the instrument execution process model may comprise one or more references (e.g., pointers) back to the biological process model so that run-time execution progress may be reported against the biological process model.

(407) In some variations, a cell product may be monitored **3616**. For example, the GUIs **5300** and **5400** of respective FIGS. **53** and **54** illustrate sensor data monitored by the system for a plurality of products. For example, a number of viable cells and a status of a process (e.g., as a function of percentage completion) may be graphically illustrated for a user.

(408) In some variations, an electronic record may be generated based on the monitored data **3618**. For example, one or more electronic batch records may be generated in compliance with, for example, 21 CFR regulations.

(409) FIG. **55** is a block diagram of an illustrative variation of a manufacturing workflow **5500** comprising a processing platform **5520** (e.g., system **100**, workcell **110**, **200**, **201**) configured to generate a plurality of cell products (e.g., first product, second product, third product) in parallel. For example, a first workflow **5510** for a first product may include a plurality of biologic processes **5512** executed in a predetermined sequence using corresponding elements **5522** (e.g., hardware) of the platform **5520**. Simultaneously, a second workflow **5530** for a second product may execute a predetermined sequence of biologic processes **5530** using corresponding elements **5524** of the platform **5520**. In this manner, hardware resources of the platform **5520** may be efficiently utilized to increase throughput. In some variations, about 2, 3, 4, 5, 6, 7, 8, 9, 10, or more cell products may be manufactured simultaneously on the platform **5520**. The transformation model may include hardware constraints that eliminate scheduling conflicts to ensure that, for example, the same instrument is not used for different products at the same time.

(410) Graphical User Interface

(411) In some variations, a graphical user interface (GUI) may be configured for designing a process and monitoring a product. FIG. **37** is a variation of a GUI **3700** comprising an initial process design interface. For example, GUI **3700** may be a process design home page. The GUI **3700** may indicate that no processes have been selected or loaded. A create icon **3710** (e.g., “Create a Process”) may be selectable for a user to begin a process design process. In some variations, one or more of the GUIs described herein may include a search bar.

(412) FIG. **38** is a variation of a GUI **3800** relating to creating a process. GUI **3800** may be displayed following selection of the create icon **3710** in FIG. **37**. For example, GUI **3800** may comprise a process creation window **3810** allowing a user to input and/or select one or more of a process name, process description, and template. In some variations, a user may select from a list of predetermined templates. For example, a user may create a process and save it as a template for later selection.

(413) FIG. **39** is a variation of a GUI **3900** comprising relating to an empty process. GUI **3900** may be displayed following confirmation in GUI **3800** that a process is to be created. GUI **3900** may indicate the process name (e.g., Car T Therapy) and may highlight Process Setup icon **3910** and allow process specific parameters to be added such as process reagents and containers, process parameters, and preprocess analytics. GUI **3900** may further comprise an Add Process Reagents and Containers icon **3920**, Add Process Parameters icon **3930**, and Add Preprocess Analytics icon **3940**. Once process setup is completed, one or more process elements may be specified.

(414) In some variations, the GUI **3900** may comprise one or more predetermined templates for a set of biological processes (e.g., CAR-T, NK cells, HSC, TIL, etc.). For example, the templates may aid process development and be validated starting points for process development. The templates may be further modified (e.g., customized) based on user requirements.

(415) FIG. **40** is a variation of a GUI **4000** comprising relating to adding a reagent and a consumable container. GUI **4000** may be displayed following selection of an Add Process Reagents

and Containers icon **3920** in FIG. 39. For example, GUI **4000** may comprise an Add Reagent and Container window **4010** enabling a user to input and/or select one or more reagents comprising a reagent kind, manufacturer, part number, volume per unit, required volume and required reagent inputs (e.g., lot number, expiration date, requires container transfer). Add Reagent and Container window **4010** may comprise one or more of an input field, selection box, drop-down selector, and the like. Furthermore, the Add Reagent and Container window **3810** may enable a user to input and/or select one or more consumable containers comprising a manufacturer, part number, volume per unit, and required container inputs (e.g., lot number, expiration date). In some variations, a user may select from a list of predetermined templates. For example, a user may create a process and save it as a template.

(416) FIG. 41 is a variation of a GUI **4100** comprising relating to a process parameter. GUI **4100** may be displayed following selection of an Add Process Reagents and Containers icon **3930** in FIG. 39. For example, GUI **4100** may comprise an Add Process Parameter window **4110** enabling a user to input and/or select one or more parameters comprising a name, parameter identification, description, data type, units, and parameter type. Add Process Parameter window **4010** may comprise one or more of an input field, selection box, drop-down selector, and the like. In some variations, a user may select from a list of predetermined templates. For example, a user may create a parameter and save it as a template. FIG. 42 is a variation of a GUI **4200** comprising relating to a patient weight process parameter. For example, GUI **4200** may comprise an Add Process Parameter window **4110** having filled in parameter information including patient weight, data type (e.g., integer), units (e.g., kg), and parameter type (e.g., input).

(417) FIG. 43 is a variation of a GUI **4300** relating to a preprocess analytic. GUI **4300** may be displayed following selection of an Add Preprocess analytics icon **3940** in FIG. 39. For example, GUI **4300** may comprise an Add Preprocess Analytic window **4310** enabling a user to input and/or select one or more parameters comprising a name, identifier, description, data type, and display group. Add Preprocess Analytic window **4310** may comprise one or more of an input field, selection box, drop-down selector, and the like. In some variations, a user may select from a list of predetermined templates. For example, a user may create a parameter and save it as a template.

(418) FIG. 44 is a variation of a GUI **4400** relating to a white blood cell count preprocess analytic. For example, GUI **4400** may comprise an Add Preprocess Analytic window **4410** having filled in preprocess analytic information including name (e.g., CBC White Blood Cell Count), identifier (e.g., CBC-white-blood-cell-count), description (e.g., Number of white blood cells in a sample), data type (e.g., float), and display group (e.g., WBC).

(419) FIG. 45 is a variation of a GUI **4500** relating to a process parameter calculation. GUI **4500** may be displayed following selection of an Add Preprocess analytics icon **3940** in FIG. 39 and selection of a “Calculation” parameter type. For example, GUI **4500** may comprise an Add Preprocess Analytic window **4510** enabling a user to input and/or select one or more parameters comprising a name, identifier, description, data type, display group, units, and parameter type. Furthermore, a Calculation Builder may enable a user to define a formula (e.g., algorithm, equation) to perform a predetermined calculation. For example, a Calculation Builder may comprise one or more of a set of available parameters (e.g., patient weight), constant value, equation, and operands.

(420) FIG. 46 is a variation of a GUI **4600** relating to a completed process setup. For example, GUI **4600** may comprise a Process Setup window **4610** having a filled in process reagents, containers, process parameters, and preprocess analytics. Once process setup is completed, one or more process elements may be specified.

(421) FIG. 47 is a variation of a GUI **4700** relating to process operations activation settings. GUI **4700** may be displayed following selection of a Process elements icon **4620** in FIG. 46. For example, GUI **4700** may comprise an Activation settings window **4710** allowing a user to input and/or select one or more of activation concentration (e.g., mg/L), activation culture time (e.g.,

seconds), activation temperature (e.g., ° C.), and gas mix mode. In some variations, a user may select from a list of predetermined templates. For example, a user may create a set of activation settings and save it as a template for later selection.

(422) FIG. **48** is a variation of a GUI **4800** relating to a filled process operations activation settings. For example, GUI **4800** may comprise an Activation settings window **4810** having filled in Activation setting information. In some variations, a set of gases (e.g., O.sub.2, N.sub.2, CO.sub.2) and corresponding concentrations may be specified.

(423) FIG. **49** is a variation of a GUI **4900** relating to a process operations interface. The GUI **4900** may comprise an Available Operations window **4910** and a Selected Operations window **4920**. The available options for selection may include one or more biologic process inputs as described herein including, but not limited to, enrichment, MACS selection, activation, transduction, transfection, expansion, and inline analysis. One or more of the operations may be selected and dragged into the Selected Operations window **4920**. The selected operations may be reordered within the Selected Operations window **4920**.

(424) FIG. **50** is a variation of a GUI **5000** relating to dragging process operations. The GUI **5000** may comprise an Available Operations window **5010**, a Selected Operations window **5020**, and a selected (e.g., dragged) operation **5030** that may be drag and dropped between the Available Operations window **5010** and the Selected Operations window **5020**. The Selected Operations window **5020** may comprise a plurality of selected operations.

(425) FIG. **51** is a variation of a GUI **5100** relating to dragging process operations. The GUI **5100** may comprise an Available Operations window **5110**, a Selected Operations window **5120**, and a selected (e.g., dragged) operation **5130** that may be drag and dropped between the Available Operations window **5110** and the Selected Operations window **5120**. The Selected Operations window **5120** may comprise a plurality of selected operations.

(426) FIG. **52** is a variation of a GUI **5200** relating to a filled process operations. For example, the GUI **5200** may comprise an Available Operations window **5210** and a Selected Operations window **5220** comprising a completed set of selected operations. In some variations, the settings (e.g., parameters) of each operation may be selectively modified by the user by selecting a corresponding icon (e.g., gear icon).

(427) FIGS. **53** and **54** are variations of a GUI **5300** and **5400** relating to product monitoring. The GUI **5300** and **5400** may comprise respective monitoring windows **5310**, **5410**. For example, the GUI **5310** may monitor a plurality of products **5320** and output one or more product characteristics **5330** including, but not limited to, a summary, process data, online analytics, imaging, process audit logs, process parameters, and process schedule. The monitoring window **5410** may monitor one or more product characteristics of one or more products. For example, the product characteristics may include, but is not limited to, one or more of a process name, identification, process identification, progress, estimated completion, current step, and message.

(428) FIG. **77A** is a flowchart of a method of separating cells **7700** using a CCE module. FIG. **77B** is a flowchart of a method of concentrating cells **7710** using a CCE module. FIG. **77C** is a flowchart of a method of buffer exchange **7720** using a CCE module.

(429) FIG. **78** is a flowchart of a method of separating cells **7800**. A method of counterflow centrifugal elutriation (CCE) **7800** may comprise the step moving a rotor towards a magnet **7802**. The rotor may define a rotational axis. In some variations, moving the rotor comprises advancing and withdrawing the magnet relative to the rotor using a robot. The rotor may be optionally moved towards an illumination source and an optical sensor **7804**. Fluid may be flowed through the rotor **7806**. In some variations, flowing the fluid comprises a flow rate of up to about 150 ml/min while rotating the rotor. The rotor may be magnetically rotated about the rotational axis using the magnet while flowing the fluid through the rotor **7808**. In some variations, rotating the rotor comprises a rotation rate of up to 6,000 RPM. One or more of the fluid and the cells may be optionally illuminated using an illumination source **7810**. Image data of one or more of the fluid and

biological material (e.g., particles, cellular material) in the rotor may optionally be generated using an optical sensor **7812**. One or more of a rotation rate of the rotor and a flow rate of the fluid may optionally be selected based at least in part on the image data **7814**. The fluid may be flowed out of the rotor **7816**. The rotor may be moved away from the magnet **7818**. The rotor may optionally be moved away from the illumination source and the optical sensor **7820**.

(430) FIG. **79A** is a flowchart of a closed-loop method of separating cells **7900**. FIG. **79B** is a flowchart of a closed-loop method of elutriating cells **7910**. FIG. **79C** is a flowchart of a closed-loop method of harvesting cells **7920**.

(431) FIG. **80A** is a flowchart of a method of separating cells **8000**. FIG. **80B** is a flowchart of a method of selecting cells **8010**.

(432) FIG. **81** is a flowchart of a method of separating cells **8100**. A method of magnetic-activated cell selection (MACS) may comprise labeling cells with a reagent **8102**. In some variations, a magnetic-activated cell selection (MACS) reagent may be incubated with the input cells to label the set of cells with the MACS reagent. In some variations, incubating the MACS reagent comprises a temperature between about 1° C. and about 10° C. The fluid comprising input cells may be flowed into a flow cell **8104**. A set of the cells are labeled with the MACS reagent. In some variations, the magnet array may optionally be moved relative to the flow cell **8106**. In some variations, the set of cells may be magnetically attracted towards a magnet array for a dwell time **8108**. In some variations, the dwell time may be at least about one minute. In some variations, the magnet array may be disposed external to the flow cell. In some variations, a longitudinal axis of the flow cell is perpendicular to ground. In some variations, the flow cell may be absent beads. In some variations, the magnet array may optionally be moved away from the flow cell to facilitate flowing the set of cells out of the flow cell **8110**. The set of cells may be flowed out of the flow cell after the dwell time **8112**. For example, flowing the set of cells out of the flow cell may comprise flowing a gas through the flow cell. The fluid without the set of cells may optionally be flowed out of the flow cell after the dwell time **8114**.

(433) FIG. **82A** is a flowchart of a method of preparing a bioreactor **8200**. FIG. **82B** is a flowchart of a method of loading a bioreactor **8210**. FIG. **82C** is a flowchart of a method of preparing a bioreactor **8220**. FIG. **82D** is a flowchart of a method of calibration for a bioreactor **8230**. FIG. **82E** is a flowchart of a method of mixing reagents **8240**. FIG. **82F** is a flowchart of a method of mixing reagents **8250**. FIG. **82G** is a flowchart of a method of culturing cells **8260**. FIG. **82H** is a flowchart of a method of refrigerating cells **8270**. FIG. **82I** is a flowchart of a method of taking a sample **8270**. FIG. **82J** is a flowchart of a method of culturing cells **8280**. FIG. **82K** is a flowchart of a method of media exchange **8290**. FIG. **82L** is a flowchart of a method of controlling gas **8292**. FIG. **82M** is a flowchart of a method of controlling pH **8294**.

(434) FIG. **83** is a flowchart of a method of electroporating cells **8300** using an electroporation module. In some variations, an electroporation module may comprise a fluid conduit configured to receive a first fluid comprising cells and a second fluid, a set of electrodes coupled to the fluid conduit, a pump coupled to the fluid conduit, and a controller comprising a processor and memory.

(435) A method of electroporating cells may optionally comprise generating a first signal to introduce the first fluid into the fluid conduit using the pump **8302**. A first fluid comprising cells in a fluid conduit may be received **8304**. In some variations, a second signal may optionally be generated to introduce the second fluid into the fluid conduit such that the second fluid separates the first fluid from a third fluid **8306**. In some variations, the second fluid may comprise a gas or oil. A second fluid in the fluid conduit may be received to separate the first fluid from a third fluid **8308**. An electroporation signal may optionally be generated to electroporate the cells in the fluid conduit using the set of electrodes **8310**. An electroporation signal may be applied to the first fluid to electroporate the cells **8312**. In some variations, the first fluid may be substantially static when applying the electroporation signal. In some variations, a third signal may optionally be generated to introduce the third fluid into the fluid conduit **8314**. The third fluid may be separated from the

first fluid by the second fluid. The third fluid may optionally be received in the fluid conduit separated from the first fluid by the second fluid **8316**.

(436) FIG. **84** is a flowchart of a method of electroporating cells **8400**. A method of electroporating cells may comprise receiving a first fluid comprising cells in a fluid conduit **8402**. A resistance measurement signal may be applied to the first fluid using a set of electrodes **8404**. A resistance may be measured between the first fluid and the set of electrodes **8406**. An electroporation signal may be applied to the first fluid based on the measured resistance **8408**. In some variations, a second fluid comprising a gas may optionally be received in the fluid conduit before applying the electroporation signal to the fluid. The first fluid may be separated from a third fluid by the second fluid.

(437) Fluid Connector

(438) A method of transferring fluid using a fluid connector **2700** is described in the flowchart of FIG. **27** and illustrated schematically in the corresponding steps depicted in FIGS. **16B-16L**. The method **2700** may comprise the step of coupling a sterilant source to a fluid connector **2702**. For example, as shown in FIG. **16B**, the inlet **1652** and outlet **1654** is coupled to a sterilant source to form a fluid pathway or connection. In some variations, a robot may be configured to couple and decouple the sterilant source to the sterilant port **1650** using a fluid conduit such as a tube. In some variations, the fluid connector **1600** may comprise a plurality of sterilant ports **1650**. As described herein, in some variations, a sterilant port may optionally comprise one or more of a check valve and a particle filter configured to reduce ingress of debris (e.g., after disconnecting the fluid connector). In some variations, the sterilant source may comprise or be coupled to a pump configured to circulate a sterilant through the sterilant port **1650**. In some variations, the sterilant port **1650** may be coupled to one or more of a sterilant source and a fluid source such as a heated air source. For example, a first sterilant port may be configured to couple to a first sterilant source, a second sterilant port may be configured to couple to a second sterilant source, and a third sterilant source may be configured to couple to an air source.

(439) The separate portions of the fluid connector **1600** may be brought together and mated. The method **2700** may comprise coupling a first port of a first connector to a second port of a second connector **2704**. FIG. **16C** is a schematic diagram of the fluid connector **1600** where the first port **216** and second port **226** are in a coupled configuration (e.g. docked position) that forms a first seal. In some variations, the first connector **1610** and the second connector **1620** may be axially and/or rotationally aligned, and one or more of the connectors **1610**, **1620** may be translated to couple the connectors **1610**, **1620** together. In FIG. **16C**, the first port **1616** and the second port **1626** are each in a closed configuration where the lumens of the respective first connector **1610** and second connector **1620** are sealed from the external environment to maintain sterility of the lumen of the fluid connector **1600**. Furthermore, the first valve **1618** and the second valve **1628** are each in a closed configuration that seals the proximal and distal ends of the connectors from each other. For example, the first valve **1618** in the closed configuration forms a seal (e.g., barrier) between the first proximal end **1612** and the first distal end **1614**. Similarly, the second valve **1628** in the closed configuration forms a seal between the second proximal end **1622** and the second distal end **1624**. In this manner, even if a portion of a connector is contaminated (e.g., first distal end **1614**), then the other portions of the fluid connector **1600** (e.g., first proximal end **1612**, second connector **1620**) may remain sterile by virtue of one or more of the port seals and valve seals.

(440) The ports may be transitioned to an open configuration such that a distal end of the connectors may be in fluid communication. The method **2700** may comprise transitioning the ports to an open configuration **2706**. FIG. **16D** is a schematic diagram of the fluid connector **1600** where the first port **1616** and the second port **1626** are transitioned into an open port configuration to create a shared volume between the valves **1618**, **1628** that is isolated from the external environment. In FIG. **16D**, the first valve **1618** and the second valve **1628** are in the closed configuration such that the chamber **1615** defines the volume (e.g., cavity) of the fluid connector

1600 between the first valve **1618** and the second valve **1628**. That is, the first distal end **1614** is in fluid communication with the second distal end **1624**. The ports **1616**, **1627** may be received and/or held in respective housings **1617**, **1627** in the closed configuration. In some variations, a robot may be configured to transition the ports **1616**, **1626** between the open configuration and the closed configuration as described in more detail herein. Additionally or alternatively, the first port **1616** and second port **1626** may automatically transition (e.g., mechanically actuate) from the closed configuration to the open configuration upon mating the first port **1616** to the second port **1626**. (441) In some variations, a fluid may be flowed into the fluid connector to aid sterilization. The method **2700** may comprise flowing fluid (e.g., liquid, gas) into the fluid connector through the sterilant port **2708**. FIG. **16E** is a schematic diagram of the fluid connector **1600** where the first chamber **1615** receives a fluid such as air at a predetermined temperature, pressure, and/or humidity. In some variations, one or more portions of the fluid connector **1600** may be dehumidified. For example, pressurized hot air may optionally be circulated within chamber **1615** in order to remove residual fluid, moisture, and raise a temperature of the inner surfaces of the chamber **1615**. The circulated fluid may flow through housings **1617**, **1627** and over inner and/or outer surfaces of the ports **1616**, **1626**.

(442) Generally, sterilization of a fluid connector may comprise one or more steps of dehumidification, conditioning, decontamination, and aeration (e.g., ventilation). Dehumidification may include removing moisture from the fluid connector. Conditioning may include heating the surfaces of the fluid connector to be decontaminated in order to prevent condensation and aid sterilization. Decontamination may include circulating a sterilant through the fluid connector at a predetermined concentration, rate, and exposure time. Aeration may include removing the sterilant from the fluid connector by circulating a gas (e.g., sterile air) through the fluid connector.

(443) A sterilant may be flowed into the fluid connector to sterilize one or more portions of the fluid connector. As described in more detail herein, the sterilant may be, for example, vaporized hydrogen peroxide (VHP) and/or ionized hydrogen peroxide (IHP). The method **2700** may comprise flowing a sterilant into the fluid connector through the sterilant port **2710**. FIG. **16F** is a schematic diagram of the fluid connector **1600** where the first chamber **1615** receives the sterilant for a predetermined amount of time (e.g., dwell time). For example, the sterilant may be circulated within the chamber **1615** to sterilize the chamber **1615** of the fluid connector **1600** and any contents disposed therein (e.g., other fluid, biological material). In some variations, the dwell time may be up to about 10 minutes, and between about 1 minute to about 10 minutes, including all ranges and sub-values in-between. In some variations, the vaporized hydrogen peroxide may comprise a concentration between about 50% and about 70%, including all ranges and sub-values in-between. Additionally or alternatively, one or more of the first valve **1618** and the second valve **1628** may be in the open configuration such that the sterilant may be circulated through other portions of the fluid connector **1600** such as first proximal end **1612** and second proximal end **1622**.

(444) In some variations, the valves may be translated relative to each other. The method **2700** may comprise translating a first valve relative to a second valve **2712**. FIG. **16G** is a schematic diagram of the fluid connector **1600** where the first valve **1618** and second valve **1628** are coupled to each other (e.g., transfer position). The first valve **1618** coupled to the second valve **1628** forms a second seal between the first connector **1610** and the second connector **1620**.

(445) The valves may be transitioned to an open configuration such that each end of the fluid connector is in fluid communication. The method **2700** may comprise transitioning the first valve and the second valve from a closed configuration to an open configuration **2714**. In some variations, the first valve and the second valve may comprise a spring-loaded shutoff configured to actuate to the open configuration, thereby allowing for fluidic communication between the sterile lumens of the first connector **1610** and the second connector **1620**. In some variations, each of the first valve **1618** of a first connector **1610** and the second valve **1628** of a second connector **1620** may comprise an engagement feature such as threading configured to facilitate coupling between

the first valve **1618** and the second valve **1628**. For example, once the second valve **1628** is translated to contact the first valve **1618**, the engagement features of the valves **1618**, **1628** may be coupled (e.g., locked) by rotating (e.g., twisting) one of the first valve **1618** and the second valve **1628** to engage their respective threads to each other. Conversely, one of the first valve **1618** and the second valve **1628** may be rotated in the opposite direction to uncouple (e.g., unlock) the first valve **1618** from the second valve **1628**.

(446) In some variations, fluid may flow through the fluid connector **2716**. FIG. **16H** is a schematic diagram of the fluid connector depicted in FIG. **16A** transferring fluid between fluid devices coupled to the fluid connector. For example, the contents (e.g., fluid, biological material) of the first fluid device **1630** and the second fluid device **1640** may be transferred through the fluid connector **1600**. In some variations, one or more of a pump, gravity feed, and the like may aid transfer through the fluid connector **1600**.

(447) In some variations, another fluid may be flowed into the fluid connector after fluid transfer between a first fluid device and a second fluid device has been completed. The method **2700** may comprise flowing fluid (e.g., liquid, gas, sterilant) into the fluid connector through the sterilant port **2708** to remove a fluid and/or biological material from the fluid connector **2718**. For example, flowing an inert gas into the fluid connector may reduce drops of liquid from forming when the first connector and second connector are separated. If a sterilant is flowed through the fluid connector, another fluid such as an inert gas may be flowed to aerate the fluid connector and ensure that the sterilant is removed.

(448) To begin decoupling the fluid connector, the valves may be translated away from each other. The method **2700** may comprise decoupling the first connector and the second connector **2720**. In some variations, a robot may be configured to manipulate the fluid connector **1600** to transition the valves **1618**, **1628** to a closed configuration and to translate the valves **1618**, **1628** away from each other, which may occur simultaneously or independently. The valves **1618**, **1628** in the closed configuration inhibit fluid flow between the first connector **1610** and the second connector **1620**. FIG. **16I** is a schematic diagram of the fluid connector **1600** in a closed valve configuration where the second valve **1628** is translated away from the first valve **1618**. Accordingly, the fluid connector **1600** returns to the docked position. For example, the first valve **1618** and the second valve **1628** may be configured to engage their respective spring-loaded shutoff features to form a seal and reduce drips and/or leaks. In some variations, one or more of a fluid and sterilant may optionally be configured to circulate through the chamber **1615** to remove moisture and/or sterilize the chamber **1615**.

(449) FIG. **16J** is a schematic diagram of the fluid connector **1600** where the first port **1616** and the second port **1626** are transitioned from the open port configuration to the closed port configuration. In some variations, a robot may be configured to manipulate the fluid connector **1600** to transition the ports **1616**, **1626** to a closed position to seal a lumen of the first connector **1610** from a lumen of the second connector **1620**. In some variations, the ports **1616**, **1626** may be configured to automatically transition to the closed port configuration when the first valve **1618** separates from the second valve **1628**.

(450) FIG. **16K** is a schematic diagram of the fluid connector **1600** where the second connector **1620** is translated away from the first connector **1610**. In some variations, a robot may be configured to manipulate the fluid connector **1600** to separate the first connector **1610** from the second connector **1620**. FIG. **16K** depicts the fluid connector **1600** in a disengaged configuration.

(451) FIG. **16L** is a schematic diagram of the fluid connector **1600** decoupled from the sterilant source. In some variations, a robot may be configured to manipulate the fluid connector **1600** and/or sterilant source to separate the sterilant source **1650** from the sterilant source. In some variations, the sterilant source may be decoupled from the fluid connector **1600** at any point after completing a sterilization process.

(452) In some variations, the cartridge comprises one or more Sterile Liquid Transfer Ports (SLTPs)

configured for use with a Sterile Liquid Transfer Device (SLTD). In some variations, the SLTP comprises one or more of a cap, a fitting, and a tube fluidically coupled to the fitting. The cap may be removable or pierceable. The fitting may be a push-to-connect fitting (PTCF) or a threaded fitting. PTCF include male-to-female, female-to-male, and androgynous fittings. Illustrative SLTPs and SLTDs suitable for use in the systems of the disclosure may include, for example, AseptiQuik® S connectors, Lynx® CDR connectors, Kleenpak™ connectors, Intact™ M connectors, GE LifeScience® ReadyMate connectors.

(453) When the disclosure refers to sterile liquid transfer devices, sterile liquid transfer ports, and sterile liquid transfer, the word “sterile” should be understood as a non-limiting description of some variations—an optional feature providing advantages in operation of certain systems and methods of the disclosure. Maintaining sterility is typically desirable for cell processing but may be achieved in various ways, including but not limited to providing sterile reagents, media, cells, and other solutions; sterilizing cartridge(s) and/or cartridge component(s) after loading (preserving the cell product from destruction); and/or operating the system in a sterile enclosure, environment, building, room, or the like. Such operator performed or system performed sterilization steps may make the cartridge or cartridge components sterile and/or preserve the sterility of the cartridge or cartridge components.

III. Examples

(454) FIGS. **85-96D** are diagrams of other variations of a fluid connector. FIG. **85** depicts a fluid connector **8500** comprising a first connector **8510** including a first cap **8516** and a second connector **8520** including a second cap **8526**. Fluid connector **8500** may comprise a male connector and a female connector, each with a removable cap and internal self-shutoff valve configured to reduce leaks and drips. The first cap **8516** and the second cap **8526** may be removable from their respective connectors **8510**, **8520**.

(455) In some variations, the fluid connector may be used with a self-sterilizing cap and decap tool **8600** depicted in FIG. **86**. The cap/decap tool **8600** may be configured to facilitate a sterile environment (e.g., ISO5) where the caps may be removed and the connectors pressed together, first sealing the connectors to each other, and then pressed further to transition the internal self-shutoff valves to an open configuration.

(456) In some variations, the tool **8600** may be configured to remove and re-apply caps to the fluid connector **8500**, and to provide a sterile volume for aseptic connection and disconnection of the fluid connector **8500** pair. In some variations, a method of using the tool **8600** may comprise inserting both capped connectors in a first configuration (e.g., where the caps approach the closed shutters) such that the fluid connectors form a seal within a lumen of the decap tool **8600**. In some variations the shutters may be opened to ensure a decap mechanism is retracted. Both capped connectors may be pushed to form a second configuration. The decap mechanism may be engaged to lock into features on the caps. Both capped connectors may be retracted to the first configuration where the caps are retained in the decap mechanism. The decap mechanism may be retracted such that the caps are held within a recess in the tool **8600**. The internal volume may optionally be decontaminated with sterilant or heat. Both connectors may be advanced to connect and perform the transfer. The steps described herein may be sequentially reversed.

(457) FIG. **87** depict a coupling sequence for a self-sealing fluid connector **8700** comprising a first connector **8710** and a second connector **8720**. The fluid connector **8700** may be configured to reduce leaks and drips and may facilitate smoother fluid flow path by removing spring elements from contact with fluid.

(458) FIG. **88** depict a coupling sequence for a self-sealing fluid connector **8800** comprising a first connector **8810** and a second connector **8820**.

(459) In some variations, a fluid connector may transfer fluids in a sterile manner using a retractable needle. FIG. **89** depicts a fluid connector **8900** comprising a first connector **8910** and a second connector **8920**. The first connector **8910** may comprise a first cap **8916** configured to

removably couple to a distal end of the first connector **8910**. The first connector **8910** may comprise a first elastomeric member **8970** (e.g., sealing septum) and a first thermal member **8972** (e.g., thermally resealable septum) disposed at a distal end of the first connector **8910**. The first connector **8910** may further comprise a needle **8990** and a spring **8992** coupled to the first elastomeric member **8970** and the needle **8990**. The second connector **8920** may comprise a second cap **8926** configured to removably couple to a distal end of the second connector **8920**. The second connector **8920** may comprise a second elastomeric member **8980** (e.g., sealing septum) and a second thermal member **8982** (e.g., thermally resealable septum) disposed at a distal end of the second connector **8920**.

(460) In some variations, the needle **8990** may be advanced through each of the first elastomeric member **8970**, first thermal member **8972**, second thermal member **8982**, and second elastomeric member **8980** to form a fluid pathway between the first connector **8910** and the second connector **8920**. Fluid may flow through the first connector **8910** and into the second connector **8920** via a lumen of needle **8990**. Each of the elastomeric members **8970**, **8980** and thermal members **8972**, **8982** may seal once the needle **8990** is withdrawn from a distal end of the first connector **8910**. For example, the thermal member **8972**, **8982** may be configured to thermally seal at a predetermined temperature and the elastomeric members **8970**, **8980** may self-seal once the needle **8990** has been withdrawn. In some variations, the fluid connector **8900** may be thermally decontaminated and resealed after fluid transfer. For example, the fluid connector **8900** (e.g., thermal members **8972**, **8982**) may be heated using one or more of a laser, contact heating, heated air, combinations thereof, and the like.

(461) In some variations, a fluid connector may comprise a port comprising an actuator configured to transition the port between a closed port configuration and an open port configuration. In some variations, the actuator may comprise a spring such as an external spring, a rotary spring, and a linear spring, as described in more detail with respect to FIGS. **90A-96D**.

(462) FIGS. **90A-90C** depict a fluid connector having an external spring actuator. FIG. **90A** is a side view, FIG. **90B** is a perspective view, and FIG. **90C** is a cross-sectional side view of a fluid connector **9000** comprising a first connector **9010** and second connector **9020**. The first connector **9010** may comprise a first port **9016** comprising a first spring **9036**, and the second connector **9020** may comprise a second port **9026** comprising a second spring **9046**. The springs **9036**, **9046** may be configured to actuate respective ports **9016**, **9026** between a closed port configuration and an open port configuration. Although not shown in FIG. **90C**, springs **9036**, **9046** may be coupled in an extended configuration to the pin in the open port configuration.

(463) FIGS. **91A-91F** depict a fluid connector having a linear spring actuator. FIG. **91A** is a side view, FIG. **91B** is a perspective view, and FIG. **91C** is a cross-sectional side view of the fluid connector **9100** in an open port configuration. The fluid connector **9100** may comprise a first connector **9110** and second connector **9120**. The first connector **9110** may comprise a first port **9116** comprising a first spring **9136**, and the second connector **9120** may comprise a second port **9126** comprising a second spring **9146**. The springs **9136**, **9146** may be configured to actuate respective ports **9116**, **9126** between a closed port configuration and an open port configuration. FIG. **91D** is a side view, FIG. **91E** is a perspective view, and FIG. **91F** is a cross-sectional side view of the fluid connector **9100** in a closed configuration.

(464) FIGS. **92A-92D** depict a fluid connector having a rotary spring actuator. FIG. **92A** is a side view, FIG. **92B** is a transparent side view, FIG. **92C** is a perspective view, and FIG. **92D** is a cross-sectional side view of a fluid connector **9200** comprising a first connector **9210** and second connector **9220**. The first connector **9210** may comprise a first port **9216** comprising a first spring **9236**, and the second connector **9220** may comprise a second port **9226** comprising a second spring **9246**. The springs **9236**, **9246** may be configured to actuate respective ports **9216**, **9226** between a closed port configuration and an open port configuration. FIG. **92B** shows the ports **9216**, **9226** in an open port configuration and FIG. **92D** shows the ports **9216**, **9226** in a closed port configuration.

(465) FIGS. 93A-94B depict fluid connectors having ports enclosed within a housing (e.g., enclosure). FIG. 93A is a perspective view and FIG. 93B is a transparent perspective view of a fluid connector **9300** comprising a first connector **9310** having a first housing **9338** and first actuator **9336**, and a second connector **9320** having a second housing **9348** and a second actuator **9346**. FIG. 93B shows a first port **9316** enclosed within first **9338** housing. The first port **9316** is coupled to the first actuator **9336** configured to transition the first port **9316** between an open port configuration (shown in FIG. 93B) and a closed port configuration.

(466) FIG. 94A is a perspective and FIG. 94B is a transparent perspective view of a fluid connector **9400** comprising a first connector **9410** having a first housing **9438** and a first actuator **9436**, and a second connector **9420** having a second housing **9448** and a second actuator **9446**. FIG. 94B shows a first port **9416** enclosed within first **9438** housing. The first actuator **9436** coupled to the first port **9416** may be configured to transition the first port **9416** between an open port configuration (shown in FIG. 94B) and a closed port configuration.

(467) FIG. 95A is a perspective view and FIG. 95B is a transparent perspective view of a fluid connector **9500** comprising a first connector **9510** having a first housing **9538**, first port **9516**, and a first actuator **9536**. A second connector **9520** may comprise a second housing **9548**, second port **9526**, and a second actuator **9546**. FIG. 95B shows the first port **9516** and the second port **9526** each in an open port configuration. For example, the first actuator **9536** coupled to the first port **9516** may be configured to transition the first port **9516** between an open port configuration and a closed port configuration. FIG. 95C is a detailed side view of the first port **9516** and first actuator **9536** in an open port configuration, and FIG. 95D is a detailed side view of the first port **9516** and first actuator **9536** in a closed port configuration.

(468) FIG. 97A is a perspective view of a MACS module. FIG. 97B is a cross-sectional perspective view of a MACS module. FIG. 97C is a cross-sectional side view of a MACS module.

(469) As used herein, sterile should be understood as a non-limiting description of some variations, an optional feature providing advantages in operation of certain systems and methods of the disclosure. Maintaining sterility is typically desirable for cell processing but may be achieved in various ways, including but not limited to providing sterile reagents, media, cells, and other solutions; sterilizing cartridge(s) and/or cartridge component(s) after loading (preserving the cell product from destruction); and/or operating the system in a sterile enclosure, environment, building, room, or the like. Such user or system performed sterilization steps may make the cartridge or cartridge components sterile and/or preserve the sterility of the cartridge or cartridge components.

(470) All references cited are herein incorporated by reference in their entirety.

(471) As used herein, the singular forms “a”, “an” and “the” include plural referents unless the context clearly dictates otherwise. “And” as used herein is interchangeably used with “or” unless expressly stated otherwise.

(472) All embodiments of any aspect of the disclosure can be used in combination, unless the context clearly dictates otherwise.

(473) Unless the context clearly requires otherwise, throughout the description and the claims, the words ‘comprise’, ‘comprising’, and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of “including, but not limited to”. Words using the singular or plural number also include the plural and singular number, respectively. Additionally, the words “herein,” “above,” “below,” and words of similar import, when used in this application, shall refer to this application as a whole and not to any particular portions of the application.

(474) While embodiments of the present invention have been shown and described herein, those skilled in the art will understand that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the invention. It should be understood that various alternatives to the embodiments

of the invention described herein may be employed in practicing the invention. It is intended that the following claims define the scope of the invention and that methods and structures within the scope of these claims and their equivalents be covered thereby.

Claims

1. A system for processing cell products in parallel comprising: an enclosed workcell comprising: a first instrument for cell processing a second instrument for cell processing; a robotic arm coupled to a linear rail; and an enclosed cartridge configured to receive a cell product and to independently interface with the first and second instruments, wherein the cartridge is coupled to one or more fluidic pathways for transferring fluid into the cartridge; and wherein the robotic arm is configured to move the enclosed cartridge between the first instrument and the second instrument.
2. The system of claim 1, wherein the enclosed workcell further comprises a feedthrough configured to receive the enclosed cartridge.
3. The system of claim 2, wherein the feedthrough is in fluid communication with a sterilization system.
4. The system of claim 3, wherein the sterilization system is configured to perform a sterilization procedure when the enclosed cartridge is within the feedthrough.
5. The system of claim 4, wherein the sterilization procedure comprises circulating a sterilant within the feedthrough.
6. The system of claim 5, wherein the sterilant comprises one or both of heated air and vaporized hydrogen peroxide.
7. The system of claim 1, wherein each of the first and second instruments comprise a bioreactor instrument, a cell selection instrument, a magnetic-activated cell selection instrument, a sorting instrument, an electroporation instrument, and a counterflow centrifugal elutriation (CCE) instrument.
8. The system of claim 7, wherein the first and second instruments are different.
9. The system of claim 1, wherein the enclosed cartridge comprises one or more of a bioreactor module, a cell selection module, a magnetic-activated cell selection module, a sorting module, a fluorescence activated cell sorting (FACS) module, an electroporation module, a counterflow centrifugal elutriation (CCE) module.
10. The system of claim 1 further comprising a sterile liquid transfer device (SLTD) configured to store one or more fluids.
11. The system of claim 10, wherein the SLTD comprises a portable container.
12. The system of claim 10, wherein the one or more fluids comprise one or more of a reagent and a cell culture medium.
13. The system of claim 10, wherein the SLTD is configured to be stored in a reagent vault of the workcell.
14. The system of claim 13, wherein the robotic arm is further configured to move the SLTD from the reagent vault to the first or second instrument of the workcell.
15. The system of claim 14, wherein the first or second instrument of the workcell comprises a sterile liquid transfer instrument (SLTI).
16. The system of claim 15, wherein the SLTI comprises a fluid connector configured to direct a fluid of the one or more fluids into the enclosed cartridge.
17. A system for processing cell products in parallel comprising: an enclosed workcell comprising: a first instrument for cell processing a second instrument for cell processing; a robotic arm; and a feedthrough for sterilization; and an enclosed cartridge configured to receive a cell product and to independently interface with the first and second instruments, wherein the robotic arm is configured to move the enclosed cartridge between the first instrument and the second instrument.
18. The system of claim 17, wherein the sterilization occurs via a sterilization system coupled to

the feedthrough.

19. The system of claim 18, wherein the sterilization system comprises a sterilant source and a pump.

20. The system of claim 19, wherein the sterilization system is configured to circulate a sterilant within the feedthrough.
