

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405562
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Morihara; Ryo et al.

Image forming apparatus having toner replenishment container control

Abstract

An image forming apparatus includes an apparatus body, a process unit having an image bearing member, a developer container configured to accommodate toner, a developing portion to develop an electrostatic latent image formed on the image bearing member into a toner image by using the toner accommodated in the developer container; and a replenishment port configured to allow replenishment of toner from the replenishment container, and a display portion. A controller notifies a user of information related to a toner amount by using the display portion in a case where it is determined that a lifetime of the process unit will expire before a sum of toner accommodated in the developer container and toner accommodated in the replenishment container is consumed, wherein the information related to a toner amount is a notification about toner, to be supplied from the replenishment container, which goes to waste.

Inventors:	Morihara; Ryo (Tokyo, JP), Umeda; Kensuke (Kanagawa, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	75275115
Assignee:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Appl. No.:	18/678184
Filed:	May 30, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240319655 A1	Sep. 26, 2024

Foreign Application Priority Data

JP	2019-184767	Oct. 07, 2019
----	-------------	---------------

Related U.S. Application Data

continuation parent-doc US 18102124 20230127 US 12032324 child-doc US 18678184
continuation parent-doc US 17580704 20220121 US 11592781 20230228 child-doc US 18102124
continuation parent-doc US 17037803 20200930 US 11262686 20220301 child-doc US 17580704

Publication Classification

Int. Cl.: G03G15/00 (20060101); G03G15/08 (20060101); G03G21/00 (20060101); G03G21/12 (20060101); G03G21/16 (20060101)

U.S. Cl.:

CPC G03G21/12 (20130101); G03G15/0863 (20130101); G03G15/0886 (20130101); G03G15/556 (20130101); G03G21/1633 (20130101); G03G21/1647 (20130101);

Field of Classification Search

CPC: G03G (15/0856); G03G (15/0863); G03G (15/0865); G03G (15/0877); G03G (15/0886); G03G (15/556); G03G (21/12); G03G (21/1633); G03G (21/1647)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5918094	12/1998	Masuda et al.	N/A	N/A
7440705	12/2007	Hatakeyama	N/A	N/A
7978989	12/2010	Nagano et al.	N/A	N/A
8649693	12/2013	Mitsui	N/A	N/A
8666266	12/2013	Ajima	N/A	N/A
11209762	12/2020	Lim et al.	N/A	N/A
11592781	12/2022	Morihara et al.	N/A	N/A
12032324	12/2023	Morihara	N/A	G03G 15/0877
2015/0063874	12/2014	So et al.	N/A	N/A
2018/0284681	12/2017	Yabuki	N/A	N/A
2018/0307172	12/2017	Ohshika	N/A	N/A
2020/0292960	12/2019	Suzuki et al.	N/A	N/A
2020/0292966	12/2019	Umeda et al.	N/A	N/A
2021/0103235	12/2020	Oshima et al.	N/A	N/A
2021/0103242	12/2020	Umeda et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101813903	12/2009	CN	N/A
102236295	12/2010	CN	N/A
102736462	12/2011	CN	N/A
103207548	12/2012	CN	N/A
H08-30084	12/1995	JP	N/A
H09-190068	12/1996	JP	N/A

H11-231631	12/1998	JP	N/A
2006-267528	12/2005	JP	N/A
2011-186176	12/2010	JP	N/A
2016-184027	12/2015	JP	N/A

OTHER PUBLICATIONS

Chinese Office Action dated Sep. 29, 2023, in related Chinese Patent Application No. 202011067689.1. cited by applicant

Japanese Office Action dated Aug. 29, 2023, in related Japanese Patent Application No. 2019-184767. cited by applicant

Primary Examiner: Chen; Sophia S

Attorney, Agent or Firm: VENABLE LLP

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The present invention relates to an image forming apparatus that forms an image on a recording material.

Description of the Related Art

(2) Typically, an image forming apparatus of an electrophotographic system forms an image on a recording material by developing an electrostatic latent image formed on the surface of a photosensitive member into a toner image by using toner, and then transferring the toner image from the photosensitive member onto the recording material. As methods for replenishing an image forming apparatus with toner consumed by repetitively performing image formation, a process cartridge system and a consecutive replenishment system are known. The process cartridge system is a system in which a photosensitive member and a developer container accommodating toner are integrated as a process cartridge, and the process cartridge is replaced by a brand-new one when all toner in the developer container is consumed.

(3) Meanwhile, Japanese Patent Laid-Open No. H08-30084 discloses a developing unit of a consecutive replenishment system that includes a toner conveyance path through which toner is supplied to a developing roller, and a developer supply box connected to the toner conveyance path, and that supplies toner from the developer supply box to the toner conveyance path in accordance with a detection result of a toner remainder amount.

(4) In recent years, demand from users for a wider variety of use of the image forming apparatus has been increasing in addition to the process cartridge system and the consecutive replenishment system described above.

SUMMARY OF THE INVENTION

(5) According to a first aspect of the present invention, an image forming apparatus to and from which a replenishment container accommodating toner is attachable and detachable and which is configured to form an image on a recording material, the image forming apparatus including an apparatus body, a cartridge attachable to and detachable from the apparatus body, the cartridge comprising an image bearing member, a developer container configured to accommodate toner, a developing portion configured to develop an electrostatic latent image formed on the image bearing member into a toner image by using the toner accommodated in the developer container, and a replenishment port configured to allow replenishment of toner from the replenishment container,

which is arranged outside of the image forming apparatus, to the developer container therethrough in a state where the replenishment container is attached to the replenishment port, a replenishment restriction portion configured to switch between a restricting state in which toner replenishment through the replenishment port is restricted and an allowing state in which toner replenishment through the replenishment port is allowed, a toner remainder amount detection portion whose output value changes on a basis of an amount of toner accommodated in the developer container, and a controller configured to, when the replenishment container is attached to the replenishment port, maintain the replenishment restriction portion in the restricting state in a case where a second printable sheet number is larger than a first printable sheet number, the first printable sheet number being obtained from a lifetime of the cartridge, the second printable sheet number being obtained from a sum of the amount of toner accommodated in the developer container and an amount of toner accommodated in the replenishment container.

(6) According to a second aspect of the present invention, an image forming apparatus to and from which a replenishment container accommodating toner is attachable and detachable and which is configured to form an image on a recording material, the image forming apparatus including an apparatus body, a cartridge attachable to and detachable from the apparatus body, the cartridge comprising an image bearing member, a developer container configured to accommodate toner, a developing portion configured to develop an electrostatic latent image formed on the image bearing member into a toner image by using the toner accommodated in the developer container, and a replenishment port configured to allow replenishment of toner from the replenishment container, which is arranged outside of the image forming apparatus, to the developer container therethrough in a state where the replenishment container is attached to the replenishment port, a toner remainder amount detection portion whose output value changes on a basis of an amount of toner accommodated in the developer container, a display portion, and a controller configured to, when the replenishment container is attached to the replenishment port, display a warning prompting replacement of the cartridge on the display portion on a basis of the output value of the toner remainder amount detection portion.

(7) According to a third aspect of the present invention, an image forming apparatus to and from which a replenishment container accommodating toner is attachable and detachable and which is configured to communicate with an information processing apparatus comprising a display portion and form a toner image on a recording material, the image forming apparatus including an apparatus body, a cartridge attachable to and detachable from the apparatus body, the cartridge comprising an image bearing member, a developer container configured to accommodate toner, a developing portion configured to develop an electrostatic latent image formed on the image bearing member into a toner image by using the toner accommodated in the developer container, and a replenishment port configured to allow replenishment of toner from the replenishment container, which is arranged outside of the image forming apparatus, to the developer container therethrough in a state where the replenishment container is attached to the replenishment port, a toner remainder amount detection portion whose output value changes on a basis of an amount of toner accommodated in the developer container, and a controller configured to, when the replenishment container is attached to the replenishment port, display a warning prompting replacement of the cartridge on the display portion on a basis of the output value of the toner remainder amount detection portion.

(8) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a section view of an image forming apparatus according to a first embodiment.
- (2) FIG. 1B is a perspective view of the image forming apparatus according to the first embodiment.
- (3) FIG. 2A is a section view of the image forming apparatus according to the first embodiment.
- (4) FIG. 2B is a perspective view of the image forming apparatus according to the first embodiment.
- (5) FIG. 3 is a diagram for describing attachment and detachment of a process cartridge according to the first embodiment.
- (6) FIG. 4A is a diagram for describing an openable and closable member of the image forming apparatus according to the first embodiment.
- (7) FIG. 4B is a diagram for describing the openable and closable member of the image forming apparatus according to the first embodiment.
- (8) FIG. 4C is a diagram for describing the openable and closable member of the image forming apparatus according to the first embodiment.
- (9) FIG. 5A is a diagram for describing a configuration of the process cartridge according to the first embodiment.
- (10) FIG. 5B is a diagram for describing the configuration of the process cartridge according to the first embodiment.
- (11) FIG. 6A is a diagram for describing the configuration of the process cartridge according to the first embodiment.
- (12) FIG. 6B is a diagram for describing the configuration of the process cartridge according to the first embodiment.
- (13) FIG. 6C is a diagram for describing the configuration of the process cartridge according to the first embodiment.
- (14) FIG. 7A is a perspective view of a toner pack according to the first embodiment.
- (15) FIG. 7B is a side view of the toner pack according to the first embodiment.
- (16) FIG. 8A is a perspective view of the toner pack according to the first embodiment.
- (17) FIG. 8B is a side view of the toner pack according to the first embodiment.
- (18) FIG. 8C is a diagram illustrating how toner is discharged.
- (19) FIG. 9A is a perspective view of a replenishment container attaching portion according to the first embodiment.
- (20) FIG. 9B is a top view of the replenishment container attaching portion according to the first embodiment.
- (21) FIG. 9C is an enlarged view of the replenishment container attaching portion according to the first embodiment.
- (22) FIG. 10A is a diagram for describing an operation of the replenishment container attaching portion according to the first embodiment.
- (23) FIG. 10B is a diagram for describing the operation of the replenishment container attaching portion according to the first embodiment.
- (24) FIG. 10C is a diagram for describing the operation of the replenishment container attaching portion according to the first embodiment.
- (25) FIG. 11A is a diagram illustrating a position of a locking member according to the first embodiment.
- (26) FIG. 11B is a diagram illustrating a position of the locking member according to the first embodiment.
- (27) FIG. 12 is a perspective view of the toner pack according to the first embodiment.
- (28) FIG. 13 is a diagram illustrating a pressing mechanism of the locking member according to the first embodiment.

- (29) FIG. 14A is a diagram illustrating a panel according to the first embodiment.
- (30) FIG. 14B is a diagram illustrating the panel according to the first embodiment.
- (31) FIG. 14C is a diagram illustrating the panel according to the first embodiment.
- (32) FIG. 15A is a perspective view of a toner bottle unit according to a first modification example.
- (33) FIG. 15B is a perspective view of the toner bottle unit according to the first modification example.
- (34) FIG. 15C is a side view of the toner bottle unit according to the first modification example.
- (35) FIG. 15D is a section view of the toner bottle unit according to the first modification example.
- (36) FIG. 16A is a diagram for describing an inner configuration of the toner bottle unit according to the first modification example.
- (37) FIG. 16B is a diagram for describing the inner configuration of the toner bottle unit according to the first modification example.
- (38) FIG. 16C is a diagram for describing the inner configuration of the toner bottle unit according to the first modification example.
- (39) FIG. 16D is a diagram for describing the inner configuration of the toner bottle unit according to the first modification example.
- (40) FIG. 16E is a diagram for describing detection of rotation of the toner bottle unit.
- (41) FIG. 16F is a diagram for describing detection of rotation of the toner bottle unit.
- (42) FIG. 17A is a perspective view of a process cartridge according to a second modification example.
- (43) FIG. 17B is a top view of the process cartridge according to the second modification example.
- (44) FIG. 17C is a section view of the process cartridge according to the second modification example.
- (45) FIG. 17D is a section view of the process cartridge according to the second modification example.
- (46) FIG. 18A is a perspective view of a process cartridge according to a third modification example.
- (47) FIG. 18B is a top view of the process cartridge according to the third modification example.
- (48) FIG. 18C is a section view of the process cartridge according to the third modification example.
- (49) FIG. 19 is a block diagram illustrating a control system of the image forming apparatus according to the first embodiment.
- (50) FIG. 20 is a flowchart illustrating calculation control for calculating a counter.
- (51) FIG. 21 is a perspective view of a display portion displaying a toner remainder amount insufficiency message.
- (52) FIG. 22 is a flowchart for describing operation conditions of a locking member.
- (53) FIG. 23 is a flowchart illustrating control related to a toner consumption amount and expiration of a process cartridge.
- (54) FIG. 24 is a flowchart illustrating control related to the toner consumption amount and expiration of a process cartridge.
- (55) FIG. 25 is a perspective view of a personal computer and a mobile information processing terminal that are connected to an image forming apparatus.

DESCRIPTION OF THE EMBODIMENTS

(56) Exemplary embodiments of the present invention will be described below with reference to drawings.

First Embodiment

(57) (1) Image Forming Apparatus

(58) FIG. 1A is a schematic diagram illustrating a configuration of an image forming apparatus 1 according to a first embodiment. The image forming apparatus 1 is a monochromatic printer that forms an image on a recording material on the basis of image information input from an external

device. Examples of the recording material include sheet materials of different natures. Examples of the sheet materials include paper sheets such as regular paper sheets and cardboards, plastic films such as sheets for overhead projectors, sheets having irregular shapes such as envelopes and index sheets, and cloths.

(59) (1-1) Overall Configuration

(60) As illustrated in FIGS. **1A** and **1**, the image forming apparatus **1** includes a printer body **100** serving as an apparatus body, a reading apparatus **200** openably and closably supported on the printer body **100**, and an operation portion **300** attached to an exterior surface of the printer body **100**. The printer body **100** includes an image forming portion **10**, a feeding portion **60**, a fixing portion **70**, and a discharge roller pair **80**. The feeding portion **60** feeds a recording material to the image forming portion **10**, and the image forming portion **10** forms a toner image on the recording material. The fixing portion **70** fixes the toner image formed by the image forming portion **10** onto the recording material, and the discharge roller pair **80** discharges the recording material having passed through the fixing portion **70** to the outside of the apparatus. In addition, a direct replenishment system in which toner is directly replenished from the outside of the image forming apparatus **1** by using a toner pack **40** filled with toner for replenishment is employed for a process cartridge **20** of the present embodiment.

(61) The image forming portion **10** is an image forming portion of an electrophotographic system including a scanner unit **11**, the process cartridge **20**, and a transfer roller **12**. The process cartridge **20** includes a photosensitive drum **21**, a charging roller **22** disposed in the vicinity of the photosensitive drum **21**, a developing roller **31**, and a cleaning blade **24**.

(62) The photosensitive drum **21** serving as an image bearing member of the present embodiment is a photosensitive member formed in a cylindrical shape. The photosensitive drum **21** of the present embodiment includes a drum-shaped base body formed from aluminum, and a photosensitive layer formed from a negatively-chargeable organic photoconductor on the base body. In addition, the photosensitive drum **21** is rotationally driven by a motor at a predetermined process speed in a predetermined direction, which is a clockwise direction in FIG. **1A**.

(63) The charging roller **22** comes into contact with the photosensitive drum **21** at a predetermined pressure contact force, and thus forms a charging portion. In addition, a desired charging voltage is applied to the charging roller **22** from a charging high-voltage power source, and thus the charging roller **22** uniformly charges the surface of the photosensitive drum **21** to a predetermined potential. In the present embodiment, the photosensitive drum **21** is negatively charged by the charging roller **22**.

(64) The scanner unit **11** radiates laser light **L** corresponding to image information input from an external device or the reading apparatus **200** onto the photosensitive drum **21** by using a polygonal mirror, and thus exposes the surface of the photosensitive drum **21** in a scanning manner. As a result of this exposure, an electrostatic latent image corresponding to the image information is formed on the surface of the photosensitive drum **21**. To be noted, the scanner unit **11** is not limited to a laser scanner unit. For example, a light-emitting diode: LED exposing unit including an LED array in which a plurality of LEDs are arranged along the longitudinal direction of the photosensitive drum **21** may be employed.

(65) A developing unit **802** includes a developing roller **31** serving as a developer bearing member configured to bear a developer, a developer container **32** serving as a frame member of the developing unit **802**, and a supply roller **33** capable of supplying the developer to the developing roller **31**. The developing roller **31** and the supply roller **33** are rotatably supported by the developer container **32**. In addition, the developing roller **31** is disposed in an opening portion of the developer container **32** so as to oppose the photosensitive drum **21**. The supply roller **33** is rotatably in contact with the developing roller **31**, and toner serving as the developer accommodated in the developer container **32** is applied on the surface of the developing roller **31** by the supply roller **33**. The developer container is also called a developer storage container.

(66) The developing unit **802** of the present embodiment employs a contact developing system as a developing system. That is, a toner layer born on the developing roller **31** serving as a developing portion comes into contact with the photosensitive drum **21** in a developing portion serving as a developing region where the photosensitive drum **21** and the developing roller **31** oppose each other. A developing voltage is applied to the developing roller **31** from a developing high-voltage power source. Under the influence of the developing voltage, the toner born on the developing roller **31** transfers from the developing roller **31** onto the surface of the photosensitive drum **21** in accordance with the potential distribution of the surface of the photosensitive drum **21**, and thus the electrostatic latent image is developed into a toner image. To be noted, in the present embodiment, a reversal development system is employed. That is, the toner image is formed by the toner attaching to a region where the amount of charge is reduced by being exposed in an exposing step on the surface of the photosensitive drum **21** charged in a charging step.

(67) In addition, in the present embodiment, toner which has a particle diameter of 6 μm and whose normal charging polarity is a negative polarity is used. For example, a polymer toner generated by a polymerization method is employed as the toner of the present embodiment. In addition, the toner of the present embodiment is a so-called nonmagnetic one-component developer that does not contain a magnetic component, and is born on the developing roller **31** mainly by an intermolecular force and an electrostatic force, that is, an image force. However, a one-component developer containing a magnetic component may be used. In addition, in some cases, the one-component developer contains additives for adjusting the fluidity and charging performance of the toner in addition to the toner particles. Examples of the additives include wax and silica fine particles. In addition, a two-component developer constituted by a nonmagnetic toner and a magnetic carrier may be used as the developer. In the case of using a magnetic developer, a cylindrical developing sleeve in which a magnet is disposed is used as the developer bearing member. That is, the developer contained in the developer container **32** is not limited to a one-component developer containing only a toner component, and may be a two-component developer containing toner and carrier.

(68) An agitation member **34** serving as an agitation portion is provided inside the developer container **32**. The agitation member **34** is driven to pivot, and thus agitates the toner in the developer container **32** and conveys the toner toward the developing roller **31** and the supply roller **33**. In addition, the agitation member **34** has a function of circulating toner not used for development and peeled off from the developing roller **31** in the developer container **32**, and thus making the toner in the developer container **32** uniform.

(69) In addition, a developing blade **35** that regulates the amount of toner born on the developing roller **31** is disposed at an opening portion of the developer container **32** where the developing roller **31** is disposed. In accordance with the rotation of the developing roller **31**, the toner supplied to the surface of the developing roller **31** passes through a portion where the developing roller **31** and the developing blade **35** oppose each other, thus forms a uniform thin layer, and is negatively charged as a result of frictional charging.

(70) The feeding portion **60** includes a front door **61** supported to be openable and closable with respect to the printer body **100**, a supporting tray **62**, an inner plate **63**, a tray spring **64**, and a pickup roller **65**. The supporting tray **62** constitutes a bottom surface of a recording material accommodating space exposed by opening the front door **61**, and the inner plate **63** is supported on the supporting tray **62** so as to be capable of ascending and descending. The tray spring **64** urges the inner plate **63** upward, and presses a recording material P supported on the inner plate **63** against the pickup roller **65**. To be noted, the front door **61** closes the recording material accommodating space in the state of being closed with respect to the printer body **100**, and supports the recording material P together with the supporting tray **62** and the inner plate **63** in the state of being open with respect to the printer body **100**.

(71) The transfer roller **12** serving as a transfer portion transfers the toner image formed on the

photosensitive drum **21** of the process cartridge **20** onto the recording material. To be noted, although a direct transfer system in which the toner image formed on the image bearing member is directly transferred from the image bearing member onto the recording material will be described in the present embodiment, an intermediate transfer system in which the toner image is transferred from the image bearing member via an intermediate transfer member such as an intermediate transfer belt may be employed. In that case, for example, a transfer unit constituted by an intermediate transfer belt, a primary transfer roller that transfers the toner image from the photosensitive drum onto the intermediate transfer belt through primary transfer, and a secondary transfer roller that transfers the toner image from the intermediate transfer belt onto the recording material functions as a transfer portion.

(72) The fixing portion **70** is a thermal fixation system that performs an image fixing process by heating and melting the toner on the recording material. The fixing portion **70** includes a fixing film **71**, a fixing heater such as a ceramic heater that heats the fixing film **71**, a thermistor that measures the temperature of the fixing heater, and a pressurizing roller **72** that comes into pressure contact with the fixing film **71**.

(73) Next, an image forming operation of the image forming apparatus 1 will be described. When a command for image formation is input to the image forming apparatus 1, an image forming process by the image forming portion **10** is started on the basis of image information input from an external computer connected to the image forming apparatus 1 or image information input from the reading apparatus 200. The scanner unit **11** radiates laser light L toward the photosensitive drum **21** on the basis of the input image information. At this time, the photosensitive drum **21** has been charged by the charging roller **22** in advance, and an electrostatic latent image is formed on the photosensitive drum **21** by being irradiated with the laser light L. Then, this electrostatic latent image is developed by the developing roller **31**, and a toner image is formed on the photosensitive drum **21**.

(74) In parallel with the image forming process described above, the pickup roller **65** of the feeding portion **60** delivers out the recording material P supported on the front door **61**, the supporting tray **62**, and the inner plate **63**. The recording material P is fed to the registration roller pair **15** by the pickup roller **65**, and the skew thereof is corrected by abutting a nip of the registration roller pair **15**. In addition, the registration roller pair **15** is driven in accordance with a transfer timing of the toner image obtained from the start time of exposure performed by the scanner unit **11**, and conveys the recording material P to a transfer portion that is a nip portion formed between the transfer roller **12** and the photosensitive drum **21**.

(75) A transfer voltage is applied to the transfer roller **12** from the transfer high-voltage power source, and the toner image born on the photosensitive drum **21** is transferred onto the recording material P conveyed by the registration roller pair **15**. After the transfer, transfer residual toner on the surface of the photosensitive drum **21** is removed by the cleaning blade **24**, which is an elastic blade in contact with the photosensitive drum **21**. The recording material P onto which the toner image has been transferred is conveyed to the fixing portion **70** and passes through a nip portion formed between the fixing film **71** and the pressurizing roller **72** of the fixing portion **70**, and thus the toner image is heated and pressurized. As a result of this, the toner particles melt and then adhere to the recording material P. Thus, the toner image is fixed to the recording material P. The recording material P having passed through the fixing portion **70** is discharged to the outside of the image forming apparatus 1 by a discharge roller pair **80**, and is supported on a discharge tray **81** formed on an upper portion of the printer body **100**.

(76) The discharge tray **81** is inclined upward toward the downstream side in a discharge direction of the recording material, and trailing ends of recording materials discharged onto the discharge tray **81** are aligned by a regulating surface **84** by sliding down the discharge tray **81**.

(77) (1-2) Openable and Closable Part of Image Forming Apparatus

(78) As illustrated in FIGS. 2A, 2B, and 3, a first opening portion **101** opening upward is provided in an upper portion of the printer body **100**. The first opening portion **101** is covered by a top cover

82 during use as illustrated in FIG. 1B, and the process cartridge **20** is exposed by opening the top cover **82** upward as illustrated in FIG. 2B. The top cover **82** is supported so as to be openable and closable with respect to the printer body **100** by rotating around a rotation shaft **82c** illustrated in FIG. 3 extending in the left-right direction, and the discharge tray **81** is provided on the upper surface thereof. The top cover **82** is opened from the front side toward the rear side when the reading apparatus 200 is opened with respect to the printer body **100**. To be noted, the reading apparatus 200 and the top cover **82** are configured to be held in a state of being open and a state of being closed, by a holding mechanism such as a hinge mechanism.

(79) For example, the user opens the top cover **82** together with the reading apparatus 200 in the case where jam of the recording material has occurred in a conveyance path CP which the recording material fed by the pickup roller **65** passes through. Then, the user accesses the process cartridge **20** through the first opening portion **101** exposed by opening the top cover **82**, and pulls out the process cartridge **20** along a cartridge guide **102**. A projection portion **21a** provided on an end portion of the process cartridge **20** in the axial direction of the photosensitive drum **21** illustrated in FIG. 5A slides on the cartridge guide **102**, and thus the process cartridge **20** is guided by the cartridge guide **102**.

(80) Then, as a result of the process cartridge **20** being pulled out to the outside through the first opening portion **101**, a space through which a hand can reach the inside of the conveyance path CP is generated. The user can put their hand in the printer body **100** through the first opening portion **101** to access the recording material causing the jam in the conveyance path CP, and thus remove the recording material causing the jam.

(81) In addition, in the present embodiment, an opening/closing member **83** is openably and closably provided on the top cover **82** as illustrated in FIGS. 1B and 4C. An opening portion **82a** opening upward is provided in the upper surface of the top cover **82** on which the discharge tray **81** is provided, and the opening portion **82a** is covered by closing the opening/closing member **83**. The opening/closing member **83** and the opening portion **82a** are provided on the right side of the top cover **82**. In addition, the opening/closing member **83** is supported on the top cover **82** so as to be openable and closable about a pivot shaft **83a** extending in the front-rear direction, and is opened to the right by hooking a finger through a groove portion **82b** provided on the top cover **82**. The opening/closing member **83** is formed in an approximately L-shape in accordance with the shape of the top cover **82**. To be noted, the opening/closing member **83** is not limited to the opening/closing mechanism described above. For example, the opening/closing member **83** may be disposed on the top cover **82** so as to cover a replenishment container attaching portion **701** and configured to open and close the opening portion **82a** by sliding and pivoting on the upper surface of the top cover **82** about a pivot shaft perpendicular to the top cover **82**. Here, sliding on the upper surface of the top cover **82** means that the movement of the opening/closing member **83** in the pivot axis direction is restricted.

(82) The opening portion **82a** is opened so as to expose the replenishment container attaching portion **701** provided in an upper portion of the process cartridge **20** for toner replenishment. By opening the opening/closing member **83**, the user can access the replenishment container attaching portion **701** without opening the top cover **82**. The user can replenish the process cartridge **20** with toner by attaching a toner pack **40** to the replenishment container attaching portion **701**.

(83) In the present embodiment, a system in which the user replenishes the process cartridge **20** with toner from the toner pack **40** filled with toner for replenishment illustrated in FIGS. 1A and 1B in a state in which the process cartridge **20** is still attached to the image forming apparatus 1, that is, a direct replenishment system, is employed. Therefore, an operation of taking out the process cartridge **20** from the printer body **100** and replacing the process cartridge **20** by a brand-new process cartridge in the case where the amount of toner remaining in the process cartridge **20** has become small becomes unnecessary, and therefore the usability can be improved. To be noted, the image forming apparatus 1 and the toner pack **40** constitute an image forming system.

(84) To be noted, in the present embodiment, the reading apparatus 200 is provided in an upper portion of the image forming apparatus 1, and in the case of opening the opening/closing member **83**, the reading apparatus 200 needs to be opened first to expose the top cover **82**. However, a configuration in which the reading apparatus 200 is omitted and the opening/closing member **83** is exposed in an upper portion of the image forming apparatus 1 from the beginning may be employed.

(85) (1-3) Reading Apparatus

(86) As illustrated in FIGS. **4A** and **4B**, the image reading apparatus 200 includes a reading unit **201** including an unillustrated reading portion therein, and a pressure plate **202** openably and closably supported by the reading unit **201**. A platen glass **203** that transmits light emitted from the reading portion and supports a document placed thereon is provided on the upper surface of the reading unit **201**.

(87) In the case of reading an image of a document by the reading apparatus 200, the user places the document on the platen glass **203** in a state in which the pressure plate **202** is open. Then, the pressure plate **202** is closed to suppress displacement of the document on the platen glass **203**, and a reading command is output to the image forming apparatus 1 by, for example, operating the operation portion **300**. When the reading operation is started, the reading portion in the reading unit **201** reciprocates in a sub-scanning direction, that is, in the left-right direction in a state of facing the operation portion **300** of the image forming apparatus 1 on the front side. The reading portion receives light reflected on the document by a light receiving portion while radiating light onto the document from a light emitting portion, and reads the image of the document by performing photoelectric conversion.

(88) To be noted, in the description below, the front-rear direction, left-right direction, and up-down direction of the image forming apparatus 1 are defined on the basis of a state of facing the operation portion **300** on the front side as a standard. The up-down direction corresponds to the gravity direction. The positional relationship between members attachable to and detachable from the printer body **100** such as the process cartridge **20** will be described on the basis of a state where the members are attached to the printer body **100**. In addition, the “longitudinal direction” of the process cartridge **20** refers to an axial direction of the photosensitive drum **21**.

(89) (1-4) Configuration of Process Cartridge

(90) Next, a configuration of the process cartridge **20** will be described. FIG. **5A** is a perspective view of the process cartridge **20** and the toner pack **40**, and FIG. **5B** is a side view of the process cartridge **20** and the toner pack **40**. FIG. **6A** is a section view taken along a line **6A-6A** of FIG. **5B**, FIG. **6B** is a section view taken along a line **6B-6B** of FIG. **5B**, and FIG. **6C** is a section view taken along a line **6C-6C** of FIGS. **6A** and **6B**. To be noted, in FIGS. **5A** to **6C**, the outer shape of the replenishment container attaching portion **701** is illustrated in a simplified manner. For the detailed shape, see, for example, FIG. **9A**.

(91) As illustrated in FIGS. **5A** to **6C**, the process cartridge **20** is constituted by a toner receiving unit **801**, a developing unit **802**, and a cleaning unit **803**. The toner receiving unit **801**, the cleaning unit **803**, and the developing unit **802** are arranged in this order from the upper side to the lower side in the gravity direction. Each unit will be sequentially described below.

(92) The toner receiving unit **801** is disposed in an upper portion of the process cartridge **20**. A toner storage portion **8011** constituted by a frame member that stores toner is provided in the toner receiving unit **801**, and the replenishment container attaching portion **701** that couples to a toner pack **40** is provided at an end portion of the toner receiving unit **801**. To be noted, the frame member constituting the toner storage portion **8011** may be made up of a single member or a combination of a plurality of members. The replenishment container attaching portion **701** includes a replenishment port **8012** through which toner discharged from the toner pack **40** is received. The detailed configuration of the replenishment container attaching portion **701** and attachment of the toner pack **40** to the replenishment container attaching portion **701** will be described later.

(93) Further, a first conveyance member **8013**, a second conveyance member **8014**, and a third conveyance member **8015** are provided inside the toner receiving unit **801**. The first conveyance member **8013** conveys, in an arrow direction H illustrated in FIG. 6C toward a center portion of the toner storage portion **8011**, toner that has fallen into an end portion of the toner storage portion **8011** in the longitudinal direction through the replenishment port **8012**. The second conveyance member **8014** conveys the toner conveyed by the first conveyance member **8013**, in an arrow J direction illustrated in FIG. 6C perpendicular to the longitudinal direction, to an upper portion of the developing unit **802**, that is, to discharge ports **8016**. The third conveyance member **8015** receives the toner from the second conveyance member **8014** mainly at a center portion in the longitudinal direction, and conveys the toner to a first side and a second side in the longitudinal direction, that is, in an arrow K direction and an arrow K' direction. To be noted, the first to third conveyance members are operated so as to move the toner, and can be therefore also referred to as first to third developer moving members.

(94) When the toner from the toner pack **40** serving as a replenishment container flows into the toner receiving unit **801**, air also flows in. The replenishment container is also called a developer supply container. The toner receiving unit **801** includes an air filter **8017** illustrated in FIG. 5A for allowing the air to flow in the arrow H direction when replenishing toner, such that it is easier to replenish toner. This air filter **8017** suppresses blowout of the toner from the replenishment port **8012** occurring as a result of the inner pressure of the toner receiving unit **801** increasing when replenishing toner and part of the air flowing in a direction opposite to the arrow H direction.

(95) Further, the discharge ports **8016** illustrated in FIG. 6B for discharging toner from the toner storage portion **8011** to the developer container **32** of the developing unit **802** are respectively provided at two end portions of the toner receiving unit **801** in the longitudinal direction. The toner having reached the discharge ports **8016** by being conveyed by the third conveyance member **8015** falls into the developer container **32** in accordance with the gravity. To be noted, a conveyance member may be further provided in paths of the discharge ports **8016** to help the toner movement in accordance with the gravity.

(96) The developing unit **802** positioned in a lower portion of the process cartridge **20** includes openings **8021** illustrated in FIG. 6B that receive the toner discharged through the discharge ports **8016**. Unillustrated sealing members are provided between the discharge ports **8016** and the openings **8021** such that the toner does not leak through a gap between the discharge ports **8016** and the openings **8021**.

(97) The toner having fallen into the toner receiving unit **801** from the toner pack **40** through the replenishment port **8012** is conveyed in the toner receiving unit **801** by the first conveyance member **8013**, the second conveyance member **8014**, and the third conveyance member **8015**. Then, the toner is delivered from the toner receiving unit **801** to the developing unit **802** through the discharge ports **8016** and openings **8021** provided at the two end portions in the longitudinal direction. In this manner, the toner supplied through the replenishment port **8012**, which is positioned at an end portion of the process cartridge **20** in the longitudinal direction and away from the developer container **32** in the horizontal direction as viewed in the longitudinal direction, is conveyed in the process cartridge **20** and reaches the developer container **32**.

(98) As described above, the toner storage portion **8011** of the toner receiving unit **801** and the developer container **32** of the developing unit **802** communicate with each other, and thus constitute a storage container defining a space to store the toner in the process cartridge **20**. Therefore, in the present embodiment, the replenishment port **8012** for replenishing toner from the outside is provided as a part of the storage container of the process cartridge **20**. However, a replenishment port directly connected to the replenishment container may be provided in the printer body, and the process cartridge may receive the toner through this replenishment port. In this case, a part of the process cartridge **20** excluding the replenishment port is detachable from the image forming apparatus 1 as illustrated in FIG. 3.

(99) The toner supplied to the developing unit **802** through the openings **8021** is stored in a conveyance chamber **36** formed in the developer container **32** constituted by a frame member of the developing unit **802** as illustrated in FIGS. **6A** and **6B**. To be noted, the frame member constituting the developer container **32** may be constituted by a single member or a combination of a plurality of members. Here, an agitation member **34** is provided in the conveyance chamber **36**. The agitation member **34** includes a shaft member **34a** provided near the rotation center of the agitation member **34**, and a blade portion **34b** extending in the radial direction from the shaft member **34a**. In section view, toner within the rotation trajectory of the distal end of the blade portion **34b** is pushed and moved in accordance with the movement of the blade portion **34b**. The toner replenished through the openings **8021** is conveyed toward the developing roller **31**, the supply roller **33**, and the developing blade **35** while being agitated by the agitation member **34**.

(100) The cleaning unit **803** includes a fourth conveyance member **8031**, a fifth conveyance member **8032**, and a waste toner chamber **8033** constituted by a frame member as illustrated in FIGS. **6A** and **6B**. To be noted, the frame member constituting the waste toner chamber **8033** may be made up of a single member or a combination of a plurality of members. The waste toner chamber **8033** is a space for storing collected matter, that is, so-called waste toner, such as transfer residual toner collected from the photosensitive drum **21** by the cleaning blade **24**, and is independent from the inner spaces of the toner receiving unit **801** and the developing unit **802**. The waste toner collected by the cleaning blade **24** is conveyed in an arrow M direction by the fourth conveyance member **8031** and the fifth conveyance member **8032**, and is gradually accumulated starting from the front side of a rear portion **8033a** of the waste toner chamber **8033**.

(101) Here, a laser passing space SP that is a gap which the laser light L emitted from the scanner unit **11** illustrated in FIG. **1A** toward the photosensitive drum **21** can pass through is defined between the cleaning unit **803** and the developing unit **802** as illustrated in FIG. **6A**. As described above, the discharge ports **8016** and the openings **8021** for delivering the toner from the toner receiving unit **801** to the developing unit **802** are provided at end portions of the respective units in the longitudinal direction. Therefore, toner replenished from the outside of the image forming apparatus 1, particularly through the replenishment port **8012** opening in the upper surface of the apparatus, can be conveyed to the developer container **32** provided in a lower portion of the process cartridge **20** while securing the laser passing space SP in a configuration of a small size as the whole of the process cartridge **20**.

(102) (1-5) Configuration of Toner Pack

(103) The configuration of the toner pack **40** will be described. FIG. **7A** is a perspective view of the toner pack **40** in a state in which a shutter member **41** is closed, and FIG. **7B** is a bottom view thereof. FIG. **8A** is a perspective view of the toner pack **40** in a state in which the shutter member **41** is open, FIG. **8B** is a bottom view thereof, and FIG. **8C** illustrates how the user squeezes the toner pack **40** with hands when replenishing toner. In addition, FIG. **12** is a perspective view of the toner pack **40** in the state in which the shutter member **41** is closed as viewed from below.

(104) As illustrated in FIGS. **7A** to **8C**, the toner pack **40** serving as an example of a replenishment container includes a bag member **43** filled with toner, a discharge portion **42** formed from resin and attached to the bag member **43**, and the shutter member **41** capable of opening and closing an opening portion of the discharge portion **42**. A memory unit **45** serving as a storage portion that stores information of the toner pack **40** is attached to the discharge portion **42**. The memory unit **45** includes, as a contact portion **45a** that comes into contact with a contact portion **70133** of the replenishment container attaching portion **701** that is illustrated in FIGS. **9A** and **9B** and will be described later, a plurality of metal plates serving as metal terminals exposed to the outside of the toner pack **40**. In addition, as a material of the bag member **43**, polypropylene resin, polyethylene terephthalate resin, cardboards, paper, and so forth can be employed. In addition, the thickness of the bag member **43** can be set to 0.01 mm to 1.2 mm. In addition, the thickness is further preferably 0.05 mm to 1.0 mm from the viewpoint of squeezability for the user and the durability of the bag.

(105) As illustrated in FIGS. 7B, 8B, and 12, the shutter member **41** has a shape obtained by cutting out a part of a disk relatively rotatable with respect to the discharge portion **42**. A side surface of the shutter member **41** extending in a thickness direction at the cutout portion functions as an engagement surface **41s**. Meanwhile, the discharge portion **42** also has a shape having a cutout portion therein. The cutout portion of the discharge portion **42** includes an engagement surface **42s** parallel to the engagement surface **41s**. Further, a discharge port **42a** is provided at a position at approximately 180° from the engagement surface **42s** in the circumferential direction of the discharge port **42a**. To be noted, details of the engagement surface **41s** and **42s** are illustrated in FIG. 12.

(106) As illustrated in FIGS. 7B and 12, when the positions of the cutouts of the shutter member **41** and the discharge portion **42** as viewed from above or below are aligned, the discharge port **42a** is covered by the shutter member **41**. This state will be referred to as a closed state. As illustrated in FIG. 8B, when the shutter member **41** rotates by 180° with respect to the discharge portion **42**, the discharge port **42a** is exposed through the cutout portion of the shutter member **41**, and the inner space of the bag member **43** communicates with a space outside the toner pack **40**. To be noted, as illustrated in FIG. 12, the shutter member **41** preferably has a structure in which a sealing layer **41b** formed from an elastic material such as a sponge is stuck on a body portion **41a** having stiffness. In this case, the sealing layer **41b** is in firm contact with a sealing layer **42c** covering a peripheral edge portion of the discharge port **42a** in the closed state, and thus toner leakage is suppressed. The sealing layer **42c** is illustrated in FIG. 12, and is formed from an elastic material such as a sponge similarly to the sealing layer **41b**.

(107) As will be described later, when replenishing the image forming apparatus 1 with toner from the toner pack **40**, the toner pack **40** is inserted in and coupled to the replenishment container attaching portion **701** by aligning the discharge portion **42** with a predetermined position. Then, when the discharge portion **42** is rotated by 180°, the discharge portion **42** relatively rotates with respect to the shutter member **41** to open the discharge port **42a**, and the toner in the bag member **43** falls into the toner receiving unit **801** in accordance with the gravity. At this time, the shutter member **41** does not relatively move with respect to the replenishment container attaching portion **701**.

(108) As illustrated in FIG. 8C, the user squeezes the bag member **43** in the state in which the toner pack **40** is attached to the replenishment container attaching portion **701** and rotated by 180°, and thus can promote discharge of toner from the toner pack **40**.

(109) To be noted, although the shutter member **41** that is rotatable has been described as an example herein, the shutter member may be omitted, and a shutter member of a slide type may be used instead of the rotary shutter member **41**. In addition, the shutter member **41** may be configured to be broken by attaching the toner pack **40** to a replenishment port **8012** or rotating the toner pack **40** in an attached state, or may have a detachable lid structure such as a sticker.

(110) In addition, it is preferable that a protective cap is attached to the discharge portion **42** of an unused toner pack **40** such that toner does not leak during transport or the like. For example, the protective cap engages with the cutout portions of the shutter member **41** and the discharge portion **42** in a state of being attached to the discharge portion **42** so as to restrict relative rotation of the shutter member **41** and the discharge portion **42**. By removing the protective cap, it becomes possible for the user to attach the toner pack **40** to the replenishment container attaching portion **701**.

(111) (1-6) Configuration of Replenishment Container Attaching Portion

(112) A shutter opening/closing mechanism of the toner pack **40** and the toner receiving unit **801**, and a locking mechanism of the shutter member **41** will be described. FIG. 9A is a perspective view of the replenishment container attaching portion **701**, and FIG. 9B is a top view of the replenishment container attaching portion **701**. The replenishment container attaching portion **701** includes the replenishment port **8012**, a replenishment port shutter **7013**, a locking member **7014**,

and a rotation detection portion **7015**.

(113) The replenishment port **8012** is an opening portion communicating with the toner storage portion **8011** of the toner receiving unit **801** illustrated in FIG. **6**, and is fixed to the frame member **8010** of the toner receiving unit **801**. The replenishment port shutter **7013** includes a lid portion **70131** covering the replenishment port **8012**, a cylindrical portion **70132** that receives the discharge portion **42** of the toner pack **40**, and the contact portion **70133** connected to the contact portion **45a** of the memory unit **45** of the toner pack **40** illustrated in FIG. **8B**. In FIG. **9A**, a part of the cylindrical portion **70132** covering the contact portion **70133** is indicated as a cylindrical portion **70132a**. The replenishment port shutter **7013** is a member in which the lid portion **70131**, the cylindrical portion **70132**, and the contact portion **70133** are integrated, and is rotatably attached to the frame member **8010** of the toner receiving unit **801**. Each conductor exposed on the contact portion **70133** is electrically connected to a controller of the image forming apparatus 1 incorporated in the printer body **100**, via wiring provided in the process cartridge **20** and contacts between the process cartridge **20** and the printer body **100**.

(114) The rotation detection portion **7015** serving as a rotation detection sensor is a mechanism that detects the rotation of the replenishment port shutter **7013**. The rotation detection portion **7015** of the present embodiment is constituted by two conductive leaf springs **70151** and **70152**. The leaf spring **70152** springs in a clockwise direction, and when pressed by a projection portion **70135a** provided on an outer periphery of the replenishment port shutter **7013**, comes into contact with the leaf spring **70151** at a distal end portion **701521**. That is, the rotation detection portion **7015** is an electric circuit configured such that a connected state and disconnected state thereof switch in accordance with the rotation angle, that is, rotational position of the replenishment port shutter **7013**. As will be described later, a controller **90** of the image forming apparatus 1 illustrated in FIG. **19** recognizes whether or not the discharge port **42a** of the toner pack **40** communicates with the replenishment port **8012** of the replenishment container attaching portion **701**, on the basis of whether the rotation detection portion **7015** is in the connected state or the disconnected state. In other words, the controller **90** can determine that the replenishment operation by the user using the toner pack **40** has been normally performed at least up to the communication between the discharge port **42a** and the replenishment port **8012**.

(115) As illustrated in FIGS. **9A** to **10C**, a plurality of projection portions **70135a** and **70135b** are provided at an outer peripheral portion of the cylindrical portion **70132** of the replenishment port shutter **7013**. In addition, the frame member **8010** includes a shutter supporting portion **7011**, and the shutter supporting portion **7011** rotatably supports the cylindrical portion **70132** of the replenishment port shutter **7013**. A plurality of projection portions **70125a** and **70125b** are also provided on the cylindrical portion **7011a** of the shutter supporting portion **7011**. The plurality of projection portions **70125a** and **70125b** are positioned below the projection portion **70135a** illustrated on the right side in FIG. **10A** in the gravity direction. The projection portion **70125b** allows the projection portion **70135a** illustrated on the right side in FIG. **10A** to pass through by rotational movement. In contrast, the projection portion **70135a** illustrated on the left side in FIG. **10A** is positioned at the same height as the projection portion **70135a** illustrated on the right side of FIG. **10A**, and extends downward to such a height as to overlap with the projection portions **70125a** and **70125b**. Therefore, the projection portion **70125b** comes into contact with the projection portion **70135a** illustrated on the left side in FIG. **10A** depending on the rotation angle, that is, rotational position of the replenishment port shutter **7013**, and thus restricts rotational movement of the projection portion **70135a** illustrated on the left side in FIG. **10A**.

(116) In addition, before the replenishment port shutter **7013** rotates in an R1 direction, the projection portion **70125a** comes into contact with the projection portion **70135a** illustrated on the left side, and restricts the rotational movement of the projection portion **70135a** in an R2 direction. In addition, the projection portion **70135a** illustrated on the right side in FIG. **10A** abuts the locking member **7014**, and thus the rotational movement of the locking member **7014** in the R1 direction is

restricted. In addition, after the replenishment port shutter **7013** has rotated in the R1 direction, the projection portion **70135b** abuts the locking member **7014** that has moved to a locking position, and thus restricts the rotational movement of the locking member **7014** in the R2 direction. In addition, the projection portion **70135a** illustrated on the right side in FIG. **10A** abuts the projection portion **70125b**, and thus restricts further rotational movement of the projection portion **70135a** in the R1 direction. To be noted, the rotation direction of the replenishment port shutter **7013** is the R1 direction when attaching the toner pack **40**, and is the R2 direction when detaching the toner pack **40**.

(117) The locking member **7014** is a member that restricts the rotation of the replenishment port shutter **7013**. FIG. **11A** illustrates a state in which the locking member **7014** is in the locking position, and FIG. **11B** illustrates a state in which the locking member **7014** is in a lock releasing position. The locking member **7014** can be switched between the locking position serving as a restricting position and the lock releasing position serving as an allowing position by moving in the up-down direction. As illustrated in FIGS. **9B** and **11A**, when the locking member **7014** abuts the projection portion **70135a** of the replenishment port shutter **7013** in the locking position, the rotation of the replenishment port shutter **7013** is restricted. When the locking member **7014** moves to the lock releasing position as illustrated in FIG. **11B**, the locking member **7014** retracts from the movement trajectory of the projection portion **70135a** drawn when the replenishment port shutter **7013** moves, and thus the rotation of the replenishment port shutter **7013** is allowed.

(118) (1-7) Pressing Mechanism of Locking Member

(119) FIG. **13** illustrates a pressing mechanism **600** that moves the locking member **7014** between the locking position and the lock releasing position. The pressing mechanism **600** includes a motor **601**, an input gear **602**, a cam gear **603**, and an advancing/retracting pin **604**. The input gear **602** is a crossed helical gear attached to an output shaft of the motor **601**. The cam gear **603** includes a gear portion **6032** constituted by a helical gear that engages with the input gear **602**, and a cam portion **6031** for reciprocating the advancing/retracting pin **604**.

(120) The advancing/retracting pin **604** is supported by a holding member so as to be linearly movable in the gravity direction and an opposite direction thereto in the vertical direction. When the motor **601** rotates, the cam gear **603** is rotated via the input gear **602**, the advancing/retracting pin **604** reciprocates in the up-down direction by being pressed by the cam portion **6031**, and in accordance with this, the locking member **7014** also moves up and down between the locking position and the lock releasing position. FIG. **13** illustrates a locked state.

(121) To be noted, although a combination of a helical gear and a crossed helical gear has been used as the drive transmission configuration of the pressing mechanism **600** of the present embodiment, the configuration is not limited to this as long as the rotation of the motor can be converted into a linear motion. For example, a bevel gear may be used, or the input gear **602** may be removed and the cam gear **603** may be directly driven by the motor **601**. In addition, an actuator that outputs a linear motion such as a solenoid may be used as the drive source instead of the motor **601**.

(122) In addition, each member constituting the pressing mechanism **600** illustrated in FIG. **13** is supported by the frame member **609** of the printer body **100**, and the advancing/retracting pin **604** is supported by a guide portion **604a** so as to be capable of reciprocating in the up-down direction. The guide portion **604a** is provided in the casing of the printer body **100**. Meanwhile, a pivot shaft **7014a** of the locking member **7014** is held by a holding portion provided on the frame member **8010** of the toner receiving unit **801** so as to be pivotable and slidable in the vertical direction. Therefore, when replacing the process cartridge **20**, the locking member **7014** is also replaced, and the pressing mechanism **600** is left in the printer body **100**. The pivot shaft **7014a** and the advancing/retracting pin **604** are formed as separate members. When the locking member **7014** is in the lock releasing position, the advancing/retracting pin **604** is away from the locking member **7014**, and the process cartridge **20** is detached from the body with the advancing/retracting pin **604**.

left in the body. However, the configuration is not limited to this, and for example, the pivot shaft **7014a** of the locking member **7014** may be supported by the printer body **100**.

(123) (1-8) Procedure of Replenishment Operation Using Toner Pack

(124) A procedure of the operation performed when detaching the toner pack **40** after attaching the toner pack **40** to the replenishment container attaching portion **701** and replenishing toner will be described on the basis of the configuration of the toner pack **40**, the replenishment container attaching portion **701**, and the pressing mechanism **600** described above. FIG. **10A** is a top view of the replenishment container attaching portion **701** when the replenishment port **8012** is in the closed state, and FIG. **10B** is a top view of the replenishment container attaching portion **701** when the replenishment port **8012** is in the open state. FIG. **10C** is a perspective view of the replenishment container **701** in a state in which the replenishment port **8012** is in the open state.

(125) As illustrated in FIG. **10A**, the replenishment port shutter **7013** in the closed state is fixed so as to be unrotatable with respect to the replenishment port **8012** by the projection portion **70135a** abutting the locking member **7014** positioned in the locking position in the rotation direction. At this time, the lid portion **70131** of the replenishment port shutter **7013** completely blocks the replenishment port **8012**. In addition, the leaf springs **70151** and **70152** of the rotation detection portion **7015** are separated from each other, and the rotation detection portion **7015** is in the disconnected state.

(126) When inserting the toner pack **40** in the replenishment container attaching portion **701**, the user aligns the cutout portions of the discharge portion **42** of the toner pack **40** and the shutter member **41** illustrated in FIG. **12** with the replenishment port **8012** and the lid portion **70131** of the replenishment port shutter **7013** and inserts the toner pack **40**. In this case, the engagement surface **42s** of the discharge portion **42** engages with an engagement surface **7013s** illustrated in FIG. **9C**, which is a side surface of the lid portion **70131**, and the engagement surface **41s** of the shutter member **41** engages with an engagement surface **8012s** illustrated in FIG. **9C**, which is provided on an outer peripheral portion of the replenishment port **8012**. At this time, the discharge portion **42** engaging with the lid portion **70131** of the replenishment port shutter **7013** is unrotatable until the lock of the replenishment port shutter **7013** by the locking member **7014** is released later, and becomes rotatable together with the replenishment port shutter **7013** after the release of the lock. In addition, the shutter member **41** of the toner pack **40** is in an unrotatable state by engaging with the replenishment port **8012** fixed to the frame member **8010** of the toner receiving unit **801**. To be noted, as a different engagement mechanism of the lid portion **70131** and the discharge portion **42**, a projection portion projecting upward may be provided on the upper surface of the lid portion **70131** and a recess portion that engages with this projection portion may be provided on a lower surface **42b** of the discharge portion **42** illustrated in FIG. **12**.

(127) In addition, by inserting the toner pack **40**, the contact portion **45a** of the memory unit **45** illustrated in FIGS. **7A** and **7B** comes into contact with the contact portion **70133** of the replenishment container attaching portion **701**, and information stored in the memory unit **45** is read by the controller **90** of the image forming apparatus 1. The memory unit **45** stores information indicating whether or not toner is in the toner pack **40**, that is, whether or not the toner pack **40** has been already used. This information will be also referred to as a brand-new product flag. When the controller **90** reads the brand-new product flag and determines that the toner pack **40** currently attached includes toner, that is, the toner pack **40** currently attached has not been used, the controller **90** controls the pressing mechanism **600** to push up the locking member **7014**. As a result of this, the locking member **7014** moves from the locking position to the lock releasing position illustrated in FIG. **11B**.

(128) In the state in which the locking member **7014** has moved to the lock releasing position, the locking member **7014** is separated from the projection portion **70135a** of the replenishment port shutter **7013**, and thus the replenishment port shutter **7013** becomes rotatable in the R1 direction of FIGS. **10A** and **10B**. However, since the projection portion **70125a** provided on the frame member

8010 of the toner receiving unit **801** interferes with the projection portion **70135a** illustrated in FIG. **10A**, rotation of the replenishment port shutter **7013** in the R2 direction is restricted. That is, in FIG. **10A**, the projection portions **70125a** and **70125b** are positioned below the projection portions **70135a** and **70135b** such that the projection portions **70135a** and **70135b** can move and pass the projection portions **70125a** and **70125b** in the rotation direction.

(129) When the user grabs the toner pack **40** and rotates the discharge portion **42** or a portion of the bag member **43** close to the discharge portion **42** by **1800** in the R1 direction, a state illustrated in FIG. **10B** is taken. The replenishment port shutter **7013** also rotates by 180° together with the discharge portion **42** of the toner pack **40**, thus the lid portion **70131** moves from the position covering the replenishment port **8012**, and the replenishment port **8012** is exposed. The side surface of the lid portion **70131** is pushed by the engagement surface **42s**, which is a part of the discharge portion **42** that is rotating, and thus the lid portion **70131** rotationally moves together with the engagement surface **42s**. In addition, as a result of the discharge portion **42** rotating by 180° in a state in which the shutter member **41** is fixed, the discharge port **42a** of the toner pack **40** illustrated in FIG. **8B** is exposed, and faces the replenishment port **8012**. As a result of this, the inner space of the toner pack **40** and the inner space of the toner receiving unit **801** communicate with each other through the discharge port **42a** and the replenishment port **8012**, and the toner stored in the bag member **43** flows down into the toner storage portion **8011**.

(130) The toner having fallen into the toner storage portion **8011** is, as described above, conveyed inside the toner receiving unit **801**, reaches the developer container **32**, and becomes available for a developing process. To be noted, a configuration in which the developing unit **802** can perform the developing process as long as toner of an amount required for maintaining the image quality remains in the developer container **32** even before the newly replenished toner reaches the developer container **32** may be employed. That is, a configuration in which toner can be supplied to the developer container from a replenishment container disposed outside the image forming apparatus regardless of whether or not the image forming operation by the image forming portion **10** illustrated in FIG. **1A** is being performed may be employed.

(131) In addition, the projection portion **70125b** is disposed so as to abut the projection portion **70135a** of the replenishment port shutter **7013** when the replenishment port shutter **7013** is rotated by **1800** in the R1 direction from the state of FIG. **10A** as illustrated in FIG. **10B**. That is, the projection portion **70125b** is also positioned below the projection portions **70135a** and **70135b** similarly to the projection portion **70125a**. As a result of this, pivoting of the replenishment port shutter **7013** beyond 180° in the R1 direction is restricted. At the same time, the projection portion **70135a** of the replenishment port shutter **7013** presses the leaf spring **70152** of the rotation detection portion **7015**, and the distal end portion **701521** thereof is brought into contact with the leaf spring **70151**. When the rotation detection portion **7015** is in the connected state, the controller **90** recognizes that the replenishment port shutter **7013** has transitioned to the open state, and operates the pressing mechanism **600** to move the locking member **7014** again to the locking position. Then, the locking member **7014** engages with the projection portion **70135b** of the replenishment port shutter **7013** to restrict the rotation in the R2 direction, and thus the replenishment port shutter **7013** and the toner pack **40** both becomes unrotatable in any direction.

(132) Further, in the state of FIG. **10B** in which the discharge portion **42** of the toner pack **40** and the replenishment port shutter **7013** have been rotated by 180°, the lid portion **70131** of the replenishment port shutter **7013** covers an upper portion of the shutter member **41** of the toner pack **40**. Therefore, when it is attempted to pick up the toner pack **40** from the replenishment container attaching portion **701**, the shutter member **41** interferes with the lid portion **70131**, and the movement of the toner pack **40** is restricted. Therefore, detachment of the toner pack **40** from the replenishment container attaching portion **701** is suppressed unless the user performs the detachment operation of the toner pack **40** in accordance with a predetermined procedure that will be described below.

(133) After the start of discharge of toner from the toner pack **40**, if a condition for determining that the discharge of toner has been completed is satisfied, the controller **90** operates the pressing mechanism **600** to move the locking member **7014** to the lock releasing position. In the present embodiment, completion of the discharge of toner is determined on the basis of the time elapsed from the time point at which the rotation detection portion **7015** has transitioned to the connected state.

(134) After the locking member **7014** has moved to the lock releasing position, the user can detach the toner pack **40** by following a procedure reversed from the procedure performed when attaching the toner pack **40**. That is, the user grabs the discharge portion **42** of the toner pack **40** or a part of the bag member **43** close to the discharge portion **42**, and rotates the toner pack **40** by 180° in the R2 direction, which is opposite to the direction of rotation at the time of attachment. In this case, the replenishment port shutter **7013** rotates by 180° together with the discharge portion **42**, and the replenishment port **8012** is covered by the lid portion **70131** of the replenishment port shutter **7013** as illustrated in FIG. **10A**. In addition, the projection portion **70135a** of the replenishment port shutter **7013** illustrated on the left side in FIG. **10A** abuts the projection portion **70125a**, and thus the rotation of the replenishment port shutter **7013** beyond 180° in the R2 direction is restricted.

(135) In the state in which the discharge portion **42** of the toner pack **40** has been rotated by 180° in the R2 direction, the position of the cutout portion of the discharge portion **42** and the position of the cutout portion of the shutter member **41** are aligned as illustrated in FIG. **12**. Therefore, even if the toner pack **40** is moved upward, the shutter member **41** does not interfere with the lid portion **70131** of the replenishment port shutter **7013**, and therefore the user can detach the toner pack **40** from the replenishment container attaching portion **701** by grabbing and lifting the toner pack **40**.

(136) To be noted, in the course of rotating the replenishment port shutter **7013** by 180° in the R2 direction, the projection portion **70135a** is separated from the leaf spring **70152**, and the rotation detection portion **7015** returns to the disconnected state. Then, the controller **90** recognizes that the replenishment port shutter **7013** has transitioned to the closed state, and operates the pressing mechanism **600** to move the locking member **7014** to the locking position. As a result of this, the replenishment container attaching portion **701** transitions back to the initial state as before the toner replenishment operation is performed. For example, the controller **90** may determine that a predetermined condition to move the locking member **7014** to the lock releasing position is satisfied when a predetermined time has elapsed after the rotation detection portion **7015** has transitioned to the connected state. To be noted, the trigger for moving the locking member **7014** to the locking position may be loss of connection between the contact portion **70133** of the replenishment container attaching portion **701** and the contact portion **45a** of the toner pack **40** illustrated in FIG. **7** caused by detachment of the toner pack **40** from the replenishment container attaching portion **701**.

(137) Although the positional relationship is set such that the discharge port **42a** of the toner pack **40** and the replenishment port **8012** communicate with each other after the rotation by 180° in the present embodiment, the rotation angle required for the communication may be changed as long as the detachment of the toner pack **40** is made possible by an operation similar to that of the present embodiment.

(138) (1-9) Panel

(139) Next, a panel **400** will be described. For example, the Panel **400** is provided on the front surface of the casing of the printer body **100** as illustrated in FIGS. **1B** and **14A** to **14C**. The panel **400** is an example of a display portion that displays information related to the remainder amount of toner in the developer container **32**, or a remaining capacity of the developer container **32**. The panel **400** is constituted by a liquid crystal panel including a plurality of indicators. In the present embodiment, three indicators **4001**, **4002**, and **4003** are arranged in this order from the upper side to the lower side in the vertical direction. The panel **400** indicates the amount of toner that can be added to the developer container **32** for replenishment by the display of the indicators **4001** to **4003**.

that changes stepwise. The controller **90** constantly updates the display of the panel **400** on the basis of replenishment operation completion recognition that will be described later. In addition, in the case where the completion of the replenishment operation is not reflected on the toner remainder amount, the toner remainder amount may be detected subsequently, and the display of the panel **400** may be updated. For example, in the case where the controller **90** has detected by an optical sensor denoted by **51a** and **51b** that actually the toner has not been sufficiently replenished after the light of the indicator **4002** has been turned on, the controller **90** updates the display of the panel **400** by turning off the light of the indicator **4002**. In addition, the lowermost indicator **4003** also indicates whether the toner in the developer container **32** is at a Low level or at an Out level. To be noted, the Low level is a level at which, although the developer container **32** needs to be replenished with toner, at least toner of an amount required for maintaining the image quality remains and the image forming operation can be still performed. The Out level is a level at which almost no toner remains in the developer container **32** and the image forming operation cannot be performed.

(140) In the illustrated configuration example of the panel **400**, lights of the three indicators **4001** to **4003** all being off indicates that the toner in the developer container **32** is at the Out level. This state serves as a fourth state.

(141) In the case where only the light of the lower indicator **4003** is on as illustrated in FIG. **14A**, the toner remainder amount in the developer container **32** is at the Low level. In this state, lights of two of the indicators are off, and therefore it can be seen that toner of an amount corresponding to two toner packs **40** can be added for replenishment. This state serves as a third state. In addition, it can be also seen that toner of an amount corresponding to two toner packs **40** can be added for replenishment from the fact that lights of number panels “+1” and “+2” next to the indicators are on.

(142) In the case where lights of the middle and lower indicators **4002** and **4003** are on and the light of the upper indicator **4001** is off as illustrated in FIG. **14B**, the toner remainder amount in the developer container **32** is larger than that of the Low level and smaller than that of a Full level in which the developer container **32** is full. In this state, the light of one indicator is off, and therefore it can be seen that, for example, toner of an amount corresponding to one toner pack **40** can be added for replenishment. This state serves as a second state. In addition, it can be also seen that toner of an amount corresponding to one toner pack **40** can be added for replenishment from the fact that the light of the number panel “+1” next to an indicator is on and the light of the number panel “+2” next to an indicator is off.

(143) In the case where all the three indicators **4001** to **4003** are on as illustrated in FIG. **14C**, the toner remainder amount in the developer container **32** is at the Full level. In this state, light of no indicator is off, and therefore it can be seen that, for example, no toner can be added for replenishment from the toner pack **40**. This state serves as a first state. In addition, it can be also seen that no toner can be added for replenishment from the toner pack **40** from the fact that the lights of the number panels “+1” and “+2” next to the indicators are off.

(144) To be noted, the panel **400** illustrated in FIGS. **14A** to **14C** is an example of a display portion whose display content changes in accordance with the toner remainder amount in the developer container **32**, and a different configuration may be employed. For example, the panel may be constituted by a combination of a light source such as an LED or an incandescent lamp and a diffusion lens instead of a liquid crystal panel. Alternatively, a configuration in which the indicators are omitted and only the number panels are used or a configuration in which the number panels are omitted and only the indicators are used may be employed.

(145) In addition, the number and display method of the indicators of the panel **400** may be appropriately modified. For example, the user may be prompted to replenish toner by flickering the light of the lower indicator in the case where the toner remainder amount in the developer container **32** is at the Low level.

(2) First Modification Example

(146) Next, a first modification example in which a toner bottle unit having a bottle shape is used as another example of a replenishment container instead of the toner pack having a bag shape will be described with reference to FIGS. **15A** to **15D**. To be noted, this toner bottle unit is configured to be attachable to and detachable from the replenishment container attaching portion **701** described above similarly to the toner pack **40** described above. Therefore, description of elements of the image forming apparatus that are the same as in the first embodiment will be omitted.

(147) (2-1) Configuration of Toner Bottle Unit

(148) FIG. **15A** is a perspective view of a toner bottle unit **900** illustrating the external appearance thereof, and FIG. **15B** is a perspective view of the toner bottle unit **900** after discharge of toner. FIG. **15C** is a diagram illustrating the toner bottle unit **900** as viewed from the lower side of a piston, and FIG. **15D** is a section view of the toner bottle unit **900** taken along a line D-D of FIG. **15C**.

(149) In addition, FIG. **16A** is a perspective view of the toner bottle unit **900** in which illustration of an outer cylinder **903** illustrated in FIG. **15A** is omitted, and FIG. **16B** is a perspective view of the toner bottle unit **900** after the discharge of toner in which illustration of the outer cylinder **903** is omitted. FIG. **16C** is a diagram illustrating a state before a push-in operation of a component related to push-in detection of the toner bottle unit **900**, and FIG. **16D** is a diagram illustrating a state after the push-in operation of the component related to push-in detection. FIG. **16E** is a diagram illustrating a state before a rotating operation of a component related to rotation detection of the toner bottle unit **900**, and FIG. **16F** is a diagram illustrating a state after the rotating operation of the component related to the rotation detection of the toner bottle unit **900**.

(150) As illustrated in FIGS. **15A** and **15D**, the toner bottle unit **900** roughly includes the outer cylinder **903**, an inner cylinder **901**, a piston **902**, a shutter member **904**, and a memory unit **911**. The outer cylinder **903** and the inner cylinder **901** have cylindrical shapes, the inner cylinder **901** is fit inside the outer cylinder **903**, and the piston **902** is fit inside the inner cylinder **901** and is slidable with respect to the inner cylinder **901**. In the description below, the direction in which the piston **902** moves, that is, the direction of the axis of the outer cylinder **903** and the inner cylinder **901** will be referred to as the axial direction of the toner bottle unit **900**. In addition, the piston **902** serves as an example of a pressing member.

(151) The inner cylinder **901** includes a toner storage portion **9014** that has a cylindrical shape and stores toner, a bottom portion **9013** provided on a first end side in the axial direction, and a discharge port **9011** provided in the bottom portion **9013**. The inner cylinder **901** has a cylindrical shape in which a first end portion of the toner storage portion **9014** in the axial direction is closed by the bottom portion **9013**. An opening portion **9012** is provided on a second end side of the toner storage portion **9014**, and the piston **902** is inserted in the toner storage portion **9014** through the opening portion **9012**. In addition, a weight member **905** having a spherical shape and movable in the toner storage portion **9014** is included in the inner cylinder **901**.

(152) The outer cylinder **903** includes an inner cylinder accommodating portion **9034** having a cylindrical shape that accommodates the toner storage portion **9014** of the inner cylinder **901** therein, a bottom portion **9033** provided on the first end side in the axial direction, and a discharge port **9031** provided in the bottom portion **9033**. The outer cylinder **903** has a cylindrical shape in which a first end portion of the inner cylinder accommodating portion **9034** in the axial direction is closed by the bottom portion **9033** similarly to the inner cylinder **901**, and holds the inner cylinder **901** relatively unmovably. An opening portion **9032** through which the piston **902** is inserted is provided on the second end side of the inner cylinder accommodating portion **9034**.

(153) The discharge port **9011** of the inner cylinder **901** has a thin cylindrical shape extending from the bottom portion **9013** toward the first end side in the axial direction. The discharge port **9031** of the outer cylinder **903** is provided at a position corresponding to the discharge port **9011** of the inner cylinder **901** in the bottom portion **9033**. The discharge port **9031** of the outer cylinder **903** is

a discharge port through which the toner stored in the toner storage portion **9014** is discharged to the outside of the toner bottle unit **900**. To be noted, a retracting space **9013a** for the weight member **905** to retract into so as not to block the discharge port **9011** when pushing the piston **902** in is provided adjacent to the discharge port **9011** of the inner cylinder **901**.

(154) To be noted, the bottom portion **9013** of the inner cylinder **901** has an inclined shape whose sectional area is smaller on the discharge port side in the axial direction, particularly a conical shape whose inner diameter is smaller on the discharge port side in the axial direction. The bottom portion **9033** of the outer cylinder **903** opposing the bottom portion **9013** of the inner cylinder **901** also has a similar inclined shape. The discharge port **9011** of the inner cylinder **901** and the retracting space **9013a** are provided at a vertex portion of the inclined shape of the bottom portion **9033**. The weight member **905** has a spherical shape, and is guided by the bottom portion **9013** to move to the retracting space **9013a** by the gravity.

(155) The piston **902** includes an elastic member **906** attached to a first end portion **9023** on the first end side in the axial direction, that is, on the discharge port side, and a push-in rib **9021** provided in the vicinity of a second end portion **9022** on the second end side, which is a part that the user pushes when pushing in the piston **902**. The elastic member **906** is configured to come into contact with the inner circumferential surface of the toner storage portion **9014** with no gap therebetween, and has a function of suppressing leakage of toner when pushing in the piston **902**. In addition, the push-in rib **9021** is a projection shape projecting outward in the radial direction from the outer circumferential surface of the piston **902**.

(156) The configuration of the shutter member **904** is similar to that of the shutter member **41** provided in the toner pack **40** described above. That is, as illustrated in FIG. **15C**, the shutter member **904** has a shape of a disk partially cut out and relatively rotatable with respect to the outer cylinder **903**. A side surface of the shutter member **904** extending in the thickness direction in the cutout portion functions as an engagement surface **904s**. Meanwhile, the outer cylinder **903** also has a shape with a cutout. The outer cylinder **903** includes an engagement surface **903s** parallel to the engagement surface **904s** in the cutout portion. In addition, the discharge port **9031** is provided at a position away from the engagement surface **903s** by approximately 180° in the circumferential direction of the outer cylinder **903**.

(157) FIG. **15C** illustrates a state in which the discharge port **9031** is already exposed, but in the state at the time when the toner bottle unit **900** is shipped, the positions of the cutout engagement surfaces **903s** and **904s** of the shutter member **904** and the outer cylinder **903** are aligned. In this case, the discharge port **9031** is covered by the shutter member **904**, and the sealed state of the toner storage portion **9014**, that is, the closed state is maintained. As illustrated in FIG. **15C**, when the shutter member **904** is rotated by 180° with respect to the outer cylinder **903**, the discharge port **9031** is exposed through the cutout portion of the shutter member **904**, thus the sealing of the toner storage portion **9014** is cancelled, and it becomes possible to discharge the toner. This state corresponds to the open state. The configuration of the discharge port **9031**, the engagement surface **903s**, and the shutter member **904** are basically the same as the configuration described with reference to FIGS. **7A** to **8C** and **12**.

(158) A memory unit **911** serving as a storage portion that stores information of the toner bottle unit **900** is attached to a portion near the discharge port **9031** of the outer cylinder **903**. The memory unit **911** includes a plurality of metal plates **9111**, **9112**, and **9113** illustrated in FIG. **16A** exposed to the outside of the toner bottle unit **900** as a contact portion **911a** that comes into contact with the contact portion **70133** of the replenishment container attaching portion **701** illustrated in FIG. **9A**.

(159) (2-2) Push-in Detection Mechanism of Piston

(160) In addition, as illustrated in FIGS. **16A** and **16C**, as a push-in detection mechanism that detects a push-in operation of the piston **902**, a push-in detection rod **907**, a first contact plate **908**, and a second contact plate **909** are disposed between the outer cylinder **903** and the inner cylinder **901**. The push-in detection rod **907** is formed from an insulating material such as a resin, and the

first contact plate **908** and the second contact plate **909** are formed from a conductive material such as metal. The push-in detection rod **907** includes a contact cancelling portion **9072** on the first end side in the axial direction, that is, on the discharge port side, and a piston contact portion **9071** capable of abutting the push-in rib **9021** of the piston **902** on the second end side in the axial direction. The push-in detection rod **907** moves in the axial direction in accordance with the push-in operation of the piston **902** as a result of the push-in rib **9021** pressing the piston contact portion **9071**.

(161) For example, the push-in detection rod **907** is fit in a groove shape defined in the axial direction in the outer circumferential surface of the inner cylinder **901** or the inner circumferential surface of the outer cylinder **903**, and is thus held so as to be movable in the axial direction with respect to the inner cylinder **901** and the outer cylinder **903** while the movement of the push-in detection rod **907** in a direction perpendicular to the axial direction is restricted. In addition, the piston contact portion **9071** has a shape bent perpendicularly to the axial direction, that is, a shape bent into an L shape such that the push-in rib **9021** more reliably abuts the piston contact portion **9071**. To be noted, although the push-in rib **9021** is provided to extend all around the piston **902** on the outer circumferential surface of the piston **902** in FIG. **16A**, a configuration in which the push-in rib **9021** is formed in only a position corresponding to the piston contact portion **9071** in the circumferential direction may be employed.

(162) The first contact plate **908** and the second contact plate **909** are metal plates whose connected state and disconnected state are switched in accordance with the position of the push-in detection rod **907** formed from an insulating resin. A brand-new product detection method of the toner bottle unit **900** using the first contact plate **908** and the second contact plate **909** will be described later.

(163) In addition, a cylinder cover **910** illustrated in FIG. **15A** is provided at an end portion of the outer cylinder **903** on the opening portion side so as to suppress dropping of the push-in detection rod **907**. That is, the cylinder cover **910** defining the opening portion **9032** of the outer cylinder **903** is narrowed such that the edge of the opening portion **9032** is further on the inside than the outer edge of the piston contact portion **9071** illustrated in FIG. **16B** in the radial direction as illustrated in FIG. **15D**. Therefore, even when a force to move the push-in detection rod **907** toward the opening portion side in the axial direction is applied, the piston contact portion **9071** interferes with the cylinder cover **910**, and therefore the push-in detection rod **907** does not drop from the toner bottle unit **900**.

(164) (2-3) Brand-new/Used Determination of Toner Bottle Unit

(165) Next, a configuration for detecting whether the toner bottle unit **900** is unused, that is, brand-new, or used when attaching the toner bottle unit **900** to the replenishment container attaching portion **701** will be described. As illustrated in FIGS. **16C** and **16D**, the contact cancelling portion **9072** of the push-in detection rod **907** is positioned near the first contact plate **908** and the second contact plate **909**.

(166) FIG. **16C** corresponds to a state before the piston push-in illustrated in FIG. **16A**, and the first contact plate **908** and the second contact plate **909** are in contact with each other and thus are in the connected state. At this time, it is preferable that the one of the first contact plate **908** and the second contact plate **909** that are formed from metal is formed in a leaf spring shape and is in pressure contact with the other. In addition, for example, the conduction between the first contact plate **908** and the second contact plate **909** can be made more reliable by applying a conductive grease on the contact surfaces of the first contact plate **908** and the second contact plate **909**.

(167) FIG. **16D** corresponds to a state after the piston push-in illustrated in FIG. **16B**, and the first contact plate **908** and the second contact plate **909** are in the disconnected state. In this state, the contact cancelling portion **9072** of the push-in detection rod **907** pushed in by the push-in rib **9021** gets between the first contact plate **908** and the second contact plate **909**, and thus physically separate the first contact plate **908** and the second contact plate **909**. At least the contact cancelling portion **9072** of the push-in detection rod **907** is formed from an insulating material, and the

conduction between the first contact plate **908** and the second contact plate **909** is disconnected in the state of FIG. **16D** in which the contact cancelling portion **9072** is present therebetween.

(168) The first contact plate **908** and the second contact plate **909** are connected to different metal plates among the plurality of metal plates **9111** to **9113**, at end portions opposite to end portions that come into contact with the contact cancelling portion **9072** of the push-in detection rod **907**. Here, the first contact plate **908** is connected to the metal plate **9111**, and the second contact plate **909** is connected to the metal plate **9113**. In this case, whether the toner bottle unit **900** is in a state before the piston push-in or in a state after the piston push-in, that is, whether the toner bottle unit **900** is unused or used can be determined by detecting whether a current is generated when a minute voltage is applied between the metal plates **9111** and **9113**. That is, in a state in which the toner bottle unit **900** is attached to the replenishment container attaching portion **701**, the controller **90** of the image forming apparatus 1 can determine whether the toner bottle unit **900** is used or unused, on the basis of presence/absence of conduction between the metal plates **9111** and **9113**. In addition, the controller **90** can determine that the replenishment operation by the user has been finished, on the basis of disconnection between the first contact plate **908** and the second contact plate **909**. On the basis of this determination, the controller **90** performs display control of the panel **400** described above. In addition, the controller **90** writes, in the memory unit **45** and in accordance with the change in the conduction between the metal plates **9111** and **9113**, a brand-new product flag indicating whether or not the toner bottle unit **900** is used. The brand-new product flag being 1 corresponds to being brand-new, and the brand-new product flag being 0 corresponds to having been used.

(169) To be noted, in the case of the configuration described above, the memory unit **911** is preferably disposed in a circuit connecting the metal plates **9111** and **9112**. As a result of this, the controller **90** of the image forming apparatus can access the memory unit **911** through the metal plates **9111** and **9112** while monitoring the push-in operation of the toner bottle unit **900** via the metal plates **9111** and **9113**.

(170) (2-4) Rotation Detection of Toner Bottle Unit

(171) Next, a method for detecting the rotation of the toner bottle unit **900** will be described with reference to FIGS. **16E** and **16F**. To be noted, the rotation detection method of the present embodiment is the same as in the embodiment described above in which the toner pack **40** is used, except that the shutter member **904** that seals the discharge port of the replenishment container is attached to the outer cylinder **903** of the toner bottle unit **900**.

(172) As illustrated in FIGS. **16E** and **16F**, the two conductive leaf springs **70151** and **70152** are provided in the replenishment container attaching portion **701** of the process cartridge **20** as the rotation detection portion **7015**. In addition, the projection portion **70135b** is provided on an outer peripheral portion of the replenishment port shutter **7013**.

(173) As illustrated in FIG. **16E**, in a state before the toner bottle unit **900** inserted in the replenishment container attaching portion **701** is rotated, the distal end portion **701521** of the leaf spring **70152** is not in contact with the leaf spring **70151**, and therefore the rotation detection portion **7015** is in the disconnected state. That is, no current flows when a minute voltage is applied between the leaf springs **70151** and **70152**. As illustrated in FIG. **16F**, when the toner bottle unit **900** is rotated by 180°, the leaf spring **70152** is pressed by the projection portion **70135a**, thus the distal end portion **701521** comes into contact with the leaf spring **70151**, and the rotation detection portion **7015** is switched to the connected state. In this state, a current flows when a minute voltage is applied between the plate springs **70151** and **70152**. The controller **90** of the image forming apparatus 1 recognizes whether or not the discharge port **9031** of the toner bottle unit **900** and the replenishment port **8012** of the replenishment container attaching portion **701** communicate with each other, on the basis of whether the rotation detection portion **7015** is in the connected state or in the disconnected state.

(174) (2-5) Flow of Replenishment Operation Using Toner Bottle Unit

(175) A series of operation for detaching the toner bottle unit **900** after attaching the toner bottle unit **900** to the replenishment container attaching portion **701** and replenishing toner will be described. To be noted, description of elements same as in the embodiment described above where the toner pack **40** is used will be omitted.

(176) First, the user attaches an unused toner bottle unit **900** to the replenishment container attaching portion **701**. Specifically, the cutout engagement surfaces **903s** and **904s** of the outer cylinder **903** and the shutter member **904** illustrated in FIG. **15C** are aligned with the replenishment port **8012** and the lid portion **70131** of the replenishment port shutter **7013**, and the toner bottle unit **900** is inserted. In this case, the engagement surface **903s** of the outer cylinder **903** engages with the engagement surface **7013s**, which is a side surface of the lid portion **70131**, and the engagement surface **904s** of the shutter member **904** engages with the engagement surface **8012s** provided on an outer peripheral portion of the replenishment port **8012**. At this time, the outer cylinder **903** engaging with the lid portion **70131** of the replenishment port shutter **7013** is unrotatable until the lock of the replenishment port shutter **7013** by the locking member **7014** is released later, and becomes rotatable together with the replenishment port shutter **7013** after the release of the lock. In addition, the shutter member **904** is in an unrotatable state by engaging with the replenishment port **8012** fixed to the frame member **8010** of the toner receiving unit **801**. Further, the leaf springs **70151** and **70152** of the rotation detection portion **7015** are away from each other, and the rotation detection portion **7015** is in the disconnected state as illustrated in FIG. **16E**.

(177) In the case where an unused toner bottle unit **900** is inserted in the replenishment container attaching portion **701**, the controller **90** recognizes that the toner bottle unit **900** is brand-new by the brand-new product detection mechanism described above. The controller **90** may recognize the conduction between the metal plates **9111** and **9113** or make determination by reading the brand-new product flag in the memory unit **45**. The brand-new product flag being 1 corresponds to being brand-new, and the brand-new product flag being 0 corresponds to having been used. In this case, the controller **90** operates the pressing mechanism **600** to move the locking member **7014** to the lock releasing position, and thus the toner bottle unit **900** becomes rotatable.

(178) Then, when the user grabs the toner bottle unit **900** and rotates the toner bottle unit **900** by 180°, the shutter member **904** and the replenishment port shutter **7013** are opened, and the discharge port **9031** of the toner bottle unit **900** and the replenishment port **8012** of the replenishment container attaching portion **701** communicate with each other. The operation of opening the shutter member **904** and the replenishment port shutter **7013** in accordance with the rotation of the toner bottle unit **900** is similar to the case of the toner pack **40** described with reference to FIGS. **10A** and **10B**.

(179) As illustrated in FIG. **16F**, in a state in which the toner bottle unit **900** is rotated by 180°, the distal end portion **701521** of the leaf spring **70152** pressed by the projection portion **70135b** of the replenishment port shutter **7013** comes into contact with the leaf spring **70151**. When the rotation detection portion **7015** is switched to the connected state in this manner, the controller **90** of the image forming apparatus 1 detects that the rotation operation of the toner bottle unit **900** has been performed. That is, the controller **90** recognizes that the sealing by the shutter member **904** and the replenishment port shutter **7013** has been cancelled and the discharge port **42a** of the toner pack **40** and the replenishment port **8012** of the replenishment container attaching portion **701** communicate with each other. In addition, the controller **90** operates the pressing mechanism **600** to move the locking member **7014** to the locking position, and thus restricts the rotation of the toner bottle unit **900**.

(180) Next, the user presses the piston **902** of the toner bottle unit **900** to start discharge of toner. The toner having fallen into the toner storage portion **8011** is conveyed inside the toner receiving unit **801** and reaches the developer container **32**. Also in the present modification example, when the piston **902** is pushed to the deepest position, the push-in detection mechanism described above detects that the push-in operation of the piston **902** has been completed. That is, as illustrated in

FIG. 16B, the push-in rib **9021** of the piston **902** presses the piston contact portion **9071** of the push-in detection rod **907**, and thus the push-in detection rod **907** moves accompanied by the piston **902**.

(181) Then, as illustrated in FIG. 16D, the contact cancelling portion **9072** of the push-in detection rod **907** disconnects the conduction between the first contact plate **908** and the second contact plate **909**. The controller **90** of the image forming apparatus 1 recognizes the completion of the push-in of the piston **902** on the basis of the fact that no longer a current flows even if a voltage is applied between the metal plate **9111** connected to the first contact plate **908** and the metal plate **9113** connected to the second contact plate **909**. That is, in the present modification example, detection of completion of the push-in operation of the piston **902** by the push-in detection mechanism serves as a condition for determining that discharge of toner is completed. To be noted, a configuration in which the controller **90** rewrites the brand-new product flag in the memory unit **911** in the case where the conduction between the first contact plate **908** and the second contact plate **909** is disconnected, and determines that the discharge of toner has been completed on the basis of the rewriting of the brand-new flag may be employed.

(182) The controller **90** that has detected the completion of discharge of toner from the toner bottle unit **900** operates the pressing mechanism **600** again to move the locking member **7014** to the lock releasing position, and thus makes the toner bottle unit **900** rotatable. The user grabs the toner bottle unit **900** and rotates the toner bottle unit **900** by 180°. In this case, the discharge port **9031** of the toner bottle unit **900** is covered by the shutter member **904**, and the replenishment port **8012** of the replenishment container attaching portion **701** is covered by the lid portion **70131** of the replenishment port shutter **7013**. In addition, the leaf springs **70151** and **70152** are separated as illustrated in FIG. 16E, and the rotation detection portion **7015** returns to the disconnected state. Then, the controller **90** recognizes that the replenishment port shutter **7013** has been switched to the closed state, and operates the pressing mechanism **600** to move the locking member **7014** to the locking position. As a result of this, the replenishment container attaching portion **701** returns to the initial state before the toner replenishment.

(3) Second Modification Example

(183) Next, a second modification example in which the configuration of the process cartridge is different will be described. The present modification example has the same elements as in the first embodiment except for elements related to the process cartridge, and therefore description of the same elements will be omitted.

(184) (3-1) Process Cartridge

(185) FIGS. 17A to 17D are respectively a perspective view, a side view, a section view, and another section view of a process cartridge **20A** according to the present modification example. FIGS. 17C and 17D are section views taken at cutting positions respectively illustrated in FIG. 17B.

(186) As illustrated in FIGS. 17A to 17D, the process cartridge **20A** of the present modification example includes the toner receiving unit **801**, the developing unit **802**, and a drum unit **803A**. In contrast with the first embodiment, the drum unit **803A** does not include the cleaning blade **24** that cleans the surface of the photosensitive drum **21** or the waste toner chamber **8033** illustrated in FIG. 6A that accommodates waste toner. This is because a cleanerless configuration is employed in the present modification example. In the cleanerless configuration, the transfer residual toner remaining on the surface of the photosensitive drum **21** without being transferred onto the recording material is collected into the developing unit **802** and reused is employed. To be noted, for example, nonmagnetic or magnetic one-component developer is also used herein.

(187) In the illustrated example, the developing unit **802** is positioned in a lower portion of the process cartridge **20A**, and the toner receiving unit **801** and the drum unit **803A** are positioned above the developing unit **802** in the gravity direction. Although the toner receiving unit **801** and the drum unit **803A** do not overlap as viewed in the gravity direction as illustrated in FIG. 17B, the

two may be aligned in the up-down direction at least partially. In addition, the toner receiving unit **801** is disposed in the space where the cleaning blade **24** and the waste toner chamber **8033** are provided in the first embodiment. The configuration of the replenishment container attaching portion **701** provided in the toner receiving unit **801** is the same as in the first embodiment, and FIGS. **17A** to **17D** illustrate a simplified shape thereof.

(188) A laser passing space **SP** serving as a gap for the laser light **L** emitted from the scanner unit **11** illustrated in FIG. **1A** toward the photosensitive drum **21** to pass through is defined between the developing unit **802**, the drum unit **803A**, and the toner receiving unit **801**. In addition, it is preferable that, in the drum unit **803A**, a pre-exposing unit for removing the electrostatic latent image by radiating light onto the surface of the photosensitive drum **21** is disposed downstream of the transfer portion and between the transfer portion and the charging roller **22** in the rotation direction of the photosensitive drum **21**.

(189) (3-2) Behavior of Toner in Cleanerless Configuration

(190) The behavior of toner in the cleanerless configuration will be described. The transfer residual toner remaining on the photosensitive drum **21** in the transfer portion is removed in accordance with the following procedure. The transfer residual toner includes a mixture of toner that is positively charged and toner that is negatively charged but does not have enough charges. The charges on the photosensitive drum **21** after transfer is removed by the pre-exposing unit, and by causing uniform electrical discharge from the charging roller **22**, the transfer residual toner is charged again to a negative polarity. The transfer residual toner recharged to a negative polarity by the charging portion reaches the developing portion in accordance with the rotation of the photosensitive drum **21**. Then, the surface region of the photosensitive drum **21** having passed the charging portion is exposed by the scanner unit **11** and an electrostatic latent image is drawn thereon in a state in which the transfer residual toner is still attached thereto.

(191) Here, the behavior of the transfer residual toner having reached the developing portion will be described for an exposed portion and a non-exposed portion of the photosensitive drum **21** separately. In the developing portion, the transfer residual toner attached to the non-exposed portion of the photosensitive drum **21** is transferred onto the developing roller **31** due to the potential difference between the developing voltage and the potential of the non-exposed portion of the photosensitive drum **21**, that is, the dark potential, and is collected into the developer container **32**. This is because assuming that the normal charging polarity of the toner is a negative polarity, the polarity of the developing voltage applied to the developing roller **31** is relatively positive with respect to the potential of the non-exposed portion. To be noted, the toner collected into the developer container **32** is dispersed in the toner in the developer container **32** by being agitated by the agitation member **34**, and is used for the developing process again by being born on the developing roller **31**.

(192) In contrast, the transfer residual toner attached to the exposed portion of the photosensitive drum **21** is not transferred from the photosensitive drum **21** to the developing roller **31** in the developing portion, and remains on the surface of the photosensitive drum **21**. This is because assuming that the normal charging polarity of the toner is a negative polarity, the polarity of the developing voltage applied to the developing roller **31** is further negative with respect to the potential of the exposed portion, that is, light potential. The transfer residual toner remaining on the surface of the photosensitive drum **21** is born on the photosensitive drum **21** moved to the transfer portion together with other particles of toner transferred from the developing roller **31** onto the exposed portion, and is transferred onto the recording material in the transfer portion.

(193) By employing the cleanerless configuration, a space for installing a collection container for collecting the transfer residual toner or the like becomes unnecessary, thus the size of the image forming apparatus **1** can be further reduced, and the cost of printing can be reduced by reusing the transfer residual toner.

(4) Third Modification Example

(194) Next, a third modification example in which the configuration of the process cartridge is different from any embodiments described above will be described. The present modification example has the same elements as in the first embodiment except for elements related to the process cartridge, and therefore description of the same elements will be omitted.

(195) (4-1) Third Mode of Process Cartridge

(196) FIGS. **18A** to **18C** are respectively a perspective view, a side view, and a section view of a process cartridge **20B** according to the present modification example. FIG. **18C** is a section view taken at a cutting position illustrated in FIG. **18B**.

(197) As illustrated in FIGS. **18A** to **18C**, the process cartridge **20B** of the present modification example includes the developing unit **802** and the drum unit **803A**. In contrast with the third embodiment, the toner receiving unit **801** is omitted, and the replenishment container attaching portion **701**, the first conveyance member **8013**, and the second conveyance member **8014** are disposed in the developing unit **802**. That is, the present modification example is a configuration in which a replenishment container such as the toner pack **40** or the toner bottle unit **900** is attached to the replenishment port **8012** provided in the developer container **32** from the outside of the image forming apparatus to perform toner replenishment. The configuration of the replenishment container attaching portion **701** is the same as in the first embodiment, and FIGS. **18A** to **18C** illustrate a simplified shape thereof.

(198) The laser passing space **SP** serving as a gap for the laser light **L** emitted from the scanner unit **11** illustrated in FIG. **1A** toward the photosensitive drum **21** to pass through is defined between the developing unit **802**, the drum unit **803A**, and the toner receiving unit **801**. In addition, it is preferable that, in the drum unit **803A**, a pre-exposing unit for removing the electrostatic latent image by radiating light onto the surface of the photosensitive drum **21** is disposed downstream of the transfer portion and between the transfer portion and the charging roller **22** in the rotation direction of the photosensitive drum **21**. A cleanerless configuration is employed in the present modification example. The behavior of toner in the cleanerless configuration is the same as in the second modification example, and therefore the description thereof will be omitted.

(199) (5) Control System of Image Forming Apparatus

(200) FIG. **19** is a block diagram illustrating a control system of the image forming apparatus **1** according to the first embodiment. The controller **90** serving as a controller of the image forming apparatus **1** includes a central processing unit: CPU **91** serving as a processing device, a random access memory: RAM **92** used as a work area of the CPU **91**, and a nonvolatile memory **93** that stores various programs. In addition, the controller **90** includes an I/O interface **94** serving as an input/output port connected to an external device, and an A/D conversion portion **95** that converts an analog signal into a digital signal. The CPU **91** reads out and executes a control program stored in the nonvolatile memory **93**, and thus controls each component of the image forming apparatus **1**. Therefore, the nonvolatile memory **93** serves as a non-transitory computer-readable recording medium storing a control program for causing an image forming apparatus to operate by a specific method.

(201) In addition, the controller **90** is connected to a T memory **57** and a P memory **58**. The T memory **57** is a nonvolatile memory included in a replenishment container such as the toner pack **40** or the toner bottle unit **900**, and the P memory **58** is a nonvolatile memory included in the process cartridge **20**. Examples of the T memory **57** serving as a storage portion provided in the replenishment container include the memory unit **45** included in the toner pack **40** described above, and the memory unit **911** included in the toner bottle unit **900** described above. In addition, the T memory **57** also stores toner information indicating that the toner stored in the replenishment container such as the toner pack **40** or the toner bottle unit **900** can be supplied to the developer container **32** for replenishment. The toner information is, for example, information describing whether or not the toner pack **40** is unused, and describing the initial amount, expiration date, and the like of the toner. In addition, the P memory **58** stores information of the remainder amount of

toner accommodated in the developer container **32**, information of the total amount of toner that has been supplied from the replenishment container, information of the lifetime of the photosensitive member, information of the replacement timing of the process cartridge **20**, and the like.

(202) Further, the controller **90** is connected to a rotation locking mechanism **59** and the image forming portion **10**. Examples of the rotation locking mechanism **59** include the locking member **7014** illustrated in FIGS. **9A** to **9C**, **11A**, and **11B** provided in the replenishment container attaching portion **701** and the pressing mechanism **600** illustrated in FIG. **13** that moves the locking member **7014**. The image forming portion **10** includes a motor **M1** as a drive source that drives the photosensitive drum **21**, the developing roller **31**, the supply roller **33**, the agitation member **34**, and the like. To be noted, a single drive source does not have to be shared among these rotary members, and for example, the photosensitive drum **21**, the developing roller **31**, the supply roller **33**, and the agitation member **34** may be respectively driven by different motors. In addition, the image forming portion **10** also includes a power source portion for applying a voltage to each member such as the developing roller **31**, and an exposure controller that controls the scanner unit **11**.

(203) A toner remainder amount detection portion **51**, a waste toner fullness detection portion **52**, an attachment detection portion **53**, an opening/closing detection portion **54**, a rotation detection portion **55**, and a push-in detection portion **56** are connected to the input side of the controller **90**.

(204) The toner remainder amount detection portion **51** detects the remainder amount of toner accommodated in the developer container **32**, and the detection method thereof will be described later. The waste toner fullness detection portion **52** detects that the amount of waste toner accumulated in the waste toner chamber **8033** of the cleaning unit **803** illustrated in FIG. **6A** has reached a predetermined upper limit.

(205) The attachment detection portion **53** detects that a replenishment container such as the toner pack **40** is attached to the replenishment container attaching portion **701**. For example, the attachment detection portion **53** is constituted by a pressure switch that is provided in the replenishment container attaching portion **701** and outputs a detection signal when pressed by the bottom surface of the toner pack **40**. In addition, the attachment detection portion **53** may be a detection circuit that detects that the T memory **57** has been electrically connected to the controller **90** via the contact portion **70133** of the replenishment container attaching portion **701** illustrated in FIGS. **9A** to **9C**.

(206) The rotation detection portion **55** detects the rotation of the replenishment container attached to the replenishment container attaching portion **701**. Examples of the rotation detection portion **55** include the rotation detection portion **7015** constituted by the leaf springs **70151** and **70152** illustrated in FIGS. **9A** to **9C** and **16A** to **16F**. The rotation detection portion **7015** is merely an example of the rotation detection portion **55**, and alternatively, for example, a photoelectric sensor shielded by a projection portion provided on the replenishment port shutter **7013** may be used as a rotation detection sensor. In addition, as another example of the rotation detection sensor, a configuration in which the conduction between the leaf springs **70151** and **70152** of the rotation detection portion **7015** is caused by a projection portion provided on the discharge portion **42** of the toner pack **40** may be employed.

(207) The push-in detection portion **56** is an element that is additionally provided in the case of using the toner bottle unit **900** as in the first modification example, and detects completion of push-in of the piston **902** of the toner bottle unit **900**. Examples of the push-in detection portion **56** include a detection circuit that is provided in the image forming apparatus **1** and detects the change in the state of the push-in detection mechanism illustrated in FIGS. **16A** to **16F** constituted by the push-in detection rod **907**, the first contact plate **908**, and the second contact plate **909** provided in the toner bottle unit **900**. This detection circuit monitors the value of current generated when a voltage is applied between the metal plates **9111** and **9113** respectively connected to the first

contact plate **908** and the second contact plate **909**, and thus detects whether the piston **902** has been pushed in or has not been pushed in yet.

(208) In addition, the controller **90** is connected to the operation portion **300** serving as a user interface of the image forming apparatus 1, and the panel **400** serving as a notification portion that notifies the user of information related to the toner remainder amount in the developer container **32**. Here, the information related to the toner remainder amount is not limited to information indicating the toner remainder amount itself. In addition to this, examples of the information related to the toner remainder amount include information indicating the amount of toner that has been already supplied from the toner pack **40** or the toner bottle unit **900** for replenishment. In addition, examples of the information related to the toner remainder amount include information indicating the remaining capacity of the developer container **32** that indicates the amount of toner that can be accepted by the developer container **32** for replenishment in terms of the number of toner packs **40** or toner bottle units **900**.

(209) The operation portion **300** includes a display portion **301** capable of displaying various setting screens. For example, the display portion **301** is constituted by a liquid crystal panel. Further, the controller **90** is connected to an external device such as a desktop computer or a smartphone via the I/O interface **94**.

(210) (6) Control for Calculation of Printable Sheet Number

(211) Next, control performed in toner replenishment in the present embodiment will be described. In the present embodiment, control is performed by converting all parameters related to the amount of usable toner and all parameters related to the amount of wear of members other than toner into printable sheet numbers. Control for calculation of the printable sheet number will be described below. To be noted, although a case where the toner pack **40** is attached to the replenishment port **8012** will be described below as an example, the toner bottle unit **900** may be attached instead of the toner pack **40** as a matter of course.

(212) The controller **90** of the present embodiment includes a counter A01 indicating the printable sheet number obtained from the amount of toner accommodated in the developer container **32**, and a counter A02 indicating the printable sheet number obtained from the lifetime of members of the process cartridge **20** other than toner. In addition, the process cartridge **20** includes the P memory **58**. The P memory **58** stores a value S01, which is the printable sheet number obtained from the amount of toner accommodated in the developer container **32**, and a value S02, which is the printable sheet number obtained from the lifetime of the members of the process cartridge **20** other than toner. In addition, the P memory **58** stores a value D01, which is the printable sheet number obtained from the maximum amount of toner that can be accommodated in the developer container **32** provided in the process cartridge **20**.

(213) The toner pack **40** includes the T memory **57**. The T memory **57** stores a value PAC02, which is the printable sheet number obtained from the amount of toner accommodated in the toner pack **40**. To be noted, the conversion of each toner amount into a printable sheet number is performed on the basis of results of preliminary evaluation on the number of sheets printed until toner of a predetermined amount is completely consumed in the case of performing intermittent printing on regular paper sheets at an image coverage of 4%.

(214) In addition, the printable sheet number obtained from the lifetime of the members of the process cartridge **20** other than toner is calculated on the basis of results of preliminary evaluation made in the conditions of intermittent printing on regular paper sheets at an image coverage of 4% similarly to the case of toner. For example, the printable sheet number representing the number of sheets that can be printed before the photosensitive drum **21** becomes unusable due to wear of a coating layer is set as the value S02. In addition, although the value S02 may be obtained on the basis of the lifetime of any part in the case of not the photosensitive drum **21** but expendable parts of the process cartridge **20**, it is preferable that the value S02 is obtained on the basis of the expendable part having the shortest lifetime. For example, the value S02 may be alternatively

obtained on the basis of the number of printed sheets, the amount of toner accommodated in the waste toner chamber **8033**, and the like after replacing the charging roller **22**, the developing roller **31**, and the process cartridge **20**.

(215) FIG. **20** is a flowchart illustrating calculation control for calculating the values of counters A01 and A02. As illustrated in FIG. **20**, when the calculation control is started, the controller **90** determines in step **S11** whether or not the power has been turned on or the top cover **82** has been opened or closed. In the case where it has been determined that the power has been turned on or the top cover **82** has been opened or closed, that is, in the case where the result of step **S11** is YES, the controller **90** reads out the values S01 and S02 from the P memory **58**, and overwrites the counters A01 and A02 respectively with the values S01 and S02 in step **S12**.

(216) Next, the controller **90** determines in step **S13** whether or not the toner replenishment operation that will be described later has been completed. To be noted, in the case where it has not been determined that the power has been turned on or the top cover **82** has been opened or closed in step **S11**, that is, in the case where the result of step **S11** is NO, the controller **90** proceeds to step **S13** without performing the processing of step **S12**.

(217) In the case where it has been determined that the toner replenishment operation has been completed, that is, in the case where the result of step **S13** is YES, the controller **90** adds the value PAC02 read from the T memory **57** to the counter A01, and overwrites the value S01 of the P memory **58** with the value of the counter A01 in step **S14**. Next, the controller **90** determines in step **S15** whether or not a new job has been received or a toner-related printable sheet number is 1 or more. The toner-related printable sheet number is a value calculated from the toner remainder amount in the developer container **32** and represents the number of sheets on which printing can be performed before toner in the developer container **32** is consumed to a such a degree that printing can no longer be performed. To be noted, in the case where the toner replenishment operation has not been completed in step **S13**, that is, in the case where the result of step **S13** is NO, the controller **90** proceeds to step **S15** without performing the processing of step **S14**.

(218) In the case where a new job has not been received and the toner-related printable sheet number is not 1 or more, that is, in the case where the result of step **S15** is NO, the controller **90** returns to step **S11**. In the case where a new job has been received or the toner-related printable sheet number is 1 or more, that is, in the case where the result of step **S15** is YES, the controller **90** determines in step **S16** whether or not the value of the counter A01 is 1 or more. In the case where the value of the counter A01 is 1 or more, that is, in the case where the result of step **S16** is YES, the controller **90** determines in step **S17** whether or not the value of the counter A02 is 1 or more.

(219) In the case where the value of the counter A02 is 1 or more, that is, in the case where the result of step **S17** is YES, the controller **90** performs printing on one sheet, subtracts 1 from the values of the counters A01 and A02, and overwrites the values S01 and S02 with the values of the counters A01 and A02 in step **S18**.

(220) In the case where the value of the counter A01 is not 1 or more in step **S16**, that is, in the case where the value of the counter A01 is 0 and the result of step **S16** is NO, the controller **90** does not perform the printing operation, and displays a toner remainder amount insufficiency message on the display portion **301** in step **S19**. The toner remainder amount insufficiency message is a message indicating that the toner remainder amount is insufficient, and for example, "Printing is not available due to shortage of toner. Please replenish toner" is displayed as the toner remainder amount insufficiency message as illustrated in FIG. **21**. For example, when the user replenishes the toner in step **S13** in response to this message, the value PAC02 is added to the counter A01 in step **S14**, and it becomes possible to perform the printing operation again in steps **S15** to **S18**.

(221) In the case where the value of the counter A02 is not 1 or more in step **S17**, that is, in the case where the value of the counter A02 is 0 and the result of step **S17** is NO, the controller **90** does not perform the printing operation and displays a cartridge expiration message on the display portion **301** in step **S20**. The cartridge expiration message is a message indicating that the process cartridge

20 has expired, and for example, “Printing is not available because the process cartridge has expired. Please replace the process cartridge.” is displayed as the cartridge expiration message. For example, when the user replaces the process cartridge **20** in step **S11** in response to this message, the value of the counter **A01** is updated in step **S12**, and it becomes possible to perform the printing operation again in steps **S15** to **S18**.

(222) After step **S19**, the controller **90** returns to step **S13**, and after step **S20**, the controller **90** returns to step **S11**. As described above, the calculation control for calculating the values of the counters **A01** and **A02** is finished. This calculation control is regularly performed each time a predetermined time elapses. In addition, the values **S01** and **S02** are updated in step **S12** when the counters **A01** and **A02** are updated. Therefore, in the case where the process cartridge **20** itself is replaced, the values in the P memory **58** of the new process cartridge **20** are read, and the counters **A01** and **A02** are updated. As a result of this, control reflecting the toner amount in the process cartridge **20** and the printable sheet number corresponding to the expendable parts can be performed also in the case where the process cartridge **20** is still in use or has already expired.

(223) (6) Operation Conditions of Locking Member

(224) Next, operation conditions of the locking member **7014** when the toner pack **40** is attached to the replenishment port **8012** will be described. The locking member **7014** is capable of restricting the rotation of the replenishment port shutter **7013** by positioning in the locking position illustrated in FIG. **11A** as described above, and allows the rotation of the replenishment port shutter **7013** by positioning in the lock-releasing position illustrated in FIG. **11B**. To be noted, the replenishment port shutter **7013** serving as an opening/closing portion and the locking member **7014** constitute a replenishment restriction portion **70134** as illustrated in FIG. **11A**. In the description below, an operation of moving the locking member **7014** from the lock-releasing position to the locking position will be referred to as “locking”, and an operation of moving the locking member **7014** from the locking position to the lock-releasing position will be referred to as “unlocking”. In addition, a state where the locking member **7014** is positioned in the locking position with respect to the replenishment restriction portion **70134** will be referred to as a restricting state, and a state where the locking member **7014** is positioned in the lock-releasing position will be referred to as an allowing state.

(225) FIG. **22** is a flowchart for describing the operation conditions of the locking member **7014**. In addition, the controller **90** determines in step **S31** whether or not the toner pack **40** is coupled to, that is, attached to the replenishment port **8012**. In the case where the toner pack **40** is coupled to the replenishment port **8012**, that is, in the case where the result of step **S31** is YES, the controller **90** reads the value **PAC02** from the T memory **57** and the value **D01** from the P memory **58** in step **S32**.

(226) Next, the controller **90** compares a value obtained by adding up the value of the counter **A01** and the value **PAC02** with the value **D01**, and determines in step **S33** whether or not “counter **A01**+value **PAC02**≤value **D01**” is satisfied. The relationship “counter **A01**+value **PAC02**≤value **D01**” indicates that even if all toner in the currently-attached toner pack **40** is supplied to the developer container **32**, the developer container **32** can accommodate the toner without spilling the toner. In the case where “counter **A01**+value **PAC02**≤value **D01**” is satisfied, that is, in the case where the result of step **S33** is YES, the controller **90** turns on a flag **F01** in step **S34**, and proceeds to step **S35**.

(227) In the case where “counter **A01**+value **PAC02**≤value **D01**” is not satisfied, that is, in the case where the result of step **S33** is NO, the controller **90** turns off the flag **F01** and continuously displays a remaining capacity insufficiency message on the display portion **301** in step **S42**, and proceeds to step **S35**. The remaining capacity insufficiency message is a message indicating that the remaining capacity of the developer container **32** is insufficient, and for example, “Toner replenishment is not available due to lack of remaining capacity.” is displayed as the remaining capacity insufficiency message.

(228) Next, the controller **90** determines in step **S35** whether or not the value of the counter **A02** is 1 or more. In the case whether the value of the counter **A02** is 1 or more, that is, in the case where the result of step **S35** is YES, the controller **90** compares a value obtained by adding up the value of the counter **A01** and the value **PAC02** with the value of the counter **A02**, and determines in step **S36** whether or not “counter **A01**+value **PAC02**≤counter **A02**” is satisfied. In other words, the controller **90** determines whether or not a second printable sheet number obtained from the value obtained by adding up the value of the counter **A01** and the value **PAC02** is larger than the value of the counter **A02** serving as a first printable sheet number.

(229) The relationship “counter **A01**+value **PAC02**≤counter **A02**” indicates that the process cartridge **20** does not expire even when all toner in the currently-attached toner pack **40** is consumed. Conversely, in the case where “counter **A01**+value **PAC02**≤counter **A02**” is not satisfied, the process cartridge **20** expires before all toner in the currently-attached toner pack **40** is consumed, which means that the replenished toner goes to waste.

(230) In the case where “counter **A01**+value **PAC02**≤counter **A02**” is satisfied, that is, in the case where the result of step **S36** is YES, the controller **90** compares a value obtained by adding up the value of the counter **A01** and the double of the value **PAC02** with the value of the counter **A02**. Then, the controller **90** determines in step **S37** whether or not “counter **A01**+value **PAC02**×2≤counter **A02**” is satisfied. In other words, the controller **90** determines whether or not “counter **A01**+value **PAC02**×2” serving as a third printable sheet number is larger than the value of the counter **A02** serving as a first printable sheet number.

(231) The relationship “counter **A01**+value **PAC02**×2≤counter **A02**” indicates that the process cartridge **20** does not expire even when all toner in the currently-attached toner pack **40** and all toner in the toner pack **40** to be attached next are consumed. Conversely, in the case where “counter **A01**+value **PAC02**×2≤counter **A02**” is not satisfied, the process cartridge **20** expires before all toner in the toner pack **40** to be attached next is consumed. That is, in the case where “counter **A01**+value **PAC02**×2≤counter **A02**” is not satisfied, it is more economical for the user to prepare a new process cartridge **20** for preparation for the next toner replenishment instead of preparing a new toner pack **40**.

(232) Therefore, in the case where “counter **A01**+value **PAC02**×2≤counter **A02**” is not satisfied, that is, in the case where the result of step **S37** is NO, the controller **90** displays a pre-cartridge expiration notification message as a warning on the display portion **301** in step **S47**, and proceeds to step **S38**. The pre-cartridge expiration notification message is a message indicating that the expiration of the process cartridge **20** is near. For example, “The process cartridge will expire soon and toner replenished next time may be wasted. Please prepare a process cartridge for the next toner replenishment.” is displayed as the pre-cartridge expiration notification message.

(233) In the case where “counter **A01**+value **PAC02**×2≤counter **A02**” is satisfied in step **S37**, that is, in the case where the result of step **S37** is YES, the controller **90** determines in step **S38** whether or not the flag **F01** is ON. In the case where the flag **F01** is ON, that is, in the case where the result of step **S38** is YES, the controller **90** unlocks the locking member **7014**, that is, switches the replenishment restriction portion **70134** to the allowing state in step **S39**.

(234) Then, the controller **90** determines in step **S40** whether or not the toner pack **40** has been detached from the replenishment port **8012**. In the case where the toner pack **40** has been detached from the replenishment port **8012**, that is, in the case where the result of step **S40** is YES, the controller **90** locks the locking member **7014** in step **S41**, and finishes the processing. To be noted, in the case where the flag **F01** is OFF in step **S38**, that is, in the case where the result of step **S38** is NO, the controller **90** does not unlock the locking member **7014**, and maintains the locking member **7014** in the locked state, that is, a restricting state. This is performed for suppressing overflow of toner from the developer container **32** caused by replenishment of the developer container **32** with toner from the toner pack **40** as described above.

(235) In addition, in the case where the value of the counter **A02** is not 1 or more in step **S35**, that

is, in the case where the value of the counter A02 is 0 and the result of step S35 is NO, the controller **90** displays a cartridge expiration reaching message on the display portion **301** in step S43. The cartridge expiration reaching message is a message indicating that the process cartridge **20** has expired, and for example, “The process cartridge has expired, and toner replenishment cannot be performed because replenished toner will be wasted.” is displayed as the cartridge expiration reaching message.

(236) In addition, in the case where “counter A01+value PAC02≤counter A02” is not satisfied in step S36, that is, in the case where the result of step S36 is NO, the controller **90** displays a cartridge expiration approaching message on the display portion **301** in step S44. The cartridge expiration approaching message is a message indicating that the expiration of the process cartridge **20** is near, and for example, “The process cartridge will expire soon, and toner replenishment cannot be performed because replenished toner will be wasted.” is displayed as the cartridge expiration approaching message.

(237) After the cartridge expiration reaching message or the cartridge expiration approaching message is displayed, the controller **90** displays a toner replenishment selection message on the display portion **301** in step S45. The toner replenishment selection message is a message for asking the user whether or not to perform an allowing operation of allowing toner replenishment through the replenishment port **8012**. For example, “Replenished toner may be wasted. Do you replenish the toner?” is displayed as the toner replenishment selection message. To be noted, the cartridge expiration reaching message or the cartridge expiration approaching message and the toner replenishment selection message may be alternately displayed each time a predetermined time elapses, or may be simultaneously displayed.

(238) Then, the controller **90** determines in step S46 whether or not the user has selected “OK” via the input portion **302**. To be noted, although the allowing operation described above in the present embodiment is the selection of “OK” via the input portion **302**, the configuration is not limited to this. For example, an “OK” button may be displayed on the display portion **301**, and a touch operation on the “OK” button may be used as the allowing operation.

(239) The controller proceeds to step S38 in the case where “OK” has been selected, that is, in the case where the result of step S46 is YES, and finishes the processing in the case where “OK” has not been selected, that is, in the case where the result of step S46 is NO.

(240) As described above, in the present embodiment, in the case where “counter A01+value PAC02≤counter A02” is not satisfied, that is, in the case where the result of step S36 is NO, the locking member **7014** is maintained in the locked state, that is, the restricting state, and the cartridge expiration approaching message is displayed. In other words, the present embodiment is configured such that a warning prompting replacement of the process cartridge **20** can be displayed on the display portion **301** when the toner pack **40** is attached to the replenishment port **8012**. As a result of this, a situation in which the process cartridge **20** expires before all the toner replenished from the toner pack **40** is consumed and the toner is wasted can be suppressed. Therefore, the toner replenishment can be performed more economically.

(241) In addition, even in the case where “counter A01+value PAC02≤counter A02” is not satisfied, if the user desires to perform toner replenishment, that is, in the case where the result of step S46 is YES, toner replenishment can be performed at the user's discretion, and thus the usability can be improved.

(242) In addition, in the case where “counter A01+value PAC02×2≤counter A02” is not satisfied, the pre-cartridge expiration notification message is displayed. As a result of this, the user can prepare a new process cartridge **20** for preparation for the next toner replenishment instead of preparing the toner pack **40**, and therefore the toner replenishment can be performed more economically. In addition, a mode of an image forming apparatus can be provided.

(243) To be noted, although control of the locking member **7014** and display of a message on the display portion **301** are both performed in the present embodiment, just either one of these may be

performed. For example, in the case where “counter A01+value PAC02≤counter A02” is not satisfied, that is, in the case where the result of step S36 is NO, the locking member **7014** may be maintained in the locked state, that is, the restricting state without displaying the cartridge expiration message. For example, in the case where “counter A01+value PAC02≤counter A02” is not satisfied, that is, in the case where the result of step S36 is NO, the cartridge expiration message may be displayed without maintaining the locking member **7014** in the locked state, that is, the restricting state.

(244) In addition, conditions of unlocking of the locking member **7014** may be appropriately modified by considering the usability comprehensively. For example, in the case where “counter A01+value PAC02≤value D01” is not satisfied, that is, in the case where the result of step S33 is NO, the locked state, that is, the restricting state of the locking member **7014** is maintained. Meanwhile, in the case where “counter A01+value PAC02≤counter A02” is not satisfied, that is, in the case where the result of step S36 is NO, the cartridge expiration approaching message may be displayed on the display portion **301** without performing the control of maintaining the locking member **7014** in the locked state, that is, the restricting state.

(245) In addition, in steps S37 and S47, a case where toner packs **40** of different specifications are available, that is, a case where there are a model of the toner pack **40** accommodating a large amount of toner and a model of the toner pack **40** accommodating a small amount of toner may be considered. Values obtained by converting the toner amounts of these two models into printable sheet numbers will be respectively referred to as values PAC02-1 and PAC02-2, and it is assumed that the model of the toner pack **40** currently attached to the replenishment port **8012** corresponds to the value PAC02-1. In this case, for example, the controller **90** determines in step S37 whether or not “counter A01+value PAC02-1+value PAC02-2≤counter A02” is satisfied. To be noted, steps S37 and S47 may be omitted.

(246) To be noted, although the controller **90**, the T memory **57**, and the P memory **58** store the printable sheet number itself in the present embodiment, the configuration is not limited to this, and any configuration may be employed as long as data corresponding to the printable sheet number is stored in the controller **90**, the T memory **57**, and the P memory **58**.

Second Embodiment

(7) Second Embodiment

(247) Next, a second embodiment of the present invention will be described. In the second embodiment, control related to a toner consumption amount and expiration of the process cartridge **20** is performed instead of the control for calculation of the printable sheet number of the first embodiment. Therefore, illustration of the same elements as in the first embodiment will be omitted, or the same elements are denoted by the same reference numerals in the illustration and description thereof will be omitted.

(248) In the present embodiment, the following control is performed by using the toner remainder amount detection portion **51** and the waste toner fullness detection portion **52**. In addition, control related to deterioration of the photosensitive drum **21** in the process cartridge **20** is performed on the basis of the number of rotations of the photosensitive drum **21**. To be noted, the same control as in the first embodiment is performed on parts other than parts related to the above.

(249) First, variables included in the controller **90** will be described. The controller **90** includes, as variables, a toner remainder amount B01 indicating the toner amount in the developer container **32**, a total waste toner amount B02 indicating the amount of waste toner in the waste toner chamber **8033**, and an accumulated sheet number B03 indicating the number of sheets on which printing has been performed by using the process cartridge **20**. In addition, the controller **90** includes, as variables, a total rotation number B04 indicating the total number of rotations of the photosensitive drum **21**, a unit toner consumption amount E01 corresponding to a normal amount of toner consumption per printed sheet, and a unit waste toner generation amount E02 indicating a normal amount of generation of waste toner per printed sheet. Further, the controller **90** includes, as

variables, a unit drum rotation number E04 corresponding to the amount of rotation of the photosensitive drum **21** per printed sheet, and a waste toner chamber capacity G01 indicating the capacity of the waste toner chamber **8033**. The unit toner consumption amount E01 is calculated on the basis of results obtained by making preliminary evaluation in the conditions of intermittently printing at an image coverage of 4% similarly to the first embodiment. The unit waste toner generation amount E02 and the unit drum rotation number E04 are determined in the preliminary evaluation. To be noted, the number of rotations of the photosensitive drum **21** may be the amount of movement of the surface of the photosensitive drum **21** according to the rotation of the photosensitive drum **21**.

(250) In addition, the P memory **58** provided in the process cartridge **20** also includes variables similar to those of the controller **90**, and the variables included in the P memory **58** will be referred to as a toner remainder amount **C01**, a total waste toner amount, an accumulated sheet number, and a total drum rotation number. The T memory **57** provided in the toner pack **40** stores a value PAC03 indicating the amount of toner accommodated in the toner pack **40**.

(251) (7-1) Detection of Toner Remainder Amount in Developer Container

(252) Next, a method of detecting the toner remainder amount in the developer container **32** by the toner remainder amount detection portion **51** will be described. The toner remainder amount detection portion **51** includes the light emitting portion **51a** and the light receiving portion **51b** as illustrated in FIG. **6A**, and is provided at such a position that toner starts blocking an optical path **513** thereof when toner of an amount corresponding to one toner pack **40** is added for replenishment. In addition, the agitation member **34** includes a blade portion **34b** that cleans the light emitting portion **51a** and the light receiving portion **51b** each time the agitation member **34** rotates.

(253) The optical response of the toner remainder amount detection portion **51** is 0 when the amount of toner in the developer container **32** is larger than the amount corresponding to one toner pack **40**. In the case where the amount of toner in the developer container **32** is smaller than the amount corresponding to one toner pack **40**, a time in which the optical path **513** is opened depending on the rotation of the agitation member **34** occurs. This time will be referred to as a detection time. Further, the toner remainder amount detection portion **51** changes one of an electric signal, a current, and a voltage as the output value thereof on the basis of the amount of toner accommodated in the developer container **32**. To be noted, such an optical sensor is merely an example of a toner remainder amount detection portion, and a pressure sensor or an electrostatic capacitance sensor may be used.

(254) In the description below, the detection time per one rotation of the agitation member **34** will be referred to as a detection time **D1**, and the detection time in the case where the amount of toner in the developer container **32** is smaller than the amount corresponding to one toner pack **40** will be referred to as a first toner remainder amount threshold. In addition, when the amount of toner in the developer container **32** is smaller than 10% of the amount corresponding to one toner pack **40**, the optical path **513** is open for almost the entire time in which the agitation member **34** is rotating. The detection time of this case will be referred to as a second toner remainder amount threshold. The detection time **D1** is constantly recorded while the agitation member **34** is rotating, and the detection time **D1** is constantly updated in the controller **90** by setting the average value of the latest 20 rotations as the detection time **D1** indicating the current toner amount.

(255) (7-2) Detection of Waste Toner Amount in Waste Toner Chamber

(256) Next, a method of detecting the waste toner amount in the waste toner chamber **8033** by the waste toner fullness detection portion **52** serving as a waste toner detection portion will be described. The waste toner fullness detection portion **52** includes a light emitting portion **52a** and a light receiving portion **52b** as illustrated in FIG. **6A**, and is disposed at such a position that an optical path **522** of the waste toner fullness detection portion **52** starts being blocked when the remaining capacity of the waste toner chamber **8033** reaches 10% of the total capacity thereof. The

fifth conveyance member **8032** is formed in a grating shape, and reciprocates in the left-right direction of FIG. **6A** along the bottom surface of the waste toner chamber **8033**. As a result of this, toner conveyed to the waste toner chamber **8033** is conveyed in an arrow **M** direction toward the rear portion **8033a**. Then, when the amount of waste toner accommodated in the waste toner chamber **8033** becomes larger, the time in which the waste toner conveyed while being agitated by the fifth conveyance member **8032** blocks the optical path **522** of the waste toner fullness detection portion **52** becomes longer. The waste toner fullness detection portion **52** changes the output value thereof on the basis of the time in which the optical path **522** is opened in accordance with the reciprocation of the fifth conveyance member **8032**. This time will be hereinafter referred to as a detection time. In other words, the waste toner fullness detection portion **52** changes one of an electric signal, a current, and a voltage as the output value thereof on the basis of the amount of waste toner accommodated in the waste toner chamber **8033**. In addition, a sheet-shaped cleaning portion **8032a** is provided at a distal end portion of the fifth conveyance member **8032**, and cleans the light receiving portion **52b** when the fifth conveyance member **8032** reciprocates. To be noted, such an optical sensor is merely an example of the waste toner fullness detection portion, and a pressure sensor or an electrostatic capacitance sensor may be used.

(257) In the description below, the average detection time per one rotation of the fifth conveyance member **8032** will be referred to as a detection time **D2**, and the detection time in the case where the remaining capacity of the waste toner chamber **8033** is smaller than 10% of the total capacity will be referred to as a first waste toner remainder amount threshold. The detection time in the case where the waste toner chamber **8033** is full and the optical path **522** of the waste toner fullness detection portion **52** is blocked by toner almost the entire time will be referred to as a second waste toner remainder amount threshold.

(258) (7-3) Method of Determining Deterioration of Photosensitive Drum

(259) Next, a method of determining that the photosensitive drum **21** has deteriorated will be described. The number of rotations of the photosensitive drum **21** is calculated from the driving time of the motor **M1** that drives the photosensitive drum **21**, and is included in the total drum rotation number **B04**. A total drum rotation number at which the function of a photosensitive layer of the photosensitive drum **21** becomes insufficient due to the wear of the surface of the photosensitive drum **21** will be referred to as a threshold **H04**.

(260) To be noted, the rotation time of the photosensitive drum **21** includes an image formation rotation time in which the photosensitive drum **21** is rotated while a voltage higher than those of the charging roller **22** and the transfer roller **12** is applied to the photosensitive drum **21**, and a non-image formation rotation time in which a high voltage is not applied. The amount of wear of the surface of the photosensitive drum **21** in the non-image formation rotation time is about a half of that in the image formation rotation time. Therefore, the number of rotations in the non-image formation rotation time is included in the total drum rotation number **B04** with a weight of 0.5 with respect to the number of rotations in the image formation rotation time.

(261) (7-4) Control Related to Toner Consumption Amount and Expiration of Process Cartridge **20**

(262) Next, control related to the toner consumption amount and expiration of the process cartridge **20** will be described. FIGS. **23** and **24** are flowcharts illustrating the control related to the toner consumption amount and expiration of the process cartridge **20**.

(263) When the control related to the toner consumption amount and expiration of the process cartridge **20** is started, as illustrated in FIG. **23**, the controller **90** determines in step **S51** whether or not the power has been turned on or the top cover **82** has been opened or closed. In the case where it has been determined that the power has been turned on or the top cover **82** has been opened or closed, that is, in the case where the result of step **S51** is YES, the controller **90** reads the toner remainder amount **C01**, the total waste toner amount **C02**, the accumulated sheet number **C03**, and the total drum rotation number **C04** from the P memory **58**. Then, the controller **90** updates the toner remainder amount **B01**, the total waste toner amount **B02**, the accumulated sheet number

B03, and the total drum rotation number B04 of the controller **90** with these values in step S52.

(264) Next, the controller **90** determines in step S53 whether or not the toner replenishment operation has been completed. To be noted, in the case where it has not been determined in step S51 that the power has been turned on or the top cover **82** has been opened or closed, that is, in the case where the result of step S51 is NO, the controller **90** proceeds to step S53 without performing the processing of step S52.

(265) In the case where it has been determined that the toner replenishment operation has been completed, that is, in the case where the result of step S53 is YES, the controller **90** adds the value PAC03 read from the T memory **57** to the toner remainder amount B01, and updates the toner remainder amount C01 with the toner remainder amount B01 in step S54. Next, the controller **90** determines in step S55 whether or not a new job has been received or the toner-related printable sheet number is 1 or more. To be noted, in the case where the toner replenishment operation has not been completed in step S53, that is, in the case where the result of step S53 is NO, the controller **90** proceeds to step S55 without performing the processing of step S54.

(266) In the case where a new job has not been received and the toner-related printable sheet number is not 1 or more, that is, in the case where the result of step S55 is NO, the controller **90** returns to step S51. In the case where a new job has been received or the toner-related printable sheet number is 1 or more, that is, in the case where the result of step S55 is YES, the controller **90** determines in step S56 whether or not the toner remainder amount B01 is equal to or larger than the unit toner consumption amount E01.

(267) In the case where the toner remainder amount B01 is smaller than the unit toner consumption amount E01, that is, in the case where the result of step S56 is NO, the controller **90** displays a toner remainder amount insufficiency message on the display portion **301** in step S57 without performing the printing operation. The toner remainder amount insufficiency message is a message indicating that the toner remainder amount is insufficient, and for example, a message “Printing is not available due to shortage of toner. Please replenish toner.” is displayed as the toner remainder amount insufficiency message. For example, in the case where the user performs toner replenishment in step S53 in response to this message, the value PAC03 is added to the toner remainder amount B01 in step S54, and it becomes possible to perform the printing operation again in steps S55, S56, and S58 to S60. After step S57, the controller **90** returns to step S51.

(268) In the case where the toner remainder amount B01 is equal to or larger than the unit toner consumption amount E01, that is, in the case where the result of step S56 is YES, the controller **90** determines in step S58 whether or not “total waste toner amount B02>waste toner chamber capacity G01-unit waste toner generation amount E02” is satisfied. This condition will be referred to as a first condition. In addition, as illustrated in FIG. 24, the controller **90** also determines in step S58 whether or not “total drum rotation number B04>threshold H04-unit drum rotation number E04” is satisfied. This condition will be hereinafter referred to as a second condition.

(269) In the case where the first condition or the second condition is not satisfied, that is, in the case where the result of step S58 is NO, the controller **90** displays a cartridge expiration message on the display portion **301** in step S59 without performing the printing operation. The cartridge expiration message is a message indicating that the process cartridge **20** has expired, and for example, “Printing is not available because the process cartridge has expired. Please replace the process cartridge.” is displayed as the cartridge expiration message. For example, in the case where the user replaces the process cartridge **20** in step S51 in response to this message, the toner remainder amount B01 is updated in step S52, and it becomes possible to perform the printing operation again in steps S55, S56, and S58 to S60.

(270) In the case where the first condition and the second condition are satisfied, that is, in the case where the result of step S58 is YES, the controller **90** performs printing on one sheet in step S60. Then, in step S61, the controller **90** subtracts the unit toner consumption amount E01 from the toner remainder amount B01, adds the unit waste toner generation amount E02 to the total waste

toner amount B02, and adds 1 to the accumulated sheet number B03. In addition, in step S61, the controller 90 adds the unit drum rotation number E04 to the total drum rotation number B04, and updates the unit drum rotation number E04 by dividing the total drum rotation number B04 by the accumulated sheet number B03. Then, values of the P memory 58 are updated with these values of the controller 90.

(271) Next, the controller 90 checks the detection times D1 and D2 in step S62. Then, the controller 90 performs processing of steps S63 and S65 in parallel. That is, the controller 90 determines in step S63 whether or not the detection time D1 is longer than a predetermined threshold. Although the second toner remainder amount threshold will be described as the predetermined threshold herein, the first toner remainder amount threshold T11 may be used as the predetermined threshold.

(272) In the case where the detection time D1 is longer than the first toner remainder amount threshold serving as the predetermined threshold, that is, in the case where the result of step S63 is YES, the controller 90 updates the toner remainder amount B01 with 10% of the toner amount of one toner pack 40 in step S64. In addition, in step S64, the controller 90 updates the unit toner consumption amount E01. For example, a case where the use of the image forming apparatus is started in a state after the developer container 32 is replenished with toner of an amount corresponding to one toner pack 40 and the current accumulated sheet number B03 is 1800 is assumed. In this case, toner of an amount obtained by $0.9 \times \text{value PAC03}$, which corresponds to 90% of the amount of toner in the toner pack 40, is used in printing on 1800 sheets, and therefore the unit toner consumption amount E01 can be obtained by $0.9 \times \text{value PAC03} \div 1800$.

(273) In addition, the controller 90 determines in step S65 whether or not the detection time D2 is shorter than the predetermined threshold. Although the first waste toner remainder amount threshold will be described as an example of the predetermined threshold, the second waste toner remainder amount threshold may be used as the predetermined threshold.

(274) In the case where the detection time D2 is shorter than the first waste toner remainder amount threshold serving as the predetermined threshold, that is, in the case where the result of step S65 is YES, the controller 90 overwrites the total waste toner amount B02 with an amount that is 90% of the waste toner chamber capacity G01 in step S66. In addition, in step S66, the controller 90 updates the unit waste toner generation amount E02. For example, a case where the accumulated sheet number B03 is 45000 is assumed. In this case, toner of an amount that is 90% of the waste toner chamber capacity G01 has been accumulated in printing on 45000 sheets, and therefore the unit waste toner generation amount E02 can be obtained by $0.9 \times \text{waste toner chamber capacity G01} \div 45000$.

(275) In the case where the detection time D1 is equal to or shorter than the predetermined threshold in step S63, that is, in the case where the result of step S63 is NO, or in the case where the detection time D2 is equal to or longer than the predetermined threshold in step S65, that is, in the case where the result of step S65 is NO, the controller 90 returns to step S51. Although the control related to the toner consumption amount and expiration of the process cartridge 20 is finished as described above, this control is performed regularly each time a predetermined time elapses.

(276) In addition, the operation condition of the locking member 7014 when the toner pack 40 is attached to the replenishment port 8012 is the same as that described with reference to FIG. 22. However, the variables used in the operation conditions of the locking member 7014 are calculated as follows.

(277) The value PAC02 is calculated by dividing the value PAC03 by the unit toner consumption amount E01. The value D01 is calculated by dividing the amount of toner that can be accommodated in the developer container 32 by the unit toner consumption amount E01. The value of the counter A01 is calculated by dividing the toner remainder amount B01 by the unit toner consumption amount E01.

(278) The value of the counter A02 is calculated from a smaller one of a printable sheet number obtained from the total waste toner amount B02, the waste toner chamber capacity G01, and the unit waste toner generation amount E02, and a printable sheet number obtained from the total drum rotation number B04, the threshold H04, and the unit drum rotation number E04. The former one of the printable sheet numbers is obtained by (waste toner chamber capacity G01-total waste toner amount B02)÷unit waste toner generation amount E02, and the latter one of the printable sheet numbers is obtained by (threshold H04-total drum rotation number B04)÷unit drum rotation number E04.

(279) To be noted, the value of the counter A02 may be calculated from the number of rotations of the developing roller **31** or the charging roller **22** instead of the photosensitive drum **21**. In addition, the value of the counter A02 may be calculated by subtracting the accumulated sheet number B03 from the printable sheet number of a brand-new process cartridge **20**. In addition, the value of the counter A02 may be obtained in consideration of the accumulated sheet number B03 at a time point when the toner pack **40** is coupled to the replenishment port **8012**, the value PAC03 indicating the amount of toner replenishment from the toner pack **40**, and the number of times of toner replenishment performed on the process cartridge **20**. The value of the counter A02 may be calculated by subtracting the accumulated sheet number B03 from the printable sheet number of a brand-new process cartridge **20**. In addition, a function of suspending the printing operation for a predetermined time may be added for accurately determining the amount of toner in the developer container **32** when the toner pack **40** is coupled to the replenishment port **8012** or when the toner pack **40** is detached from the replenishment port **8012** after the replenishment.

(280) As described above, according to the present embodiment, insufficiency of toner and expiration of the process cartridge **20** can be determined in accordance with the actual use state of the user. Therefore, expiration of the process cartridge **20** can be detected with high precision before all the toner replenished from the toner pack **40** is consumed, and therefore waste of toner can be reduced and toner replenishment can be performed more economically. In addition, a mode of an image forming apparatus can be provided.

Third Embodiment

(8) Third Embodiment

(281) Next, a third embodiment of the present invention will be described. In the third embodiment, the message described in the first embodiment is displayed on a different information processing apparatus connected to the image forming apparatus 1. Therefore, illustration of the same elements as in the first embodiment will be omitted, or the same elements are denoted by the same reference numerals in the illustration and description thereof will be omitted.

(282) The image forming apparatus 1 according to the present embodiment is communicably connected to a personal computer: PC **2A**, a mobile information processing terminal **2B** such as a smartphone, and the like as illustrated in FIG. **25**. Information transmitted to the image forming apparatus 1 from the PC **2A** and the mobile information processing terminal **2B** is input to the controller **90** through the I/O interface **94**. In addition, information transmitted from the image forming apparatus 1 to the PC **2A** or the mobile information processing terminal **2B** is input to the PC **2A** or the mobile information processing terminal **2B** from the controller **90** through the I/O interface **94**. To be noted, a sound generating portion such as a loudspeaker may be provided in the PC **2A** and the mobile information processing terminal **2B**. As a result of this, a mode of an image forming apparatus can be provided.

(283) In the present embodiment, each message of the control described with reference to FIGS. **20** to **24** is displayed on the display portion **301** of the PC **2A** or a display portion **304** of the mobile information processing terminal **2B**. To be noted, the message described above may be displayed on two or more of the display portions **301** and **304**.

Other Embodiments

(284) Embodiment(s) of the present invention can also be realized by a computer of a system or

apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a ‘non-transitory computer-readable storage medium’) to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

(285) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(286) This application claims the benefit of Japanese Patent Application No. 2019-184767, filed Oct. 7, 2019, which is hereby incorporated by reference herein in its entirety.

Claims

1. An image forming apparatus to and from which a replenishment container accommodating toner is attachable and detachable and which is configured to form an image on a recording material, the image forming apparatus comprising: an apparatus body; a process unit comprising: an image bearing member; a developer container configured to accommodate toner; a developing portion configured to develop an electrostatic latent image formed on the image bearing member into a toner image by using the toner accommodated in the developer container; and a replenishment port configured to allow replenishment of toner from the replenishment container; a display portion; a controller configured to notify a user of information related to a toner amount by using the display portion in a case where it is determined that a lifetime of the process unit will expire before a sum of toner accommodated in the developer container and toner accommodated in the replenishment container is consumed; an input portion through which a user performs an allowing operation of allowing toner replenishment after a notification is displayed on the display portion, wherein the information related to a toner amount is the notification about toner, to be supplied from the replenishment container, which goes to waste.
 2. The image forming apparatus according to claim 1, wherein the lifetime of the process unit is less than a threshold corresponding to a printable sheet number depending on the sum of toner.
 3. The image forming apparatus according to claim 1, wherein the replenishment container is arranged outside of the image forming apparatus in a state where the replenishment container is attached to the replenishment port.
 4. The image forming apparatus according to claim 1, wherein the process unit is attachable to and detachable from the image forming apparatus.
 5. The image forming apparatus according to claim 1, further comprising a detection unit configured to detect that the replenishment container is attached to the replenishment port.
-

