

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                      |
|----------------------|----------------------|
| United States Patent | 12406319             |
| Kind Code            | B2                   |
| Date of Patent       | September 02, 2025   |
| Inventor(s)          | Otani; Takumi et al. |

---

### Program, information processing apparatus, and information processing method

---

#### Abstract

A program in the present invention causes a computer to perform: performing a first process for performing a predetermined process related to an aircraft boarding procedure and acquiring boarding reservation information on a user; when the process is completed, performing a second process for matching biometric information acquired from the user with passport biometric information included in passport information acquired from a passport of the user and, when a result of the matching of the biometric information with the passport biometric information is that the matching is successful, associating the passport information, the biometric information, and the boarding reservation information with each other; and performing a switching process for switching whether to perform the first process or the second process.

---

|                   |                                                                 |
|-------------------|-----------------------------------------------------------------|
| <b>Inventors:</b> | <b>Otani; Takumi (Tokyo, JP), Sasamoto; Takeshi (Tokyo, JP)</b> |
| <b>Applicant:</b> | <b>NEC Corporation (Tokyo, JP)</b>                              |
| <b>Family ID:</b> | <b>75849678</b>                                                 |
| <b>Assignee:</b>  | <b>NEC CORPORATION (Tokyo, JP)</b>                              |
| <b>Appl. No.:</b> | <b>18/670787</b>                                                |
| <b>Filed:</b>     | <b>May 22, 2024</b>                                             |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20240311944 A1          | Sep. 19, 2024           |

#### Related U.S. Application Data

continuation parent-doc US 17771123 US 12045907 WO PCT/JP2019/043740 20191107 child-doc US 18670787

---

## Publication Classification

**Int. Cl.:** G06Q50/40 (20240101); G06Q10/02 (20120101); G07C9/25 (20200101); G07C9/27 (20200101)

**U.S. Cl.:**

**CPC** G06Q50/40 (20240101); G06Q10/02 (20130101); G07C9/25 (20200101); G07C9/27 (20200101);

## Field of Classification Search

**CPC:** G06Q (50/40); G06Q (10/02); G07C (9/27); G07C (9/25)

**USPC:** 235/384

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name    | U.S. Cl. | CPC         |
|--------------|-------------|------------------|----------|-------------|
| 8571902      | 12/2012     | Glavan           | 705/325  | G06Q 50/10  |
| 9665998      | 12/2016     | Shields          | N/A      | G06Q 10/04  |
| 12045907     | 12/2023     | Otani            | N/A      | G07C 9/257  |
| 2002/0193973 | 12/2001     | Kinoshita et al. | N/A      | N/A         |
| 2013/0027187 | 12/2012     | Yepez            | 340/10.1 | G07C 9/27   |
| 2015/0039354 | 12/2014     | Murphy           | 705/5    | G06Q 10/02  |
| 2017/0046808 | 12/2016     | Parrish          | N/A      | G06K 7/1417 |
| 2017/0262625 | 12/2016     | Takeda           | N/A      | N/A         |
| 2019/0147558 | 12/2018     | Cheikh et al.    | N/A      | N/A         |
| 2020/0380426 | 12/2019     | Schlank          | N/A      | G06Q 50/265 |

### FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| 1619638     | 12/2005          | EP      | N/A |
| 2002-373217 | 12/2001          | JP      | N/A |
| 2003-296766 | 12/2002          | JP      | N/A |
| 2005-135310 | 12/2004          | JP      | N/A |
| 2017-167621 | 12/2016          | JP      | N/A |
| 2018-045340 | 12/2017          | JP      | N/A |
| 2018-190307 | 12/2017          | JP      | N/A |
| 2005/055151 | 12/2004          | WO      | N/A |

### OTHER PUBLICATIONS

International Search Report for PCT Application No. PCT/JP2019/043740, mailed on Jan. 7, 2020. cited by applicant

Extended European Search Report for EP Application No. 19951940.6, dated on Oct. 11, 2022. cited by applicant

JP Office Action for JP Application No. 2022-024514, mailed on Feb. 9, 2023 with English Translation. cited by applicant

---

## Background/Summary

(1) This application is a continuation application of U.S. patent application Ser. No. 17/771,123 filed on Apr. 22, 2022, which is a National Stage Entry of PCT/JP2019/043740 filed on Nov. 7, 2019, the contents of all of which are incorporated herein by reference, in their entirety.

### TECHNICAL FIELD

(1) The present invention relates to a program, an information processing apparatus, and an information processing method.

### BACKGROUND ART

(2) Patent Literature 1 discloses a check-in system having a check-in terminal (boarding ticket vending machine) that acquires user's face data, and if a result of matching of the face data with face data separately acquired from a passport is that the matching is successful, prints a boarding ticket with user face data.

### CITATION LIST

#### Patent Literature

(3) PTL 1: Japanese Patent Application Laid-Open No. 2005-135310

### SUMMARY OF INVENTION

#### Technical Problem

(4) The check-in terminal disclosed in Patent Literature 1 is provided in advance with a face authentication function that extracts a feature part of face from image information acquired by each of a reading device and a camera to create face data and matches two face data with each other to authenticate the user. In existing airports, however, there still are a large number of check-in terminals that do not have such a face authentication function. There is a problem of significant cost being required in introducing new-model check-in terminals having a face authentication function in place of existing check-in terminals.

(5) Accordingly, in view of the problems described above, the present invention intends to provide a program, an information processing apparatus, and an information processing method that can easily implement a face authentication function to an existing check-in terminal.

#### Solution to Problem

(6) According to one aspect of the present invention, provided is a program that causes a computer to perform: performing a first process for performing a predetermined process related to an aircraft boarding procedure and acquiring boarding reservation information on a user; when the process is completed, performing a second process for matching biometric information acquired from the user with passport biometric information included in passport information acquired from a passport of the user and, when a result of the matching of the biometric information with the passport biometric information is that the matching is successful, associating the passport information, the biometric information, and the boarding reservation information with each other; and performing a switching process for switching whether to perform the first process or the second process.

(7) According to another aspect of the present information processing invention, provided is an apparatus including: a first processing unit that performs a predetermined process related to an aircraft boarding procedure and acquires boarding reservation information on a user; a second processing unit that, when the process is completed, matches biometric information acquired from the user with passport biometric information included in passport information acquired from a passport of the user and, when a result of the matching of the biometric information with the passport biometric information is that the matching is successful, associates the passport

information, the biometric information, and the boarding reservation information with each other; and a switching unit that switches whether to operate the first processing unit or the second processing unit.

(8) According to yet another aspect of the present invention, provided is an information processing method including: performing a first process for performing a predetermined process related to an aircraft boarding procedure and acquiring boarding reservation information on a user; when the process is completed, performing a second process for matching biometric information acquired from the user with passport biometric information included in passport information acquired from a passport of the user and, when a result of the matching of the biometric information with the passport biometric information is that the matching is successful, associating the passport information, the biometric information, and the boarding reservation information with each other; and performing a switching process for switching whether to perform the first process or the second process.

#### Advantageous Effects of Invention

(9) According to the present invention, it is possible to easily implement a face authentication function to an existing check-in terminal.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram illustrating an example of an overall configuration of an information processing system in a first example embodiment.

(2) FIG. 2 is a diagram illustrating an example of information stored in a token ID information DB in the first example embodiment.

(3) FIG. 3 is a diagram illustrating an example of information stored in a passage history information DB in the first example embodiment.

(4) FIG. 4 is a diagram illustrating an example of information stored in an operation information DB in the first example embodiment.

(5) FIG. 5 is a diagram illustrating an example of information stored in a reservation information DB in the first example embodiment.

(6) FIG. 6 is a block diagram illustrating an example of a hardware configuration of the management server in the first example embodiment.

(7) FIG. 7 is a block diagram illustrating an example of a hardware configuration of a check-in terminal in the first example embodiment.

(8) FIG. 8 is a block diagram illustrating an example of a hardware configuration of an automatic baggage check-in machine in the first example embodiment.

(9) FIG. 9 is a block diagram illustrating an example of a hardware configuration of a security inspection apparatus in the first example embodiment.

(10) FIG. 10 is a block diagram illustrating an example of a hardware configuration of an automated gate apparatus in the first example embodiment.

(11) FIG. 11 is a block diagram illustrating an example of a hardware configuration of a boarding gate apparatus in the first example embodiment.

(12) FIG. 12 is a block diagram illustrating an example of a software configuration of the check-in terminal in the first example embodiment.

(13) FIG. 13 is a sequence diagram illustrating an example of a process of the check-in terminal and the management server in the first example embodiment.

(14) FIG. 14 is a sequence diagram illustrating an example of a process of the check-in terminal and the management server in the first example embodiment.

(15) FIG. 15 is a sequence diagram illustrating an example of a process of the automatic baggage

check-in machine and the management server in the first example embodiment.

(16) FIG. **16** is a sequence diagram illustrating an example of a process of the security inspection apparatus and the management server in the first example embodiment.

(17) FIG. **17** is a sequence diagram illustrating an example of a process of the automated gate apparatus and the management server in the first example embodiment.

(18) FIG. **18** is a sequence diagram illustrating an example of a process of the boarding gate apparatus and the management server in the first example embodiment.

(19) FIG. **19** is a block diagram illustrating a configuration of an information processing apparatus in a second example embodiment.

## DESCRIPTION OF EMBODIMENTS

(20) Exemplary embodiments of the present invention will be described below with reference to the drawings. Throughout the drawings, the same or corresponding components are labeled with the same references, and the description thereof may be omitted or simplified.

### First Example Embodiment

(21) FIG. **1** is a schematic diagram illustrating an example of an overall configuration of an information processing system **1** in the present example embodiment. The information processing system **1** is a computer system that supports operations related to a series of inspection procedures performed on a user (passenger) **U** using an airport **A**. The information processing system **1** is operated by a public institution such as an immigration control bureau or a trustee entrusted with the operation from such an institution, for example.

(22) In the information processing system **1** of the present example embodiment, a check-in terminal **20**, an automatic baggage check-in machine **30**, a security inspection apparatus **40**, an automated gate apparatus **50**, and a boarding gate apparatus **60** are connected to a shared management server **10** via a network **NW1**, respectively. Further, the check-in terminal **20**, the automatic baggage check-in machine **30**, the security inspection apparatus **40**, the automated gate apparatus **50**, and the boarding gate apparatus **60** are connected to a reservation system **2** of an airline company via a network **NW2**, respectively. The security inspection apparatus **40**, the automated gate apparatus **50**, and the boarding gate apparatus **60** are installed in a security area **SA** illustrated by a dashed line. The networks **NW1** and **NW2** is formed of a local area network (LAN) including a private communication network of the airport **A**, a wide area network (WAN), a mobile communication network, or the like. The connection scheme may be a wireless scheme without being limited to a wired scheme. Note that, for simplified illustration, FIG. **1** illustrates only terminal apparatuses (operation terminals) used for procedures for departure from a country via the airport **A**.

(23) The management server **10** manages operations related to inspection procedures in immigration of the user **U**. The management server **10** is installed in a facility of an airport company operating the airport **A**, an airline company, or the like, for example. Further, the management server **10** may be a cloud server instead of a server installed in the facility in which operations are actually performed. Note that the management server **10** is not necessarily required to be a single server and may be formed as a server group including a plurality of servers.

(24) As illustrated in FIG. **1**, the inspection procedures in the airport **A** for departure from country are sequentially performed at five touch points **P1** to **P5**. The relationship between each apparatus and the touch points **P1** to **P5** will be described below.

(25) The check-in terminal **20** is installed in a check-in lobby (hereafter, referred to as “touch point **P1**”) in the airport **A**. The check-in terminal **20** is a self-service terminal operated by the user **U** by himself/herself to perform a check-in procedure (boarding procedure). The check-in terminal **20** is also called a Common Use Self Service (CUSS) terminal. After completion of the check-in procedure at the touch point **P1**, the user **U** moves to a baggage check-in place or a security inspection site.

(26) The automatic baggage check-in machine **30** is installed in a region adjacent to a baggage

counter (manned counter) in the airport A or a region near the check-in terminal **20** (hereafter, referred to as “touch point P2”). The automatic baggage check-in machine **30** is a self-service terminal operated by the user U by himself/herself to perform procedure to check in baggage not carried in the aircraft (baggage check-in procedure). The automatic baggage check-in machine **30** is also called a Common Use Bag Drop (CUBD) terminal. After completion of the baggage check-in procedure, the user U moves to the security inspection site. Note that, when the user U does not check in his/her baggage, the procedure at the touch point P2 is omitted.

(27) The security inspection apparatus **40** is installed in the security inspection site (hereafter, referred to as “touch point P3”) in the airport A. The security inspection apparatus **40** is an apparatus that uses a metal detector to check whether or not the user U is wearing a metal object that may be a dangerous object. Note that the term “security inspection apparatus” in the present example embodiment is used as a meaning including not only a metal detector but also an X-ray inspection device that uses an X-ray to check whether or not there is a dangerous object in carry-on baggage or the like, a terminal device of a Passenger Reconciliation System (PRS) that determines whether or not to permit passage of the user U at the entrance of a security inspection site, or the like. After completion of the security inspection procedure with the security inspection apparatus **40** at the touch point P3, the user U moves to a departure inspection site.

(28) The automated gate apparatus **50** is installed in the departure inspection site (hereafter, referred to as “touch point P4”) in the airport A. The automated gate apparatus **50** is an apparatus that automatically performs a departure inspection procedure on the user U. After completion of the departure inspection procedure at the touch point P4, the user U moves to a departure area where duty free shops or boarding gates are provided.

(29) The boarding gate apparatus **60** is a passage control apparatus each installed at a boarding gate (hereafter, referred to as “touch point P5”) of the departure area. The boarding gate apparatus **60** is also called an Automated Boarding Gates (ABG) terminal. The boarding gate apparatus **60** confirms that the user U is a passenger of an aircraft that is available for boarding through the boarding gate. After completion of the procedure at the touch point P5, the user U boards the aircraft and departs from the country to a second country.

(30) Further, as illustrated in FIG. 1, the management server **10** has a token ID information DB **11**, a passage history information DB **12**, and an operation information DB **13**. Note that the database included in the management server **10** is not limited to these databases.

(31) FIG. 2 is a diagram illustrating an example of information stored in the token ID information DB **11**. The token ID information DB **11** has data items of a token ID, a group ID, a registered face image, a feature amount, a token issuance time, a token issuance device name, an invalidation flag, and an invalidation time. The token ID is an identifier that uniquely identifies ID information. The token ID in the present example embodiment is temporarily issued provided that there is a matching in a result of matching between a face image in which the user U possessing a passport is captured at the touch point P1 and a passport face image read from the passport. The token ID is then invalidated once the user U completes a procedure at the touch point P5 (boarding gate). That is, the token ID is not an identifier to be permanently used but as a one-time ID having a validated period (lifecycle).

(32) The group ID is an identifier used for grouping ID information. The registered face image is a face image registered for the user U. The feature amount is a value extracted from biometric information (registered face image). Note that, although the term of biometric information in the present example embodiment means a face image or a feature amount extracted from a face image, biometric information is not limited to a face image or a face feature amount. That is, biometric authentication may be performed by using an iris image, a fingerprint image, a palmprint image, an auricle image, or the like as biometric information on the user U.

(33) The token issuance time is a time that the management server **10** issued a token ID. The token issuance device name is a device name of an acquisition source of a registered face image that

triggered issuance of a token ID. The invalidation flag is flag information indicating whether or not the token ID is currently valid. In response to issuance of a token ID, the invalidation flag in the present example embodiment becomes a value of “1” indicating a state where the token ID is valid. Further, if a predetermined condition is satisfied, the invalidation flag is updated to a value of “0” indicating a state where the token ID is invalid. The invalidation time is a timestamp of a time that the invalidation flag was invalidated.

(34) FIG. 3 is a diagram illustrating an example of information stored in the passage history information DB 12. The passage history information DB 12 has data items of a passage history ID, a token ID, a passage time, a device name, an operation system type, and a passage touch point. The passage history ID is an identifier that uniquely identifies passage history information. The passage time is a timestamp at passage of a touch point. The device name is a machine name of an operation terminal used in a procedure at a touch point. The operation system type is a type of an operation system to which an operation terminal belongs. A passage touch point is a touch point by which the user passed. Note that, by extracting passage history information on a token ID basis, the management server 10 can know up to which touch point the user U has completed procedures.

(35) FIG. 4 is a diagram illustrating an example of information stored in the operation information DB 13. The operation information DB 13 has data items of a token ID, a passenger name, a reservation number, a departure place, a destination, an airline code, a flight number, a flight date, a seat number, a nationality, a passport number, a family name, a first name, a date of birth, and a sexuality. In such a way, the operation information DB 13 stores operation information related to predetermined operations on a token ID basis. In the present example embodiment, “predetermined operation” means a procedure operation performed at each of the touch points P1 to P5.

(36) The reservation number is an identifier that uniquely identifies boarding reservation information. The airline code is an identifier that uniquely identifies an airline company. Boarding reservation information included in operation information may be a passenger name, a reservation number, a departure place, a destination, an airline code, a flight number, a flight date, a seat number, a nationality, a passport number, a family number, a first name, a date of birth, a sexuality, or the like. The boarding reservation information can be acquired from a recording medium such as a passport, a boarding ticket, or the like. Further, the boarding reservation information can also be acquired from a reservation system 2 of an airline company by using a passport number, a reservation number, or the like as a key. The acquired boarding reservation information is then stored as operation information in the operation information DB 13.

(37) FIG. 5 is a diagram illustrating an example of information stored in a reservation information DB 3. The reservation information DB 3 has data items of a reservation number, an airline code, a passenger name, a departure place, a destination, a flight number, a flight date, a seat number, a seat class (for example, first class/business class/economy class), a nationality, a passport number, a family name, a first name, a date of birth, and a sexuality.

(38) In the present example embodiment, the operation information DB 13 and the reservation information DB 3 are associated with each other by a reservation number, a passport number, and an airline code. Once reading a reservation number, a passport number, and an airline code from an airline ticket medium presented by the passenger, the terminal devices (the check-in terminal 20 or the like) at respective touch points can query the reservation system 2 of an airline company corresponding to the airline code about boarding reservation information based on the reservation number or the passport number. Note that the method of querying the reservation system 2 about boarding reservation information is not limited to the above.

(39) Subsequently, the hardware of respective devices forming the information processing system 1 and software installed in the check-in terminal 20 will be described with reference to FIG. 6 to FIG. 12. Note that, in FIG. 6 to FIG. 12, devices having the same name but different references are devices having substantially the same function, and the detailed description thereof will thus be omitted in subsequent drawings.

(40) FIG. 6 is a block diagram illustrating an example of the hardware configuration of the management server **10**. As illustrated in FIG. 8, the management server **10** has a central processing unit (CPU) **101**, a random access memory (RAM) **102**, a storage device **103**, and a communication I/F **104**. Each device is connected to a bus line **105**.

(41) The CPU **101** is a processor having a function of performing a predetermined operation in accordance with a program stored in the storage device **103** and controlling each component of the management server **10**. The RAM **102** is formed of a volatile storage medium and provides a temporary memory area required for the operation of the CPU **101**.

(42) The storage device **103** is formed of a storage medium such as a nonvolatile memory, a hard disk drive, or the like. The storage device **103** stores a program executed by the CPU **101**, data referenced by the CPU **101** in execution of the program, or the like.

(43) The communication I/F **104** is a communication interface based on a specification such as Ethernet (registered trademark), Wi-Fi (registered trademark), 4G, or the like and is a module for communicating with the check-in terminal **20** or the like.

(44) FIG. 7 is a block diagram illustrating an example of the hardware configuration of the check-in terminal **20**. As illustrated in FIG. 9, the check-in terminal **20** has a CPU **201**, a RAM **202**, a storage device **203**, a communication I/F **204**, an input device **206**, a display device **207**, a medium reading device **208**, a biometric information acquisition device **209**, and a printer **210**. Each device is connected to a bus line **205**.

(45) The input device **206** is a pointing device such as a touch panel, a keyboard, or the like, for example. In the check-in terminal **20** of the present example embodiment, the display device **207** and the input device **206** are integrally formed as a touch panel. The display device **207** is a liquid crystal display device, an organic light emitting diode (OLED) display device, or the like and is used for displaying a moving image, a still image, a text, or the like.

(46) The medium reading device **208** is a device that reads a medium such as a passport, an airline ticket, or the like of the user U and acquires information recorded in the medium. The airline ticket medium may be, for example, a paper airline ticket, a mobile terminal displaying an e-ticket receipt, or the like.

(47) The medium reading device **208** is formed of a code reader, an image scanner, a contactless integrated circuit (IC) reader, an optical character reader (OCR) device, or the like, for example, and acquires information from various media presented to the reading unit thereof.

(48) The biometric information acquisition device **209** is a device that acquires a face image of the user U as biometric information on the user U. The biometric information acquisition device **209** is, for example, a digital camera used for capturing a face of the user U standing in front of the check-in terminal **20** and captures the face of the user U to acquire the face image. Note that, when an existing check-in terminal **20** does not have a biometric authentication function, the biometric information acquisition device **209** may be added to the check-in terminal **20** as a peripheral via a USB terminal or the like. The printer **210** prints a boarding ticket or the like on a predetermined sheet under the control of the CPU **201**.

(49) FIG. 8 is a block diagram illustrating an example of the hardware configuration of the automatic baggage check-in machine **30**. As illustrated in FIG. 10, the automatic baggage check-in machine **30** has a CPU **301**, a RAM **302**, a storage device **303**, a communication I/F **304**, an input device **306**, a display device **307**, a medium reading device **308**, a biometric information acquisition device **309**, a baggage transport device **310**, and an output device **311**. Each device is connected to a bus line **305**.

(50) The baggage transport device **310** transports baggage of the user U for loading the baggage to the aircraft that the user U boards. The baggage transport device **310** transports, to a baggage handling place, baggage which is placed on receiving part by the user U and to which a baggage tag is attached.

(51) The output device **311** is a device that outputs a baggage tag to be attached to checking-in



baggage. Further, the output device **311** outputs a baggage claim tag that is necessary when the user U claims his/her baggage after arriving at the destination. Note that a baggage tag or a baggage claim tag is associated with at least one of a passport number, a reservation number, and a token ID.

(52) FIG. **9** is a block diagram illustrating an example of the hardware configuration of the security inspection apparatus **40**. As illustrated in FIG. **11**, the security inspection apparatus **40** has a CPU **401**, a RAM **402**, a storage device **403**, a communication I/F **404**, an input device **406**, a display device **407**, a medium reading device **408**, a biometric information acquisition device **409**, and a metal detector gate **410**. Each device is connected to a bus line **405**.

(53) The metal detector gate **410** is a gate type metal detector and detects a metal object worn by the user U passing through the metal detector gate **410**.

(54) FIG. **10** is a block diagram illustrating an example of the hardware configuration of the automated gate apparatus **50**. The automated gate apparatus **50** has a CPU **501**, a RAM **502**, a storage device **503**, a communication I/F **504**, an input device **506**, a display device **507**, a medium reading device **508**, a biometric information acquisition device **509**, and a gate **511**. Each device is connected to a bus line **505**.

(55) The gate **511** transitions from a closed state to block passage of the user U during standby to an open state to permit passage of the user U under the control of the CPU **501** when identity verification of the user U at the automated gate apparatus **50** is successful and the user U has passed through the departure inspection. The scheme of the gate **511** is not particularly limited, and the gate **511** may be, for example, a flapper gate in which one or more flappers provided to one side or both sides of a passage are opened and closed, a turn style gate in which three bars are revolved, or the like.

(56) FIG. **11** is a block diagram illustrating an example of the hardware configuration of the boarding gate apparatus **60**. As illustrated in FIG. **13**, the boarding gate apparatus **60** has a CPU **601**, a RAM **602**, a storage device **603**, a communication I/F **604**, an input device **606**, a display device **607**, a biometric information acquisition device **609**, and a gate **611**. Each device is connected to a bus line **605**.

(57) FIG. **12** is a block diagram illustrating an example of the software configuration of the check-in terminal **20**. The check-in terminal **20** has operating system (OS) **21**, middleware **22**, an airline application **23**, and a token issuing application **24**.

(58) The OS **21** provides standard interface to the user and applications (the airline application **23** and the token issuing application **24**) and manages each resource such as hardware. Specifically, the OS **21** performs management of the storage device **203**, memory management such as virtual storage, process management such as multitask, control of graphical user interface (GUI), communication control, and the like.

(59) The middleware **22** is software that plays an intermediate role between the OS **21** that performs basic control of a computer and an application that performs each operation process. In other words, the middleware **22** is software that expands the function of the OS **21** or gathers functions common to applications (the airline application **23** and the token issuing application **24**).

(60) In FIG. **12**, scanner control MW1, printer control MW2, display control MW3, communication control MW4, camera control MW5, and event detection MW6 are illustrated as examples for the middleware **22**. When an application outputs a request to the middleware **22**, the middleware **22** outputs a necessary request to the OS **21**. The OS **21** then returns a process result to the application. Furthermore, the middleware **22** controls startup, stop, monitoring, and the like of each application.

(61) The airline application **23** is an application for communicating with a host computer (not illustrated) of the reservation system **2** of an airline company and performing an aircraft check-in procedure (boarding procedure) based on information on operation input performed by the user U.

(62) The airline application **23** of the present example embodiment sequentially displays a

dangerous object inquiry screen, a reservation information search method searching screen, a reservation information confirmation screen, and the like on the display device **207** in cooperation with the middleware **22** in response to a request for a check-in procedure from the user U, then performs a check-in procedure based on information on the operation input performed by the user U, and controls the printer **210** to print a boarding ticket. Note that the airline application **23** is provided on an airline company basis. For example, when a single check-in terminal **20** is used for check-in procedures to a plurality of airline companies, a plurality of airline applications **23** may be installed. Further, the display order of screens and displayed screens differ for respective airline applications **23**.

(63) On the other hand, the token issuing application **24** is an application installed for newly implementing a face authentication function to the check-in terminal **20**. The token issuing application **24** of the present example embodiment has, in cooperation with the middleware **22**, a function of acquiring biometric information on the user U (a captured face image) by using the biometric information acquisition device **209** and a function of reading passport information from a passport by using the medium reading device **208**.

(64) Furthermore, the token issuing application **24** has a function of matching biometric information on the user U with a passport face image included in passport information and a function of issuing a token ID on a user U basis if a result of the matching is that the matching is successful and storing face images of the user U (a captured face image, a passport face image) and boarding reservation information in association with each other. Specifically, the token issuing application **24** sequentially displays a passport information registration screen, a biometric information registration screen, and the like on the display device **207**, performs a reading process or a matching process described above based on information on operation input from the user U, and outputs a result of the process to the airline application **23** or the management server **10**.

(65) Note that the middleware **22**, the airline application **23**, and the token issuing application **24** of the present example embodiment are all created in compliance with the rules defined by International Air Transport Association (IATA).

(66) Subsequently, the operation of respective devices in the information processing system **1** in the present example embodiment will be described with reference to FIG. **13** to FIG. **18**.

(67) [Check-In Procedure]

(68) FIG. **13** and FIG. **14** are sequence diagrams illustrating an example of the process of the check-in terminal **20** and the management server **10**. This process is performed when the user U uses the check-in terminal **20** to perform a check-in procedure.

(69) First, the check-in terminal **20** displays an initial screen on the display device **207** by using the airline application **23** (step **S101**). Next, the check-in terminal **20** determines whether or not check-in has been requested by the user U (step **S102**) and stands by until a check-in request is made (step **S102**, NO).

(70) Next, if the check-in terminal **20** determines that check-in has been requested by the user U (step **S102**, YES), the process proceeds to step **S103**.

(71) In step **S103**, the check-in terminal **20** displays the dangerous object inquiry screen on the display device **207**. After confirmation by the user U is completed, the check-in terminal **20** displays the reservation search screen on the display device **207** (step **S104**). A search method for reservation information may be a method using an e-ticket number, a reservation number, a passport number, or a two-dimensional barcode, for example.

(72) Next, the check-in terminal **20** determines whether or not a search method is specified by the user U on the reservation search screen (step **S105**) and stands by until a search method is specified (step **S105**, NO).

(73) Next, if the check-in terminal **20** determines that a search method is specified (step **S105**, YES), the check-in terminal **20** performs a process of searching for reservation information based on the specified method (step **S106**). In this step, the check-in terminal **20** holds a search result in

the storage device **203** or the RAM **202**.

(74) Next, the check-in terminal **20** starts the token issuing application **24** (step **S107**) and switches the application that controls the screen from the airline application **23** to the token issuing application **24** (step **S108**).

(75) Next, the check-in terminal **20** displays the passport information registration screen on the display device **207** by using the token issuing application **24** (step **S109**), then determines whether or not the passport of the user **U** is presented to the reading unit of the medium reading device **208** (step **S110**), and stands by until a passport is presented (step **S110**, NO).

(76) Next, if the check-in terminal **20** determines that a passport is presented to the reading unit of the medium reading device **208** (step **S110**, YES), the check-in terminal **20** acquires passport information on the user **U** from the presented passport by using the token issuing application **24** (step **S111**). The acquired passport information includes a passport face image of the user **U**, identity verification information, a passport number, a passport issuance nation, or the like. In this step, the check-in terminal **20** (token issuing application **24**) holds the passport information in the storage device **203** or the RAM **202**.

(77) Next, the check-in terminal **20** displays the face image registration screen on the display device **207** by using the token issuing application **24** (step **S112**) and determines whether or not a consent about registration of a face image is obtained from the user **U** (step **S113**). For example, it is preferable to display a guidance message such as “By registering your face image, you can easily perform the following procedures required before departure through face recognition. The registered face image will be deleted from the system after boarding is completed.” on a face image registration screen and obtain the consent from the user **U**.

(78) If the check-in terminal **20** determines that a consent about registration of a face image is obtained from the user **U** (step **S113**, YES), the process proceeds to step **S114**. In contrast, if the check-in terminal **20** determines that a consent about registration of a face image is not obtained from the user **U** (step **S113**, NO), the process proceeds to step **S117**.

(79) In step **S114**, the check-in terminal **20** captures the user **U** to acquire a face image from the captured image. The check-in terminal **20** then matches the face image with the passport face image in a one-to-one manner (step **S115**).

(80) Next, the check-in terminal **20** determines whether or not a result of the matching of the captured face image with the passport face image is that the matching is successful (step **S116**). Herein, if the check-in terminal **20** determines that the result of the matching is that the matching is successful (step **S116**, YES), the process proceeds to step **S117**. In contrast, if the check-in terminal **20** determines that the result of the matching is that the matching failed (step **S116**, NO), the check-in terminal **20** notifies the user of an error message (step **S118**). For example, a notification screen including a message such as “Please perform a check-in procedure at the manned counter” is displayed on the display device **207**.

(81) In step **S117**, the check-in terminal **20** switches the application that controls the screen from the token issuing application **24** to the airline application **23**. The check-in terminal **20** then displays the reservation information confirmation screen by using the airline application **23** (step **S119**). The reservation information held in the storage device **203** or the like in step **S106** is displayed in the reservation information confirmation screen. The user may confirm reservation information in the reservation information confirmation screen and apply for a seat change or the like.

(82) Next, the check-in terminal **20** determines whether or not confirmation of reservation information performed by the user **U** is completed (step **S120**). Herein, if the check-in terminal **20** determines that confirmation of the reservation information is completed (step **S120**, YES), the process proceeds to step **S121**. In contrast, if the check-in terminal **20** determines that confirmation of the reservation information is not completed (step **S120**, NO), the check-in terminal **20** stands by until confirmation is completed.

(83) In step **S121**, the check-in terminal **20** prints a boarding ticket by using the printer **210** and displays a check-in completion screen on the display device **207** by using the airline application **23** (step **S122**).

(84) Next, in response to the completion of the check-in procedure, the check-in terminal **20** determines whether or not the user **U** is a subject for issuance of a token ID (step **S123**). Specifically, if it has been determined in the process of steps **S113** to **S116** that the result of matching of the passport face image with the captured face image is that the matching is successful and the user **U** is a person whose face image can be registered in a database, the user **U** is determined to be a subject for issuance of a token ID. Herein, if the check-in terminal **20** determines that the user **U** is a subject for issuance of a token ID (step **S123**, YES), the check-in terminal **20** transmits request data including an issuance request for a token ID and a registration request for the passage history information, the passport information, the captured face image, and the boarding reservation information (boarding information) to the management server **10** (step **S124**). In contrast, if the check-in terminal **20** determines that the user **U** is not a subject for issuance of a token ID (step **S123**, NO), the process proceeds to step **S130**.

(85) Next, in response to receiving the request data from the check-in terminal **20**, the management server **10** issues a token ID (step **S125**). The token ID is set to a unique value based on date and time of processing or a sequence number, for example.

(86) Next, the management server **10** uses the captured face image as a registered face image and registers the relationship between the token ID and the registered face image information to the token ID information DB **11** (step **S126**).

(87) In the present example embodiment, the reason why a captured face image captured on site is used as a registered face image is that the validated period (lifecycle) of a token ID expires within the day, that a captured face image is of closer quality (appearance) to an image captured in a subsequent authentication process than a passport face image, or the like. However, instead of a captured face image, a passport face image may be set to a registered face image (registered biometric information). For example, when the lifecycle of a token ID is long (for example, when a token ID is validated for a certain validated period for a membership in the airline business or the like), a face image of a passport or a license can be set as a registered face image.

(88) Next, the management server **10** uses passport information and boarding reservation information as operation information to register the relationship between the token ID and the operation information to the operation information DB **13** (step **S127**). In such a way, while control data required for face authentication and operation information required for performing operation are managed in separate databases, a registered face image and the operation information are associated with each other by a token ID. Further, the passport face image of the user **U** may be further registered in the operation information DB **13** or the token ID information DB **11**.

(89) Next, the management server **10** registers passage history information indicating the relationship between the token ID and passage information at the touch point **P1** to the passage history information DB **12** (step **S128**).

(90) The management server **10** then transmits response data including respective process results of the token ID issuance process, the operation information registration process, and the passage history information registration process to the check-in terminal **20** (step **S129**). The check-in terminal **20** ends the token issuing application **24** based on reception of the determination result of step **S123** or the response data from the management server **10** (step **S130**) and ends the process of FIG. **13** and FIG. **14**.

(91) In such a way, a target face image (captured face image) successfully matched with a passport face image acquired from a passport in a check-in procedure is registered to the token ID information DB **11** as a registered face image, and a registered face image and operation information of the operation information DB **13** are associated with each other by the issued token ID. This enables a matching process between the captured face image and the registered face image

to be made at each subsequent touch point. That is, the token ID associated with the registered face image is identification information that can be commonly used at all the touch points. The use of such a commonized token ID can increase efficiency of inspection on the user U.

(92) [Baggage Check-In Procedure]

(93) FIG. 15 is a sequence diagram illustrating an example of the process of the automatic baggage check-in machine **30** and the management server **10**. This process is performed when the user U who completed a check-in procedure is subjected to a baggage check-in procedure as needed.

(94) The automatic baggage check-in machine **30** captures an image of an area in front of the machine continually or periodically and determines whether or not a face of the user U standing in front of the automatic baggage check-in machine **30** is detected in the captured image (step S201). The automatic baggage check-in machine **30** stands by until a face of the user U is detected in an image by the biometric information acquisition device **309** (step S201, NO).

(95) If the automatic baggage check-in machine **30** determines that a face of the user U is detected by the biometric information acquisition device **309** (step S201, YES), the automatic baggage check-in machine **30** captures the face of the user U and acquires a face image of the user U as a target face image (step S202).

(96) Next, the automatic baggage check-in machine **30** transmits the request data that requests execution of a matching process between the target face image and the registered face image to the management server **10** (step S203).

(97) In response to receiving the request data from the automatic baggage check-in machine **30**, the management server **10** performs matching of a face image of the user U (step S204). That is, the management server **10** matches the target face image included in the request data received from the automatic baggage check-in machine **30** with a plurality of registered face images registered in the token ID information DB **11** on a one-to-N basis. Note that the registered face images to be matched are limited to images associated with a token ID whose invalidation flag value is "1" (valid).

(98) Herein, if the management server **10** determines that the result of matching is that the matching failed (step S205, NO), the management server **10** transmits the response data including matching result information indicating the failed matching to the automatic baggage check-in machine **30** (step S207), and the process proceeds to step S209. In contrast, if the management server **10** determines that the result of matching is that the matching is successful (step S205, YES), the process proceeds to step S206.

(99) In step S206, the management server **10** acquires operation information from the operation information DB **13** by using, as a key, the token ID associated with the successfully matched registered face image in the token ID information DB **11**. The management server **10** then transmits the response data to the automatic baggage check-in machine **30** (step S208).

(100) Next, if the automatic baggage check-in machine **30** references the response data and determines that it is possible to perform the procedure (step S209, YES), the automatic baggage check-in machine **30** performs a process of a baggage check-in procedure for the user U (step S210).

(101) Next, the automatic baggage check-in machine **30** transmits request data that requests registration of passage history information on the user U to the management server **10** (step S211).

(102) In response to receiving the request data from the automatic baggage check-in machine **30**, the management server **10** registers passage history information indicating the relationship between the token ID and passage information on the user U at the touch point P2 to the passage history information DB **12** (step S212).

(103) The management server **10** then transmits the response data to the automatic baggage check-in machine **30** (step S213) and ends the process.

(104) On the other hand, if the automatic baggage check-in machine **30** references the response data and determines that it is not possible to perform the procedure (step S209, NO), the automatic

baggage check-in machine **30** notifies the user U of an error message (step **S214**). For example, a notification screen including a message such as “Please check in your baggage at the manned counter.” is displayed on the display device **307**.

(105) [Security Inspection Procedure]

(106) FIG. **16** is a sequence diagram illustrating an example of the process of the security inspection apparatus **40** and the management server **10**. This process is performed when the user U who completed a check-in procedure is subjected to a security inspection procedure.

(107) The security inspection apparatus **40** captures an image of an area in front of the entrance of the security inspection site continually or periodically and determines whether or not a face of the user U standing in front of the entrance is detected in the captured image (step **S301**). The security inspection apparatus **40** stands by until a face of the user U is detected in an image by the biometric information acquisition device **409** (step **S301**, NO).

(108) If the security inspection apparatus **40** determines that a face of the user U is detected by the biometric information acquisition device **409** (step **S301**, YES), the security inspection apparatus **40** captures the face of the user U and acquires a face image of the user U as a target face image (step **S302**).

(109) Next, the security inspection apparatus **40** transmits the request data that requests execution of a matching process between the target face image and the registered face image to the management server **10** (step **S303**).

(110) In response to receiving the request data from the security inspection apparatus **40**, the management server **10** performs matching of a face image of the user U (step **S304**). That is, the management server **10** matches the target face image included in the request data received from the security inspection apparatus **40** with a plurality of registered face images registered in the token ID information DB **11** on a one-to-N basis. Note that the registered face images to be matched are limited to images associated with a token ID whose invalidation flag value is “1” (valid).

(111) Herein, if the management server **10** determines that the result of matching is that the matching failed (step **S305**, NO), the management server **10** transmits the response data including the result of matching of the failed matching to the security inspection apparatus **40** (step **S307**), and the process proceeds to step **S309**. In contrast, if the management server **10** determines that the result of matching is that the matching is successful (step **S305**, YES), the process proceeds to step **S306**.

(112) In step **S306**, the management server **10** acquires operation information from the operation information DB **13** by using, as a key, the token ID associated with the successfully matched registered face image in the token ID information DB **11**. The management server **10** then transmits the response data including the matching result information, the token ID, and the operation information to the security inspection apparatus **40** (step **S308**).

(113) Next, if the security inspection apparatus **40** references the response data and determines that it is possible to perform the procedure (step **S309**, YES), the security inspection apparatus **40** performs a security inspection process on the user U (step **S310**). In the security inspection process, the CPU **401** controls each component of the security inspection apparatus **40**. Accordingly, the security inspection apparatus **40** detects a metal object worn by the user U passing through the metal detector gate **410**. The user U who has passed through the metal detector gate **410** moves to the departure inspection site.

(114) Next, the security inspection apparatus **40** transmits the request data that requests registration of passage history information on the user U to the management server **10** (step **S311**).

(115) In response to receiving the request data from the security inspection apparatus **40**, the management server **10** registers passage history information indicating the relationship between the token ID and passage information on the user U at the touch point **P3** to the passage history information DB **12** (step **S312**).

(116) The management server **10** then transmits the response data to the security inspection

apparatus **40** (step **S313**) and ends the process.

(117) On the other hand, if the security inspection apparatus **40** references the response data and determines that it is not possible to perform the procedure (step **S309**, NO), the security inspection apparatus **40** notifies the user **U** of an error message (step **S314**). For example, a notification screen including a message such as “A staff member will come. Please wait a moment” is displayed on the display device **407**.

(118) [Departure Inspection Procedure]

(119) FIG. **17** is a sequence diagram illustrating an example of the process of the automated gate apparatus **50** and the management server **10**. This process is performed when the user **U** who completed a security inspection procedure is subjected to a departure inspection procedure.

(120) The automated gate apparatus **50** captures an image of an area in front of the automated gate apparatus **50** continually or periodically and determines whether or not a face of the user **U** standing in front of the automated gate apparatus **50** is detected in the captured image (step **S401**). The automated gate apparatus **50** stands by until a face of the user **U** is detected in an image by the biometric information acquisition device **509** (step **S401**, NO).

(121) If the automated gate apparatus **50** determines that a face of the user **U** is detected by the biometric information acquisition device **509** (step **S401**, YES), the automated gate apparatus **50** captures the face of the user **U** and acquires a face image of the user **U** as a target face image (step **S402**).

(122) Next, the automated gate apparatus **50** transmits the request data that requests execution of a matching between the target face image and the process registered face image to the management server **10** (step **S403**).

(123) In response to receiving the request data from the automated gate apparatus **50**, the management server **10** performs matching of a face image of the user **U** (step **S404**). That is, the management server **10** matches the target face image included in the request data received from the automated gate apparatus **50** with a plurality of registered face images registered in the token ID information DB **11** on a one-to-N basis. Note that the registered face images to be matched are limited to images associated with a token ID whose invalidation flag value is “1” (valid).

(124) Herein, if the management server **10** determines that the result of matching is that the matching failed (step **S405**, NO), the management server **10** transmits the response data including matching result information indicating the failed matching to the automated gate apparatus **50** (step **S407**), and the process proceeds to step **S409**. In contrast, if the management server **10** determines that the result of matching is that the matching is successful (step **S405**, YES), the process proceeds to step **S406**.

(125) In step **S406**, the management server **10** acquires operation information from the operation information DB **13** by using, as a key, the token ID associated with the successfully matched registered face image in the token ID information DB **11**. The management server **10** then transmits the response data including the matching result information, the token ID, and the operation information to the automated gate apparatus **50** (step **S408**).

(126) Next, if the automated gate apparatus **50** references the response data and determines that it is possible to perform the procedure (step **S409**, YES), the automated gate apparatus **50** performs a departure inspection procedure on the user **U** and opens the gate **511** (step **S410**). The user **U** who has passed through the touch point **P4** moves to the departure area where a boarding gate is present.

(127) Next, the automated gate apparatus **50** transmits the request data that requests registration of passage history information on the user **U** to the management server **10** (step **S411**).

(128) In response to receiving the request data from the automated gate apparatus **50**, the management server **10** registers passage history information indicating the relationship between the token ID and passage information on the user **U** at the touch point **P4** to the passage history information DB **12** (step **S412**).

(129) The management server **10** then transmits the response data to the automated gate apparatus

**50** (step **S413**) and ends the process.

(130) On the other hand, if the automated gate apparatus **50** references the response data and determines that it is not possible to perform the procedure (step **S409**, NO), the automated gate apparatus **50** notifies the user **U** of an error message (step **S414**). For example, a notification screen including a message such as “Please perform a departure inspection procedure at the manned counter.” is displayed on the display device **507**.

(131) [Identity Verification Procedure at Boarding Gate]

(132) FIG. **18** is a sequence diagram illustrating an example of the process of the boarding gate apparatus **60** and the management server **10**. This process is performed when the user **U** who completed a departure inspection procedure passes through a boarding gate in order to board an aircraft.

(133) The boarding gate apparatus **60** captures an image of an area in front of the apparatus continually or periodically and determines whether or not a face of the user **U** standing in front of the boarding gate apparatus **60** is detected in the captured image (step **S501**). The boarding gate apparatus **60** stands by until a face of the user **U** is detected in an image by the biometric information acquisition device **609** (step **S501**, NO).

(134) If the boarding gate apparatus **60** determines that a face of the user **U** is detected by the biometric information acquisition device **609** (step **S501**, YES), the boarding gate apparatus **60** captures the face of the user **U** and acquires a face image of the user **U** as a target face image (step **S502**).

(135) Next, the boarding gate apparatus **60** transmits the request data that requests execution of a matching process between the target face image and the registered face image to the management server **10** (step **S503**).

(136) In response to receiving the request data from the boarding gate apparatus **60**, the management server **10** performs matching of a face image of the user **U** (step **S504**). That is, the management server **10** matches the target face image included in the request data received from the boarding gate apparatus **60** with a plurality of registered face images registered in the token ID information DB **11** on a one-to-N basis. Note that the registered face images to be matched are limited to images associated with a token ID whose invalidation flag value is “1” (valid).

(137) Herein, if the management server **10** determines that the result of matching is that the matching failed (step **S505**, NO), the management server **10** transmits the response data including matching result information indicating the failed matching to the boarding gate apparatus **60** (step **S507**), and the process proceeds to step **S509**. In contrast, if the management server **10** determines that the result of matching is that the matching is successful (step **S505**, YES), the process proceeds to step **S506**.

(138) In step **S506**, the management server **10** acquires operation information from the operation information DB **13** by using, as a key, the token ID associated with the successfully matched registered face image in the token ID information DB **11**. The management server **10** then transmits the response data including the matching result information, the token ID, and the operation information to the boarding gate apparatus **60** (step **S508**).

(139) Next, if the boarding gate apparatus **60** references the response data and determines that it is possible to perform the procedure (step **S509**, YES), the boarding gate apparatus **60** performs an aircraft boarding procedure on the user **U** and opens the gate **611** (step **S510**). The user **U** who has passed through the touch point **P5** boards the aircraft.

(140) Next, the boarding gate apparatus **60** transmits the request data that requests invalidation of the token ID and registration of passage history information on the user **U** to the management server **10** (step **S511**).

(141) In response to receiving the request data from the boarding gate apparatus **60**, the management server **10** updates the token ID information DB **11** (step **S512**). Specifically, the management server **10** updates the invalidation flag of the token ID information DB **11** to a value



of invalid (“0”). Accordingly, the validated period (lifecycle) of the token ID expires.

(142) Next, the management server **10** registers passage history information indicating the relationship between the token ID and passage information on the user U at the touch point P5 to the passage history information DB **12** (step S513).

(143) The management server **10** then transmits the response data to the boarding gate apparatus **60** (step S514) and ends the process.

(144) On the other hand, if the boarding gate apparatus **60** references the response data and determines that it is not possible to perform the procedure (step S509, NO), the boarding gate apparatus **60** notifies the user U of an error message (step S515). For example, the boarding gate apparatus **60** displays a notification screen including a message such as “Please perform the procedure at the manned counter.” on the display device **607**.

(145) As described above, according to the present example embodiment, in a check-in procedure, a series of processes related to biometric authentication (steps S107 to S112 of FIG. 13 and steps S113 to S117 of FIG. 14) and a token ID issuance request (step S124 of FIG. 14) are performed based on control of the token issuing application **24** and the middleware **22**. It is thus possible to easily implement a biometric authentication function by simply installing the token issuing application **24** separately to an existing check-in terminal **20** having no biometric authentication function and modifying a part of the middleware **22**.

(146) Further, the token issuing application **24** (second processing unit) performs a process of acquiring biometric information, a process of reading passport information, and a matching process before the elapsed time from completion of the process in the airline application **23** (first processing unit) reaches a predetermined time limit. Specifically, since biometric authentication is performed by using a waiting time after the process of inquiry about a dangerous object or the like is performed at the check-in terminal **20**, it is possible to implement a biometric authentication function without affecting a process of an existing airline application **23**. Further, in a general check-in terminal **20**, a sufficient operation time (time limit) has been set from a time of displaying a passport information registration screen that requests the user U to perform a passport reading operation to a time of allowing the user U to complete the passport reading operation. It is thus preferable to start measuring the elapsed time described above from the time of displaying the passport information registration screen.

#### Second Example Embodiment

(147) FIG. 19 is a block diagram illustrating a configuration of the information processing apparatus **100** in a second example embodiment. The information processing apparatus **100** includes a first processing unit **100A**, a second processing unit **100B**, and a switching unit **100C**. The first processing unit **100A** performs a predetermined process related to an aircraft boarding procedure and acquires boarding reservation information on a user. When the process is completed, the second processing unit matches biometric information acquired from the user with passport biometric information included in passport information acquired from the user's passport and, when a result of the matching of the biometric information with the passport biometric information is that the matching is successful, associates the passport information, the biometric information, and the boarding reservation information with each other. The switching unit **100C** switches whether to operate the first processing unit or the second processing unit. According to the present example embodiment, it is possible to easily implement a face authentication function to an existing check-in terminal **20**.

#### Modified Example Embodiment

(148) Although the present invention has been described above with reference to the example embodiments, the present invention is not limited to the example embodiments described above. Various modifications that can be understood by those skilled in the art can be made to the configuration and details of the present invention within the scope not departing from the spirit of the present invention. For example, it should be understood that an example embodiment in which

a configuration of a part of any of the example embodiments is added to another example embodiment or an example embodiment in which a configuration of a part of any of the example embodiments is replaced with a configuration of a part of another example embodiment is also an example embodiment to which the present invention may be applied.

(149) Although the configuration that performs a matching process between a captured face image and a passport face image at the check-in terminal **20** (token issuing application **24**) has been described in the above example embodiments, the matching process may be performed on the management server **10** side. That is, the check-in terminal **20** may be configured to transmit request data including a captured face image and a passport face image to the management server **10** and receive a result of the matching from the management server **10**. In such a case, since only the management server **10** needs to have a matching function, the function to be added to the check-in terminal **20** can be reduced.

(150) Although the configuration in which the airline application **23** and the token issuing application **24** are installed in terminal the check-in **20** has been described in the above example embodiment, each application may be implemented as a web application. In such a case, the check-in terminal **20** can transmit request data to the host computer of the reservation system **2** and the management server **10** of the present system by using browser applications (not illustrated), respectively, and perform screen display based on response data received from applications on the host computer and the management server **10** side, respectively.

(151) In the above example embodiments, the case where the check-in terminal **20** switches the application that controls a display screen from the airline application **23** to the token issuing application **24** before a passport reading operation takes place has been described. However, the passport registration screen may be displayed by the airline application **23**, and when a passport reading operation is detected, the screen may be switched. That is, the passport reading function may be implemented in any of the airline application **23** and the token issuing application **24**.

(152) The scope of each of the example embodiments also includes a processing method that stores, in a storage medium, a program that causes the configuration of each of the example embodiments to operate so as to implement the function of each of the example embodiments described above, reads the program stored in the storage medium as a code, and executes the program in a computer. That is, the scope of each of the example embodiments also includes a computer readable storage medium. Further, each of the example embodiments includes not only the storage medium in which the program described above is stored but also the individual program itself.

(153) As the storage medium, for example, a floppy (registered trademark) disk, a hard disk, an optical disk, a magneto-optical disk, a CD-ROM, a magnetic tape, a nonvolatile memory card, or the like can be used. Further, the scope of each of the example embodiments also includes an example that operates on OS to perform a process in cooperation with another software or a function of an add-in board without being limited to an example that performs a process by an individual program stored in the storage medium.

(154) The whole or part of the example embodiments disclosed above can be described as, but not limited to, the following supplementary notes.

#### Supplementary Note 1

(155) A program that causes a computer to perform: performing a first process for performing a predetermined process related to an aircraft boarding procedure and acquiring boarding reservation information on a user; when the process is completed, performing a second process for matching biometric information acquired from the user with passport biometric information included in passport information acquired from a passport of the user and, when a result of the matching of the biometric information with the passport biometric information is the matching is that successful, passport information, the biometric information, and the boarding reservation information with each other; and performing a switching process for switching whether to perform the first process

or the second process.

#### Supplementary Note 2

(156) The program according to supplementary note 1, wherein in the switching process, a screen to be displayed on a display device is switched from a first screen controlled by the first process to a second screen controlled by the second process.

#### Supplementary Note 3

(157) The program according to supplementary note 2, wherein in the switching process, the second process is started to switch the screen when the process is completed and occurrence of an operation of reading the passport is detected.

#### Supplementary Note 4

(158) The program according to supplementary note 2, wherein in the switching process, the second process is started to switch the screen after the process is completed and before an operation of reading the passport takes place.

#### Supplementary Note 5

(159) The program according to any one of supplementary notes 1 to 4, wherein in the second process, a process of acquiring the biometric information, a process of reading the passport information, and a matching process are performed before an elapsed time from completion of the process in the first process reaches a predetermined time limit.

#### Supplementary Note 6

(160) The program according to any one of supplementary notes 1 to 5, wherein in the second process, the passport information, the biometric information, and the boarding reservation information are transmitted to a server apparatus to be connected, and an identifier that associates the passport information, the biometric information, and the boarding reservation information with each other is issued.

#### Supplementary Note 7

(161) The program according to any one of supplementary notes 1 to 6, wherein in the first process, the boarding reservation information is acquired based on a process of reading an airline ticket medium possessed by the user.

#### Supplementary Note 8

(162) The program according to any one of supplementary notes 1 to 6, wherein in the first process, based on the passport information read in the second process, the boarding reservation information is acquired from a computer system managed by an airline company.

#### Supplementary Note 9

(163) The program according to any one of supplementary notes 1 to 8, wherein the biometric information is any of a face image, an iris image, and a fingerprint image.

#### Supplementary Note 10

(164) An information processing apparatus comprising: a first processing unit that performs a predetermined process related to an aircraft boarding procedure and acquires boarding reservation information on a user; a second processing unit that, when the process is completed, matches biometric information acquired from the user with passport biometric information included in passport information acquired from a passport of the user and, when a result of the matching of the biometric information with the passport biometric information is that the matching is successful, associates the passport information, the biometric information, and the boarding reservation information with each other; and a switching unit that switches whether to perform the first processing unit or the second processing unit.

#### Supplementary Note 11

(165) An information processing method comprising: performing a first process for performing a predetermined process related to an aircraft boarding procedure and acquiring boarding reservation information on a user; when the process is completed, performing a second process for matching biometric information acquired from the user with passport biometric information included in

passport information acquired from a passport of the user and, when a result of the matching of the biometric information with the passport biometric information is that the matching is successful, associating the passport information, the biometric information, and the boarding reservation information with each other; and performing a switching process for switching whether to perform the first process or the second process.

#### REFERENCE SIGNS LIST

(166) NW1, NW2 network 1 information processing system 2 reservation system 10 management server 11 token ID information DB 12 passage history information DB 13 operation information DB 20 check-in terminal 23 airline application 24 token issuing application 30 automatic baggage check-in machine 40 security inspection apparatus 50 automated gate apparatus 60 boarding gate apparatus 100 information processing apparatus 100A first processing unit 100B second processing unit 100C switching unit

#### Claims

1. A non-transitory computer-readable medium storing a program executable by a computer to perform processing comprising: acquiring passport information on a user from a first terminal employed in a first procedure that a passenger performs regarding the boarding process; acquiring a first biometric information on the user from the first terminal; acquiring boarding reservation information on the user; and issuing a token ID associated with the passport information, the biometric information, and the boarding reservation information, wherein the token ID is invalidated in a case in which the user boards an aircraft, wherein the token ID after being issued, is identified by matching the second biometric information of the user acquired by a second terminal used for the second procedure related to the boarding process with the first biometric information, and wherein the identified token ID is used to determine, based on the passport information and boarding reservation information associated with the token ID, whether the user can carry out the second procedure at the second terminal.
2. The non-transitory computer-readable medium according to claim 1, wherein the processing further comprises: controlling an authentication process between the biometric information acquired from the user and passport biometric information included in the passport information.
3. The non-transitory computer-readable medium according to claim 2, wherein acquiring the boarding reservation information on the user, in a case in which the authentication process is completed, comprises acquiring the boarding reservation information via a server of an airline company based on the passport information, wherein the server stores the passport information of the user acquired at the time of reservation of a flight ticket in association with the boarding reservation information.
4. An information processing apparatus comprising: a memory storing instructions; and a processor configured to execute the instructions to: acquire passport information on a user from a first terminal employed in a first procedure that a passenger performs regarding the boarding process; acquire a first biometric information on the user from the first terminal; acquire boarding reservation information on the user; and issue a token ID associated with the passport information, the biometric information, and the boarding reservation information, wherein the token ID is invalidated in a case in which the user boards an aircraft, wherein the token ID after being issued, is identified by matching the second biometric information of the user acquired by a second terminal used for the second procedure related to the boarding process with the first biometric information, and wherein the identified token ID is used to determine, based on the passport information and boarding reservation information associated with the token ID, whether the user can carry out the second procedure at the second terminal.
5. The information processing apparatus according to claim 4, wherein the processor further executes the instructions to: control an authentication process between the biometric information

- acquired from the user and passport biometric information included in the passport information.
6. The information processing apparatus according to claim 5, wherein the processor, acquires the boarding reservation information on the user, in a case in which the authentication process is completed, acquires the boarding reservation information via a server of an airline company based on the passport information, where the server stores the passport information of the user acquired at the time of reservation of a flight ticket in association with the boarding reservation information.
7. An information processing method performed by a computer and comprising: acquiring passport information on a user from a first terminal employed in a first procedure that a passenger performs regarding the boarding process; acquiring a first biometric information on the user from the first terminal; acquiring boarding reservation information on the user; and issuing a token ID associated with the passport information, the biometric information, and the boarding reservation information, wherein the token ID is invalidated in a case in which the user boards an aircraft, wherein the token ID after being issued, is identified by matching the second biometric information of the user acquired by a second terminal used for the second procedure related to the boarding process with the first biometric information, and wherein the identified token ID is used to determine, based on the passport information and boarding reservation information associated with the token ID, whether the user can carry out the second procedure at the second terminal.
8. The information processing method according to claim 7, further comprising: controlling an authentication process between the biometric information acquired from the user and passport biometric information included in the passport information.
9. The information processing method according to claim 8, wherein acquiring the boarding reservation information on the user, in a case in which the authentication process is completed, comprises acquiring the boarding reservation information via a server of an airline company based on the passport information, where the server stores the passport information of the user acquired at the time of reservation of a flight ticket in association with the boarding reservation information.
-