

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407615
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	John; Kaippallimalil Mathew et al.

Methods and apparatus for session steering to application servers

Abstract

A method includes receiving, by a control plane (CP) from an application function (AF), a traffic influence routing rule comprising a service address representing a destination address of a route to an application server, the traffic influence routing rule specifying a breakout rule for packets of a communicating device addressed to the application server; storing, by the CP, the traffic influence routing rule in a policy control function (PCF); and generating, by the CP, a traffic filter for packets of at least one traffic flow associated with the communicating device, the traffic filter directing packets of the at least one traffic flow that are addressed to the application server to the service address, the traffic filter being generated in accordance with the traffic influence routing rule.

Inventors: John; Kaippallimalil Mathew (Carrollton, TX), Saboorian; Khosrow Tony (Plano, TX), Xiang; Zhixian (Frisco, TX)

Applicant: Huawei Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 75478274

Assignee: HUAWEI TECHNOLOGIES CO., LTD. (Shenzhen, CN)

Appl. No.: 17/981068

Filed: November 04, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230096469 A1	Mar. 30, 2023

Related U.S. Application Data

continuation parent-doc WO PCT/US2021/023322 20210319 PENDING child-doc US 17981068
us-provisional-application US 63019754 20200504

Publication Classification

Int. Cl.: H04L47/20 (20220101); H04L45/74 (20220101); H04L47/2441 (20220101)

U.S. Cl.:

CPC H04L47/20 (20130101); H04L45/74 (20130101); H04L47/2441 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0192390	12/2017	Li	N/A	H04W 72/53
2019/0053117	12/2018	Bae	N/A	H04W 76/30
2019/0394833	12/2018	Talebi Fard	N/A	H04W 4/80
2020/0128503	12/2019	Li	N/A	H04W 4/60
2020/0267785	12/2019	Talebi Fard	N/A	H04L 45/04
2022/0007180	12/2021	Liao	N/A	H04L 67/14
2022/0141662	12/2021	Liao	726/1	H04W 12/37
2022/0159527	12/2021	Lee	N/A	H04W 8/24
2022/0312158	12/2021	Gonzalez	N/A	H04M 15/80

Primary Examiner: Choi; Eunsook

Attorney, Agent or Firm: Slater Matsil, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of International Application No. PCT/US2021/023322, filed Mar. 19, 2021, entitled “Methods and Apparatus for Session Steering to Application Servers,” which claims the benefit of U.S. Provisional Application No. 63/019,754, filed on May 4, 2020, entitled “Apparatus and Methods for PDU Session Steering for Edge Computing,” applications of which are incorporated herein by reference in their entireties.

TECHNICAL FIELD

(1) The present disclosure relates generally to methods and apparatus for digital communications, and, in particular embodiments, to methods and apparatus for session steering to application servers.

BACKGROUND

(2) Fifth Generation (5G) networks that host edge computing (EC) sites close to the radio access network (RAN) may have a split packet data unit (PDU) session, where a default PDU session path is terminated at a central data network, and a local path is terminated closed to the access network (AN) or RAN. Routing to the local path uses a user plane function (UPF) that forwards to the local

UPF PDU session anchor (PSA) if there is a match on forwarding rules configured during the setup of the PDU session. An example of such a UPF is the uplink classifier (ULCL) UPF.

(3) EC services, as well as application services, typically use an anycast Internet protocol (IP) address that represents a service address. The availability of an application server (AS) is programmed in route controllers and advertised using a border gateway protocol (BGP) (or an interior gateway protocol (IGP)). This provides a scalable and resilient means for users to reach application servers.

(4) The PDU session (or similarly, the network access) to edge application servers (EASs) deployed at the mobile edge spans from the user equipment (UE) to the UPF that selectively steers traffic to the local UPF-PSA. Because routes advertised by BGP, IGP, etc., are not known, the UPF will not be able to steer packets to the EASs unless the UPF is made aware of the application services at the edge. Therefore, there is a need for methods and apparatus for session steering with application servers.

SUMMARY

(5) According to a first aspect, a method is provided. The method comprising: receiving, by a control plane (CP) from an application function (AF), a traffic influence routing rule comprising a service address representing a destination address of a route to an application server, the traffic influence routing rule specifying a breakout rule for packets of a communicating device addressed to the application server; storing, by the CP, the traffic influence routing rule in a Policy Control Function (PCF); and generating, by the CP, a traffic filter for packets of at least one traffic flow associated with the communicating device, the traffic filter directing packets of the at least one traffic flow that are addressed to the application server to the service address, the traffic filter being generated in accordance with the traffic influence routing rule.

(6) In a first implementation form of the method according to the first aspect, the traffic influence routing rule comprising at least one of a traffic influence create rule, a traffic influence update rule, or a traffic influence delete rule.

(7) In a second implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, the traffic influence routing rule further comprising at least one gateway address associated with the service address.

(8) In a third implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, the traffic filter comprising the service address and the at least one gateway address.

(9) In a fourth implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, the traffic filter being stored in accordance with a network slice selection assistance information.

(10) In a fifth implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, further comprising sending, by the CP to the AF, a traffic influence routing rule response.

(11) In a sixth implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, the traffic filter being stored in a unified data repository (UDR).

(12) In a seventh implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, storing the traffic filter comprising updating an existing traffic filter with the traffic filter.

(13) In an eighth implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, the service address comprising an Internet Protocol address, a port address, and a protocol.

(14) In a ninth implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, further comprising generating, by the CP, information associated with the traffic filter.

- (15) In a tenth implementation form of the method according to the first aspect or any preceding implementation form of the first aspect, the information comprising a single network slice selection assistance information (S-NSSAI).
- (16) According to a second aspect, a method is provided. The method comprising: receiving, by a PCF, a traffic filter for packets of at least one traffic flow associated with a communicating device, the traffic filter comprising a traffic influence routing rule specifying a breakout rule for packets addressed to an application server; deriving, by the PCF, a network identifier associated with the traffic filter; and providing, by the PCF to a session management function (SMF), the network identifier and the traffic filter.
- (17) In a first implementation form of the method according to the second aspect, the network identifier comprising a data network access identifier (DNAI).
- (18) In a second implementation form of the method according to the second aspect or any preceding implementation form of the second aspect, the traffic filter comprising a service address and at least one gateway address.
- (19) In a third implementation form of the method according to the second aspect or any preceding implementation form of the second aspect, the traffic filter further comprising a network slice selection assistance information.
- (20) In a fourth implementation form of the method according to the second aspect or any preceding implementation form of the second aspect, providing the network identifier and the traffic filter comprising initiating a session management policy control service. According to a third aspect, a CP is provided. The CP comprising: a non-transitory memory storage comprising instructions; and one or more processors in communication with the memory storage, wherein the one or more processors execute the instructions to: receive, from an AF, a traffic influence routing rule comprising a service address representing a destination address as a route to an application server, the traffic influence routing rule specifying a breakout rule for packets of a communicating device addressed to the application server; store the traffic influence routing rule in a PCF; and generate a traffic filter for packets of at least one traffic flow associated with the communicating device, the traffic filter directing packets of the at least one traffic flow that are addressed to the application server to the service address, the traffic filter being generated in accordance with the traffic influence routing rule.
- (21) In a first implementation form of the CP according to the third aspect, the traffic influence routing rule comprising at least one of a traffic influence create rule, a traffic influence update rule, or a traffic influence delete rule.
- (22) In a second implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, the traffic influence routing rule further comprising at least one gateway address associated with the service address.
- (23) In a third implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, the traffic filter comprising the service address and the at least one gateway address.
- (24) In a fourth implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, the traffic filter being stored in accordance with a network slice selection assistance information.
- (25) In a fifth implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, further comprising sending, by the CP to the AF, a traffic influence routing rule response.
- (26) In a sixth implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, the traffic filter being stored in a UDR.
- (27) In a seventh implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, storing the traffic filter comprising updating an existing traffic filter with the traffic filter.

- (28) In an eighth implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, the service address comprising an Internet Protocol address, a port address, and a protocol.
- (29) In a ninth implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, further comprising generating, by the CP, information associated with the traffic filter.
- (30) In a tenth implementation form of the CP according to the third aspect or any preceding implementation form of the third aspect, the information comprising a S-NSSAI.
- (31) According to a fourth aspect, a NF is provided. The NF comprising: a non-transitory memory storage comprising instructions; and one or more processors in communication with the memory storage, wherein the one or more processors execute the instructions to: receive a traffic filter for packets of at least one traffic flow associated with a communicating device, the traffic filter comprising a traffic influence routing rule specifying a breakout rule for packets addressed to an application server; derive a network identifier associated with the traffic filter; and provide, to a SMF, the network identifier and the traffic filter.
- (32) In a first implementation form of the NF according to the fourth aspect, the network identifier comprising a DNAI.
- (33) In a second implementation form of the NF according to the fourth aspect or any preceding implementation form of the fourth aspect, the traffic filter comprising a service address and at least one gateway address.
- (34) In a third implementation form of the NF according to the fourth aspect or any preceding implementation form of the fourth aspect, the traffic filter further comprising a network slice selection assistance information.
- (35) In a fourth implementation form of the NF according to the fourth aspect or any preceding implementation form of the fourth aspect, providing the network identifier and the traffic filter comprising initiating a session management policy control service.
- (36) An advantage of a preferred embodiment is that knowledge of edge application services allows the user plane function (UPF), e.g., the uplink classifier (ULCL), to steer traffic to the UPF PDU session anchor (PSA) serving the edge location. Steering traffic to the UPF-PSA serving the edge location enables the selection of local application service servers, which reduces the costs and latencies associated with the routing.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) For a more complete understanding of the present disclosure, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 illustrates a first example communications system;
- (3) FIG. 2 illustrates a communication system supporting edge computing (EC) and edge application servers (EASs), communication system supporting the prior art technique of programming and advertising routes;
- (4) FIG. 3 illustrates a communication system supporting the programming the presence of EASs into uplink classifiers (ULCL) so that the ULCLs can make appropriate traffic steering decisions according to example embodiments presented herein;
- (5) FIG. 4 illustrates a diagram of messages shared and processing performed by entities and functions of a communication system configuring the traffic steering rules according to example embodiments presented herein;
- (6) FIG. 5 illustrates communication system highlighting network segments and mapping

proximate EASs to data networks with data network access identifiers (DNAI) according to example embodiments presented herein;

(7) FIG. 6 illustrates a diagram of messages shared and processing performed by entities and functions of a communication system updating user equipment (UE) policies and setting up a split packet data unit (PDU) session according to example embodiments presented herein;

(8) FIG. 7 illustrates a diagram of messages shared and processing performed by entities and functions of a communication system involved in relocating a server according to example embodiments presented herein;

(9) FIG. 8A illustrates a first communication system highlighting local access;

(10) FIG. 8B illustrates a first communication system highlighting proximate access. In communication system, UE connected to data network and obtains service from EAS through flow according to example embodiments presented herein;

(11) FIG. 9A illustrates a second communication system highlighting local access to a data network;

(12) FIG. 9B illustrates a second communication system highlighting proximate access to a data network according to example embodiments presented herein;

(13) FIG. 10 illustrates a communication system highlighting an example configuration, along with PDU session and application flow according to example embodiments presented herein;

(14) FIG. 11 illustrates a flow diagram of example operation occurring in a network exposure function (NEF) according to example embodiments presented herein;

(15) FIG. 12 illustrates a flow diagram of example operations occurring in a policy control function (PCF) according to example embodiments presented herein;

(16) FIG. 13 illustrates a flow diagram of example operations occurring in a PCF participating in split model PDU session establishment and traffic steering according to example embodiments presented herein;

(17) FIG. 14 illustrates a flow diagram of example operations occurring in a session management function (SMF) participating in split model PDU session establishment and traffic steering according to example embodiments presented herein;

(18) FIG. 15 illustrates an example communication system according to example embodiments presented herein;

(19) FIGS. 16A and 16B illustrate example devices that may implement the methods and teachings according to this disclosure; and

(20) FIG. 17 is a block diagram of a computing system that may be used for implementing the devices and methods disclosed herein.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

(21) The structure and use of disclosed embodiments are discussed in detail below. It should be appreciated, however, that the present disclosure provides many applicable concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed are merely illustrative of specific structure and use of embodiments, and do not limit the scope of the disclosure.

(22) FIG. 1 illustrates a first example communications system **100**. Communications system **100** includes an access node **110**, with coverage area **101**, serving user equipments (UEs), such as UEs **120**. Access node **110** is connected to a backhaul network **115** that provides connectivity to services and the Internet. In a first operating mode, communications to and from a UE passes through access node **110**. In a second operating mode, communications to and from a UE do not pass through access node **110**, however, access node **110** typically allocates resources used by the UE to communicate when specific conditions are met. Communication between a UE pair in the second operating mode occurs over sidelinks **125**, comprising uni-directional communication links. Communication between a UE and access node pair also occur over uni-directional communication links, where the communication links between the UE and the access node are referred to as

uplinks **130**, and the communication links between the access node and UE is referred to as downlinks **135**.

(23) Access nodes may also be commonly referred to as Node Bs, evolved Node Bs (eNBs), next generation (NG) Node Bs (gNBs), master eNBs (MeNBs), secondary eNBs (SeNBs), master gNBs (MgNBs), secondary gNBs (SgNBs), network controllers, control nodes, base stations, access points, transmission points (TPs), transmission-reception points (TRPs), cells, carriers, macro cells, femtocells, pico cells, and so on, while UEs may also be commonly referred to as mobile stations, mobiles, terminals, users, subscribers, stations, and the like. Access nodes may provide wireless access in accordance with one or more wireless communication protocols, e.g., the Third Generation Partnership Project (3GPP) long term evolution (LTE), LTE advanced (LTE-A), 5G, 5G LTE, 5G NR, sixth generation (6G), High Speed Packet Access (HSPA), the IEEE 802.11 family of standards, such as 802.11a/b/g/n/ac/ad/ax/ay/be, etc. While it is understood that communications systems may employ multiple access nodes capable of communicating with a number of UEs, only one access node and two UEs are illustrated for simplicity.

(24) As discussed previously, edge computing (EC) services, as well as application services, use anycast or unicast Internet protocol (IP) addresses to represent service addresses. The availability of an application server (AS) is programmed into route controllers and advertised using a border gateway protocol (BGP) (or an interior gateway protocol (IGP)). This provides for a scalable and resilient way for users to access AS.

(25) The IP packet to edge application servers (EASs) (at the mobile edge) connection spans from the UE to a user plane function (UPF), such as an uplink classifier (ULCL) UPF, that is capable of steering traffic to a local UPF packet data unit (PDU) session anchor (PSA) or forwarding the traffic to a central UPF PSA. However, because the routes corresponding to a service destination (e.g., the EAS) are advertised using BGP, IGP, etc., they are not known to the ULCL UPF, and therefore the ULCL UPF will be unable to steer packets to the EASs unless the ULCL UPF is aware of the routes corresponding to EAS located at the edge.

(26) FIG. 2 illustrates a communication system **200** supporting EC and EASs, communication system **200** supporting the prior art technique of programming and advertising routes.

Communication system **200** includes an application service **205**. Application service **205** provides one or more servers for supporting an application or service, and includes an application function (AF) **207** that interacts with a 5G core (5GC) control plane (CP) **209**, byway of a network exposure function (NEF) **211**, for example, to access network capabilities. AF **207** also interacts with local data networks (L-DNs) or local data centers, such as L-DN1 **213** and L-DN2 **215**, and centrally located data networks (C-DNs) or data centers, such as C-DN **217**. L-DNs include EASs, such as EAS **219** and EAS **221**, and are connected to IP networks byway of gateways (GWs), such as GW **223** and **225**. C-DN **217** include a first autonomous system **227** associated with a first IP address and a second autonomous system **229** associated with a second IP address, although a C-DN may include any number of autonomous systems (e.g., one, two, three, four, and so on) associated with IP addresses. C-DN **217** is connected to IP network **231** by way of GW **233**.

(27) In addition to NEF **211**, which provides an external interface to edge network services and capabilities, 5GC CP **209** also includes a unified data repository (UDR) **235** (which may be a database for 5G specific information), a policy control function (PCF) **237** (which is a control plane network function used to control user and network policy), an access and mobility management function (AMF) **239** (which processes requests related to connectivity and mobility management), and session management function (SMF) **241** (which processes requests related to session management).

(28) Communication system **200** also includes UEs (such as UE **243** and **245**). UEs are connected to an IP network through an access node and a UPF uplink classifier (ULCL) that forwards traffic to a local UPF PDU session anchor (PSA). As an example, traffic from UE **243** travels through access node **247**, ULCL **249**, and PSA **251** to reach IP network **253**.

- (29) A prior art technique involved in programming and advertising routes includes:
- (30) Application domain service configuration (event **260**)—AF **207** provisions servers in L-DNs and C-DNs. Provisioning includes service addresses that are advertised in a set of networks identified by an autonomous system number (ASN).
- (31) Domain name server (DNS) provisioning (event **262**)—AF **207** provisions an authoritative DNS (ADNS) **264** for the services. ADNS **264** replies to DNS resolvers with the service address of a service when queried with a service fully qualified domain name (FQDN).
- (32) Application domain influences traffic routing (event **266**)—AF **207** installs traffic routing at NEF **211**.
- (33) Mobile network installs routing rules (event **268**)—Routing rules are advertised.
- (34) Steering application traffic (event **270**)—Data packets are sent to PSA **272**, where they are sent to closest EAS, AS **227**. Because the data packets are sent to PSA **272**, they are further sent to AS **227**, which is the closest EAS to PSA **272**, but may not be the desired result. The path taken by the data packets are shown as dotted line **274**. Examples of desired results include lower latency, lower cost, load balancing, improved network utilization, etc.
- (35) Therefore, there is a need for methods and apparatus for session steering to application servers.
- (36) According to an example embodiment, methods and apparatus are provided for programming the presence of EASs into the ULCL so that the ULCL can make appropriate traffic steering decisions. The ULCL can be programmed with the presence of EASs so that the ULCL can make traffic steering decisions for different deployment scenarios (such as publicly routable applications, private applications with message based security, virtual private network (VPN) access, and so on). A new ULCL can be provisioned with traffic filters to steer traffic and support the mobility of the user (i.e., UEs).
- (37) In an embodiment, the application domain influences traffic routing in the mobile network. As an example, the service addresses and locations in the application domain are used to steer traffic. The service addresses and locations in the application domain are provided to the mobile network operator (MNO), e.g., 5GC CP **209**, so that traffic of PDU sessions may be steered using the service addresses and locations, for example. An IP route control mechanism may be used to advertise the routes. In an embodiment, IP route control mechanisms are not possible for a ULCL, so an extension to AF traffic influence is provided. Details of example extensions to the AF traffic influence are provided below.
- (38) In an embodiment, service routes and traffic steering rules generated in accordance with the service addresses (server IP addresses) and locations in the application domain are provided to the user plane, e.g., the ULCL. The service routes and traffic steering rules may be provided when the UE establishes a PDU session, for example. Details of example service routes and traffic steering rules being provided during PDU session establishment are provided below. These examples may also be applicable in deployments with distributed PSAs and no ULCL.
- (39) In an embodiment, information related to service addresses and locations of mobile edge application domains are translated, stored, and provisioned in 5GC and user plane to steer data traffic to the closest EAS.
- (40) In an embodiment, data packets with destination addresses of the edge data network (e.g., L-DNs **213** and **215**) with provisioned traffic steering rules are directed to local PSAs rather than a global PSA (such as PSA **272**). From a local PSA, the data packets are routed to a closest EAS. The routing to the closest EAS may take place using standard IP anycast routing, for example.
- (41) In an embodiment, the AF in the application domain, orchestrates servers in data centers (local or cloud), generate a new request to the 5GC. The request provides the 5GC with the service address (e.g., an IP anycast address) and a data network access identifier (DNAI) where the servers are provisioned. The AF translates the DNAI using the ASN of the IP network, for example. Furthermore, when servers are removed or fail, the AF may use the interface to update and delete

the servers.

(42) In an embodiment, the NEF supports processing of the new request from the AF. Additional services at the NEF are not required. The NEF adds the network slice selection assistance information (NSSAI) or single NSSAI (S-NSSAI) and forwards it as usual.

(43) In an embodiment, the UDR stores the new information as application data, AF transactions, or S-NSSAI and data network name (DNN). Additional fields in the data set include service address (IP anycast address), list of DNAI needed, and so on.

(44) In an embodiment, the PCF follows existing procedures to subscribe to the AF traffic influence request. The PCF determines a set of DNAI that is close to each data network location (e.g., GW address). Determination of the proximity of the DNAI, GW address (e.g., data network location), involves the PCF obtaining a list of DNAI and GWs that are topologically or administratively close from the OAM. The information may be obtain as part of the configuration process, for example. The PCF organizes the received information into the list of service addresses (srv-IP-addr) for each DNAI.

(45) In an embodiment, the SMF receives the data set per DNAI with a list of service addresses (e.g., IP or IP anycast addresses) for edge application routing. The SMF may select a local PSA that is close to the DNAI and construct forwarding action rules (FAR) to be inserted into the ULCL. All service IP addresses that apply to the DNAI where the PDU session terminates (i.e., a local PSA) are inserted as FARs in the ULCL.

(46) FIG. 3 illustrates a communication system **300** supporting the programming the presence of EASs into ULCLs so that the ULCLs can make appropriate traffic steering decisions. Communication system **300** includes a variety of entities or functions, wherein entities or functions of communication system **300** that share reference numerals with entities or functions of communication system **200** behave similarly.

(47) As shown in FIG. 3, AF **305** configures application domain services (event **260**). AF **305** provisions servers in data centers (e.g., L-DNs and C-DNs). Provisioning includes specifying service addresses (e.g., an IP anycast address) that are advertised in the set of networks identified by the ASN.

(48) AF **305** also provisions the DNS (event **262**). As an example, ADNS **264** is the authoritative DNS for the service so that when queried with a FQDN for that particular service, ADNS **264** replies to the DNS resolver with the service address associated with the service. ADNS **264** may be hosted or managed in the application domain.

(49) AF **305** conveys service addresses and locations in the application domain to the MNOs (event **307**). The service addresses and locations in the application domain are conveyed to the MNOs to enable the steering of data traffic of PDU sessions. Typically, IP route control mechanisms are used to advertise the routes. But because ULCLs do not support IP route control mechanisms, extensions to the AF traffic influence are used.

(50) The service addresses and locations in the application domain may be conveyed to NEF **309** of 5GC CP **209**, for example. NEF **309** provides the service addresses and locations to UDR **235**, PCF **237**, and SMF **311**. 5GC CP **209**, byway of SMF **311**, for example, provides the service addresses and locations to ULCLs, such as ULCL **315**. As an example, traffic steering rules associated with the service addresses and locations are installed in the ULCLs. In an embodiment, SMF **311** provides the traffic steering rules associated with the service addresses and locations to all ULCLs of communication system **300**. In another embodiment, SMF **311** provides the traffic steering rules associated with the service addresses and locations to only those ULCLs of communication system **300** that are handling data packets addressed to services associated with the service addresses and locations.

(51) Data packets with destination addresses to the edge data network (e.g., L-DN **213**) are steering in accordance with the traffic steering rules provided by SMF **311** to the ULCLs (event **317**). As an example, data packets of UE **243** with the destination address of a service supported by a server in

L-DN **213** with EAS-1 **219** are traffic steered by ULCL **315** to PSA **251** instead of being routed to PSA **272**. From PSA **251**, the data packets are routed to EAS-1 **219** through GW **225**. The routing to EAS-1 **219** may use standard IP routing, for example. The path of the data packets from UE **243** with the destination address of L-DN **213** is shown in FIG. **3** as dotted line **319**.

(52) In an embodiment, traffic steering rules (e.g., service routes) are configured by the application domain to influence traffic routing in the MNOs. Configuring the traffic steering rules in the application domain allows for the steering of data packets based on the destination addresses of the data packets.

(53) FIG. **4** illustrates a diagram **400** of messages shared and processing performed by entities and functions of a communication system configuring the traffic steering rules. The entities and functions involved in the configuring of the traffic steering rules includes a UPF **405** (of UE **243**, for example), SMF **311**, PCF(s) **237**, UDR **235**, NEF **309**, and AF **305**.

(54) AF **305** orchestrates and configures the application in EASs and ASs at various data center locations by generating an AF request (block **410**). The service may be exposed via DNS using an IP anycast service address (e.g., srv-IP-addr). AF **305** configures information at ADNS **264** with service or FQDN and address resolution to srv-IP-addr, for example.

(55) AF **305** provides information related to the application to the MNO (event **412**). As an example, AF **305** provides information related to the IP anycast service address associated with the application (e.g., srv-IP-addr). AF **305** also provides information about L-DN locations where the application is configured. The information about L-DN locations may comprise a list of the L-DN locations or GWs thereof. The information may be provided to the MNO (e.g., NEF **309**) in an AF information request, e.g., a Nnef_TrafficInfluence_Create request message. Alternatively, Nnef_TrafficInfluence_Update or Nnef_TrafficInfluence_Delete request messages may be used. In a situation when there are multiple service addresses or redirect addresses for the EASs or ASs, AF **305** may provision all service addresses involved and provide information related to the service addresses to the MNO. Additionally, the FQDN may not be included in the information provided by AF **305** because the FQDN is not needed for AF influenced routing.

(56) NEF **309** performs authorization controls and adds slice information to the information provided by AF **305** (block **414**). The slice information includes NSSAI or S-NSSAI. NEF **309** also stores the information request from AF **305**. The information request from AF **305** may be stored in UDR **235**, for example. The information request stored at UDR **235** may include the data set, subset, or key. 3GPP TS 23.502, section 4.3.6, which is hereby incorporated herein by reference in its entirety, specifies the storing of the information request. NEF **309** also sends a response to the AF information request (event **416**). The response to the AF information request may be in the form of a Nnef_TrafficInfluence_Create response message. Alternatively, Nnef_TrafficInfluence_Update or Nnef_TrafficInfluence_Delete response messages may be used.

(57) PCF(s) **237** that have subscribed to modifications of the AF traffic influence dataset or subset are notified (event **418**). PCF(s) **237** may be notified by UDR **235** using a Nudr_DM_Notify message. The Nudr_DM_Notify message includes the NSSAI, srv-IP-addr, and the information about L-DN locations. PCF(s) **237** determines a DNAI of a data network (block **420**). PCF(s) **237** may determine a set of DNAIs of data networks that are close to each L-DN location (i.e., the GW addresses). PCF(s) **237** may obtain the list of DNAI and GWs that are topologically or administratively close from operations, administration, and maintenance (OAM) as part of a configuration processes. DNAIs of data networks and GWs are administratively close if they are managed by a single entity or multiple entities with an association with one another. PCF(s) **237** also stores a list of service addresses (e.g., srv-IP-addr) and the DNAIs.

(58) PCF(s) **237** determines PDU sessions impacted by the new AF traffic influence dataset (events **422**). PCF(s) **237** identifies the PDU sessions impacted by the new AF traffic influence dataset by detecting the PDU sessions with destination address of the application, for example. PCF(s) **237** updates SMF **311** with a new policy and charging control (PCC) rule for each PDU session

determined to be impacted by the new AF traffic influence dataset, for example.

(59) SMF **311** reconfigures UPF **405** (block **424**). SMF **311** reconfigures UPF **405** for each PCC rule received, for example. As related to PDU session modification where a central PSA has been established, SMF **311** combines the ULCL and a local PSA. As related to new PDU sessions, SMF **311** may establish a central PSA as well as the ULCL and the local PSA. In the situation where the PCC rule is updated due to a failure, SMF **311** may reselect a local PSA or ULCL.

(60) The messages shared and processing performed by entities and functions presented above make use of basic AF influenced traffic routing for PDU sessions not identified by a UE address, as specified in 3GPP TS 23.502, section 4.3.6.2, which is hereby incorporated herein by reference in its entirety. Route information corresponding to the services configured at a data network with a particular DNAI in the application domain is provisioned as discussed.

(61) The messages shared and processing performed by entities and functions presented above may be used for publicly accessible applications or private applications. As an example, private deployments with VPNs would expose VPN connectivity GWs only. For private deployments with zero trust and more granular access, each service with access may be separately exposed (e.g., DNS queries over HTTPS (DoH), application service(s), etc.).

(62) In an embodiment, methods and apparatus for determining the proximity of data networks with particular DNAIs and L-DN locations are provided. In block **420** of FIG. **4**, PCF(s) **237** determines DNAIs of data networks and GWs that are topologically or administratively close to each other. An example technique for determining proximity is provided below.

(63) The EASs and UPF are in different network segments. However, they may still be close topologically or administratively. FIG. **5** illustrates communication system **500** highlighting network segments and mapping proximate EASs to data networks with DNAIs. Communication system **500** comprises a variety of network segments hosting 5GC network functions, UPF, etc. **505**, as well as other network segments **507** hosting EASs with a local IP network **509** in between. Local IP network **509** has ASN=123.

(64) An OAM (implemented in 5GC **505**, for example) configures and manages the devices, and is aware of the administrative and topological distances between the GWs (e.g., GW **511**) and between GWs and local PSAs (e.g., PSA **513**) in a data network (e.g., data network **515**) with a particular DNAI. The OAM uses distance information (related to the administrative and topological distances) to configure a PCF with all GWs that are proximate. As an example, OAM configures the PCF with the proximity information: data network **515** (with DNAI=D1)=(GW-1 **511**, GW-2 **523**, GW-3 **525**, GW-4 **527**, and GW-5 **529**), with the proximity information for data network **517** (with DNAI=D2) and data network **519** (with DNAI=D3) also being equivalent to the proximity information for data network **515** (with DNAI=D1). However, the proximity information for data network **521** (with DNAI=D4)=(GW-11 **531**, and GW-12 **533**), which is different from the proximity information of the other data networks shown in FIG. **5**.

(65) As shown in FIG. **5**, GW-1 **511** and GW-2 **523** are connected to IP network **509**, hence GW-1 **511** and GW-2 **523** are proximate. The data networks are configured in UPF **405** by the OAM, while PCF(s) **237** obtains lists of GWs attached to a network with a particular ASN, as well as a list of PSAs with or without closest GWs.

(66) The proximity of a data network with a particular DNAI and GWs allows for the routing configuration in SMF **311** during the setup of a PDU session. Details are presented below.

(67) In an embodiment, a PDU session that follows the split model (where a default path from the UE (e.g., UE **243**) to a central PSA (e.g., PSA **272**), and another path from the UE to a local PSA (e.g., PSA **251**)) needs routing rules configured at the ULCL to support selective traffic steering to a local destination.

(68) FIG. **6** illustrates a diagram **600** of messages shared and processing performed by entities and functions of a communication system updating UE policies and setting up a split PDU session. The entities and functions involved include a UE **243**, an access node **605** of L-DN **213**, a UPF **607** of

L-DN 213, an EAS 609 of L-DN 213, AMF 239, SMF 311, PCF 237, and DNS 264.

(69) UE 243 registers with AMF 239 (block 610). The registration of UE 243 with AMF 239 may utilize the procedures described in 3GPP TS 23.502, section 4.2, which are hereby incorporated herein by reference in its entirety, for example. In addition, UE 243 may either be configured or dynamically provided with UE route selection policy (URSP) rules that indicate the network slice (e.g., a network slice identified by a S-NSSAI) to use for edge applications or subsets of applications.

(70) UE 243 sends a PDU session establishment request (event 612). The PDU session establishment request is sent to AMF 239. UE 243 may launch the application and select a S-NSSAI for the PDU session. The PDU session establishment request is sent with the network slice identified with S-NSSAI. AMF 239 selects a SMF (e.g., SMF 311) and sends a request message to SMF 311 (event 614). The request message is a Nsmf_PDUSession_CreateSMContext request, for example.

(71) SMF 311 selects a PCF (e.g., PCF 237) and request policy for the PDU session (event 616). SMF 311 sends a Npcf_SMPolicy_Control request message to request the policy for the PDU session from PCF 237, for example. PDU session being associated with S-NSSAI. PCF 237 fetches policy (block 618). PCF 237 fetches policy for the PDU session. The policy fetched by PCF 237 includes a list of service IP addresses for the data network with DNAI. PCF 237 sends the policy to SMF 311 (event 620). PCF 237 sends a Npcf_SMPolicy_Control response message to send the policy to SMF 311, for example. The Npcf_SMPolicy_Control response message includes the policy for the PDU session.

(72) SMF 311 selects a UPF (e.g., UPF 607) (block 622). SMF 311 selects UPF 607 in accordance with the technique described in 3GPP TS 23.502, section 4.3.2.2.1, which is hereby incorporated herein by reference in its entirety, for example. In addition to UPF selection, SMF 311 selects a local PSA, which may also be selected based on the DNAI FAR of the data network for srv-IP-addr in the ULCL.

(73) SMF 311 programs UPF 607 (event 624). The programming of UPF 607 may take place over the N4 interface. SMF 311 provisions both local and central PSAs as specified in 3GPP TS 23.502, which is hereby incorporated herein by reference in its entirety. Furthermore, the ULCL is provisioned with the DNAI FAR traffic filters for the destination addresses corresponding to the list of service IP addresses. This particular action is forwarded to the local PSA.

(74) The PDU session establishment procedure is completed (block 626).

(75) UE 243 sends a DNS query over the established PDU session (event 628). The DNS query may be sent as an application message by UE 243. If there are no routing rules corresponding to the DNS destination address, the application message (with the DNS query) is forwarded to the central PSA (e.g., PSA 272). However, if there is a routing rule corresponding to the DNS destination address (e.g., DoH in a private network), the ULCL (e.g., ULCL 315) forwards the application message to the local PSA (e.g., PSA 251). In the situation where VPNs are used, all application messages will be forwarded to the matched destination address. Because no inspection of the DNS message (e.g., DNS query or DNS response) is necessary, support for Do53, DNS over Transport Layer Security (DoT), and DoH are provided. UE 243 receives a DNS response (event 630). The DNS response includes authentication (A) or authentication/authorization/accounting (AAA) record srv-IP1, for example.

(76) UE 243 sends an application request with destination address of srv-IP1 (event 632). The application request is sent to UPF 607, for example. UPF 607 checks rules for a match with srv-IP1 (block 634). If there is a successful rule match UPF 607 forwards the application request to local PSA, which forwards the application request to EAS 609 (events 636). A response to the application request is provided to UE 243.

(77) In an embodiment, servers are relocatable as needed. The application domain determines that a server should be relocated to support local networks with split PDU sessions.

(78) FIG. 7 illustrates a diagram 700 of messages shared and processing performed by entities and functions of a communication system involved in relocating a server. The entities and functions involved in relocating the server include UE 243, a first ULCL 705 of a current UPF 707, a first PSA 709 of current UPF 707, a second ULCL 711 of a next UPF 713, a second PSA 715 of next UPF 713, a first EAS 717 of a first L-DN 719, and a second EAS 721 of a second L-DN 723.

(79) UE 243 establishes a PDU session (block 720). UE 243 attaches and establishes the PDU session to first PSA 709 of UPF 707 with address UE-IP1. UE 243 also launches an application. The application has a DNS translation with an anycast address. First EAS 717 may provide a redirect address so that the server (first EAS 717) remains sticky even after UE mobility. The server remaining sticky means that the server is not relocated after UE mobility.

(80) UE 243 sends an application message with anycast destination address A-IP (event 722). The application message with the anycast destination address A-IP matches a filter rule at first ULCL 705, and first ULCL 705 forwards the application message to first PSA 709. Routers in first L-DN 719 forward the application message to first EAS 717 using anycast routing.

(81) First EAS 717 notifies the AF (e.g., AF 305) of the IP address of UE 243 (block 724). The notification of the AF may occur in the application domain using application domain signaling. If the AF evaluates that there is a better EAS (e.g., second EAS 721) than first EAS 717, the AF may initiate server relocation procedures.

(82) For discussion purposes, consider the case where the AF initiates server relation procedures. UE 243 participates in a handover to a new access network or RAN (block 726). Additionally, second PSA 715 is selected. As a result of the handover, UE 243 has a new IP address UE-IP2. The handover may be as specified in 3GPP TS 23.502. The SMF may remove old UPFs (such as first UPF 707) after a time delay. Removal of the old UPFs may occur as detailed below. Delaying the removal of old UPFs may help to minimize the loss of in-flight data packets.

(83) UE 243 continues to send application messages (event 728). The new application messages are sent with the new IP address UE-IP2. The new application messages include the anycast destination address of first EAS 717, A-IP. In a typical request-response sequence, first EAS 717 is immediately aware of the new IP address UE-IP2 because it is the source address in the request message. However, if the application pattern is downstream biased (e.g., multicast video delivery) or notifications, UE 243 may send a new request (e.g., a subscribe, multicast status report change, etc.) to initiate redirection to the new UE location or new PSA (post handover). The action of UE 243 informs first EAS 717 of the new IP address of UE 243.

(84) First EAS 717 notifies the AF of the new IP address of UE 243 (block 730). Application domain signaling may be used to notify the AF of the new IP address of UE 243. The AF re-evaluates first EAS 717 or first L-DN 719. For discussion purposes, the case where the AF determines that relocation to second EAS 721 is warranted.

(85) A procedure to reselect the EAS is performed (block 732). Reselection of the EAS involves the AF, first EAS 717 (the current EAS), and second EAS 721 (the target EAS). Mechanisms to transfer the context and related data of UE 243 are initiated.

(86) Once second EAS 721 replicates the application state, first EAS 717 sends an application layer redirect message (event 734). The application layer redirect message is sent to UE 243, and may include a URL of second L-DN 723 or second EAS 721. UE 243 requests a DNS translation of the URL (block 736). UE 243 may transmit a DNS request, for example, and receives a DNS response with the anycast address of second L-DN 723.

(87) UE 243 sends application messages (event 738). The application messages include the source IP address of UE 243 (UE-IP2) and the destination address of second L-DN 723. The destination address of second L-DN 723 may be programmed in N6 to route to second EAS 721 unless there is a failure of some sort. Hence, N6 routers forward packets to second EAS 721.

(88) Access may be in the form of local access or proximate access. In local access, there is a one-to-one association between the 5GC and edge application resources. However, in proximate access,

there is a N-to-M association between the 5GC and edge application resources. The local access model implies that there is no separation between the 5GC and edge application domains. This leads to security implications because there is a lack of separate policy domains. Each DNAI may be required to have edge application resources. The proximate access model has separation of multiple separate policy domains (e.g., ASNs) with an interconnection methodology.

(89) Mobility in a communication system supporting local access results in also moving EASs, which requires synchronization and complicated signaling. Mobility in a communication system that supports proximate access is independent of EAS relocation, thereby eliminating complicated signaling. Hence, in the local access model, edge server relocation is complex because the relocation of the EAS is coupled to the relocation of the local PSA. This implies that when the PDU session is changed due to UE mobility, the EAS has to be relocated. This may result in more jitter than just moving one end. However, in the proximate access model, there is clear separation of the two domains and an optimal method of routing between the two domains exist. Thus UE mobility and server relocation in each domain can proceed independently. There is no need to synchronize mobility between the two domains and the result is lower transport jitter during mobility because only one end is moved.

(90) When a failure of an edge computing component in a communication system utilizing local access occurs, coordination with the 5GC may be needed to remedy the failed component. However, in a communication system utilizing proximate access, component relocation on failure of an edge computing component is independent of the 5GC. The provisioning of resources in a communication system with local access involves controllers (i.e., 5GC and AF or edge controller) synchronizing resources in different domains. In a communication system supporting proximate access, the provisioning of resources involves the 5GC and AF or edge controller only coordinating to change routes. This is referred to as loose coordination. In the local access model, failure of an application domain resource can result in the relocation of the PDU session or DNAI. This may lead to a cascade of issues because there are two controllers of different resource domains (i.e., 5GC and edge application) attempting to coordinate recovery. In the proximate access model, the AF may redirect to the next best (or automatically via anycast) server and does not require the PDU session to be modified. The resource domains independently control their resources.

(91) FIG. 8A illustrates a first communication system **800** highlighting local access. In communication system **800**, a data network **805** has a DNAI=D1. In data network **805**, EAS **807** is connected to AF **809**. The presence of EAS **807** is known by ULCL **811**, which routes traffic from access nodes, such as access node **813**, to EAS **807** through PSA **815**.

(92) FIG. 8B illustrates a first communication system **850** highlighting proximate access. In communication system **800**, UE **243** connected to data network **855** and obtains service from EAS **857** through flow **859**. UE **243** also obtains service from AS **861** through flow **863**. Traffic over flow **859** is steered by ULCL **865** to EAS **867** over PSA **869**, GW **871**, and GW **873**. Traffic over flow **863** is steered by ULCL **865** to AS **861** over GW **871**, network **875**, GW **877**, network **879**, and PSA **881**.

(93) FIG. 9A illustrates a second communication system **900** highlighting local access to a data network. Communication system **900** includes UE **243** connected to EAS **905** of data network **907**. Packets from UE **243** are steered by ULCL **909** to EAS **905** through PSA **911**. EAS **905** is connected to AF **913** and AS **915** through network **917**.

(94) PSA **911** is in the same network segment as EAS **905**, so there may be a security issue for both parties. Furthermore, AF **913** needs access to EAS **905** for orchestration. The access is not via a PDU session because orchestration uses a network-network interface (NNI) and not a user-network interface (UNI).

(95) FIG. 9B illustrates a second communication system **950** highlighting proximate access to a data network. Communication system **950** includes UE **243** connected to EAS **955** that is proximate to data network **957**. ULCL **959** steers traffic from UE **243** to EAS **955** over PSA **961**,

network **965**, and GW **967**. EAS **905** is connected to AF **969** and AS **971** through network **973**.

(96) Because PSA **961** and EAS **955** are in different network segments, different routing and security policies may be implemented in the different network segments. PSA **961**, network **965**, and EAS **955** may be implemented as part of a single data center, implemented as different ASNs, and thus supporting different policies. Orchestration is managed by the same GW (e.g., GW **975**) that grants access to remote resources.

(97) Another problem addressed herein is how to route to the nearest EAS when a split PDU session (with a ULCL) needs rules to selectively steer the traffic. Some existing techniques use a DNS agent (e.g., proxy, inspector, relay, and so on) that is located at or near the ULCL to inspect the request and determine the intended destination of the DNS service request. The example embodiments presented herein manages and scales the DNS independently while supporting Do53, DoT, and DoH.

(98) Drawbacks of the DNS methods include: Because the DNS agents inspect each request (even the ones that have no edge deployment), potentially resulting in higher DNS resolution latency. Reconfiguring the access (PDU session) during the DNS resolution process result in the DNS resolution taking additional time (not just for the translation). Access may be redirected and reconfigured based on the inspected DNS requests, which may lead to additional delay. Disruption during a handover may occur because DNS processing is required to handle selection. Privacy may not be supported, e.g., when DoH is used, the resolver may be in a third party network.

Alternatively, if VPNs are used, no DNS requests are visible.

(99) The example embodiments presented herein feature: Routes in the ULCL are provisioned during PDU session handling. Hence, there is no delay in handling DNS requests because only DNS translation needs to be performed. Reconfiguring of access during the DNS resolution process is not needed. The DNS resolvers may be deployed independently to increase scalability and resilience, with no need to place inspectors near each access or UPF. Handovers occur without disruption because the DNS translations (IP addresses) are valid even after mobility. Because there is no inspection of DNS requests, DoH, DoT, or DNS within a VPN may work with no additional changes.

(100) FIG. **10** illustrates a communication system **1000** highlighting an example configuration, along with PDU session and application flow. In events **1005**, AF **305** to 5GC **209** interaction includes traffic influenced routing with service IP address and data network locations. In this situation, the data set includes (IP-a, {data network **213**, data network **217**}), (IP-b, {data network **215**, data network **217**}), and (IP-c, {data network **215**}). AF **305** does not send a FQDN; the contract is only for routing and thus there is a minimal exchange of information. NEF **309**, PCF **237**, etc., add DNN and S-NSSAI, and organize the information based on DNAI.

(101) In events **1007**, UE **243** requests a PDU session setup (not shown in FIG. **10**) and SMF **311** fetches policy including traffic influence routing rules. SMF **311** selects UPFs (of PSAs **251** and **272**, and ULCL **315**) based on the DNAI, etc. N4 match action filters for ULCL **315**: {IP-a, PSA **251**}, {IP-b, PSA **251**}, and {IP-c, PSA **251**}.

(102) In events **1009**, UE **243** requests DNS **1011** for resolution of a FQDN. DNS **1011** forwards the FQDN to ADNS **264**, which responds with IP-a. ULCL **315** has no filter rule, thus the DNS request is not steered in this situation. For private networks, VPNs, etc., the DNS request may also be steered based on AF traffic influenced routing.

(103) In events **1013**, UE **243** sends an application request with destination address IP-a. ULCL **315** filters based on {IP-a, PSA **251**} and steers to PSA **251**. A local N6 network advertisement for anycast IP address IP-a (BGP, SDN) forwards to EAS **219**.

(104) In FIG. **10**, it is accepted that AF **305** has configured services in the data networks (events **1015** and **1017**). In events **1015** two services are configured, with one service having anycast IP address IP-a and the other having anycast IP address IP-b. ADNS **264** is configured with the corresponding FQDNs and resolution to IP-a and IP-b in event **1017**.

(105) FIG. 11 illustrates a flow diagram of example operation **1100** occurring in a NEF. Operations **1100** may be indicative of operations occurring in a NEF, such as NEF **309**, as the NEF supports the configuration of assistance information to facilitate packet steering.

(106) Operations **1100** begin with the NEF receiving addresses of services (block **1105**). The addresses of services may be received from an AF, for example. The addresses of services may represent destination addresses of routes to application servers, for example. The address of services may be received in a service operation message, such as a Nnef_TrafficInfluence_Create, Nnef_TrafficInfluence_Update, or Nnef_TrafficInfluence_Delete message. The address of a service is in the form of an IP anycast address, and an example address of a service is srv-IP-addr. The NEF also receives a list of network identifiers (block **1107**). The list of network identifiers may be received from the AF, for example. The list of network identifiers identifies local data network locations at which the addresses of services are configured. The list of network identifiers may be a list of gateways of the local data network locations, for example. The addresses of services and the list of network identifiers may be received in a single message or in separate messages. The NEF stores the addresses of services at the PCF.

(107) The NEF generates traffic filters (block **1109**). The NEF may generate the traffic filters, e.g., authorization controls, in accordance with the addresses of services and the list of network identifiers. The NEF generates information for the traffic filters (block **1111**). The information for the traffic filters may comprise S-NSSAI. The traffic filters and the information for the traffic filters may be stored in a UDR. The NEF sends a response (block **1113**). The response may be sent to the AF, for example. The response may be a service operation message, such as a Nnef_TrafficInfluence_Create, Nnef_TrafficInfluence_Update, or Nnef_TrafficInfluence_Delete response message.

(108) FIG. 12 illustrates a flow diagram of example operations **1200** occurring in a PCF. Operations **1200** may be indicative of operations occurring in a PCF, such as PCF **237**, as the PCF supports the configuration of assistance information to facilitate packet steering.

(109) Operations **1200** begin with the PCF receiving information for the traffic filters (block **1205**). The information for the traffic filters may be received from the UDR, for example. The information for the traffic filters may be received in a Nudr_DM_Notify message, and may include the S-NSSAI, the addresses of the services, and the list of network identifiers. The PCF derives a network identifier (block **1207**). The network identifier may be a set of DNAI that are close to each local data network location (e.g., gateway addresses). The DNAIs and gateways are topologically or administratively close to each other. The network identifier and the information for the traffic filters are referred to as AF traffic influence data set.

(110) The PCF stores the network identifier and the information for the traffic filters (block **1209**). The network identifier and the information for the traffic filters (such as the addresses of services) may be stored in a local memory. The PCF updates the network identifier and the information for the traffic filters (block **1211**). As an example, the network identifier and the information for the traffic filters of PDU sessions that are affected by the AF traffic influence data set. If there are multiple PDU sessions affected by the AF traffic influence data set, the multiple PDU sessions are updated. Different PDU sessions may be updated with different information.

(111) FIG. 13 illustrates a flow diagram of example operations **1300** occurring in a PCF participating in split model PDU session establishment and traffic steering. Operations **1300** may be indicative of operations occurring in a PCF, such as PCF **237**, as the PCF participates in split model PDU session establishment and traffic steering.

(112) Operations **1300** begin with the PCF participating in UE registration (block **1305**). The UE registers through the AMF. In addition to registration, the UE is either configured or dynamically provided with URSP rules indicating the network slice (identified by the S-NSSAI, for example) used for edge applications or subsets of applications. The PCF receives a policy create request (block **1307**). The policy create request may be received from the SMF selected to manage the

PDU session. The policy create request may be received as a Npcf_SMPolicy_Control message, e.g., a Npcf_SMPolicy_Control_Create request message. The policy create request includes the S-NSSAI, for example.

(113) The PCF retrieves the policy (block **1309**). The PCF retrieves the policy for the PDU session. The policy may include a list of service addresses for the DNAI, as well as the DNAI. The PCF sends a policy create response (block **1311**). The policy create response may be sent to the SMF and includes the policy retrieved by the PCF. The policy create response may be sent as a Npcf_SMPolicy_Control message, e.g., a Npcf_SMPolicy_Control_Create response message.

(114) FIG. **14** illustrates a flow diagram of example operations **1400** occurring in a SMF participating in split model PDU session establishment and traffic steering. Operations **1400** may be indicative of operations occurring in a SMF, such as SMF **311**, as the SMF participates in split model PDU session establishment and traffic steering.

(115) Operations **1400** being with the SMF participating in UE registration (block **1405**). The UE registers through the AMF. In addition to registration, the UE is either configured or dynamically provided with URSP rules indicating the network slice (identified by the S-NSSAI, for example) used for edge applications or subsets of applications. The SMF receives a service context request (block **1407**). The service context request may be received from the AMF. The service context request may be received in a Nsmf_PDUSession_CreateSMContext request message. The service context request includes the S-NSSAI used for edge applications or subsets of applications.

(116) The SMF sends a policy create request (block **1409**). The policy create request may be sent to the PCF selected to manage the PDU session. The policy create request may be sent as a Npcf_SMPolicy_Control message, e.g., a Npcf_SMPolicy_Control_Create request message. The policy create request includes the S-NSSAI, for example. The SMF receives a policy create response (block **1411**). The policy create response may be received from the PCF and includes the policy (i.e., a list of service addresses for the DNAI, as well as the DNAI) retrieved by the PCF. The policy create response may be sent as a Npcf_SMPolicy_Control message, e.g., a Npcf_SMPolicy_Control_Create response message.

(117) The SMF selects a local PSA (block **1413**). The local PSA may be selected in accordance with the DNAI FAR and the service address by the ULCL. The SMF participates in an N4 session establishment (block **1415**). The N4 session establishment includes the SMF programming UPF(s) over the N4 interface, where the UPF(s) are programmed with the DNAI FAR and the list of service addresses. The SMF also provisions the PSAs (local and central), and provisions the ULCL with the FAR traffic filters for destination addresses corresponding to the list of service addresses.

(118) FIG. **15** illustrates an example communication system **1500**. In general, the system **1500** enables multiple wireless or wired users to transmit and receive data and other content. The system **1500** may implement one or more channel access methods, such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal FDMA (OFDMA), single-carrier FDMA (SC-FDMA), or non-orthogonal multiple access (NOMA).

(119) In this example, the communication system **1500** includes electronic devices (ED) **1510a-1510c**, radio access networks (RANs) **1520a-1520b**, a core network **1530**, a public switched telephone network (PSTN) **1540**, the Internet **1550**, and other networks **1560**. While certain numbers of these components or elements are shown in FIG. **15**, any number of these components or elements may be included in the system **1500**.

(120) The EDs **1510a-1510c** are configured to operate or communicate in the system **1500**. For example, the EDs **1510a-1510c** are configured to transmit or receive via wireless or wired communication channels. Each ED **1510a-1510c** represents any suitable end user device and may include such devices (or may be referred to) as a user equipment or device (UE), wireless transmit or receive unit (WTRU), mobile station, fixed or mobile subscriber unit, cellular telephone, personal digital assistant (PDA), smartphone, laptop, computer, touchpad, wireless sensor, or

consumer electronics device.

(121) The RANs **1520a-1520b** here include base stations **1570a-1570b**, respectively. Each base station **1570a-1570b** is configured to wirelessly interface with one or more of the EDs **1510a-1510c** to enable access to the core network **1530**, the PSTN **1540**, the Internet **1550**, or the other networks **1560**. For example, the base stations **1570a-1570b** may include (or be) one or more of several well-known devices, such as a base transceiver station (BTS), a Node-B (NodeB), an evolved NodeB (eNodeB), a Next Generation (NG) NodeB (gNB), a Home NodeB, a Home eNodeB, a site controller, an access point (AP), or a wireless router. The EDs **1510a-1510c** are configured to interface and communicate with the Internet **1550** and may access the core network **1530**, the PSTN **1540**, or the other networks **1560**.

(122) In the embodiment shown in FIG. **15**, the base station **1570a** forms part of the RAN **1520a**, which may include other base stations, elements, or devices. Also, the base station **1570b** forms part of the RAN **1520b**, which may include other base stations, elements, or devices. Each base station **1570a-1570b** operates to transmit or receive wireless signals within a particular geographic region or area, sometimes referred to as a “cell.” In some embodiments, multiple-input multiple-output (MIMO) technology may be employed having multiple transceivers for each cell.

(123) The base stations **1570a-1570b** communicate with one or more of the EDs **1510a-1510c** over one or more air interfaces **1590** using wireless communication links. The air interfaces **1590** may utilize any suitable radio access technology.

(124) It is contemplated that the system **1500** may use multiple channel access functionality, including such schemes as described above. In particular embodiments, the base stations and EDs implement 5G New Radio (NR), LTE, LTE-A, or LTE-B. Of course, other multiple access schemes and wireless protocols may be utilized.

(125) The RANs **1520a-1520b** are in communication with the core network **1530** to provide the EDs **1510a-1510c** with voice, data, application, Voice over Internet Protocol (VoIP), or other services. Understandably, the RANs **1520a-1520b** or the core network **1530** may be in direct or indirect communication with one or more other RANs (not shown). The core network **1530** may also serve as a gateway access for other networks (such as the PSTN **1540**, the Internet **1550**, and the other networks **1560**). In addition, some or all of the EDs **1510a-1510c** may include functionality for communicating with different wireless networks over different wireless links using different wireless technologies or protocols. Instead of wireless communication (or in addition thereto), the EDs may communicate via wired communication channels to a service provider or switch (not shown), and to the Internet **1550**.

(126) Although FIG. **15** illustrates one example of a communication system, various changes may be made to FIG. **15**. For example, the communication system **1500** could include any number of EDs, base stations, networks, or other components in any suitable configuration.

(127) FIGS. **16A** and **16B** illustrate example devices that may implement the methods and teachings according to this disclosure. In particular, FIG. **16A** illustrates an example ED **1610**, and FIG. **16B** illustrates an example base station **1670**. These components could be used in the system **1500** or in any other suitable system.

(128) As shown in FIG. **16A**, the ED **1610** includes at least one processing unit **1600**. The processing unit **1600** implements various processing operations of the ED **1610**. For example, the processing unit **1600** could perform signal coding, data processing, power control, input/output processing, or any other functionality enabling the ED **1610** to operate in the system **1500**. The processing unit **1600** also supports the methods and teachings described in more detail above. Each processing unit **1600** includes any suitable processing or computing device configured to perform one or more operations. Each processing unit **1600** could, for example, include a microprocessor, microcontroller, digital signal processor, field programmable gate array, or application specific integrated circuit.

(129) The ED **1610** also includes at least one transceiver **1602**. The transceiver **1602** is configured

to modulate data or other content for transmission by at least one antenna or NIC (Network Interface Controller) **1604**. The transceiver **1602** is also configured to demodulate data or other content received by the at least one antenna **1604**. Each transceiver **1602** includes any suitable structure for generating signals for wireless or wired transmission or processing signals received wirelessly or by wire. Each antenna **1604** includes any suitable structure for transmitting or receiving wireless or wired signals. One or multiple transceivers **1602** could be used in the ED **1610**, and one or multiple antennas **1604** could be used in the ED **1610**. Although shown as a single functional unit, a transceiver **1602** could also be implemented using at least one transmitter and at least one separate receiver.

(130) The ED **1610** further includes one or more input/output devices **1606** or interfaces (such as a wired interface to the Internet **1550**). The input/output devices **1606** facilitate interaction with a user or other devices (network communications) in the network. Each input/output device **1606** includes any suitable structure for providing information to or receiving information from a user, such as a speaker, microphone, keypad, keyboard, display, or touch screen, including network interface communications.

(131) In addition, the ED **1610** includes at least one memory **1608**. The memory **1608** stores instructions and data used, generated, or collected by the ED **1610**. For example, the memory **1608** could store software or firmware instructions executed by the processing unit(s) **1600** and data used to reduce or eliminate interference in incoming signals. Each memory **1608** includes any suitable volatile or non-volatile storage and retrieval device(s). Any suitable type of memory may be used, such as random access memory (RAM), read only memory (ROM), hard disk, optical disc, subscriber identity module (SIM) card, memory stick, secure digital (SD) memory card, and the like.

(132) As shown in FIG. **16B**, the base station **1670** includes at least one processing unit **1650**, at least one transceiver **1652**, which includes functionality for a transmitter and a receiver, one or more antennas **1656**, at least one memory **1658**, and one or more input/output devices or interfaces **1666**. A scheduler, which would be understood by one skilled in the art, is coupled to the processing unit **1650**. The scheduler could be included within or operated separately from the base station **1670**. The processing unit **1650** implements various processing operations of the base station **1670**, such as signal coding, data processing, power control, input/output processing, or any other functionality. The processing unit **1650** can also support the methods and teachings described in more detail above. Each processing unit **1650** includes any suitable processing or computing device configured to perform one or more operations. Each processing unit **1650** could, for example, include a microprocessor, microcontroller, digital signal processor, field programmable gate array, or application specific integrated circuit.

(133) Each transceiver **1652** includes any suitable structure for generating signals for wireless or wired transmission to one or more EDs or other devices. Each transceiver **1652** further includes any suitable structure for processing signals received wirelessly or by wire from one or more EDs or other devices. Although shown combined as a transceiver **1652**, a transmitter and a receiver could be separate components. Each antenna **1656** includes any suitable structure for transmitting or receiving wireless or wired signals. While a common antenna **1656** is shown here as being coupled to the transceiver **1652**, one or more antennas **1656** could be coupled to the transceiver(s) **1652**, allowing separate antennas **1656** to be coupled to the transmitter and the receiver if equipped as separate components. Each memory **1658** includes any suitable volatile or non-volatile storage and retrieval device(s). Each input/output device **1666** facilitates interaction with a user or other devices (network communications) in the network. Each input/output device **1666** includes any suitable structure for providing information to or receiving/providing information from a user, including network interface communications.

(134) FIG. **17** is a block diagram of a computing system **1700** that may be used for implementing the devices and methods disclosed herein. For example, the computing system can be any entity of

UE, access network (AN), mobility management (MM), session management (SM), user plane gateway (UPGW), or access stratum (AS). Specific devices may utilize all of the components shown or only a subset of the components, and levels of integration may vary from device to device. Furthermore, a device may contain multiple instances of a component, such as multiple processing units, processors, memories, transmitters, receivers, etc. The computing system **1700** includes a processing unit **1702**. The processing unit includes a central processing unit (CPU) **1714**, memory **1708**, and may further include a mass storage device **1704**, a video adapter **1710**, and an I/O interface **1712** connected to a bus **1720**.

(135) The bus **1720** may be one or more of any type of several bus architectures including a memory bus or memory controller, a peripheral bus, or a video bus. The CPU **1714** may comprise any type of electronic data processor. The memory **1708** may comprise any type of non-transitory system memory such as static random access memory (SRAM), dynamic random access memory (DRAM), synchronous DRAM (SDRAM), read-only memory (ROM), or a combination thereof. In an embodiment, the memory **1708** may include ROM for use at boot-up, and DRAM for program and data storage for use while executing programs.

(136) The mass storage **1704** may comprise any type of non-transitory storage device configured to store data, programs, and other information and to make the data, programs, and other information accessible via the bus **1720**. The mass storage **1704** may comprise, for example, one or more of a solid state drive, hard disk drive, a magnetic disk drive, or an optical disk drive.

(137) The video adapter **1710** and the I/O interface **1712** provide interfaces to couple external input and output devices to the processing unit **1702**. As illustrated, examples of input and output devices include a display **1718** coupled to the video adapter **1710** and a mouse, keyboard, or printer **1716** coupled to the I/O interface **1712**. Other devices may be coupled to the processing unit **1702**, and additional or fewer interface cards may be utilized. For example, a serial interface such as Universal Serial Bus (USB) (not shown) may be used to provide an interface for an external device.

(138) The processing unit **1702** also includes one or more network interfaces **1706**, which may comprise wired links, such as an Ethernet cable, or wireless links to access nodes or different networks. The network interfaces **1706** allow the processing unit **1702** to communicate with remote units via the networks. For example, the network interfaces **1706** may provide wireless communication via one or more transmitters/transmit antennas and one or more receivers/receive antennas. In an embodiment, the processing unit **1702** is coupled to a local-area network **1722** or a wide-area network for data processing and communications with remote devices, such as other processing units, the Internet, or remote storage facilities.

(139) It should be appreciated that one or more steps of the embodiment methods provided herein may be performed by corresponding units or modules. For example, a signal may be transmitted by a transmitting unit or a transmitting module. A signal may be received by a receiving unit or a receiving module. A signal may be processed by a processing unit or a processing module. Other steps may be performed by a generating unit or module, a calculating unit or module, a storing unit or module, a deriving unit or module, or a providing unit or module. The respective units or modules may be hardware, software, or a combination thereof. For instance, one or more of the units or modules may be an integrated circuit, such as field programmable gate arrays (FPGAs) or application-specific integrated circuits (ASICs).

(140) Although the present disclosure and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the scope of the disclosure as defined by the appended claims.

Claims

1. A method comprising: receiving, by a control plane (CP) from an application function (AF), a traffic influence routing rule comprising a service address representing a destination address of a

route to an application server, the traffic influence routing rule specifying a breakout rule for packets of a communicating device addressed to the application server, wherein the breakout rule indicates whether to break out the packets to a local packet data unit (PDU) session anchor (PSA) or forward the packets to a central PSA; storing, by the CP, the traffic influence routing rule in a policy control function (PCF); and generating, by the CP, a traffic filter for packets of at least one traffic flow associated with the communicating device, the traffic filter directing the packets of the at least one traffic flow that are addressed to the application server to the service address, the traffic filter being generated in accordance with the traffic influence routing rule.

2. The method of claim 1, the traffic influence routing rule comprising at least one of a traffic influence create rule, a traffic influence update rule, or a traffic influence delete rule.

3. The method of claim 1, the traffic influence routing rule further comprising at least one gateway address associated with the service address.

4. The method of claim 3, the traffic filter comprising the service address and the at least one gateway address.

5. The method of claim 1, the traffic filter being stored in accordance with network slice selection assistance information.

6. The method of claim 1, further comprising: sending, by the CP to the AF, a traffic influence routing rule response.

7. The method of claim 1, the traffic filter being stored in a unified data repository (UDR).

8. The method of claim 1, storing the traffic filter comprising: updating an existing traffic filter with the traffic filter.

9. The method of claim 1, the service address comprising an Internet Protocol (IP) address, a port address, and a protocol.

10. The method of claim 1, further comprising: generating, by the CP, information associated with the traffic filter.

11. The method of claim 10, the information comprising single network slice selection assistance information (S-NSSAI).

12. A method comprising: receiving, by a policy control function (PCF), a traffic filter for packets of at least one traffic flow associated with a communicating device, the traffic filter comprising a traffic influence routing rule specifying a breakout rule for packets addressed to an application server, wherein the breakout rule indicates whether to break out the packets to a local packet data unit (PDU) session anchor (PSA) or forward the packets to a central PSA; deriving, by the PCF, a network identifier associated with the traffic filter; and providing, by the PCF to a session management function (SMF), the network identifier and the traffic filter.

13. The method of claim 12, the network identifier comprising a data network access identifier (DNAI).

14. The method of claim 12, the traffic filter comprising a service address and at least one gateway address.

15. The method of claim 12, the traffic filter further comprising network slice selection assistance information.

16. The method of claim 12, the providing the network identifier and the traffic filter comprising: initiating a session management policy control service.

17. A control plane (CP) comprising: a non-transitory memory storage comprising instructions; and one or more processors in communication with the non-transitory memory storage, wherein the one or more processors execute the instructions to cause the CP to: receive, from an application function (AF), a traffic influence routing rule comprising a service address representing a destination address as a route to an application server, the traffic influence routing rule specifying a breakout rule for packets of a communicating device addressed to the application server, wherein the breakout rule indicates whether to break out the packets to a local packet data unit (PDU) session anchor (PSA) or forward the packets to a central PSA; store the traffic influence routing

rule in a policy control function (PCF); and generate a traffic filter for packets of at least one traffic flow associated with the communicating device, the traffic filter directing the packets of the at least one traffic flow that are addressed to the application server to the service address, the traffic filter being generated in accordance with the traffic influence routing rule.

18. The CP of claim 17, the traffic influence routing rule comprising at least one of a traffic influence create rule, a traffic influence update rule, or a traffic influence delete rule.

19. The CP of claim 17, the traffic influence routing rule further comprising at least one gateway address associated with the service address.

20. The CP of claim 19, the traffic filter comprising the service address and the at least one gateway address.

21. The CP of claim 19, the traffic filter being stored in accordance with a network slice selection assistance information.

22. The CP of claim 17, the one or more processors further executing the instructions to cause the CP to: send, to the AF, a traffic influence routing rule response.

23. The CP of claim 17, the traffic filter being stored in a unified data repository (UDR).

24. The CP of claim 17, the instructions to cause the CP to store the traffic filter including instructions to cause the CP to: update an existing traffic filter with the traffic filter.

25. The CP of claim 17, the service address comprising an Internet Protocol address, a port address, and a protocol.

26. The CP of claim 17, the one or more processors further executing the instructions to cause the CP to: generate information associated with the traffic filter.

27. The CP of claim 26, the information comprising single network slice selection assistance information (S-NSSAI).

28. A network function (NF) comprising: a non-transitory memory storage comprising instructions; and one or more processors in communication with the non-transitory memory storage, wherein the one or more processors execute the instructions to cause the NF to: receive a traffic filter for packets of at least one traffic flow associated with a communicating device, the traffic filter comprising a traffic influence routing rule specifying a breakout rule for packets addressed to an application server, wherein the breakout rule indicates whether to break out the packets to a local packet data unit (PDU) session anchor (PSA) or forward the packets to a central PSA; derive a network identifier associated with the traffic filter; and provide, to a session management function (SMF), the network identifier and the traffic filter.

29. The NF of claim 28, the network identifier comprising a data network access identifier (DNAI).

30. The NF of claim 28, the traffic filter comprising a service address and at least one gateway address.

31. The NF of claim 28, the traffic filter further comprising network slice selection assistance information.

32. The NF of claim 28, the instructions to cause the NF to provide the network identifier and the traffic filter including instructions to cause the NF to: initiate a session management policy control service.

33. The method of claim 1, wherein the service address is indicated as an anycast Internet protocol (IP) address corresponding to the AF or multiple unicast IP addresses corresponding to the AF, and wherein a user plane function (UPF) uplink classifier (ULCL) performs breaking out the packets to the local PSA or forwarding the packets to the central PSA.
