

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408502
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tai; Ming-Jou et al.

Electronic device

Abstract

An electronic device includes a substrate, a first conductive wire, a plurality of semiconductors, an insulation layer and a plurality of conductive elements. The first conductive wire is configured to transmit a first signal and disposed on the substrate, and the first conductive wire extends along a first direction. The semiconductors are disposed on the substrate and overlapped with the first conductive wire. The insulation layer is disposed on the substrate and has a plurality of holes. The conductive elements are disposed on the substrate and overlapped with the semiconductors respectively. In a top view of the electronic device, each one of the plurality of holes overlaps with at least one semiconductor, and a number of the holes is less than a number of the plurality of conductive elements.

Inventors: Tai; Ming-Jou (Miaoli County, TW), Tsai; Chia-Hao (Miaoli County, TW)

Applicant: Innolux Corporation (Miaoli County, TW)

Family ID: 75847896

Assignee: Innolux Corporation (Miaoli County, TW)

Appl. No.: 18/764192

Filed: July 04, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240363822 A1	Oct. 31, 2024

Foreign Application Priority Data

CN	202011041245.0	Sep. 28, 2020
----	----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: H10H20/857 (20250101)

U.S. Cl.:

CPC H10H20/857 (20250101);

Field of Classification Search

CPC: H10H (20/857); H10D (84/0109); H10D (1/045); H10D (64/511); H10D (10/821); H01L (33/62); H01L (29/78618); H01L (29/41733); H01L (27/124)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
12062747	12/2023	Tai	N/A	H01L 29/41733
2014/0139774	12/2013	Tsai	257/43	H10D 86/60
2014/0145195	12/2013	Kim	438/158	H01L 21/32133
2017/0033235	12/2016	Tsao	N/A	G02F 1/136227
2018/0069099	12/2017	Yu	N/A	H10D 30/0321
2019/0296050	12/2018	Yoshida	N/A	H10D 30/6731
2021/0043657	12/2020	Song	N/A	H10D 86/021
2021/0305288	12/2020	Tai	N/A	H10D 30/6723
2024/0402551	12/2023	Sung	N/A	G02F 1/13439

Primary Examiner: Mandala; Victor A

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation application of and claims the priority benefit of a prior U.S. application Ser. No. 18/149,162, filed on Jan. 3, 2023. The prior U.S. application Ser. No. 18/149,162 is a continuation application of and claims the priority benefit of a prior U.S. application Ser. No. 17/093,638, filed on Nov. 10, 2020, which claims the priority benefit of U.S. provisional application Ser. No. 62/933,989, filed on Nov. 12, 2019, and China application serial no. 202011041245.0, filed on Sep. 28, 2020. The entirety of each of the above-mentioned patent applications is hereby incorporated by reference herein and made a part of this specification.

TECHNICAL FIELD

(1) The disclosure relates to an electronic device, and more particularly, to an electronic device that

can provide better display quality.

BACKGROUND

(2) Display panels have been widely used in electronic devices such as mobile phones, televisions, monitors, tablet computers, car displays, wearable devices, and desktop computers. With the vigorous development of electronic products, the requirements for display quality on electronic products are getting higher, making electronic devices used for display increasingly light, thin, short, small, frameless, and larger or higher resolution display effects Improve.

SUMMARY

(3) The disclosure provides an electronic device that has better reliability or better display quality.

(4) According to the embodiments of the disclosure, an electronic device includes a substrate, a plurality of transistors and a plurality of drain contact holes. The transistors are disposed on the substrate. Each transistor has a semiconductor, a source and a drain. The drains are electrically connected to the semiconductors through the drain contact holes. A number of the drain contact holes is less than a number of the drains.

(5) According to the embodiments of the disclosure, an electronic device includes a substrate, a first conductive wire, a plurality of semiconductors, an insulation layer and a plurality of conductive elements. The first conductive wire is configured to transmit a first signal and disposed on the substrate, and the first conductive wire extends along a first direction. The semiconductors are disposed on the substrate and overlapped with the first conductive wire. The insulation layer is disposed on the substrate and has a plurality of holes. The conductive elements are disposed on the substrate and overlapped with the semiconductors respectively. In a top view of the electronic device, each one of the plurality of holes overlaps with at least one semiconductor, and a number of the holes is less than a number of the plurality of conductive elements.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of the specification. The drawings illustrate embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

(2) FIG. 1A is a schematic top view of an electronic device according to an embodiment of the disclosure.

(3) FIG. 1B is a schematic cross-sectional view of the electronic device of FIG. 1A along section line A-A'.

(4) FIG. 2 is a schematic top view of an electronic device according to another embodiment of the disclosure.

(5) FIG. 3 is a schematic top view of an electronic device according to another embodiment of the disclosure.

(6) FIG. 4 is a schematic top view of an electronic device according to another embodiment of the disclosure.

(7) FIG. 5A is a schematic top view of an electronic device according to another embodiment of the disclosure.

(8) FIG. 5B is a schematic cross-sectional view of the electronic device of FIG. 5A along section line B-B'.

(9) FIG. 6 is a schematic top view of an electronic device according to another embodiment of the disclosure.

DETAILED DESCRIPTION

(10) The disclosure may be understood by referring to the following detailed description with

reference to the accompanying drawings. It is noted that for comprehension of the reader and simplicity of the drawings, in the drawings of the disclosure, only a part of the electronic device is shown, and specific components in the drawings are not necessarily drawn to scale. Moreover, the quantity and the size of each component in the drawings are only schematic and are not intended to limit the scope of the disclosure.

(11) In the following specification and claims, the terms “having”, “including”, etc. are open-ended terms, so they should be interpreted to mean “including but not limited to . . .”.

(12) It should be understood that when a component or a film layer is described as being “on” or “connected to” another component or film layer, it may be directly on or connected to the another component or film layer, or there is an intervening component or film layer therebetween (i.e., indirect connection). Conversely, when a component or film layer is described as being “directly on” or “directly connected to” another component or film layer, there is no intervening component or film layer therebetween.

(13) The terms such as “first”, “second”, “third”, etc. may be used to describe components, but the components should not be limited by these terms. The terms are only intended to distinguish a component from another component in the specification. It is possible that the claims do not use the same terms and replace the terms with “first”, “second”, “third” etc. according to the sequence declared in the claims. Accordingly, in the specification, a first component may be a second component in the claims.

(14) Herein, the terms “about”, “approximately”, “substantially”, and “essentially” usually mean within 10%, or within 5%, or within 3%, or 2% or within 1%, or within 0.5% of a given value or range. The quantity given here is an approximate quantity, that is, the meaning of “about”, “approximately”, “substantially”, and “essentially” can still be implied without specifying the terms “about”, “approximately”, “substantially”, and “essentially”. In addition, the terms “a range from a first value to a second value” and “a range between a first value and a second value” indicate that the range includes the first value, the second value, and other values in between.

(15) In some embodiments of the disclosure, unless specifically defined, terms related to bonding and connection such as “connect”, “interconnect”, etc. may mean that two structures are in direct contact, or that two structures are not in direct contact with other structures provided therebetween. The terms related to bonding and connection may also cover cases where two structures are both movable or two structures are both fixed. In addition, the term “couple” includes any direct and indirect electrical connection means.

(16) In the disclosure, the length and width may be measured by an optical microscope, and the thickness may be measured based on a cross-sectional image in an electron microscope, but the disclosure is not limited thereto. In addition, there may be a certain error between any two values or directions used for comparison.

(17) In the disclosure, the electronic device may include a display device, an antenna device, a sensing device, a touch display, a curved display, or a free shape display, but is not limited thereto. The electronic device may be a bendable or flexible electronic device. The electronic device may include, for example, a light emitting diode (LED), a liquid crystal, a fluorescence, a phosphor, a quantum dot (QD), other suitable display media, or a combination of the above, but is not limited thereto. The light emitting diode may include, for example, an organic light emitting diode (OLED), inorganic light emitting diode (LED), a mini LED, a micro LED or a quantum dot LED (e.g., QLED or QDLED), other suitable materials, or any combination of the above, but is not limited thereto. The display device may include, for example, a splicing display device, but is not limited thereto. The antenna device may be, for example, a liquid crystal antenna, but is not limited thereto. The antenna device may include, for example, an antenna splicing device, but is not limited thereto. It is noted that the electronic device may be any combination of the above, but is not limited thereto. In addition, the shape of the electronic device may be rectangular, circular, polygonal, a shape with curved edges, or other suitable shapes. The electronic device may have

peripheral systems such as a driving system, a control system, a light source system, a rack system, etc. to support a display device, an antenna device, or a splicing device. Hereinafter, an electronic device will be described to illustrate the content of the disclosure, but the disclosure is not limited thereto.

(18) It should be noted that in the following embodiments, features in a plurality of embodiments may be replaced, recombined, or mixed to complete other embodiments without departing from the spirit of the disclosure. The features of the embodiments may be used in any combination without departing from the spirit of the disclosure or conflicting with each other.

(19) Reference will now be made in detail to the exemplary embodiments of the disclosure, examples of which are illustrated in the accompanying drawings. Whenever possible, the same reference numerals are used to represent the same or similar parts in the accompanying drawings and description.

(20) FIG. 1A is a schematic top view of an electronic device according to an embodiment of the disclosure. FIG. 1B is a schematic cross-sectional view of the electronic device of FIG. 1A along section line A-A'. For clarity of the drawings and convenience of description, some components of the electronic device are not shown in FIG. 1A.

(21) Referring to FIG. 1A and FIG. 1B, an electronic device **100** includes a substrate **110**, a plurality of transistors **120**, **121**, **122**, **123**, **124** and **125** (6 transistors are schematically depicted in FIG. 1A, but not limited thereto) and a plurality of drain contact holes **130** (one drain contact hole is schematically depicted in FIG. 1A, but not limited thereto). The substrate **110** may include a rigid substrate, a flexible substrate, or a combination thereof. For example, the material of the substrate **110** may include glass, quartz, sapphire, ceramic, polycarbonate (PC), polyimide (PI), polyethylene terephthalate (PET), other suitable substrate materials, or a combination of the above, but not limited thereto.

(22) The transistors **120**, **121**, **122**, **123**, **124** and **125** are disposed on the substrate **110**. The transistor **120**, the transistor **122** and the transistor **124** are sequentially arranged along a direction X (e.g., an extending direction of a scan line SL) and adjacent to each other; the transistor **121**, the transistor **123** and the transistor **125** are sequentially arranged along the direction X and adjacent to each other; the transistor **120** and the transistor **121** are sequentially arranged along a direction Y (e.g., an extending direction of a data line DL) and adjacent to each other; the transistor **122** and the transistor **123** are sequentially arranged along the direction Y and adjacent to each other; and the transistor **124** and the transistor **125** are sequentially arranged along the direction Y and adjacent to each other (the transistors being adjacent to each other means that there is no other transistor between the two transistors in the direction X or in the direction Y). In addition, in the top view of the electronic device **100** of this embodiment (as shown in FIG. 1A), the electronic device **100** further includes a plurality of sub-pixels P0, P1, P2, P3, P4 and P5. Among them, the transistor **120** is disposed corresponding to the sub-pixel P0; the transistor **121** is disposed corresponding to the sub-pixel P1; the transistor **122** is disposed corresponding to the sub-pixel P2; the transistor **123** is disposed corresponding to the sub-pixel P3; the transistor **124** is disposed corresponding to the sub-pixel P4; and the transistor **125** is disposed corresponding to the sub-pixel P5. For descriptive convenience, the transistor **120** and the transistor **121** are taken as an example below.

(23) In this embodiment, each transistor **120** (or **121**) has a semiconductor SE (or SE1), a source SD (or SD1), a drain SD' (or SD1'), a gate GE (or GE1) and a portion of a gate insulation layer GI. A portion of the scan line SL overlapping with the semiconductor SE may be defined as the gate GE. In the schematic top view of the electronic device **100** of this embodiment (as shown in FIG. 1A), the semiconductor SE of the transistor **120** and the semiconductor SE1 of the transistor **121** adjacent in the direction Y are in the same layer. One end of the semiconductor SE and one end of the semiconductor SE1 are connected together and partially overlap with the data line DL. The other end of the semiconductor SE has a side SE'. The side SE' is located between two adjacent data lines DL. An extension direction of the side SE' is substantially parallel to the direction X. The

other end of the semiconductor SE1 has a side SE1'. The side SE1' is also located between two adjacent data lines DL. An extension direction of the side SE1' is substantially parallel to the direction X. The side SE' and the side SE1' are separated from each other in the direction Y. In detail, a distance D1 is provided between the side SE' and the side SE1' in the direction Y. Accordingly, the semiconductors of the disclosure form an outline similar to a "C" shape. The outline of the semiconductor may be different from a "C" shape, for example a "U" shape, but not limited thereto. Referring to the schematic cross-sectional view of the electronic device **100** of this embodiment (as shown in FIG. 1), when the side SE' of the semiconductor SE and the side SE1' of the semiconductor SE1 are separated from each other, a portion of a buffer layer **140** is exposed. In this embodiment, the drain SD' (or SD1') overlaps with the scan line SL in the top view of the electronic device **100** (as shown in FIG. 1A) and in the cross-sectional view of the electronic device **100** (as shown in FIG. 1B). In this embodiment, the material of the semiconductors SE and SE1 may include amorphous silicon, low temperature polysilicon (LTPS), metal oxide (e.g., indium gallium zinc oxide (IGZO)), other suitable materials, or a combination of the above, but not limited thereto. In other embodiments, different transistors may include different semiconductor materials, but not limited thereto.

(24) Referring to the schematic cross-sectional view of the electronic device **100** of this embodiment (as shown in FIG. 1B), in this embodiment, the gate insulation layer GI is disposed on the semiconductor SE (or SE1) and has an opening GIa. A width W1 at the bottom of the opening GIa can be greater than the distance D1 between the side SE' of the semiconductor SE and the side SE1' of the semiconductor SE1, so that the opening GIa can expose a portion of the semiconductor SE (or SE1) and a portion of the buffer layer **140**. In this embodiment, the width W1 is, for example, a maximum width of the opening GIa measured along the direction Y, and the distance D1 is, for example, a maximum distance between the side SE' of the semiconductor SE and the side SE1' of the semiconductor SE1 measured along the direction Y.

(25) In this embodiment, the gate GE of the transistor **120** and the gate GE1 of the transistor **121** are respectively disposed on the gate insulation layer GI. The source SD and the drain SD' of the transistor **120** are respectively disposed on the gate GE, and the source SD1 and the drain SD1' of the transistor **121** are also respectively disposed on the gate GE1. The drain SD' and the drain SD1' are disposed on the substrate **110** and overlapped with the semiconductor SE and the semiconductor SE1 respectively in the top view of the electronic device **100**. In this embodiment, the material of the sources SD and SD1 and/or the drains SD' and SD1' may include a transparent conductive material or a non-transparent conductive material, such as indium tin oxide, indium zinc oxide, indium oxide, zinc oxide, tin oxide, a metal material (e.g., aluminum, molybdenum, copper, silver), other suitable materials, or a combination of the above, but not limited thereto.

(26) In the schematic top view of the electronic device **100** of this embodiment (as shown in FIG. 1A), the electronic device **100** further includes the scan line SL for transmitting scan signal and the data line DL for transmitting data signal. The scan line SL and the data line DL are disposed on the substrate **110**. The scan line SL substantially extends along the direction X, and the data line DL substantially extends along the direction Y. A normal direction of the substrate **110** is a direction Z. The direction X, the direction Y, and the direction Z are different from each other, and the direction X, the direction Y, and the direction Z are perpendicular to each other. The source SD (or SD1) of the transistor **120** (or **121**) can be electrically connected to the data line DL, and the gate GE (or GE1) of the transistor **120** (or **121**) can be electrically connected to the scan line SL. Therefore, the transistor **120** (or **121**) can be electrically connected to the data line DL and the scan line SL. The source SD (or SD1), the drains SD' (or SD1') and the data line DL are in the same layer. In addition, in the top view of this embodiment, a portion of the data line DL extends into the drain contact hole **130**, and a width of the data line DL extending into the drain contact hole **130** is W2. A width of another portion of the data line DL disposed outside the drain contact hole **130** is W3, and the width W3 is, for example, less than or equal to W2, but not limited thereto. In some

embodiments, 2 times the width W3 may be greater than the width W2. In some embodiments, 1.7 times the width W3 may be greater than the width W2. In some embodiments, 1.3 times the width W3 may be greater than the width W2. In this embodiment, the width W2 is, for example, a maximum width of the data line DL inside the drain contact hole **130** from one side to the other side of the data line DL measured along the direction X. The width W3 is, for example, a maximum width of the data line DL outside the drain contact hole **130** from one side to the other side of the data line DL measured along the direction X.

(27) Referring to FIG. **1A** and FIG. **1B** together, in this embodiment, the electronic device **100** further includes the buffer layer **140**, a shielding layer **141**, insulation layers **142** and **142'**, an insulation layer **143**, a dielectric layer **150**, transfer pads **160** and **160'**, an insulation layer **170**, a pixel electrode (not shown), a common electrode (not shown) and an intermediate insulation layer (not shown) between the pixel electrode and the common electrode. Among them, the buffer layer **140**, the insulation layers **142** and **142'**, the insulation layer **143**, the dielectric layer **150** and the insulation layer **170** can be single-layer or multi-layer structures, and can include, for example, organic materials, inorganic materials or a combination of the above, but not limited thereto. In this embodiment, the material of the shielding layer **141** can be, for example, a metal material or other light shielding materials. In some embodiments, the electronic device may not be provided with the shielding layer (not shown). In some embodiments, the pixel electrode (not shown) and the data line DL are in the different layers.

(28) In this embodiment, the shielding layer **141** is disposed on the substrate **110**; the buffer layer **140** is disposed on the shielding layer **141**; and the shielding layer **141** and the buffer layer **140** are disposed between the transistors **120** and **121** and the substrate **110**. The insulation layer **142** (or **142'**) is disposed between the gate GE (or GE1) and the gate insulation layer GI, and the insulation layer **142** (or **142'**) is disposed corresponding to the gate GE (or GE1).

(29) In this embodiment, the dielectric layer **150** is disposed between the drains SD' and SD1' and the gate insulation layer GI to cover the gates GE and GE1 and the gate insulation layer GI. The dielectric layer **150** has an opening **151**. The opening **151** communicates with the opening GIa to form the drain contact hole **130** and expose portions of the semiconductors SE and SE1 and a portion of the buffer layer **140**. Therefore, in this embodiment, in the extending direction of the data line DL (i.e., the direction Y), the transistor **120** and the transistor **121** (or the transistor **122** and the transistor **123**, or the transistor **124** and the transistor **125**) are adjacent to each other. The drain contact hole **130** of the electronic device **100** is disposed between the two adjacent transistors **120** and **121** (or the transistors **122** and **123**, or the transistors **124** and **125**).

(30) In this embodiment, the source SD (or SD1) and the drain SD' (or SD1') can be respectively disposed on the dielectric layer **150**. The source SD of the transistor **120** and the source SD1 of the transistor **121** can also be disposed in the drain contact hole **130**, so that the source SD and the source SD1 can respectively contact and be electrically connected to semiconductor SE and semiconductor SE1 in the drain contact hole **130**. In addition, the drain SD' of the transistor **120** and the drain SD1' of the transistor **121** can also be disposed in the drain contact hole **130**, so that the drain SD' and the drain SD1' can respectively contact and be electrically connected to the semiconductor SE and the semiconductor SE1 in the drain contact hole **130**. That is to say, the source SD of the transistor **120** and the source SD1 of the transistor **121** can be electrically connected to the semiconductor SE and the semiconductor SE1 through the drain contact hole **130**, respectively. Moreover, the drain SD' of the transistor **120** and the drain SD1' of the transistor **121** can also be electrically connected to the semiconductor SE and the semiconductor SE1 through the drain contact hole **130**, respectively. That is, the source SD and the drain SD' of the transistor **120** can share the same drain contact hole **130** with the source SD1 and the drain SD1' of the transistor **121** adjacent in the direction Y.

(31) In this embodiment, the drain contact hole of the electronic device is defined as a contact hole for allowing the drain of the transistor to contact and be electrically connected to the

semiconductor. Therefore, even if there are other electrodes (e.g., the source) in the contact hole that can contact and be electrically connected to the semiconductor through the contact hole, the contact hole is still defined as the drain contact hole.

(32) In addition, similar to the case of the transistor **120** and the transistor **121**, a source SD2 of the transistor **122** and a source SD3 of the transistor **123** can also be electrically connected to a semiconductor SE2 and a semiconductor SE3 respectively through the drain contact hole **130**; a drain SD2' of the transistor **122** and a drain SD3' of the transistor **123** can also be electrically connected to the semiconductor SE2 and the semiconductor SE3 respectively through the drain contact hole **130**; a source SD4 of the transistor **124** and a source SD5 of the transistor **125** can also be electrically connected to a semiconductor SE4 and a semiconductor SE5 respectively through the drain contact hole **130**; and a drain SD4' of the transistor **124** and a drain SD5' of the transistor **125** can also be electrically connected to the semiconductor SE4 and the semiconductor SE5 respectively through the drain contact hole **130**. In other words, the source SD and the drain SD' of the transistor **120** can also share the same drain contact hole **130** with the source SD2 and the drain SD2' of the transistor **122** adjacent in the direction X. Accordingly, the source SD and the drain SD' of the transistor **120** in the sub-pixel P0, the source SD1 and the drain SD1' of the transistor **121** in the sub-pixel P1, the source SD2 and the drain SD2' of the transistor **122** in the sub-pixel P2, the source SD3 and the drain SD3' of the transistor **123** in the sub-pixel P3, the source SD4 and the drain SD4' of the transistor **124** in the sub-pixel P4, and the source SD5 and the drain SD5' of the transistor **125** in the sub-pixel P5 can all share the same drain contact hole **130** to be electrically connected to the corresponding semiconductors SE, SE1, SE2, SE3, SE4 and SE5. The semiconductor SE and the semiconductor SE1 are arranged along the direction Y, the semiconductor SE2 and the semiconductor SE3 are arranged along the direction Y, and the semiconductor SE4 and the semiconductor SE5 are also arranged along the direction Y.

(33) Therefore, in this embodiment, the drains SD', SD1', SD2', SD3', SD4' and SD5' and the sources SD, SD1, SD2, SD3, SD4 and SD5 of at least two transistors **120**, **121**, **122**, **123**, **124** and **125** among the transistors **120**, **121**, **122**, **123**, **124** and **125** can share one drain contact hole **130** among the drain contact holes (not shown). Accordingly, a number of the drain contact holes **130** can be less than a number of the drains SD', SD1', SD2', SD3', SD4' and SD5' (or a number of the sources SD, SD1, SD2, SD3, SD4 and SD5) to prevent the electronic device (e.g., a high-resolution display device, but not limited thereto) from cracking in the subsequent formation of stacked layers due to steep topography in the contact holes caused by the excessive number of the contact holes. In this way, the layout of metal lines and thin film transistor units in the display panel can be improved.

(34) In this embodiment, the insulation layer **143** is disposed on the transistors **120** and **121** to cover the sources SD and SD1, the drains SD' and SD1' and the dielectric layer **150**. The insulation layer **143** is disposed between the transfer pads **160** and **160'** and the drains SD' and SD1'. The insulation layer **143** can also be disposed in the drain contact hole **130** to cover the drains SD' and SD1' and the portion of the buffer layer **140** exposed by the opening GIa of the gate insulation layer GI. In addition, the insulation layer **143** has a first opening **1431** and a second opening **1432** to respectively expose a portion of the drain SD' and a portion of the drain SD1'.

(35) In this embodiment, the transfer pad **160** and the transfer pad **160'** are arranged corresponding to the drain SD' and the drain SD1', respectively. Specifically, the transfer pads **160** and **160'** are disposed on the insulation layer **143** and in the drain contact hole **130**. The transfer pad **160** can also be disposed in the first opening **1431** of the insulation layer **143**, so that the transfer pad **160** can be electrically connected to the drain SD' through the first opening **1431** of the insulation layer **143**. The transfer pad **160'** can also be disposed in the second opening **1432** of the insulation layer **143**, so that the transfer pad **160'** can be electrically connected to the drain SD1' through the second opening **1432** of the insulation layer **143**. In the drain contact hole **130**, the transfer pad **160** and the transfer pad **160'** are separated from each other to expose a portion of the insulation layer **143**. In

this embodiment, the material of the transfer pads **160** and **160'** may also include a metal material or a transparent conductive material. The metal material may include molybdenum, aluminum, titanium, copper, other suitable metals, or alloys or combinations of the materials above, but not limited thereto. The transparent conductive material may include indium tin oxide or indium zinc oxide, but not limited thereto.

(36) In this embodiment, the insulation layer **170** is disposed on the transfer pads **160** and **160'** and in the drain contact hole **130**. In the drain contact hole **130**, the insulation layer **170** can cover the transfer pads **160** and **160'** and a portion of the insulation layer **143** exposed by the transfer pads **160** and **160'**. The insulation layer **170** has a third opening **171** and a fourth opening **172** to respectively expose a portion of the transfer pad **160** and a portion of the transfer pad **160'**. In addition, in the top view of the electronic device **100** (as shown in FIG. 1A), the third opening **171** of the insulation layer **170** and the drain contact hole **130** are separated from each other and have a distance D2, and the fourth opening **172** of the insulation layer **170** and the drain contact hole **130** are also separated from each other and has a distance D3. In detail, in the top view of this embodiment (as shown in FIG. 1A), the distance D2 is, for example, a maximum distance between one side **171a** of the third opening **171** and one side **130a** of the drain contact hole **130** measured along the direction Y, and the distance D3 is, for example, a maximum distance between one side **172b** of the fourth opening **172** and the other side **130b** of the drain contact hole **130** measured along the direction Y. Extending directions of the side **171a** and the side **172b** are substantially parallel to the direction X (i.e., parallel to the extending direction of the scan line SL), and the side **171a** and the side **172b** are closest to each other. The distance between two openings/holes means the distance from a bottom of one opening to a bottom of another opening.

(37) Further, in this embodiment, an orthographic projection of the third opening **171** (or the fourth opening **172**) of the insulation layer **170** in the normal direction of the substrate **110** (i.e., the direction Z) does not overlap with an orthographic projection of the drain contact hole **130** in the normal direction of the substrate **110**. Specifically, the third opening **171** of the insulation layer **170** has a sidewall **171a** adjacent to the drain contact hole **130**; the fourth opening **172** of the insulation layer **170** has a sidewall **172b** adjacent to the drain contact hole **130**, and the drain contact hole **130** has a sidewall **130a** adjacent to the third opening **171** and a sidewall **130b** adjacent to the fourth opening **172**. An orthographic projection of the sidewall **171a** of the third opening **171** in the normal direction of the substrate **110** (i.e., direction Z) does not overlap with an orthographic projection of the sidewall **130a** of the drain contact hole **130** in the normal direction of the substrate **110**, and an orthographic projection of the sidewall **172b** of the fourth opening **172** in the normal direction of the substrate **110** does not overlap with an orthographic projection of the sidewall **130b** of the drain contact hole **130** in the normal direction of the substrate **110**.

(38) In this embodiment, the third opening **171** (or the fourth opening **172**) of the insulation layer **170** does not overlap with the drain contact hole **130** and the third opening **171** (or the fourth opening **172**) of the insulation layer **170**, is separated from the drain contact hole **130** and has the distance D2 (or the distance D3). The orthographic projection of the sidewall **171a** of the third opening **171** (or the sidewall **172b** of the fourth opening **172**) in the direction Z does not overlap with the orthographic projection of the sidewall **130a** (or the sidewall **130b**) of the drain contact hole **130** in the direction Z. Therefore, a relatively flat topography can be provided to prevent the intermediate insulation layer (not shown) subsequently disposed on the insulation layer **170** between the pixel electrode and the common electrode from cracking. Accordingly, the risk of short circuit caused by the pixel electrode in contact with the common electrode due to cracking of the intermediate insulation layer can be reduced.

(39) In the top view of the electronic device **100** of this embodiment, although the third opening **171** (or the fourth opening **172**) of the insulation layer **170** and the drain contact hole **130** are separated from each other, the disclosure is not limited thereto. In some embodiments, the third opening **171** (or the fourth opening **172**) of the insulation layer **170** may also partially overlap with

the drain contact hole **130** (as shown in FIG. 5A and FIG. 5B), as long as the orthographic projection of the sidewall **171a** of the third opening **171** (or the sidewall **172b** of the fourth opening **172**) in the direction Z does not overlap with the orthographic projection of the sidewall **130a** (or the sidewall **130b**) of the drain contact holes **130** in the direction Z.

(40) In the top view of the electronic device **100** of this embodiment, the source SD and the drain SD' of the transistor **120** can share the same drain contact hole **130** with the source SD1 and the drain SD1' of the transistor **121** adjacent in the direction Y, and the source SD and the drain SD' of the transistor **120** can also share the same drain contact hole **130** with the source SD2 and the drain SD2' of the transistor **122** adjacent in the direction X. However, the disclosure does not limit a coverage of the drain contact holes, as long as the number of the drain contact holes in the electronic device is less than the number of the drains. That is to say, in some embodiments, the coverage of the drain contact hole may only be shared the source and the drain of two adjacent transistors in the direction Y, as shown in FIG. 3 and FIG. 4. In some embodiments, the coverage of the drain contact hole may only be shared by the drains of two adjacent transistors in the direction Y, as shown in FIG. 2.

(41) In addition, in the electronic device **100** of this embodiment, in the direction Y, the pixel electrodes (not shown) in any two adjacent sub-pixels P0 and P1 (or the sub-pixels P2 and P3, or the sub-pixels P4 and P5) are disposed in a back-to-back manner, for example. The so-called "back-to-back manner" in the disclosure refers to a configuration in which the source and the drain of the transistors of two adjacent sub-pixels are shared in the direction Y, but not limited thereto.

(42) In short, in the electronic device **100** of the present embodiment of the disclosure, by disposing the drain contact hole **130** between two adjacent transistors **120** and **121** (or the transistors **122** and **123**, or the transistors **124** and **125**), the drains SD' and SD1' (or the drains SD2' and SD3', or the drains SD4' and SD5') of the two adjacent transistors **120** and **121** (or the transistors **122** and **123**, or the transistors **124** and **125**) can be electrically connected to the corresponding semiconductors SE and SE1 (or the semiconductors SE2 and SE3, or the semiconductors SE4 and SE5) together through the same drain contact hole **130**. Accordingly, the number of the drain contact holes **130** can be less than the number of the drains SD', SD1', SD2', SD3', SD4' and SD5'. In this way, the electronic device **100** (e.g., a high-resolution display device, but not limited thereto) may be prevented from cracking in the subsequent formation of stacked layers due to steep topography in the contact holes caused by the excessive number of the contact holes. In addition, the orthographic projection of the sidewall **171a** (or the sidewall **172b**) of the third opening **171** (or the fourth opening **172**) adjacent to the drain contact hole **130** in the normal direction of the substrate **110** (the direction Z) does not overlap with the orthographic projection of the sidewall **130a** (or the sidewall **130b**) of the drain contact hole **130** adjacent to the third opening **171** (or the fourth opening **172**) in the normal direction of the substrate **110**. Therefore, a relatively flat topography can be provided to prevent the intermediate insulation layer subsequently disposed on the insulation layer **170** between the pixel electrode and the common electrode from cracking. Accordingly, the risk of short circuit caused by the pixel electrode in contact with the common electrode due to cracking of the intermediate insulation layer can be avoided. In this way, the electronic device **100** of the embodiment of the disclosure has better reliability or better display quality.

(43) Other embodiments will be provided below for description. It is noted herein that the reference numerals and part of the descriptions of the above embodiment apply to the following embodiments, where the same numerals are used to represent the same or similar components, and descriptions of the same technical contents are omitted. Reference may be made to the above embodiment for the descriptions of the omitted contents, which will not be repeated in the following embodiments.

(44) FIG. 2 is a schematic top view of an electronic device according to another embodiment of the disclosure. For clarity of the drawings and convenience of description, FIG. 2 omits several

elements in the electronic device. For example, the scan line, the transfer pad, the first opening, the second opening, the third opening and the fourth opening are omitted, but not limited thereto. Referring to FIG. 1A and FIG. 2 together, an electronic device **100a** of this embodiment is substantially similar to the electronic device **100** of FIG. 1A, so the same and similar components in the two embodiments will not be repeatedly described herein. The electronic device **100a** of this embodiment is different from the electronic device **100** mainly in that the electronic device **100a** of this embodiment includes drain contact holes **131**, **132** and **133** and source contact holes **181**, **182** and **183**, and the drain contact hole **131**, the drain contact hole **132** and the drain contact hole **133** are separated from each other and not connected.

(45) Specifically, referring to FIG. 2, in the top view of the electronic device **100a** of this embodiment, the source SD of the transistor **120** shares the source contact hole **181** with the source SD1 of the transistor **121** adjacent in the direction Y; the drain SD' of the transistor **120** shares the drain contact hole **131** with the drain SD1' of the transistor **121** adjacent in the direction Y; and the source contact hole **181** and the drain contact hole **131** are separated from each other. The source SD2 of the transistor **122** shares the source contact hole **182** with the source SD3 of the transistor **123** adjacent in the direction Y; The drain SD2' of the transistor **122** shares the drain contact hole **132** with the drain SD3' of the transistor **123** adjacent in the direction Y; and the source contact hole **182** and the drain contact hole **132** are separated from each other. The source SD4 of the transistor **124** shares the source contact hole **183** with the source SD5 of the transistor **125** adjacent in the direction Y; the drain SD4' of the transistor **124** shares the drain contact hole **133** with the drain SD5' of the transistor **125** adjacent in the direction Y; and the source contact hole **183** and the drain contact hole **133** are separated from each other.

(46) In this embodiment, at least two of the plurality of transistors **120** and **121** (or the transistors **122** and **123**, or the transistors **124** and **125**) share one of the plurality of drain contact holes **131** (or the drain contact hole **132**, or the drain contact hole **133**) with the drain electrodes SD' and SD1' (or the drains SD2' and SD3', or the drains SD4' and SD5'), in details, the drains SD' and SD1' (or the drains SD2' and SD3', or the drains SD4' and SD5') of at least two transistors **120** and **121** (or the transistors **122** and **123**, or the transistors **124** and **125**) among the transistors **120**, **121**, **122**, **123**, **124** and **125** can share one drain contact hole **131** (or the drain contact hole **132**, or the drain contact hole **133**) among the drain contact holes **131**, **132** and **133**. Therefore, the drains SD' and SD1' (or the drains SD2' and SD3', or the drains SD4' and SD5') can be electrically connected to the semiconductors SE and SE1 (or the semiconductors SE2 and SE3, or the semiconductors SE4 and SE5) through the drain contact hole **131** (or the drain contact hole **132**, or the drain contact hole **133**). Here, the number of the drain contact holes **131**, **132** and **133** can be less than the number of the drains SD', SD1', SD2', SD3', SD4' and SD5'. The number of the source contact holes **181**, **182** and **183** can also be less than the number of the sources SD, SD1, SD2, SD3, SD4 and SD5.

(47) FIG. 3 is a schematic top view of an electronic device according to another embodiment of the disclosure. For clarity of the drawings and convenience of description, FIG. 3 omits several elements in the electronic device. For example, the scan line, the transfer pad, the first opening, the second opening, the third opening and the fourth opening are omitted, but not limited thereto. Referring to FIG. 1A and FIG. 3 together, an electronic device **100b** of this embodiment is substantially similar to the electronic device **100** of FIG. 1A, so the same and similar components in the two embodiments will not be repeatedly described herein. The electronic device **100b** of this embodiment is different from the electronic device **100** mainly in that the electronic device **100b** of this embodiment includes drain contact holes **131b**, **132b** and **133b**, and the drain contact hole **131b**, the drain contact hole **132b** and the drain contact hole **133b** are separated from each other and not connected.

(48) Specifically, referring to FIG. 3, in the top view of the electronic device **100b** of this embodiment, the source SD and the drain SD' of the transistor **120** can share the drain contact hole

131b with the source **SD1** and the drain **SD1'** of the transistor **121** adjacent in the direction **Y**. The source **SD2** and drain **SD2'** of the transistor **122** can share the drain contact hole **132b** with the source **SD3** and the drain **SD3'** of the transistor **123** adjacent in the direction **Y**. The source **SD4** and the drain **SD4'** of the transistor **124** can share the drain contact hole **133b** with the source **SD5** and the drain **SD5'** of the transistor **125** adjacent in the direction **Y**.

(49) In this embodiment, at least two of the plurality of transistors **120** and **121** (or the transistors **122** and **123**, or the transistors **124** and **125**) share one of the plurality of drain contact holes **131b** (or the drain contact hole **132b**, or the drain contact hole **133b**) with the drain electrodes **SD'** and **SD1'** (or the drains **SD2'** and **SD3'**, or the drains **SD4'** and **SD5'**) and the source electrodes **SD** and **SD1** (or the sources **SD2** and **SD3**, or the sources **SD4** and **SD5**), in details, the drains **SD'** and **SD1'** (or the drains **SD2'** and **SD3'**, or the drains **SD4'** and **SD5'**) and the sources **SD** and **SD1** (or the sources **SD2** and **SD3**, or the sources **SD4** and **SD5**) of at least two transistors **120** and **121** (or the transistors **122** and **123**, or the transistors **124** and **125**) among the transistors **120**, **121**, **122**, **123**, **124** and **125** can share one drain contact hole **131b** (or the drain contact hole **132b**, or the drain contact hole **133b**) among the drain contact holes **131b**, **132b** and **133b**. Therefore, the drains **SD'** and **SD1'** (or the drains **SD2'** and **SD3'**, or the drains **SD4'** and **SD5'**) can be electrically connected to the semiconductors **SE** and **SE1** (or the semiconductors **SE2** and **SE3**, or the semiconductors **SE4** and **SE5**) through the drain contact hole **131b** (or the drain contact hole **132b**, or the drain contact hole **133b**). Here, the number of the drain contact holes **131b**, **132b** and **133b** can be less than the number of the drains **SD'**, **SD1'**, **SD2'**, **SD3'**, **SD4'** and **SD5'**. The number of the drain contact holes **131b**, **132b** and **133b** can also be less than the number of the sources **SD**, **SD1**, **SD2**, **SD3**, **SD4** and **SD5**.

(50) In addition, in the top view of the electronic device **100b** of this embodiment, although outlines of the drain contact holes **131b**, **132b** and **133b** are quadrilateral, the disclosure does not limit the outlines of the drain contact holes. That is to say, in some embodiments, the contour of the drain contact hole may also be, for example, a C-shape (as shown in FIG. 4) or other suitable contours, as long as the sources and the drains of two transistors adjacent in the direction **Y** can share one drain contact hole to be electrically connected to the corresponding semiconductors.

(51) FIG. 4 is a schematic top view of an electronic device according to another embodiment of the disclosure. Referring to FIG. 3 and FIG. 4 together, an electronic device **100c** of this embodiment is substantially similar to the electronic device **100b** of FIG. 3, so the same and similar components in the two embodiments will not be repeatedly described herein. The electronic device **100c** of this embodiment is different from the electronic device **100b** mainly in that, in the top view of the electronic device **100c** of this embodiment, outlines of drain contact holes **131c**, **132c** and **133c** are C-shaped.

(52) FIG. 5A is a schematic top view of an electronic device according to another embodiment of the disclosure. FIG. 5B is a schematic cross-sectional view of the electronic device of FIG. 5A along section line B-B'. Referring to FIGS. 1A to 1B and FIGS. 5A to 5B together, an electronic device **100d** of this embodiment is substantially similar to the electronic device **100** of FIGS. 1A to 1B, so the same and similar components in the two embodiments will not be repeatedly described herein. The electronic device **100d** of this embodiment is different from the electronic device **100** mainly in that, in the top view of the electronic device **100d** of this embodiment, the third opening **171d** (or a fourth opening **172d**) of an insulation layer **170d** in the normal direction of the substrate **110** (i.e., the direction **Z**) partially overlaps with the drain contact hole **130** in the normal direction of the substrate **110**, and the fourth opening **172d** of an insulation layer **170d** in the normal direction of the substrate **110** partially overlaps with the drain contact hole **130** in the normal direction of the substrate **110**.

(53) Specifically, referring to FIG. 5A and FIG. 5B, in this embodiment, the third opening **171d** of the insulation layer **170d** has a sidewall **171a'** adjacent to the drain contact hole **130**; the fourth opening **172d** of the insulation layer **170d** has a sidewall **172b'** adjacent to the drain contact hole

130; and the drain contact hole **130** has the sidewall **130a** adjacent to the third opening **171d** and the sidewall **130b** adjacent to the fourth opening **172d**. An orthographic projection of the sidewall **171a'** of the third opening **171d** in the normal direction of the substrate **110** (i.e., direction Z) does not overlap with the orthographic projection of the sidewall **130a** of the drain contact hole **130** in the normal direction of the substrate **110**, and an orthographic projection of the sidewall **172b'** of the fourth opening **172d** in the normal direction of the substrate **110** does not overlap with the orthographic projection of the sidewall **130b** of the drain contact hole **130** in the normal direction of the substrate **110**. A distance D4 is provided between the sidewall **171a'** of the third opening **171d** and the sidewall **130a** of the drain contact hole **130**, and a distance D5 is provided between the sidewall **172b'** of the fourth opening **172d** and the sidewall **130b** of the drain contact hole **130**. In this embodiment, the distance D4 is, for example, a maximum between the sidewall **171a'** of the third opening **171d** and the sidewall **130a** of the drain contact hole **130** measured along the direction Y. The distance D5 is, for example, a maximum distance between the sidewall **172b'** of the fourth opening **172d** and the sidewall **130b** of the drain contact hole **130** measured along the direction Y.

(54) In this embodiment, the orthographic projection of the sidewall **171a'** of the third opening **171d** (or the sidewall **172b'** of the fourth opening **172d**) in the normal direction of the substrate **110** does not overlap with the orthographic projection of the sidewall **130a** (or the sidewall **130b**) of the drain contact hole **130** in the normal direction of the substrate **110**. Therefore, a relatively flat topography can be provided to prevent the intermediate insulation layer (not shown) subsequently disposed on the insulation layer **170d** between the pixel electrode and the common electrode from cracking. Accordingly, the risk of short circuit caused by the pixel electrode in contact with the common electrode due to cracking of the intermediate insulation layer can be avoided. Conversely, when the orthographic projection of the sidewall of the third opening adjacent the drain contact hole (or the sidewall of the fourth opening adjacent to the drain contact hole) in the normal direction of the substrate **110** overlaps with an orthographic projection (not shown) of the drain contact hole adjacent to the sidewall of the third opening (or adjacent to the sidewall of the fourth opening) in the normal direction of the substrate **110**, an invert taper topography may appear. Therefore, the intermediate insulation layer (not shown) subsequently disposed on the insulation layer and located between the pixel electrode and the common electrode may be cracked, thereby causing the pixel electrode to contact the common electrode and causing a short circuit.

(55) FIG. 6 is a schematic top view of an electronic device according to another embodiment of the disclosure. For clarity of the drawings and convenience of description, FIG. 6 omits several elements in the electronic device. For example, the scan line, the transfer pad, the first opening, the second opening, the third opening and the fourth opening are omitted, but not limited thereto. Referring to FIG. 1A and FIG. 6 together, an electronic device **100e** of this embodiment is substantially similar to the electronic device **100** of FIG. 1A, so the same and similar components in the two embodiments will not be repeatedly described herein. The electronic device **100e** of this embodiment is different from the electronic device **100** mainly in that the electronic device **100e** of this embodiment includes drain contact holes **134** and **135**, and the drain contact hole **134** and the drain contact hole **135** are separated from each other and not connected.

(56) Specifically, referring to FIG. 6, in the top view of the electronic device **100e** of this embodiment, among the transistor **120**, the transistor **122** and the transistor **124** arranged adjacent to each other in the direction X, the source SD and the drain SD' of the transistor **120**, the source SD2 and the drain SD2' of the transistor **122** and the source SD4 and the drain SD4' of the transistor **124** share the same drain contact hole **134**. Further, among the transistor **121**, the transistor **123** and the transistor **125** arranged adjacent to each other in the direction X, the source SD1 and the drain SD1' of the transistor **121**, the source SD3 and the drain SD3' of the transistor **123** and the source SD5 and the drain SD5' of the transistor **125** share the same drain contact hole **135**.

(57) In summary, in the electronic device according to the embodiments of the disclosure, by disposing the drain contact hole between two adjacent transistors, the drains of the two adjacent transistors can be electrically connected to the corresponding semiconductors together through the same drain contact hole. Accordingly, the number of the drain contact holes can be less than the number of the drains. In this way, the electronic device (e.g., a high-resolution display device, but not limited thereto) may be prevented from cracking in the subsequent formation of stacked layers due to steep topography in the contact holes caused by the excessive number of the contact holes. In this way, the layout of metal lines and thin film transistor units in the display panel can be improved. In addition, the orthographic projection of the sidewall of the third opening (or the fourth opening) adjacent to the drain contact hole in the normal direction of the substrate (the direction Z) does not overlap with the orthographic projection of the sidewall of the drain contact hole adjacent to the third opening (or the fourth opening) in the normal direction of the substrate. Therefore, a relatively flat topography can be provided to prevent the intermediate insulation layer subsequently disposed on the insulation layer between the pixel electrode and the common electrode from cracking. Accordingly, the risk of short circuit caused by the pixel electrode in contact with the common electrode due to cracking of the intermediate insulation layer can be avoided. In this way, the electronic device of the embodiment of the disclosure has better reliability or better display quality.

(58) Finally, it should be noted that the foregoing embodiments are merely used for describing the technical solutions of the disclosure, but are not intended to limit the disclosure. Although the disclosure has been described in detail with reference to the foregoing embodiments, a person of ordinary skill in the art should understand that modifications may still be made to the technical solutions in the foregoing embodiments, or equivalent replacements may be made to part or all of the technical features; and these modifications or replacements will not cause the essence of corresponding technical solutions to depart from the scope of the technical solutions in the embodiments of the disclosure.

Claims

1. An electronic device, comprising: a substrate; a first conductive wire configured to transmit a first signal and disposed on the substrate and extending along a first direction; a plurality of semiconductors disposed on the substrate and overlapped with the first conductive wire; an insulation layer disposed on the substrate and having a plurality of holes; and a plurality of conductive elements disposed on the substrate and overlapped with the plurality of semiconductors respectively; wherein, in a top view of the electronic device, each one of the plurality of holes overlaps with at least one of the plurality of semiconductors, and a number of the plurality of holes is less than a number of the plurality of conductive elements, wherein the first conductive wire is a data line, and the first signal is a data signal.
2. The electronic device of claim 1, wherein the plurality of conductive elements and the first conductive wire are in different layers.
3. The electronic device of claim 2, wherein the plurality of conductive elements are electrodes.
4. The electronic device of claim 3, wherein the electrodes comprises pixel electrodes.
5. The electronic device of claim 1, wherein the plurality of semiconductors comprises low temperature polysilicon.
6. The electronic device of claim 1, further comprising: a second conductive wire, wherein the second conductive wire overlaps with one of the plurality of semiconductors.
7. The electronic device of claim 6, wherein the first conductive wire and the second conductive wire extend in different directions.
8. The electronic device of claim 6, wherein the second conductive wire transmits a second signal different from the first signal.

9. The electronic device of claim 8, wherein the second signal is a scan signal.

10. The electronic device of claim 6, wherein the plurality of conductive elements overlap with the second conductive wire.

11. An electronic device, comprising: a substrate; a first conductive wire configured to transmit a first signal and disposed on the substrate and extending along a first direction; a plurality of semiconductors disposed on the substrate and overlapped with the first conductive wire; an insulation layer disposed on the substrate and having a plurality of holes; and a plurality of conductive elements disposed on the substrate and overlapped with the plurality of semiconductors respectively; and a second conductive wire, wherein the second conductive wire overlaps with one of the plurality of semiconductors; **P1** wherein, in a top view of the electronic device, each one of the plurality of holes overlaps with at least one of the plurality of semiconductors, and a number of the plurality of holes is less than a number of the plurality of conductive elements, and the first conductive wire and the second conductive wire extend perpendicularly.

12. An electronic device, comprising: a substrate; a first conductive wire configured to transmit a first signal and disposed on the substrate and extending along a first direction; a plurality of semiconductors disposed on the substrate and overlapped with the first conductive wire; an insulation layer disposed on the substrate and having a plurality of holes; and a plurality of conductive elements disposed on the substrate and overlapped with the plurality of semiconductors respectively; and a second conductive wire, wherein the second conductive wire overlaps with one of the plurality of semiconductors; wherein, in a top view of the electronic device, each one of the plurality of holes overlaps with at least one of the plurality of semiconductors, and a number of the plurality of holes is less than a number of the plurality of conductive elements, and wherein the second conductive wire is a scan line, the second conductive wire transmits a second signal different from the first signal, and the second signal is a scan signal.
