

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                      |
|----------------------|----------------------|
| United States Patent | 12409548             |
| Kind Code            | B2                   |
| Date of Patent       | September 09, 2025   |
| Inventor(s)          | Lee; Seung Ho et al. |

---

### Gripper for a door and a control method thereof

---

#### Abstract

A gripper mounted on a robot is used in a smart factory to pick a door loaded on a pallet. The gripper includes: a frame mounted on a tool changer of the robot; a picking unit mounted on a front of the frame and applying pressure to and regulating each of upper and lower points of an opening formed in an inner panel of the door through a bundle pin locator; and a pressure control valve adjusting the pressure of guide air cylinders. The gripper further includes: a side clamping unit mounted on the frame and holding a side point of the opening by a fixing locator and a clamper operating with a driving force of a clamping cylinder; and a control unit adjusting a moving distance of the robot based on a distance difference between the side clamping unit and the inner panel.

---

**Inventors:** Lee; Seung Ho (Incheon, KR), Kim; Beomjun (Anyang-si, KR), Lee; Seongsul (Gunpo-si, KR), Lee; Moonhee (Hwaseong-si, KR)

**Applicant:** HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

**Family ID:** 93804180

**Assignee:** HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

**Appl. No.:** 18/511310

**Filed:** November 16, 2023

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20240416511 A1   | Dec. 19, 2024    |

#### Foreign Application Priority Data

|    |                 |               |
|----|-----------------|---------------|
| KR | 10-2023-0076734 | Jun. 15, 2023 |
|----|-----------------|---------------|

---

## Publication Classification

**Int. Cl.:** B25J9/16 (20060101); B25J11/00 (20060101); B25J13/08 (20060101); B25J15/00 (20060101); B25J19/02 (20060101)

**U.S. Cl.:**

**CPC** B25J9/1612 (20130101); B25J9/1633 (20130101); B25J9/1664 (20130101); B25J13/088 (20130101); B25J15/0061 (20130101); B25J19/022 (20130101);

## Field of Classification Search

**CPC:** B25J (9/1612); B25J (9/1633); B25J (9/1664); B25J (13/088); B25J (15/0061); B25J (19/022); B25J (15/0014); B25J (9/161); B25J (9/1679)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl.  | CPC          |
|--------------|-------------|---------------|-----------|--------------|
| 4627158      | 12/1985     | Mitoh         | 29/771    | B23P 19/047  |
| 4654949      | 12/1986     | Pryor         | 29/709    | B25J 9/1697  |
| 4757608      | 12/1987     | Ochi          | 29/430    | B62D 65/06   |
| 4961257      | 12/1989     | Sakamoto      | 29/823    | B62D 65/06   |
| 5602967      | 12/1996     | Pryor         | 700/254   | G01B 11/00   |
| 5608847      | 12/1996     | Pryor         | 901/31    | A01B 69/008  |
| 6112470      | 12/1999     | Hashimoto     | 49/502    | B60J 5/0405  |
| 6167607      | 12/2000     | Pryor         | 29/702    | B25J 19/021  |
| 6301763      | 12/2000     | Pryor         | 29/702    | B23P 19/10   |
| 6314631      | 12/2000     | Pryor         | 29/407.04 | B62D 1/28    |
| 6317953      | 12/2000     | Pryor         | 29/721    | B23P 19/10   |
| 6421893      | 12/2001     | Katayama      | 29/796    | B62D 65/06   |
| 6711800      | 12/2003     | Savoy         | 29/434    | B62D 65/06   |
| 7008166      | 12/2005     | Grimes        | 254/114   | B66C 23/48   |
| 8256811      | 12/2011     | Yeum          | 269/905   | B25J 15/0052 |
| 8534983      | 12/2012     | Schoenfeld    | 414/739   | B25J 15/0206 |
| 10099737     | 12/2017     | Macri         | N/A       | B25J 11/005  |
| 10155555     | 12/2017     | Lee           | N/A       | B62D 65/06   |
| 10486759     | 12/2018     | Hahn          | N/A       | B25J 9/0084  |
| 10526032     | 12/2019     | Macri         | N/A       | B62D 65/06   |
| 10766551     | 12/2019     | Lee           | N/A       | B62D 65/06   |
| 2009/0001763 | 12/2008     | Emerich       | 296/202   | B62D 65/06   |
| 2009/0317223 | 12/2008     | Schoenfeld    | 414/800   | E02F 3/4135  |
| 2011/0022228 | 12/2010     | Mikurube      | 700/248   | B62D 65/06   |
| 2011/0133501 | 12/2010     | Yeum          | 294/81.2  | B25J 15/0061 |
| 2012/0056440 | 12/2011     | Yeum          | 294/81.2  | B25J 15/0061 |
| 2014/0165360 | 12/2013     | Mangiarino    | 29/407.1  | B62D 65/06   |
| 2015/0082608 | 12/2014     | Lee           | 29/700    | B62D 65/06   |
| 2017/0349228 | 12/2016     | Hahn          | N/A       | B25J 9/0084  |
| 2019/0071142 | 12/2018     | Lee           | N/A       | B62D 65/06   |

## FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| 20110063144 | 12/2010          | KR      | N/A |
| 20110124921 | 12/2010          | KR      | N/A |
| 102097948   | 12/2019          | KR      | N/A |

---

*Primary Examiner:* Figueroa; Jaime

*Attorney, Agent or Firm:* Lempia Summerfield Katz LLC

---

## Background/Summary

### CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to and the benefit of Korean Patent Application No. 10-2023-0076734, filed on Jun. 15, 2023, the entire contents of which are incorporated herein by reference.

### BACKGROUND

(a) Field

(2) The present disclosure relates to a gripper for a door and a control method thereof, and more specifically, to a gripper for a door mounted on a robot and extracting a door panel loaded on a pallet, and its control method.

(b) Description of the Related Art

(3) Generally, in order to automate a door mounting process in a smart factory, a pallet supplying a door panel must be placed in a designated rack and a robot must automatically pick and extract the door panel. In order to prevent a line interruption (stop) in such an automation process, a logistics rotation between real pallets on which a certain amount of door panels are loaded and empty pallets on which no door panel is loaded must be performed smoothly. Therefore, it is desired to manufacture and operate a large number of pallets for a smooth logistics rotation.

(4) A divider is installed on the pallet to fix loaded door panels in a vertical direction. The divider plays an important role in determining a picking position within the pallet so that the robot may extract the door panels through a gripper. However, the divider may be twisted or deformed during use, which causes a position error in the divider for each pallet. Therefore, when the position error in the divider for each pallet occurs while operating a large number of pallets, an event situation occurs in which the door panels may not be extracted due to a change in the picking position of the robot, which is a problem that causes a line interruption and a decrease in an operation rate in the smart factory.

(5) In order to prevent such a problem of the line interruption, when manufacturing a new pallet, a pallet teaching management work may be performed to select a reference pallet for teaching the door panel picking position of the robot and to customize and confirm that the remaining pallets have the same picking positions as the reference pallet. However, the pallet teaching management work of the related art has a problem of requiring periodic checking and incurring high cost to maintain and manage a pallet precision even during mass production, and has the disadvantage that the problem continuously occurs.

(6) In the related art, a gripper for a door utilizes upper and lower clamps movably installed through an electric cylinder and a guide rail in correspondence to differences in inner panel shapes and heights of multi-vehicle doors. However, the gripper for the door of the related art clamps the door panel in point contact and has a problem of hindering an operation rate by not picking the door panel when a loading position of the door panel within a pallet changes. In addition, when using the electric cylinder and the guide rail, the gripper for the door of the related art has a

disadvantage in that the weight of the gripper increases, which affects an operating load of the robot, and has a problem that it takes a lot of time to fix a failure when the electric cylinder fails. (7) The matters described in the Background section are provided to enhance the understanding of the background of the present disclosure, and may include matters that are not already known to those of ordinary skill in the art to which this technology pertains.

#### SUMMARY

(8) The present disclosure provides a gripper for a door that is capable of absorbing a position error of a door panel for each pallet so that a robot is capable of picking the door panel, and adapting to an inner shape of a multi-vehicle door panel so that the gripper is commonly usable in one line, and its control method.

(9) According to one aspect of the present disclosure, a gripper mounted on a robot used in a smart factory to pick a door loaded on a pallet may include: a frame mounted on a tool changer of the robot; and a picking unit mounted on a front of the frame and applying pressure to and regulating each of an upper point and a lower point of an opening formed in an inner panel of the door through a bundle type pin locator (namely, a bundle pin locator). The gripper further includes: a pressure control valve adjusting the pressure of guide air cylinders each applied to the picking unit; a side clamping unit mounted on the front of the frame and holding (e.g., clamping) a side point of the opening by using a fixing locator and a clasper operated with a driving force of a clamping cylinder; and a control unit adjusting a moving distance of the robot by measuring a distance difference between the side clamping unit and the inner panel by using a laser sensor.

(10) In addition, the frame may include a first vertical frame installed on the front and mounting the picking unit thereon; and a second vertical frame disposed at a position parallel to the first vertical frame and mounting the side clamping unit thereon.

(11) In addition, the picking unit may include an upper picking unit regulating the upper point of the inner panel through the bundle type pin locator transferring a force in an upward direction by using the pressure of the guide air cylinder; and a lower picking unit regulating the lower point of the inner panel through the bundle type pin locator transferring the force in a falling direction by using the pressure of the guide air cylinder.

(12) In addition, the bundle type pin locator may include a plurality of hexagon pin locators arranged in a bundle type structure at a part in contact with the inner panel; a support rod extending in a longitudinal direction from lower portions of the plurality of hexagon pin locators and penetrating a horizontal plate configured inside a housing; a spring installed around the support rod and supporting the lower portions of the plurality of hexagon pin locators; a locking plate installed at the lowest end of the support rod and locked on a lower surface of the horizontal plate; and a laser beam sensor installed in a horizontal direction in a lower portion of the housing and sensing falling positions of the plurality of hexagon pin locators in contact with the inner panel.

(13) In addition, the plurality of hexagon pin locators are each a pin having a regular hexagonal cross-sectional shape and may form an anti-slip pattern in a comb pattern shape on an upper surface thereof in contact with the inner panel.

(14) In addition, the plurality of hexagon pin locators may be densely arranged, with adjacent regular hexagonal cross-sections facing each other, and the plurality of hexagon pin locators may each move up and down by the weight of the inner panel in contact with the upper surface thereof and an elastic force of the spring supporting a lower portion of the inner panel.

(15) In addition, the laser beam sensor may include a light emitting unit and a light receiving unit, and sense that a falling position of the locking plate reaches a reference position by using a laser beam transmitted from the light emitting unit and received horizontally by the light receiving unit. Then, the laser beam sensor may transmit a falling sensing signal to the pressure control valve.

(16) In addition, the pressure control valve may include an upper pressure control valve and a lower pressure control valve respectively configured to correspond to the upper picking unit and the lower picking unit, and the upper pressure control valve and the lower pressure control valve

may set the pressure of the guide air cylinder to a low pressure lower than a critical pressure during initial operations of the upper picking unit and the lower picking unit to prevent damage to the inner panel.

(17) In addition, the upper pressure control valve and the lower pressure control valve may maintain a low pressure lower than the critical pressure until receiving the falling sensing signal from the laser beam sensor in a bundle type pin locator inner panel contact step. When receiving the falling sensing signal, the upper pressure control valve and the lower pressure control valve may increase the pressure of the guide air cylinder by a certain amount to strengthen a regulatory force of the inner panel.

(18) In addition, the side clamping unit may clamp or hold an inner surface of the side point with a clamper rotating around a hinge axis by a forward operation of the clamping cylinder while the fixing locator is placed on an outer surface of the side point.

(19) In addition, the control unit may control the upper point and the lower point to be regulated by using the picking unit after completing clamping of the side point by using the side clamping unit.

(20) In addition, the control unit may include a robot controller that measures an actual measurement distance from the inner panel through the laser sensor and derives a distance difference between the actual measurement distance and a reference distance set based on robot teaching. The control unit may include a gripper controller interoperating with the robot controller and controlling operations of the picking unit and the side clamping unit.

(21) In addition, the gripper controller may control the pressing force of the bundle type pin locator formed at the tip of the picking unit in stages through the pressure control valve.

(22) According to one aspect of the present disclosure, a control method of a gripper mounted on a robot used in a smart factory to pick a door loaded on a pallet includes: moving the gripper to a set picking position of the door through motion control of the robot; and adjusting a moving distance of the robot by measuring a distance difference between a side clamping unit and an inner panel by using a laser sensor mounted on the side clamping unit of the gripper. The control method further includes: holding a side point of the inner panel by using the side clamping unit; and applying pressure to and regulating the upper point and the lower point of the inner panel through a bundle type pin locator configured in a picking unit of the gripper.

(23) In addition, the adjusting of the moving distance of the robot includes measuring an actual measurement distance from the inner panel by using the laser sensor; and deriving the distance difference by subtracting a reference distance set based on robot teaching from the actual measurement distance.

(24) In addition, the adjusting of the moving distance of the robot includes: comparing the distance difference with an allowable value for a clamping operation of the side clamping unit; and adjusting a position of the gripper in a forward/backward direction by the distance difference when the distance difference exceeds the allowable value.

(25) In addition, the regulating of the upper point and the lower point may include: controlling each guide air cylinder to a low pressure by setting the pressure control valve to a low pressure in an initial operation step of the picking unit; and maintaining a low pressure while the bundle type pin locator is in contact with the inner panel and monitoring whether some of hexagon pin locators in contact with the inner panel fall to a reference position through a laser beam sensor. The control method further includes: when falling sensing signals of some of hexagon pin locators are received from the laser beam sensor, strengthening a regulatory force of the inner panel with an increased force by increasing the pressure of the guide air cylinder by a certain amount.

(26) According to an embodiment of the present disclosure, by providing the gripper capable of adjusting or correcting the position of the robot with respect to a change in the position of the door loaded on each pallet, there is an effect of preventing a line interruption in a smart factory and improving an operation rate.

(27) In addition, by providing the gripper capable of responding to the position error of the inner

panel and the change in the shape height through the picking unit to which the bundle type pin locator is applied, there is an effect of reducing pallet teaching management costs and enabling a multi-vehicle flexible production.

(28) In addition, by eliminating a heavy gripper to which the electric cylinder and guide rail of the related art are applied and using the lightweight gripper of the present disclosure, there is an effect of reducing a robot load and reducing an energy usage.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 schematically illustrates a door mounting process to which a gripper for a door is applied according to an embodiment of the present disclosure.

(2) FIGS. 2 and 3 illustrate a gripper for a door and a door panel picking state using the same, according to an embodiment of the present disclosure.

(3) FIG. 4 illustrates the detailed configuration of a bundle type pin locator according to an embodiment of the present disclosure.

(4) FIG. 5 is a cross-sectional view taken along line A-A of FIG. 2 and illustrates operating states of picking units with respect to a position error of a door, according to an embodiment of the present disclosure.

(5) FIG. 6 is a cross-sectional view taken along line B-B of FIG. 2 and illustrates a state in which clamping is impossible due to an error in a loading position of a door panel within a pallet, according to an embodiment of the present disclosure.

(6) FIG. 7 illustrates countermeasures according to a change in a loading position of a door panel within a pallet according to an embodiment of the present disclosure.

(7) FIG. 8 illustrates height differences in inner panel shapes of multi-vehicle doors according to an embodiment of the present disclosure.

(8) FIG. 9 illustrates a control method of a picking unit corresponding to a difference in a regulated cross-sectional height of a multi-vehicle door according to an embodiment of the present disclosure.

(9) FIGS. 10 and 11 are flowcharts schematically illustrating a control method of a gripper for a door according to an embodiment of the present disclosure.

### DETAILED DESCRIPTION

(10) The present disclosure is described more fully hereinafter with reference to the accompanying drawings, so that those having ordinary skill in the art to which the present disclosure pertains may easily implement the embodiments of the present disclosure.

(11) The terms used herein are for the purpose of describing specific embodiments only, and are not intended to limit the present disclosure. As used herein, singular forms are intended to also include plural forms unless the context clearly indicates otherwise. It should also be understood that the terms “comprises” and/or “comprising,” when used herein, specify the presence of mentioned features, integers, steps, actions, elements and/or components, but do not exclude the presence or addition of one or more of other features, integers, steps, actions, elements, components, and/or groups thereof. As used herein, the term “and/or” includes any one or all combinations of the associated listed items.

(12) Throughout the specification, the terms first, second, A, B, (a), (b), etc. may be used to describe various components, but the components should not be limited by the terms. These terms are only used to distinguish the component from other components, and the nature, sequence, or order of the component is not limited by the terms.

(13) Throughout the specification, when a component is referred to as being “connected to” or “coupled to” another component, the component may be connected or coupled to the other

component or intervening components may be present. In contrast, when a component is referred to as being “directly connected to” or “directly coupled to” another component, there are no intervening components present. When a component, device, element, or the like of the present disclosure is described as having a purpose or performing an operation, function, or the like, the component, device, or element should be considered herein as being “configured to” meet that purpose or to perform that operation or function.

(14) Throughout the specification, the terms used are for the purpose of describing a specific embodiment only and is not intended to limit the present disclosure. The singular expression includes the plural expression unless the context clearly dictates otherwise.

(15) Additionally, it is understood that one or more of the methods below or aspects thereof may be executed by at least one or more controllers. The term “controller” may refer to a hardware device including a memory and a processor. The memory is configured to store program instructions, and the processor is specifically programmed to execute the program instructions to perform one or more processes described in more detail below. A controller may control operations of units, modules, parts, devices, or similar thereto, as described herein. It is also understood that the methods below may be performed by a device including a controller along with one or more other components, as should be appreciated by those having ordinary skill in the art.

(16) Now, a gripper for a door and its control method according to an embodiment of the present disclosure are described in detail with reference to the drawings.

(17) FIG. 1 schematically illustrates a door mounting process to which a gripper for a door is applied according to an embodiment of the present disclosure.

(18) FIGS. 2 and 3 illustrate the configuration of the gripper for the door according to an embodiment of the present disclosure and a door panel picking state using the same.

(19) Referring to FIGS. 1 to 3, a gripper **100** is mounted on a robot **10** installed in a smart factory for a door mounting process. The gripper **100** is used to pick and extract a door panel **30** loaded on a pallet **20** and assemble the door panel **30** into a car body **50**.

(20) For example, the pallet **20** is loaded with a plurality of door panels **30** (hereinafter referred to as “doors” for convenience) in an upright state by a divider **21** and moves to a pallet rack **40** set through a logistics transportation means such as an automated guided vehicle (AGV) or autonomous mobile robots (AMR) and then stands by.

(21) The gripper **100** moves to a picking position of the door **30** set through motion control of the robot **10** having six-axis or more degrees of freedom. In addition, the gripper **100** picks the door **30** through mechanical units **120-1**, **120-2**, and **130** respectively regulating an upper point P1, a lower point P2, and a side point P3 of an opening **32** formed in an inner panel **31** of the door **30**. Here, the picking means a state in which the door **30** is capable of being extracted (transferred) by the gripper **100** through successfully regulating (fixing) the upper point P1, the lower point P2, and the side point P3 of the opening **32**. Accordingly, the robot **10** may extract the door **30** that has been successfully picked by the gripper **100** from the pallet **20**.

(22) As described above, in the related art, there was a problem causing a position error when the divider **21** fixing door panels upright loaded on the pallet **20** in the vertical direction is twisted or deformed, and this position error causes a situation in which picking the door **30** from each pallet is impossible (fails).

(23) Accordingly, the present disclosure provides the gripper **100** for a multi-vehicle common door that enables door picking by absorbing the position error for each pallet in correspondence to the problem causing the situation in which picking is impossible due to the position error in each pallet.

(24) The gripper **100** according to an embodiment of the present disclosure includes a frame **110**, a picking unit **120**, a side clamping unit **130**, a pressure control valve **140**, and a control unit **150**.

(25) The frame **110** is mounted on a tool changer **11** of the robot **10** through a tool mounting portion **113** formed on the rear side thereof.

(26) The frame **110** includes a first vertical frame **111** installed in the front thereof and mounting the picking unit **120**, and a second vertical frame **112** disposed in parallel with the first vertical frame **111** and mounting the side clamping unit **130**.

(27) The picking unit **120** applies pressure to and regulates each of the upper point **P1** and the lower point **P2** of the opening **32** formed in the inner panel **31** of the door **30** through a bundle type pin locator **121** to which a spring is applied.

(28) The pressure control valve **140** controls the pressure of a guide air cylinder applied to the picking unit **120**.

(29) The side clamping unit **130** clamps the side point **P3** of the opening **32** by using a fixing locator **131** and a clammer **132** operating with a driving force of a clamping cylinder **133**.

(30) The control unit **150** corrects a moving distance of the robot **10** by measuring a distance deviation with the inner panel **31** through a laser sensor **134** before clamping.

(31) The picking unit **120** includes the upper picking unit **120-1** and the lower picking unit **120-2** installed on the first vertical frame **111**. The upper picking unit **120-1** and the lower picking unit **120-2** only have different operating directions according to installed positions but have the same configuration.

(32) For example, the upper picking unit **120-1** may regulate the upper point **P1** of the inner panel **31** through the bundle type pin locator **121** transferring force in an upward direction by using the pressure of the guide air cylinder **122**.

(33) In addition, the lower picking unit **120-2** may regulate the lower point **P2** of the inner panel **31** through the bundle type pin locator **121** transferring force in a falling direction by using the pressure of the guide air cylinder **122**.

(34) FIG. 4 illustrates the detailed configuration of the bundle type pin locator according to an embodiment of the present disclosure.

(35) Referring to FIG. 4, in the bundle type pin locator **121** according to an embodiment of the present disclosure, a plurality of hexagon pin locators **1211** are disposed in a bundle type structure in a part in contact with the inner panel **31** so that regulation is possible even though the position and/or shape of the inner panel **31** is changed in various ways due to a position error of the pallet **20**.

(36) The bundle type pin locator **121** includes the plurality of hexagon pin locators **1211** disposed in the bundle type structure in the part in contact with the inner panel **31**, a support rod **1212** extending in a longitudinal direction from a lower portion of the hexagon pin locator **1211** and penetrating a horizontal plate **1216** formed inside a housing **1215**, a locking plate **1213** installed at the lowest end of the support rod **1212** and locked on a lower surface of the horizontal plate **1216**, a spring **1214** installed around the support rod **1212** and supporting the lower portion of the hexagon pin locator **1211**, and a laser beam sensor **1218** installed in a horizontal direction in a lower portion of the housing **1215** and sensing a falling position of the hexagon pin locator **1211** in contact with the inner panel **31**.

(37) The hexagon pin locators **1211** are each a pin having a regular hexagonal cross-section shape and may form an anti-slip pattern **1217** in a comb pattern shape on an upper surface thereof in contact with the inner panel **31** of a door.

(38) The hexagon pin locators **1211** may be densely disposed in the longitudinal direction of the pin, with adjacent regular hexagonal cross-sections facing each other, to form the bundle type structure.

(39) The hexagon pin locators **1211** may each move up and down by the weight of the inner panel **31** in contact with the upper surface thereof and an elastic force of the spring **1214** supporting a lower portion thereof. At this time, the hexagon pin locators **1211** may each move up and down according to the shape of the inner panel **31** in contact with the upper surface thereof.

(40) The laser beam sensor **1218** senses the falling position of the locking plate **1213** installed at the lowest end from the hexagon pin locator **1211**.

(41) The laser beam sensor **1218** senses that the falling position of the locking plate **1213** reaches a reference position by using a laser beam transmitted and received horizontally through a light emitting unit **1218a** and a light receiving unit **1218b**, and transmits a falling sensing signal to the pressure control valve **140**. Accordingly, the pressure control valve **140** may receive the falling sensing signal from the laser beam sensor **1218** to determine a time when the inner panel **31** is finally seated on the bundle type pin locator **121**.

(42) FIG. 5 is a cross-sectional view taken along line A-A of FIG. 2 according to an embodiment of the present disclosure, and illustrates operating states of picking units with respect to a position error of a door.

(43) First, FIG. 5(A) illustrates states where the upper point P1 and the lower point P2 of the inner panel **31**, which is normally (no position error) loaded on the pallet **20**, are respectively regulated by using the upper picking unit **120-1** and the lower picking unit **120-2**.

(44) Force is applied to the bundle type pin locator **121** by the pressure of each guide air cylinder **122**, so that some of hexagon pin locators **1211a** in contact with the inner panel **31** move backward and the remaining hexagon pin locators **1211b** remain in place. At this time, the bundle type pin locator **121** of the bundle type structure may complete picking by fixing the inner panel **31** with the pressing force of some of the hexagon pin locators **1211a**, and forming a step around the inner panel **31** by the remaining hexagon pin locators **1211b** to prevent the inner panel **31** from separating.

(45) Next, FIG. 5(B) illustrates states where the upper point P1 and the lower point P2 of the inner panel **31** whose loading position has changed while a position error “e” of the pallet **20** has occurred are respectively regulated by using the upper picking unit **120-1** and the lower picking unit **120-2**.

(46) As described above, even in the state in which the position error e of the pallet **20** has occurred, the bundle type pin locator **121** of the bundle type structure may fix the inner panel **31** whose loading position has changed due to the pressing force of some of the hexagon pin locators **1211a**. In addition, at the same time, the bundle type pin locator **121** of the bundle type structure may complete picking by forming a step around the inner panel **31** by the remaining hexagon pin locator **1211b** to prevent the inner panel **31** from separating arbitrarily.

(47) Therefore, the picking unit **120** according to the embodiment of the present disclosure may absorb the position error e occurred for each pallet by using the bundle type pin locator **121**, thereby maintaining a state in which the robot **10** is capable of picking the door.

(48) Referring again to FIGS. 1 to 3, the side clamping unit **130** regulates the side point P3 of the inner panel **31** by using the fixing locator **131** and the clasper **132** operating by the clamping cylinder **133**.

(49) The side clamping unit **130** clamps an inner surface of the side point P3 with the clasper **132** rotating around a hinge axis **135** by a forward operation of the clamping cylinder **133** while the fixing locator **131** is placed in an outer surface of the side point P3. In an operation opposite this, the side clamping unit **130** operates the clamping cylinder **133** backward to release the clamping of the side point P3.

(50) The side clamping unit **130** according to an embodiment of the present disclosure includes a laser sensor **134** measuring a distance deviation (i.e., distance difference) “D” between a reference position of the inner panel **31** set based on robot teaching and a change position of the actually loaded inner panel **31**.

(51) Meanwhile, FIG. 6 is a cross-sectional view taken along line B-B of FIG. 2 according to an embodiment of the present disclosure, and illustrates a state in which clamping is impossible due to an error in a loading position of a door panel within a pallet.

(52) Referring to FIG. 6, the side clamping unit **130** moves to a reference position of the inner panel **31** set based on robot teaching and operates to clamp the side point P3 of the inner panel **31** by using the fixing locator **131** and the clasper **132**. The reference position refers to a position set

to have a reference distance **D1** with the inner panel **31** based on robot teaching.

(53) However, when the loading position of the door **30** changes due to a position error of a divider within the pallet **20**, a deformation in a left and right direction (x-axis) is small, but a deformation in a front and back direction (y-axis) is relatively large, causing a situation in which clamping is impossible. Therefore, when picking the inner panel **31**, it is necessary to compensate for a distance deviation between the side clamping unit **130** and the inner panel **31** by a change position in the front and back direction (y-axis).

(54) Accordingly, FIG. 7 illustrates countermeasures according to a change in a loading position of a door panel within a pallet according to an embodiment of the present disclosure.

(55) Referring to FIG. 7(A), the side clamping unit **130** according to an embodiment of the present disclosure may measure the distance deviation **D** between a reference position of the inner panel **31** set based on robot teaching and a change position of the actually loaded inner panel **31** by using the laser sensor **134** before clamping the inner panel **31**.

(56) For example, according to an embodiment, the laser sensor **134** may include a calculation function to calculate the distance deviation **D** obtained by subtracting the reference distance **D1** from an actual measurement distance **D2** measured before the clamping. In addition, according to an embodiment, the laser sensor **134** may transfer the actual measurement distance **D2** measured before the clamping to the control unit **150** to derive the distance deviation **D** obtained by subtracting the reference distance **D1** from the actual measurement distance **D2**.

(57) Accordingly, referring to FIG. 7(B), the control unit **150** controlling the robot **10** adjusts a moving distance of the robot **10** based on the distance deviation (e.g., the distance difference) “**D**”, thereby allowing the side clamping unit **130** to pick the inner panel **31** at the changed position.

(58) In other words, the side clamping unit **130** is placed at the reference distance **D1** from the inner panel **31** at the change position through correction of the moving distance of the robot **10**, thereby clamping the side point **P3** of the inner panel **31** by using the fixing locator **131** and clamper **132**.

(59) Meanwhile, FIG. 8 illustrates heights differences in inner panel shapes of multi-vehicle doors according to an embodiment of the present disclosure.

(60) Referring to FIG. 8, heights (i.e., regulated cross-sectional heights) of inner panel shapes of multi-vehicle doors applied to a door mounting process according to an embodiment of the present disclosure may be different from each other, such as 460 mm for a door **30a** of car type A, 499 mm for a door **30b** of car type B, 484 mm for a door **30c** of car type C, etc. Therefore, in order for the robot **10** to pick multi-vehicle doors, the picking unit **120** must move in an up/down direction (z-axis).

(61) In this regard, the related art has proposed a gripper for a door using an upper/lower clamp movably installed through an electric cylinder and a guide rail, but has the disadvantage of increasing the weight and the problem of taking a lot of time to fix a failure.

(62) Accordingly, the present disclosure may slowly operate the bundle type pin locator **121** up and down through force control that adjusts pressure of the guide air cylinder **122** of the picking unit **120** in stages by using the pressure control valve **140**, without using an electric cylinder and a guide rail. Here, the force control refers to a degree to which the bundle type pin locator **121** presses a regulation point of the inner panel **31**.

(63) FIG. 9 illustrates a control method of a picking unit corresponding to a difference in a regulated cross-sectional height of a multi-vehicle door according to an embodiment of the present disclosure.

(64) FIG. 9 illustrates a process in which the pressure control valve **140** regulates the upper point **P1** and the lower point **P2** of an inner panel through pressure adjustment in stages in a state in which the picking unit **120** according to an embodiment of the present disclosure is aligned at a picking position of a multi-vehicle door **30**.

(65) The pressure control valve **140** includes an upper pressure control valve **140-1** and a lower

pressure control valve **140-2** configured to correspond to the upper picking unit **120-1** and the lower picking unit **120-2**, respectively. The upper pressure control valve **140-1** and the lower pressure control valve **140-2** operate in the same manner. Therefore, hereinafter, an operation of the upper pressure control valve **140-1** is mainly described, but the lower pressure control valve **140-2** may also operate in the same manner.

(66) For example, in an initial operation step, the upper pressure control valve **140-1** sets the pressure of the guide air cylinder **122** to a small force of a low pressure during the initial operation of the upper picking unit **120-1**, to prevent damage to the inner panel **31**. For example, the low pressure is lower than a set pressure, and the set pressure may be a critical pressure causing damage to the inner panel **31**. Such a set pressure may vary depending on specifications such as a material and thickness of a door of the car body **50**, and it may be understood that a person skilled in the art may apparently set the set pressure.

(67) In a bundle type pin locator inner panel contact step, the upper pressure control valve **140-1** maintains the low pressure until receiving falling sensing signals of some of the hexagon pin locators **1211** in contact with the inner panel **31** through the laser beam sensor **1218**.

(68) In addition, in an upper/lower unit panel regulation step, the upper pressure control valve **140-1** may strengthen a regulatory force of the inner panel **31** by increasing the pressure of the guide air cylinder **122** by a certain amount (e.g. 6 bar) when receiving the falling sensing signals of the hexagon pin locators **1211** from the laser beam sensor **1218**.

(69) In other words, the upper pressure control valve **140-1** may lift the inner panel **31** with a small force to prevent damage to the inner panel **31** when the upper picking unit **120-1** rises, and, after being located in a range where the inner panel **31** is not damaged by the bundle type pin locator **121**, change the pressing force with a force for handling the door **30**.

(70) In the same manner as above, the upper picking unit **120-1** and the lower picking unit **120-2** may commonly regulate the multi-vehicle door **30** regardless of the difference in the inner panel shape height within a stroke range of the guide air cylinder **122**.

(71) Meanwhile, the control unit **150** controls the overall operations of the robot **10** provided in the door mounting process and the gripper **100** mounted on the robot **10**.

(72) After completing the clamping of the side point **P3** by using the side clamping unit **130**, the control unit **150** may control each of the upper point **P1** and the lower point **P2** to be regulated by using the picking unit **120**.

(73) The control unit **150** may include a robot controller **151** and a gripper controller **152** that interoperate with each other.

(74) The robot controller **151** moves the gripper **100** to the picking position of the door **30** loaded on the pallet **20** through motion control of the robot **10**.

(75) When moving the gripper **100** to the picking position, the robot controller **151** may measure the actual measurement distance **D2** from the inner panel **31** through the laser sensor **134** and derive the distance deviation **D** between the reference distance **D1** of the inner panel **31** set based on robot teaching and the actual measurement distance **D2**. In addition, the robot controller **151** may correct the position of the gripper **100** by the distance deviation **D**.

(76) The gripper controller **152** may control operations of the picking unit **120** and the side clamping unit **130** of the gripper **100** that have moved to the picking position of the door **30**, respectively, to regulate the upper, lower, and side points **P1**, **P2**, and **P3** corresponding to the inner panel **31** of the door.

(77) At this time, the gripper controller **152** controls the pressing force of the bundle type pin locator **121** configured at the tip of the picking unit **120** in stages through the pressure control valve **140**, thereby performing adaptive regulation with respect to a change in the position and/or shape of the inner panel **31**.

(78) The control unit **150** may be implemented as one or more processors operating according to a set program, and the set program may be programmed to perform each step of a control method of

a gripper for a door according to an embodiment of the present disclosure.

(79) The control method of the gripper for the door is described in more detail with reference to the drawings below.

(80) FIGS. **10** and **11** are flowcharts schematically illustrating a control method of a gripper for a door according to an embodiment of the present disclosure.

(81) First, referring to FIG. **10**, the control unit **150** of the gripper **100** for the door **30** mounted on the robot **10** according to an embodiment of the present disclosure moves the gripper **100** to a set picking position of the door **30** through motion control of the robot **10** (S10). The picking position may be a position for measuring whether a loading position of the door **30** within the pallet **20** changes before picking.

(82) The control unit **150** measures the actual measurement distance D2 from the inner panel **31** by using the laser sensor **134** mounted on the side clamping unit **130** of the gripper **100** (S20).

(83) The control unit **150** derives the distance deviation (i.e., distance difference) “D” obtained by subtracting the reference distance D1 set based on robot teaching from the actual measurement distance D2 (S30).

(84) The control unit **150** compares the distance deviation D with an allowable value (e.g.,  $\pm 2$  mm) for a clamping operation of the side clamping unit **130** (S40).

(85) At this time, when the distance deviation D exceeds the allowable value (S40; Yes), the control unit **150** corrects a position (that is, a position of the side clamping unit **130**) of the gripper **100** in a forward/backward direction (y-axis) by the distance deviation D (S50), and operates the side clamping unit **130** to regulate (clamp) the side point P3 of the inner panel **31** (S60).

(86) On the other hand, when the distance deviation D does not exceed the allowable value (S40; No), the control unit **150** operates the side clamping unit **130** without correcting the position of the gripper **100** to regulate the side point P3 of the inner panel **31** (S60).

(87) According to the control method of the gripper **100** for the door **30** of the present disclosure as above, even though the loading position of the door **30** within the pallet **20** changes, the side clamping unit **130** may be clamped through distance correction. In addition, by clamping the side clamping unit **130**, the picking unit **120** parallel to the front of the gripper **100** is placed at a picking possible position.

(88) Next, FIG. **11** illustrates the flowchart in which the control unit **150** applies pressure to and regulates the upper point P1 and the lower point P2 of the inner panel **31** through the bundle type pin locator **121** configured in the picking unit **120** of the gripper **100** to rise or fall.

(89) Specifically, the control unit **150** controls each guide air cylinder **122** to the low pressure by setting the pressure control valve **140** to a low pressure in an initial operation step of the picking unit **120**. At this time, the bundle type pin locators **121** each mounted on the tip of the picking unit **120** rise/fall with a small force (S70).

(90) The control unit **150** maintains the low pressure control while the bundle type pin locator **121** is in contact with the inner panel **31** (S80), and monitors whether some of the hexagon pin locators **1211a** in contact with the inner panel **31** fall to a reference position through the laser beam sensor **1218** (S90).

(91) At this time, when the control unit **150** does not receive falling sensing signals of some of the hexagon pin locators **1211a** from the laser beam sensor **1218** (S100; No), the control unit **150** stands by while maintaining the low pressure control.

(92) On the other hand, when the control unit **150** receives the falling sensing signals of some of the hexagon pin locators **1211a** from the laser beam sensor **1218** (S100; Yes), the control unit **150** strengthens a regulatory force of the inner panel **31** with increased force by increasing the pressure of the guide air cylinder **122** by a certain amount (e.g.; 6 bar) (S110).

(93) At this time, the control unit **150** may fix the inner panel **31** with the pressing force of some of the hexagon pin locators **1211a** among the bundle type pin locators **121** of a bundle type structure, and form a step around the inner panel **31** by the remaining hexagon pin locators **1211b** to complete

door picking in a state where handling is possible (S120).

(94) As described above, according to an embodiment of the present disclosure, by providing the gripper capable of correcting the position of the robot with respect to a change in the position of the door loaded on each pallet, there is an effect of preventing a line interruption in a smart factory and improving an operation rate.

(95) In addition, by providing the gripper capable of responding to the position error of the inner panel and the change in the shape height through the picking unit to which the bundle type pin locator is applied, there is an effect of reducing pallet teaching management costs and enabling a multi-vehicle flexible production.

(96) In addition, by eliminating a heavy gripper (e.g., 120 kg) to which the electric cylinder and guide rail of the related art are applied and using the lightweight gripper (e.g., 55 kg) of the present disclosure, there is an effect of reducing a robot load and reducing an energy usage.

(97) The embodiment of the present disclosure is not implemented only through the device and/or method described above, and may be implemented through a program for realizing a function corresponding to the configuration of the embodiment of the present disclosure or a recording medium on which the program is recorded. Such an implementation may be easily implemented by an expert in the technical field to which the present disclosure pertains from the description of the above-described embodiments.

(98) Although the embodiment of the present disclosure has been described in detail above, the scope of the present disclosure is not limited thereto, and various modifications and improvement forms of those skilled in the art using the basic concept of the present disclosure as defined in the following claims are also within the scope of the present disclosure.

(99) TABLE-US-00001 <Description of symbols> 10: robot 11: tool changer 20: palette 21: divider 30: door 31: inner panel 32: opening 40: rack 50: vehicle body 100: gripper 110: frame 111: first vertical frame 112: second vertical frame 113: tool mounting portion 120: picking unit 120-1: upper picking unit 120-2: lower picking unit 121: bundle type pin locator 1211: hexagon pin locator 1212: support rod 1213: locking plate 1214: spring 1215: housing 1216: horizontal plate 1217: anti-slide pattern 1218: laser beam sensor 122: guide air cylinder 130: side clamping unit 131: fixing locator 132: clumper 133: clamping cylinder 134: laser sensor 135: hinge axis 140: pressure control valve 140-1: upper pressure control valve 140-2: lower pressure control valve 150: control unit 151: robot controller 152: gripper controller P1: upper point P2: lower point P3: side point

## Claims

1. A gripper mounted on a robot to pick a door loaded on a pallet, the gripper comprising: a frame mounted on a tool changer of the robot; a picking unit mounted on a front of the frame and configured to apply pressure to and regulate each of an upper point and a lower point of an opening formed in an inner panel of the door through a bundle pin locator; a pressure control valve configured to adjust a pressure of guide air cylinders each applied to the picking unit; a side clamping unit mounted on the front of the frame and configured to hold a side point of the opening using a fixing locator and a clumper operated with a driving force of a clamping cylinder; and a control unit configured to adjust a moving distance of the robot by measuring a distance difference between the side clamping unit and the inner panel.

2. The gripper for the door of claim 1, wherein the frame comprises: a first vertical frame installed on the front and mounting the picking unit thereon; and a second vertical frame disposed at a position parallel to the first vertical frame and mounting the side clamping unit thereon.

3. The gripper for the door of claim 1, wherein the picking unit comprises: an upper picking unit configured to regulate the upper point of the inner panel through the bundle pin locator transferring a force in an upward direction using the pressure of the guide air cylinder; and a lower picking unit configured to regulate the lower point of the inner panel through the bundle pin locator transferring

the force in a falling direction by using the pressure of the guide air cylinder.

4. The gripper for the door of claim 3, wherein the bundle pin locator comprises: a plurality of hexagon pin locators arranged in a bundle structure at a part in contact with the inner panel; a support rod configured to extend in a longitudinal direction from lower portions of the plurality of hexagon pin locators and configured to penetrate a horizontal plate configured inside a housing; a spring installed around the support rod and configured to support the lower portions of the plurality of hexagon pin locators; a locking plate installed at a lowest end of the support rod and locked on a lower surface of the horizontal plate; and a laser beam sensor installed in a horizontal direction in a lower portion of the housing and configured to sense falling positions of the plurality of hexagon pin locators in contact with the inner panel.

5. The gripper for the door of claim 4, wherein each hexagon pin locator of the plurality of hexagon pin locators is a pin having a regular hexagonal cross-sectional shape, and the plurality of hexagon pin locators forms an anti-slip pattern in a comb pattern shape on an upper surface thereof in contact with the inner panel.

6. The gripper for the door of claim 5, wherein: the plurality of hexagon pin locators are densely arranged, with adjacent regular hexagonal cross-sections facing each other, and each of the plurality of hexagon pin locators is configured to move up and down by a weight of the inner panel in contact with the upper surface thereof and an elastic force of the spring supporting a lower portion of the inner panel.

7. The gripper for the door of claim 4, wherein: the laser beam sensor comprises a light emitting unit and a light receiving unit, and the laser beam sensor is configured to sense that a falling position of the locking plate reaches a reference position by using a laser beam transmitted from the light emitting unit and received by the light receiving unit and further configured to transmit a falling sensing signal to the pressure control valve.

8. The gripper for the door of claim 7, wherein: the pressure control valve includes an upper pressure control valve and a lower pressure control valve respectively configured to correspond to the upper picking unit and the lower picking unit, and the upper pressure control valve and the lower pressure control valve set the pressure of the guide air cylinder to a low pressure lower than a critical pressure during initial operations of the upper picking unit and the lower picking unit to prevent damage to the inner panel.

9. The gripper for the door of claim 8, wherein: the upper pressure control valve and the lower pressure control valve maintain a low pressure lower than a critical pressure until receiving the falling sensing signal from the laser beam sensor, and when receiving the falling sensing signal, the upper pressure control valve and the lower pressure control valve increase the pressure of the guide air cylinder by a certain amount to strengthen a regulatory force of the inner panel.

10. The gripper for the door of claim 1, wherein the side clamping unit is configured to hold an inner surface of the side point with a clasper rotating around a hinge axis by a forward operation of the clamping cylinder while the fixing locator is placed on an outer surface of the side point.

11. The gripper for the door of claim 1, wherein the control unit is configured to control the upper point and the lower point to be controlled by using the picking unit after completing clamping of the side point by using the side clamping unit.

12. The gripper for the door of claim 1, wherein the control unit comprises: a robot controller configured to measure an actual measurement distance from the inner panel through a laser sensor and derive a distance difference between the actual measurement distance and a reference distance set based on robot teaching; and a gripper controller configured to interoperate with the robot controller and control operations of the picking unit and the side clamping unit.

13. The gripper for the door of claim 12, wherein the gripper controller is configured to control a pressing force of the bundle pin locator formed at a tip of the picking unit in stages through the pressure control valve.

14. A control method of a gripper mounted on a robot to pick a door loaded on a pallet, the control

method comprising: moving the gripper to a set picking position of the door through motion control of the robot; adjusting a moving distance of the robot by measuring a distance difference between a side clamping unit and an inner panel by using a laser sensor mounted on the side clamping unit of the gripper; holding a side point of the inner panel by using the side clamping unit; and applying pressure to and regulating an upper point and a lower point of the inner panel through a bundle pin locator configured in a picking unit of the gripper.

15. The control method of claim 14, wherein adjusting the moving distance of the robot comprises: measuring an actual measurement distance from the inner panel by using the laser sensor; and deriving the distance difference by subtracting a reference distance set based on robot teaching from the actual measurement distance.

16. The control method of claim 14, wherein adjusting the moving distance of the robot comprises: comparing the distance difference with an allowable value for a clamping operation of the side clamping unit; and adjusting a position of the gripper in a forward/backward direction based on the distance difference when the distance difference exceeds the allowable value.

17. The control method of claim 14, wherein regulating the upper point and the lower point comprises: controlling each guide air cylinder to a low pressure by setting a pressure control valve in an initial operation step of the picking unit; maintaining the low pressure while the bundle pin locator is in contact with the inner panel and monitoring whether some of hexagon pin locators in contact with the inner panel reach at a reference position through a laser beam sensor; and when falling sensing signals of some of the hexagon pin locators are received from the laser beam sensor, strengthening a regulatory force of the inner panel with an increased force by increasing the pressure of the guide air cylinder by a certain amount.

---