

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410763
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Miller; Brandon Wayne et al.

Gas turbine engine with third stream

Abstract

A gas turbine engine is provided. The gas turbine engine includes a turbomachine defining an engine inlet to an inlet duct, a fan duct inlet to a fan duct, and a core inlet to a core duct; a primary fan driven by the turbomachine; and a secondary fan located downstream of the primary fan within the inlet duct. The gas turbine engine defines a thrust to power airflow ratio between 3.5 and 100 and a core bypass ratio between 0.1 and 10, wherein the thrust to power airflow ratio is a ratio of an airflow through a bypass passage over the turbomachine plus an airflow through the fan duct to an airflow through the core duct, and wherein the core bypass ratio is a ratio of the airflow through the fan duct to the airflow through the core duct.

Inventors: Miller; Brandon Wayne (Middletown, OH), Vondrell; Randy M. (Newport, KY), Ostdiek; David Marion (Liberty Township, OH), Higgins; Craig William (Liberty Township, OH), Simpson; Alexander Kimberly (Cincinnati, OH)

Applicant: General Electric Company (Evendale, OH)

Family ID: 94176663

Assignee: General Electric Company (Evendale, OH)

Appl. No.: 18/888873

Filed: September 18, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20250012235 A1	Jan. 09, 2025

Related U.S. Application Data

continuation parent-doc US 17879384 20220802 US 12031504 20240709 child-doc US 18675270
continuation-in-part parent-doc US 18675270 20240528 PENDING child-doc US 18888873

Publication Classification

Int. Cl.: F02K3/065 (20060101); F02C3/06 (20060101)

U.S. Cl.:

CPC F02K3/065 (20130101); F02C3/06 (20130101);

Field of Classification Search

CPC: F02K (3/02); F02K (3/025); F02K (3/065); F02C (3/06); F02C (3/107); F02C (7/36)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2999630	12/1960	Warren et al.	N/A	N/A
3528250	12/1969	Johnson	N/A	N/A
3540682	12/1969	Dibble et al.	N/A	N/A
3542152	12/1969	Adamson et al.	N/A	N/A
3750402	12/1972	Vdoviak et al.	N/A	N/A
4010608	12/1976	Simmons	N/A	N/A
4043121	12/1976	Thomas et al.	N/A	N/A
4163366	12/1978	Kent	N/A	N/A
4446696	12/1983	Sargisson et al.	N/A	N/A
4486146	12/1983	Campion	N/A	N/A
4569199	12/1985	Klees et al.	N/A	N/A
4607657	12/1985	Hirschkron	N/A	N/A
4784575	12/1987	Nelson et al.	N/A	N/A
4860537	12/1988	Taylor	N/A	N/A
4892269	12/1989	Greco et al.	N/A	N/A
4907946	12/1989	Ciokajlo et al.	N/A	N/A
4916894	12/1989	Adamson et al.	N/A	N/A
4976102	12/1989	Taylor	N/A	N/A
5054998	12/1990	Davenport	N/A	N/A
5190441	12/1992	Murphy et al.	N/A	N/A
5197855	12/1992	Magliozzi et al.	N/A	N/A
5259187	12/1992	Dunbar et al.	N/A	N/A
5261227	12/1992	Giffin, III	N/A	N/A
5345760	12/1993	Giffin, III	N/A	N/A
5457346	12/1994	Blumberg et al.	N/A	N/A
5950308	12/1998	Koff et al.	N/A	N/A
6339927	12/2001	DiPietro, Jr.	N/A	N/A
6547518	12/2002	Czachor et al.	N/A	N/A
6763654	12/2003	Orlando et al.	N/A	N/A
6792758	12/2003	Dowman	N/A	N/A
7559191	12/2008	Parks	N/A	N/A
7658063	12/2009	Matheny	N/A	N/A
7762766	12/2009	Shteyman et al.	N/A	N/A

8256202	12/2011	Paulino	N/A	N/A
8276392	12/2011	van der Woude	N/A	N/A
8382430	12/2012	Parry et al.	N/A	N/A
8459035	12/2012	Smith et al.	N/A	N/A
8689538	12/2013	Sankrithi et al.	N/A	N/A
8762766	12/2013	Ferguson et al.	N/A	N/A
8876465	12/2013	Stretton	N/A	N/A
8910465	12/2013	Snyder	N/A	N/A
8943796	12/2014	McCaffrey	N/A	N/A
8967967	12/2014	Stretton et al.	N/A	N/A
9017028	12/2014	Fabre	N/A	N/A
9045996	12/2014	Anghel et al.	N/A	N/A
9057328	12/2014	Kupratis	N/A	N/A
9096312	12/2014	Moxon	N/A	N/A
9097134	12/2014	Ferch et al.	N/A	N/A
9534538	12/2016	Cerny	N/A	N/A
9677501	12/2016	Pierluissi et al.	N/A	N/A
9759160	12/2016	Sankrithi et al.	N/A	N/A
9845768	12/2016	Pesyna et al.	N/A	N/A
9982555	12/2017	Thet et al.	N/A	N/A
9995314	12/2017	Miller et al.	N/A	N/A
10077660	12/2017	Hoefer et al.	N/A	N/A
10090676	12/2017	Knowles et al.	N/A	N/A
10126062	12/2017	Cerny et al.	N/A	N/A
10184400	12/2018	Cerny et al.	N/A	N/A
10202865	12/2018	Breeze-Stringfellow et al.	N/A	N/A
10253648	12/2018	Bentley et al.	N/A	N/A
10260419	12/2018	Cerny et al.	N/A	N/A
10263550	12/2018	Thet et al.	N/A	N/A
10344674	12/2018	Cerny et al.	N/A	N/A
10364750	12/2018	Rambo	N/A	N/A
10443436	12/2018	Miller et al.	N/A	N/A
10487739	12/2018	Miller et al.	N/A	N/A
10644630	12/2019	Smith et al.	N/A	N/A
10787996	12/2019	Kupratis et al.	N/A	N/A
2004/0197187	12/2003	Usab et al.	N/A	N/A
2004/0234372	12/2003	Shahpar	N/A	N/A
2005/0109012	12/2004	Johnson	N/A	N/A
2005/0241292	12/2004	Taylor et al.	N/A	N/A
2007/0186535	12/2006	Powell et al.	N/A	N/A
2007/0251212	12/2006	Tester	N/A	N/A
2009/0078819	12/2008	Guering et al.	N/A	N/A
2009/0090096	12/2008	Sheridan	N/A	N/A
2010/0014977	12/2009	Shattuck	N/A	N/A
2010/0111674	12/2009	Sparks	N/A	N/A
2010/0251726	12/2009	Jones et al.	N/A	N/A
2010/0326050	12/2009	Schilling et al.	N/A	N/A
2010/0329856	12/2009	Hofer et al.	N/A	N/A
2011/0150659	12/2010	Micheli et al.	N/A	N/A

2011/0192166	12/2010	Mulcaire	N/A	N/A
2012/0177493	12/2011	Fabre	N/A	N/A
2013/0056553	12/2012	Mouchoux et al.	N/A	N/A
2013/0098050	12/2012	Kupratis	N/A	N/A
2013/0104521	12/2012	Kupratis	N/A	N/A
2013/0104522	12/2012	Kupratis	N/A	N/A
2013/0104560	12/2012	Kupratis	N/A	N/A
2014/0133982	12/2013	Dejeu et al.	N/A	N/A
2014/0345253	12/2013	Dawson et al.	N/A	N/A
2014/0345254	12/2013	Dawson et al.	N/A	N/A
2015/0003993	12/2014	Kim et al.	N/A	N/A
2015/0098813	12/2014	Jarrett, Jr.	N/A	N/A
2015/0121893	12/2014	Kupratis	N/A	N/A
2015/0284070	12/2014	Breeze-Stringfellow et al.	N/A	N/A
2015/0291276	12/2014	Zatorski et al.	N/A	N/A
2016/0010487	12/2015	Breeze-Stringfellow et al.	N/A	N/A
2016/0053692	12/2015	Izquierdo	N/A	N/A
2016/0090863	12/2015	Diaz et al.	N/A	N/A
2016/0160647	12/2015	Hofer et al.	N/A	N/A
2016/0230658	12/2015	Hanlon et al.	N/A	N/A
2016/0298550	12/2015	Kupratis et al.	N/A	N/A
2016/0333734	12/2015	Bowden et al.	N/A	N/A
2016/0347463	12/2015	Negulescu	N/A	N/A
2017/0051678	12/2016	Becker, Jr.	N/A	N/A
2017/0051680	12/2016	Becker, Jr. et al.	N/A	N/A
2017/0102006	12/2016	Miller et al.	N/A	N/A
2017/0114721	12/2016	Miller et al.	N/A	N/A
2017/0167382	12/2016	Miller et al.	N/A	N/A
2017/0184027	12/2016	Moniz et al.	N/A	N/A
2017/0198719	12/2016	Cerny et al.	N/A	N/A
2018/0065727	12/2017	Gruber et al.	N/A	N/A
2018/0118364	12/2017	Golshany et al.	N/A	N/A
2018/0215475	12/2017	Hurt et al.	N/A	N/A
2018/0283795	12/2017	Cerny et al.	N/A	N/A
2019/0136710	12/2018	Breeze-Stringfellow et al.	N/A	N/A
2019/0153952	12/2018	Niergarth et al.	N/A	N/A
2019/0153953	12/2018	Niergarth et al.	N/A	N/A
2019/0218971	12/2018	Niergarth et al.	N/A	N/A
2019/0249599	12/2018	Sen et al.	N/A	N/A
2019/0257247	12/2018	Pal et al.	N/A	N/A
2019/0360401	12/2018	Rambo et al.	N/A	N/A
2020/0025109	12/2019	Stieger et al.	N/A	N/A
2020/0095939	12/2019	Epstein	N/A	N/A
2020/0116104	12/2019	Levisse et al.	N/A	N/A
2020/0332718	12/2019	Rambo	N/A	N/A
2021/0108573	12/2020	Sibbach et al.	N/A	N/A
2021/0108595	12/2020	Khalid et al.	N/A	N/A

2021/0108597	12/2020	Ostdiek et al.	N/A	N/A
2022/0042463	12/2021	Molesini et al.	N/A	N/A
2022/0056811	12/2021	Molesini et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1204005	12/1998	CN	N/A
101657607	12/2009	CN	N/A
1081277	12/1959	DE	N/A
0385913	12/1989	EP	N/A
0887259	12/1997	EP	N/A
1493900	12/2004	EP	N/A
1988274	12/2007	EP	N/A
2540989	12/2012	EP	N/A
2562082	12/2012	EP	N/A
3093443	12/2015	EP	N/A
2100799	12/1982	GB	N/A
2196390	12/1987	GB	N/A
2461811	12/2009	GB	N/A
H0370698	12/1990	JP	N/A
2006123880	12/2005	JP	N/A
2009508748	12/2008	JP	N/A
2011527263	12/2010	JP	N/A
101179277	12/2011	KR	N/A
WO2004/033295	12/2003	WO	N/A
WO2005/111413	12/2004	WO	N/A
WO2011/020458	12/2010	WO	N/A
WO2011/094477	12/2010	WO	N/A
WO2011/107320	12/2010	WO	N/A
WO2014/143248	12/2013	WO	N/A

OTHER PUBLICATIONS

Crigler, Application of Theodorsen's Theory to Propeller Design, NACA (National Advisory Committee for Aeronautics) Report 924, 1948, pp. 83-99. cited by applicant

Naveen et al., CFD Analysis of Low Pressure Turbine Blade Using Vortex Generator Jets, Proceedings of 7.SUP.th .International Conference on Intelligent Systems and Control (ISCO 2013) IEEE Explore, Coimbatore, Tamil Nadu, India, Jan. 4-5, 2013, pp. 541-544.
<https://ieeexplore.ieee.org/document/6481213>. cited by applicant

Smith Jr, Unducted Fan Aerodynamic Design, Journal of Turbomachinery, vol. 109, Jul. 1987, pp. 313-324. cited by applicant

Theodorsen, Theory of Propellers, Wartime Report, NACA (National Advisory Committee for Aeronautics), Aug. 1944, pp. 1-53. cited by applicant

Yamamoto et al., Numerical Calculation of Propfan/Swirl Recovery Vane Flow Field, AIAA-92-3771, AIAA//SAE//ASME//ASEE 28th Joint Propulsion Conference And Exhibit, Jul. 6-8, 1992, Nashville TN, pp. 1-9. cited by applicant

Primary Examiner: Sutherland; Steven M

Attorney, Agent or Firm: Dority & Manning, P.A.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation in part application of U.S. application Ser. No. 18/675,270, filed May 28, 2024, which is a continuation application of U.S. application Ser. No. 17/879,384 filed Aug. 2, 2022. Each of these applications is hereby incorporated by reference in their entireties.

FIELD

(1) The present disclosure relates to a gas turbine engine with a third stream.

BACKGROUND

(2) A gas turbine engine typically includes a fan and a turbomachine. The turbomachine generally includes an inlet, one or more compressors, a combustor, and at least one turbine. The compressors compress air which is channeled to the combustor where it is mixed with fuel. The mixture is then ignited for generating hot combustion gases. The combustion gases are channeled to the turbine(s) which extracts energy from the combustion gases for powering the compressor(s), as well as for producing useful work to propel an aircraft in flight. The turbomachine is mechanically coupled to the fan for driving the fan during operation.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) A full and enabling disclosure of the present disclosure, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:
- (2) FIG. 1 is a schematic cross-sectional view of a three-stream engine in accordance with an exemplary embodiment of the present disclosure.
- (3) FIG. 2 is a close-up, schematic view of the exemplary three-stream engine of FIG. 1.
- (4) FIG. 3 is a close-up view of an area surrounding a leading edge of a core cowl of the exemplary three-stream engine of FIG. 2.
- (5) FIGS. 4A through 4H are tables depicting numerical values showing the relationships between various parameters in accordance with various example embodiments of the present disclosure.
- (6) FIGS. 5A through 5D are graphs depicting a range of thrust to power airflow ratios and core bypass ratios in accordance with various example embodiments of the present disclosure.
- (7) FIG. 6 is a schematic view of a turboprop engine in accordance with an exemplary aspect of the present disclosure.
- (8) FIG. 7 is a schematic view of a direct drive, ducted, turbofan engine in accordance with an exemplary aspect of the present disclosure.
- (9) FIG. 8 is a schematic view of a geared, ducted, turbofan engine in accordance with an exemplary aspect of the present disclosure.
- (10) FIG. 9 is a schematic view of a geared, ducted, turbofan engine in accordance with another exemplary aspect of the present disclosure.
- (11) FIG. 10 is a schematic view of an unducted gas turbine engine in accordance with another exemplary aspect of the present disclosure.
- (12) FIG. 11 is a schematic view of an unducted gas turbine engine in accordance with yet another exemplary aspect of the present disclosure.
- (13) FIG. 12 is a schematic view of an unducted gas turbine engine in accordance with still another exemplary aspect of the present disclosure.

DETAILED DESCRIPTION

- (14) Reference will now be made in detail to present embodiments of the disclosure, one or more

examples of which are illustrated in the accompanying drawings. The detailed description uses numerical and letter designations to refer to features in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar parts of the disclosure.

(15) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations. Additionally, unless specifically identified otherwise, all embodiments described herein should be considered exemplary.

(16) As used herein, the terms “first”, “second”, and “third” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.

(17) The terms “forward” and “aft” refer to relative positions within a gas turbine engine or vehicle, and refer to the normal operational attitude of the gas turbine engine or vehicle. For example, with regard to a gas turbine engine, forward refers to a position closer to an engine inlet and aft refers to a position closer to an engine nozzle or exhaust.

(18) The terms “upstream” and “downstream” refer to the relative direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(19) The terms “coupled,” “fixed,” “attached to,” and the like refer to both direct coupling, fixing, or attaching, as well as indirect coupling, fixing, or attaching through one or more intermediate components or features, unless otherwise specified herein.

(20) The singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise.

(21) The phrases “from X to Y” and “between X and Y” each refers to a range of values inclusive of the endpoints (i.e., refers to a range of values that includes both X and Y).

(22) A “third stream” as used herein means a non-primary air stream capable of increasing fluid energy to produce a minority of total propulsion system thrust. A pressure ratio of the third stream may be higher than that of the primary propulsion stream (e.g., a bypass or propeller driven propulsion stream). The thrust may be produced through a dedicated nozzle or through mixing of an airflow through the third stream with a primary propulsion stream or a core air stream, e.g., into a common nozzle.

(23) In certain exemplary embodiments an operating temperature of the airflow through the third stream may be less than a maximum compressor discharge temperature for the engine, and more specifically may be less than 350 degrees Fahrenheit (such as less than 300 degrees Fahrenheit, such as less than 250 degrees Fahrenheit, such as less than 200 degrees Fahrenheit, and at least as great as an ambient temperature). In certain exemplary embodiments these operating temperatures may facilitate heat transfer to or from the airflow through the third stream and a separate fluid stream. Further, in certain exemplary embodiments, the airflow through the third stream may contribute less than 50% of the total engine thrust (and at least, e.g., 2% of the total engine thrust) at a takeoff condition, or more particularly while operating at a rated takeoff power at sea level, static flight speed, 86 degrees Fahrenheit ambient temperature operating conditions.

(24) Furthermore in certain exemplary embodiments, aspects of the airflow through the third stream (e.g., airstream, mixing, or exhaust properties), and thereby the aforementioned exemplary percent contribution to total thrust, may passively adjust during engine operation or be modified purposefully through use of engine control features (such as fuel flow, electric machine power, variable stators, variable inlet guide vanes, valves, variable exhaust geometry, or fluidic features) to adjust or optimize overall system performance across a broad range of potential operating conditions.

(25) The term “bypass passage” refers generally to a passage with an airflow from a fan of the gas turbine engine that flows over an upstream-most inlet to a turbomachine of the gas turbine engine.

In a ducted gas turbine engine, the bypass passage is the passage defined between an outer nacelle (surrounding the fan of the gas turbine engine) and one or more cowls inward of the outer nacelle (e.g., a fan cowl, a core cowl or both if both are present; see, e.g., FIGS. 7 through 9). In an unducted gas turbine engine, the bypass passage refers to an open sided passage (i.e., not explicitly defined by structure such as an outer nacelle) where airflow from the fan passes over an upstream-most inlet to the turbomachine (e.g., inlet **182** to inlet duct **180** in FIGS. 1 and 2), defined at least in part by a primary fan outer fan area, which refers to an area defined by an annulus representing a portion of the fan located outward of an inlet splitter at the upstream-most inlet to the turbomachine (e.g., inlet splitter **196** of the fan cowl **170** in the embodiment of FIGS. 1 and 2). An airflow through the bypass passage of a ducted or an unducted engine refers to all of the airflow from the fan that is not provided through the upstream-most inlet to the turbomachine.

(26) The term “disk loading” refers to an average pressure change across a plurality of rotor blades of a rotor assembly, such as the average pressure change across a plurality of fan blades of a fan.

(27) The term “rated speed” refers to an operating condition of an engine whereby the engine is operating in the maximum, full load operating condition that is rated by the manufacturer. For example, in an engine certified by the Federal Aviation Administration (“FAA”), the rated speed refers to a rotation speed of the engine during the highest sustainable and continuous power operation in the certification documents, such as a rotational speed of the gas turbine engine when operating under a maximum continuous operation.

(28) The term “standard day operating condition” refers to ambient conditions of sea level altitude, 59 degrees Fahrenheit, and 60 percent relative humidity.

(29) The term “propulsive efficiency” refers to an efficiency with which the energy contained in an engine's fuel is converted into kinetic energy for the vehicle incorporating the engine, to accelerate it, or to replace losses due to aerodynamic drag or gravity.

(30) Generally, an aeronautical gas turbine engine includes a fan to provide a desired amount of thrust without overloading the fan blades (i.e., without increasing a disk loading of the fan blades of the fan beyond a certain threshold), and therefore to maintain a desired overall propulsive efficiency for the gas turbine engine. Conventional gas turbine engine design practice has been to provide an outer nacelle surrounding the fan to provide relatively efficient thrust for the gas turbine engine. Such a configuration, sometimes referred to as a turbofan engine configuration, may generally limit a permissible size of the fan (i.e., a diameter of the fan). However, the inventors of the present disclosure have found that gas turbine engine design is now driving the diameter of the fan higher to provide as much thrust for the gas turbine engine as possible from the fan to improve an overall propulsive efficiency of the gas turbine engine.

(31) By increasing the fan diameter, an installation of the gas turbine engine becomes more difficult. In addition, if an outer nacelle is maintained, the outer nacelle may become weight prohibitive with some larger diameter fans. Further, as the need for gas turbine engines to provide more thrust continues, the thermal demands on the gas turbine engines correspondingly increases.

(32) The inventors of the present disclosure found that for a three stream gas turbine engine having a primary fan and a secondary fan, with the secondary fan being a ducted fan providing an airflow to a third stream of the gas turbine engine, an overall propulsive efficiency of the gas turbine engine that results from providing a high diameter fan may be maintained at a high level, while reducing the size of the primary fan. Such a configuration may maintain a desired overall propulsive efficiency for the gas turbine engine, or unexpectedly may in fact increase the overall propulsive efficiency of the gas turbine engine.

(33) The inventors proceeded in the manner of designing a gas turbine engine with given primary fan characteristics, secondary fan characteristics, and turbomachine characteristics; checking the propulsive efficiency of the designed gas turbine engine; redesigning the gas turbine engine with varying primary fan, secondary fan, and turbomachine characteristics; rechecking the propulsive efficiency of the redesigned gas turbine engine; etc. during the design of several different types of

gas turbine engines, including the gas turbine engines described below with reference to FIGS. **1** and **6** through **10**. During the course of this practice of studying/evaluating various primary fan characteristics, secondary fan characteristics, and turbomachine characteristics considered feasible for best satisfying mission requirements, it was discovered that certain relationships exist between a ratio of an airflow through the bypass passage and the third stream to an airflow through a core duct (referred to hereinbelow as a thrust to power airflow ratio), as well as between a ratio of an airflow through the third stream to the airflow through the core duct (referred to hereinbelow as a core bypass ratio). In particular, the inventors of the present disclosure have found that these ratios can be thought of as an indicator of the ability of a gas turbine engine to maintain or even improve upon a desired propulsive efficiency via the third stream and, additionally, indicating an improvement in the gas turbine engine's packaging concerns and weight concerns, and thermal management capabilities.

(34) Referring now to FIG. **1**, a schematic cross-sectional view of a gas turbine engine **100** is provided according to an example embodiment of the present disclosure. Particularly, FIG. **1** provides a gas turbine engine having a rotor assembly with a single stage of unducted rotor blades. In such a manner, the rotor assembly may be referred to herein as an “unducted fan,” or the entire engine **100** may be referred to as an “unducted gas turbine engine.” In addition, the engine **100** of FIG. **1** includes a third stream extending from the compressor section to a rotor assembly flowpath over the turbomachine, as will be explained in more detail below.

(35) For reference, the engine **100** defines an axial direction A, a radial direction R, and a circumferential direction C. Moreover, the engine **100** defines an axial centerline or longitudinal axis **112** that extends along the axial direction A. In general, the axial direction A extends parallel to the longitudinal axis **112**, the radial direction R extends outward from and inward to the longitudinal axis **112** in a direction orthogonal to the axial direction A, and the circumferential direction extends three hundred sixty degrees (360°) around the longitudinal axis **112**. The engine **100** extends between a forward end **114** and an aft end **116**, e.g., along the axial direction A.

(36) The engine **100** includes a turbomachine **120** and a rotor assembly, also referred to a fan section **150**, positioned upstream thereof. Generally, the turbomachine **120** includes, in serial flow order, a compressor section, a combustion section, a turbine section, and an exhaust section. Particularly, as shown in FIG. **1**, the turbomachine **120** includes a core cowl **122** that defines an annular core inlet **124**. The core cowl **122** further encloses at least in part a low pressure system and a high pressure system. For example, the core cowl **122** depicted encloses and supports at least in part a booster or low pressure (“LP”) compressor **126** for pressurizing the air that enters the turbomachine **120** through core inlet **124**. A high pressure (“HP”), multi-stage, axial-flow compressor **128** receives pressurized air from the LP compressor **126** and further increases the pressure of the air. The pressurized air stream flows downstream to a combustor **130** of the combustion section where fuel is injected into the pressurized air stream and ignited to raise the temperature and energy level of the pressurized air.

(37) It will be appreciated that as used herein, the terms “high/low speed” and “high/low pressure” are used with respect to the high pressure/high speed system and low pressure/low speed system interchangeably. Further, it will be appreciated that the terms “high” and “low” are used in this same context to distinguish the two systems, and are not meant to imply any absolute speed and/or pressure values.

(38) The high energy combustion products flow from the combustor **130** downstream to a high pressure turbine **132**. The high pressure turbine **132** drives the high pressure compressor **128** through a high pressure shaft **136**. In this regard, the high pressure turbine **132** is drivingly coupled with the high pressure compressor **128**. As will be appreciated, the high pressure compressor **128**, the combustor **130**, and the high pressure turbine **132** may collectively be referred to as the “core” of the engine **100**. The high energy combustion products then flow to a low pressure turbine **134**. The low pressure turbine **134** drives the low pressure compressor **126** and components of the fan

section **150** through a low pressure shaft **138**. In this regard, the low pressure turbine **134** is drivingly coupled with the low pressure compressor **126** and components of the fan section **150**. The LP shaft **138** is coaxial with the HP shaft **136** in this example embodiment. After driving each of the turbines **132**, **134**, the combustion products exit the turbomachine **120** through a turbomachine exhaust nozzle **140**.

(39) Accordingly, the turbomachine **120** defines a working gas flowpath or core duct **142** that extends between the core inlet **124** and the turbomachine exhaust nozzle **140**. The core duct **142** is an annular duct positioned generally inward of the core cowl **122** along the radial direction R. The core duct **142** (e.g., the working gas flowpath through the turbomachine **120**) may be referred to as a second stream.

(40) The fan section **150** includes a fan **152**, which is the primary fan in this example embodiment. For the depicted embodiment of FIG. 1, the fan **152** is an open rotor or unducted fan **152**. In such a manner, the engine **100** may be referred to as an open rotor engine.

(41) As depicted, the fan **152** includes an array of fan blades **154** (only one shown in FIG. 1). The fan blades **154** are rotatable, e.g., about the longitudinal axis **112**. As noted above, the fan **152** is drivingly coupled with the low pressure turbine **134** via the LP shaft **138**. For the embodiments shown in FIG. 1, the fan **152** is coupled with the LP shaft **138** via a speed reduction gearbox **155**, e.g., in an indirect-drive or geared-drive configuration.

(42) Moreover, the array of fan blades **154** can be arranged in equal spacing around the longitudinal axis **112**. Each fan blade **154** has a root and a tip and a span defined therebetween. Further, each fan blade **154** defines a fan blade tip radius $R_{sub.1}$ along the radial direction R from the longitudinal axis **112** to the tip, and a hub radius (or inner radius) $R_{sub.2}$ along the radial direction R from the longitudinal axis **112** to the base of each fan blade **154** (i.e., from the longitudinal axis **112** to a radial location where each fan blade **154** meets a front hub of the gas turbine engine **100** at a leading edge of the respective fan blade **154**). As will be appreciated, a distance from the base of each fan blade **154** to a tip of the respective fan blade **154** is referred to as a span of the respective fan blade **154**. Further, the fan **152**, or rather each fan blade **154** of the fan **152**, defines a fan radius ratio, R_{qR} , equal to $R_{sub.2}$ divided by $R_{sub.1}$. As the fan **152** is the primary fan of the engine **100**, the fan radius ratio, R_{qR} , of the fan **152** may be referred to as the primary fan radius ratio, $R_{qR.sub.Prim.-Fan}$.

(43) Moreover, each fan blade **154** defines a central blade axis **156**. For this embodiment, each fan blade **154** of the fan **152** is rotatable about their respective central blade axis **156**, e.g., in unison with one another. One or more actuators **158** are provided to facilitate such rotation and therefore may be used to change a pitch of the fan blades **154** about their respective central blades' axes **156**.

(44) The fan section **150** further includes a fan guide vane array **160** that includes fan guide vanes **162** (only one shown in FIG. 1) disposed around the longitudinal axis **112**. For this embodiment, the fan guide vanes **162** are not rotatable about the longitudinal axis **112**. Each fan guide vane **162** has a root and a tip and a span defined therebetween. The fan guide vanes **162** may be unshrouded as shown in FIG. 1 or, alternatively, may be shrouded, e.g., by an annular shroud spaced outward from the tips of the fan guide vanes **162** along the radial direction R or attached to the fan guide vanes **162**.

(45) Each fan guide vane **162** defines a central blade axis **164**. For this embodiment, each fan guide vane **162** of the fan guide vane array **160** is rotatable about its respective central blade axis **164**, e.g., in unison with one another. One or more actuators **166** are provided to facilitate such rotation and therefore may be used to change a pitch of the fan guide vane **162** about its respective central blade axis **164**. However, in other embodiments, each fan guide vane **162** may be fixed or unable to be pitched about its central blade axis **164**. The fan guide vanes **162** are mounted to a fan cowl **170**.

(46) As shown in FIG. 1, in addition to the fan **152**, which is unducted, a ducted fan **184** is included aft of the fan **152**, such that the engine **100** includes both a ducted and an unducted fan which both serve to generate thrust through the movement of air without passage through at least a portion of

the turbomachine **120** (e.g., without passage through the HP compressor **128** and combustion section for the embodiment depicted). The ducted fan **184** is rotatable about the same axis (e.g., the longitudinal axis **112**) as the fan blade **154**. The ducted fan **184** is, for the embodiment depicted, driven by the low pressure turbine **134** (e.g. coupled to the LP shaft **138**). In the embodiment depicted, as noted above, the fan **152** may be referred to as the primary fan, and the ducted fan **184** may be referred to as a secondary fan. It will be appreciated that these terms “primary” and “secondary” are terms of convenience, and do not imply any particular importance, power, or the like.

(47) The ducted fan **184** includes a plurality of fan blades (not separately labeled in FIG. **1**; see fan blades **185** labeled in FIG. **2**) arranged in a single stage, such that the ducted fan **184** may be referred to as a single stage fan. The fan blades of the ducted fan **184** can be arranged in equal spacing around the longitudinal axis **112**. Each blade of the ducted fan **184** has a root and a tip and a span defined therebetween. Further, each fan blade of the ducted fan **184** defines a fan blade tip radius $R_{sub.3}$ along the radial direction R from the longitudinal axis **112** to the tip, and a hub radius (or inner radius) $R_{sub.4}$ along the radial direction R from the longitudinal axis **112** to the base of the respective fan blades of the ducted fan **184** (i.e., a location where the respective fan blades of the ducted fan **184** meet an inner flowpath liner at a leading edge of the respective fan blades of the ducted fan **184**). As will be appreciated, a distance from the base of each fan blade of the ducted fan **184** to a tip of the respective fan blade is referred to as a span of the respective fan blade. Further, the ducted fan **184**, or rather each fan blade of the ducted fan **184**, defines a fan radius ratio, R_qR , equal to $R_{sub.4}$ divided by $R_{sub.3}$. As the ducted fan **184** is the secondary fan of the engine **100**, the fan radius ratio, R_qR , of the ducted fan **184** may be referred to as the secondary fan radius ratio, $R_qR_{sub.Sec.-Fan}$.

(48) The fan cowl **170** annularly encases at least a portion of the core cowl **122** and is generally positioned outward of at least a portion of the core cowl **122** along the radial direction R . Particularly, a downstream section of the fan cowl **170** extends over a forward portion of the core cowl **122** to define a fan duct flowpath, or simply a fan duct **172**. According to this embodiment, the fan flowpath or fan duct **172** may be understood as forming at least a portion of the third stream of the engine **100**.

(49) Incoming air may enter through the fan duct **172** through a fan duct inlet **176** and may exit through a fan exhaust nozzle **178** to produce propulsive thrust. The fan duct **172** is an annular duct positioned generally outward of the core duct **142** along the radial direction R . The fan cowl **170** and the core cowl **122** are connected together and supported by a plurality of substantially radially-extending, circumferentially-spaced stationary struts **174** (only one shown in FIG. **1**). The stationary struts **174** may each be aerodynamically contoured to direct air flowing thereby. Other struts in addition to the stationary struts **174** may be used to connect and support the fan cowl **170** and/or core cowl **122**. In many embodiments, the fan duct **172** and the core duct **142** may at least partially co-extend (generally axially) on opposite sides (e.g., opposite radial sides) of the core cowl **122**. For example, the fan duct **172** and the core duct **142** may each extend directly from a leading edge **144** of the core cowl **122** and may partially co-extend generally axially on opposite radial sides of the core cowl **122**.

(50) The engine **100** also defines or includes an inlet duct **180**. The inlet duct **180** extends between an engine inlet **182** and the core inlet **124**/fan duct inlet **176**. The engine inlet **182** is defined generally at the forward end of the fan cowl **170** and is positioned between the fan **152** and the fan guide vane array **160** along the axial direction A . The inlet duct **180** is an annular duct that is positioned inward of the fan cowl **170** along the radial direction R . Air flowing downstream along the inlet duct **180** is split, not necessarily evenly, into the core duct **142** and the fan duct **172** by a fan duct splitter or leading edge **144** of the core cowl **122**. The inlet duct **180** is wider than the core duct **142** along the radial direction R . The inlet duct **180** is also wider than the fan duct **172** along the radial direction R . The secondary fan **184** is positioned at least partially in the inlet duct **180**.

(51) Notably, for the embodiment depicted, the engine **100** includes one or more features to increase an efficiency of a third stream thrust, $F_{n.sub.3S}$ (e.g., a thrust generated by an airflow through the fan duct **172** exiting through the fan exhaust nozzle **178**, generated at least in part by the ducted fan **184**). In particular, the engine **100** further includes an array of inlet guide vanes **186** positioned in the inlet duct **180** upstream of the ducted fan **184** and downstream of the engine inlet **182**. The array of inlet guide vanes **186** are arranged around the longitudinal axis **112**. For this embodiment, the inlet guide vanes **186** are not rotatable about the longitudinal axis **112**. Each inlet guide vanes **186** defines a central blade axis (not labeled for clarity), and is rotatable about its respective central blade axis, e.g., in unison with one another. In such a manner, the inlet guide vanes **186** may be considered a variable geometry component. One or more actuators **188** are provided to facilitate such rotation and therefore may be used to change a pitch of the inlet guide vanes **186** about their respective central blade axes. However, in other embodiments, each inlet guide vanes **186** may be fixed or unable to be pitched about its central blade axis.

(52) Further, located downstream of the ducted fan **184** and upstream of the fan duct inlet **176**, the engine **100** includes an array of outlet guide vanes **190**. As with the array of inlet guide vanes **186**, the array of outlet guide vanes **190** are not rotatable about the longitudinal axis **112**. However, for the embodiment depicted, unlike the array of inlet guide vanes **186**, the array of outlet guide vanes **190** are configured as fixed-pitch outlet guide vanes.

(53) Further, it will be appreciated that for the embodiment depicted, the fan exhaust nozzle **178** of the fan duct **172** is further configured as a variable geometry exhaust nozzle. In such a manner, the engine **100** includes one or more actuators **192** for modulating the variable geometry exhaust nozzle. For example, the variable geometry exhaust nozzle may be configured to vary a total cross-sectional area (e.g., an area of the nozzle in a plane perpendicular to the longitudinal axis **112**) to modulate an amount of thrust generated based on one or more engine operating conditions (e.g., temperature, pressure, mass flowrate, etc. of an airflow through the fan duct **172**). A fixed geometry exhaust nozzle may also be adopted.

(54) The combination of the array of inlet guide vanes **186** located upstream of the ducted fan **184**, the array of outlet guide vanes **190** located downstream of the ducted fan **184**, and the fan exhaust nozzle **178** may result in a more efficient generation of third stream thrust, $F_{n.sub.3S}$, during one or more engine operating conditions. Further, by introducing a variability in the geometry of the inlet guide vanes **186** and the fan exhaust nozzle **178**, the engine **100** may be capable of generating more efficient third stream thrust, $F_{n.sub.3S}$, across a relatively wide array of engine operating conditions, including takeoff and climb (where a maximum total engine thrust $F_{n.sub.Total}$, is generally needed) as well as cruise (where a lesser amount of total engine thrust, $F_{n.sub.Total}$, is generally needed).

(55) Moreover, referring still to FIG. **1**, in exemplary embodiments, air passing through the fan duct **172** may be relatively cooler (e.g., lower temperature) than one or more fluids utilized in the turbomachine **120**. In this way, one or more heat exchangers **200** may be positioned in thermal communication with the fan duct **172**. For example, one or more heat exchangers **200** may be disposed within the fan duct **172** and utilized to cool one or more fluids from the core engine with the air passing through the fan duct **172**, as a resource for removing heat from a fluid, e.g., compressor bleed air, oil or fuel.

(56) Although not depicted, the heat exchanger **200** may be an annular heat exchanger extending substantially 360 degrees in the fan duct **172** (e.g., at least 300 degrees, such as at least 330 degrees). In such a manner, the heat exchanger **200** may effectively utilize the air passing through the fan duct **172** to cool one or more systems of the engine **100** (e.g., lubrication oil systems, compressor bleed air, electrical components, etc.). The heat exchanger **200** uses the air passing through duct **172** as a heat sink and correspondingly increases the temperature of the air downstream of the heat exchanger **200** and exiting the fan exhaust nozzle **178**.

(57) Referring now to FIG. **2**, a close-up, simplified, schematic view of the gas turbine engine **100**

of FIG. 1 is provided. The gas turbine engine **100**, as noted above includes a primary fan, or rather fan **152** having fan blades **154**, and a secondary fan, or rather ducted fan **184** having fan blades **185**. Airflow from the fan **152** is split between a bypass region **194** (as defined below) and the inlet duct **180** by an inlet splitter **196**. Airflow from the ducted fan **184** is split between the fan duct **172** and the core duct **142** by the leading edge **144** (sometimes also referred to as a fan duct splitter).

(58) The exemplary gas turbine engine **100** depicted in FIG. 2 further defines a primary fan outer fan area, A.sub.P_Out, a primary fan inner fan area, A.sub.P_In, a secondary fan outer fan area, A.sub.S_Out, and a secondary fan inner fan area, A.sub.S_In.

(59) The primary fan outer fan area, A.sub.P_Out, refers to an area defined by an annulus representing a portion of the fan **152** located outward of the inlet splitter **196** of the fan cowl **170**. In particular, the gas turbine engine **100** further defines a fan cowl splitter radius, R.sub.5. The fan cowl splitter radius, R.sub.5, is defined along the radial direction R from the longitudinal axis **112** to the inlet splitter **196**. The primary fan outer fan area, A.sub.P_Out, refers to an area defined by the formula: $\pi R_{\text{sub.1}}^2 - \pi R_{\text{sub.5}}^2$.

(60) The primary fan inner fan area, A.sub.P_In, refers to an area defined by an annulus representing a portion of the fan **152** located inward of the inlet splitter **196** of the fan cowl **170**. In particular, the gas turbine engine **100** further defines an engine inlet inner radius, R.sub.6. The engine inlet inner radius, R.sub.6, is defined along the radial direction R from the longitudinal axis **112** to an inner casing defining the engine inlet **182** directly inward along the radial direction R from the inlet splitter **196**. The primary fan inner fan area, A.sub.P_In, refers to an area defined by the formula: $\pi R_{\text{sub.5}}^2 - \pi R_{\text{sub.6}}^2$.

(61) The secondary fan outer fan area, A.sub.S_Out, refers to an area representing a portion of an airflow from the ducted fan **184** that is provided to the fan duct **172**. In particular, the leading edge **144** defines a leading edge radius, R.sub.7, and the gas turbine engine **100** defines an effective fan duct inlet outer radius, R.sub.8 (see FIG. 3). The leading edge radius, R.sub.7, is defined along the radial direction R from the longitudinal axis **112** to the leading edge **144**.

(62) Referring briefly to FIG. 3, providing a close-up view of an area surrounding the leading edge **144**, the fan duct **172** defines a cross-wise height **198** measured from the leading edge **144** to the fan cowl **170** in a direction perpendicular to a mean flow direction **204** of an airflow through a forward 10% of the fan duct **172**. An angle **206** is defined by the mean flow direction **204** relative to a reference line **208** extending parallel to the longitudinal axis **112**. The angle **206** is referred to as θ . In certain embodiments, the angle **206** may be between 5 degrees and 80 degrees, such as between 10 degrees and 60 degrees (an increased angle is a counterclockwise rotation in FIG. 3). The effective fan duct inlet outer radius, R.sub.8, is defined along the radial direction R from the longitudinal axis **112** to where the cross-wise height **198** meets the fan cowl **170**. The secondary fan outer fan area, A.sub.S_Out, refers to an area defined by the formula:

(63)
$$\frac{(R_8^2 - R_7^2)}{\cos(\theta)}$$
.

(64) Referring back to FIG. 2, the secondary fan inner fan area, A.sub.S_In, refers to an area defined by an annulus representing a portion of the ducted fan **184** located inward of the leading edge **144** of the core cowl **122**. In particular, the gas turbine engine **100** further defines a core inlet inner radius, R.sub.9. The core inlet inner radius, R.sub.9, is defined along the radial direction R from the longitudinal axis **112** to an inner casing defining the core inlet **124** directly inward along the radial direction R from the leading edge **144**. The secondary fan inner fan area, A.sub.S_In, refers to an area defined by the formula: $\pi R_{\text{sub.7}}^2 - \pi R_{\text{sub.9}}^2$.

(65) The primary fan outer fan area, A.sub.P_Out, the primary fan inner fan area, A.sub.P_In, the secondary fan outer fan area, A.sub.S_Out, and the secondary fan inner fan area, A.sub.S_In, may be used in defining various airflow ratios for the engine **100**. In particular, it will be appreciated that the exemplary engine **100** of FIGS. 1 through 3 further defines a thrust to power airflow ratio and a core bypass ratio, which as discussed herein are used to define an engine in accordance with

the present disclosure. The thrust to power airflow ratio is a ratio of an airflow through the bypass passage of the engine **100** and through the fan duct **172** to an airflow through the core duct **142**. The bypass passage (not separately labeled) is located within the bypass region **194** and refers to a passage where airflow from the fan **152** passes over the inlet duct **180**. Further, the core bypass ratio is a ratio of an airflow through the fan duct **172** to the airflow through the core duct **142**. These ratios are calculated while the engine **100** is operating at a rated speed during standard day operating conditions, and the amounts of airflow used to calculate these ratios are each expressed as a mass flowrate in the same units (mass per unit time).

(66) More specifically, the amount of airflow through the engine's bypass passage can be determined using a fan pressure ratio for the fan **152**, a rotational speed of the fan **152**, or both while the engine is operating at the rated speed during standard day operating conditions, and the primary fan outer fan area, $A_{sub.P_Out}$. The amount of airflow through the inlet duct **180** can be determined using a fan pressure ratio for the fan **152**, a rotational speed of the fan **152**, or both while operating at a rated speed during standard day operating conditions, and the primary fan inner fan area, $A_{sub.P_In}$. The amount of airflow through the fan duct **172** and the amount of airflow through the core duct **142** can be determined based on the amount of airflow through the inlet duct **180** while the engine is operating at the rated speed during standard day operating conditions; a fan pressure ratio, a rotational speed, or both of the ducted fan **184** while the engine is operating at the rated speed during standard day operating conditions; and the secondary fan outer fan area, $A_{sub.S_Out}$, and the secondary fan inner fan area, $A_{sub.S_In}$.

(67) As alluded to earlier, the inventors discovered, unexpectedly during the course of gas turbine engine design—i.e., designing gas turbine engines (e.g., both ducted and unducted gas turbine engines and turboprop engines) having a variety of different primary fan and secondary fan characteristics—and evaluating an overall propulsive efficiency, significant relationships exist in a ratio of an airflow through a bypass passage and through a third stream to an airflow through a core duct (referred to herein as a thrust to power airflow ratio), as well as in a ratio of an airflow through the third stream to the airflow through the core duct (referred to herein as a core bypass ratio). These relationships can be thought of as an indicator of the ability of a gas turbine engine to maintain or even improve upon a desired propulsive efficiency via the third stream and, additionally, indicating an improvement in the gas turbine engine's packaging concerns and weight concerns, and thermal management capabilities.

(68) As will be appreciated, it may generally be desirable to increase a fan diameter in order to provide a higher thrust to power airflow ratio, which typically correlates to a higher overall propulsive efficiency. However, increasing the fan diameter too much may actually result in a decrease in propulsive efficiency at higher speeds due to a drag from the fan blades. Further, increasing the fan diameter too much may also create prohibitively heavy fan blades, creating installation problems due to the resulting forces on the supporting structure (e.g., frames, pylons, etc.), exacerbated by a need to space the engine having such fan blades further from a mounting location on the aircraft to allow the engine to fit, e.g., under/over the wing, adjacent to the fuselage, etc.

(69) Similarly, it may generally be desirable to increase an airflow through the fan duct relative to the core duct in order to provide a higher core bypass ratio, as such may also generally correlate to a higher overall propulsive efficiency. Notably, however, the higher the core bypass ratio, the less airflow provided to the core of the gas turbine engine. For a given amount of power needed to drive, e.g., a primary fan and a secondary fan of the gas turbine engine, if less airflow is provided, either a maximum temperature of the core needs to be increased or a size of the primary fan or secondary fan needs to be decreased. Such a result can lead to either premature wear of the core or a reduction in propulsive efficiency of the gas turbine engine.

(70) As noted above, the inventors of the present disclosure discovered bounding the relationships defined by the thrust to power airflow ratio and core bypass ratio can result in a gas turbine engine

maintaining or even improving upon a desired propulsive efficiency, while also taking into account the gas turbine engine's packaging concerns and weight concerns, and also providing desired thermal management capabilities. The relationship discovered, infra, can identify an improved engine configuration suited for a particular mission requirement, one that takes into account installation, packaging and loading, thermal sink needs and other factors influencing the optimal choice for an engine configuration.

(71) In addition to yielding an improved gas turbine engine, as explained in detail above, utilizing this relationship, the inventors found that the number of suitable or feasible gas turbine engine designs incorporating a primary fan and a secondary fan, and defining a third stream, capable of meeting both the propulsive efficiency requirements and packaging, weight, and thermal sink requirements could be greatly diminished, thereby facilitating a more rapid down selection of designs to consider as a gas turbine engine is being developed. Such a benefit provides more insight to the requirements for a given gas turbine engine well before specific technologies, integration and system requirements are developed fully. Such a benefit avoids late-stage redesign.

(72) The desired relationships providing for the improved gas turbine engine, discovered by the inventors, are expressed as:

(73) $TPAR = (A_B + A_{3S}) / A_C$ (1) $CBR = A_{3S} / A_C$ (2)

where TPAR is a thrust to power airflow ratio, CBR is a core bypass ratio, A_B is an airflow through a bypass passage of the gas turbine engine while the engine is operated at a rated speed during standard day operating conditions, A_{3S} is an airflow through a third stream of the gas turbine engine while the engine is operated at the rated speed during standard day operating conditions, and A_C is an airflow through a core of the gas turbine engine while the engine is operated at the rated speed during standard day operating conditions. The airflow through the core of the gas turbine engine may refer to an airflow through an upstream end of the core (e.g., an airflow through a first stage of a high pressure compressor of the core). A_B , A_{3S} , and A_C are each expressed as mass flowrate, with the same units as one another.

(74) Values for various parameters of the influencing characteristics of an engine defined by Expressions (1) and (2) are set forth below in TABLE 1:

(75) TABLE-US-00001 TABLE 1 Ranges appropriate for using Symbol Description Expression (1) R.sub.1/R.sub.3 Tip radius ratio 1.35 to 10, such as 2 to 7, such as 3 to 5, such as at least 3.5, such as at least 3.7, such as at least 4, such as up to 10, such as up to 7 RqR.sub.Sec.-Fan Secondary fan 0.2 to 0.9, such as 0.2 to 0.7, radius ratio such as 0.57 to 0.67 RqR.sub.Prim.-Fan Primary fan radius 0.2 to 0.4, such as 0.25 to 0.35 ratio TPAR Thrust to power 3.5 to 100, such as 4 to 75 airflow ratio (see also, TABLE 2, below) CBR Core Bypass Ratio 0.1 to 10, such as 0.3 to 5 (see also, TABLE 2, below)

(76) Referring now to FIGS. 4A through 4H and 5A through 5D, the relationships between the various parameters of Expressions (1) and (2) of exemplary gas turbine engines are illustrated in accordance with one or more exemplary embodiments of the present disclosure. In particular, FIGS. 4A through 4H provide a table including numerical values corresponding to several of the plotted gas turbine engines in FIGS. 5A through 5D. FIGS. 5A through 5D are plots of gas turbine engines in accordance with one or more exemplary embodiments of the present disclosure, showing the TPAR (Y-Axis) and the CBR (X-axis). FIGS. 5A through 5D highlight preferred subranges, including subranges for unducted engines, ducted engines, and turboprop engines, as discussed hereinbelow.

(77) Referring particularly to FIG. 5A, a first range 402 and a second range 404 are provided, and exemplary embodiments 406 are plotted. The exemplary embodiments 406 include a variety of gas turbine engine types in accordance with aspects of the present disclosure, including unducted gas turbine engines, ducted gas turbine engines (turbofan engines), and turboprop engines. The first range 402 corresponds to a TPAR between 3.5 and 100 and a CBR between 0.1 and 10. The first

range **402** captures the benefits of the present disclosure across the variety of engine types. The second range **404** corresponds to a TPAR between 14 and 75 and a CBR between 0.3 and 5. The second range **404** may provide more desirable TPAR and CBR relationships across the variety of engine types to achieve propulsive efficiency, while still providing packaging and weight benefits, thermal benefits, etc.

(78) Referring particularly to FIG. 5B, a third range **408** and a fourth range **410** are provided, and exemplary embodiments **412** are plotted. The exemplary embodiments **412** include a variety of unducted gas turbine engines in accordance with aspects of the present disclosure. In particular, the exemplary embodiments **412** include a variety of gas turbine engines having an unducted primary fan, similar to the exemplary embodiments described herein with reference to FIGS. **1** and **10**. The third range **408** corresponds to a TPAR between 30 and 56 and a CBR between 0.3 and 5. The third range **408** captures the benefits of the present disclosure for unducted gas turbine engines. The fourth range **410** corresponds to a TPAR between 35 and 50 and a CBR between 0.5 and 3. The fourth range **410** may provide more desirable TPAR and CBR relationships for the unducted gas turbine engines to achieve propulsive efficiency, while still providing packaging and weight benefits, thermal benefits, etc. As will be appreciated, the unducted gas turbine engines may have, on the whole, a higher TPAR as compared to the ducted gas turbine engines (see FIG. 5C), enabled by a lack of an outer nacelle or other casing surrounding a primary fan. The range of CBR values in the fourth range **410** isn't as large as the range of CBR values in the third range **408**, as in the embodiments with a higher TPAR, the CBR needs to be lower to provide a necessary amount of airflow to a core of the engine without exceeding temperature thresholds or requiring an undesired reduction in a size of the primary fan.

(79) The inventors of the present disclosure have found that the TPAR values and CBR values in the third and fourth ranges **408**, **410** shown may provide a desirable propulsive benefit, while still enabling operation of the core in a reasonable manner, and balancing installation and thermal load considerations.

(80) Referring particularly to FIG. 5C, a fifth range **414**, a sixth range **416**, a seventh range **417**, an eighth range **418**, a ninth range **419**, and a tenth range **420** are provided, and exemplary embodiments **421** are plotted. The exemplary embodiments **421** include a variety of ducted gas turbine engines in accordance with aspects of the present disclosure. In particular, the exemplary embodiments **421** include a variety of gas turbine engines having a ducted primary fan, similar to the exemplary embodiments described herein with reference to FIGS. **7** through **9**. The fifth range **414** corresponds to a TPAR between 3.5 and 40 and a CBR between 0.3 and 5. The fifth range **414** captures the benefits of the present disclosure for ducted gas turbine engines.

(81) The sixth range **416** corresponds to a TPAR between 3.5 and 20 and a CBR between 0.2 and 5. The sixth range **416** captures the benefits of the present disclosure for ducted gas turbine engines in a direct drive configuration (see, e.g., FIG. **7**). As will be appreciated, with a ducted, direct drive gas turbine engine a primary fan may be smaller, limiting a TPAR. The seventh range **417**, which also corresponds to ducted gas turbine engines in a direct drive configuration, corresponds to a TPAR between 6 and 15 and a CBR between 0.3 and 1.8, and may represent a more preferable range.

(82) The eighth range **418** corresponds to a TPAR between 8 and 40 and a CBR between 0.2 and 5. The eighth range **418** captures the benefits of the present disclosure for ducted gas turbine engines in a geared configuration (see, e.g., FIGS. **8** and **9**). As will be appreciated, with a ducted, geared gas turbine engine a primary fan may be larger as compared to a ducted, direct drive gas turbine engine, allowing for a larger TPAR. TPAR is, in turn limited by an allowable nacelle drag and fan operability.

(83) The ninth range **419** corresponds to ducted gas turbine engines in a geared configuration having a variable pitch primary fan (see FIGS. **8** and **9**) and the tenth range **420** corresponds to ducted gas turbine engines in a geared configuration having a fixed pitch primary fan. Inclusion of

a variable pitch primary fan may allow for a larger fan, but may also necessitate higher heat rejection abilities for the gas turbine engine, which may, in turn increase a CBR. The ninth range **419** corresponds to a TPAR between 20 and 35 and a CBR between 0.5 and 3, and the tenth range **420** corresponds to a TPAR between 10 and 20 and a CBR between 0.3 and 2. It will be appreciated that in other exemplary aspects, a gas turbine engine of the present disclosure in a ducted, geared, variable pitch configuration may have TPAR between 15 and 40 and a CBR between 0.3 and 5, and a gas turbine engine in a ducted, geared, fixed pitch configuration may have TPAR between 8 and 25 and a CBR between 0.3 and 5.

(84) As will be appreciated, the ducted gas turbine engines may have, on the whole, a lower TPAR than the unducted gas turbine engines as a result of an outer nacelle surrounding a primary fan (the outer nacelle becoming prohibitively heavy with higher diameter primary fans). Further, it will be appreciated that the TPAR values for geared engines may be higher than the TPAR values for direct drive engines, as inclusion of the gearbox allows the primary fan to rotate more slowly than the driving turbine, enabling a comparatively larger primary fan without overloading the primary fan or generating shock losses at a tip of the primary fan. The range of CBR values may generally be relatively high given the relatively low TPAR values (since a relatively high amount of airflow is provided to a secondary fan through an engine inlet when the TPAR values are low), as a necessary amount of airflow to a core of the ducted gas turbine engine may still be provided with a relatively high CBR without exceeding temperature thresholds or requiring a reduction in a size of the primary fan.

(85) The inventors of the present disclosure have found that the TPAR values and CBR values in the fifth, sixth, seventh, eighth, ninth, and tenth ranges **414, 416, 417, 418, 419, 420** shown may provide a desirable propulsive benefit, while still enabling operation of the core in a reasonable manner, and balancing installation and thermal load considerations.

(86) Referring particularly to FIG. 5D, an eleventh range **422** and a twelfth range **423** are provided, and exemplary embodiments **424** are plotted. The exemplary embodiments **424** include a variety of turboprop gas turbine engines in accordance with aspects of the present disclosure. In particular, the exemplary embodiments **424** include a variety of turboprop gas turbine engine similar to the exemplary embodiment described herein with reference to FIG. 6. The eleventh range **422** corresponds to a TPAR between 40 and 100 and a CBR between 0.3 and 5. The eleventh range **422** captures the benefits of the present disclosure for turboprop gas turbine engines. The twelfth range **423** corresponds to a TPAR between 50 and 70 and a CBR between 0.5 and 3, and may represent a more preferable range.

(87) As will be appreciated, the turboprop gas turbine engines may have, on the whole, higher TPAR values than turbofan engines, enabled by the lack of an outer nacelle or other casing surrounding a primary fan and a relatively slow operational speed of the primary fan and aircraft incorporating the turboprop gas turbine engine. The range of CBR values in the eleventh range **422** and the twelfth range **423** may be relatively small, as less air may be provided through a third stream with such a high TPAR without compromising operation of a core of the gas turbine engine.

(88) The inventors of the present disclosure have found that the TPAR values and CBR values in the eleventh range **422** and twelfth range **423** shown may provide a desirable propulsive benefit, while still enabling operation of the core in a reasonable manner, and balancing installation and thermal load considerations.

(89) TABLE 2, below provides a summary of TPAR values and CBR values for various gas turbine engines in accordance with one or more exemplary aspects of the present disclosure.

(90) TABLE-US-00002

Engine Type	TPAR Value	CBR Value
All Aeronautical Gas Turbine Engines	3.5 to 100	0.1 to 10 (“GTE”)
All Aeronautical GTE	4 to 75	0.3 to 5
Open Rotor GTE	30 to 60	0.3 to 5
Ducted Gas GTE	3.5 to 40	0.2 to 5
Ducted, Geared GTE	8 to 40	0.2 to 5
Ducted, Geared, Variable Pitch GTE	15 to 40	0.3 to 5
Ducted, Geared, Fixed-Pitch GTE	8 to 25	0.3 to 5

0.2 to 5 Ducted, Geared, Fixed-Pitch GTE 10 to 20 0.3 to 2 Ducted, Direct Drive GTE 3.5 to 20 0.2 to 5 Ducted, Direct Drive GTE (lower flight 6 to 20 0.2 to 5 speed) Ducted, Direct Drive GTE (lower flight 8 to 15 .sup. 0.3 to 1.8 speed) Ducted, Direct Drive GTE (higher flight 3.5 to 10 0.2 to 2 speed) Ducted, Direct Drive GTE (higher flight 3.5 to 6.sup. .sup. 0.3 to 1.5 speed) Turboprop GTE 40 to 100 0.3 to 5 Turboprop GTE 50 to 70 0.5 to 3

(91) For the purposes of Table 2, the term “Ducted” refers to inclusion of an outer nacelle around a primary fan (see, e.g., FIGS. 7 to 9); “Open Rotor” refers to inclusion of an unducted primary fan (see, e.g., FIGS. 1, 10); “Geared” refers to inclusion of a reduction gearbox between the primary fan and a driving turbine (see, e.g., FIGS. 8 to 10); “Direct Drive” refers to exclusion of a reduction gearbox between the primary fan and a driving turbine (see, e.g., FIG. 7); “Variable Pitch” refers to inclusion of a pitch change mechanism for changing a pitch of fan blades on a primary fan (see, e.g., FIGS. 1, 8, 9); “Fixed Pitch” refers to exclusion of a pitch change mechanism for changing a pitch of fan blades on a primary fan (see, e.g., FIGS. 6 to 7); “lower flight speed” refers to an engine designed to operate at a flight speed less than 0.85 Mach; and “higher flight speed” refers to an engine designed to operate at a flight speed higher than 0.85 Mach.

(92) It will be appreciated that although the discussion above is generally relating to the open rotor engine 100 described above with reference to FIGS. 1 and 2, in various embodiments of the present disclosure, the relationships outlined above with respect to, e.g., Expressions (1) and (2) may be applied to any other suitable engine architecture. For example, reference will now be made to FIGS. 6 through 12, each depicting schematically an engine architecture associated with the present disclosure.

(93) Each of the gas turbine engines of FIGS. 6 through 9 generally include a rotor 502 rotatable about a rotor axis 504 and a turbomachine 506 rotatable about a longitudinal axis 508. The rotor 502 corresponds to the “primary fan” described herein. The turbomachine 506 is surrounded at least in part by a core cowl 510 and includes a compressor section 512, a combustion section 514, and a turbine section 516 in serial flow order. In addition to the rotor 502, the gas turbine engines of FIGS. 7 through 9 each also include a ducted mid-fan or secondary fan 518. The gas turbine engines each include a fan cowl 520 surrounding the secondary fan 518.

(94) Referring still to the gas turbine engines of FIGS. 6 through 9, the gas turbine engines each also define a bypass passage 522 downstream of the respective rotor 502 and over the respective fan cowl 520 and core cowl 510, and further define a third stream 524 extending from a location downstream of the respective secondary fan 518 to the respective bypass passage 522 (at least in the embodiments depicted; in other embodiments, the third stream 524 may instead extend to a location downstream of the bypass passage 522).

(95) Referring particularly to FIG. 6, the exemplary gas turbine engine depicted is configured as a turboprop engine 526. In such a manner, the rotor 502 (or primary fan) is configured as a propeller, defining a relatively large diameter. Further, the turboprop engine 526 includes an engine shaft 528 driven by the turbomachine 506, a fan shaft 530 rotatable with the rotor 502, and a gearbox 532 mechanically coupling the engine shaft 528 with the fan shaft 530. The gearbox 532 is an offset gearbox such that the rotor axis 504 is radially offset from the longitudinal axis 508 of the turboprop engine 526.

(96) Notably, in other embodiments of the present disclosure, a turboprop engine may be provided with a reverse flow combustor.

(97) Referring to FIGS. 7 through 9, the gas turbine engines are each configured as turbofan engines, and more specifically as ducted turbofan engines. In such a manner, the gas turbine engines each include an outer nacelle 534 surrounding the rotor 502, and the rotor 502 (or primary fan) of each is therefore configured as a ducted fan. Further, each of the gas turbine engines includes outlet guide vanes 536 extending through the bypass passage 522 to the outer nacelle 534 from the fan cowl 520, the core cowl 510, or both.

(98) More specifically, still, the gas turbine engine of FIG. 7 is configured as a direct drive, ducted,

turbofan engine **538**. In particular, the direct drive, ducted, turbofan engine **538** includes an engine shaft **540** driven by the turbine section **516** and a fan shaft **542** rotatable with the rotor **502**. The fan shaft **542** is configured to rotate directly with (i.e., at the same speed as) the engine shaft **540**.

(99) By contrast, the gas turbine engine of FIG. **8** is configured as a geared, ducted, turbofan engine **544**. In particular, the geared, ducted, turbofan engine **544** includes the engine shaft **540** driven by the turbine section **516** and the fan shaft **542** rotatable with the rotor **502**. However, the exemplary geared, ducted, turbofan engine **544** further includes a gearbox **546** mechanically coupling the engine shaft **540** to the fan shaft **542**. The gearbox **546** allows the rotor **502** to rotate at a slower speed than the engine shaft **540**, and thus at a slower speed than the secondary fan **518**.

(100) Notably, the exemplary geared, ducted, turbofan engine **544** of FIG. **8** further includes a pitch change mechanism **548** operable with the rotor **502** to change a pitch of the rotor blades of the rotor **502**. Such may allow for an increased efficiency of the gas turbine engine.

(101) Further, the exemplary gas turbine engine of FIG. **9** is again configured as a direct drive, ducted, turbofan engine **538**. However, by contrast to the embodiment of FIG. **8** where a fan duct outlet defined by the fan duct is upstream of a bypass passage outlet defined by the bypass passage, in the embodiment of FIG. **9**, the fan duct outlet defined by the fan duct is downstream of the bypass passage outlet defined by the bypass passage.

(102) Moreover, in other exemplary embodiments, other suitable gas turbine engines may be provided. For example, referring now to FIG. **10**, a gas turbine engine in accordance with yet another exemplary embodiment of the present disclosure is provided. The exemplary gas turbine engine of FIG. **10** may be configured in a similar manner as the exemplary gas turbine engines described above with reference to FIGS. **7** and **8**.

(103) For example, the exemplary gas turbine engine of FIG. **10** includes a rotor **502** rotatable about a rotor axis **504** and a turbomachine **506** rotatable about a longitudinal axis **508**. The rotor axis **504** and the longitudinal axis **508** are aligned in the embodiment of FIG. **10**. The rotor **502** corresponds to the “primary fan” described herein. The turbomachine **506** is surrounded at least in part by a core cowl **510** and includes a compressor section **512** (and, not shown, a combustion section and a turbine section in serial flow order with the compressor section **512**). In addition to the rotor **502**, the gas turbine engine also includes a ducted mid-fan or secondary fan **518** and a fan cowl **520** surrounding the secondary fan **518**.

(104) However, for the embodiment of FIG. **10**, the gas turbine engine is configured as an unducted gas turbine engine **550** (see, e.g., FIG. **1**), and the secondary fan **518** is not configured as a single stage fan (see fan **184** of FIG. **1**). Instead, for the embodiment of FIG. **10**, the secondary fan **518** is configured as a multi-stage secondary fan, and more specifically still as a two-stage secondary fan having a total of two stages of rotating compressor rotor blades, and more specifically having a first stage **552** of secondary fan rotor blades and a second stage **554** of secondary fan rotor blades. Notably, with such a configuration, the turbomachine **506** does not include a separate low pressure compressor.

(105) Additionally, in still other exemplary embodiments, the gas turbine engine may have other configurations. For example, referring now to FIG. **11**, a gas turbine engine in accordance with yet another exemplary embodiment of the present disclosure is provided. The exemplary gas turbine engine of FIG. **11** may be configured in a similar manner as the exemplary gas turbine engines described above with reference to, e.g., FIGS. **1** through **3**.

(106) For example, the exemplary gas turbine engine of FIG. **11** includes a turbomachine **120** and a rotor assembly, also referred to a fan section **150**, positioned upstream thereof. The engine **100** further includes a fan cowl **170** and a core cowl **122**, the fan cowl **170** annularly encasing at least a portion of the core cowl **122** and generally positioned outward of at least a portion of the core cowl **122** along the radial direction **R**. Particularly, a downstream section of the fan cowl **170** extends over a forward portion of the core cowl **122** to define a fan duct flowpath, or simply fan duct **172**. Incoming air may enter through the fan duct **172** through a fan duct inlet **176** and may exit through

a fan exhaust nozzle **178** to produce propulsive thrust. The fan duct **172** extends from a leading edge **144** of the core cowl **122**.

(107) The engine **100** also defines an inlet duct **180**. The inlet duct **180** extends between an engine inlet **182** and a core inlet **124**. The engine inlet **182** is defined generally at the forward end of the fan cowl **170** and is positioned between a fan **152** of the fan section **150** and a fan guide vane array **160** along the axial direction A. The engine **100** further includes a ducted fan **184** with a plurality of fan blades located at least partially in the inlet duct **180**.

(108) However, for the embodiment of FIG. **11**, the core cowl **122** carries forward to an aft edge of the fan blades of the ducted fan **184** and the fan blades themselves include an integral splitter **556**. This may be termed a blade-on-blade configuration where inner and outer blades are effectively superimposed upon one another and may be unitarily formed or otherwise fabricated to achieve the split between streams.

(109) The core cowl **122** further includes a section **558** extending forward past the fan blades of the ducted fan **184**, such that the leading edge **144** is located forward of the fan blades of the ducted fan **184**. With such an arrangement, the fan duct inlet **176** is also located forward of the fan blades of the ducted fan **184**, and an outer portion of the fan blades along the radial direction R is positioned within the fan duct **172**. With this configuration, a secondary fan outer fan area, A.sub.S_Out, may be calculated at the fan duct inlet **176** in the same manner discussed above with reference to, e.g., FIGS. **2** and **3**.

(110) Further, with such a configuration, the secondary fan inner fan area, A.sub.S_In, still refers to an area defined by an annulus representing a portion of the ducted fan **184** located inward of the leading edge **144** of the core cowl **122**. However, a calculation of the secondary fan inner fan area, A.sub.S_In, is based on a leading edge radius, R.sub.7, of the leading edge **144** and an inner fan duct radius, defined along the radial direction R, directly inward along the radial direction R from the leading edge **144** (and not a core inlet inner radius at the core inlet **124**).

(111) Further, still, in other exemplary embodiments, other engine configurations may be provided. For example, referring now to FIG. **12**, an engine **100** in accordance with another embodiment of the present disclosure is provided. The engine **100** of FIG. **12** may be configured in a similar manner as the exemplary engine **100** of, e.g., FIGS. **1** through **3**.

(112) For example, the exemplary gas turbine engine of FIG. **12** includes a turbomachine **120** and a rotor assembly, also referred to a fan section **150**, positioned upstream thereof. The engine **100** further includes a fan cowl **170** and a core cowl **122**, the fan cowl **170** annularly encasing at least a portion of the core cowl **122** and generally positioned outward of at least a portion of the core cowl **122** along the radial direction R. Particularly, a downstream section of the fan cowl **170** extends over a forward portion of the core cowl **122** to define a fan duct flowpath, or simply fan duct **172**. Incoming air may enter through the fan duct **172** through a fan duct inlet **176** and may exit through a fan exhaust nozzle **178** to produce propulsive thrust. The fan duct **172** extends from a leading edge **144** of the core cowl **122**.

(113) However, for the embodiment of FIG. **12**, the fan duct **172** of the exemplary engine **100** is an elongated fan duct **172** extending between the fan cowl **170** and the core cowl **122**, a full length of the core cowl **122**. With such a configuration, the fan exhaust nozzle **178** is downstream of an exhaust nozzle **140** of the turbomachine **120**. The engine **100** of FIG. **12** further includes a mixing device **560** in the region aft of the exhaust nozzle **140** to aid in mixing airflow from the fan duct **172** and from a working gas flowpath **142** of the turbomachine **120**, e.g., to improve acoustic performance by directing airflow from the working gas flowpath **142** of the turbomachine **120** outward and from the fan duct **172** inward. Mixing in such a manner may improve performance and noise emissions.

(114) Moreover, in other exemplary embodiments of the present disclosure, a gas turbine engine may have still other suitable configurations. For example, in other embodiments, the gas turbine engine may include any suitable number of shafts or spools, compressors, or turbines (e.g., the gas

turbine engine may be a three-spool engine having three turbines and associated spools).

(115) Further, it will be appreciated that in at least certain exemplary embodiments of the present disclosure, a method of operating a gas turbine engine is provided. The method may be utilized with one or more of the exemplary gas turbine engines discussed herein, such as in FIGS. 1 through 12. The method includes operating the gas turbine engine at a rated speed, wherein operating the gas turbine engine at the rated speed comprises operating the gas turbine engine to define a thrust to power airflow ratio between 3.5 and 100 and a core bypass ratio between 0.1 and 5. For the exemplary method, the thrust to power airflow ratio is a ratio of an airflow through a bypass passage over a turbomachine of the gas turbine engine plus an airflow through a fan duct to an airflow through a core duct, and the core bypass ratio is a ratio of the airflow through the fan duct to the airflow through the core duct.

(116) As will be appreciated from the description herein, various embodiments of a gas turbine engine are provided. Certain of these embodiments may be an unducted, single rotor gas turbine engine (see FIGS. 1 and 2, 11, and 12), a turboprop engine (see FIG. 6), or a ducted turbofan engine (see FIGS. 7 through 9). Another example of a ducted turbofan engine can be found in U.S. patent application Ser. No. 16/811,368 (Published as U.S. Patent Application Publication No. 2021/0108597), filed Mar. 6, 2020 (FIG. 10, Paragraph [0062], et al.; including an annular fan case 13 surrounding the airfoil blades 21 of rotating element 20 and surrounding vanes 31 of stationary element 30; and including a third stream/fan duct 73 (shown in FIG. 10, described extensively throughout the application)). Various additional aspects of one or more of these embodiments are discussed below. These exemplary aspects may be combined with one or more of the exemplary gas turbine engine(s) discussed above with respect to the figures.

(117) For example, in some embodiments of the present disclosure, the engine may include a heat exchanger located in an annular duct, such as in a third stream. The heat exchanger may extend substantially continuously in a circumferential direction of the gas turbine engine (e.g., at least 300 degrees, such as at least 330 degrees).

(118) In one or more of these embodiments, a threshold power or disk loading for a fan (e.g., an unducted single rotor or primary forward fan) may range from 25 horsepower per square foot (hp/ft.²) or greater at cruise altitude during a cruise operating mode. In particular embodiments of the engine, structures and methods provided herein generate power loading between 80 hp/ft.² and 160 hp/ft.² or higher at cruise altitude during a cruise operating mode, depending on whether the engine is an open rotor or ducted engine.

(119) In various embodiments, an engine of the present disclosure is applied to a vehicle with a cruise altitude up to approximately 65,000 ft. In certain embodiments, cruise altitude is between approximately 28,000 ft and approximately 45,000 ft. In still certain embodiments, cruise altitude is expressed in flight levels based on a standard air pressure at sea level, in which a cruise flight condition is between FL280 and FL650. In another embodiment, cruise flight condition is between FL280 and FL450. In still certain embodiments, cruise altitude is defined based at least on a barometric pressure, in which cruise altitude is between approximately 4.85 psia and approximately 0.82 psia based on a sea level pressure of approximately 14.70 psia and sea level temperature at approximately 59 degrees Fahrenheit. In another embodiment, cruise altitude is between approximately 4.85 psia and approximately 2.14 psia. It should be appreciated that in certain embodiments, the ranges of cruise altitude defined by pressure may be adjusted based on a different reference sea level pressure and/or sea level temperature.

(120) As such, it will be appreciated that an engine of such a configuration may be configured to generate at least 25,000 pounds and less than 80,000 of thrust during operation at a rated speed, such as between 25,000 and 50,000 pounds of thrust during operation at a rated speed, such as between 25,000 and 40,000 pounds of thrust during operation at a rated speed. Alternatively, in other exemplary aspects, an engine of the present disclosure may be configured to generate much less power, such as at least 2,000 pounds of thrust during operation at a rated speed.

(121) In various exemplary embodiments, the fan (or rotor) may include twelve (12) fan blades. From a loading standpoint, such a blade count may allow a span of each blade to be reduced such that the overall diameter of the primary fan may also be reduced (e.g., to twelve feet in one exemplary embodiment). That said, in other embodiments, the fan may have any suitable blade count and any suitable diameter. In certain suitable embodiments, the fan includes at least eight (8) blades. In another suitable embodiment, the fan may have at least twelve (12) blades. In yet another suitable embodiment, the fan may have at least fifteen (15) blades. In yet another suitable embodiment, the fan may have at least eighteen (18) blades. In one or more of these embodiments, the fan includes twenty-six (26) or fewer blades, such as twenty (20) or fewer blades. Alternatively, in certain suitable embodiments, the fan may only include at least four (4) blades, such as with a fan of a turboprop engine.

(122) Further, in certain exemplary embodiments, the rotor assembly may define a rotor diameter (or fan diameter) of at least 10 feet, such as at least 11 feet, such as at least 12 feet, such as at least 13 feet, such as at least 15 feet, such as at least 17 feet, such as up to 28 feet, such as up to 26 feet, such as up to 24 feet, such as up to 18 feet.

(123) In various embodiments, it will be appreciated that the engine includes a ratio of a quantity of vanes to a quantity of blades that could be less than, equal to, or greater than 1:1. For example, in particular embodiments, the engine includes twelve (12) fan blades and ten (10) vanes. In other embodiments, the vane assembly includes a greater quantity of vanes to fan blades. For example, in particular embodiments, the engine includes ten (10) fan blades and twenty-three (23) vanes. For example, in certain embodiments, the engine may include a ratio of a quantity of vanes to a quantity of blades between 1:2 and 5:2. The ratio may be tuned based on a variety of factors including a size of the vanes to ensure a desired amount of swirl is removed for an airflow from the primary fan.

(124) Additionally, in certain exemplary embodiments, where the engine includes the third stream and a mid-fan (a ducted fan aft of the primary, forward fan), a ratio $R1/R2$ may be between 1 and 10, or 2 and 7, or at least 3.3, at least 3.5, at least 4 and less than or equal to 7, where $R1$ is the radius of the primary fan and $R2$ is the radius of the mid-fan.

(125) It should be appreciated that various embodiments of the engine, such as the single unducted rotor engine depicted and described herein, may allow for normal subsonic aircraft cruise altitude operation at or above Mach 0.5. In certain embodiments, the engine allows for normal aircraft operation between Mach 0.55 and Mach 0.85 at cruise altitude. In still particular embodiments, the engine allows for normal aircraft operation between Mach 0.75 and Mach 0.85. In certain embodiments, the engine allows for rotor blade tip speeds at or less than 750 feet per second (fps). In other embodiments, the rotor blade tip speed at a cruise flight condition can be 650 to 900 fps, or 700 to 800 fps. Alternatively, in certain suitable embodiments, the engine allows for normal aircraft operation of at least Mach 0.3, such as with turboprop engines.

(126) A fan pressure ratio (FPR) for the primary fan of the fan assembly can be 1.04 to 2.20, or in some embodiments 1.05 to 1.2, or in some embodiments less than 1.08, as measured across the fan blades of the primary fan at a cruise flight condition.

(127) In order for the gas turbine engine to operate with a fan having the above characteristics to define the above FPR, a gear assembly may be provided to reduce a rotational speed of the fan assembly relative to a driving shaft (such as a low pressure shaft coupled to a low pressure turbine). In some embodiments, a gear ratio of the input rotational speed to the output rotational speed is between 3.0 and 4.0, between 3.2 and 3.5, or between 3.5 and 4.5. In some embodiments, a gear ratio of the input rotational speed to the output rotational speed is greater than 4.1. For example, in particular embodiments, the gear ratio is within a range of 4.0 to 4.5, within a range of 4.1 to 14.0, within a range of 4.5 to 14.0, or within a range of 6.0 to 14.0. In certain embodiments, the gear ratio is within a range of 4.5 to 12 or within a range of 6.0 to 11.0.

(128) With respect to a turbomachine of the gas turbine engine, the compressors and/or turbines can

include various stage counts. As disclosed herein, the stage count includes the number of rotors or blade stages in a particular component (e.g., a compressor or turbine). For example, in some embodiments, a low pressure compressor may include 1 to 8 stages, a high-pressure compressor may include 4 to 15 stages, a high-pressure turbine may include 1 to 2 stages, and/or a low pressure turbine (LPT) may include 1 to 7 stages. In particular, the LPT may have 4 stages, or between 4 and 7 stages. For example, in certain embodiments, an engine may include a one stage low pressure compressor, an 11 stage high pressure compressor, a two stage high pressure turbine, and 4 stages, or between 4 and 7 stages for the LPT. As another example, an engine can include a three stage low-pressure compressor, a 10 stage high pressure compressor, a two stage high pressure turbine, and a 7 stage low pressure turbine.

(129) A core engine is generally encased in an outer casing defining one half of a core diameter (D_{core}), which may be thought of as the maximum extent from a centerline axis (datum for R). In certain embodiments, the engine includes a length (L) from a longitudinally (or axial) forward end to a longitudinally aft end. In various embodiments, the engine defines a ratio of L/D_{core} that provides for reduced installed drag. In one embodiment, L/D_{core} is at least 2. In another embodiment, L/D_{core} is at least 2.5. In some embodiments, the L/D_{core} is less than 5, less than 4, and less than 3. In various embodiments, it should be appreciated that the L/D_{core} is for a single unducted rotor engine.

(130) The reduced installed drag may further provide for improved efficiency, such as improved specific fuel consumption. Additionally, or alternatively, the reduced installed drag may provide for cruise altitude engine and aircraft operation at the above describe Mach numbers at cruise altitude. Still particular embodiments may provide such benefits with reduced interaction noise between the blade assembly and the vane assembly and/or decreased overall noise generated by the engine by virtue of structures located in an annular duct of the engine.

(131) Additionally, it should be appreciated that ranges of power loading and/or rotor blade tip speed may correspond to certain structures, core sizes, thrust outputs, etc., or other structures of the core engine. However, as previously stated, to the extent one or more structures provided herein may be known in the art, it should be appreciated that the present disclosure may include combinations of structures not previously known to combine, at least for reasons based in part on conflicting benefits versus losses, desired modes of operation, or other forms of teaching away in the art.

(132) Although depicted above as an unshrouded or open rotor engine in the embodiments depicted above, it should be appreciated that aspects of the disclosure provided herein may be applied to shrouded or ducted engines, partially ducted engines, aft-fan engines, or other gas turbine engine configurations, including those for marine, industrial, or aero-propulsion systems. Certain aspects of the disclosure may be applicable to turbofan, turboprop, or turboshaft engines. However, it should be appreciated that certain aspects of the disclosure may address issues that may be particular to unshrouded or open rotor engines, such as, but not limited to, issues related to gear ratios, fan diameter, fan speed, length (L) of the engine, maximum diameter of the core engine (D_{core}) of the engine, L/D_{core} of the engine, desired cruise altitude, and/or desired operating cruise speed, or combinations thereof.

(133) This written description uses examples to disclose the present disclosure, including the best mode, and also to enable any person skilled in the art to practice the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosure is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

(134) Further aspects are provided by the subject matter of the following clauses:

(135) A gas turbine engine comprising: a turbomachine comprising a compressor section, a combustion section, and a turbine section arranged in serial flow order, the turbomachine defining an engine inlet to an inlet duct, a fan duct inlet to a fan duct, and a core inlet to a core duct; a primary fan driven by the turbomachine; and a secondary fan located downstream of the primary fan within the inlet duct, the gas turbine engine defining a thrust to power airflow ratio between 3.5 and 100 and a core bypass ratio between 0.1 and 10, wherein the thrust to power airflow ratio is a ratio of an airflow through a bypass passage over the turbomachine plus an airflow through the fan duct to an airflow through the core duct, and wherein the core bypass ratio is a ratio of the airflow through the fan duct to the airflow through the core duct.

(136) The gas turbine engine of any preceding clause, wherein the thrust to power airflow ratio and the core bypass ratio are defined when the gas turbine engine is operated at a rated speed during standard day operating conditions.

(137) The gas turbine engine of any preceding clause, wherein the thrust to power airflow ratio between 4 and 75.

(138) The gas turbine engine of any preceding clause, wherein the primary fan is an unducted primary fan, and wherein the thrust to power airflow ratio between 30 and 60.

(139) The gas turbine engine of any preceding clause, wherein the thrust to power airflow ratio between 35 and 50.

(140) The gas turbine engine of any preceding clause, wherein the core bypass ratio between 0.3 and 5.

(141) The gas turbine engine of any preceding clause, wherein the gas turbine engine is a turboprop engine, and wherein the thrust to power airflow ratio between 40 and 100.

(142) The gas turbine engine of any preceding clause, wherein the primary fan is a ducted primary fan, and wherein the thrust to power airflow ratio is between 3.5 and 40.

(143) The gas turbine engine of any preceding clause, wherein the gas turbine engine is a direct drive gas turbine engine, and wherein the thrust to power airflow ratio is between 3.5 and 20.

(144) The gas turbine engine of any preceding clause, wherein the gas turbine engine is a geared gas turbine engine, and wherein the thrust to power airflow ratio is between 8 and 40.

(145) The gas turbine engine of any preceding clause, wherein the secondary fan is a single stage secondary fan.

(146) The gas turbine engine of any preceding clause, wherein the secondary fan is a multi-stage secondary fan.

(147) The gas turbine engine of any preceding clause, wherein the multi-stage secondary fan is a two stage secondary fan.

(148) The gas turbine engine of any preceding clause, wherein the primary fan is a ducted primary fan comprising an outer nacelle surrounding the primary fan and defining the bypass passage downstream of the primary fan and over the turbomachine, wherein the gas turbine engine further defines a bypass passage outlet at a downstream end of the outer nacelle, wherein the fan duct defines a fan duct outlet, and wherein the fan duct outlet is downstream of the bypass passage outlet.

(149) The gas turbine engine of any preceding clause, wherein the primary fan is a ducted primary fan comprising an outer nacelle surrounding the primary fan and defining the bypass passage downstream of the primary fan and over the turbomachine, wherein the gas turbine engine further defines a bypass passage outlet at a downstream end of the outer nacelle, wherein the fan duct defines a fan duct outlet, and wherein the fan duct outlet is upstream of the bypass passage outlet.

(150) The gas turbine engine of any preceding clause, wherein the primary fan, the secondary fan, the compressor section, the combustion section, and the turbine section are arranged in serial flow order.

(151) A method of operating a gas turbine engine, comprising: operating the gas turbine engine at a rated speed, wherein operating the gas turbine engine at the rated speed comprises operating the gas

turbine engine to define a thrust to power airflow ratio between 3.5 and 100 and a core bypass ratio between 0.1 and 5, wherein the thrust to power airflow ratio is a ratio of an airflow through a bypass passage over a turbomachine of the gas turbine engine plus an airflow through a fan duct to an airflow through a core duct, and wherein the core bypass ratio is a ratio of the airflow through the fan duct to the airflow through the core duct.

(152) The method of any preceding clause, wherein The gas turbine engine of claim 1, wherein the thrust to power airflow ratio between 4 and 75.

(153) The method of any preceding clause, wherein the primary fan is an unducted primary fan, and wherein the thrust to power airflow ratio between 30 and 60.

(154) The method of any preceding clause, wherein the thrust to power airflow ratio between 35 and 50.

(155) The method of any preceding clause, wherein the core bypass ratio between 0.3 and 5.

Claims

1. A gas turbine engine comprising: a turbomachine comprising a compressor section, a combustion section, and a turbine section arranged in serial flow order, the turbomachine defining an engine inlet to an inlet duct, a fan duct inlet to a fan duct, and a core inlet to a core duct; a primary fan driven by the turbomachine; and a secondary fan in serial flow order with the primary fan and located downstream of the primary fan within the inlet duct, the gas turbine engine defining a thrust to power airflow ratio between 3.5 and 100 and a core bypass ratio between 0.1 and 10, wherein the thrust to power airflow ratio is a ratio of an airflow through a bypass passage over the turbomachine plus an airflow through the fan duct to an airflow through the core duct, and wherein the core bypass ratio is a ratio of the airflow through the fan duct to the airflow through the core duct.

2. The gas turbine engine of claim 1, wherein the thrust to power airflow ratio and the core bypass ratio are defined when the gas turbine engine is operated at a rated speed during standard day operating conditions.

3. The gas turbine engine of claim 1, wherein the thrust to power airflow ratio is between 4 and 75.

4. The gas turbine engine of claim 1, wherein the primary fan is an unducted primary fan, and wherein the thrust to power airflow ratio is between 30 and 60.

5. The gas turbine engine of claim 4, wherein the thrust to power airflow ratio is between 35 and 50.

6. The gas turbine engine of claim 1, wherein the core bypass ratio is between 0.3 and 5.

7. The gas turbine engine of claim 1, wherein the gas turbine engine is a turboprop engine, and wherein the thrust to power airflow ratio is between 40 and 100.

8. The gas turbine engine of claim 1, wherein the primary fan is a ducted primary fan, and wherein the thrust to power airflow ratio is between 3.5 and 40.

9. The gas turbine engine of claim 8, wherein the gas turbine engine is a direct drive gas turbine engine, and wherein the thrust to power airflow ratio is between 3.5 and 20.

10. The gas turbine engine of claim 8, wherein the gas turbine engine is a geared gas turbine engine, and wherein the thrust to power airflow ratio is between 8 and 40.

11. The gas turbine engine of claim 1, wherein the secondary fan is a single stage secondary fan.

12. The gas turbine engine of claim 1, wherein the secondary fan is a multi-stage secondary fan.

13. The gas turbine engine of claim 1, wherein the primary fan, the secondary fan, the compressor section, the combustion section, and the turbine section are arranged in serial flow order.

14. The gas turbine engine of claim 1, wherein the primary fan is a ducted primary fan comprising an outer nacelle surrounding the primary fan and defining the bypass passage downstream of the primary fan and over the turbomachine, wherein the gas turbine engine further defines a bypass passage outlet at a downstream end of the outer nacelle, wherein the fan duct defines a fan duct

outlet, and wherein the fan duct outlet is downstream of the bypass passage outlet.

15. The gas turbine engine of claim 1, wherein the primary fan is a ducted primary fan comprising an outer nacelle surrounding the primary fan and defining the bypass passage downstream of the primary fan and over the turbomachine, wherein the gas turbine engine further defines a bypass passage outlet at a downstream end of the outer nacelle, wherein the fan duct defines a fan duct outlet, and wherein the fan duct outlet is upstream of the bypass passage outlet.

16. A method of operating a gas turbine engine, comprising: operating the gas turbine engine at a rated speed, wherein operating the gas turbine engine at the rated speed comprises operating the gas turbine engine to define a thrust to power airflow ratio between 3.5 and 100 and a core bypass ratio between 0.1 and 5, wherein the thrust to power airflow ratio is a ratio of an airflow through a bypass passage over a turbomachine of the gas turbine engine plus an airflow through a fan duct to an airflow through a core duct, and wherein the core bypass ratio is a ratio of the airflow through the fan duct to the airflow through the core duct.

17. The method of claim 16, wherein the thrust to power airflow ratio is between 4 and 75.

18. The method of claim 16, wherein the primary fan is an unducted primary fan, and wherein the thrust to power airflow ratio is between 30 and 60.

19. The method of claim 18, wherein the thrust to power airflow ratio is between 35 and 50.

20. The method of claim 16, wherein the core bypass ratio is between 0.3 and 5.
