

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12411644
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Kim; Shin Yeong

Rollable display apparatus

Abstract

A rollable display apparatus including: a display panel configured to display a video; a rolling part located at one end of the display panel and including an internal space in which the display panel is rolled and accommodated; a supporter located at another end of the display panel; and an anchor body configured such that at least one area of the rolling part and at least one area of the supporter are detachable from the anchor body, and comprising a plurality of anchor areas configured to maintain an unrolled state of the display panel when the at least one area of the rolling part and the at least one area of the supporter are attached to the anchor body.

Inventors:	Kim; Shin Yeong (Yongin-si, KR)
Applicant:	HYUNDAI MOBIS CO., LTD. (Seoul, KR)
Family ID:	93379631
Assignee:	HYUNDAI MOBIS CO., LTD. (Seoul, KR)
Appl. No.:	18/637945
Filed:	April 17, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240378008 A1	Nov. 14, 2024

Foreign Application Priority Data

KR	10-2023-0058928	May. 08, 2023
KR	10-2023-0063026	May. 16, 2023

Publication Classification

Int. Cl.: G06F3/14 (20060101); **G09G3/00** (20060101)

U.S. Cl.:

CPC **G06F3/1446** (20130101); **G09G3/035** (20200801); G09G2300/026 (20130101); G09G2380/10 (20130101)

Field of Classification Search

CPC: G06F (3/1446); G09G (3/035); G09G (2300/026); G09G (2380/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2791272	12/1956	Stehlik	296/97.7	B60J 1/2052
4762358	12/1987	Levosky	296/97.7	B60J 1/2063
6131986	12/1999	Rosen	296/97.12	B60J 3/0208
6503188	12/2002	August	248/466	A47C 21/00
7143805	12/2005	Weir	160/370.22	B60J 1/2069
9272671	12/2015	Vander Sluis	N/A	B60R 11/0235
2012/0002357	12/2011	Auld	361/679.01	G09F 11/30
2012/0268665	12/2011	Yetukuri	348/837	B60R 11/0235
2013/0201208	12/2012	Cho	345/619	G06F 3/0488
2013/0203469	12/2012	Cho	345/173	H04M 1/0268
2014/0263511	12/2013	Clements	224/483	B60R 7/06
2016/0068113	12/2015	Clements	224/483	B60R 11/02
2018/0068612	12/2017	Cho	N/A	G09G 3/035
2018/0364827	12/2017	Chung	N/A	G06F 1/1677
2019/0012008	12/2018	Yoon	N/A	G06F 1/1652
2019/0197960	12/2018	Kim	N/A	G09G 3/035
2019/0355923	12/2018	Kishimoto	N/A	G09F 9/00
2020/0135535	12/2019	Li	N/A	H01L 21/68728
2020/0170114	12/2019	Choi	N/A	G09F 9/301
2021/0206270	12/2020	Diboine	N/A	B60K 35/10
2023/0031862	12/2022	Szczerba	N/A	G09F 9/301
2023/0050312	12/2022	Guzel	N/A	G09G 3/32
2023/0206860	12/2022	Lee	N/A	G09G 3/3266

Primary Examiner: Leiby; Christopher E

Attorney, Agent or Firm: Morgan, Lewis & Bockius LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) The present application claims priority to Patent Applications No. 10-2023-0063026, filed on May 16, 2023 in Korea, and No. 10-2023-0058928, filed on May 8, 2023 in Korea the entire

contents of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a rollable display apparatus.

BACKGROUND

(3) The content described in this section simply provides background information for the present disclosure and does not constitute related art.

(4) A display apparatus is a device for visually displaying information. The display apparatus may be used in computers, mobile devices, televisions, watches, vehicles, and the like. The display apparatus is used in a vehicle so that various types of content such as driving information of a vehicle, vehicle status, and entertainment can be provided to a user.

(5) A plurality of display apparatus used in a vehicle may be required to provide various types of content. Accordingly, in the related art, a plurality of display apparatus are mounted at several positions inside a vehicle. Such display apparatus have problems in that a user cannot select the number of display apparatus, it is difficult to cope with a malfunction of the display apparatus, and a lot of an inner space of the vehicle is occupied.

(6) A display of the related art is rolled or slid in one direction so that a display screen is exposed. Therefore, when infotainment is provided using a display disposed in a vehicle, occupants in the vehicle can view only video information corresponding to a maximum size of the display. The display is limited in size because the display is rolled or slid in one direction. Therefore, there is a problem that the sense of immersion of a video is degraded and emotional quality is degraded.

SUMMARY

(7) Therefore, the present disclosure is intended to solve these problems, and a main object of the present disclosure is to provide a display apparatus that allows the number of display apparatus to be selected depending on a user's need, allows malfunctions of the display apparatus to be easily coped, and allows utilization of an inner space of a vehicle to be maximized.

(8) A rollable display apparatus and control method therefor according to another embodiment can provide video information of various display sizes and video ratios on the basis of an integration form of a plurality of displays.

(9) A rollable display apparatus and control method according to another embodiment can form an integrated display by using integration between a plurality of displays to form an improved video ratio and display size, thereby increasing the sense of immersion in a video.

(10) As described above, according to the present embodiment, there is an effect that it is possible to select the number of display apparatus depending on a user's need, easily cope with malfunctions of the display apparatus, and maximize the utilization of the inner space of a vehicle.

(11) As described above, according to another embodiment, the rollable display apparatus and control method therefor have an effect that it is possible to provide video information of various display sizes and video ratios on the basis of the integration form of the plurality of displays.

(12) As described above, according to another embodiment, the rollable display apparatus and control method therefor have an effect that it is possible to form the integrated display by using the integration between the plurality of displays to form an improved video ratio and display size, thereby increasing the sense of immersion in a video.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view of a rollable display apparatus according to a first embodiment of the present disclosure.

(2) FIG. 2 is a diagram illustrating an operating state of the rollable display apparatus according to the first embodiment of the present disclosure.

- (3) FIG. 3 is a diagram illustrating a form in which a rolling part and a supporter are accommodated in an internal space of an anchor body according to the first embodiment of the present disclosure.
- (4) FIG. 4 is a perspective view of a rollable display apparatus according to a second embodiment of the present disclosure.
- (5) FIGS. 5 to 8 are diagrams illustrating examples in which the rollable display apparatus are mounted at various positions according to the first embodiment of the present disclosure.
- (6) FIG. 9 is a block configuration diagram illustrating a configuration of a rollable display apparatus according to another embodiment of the present invention.
- (7) FIG. 10 is a flowchart illustrating a display control method according to another embodiment of the present invention.
- (8) FIG. 11 is a flowchart specifically illustrating step S1050 of FIG. 10.
- (9) FIG. 12 is a diagram illustrating an operating state of a plurality of displays that output videos of a traveling vehicle according to another embodiment of the present invention.
- (10) FIG. 13 is a diagram illustrating an operating state of a second display in which the display is rolled or slid to a maximum size according to another embodiment of the present invention.
- (11) FIG. 14 is a diagram illustrating an operating state of a plurality of displays in which a parking mode or an autonomous driving mode is activated according to another embodiment of the present invention.
- (12) FIG. 15 is a diagram illustrating an operating state in which a video is output by using a first integrated display according to another embodiment of the present invention.
- (13) FIG. 16 is a block configuration diagram briefly illustrating a configuration of a main control unit and an auxiliary control unit for adjusting a video ratio in the integrated display according to another embodiment of the present invention.
- (14) FIG. 17 is a diagram illustrating an operating state in which video information is output by using a second integrated display according to another embodiment of the present invention.

DETAILED DESCRIPTION

- (15) A rollable display apparatus **100** or **400** according to the present disclosure may be mounted on a vehicle such as a car. The rollable display apparatus **100** or **400** according to the present disclosure may be a liquid crystal display apparatus (LDC), a quantum dot display apparatus (QD), a field emission display apparatus (FED), an electro-wetting display apparatus (EWD), an organic light emitting display apparatus (OLED), or the like. However, the rollable display apparatus **100** or **400** according to the present disclosure is not limited to the above-described display apparatus.
- (16) In the present disclosure, the term rolling a display panel refers to winding the display panel. In the present disclosure, the term unrolling the display panel refers to unfolding a portion of the display panel and discharging the portion from a rolling part.
- (17) In the present disclosure, the term user refers to a person who uses the rollable display apparatus **100** or **400** according to the present disclosure or a device (for example, artificial intelligence) that uses the rollable display apparatus **100** or **400** according to the present disclosure. Accordingly, the term user may include a driver of the vehicle and an occupant of the vehicle.
- (18) FIG. 1 is a perspective view of the rollable display apparatus according to a first embodiment of the present disclosure.
- (19) FIG. 2 is a diagram illustrating an operating state of the rollable display apparatus according to the first embodiment of the present disclosure.
- (20) FIG. 3 is a diagram illustrating a form in which a rolling part and a supporter are accommodated in an internal space of an anchor body according to the first embodiment of the present disclosure.
- (21) FIGS. 5 to 8 are diagrams illustrating examples in which the rollable display apparatus is mounted at various positions according to the first embodiment of the present disclosure. To be specific, FIG. 5 is a diagram illustrating a form in which the rollable display apparatus is mounted

at a cluster position of a vehicle according to the first embodiment of the present disclosure. FIG. 6 is a diagram illustrating a form in which the rollable display apparatus is mounted on a cluster of the vehicle and a center fascia position of the vehicle according to the first embodiment of the present disclosure. FIG. 7 is a diagram illustrating a form in which the rollable display apparatus is mounted on a rear part of a seat of the vehicle according to the first embodiment of the present disclosure. FIG. 8 is a diagram illustrating a form in which the rollable display apparatus is mounted on a ceiling of a vehicle according to the first embodiment of the present disclosure.

(22) Referring to FIGS. 1 to 3 and 5 to 8, the rollable display apparatus **100** according to the first embodiment of the present disclosure may include all or some of a display panel **110**, a rolling part **120**, a supporter **130**, a plurality of anchor areas **141**, and an anchor body **140**.

(23) The display panel **110** may display a video or image to the user. The display panel **110** may display a screen for information on the vehicle, a forward side of the vehicle, and entertainment. The display panel **110** may include several components for displaying the screen. The display panel **110** may include flexible characteristics in at least one area of the display panel **110**.

(24) The rolling part **120** may be located at one end of the display panel **110**. Here, the one end of the display panel **110** is an edge of the end of the display panel **110**. The rolling part **120** may include an internal space in which the display panel **110** is rolled and accommodated. The rolling part **120** may be a long bar. A length of the rolling part **120** may be longer than the length of the one end of the display panel **110**. The rolling part **120** may be divided into a plurality of parts **121**, **122**, and **123**. For example, as can be seen in FIG. 1, the rolling part **120** may be divided into a first part **121**, a second part **122**, and a third part **123**. At least one of the plurality of parts **121**, **122**, and **123** of the rolling part **120** may include a first connector (not illustrated). For example, the first connector may be included in the first part **121** and the third part **123**. However, the part in which the first connector is included is not limited to the above-described example.

(25) The first connector may be configured to transmit or receive an electrical signal to or from the display panel **110**. For example, the first connector may be configured to receive an electrical signal from the outside of the display panel **110** to the display panel **110**. The first connector may be configured to transmit an electrical signal from the display panel **110** to the outside of the display panel **110**. In order for the first connector to transmit or receive an electrical signal to or from the display panel **110**, the first connector may be connected to the display panel **110** using a wire. Alternatively, the first connector may be connected to the display panel **110** using short range wireless communication. The first connector may be configured to be electrically connected to a second connector (not illustrated), which will be described below.

(26) The supporter **130** may be located at the other end of the display panel **110**. Here, the other end of the display panel **110** is an edge at an end located in a direction opposite to the one end of the display panel **110**. The supporter **130** may function as a handle. For example, when the display panel **110** is rolled and accommodated in the rolling part **120**, the display panel **110** may be unrolled by pulling the supporter **130**. The supporter **130** may be divided into a plurality of parts **131**, **132**, and **133**. For example, the supporter **130** may be divided into a first part **131**, a second part **132**, and a third part **133**. At least one of the plurality of parts of the supporter **130** may include a first connector (not illustrated). Since the first connector included in the supporter **130** may have the same operating principle and effect as the first connector included in the rolling part **120**, detailed description thereof will be omitted.

(27) The plurality of anchor areas **141** may be disposed inside the vehicle or in the anchor body **140**, which will be described below. Each of the plurality of anchor areas **141** may be configured so that at least one area of the rolling part **120** and at least one area of the supporter **130** are detachable. For example, the third part **123** of the rolling part **120** and the third part **133** of the supporter **130** may be configured to be attached and detachable to and from the anchor area **141**. When the at least one area of the rolling part **120** and the at least one area of the supporter **130** are attached to the plurality of anchor areas **141**, an unrolled state of the display panel **110** may be

fixed. That is, the plurality of anchor areas **141** may be configured to allow the user to adjust a size of the display panel **110**. Although the plurality of anchor areas **141** are illustrated in a circular shape in the drawing, it is to be noted that this is for convenience of description. Each of the plurality of anchor areas **141** may include a second connector (not illustrated).

(28) The second connector may be electrically connected to the first connector. The second connector and the first connector may be configured in the form of a plug or jack. Alternatively, the second connector and the first connector may be connected using a magnet and electrically connected to each other using short-distance wireless communication. The second connector may be connected to the first connector to transmit or receive an electrical signal to or from the display panel **110**. The second connectors included in the plurality of anchor areas **141** may have different connection pins. Since the second connectors have the different connection pins, the display panel **110** may receive information from the different second connectors. That is, the second connector may be configured to allow the display panel **110** to distinguish between the different second connectors.

(29) Since the display panel **110** receive information on the different second connectors, the display panel **110** may determine whether the first connector is connected to the second connector at a certain position. For example, when the display panel **110** is mounted on the anchor areas **141** located in a cluster and a center fascia of the vehicle as can be seen in FIGS. **5** and **6**, the display panel **110** may be determined to have been mounted on the anchor areas **141** located in the cluster and center fascia of the vehicle. In this case, the display panel **110** may serve as the cluster and the center fascia of the vehicle. That is, the display panel **110** may be configured to receive, from the second connector, information necessary for the cluster and the center fascia of the vehicle and display the information. On the other hand, when the display panel **110** is mounted on the anchor areas **141** located on a rear part of a seat or a roof of the vehicle as can be seen in FIGS. **7** and **8**, the display panel **110** may be configured to display entertainment content.

(30) The rollable display apparatus **100** according to the first embodiment can provide a plurality of pieces of content with only one display apparatus by providing different information to the user depending on mounting positions of the display panel **110**. In this case, the display panel **110** can provide content corresponding to a situation of the user. The rollable display apparatus **100** according to the first embodiment can provide an environment in which the user can select the number of display apparatus included in the vehicle by providing a plurality of pieces of content with only one display apparatus.

(31) When the first connector included in the rolling part **120** and the first connector included in the supporter **130** are connected to different second connectors, the display panel **110** may be configured to recognize an unrolling partner of the display panel **110**. For example, when the display panel **110** is unrolled to a size of eight inches and then mounted on the two anchor areas **141**, the display panel **110** may recognize the two connected second connectors. The display panel **110** may determine that the display panel **110** has been unrolled to the size of eight inches on the basis of information received from the two recognized second connectors. The display panel **110** may be configured to modify and display information with resolution corresponding to the size of eight inches when a determination is made that the display panel **110** has been unrolled to the size of eight inches. On the other hand, the display panel **110** may be configured to modify and display information with a resolution corresponding to a size of 12 inches when the display panel **110** has been unrolled to the size of 12 inches and then mounted on the plurality of anchor areas **141**.

(32) The rollable display apparatus **100** according to the first embodiment is configured so that the size of the display panel **110** can be selected as necessary, thereby making it possible to provide content according to a position and purpose of the user.

(33) As described above, it is possible to easily cope with a malfunction of the rollable display apparatus **100** by configuring the rollable display apparatus **100** so that the rollable display apparatus **100** is attachable and detachable inside the vehicle. For example, when the rollable

display apparatus **100** fails, it is possible to separate and repair only a failing display apparatus without the need to disassemble the inside of the vehicle to replace or repair the display apparatus.

(34) A plurality of anchor bodies **140** may be disposed inside the vehicle. For example, the anchor body **140** may be disposed in a cockpit, a ceiling, an armrest, or a rear part of a seat of the vehicle. The anchor body **140** may be integrated with the cockpit, the ceiling, the armrest, or the rear part of the seat of the vehicle. When the display panel **110** is rolled and completely accommodated in the rolling part **120**, the anchor body **140** may include an internal space **142** that accommodates the rolling part **120** and the supporter **130**. The anchor body **140** may include a button (not illustrated). When the button is pressed, the anchor body **140** may be configured to discharge the rolling part **120** and the supporter **130** accommodated in the internal space **142** of the anchor body **140**.

(35) As described above, it is possible to efficiently utilize the inner space of the vehicle so that the rollable display apparatus **100** can be accommodated in the anchor body **140**. For example, when the user stops usage of the rollable display apparatus **100** according to the present disclosure, the rollable display apparatus **100** is accommodated in the anchor body **140**, so that the rollable display apparatus **100** can be hidden from the field of view of the user.

(36) FIG. **4** is a perspective view of the rollable display apparatus according to a second embodiment of the present disclosure.

(37) Referring to FIG. **4**, the rollable display apparatus according to the second embodiment of the present disclosure may include all or some of a display panel **410**, a first rolling part **420**, a second rolling part **430**, a plurality of anchor areas **441**, and an anchor body **440**.

(38) Since components according to the second embodiment of the present disclosure may be the same as the components according to the first embodiment except for components to be particularly described below, detailed description of the same parts will be omitted.

(39) The first rolling part **420** may be located at one end of the display panel **410**. The first rolling part **420** may include an internal space in which a portion of the display panel **410** is rolled and accommodated. The first rolling part **420** may be a long bar. A length of the first rolling part **420** may be longer than a length of the one end of the display panel **410**. The first rolling part **420** may be divided into a plurality of parts **421**, **422**, and **423**. At least one of the plurality of parts **421**, **422**, and **423** of the first rolling part **420** may include a first connector (not illustrated).

(40) The second rolling part **430** may be located at the other end of the display panel **410**. The second rolling part **430** may include an internal space in which all but a portion of the display panel **410** rolled on and accommodated in the first rolling part **420** is rolled and accommodated. The second rolling part **430** may be a long bar. A length of the second rolling part **430** may be larger than the length of the one end of the display panel **410**. The second rolling part **430** may be divided into a plurality of parts **431**, **432**, and **433**. At least one of the plurality of parts **431**, **432**, and **433** of the second rolling part **430** may include a first connector (not illustrated).

(41) The rollable display apparatus **400** according to the second embodiment of the present disclosure may be configured so that the display panel **110** is rolled or unrolled in both directions, unlike the rollable display apparatus **100** according to the first embodiment of the present disclosure. Accordingly, the rollable display apparatus may be configured using a larger display panel as compared to the rollable display apparatus **100** according to the first embodiment.

(42) FIG. **9** is a block configuration diagram illustrating a configuration of a rollable display apparatus according to another embodiment of the present invention.

(43) Referring to FIG. **9**, a rollable display apparatus **900** according to another embodiment of the present invention includes some or all of a drive unit **910**, a drive control unit **912**, a plurality of displays **920**, and a display control unit **930**.

(44) The drive unit **910** is disposed inside a housing (not illustrated) formed in a cockpit **1200** of the vehicle. The drive unit **910** is formed to move each of the plurality of displays **920** in a second direction and/or a third direction. The drive unit **910** is formed so that the plurality of displays **920** move along a longitudinal direction of the cockpit **1200**. The drive unit **910** may include a rail

structure to move the plurality of displays **920**. Here, the second direction and the third direction are opposite directions. A direction perpendicular to one surface of the cockpit **1200**, that is, a direction in which the plurality of displays **920** are exposed by being rolled or slid is a first direction. The second and third directions are directions perpendicular to the first direction.

(45) In one embodiment, the drive control unit **912** may include a processor (e.g., computer, microprocessor, CPU, ASIC, circuitry, logic circuits, etc.) and an associated non-transitory memory storing software instructions which, when executed by the processor, provides the functionalities of the drive control unit **912** described hereinafter.

(46) The drive control unit **912** may control integration between the plurality of displays **920** by moving each of the plurality of displays **920** in the second direction and/or the third direction. For example, the drive control unit **912** may perform control so that a position of each of the plurality of displays **920** can be determined on the rail structure of the drive unit **910**.

(47) The plurality of displays **920** includes a first display **921**, a second display **922**, and a third display **923**.

(48) The first display **921** is located on one side of the drive unit **910**. The third display **923** is located on the other side of the drive unit **910**. The second display **922** is located in the middle of the first display **921** and the third display **923** on the drive unit **910**. For example, the first display **921** may be a display located on the cluster. The second display **922** may be a display located on the center fascia. The third display **923** may be a display located in front of a passenger seat. The plurality of displays **920** according to an embodiment of the present invention will be described as, for example, three displays. However, this is only an embodiment, and there may be a larger or smaller number of displays.

(49) The plurality of displays **920** may form a first integrated display **1500** or a second integrated display **1700** on the basis of an integration state.

(50) The first integrated display **1500** is one display in which at least two of the first to third displays **921** to **923** are integrated. For example, in the first integrated display **1500**, the first display **921** and the second display **922** are integrated or the second display **922** and the third display **923** are integrated. The first integrated display **1500** may be moved in the second or third direction along the longitudinal direction of the cockpit **1200** and located at any one point.

(51) The second integrated display **1700** is one display in which all of the first to third displays **921** to **923** are integrated. For example, in the second integrated display **1700**, the integration may be made with any one of the positions of the first display **921**, the second display **922**, and the third display **923** as a reference. The second integrated display **1700** may be moved in the second or third direction along the longitudinal direction of the cockpit **1200** and located at any one point.

(52) The display control unit **930** includes a video signal reception unit **931**, a ratio adjustment unit **932**, and a video output unit **933**.

(53) In one embodiment, the display control unit **930** may include a processor (e.g., computer, microprocessor, CPU, ASIC, circuitry, logic circuits, etc.) and an associated non-transitory memory storing software instructions which, when executed by the processor, provides the functionalities of the video signal reception unit **931**, the ratio adjustment unit **932**, and the video output unit **933**. The processor may take the form of one or more processor(s) and associated memory storing program instructions.

(54) The video signal reception unit **931** receives video information that is displayed on each of the plurality of displays **920**. Here, the video information includes, for example, position information of surrounding vehicles, navigation information, shared screen information in which a screen of another device is shared for an output, and entertainment information including a variety of entertainment.

(55) The ratio adjustment unit **932** adjusts a video ratio of the plurality of displays **920**. The ratio adjustment unit **932** may adjust a ratio of video pieces of information that are output to the first display **921**, the second display **922**, and the third display **923**. Further, the ratio adjustment unit

932 may adjust a video ratio of the first integrated display **1500** and the second integrated display **1700**. The video ratio of the first integrated display **1500** corresponds, for example, to a size of at least two integrated displays. The video ratio of the second integrated display **1700** corresponds to, for example, a display size of the first to third integrated displays **921** to **923**.

(56) The video output unit **933** outputs a video on the display whose video ratio has been adjusted by the ratio adjustment unit **932**. The video output unit **933** outputs the video to some or all of the first display **921**, the second display **922**, and the third display **923** on the basis of an output signal adjusted by the ratio adjustment unit **932**.

(57) FIG. **10** is a flowchart illustrating a display control method according to an embodiment of the present invention.

(58) Referring to FIG. **10**, it is sensed that a parking mode or an autonomous driving mode has been activated in the vehicle (**S1000**).

(59) One of the plurality of displays **920** is rolled or slid in the first direction and exposed to a maximum size (**S1010**). One of the plurality of displays **920** arranged side by side with the longitudinal direction of the cockpit **1200** of the vehicle as a reference is rolled or slid in the first direction and exposed to the maximum size. Here, the first direction is a direction perpendicular to the one side of the cockpit **1200**.

(60) A determination is made as to whether the plurality of displays **920** are integrated (**S1020**). The display control unit **930** may determine whether or not the plurality of displays **920** are integrated on the basis of position information of the occupant. For example, the display control unit **930** may determine whether or not the displays are optimally integrated on the basis of position information of an occupant, by using a sensor (not illustrated) that senses whether or not a user is seated on a seat included inside the vehicle.

(61) When a determination is made in step **S1020** that the integration of the plurality of displays **920** is necessary, a display integration form is selected (**S1030**). The integration form of the displays according to an embodiment of the present invention may include first to fifth integration forms on the basis of the integration form of the plurality of displays **920**.

(62) For example, the first integration form refers to integration of the first display **921** and the second display **922** among the plurality of displays **920**. The second integration form refers to integration of the second display **922** and the third display **923** among the plurality of displays **920**. The third integration form refers to integration of the first to third displays **921** to **923** on the basis of a position of the first display **921** among the plurality of displays **920**. The fourth integration form refers to integration of the first to third displays **921** to **923** on the basis of the position of the second display **922** among the plurality of displays **920**. The fifth integration form refers to integration of the first to third displays **921** to **923** on the basis of the position of the third display **923** among the plurality of displays **920**. The first to fifth integration forms according to an embodiment of the present invention are described with three displays as references. However, this is only one embodiment, and in another embodiment, there may be a smaller or larger number of displays.

(63) Some or all of the plurality of displays **920** are moved in the second direction and/or the third direction (**S1040**). When a determination is made that the parking mode or the autonomous driving mode of the vehicle has been activated, the plurality of displays **920** may be integrated with each other on the basis of position information of occupants in the vehicle. For example, when a determination is made that an occupant is located on a left front side or a right front side inside the vehicle, some or all of the plurality of displays **920** may be combined to the left side or right side along the longitudinal direction of the cockpit **1200**.

(64) The video is output using the integrated display (**S1050**). The video output unit **933** outputs a video using the first integrated display **1500** and the second integrated display **1700**.

(65) When a determination is made in step **S1020** that the integration of the plurality of displays **920** is not necessary, a driving state of the plurality of displays **920** is maintained (**S1060**). When

the integration of the plurality of displays **920** is not necessary, a state in which the first display **921**, the second display **922**, and the third display **923** are rolled or slid in the first direction is maintained.

(66) FIG. **11** is a flowchart specifically illustrating step **S1050** of FIG. **10**.

(67) Referring to FIG. **11**, a video signal is received (**S1110**). The video signal reception unit **931** receives a video signal including video information output to the integrated display.

(68) A determination is made as to whether some of the plurality of displays **920** have been integrated (**S1120**). The display control unit **930** may determine whether some or all of the plurality of displays **920** have been integrated.

(69) When a determination is made in step **S1120** that some of the plurality of displays **920** have been integrated, a video ratio corresponding to a size of the first integrated display **1500** is adjusted (**S1130**). The first integrated display **1500** has a display size in which two of the plurality of displays **920** have been integrated. Accordingly, the ratio adjustment unit **932** may adjust the video ratio corresponding to the size of the first integrated display **1500**.

(70) When a determination is made in step **S1120** that some of the plurality of displays **920** have not been integrated, a determination is made that all of the plurality of displays **920** have been integrated (**S1140**). Accordingly, the ratio adjustment unit **932** may adjust the video ratio corresponding to the size of the second integrated display **1700**.

(71) The video is output by using one integrated display (**S1150**). Here, the one integrated display includes the first integrated display **1500** or the second integrated display **1700**. The video output unit **933** outputs the video on the basis of a video ratio based on the size of the first integrated display **1500** or the second integrated display **1700**.

(72) FIG. **12** is a diagram illustrating an operating state of the plurality of displays **920** that output videos of a traveling vehicle according to an embodiment of the present invention.

(73) Referring to FIG. **12**, when the user is driving by manipulating a steering wheel, a forward viewing angle corresponding to a windshield **1240** of the vehicle should be secured. Accordingly, the first to third displays **921** to **923** all output video information necessary for traveling on the basis of a state in which the displays are rolled or slid by a predetermined height. For example, the first display **921** may output position information of a traveling vehicle. The second display **922** may output navigation information. The third display **923** may output an entertainment video. Here, the video information output to each of the first to third displays **921** to **923** is only an example, and the present disclosure is not limited thereto. This is only an embodiment, and in another embodiment, video information different from the video information illustrated in FIG. **12** may be output on each of the first to third displays **921** to **923**.

(74) FIG. **13** is a diagram illustrating an operating state of the second display **922** in which the display is rolled or slid to the maximum size according to an embodiment of the present invention.

(75) Referring to FIG. **13**, when the parking mode or the autonomous driving mode of the vehicle has been activated, the second display **922** among the plurality of displays **920** may be rolled or slid to the maximum size. Passengers of the vehicle, including a driver, can view various types of video information using the second display **922** exposed to the maximum size.

(76) FIG. **14** is a diagram illustrating an operating state of the plurality of displays **920** in which the parking mode or the autonomous driving mode has been activated according to an embodiment of the present invention.

(77) FIG. **15** is a diagram illustrating operating state in which a video is output by using the first integrated display **1500** according to an embodiment of the present invention.

(78) Referring to FIGS. **13** to **15**, after the second display **922** is exposed to a maximum size, the first display **921** and the third display **923** are also rolled or slid to a maximum size. The plurality of displays **920** may determine whether or not the plurality of displays **920** have been integrated by using an operation of the user or sensors disposed inside the vehicle. Here, the integration form of the plurality of displays **920** may be a form of the first integrated display **1500**. The second display

922 may be moved toward the first display **921** along the drive unit **910** with the position of the first display **921** as a reference and integrated with the first display **921**.

(79) In FIG. **15**, a case where the second display **922** moves toward the first display **921** and the first display **921** and the second display **922** are integrated has been illustrated, but the first integrated display **1500** is not limited. In the first integrated display **1500**, either the first display **921** or the third display **923** may be integrated with the second display **922** with the position of the second display **922** as a reference. Further, the second display **922** may be integrated with the third display **923** with the position of the third display **923** as a reference.

(80) FIG. **16** is a block configuration diagram briefly illustrating a configuration of the main control unit and the auxiliary control unit for adjusting a video ratio of the integrated display according to an embodiment of the present invention.

(81) Referring to FIGS. **15** and **16**, the rollable display apparatus **900** may further include a main control unit **1610** and an auxiliary control unit **1620**.

(82) The main control unit **1610** includes a first video signal reception unit **1611**, a ratio adjustment unit **1613**, and a first video output unit **1615**. The main control unit **1610** may be an electronic control unit disposed in any one of the first to third displays **921** to **923**. Hereinafter, a case in which the main control unit **1610** is disposed in the second display **922** among the first to third displays **921** to **923** will be described.

(83) When the second display **922** is integrated with the first display **921** or the third display **923** to form the first integrated display **1500**, the main control unit **1610** may adjust a ratio of a video. For example, the main control unit **1610** receives a video signal to be output to the first integrated display **1500** by using the first video signal reception unit **1611**.

(84) The de-serializers **1612** and **1622** de-serialize the serialized video signal received by the first video signal reception unit **1611**.

(85) The ratio adjustment unit **1613** adjusts the de-serialized video signal to a video ratio corresponding to a screen size of the first display **921** and the second display **922**. A serializer **1614** serializes the video signal on the basis of the adjusted video ratio and transmits the resultant video ratio to the first video output unit. The first video output unit may output a video at a first video ratio by using, for example, the second display **922**.

(86) The auxiliary control unit **1620** includes a second video signal reception unit **1621** and a second video output unit **1623**.

(87) The auxiliary control unit **1620** is disposed on the first display **921** and the third display **923**. Although only one auxiliary control unit **1620** is illustrated in FIG. **9**, the number of auxiliary control units **1620** may be proportional to the number of displays **920**. For example, when the main control unit **1610** is an electronic control unit of the second display **922**, the auxiliary control unit **1620** may be an electronic control unit of each of the first display **921** and the second display **922**.

(88) The second video signal reception unit **1621** may receive the video signal output from the first video output unit of the main control unit **1610**. The de-serializer **822** de-serializes the video information received by the second video signal reception unit **1621** and transmits the resultant video information to the second video output unit. The second video output unit may output the video at a second video ratio by using the first display **921**. Accordingly, the first integrated display **1500** may output video information on the basis of the first video ratio and the second video ratio by using the first display **921** and the second display **922**.

(89) FIG. **17** is a diagram illustrating operating state in which video information is output by using the second integrated display **1700** of the present invention.

(90) Referring to FIG. **17**, the plurality of displays **920** may be all integrated to form the second integrated display **1700**. The second integrated display **1700** may have a largest size as compared with the plurality of displays **920**. In FIG. **9**, the second integrated display **1700** in which the first display **921** and the third display **923** are moved toward and integrated with the second display **922** with the position of the second display **922** as a reference has been illustrated, but the present

disclosure is not limited thereto. The second integrated display **1700** may be located at any one place on the rail structure of the drive unit **910**.

(91) Although not illustrated in FIG. **17**, the second integrated display **1700** adjusts the video ratio using the same control method as the control method for adjusting the video ratio of the first integrated display **1500**. For example, the video information may be output using the first to third displays **921** to **923** on the basis of the video signal to be output to the second integrated display **1700**.

Claims

1. A rollable display apparatus disposed in a vehicle, comprising: a display panel configured to display a video; a rolling part located at one end of the display panel and including an internal space in which the display panel is rolled and accommodated; a supporter located at another end of the display panel; and an anchor body configured such that at least one area of the rolling part and at least one area of the supporter are detachable from the anchor body, and comprising a plurality of anchor areas configured to maintain an unrolled state of the display panel when the at least one area of the rolling part and the at least one area of the supporter are attached to the anchor body.
2. The rollable display apparatus of claim 1, wherein: the rolling part includes a first connector to transmit and receive an electrical signal to and from the display panel, and each of the plurality of anchor areas includes a second connector electrically connected to the first connector.
3. The rollable display apparatus of claim 2, wherein, the plurality of anchor areas are configured such that the second connectors have connection pins that are differently arranged from each other so that the display panel recognizes attachment positions of the first connectors and an unrolled state of the display panel.
4. The rollable display apparatus of claim 1, wherein: the supporter includes a first connector to transmit and receive an electrical signal to and from the display panel, and each of the plurality of anchor areas includes a second connector electrically connected to the first connector.
5. The rollable display apparatus of claim 4, wherein, the plurality of anchor areas are configured such that the second connectors have connection pins that are differently arranged from each other so that the display panel recognizes attachment positions of the first connector and an unrolled state of the display panel.
6. The rollable display apparatus of claim 1, wherein the anchor body includes the internal space configured to accommodate the rolling part and the supporter.
7. The rollable display apparatus of claim 1, wherein the anchor body is integrated with a cockpit, a ceiling, an armrest, and a rear part of a seat of the vehicle.
8. A rollable display apparatus disposed in a vehicle, comprising: a display panel configured to display a video; a rolling part located at one end of the display panel and including an internal space in which the display panel is rolled and accommodated; a supporter coupled to another end of the display panel; and a plurality of anchor areas disposed inside the vehicle, configured such that at least one area of the rolling part and at least one area of the supporter are detachable from the plurality of anchor areas, and configured to maintain an unrolled state of the display panel when the at least one area of the rolling part and the at least one area of the supporter are attached to the plurality of anchor areas.
9. A rollable display apparatus comprising: a display panel configured to display a video; a first rolling part coupled to one end of the display panel and including an internal space in which a portion of the display panel is rolled and accommodated; a second rolling part coupled to another end of the display panel and including an internal space in which a portion other than the portion of the display panel that is rolled and accommodated in the first rolling part is rolled and accommodated; and an anchor body including a plurality of anchor areas, the anchor areas configured such that at least one area of the first rolling part and at least one area of the second

rolling part are detachable from the anchor body, and configured to maintain an unrolled state of the display panel when the at least one area of the first rolling part and the at least one area of the second rolling part are attached to the anchor body.
