

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413524
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Sowpati; Praveenkumar et al.

Access control for restricted entities

Abstract

Methods, apparatuses, and computer-program products are disclosed. A method may include activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity. The method may include generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including access configurations for the processing entity. The method may include retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the plurality of access configurations and the one or more first access configurations may be associated with the processing entity.

Inventors: Sowpati; Praveenkumar (Bangalore, IN), P J; Jose Lejin (Bangalore, IN), Talla; Ramanjaneyulu Y (Bangalore, IN)

Applicant: Salesforce, Inc. (San Francisco, CA)

Family ID: 93120978

Assignee: Salesforce, Inc. (San Francisco, CA)

Appl. No.: 18/303314

Filed: April 19, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240356854 A1	Oct. 24, 2024

Publication Classification

Int. Cl.: G06F15/173 (20060101); H04L47/125 (20220101)

U.S. Cl.:

CPC **H04L47/125** (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0034669	12/2020	McLaughlin	N/A	G06F 16/8365

Primary Examiner: Chan; Wing F

Assistant Examiner: Woo; Andrew

Attorney, Agent or Firm: Holland & Hart LLP

Background/Summary

FIELD OF TECHNOLOGY

(1) The present disclosure relates generally to database systems and data processing, and more specifically to access controls and configurations for restricted entities.

BACKGROUND

(2) A cloud platform (i.e., a computing platform for cloud computing) may be employed by multiple users to store, manage, and process data using a shared network of remote servers. Users may develop applications on the cloud platform to handle the storage, management, and processing of data. In some cases, the cloud platform may utilize a multi-tenant database system. Users may access the cloud platform using various user devices (e.g., desktop computers, laptops, smartphones, tablets, or other computing systems, etc.).

(3) In one example, the cloud platform may support customer relationship management (CRM) solutions. This may include support for sales, service, marketing, community, analytics, applications, and the Internet of Things. A user may utilize the cloud platform to help manage contacts of the user. For example, managing contacts of the user may include analyzing data, storing and preparing communications, and tracking opportunities and sales.

(4) In some cloud platform scenarios, access controls and configurations for processing entities may be employed. However, such approaches may be improved.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates an example of a system for data processing that supports access control for restricted entities in accordance with examples provided herein.

(2) FIG. 2 shows an example of an access control system that supports access control for restricted entities in accordance with examples provided herein.

- (3) FIG. 3 shows an example of an access control system that supports access control for restricted entities in accordance with examples provided herein.
- (4) FIG. 4 shows an example of a process flow that supports access control for restricted entities in accordance with examples provided herein.
- (5) FIG. 5 shows a block diagram of an apparatus that supports access control for restricted entities in accordance with examples provided herein.
- (6) FIG. 6 shows a block diagram of an access manager that supports access control for restricted entities in accordance with examples provided herein.
- (7) FIG. 7 shows a diagram of a system including a device that supports access control for restricted entities in accordance with examples provided herein.
- (8) FIGS. 8 through 10 show flowcharts illustrating methods that support access control for restricted entities in accordance with examples provided herein.

DETAILED DESCRIPTION

(9) Service-oriented architectures running in private cloud substrates may include highly restricted entities (e.g., sub-networks, groups of devices, or individual devices) that may be subject to restrictions due to increased security or limited access (e.g., due to sensitive or confidential data). It is technically complex to configure access control lists in such restricted environments (e.g., even administrators may not have permissions to configure access for entities in the restricted environment). Further, existing approaches to configure access control may operate by directly calling application programming interface (API) endpoints or via commands that directly interface the entity with other resources. However, such approaches may not function in highly restricted entities or environments, as, for example, such APIs or commands may not be accessible or such an access may pose a security risk. Additionally, some datacenters may include thousands or tens of thousands of entities that may be operating in a restricted environment or may be restricted entities, thereby requiring complicated access configuration at large scale. Further, different entities may have network topologies or characteristics (e.g., entities may include different types, formats, or configurations of devices or nodes), and configuration solutions may not be generalized across such different topologies or characteristics. As such, access control for such environments may be improved.

(10) Techniques for access control in highly restricted environments at scale may be employed. For example, an agent object or program may be inserted or activated in a restricted processing entity alongside a manifest for the entity (e.g., that describes one or more characteristics associated with the processing entity). The agent may allow a system or application server to configure the connection (e.g., access control configurations or parameters) for the restricted entity. For example, the system may configure a collection of one or more dynamic endpoints (e.g., randomly generated endpoints) that may be used for retrieving a configuration for the restricted entity. Further, the system may select or create one or more such dynamic endpoints based on information included in the manifest for the entity and different entities may be associated with different characteristics that may lead to different information being included in respective manifests, so that the dynamic endpoints may be selected or created to suit the different restricted entities' configurations needs. These various dynamic endpoints may include or provide access to one or more APIs that the restricted entities may use to retrieve their configuration information. Once the agent is aware of the various endpoints available, the agent may then connect to the APIs through the dynamic endpoints to retrieve the associated configuration(s) for the entity.

(11) In this way, even restricted entities with limitations due to security practices (e.g., that may not otherwise be configured for access due to such restrictions, such as a lack of access to APIs or direct configuration by administrators) may be configured for access. Additionally, or alternatively, security levels or protocols may be maintained for such restricted entities. For example, calls are made from the restricted entities and no calls made outside the restricted cloud substrate are directed into the restricted cloud substrate. Further, storage that may maintain the access

configurations may also be kept secure and access may be permitted by the processing entities using the dynamic endpoints while denying access to other entities.

(12) In some examples, once the dynamic endpoints are used to configure a processing entity, the dynamic endpoints may be disabled or may be self-disabling (e.g., to increase security).

Additionally, or alternatively, in some examples, one or more dynamic endpoints may be reassigned for use by a different processing entity that may access the same resources that a first processing entity accessed. In some examples, the dynamic endpoints may be mapped to one or more services that may retrieve one or more aspects of one or more access configurations. Further, in some examples, the dynamic endpoints may be randomly generated (e.g., address of such endpoints may be randomly generated) to support security considerations.

(13) Aspects of the disclosure are initially described in the context of an environment supporting an on-demand database service. Aspects of the disclosure are then described with reference to access control systems and a process flow. Aspects of the disclosure are further illustrated by and described with reference to apparatus diagrams, system diagrams, and flowcharts that relate to access control for restricted entities.

(14) FIG. 1 illustrates an example of a system **100** for cloud computing that supports access control for restricted entities in accordance with various aspects of the present disclosure. The system **100** includes cloud clients **105**, contacts **110**, cloud platform **115**, and data center **120**. Cloud platform **115** may be an example of a public or private cloud network. A cloud client **105** may access cloud platform **115** over network connection **135**. The network may implement transfer control protocol and internet protocol (TCP/IP), such as the Internet, or may implement other network protocols. A cloud client **105** may be an example of a user device, such as a server (e.g., cloud client **105-a**), a smartphone (e.g., cloud client **105-b**), or a laptop (e.g., cloud client **105-c**). In other examples, a cloud client **105** may be a desktop computer, a tablet, a sensor, or another computing device or system capable of generating, analyzing, transmitting, or receiving communications. In some examples, a cloud client **105** may be operated by a user that is part of a business, an enterprise, a non-profit, a startup, or any other organization type.

(15) A cloud client **105** may interact with multiple contacts **110**. The interactions **130** may include communications, opportunities, purchases, sales, or any other interaction between a cloud client **105** and a contact **110**. Data may be associated with the interactions **130**. A cloud client **105** may access cloud platform **115** to store, manage, and process the data associated with the interactions **130**. In some cases, the cloud client **105** may have an associated security or permission level. A cloud client **105** may have access to at least some applications, data, and database information within cloud platform **115** based on the associated security or permission level, and may not have access to others.

(16) Contacts **110** may interact with the cloud client **105** in person or via phone, email, web, text messages, mail, or any other appropriate form of interaction (e.g., interactions **130-a**, **130-b**, **130-c**, and **130-d**). The interaction **130** may be a business-to-business (B2B) interaction or a business-to-consumer (B2C) interaction. A contact **110** may also be referred to as a customer, a potential customer, a lead, a client, or some other suitable terminology. In some cases, the contact **110** may be an example of a user device, such as a server (e.g., contact **110-a**), a laptop (e.g., contact **110-b**), a smartphone (e.g., contact **110-c**), or a sensor (e.g., contact **110-d**). In other cases, the contact **110** may be another computing system. In some cases, the contact **110** may be operated by a user or group of users. The user or group of users may be associated with a business, a manufacturer, or any other appropriate organization.

(17) Cloud platform **115** may offer an on-demand database service to the cloud client **105**. In some cases, cloud platform **115** may be an example of a multi-tenant database system. In this case, cloud platform **115** may serve multiple cloud clients **105** with a single instance of software. However, other types of systems may be implemented, including—but not limited to—client-server systems, mobile device systems, and mobile network systems. In some cases, cloud platform **115** may

support CRM solutions. This may include support for sales, service, marketing, community, analytics, applications, and the Internet of Things. Cloud platform **115** may receive data associated with contact interactions **130** from the cloud client **105** over network connection **135**, and may store and analyze the data. In some cases, cloud platform **115** may receive data directly from an interaction **130** between a contact **110** and the cloud client **105**. In some cases, the cloud client **105** may develop applications to run on cloud platform **115**. Cloud platform **115** may be implemented using remote servers. In some cases, the remote servers may be located at one or more data centers **120**.

(18) Data center **120** may include multiple servers. The multiple servers may be used for data storage, management, and processing. Data center **120** may receive data from cloud platform **115** via connection **140**, or directly from the cloud client **105** or an interaction **130** between a contact **110** and the cloud client **105**. Data center **120** may utilize multiple redundancies for security purposes. In some cases, the data stored at data center **120** may be backed up by copies of the data at a different data center (not pictured).

(19) Subsystem **125** may include cloud clients **105**, cloud platform **115**, and data center **120**. In some cases, data processing may occur at any of the components of subsystem **125**, or at a combination of these components. In some cases, servers may perform the data processing. The servers may be a cloud client **105** or located at data center **120**.

(20) The system **100** may be an example of a multi-tenant system. For example, the system **100** may store data and provide applications, solutions, or any other functionality for multiple tenants concurrently. A tenant may be an example of a group of users (e.g., an organization) associated with a same tenant identifier (ID) who share access, privileges, or both for the system **100**. The system **100** may effectively separate data and processes for a first tenant from data and processes for other tenants using a system architecture, logic, or both that support secure multi-tenancy. In some examples, the system **100** may include or be an example of a multi-tenant database system. A multi-tenant database system may store data for different tenants in a single database or a single set of databases. For example, the multi-tenant database system may store data for multiple tenants within a single table (e.g., in different rows) of a database. To support multi-tenant security, the multi-tenant database system may prohibit (e.g., restrict) a first tenant from accessing, viewing, or interacting in any way with data or rows associated with a different tenant. As such, tenant data for the first tenant may be isolated (e.g., logically isolated) from tenant data for a second tenant, and the tenant data for the first tenant may be invisible (or otherwise transparent) to the second tenant. The multi-tenant database system may additionally use encryption techniques to further protect tenant-specific data from unauthorized access (e.g., by another tenant).

(21) Additionally, or alternatively, the multi-tenant system may support multi-tenancy for software applications and infrastructure. In some cases, the multi-tenant system may maintain a single instance of a software application and architecture supporting the software application in order to serve multiple different tenants (e.g., organizations, customers). For example, multiple tenants may share the same software application, the same underlying architecture, the same resources (e.g., compute resources, memory resources), the same database, the same servers or cloud-based resources, or any combination thereof. For example, the system **100** may run a single instance of software on a processing device (e.g., a server, server cluster, virtual machine) to serve multiple tenants. Such a multi-tenant system may provide for efficient integrations (e.g., using application programming interfaces (APIs)) by applying the integrations to the same software application and underlying architectures supporting multiple tenants. In some cases, processing resources, memory resources, or both may be shared by multiple tenants.

(22) As described herein, the system **100** may support any configuration for providing multi-tenant functionality. For example, the system **100** may organize resources (e.g., processing resources, memory resources) to support tenant isolation (e.g., tenant-specific resources), tenant isolation within a shared resource (e.g., within a single instance of a resource), tenant-specific resources in a

resource group, tenant-specific resource groups corresponding to a same subscription, tenant-specific subscriptions, or any combination thereof. The system **100** may support scaling of tenants within the multi-tenant system, for example, using scale triggers, automatic scaling procedures, scaling requests, or any combination thereof. In some cases, the system **100** may implement one or more scaling rules to enable relatively fair sharing of resources across tenants. For example, a tenant may have a threshold quantity of processing resources, memory resources, or both to use, which in some cases may be tied to a subscription by the tenant.

(23) For example, a cloud client **105** may be included in a restricted processing entity associated with a restricted cloud substrate (e.g., which may be associated with a restricted business group or business unit). The cloud client **105** may not allow direct access or configuration of access control due to restricted or secure characteristics. As such, the cloud platform **115** may activate a connection agent and a manifest in the cloud client **105** and generate one or more dynamic endpoints

(24) In some cases, administrators may not have direct access to entities or nodes operating in highly restricted environments (e.g., due to security measures or configurations). In some examples, even senior or core administrators do not have access. Additionally, some API commands or even entire APIs may not be accessible by an entity within the restricted environment. Further, many cloud platforms involve multiple data centers or large quantities of entities with complex configurations, topologies, hierarchies, network organizations, device types, and other considerations.

(25) The subject matter described herein reduces or eliminates such challenges by inserting agents into the entities that communicate with randomly generated endpoints connected to retrieval services, some or all of which may be contained within the restricted environment. These retrieval services may then connect to external, secure storage that includes one or more aspects of one or more access configurations that may be used to configure access for the restricted entities. In this way, even though administrators may not have access to entities, or some APIs may not otherwise be available, the agent injected into the restricted entity may connect to the randomly generated API endpoints that, in some cases, may be specifically generated for the entity and allow the access configuration information to be retrieved. These API endpoints may then be disabled after usage and sometimes regenerated dynamically to prevent unauthorized devices from accessing the access configuration information, maintaining security.

(26) For example, in response to detecting the presence of a processing entity (which itself may include one or more devices), the system may inject the connection agent into the entity. The entity may already have a manifest describing characteristics or other information associated with the entity. Using these characteristics, the system may generate one or more dynamic endpoints for the connection agent to connect to and retrieve access configuration information from secure storage (e.g., that may be outside the restricted environment). For example, some devices may be configured differently from other devices, which may result in different methods or information used to configure access for the devices. By accounting for these differences, the system can provide a secure connection for the connection agent to retrieve the configuration information and configure access for the entity, even though an administrator may not be able to directly configure such information and there are security restrictions or limitations in place in the restricted environment.

(27) It should be appreciated by a person skilled in the art that one or more aspects of the disclosure may be implemented in a system **100** to additionally or alternatively solve other problems than those described herein. Further, aspects of the disclosure may provide technical improvements to “conventional” systems or processes as described herein. However, the description and appended drawings only include example technical improvements resulting from implementing aspects of the disclosure, and accordingly do not represent all of the technical improvements provided within the scope of the claims.

(28) FIG. 2 shows an example of an access control system **200** that supports access control for restricted entities in accordance with examples provided herein.

(29) In some cases, a cloud substrate **215** may be described as an underlying infrastructure (e.g., such as a physical datacenter infrastructure that may be managed by an organization). The cloud substrate **215** may, in some cases, be a private cloud substrate. The substrate may include different categories, divisions, or other organizational elements (e.g., data center, network, storage, rack provisioning, architecture, hardware engineering, one or more other elements, or any combination thereof) that may form a base layer for products in the organization to operate and innovate on.

(30) In some examples, service-oriented architectures running in private cloud substrates may include large quantities of highly restricted entities. It is not straightforward to configure access configurations (e.g., access control lists (ACLs)) in these restricted environments. For example, most service administrators may not have access to such restricted entities, and even senior or core system administrators may not have direct access. Such entities may be associated with commerce, government operations, or other operations that may involve increased security or restrictions.

(31) In some examples, access configuration information (e.g., including ACLs) may include configuration information associated with network traffic (e.g., L3 or L4 network layer traffic, one or more other network layers, or any combination thereof). For example, such information may include internet protocol (IP) addresses, ports, and domain names, as well as other configuration information such as settings, permissions, policies, or other configuration information.

(32) Some other approaches for configuring access for processing entities directly call API endpoints or issue commands that are directly executed in entities. However, in restricted environments, such APIs or commands may not be accessible. Further, data centers often operate on large scales, including large quantities of entities. Such entities may include sub-networks, service pods, or other data center divisions or organizations, and configuration of such is not simple. Further, in some cases, different entities may include different network topologies different types of devices or nodes, one or more other differing characteristics, or any combination thereof. As such, approaches for configuring access for such entities cannot be simply generalized for a configuration solution.

(33) As such the techniques and architecture described herein provides efficient, scalable, and reliable manners of configuring access for entities in highly restricted data environments.

(34) For example, the access control system **200** may inject the agent **225** and the manifest **230** into the processing entity **220**. The manifest **230** may include a data signature of data associated with the processing entity **220**, one or more compatible endpoint types for the processing entity **220**, other information, or any combination thereof. The access control system **200** may generate the endpoints **235** to which the agent **225** may connect. The endpoints **235** may be randomly generated endpoints that may be generated specifically for the processing entity **220**. For example, the access control system **200** may read the information stored in the manifest **230** (e.g., the data signature of data associated with the processing entity **220**, one or more compatible endpoint types for the processing entity **220**, other information, or any combination thereof) and generate the endpoints **235** based on such information. The endpoints **235** may be associated with corresponding APIs **240** that may connect to the repository **245** that is located outside the cloud substrate **215**, and these APIs **240** may be mapped to retrieval services for retrieving one or more access configurations **250**. The repository **245** may include or store the one or more access configurations **250** that may themselves include entire configurations, partial configurations, or other information that may be used by the agents **225** to configure the processing entity **220** for access even though the processing entity **220**, the cloud substrate **215**, or both may operate in a restricted environment.

(35) FIG. 3 shows an example of an access control system **300** that supports access control for restricted entities in accordance with examples provided herein. Though some example connections, data paths, or arrangements are shown and described, other connections, data paths, and arrangements are possible and contemplated by the subject matter described herein.

(36) The access control system **300** may include a cloud substrate **315** that may itself include entities, devices, networks, subnetworks, or other organizational divisions of one or more data centers for processing. For example, the cloud substrate **315** may include multiple highly restricted processing entities **320** such as network devices, logical network groups (e.g., container pods), one or more collections of heterogeneous services, service groups, other processing devices, nodes, or services, or any combination thereof. In some cases, a processing entity **320** may include many types of devices.

(37) Since these processing entities **320** may be restricted for access, there may be no direct way to configure them. As such, in response to the processing entity **320** being deployed or activated, the access control system **300** may cause the injector **395** to inject the agent **325**, the manifest **330**, or both into the processing entity **320**. For example, in some cases, the manifest **330** may be included as part of the activation or provisioning of the processing entity **320**, or it may be added (e.g., by the injector **395**) at another time. In some examples, the access control system **300** may monitor for the presence of the processing entity **320** and may inject the agent **325** into the processing entity **320** alongside an already present manifest **330** in the processing entity **320**. In some examples, the agent **325** may activate automatically after or in response to being injected into the processing entity **320**.

(38) In some examples, the manifest **330** may not include actual endpoint names, addresses, or paths, but may instead include one or more of a data signature **332**, an endpoint type **333**, or both. In some examples, the data signature **332** may include or indicate a data format, a quantity of data, a data configuration rate, one or more dependent configurations, or any combination thereof. In some examples, the endpoint type may include or indicate a representational state transfer (REST) API model, a global remote procedure call (RPC) API model, an input schema, an output schema, or any combination thereof.

(39) In some examples, the access control system **300** may include an endpoint generator **335**. The endpoint generator **335** may monitor for the presence of the processing entity **320** and (e.g., in response to detecting the processing entity **320**), may scan the processing entity **320** (e.g., to obtain additional information about the processing entity **320** for generating the endpoints **350** that are associated with the APIs **355**). In some examples, to detect the processing entity **320**, to scan the processing entity **320**, or both, the injector **395** may use dynamic discovery methods, such as port polling, network traffic change monitoring, network advertisement monitoring, other monitoring or scanning approaches, or any combination thereof.

(40) In some examples, the endpoint generator **335** (e.g., based on scanning the processing entity **320**) may obtain an indication of an available endpoint of the agent **325** and may communicate with the agent **325** via such an endpoint. The endpoint generator **335** may generate one or more dynamic endpoints **350** to which the processing entity **320** may connect to fetch the access configurations **370**. In some cases, the endpoints **350** may be reused, regenerated, or reassigned for another processing entity **321** (that may include its own agent **326** and manifest **331**) to use. Further, the endpoints **350** may be associated with one or more load balancers **390**, as, in some examples, multiple processing entities **320** may connect to the same endpoint(s) **350**. In some examples, the agent **325**, the endpoint generator **335**, or both may read the information stored in the manifest **330** (e.g., the data signature **332**, the endpoint type **333**, or both) and may determine what type or configuration of one or more endpoints **350** are to be generated for the processing entity **320**. Additionally, such endpoints **350** may include authentication built into the endpoints **350** so that access to the endpoints **350** may be restricted to the processing entity **320** or multiple processing entities **320** for which access is intended or specified (e.g., based on information in the manifest **330**).

(41) The processing entity **320** (e.g., either using the agent **325** or by other means) may then connect to the endpoints **350**. However, to form such a connection, the processing entity **320** may connect to the load balancer **385** (e.g., which may be used to balance the load of multiple

processing entities **320**) and may then connect to the endpoint dispatcher **345**. The endpoint dispatcher **345** may be a collection of such dispatchers operating in a cluster. In some examples, the endpoint dispatcher **345** may translate, encode, or decode information passed between the processing entity **320** and the endpoints **350** (e.g., API requests, data, access configuration information, logs, or other information associated with the operation of the access control system **300**). For example, the processing entity **320** includes a first type of device, then the endpoint dispatcher **345** may translate, decode, encode, or otherwise convert information to support communications of the first type of device in the processing entity **320** in one or more formats that are compatible with the first type of device.

(42) By connection to the endpoints **350** of the APIs **355**, the processing entity **320** may gain access to one or more services that may provide the configuration information for access for the processing entity **320** to other resources. The system may offer such access to services using the endpoint realizer cluster **360**. The endpoint realizer cluster **360** may itself be an entity within the cloud substrate **315** that may itself be a restricted entity or may operate within a restricted environment. The endpoint realizer cluster **360** may include a collection of services that may communicate with the processing entity **320** to retrieve configuration information and may also communicate with one another. For example, if an endpoint **350** is to be used with combined information from multiple services, the endpoint **350** may be mapped (e.g., by the endpoint realizer cluster **360**) to the corresponding services. Such services may themselves communicate, such as to generate consolidated data responses. In some examples, correct information may be formed by nested calls of multiple services until the requested data is compiled, organized, transmitted, or any combination thereof.

(43) In some examples, the APIs **355** are not simple APIs, but may be a collection of different sets of APIs serving the processing entity **320** to retrieve configuration information. In some cases, a single processing entity **320** may connect to hundreds of such APIs **355** to retrieve different access data or configurations, such as ACL ingress block information, ACL egress block information, ACL settings, ACL permissions, other access configuration information, or any combination thereof.

(44) As the endpoints are dynamically generated, the component lifecycle manager **340** (e.g., which may be coupled with the endpoint generator **335**) may manage the lifecycles of the endpoints **350**. For example, if any of the endpoints are not used by any processing entity **320**, the endpoint may be self destroyed or disabled. For at least this purpose, references may be automatically tracked and, optionally, a lifetime or expiration for the endpoints **350** may be applied.

(45) Once the endpoints **350** are active, the agent **325** may receive information about the endpoints **350** (e.g., endpoint configurations, addresses, or other information) used to connect to the endpoints **350**. The agent **325** may then connect or trigger the endpoints **350** of the APIs **355** to begin retrieval of the access configuration information. Such triggering may, for example, be done via representational state transfer (REST) or global remote procedure calls (RPC).

(46) In response, the endpoint realizer cluster **360** may connect to the repository **365** which may be an external data source. For example, the **365** may be any data storage implementation that may include or store the access configurations **370**. The access configurations **370** may include complete access configurations, partial access configurations, other access configuration information, or any combination thereof, that the processing entity **320** may use to configure access. For example, the repository **365** may include configuration information such as a global L3/L4 configuration of networks.

(47) This repository **365** may be outside of the highly restricted environment (e.g., outside of the cloud substrate **315**). By using this architecture, no call from outside is made inside such a highly restricted environment. In other words, the call direction may be from the highly restricted environment (e.g., the cloud substrate **315**), and may be performed on an “as-needed” or “on-demand” basis. Further, the repository **365** may be configured such that the access configurations **370** may be pulled from the cloud substrate **315** or other highly restricted environment, and the

access configurations **370** may not be pulled from a different environment or entity, including tight or strict authentication and authorization.

(48) In some examples, the agent **325** may receive the access configurations **370** for the processing entity **320**. The access configurations **370** may be translated, encoded, decoded, or otherwise altered to match a format associated with the processing entity **320** or one or more devices associated with the processing entity **320**. In some examples, the agent **325** may process and validate the received access configurations **370**. After passing the processing and validation, the agent **325** may convert the access configurations **370** or information included therein into one or more access policies, device configurations, or both, that may be pushed to one or more target devices, services, or entities of the processing entity **320**. Once the one or more policies are pushed and activated in the targets, access configuration may be completed. However, in the case of errors at any point in the process, the agent **325** may resolve such errors by repeating one or more actions or operations or may alter one or more settings or configurations in efforts to retrieve and implement the access configurations **370**. Additionally, or alternatively, the agent **325** may revert one or more changes made if an operation results in an error.

(49) Throughout the various operations described herein, some or all of the different components or operations may generate logs and statistics. Such logs and statistics may be redirected to the endpoint dispatcher **345**. The endpoint dispatcher **345** may transmit the logs and statistics to the log analyzer **380**. In some examples, one or more formats of the logs and statics may be encrypted such that other entities besides the log analyzer **380** may not be able to read the logs and statistics. The log analyzer **380** may analyze, compile, and provide logs, statistics, results, other monitoring information, or any combination thereof to administrators on demand.

(50) Further, the change tracker **375** may create work items, progress information, or other monitoring information that may be made available to management or administrators to maintain visibility on operations being performed in the restricted environment.

(51) FIG. **4** shows an example of a process flow **400** that supports access control for restricted entities in accordance with examples provided herein. The process flow **400** may implement various aspects of the present disclosure described herein. The elements described in the process flow **400** (e.g., the application server **405**, the processing entity **410**, the repository **415**, or any combination thereof) may be examples of similarly named elements described herein.

(52) In the following description of the process flow **400**, the operations between the various entities or elements may be performed in different orders or at different times. Some operations may also be left out of the process flow **400**, or other operations may be added. Although the various entities or elements are shown performing the operations of the process flow **400**, some aspects of some operations may also be performed by other entities or elements of the process flow **400** or by entities or elements that are not depicted in the process flow, or any combination thereof.

(53) At **420**, the application server **405** may monitor for a presence of the processing entity **410**.

(54) At **425**, the application server **405** may activate, in a processing entity **410**, a connection agent and a manifest, the manifest that may include a data signature and an endpoint type that are associated with the processing entity **410**. In some examples, the application server **405** may activate, in the processing entity **410**, the connection agent based on detecting the presence of the processing entity **410**. In some examples, the data signature may indicate a data format, a quantity of data, a data configuration rate, one or more dependent configurations, or any combination thereof. In some examples, the endpoint type may indicate a representational state transfer (REST) API model, a global remote procedure call (RPC) API model, an input schema, an output schema, or any combination thereof.

(55) At **430**, the application server **405** may receive, from the connection agent, an access request indicating the one or more first access configurations; and

(56) At **435**, the application server **405** may map the one or more load balanced dynamic endpoints to one or more access configuration retrieval services associated with the plurality of access

configurations.

(57) At **440**, the application server **405** may generate, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository **415** that may include a plurality of access configurations for the processing entity **410**. In some examples, the one or more load balanced dynamic endpoints disallow connections from processing entities different than the processing entity **410**.

(58) At **445**, the application server **405** may generate random endpoint addresses associated with the one or more load balanced dynamic endpoints.

(59) At **450**, the application server **405** may retrieve, via the one or more load balanced dynamic endpoints and from the repository **415**, one or more first access configurations of the plurality of access configurations and the one or more first access configurations are associated with the processing entity **410**. In some examples, the application server **405** may retrieve the one or more first access configurations based on the access request. In some examples, the application server **405** may retrieve the one or more first access configurations via the one or more access configuration retrieval services. In some examples, the plurality of access configurations comprises one or more access control lists, one or more internet protocol address configurations, one or more domain name configurations, one or more permissions configurations, one or more access policy configurations, one or more network layer configurations, one or more transport layer configurations, one or more ingress block configurations, one or more egress block configurations, or any combination thereof.

(60) At **455**, the application server **405** may translate the one or more first access configurations from a first format to a second format that corresponds to the processing entity **410**.

(61) At **460**, the application server **405** may transmit the translated one or more first access configurations to the processing entity **410** via the connection agent.

(62) At **465**, the application server **405** may disassociate the one or more load balanced dynamic endpoints from the processing entity **410**.

(63) At **470**, the application server **405** may associate the one or more load balanced dynamic endpoints with a second processing entity **410**.

(64) At **475**, the application server **405** may disable the one or more load balanced dynamic endpoints based on retrieving, via the one or more load balanced dynamic endpoints, the one or more first access configurations.

(65) At **480**, the application server **405** may store one or more records (e.g., logs, work items, or other records, which may be associated with a log analyzer, a change tracker, or both, such as the log analyzer **380**, the change tracker **375**, or both) associated with activation of the connection agent, the manifest, or both, the generation of the one or more load balanced dynamic endpoints, a disablement of the one or more load balanced dynamic endpoints, a reassignment of the one or more load balanced dynamic endpoints, or any combination thereof.

(66) FIG. 5 shows a block diagram **500** of a device **505** that supports access control for restricted entities in accordance with examples provided herein. The device **505** may include an input module **510**, an output module **515**, and an access manager **520**. The device **505** may also include a processor. Each of these components may be in communication with one another (e.g., via one or more buses).

(67) The input module **510** may manage input signals for the device **505**. For example, the input module **510** may identify input signals based on an interaction with a modem, a keyboard, a mouse, a touchscreen, or a similar device. These input signals may be associated with user input or processing at other components or devices. In some cases, the input module **510** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system to handle input signals. The input module **510** may send aspects of these input signals to other components of the device **505** for processing. For

example, the input module **510** may transmit input signals to the access manager **520** to support access control for restricted entities. In some cases, the input module **510** may be a component of an I/O controller **710** as described with reference to FIG. 7.

(68) The output module **515** may manage output signals for the device **505**. For example, the output module **515** may receive signals from other components of the device **505**, such as the access manager **520**, and may transmit these signals to other components or devices. In some examples, the output module **515** may transmit output signals for display in a user interface, for storage in a database or data store, for further processing at a server or server cluster, or for any other processes at any quantity of devices or systems. In some cases, the output module **515** may be a component of an I/O controller **710** as described with reference to FIG. 7.

(69) For example, the access manager **520** may include an activation component **525**, an endpoint generation component **530**, a configuration retrieval component **535**, or any combination thereof. In some examples, the access manager **520**, or various components thereof, may be configured to perform various operations (e.g., receiving, monitoring, transmitting) using or otherwise in cooperation with the input module **510**, the output module **515**, or both. For example, the access manager **520** may receive information from the input module **510**, send information to the output module **515**, or be integrated in combination with the input module **510**, the output module **515**, or both to receive information, transmit information, or perform various other operations as described herein.

(70) The access manager **520** may support data processing at an application server in accordance with examples as disclosed herein. The activation component **525** may be configured to support activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity. The endpoint generation component **530** may be configured to support generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity. The configuration retrieval component **535** may be configured to support retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity.

(71) FIG. 6 shows a block diagram **600** of an access manager **620** that supports access control for restricted entities in accordance with examples provided herein. The access manager **620** may be an example of aspects of an access manager or an access manager **520**, or both, as described herein. The access manager **620**, or various components thereof, may be an example of means for performing various aspects of access control for restricted entities as described herein. For example, the access manager **620** may include an activation component **625**, an endpoint generation component **630**, a configuration retrieval component **635**, an access request component **640**, a mapping component **645**, an endpoint management component **650**, a configuration format component **655**, a monitoring component **660**, a logging component **665**, or any combination thereof. Each of these components may communicate, directly or indirectly, with one another (e.g., via one or more buses).

(72) The access manager **620** may support data processing at an application server in accordance with examples as disclosed herein. The activation component **625** may be configured to support activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity. The endpoint generation component **630** may be configured to support generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity. The configuration

retrieval component **635** may be configured to support retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity.

(73) In some examples, the access request component **640** may be configured to support receiving, from the connection agent, an access request indicating the one or more first access configurations. In some examples, the configuration retrieval component **635** may be configured to support retrieving the one or more first access configurations based on the access request.

(74) In some examples, the mapping component **645** may be configured to support mapping the one or more load balanced dynamic endpoints to one or more access configuration retrieval services associated with the set of multiple access configurations. In some examples, the configuration retrieval component **635** may be configured to support retrieving the one or more first access configurations via the one or more access configuration retrieval services.

(75) In some examples, the endpoint management component **650** may be configured to support disabling the one or more load balanced dynamic endpoints based on retrieving, via the one or more load balanced dynamic endpoints, the one or more first access configurations.

(76) In some examples, the endpoint management component **650** may be configured to support disassociating the one or more load balanced dynamic endpoints from the processing entity. In some examples, the endpoint management component **650** may be configured to support associating the one or more load balanced dynamic endpoints with a second processing entity.

(77) In some examples, the endpoint generation component **630** may be configured to support generating random endpoint addresses associated with the one or more load balanced dynamic endpoints.

(78) In some examples, the configuration format component **655** may be configured to support translating the one or more first access configurations from a first format to a second format that corresponds to the processing entity. In some examples, the configuration format component **655** may be configured to support transmitting the translated one or more first access configurations to the processing entity via the connection agent.

(79) In some examples, the monitoring component **660** may be configured to support monitoring for a presence of the processing entity. In some examples, the activation component **625** may be configured to support activating, in the processing entity, the connection agent based on detecting the presence of the processing entity.

(80) In some examples, the logging component **665** may be configured to support storing one or more records associated with activation of the connection agent, the manifest, or both, the generation of the one or more load balanced dynamic endpoints, a disablement of the one or more load balanced dynamic endpoints, a reassignment of the one or more load balanced dynamic endpoints, or any combination thereof.

(81) In some examples, the one or more load balanced dynamic endpoints disallow connections from processing entities different than the processing entity.

(82) In some examples, the set of multiple access configurations include one or more access control lists, one or more internet protocol address configurations, one or more domain name configurations, one or more permissions configurations, one or more access policy configurations, one or more network layer configurations, one or more transport layer configurations, one or more ingress block configurations, one or more egress block configurations, or any combination thereof.

(83) In some examples, the data signature indicates a data format, a quantity of data, a data configuration rate, one or more dependent configurations, or any combination thereof.

(84) In some examples, the endpoint type indicates a representational state transfer (REST) API model, a global remote procedure call (RPC) API model, an input schema, an output schema, or any combination thereof.

(85) FIG. 7 shows a diagram of a system **700** including a device **705** that supports access control

for restricted entities in accordance with examples provided herein. The device **705** may be an example of or include the components of a device **505** as described herein. The device **705** may include components for bi-directional data communications including components for transmitting and receiving communications, such as an access manager **720**, an I/O controller **710**, a database controller **715**, a memory **725**, a processor **730**, and a database **735**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **740**).

(86) The I/O controller **710** may manage input signals **745** and output signals **750** for the device **705**. The I/O controller **710** may also manage peripherals not integrated into the device **705**. In some cases, the I/O controller **710** may represent a physical connection or port to an external peripheral. In some cases, the I/O controller **710** may utilize an operating system such as iOS®, ANDROID®, MS-DOS®, MS-WINDOWS®, OS/2®, UNIX®, LINUX®, or another known operating system. In other cases, the I/O controller **710** may represent or interact with a modem, a keyboard, a mouse, a touchscreen, or a similar device. In some cases, the I/O controller **710** may be implemented as part of a processor **730**. In some examples, a user may interact with the device **705** via the I/O controller **710** or via hardware components controlled by the I/O controller **710**.

(87) The database controller **715** may manage data storage and processing in a database **735**. In some cases, a user may interact with the database controller **715**. In other cases, the database controller **715** may operate automatically without user interaction. The database **735** may be an example of a single database, a distributed database, multiple distributed databases, a data store, a data lake, or an emergency backup database.

(88) Memory **725** may include random-access memory (RAM) and ROM. The memory **725** may store computer-readable, computer-executable software including instructions that, when executed, cause the processor **730** to perform various functions described herein. In some cases, the memory **725** may contain, among other things, a BIOS which may control basic hardware or software operation such as the interaction with peripheral components or devices.

(89) The processor **730** may include an intelligent hardware device, (e.g., a general-purpose processor, a DSP, a CPU, a microcontroller, an ASIC, an FPGA, a programmable logic device, a discrete gate or transistor logic component, a discrete hardware component, or any combination thereof). In some cases, the processor **730** may be configured to operate a memory array using a memory controller. In other cases, a memory controller may be integrated into the processor **730**. The processor **730** may be configured to execute computer-readable instructions stored in a memory **725** to perform various functions (e.g., functions or tasks supporting access control for restricted entities).

(90) The access manager **720** may support data processing at an application server in accordance with examples as disclosed herein. For example, the access manager **720** may be configured to support activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity. The access manager **720** may be configured to support generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity. The access manager **720** may be configured to support retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity.

(91) By including or configuring the access manager **720** in accordance with examples as described herein, the device **705** may support techniques for improved communication reliability, reduced latency, improved user experience related to reduced processing, reduced power consumption, more efficient utilization of communication resources, improved coordination between devices, longer battery life, improved utilization of processing capability, or any combination thereof.

(92) FIG. 8 shows a flowchart illustrating a method **800** that supports access control for restricted entities in accordance with examples provided herein. The operations of the method **800** may be implemented by an application server or its components as described herein. For example, the operations of the method **800** may be performed by an application server as described with reference to FIGS. 1 through 7. In some examples, an application server may execute a set of instructions to control the functional elements of the application server to perform the described functions. Additionally, or alternatively, the application server may perform aspects of the described functions using special-purpose hardware.

(93) At **805**, the method may include activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity. The operations of **805** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **805** may be performed by an activation component **625** as described with reference to FIG. 6.

(94) At **810**, the method may include generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity. The operations of **810** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **810** may be performed by an endpoint generation component **630** as described with reference to FIG. 6.

(95) At **815**, the method may include retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity. The operations of **815** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **815** may be performed by a configuration retrieval component **635** as described with reference to FIG. 6.

(96) FIG. 9 shows a flowchart illustrating a method **900** that supports access control for restricted entities in accordance with examples provided herein. The operations of the method **900** may be implemented by an application server or its components as described herein. For example, the operations of the method **900** may be performed by an application server as described with reference to FIGS. 1 through 7. In some examples, an application server may execute a set of instructions to control the functional elements of the application server to perform the described functions. Additionally, or alternatively, the application server may perform aspects of the described functions using special-purpose hardware.

(97) At **905**, the method may include activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity. The operations of **905** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **905** may be performed by an activation component **625** as described with reference to FIG. 6.

(98) At **910**, the method may include generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity. The operations of **910** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **910** may be performed by an endpoint generation component **630** as described with reference to FIG. 6.

(99) At **915**, the method may include retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity. The operations of **915** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **915** may be performed by a configuration retrieval component **635** as described with reference to FIG. 6.

(100) At **920**, the method may include disabling the one or more load balanced dynamic endpoints based on retrieving, via the one or more load balanced dynamic endpoints, the one or more first access configurations. The operations of **920** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **920** may be performed by an endpoint management component **650** as described with reference to FIG. 6.

(101) FIG. 10 shows a flowchart illustrating a method **1000** that supports access control for restricted entities in accordance with examples provided herein. The operations of the method **1000** may be implemented by an application server or its components as described herein. For example, the operations of the method **1000** may be performed by an application server as described with reference to FIGS. 1 through 7. In some examples, an application server may execute a set of instructions to control the functional elements of the application server to perform the described functions. Additionally, or alternatively, the application server may perform aspects of the described functions using special-purpose hardware.

(102) At **1005**, the method may include activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity. The operations of **1005** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1005** may be performed by an activation component **625** as described with reference to FIG. 6.

(103) At **1010**, the method may include generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity. The operations of **1010** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1010** may be performed by an endpoint generation component **630** as described with reference to FIG. 6.

(104) At **1015**, the method may include generating random endpoint addresses associated with the one or more load balanced dynamic endpoints. The operations of **1015** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1015** may be performed by an endpoint generation component **630** as described with reference to FIG. 6.

(105) At **1020**, the method may include retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity. The operations of **1020** may be performed in accordance with examples as disclosed herein. In some examples, aspects of the operations of **1020** may be performed by a configuration retrieval component **635** as described with reference to FIG. 6.

(106) A method for data processing at an application server is described. The method may include activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity, generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity, and retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity.

(107) An apparatus for data processing at an application server is described. The apparatus may include a processor, memory coupled with the processor, and instructions stored in the memory. The instructions may be executable by the processor to cause the apparatus to activate, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity, generate, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by

the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity, and retrieve, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity.

(108) Another apparatus for data processing at an application server is described. The apparatus may include means for activating, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity, means for generating, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity, and means for retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity.

(109) A non-transitory computer-readable medium storing code for data processing at an application server is described. The code may include instructions executable by a processor to activate, in a processing entity, a connection agent and a manifest, the manifest including a data signature and an endpoint type that are associated with the processing entity, generate, based on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository including a set of multiple access configurations for the processing entity, and retrieve, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the set of multiple access configurations, where the one or more first access configurations are associated with the processing entity.

(110) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for receiving, from the connection agent, an access request indicating the one or more first access configurations and retrieving the one or more first access configurations based on the access request.

(111) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for mapping the one or more load balanced dynamic endpoints to one or more access configuration retrieval services associated with the set of multiple access configurations and retrieving the one or more first access configurations via the one or more access configuration retrieval services.

(112) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for disabling the one or more load balanced dynamic endpoints based on retrieving, via the one or more load balanced dynamic endpoints, the one or more first access configurations.

(113) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for disassociating the one or more load balanced dynamic endpoints from the processing entity and associating the one or more load balanced dynamic endpoints with a second processing entity.

(114) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for generating random endpoint addresses associated with the one or more load balanced dynamic endpoints.

(115) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for translating the one or more first access configurations from a first format to a second format that corresponds to the processing entity and transmitting the translated one or more first access configurations to the processing entity via the connection agent.

(116) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for monitoring for a presence of the processing entity and activating, in the processing entity, the connection agent based on detecting the presence of the processing entity.

(117) Some examples of the method, apparatuses, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for storing one or more records associated with activation of the connection agent, the manifest, or both, the generation of the one or more load balanced dynamic endpoints, a disablement of the one or more load balanced dynamic endpoints, a reassignment of the one or more load balanced dynamic endpoints, or any combination thereof.

(118) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the one or more load balanced dynamic endpoints disallow connections from processing entities different than the processing entity.

(119) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the set of multiple access configurations include one or more access control lists, one or more internet protocol address configurations, one or more domain name configurations, one or more permissions configurations, one or more access policy configurations, one or more network layer configurations, one or more transport layer configurations, one or more ingress block configurations, one or more egress block configurations, or any combination thereof.

(120) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the data signature indicates a data format, a quantity of data, a data configuration rate, one or more dependent configurations, or any combination thereof.

(121) In some examples of the method, apparatuses, and non-transitory computer-readable medium described herein, the endpoint type indicates a representational state transfer (REST) access point API model, a global remote procedure call (RPC) API model, an input schema, an output schema, or any combination thereof.

(122) The following provides an overview of aspects of the present disclosure:

(123) Aspect 1: A method for data processing at an application server, comprising: activating, in a processing entity, a connection agent and a manifest, the manifest comprising a data signature and an endpoint type that are associated with the processing entity; generating, based at least in part on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository comprising a plurality of access configurations for the processing entity; and retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the plurality of access configurations, wherein the one or more first access configurations are associated with the processing entity.

(124) Aspect 2: The method of aspect 1, further comprising: receiving, from the connection agent, an access request indicating the one or more first access configurations; and retrieving the one or more first access configurations based at least in part on the access request.

(125) Aspect 3: The method of any of aspects 1 through 2, further comprising: mapping the one or more load balanced dynamic endpoints to one or more access configuration retrieval services associated with the plurality of access configurations; and retrieving the one or more first access configurations via the one or more access configuration retrieval services.

(126) Aspect 4: The method of any of aspects 1 through 3, further comprising: disabling the one or more load balanced dynamic endpoints based at least in part on retrieving, via the one or more load balanced dynamic endpoints, the one or more first access configurations.

(127) Aspect 5: The method of any of aspects 1 through 4, further comprising: disassociating the one or more load balanced dynamic endpoints from the processing entity; and associating the one or more load balanced dynamic endpoints with a second processing entity.

(128) Aspect 6: The method of any of aspects 1 through 5, further comprising: generating random

endpoint addresses associated with the one or more load balanced dynamic endpoints.

(129) Aspect 7: The method of any of aspects 1 through 6, further comprising: translating the one or more first access configurations from a first format to a second format that corresponds to the processing entity; and transmitting the translated one or more first access configurations to the processing entity via the connection agent.

(130) Aspect 8: The method of any of aspects 1 through 7, further comprising: monitoring for a presence of the processing entity; and activating, in the processing entity, the connection agent based at least in part on detecting the presence of the processing entity.

(131) Aspect 9: The method of any of aspects 1 through 8, further comprising: storing one or more records associated with activation of the connection agent, the manifest, or both, the generation of the one or more load balanced dynamic endpoints, a disablement of the one or more load balanced dynamic endpoints, a reassignment of the one or more load balanced dynamic endpoints, or any combination thereof.

(132) Aspect 10: The method of any of aspects 1 through 9, wherein the one or more load balanced dynamic endpoints disallow connections from processing entities different than the processing entity.

(133) Aspect 11: The method of any of aspects 1 through 10, wherein the plurality of access configurations comprise one or more access control lists, one or more internet protocol address configurations, one or more domain name configurations, one or more permissions configurations, one or more access policy configurations, one or more network layer configurations, one or more transport layer configurations, one or more ingress block configurations, one or more egress block configurations, or any combination thereof.

(134) Aspect 12: The method of any of aspects 1 through 11, wherein the data signature indicates a data format, a quantity of data, a data configuration rate, one or more dependent configurations, or any combination thereof.

(135) Aspect 13: The method of any of aspects 1 through 12, wherein the endpoint type indicates a representational state transfer (REST) API model, a global remote procedure call (RPC) API model, an input schema, an output schema, or any combination thereof.

(136) Aspect 14: An apparatus for data processing at an application server, comprising a processor: memory coupled with the processor; and instructions stored in the memory and executable by the processor to cause the apparatus to perform a method of any of aspects 1 through 13.

(137) Aspect 15: An apparatus for data processing at an application server, comprising at least one means for performing a method of any of aspects 1 through 13.

(138) Aspect 16: A non-transitory computer-readable medium storing code for data processing at an application server, the code comprising instructions executable by a processor to perform a method of any of aspects 1 through 13.

(139) It should be noted that the methods described herein describe possible implementations, and that the operations and the steps may be rearranged or otherwise modified and that other implementations are possible. Further, aspects from two or more of the methods may be combined.

(140) The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “exemplary” used herein means “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(141) In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first

reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

(142) Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(143) The various illustrative blocks and modules described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a DSP, an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration).

(144) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described herein can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(145) Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A non-transitory storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, non-transitory computer-readable media can comprise RAM, ROM, electrically erasable programmable ROM (EEPROM), compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that can be used to carry or store desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope

of computer-readable media.

(146) The description herein is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein, but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. A method for data processing at an application server, comprising: monitoring for a presence of a processing entity; activating, in the processing entity and based at least in part on detecting the presence of the processing entity, a connection agent and a manifest, the manifest comprising a data signature and an endpoint type that are associated with the processing entity; generating, based at least in part on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository comprising a plurality of access configurations for the processing entity; and retrieving, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the plurality of access configurations, wherein the one or more first access configurations are associated with the processing entity.
2. The method of claim 1, further comprising: receiving, from the connection agent, an access request indicating the one or more first access configurations; and retrieving the one or more first access configurations based at least in part on the access request.
3. The method of claim 1, further comprising: mapping the one or more load balanced dynamic endpoints to one or more access configuration retrieval services associated with the plurality of access configurations; and retrieving the one or more first access configurations via the one or more access configuration retrieval services.
4. The method of claim 1, further comprising: disabling the one or more load balanced dynamic endpoints based at least in part on retrieving, via the one or more load balanced dynamic endpoints, the one or more first access configurations.
5. The method of claim 1, further comprising: disassociating the one or more load balanced dynamic endpoints from the processing entity; and associating the one or more load balanced dynamic endpoints with a second processing entity.
6. The method of claim 1, further comprising: generating random endpoint addresses associated with the one or more load balanced dynamic endpoints.
7. The method of claim 1, further comprising: translating the one or more first access configurations from a first format to a second format that corresponds to the processing entity; and transmitting the translated one or more first access configurations to the processing entity via the connection agent.
8. The method of claim 1, further comprising: storing one or more records associated with the activation of the connection agent, the manifest, or both, the generation of the one or more load balanced dynamic endpoints, a disablement of the one or more load balanced dynamic endpoints, a reassignment of the one or more load balanced dynamic endpoints, or any combination thereof.
9. The method of claim 1, wherein the one or more load balanced dynamic endpoints disallow connections from processing entities different than the processing entity.
10. The method of claim 1, wherein the plurality of access configurations comprise one or more access control lists, one or more internet protocol address configurations, one or more domain name configurations, one or more permissions configurations, one or more access policy configurations, one or more network layer configurations, one or more transport layer configurations, one or more ingress block configurations, one or more egress block configurations,

or any combination thereof.

11. The method of claim 1, wherein the data signature indicates a data format, a quantity of data, a data configuration rate, one or more dependent configurations, or any combination thereof.

12. The method of claim 1, wherein the endpoint type indicates a representational state transfer (REST) API model, a global remote procedure call (RPC) API model, an input schema, an output schema, or any combination thereof.

13. An apparatus for data processing at an application server, comprising: a processor; memory coupled with the processor; and instructions stored in the memory and executable by the processor to cause the apparatus to: monitor for a presence of a processing entity; activate, in the processing entity and based at least in part on detecting the presence of the processing entity, a connection agent and a manifest, the manifest comprising a data signature and an endpoint type that are associated with the processing entity; generate, based at least in part on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository comprising a plurality of access configurations for the processing entity; and retrieve, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the plurality of access configurations, wherein the one or more first access configurations are associated with the processing entity.

14. The apparatus of claim 13, wherein the instructions are further executable by the processor to cause the apparatus to: receive, from the connection agent, an access request indicating the one or more first access configurations; and retrieve the one or more first access configurations based at least in part on the access request.

15. The apparatus of claim 13, wherein the instructions are further executable by the processor to cause the apparatus to: map the one or more load balanced dynamic endpoints to one or more access configuration retrieval services associated with the plurality of access configurations; and retrieve the one or more first access configurations via the one or more access configuration retrieval services.

16. The apparatus of claim 13, wherein the instructions are further executable by the processor to cause the apparatus to: disable the one or more load balanced dynamic endpoints based at least in part on retrieving, via the one or more load balanced dynamic endpoints, the one or more first access configurations.

17. The apparatus of claim 13, wherein the instructions are further executable by the processor to cause the apparatus to: generate random endpoint addresses associated with the one or more load balanced dynamic endpoints.

18. The apparatus of claim 13, wherein the instructions are further executable by the processor to cause the apparatus to: translate the one or more first access configurations from a first format to a second format that corresponds to the processing entity; and transmit the translated one or more first access configurations to the processing entity via the connection agent.

19. A non-transitory computer-readable medium storing code for data processing at an application server, the code comprising instructions executable by a processor to: monitor for a presence of a processing entity; activate, in the processing entity and based at least in part on detecting the presence of the processing entity, a connection agent and a manifest, the manifest comprising a data signature and an endpoint type that are associated with the processing entity; generate, based at least in part on the data signature, the endpoint type, or both, one or more load balanced dynamic endpoints configured for access, by the connection agent and via one or more application programming interfaces, to a repository comprising a plurality of access configurations for the processing entity; and retrieve, via the one or more load balanced dynamic endpoints and from the repository, one or more first access configurations of the plurality of access configurations, wherein the one or more first access configurations are associated with the processing entity.
