

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413909
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Xu; Yu-Xuan et al.

Package structure of micro speaker

Abstract

A package structure of a micro speaker is provided, and includes a substrate, a membrane, a coil, and a magnetic element. The substrate has a hollow chamber. The membrane is disposed on the substrate and covers the hollow chamber. The coil is embedded in the membrane. The magnetic element is disposed in the hollow chamber. A vent hole is formed in and penetrates the membrane, and the vent hole is separated from the coil and communicates with the hollow chamber.

Inventors:	Xu; Yu-Xuan (Hsinchu, TW), Gong; Shih-Chin (Taipei, TW)
Applicant:	Fortemedia, Inc. (Alviso, CA)
Family ID:	93083099
Assignee:	FORTEMEDIA, INC. (Alviso, CA)
Appl. No.:	18/302207
Filed:	April 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240357294 A1	Oct. 24, 2024

Publication Classification

Int. Cl.: **H04R7/04** (20060101); **H04R1/02** (20060101); **H04R9/02** (20060101); **H04R9/04** (20060101); **H04R9/06** (20060101)

U.S. Cl.:

CPC **H04R7/04** (20130101); **H04R1/025** (20130101); **H04R9/025** (20130101); **H04R9/047** (20130101); **H04R9/06** (20130101); **H04R2201/003** (20130101)

Field of Classification Search

CPC: B81B (7/0019); B81B (7/0061); B81B (7/0087); B81B (3/0081); B81B (2201/0264); B81B (2207/012); B81B (2207/015); B81B (2203/0127); B81B (2201/0257); H04R (19/04); H04R (19/005); H04R (1/04); H04R (2201/003); H04R (2410/03); H04R (7/02); H04R (31/00); H04R (7/18); B81C (1/0069)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2006/0056651	12/2005	Yao	381/399	H04R 9/048
2012/0104521	12/2011	Higashi	257/419	G01L 9/0042
2012/0131792	12/2011	Tseng	29/602.1	H01F 41/046
2016/0021459	12/2015	Inoue	381/174	B81B 7/0006
2018/0132023	12/2017	Yoo	N/A	H04R 1/04
2019/0116427	12/2018	Inoue	N/A	B81B 3/0072
2020/0055726	12/2019	Deas	N/A	B81B 7/0019
2020/0196049	12/2019	Zhang	N/A	H04R 9/022
2020/0344551	12/2019	Chen	N/A	H05K 1/181
2021/0160619	12/2020	Shymanovych	N/A	H04R 1/1008

Primary Examiner: Edwards; Carolyn R

Assistant Examiner: Dang; Julie X

Attorney, Agent or Firm: McClure, Qualey & Rodack, LLP

Background/Summary

BACKGROUND OF THE DISCLOSURE

Field of the Disclosure

(1) The present disclosure relates to a micro speaker, and, in particular, to a package structure of a micro speaker including a membrane having a straight edge and a vent hole.

Description of the Related Art

(2) Since electronic products are being developed to be smaller and thinner, how to scale down the size of these electronic products is an important topic. The micro electromechanical system (MEMS) technique is a technique for effectively scaling down the size of elements. The concept of the MEMS technique is to combine semiconductor process techniques and precision micromachining techniques, and to manufacture micro elements and micro systems with multiple functions. However, there is still room for improvement of micro speakers using the MEMS technique.

BRIEF SUMMARY OF THE DISCLOSURE

(3) An embodiment of the present invention provides a package structure of a micro speaker, which includes a substrate, a membrane, a coil, and a magnetic element. The substrate has a hollow chamber. The membrane is disposed on the substrate and covers the hollow chamber. The coil is embedded in the membrane. The magnetic element is disposed in the hollow chamber. A vent hole

is formed in and penetrates the membrane, and the vent hole is separated from the coil and communicates with the hollow chamber.

(4) An embodiment of the present disclosure provides package structure of a micro speaker, which includes a substrate, a membrane, a coil, and a magnetic element. The substrate has a hollow chamber. The membrane is disposed on the substrate and covers the hollow chamber. The membrane has at least one straight edge. The coil is embedded in the membrane. In addition, the magnetic element is disposed in the hollow chamber.

(5) In addition, an embodiment of the present disclosure provides package structure of a micro speaker, which includes a substrate, a membrane, a coil, and a magnetic element. The substrate has a hollow chamber. The membrane is disposed on the substrate and covers the hollow chamber. The membrane has at least one straight edge. The coil is embedded in the membrane. In addition, the magnetic element is disposed in the hollow chamber. A vent hole is formed in and penetrates the membrane, and the vent hole is separated from the coil and communicates with the hollow chamber.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The present disclosure can be more fully understood by reading the subsequent detailed description and examples with references made to the accompanying drawings, wherein:

(2) FIG. 1 is a schematic top view illustrating a package structure of a micro speaker in accordance with some embodiments of the present disclosure;

(3) FIG. 2 is a schematic enlarged view illustrating a region I shown in FIG. 1 in accordance with some embodiments of the present disclosure;

(4) FIGS. 3A-3F are schematic cross-sectional views illustrating manufacturing processes of the package structure of the micro speaker shown in FIG. 1;

(5) FIG. 4 is a schematic top view illustrating a package structure of a micro speaker in accordance with some embodiments of the present disclosure;

(6) FIG. 5 is a schematic top view illustrating a package structure of a micro speaker in accordance with some embodiments of the present disclosure;

(7) FIG. 6 is a schematic top view illustrating a package structure of a micro speaker in accordance with some embodiments of the present disclosure;

(8) FIG. 7A is a schematic top view illustrating a package structure of a micro speaker in accordance with some embodiments of the present disclosure;

(9) FIG. 7B is a schematic enlarged view illustrating the membrane shown in FIG. 7A in accordance with some embodiments of the present disclosure;

(10) FIG. 8A is a schematic top view illustrating a package structure of a micro speaker in accordance with some embodiments of the present disclosure; and

(11) FIG. 8B is a schematic enlarged view illustrating the membrane shown in FIG. 8A in accordance with some embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE DISCLOSURE

(12) The package structures of the micro speaker of some embodiments of the present disclosure are described in the following description. However, it should be appreciated that the following detailed description of some embodiments of the disclosure provides various concepts of the present disclosure which may be performed in specific backgrounds that can vary widely. The specific embodiments disclosed are provided merely to clearly describe the usage of the present disclosure by some specific methods without limiting the scope of the present disclosure.

(13) Unless defined otherwise, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this

disclosure belongs. It should be appreciated that, in each case, the term, which is defined in a commonly used dictionary, should be interpreted as having a meaning that conforms to the relative skills of the present disclosure and the background or the context of the present disclosure, and should not be interpreted in an idealized or overly formal manner unless so defined in the present disclosure.

(14) FIG. 1 is a top view illustrating a package structure **10** of a micro speaker in accordance with some embodiments of the present disclosure. As shown in FIG. 1, the package structure **10** of the micro speaker includes a substrate **100**, a membrane **110**, a multi-layered coil **120**, and a lid **108**. Referring to FIG. 1, the membrane **110** is disposed on the substrate **100** and can vibrate up and down in the normal direction (such as the Z-axis) of the substrate **100**. It should be noted that the lid **108** is briefly shown and the top of the lid **108** is hidden to clearly show the interior structure of the package structure **10** of the micro speaker.

(15) In some embodiments, the membrane **110** has at least straight edge. For example, the membrane **110** may be shaped like a rectangle, a rounded rectangle, a polygon, a rounded polygon, or another regular or irregular shape, when viewed from a top view. More specifically, the membrane **110** has a plurality of edges **111** and a plurality of corners **112**, and each of the corners **112** is connected between two adjacent edges **111**. Accordingly, compared to a conventional circular membrane, the membrane **110** may have more surface area under the same chip size, and therefore may achieve a higher sound pressure level and better performance (for example, higher sensitivity) than the conventional design.

(16) In addition, at least one vent hole **113** is formed in and penetrates the membrane **110**. The vent hole **113** is shown to penetrate the membrane **110** in the normal direction of the substrate **100**. However, other directions are also possible and included within the scope of the present disclosure. In some embodiments, the vent hole **113** is separated from the multi-layered coil **120** in a top view. As a result, the vent hole **113** may not make negative impact to the operation of the multi-layered coil **120**. The vent hole **113** may connect the front side of the membrane **110** and the back side of the membrane **110**, and therefore the pressure of two sides is balanced via the vent hole **113**. Therefore, better user experience may be provided, and the reliability of the speaker may also be increased. For example, the vent hole **113** may reduce the defect (such as leakage, which may be referred to as “roll-off”) occurred in the low frequency range. In some embodiments, the diameter of the vent hole **113** is between about 1 μm and about 100 μm . However, the present disclosure is not limited thereto. In some embodiments, the vent hole **113** may have non-circular shape, and the length and/or width of the vent hole **113** is between about 1 μm and about 100 μm .

(17) The multi-layered coil **120** is embedded in the membrane **110**. That is, the multi-layered coil **120** is not actually exposed from the top surface of the membrane **110** in the top view. For the purpose of illustration, the multi-layered coil **120** is shown in the present disclosure. The multi-layered coil **120** is configured to transmit electrical signals and drive the membrane **110** to deform relative to the substrate **100** according to the electrical signals.

(18) In some embodiments, the multi-layered coil **120** includes a first metal layer **121** and a second metal layer **122**. The first metal layer **121** is electrically connected to the second metal layer **122** in an opening **110E** of the membrane **110** to transmit electrical signals and control the operation of the package structure **10** of the micro speaker. In some embodiments, the first metal layer **121** includes a spiral structure **121A** located in the center of the membrane **110** and a wavy structure **121B** extending from the spiral structure **121A** to the periphery of the membrane **110**. The spiral structure **121A** surrounds the central axis O of the membrane **110**, and the wavy structure **121B** connects the spiral structure **121A** to the opening **110E**. By providing the wavy structure **121B**, the membrane **110** can be more flexible and the difficulty of vibration can be reduced.

(19) FIG. 2 is a schematic enlarged view illustrating the region I shown in FIG. 1 in accordance with some embodiments of the present disclosure. Referring to FIG. 2, the first metal layer **121** and the second metal layer **122** are located on different levels, and the second metal layer **122** is higher

than the first metal layer **121**. That is, the second metal layer **122** is closer to the top of the membrane **110** than the first metal layer **121**.

(20) In some embodiments, a dielectric layer **130** is disposed between the first metal layer **121** and the second metal layer **122** to prevent a short circuit between the first metal layer **121** and the second metal layer **122**. A via hole **132** is formed in the dielectric layer **130**. The second metal layer **122** crosses the spiral structure **121A** and is electrically connected to the first metal layer **121** through the via hole **132**. The process of manufacturing the package structure **10** is described in detail below in conjunction with FIGS. **3A** to **3F**.

(21) FIGS. **3A** to **3F** show schematic cross-sectional views of the package structure **10** shown in FIG. **1** during the manufacturing process. It should be understood that each of FIGS. **3A** to **3F** includes a cross-sectional view along the lines A-A, B-B, and C-C shown in FIG. **1**. The manufacturing processes of different parts (for example, the parts along the lines A-A, B-B, and C-C) of the package structure **10** are shown in a single figure for those skilled in the art to understand easily.

(22) Referring to FIG. **3A**, a plurality of dielectric layers **115A** and **115B** are formed on the substrate **100**. In some embodiments, the substrate **100** may be part of a semiconductor wafer. In some embodiments, the substrate **100** may be formed of silicon (Si) or other semiconductor materials. Alternatively or additionally, the substrate **100** may include other element semiconductor materials, such as germanium (Ge); a compound semiconductor, such as silicon carbide (SiC), gallium arsenide (GaAs), indium arsenide (InAs), indium phosphide (InP); and an alloy semiconductor, such as silicon germanium (SiGe), silicon germanium carbide (SiGeC), gallium arsenide phosphide (GaAsP), indium gallium phosphide (InGaP). In some embodiments, the thickness of the substrate **100** may be between about 100 μm and about 1000 μm . However, the present disclosure is not limited thereto.

(23) In some embodiments, the dielectric layer **115A** may be silicon dioxide (SiO_2) or other oxides or nitrides that can be used as a dielectric layer. The dielectric layer **115A** may be formed on the substrate **100** through thermal oxidation, chemical vapor deposition (CVD), low pressure CVD (LPCVD), atmospheric pressure CVD (APCVD), plasma-enhanced chemical vapor deposition (PECVD), or a combination thereof.

(24) In some embodiments, the dielectric layer **115B** may be silicon dioxide (SiO_2) or other oxides or nitrides that can be used as a dielectric layer. The dielectric layer **115B** may be formed on the dielectric layer **115A** through thermal oxidation, chemical vapor deposition (CVD), plasma-enhanced chemical vapor deposition (PECVD), or a combination thereof. It is noted that although two dielectric layers **115A** and **115B** are shown in the present embodiments, less or more dielectric layers may be provided in other embodiments, and these configurations are within the scope of the present disclosure.

(25) Still referring to FIG. **3A**, the first metal layer **121** of the multi-layered coil **120** is formed on the dielectric layer **115B**. The first metal layer **121** may be formed through electroplating or physical vapor deposition (PVD), such as sputtering or evaporation coating. Then, the first metal layer **121** is patterned to form the spiral structure **121A** and the wavy structure **121B** as shown in FIG. **1**. The patterning process may include photolithography processes (for example, photoresist coating, soft baking, mask alignment, exposure, post-exposure baking, photoresist development, other suitable processes or a combination thereof), etching processes (for example, wet etching process, dry etching process, other suitable processes or a combination thereof), other suitable processes, or a combination thereof.

(26) In some embodiments, the first metal layer **121** may include aluminum silicon, aluminum, copper, or a combination thereof. In some embodiments, the width of the first metal layer **121** may be between about 1 μm and about 500 μm , and the thickness of the first metal layer **121** may be between about 0.1 μm and about 20 μm . However, the present disclosure is not limited thereto.

(27) Still referring to FIG. **3A**, a dielectric layer **130** is formed on the first metal layer **121** and the

dielectric layer **115B**. In some embodiments, the dielectric layer **130** may be formed through a furnace process or a chemical vapor deposition process. In some embodiments, the dielectric layer **130** may be carbon-doped oxides or other suitable insulating materials.

(28) Referring to FIG. 3B, a lithography process and an etching process are performed on the dielectric layer **130** to form a via hole **132** in the dielectric layer **130** and expose a portion of the first metal layer **121**. Then, the second metal layer **122** of the multi-layered coil **120** is formed on the dielectric layer **130** and the first metal layer **121** through electroplating or physical vapor deposition (for example, sputtering or evaporation coating). The second metal layer **122** is subsequently patterned. It should be noted that the dielectric layer **130** is cut into separate segments through the lithography process and etching process, leaving only the necessary portion to insulate the first metal layer **121** and the second metal layer **122**. By removing unnecessary portion of the dielectric layer **130**, the membrane **110** can be more flexible and thus improve the performance of the package structure.

(29) In some embodiments, the second metal layer **122** may include aluminum silicon, aluminum, copper, or a combination thereof. In some embodiments, the width of the second metal layer **122** may be between about 1 μm and about 500 μm , and the thickness of the second metal layer **122** may be between about 0.1 μm and about 20 μm . However, the present disclosure is not limited thereto.

(30) Referring to FIG. 3C, the membrane **110** is formed on the second metal layer **122**. In some embodiments, the membrane **110** may be formed through spin coating, slot-die coating, blade coating, wire bar coating, gravure coating, spray coating, chemical vapor deposition, other suitable methods, or a combination thereof. As shown in FIG. 3C, the first metal layer **121**, the second metal layer **122**, and the dielectric layer **130** are embedded in the membrane **110**. In some embodiments, the membrane **110** may include polydimethylsiloxane (PDMS), phenolic epoxy resin (such as SU-8), polyimide (PI), or a combination thereof. In one embodiment, the membrane **110** is formed of PDMS, and the Young's modulus of the membrane **110** is between 1 MPa and 100 GPa. However, the present disclosure is not limited thereto. Compared with a film formed of polyimide, the membrane **110** formed of PDMS has a smaller Young's modulus and a softer film structure, which makes the membrane **110** have a larger displacement, thereby generates a larger sound amplitude.

(31) Referring to FIG. 3D, the membrane **110** is patterned to form an opening **110E** in the membrane **110**, forming a scribe line **140** is formed around the membrane **110**. The opening **110E** may expose the second metal layer **122**. The first metal layer **121** is electrically connected to the second metal layer **122** in the opening **110E**. The scribe line **140** may define an area of each package structure on the wafer. In this way, the scribe line **140** may facilitate cutting (for example, laser cutting) to separate the package structure. In some embodiments, the membrane **110** may be light-sensitive or not light-sensitive.

(32) In some embodiments, the vent hole **113** is formed and communicates with the hollow chamber **150** during the formation of the scribe line **140**. That is, the vent hole **113** may be formed along with the scribe line **140**. In some embodiments, the vent hole **113** may be formed during some other etching process. such as a singulation process, etc. Accordingly, additional process is not required for forming the vent hole **113**, reducing the time and cost of manufacturing the package **10** of the speaker.

(33) Still referring to FIG. 3D, a deep reactive-ion etching process or an etching process which applies an etchant (such as ammonium hydroxide (NH_4OH), hydrofluoric acid (HF), deionized water, tetramethylammonium hydroxide (TMAH), potassium hydroxide (KOH)) is performed on the substrate **100** to form a hollow chamber **150** in the substrate **100**. As shown in FIG. 3D, the membrane **110** is disposed (for example, suspended) over the hollow chamber **150**. It should be noted that the dielectric layers **115A** and **115B** may be used as etch stop layers to protect the membrane **110** and the multi-layered coil **120** from being etched. For example, the dielectric

layers **115A** and **115B** may overlap at least a portion of the first metal layer **121** and the second metal layer **122**, such as under the first metal layer **121** and the second metal layer **122**. Since the etching rates of the dielectric layers **115A** and **115B** may be different, after the etching process, the dielectric layers **115A** and **115B** may not completely overlap. For example, the dielectric layer **115A** may shrink to form a trough on the side facing the hollow chamber **150**.

(34) Referring to FIG. 3E, a carrier board **160** is disposed on the bottom surface of the substrate **100**. In some embodiments, the carrier board **160** may include a printed circuit board (PCB). The carrier **160** board includes air holes **151** which allow the hollow chamber **150** to communicate with the external environment. The first permanent magnetic element **170** is disposed on the carrier board **160** and is accommodated in the hollow chamber **150**. The first permanent magnetic element **170** is configured to cooperate with the multi-layered coil **120** to generate a force toward the normal direction of the substrate **100**, and the membrane **110** can vibrate relative to the substrate **100** according to the force. In some embodiments, the first permanent magnetic element **170** may include a neodymium iron boron magnet.

(35) Referring to FIG. 3F, a lid **108** is disposed on the carrier board **160**. The lid **108** wraps around the substrate **100** and the membrane **110**, and the end **108A** of the lid **108** exposes a portion of the top surface of the membrane **110**. In some embodiments, the lid may include metals with lower magnetic permeability than 1.25×10^{-4} H/mm, such as gold (Au), copper (Cu), aluminum (Al), or a combination thereof. In some embodiments, additional permanent magnetic element (not shown) may be disposed on the lid **108**, and may be disposed above the membrane **102**. As a result, the force generated by the current passing through the multi-layered coil **120** and the planar magnetic field in the normal direction of the substrate **100** is increased, so that the membrane **102** has a better frequency response, thereby improving the performance of the package structure.

(36) FIG. 4 is a schematic top view illustrating the package structure **10** of the micro speaker in accordance with some embodiments of the present disclosure. It should be noted that the package structure **10** of the micro speaker in the present embodiment includes the same or similar elements as the package structure **10** of the micro speaker shown in FIG. 1. These same or similar elements are denoted by the same or similar numerals, and will not be discussed in detail as follows. For example, as shown in FIG. 4, the package structure **10** of the micro speaker includes a substrate **100**, a membrane **110**, a multi-layered coil **125**, and a lid **108**. The multi-layered coil **125** is disposed to be rectangular, corresponding to the profile of the membrane **110**. To be more specific, the spiral structure **121A** of the multi-layered coil **125** may have a rectangular profile, which is parallel to the edges **111** of the membrane **110**. As a result, higher sound pressure level and better performance (for example, higher sensitivity) may be achieved.

(37) FIG. 5 is a schematic top view illustrating the package structure **10** of the micro speaker in accordance with some embodiments of the present disclosure. It should be noted that the package structure **10** of the micro speaker in the present embodiment includes the same or similar elements as the package structure **10** of the micro speaker shown in FIG. 1. These same or similar elements are denoted by the same or similar numerals, and will not be discussed in detail as follows. For example, as shown in FIG. 5, the package structure **10** of the micro speaker includes a substrate **100**, a membrane **110**, a multi-layered coil **120**, and a lid **108**.

(38) A plurality of vent holes **113** are formed in and penetrate the membrane **110**. In some embodiments, the vent holes **113** are separated from the multi-layered coil **120** and arranged along the profile of the membrane **110** in a top view. The vent holes **113** may connect the front side of the membrane **110** and the back side of the membrane **110**, and therefore the pressure of the two sides is balanced via the vent holes **113**. Furthermore, multiple vent holes **113** may help to decrease the stiffness of the membrane **110**, improving the sensitivity of the membrane **110**, which relates to the performance (such as sound pressure level) of the micro speaker. In some other embodiments, the vent holes **113** may be arranged in the membrane **110** irregularly, and any possible arrangement of the vent holes **113** is included within the scope of the present disclosure.

(39) FIG. 6 is a schematic top view illustrating the package structure **10** of the micro speaker in accordance with some embodiments of the present disclosure. It should be note that the package structure **10** of the micro speaker in the present embodiment includes the same or similar elements as the package structure **10** of the micro speaker shown in FIG. 1. These same or similar elements are denoted by the same or similar numerals, and will not be discussed in detail as follows. For example, as shown in FIG. 6, the package structure **10** of the micro speaker includes a substrate **100**, a membrane **110**, a multi-layered coil **120**, and a lid **108**.

(40) A plurality of vent holes **114** are formed in and penetrates the membrane **110**. In some embodiments, the vent holes **114** are separated from the multi-layered coil **120** and arranged along the profile of the membrane **110** in a top view. The vent holes **114** may connect the front side of the membrane **110** and the back side of the membrane **110**, and therefore the pressure of the two sides is balanced via the vent holes **114**. In some embodiments, each of the vent holes **114** has an elongated shape, and therefore the vent holes **114** may be referred to as “vent slots” sometimes. Similarly, these vent holes **114** may help to decrease the stiffness of the membrane **110**, improving the sensitivity of the membrane **110**, which relates to the performance (such as sound pressure level) of the micro speaker. In some other embodiments, the elongated vent holes **114** may be arranged along with the circular vent holes **113** in the membrane **110** arbitrarily, and any possible arrangement of the vent holes **113** and **114** is included within the scope of the present disclosure.

(41) FIG. 7A is a schematic top view illustrating the package structure **10** of the micro speaker in accordance with some embodiments of the present disclosure. FIG. 7B is a schematic enlarged view illustrating the membrane **110** shown in FIG. 7A in accordance with some embodiments of the present disclosure. It should be note that the package structure **10** of the micro speaker in the present embodiment includes the same or similar elements as the package structure **10** of the micro speaker shown in FIG. 1. These same or similar elements are denoted by the same or similar numerals, and will not be discussed in detail as follows. For example, as shown in FIG. 7A, the package structure **10** of the micro speaker includes a substrate **100**, a membrane **110**, a multi-layered coil **120**, and a lid **108**.

(42) A vent hole **116** is formed in and penetrates the membrane **110**. In some embodiments, the vent hole **116** is separated from the multi-layered coil **120** in a top view. The vent hole **116** may connect the front side of the membrane **110** and the back side of the membrane **110**, and therefore the pressure of the two sides is balanced via the vent hole **116**.

(43) In some embodiments, the vent hole **116** has a bow profile in the top view and divides the membrane **110** into a main body **110M** and a vent portion **110A** that is connected to the main body **110M**. When the pressures are different on opposite sides of the membrane **110**, airflow may pass through the vent hole **116** and push the vent portion **110A** to move relative to the main body **110M**, and the pressures may be balanced more rapidly. Otherwise, when the pressures are substantially the same on opposite sides of the membrane **110**, the vent portion **110A** may be substantially coplanar with the main body **110M**. As such, the effective surface area of the membrane **110** may be obtained (including the vent portion **110A**) for higher sensitivity.

(44) Therefore, the vent hole **116** may be referred to as “dynamic vent hole” sometimes. Similarly, the vent hole **116** may help to decrease the stiffness of the membrane **110**, improving the sensitivity of the membrane **110**, which relates to the performance (such as sound pressure level) of the micro speaker. It is noted that although one vent hole **116** is shown in the present embodiments, more vent hole **116** may be provided regularly or irregularly in other embodiments, and these configurations are within the scope of the present disclosure.

(45) FIG. 8A is a schematic top view illustrating the package structure **10** of the micro speaker in accordance with some embodiments of the present disclosure. FIG. 8B is a schematic enlarged view illustrating the membrane **110** shown in FIG. 8A in accordance with some embodiments of the present disclosure. It should be note that the package structure **10** of the micro speaker in the present embodiment includes the same or similar elements as the package structure **10** of the micro

speaker shown in FIG. 1. These same or similar elements are denoted by the same or similar numerals, and will not be discussed in detail as follows. For example, as shown in FIG. 8A, the package structure **10** of the micro speaker includes a substrate **100**, a membrane **110**, a multi-layered coil **120**, and a lid **108**.

(46) A vent hole **117** is formed in and penetrates the membrane **110**. In some embodiments, the vent hole **117** is separated from the multi-layered coil **120** in a top view. The vent hole **117** may connect the front side of the membrane **110** and the back side of the membrane **110**, and therefore the pressure of the two sides is balanced via the vent hole **117**.

(47) In some embodiments, the vent hole **117** has a bow portion **117A** and a linear portion **117B** that is connected to the bow portion **117B**. Correspondingly, the membrane **110** is divided into a main body **110M**, a round portion **110A**, and a linear portion **110B**. The round portion **110A** is connected to the main body **110M** via the linear portion **110B**. When the pressures are different on opposite sides of the membrane **110**, airflow may pass through the vent hole **117** and push the round portion **110A** and the linear portion **110B** to move relative to the main body **110M**, and the pressures may be balanced more rapidly. As such, the round portion **110A** and the linear portion **110B** may be referred to as “vent portion” for equalizing the pressure on opposite sides of the membrane **110**. Otherwise, when the pressures are substantially the same on opposite sides of the membrane **110**, the round portion **110A** and the linear portion **110B** may be substantially coplanar with the main body **110M**. As such, the effective surface area of the membrane **110** may be obtained for higher sensitivity.

(48) As described above, some embodiments of the present disclosure provide a package structure of a micro speaker including a membrane having a straight edge and/or a vent hole. In some embodiments, compared to conventional circular membrane, the disclosed membrane (such as having a shape of rounded rectangle) may have greater surface area under the same chip size, and therefore higher sound pressure level and better performance (for example, higher sensitivity) may be achieved. In addition, one or more vent hole are formed in the membrane for equalizing pressures of opposite sides of the membrane. Therefore, better user experience may be provided, and the reliability of the speaker may also be increased.

(49) While the embodiments and the advantages of the present disclosure have been described above, it should be understood that those skilled in the art may make various changes, substitutions, and alterations to the present disclosure without departing from the spirit and scope of the present disclosure. In addition, the scope of the present disclosure is not limited to the processes, machines, manufacture, composition, devices, methods and steps in the specific embodiments described in the specification. Those skilled in the art may understand existing or developing processes, manufacture, compositions, devices, methods and steps from some embodiments of the present disclosure. As long as those may perform substantially the same function in the aforementioned embodiments and obtain substantially the same result, they may be used in accordance with some embodiments of the present disclosure. Therefore, the scope of the present disclosure includes the aforementioned processes, manufacture, composition, devices, methods, and steps. Furthermore, each of the appended claims constructs an individual embodiment, and the scope of the present disclosure also includes every combination of the appended claims and embodiments.

Claims

1. A package structure of a micro speaker, comprising: a substrate having a hollow chamber; a membrane, disposed on the substrate, covering the hollow chamber; a multi-layers coil includes a first metal layer and a second metal layer embedded in the membrane, wherein the coil comprises: a spiral structure located in a center of the membrane; and a wavy structure extending from the spiral structure to a periphery of the membrane; and a magnetic element disposed in the hollow

- chamber, wherein a vent hole is formed in and penetrates the membrane, and in a top view, the vent hole is separated from the coil, located on a side opposite to the wavy structure, and is in fluid communication with and is aligned communicates with and overlaps with the hollow chamber.
2. The package structure of the micro speaker as claimed in claim 1, wherein the vent hole has a bow profile in the top view and divides the membrane into a main body and a vent portion connected to the main body.
 3. The package structure of the micro speaker as claimed in claim 2, wherein the vent hole has a bow portion and a linear portion connected to the bow portion.
 4. The package structure of the micro speaker as claimed in claim 3, wherein the vent portion of the membrane comprises a round portion and a linear portion connected to the round portion.
 5. The package structure of the micro speaker as claimed in claim 2, wherein the vent portion is movable relative to the main body.
 6. The package structure of the micro speaker as claimed in claim 1, further comprising: a carrier board bonded to the substrate, wherein the magnetic element is disposed on the carrier board.
 7. The package structure of the micro speaker as claimed in claim 1, wherein a plurality of vent holes are formed in the membrane and arranged parallel to an edge of the membrane.
 8. The package structure of the micro speaker as claimed in claim 1, wherein the vent hole has an elongated shape.
 9. The package structure of the micro speaker as claimed in claim 1, wherein a diameter of the vent hole is between 1 μm and 100 μm .
 10. A package structure of a micro speaker, comprising: a substrate having a hollow chamber; a membrane, disposed on the substrate, covering the hollow chamber, wherein the membrane has at least one straight edge; a multi-layers coil includes a first metal layer and a second metal layer embedded in the membrane, wherein the coil comprises: a spiral structure located in a center of the membrane; and a wavy structure extending from the spiral structure to a periphery of the membrane; and a magnetic element disposed in the hollow chamber, wherein a vent hole is formed in and penetrates the membrane, and in a top view, the vent hole is separated from the coil, located on a side opposite to the wavy structure, and is aligned overlaps with the hollow chamber.
 11. The package structure of the micro speaker as claimed in claim 10, wherein the membrane has a rectangular shape with rounded corners.
 12. The package structure of the micro speaker as claimed in claim 10, wherein the straight edge of the membrane is parallel to an edge of the substrate.
 13. A package structure of a micro speaker, comprising: a substrate having a hollow chamber; a membrane, disposed on the substrate, covering the hollow chamber, wherein the membrane has at least one straight edge; a multi-layers coil includes a first metal layer and a second metal layer embedded in the membrane, wherein the coil comprises: a spiral structure located in a center of the membrane; and a wavy structure extending from the spiral structure to a periphery of the membrane; and a magnetic element disposed in the hollow chamber, wherein a vent hole is formed in and penetrates the membrane, and in a top view, the vent hole is separated from the coil, located on a side opposite to the wavy structure, and is in fluid communication with and is aligned communicates with the hollow chamber.
 14. The package structure of the micro speaker as claimed in claim 13, wherein the straight edge of the membrane is parallel to an edge of the substrate.
 15. The package structure of the micro speaker as claimed in claim 13, wherein the vent hole has a bow profile in the top view and divides the membrane into a main body and a vent portion connected to the main body.
 16. The package structure of the micro speaker as claimed in claim 15, wherein the vent hole has a bow portion and a linear portion connected to the bow portion.
 17. The package structure of the micro speaker as claimed in claim 15, wherein the vent portion of the membrane comprises a round portion and a linear portion connected to the round portion.

18. The package structure of the micro speaker as claimed in claim 13, wherein a plurality of vent holes are formed in the membrane and arranged parallel to the edge of the membrane.
 19. The package structure of the micro speaker as claimed in claim 13, wherein the vent hole has an elongated shape.
 20. The package structure of the micro speaker as claimed in claim 13, wherein a diameter of the vent hole is between 1 μm and 100 μm .
-