

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396564
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Long; Kevin Jeffrey et al.

Outdoor furniture piece with temperature control

Abstract

An outdoor furniture piece, including: a plurality of members coupled together to form a structure of the outdoor furniture piece; a cushion positioned adjacent to one or more first members of the plurality of members of the structure; a heating element coupled to the cushion; and a power source coupled to a second member of the plurality of members, the power source in electrical communication with the heating element such that the power source provides electrical energy to the heating element, wherein when the heating element receives the electrical energy from the power source, the heating element converts the electrical energy to thermal energy at the cushion.

Inventors: Long; Kevin Jeffrey (Austin, TX), Duncan; Alex Joseph (The Woodlands, TX)

Applicant: Outmore Living, Inc. (Austin, TX)

Family ID: 1000008779607

Assignee: Outmore Living, Inc. (Austin, TX)

Appl. No.: 18/060459

Filed: November 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240172874 A1	May. 30, 2024

Publication Classification

Int. Cl.: A47C7/74 (20060101)

U.S. Cl.:

CPC A47C7/748 (20130101);

Field of Classification Search

CPC: A47C (7/748)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9775438	12/2016	Schulenberg	N/A	N/A
2006/0289421	12/2005	Axinte et al.	N/A	N/A
2010/0025388	12/2009	Ono	219/217	A47C 7/748
2010/0283295	12/2009	Smith	219/217	A47C 4/286
2014/0217785	12/2013	Arens et al.	N/A	N/A
2017/0013965	12/2016	Schurink et al.	N/A	N/A
2017/0143122	12/2016	Nelson et al.	N/A	N/A
2017/0245325	12/2016	Fee et al.	N/A	N/A
2018/0325265	12/2017	Warner	N/A	N/A
2020/0037768	12/2019	Gober	N/A	H05B 1/0275
2022/0175145	12/2021	Pomeroy et al.	N/A	N/A
2022/0194264	12/2021	Kaku et al.	N/A	N/A
2022/0211188	12/2021	Daub et al.	N/A	N/A
2024/0041210	12/2023	Dukart	N/A	A47C 4/286
2024/0176371	12/2023	Long et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017101323	12/2017	AU	N/A
3141037	12/2021	CA	A47C 7/748
108618442	12/2017	CN	N/A
109124145	12/2018	CN	A47C 7/744
112493922	12/2020	CN	N/A
114359524	12/2021	CN	N/A
217827295	12/2021	CN	N/A
202010005295	12/2009	DE	A47C 7/748
201911028401	12/2020	IN	N/A
202211010724	12/2021	IN	N/A
2002065630	12/2001	JP	N/A
101671147	12/2015	KR	N/A
102035420	12/2018	KR	N/A
102059097	12/2018	KR	N/A
102086623	12/2019	KR	N/A
20200032476	12/2019	KR	N/A
102109946	12/2019	KR	N/A
20210027684	12/2020	KR	N/A

20220048157	12/2021	KR	N/A
10-2022-0116902	12/2021	KR	N/A
2019054648	12/2018	WO	N/A
WO-2021097432	12/2020	WO	A47C 4/00

OTHER PUBLICATIONS

PCT Search Report, International Application No. PCT/US2023/080056, Feb. 23, 2024, 3 pages.
cited by applicant

PCT Written Opinion, International Application No. PCT/US2023/080056, Feb. 23, 2024, 4 pages.
cited by applicant

PCT Search Report, International Application No. PCT/US2023/080054, Feb. 16, 2024, 3 pages.
cited by applicant

PCT Written Opinion, International Application No. PCT/US2023/080054, Feb. 16, 2024, 6 pages.
cited by applicant

Primary Examiner: Brindley; Timothy J

Attorney, Agent or Firm: McDermott Will & Emery

Background/Summary

BACKGROUND

Field of the Disclosure

(1) The disclosure relates generally to an outdoor furniture piece with temperature control.

SUMMARY

(2) Innovative aspects of the subject matter described in this specification may be embodied in an outdoor furniture piece, including: a plurality of members coupled together to form a structure of the outdoor furniture piece; a cushion positioned adjacent to one or more first members of the plurality of members of the structure; a heating element coupled to the cushion; and a power source coupled to a second member of the plurality of members, the power source in electrical communication with the heating element such that the power source provides electrical energy to the heating element, wherein when the heating element receives the electrical energy from the power source, the heating element converts the electrical energy to thermal energy at the cushion.

(3) Other embodiments of these aspects include corresponding systems and apparatus.

(4) These and other embodiments may each optionally include one or more of the following features. For instance, the second member is one of the first members. The second member is distinct from the first members. The power source is a rechargeable battery. The power source further includes an input power source outlet to receive input power to charge the rechargeable battery. The power source is removably coupled to the second member. A bracket coupled to the second member, wherein the power source is removably coupled to the bracket. The power source further includes first magnetic coupling members and the bracket includes second magnetic coupling members, wherein when the power source is coupled to the bracket, the first magnetic coupling members are coupled to the second magnetic coupling members such that the power source provides the electrical energy from the first magnetic coupling members to the second magnetic coupling members. The bracket further includes third magnetic coupling members that are in electrical communication with the second magnetic coupling members such that the electrical energy provided by the power source is transmitted through the second magnetic coupling members to the third magnetic coupling members. The heating element further includes

fourth magnetic coupling members, wherein when the heating element is in electrical communication with the power source, the third magnetic coupling members are coupled to the fourth magnetic coupling members such that electrical energy provided by the power source is transmitted through the third magnetic coupling members to the fourth magnetic coupling members. When the heating element is in electrical communication with the power source, the electrical energy provided by the power source is transmitted through the fourth magnetic coupling members to wiring of the heating element to convert the electrical energy to thermal energy at the cushion. Further including an additional cushion positioned adjacent to one or more third members of the plurality of members of the structure; and an additional heating element coupled to the additional cushion, wherein the additional heating element is in electrical communication with the heating element such that the additional heating element receives the electrical energy from the power source through the heating element, the additional heating element converting the electrical energy to thermal energy at the additional cushion. The heating element includes fifth magnetic coupling members that are in electrical communication with the wiring of the heating element such that electrical energy provided by the power source is transmitted through the wiring to the fifth magnetic coupling members. The additional heating element includes sixth magnetic coupling members, wherein when the additional heating element is in electrical communication with the heating element, the sixth magnetic coupling members are coupled to the fifth magnetic coupling members such that electrical energy provided by the power source is transmitted through the fifth magnetic coupling members to the sixth magnetic coupling members. When the additional heating element is in electrical communication with the power source, the electrical energy provided by the power source is transmitted through the sixth magnetic coupling members to additional wiring of the additional heating element to convert the electrical energy to thermal energy at the additional cushion. The structure of the outdoor furniture piece is a chair. Further including a microcontroller in communication with the power source, the microcontroller controlling the electrical energy provided by the power source; and a physical button in communication with the microcontroller, wherein, in response to user input at the physical button, the microcontroller is configured to adjust the electrical energy output by the power source.

(5) Innovative aspects of the subject matter described in this specification may be embodied in a method of managing temperature control of a heating element of an outdoor furniture piece, including performing, at a first time, a calibration and configuration of a temperature control management model, including: identifying telemetry data associated with one or more sensors of the outdoor furniture piece; receiving external data associated with environmental conditions of the outdoor furniture piece based on a geographic location of the outdoor furniture piece; and training, based on the telemetry data and the external data, the temperature control management model, including generating a thermal policy including configuration rules, the configuration rules for automatically adjusting electrical energy output by a power source in communication with the heating element; performing, at a second time, a steady-state management of the temperature control of the heating element of the outdoor furniture piece, including: monitoring the telemetry data associated with the sensors of the outdoor furniture piece; monitoring the environmental conditions of the outdoor furniture piece; and in response to monitoring the sensors and the environmental conditions, i) accessing the temperature control management model including the thermal policy, ii) identifying one or more of the configuration rules based on the monitored telemetry data and the monitored environmental conditions, and iii) applying the one or more configuration rules to perform adjustment of the electrical energy output by the power source.

(6) Other embodiments of these aspects include corresponding systems, apparatus, and computer programs, configured to perform the actions of the methods, encoded on computer storage devices.

(7) These and other embodiments may each optionally include one or more of the following features. For instance, applying the one or more configuration rules to perform adjustment of the electrical energy output by the power source adjusts a temperature of the heating element.

Identifying the telemetry data associated with one or more sensors of the outdoor furniture piece further includes identifying ambient conditions associated with an environment of the outdoor furniture piece, the ambient conditions including i) a temperature of the environment proximate to the outdoor furniture piece, ii) a humidity of the environment proximate to the outdoor furniture piece, and iii) a pressure of the environment proximate to the outdoor furniture piece. Identifying the telemetry data associated with one or more sensors of the outdoor furniture piece further includes identifying conditions at the outdoor furniture piece, including i) a temperature at a cushion of the outdoor furniture piece, ii) a moisture at the cushion of the outdoor furniture piece, iii) and an occupancy of a user at the cushion of the outdoor furniture piece. Performing the calibration and configuration of the temperature control management model further includes identifying a first time period for which a particular sensor of the one or more sensors indicates the occupancy of the user, and performing the steady-state management of the temperature control of the heating element of the outdoor furniture piece further includes monitoring a second time period for which the particular sensor indicates the occupancy of the user. The first time period includes a time of day and a day of week, and the second time period includes a time of day and a day of week. The power source is a rechargeable battery, and wherein identifying the telemetry data associated with one or more sensors of the outdoor furniture piece further includes identifying i) a voltage of the electrical energy output by the rechargeable battery, ii) a current capacity of the rechargeable battery, and iii) a health of the rechargeable battery. In the external data associated with environmental conditions of the outdoor furniture piece includes i) a temperature forecast for the geographic location of the outdoor furniture piece, ii) a wind forecast for the geographic location of the outdoor furniture piece, iii) historical weather data for the geographic location of the outdoor furniture piece, and iv) precipitation trends for the geographic location of the outdoor furniture piece. Performing the calibration and configuration of the temperature control management model is performed multiple times prior to performing the steady-state management of the temperature control of the heating element of the outdoor furniture piece.

(8) The details of one or more embodiments of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other potential features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIGS. 1 and 2 illustrate a perspective view of an outdoor furniture piece.
- (2) FIG. 3 illustrates a control unit coupled to a member of the outdoor furniture piece.
- (3) FIG. 4 illustrates a partially transparent view of the control unit.
- (4) FIG. 5 illustrates a bottom up perspective view of a bracket of the outdoor furniture piece.
- (5) FIG. 6 illustrates a front view of the bracket.
- (6) FIG. 7 illustrates a perspective view of the control unit.
- (7) FIGS. 8 and 9 illustrate the control unit coupled to the bracket.
- (8) FIG. 10 illustrates a side view of the control unit.
- (9) FIG. 11 illustrates a back view of the outdoor furniture piece.
- (10) FIG. 12 is a block diagram of selected elements of an embodiment of a computing device.
- (11) FIG. 13 illustrates a block diagram of a computing environment for managing temperature control of a heating element of an outdoor furniture piece.
- (12) FIG. 14 illustrates a method for managing temperature control of a heating element of the outdoor furniture piece.

DESCRIPTION OF PARTICULAR EMBODIMENT(S)

(13) This disclosure discusses an outdoor furniture piece with temperature control. In short, an outdoor furniture piece can include a heating element coupled to a cushion. The heating element can be coupled to a power source. The heating element can receive electrical energy from the power source, and convert such to thermal energy at the cushion. Additionally, the temperature control of the heating element can be managed based on recommendations determined from, among other data points, sensor data and historical usage.

(14) In the following description, details are set forth by way of example to facilitate discussion of the disclosed subject matter. It should be apparent to a person of ordinary skill in the field, however, that the disclosed embodiments are exemplary and not exhaustive of all possible embodiments.

(15) FIG. 1 illustrates a perspective view of an outdoor furniture piece **100**. The outdoor furniture piece **100** can include a plurality of members **102** coupled together to form a structure of the furniture piece **100**. For ease of illustration, only a portion of the members **102** are specifically referenced by FIG. 1. In some examples, the outdoor furniture piece **100** can include a chair, couch, or any seated type of furniture. In some examples, the outdoor furniture piece **100** can include any type of furniture. In some examples, the outdoor furniture piece **100** is formed of one or more combinations of wood, metal (e.g., aluminum), plastic, or any composite materials. In some examples, at least one or more of the members **102** of the outdoor furniture piece **100** is hollow. In some examples, at least one or more of the members **102** of the outdoor furniture piece **100** is solid.

(16) FIG. 2 illustrates a perspective view of the outdoor furniture piece **100**. Referring to FIGS. 1 and 2, the outdoor furniture piece **100** includes a first cushion **202a** and a second cushion **202b** (collectively referred to as cushions **202**). The cushions **202** can be formed from any type of appropriate material such as foam, and covered with any type of appropriate material, such as fabric, vinyl, and/or plastic. The first cushion **202a** can be positioned adjacent to a first set of the members **102**, illustrated as members **102a**. For example, when the outdoor furniture piece **100** is a chair, the first cushion **202a** can generally be referred to as a “seat” of the chair. The second cushion **202b** can be positioned adjacent to a second set of the members **102**, illustrated as members **102b**. For example, when the outdoor furniture piece **100** is a chair, the second cushion **202b** can generally be referred to as a “back” of the chair.

(17) The outdoor furniture piece **100** can further include a first heating element **204a** and a second heating element **204b** (collectively referred to as heating elements **204**). The heating elements **204** can be any form of a localized heating source, such as a heating pad. The first heating element **204a** can be coupled to the first cushion **202a**. In some examples, the first heating element **204a** is formed within the first cushion **202a**—a part of the body (foam) of the first cushion **202a** or a part of the cover of the first cushion **202a**. In some examples, the first heating element **204a** is formed between the body (foam) of the first cushion **202a** and the cover of the first cushion **202a**. The second heating element **204b** can be coupled to the second cushion **202b**. In some examples, the second heating element **204b** is formed within the second cushion **202b**—a part of the body (foam) of the second cushion **202b** or a part of the cover of the second cushion **202b**. In some examples, the second heating element **204b** is formed between the body (foam) of the second cushion **202b** and the cover of the second cushion **202b**.

(18) The outdoor furniture piece **100** can further include a control unit **210**. The control unit **210** can be coupled to any member **102** (or members **102**) of the outdoor furniture piece **100**. In some examples, as illustrated in FIG. 2, the control unit **210** is coupled to one of the members **102a**, illustrated as member **102aa** (e.g., a front seat member). In some examples, as illustrated in FIG. 3, the control unit **210** is coupled to a member **102c** of the members **102** (e.g., an arm rest member). The location of the control unit **210** with respect to coupling with the outdoor furniture piece **100** can be location agnostic. In some examples, the control unit **210** is partially or fully integrated with one or more members **102** of the outdoor furniture piece **100**. In some examples, when the control unit **210** is partially or fully integrated with one or more members **102** of the outdoor furniture

piece **100**, the corresponding members **102** can include one or more holes to access one or more interactable elements of the control unit **210**. In some examples, when the control unit **210** is partially or fully integrated with one or more members **102** of the outdoor furniture piece **100**, the control unit **210** can include a detachable panel for access to the control unit **210** coupled to the corresponding member **102** (e.g., for access to internal components to the control unit **210**).

(19) FIG. **4** illustrates a partially transparent view of the control unit **210**. The control unit **210** can include a power source **402**, a microcontroller **404**, a physical button (interface) **406**, and an outlet interface **408**

(20) Referring back to FIGS. **2** and **3**, the outdoor furniture piece **100** can further include a bracket **220**. The bracket **220** can be coupled to any member **102** (or members **102**) of the outdoor furniture piece **100**. For example, as illustrated in FIG. **2**, the bracket **220** is coupled to member **102aa** (e.g., the front seat member). For example, as illustrated in FIG. **3**, the bracket **220** is coupled to the member **102c** (e.g., the arm rest member). The bracket **220** can be coupled to the member **102** by any means, such as by fasteners, or adhesive. In some examples, the member **102** can include a recession (not shown) that the bracket **220** is positioned within for coupling with the member **102**.

(21) FIG. **5** illustrates a bottom up perspective view of the bracket **220**; and FIG. **6** illustrates a front view of the bracket **220**. Referring to FIGS. **5** and **6**, the control unit **210**, and in particular, the power source **402** (shown in FIG. **4**), are removably coupled to the bracket **220** (and thus, removably coupled to a member **102** that the bracket **220** is coupled to).

(22) For example, the bracket **220** can include protrusions **502a**, **502b** (collectively referred to as protrusions **502**) extending from a surface **602**. Each of the protrusions **502** can form a trapezoidal shape. The bracket **220** can include any number of protrusions **502**. Further, as shown in FIG. **7**, the control unit **210** includes recessions **702a**, **702b** (collectively referred to as recessions **702**) on a surface **704** of the control unit **210**. The recessions **702** can have a corresponding trapezoidal shape. To that end, when the control unit **210** is coupled to the bracket **220**, the control unit **210** can be “slid” onto the bracket **220** such that the protrusions **502** are positioned within corresponding recessions **702**. The corresponding shapes of the protrusions **502** and the recessions **702** can “hold” the coupling of the control unit **210** to the bracket **220** (e.g., against gravity).

(23) For example, referring to FIGS. **8** and **9**, the bracket **220** can include a holding lip **802** extending from a body **803** of the bracket **220** on at least a portion of the perimeter of the bracket **220**. Further, the control unit **210** includes a protruding portion **804**. To that end, when the control unit **210** is coupled to the bracket **220**, the control unit **210** can be “slid” onto the bracket **220** such that the protruding portion **804** is positioned within the lip **802** (e.g., between the body **803** and the lip **802**). The lip **802** can “hold” the coupling of the control unit **210** to the bracket **220** (e.g., against gravity).

(24) Referring back to FIG. **4**, the power source **402** can be a rechargeable battery. For example, the power source **402** can be an integrated lithium rechargeable battery.

(25) FIG. **10** illustrates a side view of the control unit **210**, and in particular the outlet interface **408**. The control unit **210** can include outlets **1002a**, **1002b** and a power state button **1004**. However, the control unit **210** can include any number of outlets. As illustrated, the outlet **1002a** is a USB-C outlet, and the outlet **1002b** is a USB-A outlet; however, the outlets **1002a**, **1002b** can be any type of charging outlet. In some cases, the outlets **1002a**, **1002b** can be power out outlets. In some cases, the outlets **1002a**, **1002b** can be power in outlets. To that end, when the power source **402** is a rechargeable battery, the battery can be recharged when an AC source (not shown) is coupled to one of the outlets **1002a**, **100b**. In some cases, the control unit **210** can be powered by the power source **402** and/or an AC source when coupled to one of the outlets **1002a**, **1002b** (e.g., the control unit **210** is “plugged in”). That is, the AC source, when coupled to one of the outlets **1002a**, **1002b**, can i) provide energy to the recharge battery (the power source **402**), and ii) provide energy to power the control unit **210** (and in particular, the microcontroller **404**). In some cases, the rechargeable battery provides energy to power the control unit **210** (and in particular, the

microcontroller **404**) independent of any AC source or in coordination with the AC power source.

(26) The power state button **1004** can control a power state of the control unit **210**. That is, a user can interact with the power state button **1004** to adjust the power state of the control unit **210** between an off-power state and an on-power state. In some cases, a light surrounds the power state button (e.g., LED light) to visually indicate the power state of the control unit **210**.

(27) Referring back to FIGS. **2** and **4**, the control unit **210**, and in particular, the power source **402**, is in electrical communication with one or more of the heating elements **204** such that the power source **402** provides electrical energy to the one or more heating elements **204**, described further herein.

(28) Referring to FIG. **4**, the microcontroller **404** is in communication with the power source **402**, and in particular, in communication with the power source **402** to control (or manage) the electrical energy that is output by the power source **402**. Further, the physical button (interface) **406** can be in communication with the microcontroller **404**. In some examples, the microcontroller **404** adjusts the electrical energy output by the power source **402** in response to user input at the physical button **406**. For example, a user can provide input at the physical button **406** indicating a desired temperature setting. The microcontroller **404** can receive data from the physical button **406** indicating the desired temperature setting, and in response, provide control signals to the power source **402** to adjust the electrical energy output by the power source **402** to correspond to the desired temperature setting. For example, the physical button **406** can include “up” and “down” buttons for adjusting the temperature setting up or down. For example, the physical button **406** can include a scroll wheel for adjusting the temperature setting up or down. For example, the physical button **406** can be touch sensitive for adjusting the temperature setting up or down.

(29) In some examples, the microcontroller **404** adjusts the electrical energy output by the power source **402** in response to user input provided at a separate computing device and received wireless over a communication channel. For example, a user can provide input at a portable computing device indicating a desired temperature setting. The microcontroller **404** can receive data from the computing device indicating the desired temperature setting, and in response, provide control signals to the power source **402** to adjust the electrical energy output by the power source **402** to correspond to the desired temperature setting.

(30) Referring back to FIG. **7**, the control unit **210** can include first magnetic coupling members **151a**, **151b** (collectively referred to as first magnetic coupling members **151**). However, the control unit **210** can include any number of first magnetic coupling members **151**. The power source **402** can provide the electrical energy to the first magnetic coupling members **151**. Referring back to FIGS. **5** and **6**, the bracket **220** includes second magnetic coupling members **152a**, **152b** (collectively referring to as second magnetic coupling members **152**). However, the bracket **220** can include any number of second magnetic coupling members **152** (e.g., corresponding to the number of first magnetic coupling members **151**).

(31) To that end, when the control unit **210** (and the power source **402**) is coupled to the bracket **220** (as shown in FIGS. **1** and **2**), the first magnetic coupling members **151** of the control unit **210** are coupled to (in contact with) the second magnetic coupling members **152** of the bracket **220**. When the first magnetic coupling members **151** are coupled to (in contact with) the second magnetic coupling members **152**, the power source **402** provides the electrical energy from the first magnetic coupling members **151** to the second magnetic coupling members **152**.

(32) Referring back to FIG. **6**, the bracket **220** can further include a third magnetic coupling member **153**. However, the bracket **220** can include any number of third magnetic coupling members **153**. The third magnetic coupling member **153** is in electrical communication with the second magnetic coupling **152**. When the second magnetic coupling members **152** are in electrical communication with the third magnetic coupling members **153**, the electrical energy provided by the power source **402** is transmitted through the second magnetic coupling members **152** to the third magnetic coupling member **153**.

(33) Referring back to FIG. 2, the first heating element **204a** includes a fourth magnetic coupling members **154**. However, the first heating element **204a** can include any number of fourth magnetic coupling members **154**. To that end, when first heating element **204a** is in electrical communication with the power source **402**, the third magnetic coupling member **153** of the bracket **220** is coupled to (in contact with) the fourth magnetic coupling member **154** of the first heating element **204a**. When the third magnetic coupling member **153** is coupled to (in contact with) the fourth magnetic coupling member **154**, the electrical energy provided by the power source **402** is transmitted through the third magnetic coupling member **153** to the fourth magnetic coupling member **154**.

(34) To that end, when the first heating element **204a** receives the electrical energy from the power source **402**, the first heating element **204a** converts the electrical energy to thermal energy at the first cushion **202a**. That is, end, when first heating element **204a** is in electrical communication with the power source **402**, the electrical energy provided by the power source **402** is transmitted through the fourth magnetic coupling member **154** to wiring of the first heating element **204a** to convert the electrical energy to thermal energy at the first cushion **202a**. Specifically, the first heating element **204a** receives the electrical energy from the power source **402** through the first magnetic coupling members **151** to the second magnetic coupling members **152** to the third magnetic coupling member **153** to the fourth magnetic coupling member **154**. The first heating element **204a** coverts the received electrical energy to thermal energy such that a temperature of the first cushion **202a** (or at the first cushion **202a** or proximate to the first cushion **202a**) is adjusted (e.g., based on the user input at the physical button **406** of the control unit **210**).

(35) FIG. 11 illustrates a back view of the outdoor furniture piece **100**. The first heating element **204a** includes a fifth magnetic coupling member **155**. However, the first heating element **204a** can include any number of fifth magnetic coupling member **155**. The fifth magnetic coupling member **155** is in electrical communication with the wiring of the first heating element **204a** such that electrical energy provided by the power source **402** is transmitted through the writing of the first heating element **204a** to the fifth magnetic coupling member **155**.

(36) Referring to FIGS. 2 and 11, the second heating element **204b** includes a sixth magnetic couple member **156**. However, the second heating element **204b** can include any number of sixth magnetic coupling members **156**. To that end, when the second heating element **204b** is in electoral communication with the first heating element **204a**, the sixth magnetic coupling member **156** of the second heating element **204b** is coupled to (in contact with) the fifth magnetic coupling member **155** of the first heating element **204a**. When the sixth magnetic coupling member **156** is coupled to (in contact with) the fifth magnetic coupling member **155**, the electrical energy provided by the power source **402** is transmitted through the fifth magnetic coupling member **155** to the sixth magnetic coupling member **156**. To that end, when the second heating element **204b** is electrical communication with the first heating element **204a** such that the second heating element **204b** receives the electrical energy from the power source **402** through the first heating element **204a**, the second heating element **204b** converts the electrical energy to thermal energy at the second cushion **202b**. That is, end, when second heating element **204b** is in electrical communication with the power source **402**, the electrical energy provided by the power source **402** is transmitted through the sixth magnetic coupling member **156** to wiring of the second heating element **204b** to convert the electrical energy to thermal energy at the second cushion **202b**. Specifically, the second heating element **204b** receives the electrical energy from the power source **402** through the first magnetic coupling members **151** to the second magnetic coupling members **152** to the third magnetic coupling member **153** to the fourth magnetic coupling member **154** to the wiring of the first heating element **204a** to the fifth magnetic coupling member **155** to the sixth magnetic coupling member **156**. The second heating element **204b** coverts the received electrical energy to thermal energy such that a temperature of the second cushion **202b** (or at the second cushion **202b** or proximate to the second cushion **202b**) is adjusted (e.g., based on the user input at the physical button **406** of the control unit **210**).

(37) FIGS. **12-14** describe managing temperature control of the heating element of the outdoor furniture piece.

(38) For the purposes of this disclosure, a computing device may include an instrumentality or aggregate of instrumentalities operable to compute, classify, process, transmit, receive, retrieve, originate, switch, store, display, manifest, detect, record, reproduce, handle, or utilize various forms of information, intelligence, or data for business, scientific, control, entertainment, or other purposes. For example, a computing device may be a personal computer, a PDA, a consumer electronic device, a network storage device, or another suitable device and may vary in size, shape, performance, functionality, and price. The computing device may include memory, one or more processing resources such as a central processing unit (CPU) or hardware or software control logic. Additional components of the computing device may include one or more storage devices, one or more communications ports for communicating with external devices as well as various input and output (I/O) devices, such as a keyboard, a mouse, and a video display. The computing device may also include one or more buses operable to transmit communication between the various hardware components.

(39) For the purposes of this disclosure, computer-readable media may include an instrumentality or aggregation of instrumentalities that may retain data and/or instructions for a period of time. Computer-readable media may include, without limitation, storage media such as a direct access storage device (e.g., a hard disk drive or floppy disk), a sequential access storage device (e.g., a tape disk drive), compact disk, CD-ROM, DVD, random access memory (RAM), read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), and/or flash memory (SSD); as well as communications media such wires, optical fibers, microwaves, radio waves, and other electromagnetic and/or optical carriers; and/or any combination of the foregoing.

(40) Particular embodiments are best understood by reference to FIGS. **12-14** wherein like numbers are used to indicate like and corresponding parts.

(41) Turning now to the drawings, FIG. **12** illustrates a block diagram depicting selected elements of a computing device **1200** in accordance with some embodiments of the present disclosure. In various embodiments, the computing device **1200** may represent different types of portable computing devices, such as, display devices, head mounted displays, head mount display systems, smart phones, tablet computers, notebook computers, media players, digital cameras, 2-in-1 tablet-laptop combination computers, and wireless organizers, or other types of portable computing devices. In one or more embodiments, computing device **1200** may also represent other types of computing devices, including desktop computers, server systems, controllers, and microcontroller units, among other types of computing devices. Components of computing device **1200** may include, but are not limited to, a processor subsystem **1220**, which may comprise one or more processors, and system bus **1221** that communicatively couples various system components to processor subsystem **1220** including, for example, a memory subsystem **1230**, an I/O subsystem **1240**, a local storage resource **1250**, and a network interface **1260**. System bus **1221** may represent a variety of suitable types of bus structures, e.g., a memory bus, a peripheral bus, or a local bus using various bus architectures in selected embodiments. For example, such architectures may include, but are not limited to, Micro Channel Architecture (MCA) bus, Industry Standard Architecture (ISA) bus, Enhanced ISA (EISA) bus, Peripheral Component Interconnect (PCI) bus, PCI-Express bus, HyperTransport (HT) bus, and Video Electronics Standards Association (VESA) local bus.

(42) As depicted in FIG. **12**, processor subsystem **1220** may comprise a system, device, or apparatus operable to interpret and/or execute program instructions and/or process data, and may include a microprocessor, microcontroller, digital signal processor (DSP), application specific integrated circuit (ASIC), or another digital or analog circuitry configured to interpret and/or execute program instructions and/or process data. In some embodiments, processor subsystem **1220** may interpret and/or execute program instructions and/or process data stored locally (e.g., in

memory subsystem **1230** and/or another component of computing device). In the same or alternative embodiments, processor subsystem **1220** may interpret and/or execute program instructions and/or process data stored remotely (e.g., in network storage resource **1270**).

(43) Also in FIG. **12**, memory subsystem **1230** may comprise a system, device, or apparatus operable to retain and/or retrieve program instructions and/or data for a period of time (e.g., computer-readable media). Memory subsystem **1230** may comprise random access memory (RAM), electrically erasable programmable read-only memory (EEPROM), a PCMCIA card, flash memory, magnetic storage, opto-magnetic storage, and/or a suitable selection and/or array of volatile or non-volatile memory that retains data after power to its associated computing device, such as system **1200**, is powered down.

(44) In computing device **1200**, I/O subsystem **1240** may comprise a system, device, or apparatus generally operable to receive and/or transmit data to/from/within computing device **1200**. I/O subsystem **1240** may represent, for example, a variety of communication interfaces, graphics interfaces, video interfaces, user input interfaces, and/or peripheral interfaces. In various embodiments, I/O subsystem **1240** may be used to support various peripheral devices, such as a touch panel, a display adapter, a keyboard, an accelerometer, a touch pad, a gyroscope, an IR sensor, a microphone, a sensor, or a camera, or another type of peripheral device.

(45) Local storage resource **1250** may comprise computer-readable media (e.g., hard disk drive, floppy disk drive, CD-ROM, and/or other type of rotating storage media, flash memory, EEPROM, and/or another type of solid state storage media) and may be generally operable to store instructions and/or data. Likewise, the network storage resource may comprise computer-readable media (e.g., hard disk drive, floppy disk drive, CD-ROM, and/or other type of rotating storage media, flash memory, EEPROM, and/or other type of solid state storage media) and may be generally operable to store instructions and/or data.

(46) In FIG. **12**, network interface **1260** may be a suitable system, apparatus, or device operable to serve as an interface between computing device **1200** and a network **1210**. Network interface **1260** may enable computing device **1220** to communicate over network **1210** using a suitable transmission protocol and/or standard, including, but not limited to, transmission protocols and/or standards enumerated below with respect to the discussion of network **1210**. In some embodiments, network interface **160** may be communicatively coupled via network **1210** to a network storage resource **1270**. Network **1220** may be a public network or a private (e.g., corporate) network. The network may be implemented as, or may be a part of, a storage area network (SAN), personal area network (PAN), local area network (LAN), a metropolitan area network (MAN), a wide area network (WAN), a wireless local area network (WLAN), a virtual private network (VPN), an intranet, the Internet or another appropriate architecture or system that facilitates the communication of signals, data and/or messages (generally referred to as data). Network interface **1260** may enable wired and/or wireless communications (e.g., NFC or Bluetooth) to and/or from computing device **1200**.

(47) In particular embodiments, network **1210** may include one or more routers for routing data between client computing devices **1200** and server computing devices **1200**. A device (e.g., a client computing device **1200** or a server computing device **1200**) on network **1210** may be addressed by a corresponding network address including, for example, an Internet protocol (IP) address, an Internet name, a Windows Internet name service (WINS) name, a domain name or other system name. In particular embodiments, network **1210** may include one or more logical groupings of network devices such as, for example, one or more sites (e.g. customer sites) or subnets. As an example, a corporate network may include potentially thousands of offices or branches, each with its own subnet (or multiple subnets) having many devices. One or more client computing devices **1200** may communicate with one or more server computing devices **1200** via any suitable connection including, for example, a modem connection, a LAN connection including the Ethernet or a broadband WAN connection including DSL, Cable, T1, T3, Fiber Optics, Wi-Fi, or a mobile

network connection including GSM, GPRS, 3G, or WiMax.

(48) Network **1210** may transmit data using a desired storage and/or communication protocol, including, but not limited to, Fibre Channel, Frame Relay, Asynchronous Transfer Mode (ATM), Internet protocol (IP), other packet-based protocol, small computer system interface (SCSI), Internet SCSI (iSCSI), Serial Attached SCSI (SAS) or another transport that operates with the SCSI protocol, advanced technology attachment (ATA), serial ATA (SATA), advanced technology attachment packet interface (ATAPI), serial storage architecture (SSA), integrated drive electronics (IDE), and/or any combination thereof. Network **1210** and its various components may be implemented using hardware, software, or any combination thereof.

(49) The computing device **1200** can also include a temperature control management computing module **1290**. The temperature control management computing module **1290** can be included by the memory subsystem **1230**. The temperature control management computing module **1290** can include a computer-executable program (software). The temperature control management computing module **1290** can be executed by the processor subsystem **1220**.

(50) Turning to FIG. **13**, FIG. **13** illustrates an environment **1300** including a computing device **1302**, an outdoor furniture piece **1304**, a server computing system **1306**, and a network **1308**. The computing device **1302** can include a temperature control management computing module **1312**. In some examples, the computing device **1302** is similar to, or includes, the computing device **1200** of FIG. **12**. In some examples, the server computing system **1306** is similar to, or includes, the computing device **1200** of FIG. **12**. In some examples, the temperature control management computing module **1312** is the same, or substantially the same, as the temperature control management computing module **1290** of FIG. **12**.

(51) The outdoor furniture piece **1304** can include sensors **1320**, a heating element **1322**, a cushion **1324**, and a power source **1326**. The heating element **1322** is in communication with the power source **1326** and coupled to (or coupled at) the cushion **1324**. The sensors **1320** are in communication with the power source **1326**. In some examples, the outdoor furniture piece **1304** is the same, or substantially the same, as the outdoor furniture piece **100** of FIGS. **1-11**. In some examples, the heating element **1322** is the same, or substantially the same, as the heating element **204** of FIGS. **1-11**. In some examples, the cushion **1324** is the same, or substantially the same, as the cushion **202** of FIGS. **1-11**. In some examples, the power source **1326** is the same as the power source **402** of FIGS. **1-11**. In some examples, the power source **1326** is a rechargeable battery.

(52) The computing device **1302** can be in communication with the outdoor furniture piece **1304**, and in communication with the server computing system **1306** over the network **1308**.

(53) In some examples, the computing device **1302** is integrated within the outdoor furniture piece **1304**. In some examples, the computing device **1302** is separate from the outdoor furniture piece **1304**. In some examples, the computing device **1302** is a smartphone, a tablet computing device, or a portable computing device.

(54) To that end, the computing device **1302**, and in particular, the temperature control management computing module **1312** can manage temperature control of the heating element **1322** of the outdoor furniture piece **1304**, described further herein.

(55) In some embodiments, the temperature control management computing module **1312** can perform, at a first time, a calibration and configuration of a temperature control management module model **1330**. Specifically, performing of the calibration and the configuration of the temperature control management model **1330** can include identifying telemetry data **1340** associated with the sensors **1320**. Specifically, the sensors **1320** can provide the telemetry data **1320** to the computing device **1302**, and ultimately, the temperature control management computing module **1312**. The sensors **1320** can provide the telemetry data **1340** in response to a request from the computing device **1320**, or automatically. In some examples, the sensors **1320** can provide the telemetry data **1340** periodically, e.g., every 1 millisecond, 1 second, 1 minute, 1 hour, 1 day. For example, the sensors **1320** can include an ambient air sensor, a thermostat, an occupancy

sensor, and the like.

(56) In some examples, the telemetry data **1340** can include data regarding ambient conditions of an environment proximate to the outdoor furniture piece **1304**. For example, the ambient conditions, and the telemetry data, can include i) a temperature of the environment proximate to the outdoor furniture piece **1304**; ii) a humidity of the environment proximate to the outdoor furniture piece **1304**; and iii) a pressure of the environment proximate to the outdoor furniture piece **1304**.

(57) In some examples, the telemetry data **1340** can include data regarding conditions at the outdoor furniture piece **1304**. For example, the conditions, and the telemetry data, can include a temperature at the cushion **1324** of the outdoor furniture piece **1304**; a moisture at the cushion **1324** of the outdoor furniture piece **1304**; and iii) an occupancy of a user at the cushions **1324** of the outdoor furniture piece **1304** (e.g., the user sitting at the outdoor furniture piece **1304**).

(58) In some examples, the telemetry data **1340** can include data regarding the power source **1326**. For example, the battery conditions, and the telemetry data, can include i) a voltage of electrical energy output by the power source (rechargeable battery) **1326**; ii) a current capacity of the power source (rechargeable battery) **1326**; and iii) a health of the power source (rechargeable battery) **1326**.

(59) In some examples, the temperature control management computing module **1312** can perform, at the first time period, the calibration and configuration of the temperature control management module model **1330** when an occupancy sensor of the sensors **1320** indicates the occupancy of the user (the user sitting at the outdoor furniture piece **1304**). That is, the temperature control management computing module **1312** can perform, at the first time period, the calibration and configuration of the temperature control management module model **1330** when the user is “sitting” upon the outdoor furniture piece **1304**, and thus, triggering an occupancy sensor of the sensor **1320** to indicate such occupancy of the user. In some examples, the first time period can include a time of day and a day of week.

(60) Performing the calibration and configuration of the temperature control management module model **1330** by the temperature control management computing module **1312** can further include receiving external data **1342** associated with environmental conditions of the outdoor furniture piece **1304** based on a geographic location of the outdoor furniture piece **1304**. Specifically, performing the calibration and the configuration of the temperature control management model **1330** can include receiving the external data **1342** from the server computing system **1306** over the network **1308**. Specifically, the server computing system **1306** can provide the external data **1342** to the computing device **1302**, and ultimately, the temperature control management computing module **1312**. The server computing system **1306** can provide the external data **1342** in response to a request from the computing device **1320**, or automatically. In some examples, the server computing system **1306** can provide the external data **1342** periodically, e.g., every 1 millisecond, 1 second, 1 minute, 1 hour, 1 day.

(61) To that end, the outdoor furniture piece **1304** can be associated with a particular geographic location. The computing device **1302** can identify the particular geographic location of the outdoor furniture piece **1304** and provide data associated the geographic location to the server computing system **1306**. In some examples, the computing device **1302** can identify the geographic location of the outdoor furniture piece **1304** based on a received geographic location from a geographic location sensor of the sensor **1320** from the outdoor furniture piece **1340** (e.g., a “GPS” chip). In some examples, when the computing device **1302** is integrated with the outdoor furniture piece **1304**, the computing device **1302** can include a geographic location sensor. In some examples, a user can manually provide the geographic location of the outdoor furniture piece **1304** to the computing device **1302** (e.g., through one or more user-interactable elements of the computing device **1302**). In some examples, the geographic location can include longitude/latitude coordinates, zip code, city, state, or other.

(62) The server computing system **1306** can receive the geographic location data associated with

the outdoor furniture piece **1304** over the network **1308**. The server computing system **1306** can identify historical weather data and/or forecasted weather data associated with the geographic location, and provide such as the external data **1342** to the computing device **1302**. In some examples, the external data **1342** can include data regarding environmental conditions of the geographic location of the outdoor furniture piece **1304**, such as i) a temperature forecast for the geographic location of the outdoor furniture piece **1304**; ii) a wind forecast for the geographic location of the outdoor furniture piece **1304**; iii) historical weather data for the geographic location of the outdoor furniture piece **1304**; and iv) precipitation trends for the geographic location of the outdoor furniture piece **1304**.

(63) The temperature control management computing module **1312** can train, based on the telemetry data **1340** and the external data **232**, the temperature control management model **1330**. Specifically, the temperature control management computing module **1312** can generate, based the telemetry data **1340** and the external data **1342** at the first time, a configuration policy **1332** that includes configuration rules **1334**.

(64) To that end, the temperature control management computing module **1312** can train the temperature control management model **1330** to establish connections between i) the telemetry data **1340** and the external data **1342** and ii) the configuration rules **1334**. Specifically, the temperature control management model **1330** can identify one or more configurations rules **1334** to be applied based on a connection with one or more of the telemetry data **1340** and the external data **1342**. In some examples, the temperature control management computing module **1312** can train the temperature control management model **1330** using a machine learning process, and/or a neural network.

(65) In some examples, the configuration rules **1334** can include automatically adjusting the electrical energy output by the power source **1326**. In some examples, the configuration rules **1334** include increasing the electrical energy output by the power source **1326**. In some examples, the configuration rules **1334** include decreasing the electrical energy output by the power source **1326**. In some examples, the configuration rules **1334** can include automatically adjusting the electrical energy output by the power source **1326**. In some examples, the configuration rules **1334** include adjusting the electrical energy output by the power source **1326** without user interaction. In some examples, the configuration rules **1334** can include automatically adjusting the electrical energy output by the power source **1326** based on a correspondence of the adjusted electrical energy to a temperature at the cushion **1324**. In some examples, the configuration rules **1334** can include automatically adjusting the electrical energy output by the power source **1326** based on a correspondence of the adjusted electrical energy to a temperature at the cushion **1324** without user interaction. In some examples, the configuration rules **1334** can include automatically increasing the electrical energy output by the power source **1326** based on a correspondence of the adjusted electrical energy to a temperature at the cushion **1324**. In some examples, the configuration rules **1334** can include automatically decreasing the electrical energy output by the power source **1326** based on a correspondence of the adjusted electrical energy to a temperature at the cushion **1324**.

(66) In some examples, the configuration rules **1334** can include providing a notification to a display screen of the computing device **1302**. For example, the notification can indicate a recommended action to be taken by the user of the outdoor furniture piece **1304** with respect to the outdoor furniture piece **1304**.

(67) In some examples, the temperature control management computing module **1312** can perform the calibration and the configuration of the temperature control management model **1330** iteratively. In some examples, the temperature control management computing module **1312** can perform the calibration and the configuration of the temperature control management model **1330** multiple times.

(68) The temperature control management computing module **1312** can perform, at a second time (after the first time), a steady-state management of the temperature control of the heating element

1322 of the outdoor furniture piece **1304**. Specifically, the temperature control management computing module **1312** can monitor the telemetry data **1340** associated with the sensors **1320**. The sensors **1320** can provide the telemetry data **1340** to the computing device **1302**. The sensors **1320** can provide the telemetry data **1340** in response to a request from the computing device **1302**, or automatically. In some examples, the sensors **1320** can provide the telemetry data **1340** periodically, e.g., every 1 millisecond, 1 second, 1 minute, 1 hour, 1 day. Further, the temperature control management computing module **1312** can monitor the external data **1342** from the server computing system **1306**. The server computing system **1306** can provide the external data **1342**. The server computing system **1306** can provide the external data **1342** in response to a request from the computing device **1302**, or automatically. In some examples, the server computing system **1306** can provide the external data **1342** periodically, e.g., every 1 millisecond, 1 second, 1 minute, 1 hour, 1 day.

(69) The temperature control management computing module **1312** can, in response to monitoring the telemetry data **1340** and the external data **1342**, access the temperature control management model **1330** including the configuration policy **1332**. The temperature control management computing module **1312** can further identify one or more of the configuration rules **1334** based on the monitored telemetry data **1340** and/or the external data **1342**. Furthermore, the temperature control management computing module **1312** can apply the configuration rules **1334** to the power source **1326**, and in particular, apply the configuration rules **1334** to perform adjustment of the electrical energy output by the power source **1326**. In other words, the temperature control management computing module **1312** can apply appropriate configuration rules **1334** based on the monitored telemetry data **1340** and the monitored external data **1342** as provided by the temperature control management model **1330**. In some examples, the temperature control management computing module **1312** can apply the configuration rules **1334** to the power source **1326**, and in particular, apply the configuration rules **1334** to perform adjustment of the electrical energy output by the power source **1326** without user interaction. In some examples, the temperature control management computing module **1312** can apply the configuration rules **1334** to the power source **1326**, and in particular, apply the configuration rules **1334** to perform adjustment of the electrical energy output by the power source **1326** to adjust the temperature of the heating element **1322**.

(70) In some examples, the temperature control management computing module **1312** can apply the configuration rules **1334** to the power source **1326**, and in particular, apply the configuration rules **1334** to provide a notification to the display screen of the computing device **1302**. For example, the notification can indicate a recommended action that can be taken by the user of the outdoor furniture piece **1304** with respect to the outdoor furniture piece **1304**.

(71) In some examples, the temperature control management computing module **1312** can perform, at the second time period, the steady-state management of the temperature control of the heating element **1332** of the outdoor furniture piece **1304** when an occupancy sensor of the sensors **1320** indicates the occupancy of the user. That is, the temperature control management computing module **1312** can perform, at the second time period, steady-state management of the temperature control of the heating element **1332** when the user is “sitting” upon the outdoor furniture piece **1304**, and thus, triggering an occupancy sensor of the sensor **1320** to indicate such occupancy of the user. In some examples, the second time period can include a time of day and a day of week.

(72) In some examples, the temperature control management computing module **1312** can perform the steady-state management of the temperature control of the heating element **1332** of the outdoor furniture piece **1304** iteratively.

(73) In a use case example, the temperature control management computing module **1312** can monitor the telemetry data **1340** and the external data **1342** and identify a particular environmental temperature surrounding the outdoor furniture piece **1304**, a temperature setting provided by a user of the outdoor furniture piece **1304**, and a time associated with occupancy of the outdoor furniture

piece **1304** by the user. In response, the temperature control management computing module **1312** can access the temperature control management model **1330**, identify the configuration rules **1334** that are applicable to i) the environmental temperature surrounding the outdoor furniture piece **1304**, ii) the temperature setting, and iii) the time associated with occupancy of the outdoor furniture piece **1304** by the user, and apply such configuration rules **1334**. For example, the temperature control management computing module **1312** can apply configuration rules **1334** to continuously adjust the electrical energy output (e.g., non-linearly or linearly) by the power source **1326** to maintain a substantially constant temperature at the cushion **1324**. For example, the user typically sets the temperature setting 60 degrees Fahrenheit (F) greater than the environmental temperature surrounding the outdoor furniture piece **1304** between the hours of 7 pm-10 pm. On a particular night, at 7 pm, the environmental temperature surrounding the outdoor furniture piece **1304** is 50 degrees F., and the electrical energy output by the power source **1326** is automatically adjusted to obtain a temperature at the cushion **1324** of 110 degrees F. Further, on the particular night, at 9 pm, the environmental temperature surrounding the outdoor furniture piece **1304** is 40 degrees F., and the electrical energy output by the power source **1326** is automatically adjusted to obtain a temperature at the cushion **1324** of 120 degrees F.

(74) In a use case example, the temperature control management computing module **1312** can monitor the telemetry data **1340** and the external data **1342** and identify a particular environmental temperature surrounding the outdoor furniture piece **1304**, a temperature setting provided by a user of the outdoor furniture piece **1304**, a time associated with occupancy of the outdoor furniture piece **1304** by the user, a wind forecast for the geographic location of the outdoor furniture piece **1304**, and a humidity forecast for the geographic location of the outdoor furniture piece **1304**. In response, the temperature control management computing module **1312** can access the temperature control management model **1330**, identify the configuration rules **1334** that are applicable to i) the environmental temperature surrounding the outdoor furniture piece **1304**, ii) the temperature setting, iii) the time associated with occupancy of the outdoor furniture piece **1304** by the user, iv) the wind forecast for the outdoor furniture piece **1304**, and v) the humidity forecast for the outdoor furniture piece **1304**, and apply such configuration rules **1334**. For example, the temperature control management computing module **1312** can apply configuration rules **1334** to continuously adjust the electrical energy output (e.g., non-linearly or linearly) by the power source **1326** to maintain a substantially constant temperature at the cushion **1324**. For example, the user typically sets the temperature setting 60 degrees Fahrenheit (F) greater than the environmental temperature surrounding the outdoor furniture piece **1304** between the hours of 7 pm-10 pm. On a particular night, at 7 pm, the environmental temperature surrounding the outdoor furniture piece **1304** is 50 degrees F., and the electrical energy output by the power source **1326** is automatically adjusted to obtain a temperature at the cushion **1324** of 110 degrees F. Further, on the particular night, at 9 pm, the environmental temperature surrounding the outdoor furniture piece **1304** is 40 degrees F., and the electrical energy output by the power source **1326** is automatically adjusted to obtain a temperature at the cushion **1324** of 120 degrees F.

(75) In a use case example, the temperature control management computing module **1312** can monitor the telemetry data **1340** and the external data **1342** and identify a weather forecast for the particular geographic location of the outdoor furniture piece **1304**, a historical temperature setting over a time period provided by a user of the outdoor furniture piece **1304**, and a temperature setting provided by the user of the outdoor furniture piece associated with occupancy sessions (as indicated by the occupancy sensor) greater than a threshold amount of time. In response, the temperature control management computing module **1312** can access the temperature control management model **1330**, identify the configuration rules **1334** that are applicable to i) the weather forecast for the particular geographic location of the outdoor furniture piece **1304**, ii) historical temperature setting over a time period provided by a user of the outdoor furniture piece **1304**, and iii) temperature setting provided by the user of the outdoor furniture piece associated with

occupancy sessions greater than the threshold amount of time. For example, the temperature control management computing module **1312** can apply configuration rules **1334** to adjust the electrical energy output by the power source **1326** associated with a recommended temperature at the cushion **1324**. For example, the user at a particular day and time, via the computing device **1302**, receives a prompt indicating a “daily smart preset temperature” for the outdoor furniture piece **1304** for the particular day and time.

(76) In a use case example, the temperature control management computing module **1312** can monitor the telemetry data **1340** and the external data **1342** and identify a temperature setting provided by a user of the outdoor furniture piece **1304**, the date, and historical average temperature settings for a particular geographic region of the outdoor furniture piece **1304**. In response, the temperature control management computing module **1312** can access the temperature control management model **1330**, identify the configuration rules **1334** that are applicable to i) the temperature setting provided by a user of the outdoor furniture piece **1304**, ii) the date and iii) the historical average temperature settings for a particular geographic region of the outdoor furniture piece **1304**, and apply such configuration rules **1334**. For example, the temperature control management computing module **1312** can apply configuration rules **1334** to adjust the electrical energy output by the power source **1326** associated with a recommended temperature at the cushion **1324**. For example, the user typically sets the temperature setting at 92 degrees Fahrenheit (F) at a first geographic location of the outdoor furniture piece **1304**. For a differing geographic location of another outdoor furniture piece, the historical average temperature for the differing geographic location is 30 degrees F. colder. The electrically energy output the power source **1326** is automatically adjusted to correspond to a temperature at the cushion **1324** of 122 degrees F.

(77) In a use case example, the temperature control management computing module **1312** can monitor the telemetry data **1340** and the external data **1342** and determine historical temperature setting provided by a user of the outdoor furniture piece **1304**, current weather predictions for the geographic location of the outdoor furniture piece **1304**, historical weather conditions for the geographic location of the outdoor furniture piece **1304**, and the date most often indicated by the occupancy sensor as occupied. In response, the temperature control management computing module **1312** can access the temperature control management model **1330**, identify the configuration rules **1334** that are applicable to i) the historical temperature setting provided by a user of the outdoor furniture piece **1304**, ii) the current weather conditions for the geographic location of the outdoor furniture piece **1304**, iii) the historical weather predictions for the geographic location of the outdoor furniture piece **1304**, and iv) the date most often indicated by the occupancy sensor as occupied, and apply such configuration rules **1334**. For example, the temperature control management computing module **1312** can apply configuration rules **1334** to automatically adjust the electrical energy by the power source **1326** associated with a recommended temperature at the cushion **1324**. Further, the temperature control management computing module **1312** can provide a notification indicating a recommendation of use by the user for a specific date/time.

(78) In a use case example, the temperature control management computing module **1312** can monitor the telemetry data **1340** and the external data **1342** and identify a current temperature proximate to the outdoor furniture piece **1304** and a predicated precipitation proximate to the outdoor furniture piece **1304**. In response, the temperature control management computing module **1312** can access the temperature control management model **1330**, identify the configuration rules **1334** that are applicable to i) the current temperature proximate to the outdoor furniture piece **1304** and ii) the predicated precipitation proximate to the outdoor furniture piece **1304**, and apply such configuration rules **1334**. For example, the temperature control management computing module **1312** can apply configuration rules **1334** to provide a notification at the computing device **1302** to move the cushion **1324** inside when rain is predicted; provide a notification at the computing device **1302** to move the power source **1326** inside when the temperature is below a threshold; or

provide a notification at the computing device **1302** to move the power source **1326** inside when the temperature is above a threshold.

(79) FIG. **14** illustrates a flowchart depicting selected elements of an embodiment of a method **1400** for managing temperature control of a heating element of an outdoor furniture piece. The method **1400** may be performed by the information handling system **1200**, the computing device **1302**, and/or the temperature control management model **1330**, and with reference to FIGS. **12-13**. It is noted that certain operations described in method **1400** may be optional or may be rearranged in different embodiments.

(80) The temperature control management computing module **1320** can perform, at a first time, a calibration and configuration of the temperature control management model **1330** (**1402**). The temperature control management computing module **1320** can identify telemetry data **1340** (**1404**) and external data **1342** (**1406**). The temperature control management computing module **1320** can train, based on the telemetry data **1340** and the external data **1342**, the temperature control management model **1330** (**1408**). In some examples, the temperature control management computing module **1320** can generate, based on the telemetry data **1340** and the external data **1342** identified at the first time, the configuration policy **1332** that includes the configuration rules **1334**. In some examples, the configuration rules **1334** are rules for adjusting the electrical energy output by the power source **1326**. The temperature control management computing module **1320** performs steady-state management of the temperature control management model **1330** (**1410**). The temperature control management computing module **1320** monitors the telemetry data **1340** (**1412**) and environmental conditions of the external data **1342** (**1414**). The temperature control management computing module **1320** can, in response to monitoring the telemetry data **1340** and the environmental conditions of the external data **1342**, access the temperature control management model **1330** including the configuration policy **1332** (**1416**). The temperature control management computing module **1320** can further identify one or more of the configuration rules **1334** based on the monitored the telemetry data **1340** and the environmental conditions of the external data **1342** (**1418**). The temperature control management computing module **1320** can apply the configuration rule(s) **1418** to adjust the electrical energy output by the power source **1326** (**1420**).

(81) The above disclosed subject matter is to be considered illustrative, and not restrictive, and the appended claims are intended to cover all such modifications, enhancements, and other embodiments which fall within the true spirit and scope of the present disclosure. Thus, to the maximum extent allowed by law, the scope of the present disclosure is to be determined by the broadest permissible interpretation of the following claims and their equivalents, and shall not be restricted or limited by the foregoing detailed description.

(82) Herein, “or” is inclusive and not exclusive, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A or B” means “A, B, or both,” unless expressly indicated otherwise or indicated otherwise by context. Moreover, “and” is both joint and several, unless expressly indicated otherwise or indicated otherwise by context. Therefore, herein, “A and B” means “A and B, jointly or severally,” unless expressly indicated otherwise or indicated otherwise by context.

(83) The scope of this disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments described or illustrated herein that a person having ordinary skill in the art would comprehend. The scope of this disclosure is not limited to the example embodiments described or illustrated herein. Moreover, although this disclosure describes and illustrates respective embodiments herein as including particular components, elements, features, functions, operations, or steps, any of these embodiments may include any combination or permutation of any of the components, elements, features, functions, operations, or steps described or illustrated anywhere herein that a person having ordinary skill in the art would comprehend. Furthermore, reference in the appended claims to an apparatus or system or a component of an

apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative.

Claims

1. An outdoor furniture piece, including: a plurality of members coupled together to form a structure of the outdoor furniture piece; a cushion positioned adjacent to one or more first members of the plurality of members of the structure; a heating element coupled to the cushion; a bracket coupled to a second member of the plurality of members, the bracket including one or more protrusions extending from a surface of the bracket; a control unit removably coupled to the bracket, including: one or more recessions on a surface of the control unit; a power source, the power source in electrical communication with the heating element such that the power source provides electrical energy to the heating element, wherein, in response to user input received at a computing device separate from the outdoor furniture piece, the control unit is configured to adjust the electrical energy provided by the power source, wherein when the heating element receives the electrical energy from the power source, the heating element converts the electrical energy to thermal energy at the cushion, wherein when the control unit is coupled to the bracket, the protrusions of the bracket are positioned within corresponding recessions of the control unit.
2. The outdoor furniture piece of claim 1, wherein the second member is one of the first members.
3. The outdoor furniture piece of claim 1, wherein the second member is distinct from the first members.
4. The outdoor furniture piece of claim 1, wherein the power source is a rechargeable battery.
5. The outdoor furniture piece of claim 4, wherein the power source further includes an input power source outlet to receive input power to charge the rechargeable battery.
6. The outdoor furniture piece of claim 1, wherein the power source further includes first magnetic coupling members and the bracket includes second magnetic coupling members, wherein when the power source is coupled to the bracket, the first magnetic coupling members are coupled to the second magnetic coupling members such that the power source provides the electrical energy from the first magnetic coupling members to the second magnetic coupling members.
7. The outdoor furniture piece of claim 6, wherein the bracket further includes third magnetic coupling members that are in electrical communication with the second magnetic coupling members such that the electrical energy provided by the power source is transmitted through the second magnetic coupling members to the third magnetic coupling members.
8. The outdoor furniture piece of claim 7, wherein the heating element further includes fourth magnetic coupling members, wherein when the heating element is in electrical communication with the power source, the third magnetic coupling members are coupled to the fourth magnetic coupling members such that electrical energy provided by the power source is transmitted through the third magnetic coupling members to the fourth magnetic coupling members.
9. The outdoor furniture piece of claim 8, wherein when the heating element is in electrical communication with the power source, the electrical energy provided by the power source is transmitted through the fourth magnetic coupling members to wiring of the heating element to convert the electrical energy to thermal energy at the cushion.
10. The outdoor furniture piece of claim 9, further including: an additional cushion positioned adjacent to one or more third members of the plurality of members of the structure; and an additional heating element coupled to the additional cushion, wherein the additional heating element is in electrical communication with the heating element such that the additional heating element receives the electrical energy from the power source through the heating element, the

additional heating element converting the electrical energy to thermal energy at the additional cushion.

11. The outdoor furniture piece of claim 10, wherein the heating element includes fifth magnetic coupling members that are in electrical communication with the wiring of the heating element such that electrical energy provided by the power source is transmitted through the wiring to the fifth magnetic coupling members.

12. The outdoor furniture piece of claim 11, wherein the additional heating element includes sixth magnetic coupling members, wherein when the additional heating element is in electrical communication with the heating element, the sixth magnetic coupling members are coupled to the fifth magnetic coupling members such that electrical energy provided by the power source is transmitted through the fifth magnetic coupling members to the sixth magnetic coupling members.

13. The outdoor furniture piece of claim 12, wherein when the additional heating element is in electrical communication with the power source, the electrical energy provided by the power source is transmitted through the sixth magnetic coupling members to additional wiring of the additional heating element to convert the electrical energy to thermal energy at the additional cushion.

14. The outdoor furniture piece of claim 1, wherein the structure of the outdoor furniture piece is a chair.

15. The outdoor furniture piece of claim 1, wherein the control unit further includes: a microcontroller in communication with the power source, the microcontroller controlling the electrical energy provided by the power source; and a physical button in communication with the microcontroller, the physical button located on the control unit, wherein, in response to user input at the physical button, the microcontroller is additionally configured to adjust the electrical energy output by the power source.

16. The outdoor furniture piece of claim 1, wherein each of the one or more protrusions of the bracket form a trapezoidal shape, wherein each of the one or more recessions form a trapezoidal shape such that when the control unit is coupled to the bracket, the protrusions of the bracket are positioned within corresponding recessions of the control unit.

17. An outdoor furniture piece, including: a plurality of members coupled together to form a structure of the outdoor furniture piece; a cushion positioned adjacent to one or more first members of the plurality of members of the structure; a heating element coupled to the cushion; a bracket coupled to a second member of the plurality of members, the bracket including one or more protrusions extending from a surface of the bracket; and a control unit removably coupled to the bracket, including: one or more recessions on a surface of the control unit; a power source, the power source in electrical communication with the heating element such that the power source provides an electrical energy to the heating element; a microcontroller in communication with the power source; and a physical button in communication with the microcontroller, wherein, in response to user input received at a computing device separate from the outdoor furniture piece, the microcontroller is configured to adjust the electrical energy provided by the power source, wherein when the heating element receives the electrical energy from the power source, the heating element converts the electric energy to thermal energy at the cushion, wherein when the control unit is coupled to the bracket, the protrusions of the bracket are positioned within corresponding recessions of the control unit.

18. The outdoor furniture piece of claim 17, wherein the power source is a rechargeable battery.

19. The outdoor furniture piece of claim 17, wherein each of the one or more protrusions of the bracket form a trapezoidal shape, wherein each of the one or more recessions form a trapezoidal shape such that when the control unit is coupled to the bracket, the protrusions of the bracket are positioned within corresponding recessions of the control unit.

20. An outdoor furniture system, including: an outdoor furniture piece, including: a plurality of members coupled together to form a structure of the outdoor furniture piece; a cushion positioned

adjacent to one or more first members of the plurality of members of the structure; a heating element coupled to the cushion; a bracket coupled to a second member of the plurality of members, the bracket including one or more protrusions extending from a surface of the bracket; and a control unit removably coupled to the bracket, including: one or more recessions on a surface of the control unit; a rechargeable battery, the rechargeable battery in electrical communication with the heating element such that the rechargeable battery provides an electrical energy to the heating element, a microcontroller in communication with the rechargeable battery; wherein when the heating element receives the electrical energy from the rechargeable battery, the heating element converts the electrical energy to thermal energy at the cushion; a computing device, separate from the outdoor furniture piece, in communication with the microcontroller, the computing device configured to: i) receive user input indicating one or more control settings associated with the thermal energy at the cushion; and ii) provide a communication to the microcontroller indicating the user input, wherein the microcontroller is further configured to receive the user input, and in response, adjust the electrical energy provided by the rechargeable battery based on the control settings, wherein when the control unit is coupled to the bracket, the protrusions of the bracket are positioned within corresponding recessions of the control unit.

21. The outdoor furniture system of claim 20, wherein each of the one or more protrusions of the bracket form a trapezoidal shape, wherein each of the one or more recessions form a trapezoidal shape such that when the control unit is coupled to the bracket, the protrusions of the bracket are positioned within corresponding recessions of the control unit.
