

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396630
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Kaji; Ryosuke et al.

Imaging support device, scanner system, and imaging support method

Abstract

An imaging support device that supports imaging of teeth inside an oral cavity is provided. The imaging support device includes an input unit, an identification unit, a specification unit, and an output unit. The input unit receives a tooth image obtained by imaging the teeth inside the oral cavity. The identification unit identifies a type of a tooth based on the tooth image received by the input unit. Based on the type of the tooth identified by the identification unit, the specification unit specifies a type of a tooth as a target for imaging support. The output unit outputs information about the type of the tooth specified by the specification unit to an outside at a prescribed timing.

Inventors:	Kaji; Ryosuke (Kyoto, JP), Nishimura; Mikinori (Kyoto, JP)
Applicant:	J. MORITA MFG. CORP. (Kyoto, JP)
Family ID:	1000008779551
Assignee:	J. MORITA MFG. CORP. (Kyoto, JP)
Appl. No.:	17/421235
Filed (or PCT Filed):	January 06, 2020
PCT No.:	PCT/JP2020/000034
PCT Pub. No.:	WO2020/145225
PCT Pub. Date:	July 16, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220117480 A1	Apr. 21, 2022

Foreign Application Priority Data

JP	2019-001021	Jan. 08, 2019
----	-------------	---------------

Publication Classification

Int. Cl.: **A61B1/24** (20060101); **A61B1/00** (20060101); **A61B1/04** (20060101); **A61C9/00** (20060101); **G06V40/10** (20220101); G06V10/82 (20220101)

U.S. Cl.:

CPC **A61B1/24** (20130101); **A61B1/000094** (20220201); **A61B1/04** (20130101); **A61C9/0053** (20130101); G06V10/82 (20220101); G06V40/10 (20220101)

Field of Classification Search

CPC: A61B (1/24); A61B (1/000094); A61B (1/04); A61C (9/0053)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0320320	12/2014	Kopelman	433/215	G06T 7/579
2017/0340419	12/2016	Ohtake	N/A	A61C 13/0004
2017/0367789	12/2016	Fujiwara	N/A	A61C 5/77
2018/0168781	12/2017	Kopelman	N/A	A61B 34/10
2018/0296131	12/2017	Kaji	N/A	G01B 11/24
2019/0175303	12/2018	Akopov	N/A	A61C 7/002
2020/0297187	12/2019	Wakazome	N/A	A61B 1/24

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3 901 901	12/2020	EP	N/A
2009517144	12/2008	JP	N/A
2009523552	12/2008	JP	N/A
2011-212234	12/2010	JP	N/A
2012245064	12/2011	JP	N/A
2017521113	12/2016	JP	N/A
2017213060	12/2016	JP	N/A
2007062658	12/2006	WO	N/A
2007084647	12/2006	WO	N/A
2015170162	12/2014	WO	N/A
2016143022	12/2015	WO	N/A
2017111116	12/2016	WO	N/A
2018/167530	12/2017	WO	N/A

OTHER PUBLICATIONS

Office Action issued in counterpart Japanese Patent Application No. 2019-001021 mailed on Jan. 10, 2023 (5 pages). cited by applicant

International Search Report issued in International Application No. PCT/JP2020/000034, mailed Mar. 17, 2020 (5 pages). cited by applicant

Written Opinion issued in International Application No. PCT/JP2020/000034; Dated Mar. 17, 2020 (6 pages). cited by applicant

Extended European Search Report in counterpart European Application No. 20 73 8722.6 issued Aug. 19, 2022 (7 pages). cited by applicant
Office Action issued in Japanese Application No. 2019-001021; Dated Jan. 18, 2022 (13 pages). cited by applicant

Primary Examiner: Bilodeau; David

Attorney, Agent or Firm: Osha Bergman Watanabe & Burton LLP

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to an imaging support device, a scanner system including the imaging support device, and an imaging support method.

BACKGROUND ART

(2) In the dental field, various devices have been developed as imaging devices for imaging the inside of an oral cavity. For example, a scanner device for obtaining three-dimensional (3D) data of a dental site inside the oral cavity of a patient has been developed as an imaging device. However, when the scanner device is used to scan the inside of the oral cavity to acquire three-dimensional data of a dental arch, an overlapping area, a defect area, or the like occurs among a plurality of captured images depending on the user's operation.

(3) Accordingly, in PTL 1, such an overlapping area and a defect area can be identified and displayed as an area of interest in the image captured by the scanner device. Thus, immediately after the user uses the scanner device to captures one or more images, the user can be notified of the area of interest that needs to be re-scanned, thereby allowing easy, quick and accurate scanning with the scanner device.

CITATION LIST

Patent Literature

(4) PTL 1: Japanese National Patent Publication No. 2017-521113

SUMMARY OF INVENTION

Technical Problem

(5) In PTL 1, when the user uses the scanner device to capture an image of a dental arch, the image of the dental arch includes gums and a plurality of teeth, and additionally a plurality of areas of interest. However, by merely showing the area of interest in the image of the dental arch, it cannot be sometimes easily recognized as to which tooth in the dental arch shows an area of interest.

(6) Further, in PTL 1, it cannot be sometimes easily recognized as to which tooth inside the oral cavity of an actual patient corresponds to the tooth having the area of interest shown in the image of the dental arch. Thus, by merely showing an area of interest in the image of the dental arch, there is a limit on imaging support for the scanner device.

(7) The present invention has been made in order to solve the above-described problems, and an object of the present invention is to provide an imaging support device capable of outputting information as a target for imaging support in an imaging device that images an inside of an oral cavity, a scanner system including the imaging support device, and an imaging support method.

Solution to Problem

(8) An imaging support device according to the present invention is an imaging support device that supports imaging of teeth inside an oral cavity, and includes: an input unit that receives a tooth image obtained by imaging the teeth inside the oral cavity; an identification unit that identifies a type of a tooth based on the tooth image received by the input unit; a specification unit that, based

on the type of the tooth identified by the identification unit, specifies a type of a tooth as a target for imaging support; and an output unit that outputs information about the type of the tooth specified by the specification unit to an outside at a prescribed timing.

(9) A scanner system according to the present invention is a scanner system that acquires shape information of a tooth, and includes: a three-dimensional scanner that images teeth using a three-dimensional camera; and an imaging support device that identifies a type of a tooth based on a tooth image in three dimensions that is acquired by the three-dimensional scanner, and gives a notification about the identified type of the tooth. The imaging support device includes: an input unit that receives a tooth image obtained by imaging teeth inside an oral cavity; an identification unit that identifies a type of a tooth based on the tooth image received by the input unit; a specification unit that, based on the type of the tooth identified by the identification unit, specifies a type of a tooth as a target to be imaged; and an output unit that outputs information about the type of the tooth specified by the specification unit to an outside at a prescribed timing.

(10) An imaging support method according to the present invention is an imaging support method of supporting imaging of teeth inside an oral cavity, and includes: receiving a tooth image obtained by imaging the teeth inside the oral cavity; identifying a type of a tooth based on the received tooth image; based on the identified type of the tooth, specifying a type of a tooth as a target to be imaged; and outputting information about the specified type of the tooth to an outside at a prescribed timing.

Advantageous Effects of Invention

(11) The imaging support device according to the present invention specifies a type of a tooth as a target for imaging support based on the type of the tooth identified by the identification unit, and thereby can output the information for imaging support to a user so as to allow the user to easily recognize which tooth inside the oral cavity corresponds to the tooth as a target for imaging support.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram showing an application example of an imaging support device according to the present first embodiment.

(2) FIG. 2 is a schematic diagram showing an entire configuration of a scanner system according to the present first embodiment.

(3) FIG. 3 is a schematic diagram showing a hardware configuration of the imaging support device according to the present first embodiment.

(4) FIG. 4 is a schematic diagram showing a hardware configuration of a server device according to the present first embodiment.

(5) FIG. 5 is a schematic diagram showing a manner of use of the imaging support device according to the present first embodiment.

(6) FIG. 6 is a schematic diagram showing a functional configuration of the imaging support device according to the present first embodiment.

(7) FIG. 7 is a schematic diagram for illustrating an identification process by the imaging support device according to the present first embodiment.

(8) FIG. 8 is a schematic diagram showing examples of teeth to be identified in the identification process according to the present first embodiment.

(9) FIG. 9 is a flowchart for illustrating an example of a support process performed by the imaging support device according to the present first embodiment.

(10) FIG. 10 is a flowchart for illustrating an example of a process of identifying a type of a tooth performed by the imaging support device according to the present first embodiment.

(11) FIG. 11 is a flowchart for illustrating another example of the support process performed by the imaging support device according to the present first embodiment.

(12) FIG. 12 is a flowchart for illustrating still another example of the support process performed by the imaging support device according to the present first embodiment.

(13) FIG. 13 is a flowchart for illustrating an example of a process of identifying a type of a tooth performed by an imaging support device according to the present second embodiment.

DESCRIPTION OF EMBODIMENTS

(14) Embodiments of the present invention will be hereinafter described in detail with reference to the accompanying drawings, in which the same or corresponding components are denoted by the same reference characters, and the description thereof will not be repeated.

First Embodiment

(15) Referring to FIGS. 1 and 2, the following describes an example of a scanner system to which an imaging support device **100** according to the present first embodiment is applied. FIG. 1 is a schematic diagram showing an application example of imaging support device **100** according to the present first embodiment. FIG. 2 is a schematic diagram showing an entire configuration of a scanner system according to the present first embodiment.

(16) As shown in FIG. 1, a user **1** images teeth inside an oral cavity with a scanner system **10**, and thereby can acquire data of a three-dimensional shape (hereinafter also referred to as “three-dimensional data”) including data of teeth of a subject **2**. The “user” may be any person (a user) who uses scanner system **10**, for example, an operator such as a dentist, a dental assistant, a teacher or a student of a dental university, a dental engineer, an engineer of a manufacturer, an operator in a manufacturing factory, and the like. The “subject” may be any person as a target of scanner system **10**, such as a patient in a dental clinic or a subject in a dental university.

(17) Scanner system **10** according to the present first embodiment includes a three-dimensional scanner **200**, an imaging support device **100**, a display **300**, and a speaker **400**. Three-dimensional scanner **200** acquires three-dimensional data by imaging a scan target with a built-in three-dimensional camera. Specifically, three-dimensional scanner **200** scans the inside of an oral cavity with an optical sensor or the like to acquire, as three-dimensional data, position information (coordinates of each of axes in the vertical direction, the horizontal direction, and the height direction) at each of a plurality of points forming a tooth to be scanned. Imaging support device **100** causes display **300** to show a three-dimensional image generated based on the three-dimensional data acquired by three-dimensional scanner **200**.

(18) For example, in order to digitally design a prosthesis or the like on a computer for filling a defect portion in a tooth of subject **2**, user **1** uses three-dimensional scanner **200** to image the inside of the oral cavity of subject **2** to thereby acquire three-dimensional data of the inside of the oral cavity including teeth. Each time user **1** images the inside of the oral cavity, three-dimensional data is sequentially acquired and then a three-dimensional image of the inside of the oral cavity is shown on display **300**. User **1** performs scanning so as to prevent excess and insufficiency in acquiring three-dimensional data while checking the three-dimensional image shown on display **300**. At this time, based on the three-dimensional image obtained by visualization of the three-dimensional data including data of the teeth acquired by three-dimensional scanner **200**, and also from the knowledge of user **1**, user **1** identifies a type of the tooth that is being scanned or that has been completely scanned. However, since the level of knowledge is different for each user **1**, the accuracy of the identification result may vary depending on the knowledge of user **1**.

(19) Thus, scanner system **10** according to the present first embodiment is configured to perform a process of automatically identifying a type of a tooth based on the three-dimensional data acquired by three-dimensional scanner **200** with the help of artificial intelligence (AI) included in imaging support device **100** to specify a type of a tooth as a target for imaging support. The process of identifying a type of a tooth using AI by imaging support device **100** will also be referred to as an “identification process”.

(20) A “type of a tooth” means a type of each of teeth such as: a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the right side in an upper jaw; a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the left side in the upper jaw; a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the right side in a lower jaw; and a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the left side in the lower jaw.

(21) Specifically, when user **1** scans teeth inside the oral cavity of subject **2** using three-dimensional scanner **200**, three-dimensional data including data of teeth is input into imaging support device **100**. Imaging support device **100** performs an identification process of identifying a type of a tooth based on the input three-dimensional data including a feature of the tooth and an estimation model including a neural network.

(22) The “estimation model” includes a neural network and a parameter used by the neural network, and is optimized (adjusted) when this “estimation model” is learned based on: the tooth information corresponding to the type of the tooth associated with the three-dimensional data; and an identification result about the type of the tooth that is obtained using the three-dimensional data. Specifically, when the three-dimensional data including data of teeth is input, the estimation model extracts a feature of the tooth by the neural network based on the three-dimensional data, and estimates a type of the tooth based on the extracted feature of the tooth. As to the estimation model, based on the comparison between the type of the tooth estimated by the estimation model and the type of the tooth (tooth information) associated with the input three-dimensional data, if the types match with each other, the parameter is not updated, whereas, if the types do not match with each other, the parameter is updated such that the types match with each other, thereby optimizing the parameter. In this way, the estimation model is learned by optimizing the parameter using teacher data including the three-dimensional data as input data and the type of the tooth (tooth information) as correct data.

(23) Such a process of learning the estimation model will also be referred to as a “learning process”. The estimation model optimized by the learning process will also be particularly referred to as a “learned model”. In other words, in the present first embodiment, the estimation model before learning and the learned estimation model will be collectively referred to as an “estimation model”, and particularly, the learned estimation model will also be referred to as a “learned model”.

(24) The “tooth information” includes names of teeth such as: a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the right side in an upper jaw; a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the left side in the upper jaw; a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the right side in a lower jaw; and a central incisor, a lateral incisor, a canine, a first premolar, a second premolar, a first molar, a second molar, and a third molar on the left side in the lower jaw. Further, the “tooth information” includes numbers assigned to respective teeth (for example, the tooth numbers generally used in the dental field) such as: number **1** assigned to a central incisor, number **2** assigned to a lateral incisor, number **3** assigned to a canine, number **4** assigned to a first premolar, number **5** assigned to a second premolar, number **6** assigned to a first molar, number **7** assigned to a second molar, and number **8** assigned to a third molar. In addition, the “tooth information” may include information of colors assigned to the respective teeth or information of symbols assigned to the respective teeth.

(25) For example, when imaging support device **100** outputs, as imaging support, the information about the tooth that has been completely scanned (imaged), an identification process is performed using a learned model. Then, based on the identified type of the tooth, the type of the tooth as a target for imaging support is specified, and the specification result is output to display **300** and

speaker **400**.

(26) Display **300** shows at least one of an image, a character, a numeral, an icon, and a symbol that correspond to the specification result. For example, when imaging support device **100** performs a support process of giving a notification about the type of the tooth that has been completely scanned, after three-dimensional scanner **200** completes scanning of the second molar corresponding to number **7** on the right side in the lower jaw, display **300** shows, as the specification result, an image indicating that scanning of the second molar corresponding to number **7** on the right side in the lower jaw has completed, for example, by showing a message such as “Scanning of number **7** on lower right has completed”. When the specification result is incorrect, imaging support device **100** may accept the correction result through an operation input, an audio input, or the like. The audio input may be accepted by receiving a sound through a microphone (not shown).

(27) Speaker **400** outputs a sound corresponding to the specification result. For example, after three-dimensional scanner **200** completes scanning of the second molar corresponding to number **7** on the right side in the lower jaw, speaker **400** adopts the specification result about the tooth obtained by imaging support device **100**, and outputs a sound indicating that scanning of the second molar corresponding to number **7** on the right side in the lower jaw has completed, for example, by showing a message such as “Number **7** on lower right has completed”. Also, imaging support device **100** does not output the type of the tooth that has been completely scanned to display **300**, speaker **400**, and the like, but may specify a type of a tooth that has been completely scanned, and then output the type of the tooth, which is to be scanned next, to display **300**, speaker **400**, and the like. When predicting a type of a tooth to be scanned next based on the information used for specifying the type of the tooth that has been completely scanned, imaging support device **100** predicts a type of a tooth that is not scanned and located close to the tooth of the type having been completely scanned, for example, as a type of a tooth to be scanned next. Further, imaging support device **100** may predict a type of a tooth to be scanned next, in combination with a motion sensor, a gyro sensor, or the like.

(28) Further, the identification result obtained by the identification process performed by imaging support device **100** may be output together with the three-dimensional data used in the identification process, as scan information, to a dental laboratory and a server device **500** disposed in a management center. Imaging support device **100** may require user **1** to check the scan information when it outputs the scan information to the dental laboratory and server device **500** disposed in the management center.

(29) For example, as shown in FIG. **2**, scanner system **10** is disposed in each of a plurality of locals A to C. For example, locals A and B each are a dental clinic. In such a dental clinic, an operator or a dental assistant as user **1** uses scanner system **10** to acquire three-dimensional data including data of teeth of a patient as subject **2**. Local C is a dental university, in which a teacher or a student as user **1** acquires three-dimensional data of the inside of the oral cavity of a target as subject **2**. The scan information (three-dimensional data, identification result) acquired in each of locals A to C is output through a network **5** to a dental laboratory as a local and server device **500** disposed in a management center.

(30) In the dental laboratory, based on the scan information acquired from each of locals A to C, a dental engineer or the like creates a prosthesis or the like for filling a defect portion in a tooth of subject **2**. In the management center, server device **500** stores an accumulation of the scan information acquired from each of locals A to C, and holds the stored information as big data.

(31) It should be noted that server device **500** does not necessarily have to be disposed in a management center different from a local in which the dental clinic is disposed, but may be disposed in a local. For example, server device **500** may be disposed in any one of locals A to C. Further, a plurality of imaging support devices **100** may be disposed in one local. Also, server device **500** capable of communicating with the plurality of imaging support devices **100** may be

disposed in this one local. Further, server device **500** may be implemented in the form of a cloud service.

(32) In a dental laboratory, scan information is aggregated from various locations such as locals A to C. Thus, the scan information held in the dental laboratory may be transmitted to the management center through network **5**, or may be transmitted to the management center through a removable disk **550** such as a compact disc (CD) and a universal serial bus (USB) memory.

(33) In addition, the scan information may be sent to the management center also from each of locals A to C through removable disk **550** without through network **5**. Further, the scan information may be exchanged also among locals A to C through network **5** or removable disk **550**.

(34) Imaging support device **100** in each of locals A to C holds an estimation model, and uses the holding estimation model to identify a type of a tooth during the identification process. Imaging support devices **100** in locals A to C learn their respective estimation models by their respective learning processes to generate learned models. Further, in the present first embodiment, server device **500** also holds an estimation model. Server device **500** learns the estimation model by the learning process performed using the scan information acquired from imaging support device **100** in each of locals A to C and from the dental laboratory, to thereby generate a learned model and then distribute the learned model to imaging support device **100** in each of locals A to C. In the present first embodiment, each of imaging support devices **100** in locals A to C and server device **500** performs the learning process, but only each of imaging support devices **100** in locals A to C may perform the learning process, or only server device **500** may perform the learning process. In the case where only server device **500** performs the learning process, the estimation model (learned model) held by imaging support device **100** in each of locals A to C is shared among imaging support devices **100** in locals A to C.

(35) Further, server device **500** may have functions of the identification process and the specification process in imaging support device **100**. For example, each of locals A to C may transmit the acquired three-dimensional data to server device **500**. Then, server device **500** may calculate the identification result about the type of the tooth in each three-dimensional data received from each of local areas A to C based on the three-dimensional data, or may specify a type of a tooth as a target for imaging support based on the identified type of the tooth. Then, server device **500** may transmit the identification results and the specification results to their respective locals A to C. Then, locals A to C each may specify a type of a tooth as a target for imaging support based on the identification result received from server device **500** or may output the specification results to their respective displays or the like. In this way, each of locals A to C and server device **500** may be configured in the form of a cloud service. In this way, server device **500** only has to hold the estimation model (learned model), and thereby, each of locals A to C can obtain the identification result without having to hold the estimation model (learned model).

(36) In this way, according to scanner system **10** of the present first embodiment, the AI included in imaging support device **100** is used to automatically identify a type of a tooth based on the three-dimensional data acquired by three-dimensional scanner **200** and specify a type of a tooth as a target for imaging support based on the identified type of the tooth. By using the AI, the feature of a tooth obtained from the knowledge of user **1** can be found. Further, the feature of a tooth that cannot be extracted by user **1** can also be found. Thereby, user **1** can accurately identify a type of a tooth without relying on his/her own knowledge. Imaging support device **100** uses the identification result, for example, to perform imaging support for specifying a type of a tooth that has been completely imaged, thereby allowing user **1** to easily recognize the correspondence between the tooth that has been completely imaged and the type of the tooth.

(37) [Hardware Configuration of Imaging Support Device]

(38) An example of a hardware configuration of imaging support device **100** according to the present first embodiment will be hereinafter described with reference to FIG. **3**. FIG. **3** is a schematic diagram showing a hardware configuration of imaging support device **100** according to

the present first embodiment. Imaging support device **100** may be implemented, for example, by a general-purpose computer or a computer dedicated to scanner system **10**.

(39) As shown in FIG. **3**, imaging support device **100** includes, as main hardware elements, a scanner interface **102**, a display interface **103**, a speaker interface **104**, a peripheral interface **105**, a network controller **106**, a medium reading device **107**, a PC display **108**, a memory **109**, a storage **110**, and a computing device **130**.

(40) Scanner interface **102**, which is an interface for connecting three-dimensional scanner **200**, implements input/output of data between imaging support device **100** and three-dimensional scanner **200**.

(41) Display interface **103**, which is an interface for connecting display **300**, implements input/output of data between imaging support device **100** and display **300**. Display **300** is configured, for example, by a liquid crystal display (LCD), an organic electroluminescence (ELD) display or the like.

(42) Speaker interface **104**, which is an interface for connecting speaker **400**, implements input/output of data between imaging support device **100** and speaker **400**.

(43) Peripheral interface **105**, which is an interface for connecting peripheral devices such as a keyboard **601** and a mouse **602**, implements input/output of data between imaging support device **100** and each peripheral device.

(44) Network controller **106** transmits and receives data through network **5** to and from each of: a device disposed in the dental laboratory; server device **500** disposed in the management center; and other imaging support devices **100** disposed in other locals. Network controller **106** supports optional communication schemes such as Ethernet (registered trademark), a wireless local area network (LAN), or Bluetooth (registered trademark).

(45) Medium reading device **107** reads various pieces of data such as scan information stored in removable disk **550**.

(46) PC display **108** is a display dedicated to imaging support device **100**. PC display **108** is configured by an LCD or an organic EL display, for example. In the present first embodiment, PC display **108** is provided separately from display **300** but may be integrated with display **300**.

(47) Memory **109** provides a storage area in which program codes, work memory, and the like are temporarily stored when computing device **130** executes an optional program. Memory **109** is configured by a volatile memory device such as a dynamic random access memory (DRAM) or a static random access memory (SRAM), for example.

(48) Storage **110** provides a storage area in which various pieces of data required for the identification process, the learning process, and the like are stored. Storage **110** is configured by a non-volatile memory device such as a hard disk or a solid state drive (SSD), for example.

(49) Storage **110** stores scan information **112**, an estimation model **114** (a learned model **114a**), a learning data set **116**, color classification data **118**, profile data **119**, an identification program **120**, a learning program **121**, and an operating system (OS) **127**.

(50) Scan information **112** includes three-dimensional data **122** acquired by three-dimensional scanner **200**, and an identification result **124** obtained by the identification process performed based on three-dimensional data **122**. Identification result **124** is associated with three-dimensional data **122** used in the identification process and is stored in storage **110**. Learning data set **116** is a group of learning data used for the learning process of estimation model **114**. Color classification data **118** is data used for generation of learning data set **116** and the learning process. Profile data **119** is attribute information related to subject **2** and includes a summary of profiles about subject **2** (for example, information on medical charts) such as an age, a gender, a race, a height, a weight, and a place of residence. Identification program **120** is a program for performing the identification process. A specification program **120a** is a program for performing the specification process of specifying a type of a tooth as a target for imaging support. Learning program **121** is a program for performing the learning process of estimation model **114**, and also includes a program for

performing the identification process.

(51) Computing device **130** is a computing entity that executes various programs to thereby perform various processes such as an identification process and a learning process. Computing device **130** is also one example of a computer. Computing device **130** is configured, for example, by a central processing unit (CPU) **132**, a field-programmable gate array (FPGA) **134**, a graphics processing unit (GPU) **136**, and the like.

(52) [Hardware Configuration of Server Device]

(53) An example of a hardware configuration of server device **500** according to the present first embodiment will be hereinafter described with reference to FIG. **4**. FIG. **4** is a schematic diagram showing a hardware configuration of server device **500** according to the present first embodiment. Server device **500** may be implemented, for example, by a general-purpose computer or by a computer dedicated to scanner system **10**.

(54) As shown in FIG. **4**, server device **500** includes, as main hardware elements, a display interface **503**, a peripheral interface **505**, a network controller **506**, a medium reading device **507**, a memory **509**, a storage **510**, and a computing device **530**.

(55) Display interface **503**, which is an interface for connecting display **350**, implements input/output of data between server device **500** and display **350**. Display **350** is configured, for example, by an LCD, an organic ELD display, or the like.

(56) Peripheral interface **505**, which is an interface for connecting peripheral devices such as a keyboard **651** and a mouse **652**, implements input/output of data between server device **500** and each peripheral device.

(57) Network controller **506** transmits and receives data through network **5** to and from each of imaging support device **100** disposed in each local and a device disposed in a dental laboratory. Network controller **506** may support optional communication schemes such as Ethernet (registered trademark), a wireless LAN, or Bluetooth (registered trademark).

(58) Medium reading device **507** reads various pieces of data such as scan information stored in removable disk **550**.

(59) Memory **509** provides a storage area in which program codes, work memory, and the like are temporarily stored when computing device **530** executes an optional program. Memory **509** is configured, for example, by a volatile memory device such as a DRAM or an SRAM.

(60) Storage **510** provides a storage area in which various pieces of data required for the learning process and the like is stored. Storage **510** is configured, for example, by a non-volatile memory device such as a hard disk or an SSD.

(61) Storage **510** stores scan information **512**, an estimation model **514** (a learned model **514a**), a learning data set **516**, color classification data **518**, profile data **519**, a learning program **521**, and an OS **527**.

(62) Scan information **512** includes: three-dimensional data **522** acquired through network **5** from imaging support device **100** and a dental laboratory disposed in locals; and an identification result **524** obtained by an identification process performed based on three-dimensional data **522**.

Identification result **524** is associated with three-dimensional data **522** used in the identification process and is stored in storage **510**. Learning data set **516** is a group of learning data used for the learning process of estimation model **514**. Color classification data **518** is data used for generation of learning data set **516** and the learning process. Profile data **519** is attribute information related to subject **2** and includes a summary of profiles about subject **2** (for example, information on medical charts) such as an age, a gender, a race, a height, a weight, and a place of residence. Learning program **521** is a program for performing the learning process of estimation model **514**, and also includes a program for performing the identification process.

(63) In addition, estimation model **514** (learned model **514a**) is transmitted to imaging support device **100** in each local, and thereby, held as estimation model **114** (learned model **114a**) by imaging support device **100**.

(64) Computing device **530** is a computing entity that executes various programs to thereby perform various processes such as a learning process. Computing device **530** is also one example of a computer. Computing device **530** is configured, for example, by a CPU **532**, an FPGA **534**, a GPU **536**, and the like.

(65) [Specification Process by Imaging Support Device]

(66) The following describes an example of an imaging support device in accordance with imaging support device **100** according to the present first embodiment with reference to FIGS. **5** to **8**. FIG. **5** is a schematic diagram showing a manner of use of imaging support device **100** according to the present first embodiment. The following describes the case of supporting three-dimensional scanner **200** (scanning device) that acquires three-dimensional data of a dental arch by joining a plurality of pieces of three-dimensional data acquired by scanning (imaging) the inside of an oral cavity. Of course, three-dimensional scanner **200** may be a device that scans the inside of the oral cavity to acquire a plurality of pieces of three-dimensional data of some portions of a dentition without joining the plurality of pieces of three-dimensional data.

(67) Three-dimensional scanner **200** scans the inside of the oral cavity as shown in FIG. **5** and thereby can sequentially acquire pieces of three-dimensional data of some portions of the dental arch. Then, by joining these pieces of three-dimensional data, three-dimensional data of the entire dental arch can be acquired. However, when three-dimensional scanner **200** is used to scan the inside of the oral cavity to acquire three-dimensional data of the dental arch, an overlapping area, a defect area, and the like may exist in the plurality of pieces of imaged three-dimensional data depending on the user's operation.

(68) Thus, at the timing at which the entire dental arch is imaged, imaging support device **100** specifies a lacking portion (defect area) of a tooth for which the information obtained from the three-dimensional data does not satisfy a prescribed criterion, and then, outputs the specification result to display **300** as support information. In other words, as shown in FIG. **5**, imaging support device **100** puts a marking on the tooth having a lacking portion and outputs a message of “re-measure buccal-side plane of first molar on left side in lower jaw” to display **300**, for implementing imaging support. Thus, by the output of imaging support device **100**, user **1** can easily, quickly and accurately perform re-scanning with three-dimensional scanner **200**. In this case, the prescribed criterion is a criterion at which the amount of data is predetermined with the degree of accuracy required to create a prosthesis from the three-dimensional data acquired by three-dimensional scanner **200**.

(69) In FIG. **5**, imaging support device **100** specifies the type of the tooth lacking three-dimensional data as “buccal-side plane of first molar on left side in lower jaw” or the like, and thus, specifies not only the type of the tooth but also a partial area in the tooth. Of course, imaging support device **100** may specify only the type of the tooth lacking three-dimensional data, for example, only the “first molar on left side in lower jaw”.

(70) FIG. **6** is a schematic diagram showing a functional configuration of imaging support device **100** according to the present first embodiment. FIG. **7** is a schematic diagram for illustrating the identification process by imaging support device **100** according to the present first embodiment. FIG. **8** is a schematic diagram showing examples of teeth to be identified in the identification process according to the present first embodiment. In FIG. **8**, teeth to be scanned by three-dimensional scanner **200** are represented by diagrammatic drawings.

(71) As shown in FIG. **6**, imaging support device **100** includes an input unit **1102**, a profile acquisition unit **1119**, an identification unit **1130**, a specification unit **1150**, and an output unit **1103**, each of which is provided as a functional unit related to the identification process and the specification process. Each of these functions is implemented by computing device **130** of imaging support device **100** executing an OS **127**, identification program **120**, and specification program **120a**.

(72) Input unit **1102** receives three-dimensional data acquired by three-dimensional scanner **200**.

Profile acquisition unit **1119** acquires profile data **119** of subject **2**. Based on the three-dimensional data input into input unit **1102** and profile data **119** of subject **2** acquired by profile acquisition unit **1119**, identification unit **1130** performs an identification process of identifying a type of a tooth using estimation model **114** (learned model **114a**).

(73) Estimation model **114** includes a neural network **1142** and a parameter **1144** used by neural network **1142**. Parameter **1144** includes a weighting factor used for calculation by neural network **1142** and a determination value used for determination of identification. From among teeth that need to be imaged for user **1**, specification unit **1150** specifies a type of a tooth for which information obtained from a tooth image (for example, three-dimensional data) does not satisfy a prescribed criterion. Specifically, based on the type of the tooth identified by identification unit **1130**, specification unit **1150** specifies a type of a tooth corresponding to a portion of the acquired three-dimensional data that does not exceed a predetermined amount of data. Also, specification unit **1150** does not necessarily have to specify a type of a tooth for which data is insufficient, but also may specify other types of teeth such as a type of a tooth to be imaged next, or a type of a tooth at the time when imaging is stopped. Output unit **1103** outputs the specification result obtained by specification unit **1150** to display **300**, speaker **400**, and the like.

(74) In this case, as shown in FIG. 7, the three-dimensional data input into input unit **1102** includes three-dimensional position information at each of points of a tooth and color information at each of points of a tooth. In the identification process, the position information is used. The position information includes coordinates of an absolute position in three dimensions with respect to a predetermined position. For example, the position information includes coordinates of an absolute position on each of axes including an X axis (for example, an axis of a tooth in the horizontal direction), a Y axis (for example, an axis of a tooth in the vertical direction), and a Z axis (for example, an axis of a tooth in the height direction) with reference to a central position at each of points of a tooth as an origin point. The position information is not limited to the coordinates of an absolute position in three dimensions with respect to a predetermined position, but may include coordinates of a relative position in three dimensions indicating the distance from an adjacent point, for example.

(75) In this case, as shown in FIG. 8, when the tooth to be scanned by three-dimensional scanner **200** is an incisor in an upper jaw, user **1** scans the inside of the oral cavity of subject **2** such that the three-dimensional image to be obtained includes at least an image of an area on the upper lip side, an image of an area on the palate side, and an image of an area on the incisal edge side. When the teeth to be scanned by three-dimensional scanner **200** are a canine and a molar in the upper jaw, user **1** scans the inside of the oral cavity of subject **2** such that the three-dimensional image to be obtained includes at least an image of an area on the buccal side, an image of an area on the palate side, and an image of an occlusion area. When the tooth to be scanned by three-dimensional scanner **200** is an incisor in the lower jaw, user **1** scans the inside of the oral cavity of subject **2** such that the three-dimensional image to be obtained includes at least an image of an area on the lower lip side, an image of an area on the tongue side, and an image of an area on the incisal edge side. When the teeth to be scanned by three-dimensional scanner **200** are a canine and a molar in the lower jaw, user **1** scans the inside of the oral cavity of subject **2** such that the three-dimensional image to be obtained includes at least an image of an area on the buccal side, an image of an area on the tongue side, and an image of an occlusion area.

(76) In general, the teeth of subject **2** vary in shape and size depending on their types. For example, in the case of an incisor in the upper jaw, the plane on the upper lip side generally has a U-shape. In the case of a canine in the upper jaw, the plane on the buccal side generally has a pentagonal shape. Each tooth has a characteristic shape and a characteristic size depending on its type. Based on the three-dimensional data obtained by digitizing such a characteristic shape and a characteristic size, identification unit **1130** uses estimation model **114** to identify a type of a tooth corresponding to the three-dimensional data.

(77) As shown in FIG. 7, estimation model **114** includes neural network **1142**. In neural network **1142**, a value of the position information included in the three-dimensional data input into input unit **1102** is input to an input layer. Then, in neural network **1142**, for example, by the intermediate layer, the input value of the position information is multiplied by a weighting factor, and a predetermined bias is added to the input value of the position information, and also, calculation with a predetermined function is performed. Then, the calculation result is compared with the determination value. Further, in neural network **1142**, the result obtained by the above-mentioned calculation and determination is output as the identification result from the output layer. The calculation and determination by neural network **1142** may be performed by any method as long as a tooth can be identified based on the three-dimensional data.

(78) In neural network **1142** of estimation model **114**, the intermediate layer has a multi-layered structure, and thus, a process by deep learning is performed. In the present embodiment, examples of identification program **120** for performing an identification process specialized for a three-dimensional image may be VoxNet, 3D ShapeNets, Multi-View CNN, RotationNet, OctNet, FusionNet, PointNet, PointNet++, SSCNet, MarrNet, and the like, but other programs may be used. An existing mechanism may also be applied to neural network **1142**.

(79) In such a configuration, when imaging support device **100** receives three-dimensional data corresponding to a three-dimensional image including a plurality of teeth, imaging support device **100** can extract respective features of the teeth using neural network **1142** of estimation model **114** based on the three-dimensional data, and then identify respective types of the teeth based on the extracted features of the teeth. Further, as shown in FIG. 7, imaging support device **100** receives not only a target tooth to be identified but also three-dimensional data including data of teeth adjacent to this target tooth, and thereby, neural network **1142** of estimation model **114** can extract the feature of the target tooth also in consideration of the relation with the shapes of the adjacent teeth. Imaging support device **100** can extract not only a tooth feature that is generally recognized but also a tooth feature that is not generally recognized, and thereby, can accurately identify a type of a tooth.

(80) The neural network included in estimation model **514** held in server device **500** has the same configuration as that of neural network **1142** included in estimation model **114** shown in FIG. 7.

(81) [Generation of Learning Data]

(82) An example of generation of learning data set **116** will be hereinafter described. First, three-dimensional data is acquired by three-dimensional scanner **200**. The three-dimensional data includes three-dimensional position information at each of points of a corresponding tooth and color information (RGB values) at each of points of the tooth. When a three-dimensional image is generated based on the three-dimensional data acquired by three-dimensional scanner **200**, a three-dimensional image including teeth in actual colors is generated.

(83) Then, a noise removing process is performed as a preparation for a color-coding process for each tooth. For example, in the present first embodiment, a three-dimensional image corresponding to the three-dimensional data is gray-scaled. Then, predetermined colors are applied to the respective teeth included in the three-dimensional image corresponding to the three-dimensional data, and thereby, the teeth are color-coded. For example, color classification data **118** held in imaging support device **100** is provided for each of areas inside the oral cavity, such as the left side in the lower jaw, the right side in the lower jaw, the left side in the upper jaw, and the right side in the upper jaw.

(84) For example, the second molar is assigned number **7** as a tooth number and assigned red as color information. The first molar is assigned number **6** as a tooth number and assigned green as color information. The second premolar is assigned number **5** as a tooth number and assigned blue as color information. In this way, in each color classification data **118**, the tooth number and the color information are assigned in advance for each type of tooth.

(85) Application of colors to the respective teeth is performed by user **1** (such as an engineer of a

manufacturer or an operator in a manufacturing factory). Specifically, user **1** identifies a type of each tooth included in the three-dimensional image based on his/her knowledge, specifies colors corresponding to the identified types of teeth while referring to color classification data **118**, and then, applies the specified colors to the images of the respective teeth.

(86) For example, when user **1** identifies the tooth included in the three-dimensional image as the second molar, user **1** applies a red color to an image of the tooth. When user **1** identifies the tooth included in the three-dimensional image as the first molar, user **1** applies a green color to an image of the tooth.

(87) Further, in accordance with the color-coding of the teeth, the color information (RGB values) at each point of each of the teeth corresponding to the three-dimensional data is changed to a value corresponding to the color applied to each tooth. For example, the color information (RGB values) is “255000000” for each position coordinate of the second molar in red color; the color information (RGB values) is “000255000” for each position coordinate of the first molar in green color; and the color information (RGB values) is “00000255” for each position coordinate of the second premolar in blue color. In other words, predetermined color information (RGB values) is associated with each of points of a tooth corresponding to the three-dimensional data.

(88) When the predetermined color information is associated with each tooth, the three-dimensional data includes position information and color information that corresponds to the applied color. Then, such three-dimensional data is employed as learning data. In other words, in the learning data according to the present embodiment, the color information corresponding to each type of tooth is associated (labeled) with the position information referred to in the identification process. Further, the color information is associated with the three-dimensional data such that the range of each of the teeth corresponding to the three-dimensional data can be specified.

Specifically, the same color information is associated for each position information corresponding to each tooth. A collection of such learning data is held in imaging support device **100** as learning data set **116**.

(89) Thus, when generating learning data, user **1** applies colors to the respective teeth included in the three-dimensional image to thereby label the correct data, which provides many advantages. For example, in the case of labeling with simple characters or symbols, it is difficult for user **1** to recognize the range of each tooth. However, in the case of labeling by color-coding, application of colors allows user **1** to readily recognize the boundary between a target tooth to be labeled and a tooth adjacent to the target tooth, and the boundary between a target tooth to be labeled and gums. Further, user **1** applies colors while checking the three-dimensional image from various angles during labeling. Even when the angle at which the image is viewed is changed, user **1** still readily recognizes a specific range in which application of colors to the teeth that are being labeled has completed.

(90) In the present embodiment, based on the knowledge of user **1**, user **1** manually applies colors to the respective teeth included in the three-dimensional image. However, such a manual operation can also be partially performed complementarily by software. For example, the boundary between a target tooth to be labeled and a tooth adjacent to the target tooth and the boundary between a target tooth to be labeled and gums may be specified by edge detection, which allows extraction of only the target tooth to be labeled.

(91) Further, generation of learning data set **116** is also applicable to generation of learning data set **516** held in server device **500**. For example, learning data set **116** may be applied to learning data set **516** held in server device **500**, or color classification data **118** may be applied to color classification data **518** held in server device **500**.

(92) [Generation of Learned Model]

(93) An example of generation of learned model **114a** will be hereinafter described. Learning data set **116** can be classified for each category based on the profile of subject **2** as a target to be scanned when learning data set **116** is generated. For example, the learning data sets generated from the

three-dimensional data including data of applicable subject **2** can be assigned to an age (minors, adults, elderly people), a gender (males, females), a race (Asians, Europeans, Africans), a height (less than 150 cm, 150 cm or more), a weight (less than 50 kg, 50 kg or more), and a place of residence (residing in Japan, residing in regions other than Japan). The layers of the respective categories can be set as appropriate. For example, ages can be stratified in greater detail for each prescribed age difference (in this case, for each 3 years of age), specifically for age 0 to age 3, age 4 to age 6, age 7 to age 9, and the like.

(94) Imaging support device **100** generates learned model **114a** by learning estimation model **114** using a plurality of learning data sets **116** that can be classified for each category. There may be an overlap among the pieces of learning data depending on how the categories are classified. In the case where there is an overlap among the pieces of learning data, only one piece of learning data has to be used for learning of estimation model **114**.

(95) In general, a tooth shape varies in feature depending on genetics or living environments such as an age, a gender, a race, a height, a weight, and a place of residence. For example, in general, permanent teeth of an adult are larger than primary teeth of a child, and also, permanent teeth are different in shape from primary teeth. In general, male teeth are larger than female teeth, and also, male teeth are different in shape from female teeth. In general, European teeth tend to be pointed at their tips so as to allow the Europeans to easily bite off hard meat and bread, whereas Japanese teeth tend to be smooth at their tips so as to allow the Japanese to easily mash soft rice and vegetables. Accordingly, the learning process is performed based on the profile data as in the present embodiment, to thereby allow generation of a learned model that allows identification of a type of a tooth in consideration of genetics, living environments or the like.

(96) It should be noted that generation of learned model **114a** is also applicable to generation of learned model **514a** held in server device **500**. For example, learning data set **116** may be applied to learning data set **516** held in server device **500**, or estimation model **114** may be applied to estimation model **514** held in server device **500**.

(97) [Learning Process of Identification Unit]

(98) The learning process performed by imaging support device **100** will be hereinafter described. The learning process is implemented by computing device **130** of imaging support device **100** executing OS **127** and learning program **121**. From learning data set **116**, imaging support device **100** selects learning data to be used for learning. Imaging support device **100** inputs, into estimation model **114**, the position information of the three-dimensional data included in the selected learning data and the profile data of subject **2** as a target to be scanned during generation of the learning data. At this time, the correct data labeled in the three-dimensional data is not input into imaging support device **100**. Based on the feature of a tooth corresponding to the three-dimensional data, imaging support device **100** performs an identification process of identifying a type of the tooth using estimation model **114**. In the identification process, imaging support device **100** identifies a type of the tooth using estimation model **114** based on the profile data in addition to the three-dimensional data.

(99) Imaging support device **100** updates parameter **1144** of estimation model **114** based on the error between the identification result about the type of the tooth identified by the identification process and the correct data corresponding to the learning data used in the learning process.

(100) For example, as a result of the identification based on the position information of a specific tooth, imaging support device **100** estimates color information corresponding to this specific tooth. Imaging support device **100** compares the color information (correct data) corresponding to the specific tooth included in the learning data with the color information estimated by imaging support device **100** itself. Then, when these pieces of color information match with each other, imaging support device **100** maintains parameter **1144** of estimation model **114**. In contrast, when these pieces of color information do not match with each other, imaging support device **100** updates parameter **1144** of estimation model **114** such that these pieces of color information match

with each other.

(101) Alternatively, as a result of the identification based on the position information of a specific tooth, imaging support device **100** estimates color information corresponding to this specific tooth, and specifies the type of the tooth and the number of the tooth (the correct data) that correspond to the color information based on color classification data **118**. Imaging support device **100** compares the type of the tooth and the number of the tooth (the correct data) that are assigned to the color information corresponding to the specific tooth included in the learning data with the type of the tooth and the number of the tooth that are estimated by imaging support device **100** itself. Then, when the types match with each other and the numbers match with each other, imaging support device **100** maintains parameter **1144** of estimation model **114**. When the types do not match with each other and the numbers do not match with each other, imaging support device **100** updates parameter **1144** of estimation model **114** such that the types match with each other and the numbers match with each other.

(102) In this way, imaging support device **100** can generate learned model **114a** by learning estimation model **114** based on the identification result about the type of the tooth that is obtained using the three-dimensional data obtained by the identification process, assuming that the tooth information (the color information, the tooth name, the tooth number, or the like) corresponding to the type of the tooth associated with the three-dimensional data included in the learning data is defined as correct data.

(103) Further, in the learning process, imaging support device **100** learns estimation model **114** in consideration of the profile data in addition to the learning data, so that it can generate learned model **114a** in consideration of the profile of subject **2**.

(104) [Learning Process of Server Device]

(105) The learning process performed by server device **500** will be hereinafter described. The learning process is implemented by computing device **530** of server device **500** executing OS **527** and learning program **521**.

(106) From the learning data set, server device **500** selects learning data to be used for learning. In this case, the learning data may be generated using the big data accumulated by server device **500** and stored therein. For example, server device **500** may generate, in advance, learning data using three-dimensional data included in the scan information acquired from imaging support device **100** in each of locals A to C and the dental laboratory, and then, perform the learning process using the generated learning data. Server device **500** does not necessarily have to automatically select the learning data, but may use the learning data selected by user **1** for the learning process.

(107) Server device **500** inputs, into estimation model **514**, the three-dimensional data (the position information) included in the selected learning data and the profile data of subject **2** as a target to be scanned during generation of the learning data. At this time, the correct data labeled in the three-dimensional data is not input into server device **500**. Based on the feature of a tooth corresponding to the three-dimensional data, server device **500** performs the identification process of identifying a type of this tooth by using estimation model **514**. In the identification process, based on the profile data in addition to the three-dimensional data, server device **500** identifies a type of the tooth using estimation model **514**.

(108) Then, server device **500** updates the parameter of estimation model **514** based on the error between the identification result about the type of the tooth identified by the identification process and the correct data corresponding to the learning data used for learning.

(109) For example, as a result of the identification based on the position information about a specific tooth, server device **500** estimates the color information corresponding to the specific tooth. Server device **500** compares the color information (the correct data) corresponding to the specific tooth included in the learning data set with the color information estimated by server device **500** itself. Then, when these pieces of color information match with each other, server device **500** maintains the parameter of estimation model **514**. In contrast, when these pieces of

color information do not match with each other, server device **500** updates the parameter of estimation model **514** such that these pieces of color information match with each other.

(110) Alternatively, as a result of the identification based on the position information of a specific tooth, server device **500** estimates the color information corresponding to the specific tooth, and then identifies a type of the tooth and the number of the tooth (correct data) that correspond to the color information based on color classification data **518**. Then, server device **500** compares the type of the tooth and the number of the tooth (correct data) that are assigned to the color information corresponding to the specific tooth included in the learning data set with the type of the tooth and the number of the tooth that are estimated by server device **500** itself. When the types match with each other and the numbers match with each other, server device **500** maintains the parameter of estimation model **514**. In contrast, when the types do not match with each other and the numbers do not match with each other, server device **500** updates the parameter of estimation model **514** such that the types match with each other and the numbers match with each other.

(111) When learning has been done based on all the pieces of learning data, server device **500** can store learned estimation model **514** as learned model **514a**. Then, server device **500** can transmit the generated learned model **514a** to imaging support device **100** in each local.

(112) In this way, server device **500** can generate learned model **514a** by learning estimation model **514** based on the identification result about the type of the tooth that is obtained using the three-dimensional data obtained by the identification process, assuming that the tooth information (the color information, the tooth name, the tooth number, or the like) corresponding to the type of the tooth associated with the three-dimensional data included in the learning data is defined as correct data.

(113) Further, in the learning process, server device **500** learns estimation model **514** in consideration of the profile data in addition to the learning data, so that it can generate learned model **514a** in consideration of the profile of subject **2**.

(114) Further, server device **500** uses the three-dimensional data included in the scan information acquired from imaging support device **100** in each of locals A to C and the dental laboratory as the learning data used in the learning process. Thus, server device **500** can perform the learning process based on more learning data than that in the learning process performed for each imaging support device **100**, and also, can generate learned model **514a** that allows identification of a type of a tooth with higher accuracy.

(115) [Support Process of Imaging Support Device **100**]

(116) The following describes the support process performed by imaging support device **100** based on a flowchart. FIG. **9** is a flowchart for illustrating an example of the support process performed by the imaging support device according to the present first embodiment. Each of steps shown in FIG. **9** is implemented by computing device **130** of imaging support device **100** executing OS **127** and specification program **120a**.

(117) As shown in FIG. **9**, imaging support device **100** determines whether a start condition for a support process I has been satisfied or not (**S40**). The start condition may be satisfied, for example, when the power supply of three-dimensional scanner **200** is started, or upon switching to a mode corresponding to support process I after the power supply of three-dimensional scanner **200** is started. Alternatively, the start condition may be satisfied when a start switch is operated after an icon corresponding to support process I (for example, an assist icon) is operated and turned into a blinking state. The start condition may be satisfied when a prescribed amount of three-dimensional data is acquired or may be satisfied at a timing at which the entire dental arch is imaged. The start condition may be any condition as long as it is satisfied when any action is performed on three-dimensional scanner **200**.

(118) When the start condition has not been satisfied (NO in **S40**), imaging support device **100** ends the process. On the other hand, when the start condition has been satisfied (YES in **S40**), imaging support device **100** determines whether the three-dimensional data has been acquired or

not (S41). For example, imaging support device **100** determines whether a sufficient amount of three-dimensional data for performing support process I has been input or not. When a sufficient amount of three-dimensional data has not been input (NO in S41), imaging support device **100** repeats the process in S41.

(119) On the other hand, when a sufficient amount of three-dimensional data has been input (YES in S41), imaging support device **100** performs a process of identifying a type of a tooth (S42). Imaging support device **100** identifies a type of a tooth from the input three-dimensional data based on learned model **114a**.

(120) The following further describes a process of identifying a type of a tooth that is performed by imaging support device **100**. FIG. **10** is a flowchart for illustrating an example of the process of identifying a type of a tooth that is performed by imaging support device **100** according to the present first embodiment. Each of steps shown in FIG. **10** is implemented by computing device **130** of imaging support device **100** executing OS **127** and identification program **120**. First, it is determined whether the profile data of subject **2** has been input or not by user **1** (S420). When the profile data has not been input (NO in S420), the three-dimensional data (the position information) is input into learned model **114a** (S421). On the other hand, when the profile data has been input (YES in S420), imaging support device **100** inputs the three-dimensional data (the position information) and the profile data into learned model **114a** (S422). The learned model used in this case is not limited to learned model **114a** generated by imaging support device **100**, but may be learned model **514a** generated by server device **500**.

(121) After S421 and S422, based on the feature of a tooth corresponding to the three-dimensional data, imaging support device **100** performs an identification process of identifying a type of this tooth using learned model **114a** (S423). In this case, when the profile data has been input into learned model **114a** in S422, imaging support device **100** identifies a type of the tooth using learned model **114a** based on the profile data in addition to the three-dimensional data. In this case, the type of the tooth can be identified more accurately than in the case where the type of the tooth is identified using learned model **114a** based only on the three-dimensional data.

(122) Referring back to FIG. **9**, after performing the process of identifying a type of a tooth in S42, imaging support device **100** determines whether there is insufficient three-dimensional data or not in the acquired three-dimensional data (S43). For example, imaging support device **100** determines whether or not there is a portion where the acquired three-dimensional data does not exceed a predetermined amount of data. When there is insufficient three-dimensional data (YES in S43), based on the type of the tooth identified in S42, imaging support device **100** specifies a type of a tooth in the portion where three-dimensional data is insufficient, and outputs the specification result to display **300**, speaker **400**, and the like (S44), and then, ends the present process. When there is not insufficient three-dimensional data (NO in S43), imaging support device **100** ends the present process.

(123) In this way, imaging support device **100** specifies the type of the tooth for which the amount of data is insufficient in the acquired three-dimensional data, and thereby can inform user **1** about the type of the tooth to be re-scanned (re-measured). Based on the feature of the tooth corresponding to the input three-dimensional data, imaging support device **100** identifies a type of this tooth using learned model **114a**. Thereby, imaging support device **100** can identify a type of a tooth more accurately than in the case where a type of a tooth is identified depending on the user's knowledge, and thus, can accurately specify the type of the tooth to be re-scanned and inform user **1** about the specified type of the tooth.

(124) Further, in the identification process, imaging support device **100** identifies a type of a tooth in consideration of the profile data in addition to the input three-dimensional data, thereby allowing more accurate identification of a type of a tooth.

(125) The above description is predicated on that, at the timing at which the entire dental arch is imaged, imaging support device **100** specifies the type of the tooth in a sufficient portion not

exceeding a predetermined amount of data (not satisfying a prescribed criterion) in the acquired three-dimensional data, and then, outputs the specification result to display **300**. However, without being limited to the above, at the timing of imaging a prescribed range in which an image of about $\frac{1}{2}$, about $\frac{1}{3}$, about $\frac{2}{3}$, about $\frac{1}{5}$, about $\frac{2}{5}$, about $\frac{3}{5}$, or about $\frac{4}{5}$ of the dental arch can be formed, imaging support device **100** may specify the type of the tooth in the sufficient portion and then output the specification result to display **300**. Of course, imaging support device **100** may output the information (for example, an insufficient portion) about the type of the tooth specified by specification unit **1150** to the outside at the timing at which a prescribed number of teeth are imaged or at the timing of prescribed time intervals.

(126) Support process I has been described as a process of specifying the type of the tooth in an insufficient portion in which the information obtained from the three-dimensional data does not exceed a predetermined amount of data, and then, outputting the specification result as support information. However, without being limited to the above, imaging support device **100** can perform another support process of specifying the type of the tooth and providing user **1** with the specification result as support information. For example, as another example, the following describes a support process II of specifying the type of the tooth imaged before imaging is stopped, and providing user **1** with the specified information as support information when imaging is started within a prescribed time period. FIG. **11** is a flowchart for illustrating another example of the support process performed by the imaging support device according to the present first embodiment. Each of steps shown in FIG. **11** is implemented by computing device **130** of imaging support device **100** executing OS **127** and specification program **120a**.

(127) As shown in FIG. **11**, imaging support device **100** determines whether a start condition for a support process II has been satisfied or not (**S40a**). The start condition may be satisfied, for example, when the power supply of three-dimensional scanner **200** is started, or upon switching to a mode corresponding to support process II after the power supply of three-dimensional scanner **200** is started. Alternatively, the start condition may be satisfied when a start switch is operated after an icon corresponding to support process II (for example, an assist icon) is operated and turned into a blinking state. The start condition may be any condition as long as it is satisfied when any action is performed on three-dimensional scanner **200**.

(128) When the start condition has not been satisfied (NO in **S40a**), imaging support device **100** ends the process. On the other hand, when the start condition has been satisfied (YES in **S40a**), imaging support device **100** acquires three-dimensional data (**S41a**). When a sufficient amount of three-dimensional data has been input, imaging support device **100** performs a process of identifying a type of a tooth (**S42**). In the process shown in FIG. **10**, imaging support device **100** identifies a type of a tooth from the input three-dimensional data based on learned model **114a**.

(129) Imaging support device **100** determines whether scanning of teeth by three-dimensional scanner **200** is stopped or not (**S43a**). In this case, the timing at which it is determined that scanning is stopped may be the timing at which imaging support device **100** receives an imaging stop signal, or may be the timing at which input unit **1102** does not receive a tooth image for a prescribed time period or more.

(130) When it is determined that scanning is stopped (YES in **S43a**), imaging support device **100** determines whether or not scanning of teeth by three-dimensional scanner **200** has been started within a prescribed time period (for example, within 3 minutes after scanning is stopped) (**S44a**). When scanning has been started within the prescribed time period (YES in **S44a**), then, based on the type of the tooth identified in **S42**, imaging support device **100** specifies the type of the tooth scanned before scanning is stopped, and then, notifies user **1** about the specification result (**S45a**). For example, imaging support device **100** outputs the specification result to display **300**, speaker **400**, and the like to thereby notify user **1** about the specification result. Accordingly, user **1** can start scanning of teeth by three-dimensional scanner **200** from an appropriate position based on the type of the tooth that has been scanned before scanning is stopped. The specification result of which

user **1** is notified may include information about, the type of one tooth scanned before scanning is stopped, information about the type of the tooth adjacent to this one tooth, and both pieces of information.

(131) Imaging support device **100** gives a notification about the type of the tooth scanned before scanning is stopped, and then returns the process to **S41a**. When scanning is not started within a prescribed time period (NO in **S44a**), imaging support device **100** outputs, to the outside, the type of the tooth having been scanned before scanning is stopped (**S46a**), and then, ends the present process.

(132) When it is determined that scanning is not stopped (NO in **S43a**), imaging support device **100** determines whether scanning of teeth by three-dimensional scanner **200** has ended or not (**S47a**). When scanning of teeth has not ended (NO in **S47a**), imaging support device **100** returns the process to **S41a**. When scanning of teeth ended (YES in **S47a**), imaging support device **100** ends the present process.

(133) As still another example, the following describes a support process III in which, when a plurality of three-dimensional images (three-dimensional data) are joined together, a type of a tooth is specified and provided to user **1** as support information. FIG. **12** is a flowchart for illustrating still another example of the support process performed by the imaging support device according to the present first embodiment. Each of steps shown in FIG. **12** is implemented by computing device **130** of imaging support device **100** executing OS **127** and specification program **120a**.

(134) As shown in FIG. **12**, imaging support device **100** determines whether a start condition for a support process III has been satisfied or not (**S40b**). The start condition may be satisfied, for example, when the power supply of three-dimensional scanner **200** is started, or upon switching to a mode corresponding to support process III after the power supply of three-dimensional scanner **200** is started. Alternatively, the start condition may be satisfied when a start switch is operated after an icon corresponding to support process III (for example, an assist icon) is operated and turned into a blinking state. The start condition may be any condition as long as it is satisfied when any action is performed on three-dimensional scanner **200**.

(135) When the start condition has not been satisfied (NO in **S40b**), imaging support device **100** ends the present process. On the other hand, when the start condition has been satisfied (YES in **S40b**), imaging support device **100** acquires a plurality of pieces of three-dimensional data of a plurality of portions (**S41b**). For example, when scanning a dental arch, imaging support device **100** divides the dental arch into thirds, and scans the divided three portions to acquire three pieces of three-dimensional data. When the plurality of pieces of three-dimensional data of the plurality of portions are input, imaging support device **100** performs a process of identifying a type of a tooth for each three-dimensional data (**S42**). In the process shown in FIG. **10**, imaging support device **100** identifies the type of the tooth from the plurality of pieces of input three-dimensional data of the respective portions based on learned model **114a**.

(136) Imaging support device **100** determines whether there is an overlapping type of a tooth in one portion and another portion in the plurality of pieces of three-dimensional data of the respective portions (**S43b**). When there is an overlapping type of a tooth in one portion and another portion (YES in **S43b**), imaging support device **100** performs a process of joining the three-dimensional data of one portion and the three-dimensional data of another portion based on the overlapping type of the tooth (**S44b**). For example, when imaging support device **100** acquires three-dimensional data of: a portion (one portion) obtained by scanning an area from the third molar to the first premolar on the right side in the upper jaw; and a portion (another portion) obtained by scanning an area from the first premolar to the central incisor on the right side in the upper jaw, imaging support device **100** determines that the first premolar of one portion overlaps the first premolar of another portion. Since there is an overlapping type of a tooth, imaging support device **100** joins the three-dimensional data of one portion and the three-dimensional data of another portion with respect to the first premolar to thereby form one piece of three-dimensional data.

(137) Imaging support device **100** determines whether or not there is an unjoined portion in the plurality of pieces of three-dimensional data of the respective portions (**S45b**). When there is an unjoined portion (YES in **S45b**), imaging support device **100** returns the process to **S43b**. When there is not an unjoined portion (NO in **S45b**) or there is not an overlapping type of a tooth in one portion and another portion (NO in **S43b**), imaging support device **100** ends the present process.

(138) Even when imaging support device **100** scans the dental arch separately several times and acquires a plurality of pieces of three-dimensional data of a plurality of portions, imaging support device **100** can still easily join the plurality of pieces of three-dimensional data into one piece of three-dimensional data by performing the above-mentioned support process III. If user **1** joins a plurality of pieces of three-dimensional data of a plurality of portions without performing the above-mentioned support process III, user **1** needs to perform an operation to visually determine the type of the tooth from each of the pieces of three-dimensional data and join these pieces of three-dimensional data together, with the result that the operation becomes complicated.

(139) The above-mentioned support processes I to III can be separately performed in imaging support device **100**, but may be performed in various combinations. For example, imaging support device **100** may perform support processes I and II in combination to conduct scanning to thereby specify a type of a tooth for which the amount of data is insufficient. Also, when scanning is stopped, imaging support device **100** may specify a type of a tooth before stopping of scanning. In this case, for example, when scanning is started within a prescribed time period after scanning is stopped, imaging support device **100** gives a notification preferentially about the type of the tooth for which the amount of data is insufficient. Then, when re-scanning is performed for the type of the tooth for which the amount of data is insufficient, imaging support device **100** gives a notification about the type of the tooth that has been scanned before scanning is stopped. Of course, imaging support device **100** may reverse the order of notification.

(140) As described above, imaging support device **100** according to the present first embodiment is an imaging support device that supports imaging of teeth inside an oral cavity. Imaging support device **100** includes an input unit **1102**, an identification unit **1130**, a specification unit **1150**, and an output unit **1103**. Input unit **1102** receives a tooth image obtained by imaging the teeth inside the oral cavity. Identification unit **1130** identifies a type of a tooth based on the tooth image received by input unit **1102**. Based on the type of the tooth identified by identification unit **1130**, specification unit **1150** specifies a type of a tooth as a target for imaging support. Output unit **1103** outputs information about the type of the tooth specified by specification unit **1150** to an outside at a prescribed timing.

(141) Accordingly, imaging support device **100** specifies a type of a tooth as a target for imaging support based on the type of the tooth identified by identification unit **1130**, and thereby can output the information for imaging support to a user **1** so as to allow user **1** to easily recognize which tooth inside the oral cavity corresponds to the tooth as a target for imaging support.

(142) Specification unit **1150** specifies a type of a tooth that needs to be imaged for user **1**, and output unit **1103** outputs information about the type of the tooth specified by specification unit **1150** to the outside before user **1** performs imaging.

(143) Accordingly, imaging support device **100** allows user **1** to easily recognize a tooth to be imaged next.

(144) As a type of a tooth that needs to be imaged for user **1**, specification unit **1150** specifies a type of a tooth for which information obtained from the tooth image fails to satisfy a prescribed criterion. For example, when three-dimensional scanner **200** scans teeth, the type of the tooth in a portion not exceeding a predetermined amount of data in the three-dimensional data obtained from the tooth image is specified based on the type of the tooth identified by identification unit **1130**.

(145) Accordingly, imaging support device **100** allows user **1** to recognize the type of the tooth for which the amount of data is insufficient, and thereby can urge user **1** to perform imaging again.

(146) As a type of a tooth that needs to be imaged for user **1**, specification unit **1150** specifies a

type of a tooth that is imaged at a timing at which imaging is stopped, and output unit **1130** outputs, to the outside, at least one piece of information of: the type of the tooth specified by specification unit **1150** before a timing at which user **1** starts imaging; and a type of a tooth adjacent to the specified type of the tooth.

(147) Accordingly, when imaging support device **100** starts imaging within a prescribed time period after imaging is stopped, imaging support device **100** allows user **1** to recognize the type of the first tooth from which imaging is started, thereby allowing efficient imaging to be performed.

(148) When a new tooth image is not input into input unit **1102** for a prescribed time period from the timing at which imaging is stopped to the timing at which imaging is started, output unit **1103** may output information about the specified type of the tooth to the outside.

(149) Accordingly, when imaging is not started within a prescribed time period after it is determined that imaging is stopped, user **1** is highly likely to perform an imaging operation again or shift to imaging of another patient. Thus, imaging support device **100** outputs, to the outside, the information about the type of the tooth specified at the timing at which imaging is stopped, and thereby can prevent the function of support process II from being performed.

(150) Output unit **1103** outputs information about the type of the tooth specified by specification unit **1150** to the outside at a timing at which the dental arch in a prescribed range is imaged. The prescribed range is a range in which an image of about $\frac{1}{2}$, about $\frac{1}{3}$, about $\frac{2}{3}$, about $\frac{1}{5}$, about $\frac{2}{5}$, about $\frac{3}{5}$, or about $\frac{4}{5}$ of the dental arch can be formed. Further, output unit **1103** outputs information about the type of the tooth specified by the specification unit to the outside at a timing at which a prescribed number of teeth are imaged.

(151) Accordingly, imaging support device **100** notifies user **1** about the specified type of the tooth (for example, the type of the tooth for which the amount of data is insufficient) at the timing at which a prescribed range of the dental arch is imaged or at the timing at which a prescribed number of teeth are imaged, thereby reducing complicatedness.

(152) Input unit **1102** receives three-dimensional data corresponding to a three-dimensional image of the dental arch from three-dimensional scanner **200**, and specification unit **1150** specifies a type of a tooth for which information is insufficient in the three-dimensional data input from input unit **1102**.

(153) Accordingly, imaging support device **100** allows user **1** to easily recognize the type of the tooth for which the amount of data is insufficient, and thereby can provide user **1** accurately with the information about the type of the tooth to be measured again.

(154) Specification unit **1150** specifies an overlapping type of a tooth among the tooth images as a type of a tooth used for joining.

(155) This allows imaging support device **100** to easily join a plurality of tooth images together.

(156) Based on a feature of a tooth corresponding to the tooth image input from input unit **1102**, identification unit **1130** identifies a type of the tooth using an estimation model **114** including a neural network. Estimation model **114** is learned based on: tooth information corresponding to a type of a tooth associated with the tooth image; and an identification result of the type of the tooth that is obtained using the tooth image.

(157) Accordingly, user **1** inputs three-dimensional data including data of the tooth into estimation model **114** (learned model **114a**) including neural network **1142**, and thus, can identify a type of the tooth, thereby allowing more accurate identification of a type of a tooth than in the case where a type of a tooth is identified depending on the user's knowledge.

(158) Input unit **1102** receives a tooth image including a plurality of teeth, and identification unit **1130** identifies a type of each of the teeth based on a feature of each of the teeth corresponding to the tooth image.

(159) Accordingly, user **1** inputs a tooth image including a plurality of teeth into estimation model **114** (learned model **114a**) including neural network **1142**, and thereby, can identify a type of each of the teeth. Thus, a type of a tooth can be identified more accurately and smoothly than in the case

where types of teeth are identified one by one depending on the user's knowledge. Further, user **1** can extract a feature of a tooth by estimation model **114** including neural network **1142** also in consideration of the relation with the shapes of the adjacent teeth, thereby allowing accurate identification of a type of a tooth.

(160) The tooth image includes three-dimensional position information at each of points of a tooth.

(161) Accordingly, user **1** inputs the three-dimensional position information at each of a plurality of points forming a tooth corresponding to the three-dimensional data into estimation model **114**

(learned model **114a**) including neural network **1142**, and thereby, can identify a type of the tooth.

(162) Estimation model **114** is learned based on attribute information related to a subject having teeth, in addition to the tooth information and the identification result obtained by identification unit **1130**.

(163) Accordingly, user **1** can implement learning of estimation model **114** based on the attribute information related to subject **2** in addition to the learning data, thereby allowing generation of a learned model in consideration of the attribute information about subject **2**.

(164) The attribute information includes at least one piece of information of an age, a gender, a race, a height, a weight, and a place of residence about the subject.

(165) Accordingly, user **1** can implement learning of estimation model **114** based on at least one of an age, a gender, a race, a height, a weight, and a place of residence about the subject in addition to the learning data, thereby allowing generation of learned model **114a** in consideration of the profile of subject **2**.

(166) A scanner system **10** that acquires shape information of a tooth includes: a three-dimensional scanner **200** that images teeth using a three-dimensional camera; and an imaging support device **100** that identifies a type of a tooth based on a tooth image in three dimensions that is acquired by three-dimensional scanner **200** and gives a notification about the identified type of the tooth.

Imaging support device **100** includes: an input unit **1102** that receives a tooth image obtained by imaging teeth inside an oral cavity; an identification unit **1130** that identifies a type of a tooth based on the tooth image received by input unit **1102**; a specification unit **1150** that, based on the type of the tooth identified by identification unit **1130**, specifies a type of a tooth as a target to be imaged; and an output unit **1103** that outputs information about the type of the tooth specified by specification unit **1150** to an outside at a prescribed timing.

(167) Accordingly, scanner system **10** specifies a type of a tooth as a target for imaging support based on the type of the tooth identified by identification unit **1130**, and thereby can output the information for imaging support to user **1** so as to allow user **1** to easily recognize which tooth inside the oral cavity corresponds to the tooth as a target for imaging support.

(168) An imaging support method of supporting imaging of teeth inside an oral cavity includes: receiving a tooth image obtained by imaging the teeth inside the oral cavity; identifying a type of a tooth based on the received tooth image; based on the identified type of the tooth, specifying a type of a tooth as a target to be imaged; and outputting information about the specified type of the tooth to an outside at a prescribed timing.

(169) Thus, according to the imaging support method, a type of a tooth is specified as a target for imaging support based on the identified type of the tooth, and thereby, the information for imaging support can be output to user **1** so as to allow user **1** to easily recognize which tooth inside the oral cavity corresponds to the tooth as a target for imaging support.

Second Embodiment

(170) In the above description, imaging support device **100** according to the first embodiment is configured to perform a process of automatically identifying a type of a tooth with the help of AI based on three-dimensional data acquired by three-dimensional scanner **200** to specify a type of a tooth as a target for imaging support. However, without being limited to the above, imaging support device **100** may be configured to perform a process of automatically identifying a type of a tooth with no help of AI based on the three-dimensional data acquired by three-dimensional scanner **200**

and specifying a type of a tooth as a target for imaging support. For example, it is conceivable to perform a process of automatically identifying a type of a tooth by pattern matching of the three-dimensional image acquired by three-dimensional scanner **200** and specifying a type of a tooth as a target for imaging support.

(171) The following describes a process of identifying a type of a tooth performed by an imaging support device according to the present second embodiment. FIG. **13** is a flowchart for illustrating an example of a process of identifying a type of a tooth performed by the imaging support device according to the present second embodiment. The imaging support device according to the present second embodiment has the same configuration as that of imaging support device **100** described with reference to FIGS. **3** and **5** except that estimation model **114** is not used, and thus, the detailed description thereof will not be repeated. Each of steps shown in FIG. **13** is implemented by computing device **130** of the imaging support device executing OS **127** and identification program **120**.

(172) First, the imaging support device reads pattern data stored in advance in a storage or the like (**S420a**). For example, an image of a tooth to be identified as shown in FIG. **8** is stored in the storage, and the imaging support device reads an image used as pattern data for pattern matching from the storage.

(173) The imaging support device compares the three-dimensional image acquired by three-dimensional scanner **200** with the pattern data read from the storage, to determine whether or not there is a matching shape (**S421a**). For example, the imaging support device calculates a normalized correlation between the three-dimensional image acquired by three-dimensional scanner **200** and the pattern data read from the storage to thereby determine whether the shapes match with each other.

(174) When there is no matching shape (NO in **S421a**), the imaging support device determines whether all the pieces of pattern data stored in advance in the storage or the like have been read or not (**S422a**). When all the pieces of pattern data have not been read (NO in **S422a**), the imaging support device returns the process to **S420a** and reads another pattern data (**S420a**).

(175) When there is a matching shape (YES in **S421a**), the imaging support device identifies a type of a tooth of the three-dimensional image acquired from the pattern data including a matching shape (**S423a**). For example, when the three-dimensional image acquired by three-dimensional scanner **200** matches in shape with the pattern data of the third molar on the right side in the upper jaw, the imaging support device identifies the type of the tooth in the acquired three-dimensional image as the third molar on the right side in the upper jaw.

(176) When all the pieces of pattern data have been read (YES in **S422a**), and the type of the tooth is identified from the pattern data including a matching shape (**S423a**), then, the imaging support device ends the present process. The process of identifying a type of a tooth shown in FIG. **13** can be applicable to the process of identifying a type of a tooth (**S42**) included in support process I shown in FIG. **9**, support process II shown in FIG. **11**, and support process III shown in FIG. **12**.

(177) As described above, the imaging support device according to the present second embodiment is an imaging support device that supports imaging of teeth inside an oral cavity. The imaging support device includes an input unit, an identification unit, a specification unit, and an output unit. The input unit receives a tooth image obtained by imaging the teeth inside the oral cavity. The identification unit identifies a type of a tooth by pattern matching with no help of AI, for example, based on the tooth image received by the input unit. The specification unit specifies a type of a tooth as a target for imaging support based on the type of the tooth identified by the identification unit. The output unit outputs information about the type of the tooth specified by the specification unit to an outside at a prescribed timing.

(178) Accordingly, the imaging support device specifies a type of a tooth as a target for imaging support based on the type of the tooth identified by the identification unit, and thereby can output the information for imaging support to user **1** so as to allow user **1** to easily recognize which tooth

inside the oral cavity corresponds to the tooth as a target for imaging support.

(179) (Modifications)

(180) (a) In the description in the first and second embodiments, the imaging support device supports a three-dimensional scanner (an intraoral scanner) for acquiring a three-dimensional shape of a tooth inside the oral cavity. However, the imaging device supported by the imaging support device is not limited to a three-dimensional scanner for an oral cavity, but can be applicable to an imaging device having a similar configuration, for example, can be applicable also to a three-dimensional scanner capable of imaging the inside of a human ear other than the inside of the oral cavity to acquire a three-dimensional shape inside the outer ear, and also, can be applicable to a desktop scanner capable of acquiring a three-dimensional shape of a jaw and dentition model.

(181) It should be noted that the three-dimensional scanners according to the present first and second embodiments each may be configured to acquire a three-dimensional shape using a technique such as a confocal method, a triangulation method, a white light interferometry method, a stereo method, a photogrammetry method, a simultaneous localization and mapping (SLAM) method, an optical coherence tomography (OCT) method, and the like, in addition to the configuration of acquiring a three-dimensional shape using a technique of a focus method.

(182) (b) In the first and second embodiments, the imaging device supported by the imaging support device includes, for example, an intraoral camera, an optical coherence tomography (OCT), an ultraviolet/infrared/terahertz imaging device, a fluorescent imaging device, and the like.

(183) (c) The first and second embodiments have been described with regard to a scanner system including an imaging support device and a three-dimensional scanner connected to each other. However, the imaging support device is not limited to the above, but may have a configuration in which an imaging support device is mounted on a three-dimensional scanner, or a configuration in which an imaging support device is connected to a three-dimensional scanner through a network. Further, the imaging support device may be provided in the form of a cloud service in which a plurality of three-dimensional scanners are connected through a network.

(184) (d) In the description in the present first and second embodiments, the imaging support device specifies a type of a tooth for which the amount of data is insufficient in the acquired three-dimensional data, and informs a user about the type of the tooth to be re-scanned (re-measured) as support information. Further, for example, when the user erroneously scans the buccal side in place of the tongue side during re-scanning after a notification given to the user about the type of the tooth for which the amount of data is insufficient, the imaging support device may further specify the erroneous scanning and give a notification again. Specifically, based on the value from a motion sensor provided in the three-dimensional scanner, the imaging support device determines whether or not the three-dimensional scanner is disposed at the inclination different from the intended inclination defined in the content included in the notification. In the case of an error, the imaging support device gives a notification again.

(185) (e) In the description in the present first and second embodiments, the imaging support device specifies a type of a tooth for which the amount of data is insufficient in the acquired three-dimensional data, to thereby inform the user about the type of the tooth to be re-scanned (re-measured) as support information. The number of teeth for which the amount of data is insufficient is not limited to one, but may be more than one. When there are a plurality of teeth for which the amount of data is insufficient, the imaging support device gives a notification about the types of teeth, for example, in descending order of the degree of insufficiency of the amount of data. In this way, by giving a notification in descending order of the degree of insufficiency of the amount of data, entirely highly valuable three-dimensional data can be achieved.

(186) (f) In the description in the present first and second embodiments, the imaging support device specifies a type of a tooth for which the amount of data is insufficient in the acquired three-dimensional data, and then notifies the user about the specified type of the tooth. However, without being limited thereto, it is conceivable that the imaging support device may notify the user about

overlapping data when the user uses the three-dimensional scanner to try to scan a tooth for which data overlaps in the acquired three-dimensional data. For example, when the user wastefully scans a, canine with the three-dimensional scanner even though the three-dimensional data of this canine is sufficiently acquired, the imaging support device gives a notification such as “scanning of canine is not required (is sufficient)”. Thus, the imaging support device can prevent unnecessary data from being stored in the memory of the three-dimensional scanner, and thereby, the storage capacity can be ensured and calculation delay can be avoided.

(187) It should be understood that the embodiments disclosed herein are illustrative and non-restrictive in every respect. The scope of the present invention is defined by the terms of the claims, rather than the description above, and is intended to include any modifications within the meaning and scope equivalent to the terms of the claims.

REFERENCE SIGNS LIST

(188) **1** user, **2** subject, **5** network, **10** scanner system, **100** imaging support device, **102** scanner interface **103**, **503** display interface, **104** speaker interface, **105**, **505** peripheral interface, **106**, **506** network controller, **107**, **507** medium reading device, **108** PC display, **109**, **509** memory, **110**, **510** storage, **112**, **512** scan information, **114**, **514** estimation model, **114a**, **514a** learned model, **116**, **516** learning data set, **118**, **518** color classification data, **119**, **519** profile data, **120** identification program, **120a** specification program, **121**, **521** learning program, **122**, **522** three-dimensional data, **124**, **524** identification result, **127**, **527** OS, **130**, **530** computing device, **200** three-dimensional scanner, **300**, **350** display, **400** speaker, **500** server device, **550** removable disk **601**, **651** keyboard, **602**, **652** mouse, **1102** input unit, **1103** output unit, **1119** profile acquisition unit, **1130** identification unit, **1142** neural network, **1144** parameter, **1150** specification unit.

Claims

1. An imaging support device that supports imaging of teeth inside an oral cavity, the imaging support device comprising: an input unit that receives three-dimensional data including data of the teeth obtained by imaging the teeth inside the oral cavity; an identification unit that identifies a type of a tooth based on the three-dimensional data; a specification unit that, based on the type of the tooth identified by the identification unit, specifies a type of a tooth corresponding to a portion of the three-dimensional data that does not exceed a predetermined amount of data as a target for imaging support and predicts a type of a tooth to be imaged next; and an output unit that outputs, as imaging support, information about the type of the tooth specified by specification unit and the type of the tooth to be imaged next.
2. The imaging support device according to claim 1, wherein the specification unit specifies a type of a tooth that needs to be imaged for a user, and the output unit outputs information about the type of the tooth specified by the specification unit before the user performs imaging.
3. The imaging support device according to claim 2, wherein, as a type of a tooth that needs to be imaged for the user, the specification unit specifies a type of a tooth for which information obtained from the tooth image fails to satisfy a prescribed criterion.
4. The imaging support device according to claim 1, wherein as a type of a tooth that needs to be imaged for a user, the specification unit specifies a type of a tooth that is imaged at a timing at which imaging is stopped, and the output unit outputs at least one piece of information of: the type of the tooth specified by the specification unit before a timing at which the user starts imaging; and a type of a tooth adjacent to the specified type of the tooth.
5. The imaging support device according to claim 4, wherein the timing at which imaging is stopped is a timing at which the imaging support device receives an imaging stop signal.
6. The imaging support device according to claim 4, wherein, when a new tooth image is not input to the input unit during a prescribed time period from the timing at which imaging is stopped to the timing at which imaging is started, the output unit outputs information about the specified type of

the tooth.

7. The imaging support device according to claim 1, wherein the imaging support device supports a scanning device that forms an image of a dental arch by joining a plurality of tooth images obtained by scanning and imaging an inside of the oral cavity.

8. The imaging support device according to claim 7, wherein the output unit outputs information about the type of the tooth specified by the specification unit at a timing at which a prescribed number of teeth are imaged.

9. The imaging support device according to claim 7, wherein the input unit receives three-dimensional data corresponding to a three-dimensional image of the dental arch from the scanning device, and the specification unit specifies a type of a tooth for which information is insufficient in the three-dimensional data input from the input unit.

10. The imaging support device according to claim 7, wherein the specification unit specifies an overlapping type of a tooth among the tooth images as a type of a tooth used for joining.

11. The imaging support device according to claim 1, wherein based on a feature of a tooth corresponding to the tooth image input from the input unit, the identification unit identifies a type of the tooth using an estimation model including a neural network, and the estimation model is learned based on: tooth information corresponding to a type of a tooth associated with the tooth image; and an identification result of the type of the tooth that is obtained using the tooth image.

12. The imaging support device according to claim 11, wherein the input unit receives a tooth image including a plurality of teeth, and the identification unit identifies a type of each of the teeth based on a feature of each of the teeth corresponding to the tooth image.

13. The imaging support device according to claim 11, wherein the tooth image includes three-dimensional position information at each of points of a tooth.

14. The imaging support device according to claim 11, wherein the estimation model is learned based on attribute information related to a subject having teeth in addition to the tooth information and the identification result obtained by the identification unit.

15. The imaging support device according to claim 14, wherein the attribute information includes at least one piece of information of an age, a gender, a race, a height, a weight, and a place of residence about the subject.

16. A scanner system for imaging teeth inside an oral cavity, the scanner system comprising: a three-dimensional scanner that images the teeth using a three-dimensional camera and acquires three-dimensional data including data of the teeth; and an imaging support device that identifies a type of a tooth based on the three-dimensional data, and gives a notification about the identified type of the tooth, wherein the imaging support device includes an input unit that receives the three-dimensional data, an identification unit that identifies a type of a tooth based on the three-dimensional data, a specification unit that, based on the type of the tooth identified by the identification unit, specifies a type of a tooth corresponding to a portion of the three-dimensional data that does not exceed a predetermined amount of data as a target for imaging support and predicts a type of a tooth to be imaged next, and an output unit that outputs, as imaging support, information about the type of the tooth specified by specification unit and the type of the tooth to be imaged next.

17. An imaging support method of supporting imaging of teeth inside an oral cavity, the method comprising: receiving three-dimensional data including data of the teeth obtained by imaging the teeth inside the oral cavity; identifying a type of a tooth based on the three-dimensional data; based on the identified type of the tooth, specifying a type of a tooth corresponding to a portion of the three-dimensional data that does not exceed a predetermined amount of data as a target for imaging support and predicting a type of a tooth to be imaged next; and outputting, as imaging support, information about the type of the tooth specified by specification unit and the type of the tooth to be imaged next.
