

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397106
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Baid; Rishi et al.

Safety mechanism for a huber needle assembly

Abstract

The present invention relates to a needle having safety mechanism for a huber needle assembly in which the safety mechanism comprises a needle hub, a base, a huber needle slidably disposed through the needle hub, a wing holder having two wings at the opposite end of the wing holder, a connector which connects the needle hub and the base for protecting the tip of the huber needle.

Inventors:	Baid; Rishi (New Delhi, IN), Singh; Manjit (Faridabad-Haryana, IN)
Applicant:	POLY MEDICURE LIMITED (Faridabad-Haryana, IN)
Family ID:	1000008779548
Assignee:	POLY MEDICURE LIMITED (Faridabad-Haryana, IN)
Appl. No.:	17/419007
Filed (or PCT Filed):	December 27, 2019
PCT No.:	PCT/IB2019/061389
PCT Pub. No.:	WO2020/136610
PCT Pub. Date:	July 02, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220062539 A1	Mar. 03, 2022

Foreign Application Priority Data

IN	201811049316	Dec. 27, 2018
----	--------------	---------------

Publication Classification

Int. Cl.: A61M5/158 (20060101)

U.S. Cl.:

CPC **A61M5/158** (20130101); A61M2005/1581 (20130101); A61M2005/1587 (20130101);
A61M2205/3334 (20130101)

Field of Classification Search

CPC: A61M (5/158); A61M (2005/1581); A61M (2005/1587); A61M (2205/3334); A61M
(2005/1585); A61M (2205/195); A61M (5/1626); A61M (39/0208); A61M (2005/1586)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5858001	12/1998	Tsals et al.	N/A	N/A
2003/0069546	12/2002	Sandstrom	604/263	A61M 5/158
2007/0149920	12/2006	Michels	604/93.01	A61M 5/158
2013/0085449	12/2012	Saulenas	604/164.01	A61M 5/158

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2007/079115	12/2006	WO	N/A
2013/049568	12/2012	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion issued by the European Patent Office for corresponding application PCT/IB2019/061389 dated Mar. 31, 2020. cited by applicant
First Examination Report issued by the Indian Patent Office for Indian Patent Application No. 201811049316, dated Feb. 3, 2021. cited by applicant

Primary Examiner: Mehta; Bhisma

Assistant Examiner: Alvarado, Jr.; Nelson Louis

Attorney, Agent or Firm: Bradley Arant Boult Cummings LLP

Background/Summary

FIELD OF THE INVENTION

(1) The invention generally relates to needle assemblies having safety mechanism for subcutaneous injections. More particularly, the invention relates to huber needle assemblies having a safety mechanism.

BACKGROUND OF THE INVENTION

(2) A Huber needle assembly is generally known in the art. Conventional Huber needle assemblies are widely used in hospitals and are often used in conjunction with implanted ports mostly used to treat hematology and oncology patients. Such Huber needle assemblies provide non-coring Huber

needles that are used to administer chemotherapy, IV fluids, medications, total parenteral nutrition, or to transfuse blood products through the implanted ports. The implanted port contains a self-sealing septum that seals around the non-coring needle, holds the needle in place, and allows for multiple accesses by a Huber needle.

(3) In the area of subcutaneous medication device access (port), where Huber needle assembly is used, an existing safety device offer a margin of protection from accidental needle sticks when removing the needle, or “sharp,” from the port. One danger from de-accessing a subcutaneous port is the result of how the port itself is constructed. The port is made up of metal or plastic material with a pierceable area, often made of a silicone compound, through which access is made by a Huber needle to the vascular system for the purpose of infusing medication into the body. The port is implanted within a cavity formed in the patient, such as in the chest area, and sutured to underlying tissue. From time to time, it is desirable to refill the port via the septum and/or provide an external source of fluid, e.g., IV access. One type of device used to refill an implanted port is generally known as a Huber needle.

(4) The Huber needle is specially designed to reduce the possibility of mechanically damaging and/or removing a portion of the pierceable area as it is punctured, and which is referred to as “coring.” This coring limits the number of times a port can be accessed. To combat this damage and extend the useful life of the port, the silicone compound is inserted under pressure into the device. It is this pressure that is the cause of the danger to the medical practitioner removing the needle used to cannulate the port.

(5) Conventional Huber needle assemblies are designed for safety of patients. They do, however, present considerable risks to the medical practitioners using them. A conventional Huber needle assembly requires two hands to extract its Huber needle from an implanted port. One hand is used to stabilize the implanted port, while the other hand is used to withdraw the needle. The force required to withdraw the needle from the self-sealing septum of the implanted port can cause the needle to rebound and stick the user. This may result in transfer of a blood-borne pathogen to the user. Further, it may expose the user to hazardous drugs.

(6) Although several alternate Huber needle assemblies are available, a need still exists for a Huber needle assembly with safety features that minimize the risk of exposure to blood-borne pathogens or drugs or accidental needle pricks.

SUMMARY AND OBJECTS OF THE INVENTION

(7) A primary object and advantage of the present invention is to provide a huber needle assembly which is efficient, effective and simple in its construction and use.

(8) It is another object of the present invention to provide a huber needle assembly with safety mechanism.

(9) It is another object of the present invention to provide a huber needle assembly with safety mechanism having automatic control features.

(10) It is another object of the present invention to provide a Huber needle assembly which provides better protection against accidental pricking by the needle tip.

(11) It is another object of the present invention to provide a Huber needle assembly which is inexpensive to manufacture.

(12) It is another object of the present invention to provide a compact design for a huber needle assembly.

(13) In accordance with one of the embodiments of the present invention, a huber needle assembly having a safety mechanism comprising a main body. The main body comprises a needle hub and a base, the needle hub having distal end and a proximal end, a huber needle is slidably disposed across the needle hub through the needle fitment area, the huber needle comprising a tip, a wing holder at the base having two wings at the opposite end of the wing holder, a conduit through which an axle is placed to connect the base with the needle hub, a connector is slidably arranged across the space provided between the distal end and the proximal end of the needle hub through a

lever and the chamber at the base through a lever, the dimension of the space is according to the length of the connector, so that the connector is axially arranged across the space of the needle hub at the ready position of the huber needle, the distal end of the needle hub having a flip. The connector is attached through a lever within the space which connect the needle hub and base. The needle hub having a channel through which huber needle passes and which is connected to the tube. The one end of the tube is connected to the proximal end of the needle hub and other end of the tube is connected to the luer lock, the luer lock having female luer in order to make leak-free connections between two parts. The tube has a clamp to regulate the flow of liquid through the tube.

(14) According to another embodiment, the present invention relates to a huber needle assembly having a safety mechanism according to the present invention. The main body comprises a huber needle assembly with a safety mechanism for guarding the huber needle tip against accidental pricking. The main body comprising a needle hub and a base, the needle hub which contain the huber needle with a needle tip, the needle hub having distal end and a proximal end, the distal end of the needle hub having a flip, a wing holder having two wings at the opposite end of the wing holder, the base is connected to the needle hub through the axle. A connector according to another embodiment of the present invention, which connect the needle hub and base. The connector is slidably arranged across the both side the needle hub through the lever which is attached at the chamber of the base. The needle hub having a channel through which needle passes and connected to the tube. The one end of the tube is connected to the proximal end of the needle hub and the other end of the tube is connected to the luer lock having female luer in order to make leak-free connections between two parts. The tube has a clamp to regulate the flow of liquid across supply tube.

Description

BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWINGS

- (1) The foregoing and other objects, features, and advantages of the invention will be apparent from the following detailed description taken in conjunction with the accompanying drawings, wherein:
- (2) FIG. 1 illustrates a huber needle assembly according to one of the embodiments of the present invention.
- (3) FIG. 2 illustrates the side view of the huber needle assembly in a ready position according to the embodiment of FIG. 1.
- (4) FIG. 3 illustrates the perspective view of the huber needle assembly in a locked position according to the embodiment of FIG. 1.
- (5) FIG. 4 illustrates the safety mechanism of the huber needle assembly in a safely locked position according to the embodiment of FIG. 1.
- (6) FIG. 5A-5D illustrate the views of needle hub 12 according to the embodiments of FIG. 1.
- (7) FIG. 6 illustrates the bottom view of the huber needle assembly in a safely locked position according to the embodiment of FIG. 1.
- (8) FIG. 7 illustrates a cross-section of the huber needle assembly in a safely locked position according to the embodiment of FIG. 1.
- (9) FIG. 8 illustrates a huber needle assembly according to another embodiment of the present invention.
- (10) FIG. 9 illustrates the side view of the huber needle assembly in a ready position according to another embodiment of FIG. 8.
- (11) FIG. 10 illustrates the perspective view of the huber needle assembly in a locked position according to another embodiment of FIG. 8.

- (12) FIG. 11 illustrates the locking mechanism of the huber needle assembly in a locked position according to other embodiments of FIG. 8.
- (13) FIG. 12A-12D illustrate the views of needle hub 112 according to another embodiment of FIG. 8.
- (14) FIG. 13 illustrates the top view of the huber needle assembly in a locked position according to one of the embodiments of FIG. 8.
- (15) FIG. 14 illustrates the cross-sectional view of the huber needle assembly in a locked position according to another embodiment of FIG. 8.
- (16) FIG. 15 illustrates the perspective view of the huber needle assembly with foam pad according to another embodiment of FIG. 8.

DETAILED DESCRIPTION OF THE INVENTION

- (17) Embodiments of the presently disclosed invention will now be described in detail with reference to the drawings wherein like reference numerals designate identical or corresponding elements. In the drawings and in the description, the term “proximal”, “bottom”, “down” or “lower” refers to a location on the device that is closest to the medical practitioner using the device and farthest from the patient in connection with whom the device is used when the device is used in its normal operation. Conversely, the term “distal”, “top”, “up” or “upper” refers to a location on the device that is farthest from the clinician using the device and closest to the patient in connection with whom the device is used when the device is used in its normal operation. For example, the distal region of a needle will be the region of the needle containing the needle tip which is to be inserted e.g. into a patient's vein.
- (18) As used herein, the term “in” or “inwardly” or “inner” refers to a location with respect to the device that, during normal use, is the inside of the device. Conversely, as used herein, the term “out” or “outwardly” or “outer” refers to a location with respect to the device that, during normal use, is toward the outside of the device.
- (19) As used herein, the terms first, second, third, etc. are understood to describe different structures/elements so as to distinguish one from another. However, the terms are not structurally limiting unless the context indicates otherwise.
- (20) The term “substantially” means that the recited characteristic, parameter, or value need not be achieved exactly, but that deviations or variations, including for example, tolerances, measurement error, measurement accuracy limitations and other factors known to those of skill in the art, may occur in amounts that do not preclude the effect the characteristic was intended to provide.
- (21) Moreover, the Figures may show simplified or partial views, and the dimensions of elements in the Figures may be exaggerated or otherwise not in proportion for clarity. In addition, the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to a terminal includes reference to one or more terminals. In addition, where reference is made to a list of elements (e.g., elements a, b, c), such reference is intended to include any one of the listed elements by itself, any combination of less than all of the listed elements, and/or a combination of all of the listed elements.
- (22) As used herein “ready position” means the huber needle is ready to be inserted into subcutaneously implanted ports for insertion or infusion of fluids.
- (23) As used herein “locked position” means the huber needle is safely guarded once the needle is retrieved from the subcutaneous port.
- (24) Referring now to FIG. 1, it illustrates a huber needle assembly according to one of the embodiments of the present invention. The huber needle assembly having a safety mechanism comprising a main body 10, the main body 10 comprising a needle hub 12 and a base 14, the needle hub having a distal end 28 and a proximal end 30, a huber needle 16 with a needle tip 18, the huber needle 16 is slidably disposed across the needle hub 12 through a needle fitment area 17, a wing holder 20 at the base 12 having two wings 22 at both the sides of the wing holder 20 opposing each other, a conduit 33 through which an axle 32 is placed to connect the base 14 with

the needle hub **12**, a connector **24** is slidably arranged across the space **26** provided between the distal end **28** and the proximal end **30** of the needle hub **12** through a lever **36** and across the chamber **48** of the base **14** through a lever **37** (not shown), the dimension of the space **26** is according to the length of the connector **24**, so that the connector **24** is axially arranged across the space **26** of the needle hub **12** at the ready position of the huber needle **16**, the distal end **28** of the needle hub **12** having a flip **34**.

(25) The connector **24** connect the needle hub **12** and the base **14**. The proximal end of the needle hub **12** having a channel **38** through which a tube **40** is fitted which is used for infusion of fluids. The one end of the tube **40** is connected to the proximal end **30** of the needle hub **12** and the other end of the tube **40** is connected to a luer lock **42**, the luer lock **42** having female luer **44** in order to make leak-free connections between two parts. The tube **40** has a clamp **46** to regulate the flow of liquid through the tube **40**.

(26) The two wings **22** are made up of soft material which are attached at the wing holder to provide comfortable contact and hinge connection with needle hub **12** and connector **24**. The wings **22** can be pivoted up to be grasped by in the fingers of a clinician, or pivoted downward to be applied on the skin of the patient. In some implementations, the wings **22** have a groove structure or texture formed into their upper and/or lower surfaces, to enable better grasping of the wings **22**.

(27) In some embodiments, the channel **38** is sized and adapted for a tight fit around the tube **40**. In some embodiments, the channel **38** can be formed to have a tolerance around the tube **40** that provides a predetermined coefficient of friction for relative ease or difficulty in sliding the needle hub **12** relative to the tube **40**. The luer lock **42** and female luer **44** have 6% taper fitting. The taper fitting of the luer lock and female luer can vary according the requirement.

(28) Referring to FIG. 2, a side view of the huber needle assembly in a ready position according to embodiment of FIG. 1 is illustrated. It illustrates a position when the huber needle **16** is positioned and inserted into the port for fluid extraction or insertion. At the ready position, the huber needle **16** is at 90° with respect to the base **14** and a sharp distal end that is formed (i.e. bent) and adapted to allow ease of penetration of skin and/or port while minimize coring damage, the connector **24** is axially (A) arranged across the space **26** of the needle hub **12** through the locking shaft **50** of the needle hub **12** with a knob **56**. The locking shaft **50** having a first end **52** and a second end **54**. The locking shaft **50** has a locking protrusion **55** with a groove **58** across the second end **54** of the locking shaft **50**.

(29) Referring to FIG. 3, a perspective view of the huber needle assembly in a locked position according to the embodiments of FIG. 1 is illustrated. It illustrates the position when the huber needle **16** is removed from the port and a subsequent protection of the huber needle **16** is made. The huber needle **16** passes through a bore **60** at the distal end of the needle hub **12** across a channel **38** at the proximal end of the needle hub **12** through the needle fitment area **17**, the channel **38** is connected to the tube **40** used for infusion of fluids. It shows that when the huber needle is extracted from the port, the huber needle **16** is tilted by 30°-60° with respect to the needle hub **12** and passes through the bore **60** to the channel **38**, the connector **24** will slide from first end **52** of the locking shaft **50** to the second end **54** of the locking shaft **50** with the help of lever **36** and lever **37**. The knob **56** fixed across the lever **36**, the knob **56** will slide according to the position of the lever **36** across the locking shaft **50** and stuck or locked across the groove **58** once the lever **36** locked across the locking protrusion **55**. The axle **32** at the proximal end **30** of the needle hub **12** is used to restrict upward motion of the needle hub **12**. Once the knob **56** gets locked at the groove **58**, the tip **18** of the huber needle **16** gets stuck/locked between an aperture **59** of the wing holder **20**.

(30) Referring to FIG. 4 locking mechanism of the huber needle assembly in a locked position according to the embodiments of FIG. 1 is illustrated. It illustrates the locking mechanism **62** for the safety function of the huber needle **16**, which automatically guard the huber needle while retrieving the huber needle from the port through the connector **24**. It shows the position of the

lever **36** of the connector **24** across the locking protrusion of the locking shaft **50**. The huber needle **16** is locked between the aperture **59** of the wing holder **20**.

(31) Referring to the FIGS. **5A-5D** illustrate the views of needle hub **12** according to the embodiments of FIG. **1**. FIG. **5A** shows the perspective view of the needle hub **12** having a flip **34** which is used to activate/lift the connector **24**, the channel **38** provides fitment area for the tube **40** for infusion of fluids. The locking shaft **50** for sliding the connector having locking protrusion **55** between the first end **52** and second end **54** of the locking shaft **50** which is used to permanently locked with the connector, groove **58** across the second end **54** of the locking shaft **50** which is used to lock the knob **56**. FIG. **5B** shows another perspective view of the needle hub **12** having a bore **60** through which huber needle passes to the channel. FIG. **5C** shows another perspective view of the needle hub **12** which shows the needle fitment across the Y-Section of the needle hub and the tube **40** for passage of fluid. FIG. **5D** shows the top view of the needle hub **12**. The Y-Section shows the horizontal position of the needle hub.

(32) Referring to FIG. **6** a bottom view of the huber needle assembly according to the embodiment of FIG. **1** is illustrated. It shows the bottom view of the main body **10** comprising a needle hub **12** having a space **26** across which connector **24** is attached and a bore **60** through which huber needle **16** passes to the channel **38**. The bottom side of the wings **22** at the opposite sides of the wing holder **20**. The wing holder works as a shield when safety mechanism activated and the wings **22** provide gripping to hold the needle hub **12** while insertion of huber needle **16** into the port at the subcutaneous area of the skin.

(33) The wings **22** are connected with the wing holder at the base that enables the wings **22** to be bent, rotated, pivoted, flapped or otherwise moved up or down. For instance, two opposing wings **22** can be bent upward to be grasped by the clinician to control the movement, direction, insertion and extraction of the needle attached thereto. In another instance, once the needle is inserted into the skin of the patient, the two wings **22** can be bent downward towards the skin surface of the patient, or onto a patch or other retaining mechanism.

(34) Referring to FIG. **7**, it illustrates the cross-sectional view of the huber needle assembly according to the embodiment of FIG. **1**. It illustrates the position of the huber needle **16** at its protected state. The huber needle passes across the bore **60** through the needle fitment area **17** to the channel **38** for infusion of fluid to the tube **40**.

(35) Referring to FIG. **8** a huber needle assembly according to another embodiment of the present invention is illustrated. The main body **110** comprises a huber needle assembly with a safety mechanism for guarding the huber needle tip against accidental pricking. The main body comprising a needle hub **112** and a base **114**, a huber needle **116** with a needle tip **118**, the needle hub **112** having distal end **128** and a proximal end **130**, a needle fitment area **117** between the distal end **28** and proximal end **130** of the needle hub **112** through which huber needle **116** will pass, the distal end **28** of the needle hub **12** having a flip **134**, a wing holder **120** having two wings **122** at the both side of the wing holder **120** opposing each other, a conduit **133** through which an axle **132** is placed to connect the base **114** with the needle hub **112**.

(36) A connector **124** according to another embodiment of the present invention, which connects the needle hub **112** and base **114**. The proximal end of the needle hub **112** having a channel **138** through which needle passes and connected to the tube **140**. The one end of the tube **140** is connected to the proximal end **130** of the needle hub **112** and the other end of the tube **140** is connected to a luer lock **142** having female luer **144** in order to make leak-free connections between two parts. The tube **140** has a clamp **146** to regulate the flow of liquid across tube **140**.

(37) The two wings **122** are made up of soft material which attached at the wing holder to provide comfortable contact and hinge connection with needle hub **112** and connector **124**. The wings **122** can be pivoted up to be grasped by in the fingers of a clinician, or pivoted downward to be applied on the skin of the patient. In some implementations, the wings **122** have a groove structure or texture formed into their upper and/or lower surfaces, to enable better grasping of the wings **122**.

(38) In some embodiments, the channel **138** is sized and adapted for a tight fit around the tube **140**. In some embodiments, the channel **138** can be formed to have a tolerance around the tube **140** that provides a predetermined coefficient of friction for relative ease or difficulty in sliding the needle hub **112** relative to the tube **140**. The luer lock **142** and female luer **144** have 6% taper fitting. The taper fitting of the luer lock and female luer can vary according to the requirement.

(39) Referring to FIG. **9** a side view of the huber needle assembly in a ready position according to another embodiment of FIG. **8** is illustrated. It illustrates the position when the huber needle **116** is positioned and inserted into the port for fluid extraction or insertion. At the ready position, the huber needle **116** is at 90° with respect to the base **114** and a sharp distal end that is formed (i.e. bent) and adapted to allow ease of penetration of skin and/or port while minimizing coring damage, the connector **124** is axially (A) arranged across the locking shaft **150** of the needle hub **112**. The locking shaft **150** having first end **152** and second end **154** with a groove **158** across the second end **154** of the locking shaft **150**. The connector **124** have locking protrusion **155**.

(40) Referring to FIG. **10** a perspective view of the huber needle assembly in a locked position according to another embodiment of FIG. **8** is illustrated. It illustrates the position when the huber needle **116** is removed from the port and a subsequent protection of the huber needle **116** is made. The connector **124** is slidably arranged across both side of the needle hub **112** through the lever **136** which is attached at the chamber **148** of the base **114**. The huber needle **116** passes through a bore **160** at the distal end of the needle hub **112** across a channel **138** at the proximal end of the needle hub **112**, the channel is connected to the tube **140** used for infusion of fluids. It shows that when the needle is extracted from the port the huber needle is tilted by 30°-60° with respect to the needle hub **112** and passes through the bore **160** to the channel **138**, the connector **124** will slide from first end **152** of the locking shaft **150** to the second end **154** of the locking shaft **150** where the locking protrusion **155** of the connector **124** will be stuck/locked at the groove **158** of the locking shaft **150**. The axle **132** at the proximal end **130** of the needle hub **112** is used to restrict upward motion of the needle hub **112**. Once the locking protrusion **155** will get locked at the groove **158** and the tip **118** of the huber needle **116** will stuck/locked between an aperture **159** of the wing holder **120**.

(41) Referring to FIG. **11** locking mechanism of the huber needle assembly in a locked position according to another embodiment of FIG. **8** is illustrated. It illustrates the locking mechanism **162** for the safety function of the huber needle **116**, which automatically guard the huber needle **116** while retrieving the huber needle from the port through the connector **124**. It shows the position of the locking protrusion **155** of the connector **124** across the groove **154** of the locking shaft **150**. The needle is locked between the aperture **159** of the wing holder **20**.

(42) Referring to the FIGS. **12A-12D**, they illustrate the views of needle hub **112** according to another embodiment of FIG. **8**. FIG. **12A** shows the perspective view of the needle hub **112** having a channel **38** providing fitment area to the tube **40** for infusion of fluids. The locking shaft **150** having first end **152** and second end **154**, groove **158** across the second end **154** of the locking shaft **150** which is used to permanently lock the connector **124**. FIG. **12B** shows another perspective view of the needle hub **112** having a flip **134** which is used to activate/lift the connector **24**. FIG. **12C** shows another perspective view of the needle hub **112** which shows the needle fitment area **117** horizontally (Y-Section) across the needle hub **112** and the tube **140** for passage of fluid. FIG. **12D** shows the top view of the needle hub **112**. The Y-Section shows the horizontal position of the needle hub.

(43) Referring to FIG. **13** a top view of the huber needle assembly in a locked position according to another embodiment of FIG. **8** is illustrated. It shows the top view of the main body **110** comprising the needle hub **112** and the wings **122** at the opposite sides of the wing holder **120**. The wing holder works as a shield when safety mechanism activated and the wings **122** provide gripping to hold the needle hub **112** while insertion of huber needle **116** into the port at the subcutaneous area of the skin.

(44) The wings **22** are connected with the wing holder at the base that enables the wings **22** to be

bent, rotated, pivoted, flapped or otherwise moved up or down. For instance, two opposing wings **22** can be bent upward to be grasped by the clinician to control the movement, direction, insertion and extraction of the needle attached thereto. In another instance, once the needle is inserted into the skin of the patient, the two wings **22** can be bent downward towards the skin surface of the patient, or onto a patch or other retaining mechanism.

(45) Referring to FIG. **14**, it illustrates the cross-sectional view of the huber needle assembly according to another embodiment of FIG. **8**. It illustrates the position of the huber needle at its protected state. The huber needle passes through the bore **160** to the channel **138** for infusion of fluid to the tube **140**.

(46) Referring to FIG. **15** the perspective view of the huber needle assembly with foam pad according to another embodiment of FIG. **8** is illustrated. The top of the base **114** is covered with a foam pad **164**, which is a non-absorbent foam pad, the foam pad is designed to assist with the placement of the huber needle **116** into the port for fluid extraction or insertion the base **114** with comfort of the patient and closed cell materials are designed to help reduce the risk of needlestick injuries, bacterial exchange and compression.

(47) The construction and shape of the huber needle assembly having a safety mechanism according to the various embodiments of the present disclosure provides a simple configuration. The simple and compact design of the huber needle assembly having safety mechanism according to the above disclosure is advantageous in a clinical setting because it provides an automatic protection against accidental pricking by the needle tip thereby reducing injury or discomfort to a patient and provides better safety features. In addition, such design greatly reduces manufacturing costs and is efficient, effective and simple in its construction and use.

(48) Although this invention has been disclosed in the context of certain preferred embodiments and examples, it will be understood by those skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. Thus, from the foregoing description, it will be apparent to one of ordinary skill in the art that many changes and modifications can be made thereto without departing from the spirit or scope of the invention as set forth in the claims.

(49) The scope of the present invention herein disclosed is not limited by the particular disclosed embodiments described above but determined only by a fair reading of the complete specification to be filed on this application.

LIST OF REFERENCE NUMERALS

(50) **10, 110** main body **11, 111** huber needle assembly **12, 112** needle Hub **14, 114** base **16, 116** huber Needle **17, 117** needle fitment area **18, 118** huber Needle Tip **20, 120** wing Holder **22, 122** wing(s) **24, 124** connector **26** space **28, 128** distal end **30, 130** proximal end **32, 132** axle **33, 133** conduit **34, 134** flip **36, 136** lever **37** lever **38, 138** channel **40, 140** tube **42, 142** luer lock **44, 144** female luer **46, 146** clamp **48, 148** chamber **50, 150** locking shaft **52, 152** first end **54, 154** second end **56** knob **55, 155** locking protrusion **58, 158** groove **59, 159** aperture **60, 160** bore **62, 162** locking mechanism **164** foam pad A axially Y horizontally

Claims

1. A safety mechanism for a huber needle assembly comprising: a main body having a needle hub and a base; a huber needle disposed along the needle hub with a tip wherein a proximal end of the needle hub is movably attached to a proximal end of the base; a wing holder at a distal end of the base, the wing holder having two sides and a wing extending from each side; a connector slidably arranged across a space provided between a distal end of the needle hub and the proximal end of the needle hub through a first lever at a distal end of the connector wherein a proximal end of the connector is movably connected to the base through a second lever; and wherein said needle hub comprises a flip to activate the connector and a locking shaft across the space, wherein the locking

shaft comprises a first end and a second end; and a locking protrusion with a groove across the second end of the locking shaft, wherein while retracting the huber needle, the connector slides from the first end of the locking shaft to the second end of the locking shaft with the help of the first lever at the distal end of the connector and the second lever at the proximal end of the connector; a knob fixed across the first lever at the distal end of the connector gets locked at the groove once the first lever at the distal end of the connector is locked across the locking protrusion; and the tip of the huber needle gets locked between an aperture of the wing holder.

2. The safety mechanism for a huber needle assembly as claimed in claim 1, wherein a dimension of the space is according to the length of the connector.
 3. The safety mechanism for a huber needle assembly as claimed in claim 1, further comprising an axle at the proximal end of the needle hub and wherein the axle at the proximal end of the needle hub is used to restrict upward motion of the needle hub.
 4. The safety mechanism for a huber needle assembly as claimed in claim 1, further comprising a port and wherein the huber needle is tilted by 30°-60° while retracting from the port.
 5. The safety mechanism for a huber needle assembly as claimed in claim 4, further comprising an axle at the proximal end of the needle hub and wherein the axle at the proximal end of the needle hub is used to restrict upward motion of the needle hub.
 6. The safety mechanism for a huber needle assembly as claimed in claim 1, further comprising a needle fitment area and wherein a bore at the distal end of the needle hub is connected to a channel allowing the huber needle to pass through the needle fitment area.
 7. A safety mechanism for a huber needle assembly comprising: a main body having a needle hub and a base; a huber needle disposed along the needle hub with a tip wherein a proximal end of the needle hub is movably attached to a proximal end of the base; a wing holder at a distal end of the base, the wing holder having two sides and a wing extending from each side; a lever movably connected to the base; a connector slidably arranged across both sides of the needle hub through lever; wherein said needle hub comprises a flip to activate the connector and a locking shaft, wherein the locking shaft comprises a first end and a second end; and a groove across the second end of the locking shaft; wherein while retracting the huber needle, the connector slides from the first end of the locking shaft to the second end of the locking shaft with the help of the lever; the connector has a locking protrusion, the locking protrusion of the connector gets locked at the groove; and the tip of the huber needle gets locked between an aperture of the base.
 8. The safety mechanism for a huber needle assembly as claimed in claim 7, further comprising a needle fitment area and wherein a bore at a distal end of the needle hub is connected to a channel allowing the huber needle to pass through the needle fitment area.
 9. The safety mechanism for a huber needle assembly as claimed in claim 7, further comprising a port and wherein the huber needle is tilted by 30°-60° while retracting from the port.
 10. The safety mechanism for a huber needle assembly as claimed in claim 7, wherein the base is covered with a foam pad to provide comfort to a patient and reduce risk of needlestick injuries, bacterial exchange and compression.
-