

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398706
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Rosinski; Ryan David

Ball piston pump

Abstract

A fluid pump includes a cam plate that defines an interior cam surface having an eccentric portion and a narrow portion. A hub rotates within the interior cam surface and has a piston cavity that is in communication with an inlet port and an outlet port. A piston member is operably received within the piston cavity to define a suction phase within the eccentric portion and a pressure phase within the narrowed portion. The piston member is biased outward by rotational operation of the hub. During the suction phase, the piston member is biased away from the piston cavity to define a flow cavity that draws fluid from the inlet port. During the pressure phase, the piston member is biased by the narrowed portion into the flow cavity to push the fluid from the flow cavity toward the outlet port.

Inventors:	Rosinski; Ryan David (Whitehall, MI)
Applicant:	GHSP, Inc. (Holland, MI)
Family ID:	1000008779476
Assignee:	GHSP, Inc. (Holland, MI)
Appl. No.:	17/780092
Filed (or PCT Filed):	December 02, 2020
PCT No.:	PCT/IB2020/061406
PCT Pub. No.:	WO2021/116835
PCT Pub. Date:	June 17, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220412330 A1	Dec. 29, 2022

Related U.S. Application Data

us-provisional-application US 62946004 20191210

Publication Classification

Int. Cl.: **F04B1/1071** (20200101); **F04B7/06** (20060101); **F04B53/10** (20060101)

U.S. Cl.:

CPC **F04B1/1071** (20130101); **F04B7/06** (20130101); **F04B53/10** (20130101);

Field of Classification Search

CPC: F04B (1/1071); F04B (7/06); F04B (53/10); F04B (1/10); F04B (1/113); F04B (1/1133); F04B (11/00)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2391221	12/1944	Beeh	137/565.28	F02M 69/02
3782245	12/1973	Aldinger	N/A	N/A
3835752	12/1973	D'Amata	N/A	N/A
3999466	12/1975	Aschke	91/499	F04B 1/2042
4352319	12/1981	Wegerdt	91/483	F04B 1/066
2013/0343914	12/2012	Fenny	417/273	F04B 1/0404

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
861222	12/1995	JP	N/A
2011111980	12/2010	JP	N/A
101176638	12/2011	KR	N/A
WO-2017089586	12/2016	WO	F04B 1/04

Primary Examiner: Stimpert; Philip E

Attorney, Agent or Firm: Price Heneveld LLP

Background/Summary

FIELD OF THE INVENTION

(1) The present invention generally relates to fluid pumps, and more specifically to a fluid pump having one or more piston members that operate to move fluid through a rotating hub.

BACKGROUND OF THE INVENTION

(2) Various pumps are used to move a fluid from one location to another. These fluid pumps operate by using changes in pressure to generate suction and pressure that moves fluid from an inlet

to an outlet.

SUMMARY OF THE INVENTION

(3) According to one aspect of the present invention, a fluid pump includes a cam plate that defines an interior cam surface having an eccentric portion and a narrow portion. A hub rotates within the interior cam surface and has a piston cavity that is in communication with an inlet port and an outlet port. A piston member is operably received within the piston cavity to define a suction phase within the eccentric portion and a pressure phase within the narrowed portion. The piston member is biased outward by rotational operation of the hub. During the suction phase, the piston member is biased away from the piston cavity to define a flow cavity that draws fluid from the inlet port. During the pressure phase, the piston member is biased by the narrowed portion into the flow cavity to push the fluid from the flow cavity toward the outlet port.

(4) According to another aspect of the present invention, a fluid pump includes a cam plate having an interior cam surface that defines alternating eccentric and narrowed sections. A hub rotates within the interior cam surface and includes piston cavities in communication with an inlet port and an outlet port. Piston members are respectively positioned within the piston cavities to define flow cavities therebetween. Rotation of the hub generates a centrifugal force that biases the piston members toward the interior cam surface and away from a rotational axis of the hub. The alternating eccentric and narrowed sections define respective suction and pressure phases of each piston member. Each suction phase biases the piston members outward to expand the flow cavity. The suction phases draw a fluid into the flow cavity from the inlet port. Each pressure phase biases the piston members into the respective piston cavities to compress the flow cavity and expel the fluid from the flow cavity and toward the outlet port. The inlet port is aligned with the eccentric sections and the outlet port is aligned with the narrowed sections.

(5) According to another aspect of the present invention, a fluid pump includes an end assembly having a fluid inlet and a fluid outlet. A fluid path extends between the fluid inlet and the fluid outlet. The fluid path has centrifugal sections and centripetal sections that move fluid through the fluid path. A cam plate includes an interior cam surface that defines the centrifugal sections and the centripetal sections. A hub assembly rotates about a rotational axis. The hub assembly comprises a plurality of piston members and a central hub. Rotation of the hub assembly through the centrifugal sections and the centripetal sections defines a radial movement of each piston member. The plurality of piston members operate in a radially outward direction in the centrifugal sections to expand corresponding flow cavities that draw the fluid from an inlet port. The plurality of piston members operating in a radially inward direction in the centripetal sections to compress the flow cavities and push the fluid out of the flow cavity and toward an outlet port.

(6) These and other aspects, objects, and features of the present invention will be understood and appreciated by those skilled in the art upon studying the following specification, claims, and appended drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In the drawings:

(2) FIG. 1 is a side perspective view of an aspect of a ball piston pump;

(3) FIG. 2 is another side perspective view of the ball piston pump of FIG. 1;

(4) FIG. 3 is a side elevational view of the ball piston pump of FIG. 1;

(5) FIG. 4 is a side elevational view of the ball piston pump of FIG. 2;

(6) FIG. 5 is an exploded perspective view of the ball piston pump of FIG. 1;

(7) FIG. 6 is another exploded perspective view of the ball piston pump of FIG. 1;

(8) FIG. 7 is a cross-sectional view of the ball piston pump of FIG. 1 taken along line VII-VII;

(9) FIG. 8 is a cross-sectional view of the ball piston pump of FIG. 2 taken along line VIII-VIII;
(10) FIG. 9 is a cross-sectional view of the ball piston pump of FIG. 1 taken along line IX-IX;
(11) FIG. 10 is an exploded perspective view of an aspect of a ball piston pump; and
(12) FIG. 11 is a schematic cross-sectional view of an aspect of the hub and the interior cam surface.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(13) For purposes of description herein, the terms “upper,” “lower,” “right,” “left,” “rear,” “front,” “vertical,” “horizontal,” and derivatives thereof shall relate to the invention as oriented in FIG. 1. However, it is to be understood that the invention may assume various alternative orientations, except where expressly specified to the contrary. It is also to be understood that the specific devices and processes illustrated in the attached drawings, and described in the following specification are simply exemplary embodiments of the inventive concepts defined in the appended claims. Hence, specific dimensions and other physical characteristics relating to the embodiments disclosed herein are not to be considered as limiting, unless the claims expressly state otherwise.

(14) As exemplified in FIGS. 1-11, reference numeral 10 generally refers to a ball piston pump having a cam member 12 that includes an interior cam surface 14 that cooperates with a rotating hub 16 having a plurality of piston members 18. The piston members 18 are paired within various apertures, such as piston cavities 20, defined within the hub 16. As the hub 16 rotates within the interior cam surface 14, centrifugal force 22 caused by rotation of the hub 16 within the cam member 12 causes a biasing force that moves the piston member 18 in an outward direction 24 and outside of the piston cavities 20. When the piston member 18 moves outside of the piston cavities 20, a suction 26 is generated that draws fluid 28 in through one or more inlet ports 60 and into the piston cavities 20, where a flow cavity 38 is defined between the piston members 18 and the flow cavities 38. As the hub 16 rotates, the piston member 18 and piston cavities 20 become aligned with a narrowed portion 32 of the interior cam surface 14, such that the interior cam surface 14 biases, through a centripetal force 36, the piston member 18 into the piston cavities 20. This movement of the piston member 18 into the piston cavities 20, where the piston member 18 now occupy the piston cavities 20, shrinks the flow cavity 38. In this manner, the movement of the piston member 18 pushes the piston member 18 into the piston cavity 20 and, in turn, pushes the fluid 28 out from the piston cavities 20 and into one or more corresponding outlet ports 62.

(15) Referring again to FIGS. 4-11, the rotational operation of the hub 16 and the piston members 18 within the interior cam surface 14 generates a consistent centrifugal force 22 that is applied to the piston member 18. The centrifugal force 22 biases the piston member 18 away from the piston cavities 20. Simultaneously, the interior cam surface 14 generates an opposing centripetal force 36. Through these opposing centrifugal and centripetal forces 22, 36, the motion of the piston member 18 follows the path defined by the interior cam surface 14. As discussed above, the piston members 18 are permitted to move outside of the piston cavities 20 in an eccentric portion 50 or expanded portion of the interior cam surface 14. In this suction phase 40, the flow cavities 38 between the piston member 18 and the corresponding piston cavity 20 expand to generate suction 26. This suction 26 draws fluid into the flow cavities 38. As the hub 16 rotates with respect to the interior cam surface 14, the piston member 18 reach the narrowed portion 32 of the interior cam surface 14. Movement of the piston member 18 and the piston cavity 20 through the narrowed portion 32 defines a pressure phase 42 where the piston member 18 is biased through centripetal force 36 and into the piston cavity 20. This movement of the piston member 18 into the piston cavity 20 pushes the piston member 18 into the flow cavity 38 to generate a pressure 44 that pushes the fluid from the flow cavity 38 toward a fluid outlet 34.

(16) The centrifugal force 22 that biases the piston member 18 in an outward direction 24, is counteracted by the centripetal force 36 that is generated by the interior cam surface 14. The eccentric portion 50 allows for a controlled movement of the piston member 18 in the outward direction. Conversely, the centripetal force 36 generated in the narrowed portion 32 overcomes the

centrifugal force **22** and biases the piston member **18** back into the piston cavities **20**. Accordingly, rotational motion of the hub **16** within the interior cam surface **14** generates an oscillating motion **52** of each piston member **18** with respect to a corresponding piston cavity **20**. In operation, as the hub **16** rotates about the rotational axis **54** of the hub **16**, the piston member **18** follows the path defined by the interior cam surface **14**.

(17) As exemplified herein, the interior cam surface **14** can include a generally elliptical profile having opposing eccentric portions **50** and opposing narrowed portions **32**. These eccentric and narrowed portions **50**, **32** generate a generally elliptical motion of the piston members **18** with respect to the interior cam surface **14**. This, in turn, generates the oscillating motion **52** of each piston member **18** with respect to a corresponding piston cavity **20**. Modifications in the shape of the interior cam surface **14** can be used to create a variety of patterns of eccentric portions **50** and narrowed portions **32** for managing a flow of the fluid **28** through the piston pump **10**.

(18) The shape of the interior cam surface **14** is aligned with corresponding inlet ports **60** and outlet ports **62** that are positioned within a port portion **64**, such as a porting plate, of an end assembly **66** for the piston pump **10**. Typically, the inlet ports **60** are aligned with the eccentric portions **50** of the interior cam surface **14**. Conversely, the outlet ports **62** within the port portion **64** of the end assembly **66** are aligned with the narrowed portions **32** of the interior cam surface **14**. In this manner, the oscillating motion **52** of the piston member **18** with respect to the piston cavities **20**, and the corresponding expansion and compression of the flow cavities **38**, is contemporaneous with the motion of each piston member **18** between the outlet port **62** positioned at the narrowed portion **32** and inlet port **60** positioned at the eccentric portion **50** of the interior cam surface **14**.

(19) The design of the hub **16** having the piston member **18** and piston cavities **20** set therein, and which rotates within the interior cam surface **14**, is useful in moving fluids **28** having higher viscosities. Fluids **28** having higher viscosity may include generally thicker fluids **28**, or fluids **28** that are thicker when at a lower temperature. By way of example, at a startup condition of a vehicle, a particular fluid **28** may have a higher viscosity. Operation of the piston pump **10** disclosed herein is useful in moving these higher viscosity fluids **28** through the piston pump **10**. Additionally, as the viscosity of a particular fluid **28** decreases, the fluid **28** typically warms, and the piston pump **10** remains efficient at moving fluid **28** through the ball piston pump **10**.

(20) The shape of the interior cam surface **14** can be any one of various shapes that can include, but are not limited to, ovals, rounded geometries, or other similar rounded geometries having multiple axes of symmetry. As discussed above, these various geometries of the interior cam surface **14** are shaped to include various eccentric portions **50** and narrowed portions **32** that align with the inlet ports **60** and outlet ports **62**, respectively. In certain aspects of the device, the interior cam surface **14** can take the shape of an egg-shaped geometry, where the egg-shaped geometry includes a single eccentric portion **50** and a single narrowed portion **32** with respect to a rotational axis **54** of the hub **16**. This egg-shaped geometry of the interior cam surface **14** defines a single-fill fluid pump having a single inlet port **60** and a single outlet port **62**. Typically, the interior cam surface **14** will include a geometry having a multiple axis of symmetry such that a dual-fill or multiple-fill configuration is possible. The dual-fill or multiple-fill configuration, such as a generally elliptical profile, typically provides an equalized pressure **44** around the rotational axis **54** such that the fluid apertures **110** of the piston cavities **20** are balanced around the rotational axis **54** of the hub **16** and within the interior cam surface **14**. This cam member **12** tends to maintain an alignment of the hub **16** with the rotational axis **54** of the ball piston pump **10**.

(21) According to aspects of the device, the hub **16** can include various numbers of piston members **18** and piston cavities **20**. As exemplified herein, six piston members **18** can be operable within six piston cavities **20**. It should be contemplated that additional or fewer numbers of piston members **18** and piston cavities **20** can be incorporated into the hub **16**. By way of example and not limitation, certain sized piston members **18** may be incorporated to produce a flow of a more viscous fluid. Different sizes and configurations of piston members **18** can be incorporated to

address the flow of fluids having different viscosities and variable viscosities over time. In addition, the number and shape of the narrowed and eccentric portions **32**, **50** of the interior cam surface **14** can be modified to account for fluids having different viscosities. Variations in the number and configuration of the piston members **18**, the piston cavities **20** and the interior cam surface **14** can also be used to address a wide range of piston pumps **10** for producing a variety of flow rates.

(22) According to various aspects of the device, a drive shaft **90** of the piston pump **10** can extend from a motor **92** to the hub **16**. As the motor **92** operates, the drive shaft **90** rotates the hub **16** within the interior cam surface **14**. The motor **92** can typically operate at speeds of approximately 4,000 revolutions per minute or lower speeds where the fluid **28** has a higher viscosity or where a lower flow rate is desired. Where the fluid **28** has a lower viscosity or a higher flow rate is desired, higher rotational speeds can be utilized. Higher rotational speeds may be approximately 10,000 revolutions per minute. It should be understood that the motor **92** and the hub **16** can operate at a wide range of rotational speeds greater than or less than those mentioned herein. The rotational speed utilized is typically calibrated to generate the centrifugal force **22** on the piston member **18** of a magnitude sufficient to produce a continual engagement of the piston members **18** with the interior cam surface **14**.

(23) The piston pump **10** disclosed herein can be used for applications having higher viscous fluids **28** or fluids **28** that are more viscous at cooler temperatures. Such applications can include, but are not limited to, vehicle transmissions, vehicle differentials and other similar applications where higher viscosity fluids **28** are utilized, and where the fluid **28** has a higher viscosity at lower temperatures seen at a start-up of a particular mechanism.

(24) As exemplified in FIGS. **4-11**, the various inlet ports **60** and outlet ports **62** contained within the port portion **64** of the end assembly **66** can be configured to extend to a common inlet channel **100** and a common outlet channel **102**, respectively. In such a configuration, an end plate **104** of the end assembly **66** can include a fluid inlet channel **100** that extends between each of the inlet ports **60** of the port portion **64** of the end assembly **66**. Similarly, a fluid outlet channel **102** can include a path that extends between the various fluid outlet ports **62** of the port portion **64** of the end assembly **66**. Using the fluid inlet and fluid outlet channels **100**, **102**, a single inlet path and a single outlet path can be defined within the end assembly **66** of the piston pump **10**.

(25) Referring again to FIGS. **4-11**, the hub **16** can include the various piston cavities **20** that receive the piston members **18** that operate in an oscillating motion **52** with respect to the interior cam surface **14** as oscillating members. These piston members **18** can be in the form of balls, cylinders, or other geometries that can be used to operate in an oscillating motion **52** or piston-type fashion with respect to the piston cavities **20** defined within the hub **16**.

(26) Referring again to FIGS. **1-11**, the fluid delivering piston pump **10** can include the cam member **12**, such as a cam plate having the interior cam surface **14** that defines eccentric and narrowed portions **50**, **32**. These eccentric and narrowed portions **50**, **32** can be configured as alternating eccentric and narrowed sections **120**, **122** such that multiple eccentric and narrowed sections **120**, **122** can be included within the eccentric and narrowed portions **50**, **32**. The hub **16** rotates within the interior cam surface **14** and includes piston cavities **20** in communication with the inlet port **60** and the outlet port **62**. The piston members **18**, typically in the form of the ball piston, are respectively positioned within the piston cavities **20** to define flow cavities **38** therebetween.

(27) Rotation of the hub **16** generates the centrifugal force **22** that biases the piston member **18** toward the interior cam surface **14** and away from the rotational axis **54** of the hub **16**. The alternating eccentric and narrowed sections **120**, **122** define respective suction and pressure phases **40**, **42** of each piston member **18**. Each suction phase **40** biases the piston member **18** outward to expand the respective flow cavity **38**. The suction phases **40** serve to draw the fluid **28** into the flow cavity **38** from the inlet port **60**. Accordingly, the expansion of the flow cavity **38** generates the

suction **26** that draws the fluid **28** into the flow cavity **38**. Each pressure phase **42** biases the piston member **18** back into the respective piston cavities **20** to compress the flow cavity **38**. This compression of the flow cavity **38** generates pressure **44** that serves to expel the fluid **28** from the flow cavity **38** and move the fluid **28** toward the outlet port **62**. The inlet port **60** is aligned with the eccentric sections **120** and the outlet port **62** is aligned with the narrowed sections **122**. According to various aspects of the device, each eccentric section **120** can include a corresponding inlet port **60** and each narrowed section **122** can include a corresponding outlet port **62**.

(28) Referring to FIGS. **4-11**, the inlet port **60** and the outlet port **62** are defined within the end assembly. Typically, the inlet port **60** and outlet port **62**, or the pluralities of inlet and outlet ports **60**, **62**, are defined within a porting plate or port portion **64** of the end assembly **66**. The end assembly **66** includes a fluid inlet **30** that is in communication with the inlet port **60** and a fluid outlet **34** that is in communication with the outlet port **62**. The fluid inlet **30** and fluid outlet **34** are typically positioned at an outer surface **130** of the end assembly **66** for engagement with various components of an external fluid flow path **132**. This external fluid flow path **132** can deliver the fluid **28** into the piston pump **10**, and also deliver the fluid **28** away from the piston pump **10**. Within the end assembly **66**, the inlet channel **100** extends between the fluid inlet **30** and the inlet port **60**. Similarly, the outlet channel **102** extends between the fluid outlet **34** and the outlet port **62**. As discussed above, the inlet channel **100** can also serve to provide a fluid communication between the various inlet ports **60** such that a consistent flow of fluid **28** can be maintained from the fluid inlet **30**, through the inlet channel **100**, and through the various inlet ports **60** to provide fluid **28** into the eccentric sections **120** of the piston pump **10**. Similarly, the outlet channel **102** can extend to multiple outlet ports **62** for delivering the fluid **28** from the various outlet ports **62** to the fluid outlet **34**. In this manner, a consistent flow of fluid **28** can be achieved from the narrowed sections **122** of the piston pump **10** and to the fluid outlet **34**. The positioning of the inlet ports **60** and the outlet ports **62** can be defined within a flow surface **134** of the end assembly **66**. Typically, this flow surface **134** is defined within the port portion **64** of the end assembly **66**.

(29) Referring again to FIGS. **4-9**, the eccentric portion **50** of the interior cam surface **14** can include first and second eccentric sections **150**, **152** that are positioned opposite one another. First and second narrowed sections **154**, **156** can also be positioned opposite one another such that the eccentric sections **120** and narrowed sections **122** produce a sequential and alternating pattern of narrowed sections **122** and eccentric sections **120**. This alternating pattern of narrowed sections **122** and eccentric sections **120** produces the oscillating motion **52** of the piston members **18** within the piston cavities **20** to produce the expansion and compression of the flow cavities **38**. This expansion and compression of the flow cavities **38** produces the suction **26** and pressure **44** that moves the fluid **28** from the fluid inlet **30**, through the flow cavities **38** and then to the fluid outlet **34**.

(30) In order to achieve a consistent flow of fluid **28** from the fluid inlet **30** and into the various eccentric sections **120**, a pressure relief channel **170** can be positioned within the port portion **64**. This pressure relief channel **170** can extend between the opposing first and second eccentric sections **150**, **152** and serves to equalize the suction **26** between the various eccentric sections **120** within the interior cam surface **14**. Using the pressure relief channel **170**, a consistent flow of the fluid **28** can be maintained within the interior cam surface **14**, and within the various flow cavities **38** defined between the piston members **18** and the piston cavities **20** of the piston pump **10**.

(31) In order to remove the fluid **28** from the inlet ports **60** to the flow cavities **38** and from the flow cavities **38** to the outlet ports **62**, each piston cavity **20** includes a fluid aperture **110** that extends to a porting surface **180** of the hub **16**. Typically, the port portion **64**, or porting plate, is positioned adjacent to the hub **16** and the cam member **12**. In this configuration, the porting surface **180** of the hub **16** faces the flow surface **134** of the port portion **64**. During operation of the hub **16**, the fluid apertures **110** of the various piston cavities **20** alternatively align with the inlet ports **60** and outlet ports **62** during operation of the hub **16**, in a sequential pattern of alignment.

Accordingly, the oscillating motion 52 of the piston members 18 that produces the suction 26 and pressure 44 of the fluid 28 within the piston pump 10 can provide a substantially continuous flow of fluid 28 through the piston pump 10. Through this configuration, operation of the various piston members 18 between the suction phases 40 and pressure phases 42 moves fluid 28 from the inlet port 60, into the flow cavities 38, and then toward the outlet port 62 via the fluid apertures 110 of each piston cavity 20.

(32) As exemplified in the figures, the hub 16 includes six piston cavities 20 and six corresponding piston members 18. Each of these paired piston members 18 and piston cavities 20, during one rotation of the hub 16, experiences multiple oscillations and multiple occurrences of the pressure phases 42 and suction phases 42, 40 of the piston pump 10. Again, rotation of the hub 16 within the interior cam surface 14 produces a consistent, or substantially consistent, flow of the fluid 28 through the eccentric and narrowed sections 120, 122 of the piston pump 10.

(33) Referring again to FIGS. 4-9, within the interior cam surface 14, and the porting plate, two narrowed sections 122 of the interior cam surface 14 correspond to two outlet ports 62 and two eccentric sections 120 of the interior cam surface 14 correspond to two inlet ports 60 of the port portion 64. As discussed above, the two inlet ports 60 are fluidly connected via the inlet channel 100 and the two outlet ports 62 are fluidly connected via the outlet channel 102. Accordingly, multiple inlet ports 60 and multiple outlet ports 62 can be coupled with the fluid inlet 30 and fluid outlet 34, respectively, via a single inlet channel 100 and a single outlet channel 102.

(34) Referring again to FIGS. 1-11, the fluid delivering piston pump 10 includes the end assembly 66 having the fluid inlet 30 and the fluid outlet 34. A fluid path 190 extends between the fluid inlet 30 and the fluid outlet 34. The fluid path 190 also includes various centrifugal sections and centripetal sections that move the fluid 28 through the fluid path 190. The centrifugal sections correspond to the eccentric sections 120, where the centrifugal force 22 generated by rotation of the hub 16 causes the piston member 18 to move outward in an oscillating motion 52. The centripetal sections can correspond to the narrowed sections 122, where the centripetal force 36 generated by the interior cam surface 14 biases the piston members 18 into the corresponding piston cavities 20. As discussed above, these oscillating motions 52 of the piston members 18 produce the suction phases 40 and pressure phases 42 of the piston pump 10.

(35) Referring again to FIGS. 1-11, the hub assembly 196 rotates about the rotational axis 54. The hub assembly 196 includes a plurality of piston members 18 and a central hub 16. Rotation of the hub assembly 196 through the centrifugal sections and the centripetal sections defines a radial movement or oscillating motion 52 of each piston member 18. The piston members 18 that are respectively positioned within corresponding piston cavities 20 define flow cavities 38 therebetween. Rotation of the hub 16 generates the centrifugal force 22 that biases the piston members 18 toward the interior cam surface 14 and away from the rotational axis 54 of the hub 16. At the same time, the interior cam surface 14 produces a centrifugal force 22 that maintains an outward position of each of the piston members 18. This outward position of the piston members 18 is consistent with the shape or profile of the interior cam surface 14 within which the hub assembly 196 rotates.

(36) The plurality of piston members 18 operating in the radial outward direction 24 and within the centrifugal sections serves to expand the corresponding flow cavities 38 that generates a suction 26 for drawing the fluid 28 from the inlet port 60. The plurality of piston members 18 operating in a radial inward direction occurs within the centripetal sections and operates to compress the flow cavities 38. This compression of the flow cavities 38 generates a pressure 44 that pushes the fluid 28 out of the flow cavities 38 and toward the outlet port 62. As discussed herein, the centrifugal sections and the centripetal sections sequentially define the suction phases 40 and pressure phases 42, respectively, of the piston members 18. Operation of the piston members 18 between the suction phases 40 and pressure phases 42 serve to move the fluid 28 from the inlet port 60, into the flow cavities 38 and then toward the outlet port 62.

(37) Using the piston pump **10**, fluids of various viscosities, as well as fluids **28** of changing viscosities, can be moved from the fluid inlet **30**, through the flow cavities **38**, and then to the fluid outlet **34**. As discussed above, in certain conditions, the viscosity of a fluid **28** may change over time to be less or more viscous. The operation of the ball piston pump **10** is able to accommodate these changing viscosities and fluctuating viscosities during operation of a particular device that requires a flow of fluid **28** running therethrough.

(38) It is to be understood that variations and modifications can be made on the aforementioned structure without departing from the concepts of the present invention, and further it is to be understood that such concepts are intended to be covered by the following claims unless these claims by their language expressly state otherwise.

Claims

1. A fluid pump comprising: a cam plate that defines an interior cam surface having an eccentric portion and a narrowed portion; an end assembly that includes an inlet channel and an outlet channel; a hub that rotates within the interior cam surface and having a piston cavity that is in communication with an inlet port and an outlet port and in communications with the inlet channel and the outlet channel; and a piston member that is operably received within the piston cavity to define a suction phase within the eccentric portion and a pressure phase within the narrowed portion, wherein the piston member is biased outward by rotational operation of the hub, wherein: during the suction phase, the piston member is biased away from the piston cavity to define a flow cavity that draws fluid from the inlet port; during the pressure phase, the piston member is biased by the narrowed portion into the flow cavity to push the fluid from the flow cavity toward the outlet port; the eccentric portion includes opposing first and second eccentric sections of the interior cam surface and the narrowed portion includes opposing first and second narrowed sections of the interior cam surface; and the cam plate at least partially defines a pressure relief channel that extends between the opposing first and second eccentric sections and that serves to equalize a suction between the opposing first and second eccentric sections.
2. The fluid pump of claim 1, wherein the inlet port and the outlet port are defined within the end assembly.
3. The fluid pump of claim 2, wherein the end assembly has a fluid inlet that is in communication with the inlet port and a fluid outlet in communication with the outlet port, and wherein: the fluid inlet and the fluid outlet are positioned at an outer surface of the end assembly; the inlet port and the outlet port are defined within a flow surface of the end assembly; the inlet channel extends between the fluid inlet and the inlet port and the outlet channel extends between the fluid outlet and the outlet port; and the end assembly includes a porting plate that is positioned between the cam plate and an end plate of the end assembly, the porting plate having the inlet port that extends between the eccentric portion and the inlet channel, and the outlet port extends between the narrowed portion and the outlet channel.
4. The fluid pump of claim 1, wherein the piston member is biased against the interior cam surface at least by a centrifugal force generated during rotation of the hub.
5. The fluid pump of claim 3, wherein each piston cavity includes a fluid aperture that extends to a porting surface of the hub, wherein the fluid apertures alternatively align with the inlet channel and the outlet channel during operation of the hub, wherein operation of the piston member between the suction phase and the pressure phase moves the fluid from the inlet port, into the piston cavities and toward the outlet port.
6. A fluid pump comprising: a cam plate having an interior cam surface that defines alternating eccentric and narrowed sections; an end assembly that includes an inlet channel and an outlet channel; a hub that rotates within the interior cam surface and having piston cavities in communication with an inlet port and an outlet port and in communication with the inlet channel

and the outlet channel; and piston members that are respectively positioned within the piston cavities to define flow cavities therebetween, wherein rotation of the hub generates a centrifugal force that biases the piston members toward the interior cam surface and away from a rotational axis of the hub, the interior cam surface including a generally elliptical profile having two eccentric sections and two narrowed sections, wherein: the alternating eccentric and narrowed sections define a suction phase and a pressure phase, respectively, of each piston member; each suction phase biases the piston members outward to expand the flow cavity, the suction phases drawing a fluid into the flow cavity from the inlet port; each pressure phase biases the piston members into the respective piston cavities to compress the flow cavity and expel the fluid from the flow cavity and toward the outlet port; the inlet port is aligned with the eccentric sections and the outlet port is aligned with the narrowed sections; and a pressure relief channel extends between the two eccentric sections and serves to equalize a suction of the suction phase between the two eccentric sections.

7. The fluid pump of claim 6, wherein: the two narrowed sections correspond to two outlet ports and the two eccentric sections correspond to two inlet ports; and the two inlet ports are fluidly connected via the inlet channel and the two outlet ports are fluidly connected via the outlet channel.

8. The fluid pump of claim 6, wherein the hub includes six piston cavities and the piston members include six piston members operably positioned within the six piston cavities, wherein each piston member rotationally operates about the rotational axis of the hub and sequentially operates the suction and pressure phases relative to the inlet port and the outlet port.

9. The fluid pump of claim 6, wherein the inlet ports and the outlet ports are defined within a porting plate that is positioned adjacent to the hub and the cam plate.

10. The fluid pump of claim 7, wherein the pressure relief channel is positioned within a porting plate that is positioned adjacent to the hub and the cam plate, wherein the inlet channel and the outlet channel are positioned within an end plate, wherein the porting plate is positioned between the cam plate and the end plate.

11. The fluid pump of claim 7, wherein each piston cavity includes a fluid aperture that extends to a porting surface of the hub, wherein each fluid aperture sequentially aligns with one of the two inlet ports, one of the two outlet ports, the other of the two inlet ports and the other of the two outlet ports.

12. A fluid pump comprising: an end assembly having a fluid inlet and a fluid outlet, wherein a fluid path extends between the fluid inlet and the fluid outlet, the fluid path having centrifugal sections and centripetal sections that move fluid through the fluid path; a cam plate having an interior cam surface that defines the centrifugal sections and the centripetal sections; and a hub assembly that rotates about a rotational axis, the hub assembly comprising a plurality of piston members and a central hub, wherein, rotation of the hub assembly through the centrifugal sections and the centripetal sections defines a radial movement of each piston member of the plurality of piston members; the plurality of piston members operating in a radially outward direction in the centrifugal sections to expand corresponding flow cavities that draw the fluid from an inlet port; the plurality of piston members operating in a radially inward direction in the centripetal sections to compress the corresponding flow cavities and push the fluid out of the corresponding flow cavities and toward an outlet port; and the end assembly includes a pressure relief channel that extends between the centrifugal sections and equalizes a suction within the corresponding flow cavities to draw the fluid from the inlet port.

13. The fluid pump of claim 12, wherein the end assembly includes an end plate and a porting plate, wherein the inlet port and the outlet port are defined within the porting plate that is positioned adjacent the cam plate and the hub assembly, wherein: the end plate has as inlet channel in communication with the inlet port and an outlet channel in communication with the outlet port; the fluid inlet and the fluid outlet are positioned at an outer surface of the end plate; and the inlet channel and the outlet channel extend to a flow surface of the end plate, wherein the porting plate engages the flow surface.

14. The fluid pump of claim 12, wherein the inlet port extends through an inlet channel to the fluid inlet and the outlet port extends through an outlet channel to the fluid outlet.
15. The fluid pump of claim 12, wherein the plurality of piston members are operably disposed within respective piston cavities of the central hub, wherein the respective piston cavities guide operation of the plurality of piston members in the radially outward and radially inward directions during rotational operation of the central hub.
16. The fluid pump of claim 12, wherein the flow cavities are defined between the plurality of piston members and the respective piston cavities.
17. The fluid pump of claim 12, wherein each respective piston cavity includes a fluid aperture that extends to a porting surface of the hub assembly, wherein operation of the hub assembly sequentially aligns the fluid apertures with the inlet ports and the outlet ports.
18. The fluid pump of claim 12, wherein the plurality of piston members are biased into an elliptical motion around a rotational axis of the hub assembly, wherein the elliptical motion is defined by a centrifugal force generated during rotation of the central hub and a centripetal force exerted by the interior cam surface.
19. The fluid pump of claim 12, wherein the centrifugal sections and the centripetal sections sequentially define a suction phase and a pressure phase, respectively, of the plurality of piston members, wherein operation of the plurality of piston members between the suction phase and the pressure phase moves the fluid from the inlet port, into the flow cavities and toward the outlet port.
20. The fluid pump of claim 12, wherein the pressure relief channel is at least partially defined by the cam plate.
-