

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401183
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Diop; Seydou et al.

Single person wedge clamp

Abstract

A dead-end clamp assembly for a utility conductor includes a clamp body having a base with a front end and a rear end, a first jaw guide extending from the base, and a second jaw guide extending from the base. The base, first jaw guide, and second jaw guide at least partially define a trough. A first jaw movably engages the body and a second jaw movably engages the body. The first jaw engages the second jaw such that the first and second jaws move together. A sag eye extends from the clamp body. The sag eye has an opening configured to receive a hotstick. A clevis connector extends from the rear end of the clamp body. The clevis connector is configured to receive a clevis pin so that the clevis pin is positioned below the trough.

Inventors:	Diop; Seydou (Hoover, AL), Candelaria; Adrian Beau (Montevallo, AL), Carter; Joshua Chapman (Birmingham, AL)
Applicant:	Hubbell Incorporated (Shelton, CT)
Family ID:	1000008779588
Assignee:	HUBBELL INCORPORATED (Shelton, CT)
Appl. No.:	18/007980
Filed (or PCT Filed):	June 03, 2021
PCT No.:	PCT/US2021/035670
PCT Pub. No.:	WO2021/247839
PCT Pub. Date:	December 09, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230238789 A1	Jul. 27, 2023

Related U.S. Application Data

us-provisional-application US 63034531 20200604

Publication Classification

Int. Cl.: H02G7/05 (20060101)

U.S. Cl.:

CPC H02G7/056 (20130101);

Field of Classification Search

CPC: H02G (1/00); H02G (7/05); H02G (1/04); H02G (7/00); H02G (1/02); H02G (7/056); H02G (7/02); H02G (7/053)

USPC: 248/63

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
482975	12/1891	Cope	54/33	F16G 11/04
1415112	12/1921	Perlitz	24/135R	H02G 7/056
1973502	12/1933	Olson	24/136R	H02G 7/053
2137858	12/1937	Schwabacher	174/161R	H02G 7/056
2274055	12/1941	Fitzpatrick	403/80	H02G 7/056
2775422	12/1955	Von Herbulis	24/135R	H02G 7/053
3108344	12/1962	Barron	403/373	H02G 7/056
3284863	12/1965	Lindsey	174/79	H02G 7/056
3470528	12/1968	Flynn	24/115R	H02G 7/056
4183686	12/1979	De France	24/135K	F16G 11/06
4383668	12/1982	Hall	N/A	N/A
4407471	12/1982	Wilmsmann	294/102.1	H02G 7/056
4428100	12/1983	Apperson	24/115M	H02G 7/056

4523355	12/1984	Rosa	403/209	H01B 17/06
4592117	12/1985	Ruehl	24/132WL	H02G 7/08
4719672	12/1987	Apperson	24/135R	G02B 6/48
5539961	12/1995	DeFrance	403/314	H02G 7/056
5581051	12/1995	Hill	174/138R	H01H 31/00
5752680	12/1997	Mann	N/A	N/A
6076236	12/1999	DeFrance	N/A	N/A
6282759	12/2000	Czaloun	24/132R	F16G 11/048
6547481	12/2002	Grabenstetter	294/102.1	H02G 7/056
6796854	12/2003	Mello	439/796	H01R 4/5083
7039988	12/2005	De France	439/783	H02G 7/056
7562848	12/2008	Tamm	24/67.5	H02G 7/056
8991790	12/2014	Herman	254/134.3 R	H02G 1/02
9825449	12/2016	Diop	N/A	F16B 2/065
11322918	12/2021	Schenk	N/A	H02G 1/02
2002/0106239	12/2001	Grabenstetter et al.	N/A	N/A
2013/0240685	12/2012	Bundren	248/74.1	F16L 3/1033
2015/0200527	12/2014	Shibilia et al.	N/A	N/A
2018/0375315	12/2017	Park	N/A	H02G 7/053
2019/0157850	12/2018	Herman	N/A	H02G 1/04
2020/0251833	12/2019	Schumann	N/A	H02G 7/05

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2768281	12/2011	CA	H02G 7/02
118610975	12/2023	CN	H02G 7/056
297159	12/1927	GB	H02G 7/056
H02307321	12/1989	JP	N/A
4484401	12/2009	JP	H02G 7/053
890008378	12/1988	KR	H02G 7/056
200405444	12/2005	KR	F16B 2/14
20150115426	12/2014	KR	N/A
WO-2013130346	12/2012	WO	F16B 2/065

OTHER PUBLICATIONS

Machine Translation of JP-4484401 (Year: 2010). cited by examiner

Machine Translation of JP H02307321 (Year: 1990). cited by examiner

Primary Examiner: Morris; Taylor

Attorney, Agent or Firm: Robinson + Cole LLP

Background/Summary

FIELD

(1) Various exemplary embodiments relate to a dead-end clamp or tension device for attaching a utility line cable to a support.

BACKGROUND

(2) Dead-ends are couplings used to anchor electrical transmission lines to supporting structures such as towers or poles. Typically a dead-end connects the power line to an insulated mount attached to the supporting structure. Dead-ends include a mechanism for gripping the conductor of the power line so that the tension on the line is delivered through the insulated mount to the supporting structure. Dead-ends are characterized by robust construction from high strength materials to withstand the tension on power line, which may exceed several thousand pounds of force.

(3) Weather events, such as wind and ice may place an additional strain on a transmission lines and cause downed lines or other part failures. In certain situations, a dead-end may need to be replaced or installed during extreme weather events. This can be difficult given the environmental circumstances and the presence of live power wires. Dead-ends typically need to be installed by more than one person, which can limit response time in emergency situations. Accordingly, there remains a need for a dead-end connector that can be safely installed by a single person in the presence of live power lines.

SUMMARY

(4) According to various aspects, a dead-end clamp assembly for a utility conductor includes a clamp body having a base with a front end and a rear end, a first jaw guide extending from the base, and a second jaw guide extending from the base. The base, first jaw guide, and second jaw guide at least partially define a trough. A first jaw movably engages the body and a second jaw movably engages the body. The first jaw engages the second jaw such that the first and second jaws move together. A sag eye extends from the clamp body. The sag eye has an opening configured to receive a hotstick. A clevis connector extends from the rear end of the clamp body. The clevis connector is configured to receive a clevis pin so that the clevis pin is positioned below the trough.

(5) According to various aspects, a dead-end clamp assembly for a utility conductor includes a clamp body having a base with a front end and a rear end, a first jaw guide extending from the base, and a second jaw guide extending from the base. The base, first jaw guide, and the second jaw guide at least partially define a trough. A first jaw movably engages the body and a second jaw movably engages the body. The first jaw engages the second jaw such that the first and second jaws move together. A sag eye extends from the clamp body beneath the base opposite the trough. The sag eye has an opening configured to receive a hotstick and oriented to allow a connected hotstick to be positioned beneath the base. A clevis connector extends from the rear end of the clamp body.

(6) According to various aspects, a method of installing a dead-end clamp assembly on a utility conductor includes positioning a clamp assembly including a clamp body, a first jaw, a second jaw, a sag eye, and a clevis connector. A hotstick is connected to the sag eye. The clamp assembly is moved with the hotstick, to receive a conductor. The first jaw and second jaw are engaged with the

conductor. Moving the clamp assembly to receive the conductor and engaging the first jaw and second jaw are performed using a single hotstick without requiring disengagement of the hotstick from the sag eye.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The aspects and features of various exemplary embodiments will be more apparent from the description of those exemplary embodiments taken with reference to the accompanying drawings.
- (2) FIG. 1 is a perspective view of an exemplary clamp assembly.
- (3) FIG. 2 is a top, perspective view of FIG. 1.
- (4) FIG. 3 is a side view of FIG. 1.
- (5) FIG. 4 is a top view of the first and second jaws.
- (6) FIG. 5 is a perspective view of FIG. 4.
- (7) FIG. 6 is a front view of FIG. 4.
- (8) FIG. 7 shows an installation process for the clamp of FIG. 1.
- (9) FIG. 8 shows an installation process for the clamp of FIG. 1.
- (10) FIG. 9 shows an installation process for the clamp of FIG. 1.
- (11) FIG. 10 shows an installation process for the clamp of FIG. 1.
- (12) FIG. 11 is a perspective view of an exemplary clamp assembly.
- (13) FIG. 12 is side view of the clamp body of FIG. 11.
- (14) FIG. 13 is a top view of the clamp body of FIG. 11.
- (15) FIG. 14 is a front view of the clamp body of FIG. 11.
- (16) FIG. 15 is a top view of the jaws of FIG. 11.
- (17) FIG. 16 is a side view of the first jaw of FIG. 11.
- (18) FIG. 17 is a side view of the second jaw of FIG. 11.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

- (19) A wedge type, dead-end clamp assembly **100** includes a clamp body **102** having a base **104** from which a first jaw guide **106** and a second jaw guide **108** outwardly extend. The base **104** has a front end **110** and a rear end **112**. The first and second jaw guides **106**, **108** extend from the front end **110** to the rear end **112** of the clamp body **102**. A first jaw **114** and a second jaw **116** are moveably positioned in the clamp body **102** adjacent the respective jaw guides **106**, **108** for receiving a cable or conductor therebetween. A first groove **118** is provided in the clamp body **102** for receiving the first jaw **114**. A second groove **120** is provided in the clamp body **102** for receiving the second jaw **116**.
- (20) The jaws **114**, **116** are movable between a rear position and a forward position on the clamp body **102**. In certain aspects, the jaws **114**, **116** are moved into the rear position to receive a cable and are moved into the forward position to engage and retain the cable in the dead-end clamp assembly **100**. The jaws **114**, **116** can engage the jaw guides **106**, **108** and the grooves **118**, **120** with sufficient friction to be retained in a desired place when set by a user. In other embodiments, one or more biasing members can be used to bias the first and second jaws into an engaged position. For example, a single biasing member (e.g., coil spring) is connected to the clamp body **102** and one of the jaws **114**, **116** to pull or push the jaws **114**, **116** toward the front end **110** of the clamp body **102**. A first keeper **107** is removably connected to the first jaw guide **106** and a second keeper **109** is removably connected to the second jaw guide **108** to engage the respective jaws **114**, **116** and prevent them from lifting out of the clamp body **102**. The first and second keepers **107**, **109** can include a series of slots that engage projections extending from the respective jaw guide **106**, **108**.
- (21) The first jaw guide **106** faces the second jaw guide **108** and forms a trough **122** therebetween.

The trough **122** is substantially V-Shaped with the width of the trough **122** at the rear end **112** being larger than the width at the front end **110**. The inner surfaces of the jaw guides **106,108** are angled inwardly from the rear end **112** to the front end **110** to cause the first and second jaws **114, 116** to move toward one another as the first and second jaws **114, 116** move through the trough **122** toward the front end **110** and away from each other as the jaws **114, 116** move toward rear end **112**. The first and second grooves **118, 120** extend from the rear end **112** to the front end **110** of the clamp body **102**. The trough **122** extends along a cable axis **A1** for securing a cable, such as an electrical conductor or other utility line.

(22) The dead-end clamp assembly **100** includes a sag eye **124** extending from the clamp body **102**. The sag eye **124** includes a rim **126** surrounding an opening **128**. The rim **126** extends from the side of the clamp body **102** away from the trough **122**, with the opening **128** oriented perpendicular to the cable axis **A1**. The rim **126** can extend from at or near the front end **110** of the clamp body to at or near the rear end **112**. One or more curvilinear and/or rectilinear walls make up the rim **126** and the opening **128** can have a substantially oval shape. In certain aspects, the rim **126** is configured so that the width of the opening **128** is larger in the front portion of the sag eye **124** than a rear portion. In other aspects, the size, shape and configuration of the rim **126** and opening **128** can be varied based on the environment of use and installation application.

(23) The dead-end clamp assembly **100** also includes a clevis connector **130**. The clevis connector includes a first leg **132** and a second leg **134** extending from the rear end **112** of the clamp body **102**. The first and second legs **132, 134** each terminate in a cylindrical opening **136**. The openings **136** are configured to receive a bolt or pin which can include a cotter opening. The clevis connector **130** is configured to receive a bracket or other fastening element to connect the dead-end clamp assembly **100** to a support. In certain embodiments, the legs **132, 134** are configured to extend below the clamp body **102** and the openings **136** are oriented below the cable axis **A1** and perpendicular to the cable axis **A1**. The legs **132, 134** can be angled or curved to be positioned below the clamp body **102**. For example, the legs **132, 134** can have a convex curve and a concave curve. Other configurations of a clevis connector may also be used. In certain aspects, the clamp body **102**, sag eye **124**, and clevis connector **130** are integrally formed. In other embodiments, one or more of these components can be formed separately and connected together by fasteners or a joining process (e.g., welding).

(24) The first jaw **114** includes a first jaw body **138** having a front end **140** and a rear end **142**. The first jaw body **138** tapers or narrows from the rear end **142** to the front end **140**. The first jaw body **138** includes a curved inner surface **144**. A plurality of teeth **146** are formed on the inner surface **144** and are configured to grip a cable. A ledge **148** extends from the first jaw body **138** opposite the inner surface **144**. The ledge **148** is configured to slidably engage the first jaw guide **106**. The ledge can include an outwardly facing channel **150**. One or more legs **152** can extend downwardly from the first jaw body **138** to slidably engage the first groove **118** in the clamp body **102**. For example, front and rear legs **152** can extend from the first jaw body **138**, although a single leg, a continuous leg, or more than two legs can also be used. A biasing member can be positioned inside the legs **152** and engage one of the legs **152** and a stop located in the first groove **118** to bias the first jaw **114** into an engaged position.

(25) The second jaw **116** includes a second jaw body **154** having a front end **156** and a rear end **158**. The second jaw body **154** tapers or narrows from the rear end **158** to the front end **156**. The second jaw body **154** includes a curved inner surface **160**. A plurality of teeth **162** are formed on the inner surface **160** and are configured to grip a cable. A ledge **164** extends from the second jaw body **154** opposite the inner surface **160**. The ledge **164** is configured to slidably engage the second jaw guide **108**. The ledge **165** can include an outwardly facing channel **166**. One or more legs **168** can extend downwardly from the second jaw body **154** to slidably engage the second groove **120** in the clamp body **102**. For example, a single continuous leg **168** can extend from the first jaw body, although a single leg, or multiple legs can also be used.

(26) A first tab **170** and a second tab **172** extend outwardly from the inner surface **144** of the first jaw body **138**, and are configured to extend into the trough **122**. The first and second tabs **170**, **172** can be tapered, for example at the same angle as the first jaw body **138**. A slot is formed between the first and second tab **170**, **172**. One of the tabs **170**, **172** includes a mating feature to assist engagement with the second jaw **116**. For example, the second tab **172** can include an L-shaped notch **174**.

(27) A third tab **176** extends outwardly from the inner surface **160** of the second jaw body **154**, and is configured to extend into the trough **122**. The third tab **176** can be tapered, for example at the same angle as the second jaw body **154**. The third tab **176** is configured to mate with the slot between the first and second tabs **170**, **172**. The third tab **176** can also include a mating feature to assist engagement with the first jaw **114**. For example, the third tab **176** can include an L-shaped notch **178** that mates with the L-shaped notch **174** on the second tab **172**. Engagement of the third tab **176** with the first tab **170** or second tab **172** keys the first jaw **114** and the second jaw **116** together so that they can slide forward and backward in the clamp body **102** as a single unit.

Engagement of the notches **174**, **178** enables a user to secure the jaws **114**, **116** in an open position. (28) In some embodiments, a pullback interface **180** extends upward from the second jaw body **154** and is configured to project above the clamp body **102**. The pullback interface **180** includes an interface body **182** having one or more openings. In certain embodiments the interface body **182** includes a rounded projection and the openings include a circular aperture **184** and rectilinear slot **186** formed in the projection. The opening can be configured to allow a user to engage the pullback interface **180** by hand or with a hot stick or other tool. Other sizes, shapes, and configurations for the interface body and openings may be used.

(29) During an emergency situation that involves a downed utility line (e.g., a power line) there is typically no way for a first responder, acting alone, to cut a section of a downed line without the remaining sections also falling onto the ground. This is because the portion of the conductor that is still in the air would slip out of the insulator. Accordingly, a downed conductor must be tagged and then later cut and replaced by a line crew. This process can take an extended period of time, meanwhile the downed conductor can pose a problem to emergency personnel.

(30) The dead-end clamp assembly **100** is designed to alleviate these problems by allowing a single person (such as a first responder) to position and attach the dead-end clamp assembly **100** to secure a portion of a conductor. The dead-end clamp assembly **100** is able to be attached by a single person using a hotstick while the line is energized, allowing for a safer installation process. A single hotstick can be used during installation without requiring disengagement of the hotstick from the dead-end clamp assembly **100**. When being held by the hotstick and installed, the legs **132**, **134** of the clevis **130** are positioned so that they will not come into contact with the live line or interfere in the installation process. There is also no need to contact or shape any part of the conductor prior to the installation process.

(31) FIGS. 7-10 show an exemplary installation process of the dead-end clamp assembly **100**. The dead-end clamp assembly **100** is positioned in a location for use, such as at an emergency situation near a downed power wire or at other utility line locations where the dead-end clamp assembly **100** is needed. An insulator **200** is connected to the dead-end clamp assembly **100** through the clevis connector **130**. The insulator **200** can be tied to a support, such as a utility pole cross arm, using a rope or cable **210**. The jaws **114**, **116** of the dead-end clamp assembly **100** are placed in a retracted position. The jaws **114**, **116** are configured to remain in place in the retracted position through a friction engagement without additionally input from a user. This friction engagement can be, in part, through the engagement of the legs **152**, **156** and the grooves **118** and **120**. A hotstick **220** is connected to the sag eye **124**. The dead-end clamp assembly **100** can then be hoisted until it is positioned near a conductor **230** using the rope **210**, hotstick **220**, or a combination thereof.

(32) Using the hotstick **220**, the dead-end clamp assembly **100** is positioned so that conductor **230** is positioned in the jaws **114**, **116**. The hotstick **220** is then used to manipulate the dead-end clamp

assembly **100** so that the jaws **114**, **116** move forward and engage the conductor **230**. A certain amount or type of movement in the dead-end clamp assembly **100** can dislodge the friction engagement of one or both jaws **114**, **116**. In some operations, the user can pull down and back on the hotstick **220**, engaging at least one of the jaws **114**, **116** with the conductor **230** and causing the jaws **114**, **116** to move toward the front end **110** of the clamp body **102**. In some operations, the user can shake or jerk the clamp body **102** to dislodge the jaws **114**, **116** and activate the biasing member that pulls the jaws **114**, **116** forward. Once the dead-end clamp assembly **100** is engaged, a user can cut a section of the conductor **230** that is downed to remove the energized conductor on the ground. The dead-end clamp assembly **100** will support the remaining section of the conductor **230** so that it does not disengage from the utility line support assembly.

(33) As shown, the dead-end clamp assembly **100** can be installed entirely using a single hotstick without other engagement of a user with the clamp body **102** or the first and second jaws **114**, **116**. Certain aspects of the installation procedure can be performed in various orders.

(34) The legs **132**, **134** of the clevis connector **130** position the attachment to the insulator **200** below the conductor **230** so that the insulator is not in the way of the conductor **230** or of the attachment to the conductor **230**. Additionally, the position of the sag eye **124** allows a user to position the dead-end clamp assembly **100** to engage the conductor **230** using a single hotstick **220**.

(35) FIGS. **11-16** show another exemplary embodiment of a wedge type, dead-end clamp assembly **300** that can be installed as described above. The dead-end clamp assembly **300** includes a clamp body **302** having a base **304**. A first jaw guide **306** and a second jaw guide **308** extend outwardly from the clamp body **302**. The base **304** has a front end **310** and a rear end **312**. The first and second jaw guides **306**, **308** extend from the front end **310** to the rear end **312** of the clamp body **302**. A first jaw **314** and a second jaw **316** are moveably positioned in the clamp body **302** adjacent the respective jaw guides **306**, **308** for receiving a cable or conductor therebetween. A first groove **318** is provided in the clamp body **302** for receiving the first jaw **314**. A second groove **320** is provided in the clamp body **302** for receiving the second jaw **316**.

(36) The jaws **314**, **316** are movable between a rear position and a forward position on the clamp body **302**. In certain aspects, the jaws **314**, **316** are moved into the rear position to receive a cable and are moved into the forward position to engage and retain the cable in the dead-end clamp assembly **300**. In certain embodiments, the jaws **314**, **316** engage the jaw guides **306**, **308** and the grooves **318**, **320** with sufficient friction to be retained in a desired place when set by a user. In certain embodiments, one or more biasing members **321** can be used to bias the first and second jaws into an engaged position. For example, a single biasing member **321** (e.g., coil spring) is connected to the clamp body **302** and one of the jaws **314**, **316** to pull or push the jaws **314**, **316** toward the front end **310** of the clamp body **302**. The biasing member **321** can be connected at one end to a stop **319** positioned in the first groove **318** and at a second end to one of the jaws **314**.

(37) A first keeper **307** is removably connected to the first jaw guide **306** and a second keeper **309** is removably connected to the second jaw guide **308** to engage the respective jaws **314**, **316** and prevent them from lifting out of the clamp body **302**. The first and second keepers **307**, **309** can include a series of slots that engage projections extending from the respective jaw guide **306**, **308**.

(38) The first jaw guide **306** faces the second jaw guide **308** and forms a trough **322** therebetween. The trough **322** is substantially V-Shaped with the width of the trough **322** at the rear end **312** being larger than the width at the front end **310**. The inner surfaces of the jaw guides **306**, **308** are angled inwardly from the rear end **312** to the front end **310** to cause the first and second jaws **314**, **316** to move toward one another as the first and second jaws **314**, **316** move through the trough **322** toward the front end **310** and away from each other as the jaws **314**, **316** move toward the rear end **312**. The first and second grooves **318**, **320** extend from the rear end **312** to the front end **310** of the clamp body **302**. The trough **322** extends along a cable axis **A1** for securing a cable, such as an electrical conductor or other utility line.

(39) The dead-end clamp assembly **300** includes a sag eye **324** extending from the clamp body **302**.

The sag eye **324** includes a rim **326** surrounding an opening **328**. The rim **326** extends from the bottom clamp body **302** away from the trough **322**, with the opening **328** oriented perpendicular to the cable axis **A1**. The rim **326** can extend from at or near the front end **310** of the clamp body to at or near the rear end **312**. One or more curvilinear and/or rectilinear walls make up the rim **326** and the opening **328** can have a substantially D-shape. In certain aspects, the rim **326** is configured so that the width of the opening **328** is larger in the front portion of the sag eye **324** than a rear portion. In other aspects, the size, shape and configuration of the rim **326** and opening **328** can be varied based on the environment of use and installation application.

(40) The dead-end clamp assembly **300** also includes a clevis connector **330**. The clevis connector includes a first leg **332** and a second leg **334** extending from the rear end **312** of the clamp body **302**. The first and second legs **332**, **334** each terminate in a cylindrical opening **136**. The openings **136** are configured to receive a bolt or pin **335** which can include a cotter opening to receive a cotter pin **337**. The clevis connector **330** is configured to receive a bracket or other fastening element to connect the dead-end clamp assembly **300** to a support. Other configurations of a clevis connector may also be used. In certain aspects, the clamp body **302**, sag eye **324**, and clevis connector **330** are unitarily formed. In other embodiments, one or more of these components can be formed separately and connected together by fasteners or a joining process (e.g., welding).

(41) The first jaw **314** includes a first jaw body **338** having a front end **340** and a rear end **342**. The first jaw body **338** tapers or narrows from the rear end **342** to the front end **340**. The first jaw body **338** includes a curved inner surface **344**. A plurality of teeth **346** are formed on the inner surface **344** and are configured to grip a cable. A ledge **348** extends from the first jaw body **338** opposite the inner surface **344**. The ledge **348** is configured to slidably engage the first jaw guide **306**. The ledge can include an outwardly facing channel **350**. One or more legs **352** can extend downwardly from the first jaw body **338** to slidably engage the first groove **318** in the clamp body **302**. For example, front and rear legs **352** can extend from the first jaw body **338**, although a single leg, a continuous leg, or more than two legs can also be used. The front and rear legs **352** can be positioned in the separate parts of the first groove **318** on opposite sides of the stop **319**. The biasing member **321** can be connected to the stop **319** and to either the front or rear leg **352** (depending on the type of biasing member) to bias the jaws **114**, **116** to a closed position.

(42) The second jaw **316** includes a second jaw body **354** having a front end **356** and a rear end **358**. The second jaw body **354** tapers or narrows from the rear end **358** to the front end **356**. The second jaw body **354** includes a curved inner surface **360**. A plurality of teeth **362** are formed on the inner surface **360** and are configured to grip a cable. A ledge **364** extends from the second jaw body **354** opposite the inner surface **360**. The ledge **364** is configured to slidably engage the second jaw guide **308**. The ledge **365** can include an outwardly facing channel **366**. One or more legs **368** can extend downwardly from the second jaw body **354** to slidably engage the second groove **320** in the clamp body **302**. For example, a single continuous leg **368** can extend from the first jaw body, although a single leg, or multiple legs can also be used.

(43) A first tab **370** and a second tab **372** extend outwardly from the inner surface **344** of the first jaw body **338**, and are configured to extend into the trough **322**. The first and second tabs **370**, **372** can be tapered, for example at the same angle as the first jaw body **338**. A slot is formed between the first and second tab **370**, **372**. One of the tabs **370**, **372** includes a mating feature to assist engagement with the second jaw **316**. For example, the second tab **372** can include an L-shaped notch **374**.

(44) A third tab **376** extends outwardly from the inner surface **360** of the second jaw body **354**, and is configured to extend into the trough **322**. The third tab **376** can be tapered, for example at the same angle as the second jaw body **354**. The third tab **376** is configured to mate with the slot between the first and second tabs **370**, **372**. The third tab **376** can also include a mating feature to assist engagement with the first jaw **314**. For example, the third tab **376** can include an L-shaped notch **378** that mates with the L-shaped notch **374** on the second tab **372**. Engagement of the third

tab 376 with the first tab 370 or second tab 372 keys the first jaw 314 and the second jaw 316 together so that they can slide forward and backward in the clamp body 302 as a single unit.

(45) In some embodiments, a pullback interface 380 extends upward from the second jaw body 354 and is configured to project above the clamp body 302. The pullback interface 380 includes an interface body 382 having one or more openings. In certain embodiments the body includes a rounded projection and the opening includes a circular aperture 384. The opening can be configured to allow a user to engage the pullback interface 380 by hand or with a hot stick. Other sizes, shapes, and configurations for the interface body and openings may be used.

(46) The foregoing detailed description of the certain exemplary embodiments has been provided for the purpose of explaining the general principles and practical application, thereby enabling others skilled in the art to understand the disclosure for various embodiments and with various modifications as are suited to the particular use contemplated. This description is not necessarily intended to be exhaustive or to limit the disclosure to the exemplary embodiments disclosed. Any of the embodiments and/or elements disclosed herein may be combined with one another to form various additional embodiments not specifically disclosed. Accordingly, additional embodiments are possible and are intended to be encompassed within this specification and the scope of the appended claims. The specification describes specific examples to accomplish a more general goal that may be accomplished in another way.

(47) As used in this application, the terms “front,” “rear,” “upper,” “lower,” “upwardly,” “downwardly,” and other orientational descriptors are intended to facilitate the description of the exemplary embodiments of the present disclosure, and are not intended to limit the structure of the exemplary embodiments of the present disclosure to any particular position or orientation. Terms of degree, such as “substantially” or “approximately” are understood by those of ordinary skill to refer to reasonable ranges outside of the given value, for example, general tolerances associated with manufacturing, assembly, and use of the described embodiments.

Claims

1. A dead-end clamp assembly for a utility conductor, comprising: a clamp body including a base having a front end and a rear end, a first jaw guide extending from the base, and a second jaw guide extending from the base, wherein the base, first jaw guide, and second jaw guide at least partially define a trough and the trough at least partially defines a conductor axis; a first jaw movably engaging the body and a second jaw movably engaging the body, the first jaw engaging the second jaw such that the first and second jaws move together; a sag eye extending from the clamp body, the sag eye having an opening configured to receive a hotstick; and a clevis connector extending from the rear end of the clamp body, the clevis connector configured to receive a clevis pin so that the clevis pin and a connected insulator are positioned entirely below the conductor axis when the base and the trough are positioned below the conductor relative to a ground surface.
2. The clamp assembly of claim 1, wherein the sag eye opening is oriented orthogonal to the conductor axis.
3. The clamp assembly of claim 1, wherein the clamp body, sag eye, and clevis connector are integrally formed.
4. The clamp assembly of claim 1, wherein a first groove and a second groove are formed in the base, and wherein the first groove slidably receives the first jaw and the second groove slidably receives the second jaw.
5. The clamp assembly of claim 1, wherein the clevis connector includes a first leg and a second leg extending downwardly from the base, the first leg having a first concave section and the second leg having a second concave section.
6. The clamp assembly of claim 1, wherein the sag eye opening is oriented to allow a hotstick to be positioned to a side of the clamp body.

7. The clamp assembly of claim 1, wherein the first jaw includes a first tab and a second tab, the first and second tabs spaced from each other to define a slot, and wherein the second jaw includes third tab, the third tab configured to be received in the slot when the first jaw and the second jaw are assembled with the clamp body.
8. The clamp assembly of claim 7, wherein the second tab includes a first notch and the third tab includes a second notch configured to mate with the first notch.
9. The clamp assembly of claim 1, wherein the second jaw includes a pullback interface.
10. The clamp assembly of claim 9, wherein the pullback interface includes a projection, an aperture formed in the projection, and a slot formed in the projection.
11. A dead-end clamp assembly for a utility conductor, comprising: a clamp body including a base having a front end and a rear end, a first jaw guide extending from the base, and a second jaw guide extending from the base, wherein the base, first jaw guide, and second jaw guide at least partially define a trough and the trough at least partially defines a conductor axis; a first jaw movably engaging the body and a second jaw movably engaging the body, the first jaw engaging the second jaw such that the first and second jaws move together; a sag eye extending from the clamp body beneath the base opposite the trough, the sag eye having an opening configured to receive a hotstick and oriented to allow a connected hotstick to be positioned beneath the base; and a clevis connector extending from the rear end of the clamp body, wherein the clevis connector includes a first leg and a second leg spaced from one another by a gap, and wherein the gap is positioned entirely below the conductor axis at a distance to receive a clevis pin and a connected insulator entirely below the conductor axis when the base and the trough are positioned below the conductor relative to a ground surface.
12. The clamp assembly of claim 11, wherein the sag eye opening is oriented orthogonal to the conductor axis.
13. The clamp assembly of claim 11, wherein a first groove and a second groove are formed in the base, and wherein the first groove slidably receives the first jaw and the second groove slidably receives the second jaw.
14. The clamp assembly of claim 11, further comprising a clevis pin positioned in the clevis connector.
15. The clamp assembly of claim 11, wherein the first jaw includes a first tab and a second tab, the first and second tabs spaced from each other to define a slot, and wherein the second jaw includes third tab, the third tab configured to be received in the slot when the first jaw and the second jaw are assembled with the clamp body.
16. The clamp assembly of claim 15, wherein the second tab includes a first notch and the third tab includes a second notch configured to mate with the first notch.
17. The clamp assembly of claim 11, wherein the second jaw includes a pullback interface.
18. The clamp assembly of claim 17, wherein the pullback interface includes a projection, an aperture formed in the projection, and a slot formed in the projection.
19. A method of installing a dead-end clamp assembly on a utility conductor comprising: positioning a clamp assembly including a clamp body, a first jaw, a second jaw, a sag eye, and a clevis connector, wherein the clamp body between the first jaw and the second jaw defines a trough for receiving a conductor; connecting a hotstick to the sag eye; moving the clamp assembly, with the hotstick, to receive the conductor; and engaging the first jaw and second jaw with the conductor, wherein moving the clamp assembly to receive the conductor and engaging the first jaw and second jaw are performed using a single hotstick without requiring disengagement of the hotstick from the sag eye, wherein the clamp assembly includes a conductor axis and the clevis connector is configured to receive a clevis pin so that the clevis pin and a connected insulator are positioned entirely below the conductor axis when the trough is positioned below the conductor relative to a ground surface.
20. The method of claim 19, wherein the sag eye extends from the clamp body substantially

orthogonal to the conductor.

21. The method of claim 19, further comprising attaching an insulator to the clamp assembly through the clevis connector.

22. The method of claim 19, further comprising attaching a rope to the insulator and raising the clamp assembly to the conductor using the rope.
