

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250277473

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

ADKINS; Russell et al.

HYBRID TRANSMISSION COMPONENT FOR A GAS TURBINE ENGINE

Abstract

A hybrid transmission component for a gas turbine engine has a composite body, and a metallic coupling joined with the composite body and defining a longitudinal axis along its length. The metallic coupling includes a plurality of spline teeth extending from a circumferential surface and angularly separated from each other about the longitudinal axis. Each spline tooth from the plurality of spline teeth extends radially from a root to a tip with respect to the longitudinal axis and extends axially from the leading end along the longitudinal axis. The leading end of each spline tooth includes a curved surface extending from the root and a planar surface extending from the curved surface to the tip. The planar surface is inclined obliquely to the longitudinal axis by a rake angle.

Inventors: ADKINS; Russell (Derby, GB), SPRUCE; Mark (Derby, GB), JONES; Christopher D. (Chippenham, GB), GREAVES; Richard (Derby, GB)

Applicant: ROLLS-ROYCE plc (London, GB)

Family ID: 89662939

Assignee: ROLLS-ROYCE plc (London, GB)

Appl. No.: 18/967804

Filed: December 04, 2024

Foreign Application Priority Data

GB

2319474.9

Dec. 19, 2023

Publication Classification

Int. Cl.: F02C7/36 (20060101); F16D1/10 (20060101)

CPC **F02C7/36** (20130101); F05D2230/18 (20130101); F05D2250/292 (20130101);
F05D2260/403 (20130101); F05D2300/10 (20130101); F05D2300/603 (20130101);
F16D2001/103 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This specification is based upon and claims the benefit of priority from United Kingdom patent application number GB 2319474.9 filed on Dec. 19, 2023, the entire contents of which is incorporated herein by reference.

BACKGROUND

Technical Field

[0002] The present disclosure relates to a gas turbine engine, and in particular, to a hybrid transmission component for a gas turbine engine.

Description of the Related Art

[0003] Use of a splined interface between a metallic coupling and a composite body is common in the design of hybrid composite/metallic driveline products e.g., hybrid drive shafts, gears, and transmission components. In a gas turbine, such transmission components transmit a torque between one or more components. For example, a mainline shaft may transmit torque between a fan and a turbine of the gas turbine engine. The mainline shaft may be subjected to various types of loads during operation of the gas turbine engine. For example, the mainline shaft may be subjected to a limit load that may include the highest load that could be generated during normal operation of the gas turbine engine. Further, the mainline shaft may be subjected to an ultimate load that may include a maximum load that could be generated during a fan blade off event or a fan seizure event, which may result in an increase in the application of high amounts of torque and bending load.

[0004] In hybrid transmission components, the metallic coupling may contain a male or a female spline toothed arrangement. In both cases, roots of the splined teeth are in interference fit at a joint with the composite body, with the spline teeth cutting into a surface of the composite body. Load carrying capability, fatigue properties, and any deformation of the area around the joint of the metallic coupling and the composite body are dependent upon a level of interface pressure at the joint between the metallic coupling and the composite body. The interface pressure is primarily driven by the designed level of interference fit, however, variables within manufacturing and assembly processes may cause the actual interface pressure to be unpredictable.

[0005] For gas turbine engines in aerospace applications, load intensity is significantly higher resulting in larger diameter, longer interfaces with more spline teeth, and the higher interface pressures. The manufacturing variation may be magnified by the larger scale interfaces. This may result in an unacceptably high level of variation in the mechanical behaviour of the component (i.e., the hybrid transmission component).

[0006] Generally, a design or geometry of the spline teeth is such that a leading end (cutting end) of each spline tooth from the spline teeth is adapted to engage with and centralise the composite body prior to engagement of the leading end of each spline tooth with a face of the composite body to begin the cut. One of the limitations of conventional designs of the metallic coupling is that a design of the leading end of each spline tooth results in an inefficient cutting action as the spline teeth cuts into the composite body.

[0007] In such conventionally designed metallic couplings, the leading end may cause debris generated by cutting of the composite body to be pushed to the interface rather than ejecting it from

the interface. Moreover, an angle of the cutting face (i.e., leading end) directs the cutting force away from the surface of the composite body, thereby acting to shear and lift out the debris from the cut. The debris may get trapped within the interface thereby increasing the effective interface pressure and causing excessive wear on the leading (cutting) end of the spline teeth. In other words, the debris trapped within the interface may increase variation in the interface pressure which may further cause excessive wear on the leading (cutting) end of the spline teeth. In some cases, the debris from the composite body as well as abraded metallic from the worn metallic coupling are pulled into the interface thereby adding to the interface pressure by clogging the interface and by reducing cutting efficiency of the spline teeth.

[0008] Therefore, there is a need for an improved hybrid transmission component which may overcome the above-mentioned limitations.

SUMMARY

[0009] In a first aspect, a hybrid transmission component for a gas turbine engine is provided. The hybrid transmission component includes a composite body and a metallic coupling joined with the composite body and defining a longitudinal axis along its length. The metallic coupling includes an axial end surface, a circumferential surface circumferentially extending about the longitudinal axis, and a plurality of spline teeth extending from the circumferential surface and angularly separated from each other about the longitudinal axis. Each spline tooth from the plurality of spline teeth includes a root disposed adjacent to the circumferential surface, a tip distal to the circumferential surface, and a leading end disposed proximal to the axial end surface. Each spline tooth extends radially from the root to the tip with respect to the longitudinal axis. Each spline tooth extends axially from the leading end along the longitudinal axis. The leading end of each spline tooth includes a curved surface extending from the root and a planar surface extending from the curved surface to the tip. The curved surface curves inwardly from the root away from the axial end surface, such that the curved surface is concave with respect to the axial end surface. The planar surface is inclined obliquely to the longitudinal axis by a rake angle. During joining of the composite body with the metallic coupling, the composite body is moved relative to the metallic coupling in a joining direction that extends away from the axial end surface along the longitudinal axis. The leading end of each spline tooth is configured to cut the composite body during joining of the composite body with the metallic coupling. The hybrid transmission component may be a hybrid shaft or a hybrid gear.

[0010] Due to inclusion of the curved surface and the planar surface in the leading end of each spline tooth, a shape and geometry of the leading end of each spline tooth is optimised so as to ensure free ejection of debris (generated by cutting of the composite body) out of an interface between the spline tooth and the composite body. The proposed geometry of the leading end of each spline tooth shears and lifts the debris out of the interface that could otherwise increase an effective interface pressure and cause excessive wear on the leading end of the spline teeth. As the debris is not trapped within the interface, there is minimal variation in interface pressure thereby improving the load carrying capability and fatigue properties of the area around the joint of the metallic coupling and the composite body. This may also reduce any deformation near the interface which may further minimize any variations in the mechanical behaviour of the hybrid transmission component of the present disclosure. Moreover, the geometry and shape of the leading end of each spline tooth is selected so as to centralise the composite body before the leading end of each spline tooth engages with a face of the composite body to begin the cut.

[0011] In some embodiments, the curved surface is a circular arc having a transition radius. The curved surface in the form of the circular arc with the transition radius may provide the leading end of each spline tooth with the optimised geometry so as to minimize variations in the interface pressure between the spline teeth of the metallic coupling and the composite body.

[0012] In some embodiments, the metallic coupling further includes a chamfered surface extending between the axial end surface and the circumferential surface, such that the curved surface of the

leading end of each spline tooth extends from the chamfered surface. The chamfered surface is inclined obliquely to the longitudinal axis by a lead angle. This inclination of the chamfered surface to the longitudinal axis may contribute to centralise the composite body before the leading end of each spline tooth engages with the face of the composite body to begin the cut. In other words, the inclination of the chamfered surface to the longitudinal axis may improve centralisation of the mating parts (i.e., the metallic coupling and the composite body) during assembly of the hybrid transmission component.

[0013] In some embodiments, the lead angle is from 30 degrees to 45 degrees. In some applications, the lead angle of about 30 degrees may be an ideal inclination of the chamfered surface to the longitudinal axis for desirable centring the mating parts. The lead angle of about 45 degrees may be suitable for applications where the spline teeth are deeper and therefore generate a larger quantity of composite debris. Further, higher values (about 45 degrees) of the lead angle may provide less restriction to the ejection of the debris from the composite body.

[0014] In some embodiments, the rake angle is from 55 degrees to 85 degrees. Such a range of the rake angle may ensure that the leading end of each spline tooth directs a cutting force away from the composite body acting to shear and lift out the debris from the interface. The rake angle may be selected based on cutting characteristics of a material of the composite body. For reduced shear length and lower press fitting loads, the rake angle may be from 55 degrees to 64 degrees. For braided composite body with a high tensile strength and for requirement of a stronger spline tooth, the rake angle may be from 76 degrees to 85 degrees.

[0015] In some embodiments, each spline tooth tapers from the root to the tip. The tapered profile of each spline tooth from the root to the tip may enhance cutting of a surface of the composite body by the spline teeth.

[0016] In some embodiments, the root of each spline tooth forms an interference fit with the composite body. In other words, during joining of the composite body and the metallic coupling, the root of each spline tooth forms the interference fit with the composite body, with each spline tooth cutting into the surface of the composite body.

[0017] In some embodiments, the metallic coupling further includes a main body forming the circumferential surface and the axial end surface, such that each spline tooth is disposed on the main body. Each spline tooth at least partially defines at least one groove that extends from the tip of the spline tooth, beyond the root of the spline tooth, into the main body of the metallic coupling.

[0018] Each of the at least one groove may act as a new cutting edge/end for cutting the composite body. Further, the at least one groove may serve to clean out and recut the composite body as the composite body is inserted past the at least one groove. Therefore, this recutting action provided by the at least one groove may enhance the reduction of the variation in the interface pressure between the spline teeth of the metallic coupling and the composite body. Moreover, extension of the at least one groove of each spline tooth beyond the corresponding root may form a cavity within the main body of the metallic coupling and such cavity may act as a container or a storage space for collection of debris during insertion of the composite body along the joining direction. This may prevent the debris from being recirculated into the interface.

[0019] In some embodiments, the at least one groove includes a plurality of grooves axially spaced apart from each other with respect to the longitudinal axis. The plurality of grooves defined on each spline tooth of the metallic coupling may be advantageous for applications where there is a need of a lot of recutting of the composite body as the composite body is inserted along the joining direction in order to be joined with the metallic coupling.

[0020] In some embodiments, an axial distance between adjacent grooves from the plurality of grooves along the longitudinal axis progressively increases along the joining direction. This may be advantageous so as to balance the interface pressure because the wear of each spline tooth would be higher on the grooves positioned closer to the leading end.

[0021] In some embodiments, each spline tooth includes at least one spline groove that extends

from the tip of the spline tooth to the root of the spline tooth. The composite body includes at least one body groove that is aligned with the spline groove of each spline tooth after the composite body is joined with the metallic coupling. The inclusion of the at least one body groove in addition to the at least one spline groove may be advantageous in cases where the debris generated during joining of the metallic coupling and the composite body could end up entering into the interface between the spline tooth and the composite body. During assembly of the metallic spline and the composite body, as the at least one body groove is aligned with the spline groove of each spline tooth, the at least one body groove acts as a container or a storage space for debris which was pushed down into the interface by cutting action of each spline tooth.

[0022] In some embodiments, the at least one spline groove includes a plurality of spline grooves axially spaced apart from each other with respect to the longitudinal axis. The at least one body groove includes a plurality of body grooves corresponding to the plurality of spline grooves. Each body groove is aligned with a corresponding spline groove from the plurality of body grooves after the composite body is joined with the metallic coupling. The plurality of body grooves and the corresponding plurality of spline grooves may be advantageous for applications where there is a need of a lot of recutting of the composite body as the composite body is inserted along the joining direction in order to be joined with the metallic coupling. During assembly of the metallic spline and the composite body, as each body groove is aligned with the corresponding spline groove after the composite body is joined with the metallic coupling, each body groove acts as a container or a storage space for debris which was pushed down into the interface by cutting action of each spline tooth.

[0023] In some embodiments, an axial distance between adjacent spline grooves from the plurality of spline grooves along the longitudinal axis progressively increases along the joining direction. This may be advantageous so as to balance the interface pressure because the wear of each spline tooth would be higher on the spline grooves positioned closer to the leading end.

[0024] In some embodiments, the metallic coupling further includes an overhang portion axially extending from the axial end surface along the longitudinal axis opposite to the joining direction. The overhang portion includes an overhang end surface distal to the axial end surface. Each spline tooth extends axially along the overhang portion, such that the leading end of each spline tooth is disposed adjacent to the overhang end surface. The overhang portion increases a length of the metallic coupling in the direction opposite to the joining direction. During joining of the metallic coupling and the composite body, maximum wear is observed in an initial 5% of the length of each spline tooth, when viewed from the leading end of each spline tooth. The overhang portion may remove any interference fit from the maximum worn portion of the metallic coupling thereby avoiding any local increase in the interface pressure between the metallic coupling and the composite body. In some cases, the overhang portion may be machined away or removed after joining of the composite body and the metallic coupling.

[0025] In some embodiments, the metallic coupling is annular, such that the circumferential surface is a radially inner circumferential surface of the metallic coupling. The composite body is at least partially received within the radially inner circumferential surface. Therefore, the metallic coupling is a female spline toothed arrangement, and the composite body is a male arrangement. In such applications, the metallic coupling is disposed on an outer diameter of the composite body.

[0026] In some embodiments, the circumferential surface is an outer circumferential surface of the metallic coupling. The composite body is at least partially received on the outer circumferential surface. Therefore, the metallic coupling is a male spline toothed arrangement, and the composite body is a female arrangement. In such applications, the metallic coupling is disposed in a bore of the composite body to assemble the hybrid transmission component.

[0027] In a second aspect a gas turbine engine that includes the hybrid transmission component of the first aspect is provided.

[0028] Such a gas turbine engine may comprise an engine core comprising a turbine, a combustor,

a compressor, and a core shaft connecting the turbine to the compressor. Such a gas turbine engine may comprise a fan (having fan blades) located upstream of the engine core.

[0029] Arrangements of the present disclosure may be particularly, although not exclusively, beneficial for fans that are driven via a gearbox. Accordingly, the gas turbine engine may comprise a gearbox that receives an input from the core shaft and outputs drive to the fan so as to drive the fan at a lower rotational speed than the core shaft. The input to the gearbox may be directly from the core shaft, or indirectly from the core shaft, for example via a spur shaft and/or gear. The core shaft may rigidly connect the turbine and the compressor, such that the turbine and compressor rotate at the same speed (with the fan rotating at a lower speed). The gearbox may be a reduction gearbox (in that the output to the fan is a lower rotational rate than the input from the core shaft). Any type of gearbox may be used.

[0030] The gas turbine engine as described and/or claimed herein may have any suitable general architecture. For example, the gas turbine engine may have any desired number of shafts that connect turbines and compressors, for example one, two or three shafts. Purely by way of example, the turbine connected to the core shaft may be a first turbine, the compressor connected to the core shaft may be a first compressor, and the core shaft may be a first core shaft. The engine core may further comprise a second turbine, a second compressor, and a second core shaft connecting the second turbine to the second compressor. The second turbine, second compressor, and second core shaft may be arranged to rotate at a higher rotational speed than the first core shaft.

[0031] In such an arrangement, the second compressor may be positioned axially downstream of the first compressor. The second compressor may be arranged to receive (for example directly receive, for example via a generally annular duct) flow from the first compressor.

[0032] In any gas turbine engine as described and/or claimed herein, a combustor may be provided axially downstream of the fan and compressor(s). For example, the combustor may be directly downstream of (for example at the exit of) the second compressor, where a second compressor is provided. By way of further example, the flow at the exit to the combustor may be provided to the inlet of the second turbine, where a second turbine is provided. The combustor may be provided upstream of the turbine(s).

[0033] The or each compressor (for example the first compressor and second compressor as described above) may comprise any number of stages, for example multiple stages. Each stage may comprise a row of rotor blades and a row of stator vanes, which may be variable stator vanes (in that their angle of incidence may be variable). The row of rotor blades and the row of stator vanes may be axially offset from each other.

[0034] The or each turbine (for example the first turbine and second turbine as described above) may comprise any number of stages, for example multiple stages. Each stage may comprise a row of rotor blades and a row of stator vanes. The row of rotor blades and the row of stator vanes may be axially offset from each other.

[0035] Gas turbine engines in accordance with the present disclosure may have any desired bypass ratio, where the bypass ratio is defined as the ratio of the mass flow rate of the flow through the bypass duct to the mass flow rate of the flow through the core at cruise conditions. The bypass duct may be substantially annular. The bypass duct may be radially outside the engine core. The radially outer surface of the bypass duct may be defined by a nacelle and/or a fan case.

[0036] Specific thrust of an engine may be defined as the net thrust of the engine divided by the total mass flow through the engine. At cruise conditions, the specific thrust of an engine described and/or claimed herein may be less than (or in the order of) any of the following: 110 Nkg⁻¹ s, 105 Nkg⁻¹ s, 100 Nkg⁻¹ s, 95 Nkg⁻¹ s, 90 Nkg⁻¹ s, 85 Nkg⁻¹ s or 80 Nkg⁻¹ s. The specific thrust may be in an inclusive range bounded by any two of the values in the previous sentence (i.e., the values may form upper or lower bounds), for example in the range of from 80 Nkg⁻¹ s to 100 Nkg⁻¹ s, or 85 Nkg⁻¹ s to 95 Nkg⁻¹ s. Such engines may be particularly efficient in comparison with conventional gas turbine engines.

[0037] A fan blade and/or aerofoil portion of a fan blade described and/or claimed herein may be manufactured from any suitable material or combination of materials. For example, at least a part of the fan blade and/or aerofoil may be manufactured at least in part from a composite, for example a metal matrix composite and/or an organic matrix composite, such as carbon fibre.

[0038] The fan of a gas turbine as described and/or claimed herein may have any desired number of fan blades, for example 14, 16, 18, 20, 22, 24 or 26 fan blades.

[0039] The skilled person will appreciate that except where mutually exclusive, a feature or parameter described in relation to any one of the above aspects may be applied to any other aspect. Furthermore, except where mutually exclusive, any feature or parameter described herein may be applied to any aspect and/or combined with any other feature or parameter described herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0040] Embodiments will now be described by way of example only, with reference to the Figures, in which:

[0041] FIG. 1 is a schematic sectional side view of a gas turbine engine;

[0042] FIG. 2A is a partial sectional exploded view of a hybrid transmission component for the gas turbine engine of FIG. 1;

[0043] FIG. 2B is a partial sectional view of the hybrid transmission component of FIG. 2A, illustrating a joining of a composite body of the hybrid transmission component with a metallic coupling of the hybrid transmission component;

[0044] FIG. 3 is a partial perspective side view of the metallic coupling of the hybrid transmission component of FIGS. 2A and 2B;

[0045] FIG. 4 is a zoomed-in sectional view of a portion of the metallic coupling of FIG. 3;

[0046] FIG. 5 is a partial sectional view of a hybrid transmission component for the gas turbine engine of FIG. 1;

[0047] FIG. 6 is a partial sectional view of a hybrid transmission component for the gas turbine engine of FIG. 1;

[0048] FIG. 7 is a partial sectional view of a hybrid transmission component for the gas turbine engine of FIG. 1;

[0049] FIG. 8 is a partial sectional view of a hybrid transmission component for the gas turbine engine of FIG. 1;

[0050] FIG. 9 is a partial sectional view of a hybrid transmission component for the gas turbine engine of FIG. 1; and

[0051] FIG. 10 is a partial exploded view of a hybrid transmission component for the gas turbine engine of FIG. 1.

DETAILED DESCRIPTION

[0052] Aspects and embodiments of the present disclosure will now be discussed with reference to the accompanying Figures. Further aspects and embodiments will be apparent to those skilled in the art.

[0053] FIG. 1 illustrates a gas turbine engine 10 having a principal rotational axis 9. The engine 10 comprises an air intake 12 and a propulsive fan 23 that generates two airflows: a core airflow A and a bypass airflow B. The gas turbine engine 10 comprises an engine core 11 that receives the core airflow A. The engine core 11 comprises, in axial flow series, a low pressure compressor 14, a high pressure compressor 15, a combustion equipment 16, a high pressure turbine 17, a low pressure turbine 19, and a core exhaust nozzle 20. A nacelle 21 surrounds the gas turbine engine 10 and defines a bypass duct 22 and a bypass exhaust nozzle 18. The bypass airflow B flows through the bypass duct 22. The fan 23 is attached to and driven by the low pressure turbine 19 via a shaft 26

and an epicyclic gearbox **30**.

[0054] In use, the core airflow **A** is accelerated and compressed by the low pressure compressor **14** and directed into the high pressure compressor **15** where further compression takes place. The compressed air exhausted from the high pressure compressor **15** is directed into the combustion equipment **16** where it is mixed with fuel and the mixture is combusted. The resultant hot combustion products then expand through, and thereby drive, the high pressure and low pressure turbines **17**, **19** before being exhausted through the core exhaust nozzle **20** to provide some propulsive thrust. The high pressure turbine **17** drives the high pressure compressor **15** by a suitable interconnecting shaft **27**. The fan **23** generally provides the majority of the propulsive thrust. The epicyclic gearbox **30** is a reduction gearbox.

[0055] Note that the terms “low pressure turbine” and “low pressure compressor” as used herein may be taken to mean the lowest pressure turbine stages and lowest pressure compressor stages (i.e., not including the fan **23**) respectively and/or the turbine and compressor stages that are connected together by the interconnecting shaft **26** with the lowest rotational speed in the engine **10** (i.e., not including the gearbox output shaft that drives the fan **23**). In some literature, the “low pressure turbine” and “low pressure compressor” referred to herein may alternatively be known as the “intermediate pressure turbine” and “intermediate pressure compressor”. Where such alternative nomenclature is used, the fan **23** may be referred to as a first, or lowest pressure, compression stage.

[0056] Other gas turbine engines to which the present disclosure may be applied may have alternative configurations. For example, such engines may have an alternative number of compressors and/or turbines and/or an alternative number of interconnecting shafts. By way of further example, the gas turbine engine shown in FIG. **1** has a split flow nozzle **18**, **20** meaning that the flow through the bypass duct **22** has its own nozzle **18** that is separate to and radially outside the core exhaust nozzle **20**. However, this is not limiting, and any aspect of the present disclosure may also apply to engines in which the flow through the bypass duct **22** and the flow through the core **11** are mixed, or combined, before (or upstream of) a single nozzle, which may be referred to as a mixed flow nozzle. One or both nozzles (whether mixed or split flow) may have a fixed or variable area. Whilst the described example relates to a turbofan engine, the disclosure may apply, for example, to any type of gas turbine engine, such as an open rotor (in which the fan stage is not surrounded by a nacelle) or turboprop engine, for example. In some arrangements, the gas turbine engine **10** may not comprise a gearbox **30**.

[0057] The geometry of the gas turbine engine **10**, and components thereof, is defined by a conventional axis system, comprising an axial direction (which is aligned with the rotational axis **9**), a radial direction (in the bottom-to-top direction in FIG. **1**), and a circumferential direction (perpendicular to the page in the FIG. **1** view). The axial, radial, and circumferential directions are mutually perpendicular.

[0058] In addition, the present disclosure is equally applicable to aero gas turbine engines, marine gas turbine engines, and land-based gas turbine engines.

[0059] FIG. **2A** shows a partial sectional exploded view of a hybrid transmission component **100** for the gas turbine engine **10** (shown in FIG. **1**), according to an embodiment of the present disclosure. FIG. **2B** shows a partial sectional view of the hybrid transmission component **100**, illustrating a joining of a composite body **102** of the hybrid transmission component **100** with a metallic coupling **104** of the hybrid transmission component **100**, according to an embodiment of the present disclosure. FIG. **3** shows a partial perspective side view of the metallic coupling **104** of the hybrid transmission component **100**, according to an embodiment of the present disclosure.

[0060] It should be noted that the hybrid transmission component **100** described herein is not limited to use in geared engines, such as the gas turbine engine **10** having the gearbox **30**.

Accordingly, the hybrid transmission component **100** can be used in direct drive engines that do not include the gearbox **30**.

[0061] Referring to FIGS. 2A, 2B and 3, the hybrid transmission component **100** includes the composite body **102** and the metallic coupling **104** joined with the composite body **102**. The hybrid transmission component **100** may be a hybrid shaft or a hybrid gear. The composite body **102** may be a tube of composite material. The metallic coupling **104** defines a longitudinal axis **106** along its length. The metallic coupling **104** includes an axial end surface **112**, a circumferential surface **114** (shown in FIG. 3) circumferentially extending about the longitudinal axis **106**, and a plurality of spline teeth **120** extending from the circumferential surface **114** and angularly separated from each other about the longitudinal axis **106**. The metallic coupling **104** further includes a main body **110** forming the circumferential surface **114** and the axial end surface **112**, such that each spline tooth **120** from the plurality of spline teeth **120** is disposed on the main body **110**.

[0062] In the illustrated embodiment of FIGS. 2A, 2B, and 3, the metallic coupling **104** is annular, such that the circumferential surface **114** is a radially inner circumferential surface **114i** of the metallic coupling **104**. The composite body **102** is at least partially received within the radially inner circumferential surface **114i**. Therefore, the arrangement may be done in such a way that the metallic coupling **104** is a female part, and the composite body **102** is a male part. In such applications, the metallic coupling **104** is disposed on an outer diameter of the composite body **102**.

[0063] FIG. 4 is a zoomed-in sectional view of a portion of the metallic coupling **104**, according to an embodiment of the present disclosure. Referring to FIGS. 2A to 4, each spline tooth **120** from the plurality of spline teeth **120** includes a root **122** disposed adjacent to the circumferential surface **114**, a tip **124** distal to the circumferential surface **114**, and a leading end **126** disposed proximal to the axial end surface **112**. Each spline tooth **120** extends radially from the root **122** to the tip **124** with respect to the longitudinal axis **106**. Each spline tooth **120** extends axially from the leading end **126** along the longitudinal axis **106**.

[0064] Further, during joining of the composite body **102** with the metallic coupling **104**, the composite body **102** is moved relative to the metallic coupling **104** in a joining direction **108** that extends away from the axial end surface **112** along the longitudinal axis **106**. The leading end **126** of each spline tooth **120** is configured to cut the composite body **102** during joining of the composite body **102** with the metallic coupling **104**. Further, during joining of the composite body **102** with the metallic coupling **104**, the leading end **126** of each spline tooth **120** may engage with a face **116** of the composite body **102** at an interface **150**.

[0065] In some embodiments, the root **122** of each spline tooth **120** forms an interference fit with the composite body **102**. In other words, during joining of the composite body **102** and the metallic coupling **104**, the root **122** of each spline tooth **120** forms the interference fit with the composite body **102**, with each spline tooth **120** cutting into the surface of the composite body **102**.

[0066] The leading end **126** of each spline tooth **120** includes a curved surface **128** (shown in FIG. 4) extending from the root **122** and a planar surface **130** (shown in FIG. 4) extending from the curved surface **128** to the tip **124**. The curved surface **128** curves inwardly from the root **122** away from the axial end surface **112**, such that the curved surface **128** is concave with respect to the axial end surface **112**. The planar surface **130** is inclined obliquely to the longitudinal axis **106** by a rake angle α .

[0067] Due to inclusion of the curved surface **128** and the planar surface **130** in the leading end **126** of each spline tooth **120**, a shape and geometry of the leading end **126** of each spline tooth **120** is optimised so as to ensure free ejection of debris (generated by cutting of the composite body **102**) out of the interface **150** between the spline tooth **120** and the composite body **102**. The term “debris” may refer to the material removed from the composite body **102** during joining of the composite body **102** and the metallic coupling **104**.

[0068] The proposed geometry of the leading end **126** of each spline tooth **120** shears and lifts the debris out of the interface **150** that could otherwise increase an effective interface pressure and cause excessive wear on the leading end **126** of the spline teeth **120**. As the debris is not trapped within the interface **150**, there is minimal variation in interface pressure thereby improving the load

carrying capability and fatigue properties of the area around the joint of the metallic coupling **104** and the composite body **102**. This may also reduce any deformation near the interface **150** which may further minimize any variations in the mechanical behaviour of the hybrid transmission component **100**. Moreover, the geometry and shape of the leading end **126** of each spline tooth **120** is selected so as to centralise the composite body **102** before the leading end **126** end of each spline tooth **120** engages with the face **116** of the composite body **102** to begin the cut.

[0069] In some embodiments, the rake angle α is from 55 degrees to 85 degrees. Such a range of the rake angle α may ensure that the leading end **126** of each spline tooth **120** directs a cutting force away from the composite body **102** acting to shear and lift out the debris from the interface **150**.

The rake angle α may be selected based on cutting characteristics of a material of the composite body **102**. For reduced shear length and lower press fitting loads, the rake angle α may be from 55 degrees to 64 degrees. For braided composite body **102** with a high tensile strength and for requirement of a stronger spline tooth **120**, the rake angle α may be from 76 degrees to 85 degrees.

[0070] In some embodiments, the metallic coupling **104** further includes a chamfered surface **132** (shown in FIG. 4) extending between the axial end surface **112** and the circumferential surface **114**, such that the curved surface **128** of the leading end **126** of each spline tooth **120** extends from the chamfered surface **132**. The chamfered surface **132** is inclined obliquely to the longitudinal axis **106** by a lead angle β . This inclination of the chamfered surface **132** to the longitudinal axis **106** may contribute to centralise the composite body **102** before the leading end **126** of each spline tooth **120** engages with the face **116** of the composite body **102** to begin the cut. In other words, the inclination of the chamfered surface **132** to the longitudinal axis **106** may improve centralisation of the mating parts (i.e., the metallic coupling **104** and the composite body **102**) during assembly of the hybrid transmission component **100**.

[0071] In some embodiments, the lead angle β is from 30 degrees to 45 degrees. In some applications, the lead angle β of about 30 degrees may be an ideal inclination of the chamfered surface **132** to the longitudinal axis **106** for desirable centring the mating parts. The lead angle β of about 45 degrees may be suitable for applications where the spline teeth **120** are deeper and therefore generate a larger quantity of debris from the composite body **102**. Further, higher values (about 45 degrees) of the lead angle β may provide less restriction to the ejection of the debris from the composite body **102**.

[0072] In some embodiments, the curved surface **128** is a circular arc **A1** having a transition radius **R**. The curved surface **128** in the form of the circular arc **A1** with the transition radius **R** may provide the leading end **126** of each spline tooth **120** with the optimized geometry so as to minimize variations in the interface pressure between the spline teeth **120** of the metallic coupling **104** and the composite body **102**.

[0073] In some embodiments, each spline tooth **120** tapers from the root **122** to the tip **124**. The tapered profile of each spline tooth **120** from the root **122** to the tip **124** may enhance cutting of a surface of the composite body **102** by the spline teeth **120**.

[0074] FIG. 5 is a partial sectional view of a hybrid transmission component **200** for the gas turbine engine **10** of FIG. 1, according to another embodiment of the present disclosure. The hybrid transmission component **200** is substantially similar to the hybrid transmission component **100** of FIGS. 2A and 2B, with common components being referred to by the same numerals. However, in the hybrid transmission component **200** of FIG. 5, the metallic coupling **104** further includes an overhang portion **202** axially extending from the axial end surface **112** along the longitudinal axis **106** opposite to the joining direction **108**. The overhang portion **202** includes an overhang end surface **204** distal to the axial end surface **112**. Each spline tooth **120** extends axially along the overhang portion **202**, such that the leading end **126** of each spline tooth **120** is disposed adjacent to the overhang end surface **204**.

[0075] The overhang portion **202** increases a length of the metallic coupling **104** in the direction opposite to the joining direction **108**. During joining of the metallic coupling **104** and the

composite body **102**, maximum wear may be observed in an initial 5% of the length of each spline tooth **120**, when viewed from the leading end **126** of each spline tooth **120**. The overhang portion **202** may remove any interference fit from the maximum worn portion of the metallic coupling **104** thereby avoiding any local increase in the interface pressure between the metallic coupling **104** and the composite body **102**. In some cases, the overhang portion **202** may be machined away or removed after joining of the composite body **102** and the metallic coupling **104**.

[0076] FIG. **6** is a partial sectional view of a hybrid transmission component **300** for the gas turbine engine **10** of FIG. **1**, according to another embodiment of the present disclosure. The hybrid transmission component **300** is substantially similar to the hybrid transmission component **100** of FIGS. **2A** and **2B**, with common components being referred to by the same numerals. The hybrid transmission component **300** includes a metallic coupling **304** (instead of the metallic coupling **104** shown in FIG. **2A**). The metallic coupling **304** is substantially similar to the metallic coupling **104** shown in FIG. **2A**.

[0077] However, in the metallic coupling **304** of the hybrid transmission component **300**, each spline tooth **120** at least partially defines at least one groove **305** that extends from the tip **124** of the spline tooth **120**, beyond the root **122** of the spline tooth **120**, into the main body **110** of the metallic coupling **304**.

[0078] Each of the at least one groove **305** may act as a new cutting edge/end for cutting the composite body **102**. Further, the at least one groove **305** may serve to clean out and recut the composite body **102** as the composite body **102** is inserted past the at least one groove **305**. Therefore, this recutting action provided by the at least one groove **305** may enhance the reduction of the variation in the interface pressure between the spline teeth **120** of the metallic coupling **304** and the composite body **102**. Moreover, extension of the at least one groove **305** of each spline tooth **120** beyond the corresponding root **122** may form a cavity within the main body **110** of the metallic coupling **304** and such cavity may act as a container or a storage space for collection of debris during insertion of the composite body **102** along the joining direction **108**. This may prevent the debris from being recirculated into an interface (e.g., the interface **150** shown in FIG. **2B**) between the spline tooth **120** and the composite body **102**.

[0079] FIG. **7** is a partial sectional view of a hybrid transmission component **350** for the gas turbine engine **10** of FIG. **1**, according to another embodiment of the present disclosure. The hybrid transmission component **350** is substantially similar to the hybrid transmission component **300** of FIG. **6**, with common components being referred to by the same numerals. The hybrid transmission component **350** includes a metallic coupling **354** (instead of the metallic coupling **304** shown in FIG. **6**). The metallic coupling **354** is substantially similar to the metallic coupling **304** shown in FIG. **6**. However, in the metallic coupling **354** of the hybrid transmission component **350**, the at least one groove **305** includes a plurality of grooves **305** axially spaced apart from each other with respect to the longitudinal axis **106**. In the illustrated embodiment of FIG. **7**, the plurality of grooves **305** includes three grooves **305** in total. However, the plurality of grooves **305** may include more than three grooves **305** in total. The plurality of grooves **305** defined on each spline tooth **120** of the metallic coupling **354** may be advantageous for applications where there is a need of lot of recutting of the composite body **102** as the composite body **102** is inserted along the joining direction **108** in order to be joined with the metallic coupling **354**.

[0080] In some embodiments, an axial distance **D1** between adjacent grooves **305** from the plurality of grooves **305** along the longitudinal axis **106** progressively increases along the joining direction **108**. This may be advantageous so as to balance the interface pressure because the wear of each spline tooth **120** would be higher on the grooves **305** positioned closer to the leading end **126**.

[0081] FIG. **8** is a partial sectional view of a hybrid transmission component **400** for the gas turbine engine **10** of FIG. **1**, according to another embodiment of the present disclosure. The hybrid transmission component **400** is substantially similar to the hybrid transmission component **100** of

FIGS. 2A and 2B, with common components being referred to by the same numerals. However, the hybrid transmission component **400** includes a metallic coupling **404** (instead of the metallic coupling **104** shown in FIGS. 2A and 2B) and a composite body **402** (instead of the composite body **102** shown in FIGS. 2A and 2B). The metallic coupling **404** is substantially similar to the metallic coupling **104** shown in FIGS. 2A and 2B. Further, the composite body **402** is substantially similar to the composite body **102** shown in FIGS. 2A and 2B.

[0082] However, in the metallic coupling **404**, each spline tooth **120** includes at least one spline groove **405** that extends from the tip **124** of the spline tooth **120** to the root **122** of the spline tooth **120**. The composite body **402** includes at least one body groove **410** that is aligned with the spline groove **405** of each spline tooth **120** after the composite body **402** is joined with the metallic coupling **404**.

[0083] The inclusion of the at least one body groove **410** in addition to the at least one spline groove **405** may be advantageous in cases where the debris generated during joining of the metallic coupling **404** and the composite body **402** could end up entering into the interface (e.g., the interface **150** shown in FIG. 2B) between the spline tooth **120** and the composite body **402**. During assembly of the metallic coupling **404** and the composite body **402**, as the at least one body groove **410** is aligned with the spline groove **405** of each spline tooth **120**, the at least one body groove **410** acts as a container or a storage space for debris which was pushed down into the interface (e.g., the interface **150** shown in FIG. 2B) by cutting action of each spline tooth **120**.

[0084] FIG. 9 is a partial sectional view of a hybrid transmission component **500** for the gas turbine **10** of FIG. 1, according to another embodiment of the present disclosure. The hybrid transmission component **500** is substantially similar to the hybrid transmission component **400** of FIG. 8, with common components being referred to by the same numerals. However, the hybrid transmission component **500** includes a metallic coupling **504** (instead of the metallic coupling **404** shown in FIG. 8) and a composite body **502** (instead of the composite body **402** shown in FIG. 8). The metallic coupling **504** is substantially similar to the metallic coupling **404** shown in FIG. 8. Further, the composite body **502** is substantially similar to the composite body **402** shown in FIG. 8.

[0085] However, in the metallic coupling **504**, the at least one spline groove **405** includes a plurality of spline grooves **405** axially spaced apart from each other with respect to the longitudinal axis **106**. Moreover, in the composite body **502**, the at least one body groove **410** includes a plurality of body grooves **410** corresponding to the plurality of spline grooves **405**. In the illustrated embodiment of FIG. 9, the plurality of spline grooves **405** includes three spline grooves **405** in total and the plurality of body grooves **410** includes three body grooves **410** in total.

However, the plurality of spline grooves **405** may include more than three spline grooves **405** in total and the plurality of body grooves **410** may include more than three body grooves **410** in total. Each body groove **410** is aligned with a corresponding spline groove **405** from the plurality of spline grooves **405** after the composite body **502** is joined with the metallic coupling **504**.

[0086] The plurality of body grooves **410** and the corresponding plurality of spline grooves **405** may be advantageous for applications where there is a need of lot of recutting of the composite body **502** as the composite body **502** is inserted along the joining direction **108** in order to be joined with the metallic coupling **504**. During assembly of the metallic coupling **504** and the composite body **502**, as each body groove **410** is aligned with the corresponding spline groove **405** after the composite body **502** is joined with the metallic coupling **504**, each body groove **410** acts as a container or a storage space for debris which was pushed down into the interface by cutting action of each spline tooth **120**.

[0087] In some embodiments, an axial distance **D2** between adjacent spline grooves **405** from the plurality of spline grooves **405** along the longitudinal axis **106** progressively increases along the joining direction **108**. This may be advantageous so as to balance the interface pressure because the wear of each spline tooth **120** would be higher on the spline grooves **405** positioned closer to the leading end **126**.

[0088] FIG. 10 is a partial exploded view of a hybrid transmission component 600 for the gas turbine engine 10 of FIG. 1, according to another embodiment of the present disclosure. The hybrid transmission component 600 is substantially similar to the hybrid transmission component 100 of FIGS. 2A and 2B, with common components being referred to by the same numerals.

[0089] However, the hybrid transmission component 600 includes a metallic coupling 604 (instead of the metallic coupling 104 shown in FIG. 3) and a composite body 602 (instead of the composite body 102 shown in FIG. 2B). The metallic coupling 604 is substantially similar to the metallic coupling 104 shown in FIG. 3. Further, the composite body 602 is substantially similar to the composite body 102 shown in FIG. 2B.

[0090] However, in the hybrid transmission component 600, the circumferential surface 114 is an outer circumferential surface 1140 of the metallic coupling 604. Further, in the hybrid transmission component 600, the composite body 602 is at least partially received on the outer circumferential surface 1140. Therefore, in the embodiment of FIG. 10, the metallic coupling 604 is a male spline toothed arrangement, and the composite body 602 is a female arrangement. In such applications, the metallic coupling 604 is disposed in a bore 610 of the composite body 602 to assemble the hybrid transmission component 600.

[0091] It will be understood that the present disclosure is not limited to the embodiments above described and various modifications and improvements can be made without departing from the concepts described herein. Except where mutually exclusive, any of the features may be employed separately or in combination with any other features and the disclosure extends to and includes all combinations and sub-combinations of one or more features described herein.

Claims

1. A hybrid transmission component for a gas turbine engine, the hybrid transmission component comprising: a composite body; and a metallic coupling joined with the composite body and defining a longitudinal axis along its length, the metallic coupling comprising an axial end surface, a circumferential surface circumferentially extending about the longitudinal axis, and a plurality of spline teeth extending from the circumferential surface and angularly separated from each other about the longitudinal axis, wherein each spline tooth from the plurality of spline teeth comprises a root disposed adjacent to the circumferential surface, a tip distal to the circumferential surface, and a leading end disposed proximal to the axial end surface, wherein each spline tooth extends radially from the root to the tip with respect to the longitudinal axis, wherein each spline tooth extends axially from the leading end along the longitudinal axis, the leading end of each spline tooth comprising a curved surface extending from the root and a planar surface extending from the curved surface to the tip, wherein the curved surface curves inwardly from the root away from the axial end surface, such that the curved surface is concave with respect to the axial end surface, wherein the planar surface is inclined obliquely to the longitudinal axis by a rake angle, wherein, during joining of the composite body with the metallic coupling, the composite body is moved relative to the metallic coupling in a joining direction that extends away from the axial end surface along the longitudinal axis, and wherein the leading end of each spline tooth is configured to cut the composite body during joining of the composite body with the metallic coupling.

2. The hybrid transmission component of claim 1, wherein the curved surface is a circular arc having a transition radius.

3. The hybrid transmission component of claim 1, wherein the metallic coupling further comprises a chamfered surface extending between the axial end surface and the circumferential surface, such that the curved surface of the leading end of each spline tooth extends from the chamfered surface, and wherein the chamfered surface is inclined obliquely to the longitudinal axis by a lead angle.

4. The hybrid transmission component of claim 3, wherein the lead angle is from 30 degrees to 45 degrees.

5. The hybrid transmission component of claim 1, wherein the rake angle is from 55 degrees to 85 degrees.
 6. The hybrid transmission component of claim 1, wherein each spline tooth tapers from the root to the tip.
 7. The hybrid transmission component of claim 1, wherein the root of each spline tooth forms an interference fit with the composite body.
 8. The hybrid transmission component of claim 1, wherein the metallic coupling further comprises a main body forming the circumferential surface and the axial end surface, such that each spline tooth is disposed on the main body, and wherein each spline tooth at least partially defines at least one groove that extends from the tip of the spline tooth, beyond the root of the spline tooth, into the main body of the metallic coupling.
 9. The hybrid transmission component of claim 8, wherein the at least one groove comprises a plurality of grooves axially spaced apart from each other with respect to the longitudinal axis.
 10. The hybrid transmission component of claim 9, wherein an axial distance between adjacent grooves from the plurality of grooves along the longitudinal axis progressively increases along the joining direction.
 11. The hybrid transmission component of claim 1, wherein each spline tooth comprises at least one spline groove that extends from the tip of the spline tooth to the root of the spline tooth, and wherein the composite body comprises at least one body groove that is aligned with the at least one spline groove of each spline tooth after the composite body is joined with the metallic coupling.
 12. The hybrid transmission component of claim 11, wherein the at least one spline groove comprises a plurality of spline grooves axially spaced apart from each other with respect to the longitudinal axis, wherein the at least one body groove comprises a plurality of body grooves corresponding to the plurality of spline grooves, and wherein each body groove is aligned with a corresponding spline groove) from the plurality of spline grooves after the composite body is joined with the metallic coupling.
 13. The hybrid transmission component of claim 12, wherein an axial distance between adjacent spline grooves from the plurality of spline grooves along the longitudinal axis progressively increases along the joining direction.
 14. The hybrid transmission component of claim 1, wherein the metallic coupling further comprises an overhang portion axially extending from the axial end surface along the longitudinal axis opposite to the joining direction, wherein the overhang portion comprises an overhang end surface distal to the axial end surface, and wherein each spline tooth extends axially along the overhang portion, such that the leading end of each spline tooth is disposed adjacent to the overhang end surface.
 15. The hybrid transmission component of claim 1, wherein the metallic coupling is annular, such that the circumferential surface is a radially inner circumferential surface of the metallic coupling, and wherein the composite body is at least partially received within the radially inner circumferential surface.
 16. The hybrid transmission component of claim 1, wherein the circumferential surface is an outer circumferential surface of the metallic coupling, and wherein the composite body is at least partially received on the outer circumferential surface.
 17. A gas turbine engine that includes a hybrid transmission component of claim 1.
-