

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279502

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

GUO; Manyi et al.

BATTERY AND ELECTRICAL APPARATUS

Abstract

A battery and an electrical apparatus. The battery includes a plurality of rows of battery units and a heat exchange assembly. The plurality of rows of battery units are arranged in a first direction. Each row of battery units comprises a plurality of battery cells arranged in sequence in a second direction. Each battery cell includes a first side wall. The first side wall is the side wall with the largest area. The first direction and the second direction are perpendicular to each other. The heat exchange assembly includes a heat conducting plate. The heat conducting plate extends between adjacent rows of battery units. The heat conducting plate directly faces the first side walls of at least some of the adjacent battery cells of adjacent battery units.

Inventors: GUO; Manyi (Ningde, CN), LI; Ting (Ningde, CN)

Applicant: CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED (Ningde, CN)

Family ID: 89445479

Assignee: CONTEMPORARY AMPEREX TECHNOLOGY CO., LIMITED (Ningde, CN)

Appl. No.: 19/212746

Filed: May 20, 2025

Foreign Application Priority Data

CN

202321088892.6

May. 08, 2023

Related U.S. Application Data

parent WO continuation PCT/CN2023/132385 20231117 PENDING child US 19212746

Publication Classification

Int. Cl.: H01M10/6555 (20140101); H01M10/613 (20140101); H01M10/653 (20140101); H01M10/6556 (20140101); H01M10/659 (20140101); H01M50/204 (20210101); H01M50/244 (20210101); H01M50/291 (20210101)

U.S. Cl.:

CPC H01M10/6555 (20150401); H01M10/613 (20150401); H01M10/653 (20150401); H01M10/6556 (20150401); H01M10/659 (20150401); H01M50/244 (20210101); H01M50/291 (20210101); H01M50/204 (20210101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of International Patent Application No. PCT/CN2023/132385, filed on Nov. 17, 2023, which is proposed and claims priority to Chinese Patent Application No. 202321088892.6 filed May 8, 2023, each are incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] The present application relates to the technical field of batteries, and in particular, to a battery and an electrical apparatus.

BACKGROUND

[0003] In recent years, new energy vehicles have made a leap forward in development. In the field of electric vehicles, batteries, as power sources of electric vehicles, play an irreplaceable and important role. Typically, a battery includes a plurality of battery cells which are arranged in sequence. This causes a non-uniform force between the battery cells, which can easily lead to a battery cell failure.

SUMMARY

[0004] The present application provides a battery and an electrical apparatus, which can improve an anti-deformation ability of a first side wall of a battery cell, so as to reduce a probability of a battery cell failure caused by a non-uniform force on the battery cell and improve the reliability of the battery.

[0005] In a first aspect, an embodiment of the present application provides a battery. The battery includes: a plurality of rows of battery units, wherein the plurality of rows of battery units are arranged in a first direction; each row of battery units includes a plurality of battery cells arranged in sequence in a second direction; each battery cell includes a first side wall; the first side wall is the side wall with the largest area; the first direction and the second direction are perpendicular to each other; and a heat exchange assembly, wherein the heat exchange assembly includes a heat conducting plate; the heat conducting plate extends between adjacent rows of battery units; and the heat conducting plate directly faces the first side walls of at least some of the battery cells of adjacent battery units.

[0006] In the above technical solution, the heat conducting plate extends between the adjacent battery units, and the heat conducting plate directly faces the first side walls of at least some of the battery cells of the adjacent battery units, so that it is convenient to achieve a larger direct-facing area between the heat conducting plate and at least some of the battery cells of the adjacent battery units in the first direction, which is beneficial to enhancing the temperature control effect on the battery. Meanwhile, the heat conducting plate can play an enhancement role on the first side walls of at least some of the battery cells, so as to improve the anti-deformation ability of the first side walls of the corresponding battery cells, to reduce the probability of a failure of a battery cell caused by a non-uniform force on the battery cells, thereby improving the reliability of the battery.

[0007] In some embodiments, opposite side walls of the heat conducting plate are in contact with a plurality of first side walls opposite to each other.

[0008] In the above technical solution, the opposite side walls of the heat conducting plate are in contact with the plurality of first side walls opposite to each other, so that it is convenient to achieve the heat-conducting connection between the heat conducting plate and at least some of the first side walls of the adjacent battery units, and the structure of the battery is simplified.

Meanwhile, the side walls of the heat conducting plate can directly play a role of supporting the first side walls of the battery cells, to further improve the anti-deformation ability of the first side walls, thereby further improving the problem of a non-uniform force on the battery cells.

[0009] In some embodiments, a cavity for buffering a stress is provided inside the heat conducting plate.

[0010] In the above technical solution, the cavity for buffering the stress is provided inside the heat conducting plate, so that when the battery cells expand during use, due to the cavity, the heat conducting plate can deform when it is directly or indirectly subjected to a force of the battery cells, thereby reducing an extrusion force between the heat conducting plate and the battery cells, avoiding damage to the heat conducting plate and the battery cells, and helping to improve the reliability of the heat conducting plate and the reliability of the battery cells. Meanwhile, due to the arrangement of the cavity, it is convenient to absorb an assembling tolerance of the battery cells in rows in the process of assembling the heat conducting plate and the battery cells, thereby improving the convenience of assembling of the heat conducting plate and the battery cells.

Moreover, the arrangement of the cavity helps to reduce the weight of the heat conducting plate, thereby reducing the weight of the battery and helping to improve the weight energy density of the battery.

[0011] In some embodiments, a supporting assembly is arranged inside the cavity; the heat conducting plate includes two heat conducting side walls opposite to each other; the heat conducting side walls directly face the first side walls; the supporting assembly is respectively connected to the two heat conducting side walls; and the supporting assembly is configured to make a distance between the two heat conducting side walls variable.

[0012] In the above technical solution, the supporting assembly is arranged inside the cavity, and the supporting assembly is configured to make the distance between the two heat conducting side walls variable, so that the supporting assembly can play a role of supporting the two heat conducting side walls, thereby improving the anti-bending deformation ability and elastic recovery ability of the heat conducting plate, and improving the reliability of the heat conducting plate.

Meanwhile, the supporting assembly can also adapt to direct or indirect extrusion on the heat conducting plate caused by the expansion of the battery cells, to avoid an excessive extrusion force between the heat conducting plate and the battery cells.

[0013] In some embodiments, a plurality of separated sub-chambers are defined between the supporting assembly and at least one of the heat conducting side walls.

[0014] In the above technical solution, the plurality of separated sub-chambers are defined between the supporting assembly and at least one of the heat conducting side walls. The sub-chambers can provide an avoidance space for the deformation of the supporting assembly and/or the heat conducting side wall, so that while supporting the heat conducting side walls, the supporting assembly can balance the anti-bending deformation ability, elastic deformation ability, and elastic recovery ability of the heat conducting side wall. Meanwhile, the weight of the supporting assembly cannot be excessively increased, which is beneficial to avoiding an excessive increase in the weight of the heat exchange assembly and facilitates improving the weight energy density of the battery.

[0015] In some embodiments, on a cross section parallel to the first direction and a second direction, a cross section of each of the sub-chambers is a triangle.

[0016] In the above technical solution, since the cross section of each sub-chamber is the triangle, it

is beneficial to simplifying the structure of the supporting assembly and simplifying the connection between the supporting assembly and each heat conducting side wall. Meanwhile, it is convenient for the supporting assembly to have a good elastic deformation ability and a good elastic recovery ability, so that the distance between the two heat conducting side walls can better adapt to the expansion deformation of the battery cells.

[0017] In some embodiments, the cavity is filled with a heat absorption material.

[0018] In the above technical solution, since the heat absorption material is arranged inside the cavity, it is beneficial to improving the heat exchange capability of the heat exchange assembly and facilitates improving the heat management effect on the battery cells.

[0019] In some embodiments, the heat absorption material is a solid-liquid phase change material.

[0020] In the above technical solution, since the heat absorption material is the solid-liquid phase change material, the phase change material undergoes a solid-liquid phase change at a high temperature and absorbs heat at the same time, to further improve the heat absorption and heat conduction capabilities of the heat exchange assembly and improve the temperature control capability of the battery.

[0021] In some embodiments, the battery further includes a box body, wherein the plurality of rows of battery units are arranged in the box body; and the heat conducting plate is fixed to the box body.

[0022] In the above technical solution, by the arrangement of the box body, a protection effect can be achieved on the plurality of rows of battery units and the heat conducting plate. Fixing the heat conducting plate to the box body is beneficial to improving the structural reliability of the battery. Moreover, the box body can play a limiting role on the battery units through the heat conducting plate, to achieve stable arrangement of the battery units.

[0023] In some embodiments, the heat exchange assembly further includes a heat exchange plate; in a third direction, the heat exchange plate is located on one side of the plurality of rows of battery units; the third direction is perpendicular to the first direction and the second direction respectively; and the heat conducting plate is arranged on a surface of the heat exchange plate facing the battery units and is in heat-conducting connection to the heat exchange plate.

[0024] In the above technical solution, by the arrangement of the heat exchange plate, the heat exchange plate is in heat-conducting connection to the heat conducting plate, so that the heat exchange plate can at least exchange heat with the battery cells through the heat conducting plate, so as to further reduce heat transferred from a battery cell to another single battery cell, thereby inhibiting thermal spread.

[0025] In some embodiments, the heat conducting plate is a solid metal plate.

[0026] In the above technical solution, since the heat conducting plate is the solid metal plate, it is convenient to simplify the structure and processing procedures of the heat conducting plate, and meanwhile, it is convenient to ensure the heat conduction capability of the heat conducting plate.

[0027] In some embodiments, a thermally conductive adhesive layer is arranged between the heat conducting plate and the battery cells.

[0028] In the above technical solution, since the thermally conductive adhesive layer is arranged between the heat conducting plate and the battery cells, the thermally conductive adhesive layer is arranged between the heat conducting plate and the first side walls, thereby effectively achieving the heat-conducting connection between the heat conducting plate and the battery cells, facilitating improving the heat transfer efficiency for the heat conducting plate and the battery cells, and enhancing the temperature control effect on the battery. Moreover, the heat conducting plate can also play an enhancement role on the first side walls of the corresponding battery cells to an extent, thereby improving the problem of a non-uniform force on the battery cells.

[0029] In some embodiments, the heat exchange plate and the heat conducting plate are integrated structural members.

[0030] In the above technical solution, since the heat conducting plate and the heat exchange plate are the integrated structural members, it is convenient to improve the strength of the heat

conducting plate and the strength of the heat exchange plate, save connection procedures for the heat conducting plate and the heat exchange plate, and improve the assembling efficiency of the battery. Meanwhile, it is conducive to improving the heat transfer efficiency for the heat conducting plate and the heat exchange plate to an extent.

[0031] In some embodiments, the first side walls of at least two adjacent rows of the battery units are staggered in the second direction, and at least a portion of the heat conducting plate is located between the staggered battery units.

[0032] In the above technical solution, since the first side walls of the at least two adjacent rows of battery units are staggered in the second direction, it is beneficial to making full use of an arrangement space of the battery and improving the adaptability of the plurality of battery cells to arrangement spaces in different shapes. Meanwhile, for two battery cells that are staggered, an amount of heat transferred from any one of the battery cells to the other battery cell can be reduced, thereby achieving a purpose of inhibiting thermal spread, which is beneficial to improving the reliability of use of the battery.

[0033] In a second aspect, an embodiment of the present application provides an electrical apparatus, including the above battery.

[0034] In the above technical solution, since the above battery is arranged in the electrical apparatus, and the heat conducting plate can improve the anti-deformation ability of the first side walls of the battery, it is beneficial to improving the reliability of the electrical apparatus.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0035] These and other aspects and advantages of embodiments of the present application will become apparent and more readily appreciated from the following descriptions made with reference to the drawings. Where:

[0036] FIG. 1 is a schematic structural diagram of a vehicle according to some embodiments of the present application;

[0037] FIG. 2 is an exploded view of a structure of a battery according to some embodiments of the present application;

[0038] FIG. 3 is a schematic structural diagram of a battery cell according to some embodiments of the present application;

[0039] FIG. 4 is a schematic structural diagram of a heat exchange assembly according to some embodiments of the present application;

[0040] FIG. 5 is a schematic diagram of a heat exchange plate shown in FIG. 4;

[0041] FIG. 6 is a schematic structural diagram of a battery according to some embodiments of the present application;

[0042] FIG. 7 is another schematic diagram of the battery shown in FIG. 6;

[0043] FIG. 8 is a sectional view of the battery shown in FIG. 6;

[0044] FIG. 9 is a sectional view of a battery according to some embodiments of the present application;

[0045] FIG. 10 is a sectional view of a heat conducting plate according to some embodiments of the present application;

[0046] FIG. 11 is a sectional view of a heat conducting plate according to some embodiments of the present application;

[0047] FIG. 12 is a sectional view of a heat conducting plate according to some embodiments of the present application;

[0048] FIG. 13 is a schematic diagram of an orthographic projection of two first side walls that are staggered according to some embodiments of the present application;

[0049] FIG. **14** is a schematic structural diagram of a battery according to some embodiments of the present application; and

[0050] FIG. **15** is an enlarged view of circle A in FIG. **14**.

[0051] Numerals in the accompanying drawings:

[0052] electrical apparatus **1000**, battery **200**, controller **300**, motor **400**,

[0053] first direction X, second direction Y, third direction Z, first region $\Omega 1$, second region $\Omega 2$, third region $\Omega 3$,

[0054] battery cell **10**, battery unit **10A**, first side wall **111**, second side wall **112**, terminal post **12**,

[0055] box body **30**, first box body **301**, second box body **302**,

[0056] heat conducting plate **70**, cavity **70a**, sub-chamber **70b**, heat conducting side wall **71**, supporting assembly **80**, heat absorption material **90**, heat exchange plate **100**, and heat exchange assembly **140**.

DETAILED DESCRIPTION

[0057] In order to make the objects, technical solutions and advantages of embodiments of the present application clearer, the technical solutions in the embodiments of the present application will be clearly described below with reference to the drawings for the embodiments of the present application. Apparently, the described embodiments are some of, rather than all of, the embodiments of the present application. All the other embodiments obtained by a person of ordinary skill in the art based on the embodiments of the present application without any creative effort shall fall within the scope of protection of the present application.

[0058] Unless otherwise defined, all technical and scientific terms used in the present application shall have the same meanings as those generally understood by those skilled in the art of the present application. The terms used in the present application in the specification of application are merely for the purpose of describing specific embodiments and are not intended to limit the present application. The terms “include” and “have” and any variations thereof in the specification and claims and the above brief description of the drawings of the present application are intended to cover non-exclusive inclusion. The terms “first,” “second,” etc. in the specification and the claims of the present application as well as the above drawings are used to distinguish different objects, rather than to describe a specific order or primary-secondary relationship.

[0059] The phrase “embodiment” referred to in the present application means that the descriptions of specific features, structures, and characteristics in combination with the embodiment are included in at least one embodiment of the present application. The appearances of the phrase in various places in the specification neither necessarily refer to a same embodiment, nor are independent or alternative embodiments mutually exclusive with other embodiments.

[0060] In the present application, the term “and/or” is only an association relationship for describing associated objects, indicating that three relationships may exist. For example, A and/or B may represent three situations: A exists alone, both A and B exist, and B exists alone. In addition, the character “/” in the present application generally means that the associated objects before and after it are in an “or” relationship.

[0061] In the embodiments of the present application, the same reference signs denote the same components, and for the sake of brevity, detailed descriptions of the same components are omitted in different embodiments. It should be understood that the thickness, length, width and other dimensions of the various components in the embodiments of the present application shown in the drawings, as well as the overall thickness, length, width and other dimensions of an integrated apparatus, are for illustrative purposes only, and should not constitute any limitation to the present application.

[0062] In the present application, the phrase “a plurality of” means two or more.

[0063] In the present application, the battery cell may include a lithium-ion secondary battery, a lithium-ion primary battery, a lithium sulfur battery, a sodium lithium-ion battery, a sodium-ion battery or a magnesium-ion battery and so on. This is not limited in the embodiments of the present

application. The battery cell may be in a cylindrical shape, a flat shape, a cuboid shape or another shape, which is also not limited in the embodiments of the present application. Battery cells are generally divided into three kinds according to packaging manners: cylindrical battery cells, square battery cells, and pouch cells. The embodiments of the present application do not limit this.

[0064] A battery mentioned in the embodiments of the present application refers to a single physical module including a plurality of battery cells to provide a higher voltage and capacity. For example, the battery mentioned in the present application may be a battery module, a battery pack, or the like. The battery module usually includes a plurality of battery cells. The battery usually includes a box body for encapsulating the plurality of battery cells or a plurality of battery modules. The box body can avoid liquid or other foreign matters from affecting charging or discharging of the battery cells. Certainly, the battery may not include the box body.

[0065] Exemplarily, a battery cell may generally include a case, a battery cell assembly, and an electrolyte solution. The case is configured to accommodate the battery cell assembly and the electrolyte solution, and at least one positive electrode terminal post and at least one negative electrode terminal post are arranged on the case. The battery cell assembly includes one or more electrode assemblies, and each electrode assembly is formed by stacking or winding a positive electrode plate, a negative electrode plate, and a separator.

[0066] The positive electrode plate usually includes a positive electrode current collector and a positive electrode active material layer. The positive electrode active material layer is coated on the positive electrode current collector directly or indirectly. The positive electrode current collector not coated with the positive electrode active material layer protrudes out of the positive electrode current collector coated with the positive electrode active material layer, and the positive electrode current collector not coated with the positive electrode active material layer serves as a positive tab. A plurality of positive tabs are stacked together and are electrically connected to the positive electrode terminal post. For example, the plurality of stacked positive tabs can be directly welded to the positive electrode terminal post to form an electrical connection. Alternatively, the battery cell assembly may further include a positive electrode adapter plate. The plurality of stacked positive tabs are welded to one end of the positive electrode adapter plate, and the other end of the positive electrode adapter plate is welded to the positive electrode terminal post, to form an electrical connection between the positive tabs and the positive electrode terminal post.

[0067] The negative electrode plate includes a negative electrode current collector and a negative electrode active material layer. The negative electrode active material layer is coated on the surface of the negative electrode current collector. The negative electrode current collector not coated with the negative electrode active material layer protrudes out of the negative electrode current collector coated with the negative electrode active material layer, and the negative electrode current collector not coated with the negative electrode active material layer serves as a negative tab. A plurality of negative tabs are stacked together and are electrically connected to the negative electrode terminal post. For example, the plurality of stacked negative tabs can be directly welded to the negative electrode terminal post to form an electrical connection. Alternatively, the battery cell assembly may further include a negative electrode adapter plate. The plurality of stacked negative tabs are welded to one end of the negative electrode adapter plate, and the other end of the negative electrode adapter plate is welded to the negative electrode terminal post, to form an electrical connection between the negative tabs and the negative electrode terminal post. A material of the separator is not limited, and may be polypropylene, polyethylene, or the like.

[0068] In recent years, new energy vehicles have made a leap forward in development. In the field of electric vehicles, batteries, as power sources of electric vehicles, play an irreplaceable and important role. The batteries, as core components of the new energy vehicles, have high requirements for energy densities and reliability.

[0069] In the related art, a battery includes a plurality of battery cells which are arranged in sequence. This causes a non-uniform force between the battery cells, which can easily lead to a

battery cell failure.

[0070] Based on the above considerations, in order to improve the problem of a non-uniform force between battery cells, a battery is provided. The battery includes: a plurality of rows of battery units and a heat exchange assembly. The plurality of rows of battery units are arranged in a first direction. Each row of battery units includes a plurality of battery cells arranged in sequence in a second direction. Each battery cell includes a first side wall. The first side wall is the side wall with the largest area. The first direction and the second direction are perpendicular to each other. The heat exchange assembly includes a heat conducting plate. The heat conducting plate extends between adjacent rows of battery units. The heat conducting plate directly faces the first side walls of at least some of the battery cells of adjacent battery units.

[0071] In the above technical solution, the heat conducting plate extends between the adjacent battery units, and the heat conducting plate directly faces the first side walls of at least some of the battery cells of the adjacent battery units, so that it is convenient to achieve a larger direct-facing area between the heat conducting plate and at least some of the battery cells of the adjacent battery units in the first direction, which is beneficial to enhancing the temperature control effect on the battery. Meanwhile, the heat conducting plate can play an enhancement role on the first side walls of at least some of the battery cells, so as to improve the anti-deformation ability of the first side walls of the corresponding battery cells, to reduce the probability of a failure of a battery cell caused by a non-uniform force on the battery cells, thereby improving the reliability of the battery.

[0072] Embodiments of the present application provide an electrical apparatus that uses a battery of the present disclosure as a power source, and the electrical apparatus may be, but is not limited to, a mobile phone, a tablet, a notebook, an electric toy, an electric tool, a battery vehicle, an electric vehicle, a ship, a spacecraft, and the like. The electric toy may include fixed or mobile electric toys, such as a game machine, an electric vehicle toy, an electric ship toy, and an electric airplane toy. The spacecraft may include an airplane, a rocket, a space shuttle, a spaceship, and the like.

[0073] For convenience of explanation, the following embodiments take the electrical apparatus **1000** being a vehicle as an example, and describe in detail structures of the electrical apparatus **1000**, a battery **200**, and a battery cell **10** of the present application.

[0074] Referring to FIG. 1, FIG. 1 is a schematic structural diagram of an electrical apparatus **1000** according to some embodiments of the present application. The vehicle may be a fuel vehicle, a gas vehicle, or a new energy vehicle, and the new energy vehicle may be a battery electric vehicle, a hybrid electric vehicle, an extended range vehicle, or the like. A battery **200** is arranged in the vehicle. The battery **200** may be arranged at a bottom or head or tail of the vehicle. The battery **200** may be configured to supply power the vehicle. For example, the battery **200** may be used as an operating power source of the vehicle. The vehicle may further include a controller **300** and a motor **400**. The controller **300** is configured to control the battery **200** to supply power to the motor **400**, for example, to meet a demand for working power during starting, navigation, and driving of the vehicle. In some embodiments of the present application, the battery **200** not only may serve as the operating power source of the vehicle, but also may serve as a driving power source of the vehicle, thus replacing or partially replacing fuel or natural gas to provide driving power for the vehicle.

[0075] Referring to FIG. 2, FIG. 2 is an exploded view of a structure of a battery cell **10** used in a battery **200** according to some embodiments of the present application. The battery **200** includes a box body **30** and a plurality of battery cells **10**. The battery cells **10** are accommodated in the box body **30**. The box body **30** is configured to provide an accommodating space for the battery cells, and the box body **30** may be of various structures. In some embodiments, the box body **30** may include a first box body **301** and a second box body part **302**. The first box body **301** is covered with the second box body **302**. The first box body **301** and the second box body **302** jointly define an accommodating space configured to accommodate the battery cells. The second box body **302** may be of a hollow structure with one end opened. The first box body **301** may be of a platy

structure. The first box body **301** is covered at an open side of the second box body **302**, to enable the first box body **301** and the second box body **302** to jointly define an accommodating cavity. Alternatively, both the first box body **301** and the second box body **302** are of hollow structures with one side opened (for example, as shown in FIG. 2). The open side of the first box body **301** is covered at the open side of the second box body **302**. Certainly, the box body **30** formed by the first box body **301** and the second box body **302** may be in various shapes, such as cylinders or cuboids. [0076] In the battery **200**, the plurality of battery cells may be connected in series or in parallel or be in parallel-series connection. The parallel-series connection means that the plurality of battery cells are connected in both series and parallel. The plurality of battery cells may be directly connected in series, in parallel, or in parallel-series connection, and then an entirety formed by the plurality of battery cells is accommodated in the box body **30**. Alternatively, the battery **200** may also be in a form of a battery module formed by connecting the plurality of battery cells in series, in parallel, or in parallel-series connection, and then a plurality of battery modules are connected in series, in parallel, or in parallel-series connection to form an entirety which is accommodated in the box body **30**. The battery **200** may further include other structures. For example, the battery **200** may further include a busbar for electrically connecting the plurality of battery cells.

[0077] Referring to FIG. 3, FIG. 3 is a schematic structural diagram of a battery cell **10** according to some embodiments of the present application. The battery cell **10** is a cuboid. A height direction of the battery cell **10** is a third direction Z. A length direction of the battery cell **10** is a second direction Y. A thickness direction of the battery cell **10** is a first direction X. Every two of the first direction X, the second direction Y and the third direction Z are perpendicular to each other. The shape of the battery cell **10** is not limited to this. In other embodiments of the present application, the battery cell **10** may also be a polyprism, a flat body, in another shape, or the like.

[0078] Referring to FIG. 4 and FIG. 6, in this embodiment of the present application, the battery **200** includes a plurality of rows of battery units **10A** and a heat exchange assembly **140**. The plurality of rows of battery units **10A** are arranged in the first direction X. Each row of battery units **10A** includes a plurality of battery cells **10** arranged in sequence in the second direction Y. Each battery cell **10** includes a first side wall **111**. The first side wall **111** is a side wall having a largest area. Therefore, the first side wall **111** is a “large surface” of the battery cell **10**. There may be one or more first side walls **111** of the battery cell **10**, and quantities of the first side walls **111** of the plurality of battery cells **10** can be equal or not equal. The heat exchange assembly **140** includes a heat conducting plate **70**. The heat conducting plate **70** extends between adjacent rows of battery units **10A**. The heat conducting plate **70** directly faces the first side walls **111** of at least some of the battery cells **10** of adjacent battery units **10A**. The first direction X is perpendicular to the second direction Y.

[0079] It can be seen that since the plurality of rows of battery units **10A** are arranged in sequence in the first direction X. At least a portion of the heat conducting plate **70** is located between adjacent rows of battery units **10A**, and the heat conducting plate **70** directly faces the first side walls **111** of at least some of the battery cells **10** of the adjacent battery units **10A**, so that the first direction X may be perpendicular to the first side walls **111** of the battery cells **10**. Meanwhile, it is convenient to make orthographic projections of the first side walls **111** of at least some of the battery cells **10** in the first direction X are located inside an outer contour of an orthographic projection of the heat conducting plate **70** in the first direction X. Therefore, a larger direct-facing area is provided between the heat conducting plate **70** and at least some of the battery cells **10** of the adjacent battery units **10A** in the first direction X, which is conducive to improving the conducting rate of the heat conducting plate **70** on heat of at least some of the battery cells **10**, or improving the rate of the heat conducting plate **70** for conducting other heat to the above battery cells **10** and enhancing the temperature control effect on the battery **200**. Meanwhile, the heat conducting plate **70** can play an enhancement role on the first side walls **111** of at least some of the battery cells **10**, so as to improve the anti-deformation ability of the first side walls **111** of the

corresponding battery cells **10**, to reduce the probability of a failure of a battery cell **10** caused by a non-uniform force on the battery cells **10**, thereby improving the problem of the non-uniform force on the battery cells **10**, and improving the reliability of the battery **200**.

[0080] It can be understood that for battery units **10A** adjacent to the heat conducting plate **70**, at least one first side wall **111** of the plurality of battery cells **10** in the row of battery units **10A** may directly face the heat conducting plate **70** in the first direction X. For example, for battery units **10A** adjacent to the heat conducting plate **70**, the first side wall **111** of each battery cell **10** in this row of battery units **10A** directly faces the heat conducting plate **70**. Alternatively, for battery units **10A** adjacent to the heat conducting plate **70**, the first side walls **111** of some of the battery cells **10** in this row of battery units **10A** directly face the heat conducting plate **70**, and at least one first side wall **111** in the remaining battery cells **10** may be staggered from the heat conducting plate **70** (for example, the first side wall **111** is staggered from the heat conducting plate **70** in the second direction Y, and certainly, they may also be staggered in other directions), and/or, at least one first side wall **111** in the remaining battery cells **10** may be spaced apart from the heat conducting plate **70** in the second direction Y. The first side wall **111** is staggered from the heat conducting plate **70**, which can be understood as a portion of an orthographic projection of the first side wall **111** in the first direction X is located within an orthographic projection range of the heat conducting plate **70** in the first direction X, and another portion is located beyond the orthographic projection range of the heat conducting plate **70** in the first direction X.

[0081] In addition, a quantity of the heat conducting plate **70** may be set according to an actual need. For example, a quantity of the battery units **10A** is m, and the quantity of the heat conducting plate **70** may be (m-1). In this case, the heat conducting plates **70** are respectively arranged between any adjacent battery units **10A**. Certainly, the quantity of the heat conducting plate **70** may also be less than (m-1).

[0082] In the above technical solution, the heat conducting plate **70** extends between the adjacent battery units **10A**, and the heat conducting plate **70** directly faces the first side walls **111** of at least some of the battery cells **10** of the adjacent battery units **10A**, so that it is convenient to achieve a larger direct-facing area between the heat conducting plate **70** and at least some of the battery cells **10** of the adjacent battery units **10A** in the first direction X, which is beneficial to enhancing the temperature control effect on the battery **200**. Meanwhile, the heat conducting plate **70** can play an enhancement role on the first side walls **111** of at least some of the battery cells **10**, so as to improve the anti-deformation ability of the first side walls **111** of the corresponding battery cells **10**, to reduce the probability of a failure of a battery cell **10** caused by a non-uniform force on the battery cells **10**, thereby improving the reliability of the battery **200**.

[0083] Moreover, in the above technical solution, there is no specific limitation on relative arrangement of the battery cells **10** in the adjacent rows of battery units **10A**. For example, at least two adjacent rows of battery units **10A** are staggered in the second direction Y, and/or, at least two adjacent rows of battery units **10A** directly face each other (i.e., are non-staggered in the second direction Y).

[0084] For example, a side wall of a battery cell **10** in the third direction Z is fixed to an inner wall of the box body **30** through a structural adhesive, and the third direction Z is perpendicular to the first direction X and the second direction Y respectively. For example, the third direction Z being an up-down direction is taken as an example. A terminal post **12** is arranged on a top side wall of the battery cell **10**. A bottom side wall of the battery cell **10** is fixed to the inner wall of the box body **30** through the structural adhesive, which is beneficial to improving the strength of connection between the battery cell **10** and the box body **30**, and improving the overall structural stability of the battery **200**.

[0085] Certainly, a fixing mode for the battery cells **10** is not limited to this. For example, any two adjacent battery cells **10** of a battery unit **10A** are bonded and fixed. Two battery units **10A**, located on the outermost side in the second direction Y, of the battery units **10A** are respectively bonded

and fixed to the corresponding inner walls of the box body **30**.

[0086] It can be understood that when a temperature of a battery cell **10** is too high, the heat conducting plate **70** may be configured to cool the battery cell **10**, to reduce the temperature of the battery cell **10**. When the temperature of the battery cell **10** is too low, the heat conducting plate **70** may be configured to heat the battery cell **10** to increase the temperature of the battery cell **10**. In the following description of the present application, the heat conducting plate **70** being configured to cool the battery cell **10** is taken as an example for explanation. A person skilled in the art can easily understand an implementation solution of the heat conducting plate **70** for heating the battery cell **10** after reading the following solution.

[0087] Referring to FIG. **6** to FIG. **8**, in some embodiments of the present application, opposite side walls of the heat conducting plate **70** are in contact with a plurality of first side walls **111** opposite to each other.

[0088] For example, the opposite side walls of the heat conducting plate **70** are respectively a first heat conducting side wall **71** and a second heat conducting side wall **71**. The first heat conducting side wall **71** is in contact with the plurality of first side walls **111** of one adjacent battery unit **10A**, and the second heat conducting side wall **71** is in contact with the plurality of first side walls **111** of another adjacent battery unit **10A**.

[0089] In the above technical solution, the opposite side walls of the heat conducting plate **70** are in contact with the plurality of first side walls **111** opposite to each other, so that it is convenient to achieve the heat-conducting connection between the heat conducting plate **70** and at least some of the first side walls **111** of the adjacent battery units **10A**, and the structure of the battery **200** is simplified. Meanwhile, the side walls of the heat conducting plate **70** can directly play a role of supporting the first side walls **111** of the battery cells **10**, to further improve the anti-deformation ability of the first side walls **111**, thereby further improving the problem of a non-uniform force on the battery cells **10**.

[0090] For example, the opposite side walls of the heat conducting plate **70** are in contact with the first side wall **111** of each battery cell **10** of the corresponding battery unit **10A**.

[0091] In some embodiments, the heat conducting plate **70** is in heat-conducting connection to at least one first side wall **111** of the corresponding battery unit **10A**. In the third direction Z, a height of the heat conducting plate **70** is consistent with a shoulder height of a battery cell **10**.

[0092] Referring to FIG. **9** to FIG. **12**, in some embodiments of the present application, a cavity **70a** for buffering a stress is provided inside the heat conducting plate **70**, and the cavity **70a** is configured to be deformable when the heat conducting plate **70** undergoes a pressure, to buffer the stress.

[0093] In the above technical solution, the cavity **70a** for buffering the stress is provided inside the heat conducting plate **70**, so that when the battery cells **10** expand during use, due to the cavity **70a**, the heat conducting plate **70** can deform when it is directly or indirectly subjected to a force of the battery cells **10**, thereby reducing an extrusion force between the heat conducting plate **70** and the battery cells **10**, avoiding damage to the heat conducting plate **70** and the battery cells **10**, and helping to improve the reliability of the heat conducting plate **70** and the reliability of the battery cells **10**. Meanwhile, due to the arrangement of the cavity **70a**, it is convenient to absorb an assembling tolerance of the battery cells **10** in rows in the process of assembling the heat conducting plate **70** and the battery cells **10**, thereby improving the convenience of assembling of the heat conducting plate **70** and the battery cells **10**. Moreover, the arrangement of the cavity **70a** helps to reduce the weight of the heat conducting plate **70**, thereby reducing the weight of the battery **200** and helping to improve the weight energy density of the battery **200**.

[0094] For example, the heat conducting plate **70** is bonded and fixed to the battery cells **10**.

[0095] Referring to FIG. **9**, FIG. **11**, and FIG. **12**, in some embodiments of the present disclosure, a supporting assembly **80** is arranged inside the cavity **70a**. The heat conducting plate **70a** includes two heat conducting side walls **71** opposite to each other. The heat conducting side walls **71**

directly face the first side walls **111**. The supporting assembly **80** is respectively connected to the two heat conducting side walls **71**. The supporting assembly **80** is configured to make a distance between the two heat conducting side walls **71** variable.

[0096] For example, when the heat conducting plate **70** is subjected to a pressure, the supporting assembly **80** is compressed to deform, and the distance between the two heat conducting side walls **71** decreases. When the pressure applied to the heat conducting plate **70** is removed, the supporting assembly **80** can apply a force to the heat conducting side walls **71**, so that the distance between the two heat conducting side walls **71** tends to the distance before the pressure is applied. For example, if the heat conducting side walls **71** are in contact with the plurality of first side walls **111** opposite thereto, when the expansion deformation of the battery cells **10** is reduced, the supporting assembly **80** can apply a force to the heat conducting side walls **71**, so that the heat conducting side walls **71** maintain contact with the plurality of first side walls **111**, thereby reducing the impact of the expansion deformation of the battery cells **10** on heat management of the battery cells **10**.

[0097] In the above technical solution, the supporting assembly **80** is arranged inside the cavity **70a**, and the supporting assembly **80** is configured to make the distance between the two heat conducting side walls **71** variable, so that the supporting assembly **80** can play a role of supporting the two heat conducting side walls **71**, thereby improving the anti-bending deformation ability and elastic recovery ability of the heat conducting plate **70**, and improving the reliability of the heat conducting plate **70**. Meanwhile, the supporting assembly **80** can also adapt to direct or indirect extrusion on the heat conducting plate **70** caused by the expansion of the battery cells **10**, to avoid an excessive extrusion force between the heat conducting plate **70** and the battery cells **10**.

[0098] It can be seen that the arrangement of the supporting assembly **80** will not cause the cavity **70a** to be unable to buffer the stress, but can enable the heat conducting plate **70** to simultaneously balance the anti-bending deformation ability, the elastic recovery ability, and the stress buffering ability.

[0099] For example, the two heat conducting side walls **71** of the heat conducting plate **70** are opposite to each other in the first direction X. The cavity **70a** is located between the two heat conducting side walls **71**, and each heat conducting side wall **71** extends in the second direction Y. The heat conducting plate **70** has a simple structure and is convenient to process.

[0100] Referring to FIG. 9, FIG. 11, and FIG. 12, in some embodiments of the present application, a plurality of separated sub-chambers **70b** are defined between the supporting assembly **80** and at least one of the heat conducting side walls **71**.

[0101] In the above technical solution, the plurality of separated sub-chambers **70b** are defined between the supporting assembly **80** and at least one of the heat conducting side walls **71**. The sub-chambers **70b** can provide an avoidance space for the deformation of the supporting assembly **80** and/or the heat conducting side wall **71**, so that while supporting the heat conducting side walls **71**, the supporting assembly **80** can balance the anti-bending deformation ability, elastic deformation ability, and elastic recovery ability of the heat conducting side wall **71**. Meanwhile, the weight of the supporting assembly **80** cannot be excessively increased, which is beneficial to avoiding an excessive increase in the weight of the heat exchange assembly **140** and facilitates improving the weight energy density of the battery **200**.

[0102] Exemplarily, in the example of FIG. 12, the supporting assembly **80** and each heat conducting side wall **71** respectively define a plurality of separated sub-chambers **70b**. The sub-chambers **70b** defined between the supporting structure **80** and one of the heat conducting side walls **71** are denoted as first sub-chambers, and the sub-chambers **70b** defined between the supporting structure **80** and the other heat conducting side wall **71** are recorded as second sub-chambers. Cross sections of both the first sub-chambers and the second sub-chambers are triangles. The plurality of first sub-chambers and the plurality of second sub-chambers are alternately arranged one by one in the second direction Y. Certainly, the supporting assembly **80** may also define a plurality of sub-chambers **70b** with only one of the two heat conducting side walls **71**.

[0103] Referring to FIG. 9, FIG. 11 and FIG. 12, in some embodiments of the present application, in a cross section parallel to the first direction X and the second direction Y, the cross section of each sub-chamber **70b** is a triangle.

[0104] In the above technical solution, since the cross section of each sub-chamber **70b** is the triangle, it is beneficial to simplifying the structure of the supporting assembly **80** and simplifying the connection between the supporting assembly **80** and each heat conducting side wall **71**. Meanwhile, it is convenient for the supporting assembly **80** to have a good elastic deformation ability and a good elastic recovery ability, so that the distance between the two heat conducting side walls **71** can better adapt to the expansion deformation of the battery cells **10**.

[0105] For example, the supporting assembly **80** may include a plurality of first supporting members and a plurality of second supporting members, and the plurality of first supporting members and the plurality of second supporting members may be alternately arranged one by one in the second direction Y. One second supporting member is connected between two adjacent first supporting members, and one first supporting member is connected between two adjacent second supporting members. In addition, each first supporting member is respectively connected to the two heat conducting side walls **71**, and each first supporting member is oblique relative to the two heat conducting side walls **71**. Each second supporting member is respectively connected to the two heat conducting side walls **71**, and each second supporting member is oblique relative to the two heat conducting side walls **71**. Therefore, the supporting assembly **80** can be made to have a good elastic deformation ability, an elastic recovery ability, and a simple structure.

[0106] Certainly, the shape of the cross section of each sub-chamber **70b** is not limited to this. For example, the cross section of the sub-chamber **70b** may also be another polygon.

[0107] Referring to FIG. 8 and FIG. 12, in some embodiments of the present application, the cavity **70a** is filled with a heat absorption material **90**.

[0108] In the above technical solution, since the heat absorption material **90** is arranged inside the cavity **70a**, it is beneficial to improving the heat exchange capability of the heat exchange assembly **140** and facilitates improving the heat management effect on the battery cells **10**.

[0109] In some embodiments, as shown in FIG. 12, a supporting assembly **80** and a heat absorption material **90** are arranged inside the cavity **70a**. The supporting assembly **80** is formed into a mesh structure, and the mesh structure is filled with the heat absorption material **90**, which facilitates reducing obstruction of the supporting assembly **80** on the heat absorption material **90**, helps to improve the filling capability of the heat absorption material **90** in the cavity **70a**, makes the heat absorption material **90** be in contact with the heat conducting side walls **71**, and improves the heat conduction capability. Meanwhile, the weight of the supporting assembly **80** may not be excessively increased, which is conducive to avoiding an excessive increase in the weight of the heat exchange assembly **140** and lowering a requirement on a physical state of the heat absorption material **90**. Furthermore, if the physical state of the heat absorption material **90** changes in a heat absorption process, a requirement on a physical state change of the heat absorption material **90** can also be lowered.

[0110] For example, a plurality of separated sub-chambers **70b** are defined between the supporting assembly **80** and at least one heat conducting side wall **71**. The supporting assembly **80** is formed into a mesh structure, so that adjacent sub-chambers **70b** are communicated. The heat absorption material **90** is arranged in the plurality of sub-chambers **70b**, so that the supporting assembly **80** can support each heat conducting side wall **71** and make the distance between the two heat conducting side walls **71** to change under the action of an external force, so as to better balance the stress buffering ability and the anti-bending ability.

[0111] In some embodiments of the present application, the heat absorption material **90** is a solid-liquid phase change material.

[0112] In the above technical solution, since the heat absorption material **90** is the solid-liquid phase change material, the phase change material undergoes a solid-liquid phase change at a high

temperature and absorbs heat at the same time, to further improve the heat absorption and heat conduction capabilities of the heat exchange assembly **140** and improve the temperature control capability of the battery **200**.

[0113] For example, the solid-liquid phase change material includes one or more of paraffin, fatty acid, and polyethylene.

[0114] For example, the first side walls **111** of at least two adjacent rows of battery units **10A** are staggered in the second direction Y. At least a portion of the heat conducting plate **70** is located between the staggered battery units **10A**, so that heat of a battery cell **10** (for example, heat generated by thermal runaway) can be transferred to a plurality of remaining battery cells **10** through the first side walls **111** and the heat conducting plate **70**, to reduce the heat transferred from the battery cell **10** to the remaining single battery cells **10**, thereby inhibiting thermal spread and improving the safety of the battery **200**. Further, the heat absorption material piece **90** is arranged in the cavity **70a** of the heat conducting plate **70** to absorb heat of the battery cell **10**, which is beneficial for further reducing the heat transferred from the battery cell **10** to the remaining single battery cells **10** and enhancing the inhibition effect on thermal spread.

[0115] Referring to FIG. **14** and FIG. **15**, in some embodiments of the present application, the battery **200** further includes a box body **30**. The plurality of rows of battery units **10A** are arranged in the box body **30**. The heat conducting plate **70** is fixed to the box body **30**. It can be seen that the heat conducting plate **70** may also be arranged inside the box body **30**.

[0116] In the above technical solution, by the arrangement of the box body **30**, a protection effect can be achieved on the plurality of rows of battery units **10A** and the heat conducting plate **70**. Fixing the heat conducting plate **70** to the box body **30** to connect the heat conducting plate **70** to the box body **30** into a whole, which is beneficial to improving the structural reliability of the battery **200**. Moreover, the box body **30** can play a limiting role on the battery units **10A** through the heat conducting plate **70**, to achieve stable arrangement of the battery units **10A**.

[0117] For example, the heat conducting plate **70** is bonded and fixed to an inner wall of the box body **30** through a structural adhesive, but not limited to this. For example, the heat conducting plate **70** is welded and fixed to the box body **30**.

[0118] For example, a side surface of the heat conducting plate **70** in the second direction Y and/or the third direction Z is fixed to the inner wall of the box body **30**, and the third direction Z is perpendicular to the first direction X and the second direction Y respectively.

[0119] Referring to FIG. **4**, in some embodiments of the present application, the heat exchange assembly **140** further includes a heat exchange plate **100**. In a third direction Z, the heat exchange plate **100** is located on one side of the plurality of rows of battery units **10A**. The third direction Z is perpendicular to the first direction X and the second direction Y respectively. The heat conducting plate **70** is arranged on a surface of the heat exchange plate **100** facing the battery units **10A**, and the heat conducting plate **70** is in heat-conducting connection to the heat exchange plate **100**. In this case, an arrangement mode for the plurality of battery cells **10** of the battery units **10A** includes, but is not limited to, arrangement modes shown in FIG. **6**, FIG. **7**, and FIG. **14**.

[0120] In the above technical solution, by the arrangement of the heat exchange plate **100**, the heat exchange plate **100** is in heat-conducting connection to the heat conducting plate **70**, so that the heat exchange plate **100** can at least exchange heat with the battery cells **10** through the heat conducting plate **70**, so as to further reduce heat transferred from a battery cell **10** to another single battery cell **10**, thereby inhibiting thermal spread.

[0121] For example, the third direction Z being an up-down direction is taken as an example. The heat exchange plate **100** is located on lower sides of the plurality of battery cells **10**. There is one or more heat conducting plates **70**. The heat conducting plates **70** are arranged on an upper surface of the heat exchange plate **100**, and the heat conducting plates **70** are in heat-conducting connection to the plurality of battery cells **10** of the adjacent battery units **10A**. In this way, the heat exchange plate **100** can be, for example, bonded and fixed to a bottom wall of the box body **30**.

[0122] For example, the heat exchange plate **100** is in heat-conducting connection to at least two battery cells **10** to enrich a heat transfer mode between the heat exchange plate **100** and the battery cells **10**, to disperse the heat of the battery cells **10** and facilitate further inhibition on thermal spread.

[0123] For example, a heat exchange channel **100a** for placing a heat exchange medium is arranged in the heat exchange plate **100**. The heat exchange medium may be a liquid and/or a gas. The heat exchange plate **100** is configured to adjust temperatures of the at least two battery cells **10**. In a case that the heat exchange plate **100** is configured to reduce the temperatures of the battery cells **10**, the heat exchange channel **100a** can accommodate a cooling medium to adjust temperatures of a plurality of battery cells **10**. In this case, the heat exchange medium may also be referred to as a cooling medium or a cooling fluid. More specifically, the heat exchange medium may be referred to as a cooling liquid or a cooling gas. Optionally, the heat exchange medium may be water, a mixed liquid of water and ethylene glycol, heat conducting oil, a refrigerant, air, or the like.

[0124] For example, the heat exchange channel **100a** may have an inlet and an outlet, to enable the heat exchange medium to flow and improve the heat exchange efficiency.

[0125] For example, the battery **200** includes a plurality of rows of battery units **10A** arranged in sequence in the first direction X. Each battery unit **10A** includes a plurality of battery cells **10**. In a third direction Z, the heat exchange plate **100** is located on one side of all the battery cells **10**. In this case, the heat exchange plate **100** may be configured to achieve heat management on all the battery cells **10**. Further, the heat exchange channel **100a** may be configured to include a plurality of flow sub-channels spaced apart in the first direction X. Each flow sub-channel may extend in the second direction Y, and each flow sub-channel may correspond to one row of battery units **10A**.

[0126] In some embodiments, the heat conducting plate **70** is a solid metal plate.

[0127] In the above technical solution, since the heat conducting plate **70** is the solid metal plate, it is convenient to simplify the structure and processing procedures of the heat conducting plate **70**, and meanwhile, it is convenient to ensure the heat conduction capability of the heat conducting plate **70**.

[0128] Certainly, the heat conducting plate **70** may also be configured as a hollow structure.

[0129] In some embodiments, a thermally conductive adhesive layer is arranged between the heat conducting plate **70** and the battery cells **10**.

[0130] In the above technical solution, since the thermally conductive adhesive layer is arranged between the heat conducting plate **70** and the battery cells **10**, the thermally conductive adhesive layer is arranged between the heat conducting plate **70** and the first side walls **111**, thereby effectively achieving the heat-conducting connection between the heat conducting plate **70** and the battery cells **10**, facilitating improving the heat transfer efficiency for the heat conducting plate **70** and the battery cells **10**, and enhancing the temperature control effect on the battery **200**. Moreover, the heat conducting plate **70** can also play an enhancement role on the first side walls **111** of the corresponding battery cells **10** to an extent, thereby improving the anti-deformation ability of the first side walls **111** of the battery cells **10**, to reduce the probability of a failure of a battery cell **10** caused by a non-uniform force on the battery cells **10**.

[0131] Certainly, other heat-conducting connection modes may be used for the heat conducting plate **70** and the battery cells **10**. For example, the heat conducting plate **70** is in contact with the battery cells **10**.

[0132] Referring to FIG. 4, in some embodiments of the present application, the heat exchange plate **100** and the heat conducting plate **70** are integrated structural members.

[0133] In the above technical solution, since the heat conducting plate **70** and the heat exchange plate **100** are the integrated structural members, it is convenient to improve the strength of the heat conducting plate **70** and the strength of the heat exchange plate **100**, save connection procedures for the heat conducting plate **70** and the heat exchange plate **100**, and improve the assembling efficiency of the battery **200**. Meanwhile, it is conducive to improving the heat transfer efficiency

for the heat conducting plate **70** and the heat exchange plate **100** to an extent.

[0134] For example, the heat conducting plate **70** and the heat exchange plate **100** are welded and fixed. Certainly, the connection mode for the heat conducting plate **70** and the heat exchange plate **100** is not limited to this.

[0135] Certainly, in other embodiments, the heat conducting plate **70** and the heat exchange plate **100** may also be split structural members.

[0136] Referring to FIG. **6**, FIG. **7**, and FIG. **13** to FIG. **15**, in some embodiments of the present application, the first side walls **111** of at least two adjacent rows of the battery units **10A** are staggered in the second direction Y, and at least a portion of the heat conducting plate **70** is located between the staggered battery units **10A**.

[0137] For the adjacent rows of battery units **10A** that are staggered, the first side walls **111** of at least two battery cells **10** are opposite to the corresponding heat conducting plates **70** in the first direction X, and the first side walls **111** of the at least two battery cells **10** are staggered in the second direction Y, so that a portion of an orthographic projection, in the first direction X, of each of two first side walls **111** that are opposite to each other in the first direction X is located on an outer side, in the second direction Y, of an outer contour of an orthographic projection of the other first side wall in the first direction X, and another portion may overlap the orthographic projection of the other first side wall in the first direction X. Then, the two battery cells **10** corresponding to the two opposite first side walls **111** are staggered in the second direction Y, and any two adjacent battery cells **10** in the at least two battery cells **10** are staggered in the second direction Y. In this case, two non-adjacent battery cells **10** in the at least two battery cells **10** may also be staggered in the second direction Y, or two non-adjacent battery cells **10** in the at least two battery cells **10** may also be opposite to each other in the second direction Y.

[0138] It can be understood that two battery cells **10** being adjacent in the first direction X can be understood as no other battery cells **10** being arranged between the two battery cells **10** in the first direction X. Two battery cells **10** being not adjacent in the first direction X can be understood as at least one other battery cell **10** being arranged between the two battery cells **10** in the first direction X.

[0139] For example, if a quantity of the battery units **10A** of the battery **200** is m, where m is a positive integer and $m \geq 2$. In the m battery units **10A**, the first side walls **111** of n adjacent battery units **10A** are opposite to each other in the first direction X and are staggered in the second direction Y. That is, if there are n battery units **10A** staggered, any two adjacent battery units **10A** in the n battery units **10A** are staggered, where n a positive integer and $2 \leq n \leq m$. In the staggered battery units **10A**, at least one first side wall **111** of one battery unit **10A** is staggered from a corresponding first side wall **111** of another battery unit **10A** in the second direction Y. The staggered arrangement of two first side walls **111** can be understood as corresponding two battery cells **10** are staggered.

[0140] Then, a quantity of battery cells **10** of one row of battery units **10A** that are staggered from corresponding battery cells **10** of another row of battery units **10A** is less than or equal to a total quantity of the battery cells **10** of the battery units **10A**. For example, for adjacent rows of battery units **10A** that are staggered, each battery cell **10** in the battery units **10A** is staggered from a corresponding battery cell **10** in the adjacent row of battery units **10A**. Alternatively, each of some of the battery cells **10** of the battery units **10A** is staggered from a corresponding battery cell **10** in the adjacent row of battery units **10A**, and each of some other battery cells **10** is non-staggered from a corresponding battery cell **10** in the adjacent row of battery units **10A**.

[0141] For two first side walls **111** that are staggered, a portion of an orthographic projection of one first side wall **111** in the first direction X is located on one side, in the second direction Y, of an outer contour of an orthographic projection of the other first side wall **111** in the first direction X in the second direction Y, and another portion is located within the outer contour of the orthographic projection of the other first side wall **111** in the first direction X. Furthermore, a portion of the

orthographic projection of the other first side wall **111** in the first direction X is located on one side, in the second direction Y, of an outer contour of the orthographic projection of the one first side wall **111** in the first direction X, and another portion is located within the outer contour of the orthographic projection of the one first side wall **111** in the first direction X. In this case, the orthographic projections, in the first direction X, of the two first side walls **111** that are staggered partially overlap each other.

[0142] For example, referring to FIG. **13**, a region formed combining a first region $\Omega 1$ with a second region $\Omega 2$ is an orthographic projection of one first side wall **111** of one battery unit **10A** in the first direction X. A region formed by combining the second region $\Omega 2$ with a third region $\Omega 3$ is an orthographic projection of one first side wall **111** of another battery unit **10A** in the first direction X. The second region $\Omega 2$ is an overlapping region of the orthographic projections, in the first direction X, of the two first side walls **111** that are staggered. It can be seen that for the one first side wall **111** described above, the first region $\Omega 1$ is located outside the outer contour of the orthographic projection of the other first side wall **111** in the first direction X, and the second region $\Omega 2$ is located within the outer contour of the orthographic projection of the other first side wall **111** in the first direction X. For the other first side wall **111** described above, the third region $\Omega 3$ is located outside the outer contour of the orthographic projection of the one first side wall **111** in the first direction X, and the second region $\Omega 2$ is located within the outer contour of the orthographic projection of the one first side wall **111** in the first direction X.

[0143] It can be seen that the staggered arrangement of at least two adjacent rows of battery units **10A** is conducive to making full use of an arrangement space of the battery **200**. Meanwhile, the staggered arrangement of the battery cells **10** can also be applicable to an irregular arrangement space. To an extent, a staggering distance of the battery cells **10** can be adaptively adjusted according to a shape of an arrangement space, to improve the adaptability of the battery cells **10** to the arrangement space.

[0144] In addition, when there is heat exchange between two battery cells **10** that are staggered, the “large surfaces” of the two battery cells **10** are staggered in the second direction Y, which is beneficial to reducing a heat exchange area between the two battery cells **10**, thereby reducing an amount of heat transferred between the two battery cells **10** that are staggered and reducing peak power of heat transfer, so that when a battery cell **10** has thermal runaway, it is convenient to avoid the battery cell **10** from transferring heat mainly to one battery cell **10**. By transferring the heat of the battery cell **10** having the thermal runaway in a dispersed manner, the heat transferred from the battery cell **10** having thermal runaway to the remaining single battery cell **10** can be reduced, thereby achieving a purpose of inhibiting thermal spread, which is beneficial to improving the reliability of use of the battery **200** and improving a temperature rise caused by, for example, fast charging during use.

[0145] In the above technical solution, since the first side walls **111** of the at least two adjacent rows of battery units **10A** are staggered in the second direction Y, it is beneficial to making full use of an arrangement space of the battery **200** and improving the adaptability of the plurality of battery cells **10** to arrangement spaces in different shapes. Meanwhile, for two battery cells **10** that are staggered, an amount of heat transferred from any one of the battery cells **10** to the other battery cell **10** can be reduced, thereby achieving a purpose of inhibiting thermal spread, which is beneficial to improving the reliability of use of the battery **200**. Furthermore, due to the above setting, no additional structure needs to be added for the battery **200**, to simplify the structure of the battery **200**.

[0146] It can be understood that when adjacent rows of battery units **10A** are staggered, a force between the battery cells **10** is not uniform. This embodiment of the present application effectively improves the problem of a non-uniform force on the battery cells **10** by providing the heat conducting plate **70**.

[0147] It should be noted that in the embodiments of the present application, “heat-conducting

connection” can be understood as existence of heat exchange between two components, including direct heat exchange between two components (heat of one component is directly transferred to the other component, and the two components are in contact), and indirect heat exchange between two components (heat of one component is transferred to the other component through other structures such as a thermally conductive adhesive and a thermally conductive part). Moreover, “heat-conducting connection” can mean that in any one of two components transfers heat to the other component. That is, for one component, the component can transfer heat to the other component, or the other component can also transfer heat to the component.

[0148] In a second aspect, an embodiment of the present application further provides an electrical apparatus **1000**, including the above battery **200**. The battery **200** is configured to supply electric energy.

[0149] In the above technical solution, since the above battery **200** is arranged in the electrical apparatus **1000**, and the heat conducting plate **70** can improve the anti-deformation ability of the first side walls **111** of the battery **200**, it is beneficial to improving the reliability of the electrical apparatus **1000**.

[0150] Referring to FIG. 3 to FIG. 6, FIG. 9, FIG. 12, FIG. 14, and FIG. 15 again, a battery **200** of a specific embodiment of the present application will be described.

[0151] In this embodiment of the present application, the battery **200** includes a box body **30**, battery units **10A**, and a heat exchange assembly **140**. All the battery units **10A** are arranged in the box body **30**. The battery units **10A** are arranged in a plurality of rows and are disposed in sequence in a first direction X. Each row of battery units **10A** includes a plurality of battery cells **10** arranged in sequence in a second direction Y. Each first battery cell **10** includes two first side walls **111** opposite to each other in the first direction X and two second side walls **112** opposite to each other in the second direction Y. The first side walls **111** opposite to each other in any two adjacent rows of battery units **10A** are staggered, and each first battery cell **10** in any two adjacent rows of battery units **10A** is staggered from a corresponding first battery cell **10** in the other row.

[0152] The heat exchange assembly **140** includes a heat conducting plate **70** and a heat exchange plate **100**. In a third direction Z, the heat exchange plate **100** is located on one side of the plurality of rows of battery units **10A**. The heat conducting plate **70** is arranged on a surface of the heat exchange plate **100** facing the battery units **10A**, and the heat conducting plate **70** is in heat-conducting connection to the heat exchange plate **100**. The heat conducting plate **70** is fixedly connected to the box body **30**. The heat conducting plate **70** is located between adjacent rows of battery units **10A** that are staggered, and the heat conducting plate **70** is in heat-conducting connection to the first side walls **111** of each battery cell **10** of the corresponding battery units **10A**. The first direction X is parallel to a width direction of the box body **30**. The second direction Y is parallel to a length direction of the box body **30**. The third direction Z is parallel to a height direction of the box body **30**.

[0153] A cavity **70a** for buffering a stress is provided inside the heat conducting plate **70**, and a supporting assembly **80** and a heat absorption material **90** are arranged in the cavity **70a**. The supporting assembly **80** is respectively connected to two opposite heat conducting side walls **71** of the heat conducting plate **70**, and the supporting assembly **80** is configured to make a distance between the two heat conducting side walls **71** variable. A plurality of separated sub-chambers **70b** are respectively defined between the supporting assembly **80** and each heat conducting side wall **71**. On a cross section parallel to the first direction X and the second direction Y, a cross section of each sub-chamber **70b** is a triangle.

[0154] In the above technical solution, by the arrangement of the heat exchange assembly **140**, the problem of a non-uniform force between the battery cells **10** is improved, and it facilitates the heat conducting plate **70** to adapt to expansion of the battery cells **10**, thereby improving the reliability of the battery **200**.

[0155] It should be noted that the embodiments in the present application and features in the

embodiments may be mutually combined without conflicts.

[0156] The above are only preferred examples of the present application, and are not intended to limit the present application. For those skilled in the art, the present application may have various modifications and changes. Any modification, equivalent replacement, improvement, etc. made within the spirit and principle of the present application shall fall within the scope of protection of the present application.

Claims

1. A battery, comprising: a plurality of rows of battery units, wherein the plurality of rows of battery units are arranged in a first direction; each row of battery units comprises a plurality of battery cells arranged in sequence in a second direction; each battery cell comprises a first side wall; the first side wall is the side wall with the largest area; the first direction and the second direction are perpendicular to each other; and a heat exchange assembly, wherein the heat exchange assembly comprises a heat conducting plate; the heat conducting plate extends between adjacent rows of battery units; and the heat conducting plate directly faces the first side walls of at least some of the battery cells of adjacent battery units.
 2. The battery according to claim 1, wherein opposite side walls of the heat conducting plate are in contact with a plurality of first side walls opposite to each other.
 3. The battery according to claim 1, wherein a cavity for buffering a stress is provided inside the heat conducting plate.
 4. The battery according to claim 3, wherein a supporting assembly is arranged inside the cavity; the heat conducting plate comprises two heat conducting side walls opposite to each other; the heat conducting side walls directly face the first side walls; the supporting assembly is respectively connected to the two heat conducting side walls; and the supporting assembly is configured to make a distance between the two heat conducting side walls variable.
 5. The battery according to claim 4, wherein a plurality of separated sub-chambers are defined between the supporting assembly and at least one of the heat conducting side walls.
 6. The battery according to claim 5, wherein on a cross section parallel to the first direction and a second direction, a cross section of each of the sub-chambers is a triangle.
 7. The battery according to claim 3, wherein the cavity is filled with a heat absorption material.
 8. The battery according to claim 7, wherein the heat absorption material is a solid-liquid phase change material.
 9. The battery according to claim 2, further comprising a box body, wherein the plurality of rows of battery units are arranged in the box body; and the heat conducting plate is fixed to the box body.
 10. The battery according to claim 1, wherein the heat exchange assembly further comprises a heat exchange plate; in a third direction, the heat exchange plate is located on one side of the plurality of rows of battery units; the third direction is perpendicular to the first direction and the second direction respectively; and the heat conducting plate is arranged on a surface of the heat exchange plate facing the battery units and is in heat-conducting connection to the heat exchange plate.
 11. The battery according to claim 10, wherein the heat conducting plate is a solid metal plate.
 12. The battery according to claim 10, wherein a thermally conductive adhesive layer is arranged between the heat conducting plate and the battery cells.
 13. The battery according to claim 10, wherein the heat exchange plate and the heat conducting plate are integrated structural members.
 14. The battery according to claim 1, wherein the first side walls of at least two adjacent rows of the battery units are staggered in the second direction, and at least a portion of the heat conducting plate is located between the staggered battery units.
 15. An electrical apparatus, comprising the battery according to claim 1.
-

