

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404155
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Holdeman; Brian et al.

Winch or hoist having a gearbox with high-contact ratio gears

Abstract

A winch or a hoist (**100**) includes an input shaft, a rotatable drum (**112**), and a gearbox (**120**) including a plurality of high-contact ratio spur-type gears, the gearbox coupled to the input shaft and to the rotatable drum such that rotation of the input shaft at a first speed drives rotation of the rotatable drum at a second speed that is different than the first speed.

Inventors:	Holdeman; Brian (Broken Arrow, OK), Toole; Daryl (Broken Arrow, OK)
Applicant:	BPG-ARROWHEAD WINCH INC. (Broken Arrow, OK)
Family ID:	66821436
Assignee:	BPG-ARROWHEAD WINCH INC. (Broken Arrow, OK)
Appl. No.:	17/612190
Filed (or PCT Filed):	May 21, 2019
PCT No.:	PCT/US2019/033380
PCT Pub. No.:	WO2020/236160
PCT Pub. Date:	November 26, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220212905 A1	Jul. 07, 2022

Publication Classification

Int. Cl.: B66D1/00 (20060101); **B66D1/22** (20060101); **F16H1/46** (20060101); **F16H55/08** (20060101)

U.S. Cl.:

CPC **B66D1/22** (20130101); **F16H1/46** (20130101); **F16H55/08** (20130101);

Field of Classification Search

CPC: B66D (1/08); B66D (1/12); B66D (1/22); B66D (1/7484); B66D (3/22); F16H (1/46); F16H (55/08)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2931248	12/1959	Walton	74/640	F16H 49/001
3627087	12/1970	Eskridge	188/134	F16H 1/32
4108017	12/1977	Rouverol	N/A	N/A
4453430	12/1983	Sell	475/116	B66D 1/44
4663128	12/1986	Helgeland	254/293	C30B 15/30
4736929	12/1987	McMorris	N/A	N/A
2004/0041137	12/2003	Shoji	242/390.8	B66D 1/14
2005/0279978	12/2004	Huang	N/A	N/A
2015/0210517	12/2014	Nishimoto	254/323	B66D 1/7436
2017/0166422	12/2016	Mahnken	N/A	B66D 1/39
2019/0002254	12/2018	Dennis	N/A	F16H 57/10
2019/0016571	12/2018	Thirunarayana	N/A	H02K 7/1016
2020/0140245	12/2019	Yasuda	N/A	B64C 39/024
2021/0131529	12/2020	Base	N/A	F16H 3/76

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
0211309	12/1986	EP	N/A
0 504 565	12/1991	EP	N/A
1 925 854	12/2007	EP	N/A
20150017394	12/2014	KR	N/A
2006/038901	12/2005	WO	N/A
WO-2020236160	12/2019	WO	B66D 1/22

OTHER PUBLICATIONS

AGMA 933-B03, “Basic Gear Geometry”, American Gear Manufacturers Association, Mar. 13, 2003. (26 pages). cited by applicant

Anderson et al., “Efficiency of Nonstandard and High Contact Ratio Involute Spur Gears”, NASA Technical Memorandum 83725, USAAVSCOM Technical Report 84-C-9, Forth International Power Transmission and Gearing Conference, Oct. 10-12, 1984. (35 pages). cited by applicant

ANSI/AGMA 2002-B88, “Tooth Thickness Specification and Measurement”, American Gear Manufacturers Association, Dec. 2006. (48 pages). cited by applicant
Srinivas et al., “Comparison of High Contact Ratio and Low Contact Ratio Gears”, International Journal of Scientific Research in Science and Technology, 3(8): 657-669, Dec. 9, 2017. cited by applicant
Lin et al. “Computer-Aided Design of High-Contact-Ratio Gears for Minimum Dynamic Load and Stress”, Journal of Mechanical Design, 115: 171-178, Mar. 1993. cited by applicant

Primary Examiner: Marcelo; Emmanuel M

Attorney, Agent or Firm: Seed Intellectual Property Law Group LLP

Background/Summary

BACKGROUND

Technical Field

(1) The present disclosure relates generally to winches and hoists including gear boxes, and more particularly to winches and hoists including high-contact ratio gearing.

Description of the Related Art

(2) Winches and hoists are typically driven by a motor, such as a hydraulic motor, and are often provided with gearboxes that change, e.g., increase or decrease, the speed at which the winch or hoist is driven relative to the speed of an output shaft of the motor. For example, a hydraulic motor can drive an output shaft thereof to rotate about its own central longitudinal axis at a first speed. The output shaft of the hydraulic motor can be rotationally coupled to an input shaft of a gearbox of a winch or hoist, and the gearbox can in turn drive a spool or a drum of the winch or hoist to rotate about its own central longitudinal axis at a second speed that is different than, e.g., greater than or less than, the first speed. Such gearboxes can also be used to increase or decrease the torque transferred to the spool or drum of the winch or hoist, which may in turn increase or decrease the total working capacity of the winch or hoist.

(3) Traditional spur-type gearing creates more noise than desired in some particularly noise-sensitive applications, and is in some cases not suitable where noise, vibration, and harshness (NVH) are a major concern. A relatively standard solution in such cases is to use helical gearing, which generally creates less noise, vibration, and harshness, rather than spur-type gearing. Nevertheless, helical gearing has its own drawbacks, including the generation of thrust forces, that render it undesirable in certain applications.

(4) Characteristic shapes of gear teeth are relatively standardized. Relevant information and standards have been published by the American Gear Manufacturers Association, such as in AGMA 933-B03, titled “Basic Gear Geometry,” in ANSI/AGMA B88, titled “Tooth Thickness Specification and Measurement,” in ISO 6336, and in other, related documents, such as counterpart Japanese and other national standards. Gears with teeth that do not conform to such standards have been used in certain applications. For example, gears with gear teeth shaped to provide a higher contact ratio than that specified in the AGMA and other relevant standards have been used in certain applications. Such gearing has significant disadvantages, however. For example, it requires significantly greater precision and is therefore more expensive to manufacture.

BRIEF SUMMARY

(5) A winch or hoist may be summarized as comprising: an input shaft; a rotatable drum; and a gearbox including a plurality of high-contact ratio spur-type gears, the gearbox coupled to the input shaft and to the rotatable drum such that rotation of the input shaft at a first speed drives rotation of

the rotatable drum at a second speed that is different than the first speed. The gearbox may be a planetary gearbox. The high-contact ratio spur-type gears may include internal gear teeth and external gear teeth.

(6) The high-contact ratio spur-type gears may have a higher contact ratio than specified in ANSI/AGMA B88. The high-contact ratio spur-type gears may include gear teeth having longer addendums than specified in ANSI/AGMA B88. The high-contact ratio spur-type gears may include gear teeth having longer dedendums than specified in ANSI/AGMA B88. Each of the high-contact ratio spur-type gears may have a respective diametral pitch and include gear teeth having addendums greater than 1.00, 1.05, 1.10, 1.15, or 1.20 divided by the respective diametral pitch. Each of the high-contact ratio spur-type gears may have a respective diametral pitch and include gear teeth having dedendums greater than 1.25, 1.30, 1.35, or 1.40 divided by the respective diametral pitch. Each of the high-contact ratio spur-type gears may have a contact ratio greater than 1.60, 1.80, or 2.00.

(7) A method of operating a winch or hoist or be summarized as comprising: coupling an input shaft of the winch or hoist to a motor; coupling a cable coupled to a rotatable drum of the winch or hoist to a load to be moved, wherein a gearbox including a plurality of high-contact ratio spur-type gears is coupled to the input shaft and to the rotatable drum such that rotation of the input shaft at a first speed drives rotation of the rotatable drum at a second speed that is different than the first speed; and actuating the motor to drive rotation of the input shaft at the first speed and rotation of the rotatable drum at the second speed, thereby moving the load.

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

(1) FIG. 1 illustrates a perspective view of a winch including a gearbox having high-contact ratio gearing.

(2) FIG. 2 illustrates another perspective view of the winch of FIG. 1.

(3) FIG. 3 illustrates a perspective view of a drum of the winch of FIGS. 1 and 2.

(4) FIG. 4 illustrates a perspective view of the winch of FIGS. 1 and 2 with the drum of FIG. 3 removed to illustrate other features.

(5) FIG. 5 illustrates another perspective view of the winch of FIGS. 1 and 2 with the drum of FIG. 3 removed to illustrate other features.

(6) FIG. 6 illustrates a perspective view of an input end portion of the winch of FIGS. 1 and 2 with the drum of FIG. 3 and other components removed to illustrate other features.

(7) FIG. 7 illustrates a perspective view of an input end portion of the winch of FIGS. 1 and 2 with the drum of FIG. 3 and other components removed to illustrate other features, including an exterior of a planetary gearbox of the winch.

(8) FIG. 8 illustrates a perspective view of a fixed ring gear of the planetary gearbox of FIG. 7.

(9) FIG. 9 illustrates another perspective view of the fixed ring gear of FIG. 8.

(10) FIG. 10 illustrates a perspective view of the planetary gearbox of FIG. 7 with the fixed ring gear of FIGS. 8 and 9 removed to illustrate other features.

(11) FIG. 11 illustrates another perspective view of the planetary gearbox of FIG. 7 with the fixed ring gear of FIGS. 8 and 9 removed to illustrate other features.

(12) FIG. 12 illustrates a perspective view of the planetary gearbox of FIG. 7 with the fixed ring gear of FIGS. 8 and 9 and an input shaft removed to illustrate other features.

(13) FIG. 13 illustrates a perspective view of the planetary gearbox of FIG. 7 with the fixed ring gear of FIGS. 8 and 9, an input shaft, and a first set of sun and planet gears removed to illustrate other features.

(14) FIG. 14 illustrates a perspective view of the planetary gearbox of FIG. 7 with the fixed ring

gear of FIGS. 8 and 9, an input shaft, a first set of sun and planet gears, and a first gear carrier removed to illustrate other features.

(15) FIG. 15 illustrates a perspective view of the planetary gearbox of FIG. 7 with the fixed ring gear of FIGS. 8 and 9, an input shaft, a first set of sun and planet gears, a first gear carrier, and a second set of sun and planet gears removed to illustrate other features.

(16) FIG. 16 illustrates a perspective view of the planetary gearbox of FIG. 7 with the fixed ring gear of FIGS. 8 and 9, an input shaft, a first set of sun and planet gears, a first gear carrier, a second set of sun and planet gears, and a second gear carrier removed to illustrate other features.

(17) FIG. 17 illustrates a perspective view of the planetary gearbox of FIG. 7 with the fixed ring gear of FIGS. 8 and 9, an input shaft, a first set of sun and planet gears, a first gear carrier, a second set of sun and planet gears, a second gear carrier, and a third set of sun and planetary gears removed to illustrate other features.

(18) FIG. 18 illustrates a cross-sectional view of the winch of FIG. 1.

DETAILED DESCRIPTION

(19) In the following description, certain specific details are set forth in order to provide a thorough understanding of various disclosed embodiments. However, one skilled in the relevant art will recognize that embodiments may be practiced without one or more of these specific details, or with other methods, components, materials, etc. In other instances, well-known structures associated with the technology have not been shown or described in detail to avoid unnecessarily obscuring descriptions of the embodiments.

(20) Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, the appearances of the phrases “in one embodiment” or “in an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Also, as used in this specification and the appended claims, the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. It should also be noted that the term “or” is generally employed in its sense including “and/or” unless the context clearly dictates otherwise.

(21) The use of ordinals such as first, second and third does not necessarily imply a ranked sense of order, but rather may only distinguish between multiple instances of an act or structure. Various examples of suitable dimensions of components and other numerical values are provided herein. Such dimensions are accurate to within standard manufacturing tolerances unless stated otherwise.

(22) FIG. 1 illustrates a perspective view of a first end **102** of a winch **100** that has a central longitudinal axis **106**. FIG. 2 illustrates a perspective view of a second end **104** of the winch **100**, which is opposite to the first end **102** illustrated in FIG. 1 along the central longitudinal axis **106**. FIG. 18 illustrates a cross-sectional view of the winch **100**. The winch **100** itself, as well as various components of the winch **100**, have cylindrical, generally cylindrical, rotationally symmetric, and/or generally rotationally symmetric shapes when viewed along the central longitudinal axis **106**. That is, the winch **100**, and each of a variety of components of the winch **100**, have respective central longitudinal axes, with each of those respective central longitudinal axes being coincident with one another, as illustrated by axis **106** in FIGS. 1 and 2. Some components of the winch **100** are also configured to rotate about the central longitudinal axis **106**, as described elsewhere herein.

(23) FIG. 1 illustrates that the winch **100** includes a first mounting flange **108** at its first end **102**, which is oriented perpendicular to the central longitudinal axis **106** and includes a plurality of holes or apertures extending therethrough along respective axes parallel to the central longitudinal axis **106**. In use, the winch **100** can be mounted to another piece of machinery by mechanical fasteners such as bolts or screws that extend through the apertures in the first mounting flange **108** and through corresponding apertures in a mounting flange of the other piece of machinery. When the winch **100** is mounted to another piece of machinery in this way, the mounting first flange **108** is

rigidly coupled to the other piece of machinery and remains stationary with respect to the other piece of machinery during use.

(24) FIG. 2 illustrates that the winch **100** also includes a second mounting flange **110** at its second end **104**, which is oriented perpendicular to the central longitudinal axis **106** and parallel to the first mounting flange **108**, and includes a plurality of holes or apertures extending therethrough along respective axes parallel to the central longitudinal axis **106**. In use, the winch **100** can be mounted to the other piece of machinery by mechanical fasteners such as bolts or screws that extend through the apertures in the second mounting flange **110** and through corresponding apertures in a mounting flange of the other piece of machinery. When the winch **100** is mounted to another piece of machinery in this way, the second mounting flange **110** is rigidly coupled to the other piece of machinery and remains stationary with respect to the other piece of machinery during use.

(25) FIGS. 1 and 2 illustrate that the winch **100** includes a spool or drum **112** that is rotatable about the central longitudinal axis **106** with respect to the mounting flanges **108** and **110**. In use, a cable, rope, wire, or chain having a first end and a second end opposite the first end may be fastened at the first end thereof to the drum **112**. The cable may be wound up about the drum **112**, and the second end of the cable may be coupled to a load to be pulled by the winch **100**. The winch **100** can be operated to drive rotation of the drum **112** about the central longitudinal axis **106** with respect to the mounting flanges **108** and **110** and with respect to the piece of machinery to which the winch **100** is mounted, such as to wind up the cable onto the drum **112** to pull the load toward the winch **100**.

(26) FIG. 3 illustrates a perspective view of the drum **112** by itself, so that additional features of the drum **112** are visible. For example, as seen in FIG. 3, the drum **112** is hollow and has a cylindrical open internal space that extends along the central longitudinal axis **106**. The drum **112** also has a circular internal flange **114** that extends across its open internal space and is oriented perpendicular to the central longitudinal axis **106** at a location near the midpoint of the length of the drum **112** along the central longitudinal axis **106**. The internal flange **114** includes a plurality of holes or apertures extending therethrough along respective axes parallel to the central longitudinal axis **106**. In use, components of the winch **100** coupled to the first mounting flange **108**, including a ball bearing for rotatably mounting the drum **112** to the mounting flange **108**, can be positioned within the cylindrical open internal space within the drum **112** between the mounting flange **108** and the internal flange **114** of the drum **112**. Similarly, components of the winch **100** coupled to the second mounting flange **110**, including a ball bearing for rotatably mounting the drum **112** to the mounting flange **110**, can be positioned within the cylindrical open internal space within the drum **112** between the mounting flange **110** and the internal flange **114** of the drum **112**.

(27) FIGS. 4 and 5 illustrate the winch **100** with the drum **112** removed so that internal components of the winch **100** are visible. As illustrated in FIGS. 4 and 5, the winch **100** includes a first ball bearing assembly **116** having an inner race rigidly coupled to the first mounting flange **108**, an outer race rigidly coupled to an inner surface of the drum **112**, and a plurality of balls seated within a groove formed in the inner race, within a groove formed in the outer race, and between the inner race and the outer race. The first ball bearing assembly **116** rotatably couples the drum **112** to the first mounting flange **108** such that the drum **112** can rotate about the central longitudinal axis **106** with respect to the first mounting flange **108**, but cannot translate in any direction with respect to the first mounting flange **108**.

(28) As also illustrated in FIGS. 4 and 5, the winch **100** includes a second ball bearing assembly **118** having an inner race rigidly coupled to the second mounting flange **110**, an outer race rigidly coupled to an inner surface of the drum **112**, and a plurality of balls seated within a groove formed in the inner race, within a groove formed in the outer race, and between the inner race and the outer race. The second ball bearing assembly **118** rotatably couples the drum **112** to the second mounting flange **110** such that the drum **112** can rotate about the central longitudinal axis **106** with respect to the second mounting flange **110**, but cannot translate in any direction with respect to the second

mounting flange **110**. FIGS. **4** and **5** also illustrate a planetary gearbox **120** of the winch **100**, which is described in greater detail elsewhere herein.

(29) FIG. **6** illustrates a larger perspective view of the second end **104** of the winch **100** with the drum **112** and other components removed so that other features are visible. As illustrated in FIG. **6**, the winch **100** includes an input shaft coupler **122** to which an output shaft of a motor such as a hydraulic motor may be coupled to drive operation of the gearbox **120** and the drum **112**. As also illustrated in FIG. **6**, the winch **100** includes a third ball bearing assembly **124**, which may include two ball bearings each having an inner race rigidly coupled to the input shaft coupler **122**, an outer race rigidly coupled to other components of the winch **100**, and a plurality of balls seated within a groove formed in the inner race, within a groove formed in the outer race, and between the inner race and the outer race. The third ball bearing assembly **124** rotatably couples the input shaft coupler **122** to the rest of the winch **100**, including the second mounting flange **110**, such that the input shaft coupler **122** can rotate about the central longitudinal axis **106** with respect to the second mounting flange **110**, but cannot translate in any direction with respect to the second mounting flange **110**.

(30) FIG. **7** illustrates the same view as FIG. **6** with additional components removed so that other features are visible. As illustrated in FIG. **7**, the input shaft coupler **122** is a female-female coupler having a first, internal, input set of spline teeth at a first end thereof along the central longitudinal axis **106** that are configured to engage with complementary spline teeth of an output shaft of a motor, and a second, internal, output set of spline teeth at a second end thereof opposite to the first end thereof along the central longitudinal axis **106** that are configured to engage with complementary spline teeth of an input shaft **128** of the planetary gearbox **120**. Thus, the input shaft coupler **122** can transfer rotational motion and torque from the output shaft of the motor to the input shaft **128** of the planetary gearbox **120**. As also illustrated in FIG. **7**, the input shaft coupler **122** has a first groove **126a** and a second groove **126b** formed in an outer surface thereof, within which the two ball bearings of the ball bearing assembly **124** can be seated and to which the inner races of the two ball bearings of the ball bearing assembly **124** can be rigidly coupled.

(31) FIG. **7** illustrates that most of the planetary gearbox **120** is enclosed within or surrounded by a generally cylindrical outer ring gear **130** thereof. FIG. **8** illustrates a perspective view of the cylindrical outer ring gear **130** by itself, so that additional features of the ring gear **130** are visible. FIG. **9** illustrates another perspective view of the cylindrical outer ring gear **130** by itself, so that additional features of the ring gear **130** are visible. As illustrated in FIGS. **8** and **9**, the ring gear **130** has an overall cylindrical shape that extends along the central longitudinal axis **106**, has a cylindrical open internal space that extends along the central longitudinal axis **106**, and has a relatively smooth outer surface. As also illustrated in FIGS. **8** and **9**, the ring gear **130** has a first generally cylindrical internal surface **132** at a first end thereof along the central longitudinal axis **106**, a second generally cylindrical internal surface **134** at a second end thereof opposite the first end thereof along the central longitudinal axis **106**, and a third generally cylindrical internal surface **136** between the first generally cylindrical internal surface **132** and the second generally cylindrical internal surface **134** along the central longitudinal axis **106**.

(32) As illustrated in FIGS. **8** and **9**, the first internal surface **132** is closer to the second end **104** of the winch **100** than the second internal surface **134** is, and the second internal surface **134** is closer to the first end **102** of the winch **100** than the first internal surface **132** is, when the winch **100** is assembled. As also illustrated in FIGS. **8** and **9**, the first internal surface **132** has a smaller diameter than the third internal surface **136** does, and the third internal surface **136** has a smaller internal diameter than the second internal surface **134** does, such that, when the ring gear **130** is assembled into and positioned within the winch **100**, the cylindrical open internal space within the ring gear **130** gets progressively wider, in a plurality of (e.g., three) steps in a direction extending from the second end **104** of the winch **100** to the first end **102** of the winch **100**.

(33) As illustrated in FIGS. **8** and **9**, the first internal surface **132** of the ring gear **130** includes a set

of inward-facing inner spline teeth, the second internal surface **134** of the ring gear **130** includes a first set of inward-facing inner gear teeth having a first set of dimensions, and the third internal surface **136** of the ring gear **130** includes a second set of inward-facing inner gear teeth having a second set of dimensions. As illustrated in FIG. 7, the set of inner spline teeth of the first internal surface **132** do not mate with gears or gear teeth of the planetary gearbox **120**. Rather, the set of inner spline teeth of the first internal surface **132** engage complementary spline teeth that are rigidly coupled to the second mounting flange **110**. Such engagement can prevent or prohibit rotation of the ring gear **130** about the central longitudinal axis **106** and keep the entirety of the ring gear **130** stationary with respect to the second mounting flange **110**. Thus, in use, the ring gear **130** is stationary. The first and second sets of inner gear teeth of the ring gear **130** mate with and engage with other gears of the planetary gearbox **120** when the winch **100** is in use, as described elsewhere herein.

(34) FIG. 10 illustrates a first perspective view, and FIG. 11 illustrates a second perspective view, of the planetary gearbox **120** with the outer ring gear **130** thereof removed so that other features are visible. As illustrated in FIGS. 10 and 11, the planetary gearbox **120** includes, in addition to the input shaft **128** and the outer ring gear **130**, a first sun gear **138** having, and rotatable about, a central longitudinal axis coincident with the central longitudinal axis **106**, a first set of three planet gears **140** spaced equidistantly apart from one another about the first sun gear **138** and each having, and rotatable about, a respective central longitudinal axis parallel to the central longitudinal axis **106**, and a first gear carrier **142** having, and rotatable about, a central longitudinal axis coincident with the central longitudinal axis **106**.

(35) As also illustrated in FIGS. 10 and 11, the planetary gearbox **120** further includes a second sun gear **144** having, and rotatable about, a central longitudinal axis coincident with the central longitudinal axis **106**, a second set of three planet gears **146** spaced equidistantly apart from one another about the second sun gear **144** and each having, and rotatable about, a respective central longitudinal axis parallel to the central longitudinal axis **106**, and a second gear carrier **148** having, and rotatable about, a central longitudinal axis coincident with the central longitudinal axis **106**. As also illustrated in FIGS. 10 and 11, the planetary gearbox **120** further includes a third sun gear **150** having, and rotatable about, a central longitudinal axis coincident with the central longitudinal axis **106**, a third set of three planet gears **152** spaced equidistantly apart from one another about the third sun gear **150** and each having, and rotatable about, a respective central longitudinal axis parallel to the central longitudinal axis **106**, and a third gear carrier **154** having, and rotatable about, a central longitudinal axis coincident with the central longitudinal axis **106**.

(36) As illustrated in FIG. 10 in particular, the third gear carrier **154** includes a generally cylindrical, disc-shaped main body having a central longitudinal axis coincident with the central longitudinal axis **106**, and five pegs, pins, or shafts that extend outward from a major surface of the main body along respective axes parallel to the central longitudinal axis **106** in a direction extending away from the planet gears **152**. In use, these shafts are positioned within and mated with the apertures extending through the internal flange **114** of the drum **112** illustrated in FIG. 3 such that, as the third gear carrier **154** is driven to rotate about the central longitudinal axis **106**, the drum **112** is also driven to rotate about the central longitudinal axis **106**.

(37) As illustrated in FIGS. 10 and 11, and as described further elsewhere herein, the planetary gearbox **120** includes a compound planetary gear system having a plurality of (e.g., two, three in the illustrated embodiment, four, five, six, or more) planetary gear sets or stages arranged in series with one another. In particular, the input shaft **128** drives operation and rotation of a first planetary gear stage including the first sun gear **138**, the first set of planet gears **140**, and the first gear carrier **142**, while operation and rotation of the first planetary gear stage (and an output thereof) in turn drives operation and rotation of a second planetary gear stage including the second sun gear **144**, the second set of planet gears **146**, and the second gear carrier **148**, and operation and rotation of the second planetary gear stage (and an output thereof) in turn drives operation and rotation of a

third planetary gear stage including the third sun gear **150**, the third set of planet gears **152**, and the third gear carrier **154**. Such an arrangement can result in a larger transmission ratio and/or smaller-diameter system than alternative planetary gearing arrangements. In some alternative implementations, the planetary gearbox **120** is a single-stage planetary gearbox. In other alternative implementations, the gearbox **120** is a simple spur-type gear drive rather than a planetary gearbox. (38) FIG. **12** illustrates the planetary gearbox **120** with the outer ring gear **130** and input shaft **128** thereof removed so that other features are visible. In particular, FIG. **12** illustrates that the first sun gear **138** is hollow and has a set of internal spline teeth meshed with external spline teeth formed in an end portion of the input shaft **128** engaged with the first sun gear **138**, such that rotation of the input shaft **128** about the central longitudinal axis **106** drives rotation of the first sun gear **138** about the central longitudinal axis **106** and such that torque can be transferred from the input shaft **128** to the first sun gear **138**. FIG. **12** also illustrates that the first sun gear **138** has a set of external gear teeth meshed with external gear teeth of the first set of planet gears **140**, such that rotation of the sun gear **138** about the central longitudinal axis **106** drives rotation of the planet gears **140** about their own respective central longitudinal axes and such that torque can be transferred from the sun gear **138** to the planet gears **140**.

(39) When the planetary gearbox **120** is assembled, the external gear teeth of the planet gears **140** are meshed with the internal gear teeth of the third internal surface **136** of the outer ring gear **130**. Thus, together, the first sun gear **138**, first set of planet gears **140**, the first gear carrier **142**, and the third generally cylindrical internal surface **136** of outer ring gear **130** that is meshed with the first set of planet gears **140** collectively form a first planetary gear set or first planetary gear stage. When the winch **100** is in use, the input shaft **128** drives operation of the planetary gearbox **120** by driving rotation of, or transferring torque to, the first sun gear **138**. The sun gear **138** in turn drives rotation of, or transfers torque to, the planet gears **140**. Because the planet gears **140** are meshed with the outer ring gear **130**, which is stationary, however, they are not freely rotatable about their own stationary central longitudinal axes. Thus, by driving rotation of, or transferring torque to, the planet gears **140**, the planet gears **140** are driven or urged to move circumferentially as a unit about the sun gear **138** such that their own central longitudinal axes move circumferentially as a unit about the sun gear **138** and about the central longitudinal axis **106** as they rotate about their own central longitudinal axes.

(40) FIG. **13** illustrates the planetary gearbox **120** with the outer ring gear **130**, input shaft **128**, first sun gear **138**, and first planet gears **140** thereof removed so that other features are visible. In particular, FIG. **13** illustrates that the first gear carrier **142** includes a generally cylindrical, disc-shaped, hollow main body having a central longitudinal axis coincident with the central longitudinal axis **106**, and three pegs, pins, or shafts that extend outward from a major surface of the main body along respective axes parallel to the central longitudinal axis **106** toward the planet gears **140**. In use, the first planet gears **140** are rotatably mounted onto the shafts of the gear carrier **142** such that, as the planet gears **140** are driven to rotate circumferentially as a unit about the sun gear **138** and the central longitudinal axis **106**, the gear carrier **142** is also driven to rotate about the central longitudinal axis **106**. As also illustrated in FIG. **13**, the hollow main body of the gear carrier **142** has a set of internal spline teeth meshed with external spline teeth of the second sun gear **144** such that rotation of the gear carrier **142** about the central longitudinal axis **106** drives rotation of the second sun gear **144** about the central longitudinal axis **106**.

(41) FIG. **14** illustrates the planetary gearbox **120** with the outer ring gear **130**, input shaft **128**, first sun gear **138**, first planet gears **140**, and first gear carrier **142** thereof removed so that other features are visible. In particular, FIG. **14** illustrates that the second sun gear **144** has a set of external spline teeth meshed with the internal spline teeth of the first gear carrier **142** engaged with the second sun gear **144**, such that rotation of the gear carrier **142** about the central longitudinal axis **106** drives rotation of the second sun gear **144** about the central longitudinal axis **106** and such that torque can be transferred from the gear carrier **142** to the second sun gear **144**. FIG. **14** also illustrates that the

second sun gear **144** has a set of external gear teeth meshed with external gear teeth of the second set of planet gears **146**, such that rotation of the sun gear **144** about the central longitudinal axis **106** drives rotation of the planet gears **146** about their own respective central longitudinal axes and such that torque can be transferred from the sun gear **144** to the planet gears **146**.

(42) When the planetary gearbox **120** is assembled, the external gear teeth of the planet gears **146** are meshed with the internal gear teeth of a longitudinally inner portion of the second generally cylindrical internal surface **134** of the outer ring gear **130**. Thus, together, the second sun gear **144**, second set of planet gears **146**, the second gear carrier **148**, and the longitudinally inner portion of the second generally cylindrical internal surface **134** of outer ring gear **130** that is meshed with the second set of planet gears **146** collectively form a second planetary gear set or second planetary gear stage. When the winch **100** is in use, the first planetary gear stage drives further operation of the planetary gearbox **120** by driving rotation of, or transferring torque to, the second sun gear **144**. The sun gear **144** in turn drives rotation of, or transfers torque to, the planet gears **146**. Because the planet gears **146** are meshed with the outer ring gear **130**, which is stationary, however, they are not freely rotatable about their own stationary central longitudinal axes. Thus, by driving rotation of, or transferring torque to, the planet gears **146**, the planet gears **146** are driven or urged to move circumferentially as a unit about the sun gear **144** such that their own central longitudinal axes move circumferentially as a unit about the sun gear **144** and about the central longitudinal axis **106** as they rotate about their own central longitudinal axes.

(43) FIG. **15** illustrates the planetary gearbox **120** with the outer ring gear **130**, input shaft **128**, first sun gear **138**, first planet gears **140**, first gear carrier **142**, second sun gear **144**, and second planet gears **146** thereof removed so that other features are visible. In particular, FIG. **15** illustrates that the second gear carrier **148** includes a generally cylindrical, disc-shaped, hollow main body having a central longitudinal axis coincident with the central longitudinal axis **106**, and three pegs, pins, or shafts that extend outward from a major surface of the main body along respective axes parallel to the central longitudinal axis **106** toward the planet gears **146**. In use, the second planet gears **146** are rotatably mounted onto the shafts of the gear carrier **148** such that, as the planet gears **146** are driven to rotate circumferentially as a unit about the sun gear **144** and the central longitudinal axis **106**, the gear carrier **148** is also driven to rotate about the central longitudinal axis **106**. As also illustrated in FIG. **15**, the hollow main body of the gear carrier **148** has a set of internal spline teeth meshed with external spline teeth of the third sun gear **150** such that rotation of the gear carrier **148** about the central longitudinal axis **106** drives rotation of the third sun gear **150** about the central longitudinal axis **106**.

(44) FIG. **16** illustrates the planetary gearbox **120** with the outer ring gear **130**, input shaft **128**, first sun gear **138**, first planet gears **140**, first gear carrier **142**, second sun gear **144**, second planet gears **146**, and second gear carrier **148** thereof removed so that other features are visible. In particular, FIG. **16** illustrates that the third sun gear **150** has a set of external spline teeth meshed with the internal spline teeth of the second gear carrier **148** engaged with the third sun gear **150**, such that rotation of the gear carrier **148** about the central longitudinal axis **106** drives rotation of the second sun gear **150** about the central longitudinal axis **106** and such that torque can be transferred from the gear carrier **148** to the third sun gear **150**. FIG. **16** also illustrates that the third sun gear **150** has a set of external gear teeth meshed with external gear teeth of the third set of planet gears **152**, such that rotation of the sun gear **150** about the central longitudinal axis **106** drives rotation of the planet gears **152** about their own respective central longitudinal axes and such that torque can be transferred from the sun gear **150** to the planet gears **152**.

(45) When the planetary gearbox **120** is assembled, the external gear teeth of the planet gears **152** are meshed with the internal gear teeth of a longitudinally outer portion of the second generally cylindrical internal surface **134** of the outer ring gear **130**. Thus, together, the third sun gear **150**, third set of planet gears **152**, the third gear carrier **154**, and the longitudinally outer portion of the second generally cylindrical internal surface **134** of outer ring gear **130** that is meshed with the

third set of planet gears **152** collectively form a third planetary gear set or third planetary gear stage. When the winch **100** is in use, the second planetary gear stage drives further operation of the planetary gearbox **120** by driving rotation of, or transferring torque to, the third sun gear **150**. The sun gear **150** in turn drives rotation of, or transfers torque to, the planet gears **152**. Because the planet gears **152** are meshed with the outer ring gear **130**, which is stationary, however, they are not freely rotatable about their own stationary central longitudinal axes. Thus, by driving rotation of, or transferring torque to, the planet gears **152**, the planet gears **152** are driven or urged to move circumferentially as a unit about the sun gear **150** such that their own central longitudinal axes move circumferentially as a unit about the sun gear **150** and about the central longitudinal axis **106** as they rotate about their own central longitudinal axes.

(46) FIG. **17** illustrates the planetary gearbox **120** with the outer ring gear **130**, input shaft **128**, first sun gear **138**, first planet gears **140**, first gear carrier **142**, second sun gear **144**, second planet gears **146**, second gear carrier **148**, third sun gear **150**, and third planet gears **152** thereof removed so that other features are visible. In particular, FIG. **17** illustrates that the third gear carrier **154** includes a generally cylindrical, disc-shaped main body having a central longitudinal axis coincident with the central longitudinal axis **106**, and five pegs, pins, or shafts that extend outward from a major surface of the main body along respective axes parallel to the central longitudinal axis **106** toward the planet gears **152**. In use, the third planet gears **152** are rotatably mounted onto the shafts of the gear carrier **154** such that, as the planet gears **152** are driven to rotate circumferentially as a unit about the sun gear **150** and the central longitudinal axis **106**, the gear carrier **154** is also driven to rotate about the central longitudinal axis **106**. As described elsewhere herein, in use, the gear carrier **154** is mated with the flange **114** of the drum **112** such that, as the third gear carrier **154** is driven to rotate about the central longitudinal axis **106**, the drum **112** is also driven to rotate about the central longitudinal axis **106**.

(47) As described elsewhere herein, each of the outer ring gear **130**, the first sun gear **138**, the first set of planet gears **140**, the second sun gear **144**, the second set of planet gears **146**, the third sun gear **150**, and the third set of planet gears **152** each have one or more sets of internal and/or external gear teeth meshed with corresponding gear teeth of other components of the planetary gearbox **120**. Such components are involute spur-type gears or related involute spur-type gearing components, and their respective sets of gear teeth are involute spur-type gear teeth. Further, such components may be high-contact ratio involute spur-type gears or related high-contact ratio involute spur-type gearing components, and their respective sets of gear teeth may be high-contact ratio involute spur-type gear teeth.

(48) A spur-type gear has a pitch, which is the distance (e.g., an angular distance with respect to a center of the gear) between similar or corresponding points (e.g., sides or centers) of two adjacent teeth. As used herein, the term “contact ratio” may be used to mean the number of pitches a tooth rotates through while in constant contact with a corresponding tooth of a meshed gear. The contact ratio is also a measure of the average number of teeth in contact between two meshed gears while the gears are in use, where a higher contact ratio indicates that, on average, more teeth are engaged while the gears are in use and a lower contact ratio indicates that, on average, fewer teeth are engaged while the gears are in use.

(49) As used herein, the term “high-contact ratio” may be used to mean a higher contact ratio than that specified in one or more standardized specifications for gear and gear tooth dimensions, such as may be promulgated by any of various generally recognized standards-setting organizations. For example, the term “high-contact ratio” may be used to mean a higher contact ratio than that specified in ANSI/AGMA B88, titled “Tooth Thickness Specification and Measurement.” Generally speaking, high-contact ratio gear teeth are longer than standard gear teeth such that high-contact ratio gearing provides a higher number of active teeth in mesh when in use than standard gearing.

(50) A more detailed discussion of the geometry of the gears and gear teeth described herein

follows. As used herein, geometrical terminology may be used in accordance with the explanations provided in AGMA 933-B03, titled “Basic Gear Geometry.” A spur-type gear has a central longitudinal axis and a gear center on the central longitudinal axis about which it rotates, and a plane of rotation perpendicular to the central longitudinal axis and including the gear center within which it rotates. A first spur-type gear may be meshed with a second spur-type gear such that the first and second spur-type gears have a common plane of rotation. The first spur-type gear can have a first pitch radius and the second spur-type gear can have a second pitch radius such that the sum of the first and second pitch radii is equal to the distance within the common plane of rotation from the gear center of the first spur-type gear to the gear center of the second spur-type gear, and such that a ratio of the first pitch radius to the second pitch radius is equal to the ratio of the number of gear teeth in the first spur-type gear to the number of gear teeth in the second spur-type gear.

(51) Each of the first and second spur-type gears can have a respective pitch circle centered on its respective central longitudinal axis and gear center and lying within the common plane of rotation, and having a radius equal to its respective pitch radius. Each of the first and second spur-type gears can have a respective pitch diameter that is twice its pitch radius, such that its respective pitch circle has a diameter that is twice its radius. Each of the first and second spur-type gears can also have a respective diametral pitch, which is the ratio of the spur-type gear's number of teeth to the spur-type gear's pitch diameter.

(52) A gear tooth of a gear can have an addendum, which is the radial length of the portion of the tooth that extends outward from the gear's pitch circle away from the gear center to the top of the tooth (which may be referred to as a tooth tip), and a dedendum, which is the radial length of the portion of the tooth that extends inward from the gear's pitch circle toward the gear center to the bottom of the space or gap between the gear tooth and an adjacent gear tooth (which may be referred to as a tooth root). In standard gears and gear teeth, such as those specified in relevant AGMA standards, the addendum is typically 1.00 divided by the diametral pitch, while the dedendum is typically 1.25 divided by the diametral pitch. Related metric standards, such as ISO 6336, are geometrically equivalent in this regard, but may refer to a “module” rather than a diametral pitch, where the “module” uses different units than, and is an inverse with respect to, the diametral pitch. In some cases, a high-contact ratio gear or a high-contact ratio gear tooth can therefore have a longer addendum and/or a longer dedendum than standard gears or gear teeth. As a result of having a longer addendum, the top of the tooth may be narrower and radii of curvatures thereof may be smaller. As a result of having a longer dedendum, the bottom of the tooth may be wider (and bottoms of the corresponding spaces or gaps between adjacent teeth may be narrower, and radii of curvature thereof may be smaller).

(53) For example, a high-contact ratio gear may have high-contact ratio gear teeth, and high-contact ratio gear teeth may have an addendum greater than 1.00 divided by the respective diametral pitch, greater than or equal to 1.05 divided by the respective diametral pitch, greater than or equal to 1.10 divided by the respective diametral pitch, greater than or equal to 1.15 divided by the respective diametral pitch, greater than or equal to 1.20 divided by the respective diametral pitch, greater than or equal to 1.25 divided by the respective diametral pitch, greater than or equal to 1.30 divided by the respective diametral pitch, greater than or equal to 1.35 divided by the respective diametral pitch, greater than or equal to 1.40 divided by the respective diametral pitch, greater than or equal to 1.45 divided by the respective diametral pitch, greater than or equal to 1.50 divided by the respective diametral pitch, greater than or equal to 1.55 divided by the respective diametral pitch, or greater than or equal to 1.60 divided by the respective diametral pitch.

(54) As another example, a high-contact ratio gear may have high-contact ratio gear teeth, and high-contact ratio gear teeth may have a dedendum greater than 1.25 divided by the respective diametral pitch, greater than or equal to 1.30 divided by the respective diametral pitch, greater than or equal to 1.35 divided by the respective diametral pitch, greater than or equal to 1.40 divided by

the respective diametral pitch, greater than or equal to 1.45 divided by the respective diametral pitch, greater than or equal to 1.50 divided by the respective diametral pitch, greater than or equal to 1.55 divided by the respective diametral pitch, greater than or equal to 1.60 divided by the respective diametral pitch, greater than or equal to 1.65 divided by the respective diametral pitch, greater than or equal to 1.70 divided by the respective diametral pitch, greater than or equal to 1.75 divided by the respective diametral pitch, or greater than or equal to 1.80 divided by the respective diametral pitch.

(55) In some cases, such addendum and dedendum lengths can result in a gear having a contact ratio that exceeds 1.60, or that exceeds 1.65, or that exceeds 1.70, or that exceeds 1.75, or that exceeds 1.80, or that exceeds 1.85, or that exceeds 1.90, or that exceeds 1.95, or that exceeds 2.00.

(56) Addendum and dedendum dimensions of a gear tooth generally have upper limits determined by the involute curvatures and other related dimensions of the tooth. That is, due to the involute curvatures of the tooth, as the addendum is increased, the tooth tip becomes increasingly closer to forming a point where its two sides intersect, until the tooth tip forms a point where its two sides intersect and the addendum can no longer be increased. The dedendum of the gear tooth can have an upper limit determined in a similar manner. A gear tooth having a pointed tooth tip is typically fragile and difficult to manufacture relative to a gear tooth not having a pointed tooth tip. As a result, a pointed tooth tip may be avoided by providing a gear tooth with a tooth tip thickness that extends from a radially outermost end of a first one of its sides to a radially outermost end of a second one of its sides opposite to the first.

(57) As understood in accordance with standard gear tooth dimensions and the description herein, a minimum gear tooth tip thickness (which may also be referred to in the industry as a top land thickness) may be 0.2 divided by the diametral pitch. The gears described herein may have gear teeth having gear tooth tip thicknesses greater than zero, or greater than or equal to 0.1 divided by the diametral pitch, 0.2 divided by the diametral pitch, 0.3 divided by the diametral pitch, or 0.4 divided by the diametral pitch. Maximum addendum and dedendum dimensions may be determined by specifying a gear tooth tip thickness or a minimum gear tooth tip thickness, and may be calculated based on such a specification and other known dimensions of the gear and its gear teeth. Resulting maximum addendum dimensions may be 1.05, 1.10, 1.15, 1.20, 1.25, 1.30, 1.35, 1.40, 1.45, 1.50, 1.55, 1.60, 1.65, 1.70, 1.75, or 1.80 divided by the respective diametral pitch. Resulting maximum dedendum dimensions may be 1.30, 1.35, 1.40, 1.45, 1.50, 1.55, 1.60, 1.65, 1.70, 1.75, 1.80, 1.85, 1.90, 1.95, or 2.00 divided by the respective diametral pitch.

(58) The geometry discussed herein is primarily directed to gears having external gear teeth and such external gear teeth, such as the sun gears and the sets of planet gears. Nevertheless, the geometry discussed herein can be easily adapted for use in gears having internal gear teeth and such internal gear teeth, such as the outer ring gear. Such adaptation generally requires that the geometry of the gear teeth be turned “inside-out.” In such adaptations, the addendum becomes the radial length of the portion of the tooth that extends inward from the gear's pitch circle toward the gear center to the tooth tip, and the dedendum becomes the radial length of the portion of the tooth that extends outward from the gear's pitch circle away from the gear center to the tooth root.

(59) In some implementations, all of the gears in the planetary gearbox **120** are high-contact ratio spur-type gears and all of the gear teeth in the planetary gearbox **120** are high-contact ratio spur-type gear teeth. All of, or any subset of, such gears and such gear teeth may have an addendum greater than 1.00 divided by the respective diametral pitch, or greater than or equal to 1.05, 1.10, 1.15, 1.20, 1.25, 1.30, 1.35, 1.40, 1.45, or 1.50 divided by the respective diametral pitch, as well as a dedendum greater than 1.25 divided by the respective diametral pitch, or greater than or equal to 1.30, 1.35, 1.40, 1.45, 1.50, 1.55, 1.60, 1.65, 1.70, or 1.75 divided by the respective diametral pitch, and a correspondingly high contact ratio resulting from such dimensions.

(60) In some implementations, such a subset can be all of the gears and all of the gear teeth in the first planetary gear stage of the planetary gearbox **120** (e.g., the first sun gear **138** and its gear teeth,

the first set of planet gears **140** and their gear teeth, and the third generally cylindrical internal surface **136** of outer ring gear **130** that is meshed with the first set of planet gears **140**, and its gear teeth). In some implementations, such a subset can be all of the gears and all of the gear teeth in the second planetary gear stage of the planetary gearbox **120** (e.g., the second sun gear **144** and its gear teeth, the second set of planet gears **146** and their gear teeth, and the longitudinally inner portion of the second generally cylindrical internal surface **134** of outer ring gear **130** that is meshed with the second set of planet gears **146**, and its gear teeth). In some implementations, such a subset can be all of the gears and all of the gear teeth in the third planetary gear stage of the planetary gearbox **120** (e.g., the third sun gear **150** and its gear teeth, the third set of planet gears **152** and their gear teeth, and the longitudinally outer portion of the second generally cylindrical internal surface **134** of outer ring gear **130** that is meshed with the third set of planet gears **152**, and its gear teeth).

(61) In some implementations, such a subset can be all of the sun gears and their respective gear teeth (e.g., each of the first sun gear **138**, second sun gear **144**, and third sun gear **150**, and their respective gear teeth). In some implementations, such a subset can be all of the planet gears and their respective gear teeth (e.g., each of the first set of planet gears **140**, each of the second set of planet gears **146**, each of the third set of planet gears **152**, and their respective gear teeth). In some implementations, such a subset can be the outer ring gear **130**, its second generally cylindrical internal surface **134** and third generally cylindrical internal surface **136**, and the respective gear teeth thereof.

(62) While the present disclosure has focused on high-contact ratio gearing in the winch **100**, the features described herein may be applied to other devices, such as hoists, track drives, wheel drives, or other drive systems including gearboxes. Such devices, including the winch **100**, can be mounted, such as in the manner described herein, to heavy equipment or machinery, such as cranes, mobile cranes, offshore (e.g., oil platform) cranes, utility vehicles such as bucket trucks, trucks, trailers, naval vessels, and tractor-type equipment such as bulldozers.

(63) The gears described herein are high-contact ratio gears and include high-contact ratio gear teeth. As a result, in each meshed pair of gears described herein, a greater number of gear teeth are, on average, in contact with one another than would be in comparable standard, non-high-contact ratio gear systems. As a result, loads are distributed over a greater number of teeth, thereby increasing load carrying capacity and decreasing bending or flexure of the teeth, thereby reducing noise and other NVH-related issues.

(64) The various embodiments described above can be combined to provide further embodiments. These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

Claims

1. A winch or hoist, comprising: an input shaft; a rotatable drum; and a gearbox including a plurality of high-contact ratio spur-type gears, the gearbox coupled to the input shaft and to the rotatable drum such that rotation of the input shaft at a first speed drives rotation of the rotatable drum at a second speed that is different than the first speed, wherein the gearbox is a compound planetary gearbox system having a plurality of planetary gear stages arranged in series, wherein the input shaft drives operation and rotation of a first stage of the planetary gear stages including a first sun gear, a first set of planet gears, and a first gear carrier, while operation and rotation of the first stage in turn drives operation and rotation of a second stage of the planetary gear stages including a second sun gear, a second set of planet gears, and a second gear carrier, and operation and rotation of the second stage in turn drives operation and rotation of a third stage of the planetary gear stages

- including a third sun gear, a third set of planet gears, and a third gear carrier, and wherein rotation of the third gear carrier drives rotation of the rotatable drum via an internal flange of the rotatable drum to which the third gear carrier is insertably received, and wherein each of the first, second and third sun gears and each of the first, second and third sets of planet gears are the high-contact ratio spur-type gears of the gearbox.
2. The winch or hoist of claim 1 wherein the high-contact ratio spur-type gears include internal gear teeth and external gear teeth.
 3. The winch or hoist of claim 1 wherein the high-contact ratio spur-type gears have a higher contact ratio than specified in ANSI/AGMA B88.
 4. The winch or hoist of claim 1 wherein the high-contact ratio spur-type gears include gear teeth having longer addendums than specified in ANSI/AGMA B88.
 5. The winch or hoist of claim 1 wherein the high-contact ratio spur-type gears include gear teeth having longer dedendums than specified in ANSI/AGMA B88.
 6. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having addendums greater than 1.00 divided by the respective diametral pitch.
 7. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having addendums greater than or equal to 1.05 divided by the respective diametral pitch.
 8. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having addendums greater than or equal to 1.10 divided by the respective diametral pitch.
 9. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having addendums greater than or equal to 1.15 divided by the respective diametral pitch.
 10. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having addendums greater than or equal to 1.20 divided by the respective diametral pitch.
 11. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having dedendums greater than 1.25 divided by the respective diametral pitch.
 12. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having dedendums greater than or equal to 1.30 divided by the respective diametral pitch.
 13. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having dedendums greater than or equal to 1.35 divided by the respective diametral pitch.
 14. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a respective diametral pitch and includes gear teeth having dedendums greater than or equal to 1.40 divided by the respective diametral pitch.
 15. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a contact ratio greater than 1.60.
 16. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a contact ratio greater than 1.80.
 17. The winch or hoist of claim 1 wherein each of the high-contact ratio spur-type gears has a contact ratio greater than 2.00.
-