

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12405497
B2
September 02, 2025
Oh; Chulwoo et al.

Broadband adaptive lens assembly for augmented reality display

Abstract

A display device comprises a waveguide configured to guide light in a lateral direction parallel to an output surface of the waveguide. The waveguide is further configured to outcouple the guided light through the output surface. The display device additionally comprises a broadband adaptive lens assembly configured to incouple and to diffract therethrough the outcoupled light from the waveguide. The broadband adaptive lens assembly comprises a first waveplate lens comprising a liquid crystal (LC) layer arranged such that the waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the first waveplate lens and configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm. The broadband adaptive lens assembly is configured to be selectively switched between a plurality of states having different optical powers.

Inventors: Oh; Chulwoo (Cedar Park, TX), Komanduri; Ravi Kumar (Austin, TX), Patterson; Roy Matthew (Hutto, TX), Carden; Charles Scott (Austin, TX), Miller; Michael Nevin (Austin, TX), Singh; Vikramjit (Pflugerville, TX)

Applicant: Magic Leap, Inc. (Plantation, FL)

Family ID: 66247745

Assignee: MAGIC LEAP, INC. (Plantation, FL)

Appl. No.: 18/601808

Filed: March 11, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240255796 A1	Aug. 01, 2024

Related U.S. Application Data

continuation parent-doc US 17582845 20220124 US 11960165 child-doc US 18601808
division parent-doc US 16171290 20181025 US 11231612 20220125 child-doc US 17582845
us-provisional-application US 62577672 20171026

Publication Classification

Int. Cl.: G02F1/1335 (20060101); G02B1/00 (20060101); G02B5/18 (20060101); G02B5/30 (20060101); G02B6/12 (20060101); G02B6/122 (20060101); G02B27/01 (20060101); G02F1/1337 (20060101);

G06T19/00 (20110101); **G06V20/20** (20220101); **G09G3/00** (20060101); **G09G5/00** (20060101); **G09G5/14** (20060101)

U.S. Cl.:

CPC **G02F1/133526** (20130101); **G02B1/00** (20130101); **G02B5/1833** (20130101); **G02B5/30** (20130101); **G02B6/12** (20130101); **G02B6/122** (20130101); **G02B27/0172** (20130101); **G02F1/133528** (20130101); **G02F1/1337** (20130101); **G06T19/006** (20130101); **G06V20/20** (20220101); **G09G3/002** (20130101); **G09G3/003** (20130101); **G09G5/00** (20130101); **G09G5/14** (20130101);

Field of Classification Search

CPC: G02F (1/133526); G02F (1/133528)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3632865	12/1971	Haskell et al.	N/A	N/A
4204742	12/1979	Johnson et al.	N/A	N/A
4984179	12/1990	Waldern	N/A	N/A
5138555	12/1991	Albrecht	N/A	N/A
5271093	12/1992	Hata et al.	N/A	N/A
5311879	12/1993	Yamada et al.	N/A	N/A
5311897	12/1993	Greer	N/A	N/A
5422653	12/1994	Maguire, Jr.	N/A	N/A
5526042	12/1995	Ozawa et al.	N/A	N/A
5742264	12/1997	Inagaki et al.	N/A	N/A
5933125	12/1998	Fernie et al.	N/A	N/A
6011526	12/1999	Toyoshima et al.	N/A	N/A
6151179	12/1999	Poss	N/A	N/A
6441811	12/2001	Sawada et al.	N/A	N/A
6850221	12/2004	Tickle	N/A	N/A
6882384	12/2004	Sharp	349/78	G02F 1/13473
6917370	12/2004	Benton	N/A	N/A
6947219	12/2004	Ou	N/A	N/A
7023536	12/2005	Zhang et al.	N/A	N/A
7038846	12/2005	Mandella	N/A	N/A
7088440	12/2005	Buermann et al.	N/A	N/A
7110100	12/2005	Buermann et al.	N/A	N/A
7113270	12/2005	Buermann et al.	N/A	N/A
7161664	12/2006	Buermann et al.	N/A	N/A
7203384	12/2006	Carl	N/A	N/A
7268956	12/2006	Mandella	N/A	N/A
7386799	12/2007	Clanton et al.	N/A	N/A
7474809	12/2008	Carl et al.	N/A	N/A
7729515	12/2009	Mandella et al.	N/A	N/A
7758185	12/2009	Lewis	N/A	N/A
7826641	12/2009	Mandella et al.	N/A	N/A
7961909	12/2010	Mandella et al.	N/A	N/A
8223024	12/2011	Petrou	N/A	N/A
8508830	12/2012	Wang	N/A	N/A
8542219	12/2012	Carl et al.	N/A	N/A
8553935	12/2012	Mandella et al.	N/A	N/A
8696113	12/2013	Lewis	N/A	N/A
8730129	12/2013	Solomon	N/A	N/A
8757812	12/2013	Melville et al.	N/A	N/A

8831278	12/2013	Fedorovskaya et al.	N/A	N/A
8832233	12/2013	Brin et al.	N/A	N/A
8879155	12/2013	Teller	N/A	N/A
8897494	12/2013	Mandella et al.	N/A	N/A
8970709	12/2014	Gonzalez-Banos et al.	N/A	N/A
9081426	12/2014	Armstrong	N/A	N/A
9189856	12/2014	Gonzalez-Banos et al.	N/A	N/A
9215293	12/2014	Miller	N/A	N/A
9229540	12/2015	Mandella et al.	N/A	N/A
9235934	12/2015	Mandella et al.	N/A	N/A
9239473	12/2015	Lewis	N/A	N/A
9348143	12/2015	Gao et al.	N/A	N/A
9417452	12/2015	Schowengerdt et al.	N/A	N/A
9470906	12/2015	Kaji et al.	N/A	N/A
9547174	12/2016	Gao et al.	N/A	N/A
9671566	12/2016	Abovitz et al.	N/A	N/A
9740006	12/2016	Gao	N/A	N/A
9791700	12/2016	Schowengerdt	N/A	N/A
9851563	12/2016	Gao et al.	N/A	N/A
9857591	12/2017	Welch et al.	N/A	N/A
9874749	12/2017	Bradski et al.	N/A	N/A
10055887	12/2017	Gil et al.	N/A	N/A
10185147	12/2018	Lewis	N/A	N/A
10386558	12/2018	Escuti et al.	N/A	N/A
10670808	12/2019	Trail	N/A	N/A
11170565	12/2020	Mathur et al.	N/A	N/A
11231612	12/2021	Oh et al.	N/A	N/A
11461961	12/2021	Mathur et al.	N/A	N/A
11676333	12/2022	Mathur et al.	N/A	N/A
12013537	12/2023	Komanduri et al.	N/A	N/A
12073509	12/2023	Mathur et al.	N/A	N/A
2001/0035870	12/2000	Takeuchi et al.	N/A	N/A
2003/0014212	12/2002	Ralston et al.	N/A	N/A
2003/0137449	12/2002	Vashisth et al.	N/A	N/A
2003/0156253	12/2002	Watanabe et al.	N/A	N/A
2003/0158654	12/2002	Morita	N/A	N/A
2004/0119715	12/2003	Everett et al.	N/A	N/A
2004/0130520	12/2003	Maeda et al.	N/A	N/A
2004/0178894	12/2003	Janssen	N/A	N/A
2004/0258314	12/2003	Hashimoto	N/A	N/A
2005/0046953	12/2004	Repetto et al.	N/A	N/A
2005/0110732	12/2004	Kim	N/A	N/A
2005/0148388	12/2004	Vayra et al.	N/A	N/A
2005/0232530	12/2004	Kekas	N/A	N/A
2005/0248852	12/2004	Yamasaki	N/A	N/A
2005/0254135	12/2004	Ou	N/A	N/A
2006/0007056	12/2005	Ou	N/A	N/A
2006/0028436	12/2005	Armstrong	N/A	N/A
2006/0077861	12/2005	Katsuma et al.	N/A	N/A
2006/0105838	12/2005	Mullen	N/A	N/A
2006/0109280	12/2005	Dawson	N/A	N/A
2006/0132915	12/2005	Yang et al.	N/A	N/A
2006/0214911	12/2005	Miller	N/A	N/A
2006/0226231	12/2005	Johnston et al.	N/A	N/A
2006/0227151	12/2005	Bannai	N/A	N/A
2006/0256110	12/2005	Okuno et al.	N/A	N/A
2006/0267889	12/2005	Kimura	N/A	N/A

2006/0284791	12/2005	Chen et al.	N/A	N/A
2007/0081123	12/2006	Lewis	N/A	N/A
2007/0086668	12/2006	Ackley et al.	N/A	N/A
2008/0005702	12/2007	Skourup et al.	N/A	N/A
2008/0048932	12/2007	Yanagisawa	N/A	N/A
2008/0058629	12/2007	Seibel et al.	N/A	N/A
2008/0059578	12/2007	Albertson et al.	N/A	N/A
2008/0062131	12/2007	Chan et al.	N/A	N/A
2008/0071559	12/2007	Arrasvuori	N/A	N/A
2008/0186255	12/2007	Cohen et al.	N/A	N/A
2008/0199049	12/2007	Daly	N/A	N/A
2008/0215974	12/2007	Harrison et al.	N/A	N/A
2008/0215975	12/2007	Harrison et al.	N/A	N/A
2008/0215994	12/2007	Harrison et al.	N/A	N/A
2008/0276178	12/2007	Fadell et al.	N/A	N/A
2008/0278480	12/2007	Katano	N/A	N/A
2009/0003662	12/2008	Joseph et al.	N/A	N/A
2009/0066690	12/2008	Harrison	N/A	N/A
2009/0089685	12/2008	Mordecai et al.	N/A	N/A
2009/0147331	12/2008	Ashkenazi	N/A	N/A
2009/0164916	12/2008	Jeong et al.	N/A	N/A
2009/0177042	12/2008	Johnston	N/A	N/A
2009/0187389	12/2008	Dobbins et al.	N/A	N/A
2009/0213114	12/2008	Dobbins et al.	N/A	N/A
2009/0222424	12/2008	Van	N/A	N/A
2009/0225001	12/2008	Biocca et al.	N/A	N/A
2009/0285484	12/2008	Mallinson et al.	N/A	N/A
2009/0293012	12/2008	Alter et al.	N/A	N/A
2009/0316116	12/2008	Melville et al.	N/A	N/A
2009/0322671	12/2008	Scott et al.	N/A	N/A
2010/0020216	12/2009	Christian et al.	N/A	N/A
2010/0060647	12/2009	Brown et al.	N/A	N/A
2010/0085462	12/2009	Sako et al.	N/A	N/A
2010/0110368	12/2009	Chaum	N/A	N/A
2010/0137684	12/2009	Shibasaki et al.	N/A	N/A
2010/0141555	12/2009	Rorberg et al.	N/A	N/A
2010/0149073	12/2009	Chaum et al.	N/A	N/A
2010/0197390	12/2009	Craig et al.	N/A	N/A
2010/0245954	12/2009	Ahling	N/A	N/A
2010/0260426	12/2009	Huang et al.	N/A	N/A
2010/0287500	12/2009	Whitlow et al.	N/A	N/A
2011/0075902	12/2010	Song et al.	N/A	N/A
2011/0096337	12/2010	Hirose et al.	N/A	N/A
2011/0227812	12/2010	Haddick et al.	N/A	N/A
2011/0234879	12/2010	Kashitani	N/A	N/A
2011/0246908	12/2010	Akram et al.	N/A	N/A
2011/0267361	12/2010	Kurozuka	N/A	N/A
2011/0313653	12/2010	Lindner	N/A	N/A
2012/0044431	12/2011	Osterman	349/15	H04N 13/341
2012/0050143	12/2011	Border et al.	N/A	N/A
2012/0086728	12/2011	Mcardle et al.	N/A	N/A
2012/0087580	12/2011	Woo et al.	N/A	N/A
2012/0089949	12/2011	Chen et al.	N/A	N/A
2012/0092328	12/2011	Flaks et al.	N/A	N/A
2012/0113092	12/2011	Bar-Zeev et al.	N/A	N/A
2012/0120103	12/2011	Border et al.	N/A	N/A
2012/0127062	12/2011	Bar-Zeev et al.	N/A	N/A

2012/0127136	12/2011	Schneider et al.	N/A	N/A
2012/0127284	12/2011	Bar-Zeev et al.	N/A	N/A
2012/0147038	12/2011	Perez et al.	N/A	N/A
2012/0154277	12/2011	Bar-Zeev et al.	N/A	N/A
2012/0154557	12/2011	Perez et al.	N/A	N/A
2012/0162549	12/2011	Gao et al.	N/A	N/A
2012/0169752	12/2011	Kurozuka	N/A	N/A
2012/0182313	12/2011	Ahn et al.	N/A	N/A
2012/0183137	12/2011	Laughlin	N/A	N/A
2012/0188148	12/2011	DeJong	N/A	N/A
2012/0194554	12/2011	Kaino et al.	N/A	N/A
2012/0200600	12/2011	Demaine	N/A	N/A
2012/0206452	12/2011	Geisner et al.	N/A	N/A
2012/0212399	12/2011	Border et al.	N/A	N/A
2012/0218301	12/2011	Miller	N/A	N/A
2012/0236262	12/2011	Johansson	N/A	N/A
2012/0242560	12/2011	Nakada et al.	N/A	N/A
2012/0244939	12/2011	Braun	N/A	N/A
2012/0249586	12/2011	Wither et al.	N/A	N/A
2012/0249797	12/2011	Haddick et al.	N/A	N/A
2012/0274892	12/2011	Bonnin et al.	N/A	N/A
2012/0327116	12/2011	Liu et al.	N/A	N/A
2013/0021226	12/2012	Bell	N/A	N/A
2013/0021373	12/2012	Vaught et al.	N/A	N/A
2013/0042296	12/2012	Hastings et al.	N/A	N/A
2013/0044128	12/2012	Liu et al.	N/A	N/A
2013/0050186	12/2012	Large et al.	N/A	N/A
2013/0050258	12/2012	Liu et al.	N/A	N/A
2013/0050260	12/2012	Reitan	N/A	N/A
2013/0050432	12/2012	Perez et al.	N/A	N/A
2013/0050642	12/2012	Lewis et al.	N/A	N/A
2013/0077040	12/2012	Escuti et al.	N/A	N/A
2013/0082922	12/2012	Miller	N/A	N/A
2013/0083011	12/2012	Geisner et al.	N/A	N/A
2013/0083173	12/2012	Geisner et al.	N/A	N/A
2013/0093788	12/2012	Liu et al.	N/A	N/A
2013/0114043	12/2012	Balan et al.	N/A	N/A
2013/0117377	12/2012	Miller	N/A	N/A
2013/0120224	12/2012	Cajigas et al.	N/A	N/A
2013/0120706	12/2012	Kakinuma et al.	N/A	N/A
2013/0125027	12/2012	Abovitz	N/A	N/A
2013/0141419	12/2012	Mount et al.	N/A	N/A
2013/0141434	12/2012	Sugden et al.	N/A	N/A
2013/0156266	12/2012	Horii	N/A	N/A
2013/0194164	12/2012	Sugden et al.	N/A	N/A
2013/0208014	12/2012	Fleck et al.	N/A	N/A
2013/0208234	12/2012	Lewis	N/A	N/A
2013/0215230	12/2012	Miesnieks et al.	N/A	N/A
2013/0242262	12/2012	Lewis	N/A	N/A
2013/0249946	12/2012	Kimura	N/A	N/A
2013/0257748	12/2012	Ambrus et al.	N/A	N/A
2013/0286004	12/2012	McCulloch et al.	N/A	N/A
2013/0293468	12/2012	Perez et al.	N/A	N/A
2013/0307875	12/2012	Anderson	N/A	N/A
2013/0335683	12/2012	Escuti	349/96	G02F 1/133528
2013/0342564	12/2012	Kinnebrew et al.	N/A	N/A
2013/0342569	12/2012	Karkkainen et al.	N/A	N/A

2013/0342571	12/2012	Kinnebrew et al.	N/A	N/A
2014/0002496	12/2013	Lamb et al.	N/A	N/A
2014/0064557	12/2013	Hara et al.	N/A	N/A
2014/0071163	12/2013	Kinnebrew et al.	N/A	N/A
2014/0071539	12/2013	Gao	N/A	N/A
2014/0098137	12/2013	Fein et al.	N/A	N/A
2014/0098425	12/2013	Schon et al.	N/A	N/A
2014/0118829	12/2013	Ma et al.	N/A	N/A
2014/0132484	12/2013	Pandey et al.	N/A	N/A
2014/0139551	12/2013	McCulloch et al.	N/A	N/A
2014/0145997	12/2013	Tiruvuru	N/A	N/A
2014/0168035	12/2013	Luebke et al.	N/A	N/A
2014/0168783	12/2013	Luebke et al.	N/A	N/A
2014/0177023	12/2013	Gao et al.	N/A	N/A
2014/0178029	12/2013	Raheman et al.	N/A	N/A
2014/0192851	12/2013	Tahir et al.	N/A	N/A
2014/0204077	12/2013	Kamuda et al.	N/A	N/A
2014/0218361	12/2013	Abe et al.	N/A	N/A
2014/0218468	12/2013	Gao et al.	N/A	N/A
2014/0222432	12/2013	Ahn et al.	N/A	N/A
2014/0267402	12/2013	Hing et al.	N/A	N/A
2014/0267420	12/2013	Schowengerdt et al.	N/A	N/A
2014/0306866	12/2013	Miller et al.	N/A	N/A
2014/0354685	12/2013	Lazarow et al.	N/A	N/A
2014/0368532	12/2013	Keane et al.	N/A	N/A
2015/0016777	12/2014	Abovitz et al.	N/A	N/A
2015/0097865	12/2014	Subramanian et al.	N/A	N/A
2015/0103306	12/2014	Kaji et al.	N/A	N/A
2015/0177516	12/2014	Blonde et al.	N/A	N/A
2015/0178939	12/2014	Bradski et al.	N/A	N/A
2015/0205126	12/2014	Schowengerdt	N/A	N/A
2015/0206321	12/2014	Scavezze et al.	N/A	N/A
2015/0222883	12/2014	Welch	N/A	N/A
2015/0222884	12/2014	Cheng	N/A	N/A
2015/0248046	12/2014	Schowengerdt	N/A	N/A
2015/0254793	12/2014	Hastings et al.	N/A	N/A
2015/0268415	12/2014	Schowengerdt et al.	N/A	N/A
2015/0301356	12/2014	Tabirian et al.	N/A	N/A
2015/0302652	12/2014	Miller et al.	N/A	N/A
2015/0309175	12/2014	Hinderling et al.	N/A	N/A
2015/0309263	12/2014	Abovitz et al.	N/A	N/A
2015/0326570	12/2014	Publicover et al.	N/A	N/A
2015/0346490	12/2014	Tekolste et al.	N/A	N/A
2015/0346495	12/2014	Welch et al.	N/A	N/A
2016/0011353	12/2015	Escuti et al.	N/A	N/A
2016/0011419	12/2015	Gao	N/A	N/A
2016/0026253	12/2015	Bradski et al.	N/A	N/A
2016/0033698	12/2015	Escuti et al.	N/A	N/A
2016/0041449	12/2015	Clark et al.	N/A	N/A
2016/0047956	12/2015	Tabirian et al.	N/A	N/A
2016/0055822	12/2015	Bell	N/A	N/A
2016/0063706	12/2015	Gonzalez-Banos et al.	N/A	N/A
2016/0093106	12/2015	Black	N/A	N/A
2016/0116738	12/2015	Osterhout	N/A	N/A
2016/0179336	12/2015	Ambrus et al.	N/A	N/A
2016/0278695	12/2015	Wang et al.	N/A	N/A
2016/0314624	12/2015	Li et al.	N/A	N/A

2016/0327798	12/2015	Xiao	N/A	N/A
2017/0010469	12/2016	Samec et al.	N/A	N/A
2017/0115491	12/2016	Shi et al.	N/A	N/A
2017/0168307	12/2016	Itani	N/A	N/A
2017/0184848	12/2016	Vallius	N/A	N/A
2017/0223344	12/2016	Kaehler	N/A	N/A
2017/0323615	12/2016	Hazra et al.	N/A	N/A
2017/0373459	12/2016	Weng et al.	N/A	N/A
2018/0047353	12/2017	Lin	N/A	N/A
2018/0053284	12/2017	Rodriguez et al.	N/A	N/A
2018/0129048	12/2017	Robbins et al.	N/A	N/A
2018/0180890	12/2017	Baerenrodt et al.	N/A	N/A
2018/0188528	12/2017	Browy et al.	N/A	N/A
2018/0188536	12/2017	Bell et al.	N/A	N/A
2018/0267222	12/2017	Ambur et al.	N/A	N/A
2018/0314066	12/2017	Bell et al.	N/A	N/A
2018/0356639	12/2017	Schaefer et al.	N/A	N/A
2019/0088021	12/2018	Tanaka et al.	N/A	N/A
2019/0088221	12/2018	Takahashi	N/A	N/A
2019/0227375	12/2018	Oh et al.	N/A	N/A
2019/0265465	12/2018	Wong et al.	N/A	N/A
2020/0058256	12/2019	Seibert et al.	N/A	N/A
2020/0074724	12/2019	Mathur et al.	N/A	N/A
2020/0379334	12/2019	McDowall et al.	N/A	N/A
2021/0286183	12/2020	Ouderkirk et al.	N/A	N/A
2021/0297560	12/2020	Luna et al.	N/A	N/A
2022/0011578	12/2021	Sinay et al.	N/A	N/A
2022/0128352	12/2021	Binder	N/A	N/A
2022/0146888	12/2021	Oh et al.	N/A	N/A
2023/0079929	12/2022	Bradski et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103605209	12/2013	CN	N/A
105974589	12/2015	CN	N/A
106662747	12/2016	CN	N/A
107376349	12/2016	CN	N/A
112639579	12/2020	CN	N/A
2649485	12/2012	EP	N/A
3844559	12/2020	EP	N/A
3914959	12/2020	EP	N/A
S6010224	12/1984	JP	N/A
H06342129	12/1993	JP	N/A
H08160340	12/1995	JP	N/A
2002110511	12/2001	JP	N/A
2006293604	12/2005	JP	N/A
2007240709	12/2006	JP	N/A
2008242134	12/2007	JP	N/A
2011175439	12/2010	JP	N/A
2012505430	12/2011	JP	N/A
2013513818	12/2012	JP	N/A
2013538368	12/2012	JP	N/A
2014505899	12/2013	JP	N/A
2015176104	12/2014	JP	N/A
2016519327	12/2015	JP	N/A
WO 03077012	12/2002	WO	N/A
WO 2005124431	12/2004	WO	N/A
2010042089	12/2009	WO	N/A

2012020527	12/2011	WO	N/A
2012078410	12/2011	WO	N/A
2014159045	12/2013	WO	N/A
WO 2016181108	12/2015	WO	N/A
WO 2017176898	12/2016	WO	N/A
WO 2018119276	12/2017	WO	N/A
2018231784	12/2017	WO	N/A
WO 2019084334	12/2018	WO	N/A
2020047486	12/2019	WO	N/A
WO 2020146760	12/2019	WO	N/A
WO 2021002641	12/2020	WO	N/A

OTHER PUBLICATIONS

ARToolKit: 1

<https://web.archive.org/web/20051013062315/http://www.hitl.washington.edu:80/artoolkit/documentation/hardware.htm>
archived Oct. 13, 2005. cited by applicant

Azuma, "A Survey of Augmented Reality," *Teleoperators and Virtual Environments* 6(4): 355-385,
<https://web.archive.org/web/20010604100006/http://www.cs.unc.edu/~azuma/ARpreserice.pdf>, Aug. 1997. cited by applicant

Azuma, "Predictive Tracking for Augmented Realty," TR95-007, Department of Computer Science, UNC-Chapel Hill, NC, Feb. 1995. cited by applicant

Bimber et al., "Spatial Augmented Reality—Merging Real and Virtual Worlds," <https://web.media.mit.edu/~raskar/book/BimberRaskarAugmentedRealityBook.pdf>, 2005. cited by applicant

Chinese Office Action, mailed Sep. 2, 2022, for Chinese Application No. 201980056636.9, 11 pages. cited by applicant

Crawford et al., "Liquid-Crystal Diffraction Gratings Using Polarization Holography Alignment Techniques," *Journal of Applied Physics* 98(123102), 2005. cited by applicant

Escuti et al., "39.4: Polarization—Independent Switching with High Contrast From a Liquid Crystal Polarization Grating," *SID Symposium Digest* 37: 1443-1446, Jun. 2006. cited by applicant

Escuti et al., "Polarization—Independent LC Microdisplays Using Liquid Crystal Polarization Gratings: A Viable Solution," ILCC presentation, Jul. 1, 2008. (15 pages). cited by applicant

International Preliminary Report for Patentability, dated Apr. 28, 2020, for International Application No. PCT/US18/57604. cited by applicant

International Search Report and Written Opinion, dated Mar. 3, 2019, for International Application No. PCT/US18/57604. cited by applicant

Invitation to Pay Additional Fees, dated Jan. 8, 2019, for International Application No. PCT/US18/57604. cited by applicant

Jacob, "Eye Tracking in Advanced Interface Design," Human Computer interaction Lab Naval Research Laboratory, Washington, D.C. / paper / in *Virtual Environments and Advanced Interface Design*, ed. by W. Barfield and T.A. Furness, pp. 258-288, Oxford University Press, New York (1995). cited by applicant

Japanese Office Action, mailed Aug. 24, 2022, for Japanese Application No. 2020-523003, 11 pages. (with English Translation). cited by applicant

Kim et al., "Wide-Angle, Nonmechanical Beam Steering with High Throughput Utilizing Polarization Gratings," *Applied Optics* 50(17), Jun. 10, 2011. (4 pages). cited by applicant

Komanduri et al., "18:3: Late-News Paper: Polarization Independent Liquid Crystal Microdisplays," *SID Digest* 39(1): 236-239, May 2008. cited by applicant

Komanduri et al., "34.4L: Late-News Paper: Polarization Independent Projection Systems Using Thin Film Polymer Polarization Gratings and Standard Liquid Crystal Microdisplays," *SID Digest* 40(1), Jun. 2009. (4 pages). cited by applicant

Komanduri et al., "Elastic Continuum Analysis of the Liquid Crystal Polarization Grating," *Physical Review. E, Statistical, Non Linear, and Soft Matter Physics*, May 25, 2007. (8 pages). cited by applicant

Komanduri et al., "Multi-twist Retarders: Broadband Retardation Control Using Self-aligning Reactive Liquid Crystal Layers," *Optical Society of America, Optics Express* 404, 21(1), Jan. 14, 2013. cited by applicant

Komanduri et al., "Polarization—Independent Modulation for Projection Displays Using Small-period LC Polarization Gratings," *Journal of the Society for Information Display* 15(8): 589-594, Aug. 2007. (7 pages). cited by applicant

Komanduri et al., "Polarization Independent Projection Systems Using Thin Film Polymer Polarization Gratings and Standard Liquid Crystal Microdisplays," SID-Display Week Presentation, Jun. 3, 2009. (12 pages). cited by applicant

Lee et al., "Negative Dispersion of Birefringence in Two Dimensionally Self-organized Smectic Liquid Crystal and

Monomer Thin Film,” *Optics Letters* 39(17), Sep. 1, 2014. cited by applicant

Lee et al., “Recent progress in Pancharatnam-Berry phase optical elements and the applications for virtual/augmented realities,” *De Gruyter Open, Opt. Data Process. Storage*, 3, 2017. (10 pages). cited by applicant

Lim et al., “Anisotropic Nano—Imprinting Technique for Fabricating a Patterned Optical Film of a Liquid Crystalline Polymer,” *Journal of Nanoscience and Nanotechnology* 8: 4775-4778, Oct. 2008. (4 pages). cited by applicant

Nikolova et al., “Diffraction Efficiency and Selectivity of Polarization Holographic Recording,” *Optica Acta: Int'l J Optics* 31(5): 579-588, 1984. cited by applicant

Notice of Allowance, mailed May 27, 2022, for U.S. Appl. No. 17/330,146, Mathur et al., “Spatially-Resolved Dynamic Dimming for Augmented Reality Device,” 8 pages. cited by applicant

Oh et al., “16.2: Polarization—Independent Modulation Using Standard Liquid Crystal Microdisplays and Polymer Polarization Gratings,” IDRC, 2008. (4 pages). cited by applicant

Oh et al., “Achromatic Diffraction from Polarization Gratings with High Efficiency,” *Opt Lett.* 33(20): 2287-2289, Oct. 2008 & *Erratum Opt Lett.* 34(23): 3637, Dec. 2009. cited by applicant

Oh et al., “Numerical Analysis of Polarization Gratings Using the Finite-difference Time-domain Method,” *Physical Review A* 76, Oct. 12, 2007. (8 pages). cited by applicant

Oh et al., “Polarization—Independent Modulation Using Standard LCDs and Polymer PGs,” 2008. (6 pages). cited by applicant

Oh, C., “Broadband Polarization Gratings for Efficient Liquid Crystal Display, Beam Steering, Spectropolarimetry, and Fresnel Zone Plate,” Thesis, N.C. State University, Electrical Engineering, 2009. (190 pages). cited by applicant

Tabiryan et al., “Broadband Waveplate Lenses,” *Optics Express* 24(7), Mar. 24, 2016. cited by applicant

Tabiryan et al., “Thin Waveplate Lenses of Switchable Focal Length New Generation in Optics,” *Optics Express* 23(20), Sep. 22, 2015. cited by applicant

Tanriverdi and Jacob, “Interacting With Eye Movements in Virtual Environments,” Department of Electrical Engineering and Computer Science, Tufts University, Medford, MA—paper/Proc. ACM CHI 2000 Human Factors in Computing Systems Conference, pp. 265-272, Addison-Wesley/ACM Press (2000). cited by applicant

Yang et al., “Negative Dispersion of Birefringence of Smectic Liquid Crystal-polymer Composite: Dependence on the Constituent Molecules and Temperature,” *Optical Society of America, Optics Express* 2466, 23(3), Feb. 9, 2015. cited by applicant

Aronoff et al., “Collaborative Augmented Reality for Better Standards,” *Complex Systems Concurrent Engineering*, 2007, 8 pages. cited by applicant

Chen et al. “Electrically Adjustable Location of a Projected Image in Augmented Reality Via a Liquid-Crystal Lens,” *Optics Express*, vol. 23, No. 22, Nov. 2015, 9 pages. cited by applicant

Freeman et al. “Scanned Laser Pico-Projectors: Seeing the Big Picture with a Small Device,” *Optics and Photonics News*, vol. 20, Issue 5, May 2009, pp. 28-34. cited by applicant

Roscher et al., “Low-Cost Projection Device with A 2D Resonant Microscanning Mirror,” *MOEMS Display and Imaging Systems II*, vol. 5348, Jan. 24, 2004, pp. 22-31. cited by applicant

Primary Examiner: Nguyen; Lauren

Attorney, Agent or Firm: Seed Intellectual Property Law Group LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. application Ser. No. 17/582,845, filed Jan. 24, 2022, which is a divisional application of U.S. application Ser. No. 16/171,290, filed Oct. 25, 2018, entitled “BROADBAND ADAPTIVE LENS ASSEMBLY FOR AUGMENTED REALITY DISPLAY,” now U.S. Pat. No. 11,231,612, which claims the benefit of priority to U.S. Provisional Patent Application No. 62/577,672, filed Oct. 26, 2017, entitled “BROADBAND ADAPTIVE LENS ASSEMBLY FOR AUGMENTED REALITY DISPLAY,” the content of which is hereby incorporated by reference herein in its entirety.

INCORPORATION BY REFERENCE

(1) This application incorporates by reference the entirety of each of the following patent applications: U.S. application Ser. No. 14/555,585 filed on Nov. 27, 2014, published on Jul. 23, 2015 as U.S. Publication No. 2015/0205126; U.S. application Ser. No. 14/690,401 filed on Apr. 18, 2015, published on Oct. 22, 2015 as U.S. Publication No. 2015/0302652; U.S. application Ser. No. 14/212,961 filed on Mar. 14, 2014, now U.S. Pat. No.

BACKGROUND

Field

(2) The present disclosure relates to display systems and, more particularly, to augmented and virtual reality display systems.

Description of the Related Art

(3) Modern computing and display technologies have facilitated the development of systems for so called “virtual reality” or “augmented reality” experiences, wherein digitally reproduced images or portions thereof are presented to a user in a manner wherein they seem to be, or may be perceived as, real. A virtual reality, or “VR”, scenario typically involves presentation of digital or virtual image information without transparency to other actual real-world visual input; an augmented reality, or “AR”, scenario typically involves presentation of digital or virtual image information as an augmentation to visualization of the actual world around the user. A mixed reality, or “MR”, scenario is a type of AR scenario and typically involves virtual objects that are integrated into, and responsive to, the natural world. For example, in an MR scenario, AR image content may be blocked by or otherwise be perceived as interacting with objects in the real world.

(4) Referring to FIG. 1, an augmented reality scene **10** is depicted wherein a user of an AR technology sees a real-world park-like setting **20** featuring people, trees, buildings in the background, and a concrete platform **30**. In addition to these items, the user of the AR technology also perceives that he “sees” “virtual content” such as a robot statue **40** standing upon the real-world platform **30**, and a cartoon-like avatar character **50** flying by which seems to be a personification of a bumble bee, even though these elements **40**, **50** do not exist in the real world. Because the human visual perception system is complex, it is challenging to produce an AR technology that facilitates a comfortable, natural-feeling, rich presentation of virtual image elements amongst other virtual or real-world imagery elements.

(5) Systems and methods disclosed herein address various challenges related to AR and VR technology.

SUMMARY

(6) In an aspect, a display device comprises a waveguide configured to guide light in a lateral direction parallel to an output surface of the waveguide. The waveguide is further configured to outcouple the guided light through the output surface. The display device additionally comprises a broadband adaptive lens assembly configured to incouple and to diffract therethrough the outcoupled light from the waveguide. The broadband adaptive lens assembly comprises a first waveplate lens comprising a liquid crystal (LC) layer arranged such that the waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the first waveplate lens and configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm. The broadband adaptive lens assembly is configured to be selectively switched between a plurality of states having different optical powers.

(7) In another aspect, a broadband adaptive lens assembly for a display device comprises a first waveplate lens comprising a liquid crystal (LC) layer having LC molecules and arranged such that the first waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the first waveplate lens and configured to diffract light at a diffraction efficiency greater than 90% within a wavelength in a range spanning at least 450 nm to 630 nm. The broadband adaptive lens assembly additionally comprises a switchable waveplate configured to be electrically activated and deactivated. The broadband adaptive lens assembly is configured to be selectively switched between at least two lens states. The two lens states include a first lens state configured to exert a first lens effect according to a first optical power and to alter a polarization of light passing through the broadband adaptive lens assembly, and a second lens state configured to exert a second lens effect according to a second optical power and to preserve the polarization of the light passing through the broadband adaptive lens assembly.

(8) In another aspect, a broadband adaptive lens assembly for a display device comprises a first waveplate lens comprising a liquid crystal (LC) layer formed on a substrate. The LC layer has LC molecules that are arranged such that the first waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the LC layer and configured to diffract light at a diffraction efficiency greater than 90% within a wavelength range spanning at least 450 nm to 630 nm. Ones of the LC molecules that are the closest to the substrate have generally the same orientation direction at different locations at the same radius from the central region. The broadband adaptive lens assembly is configured to be selectively switched between at least two lens states. A first lens state is configured to exert a first lens effect according to a first optical power and to alter a polarization of light passing through the broadband adaptive lens assembly. A second lens state is configured to exert a second lens effect according to a second optical power and to preserve the polarization of the light passing through the broadband adaptive lens assembly.

(9) In another aspect, an integrated broadband adaptive lens assembly for a display device comprises a first electrode, a second electrode and a liquid crystal (LC) layer stack interposed between the first electrode and the second electrode. The LC layer stack comprises a switchable liquid crystal (LC) layer comprising unpolymerized LC molecules interposed between first and second polymerized LC layers each comprising polymerized LC molecules. LC molecules in the switchable LC layer that are adjacent to LC molecules in the first polymerized LC layer are generally elongated in a first direction. LC molecules in the switchable LC layer that are adjacent to LC molecules in the second polymerized LC layer are generally elongated in a second direction crossing the first direction. The switchable LC layer comprises LC molecules configured such that under a first voltage condition across the first and second electrodes, a polarization of incident light passing therethrough is preserved, while under a second voltage condition across the first and second electrodes, the polarization of the incident light passing therethrough is altered.

(10) In another aspect, a display device comprises a pair of adaptive lens assemblies in an optical path. Each of the adaptive lens assemblies comprises a corresponding switchable waveplate configured to diffract light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and to switch between first and second states to selectively alter a polarization state of light passing therethrough. The adaptive lens assemblies have optical powers with opposite signs.

(11) In another aspect, an adaptive lens assembly comprises one or more waveplate lenses and one or more switchable waveplates aligned in an optical path. Each of the one or more waveplate lenses is configured to diffract outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm, to alter a polarization state of light passing therethrough, to provide a first optical power for light having a first polarization, and to provide a second optical power for light having a second polarization. Each of the one or more switchable waveplates is configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and is selectively switchable between a first state configured to pass the light therethrough without altering a polarization state of the light, and a second state configured to alter the polarization state of the light passing therethrough.

(12) In another aspect, a wearable augmented reality head-mountable display system comprises a light modulating system configured to output light to form an image, a head mountable frame, one or more waveguides attached to the frame and configured to receive the light from the light modulating system and a pair of adaptive lens assemblies, wherein the one or more waveguides are disposed between the adaptive lens assemblies. Each of the adaptive lens assemblies comprises one or more waveplate lenses configured to diffract outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and to provide a first optical power for light having a first polarization, and to provide a second optical power for light having a second polarization. Each of the adaptive lens assemblies additionally comprises one or more switchable waveplates in an optical path, wherein each of the one or more switchable waveplates is configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and to selectively alter a polarization state of light passing therethrough. The adaptive lens assemblies are configured to provide a respective optical power that is adjustable upon application of a respective electrical signal.

(13) In another aspect, a method of integrating a broadband adaptive lens assembly comprises forming a lower stack and an upper stack. The lower stack comprises a first electrode layer formed on a first substrate, a first alignment layer formed on the first electrode layer, and a first polymerized LC layer on the first alignment layer. The upper stack comprises a second electrode layer formed on a second substrate, a second alignment layer formed on the second electrode, and a second polymerized LC layer on the second alignment layer. The method additionally includes, after forming the lower and upper stacks, stacking the upper stack and the lower stack such that the first and second polymerized LC layers face each other, wherein stacking comprises forming spacers to create a gap between the upper and lower stacks. The method additionally comprises filling the gap with unpolymerized LC molecules to form a switchable liquid crystal (LC) layer. Forming the switchable LC layer comprises self-aligning LC molecules in the switchable LC layer that are adjacent to LC molecules in the first polymerized LC layer to be generally elongated in a first direction, and self-aligning LC molecules in the switchable LC layer that are adjacent to LC molecules in the second polymerized LC layer to be generally elongated in a second direction crossing the first direction.

(14) In another aspect, a method of fabricating a broadband waveplate lens assembly comprises providing a transparent substrate and forming an alignment layer on the transparent substrate. The alignment layer is configured to cause liquid crystal (LC) molecules formed thereon to align according to a waveplate lens pattern. The method additionally includes forming a LC layer on the alignment layer. LC molecules of the LC layer that are immediately adjacent to the alignment layer align according to the waveplate lens pattern in which the LC molecules of the LC layer at a given radius from a central region of the waveplate lens pattern have elongation

direction that are generally aligned in the same direction. The LC layer is configured to diffract light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm. The broadband adaptive lens assembly is configured to be selectively switched between a plurality of states having different optical powers.

(15) In another aspect, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of the user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The display system additionally comprises an eyepiece disposed on the frame. At least a portion of the eyepiece is transparent and disposed at a location in front of the user's eye when the user wears the head-mounted display such that the transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. The eyepiece is configured to emit light into the user's eye to display augmented reality image content to the user's vision field. At least one switchable lens assembly comprises a diffractive liquid crystal lens assembly comprising a twisted nematic switchable lens. The twisted nematic switchable lens comprises an active layer of twisted nematic liquid crystal, a first layer of polymerized liquid crystal adjacent to the active layer of twisted nematic liquid crystal, a second layer of polymerized liquid crystal adjacent to the active layer of twisted nematic liquid crystal. The active layer of twisted nematic liquid crystal disposed between the first and second layers of polymerized liquid crystal. The nematic switchable lens further comprises first and second electrodes disposed to applying an electric field to the active layer of twisted nematic liquid crystal. The first and second electrodes are on opposite sides of the active layer and the first and second layers of polymerized liquid crystal such that the active layer and the first and second layers of polymerized liquid crystal are disposed between the first and second electrodes. The head mounted display additionally comprises electronics configured to vary the optical power of the switchable lens by applying an electrical signal to the electrodes. The at least one switchable lens assembly is configured to transmit light from the environment in front of the user to the user's eye.

(16) In another aspect, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of the user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The system additionally comprises an eyepiece disposed on the frame. At least a portion of the eyepiece is transparent and disposed at a location in front of the user's eye when the user wears the head-mounted display such that the transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. The eyepiece is configured to emit light into the user's eye to display augmented reality image content to the user's vision field. The system additionally comprises at least one switchable lenses assembly comprising a diffractive liquid crystal lens assembly. The diffractive liquid crystal lens assembly comprises an active layer comprising a twisted nematic liquid crystal diffractive lens, a first and second retarders comprising polymerized liquid crystal on opposite sides of the active layer, and first and second electrodes disposed to applying an electric field to the active layer of twisted nematic liquid crystal, the first and second electrodes on opposite sides of the active layer. The system further comprises electronics configured to vary the optical power of the switchable lens by applying an electrical signal to the electrodes, wherein the at least one switchable lenses is configured to transmit light from the environment in front of the user to the user's eye.

(17) In another aspect, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of the user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The system additionally comprises an eyepiece disposed on the frame. At least a portion of the eyepiece is transparent and disposed at a location in front of the user's eye when the user wears the head-mounted display such that the transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. The eyepiece is configured to emit light into the user's eye to display augmented reality image content to the user's vision field. The system additionally includes at least one switchable lens assembly comprising a plurality of switchable lenses. Each of the switchable lenses has at least two states. The switchable lens assembly has different optical power for different states of the plurality of lenses. The switchable lens assembly has different optical power for different wavelengths when the plurality of lenses are set to a particular state. The system further comprises electronics in communication with the switchable lenses to alter the state of the plurality of lenses. The electronics are configured to cause different lenses in the plurality of switchable lenses to be in different states for different wavelengths.

(18) In another aspect, a method of fabricating an eyepiece for augmented reality eyewear configured to direct light into a wearer's eye so as to present images to the wearer comprises providing a substrate. The method additionally comprises forming a first lens region on the substrate, where the first lens region comprises a transparent liquid crystal lens having optical power. The method further comprises providing a second region on the substrate that is transparent that does not have optical power.

(19) In another aspect, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of said user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The display system additionally comprises an eyepiece disposed on the frame. At least a portion of said eyepiece is transparent and disposed at a location in front of the user's eye when the user wears said head-mounted display such that said transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. Said eyepiece is configured to emit light into said user's eye to display augmented reality image content to the user's vision field. The display system additionally comprises at least one switchable lens assembly comprising a plurality of switchable lenses, where each of said switchable lenses has at least two states. Variation in the states of said switchable lenses changes the state of the at least one switchable assembly. Said switchable lens assembly has different optical power for different states of said plurality of lenses. Said switchable lens assembly has different optical power for different wavelengths when the plurality of lenses are set to a particular state. The display system further comprises electronics in communication with said switchable lenses to alter the state of said plurality of lenses. Said display device is configured to emit a first color light into said user's eye at a first time and a second color light into said user's eye at a second time to display augmented reality image content to the user's vision field. Said electronics are configured to cause a least one of said lenses to be in different states at first and second times to provide images in said first and second colors.

(20) For purposes of summarizing the invention and the advantages achieved over the prior art, certain objects and advantages are described herein. Of course, it is to be understood that not necessarily all such objects or advantages need to be achieved in accordance with any particular embodiment. Thus, for example, those skilled in the art will recognize that the invention may be embodied or carried out in a manner that can achieve or optimize one advantage or a group of advantages without necessarily achieving other objects or advantages.

(21) All of these embodiments are intended to be within the scope of the invention herein disclosed. These and other embodiments will become readily apparent to those skilled in the art from the following detailed description having reference to the attached figures, the invention not being limited to any particular disclosed embodiment(s).

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 illustrates a user's view of augmented reality (AR) through an AR device.

(2) FIG. 2 illustrates a conventional display system for simulating three-dimensional imagery for a user.

(3) FIGS. 3A-3C illustrate relationships between radius of curvature and focal radius.

(4) FIG. 4A illustrates a representation of the accommodation-vergence response of the human visual system.

(5) FIG. 4B illustrates examples of different accommodative states and vergence states of a pair of eyes of the user.

(6) FIG. 4C illustrates an example of a representation of a top-down view of a user viewing content via a display system.

(7) FIG. 4D illustrates another example of a representation of a top-down view of a user viewing content via a display system.

(8) FIG. 5 illustrates aspects of an approach for simulating three-dimensional imagery by modifying wavefront divergence.

(9) FIG. 6 illustrates an example of a waveguide stack for outputting image information to a user.

(10) FIG. 7 illustrates an example of exit beams outputted by a waveguide.

(11) FIG. 8 illustrates an example of a stacked waveguide assembly in which each depth plane includes images formed using multiple different component colors.

(12) FIG. 9A illustrates a cross-sectional side view of an example of a set of stacked waveguides that each includes an incoupling optical element.

(13) FIG. 9B illustrates a perspective view of an example of the plurality of stacked waveguides of FIG. 9A.

(14) FIG. 9C illustrates a top-down plan view of an example of the plurality of stacked waveguides of FIGS. 9A and 9B.

(15) FIG. 9D illustrates an example of wearable display system.

(16) FIG. 10 illustrates an example of a display system comprising a pair of adaptive lens assemblies.

(17) FIG. 11A illustrates an example of the display system of FIG. 10 displaying virtual content to a user at a virtual depth plane.

(18) FIG. 11B illustrates an example of the display system of FIG. 10 providing a view of real world content to a user.

- (19) FIG. 12A illustrates an example of a waveplate lens assembly comprising liquid crystals.
- (20) FIG. 12B illustrates an example of a switchable waveplate lens comprising liquid crystals.
- (21) FIG. 13A illustrates a cross-sectional view of an example of a switchable waveplate comprising a layer of twisted nematic liquid crystals.
- (22) FIG. 13B illustrates an example of a switchable waveplate assembly comprising the switchable waveplate of FIG. 13A interposed between a pair of quarter waveplates in operation with the switchable waveplate activated or deactivated.
- (23) FIG. 13C illustrates an example of the quarter waveplate comprising a plurality of layers of twisted nematic liquid crystal layers.
- (24) FIG. 13D illustrates an example of a switchable waveplate assembly comprising the switchable waveplate of FIG. 13A interposed between a pair of quarter waveplates integrated as a single stack using adhesive layers.
- (25) FIG. 13E illustrates an example of a switchable waveplate assembly comprising a layer of twisted nematic liquid crystals interposed between a pair of quarter waveplates integrated as a single stack.
- (26) FIG. 13F illustrates an example of a switchable waveplate assembly comprising a layer of twisted nematic liquid crystals interposed between a pair of quarter waveplates of FIG. 13C integrated as a single stack.
- (27) FIG. 14A illustrates a perspective view of an example of one of a pair of transparent electrodes for switching a layer of liquid crystals.
- (28) FIG. 14B illustrates a perspective view of an example of the other of a pair of transparent electrodes for switching a layer of liquid crystals.
- (29) FIG. 14C illustrates a perspective view of an example of a pair of vertically separated transparent electrodes for switching a layer of liquid crystals.
- (30) FIG. 15A illustrates a plan view of an example of a pair of horizontally interlaced transparent electrodes for switching a layer of liquid crystals.
- (31) FIG. 15B illustrates a cross-sectional view of an example of a switchable waveplate assembly including the pair of horizontally interlaced transparent electrodes of FIG. 15A.
- (32) FIG. 16A illustrates a plan view of an example of a waveplate lens comprising liquid crystals.
- (33) FIG. 16B illustrates a plan view of an example of a waveplate lens comprising liquid crystals.
- (34) FIG. 16C illustrates an example of a waveplate lens that provides different optical power to diverge or converge light passing therethrough depending on the polarization of light and the side on which the light is incident.
- (35) FIG. 16D illustrates an example of a waveplate lens that provides different optical power to diverge or converge light passing therethrough depending on the polarization of light and the side on which the light is incident.
- (36) FIG. 17A illustrates an example of an adaptive lens assembly comprising waveplate lenses and a switchable waveplate.
- (37) FIG. 17B illustrates an example of the adaptive lens assembly of FIG. 17A in operation with the switchable waveplate activated.
- (38) FIG. 17C illustrates an example of the adaptive lens assembly of FIG. 13A in operation with the switchable waveplate deactivated.
- (39) FIG. 18A illustrates an example of a display device comprising a waveguide between pair of adaptive lens assemblies each comprising waveplate lenses and a switchable waveplate, in operation with the switchable waveplate activated.
- (40) FIG. 18B illustrates an example of the display device of FIG. 18A, in operation with the switchable waveplate deactivated.
- (41) FIG. 19A illustrates a plan view of an example arrangement of liquid crystal molecules closest to the substrate of a broadband waveplate lens comprising liquid crystals.
- (42) FIG. 19B illustrates the broadband waveplate lens comprising liquid crystals arranged as illustrated in FIG. 19A converging light having a first circular polarization.
- (43) FIG. 19C illustrates the broadband waveplate lens comprising liquid crystals arranged as illustrated in FIG. 19A diverging light having a second circular polarization.
- (44) FIG. 20A illustrates a plan view of example arrangement of liquid crystal molecules a broadband waveplate lens comprising a plurality of layers of twisted nematic liquid crystals.
- (45) FIG. 20B illustrates a cross-sectional view of an example of a broadband waveplate lens comprising a plurality of layers of twisted nematic liquid crystals.
- (46) FIG. 21 illustrates a cross-sectional view of an example of a broadband waveplate lens comprising a layer of liquid crystals having increasing birefringence with increasing wavelength.
- (47) FIG. 22A illustrates a cross-sectional view of an example of a deactivated switchable broadband waveplate

lens diverging and flipping the polarization of light having a first circular polarization.

(48) FIG. 22B illustrates a cross-sectional view of an example of a deactivated switchable broadband waveplate lens converging and flipping the polarization of light having a second circular polarization.

(49) FIG. 22C illustrates a cross-sectional view of an example of an activated switchable broadband waveplate lens passing circularly polarized light without substantially converging or diverging while preserving the polarization thereof.

(50) FIG. 23A illustrates an example of a broadband adaptive waveplate lens assembly comprising a pair of broadband switchable waveplate lenses, in operation in which both switchable waveplate lenses are deactivated.

(51) FIG. 23B illustrates the broadband adaptive waveplate lens assembly of FIG. 23A, in operation with one of the switchable waveplate lenses activated.

(52) FIG. 23C illustrates the broadband adaptive waveplate lens assembly of FIG. 23A, in operation with one of the switchable waveplate lenses activated.

(53) FIG. 23D illustrates an example of a broadband adaptive waveplate lens assembly comprising a pair of broadband switchable waveplate lenses, in operation in which both switchable waveplate lenses are activated.

(54) FIG. 24A illustrates an example of an integrated broadband adaptive waveplate lens assembly comprising a switchable broadband waveplate lens interposed between a pair of active broadband switchable waveplate lenses.

(55) FIG. 24B illustrates the broadband adaptive waveplate lens assembly of FIG. 24A in operation as combination of broadband half waveplate lenses.

(56) FIG. 24C illustrates the broadband adaptive waveplate lens assembly of FIG. 24B in operation with the switchable broadband waveplate activated.

(57) FIG. 24D illustrates the broadband adaptive waveplate lens assembly of FIG. 24B in operation with the switchable broadband waveplate deactivated.

(58) FIG. 25A illustrates simulated diffraction efficiency versus wavelength within in the visible spectrum of the broadband adaptive waveplate lens assembly of FIG. 24A with the switchable broadband waveplate activated.

(59) FIG. 25B illustrates simulated diffraction efficiency versus wavelength within in the visible spectrum of the broadband adaptive waveplate lens assembly of FIG. 24A with the switchable broadband waveplate deactivated.

(60) FIG. 26A illustrates simulated actual versus target net optical power of an example broadband adaptive waveplate lens assembly comprising three broadband switchable waveplate lenses, using a single lens state and multiple lens states for a blue wavelength.

(61) FIG. 26B illustrates simulated actual versus target net optical power of an example broadband adaptive waveplate lens assembly comprising three broadband switchable waveplate lenses, using a single lens state and multiple lens states for a green wavelength.

(62) FIG. 26C illustrates simulated actual versus target net optical power of an example broadband adaptive waveplate lens assembly comprising three broadband switchable waveplate lenses, using a single lens state and multiple lens states for a red wavelength.

(63) FIG. 27A-27C illustrate an example fabrication method of a broadband waveplate or a broadband waveplate lens.

(64) FIG. 28 illustrate an example method of configuring an alignment layer for aligning liquid crystal molecules in broadband waveplates or broadband waveplate lenses using a two-beam exposure.

(65) FIGS. 29A-29B illustrate an example method of configuring an alignment layer for aligning liquid crystal molecules in broadband waveplates or broadband waveplate lenses using a master lens.

(66) FIGS. 30A-30B illustrate an example method of configuring a nanoimprint alignment layer for aligning liquid crystal molecules in broadband waveplates or broadband waveplate lenses using a master lens and one-beam exposure.

(67) FIG. 30C illustrates an example nanoimprint alignment layer for aligning liquid crystal molecules of a broadband waveplate lens using the example method of FIGS. 30A-30B.

(68) FIGS. 31A-31C illustrate an example method of fabricating a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals using a gap fill process.

(69) FIGS. 32A-32E illustrate an example method of fabricating a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals using a layer transfer process.

(70) FIG. 33 illustrates an example of a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals formed on a portion of a substrate.

(71) FIG. 34 illustrates an example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate by selective coating.

(72) FIGS. 35A-35C illustrate an example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate by

blanket coating a layer of liquid crystals and subtractively removing.

(73) FIG. 36A-35C illustrate an example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate by using selective optical patterning of an alignment layer.

(74) FIG. 37A-37B illustrate an example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate by using selective nanoimprinting an alignment layer.

(75) Throughout the drawings, reference numbers may be re-used to indicate correspondence between referenced elements. The drawings are provided to illustrate example embodiments described herein and are not intended to limit the scope of the disclosure.

DETAILED DESCRIPTION

(76) AR systems may display virtual content to a user, or viewer, while still allowing the user to see the world around them. Preferably, this content is displayed on a head-mounted display, e.g., as part of eyewear, that projects image information to the user's eyes. In addition, the display may also transmit light from the surrounding environment to the user's eyes, to allow a view of that surrounding environment. As used herein, it will be appreciated that a "head-mounted" or "head mountable" display is a display that may be mounted on the head of a viewer or user.

(77) In some AR systems, a plurality of waveguides may be configured to form virtual images at a plurality of virtual depth planes (also referred to simply a "depth planes" herein). Different waveguides of the plurality of waveguides may have different optical powers and may be formed at different distances from the user's eye. The display systems may also include a plurality lenses that provide or additionally provide optical powers. The optical powers of the waveguides and/or the lenses may provide images at different virtual depth planes.

Undesirably, each of the waveguides and lenses may increase the overall thickness, weight and cost of the display.

(78) Advantageously, in various embodiments described herein, an adaptive lens assembly may be utilized to provide variable optical power to, e.g., modify the wavefront divergence of light propagating through the lens assembly to provide virtual depth planes at different perceived distances from a user. The adaptive lens assembly may include a pair of waveplate lenses having a switchable waveplate disposed between them. Each of the first and second waveplate lenses may be configured to alter a polarization state of the light passing therethrough, and the switchable waveplate may be switchable between a plurality of states, e.g., a first state that allows light to pass without changing a polarization of the light and a second state that alters the polarization of the light (e.g., by changing the handedness of the polarization). In some embodiments, one or both of the waveplate lenses may be switchable between these first and second states and the intervening switchable waveplate noted above may be omitted.

(79) It will be appreciated that the adaptive lens assembly may comprise a stack of a plurality of waveplate lenses and a plurality of switchable waveplates. For example, the adaptive lens assembly may comprise multiple subassemblies comprising a pair of waveplate lenses with an intervening switchable waveplate. In some embodiments, the adaptive lens assembly may include alternating waveplate lenses and switchable waveplates. Advantageously, such alternating arrangement allows a reduction in thickness and weight by having neighboring switchable waveplates share a common waveplate lens. In some embodiments, by switching the states of the various combinations of the switchable plates in the stack, more than two discrete levels of optical power may be provided.

(80) In some embodiments, the adaptive lens assembly forms a display device with a waveguide assembly to form images at different virtual depth planes. In various embodiments, the display device comprises a pair of adaptive lens assemblies interposed by a waveguide assembly. The waveguide assembly includes a waveguide configured to propagate light (e.g., visible light) therein (e.g., via total internal reflection) and to outcouple the light. For example, the light may be outcoupled along an optical axis direction normal to a major surface of the waveguide. One of the pair of adaptive lens assemblies may be formed on a first side of the waveguide assembly and may be configured to provide variable optical power to modify the wavefront of light passing through the adaptive lens assembly to form images at each of a plurality of virtual depth planes. For example, the adaptive lens assemblies may converge or diverge outcoupled light received from the waveguide assembly. To compensate for modifications of real world views due to the convergence or divergence of ambient light propagating through the adaptive lens assembly and/or the waveguide assembly, the other of the pair of adaptive lens assemblies is additionally provided on a second side of the waveguide assembly opposite the first side. When the switchable waveplates of each adaptive lens assembly assume a corresponding state, the adaptive lens assemblies may have optical powers with opposite signs, such that the other of the adaptive lens assemblies correct for distortions caused by the adaptive lens assembly on the first side of the waveguide assembly.

(81) Advantageously, relative to a continuously variable adaptive lens having continuously variable optical

elements, utilizing a waveplate that is switchable between two states simplifies the driving of the adaptive lens assembly and reduces the computational power needed to determine how to appropriately activate the adaptive lens assembly for a desired optical power. In addition, by allowing the adaptive lens assembly to modify the wavefront divergence of light outputted by a waveguide, the number waveguides needed to provide a plurality of depth planes is reduced relative to an arrangement in which each waveguide provides a particular amount of wavefront divergence.

(82) Reference will now be made to the drawings, in which like reference numerals refer to like parts throughout. Unless indicated otherwise, the drawings are schematic not necessarily drawn to scale.

(83) Example Display Systems

(84) FIG. 2 illustrates a conventional display system for simulating three-dimensional imagery for a user. It will be appreciated that a user's eyes are spaced apart and that, when looking at a real object in space, each eye will have a slightly different view of the object and may form an image of the object at different locations on the retina of each eye. This may be referred to as binocular disparity and may be utilized by the human visual system to provide a perception of depth. Conventional display systems simulate binocular disparity by presenting two distinct images **190, 200** with slightly different views of the same virtual object—one for each eye **210, 220**—corresponding to the views of the virtual object that would be seen by each eye were the virtual object a real object at a desired depth. These images provide binocular cues that the user's visual system may interpret to derive a perception of depth.

(85) With continued reference to FIG. 2, the images **190, 200** are spaced from the eyes **210, 220** by a distance **230** on a z-axis. The z-axis is parallel to the optical axis of the viewer with their eyes fixated on an object at optical infinity directly ahead of the viewer. The images **190, 200** are flat and at a fixed distance from the eyes **210, 220**. Based on the slightly different views of a virtual object in the images presented to the eyes **210, 220**, respectively, the eyes may naturally rotate such that an image of the object falls on corresponding points on the retinas of each of the eyes, to maintain single binocular vision. This rotation may cause the lines of sight of each of the eyes **210, 220** to converge onto a point in space at which the virtual object is perceived to be present. As a result, providing three-dimensional imagery conventionally involves providing binocular cues that may manipulate the vergence of the user's eyes **210, 220**, and that the human visual system interprets to provide a perception of depth.

(86) Generating a realistic and comfortable perception of depth is challenging, however. It will be appreciated that light from objects at different distances from the eyes have wavefronts with different amounts of divergence.

FIGS. 3A-3C illustrate relationships between distance and the divergence of light rays. The distance between the object and the eye **210** is represented by, in order of decreasing distance, R1, R2, and R3. As shown in FIGS. 3A-3C, the light rays become more divergent as distance to the object decreases. Conversely, as distance increases, the light rays become more collimated. Stated another way, it may be said that the light field produced by a point (the object or a part of the object) has a spherical wavefront curvature, which is a function of how far away the point is from the eye of the user. The curvature increases with decreasing distance between the object and the eye **210**. While only a single eye **210** is illustrated for clarity of illustration in FIGS. 3A-3C and other figures herein, the discussions regarding eye **210** may be applied to both eyes **210** and **220** of a viewer.

(87) With continued reference to FIGS. 3A-3C, light from an object that the viewer's eyes are fixated on may have different degrees of wavefront divergence. Due to the different amounts of wavefront divergence, the light may be focused differently by the lens of the eye, which in turn may require the lens to assume different shapes to form a focused image on the retina of the eye. Where a focused image is not formed on the retina, the resulting retinal blur acts as a cue to accommodation that causes a change in the shape of the lens of the eye until a focused image is formed on the retina. For example, the cue to accommodation may trigger the ciliary muscles surrounding the lens of the eye to relax or contract, thereby modulating the force applied to the suspensory ligaments holding the lens, thus causing the shape of the lens of the eye to change until retinal blur of an object of fixation is eliminated or minimized, thereby forming a focused image of the object of fixation on the retina (e.g., fovea) of the eye. The process by which the lens of the eye changes shape may be referred to as accommodation, and the shape of the lens of the eye required to form a focused image of the object of fixation on the retina (e.g., fovea) of the eye may be referred to as an accommodative state.

(88) With reference now to FIG. 4A, a representation of the accommodation-vergence response of the human visual system is illustrated. The movement of the eyes to fixate on an object causes the eyes to receive light from the object, with the light forming an image on each of the retinas of the eyes. The presence of retinal blur in the image formed on the retina may provide a cue to accommodation, and the relative locations of the image on the retinas may provide a cue to vergence. The cue to accommodation causes accommodation to occur, resulting in the lenses of the eyes each assuming a particular accommodative state that forms a focused image of the object on the retina (e.g., fovea) of the eye. On the other hand, the cue to vergence causes vergence movements (rotation of the eyes) to occur such that the images formed on each retina of each eye are at corresponding retinal points that

maintain single binocular vision. In these positions, the eyes may be said to have assumed a particular vergence state. With continued reference to FIG. 4A, accommodation may be understood to be the process by which the eye achieves a particular accommodative state, and vergence may be understood to be the process by which the eye achieves a particular vergence state. As indicated in FIG. 4A, the accommodative and vergence states of the eyes may change if the user fixates on another object. For example, the accommodated state may change if the user fixates on a new object at a different depth on the z-axis.

(89) Without being limited by theory, it is believed that viewers of an object may perceive the object as being “three-dimensional” due to a combination of vergence and accommodation. As noted above, vergence movements (e.g., rotation of the eyes so that the pupils move toward or away from each other to converge the lines of sight of the eyes to fixate upon an object) of the two eyes relative to each other are closely associated with accommodation of the lenses of the eyes. Under normal conditions, changing the shapes of the lenses of the eyes to change focus from one object to another object at a different distance will automatically cause a matching change in vergence to the same distance, under a relationship known as the “accommodation-vergence reflex.” Likewise, a change in vergence will trigger a matching change in lens shape under normal conditions.

(90) With reference now to FIG. 4B, examples of different accommodative and vergence states of the eyes are illustrated. The pair of eyes **222a** is fixated on an object at optical infinity, while the pair eyes **222b** are fixated on an object **221** at less than optical infinity. Notably, the vergence states of each pair of eyes is different, with the pair of eyes **222a** directed straight ahead, while the pair of eyes **222** converge on the object **221**. The accommodative states of the eyes forming each pair of eyes **222a** and **222b** are also different, as represented by the different shapes of the lenses **210a**, **220a**.

(91) Undesirably, many users of conventional “3-D” display systems find such conventional systems to be uncomfortable or may not perceive a sense of depth at all due to a mismatch between accommodative and vergence states in these displays. As noted above, many stereoscopic or “3-D” display systems display a scene by providing slightly different images to each eye. Such systems are uncomfortable for many viewers, since they, among other things, simply provide different presentations of a scene and cause changes in the vergence states of the eyes, but without a corresponding change in the accommodative states of those eyes. Rather, the images are shown by a display at a fixed distance from the eyes, such that the eyes view all the image information at a single accommodative state. Such an arrangement works against the “accommodation-vergence reflex” by causing changes in the vergence state without a matching change in the accommodative state. This mismatch is believed to cause viewer discomfort. Display systems that provide a better match between accommodation and vergence may form more realistic and comfortable simulations of three-dimensional imagery.

(92) Without being limited by theory, it is believed that the human eye typically may interpret a finite number of depth planes to provide depth perception. Consequently, a highly believable simulation of perceived depth may be achieved by providing, to the eye, different presentations of an image corresponding to each of these limited numbers of depth planes. In some embodiments, the different presentations may provide both cues to vergence and matching cues to accommodation, thereby providing physiologically correct accommodation-vergence matching.

(93) With continued reference to FIG. 4B, two depth planes **240**, corresponding to different distances in space from the eyes **210**, **220**, are illustrated. For a given depth plane **240**, vergence cues may be provided by the displaying of images of appropriately different perspectives for each eye **210**, **220**. In addition, for a given depth plane **240**, light forming the images provided to each eye **210**, **220** may have a wavefront divergence corresponding to a light field produced by a point at the distance of that depth plane **240**.

(94) In the illustrated embodiment, the distance, along the z-axis, of the depth plane **240** containing the point **221** is 1 m. As used herein, distances or depths along the z-axis may be measured with a zero-point located at the exit pupils of the user's eyes. Thus, a depth plane **240** located at a depth of 1 m corresponds to a distance of 1 m away from the exit pupils of the user's eyes, on the optical axis of those eyes with the eyes directed towards optical infinity. As an approximation, the depth or distance along the z-axis may be measured from the display in front of the user's eyes (e.g., from the surface of a waveguide), plus a value for the distance between the device and the exit pupils of the user's eyes. That value may be called the eye relief and corresponds to the distance between the exit pupil of the user's eye and the display worn by the user in front of the eye. In practice, the value for the eye relief may be a normalized value used generally for all viewers. For example, the eye relief may be assumed to be 20 mm and a depth plane that is at a depth of 1 m may be at a distance of 980 mm in front of the display.

(95) With reference now to FIGS. 4C and 4D, examples of matched accommodation-vergence distances and mismatched accommodation-vergence distances are illustrated, respectively. As illustrated in FIG. 4C, the display system may provide images of a virtual object to each eye **210**, **220**. The images may cause the eyes **210**, **220** to assume a vergence state in which the eyes converge on a point **15** on a depth plane **240**. In addition, the images may be formed by a light having a wavefront curvature corresponding to real objects at that depth plane **240**. As a

result, the eyes **210**, **220** assume an accommodative state in which the images are in focus on the retinas of those eyes. Thus, the user may perceive the virtual object as being at the point **15** on the depth plane **240**.

(96) It will be appreciated that each of the accommodative and vergence states of the eyes **210**, **220** are associated with a particular distance on the z-axis. For example, an object at a particular distance from the eyes **210**, **220** causes those eyes to assume particular accommodative states based upon the distances of the object. The distance associated with a particular accommodative state may be referred to as the accommodation distance, A.sub.d. Similarly, there are particular vergence distances, V.sub.d, associated with the eyes in particular vergence states, or positions relative to one another. Where the accommodation distance and the vergence distance match, the relationship between accommodation and vergence may be said to be physiologically correct. This is considered to be the most comfortable scenario for a viewer.

(97) In stereoscopic displays, however, the accommodation distance and the vergence distance may not always match. For example, as illustrated in FIG. 4D, images displayed to the eyes **210**, **220** may be displayed with wavefront divergence corresponding to depth plane **240**, and the eyes **210**, **220** may assume a particular accommodative state in which the points **15a**, **15b** on that depth plane are in focus. However, the images displayed to the eyes **210**, **220** may provide cues for vergence that cause the eyes **210**, **220** to converge on a point **15** that is not located on the depth plane **240**. As a result, the accommodation distance corresponds to the distance from the exit pupils of the eyes **210**, **220** to the depth plane **240**, while the vergence distance corresponds to the larger distance from the exit pupils of the eyes **210**, **220** to the point **15**, in some embodiments. The accommodation distance is different from the vergence distance. Consequently, there is an accommodation-vergence mismatch. Such a mismatch is considered undesirable and may cause discomfort in the user. It will be appreciated that the mismatch corresponds to distance (e.g., V.sub.d-A.sub.d) and may be characterized using diopters.

(98) In some embodiments, it will be appreciated that a reference point other than exit pupils of the eyes **210**, **220** may be utilized for determining distance for determining accommodation-vergence mismatch, so long as the same reference point is utilized for the accommodation distance and the vergence distance. For example, the distances could be measured from the cornea to the depth plane, from the retina to the depth plane, from the eyepiece (e.g., a waveguide of the display device) to the depth plane, and so on.

(99) Without being limited by theory, it is believed that users may still perceive accommodation-vergence mismatches of up to about 0.25 diopter, up to about 0.33 diopter, and up to about 0.5 diopter as being physiologically correct, without the mismatch itself causing significant discomfort. In some embodiments, display systems disclosed herein (e.g., the display system **250**, FIG. 6) present images to the viewer having accommodation-vergence mismatch of about 0.5 diopter or less. In some other embodiments, the accommodation-vergence mismatch of the images provided by the display system is about 0.33 diopter or less. In yet other embodiments, the accommodation-vergence mismatch of the images provided by the display system is about 0.25 diopter or less, including about 0.1 diopter or less.

(100) FIG. 5 illustrates aspects of an approach for simulating three-dimensional imagery by modifying wavefront divergence. The display system includes a waveguide **270** that is configured to receive light **770** that is encoded with image information, and to output that light to the user's eye **210**. The waveguide **270** may output the light **650** with a defined amount of wavefront divergence corresponding to the wavefront divergence of a light field produced by a point on a desired depth plane **240**. In some embodiments, the same amount of wavefront divergence is provided for all objects presented on that depth plane. In addition, it will be illustrated that the other eye of the user may be provided with image information from a similar waveguide.

(101) In some embodiments, a single waveguide may be configured to output light with a set amount of wavefront divergence corresponding to a single or limited number of depth planes and/or the waveguide may be configured to output light of a limited range of wavelengths. Consequently, in some embodiments, a plurality or stack of waveguides may be utilized to provide different amounts of wavefront divergence for different depth planes and/or to output light of different ranges of wavelengths. As used herein, it will be appreciated at a depth plane may be planar or may follow the contours of a curved surface.

(102) FIG. 6 illustrates an example of a waveguide stack for outputting image information to a user. A display system **250** includes a stack of waveguides, or stacked waveguide assembly, **260** that may be utilized to provide three-dimensional perception to the eye/brain using a plurality of waveguides **270**, **280**, **290**, **300**, **310**. It will be appreciated that the display system **250** may be considered a light field display in some embodiments. In addition, the waveguide assembly **260** may also be referred to as an eyepiece.

(103) In some embodiments, the display system **250** may be configured to provide substantially continuous cues to vergence and multiple discrete cues to accommodation. The cues to vergence may be provided by displaying different images to each of the eyes of the user, and the cues to accommodation may be provided by outputting the light that forms the images with selectable discrete amounts of wavefront divergence. Stated another way, the

display system **250** may be configured to output light with variable levels of wavefront divergence. In some embodiments, each discrete level of wavefront divergence corresponds to a particular depth plane and may be provided by a particular one of the waveguides **270, 280, 290, 300, 310**.

(104) With continued reference to FIG. **6**, the waveguide assembly **260** may also include a plurality of features **320, 330, 340, 350** between the waveguides. In some embodiments, the features **320, 330, 340, 350** may be one or more lenses. The waveguides **270, 280, 290, 300, 310** and/or the plurality of lenses **320, 330, 340, 350** may be configured to send image information to the eye with various levels of wavefront curvature or light ray divergence. Each waveguide level may be associated with a particular depth plane and may be configured to output image information corresponding to that depth plane. Image injection devices **360, 370, 380, 390, 400** may function as a source of light for the waveguides and may be utilized to inject image information into the waveguides **270, 280, 290, 300, 310**, each of which may be configured, as described herein, to distribute incoming light across each respective waveguide, for output toward the eye **210**. Light exits an output surface **410, 420, 430, 440, 450** of the image injection devices **360, 370, 380, 390, 400** and is injected into a corresponding input surface **460, 470, 480, 490, 500** of the waveguides **270, 280, 290, 300, 310**. In some embodiments, each of the input surfaces **460, 470, 480, 490, 500** may be an edge of a corresponding waveguide, or may be part of a major surface of the corresponding waveguide (that is, one of the waveguide surfaces directly facing the world **510** or the viewer's eye **210**). In some embodiments, a single beam of light (e.g. a collimated beam) may be injected into each waveguide to output an entire field of cloned collimated beams that are directed toward the eye **210** at particular angles (and amounts of divergence) corresponding to the depth plane associated with a particular waveguide. In some embodiments, a single one of the image injection devices **360, 370, 380, 390, 400** may be associated with and inject light into a plurality (e.g., three) of the waveguides **270, 280, 290, 300, 310**.

(105) In some embodiments, the image injection devices **360, 370, 380, 390, 400** are discrete displays that each produce image information for injection into a corresponding waveguide **270, 280, 290, 300, 310**, respectively. In some other embodiments, the image injection devices **360, 370, 380, 390, 400** are the output ends of a single multiplexed display which may, e.g., pipe image information via one or more optical conduits (such as fiber optic cables) to each of the image injection devices **360, 370, 380, 390, 400**. It will be appreciated that the image information provided by the image injection devices **360, 370, 380, 390, 400** may include light of different wavelengths, or colors (e.g., different component colors, as discussed herein).

(106) In some embodiments, the light injected into the waveguides **270, 280, 290, 300, 310** is provided by a light projector system **520**, which comprises a light module **530**, which may include a light emitter, such as a light emitting diode (LED). The light from the light module **530** may be directed to and modified by a light modulator **540**, e.g., a spatial light modulator, via a beam splitter **550**. The light modulator **540** may be configured to change the perceived intensity of the light injected into the waveguides **270, 280, 290, 300, 310** to encode the light with image information. Examples of spatial light modulators include liquid crystal displays (LCD) including a liquid crystal on silicon (LCOS) displays. It will be appreciated that the image injection devices **360, 370, 380, 390, 400** are illustrated schematically and, in some embodiments, these image injection devices may represent different light paths and locations in a common projection system configured to output light into associated ones of the waveguides **270, 280, 290, 300, 310**. In some embodiments, the waveguides of the waveguide assembly **260** may function as ideal lens while relaying light injected into the waveguides out to the user's eyes. In this conception, the object may be the spatial light modulator **540** and the image may be the image on the depth plane.

(107) In some embodiments, the display system **250** may be a scanning fiber display comprising one or more scanning fibers configured to project light in various patterns (e.g., raster scan, spiral scan, Lissajous patterns, etc.) into one or more waveguides **270, 280, 290, 300, 310** and ultimately to the eye **210** of the viewer. In some embodiments, the illustrated image injection devices **360, 370, 380, 390, 400** may schematically represent a single scanning fiber or a bundle of scanning fibers configured to inject light into one or a plurality of the waveguides **270, 280, 290, 300, 310**. In some other embodiments, the illustrated image injection devices **360, 370, 380, 390, 400** may schematically represent a plurality of scanning fibers or a plurality of bundles of scanning fibers, each of which are configured to inject light into an associated one of the waveguides **270, 280, 290, 300, 310**. It will be appreciated that one or more optical fibers may be configured to transmit light from the light module **530** to the one or more waveguides **270, 280, 290, 300, 310**. It will be appreciated that one or more intervening optical structures may be provided between the scanning fiber, or fibers, and the one or more waveguides **270, 280, 290, 300, 310** to, e.g., redirect light exiting the scanning fiber into the one or more waveguides **270, 280, 290, 300, 310**.

(108) A controller **560** controls the operation of one or more of the stacked waveguide assembly **260**, including operation of the image injection devices **360, 370, 380, 390, 400**, the light source **530**, and the light modulator **540**. In some embodiments, the controller **560** is part of the local data processing module **140**. The controller **560**

includes programming (e.g., instructions in a non-transitory medium) that regulates the timing and provision of image information to the waveguides **270, 280, 290, 300, 310** according to, e.g., any of the various schemes disclosed herein. In some embodiments, the controller may be a single integral device, or a distributed system connected by wired or wireless communication channels. The controller **560** may be part of the processing modules **140** or **150** (FIG. **9D**) in some embodiments.

(109) With continued reference to FIG. **6**, the waveguides **270, 280, 290, 300, 310** may be configured to propagate light within each respective waveguide by total internal reflection (TIR). The waveguides **270, 280, 290, 300, 310** may each be planar or have another shape (e.g., curved), with major top and bottom surfaces and edges extending between those major top and bottom surfaces. In the illustrated configuration, the waveguides **270, 280, 290, 300, 310** may each include out-coupling optical elements **570, 580, 590, 600, 610** that are configured to extract light out of a waveguide by redirecting the light, propagating within each respective waveguide, out of the waveguide to output image information to the eye **210**. Extracted light may also be referred to as out-coupled light and the out-coupling optical elements light may also be referred to light extracting optical elements. An extracted beam of light may be outputted by the waveguide at locations at which the light propagating in the waveguide strikes a light extracting optical element. The out-coupling optical elements **570, 580, 590, 600, 610** may, for example, be gratings, including diffractive optical features, as discussed further herein. While illustrated disposed at the bottom major surfaces of the waveguides **270, 280, 290, 300, 310**, for case of description and drawing clarity, in some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** may be disposed at the top and/or bottom major surfaces, and/or may be disposed directly in the volume of the waveguides **270, 280, 290, 300, 310**, as discussed further herein. In some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** may be formed in a layer of material that is attached to a transparent substrate to form the waveguides **270, 280, 290, 300, 310**. In some other embodiments, the waveguides **270, 280, 290, 300, 310** may be a monolithic piece of material and the out-coupling optical elements **570, 580, 590, 600, 610** may be formed on a surface and/or in the interior of that piece of material.

(110) With continued reference to FIG. **6**, as discussed herein, each waveguide **270, 280, 290, 300, 310** is configured to output light to form an image corresponding to a particular depth plane. For example, the waveguide **270** nearest the eye may be configured to deliver collimated light (which was injected into such waveguide **270**), to the eye **210**. The collimated light may be representative of the optical infinity focal plane. The next waveguide up **280** may be configured to send out collimated light which passes through the first lens **350** (e.g., a negative lens) before it may reach the eye **210**; such first lens **350** may be configured to create a slight convex wavefront curvature so that the eye/brain interprets light coming from that next waveguide up **280** as coming from a first focal plane closer inward toward the eye **210** from optical infinity. Similarly, the third up waveguide **290** passes its output light through both the first **350** and second **340** lenses before reaching the eye **210**; the combined optical power of the first **350** and second **340** lenses may be configured to create another incremental amount of wavefront curvature so that the eye/brain interprets light coming from the third waveguide **290** as coming from a second focal plane that is even closer inward toward the person from optical infinity than was light from the next waveguide up **280**.

(111) The other waveguide layers **300, 310** and lenses **330, 320** are similarly configured, with the highest waveguide **310** in the stack sending its output through all of the lenses between it and the eye for an aggregate focal power representative of the closest focal plane to the person. To compensate for the stack of lenses **320, 330, 340, 350** when viewing/interpreting light coming from the world **510** on the other side of the stacked waveguide assembly **260**, a compensating lens layer **620** may be disposed at the top of the stack to compensate for the aggregate power of the lens stack **320, 330, 340, 350** below. Such a configuration provides as many perceived focal planes as there are available waveguide/lens pairings. Both the out-coupling optical elements of the waveguides and the focusing aspects of the lenses may be static (i.e., not dynamic or electro-active). In some alternative embodiments, either or both may be dynamic using electro-active features.

(112) In some embodiments, two or more of the waveguides **270, 280, 290, 300, 310** may have the same associated depth plane. For example, multiple waveguides **270, 280, 290, 300, 310** may be configured to output images set to the same depth plane, or multiple subsets of the waveguides **270, 280, 290, 300, 310** may be configured to output images set to the same plurality of depth planes, with one set for each depth plane. This may provide advantages for forming a tiled image to provide an expanded field of view at those depth planes.

(113) With continued reference to FIG. **6**, the out-coupling optical elements **570, 580, 590, 600, 610** may be configured to both redirect light out of their respective waveguides and to output this light with the appropriate amount of divergence or collimation for a particular depth plane associated with the waveguide. As a result, waveguides having different associated depth planes may have different configurations of out-coupling optical elements **570, 580, 590, 600, 610**, which output light with a different amount of divergence depending on the associated depth plane. In some embodiments, the light extracting optical elements **570, 580, 590, 600, 610** may

be volumetric or surface features, which may be configured to output light at specific angles. For example, the light extracting optical elements **570, 580, 590, 600, 610** may be volume holograms, surface holograms, and/or diffraction gratings. In some embodiments, the features **320, 330, 340, 350** may not be lenses; rather, they may simply be spacers (e.g., cladding layers and/or structures for forming air gaps).

(114) In some embodiments, the out-coupling optical elements **570, 580, 590, 600, 610** are diffractive features that form a diffraction pattern, or “diffractive optical element” (also referred to herein as a “DOE”). Preferably, the DOE's have a sufficiently low diffraction efficiency so that only a portion of the light of the beam is deflected away toward the eye **210** with each intersection of the DOE, while the rest continues to move through a waveguide via TIR. The light carrying the image information is thus divided into a number of related exit beams that exit the waveguide at a multiplicity of locations and the result is a fairly uniform pattern of exit emission toward the eye **210** for this particular collimated beam bouncing around within a waveguide.

(115) In some embodiments, one or more DOEs may be switchable between “on” states in which they actively diffract, and “off” states in which they do not significantly diffract. For instance, a switchable DOE may comprise a layer of polymer dispersed liquid crystal, in which microdroplets comprise a diffraction pattern in a host medium, and the refractive index of the microdroplets may be switched to substantially match the refractive index of the host material (in which case the pattern does not appreciably diffract incident light) or the microdroplet may be switched to an index that does not match that of the host medium (in which case the pattern actively diffracts incident light).

(116) In some embodiments, a camera assembly **630** (e.g., a digital camera, including visible light and infrared light cameras) may be provided to capture images of the eye **210** and/or tissue around the eye **210** to, e.g., detect user inputs and/or to monitor the physiological state of the user. As used herein, a camera may be any image capture device. In some embodiments, the camera assembly **630** may include an image capture device and a light source to project light (e.g., infrared light) to the eye, which may then be reflected by the eye and detected by the image capture device. In some embodiments, the camera assembly **630** may be attached to the frame **80** (FIG. **9D**) and may be in electrical communication with the processing modules **140** and/or **150**, which may process image information from the camera assembly **630**. In some embodiments, one camera assembly **630** may be utilized for each eye, to separately monitor each eye.

(117) With reference now to FIG. **7**, an example of exit beams outputted by a waveguide is shown. One waveguide is illustrated, but it will be appreciated that other waveguides in the waveguide assembly **260** (FIG. **6**) may function similarly, where the waveguide assembly **260** includes multiple waveguides. Light **640** is injected into the waveguide **270** at the input surface **460** of the waveguide **270** and propagates within the waveguide **270** by TIR. At points where the light **640** impinges on the DOE **570**, a portion of the light exits the waveguide as exit beams **650**. The exit beams **650** are illustrated as substantially parallel but, as discussed herein, they may also be redirected to propagate to the eye **210** at an angle (e.g., forming divergent exit beams), depending on the depth plane associated with the waveguide **270**. It will be appreciated that substantially parallel exit beams may be indicative of a waveguide with out-coupling optical elements that out-couple light to form images that appear to be set on a depth plane at a large distance (e.g., optical infinity) from the eye **210**. Other waveguides or other sets of out-coupling optical elements may output an exit beam pattern that is more divergent, which would require the eye **210** to accommodate to a closer distance to bring it into focus on the retina and would be interpreted by the brain as light from a distance closer to the eye **210** than optical infinity.

(118) In some embodiments, a full color image may be formed at each depth plane by overlaying images in each of the component colors, e.g., three or more component colors. FIG. **8** illustrates an example of a stacked waveguide assembly in which each depth plane includes images formed using multiple different component colors. The illustrated embodiment shows depth planes **240a-240f**, although more or fewer depths are also contemplated. Each depth plane may have three or more component color images associated with it, including: a first image of a first color, G; a second image of a second color, R; and a third image of a third color, B. Different depth planes are indicated in the figure by different numbers for diopters (dpt) following the letters G, R, and B. Just as examples, the numbers following each of these letters indicate diopters (1/m), or inverse distance of the depth plane from a viewer, and each box in the figures represents an individual component color image. In some embodiments, to account for differences in the eye's focusing of light of different wavelengths, the exact placement of the depth planes for different component colors may vary. For example, different component color images for a given depth plane may be placed on depth planes corresponding to different distances from the user. Such an arrangement may increase visual acuity and user comfort and/or may decrease chromatic aberrations.

(119) In some embodiments, light of each component color may be outputted by a single dedicated waveguide and, consequently, each depth plane may have multiple waveguides associated with it. In such embodiments, each box in the figures including the letters G, R, or B may be understood to represent an individual waveguide, and three waveguides may be provided per depth plane where three component color images are provided per depth

plane. While the waveguides associated with each depth plane are shown adjacent to one another in this drawing for ease of description, it will be appreciated that, in a physical device, the waveguides may all be arranged in a stack with one waveguide per level. In some other embodiments, multiple component colors may be outputted by the same waveguide, such that, e.g., only a single waveguide may be provided per depth plane.

(120) With continued reference to FIG. 8, in some embodiments, G is the color green, R is the color red, and B is the color blue. In some other embodiments, other colors associated with other wavelengths of light, including magenta and cyan, may be used in addition to or may replace one or more of red, green, or blue.

(121) It will be appreciated that references to a given color of light throughout this disclosure will be understood to encompass light of one or more wavelengths within a range of wavelengths of light that are perceived by a viewer as being of that given color. For example, red light may include light of one or more wavelengths in the range of about 620-780 nm, green light may include light of one or more wavelengths in the range of about 492-577 nm, and blue light may include light of one or more wavelengths in the range of about 435-493 nm.

(122) In some embodiments, the light source 530 (FIG. 6) may be configured to emit light of one or more wavelengths outside the visual perception range of the viewer, for example, infrared and/or ultraviolet wavelengths. In addition, the in-coupling, out-coupling, and other light redirecting structures of the waveguides of the display 250 may be configured to direct and emit this light out of the display towards the user's eye 210, e.g., for imaging and/or user stimulation applications.

(123) With reference now to FIG. 9A, in some embodiments, light impinging on a waveguide may need to be redirected to in-couple that light into the waveguide. An in-coupling optical element may be used to redirect and in-couple the light into its corresponding waveguide. FIG. 9A illustrates a cross-sectional side view of an example of a plurality or set 660 of stacked waveguides that each includes an in-coupling optical element. The waveguides may each be configured to output light of one or more different wavelengths, or one or more different ranges of wavelengths. It will be appreciated that the stack 660 may correspond to the stack 260 (FIG. 6) and the illustrated waveguides of the stack 660 may correspond to part of the plurality of waveguides 270, 280, 290, 300, 310, except that light from one or more of the image injection devices 360, 370, 380, 390, 400 is injected into the waveguides from a position that requires light to be redirected for in-coupling.

(124) The illustrated set 660 of stacked waveguides includes waveguides 670, 680, and 690. Each waveguide includes an associated in-coupling optical element (which may also be referred to as a light input area on the waveguide), with, e.g., in-coupling optical element 700 disposed on a major surface (e.g., an upper major surface) of waveguide 670, in-coupling optical element 710 disposed on a major surface (e.g., an upper major surface) of waveguide 680, and in-coupling optical element 720 disposed on a major surface (e.g., an upper major surface) of waveguide 690. In some embodiments, one or more of the in-coupling optical elements 700, 710, 720 may be disposed on the bottom major surface of the respective waveguide 670, 680, 690 (particularly where the one or more in-coupling optical elements are reflective, deflecting optical elements). As illustrated, the in-coupling optical elements 700, 710, 720 may be disposed on the upper major surface of their respective waveguide 670, 680, 690 (or the top of the next lower waveguide), particularly where those in-coupling optical elements are transmissive, deflecting optical elements. In some embodiments, the in-coupling optical elements 700, 710, 720 may be disposed in the body of the respective waveguide 670, 680, 690. In some embodiments, as discussed herein, the in-coupling optical elements 700, 710, 720 are wavelength selective, such that they selectively redirect one or more wavelengths of light, while transmitting other wavelengths of light. While illustrated on one side or corner of their respective waveguide 670, 680, 690, it will be appreciated that the in-coupling optical elements 700, 710, 720 may be disposed in other areas of their respective waveguide 670, 680, 690 in some embodiments.

(125) As illustrated, the in-coupling optical elements 700, 710, 720 may be laterally offset from one another. In some embodiments, each in-coupling optical element may be offset such that it receives light without that light passing through another in-coupling optical element. For example, each in-coupling optical element 700, 710, 720 may be configured to receive light from a different image injection device 360, 370, 380, 390, and 400 as shown in FIG. 6, and may be separated (e.g., laterally spaced apart) from other in-coupling optical elements 700, 710, 720 such that it substantially does not receive light from the other ones of the in-coupling optical elements 700, 710, 720.

(126) Each waveguide also includes associated light distributing elements, with, e.g., light distributing elements 730 disposed on a major surface (e.g., a top major surface) of waveguide 670, light distributing elements 740 disposed on a major surface (e.g., a top major surface) of waveguide 680, and light distributing elements 750 disposed on a major surface (e.g., a top major surface) of waveguide 690. In some other embodiments, the light distributing elements 730, 740, 750, may be disposed on a bottom major surface of associated waveguides 670, 680, 690, respectively. In some other embodiments, the light distributing elements 730, 740, 750, may be disposed on both top and bottom major surface of associated waveguides 670, 680, 690, respectively; or the light distributing elements 730, 740, 750, may be disposed on different ones of the top and bottom major surfaces in

different associated waveguides **670, 680, 690**, respectively.

(127) The waveguides **670, 680, 690** may be spaced apart and separated by, e.g., gas, liquid, and/or solid layers of material. For example, as illustrated, layer **760a** may separate waveguides **670** and **680**; and layer **760b** may separate waveguides **680** and **690**. In some embodiments, the layers **760a** and **760b** are formed of low refractive index materials (that is, materials having a lower refractive index than the material forming the immediately adjacent one of waveguides **670, 680, 690**). Preferably, the refractive index of the material forming the layers **760a, 760b** is 0.05 or more, or 0.10 or less than the refractive index of the material forming the waveguides **670, 680, 690**. Advantageously, the lower refractive index layers **760a, 760b** may function as cladding layers that facilitate total internal reflection (TIR) of light through the waveguides **670, 680, 690** (e.g., TIR between the top and bottom major surfaces of each waveguide). In some embodiments, the layers **760a, 760b** are formed of air. While not illustrated, it will be appreciated that the top and bottom of the illustrated set **660** of waveguides may include immediately neighboring cladding layers.

(128) Preferably, for case of manufacturing and other considerations, the material forming the waveguides **670, 680, 690** are similar or the same, and the material forming the layers **760a, 760b** are similar or the same. In some embodiments, the material forming the waveguides **670, 680, 690** may be different between one or more waveguides, and/or the material forming the layers **760a, 760b** may be different, while still holding to the various refractive index relationships noted above.

(129) With continued reference to FIG. **9A**, light rays **770, 780, 790** are incident on the set **660** of waveguides. It will be appreciated that the light rays **770, 780, 790** may be injected into the waveguides **670, 680, 690** by one or more image injection devices **360, 370, 380, 390, 400** (FIG. **6**).

(130) In some embodiments, the light rays **770, 780, 790** have different properties, e.g., different wavelengths or different ranges of wavelengths, which may correspond to different colors. The in-coupling optical elements **700, 710, 720** each deflect the incident light such that the light propagates through a respective one of the waveguides **670, 680, 690** by TIR. In some embodiments, the incoupling optical elements **700, 710, 720** each selectively deflect one or more particular wavelengths of light, while transmitting other wavelengths to an underlying waveguide and associated incoupling optical element.

(131) For example, in-coupling optical element **700** may be configured to deflect ray **770**, which has a first wavelength or range of wavelengths, while transmitting rays **780** and **790**, which have different second and third wavelengths or ranges of wavelengths, respectively. The transmitted ray **780** impinges on and is deflected by the in-coupling optical element **710**, which is configured to deflect light of a second wavelength or range of wavelengths. The ray **790** is deflected by the in-coupling optical element **720**, which is configured to selectively deflect light of third wavelength or range of wavelengths.

(132) With continued reference to FIG. **9A**, the deflected light rays **770, 780, 790** are deflected so that they propagate through a corresponding waveguide **670, 680, 690**; that is, the in-coupling optical elements **700, 710, 720** of each waveguide deflects light into that corresponding waveguide **670, 680, 690** to in-couple light into that corresponding waveguide. The light rays **770, 780, 790** are deflected at angles that cause the light to propagate through the respective waveguide **670, 680, 690** by TIR. The light rays **770, 780, 790** propagate through the respective waveguide **670, 680, 690** by TIR until impinging on the waveguide's corresponding light distributing elements **730, 740, 750**.

(133) With reference now to FIG. **9B**, a perspective view of an example of the plurality of stacked waveguides of FIG. **9A** is illustrated. As noted above, the in-coupled light rays **770, 780, 790**, are deflected by the in-coupling optical elements **700, 710, 720**, respectively, and then propagate by TIR within the waveguides **670, 680, 690**, respectively. The light rays **770, 780, 790** then impinge on the light distributing elements **730, 740, 750**, respectively. The light distributing elements **730, 740, 750** deflect the light rays **770, 780, 790** so that they propagate towards the out-coupling optical elements **800, 810, 820**, respectively.

(134) In some embodiments, the light distributing elements **730, 740, 750** are orthogonal pupil expanders (OPE's). In some embodiments, the OPE's deflect or distribute light to the out-coupling optical elements **800, 810, 820** and, in some embodiments, may also increase the beam or spot size of this light as it propagates to the out-coupling optical elements. In some embodiments, the light distributing elements **730, 740, 750** may be omitted and the in-coupling optical elements **700, 710, 720** may be configured to deflect light directly to the out-coupling optical elements **800, 810, 820**. For example, with reference to FIG. **9A**, the light distributing elements **730, 740, 750** may be replaced with out-coupling optical elements **800, 810, 820**, respectively. In some embodiments, the out-coupling optical elements **800, 810, 820** are exit pupils (EP's) or exit pupil expanders (EPE's) that direct light in a viewer's eye **210** (FIG. **7**). It will be appreciated that the OPE's may be configured to increase the dimensions of the eye box in at least one axis and the EPE's may be to increase the eye box in an axis crossing, e.g., orthogonal to, the axis of the OPEs. For example, each OPE may be configured to redirect a portion of the light striking the OPE to an EPE of the same waveguide, while allowing the remaining portion of the light to continue

to propagate down the waveguide. Upon impinging on the OPE again, another portion of the remaining light is redirected to the EPE, and the remaining portion of that portion continues to propagate further down the waveguide, and so on. Similarly, upon striking the EPE, a portion of the impinging light is directed out of the waveguide towards the user, and a remaining portion of that light continues to propagate through the waveguide until it strikes the EP again, at which time another portion of the impinging light is directed out of the waveguide, and so on. Consequently, a single beam of incoupled light may be “replicated” each time a portion of that light is redirected by an OPE or EPE, thereby forming a field of cloned beams of light, as shown in FIG. 6. In some embodiments, the OPE and/or EPE may be configured to modify a size of the beams of light.

(135) Accordingly, with reference to FIGS. 9A and 9B, in some embodiments, the set **660** of waveguides includes waveguides **670, 680, 690**; in-coupling optical elements **700, 710, 720**; light distributing elements (e.g., OPE's) **730, 740, 750**; and out-coupling optical elements (e.g., EP's) **800, 810, 820** for each component color. The waveguides **670, 680, 690** may be stacked with an air gap/cladding layer between each one. The in-coupling optical elements **700, 710, 720** redirect or deflect incident light (with different in-coupling optical elements receiving light of different wavelengths) into its waveguide. The light then propagates at an angle which will result in TIR within the respective waveguide **670, 680, 690**. In the example shown, light ray **770** (e.g., blue light) is deflected by the first in-coupling optical element **700**, and then continues to bounce down the waveguide, interacting with the light distributing element (e.g., OPE's) **730** and then the out-coupling optical element (e.g., EPs) **800**, in a manner described earlier. The light rays **780** and **790** (e.g., green and red light, respectively) will pass through the waveguide **670**, with light ray **780** impinging on and being deflected by in-coupling optical element **710**. The light ray **780** then bounces down the waveguide **680** via TIR, proceeding on to its light distributing element (e.g., OPEs) **740** and then the out-coupling optical element (e.g., EP's) **810**. Finally, light ray **790** (e.g., red light) passes through the waveguide **690** to impinge on the light in-coupling optical elements **720** of the waveguide **690**. The light in-coupling optical elements **720** deflect the light ray **790** such that the light ray propagates to light distributing element (e.g., OPEs) **750** by TIR, and then to the out-coupling optical element (e.g., EPs) **820** by TIR. The out-coupling optical element **820** then finally out-couples the light ray **790** to the viewer, who also receives the out-coupled light from the other waveguides **670, 680**.

(136) FIG. 9C illustrates a top-down plan view of an example of the plurality of stacked waveguides of FIGS. 9A and 9B. As illustrated, the waveguides **670, 680, 690**, along with each waveguide's associated light distributing element **730, 740, 750** and associated out-coupling optical element **800, 810, 820**, may be vertically aligned. However, as discussed herein, the in-coupling optical elements **700, 710, 720** are not vertically aligned; rather, the in-coupling optical elements are preferably non-overlapping (e.g., laterally spaced apart as seen in the top-down view). As discussed further herein, this nonoverlapping spatial arrangement facilitates the injection of light from different resources into different waveguides on a one-to-one basis, thereby allowing a specific light source to be uniquely coupled to a specific waveguide. In some embodiments, arrangements including nonoverlapping spatially-separated in-coupling optical elements may be referred to as a shifted pupil system, and the in-coupling optical elements within these arrangements may correspond to sub pupils.

(137) FIG. 9D illustrates an example of wearable display system **60** into which the various waveguides and related systems disclosed herein may be integrated. In some embodiments, the display system **60** is the system **250** of FIG. 6, with FIG. 6 schematically showing some parts of that system **60** in greater detail. For example, the waveguide assembly **260** of FIG. 6 may be part of the display **70**.

(138) With continued reference to FIG. 9D, the display system **60** includes a display **70**, and various mechanical and electronic modules and systems to support the functioning of that display **70**. The display **70** may be coupled to a frame **80**, which is wearable by a display system user or viewer **90** and which is configured to position the display **70** in front of the eyes of the user **90**. The display **70** may be considered eyewear in some embodiments. In some embodiments, a speaker **100** is coupled to the frame **80** and configured to be positioned adjacent the ear canal of the user **90** (in some embodiments, another speaker, not shown, may optionally be positioned adjacent the other ear canal of the user to provide stereo/shapable sound control). The display system **60** may also include one or more microphones **110** or other devices to detect sound. In some embodiments, the microphone is configured to allow the user to provide inputs or commands to the system **60** (e.g., the selection of voice menu commands, natural language questions, etc.), and/or may allow audio communication with other persons (e.g., with other users of similar display systems). The microphone may further be configured as a peripheral sensor to collect audio data (e.g., sounds from the user and/or environment). In some embodiments, the display system may also include a peripheral sensor **120a**, which may be separate from the frame **80** and attached to the body of the user **90** (e.g., on the head, torso, an extremity, etc. of the user **90**). The peripheral sensor **120a** may be configured to acquire data characterizing a physiological state of the user **90** in some embodiments. For example, the sensor **120a** may be an electrode.

(139) With continued reference to FIG. 9D, the display **70** is operatively coupled by communications link **130**,

such as by a wired lead or wireless connectivity, to a local data processing module **140** which may be mounted in a variety of configurations, such as fixedly attached to the frame **80**, fixedly attached to a helmet or hat worn by the user, embedded in headphones, or otherwise removably attached to the user **90** (e.g., in a backpack-style configuration, in a belt-coupling style configuration). Similarly, the sensor **120a** may be operatively coupled by communications link **120b**, e.g., a wired lead or wireless connectivity, to the local processor and data module **140**. The local processing and data module **140** may comprise a hardware processor, as well as digital memory, such as non-volatile memory (e.g., flash memory or hard disk drives), both of which may be utilized to assist in the processing, caching, and storage of data. Optionally, the local processor and data module **140** may include one or more central processing units (CPUs), graphics processing units (GPUs), dedicated processing hardware, and so on. The data may include data a) captured from sensors (which may be, e.g., operatively coupled to the frame **80** or otherwise attached to the user **90**), such as image capture devices (such as cameras), microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, gyros, and/or other sensors disclosed herein; and/or b) acquired and/or processed using remote processing module **150** and/or remote data repository **160** (including data relating to virtual content), possibly for passage to the display **70** after such processing or retrieval. The local processing and data module **140** may be operatively coupled by communication links **170**, **180**, such as via a wired or wireless communication links, to the remote processing module **150** and remote data repository **160** such that these remote modules **150**, **160** are operatively coupled to each other and available as resources to the local processing and data module **140**. In some embodiments, the local processing and data module **140** may include one or more of the image capture devices, microphones, inertial measurement units, accelerometers, compasses, GPS units, radio devices, and/or gyros. In some other embodiments, one or more of these sensors may be attached to the frame **80**, or may be standalone structures that communicate with the local processing and data module **140** by wired or wireless communication pathways.

(140) With continued reference to FIG. **9D**, in some embodiments, the remote processing module **150** may comprise one or more processors configured to analyze and process data and/or image information, for instance including one or more central processing units (CPUs), graphics processing units (GPUs), dedicated processing hardware, and so on. In some embodiments, the remote data repository **160** may comprise a digital data storage facility, which may be available through the internet or other networking configuration in a “cloud” resource configuration. In some embodiments, the remote data repository **160** may include one or more remote servers, which provide information, e.g., information for generating augmented reality content, to the local processing and data module **140** and/or the remote processing module **150**. In some embodiments, all data is stored and all computations are performed in the local processing and data module, allowing fully autonomous use from a remote module. Optionally, an outside system (e.g., a system of one or more processors, one or more computers) that includes CPUs, GPUs, and so on, may perform at least a portion of processing (e.g., generating image information, processing data) and provide information to, and receive information from, modules **140**, **150**, **160**, for instance via wireless or wired connections.

(141) Liquid Crystal Materials for Broadband Adaptive Waveplate Lens Assemblies

(142) Generally, liquid crystals possess physical properties that may be intermediate between conventional fluids and solids. While liquid crystals are fluid-like in some aspects, unlike most fluids, the arrangement of molecules within liquid crystals exhibits some structural order. Different types of liquid crystals include thermotropic, lyotropic, and polymeric liquid crystals. Thermotropic liquid crystals disclosed herein can be implemented in various physical states, e.g., phases, including a nematic state/phase, a smectic state/phase, a chiral nematic state/phase or a chiral smectic state/phase.

(143) As described herein, liquid crystals in a nematic state or phase can have calamitic (rod-shaped) or discotic (disc-shaped) organic molecules that have relatively little positional order, while having a long-range directional order with their long axes being roughly parallel. Thus, the organic molecules may be free to flow with their center of mass positions being randomly distributed as in a liquid, while still maintaining their long-range directional order. In some implementations, liquid crystals in a nematic phase can be uniaxial; i.e., the liquid crystals have one axis that is longer and preferred, with the other two being roughly equivalent. In some implementations, the liquid crystal molecules orient their long axis. In other implementations, liquid crystals can be biaxial; i.e., in addition to orienting their long axis, the liquid crystals may also orient along a secondary axis.

(144) As described herein, liquid crystals in a smectic state or phase can have the organic molecules that form relatively well-defined layers that can slide over one another. In some implementations, liquid crystals in a smectic phase can be positionally ordered along one direction. In some implementations, the long axes of the molecules can be oriented along a direction substantially normal to the plane of the liquid crystal layer, while in other implementations, the long axes of the molecules may be tilted with respect to the direction normal to the plane of the layer.

(145) Herein and throughout the disclosure, nematic liquid crystals can be composed of rod-like molecules with

the long axes of neighboring molecules approximately aligned to one another. To describe this anisotropic structure, a dimensionless unit vector $\underline{n}$, called the director, may be used to describe the direction of preferred orientation of the liquid crystal molecules.

(146) Herein and throughout the disclosure, an azimuthal angle or a rotation angle ϕ is used to describe an angle of rotation of a liquid crystal molecule about a layer normal direction, or an axis normal to a major surface of a liquid crystal layer, which is measured in a plane parallel to a major surface of the liquid crystal layers or of the substrate, e.g., the x-y plane, and measured between an alignment direction, e.g., an elongation direction or the direction of the director, and a direction parallel to the major surface, e.g., the y-direction.

(147) Herein and throughout the disclosure, when an angle such as the rotation angle ϕ is referred to as being substantially the same or different between different regions, it will be understood that an average of the angles can, for example, be within about 1%, about 5% or about 10% of each other although the average angles can be larger in some cases.

(148) As describe herein, some liquid crystals in a nematic state or a smectic state can also exhibit a twist in a layer normal direction. Such liquid crystals are referred to as being twisted nematic (TN) liquid crystals or twisted smectic (SN) liquid crystals. TN or SN liquid crystals can exhibit a twisting of the molecules about an axis perpendicular to the director, with the molecular axis being parallel to the director. When the degree of twist is relatively large, twisted liquid crystals may be referred to as being in a chiral phase or a cholesteric phase.

(149) As described herein, TN or SN liquid crystals can be described as having a twist angle or a net twist angle (ϕ), which can refer to, for example, the relative azimuthal angular rotation between an uppermost liquid crystal molecule and a lowermost liquid crystal molecule across a specified length, e.g., the thickness of the liquid crystal layer.

(150) As described herein, “polymerizable liquid crystals” may refer to liquid crystal materials that can be polymerized, e.g., in-situ photopolymerized, and may also be described herein as reactive mesogens (RM).

(151) The liquid crystal molecules may be polymerizable in some embodiments and, once polymerized, may form a large network with other liquid crystal molecules. For example, the liquid crystal molecules may be linked by chemical bonds or linking chemical species to other liquid crystal molecules. Once joined together, the liquid crystal molecules may form liquid crystal domains having substantially the same orientations and locations as before being linked together. The term “liquid crystal molecule” may refer either or both to the liquid crystal molecules before polymerization or/and to the liquid crystal domains formed by these molecules after polymerization. Once polymerized, the polymerized network may be referred to as liquid crystal polymer (LCP).

(152) In some embodiments, unpolymerized liquid crystal molecules or polymerizable liquid crystal molecules prior to being polymerized may have at least limited rotational degree of freedom. These unpolymerized liquid crystal molecules can rotate or tilt, e.g., under an electrical stimulus, which results in alteration of the optical properties. For example, by applying an electric field, some liquid crystal layers including unpolymerized liquid crystal molecules may be switched between one or more states having different diffractive or polarization altering properties.

(153) The inventors have recognized that the above-described properties of liquid crystals or reactive mesogens (RMs) can be advantageously applied to various components of broadband switchable waveplates and waveplate lenses disclosed herein. For example, in some unpolymerized RMs, the orientations of LC molecules can be altered after deposition, e.g., by application of an external stimulus, e.g., electric field. Based on this recognition, the inventors disclose herein waveplates and waveplate lenses that can be switched between a plurality of states by application of an external stimulus.

(154) In addition, the inventors have recognized that, when unpolymerized, the orientations of LC molecules at surfaces or interfaces of some LCs or RMs can be aligned by controlling the surface or interface on which the LC molecules are formed. For example, a stack of multiple LC layers can be formed where, by controlling orientations of LC molecules closest to the surface of an LC layer, orientations of immediately adjacent LC molecules in the next LC layer can be controlled, e.g., to have the same orientation as the LC molecules closest to the surface in the previous LC layer or the same orientation as elongated microstructures in adjacent layers. In addition, LC molecules between the LC molecules at surfaces or interfaces can be controlled to have a predetermined amount of twist. Based on recognition of these and other attributes including birefringence, chirality, and ease for multiple-coating, the inventors disclose herein waveplates and waveplate lenses that have useful properties such as broadband capability with tailored optical properties, e.g., diffraction efficiency, optical power and polarizability, to name a few.

(155) Display Devices Having Switchable Broadband Adaptive Waveplate Lens Assemblies

(156) As described supra in reference to FIG. 6, some display systems according to embodiments include a waveguide assembly 260 configured to form images at a plurality of virtual depth planes. The waveguide assembly 260 includes waveguides 270, 280, 290, 300, 310 each configured to propagate light by total internal

reflection (TIR), and includes out-coupling optical elements **570, 580, 590, 600, 610** each configured to extract light out of a respective one of the waveguides **270, 280, 290, 300, 310** by redirecting the light. Each of the waveguide **270, 280, 290, 300, 310** is configured to output light to form an image corresponding to a particular depth plane. The waveguide assembly **260** may also optionally include a plurality of lenses **320, 330, 340, 350** between the waveguides for providing different optical powers for forming the images at different virtual depth planes.

(157) In the illustrated embodiment of the waveguide assembly **260** in FIG. **6**, the number of depth planes may be directly proportional to the number of waveguides and lenses. However, the inventors have recognized various challenges associated with implementing a waveguide assembly configured for displaying images at a plurality of depth planes by having a proportional number of waveguides and lenses. For example, a high number of waveguides **270, 280, 290, 300, 310** and a high number of corresponding lenses **320, 330, 340, 350** can undesirably increase the overall thickness, weight, cost, and manufacturing challenges to the waveguide assembly **260**. For example, when formed of a conventional lens material, e.g., glass, each of the lenses **320, 330, 340, 350** may add millimeters or tens of millimeters in thickness and corresponding weight to the displays. In addition, a high number of waveguides and lenses can produce undesirable optical effects to the user, e.g., relatively high absorption loss. Thus, in one aspect, the inventors have recognized a potential benefit in some cases for display systems that can generate images at a plurality of depth planes with fewer numbers of waveguides, fewer number of lenses, thinner and lighter waveguides and lenses and/or fewer numbers of lenses per waveguide.

(158) Still referring to FIG. **6**, it will be appreciated that the lenses **320, 330, 340, 350** may be configured to form images at different depth planes by exerting respective optical powers to light from the waveguides **310, 300, 290** and **280**. In various embodiments, the light outcoupled from the waveguides may have a polarization, e.g., a circular polarization. However, when polarized light outcoupled from a waveguide passes through a waveplate lens or a waveplate formed of liquid crystals, less than 100% of the outcoupled light transmitted therethrough may be optically affected, e.g., diffractively diverged, converged or altered in polarization, resulting in a portion of the outcoupled light passing through without being optically affected. The light passing through the lens without being optically affected in this manner is sometimes referred to as leakage light. The leakage light may be undesirably focused, defocused or altered in polarization in the downstream optical path, or not be affected at all. When a significant portion of the light passing through a waveplate or waveplate lens constitutes leakage light, a user may experience undesirable effects, such as, “ghost” images, which are unintended images or images that become visible to the user at unintended depth planes. The inventors have recognized that such leakage light may result from, among other causes, the waveplate lenses or waveplates formed of liquid crystals being configured to have a relatively high diffraction efficiency within a relatively narrow range of wavelengths in the visible spectrum. Thus, in another aspect, the inventors have recognized a need for a broadband adaptive waveplate lens assembly that can generate images at a plurality of depth planes with less undesirable effects arising from leakage light over a relatively wide range of wavelengths in the visible spectrum. To address these and other needs, various embodiments include broadband adaptive waveplate lens assemblies comprising switchable waveplate lenses or switchable waveplates based on liquid crystals, which are configured to provide variable optical power. The waveplate lenses and waveplates formed of liquid crystals can provide various advantages towards achieving these objectives, including small thickness, light weight and high degree of configurability at the molecular level. In various embodiments described herein, display devices are configured to form images at different virtual depth planes using a waveguide assembly configured to guide light in a lateral direction parallel to an output surface of a waveguide and to outcouple the guided light through the output surface to one or more broadband adaptive waveplate lens assemblies. In various embodiments, a broadband adaptive waveplate lens assembly is configured to incouple and to diffract therethrough the outcoupled light from the waveguide. The broadband adaptive lens assembly includes a first waveplate lens comprising a liquid crystal (LC) layer arranged such that the waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the first waveplate lens. The resulting waveplate lens can be configured to diffract the outcoupled light at a diffraction efficiency greater than 90%, greater than 95% or even greater than 99% within a broadband wavelength range including at least 450 nm to 630 nm. In some embodiments, the broadband adaptive waveplate lens assemblies according to embodiments are significantly lighter and thinner (microns) compared to conventional lenses, and can advantageously provide variable optical power over a broadband wavelength range. Advantageously, such broadband adaptive lens assemblies may reduce the number, thickness and weight of a waveguide assembly such as the waveguide assembly **260** (FIG. **6**), as well as reducing or eliminating undesirable effects arising from leakage light.

(159) As used herein, optical power (P , also referred to as refractive power, focusing power, or convergence power) refers to the degree to which a lens, mirror, or other optical system converges or diverges light. It is equal to the reciprocal of the focal length of the device: $P=1/f$. That is, high optical power corresponds to short focal

length. The SI unit for optical power is the inverse meter (m^{-1}), which is commonly called the diopter (D). (160) As described herein, converging lenses that focus light passing therethrough are described as having a positive optical power, while diverging lenses that defocus light passing therethrough are described as having a negative power. Without being bound by theory, when light passes through two or more thin lenses that are relatively close to each other, the optical power of the combined lenses may be approximated as a sum of the optical powers of the individual lenses. Thus, when light passes through a first lens having a first optical power P_1 and further passes through a second lens having a second optical power P_2 , the light may be understood to converge or diverge according to a sum of optical powers $P_{\text{net}}=P_1+P_2$.

(161) A medium having a refractive index that depends on the polarization and propagation direction of light is referred to be birefringent (or birefractive). As described throughout the specification and understood in the relevant industry, when light has a polarization that is perpendicular to the optic axis of a birefringent medium, the birefringent medium is described as having an ordinary refractive index ($n_{\text{sub.o}}$), when light has a polarization that is parallel to the optic axis of the birefringent medium, the birefringent medium is described as having an extraordinary refractive index ($n_{\text{sub.e}}$), and a difference of the refractive indices $n_{\text{sub.e}}-n_{\text{sub.o}}$ of the birefringent medium material is referred to as a birefringence Δn . The phase retardation of light in a material medium having birefringence Δn can be expressed as $\Gamma=2\pi\Delta n d/\lambda$ where λ is the wavelength of light and d is the thickness of the medium.

(162) Generally, optically anisotropic materials, e.g., liquid crystals, display a positive dispersion of birefringence (Δn) where the Δn decreases with increasing wavelength of light λ . The positive dispersion of Δn results in different phase retardation $\Gamma=2\pi\Delta n d/\lambda$ at different λ . As disclosed herein, an anisotropic material displaying a negative dispersion of birefringence (Δn) refers to a material in which the birefringence increases with increasing wavelength of light λ .

(163) As described above, the wavelength dependence of diffraction efficiency of a waveplate lens or a waveplate can be an important consideration in reducing or minimizing various undesirable optical effects. As described herein, diffraction efficiency (η) of a birefringent medium such as a layer of liquid crystals can be expressed as $\eta=\sin^2(\pi\Delta n d/\lambda)$, where Δn is birefringence, λ is wavelength and d is the thickness. Because phase retardation that light propagating through the diffractive components varies with the wavelength for conventional birefringent media, some diffractive components including waveplate lenses and waveplates display a relatively narrow range of wavelengths, or bandwidth, within the visible spectrum in which diffraction efficiency is sufficiently high. In contrast, waveplate lenses and waveplates according to embodiments display a relatively wide range of wavelengths, or bandwidth, within the visible spectrum in which diffraction efficiency is sufficiently high for various applications described herein.

(164) According to various embodiments, a broadband waveplate lens or a waveplate may be described as having a normalized bandwidth ($\Delta\lambda/\lambda_{\text{sub.0}}$), where $\lambda_{\text{sub.0}}$ is a center wavelength within the visible spectrum spanning a wavelength range of about 400-800 nm, including one or more of a red spectrum having a wavelength range of about 620-780 nm, a green spectrum having a wavelength range of about 492-577 nm and a blue spectrum having a wavelength range of about 435-493 nm, and $\Delta\lambda$ is a range of wavelengths centered about the $\lambda_{\text{sub.0}}$ within which a diffraction efficiency exceeds 70%, 80%, 90%, 95%, 99% or by any value within a range defined by these values.

(165) According to various embodiments, when a waveplate lens or a waveplate is described as being a broadband waveplate lens or a broadband waveplate, it will be understood as having an average, an instantaneous, a mean, a median or a minimum value of diffraction efficiency which exceeds 70%, 80%, 90%, 95%, 99% or a percentage within any of these values, within at least a portion of a visible spectrum spanning a wavelength range of about 400-800 nm, including one or more of a red spectrum which includes wavelengths in the range of about 620-780 nm, a green spectrum which includes wavelengths in the range of about 492-577 nm, and a blue spectrum in the range of about 435-493 nm, or within a range of wavelengths defined by any wavelength within the visible spectrum within about 400-800 nm, e.g., 400-700 nm, 430-650 nm or 450-630 nm.

(166) Based on the relationship $\eta=\sin^2(\pi\Delta n d/\lambda)$ described above for diffraction efficiency, a broadband waveplate lens or a waveplate can have an efficiency for a fixed d when the ratio of $\Delta n/\lambda$ has a positive and relatively constant value. As described herein, a medium having a positive ratio value of $\Delta n/\lambda$ is referred to as having a negative dispersion. According to embodiments, broadband waveplate lenses or broadband waveplates described herein have negative dispersion, or a birefringence (Δn) that increases with increasing wavelength (λ) within wavelength ranges described above.

(167) According to various embodiments, a broadband waveplate lens or a waveplate may be described as having an instantaneous, a mean, a median, a minimum or a maximum value of the ratio $\Delta n/\lambda$ that is a positive value within any range of the visible spectrum described above. In addition, a broadband waveplate lens or the waveplate has a relatively high ratio of $\Delta\lambda/\lambda_{\text{sub.0}}$ where $\Delta\lambda$ is a wavelength range within any range of the visible

spectrum described above and $\lambda_{sub.0}$ is a centroid wavelength within the $\Delta\lambda$. According to various embodiments, a high normalized bandwidth $\Delta\lambda/\lambda_{sub.0}$ can have a value of about 0.3-0.7, 0.4-0.7, 0.5-0.7, 0.6-0.7 or a value within any range defined by these values. In addition, the broadband waveplate lens or the waveplate has a ratio $\Delta n/\lambda$ that is relatively constant within various wavelength ranges within the visible spectrum described above. For example, the ratio $\Delta n/\lambda$ can have a deviation, e.g., a standard deviation, from a mean, a median, a minimum or a maximum value of the ratio $\Delta n/\lambda$ that does not exceed more than 30%, 20%, 10%, 5%, 1% or a percentage within any of these values.

(168) As described herein, a “transmissive” or “transparent” structure, e.g., a transparent substrate, may allow at least some, e.g., at least 20, 30, 50, 70 or 90%, of an incident light, to pass therethrough. Accordingly, a transparent substrate may be a glass, sapphire or a polymeric substrate in some embodiments. In contrast, a “reflective” structure, e.g., a reflective substrate, may reflect at least some, e.g., at least 20, 30, 50, 70, 90% or more of the incident light therefrom.

(169) FIG. 10 illustrates an example of a display device 1000, e.g., a wearable display device, comprising one or more broadband adaptive lens assemblies, e.g., a pair of broadband adaptive lens assemblies 1004, 1008 in an optical path 1016 that are interposed by a waveguide assembly 1012. As described supra, the waveguide assembly includes a waveguide configured to propagate light (e.g., visible light), e.g., under total internal reflection, and to outcouple the light in an optical axis extending from (e.g., in a direction normal to) a light output surface of the waveguide (e.g., a major surface of the waveguide). The light may be outcoupled by a diffraction grating in some embodiments. Each of the broadband adaptive lens assemblies 1004, 1008 may be configured to at least partially transmit outcoupled light therethrough. In the illustrated embodiments, each of the adaptive lens assemblies may be configured to receive outcoupled light from the waveguide assembly 1012 and to converge or diverge the outcoupled light in the optical axis direction. Each of the broadband adaptive lens assemblies 1004, 1008 comprises a waveplate lens comprising liquid crystals arranged such that the waveplate lens has birefringence (Δn) that varies in a radial direction from a central region of the waveplate lens and that increases or decreases with increasing wavelength (λ) within a range of the visible spectrum. The broadband adaptive lens assembly is configured to be selectively switched between a plurality of states having different optical powers. The broadband adaptive lens assembly is configured to alter a polarization state of the outcoupled light passing therethrough when activated (e.g., electrically activated).

(170) As described herein, an adaptive lens assembly refers to a lens assembly having at least one optical property that may be adjusted, e.g., reversibly activated and deactivated, using an external stimulus. Example optical properties that may be reversibly activated and deactivated include, among other properties, optical power (focal length), phase, polarization, polarization-selectivity, transmissivity, reflectivity, birefringence and diffraction properties, among other properties. In various embodiments, adaptive lens assemblies are capable of electrically varying the optical power and the polarization state of light passing therethrough.

(171) In the illustrated embodiment, each of the pair of broadband adaptive lens assemblies 1004, 1008 is configured to be selectively switched between at least two states. In a first state, each is configured to pass the outcoupled light therethrough without altering a polarization state thereof, while in a second state, each is configured to alter the polarization state of the outcoupled light passing therethrough. For example, in the second state, each of the broadband adaptive lens assemblies 1004, 1008 reverses the handedness of circularly polarized light, while in the first state, each of the broadband adaptive lens assemblies 1004, 1008 preserves the handedness of circularly polarized light.

(172) Still referring to FIG. 10, the display device 1000 further comprises a waveguide assembly 1012 interposed between the pair of adaptive lens assemblies 1004, 1008. The waveguide assembly 1012 may be similar to the waveguide assembly 260 described above with respect to FIG. 6, which comprises one or more waveguides, similar to one or more waveguides 270, 280, 290, 300, 310 in FIG. 6. As described supra, e.g., with respect to FIGS. 6 and 7, the waveguide may be configured to propagate light under total internal reflection in a lateral direction parallel to a major surface of the waveguide. The waveguide may further be configured to outcouple the light, e.g., in a direction normal to the major surface of the waveguide.

(173) Still referring to FIG. 10, a first adaptive lens assembly 1004 of the pair of adaptive lens assemblies is disposed on a first side of the waveguide assembly 1012, e.g., the side of the world 510 observed by a user, and a second adaptive lens assembly 1008 of the pair of lens assemblies is disposed on a second side of the waveguide assembly 1012, e.g., the side of the eye 210 of the user. As described infra, the pair of adaptive lens assemblies as configured provides to a user virtual content from the waveguide assembly 1012 at a plurality of virtual depth planes, as well the view of the real world. In some embodiments, there is little or no distortion due to the presence of the adaptive lens assemblies. The virtual content and the view of the real world are provided to the user upon activation of the first and second adaptive lens assemblies 1004, 1008, as described infra with respect to FIGS. 11A and 11B.

(174) FIGS. **11A** and **11B** illustrate examples of display devices **1100A/1100B**, each comprising adaptive lens assemblies in operation to output image information to a user. The display devices **1100A** and **1100B** in an unpowered state are structurally identical. The display device **1100A** is used herein to describe outputting virtual image to the user, while the display device **1100B** is used herein to describe transmitting a real world image through the display device **1100B** to the user. The display device **1100A/1100B** includes a pair of the switchable lenses assemblies **1004**, **1008** that are configured to be electrically activated by, e.g., application of a voltage or a current. In some embodiments, in a deactivated state, e.g., when no voltage or current is applied, each of the first and second switchable lenses assemblies **1004**, **1008** has a low, e.g., about zero, optical power. In some embodiments, in an activated state, e.g., when a voltage or a current is applied, the first adaptive lens assembly **1004** on the side of the world may provide a first net optical power (P_{net1}) having a first sign, e.g., a positive optical power. When in an activated state, the second adaptive lens assembly **1008** on the side of the user may provide a second net optical power (P_{net2}) having a second sign, e.g., a negative optical power.

(175) FIG. **11A** illustrates an example of the display system of FIG. **10** displaying virtual content to a user at a virtual depth plane, according to some embodiments. As described supra, the waveguide assembly **1012** interposed between the pair of the adaptive lens assemblies **1004**, **1008** comprises a waveguide configured to receive light containing virtual image information and to propagate the light under total internal reflection. The waveguide assembly **1012** is further configured to outcouple the light through, e.g., a diffraction grating, towards the eye **210**. The outcoupled light passes through the second adaptive lens assembly **1008** prior to entering the eye **210**. When activated, the second adaptive lens assembly **1008** has a second net optical power, P_{net2} , which may have a negative value, such that the user sees the virtual image at a virtual depth plane **1104**.

(176) In some embodiments, the second adaptive lens assembly **1008** may be adjusted electrically to adjust the second net optical power (P_{net2}) of the second adaptive lens assembly **1008**, thereby adjusting the distance to the virtual depth plane **1104**. For example, as a virtual object “moves” closer and further relative to the eye **210** within a virtual three dimensional space, the second net optical power P_{net2} of the second adaptive lens assembly **1008** may be correspondingly adjusted, such that the virtual depth plane one **1104** adjusts to track the virtual object. Thus, the user may experience relatively little or no accommodation/vergence mismatch beyond an acceptable threshold. In some embodiments, the magnitude of the distance to the virtual depth plane **1104** may be adjusted in discrete steps, while in some other embodiments, the magnitude of the distance to the virtual depth plane **1104** may be adjusted continuously.

(177) FIG. **11B** illustrates an example of the display system of FIG. **10** providing a view of real world content to a user, according to some embodiments. When the second adaptive lens assembly **1008** is activated to have the second net optical power (P_{net2}) to display the virtual content at the virtual depth plane **1104**, light from the real world passing through the second adaptive lens assembly **1008** may also be converged or diverged according to P_{net2} of the activated second adaptive lens assembly **1008**. Thus, objects in the real world may appear out of focus. To mitigate such distortion, according to embodiments, when activated, the first and second adaptive lens assemblies **1004**, **1008** may be configured to have optical powers having opposite signs. In some embodiments, light passing through the first and second adaptive lens assemblies **1004**, **1008** converges or diverges according to a combined optical power having a magnitude that is about a difference between magnitudes of first and second net optical powers P_{net1} , P_{net2} , of the first and second adaptive lens assemblies **1004**, **1008**, respectively. In some embodiments, the waveguide assembly **1012** may also have optical power and the adaptive lens assembly **1008** may be configured to account for the distortions caused by both the lens assembly **1004** and the waveguide assembly **1012**. For example, the optical power of the adaptive lens assembly **1008** may be opposite in sign to the sum of the optical powers of the lens assembly **1004** and the waveguide assembly **1012**.

(178) In some embodiments, the first adaptive lens assembly **1004** is configured to have the first net optical power P_{net1} that has a magnitude that is close to or the same as the magnitude of the second net optical power P_{net2} of the second adaptive lens assembly **1008**, while having a sign that is opposite of P_{net2} . As a result, when both the first and second adaptive lens assemblies **1004**, **1008** are activated simultaneously, objects in the real world appear relatively unaffected by the optical power of the second adaptive lens assembly **1008** provided for displaying the virtual content.

(179) In some embodiments, first adaptive lens assembly **1004** may be configured such that when activated, the first net optical power P_{net1} dynamically matches the second net optical power P_{net2} of the second adaptive lens assembly **1008**. For example, as the second net optical power P_{net1} of the second switchable assembly **1008** is adjusted to track moving virtual objects within the virtual three dimensional space, the first net optical power P_{net1} of the first adaptive lens assembly **1004** may be dynamically adjusted, such that the magnitude of the combined optical power $P = P_{net1} + P_{net2}$ may be kept less than a predetermined value. Thus, according to embodiments, the objects in the real world may be prevented from being unacceptably out of focus by compensating the second net optical power (P_{net2}) of the second adaptive lens assembly **1008**, which may have a

negative value, with the first net optical power (P_{net1}) of the first adaptive lens assembly **1004**, such that the combined optical power $P=P_{net1}+P_{net2}$ remains small, e.g., near about 0 m.sup.-1.

(180) Switchable Waveplate and Switchable Waveplate Lenses for Broadband Adaptive Waveplate Lens Assemblies

(181) As discussed above, the advantages of forming images at a plurality of depth planes with fewer waveguides includes the overall reduction in thickness and weight of the display device (e.g., display device **1000** in FIG. **10**). Thus, various embodiments described herein provide adaptive waveplate lens assemblies that are compact, lightweight and provide various optical functionalities, e.g., high bandwidth capability and variable optical power. In addition, various embodiments described herein provide adaptive lens assemblies with relatively low amount of leakage light.

(182) To provide images at a plurality of depth planes with high efficiency over a wide range of the visible spectrum, the broadband adaptive lens assembly according to various embodiments include a waveplate lens (**1154A**, **1154B** in FIGS. **12A**, **12B**, respectively) comprising liquid crystals arranged such that the waveplate lens has birefringence (Δn) that varies in a radial direction from a central region of the first waveplate lens and that increases or decreases with increasing wavelength (λ) within a range of the visible spectrum. As described above, according to various embodiments, the broadband adaptive waveplate lens assembly can generate images at multiple depth planes by being configured to be selectively switched between a plurality of states with different optical powers. The selective switching of the broadband lens assembly can in turn be performed by switching a waveplate lens or a waveplate included in the broadband adaptive waveplate lens assembly according to embodiments, as discussed herein.

(183) Referring to FIG. **12A**, in some embodiments, the broadband adaptive lens assembly **1150A** is configured to be switched between different optical power states by employing a switchable waveplate **1158** comprising liquid crystals in the same optical path as the waveplate lens **1154A**. The waveplate lens **1154A** may be a passive lens and the broadband adaptive lens assembly **1150A** may be selectively switched between different states by electrically activating and deactivating the switchable waveplate **1158**.

(184) Still referring to FIG. **12A**, in operation, the waveplate lens **1154A** is configured such that it diverges or converges incident light **1162A**, **1162B** passing therethrough depending on the polarization of the light, e.g., circular polarization, according to various embodiments. When configured as a half-waveplate (HWP) lens, the illustrated waveplate lens **1154A**, which may be a passive waveplate lens, is configured to converge a right-hand circular polarized (RHCP) light beam **1162B** incident on the waveplate lens **1154A** into a left-hand circular polarized (LHCP) light beam **1166A**. On the other hand, the waveplate lens **1154A** is configured to diverge a LHCP light beam **1162A** incident on the waveplate lens **1154A** into a right-hand circular polarized (RHCP) light beam **1166B**.

(185) Still referring to FIG. **12A**, after being focused or defocused by the waveplate lens **1154A** depending on the circular polarization of the light incident thereon, the LHCP light beam **1166A** or the RHCP light beam **1166B** is incident on a switchable waveplate **1158**. The liquid crystals of the switchable waveplate **1158** are configured such that, when activated, e.g., electrically activated, the polarization of a circularly polarized light passing therethrough is preserved (not illustrated). That is, the LHCP light beam **1166A** and the RHCP light beam **1166B** passes through the switchable waveplate **1158** unaffected. On the other hand, when deactivated, e.g., electrically activated, the polarization of the circularly polarized light passing therethrough is altered or flipped (illustrated). That is, the LHCP light beam **1166A** is converted to a RHCP light beam **1170A** and the RHCP light beam **1166B** is converted to a LHCP light beam **1170B**.

(186) Referring to FIG. **12B**, in some other embodiments, the broadband adaptive lens assembly **1150B** is configured to be switched between different optical power states by employing a switchable waveplate lens **1154B** comprising liquid crystals. The adaptive lens assembly **1150B** may be selectively switched between different states by electrically activating and deactivating the switchable waveplate lens **1154B**.

(187) In operation, the liquid crystals of the waveplate lens **1154B** are configured such that the waveplate lens **1154B** diverges or converges the incident light **1162A**, **1162B** passing therethrough depending on its polarization, e.g., circular polarization, according to various embodiments. When configured as a half-waveplate lens, when deactivated, e.g., electrically deactivated, the illustrated waveplate lens **1154B** is configured to converge a RHCP light beam **1162B** incident on the waveplate lens **1160B** into a LHCP light beam **1166A**. Conversely, when deactivated, the waveplate lens **1154B** is configured to diverge a left-hand polarized (LHCP) light beam **1162A** incident on the waveplate lens **1154B** into a RHCP beam **1166B**. On the other hand, when activated, e.g., electrically deactivated, the polarization of the circularly polarized light passing therethrough is preserved or unaffected (not illustrated), and the LHCP light beam **1162A** and the RHCP light beam **1162B** incident thereon pass through the waveplate lens **1154B** without substantially being converged or diverged and without having their polarization state affected. In various embodiments, by configuring the liquid crystals to be rearranged in

response to a switching signal, e.g., electric field, the waveplate lens assemblies **1150A**, **1150B** may be activated or deactivated to converge or diverge and to flip or conserve the polarization of circularly polarized light depending on its polarization.

(188) Broadband Switchable Waveplates

(189) As described above, according to various embodiments, the broadband adaptive waveplate lens assembly can be used to generate images at multiple depth planes by selectively switching the broadband waveplate lens assembly between a plurality of lens states having different optical powers. As described above, in some embodiments, the broadband adaptive waveplate lens assembly may be configured to be selectively switched between a plurality of lens states by electrically activating a broadband switchable waveplate included in the broadband adaptive waveplate lens assembly. In the following, embodiments of such broadband switchable waveplates are disclosed.

(190) In some embodiments, a broadband switchable waveplate comprises a layer of unpolymerized twisted nematic (TN) liquid crystals (LCs) and is configured to be switched upon application of an electric field across a thickness of the layer of TN LCs. Without being bound to any theory, the switching may be achieved upon altering orientations of the unpolymerized LC molecules across the thickness of the layer of TN LCs.

(191) Referring to FIGS. **13A-13F**, according to various embodiments, broadband switchable waveplates comprise a layer of twisted nematic (TN) liquid crystals (LCs). FIG. **13A** illustrates a cross-sectional view of an example of a switchable waveplate comprising a layer of TN LCs. A TN LC switchable waveplate **1300A** comprises a layer **1302** of TN LCs disposed between a pair of transparent substrates **1312**. Each of the transparent substrates **1312** has formed on the inner surface a conducting transparent electrode **1316**, **1320**.

(192) The surfaces of the transparent electrodes **1316**, **1320** and/or the substrates **1312** may be configured such that the TN LC molecules in contact with or immediately adjacent to the upper electrode **1316** tend to orient with their long axes extending in a first lateral direction, while the TN LC molecules in contact with or immediately adjacent to the lower electrode **1320** tend to orient with their long axes extending in a second lateral direction, which may cross, e.g., to form an angle of about 90 degrees relative to, the first lateral direction. The TN LC molecules between the TN LC molecules immediately adjacent to the lower electrode **1320** and the TN LC molecules immediately adjacent to the upper electrode **1316** undergo a twist. The illustrated TN LC switchable waveplate **1300A** is configured as a broadband waveplate.

(193) Still referring to FIG. **13A**, in operation, in the absence of an electric field (deactivated state) across the TN LC layer **1302**, the nematic director of the TN LC molecules undergoes a smooth 90 degree twist across the thickness of the TN LC layer **1302**. In this state, the incident light **1308** polarized in a first direction (same direction as the LC molecules closest to the lower electrodes **1312**, indicated by double-headed arrows) is incident on the TN LC layer **1302**. The twisted arrangement of the TN LC molecules within the TN LC layer **1302** serves as an optical wave guide and rotates the plane of polarization by a quarter turn (90 degrees) prior to reaching the upper electrodes **1316**. In this state, the TN LC layer **1302** serves to shift the polarization direction of linearly polarized light passing therethrough from one linear polarization direction to another. Thus, the transmitted light **1304A** is polarized in a second direction (same direction as the LC molecules closest to the upper electrodes **1316**) opposite the first direction.

(194) On the other hand, when a voltage exceeding a threshold voltage ($V > V_{th}$) of the TN LC switchable waveplate **1300A** is applied to across the electrodes **1316**, **1320** (activated state), the TN LC molecules within the TN LC layer **1306** tend to align with the resulting electric field and the optical wave guiding property of the TN LC layer **1304** described above with respect to the deactivated state is lost. In this state, the TN LC layer **1306** serves to preserve the polarization direction of light passing therethrough. Thus, the incident light **1308** and the transmitted light **1304B** are polarized in the same first direction (same direction as the LC molecules closest to the lower electrodes **1312**).

(195) Still referring to the activated state, when the voltage or the electric field is turned off, the TN LC molecules relax back to their twisted state and the TN LC molecules of the TN LC layer **1306** in the activated state returns to the configuration of TN LC molecules of the TN LC layer **1302** in the deactivated state.

(196) As described above, the TN LC switchable waveplate **1300A** described above with respect to FIG. **13A** serves to shift the polarization direction of linearly polarized light. However, various broadband waveplate lens assemblies described herein includes a switchable waveplate configured as a switchable half waveplate for reversing handedness of circular polarized light. Thus, in the following with respect to FIGS. **13B-13D**, switchable waveplates configured as switchable half waveplates are described, according to embodiments.

(197) FIG. **13B** illustrates a cross-sectional view of a switchable broadband waveplate **1300B** configured as a half wave plate, according to embodiments. The switchable broadband waveplate **1300B** includes the TN LC switchable waveplate **1300A** illustrated with respect to FIG. **13A**. In addition, in order to serve as a broadband half waveplate for circular polarized light, the switchable broadband waveplate **1300B** additionally includes a pair

of achromatic quarter waveplates (QWP) **1324**, **1326**.

(198) In operation, in an activated state (upper portion of FIG. **13B**) of the switchable broadband waveplate **1300B**, when an incident circularly polarized light beam **1324** having a first handedness, e.g., a left-hand circular polarized (LHCP) light beam, passes through the first QWP **1324**, the first QWP **1324** converts the circularly polarized light beam **1324** into a first linearly polarized light beam **1328** having a first linear polarization. Subsequently, upon passing through an activated TN LC switchable waveplate **1300A**, the first linearly polarized light beam **1328** is converted into a second linearly polarized light beam **1332** having a second linear polarization. Subsequently, upon passing through the second QWP **1326**, the second linearly polarized light beam **1332** is transformed into an exiting circularly polarized light beam **1340** having a second handedness opposite the first handedness, e.g., into a RHCP light beam. Thus, when activated, the switchable broadband waveplate **1300B** serves as a half waveplate that reverses the polarization of a circular polarized light beam.

(199) On the other hand, when the switchable broadband waveplate **1300B** is deactivated (lower portion of FIG. **13B**), after the incident circularly polarized light beam **1324** passes through the first QWP **1324** as described above and subsequently passes through a deactivated TN LC switchable waveplate **1300A**, the polarization of the first linearly polarized light beam **1328** is preserved. Thereafter, upon passing through the second QWP **1326**, first linearly polarized light beam **1328** is transformed into an exiting circularly polarized light beam **1340** having the first handedness, e.g., into a LHCP light beam. Thus, when deactivated, the broadband waveplate **1300B** serves as transparent medium which preserves the polarization of a circular polarized light beam.

(200) In various embodiments described herein, the first and/or second QWP **1324**, **1326** are broadband quarter waveplates having similar bandwidths compared to the TN LC switchable waveplate **1300A**. According to embodiments, quarter waveplates **1324**, **1326** can be formed using a polymerized TN LC layer. To provide broadband capability, QWPs according to various embodiments include a plurality of TN LC layers. When each of the TN LC layers are formed on its own substrate, the resulting broadband quarter waveplate and/or the optical absorption of the resulting stack may become unacceptably thick. Thus, in the following, embodiments of QWPs comprising a plurality of TN LC layers formed on a single substrate are described, for efficient integration with the TN LC switchable waveplate **1300A**.

(201) FIG. **13C** illustrates a cross-sectional view of a broadband QWP **1300C**, which can be the first and/or second QWP **1324**, **1326** illustrated above with respect to FIG. **13B**, comprising a plurality (M number) of TN LC layers **1302-1**, **1302-2**, . . . **1302-M**, stacked on an alignment layer **1302-0** formed on a substrate **1312**. The alignment layer **1302-0**, which is further described elsewhere in the specification, is configured to induce the elongation direction of the LC molecules in the first TN LC layer **1302-1** that are immediately adjacent to the alignment layer **1302-0** to be aligned in a first direction. The LC molecules above the LC molecules aligned by the alignment layer **1302-0** successively undergo a first twist, such that the LC molecules in the first TN LC layer **1302-1** that are farthest from the alignment layer **1302-0**, which are directly adjacent to the second TN LC layer **1302-2**, are elongated in a second direction. The alignment of LC molecules in each of the subsequent TN LC layers **1302-2** to **1302-M** are aligned in a similar manner as the first TN LC layer **1302-1** except, the LC molecules closest to the previous layer is aligned in the same direction as the topmost LC molecules of the previous layer. For example, the topmost LC molecules in the first TN LC layer **1302-1** and the bottommost LC molecules in the second TN LC layer **1302-2** are aligned in the same second direction. The LC molecules in the second TN LC layer **1302-2** undergo a second twist, such that the topmost LC molecules in the second TN LC layer **1302-2** are elongated in a third direction. Such alignment of LC molecules in a given TN LC layer as a result of the alignment of LC molecules in an adjacent layer in contact therewith is sometimes referred to as self-alignment, because no intervening alignment layer is interposed therebetween. Thus, in some embodiments, broadband QWPs comprise a plurality of TN LC layers having two or more self-aligned TN LC layers each having a non-zero twist.

(202) In embodiments, the TN LC layers comprise polymerized LC molecules (LCPs), formed using, e.g., reactive mesogens. As described above, reactive mesogens are initially low molecular weight LCs which may be aligned by surfaces and a twist to have complex profiles, as with conventional LCs, but which may then be cured into a solid polymer film by, e.g., photo-polymerization.

(203) FIG. **13D** illustrates a cross-sectional view of an integrated switchable broadband waveplate **1300D** in which a TN LC switchable waveplate **1300A** similar to that described above with respect to FIG. **13A** is integrated into a single stack with a pair of broadband QWP **1324**, **1326** similar to that described above with respect to FIG. **13C**. In the illustrated embodiment, the TN LC switchable waveplate **1300A** is integrated into a single stack by having attached on opposing sides thereof the pair of broadband quarter waveplates **1324**, **1326** using adhesive layers **1348**.

(204) FIG. **13E** illustrates a cross-sectional view of an integrated switchable broadband waveplate **1300E** in which a TN LC switchable waveplate **1300A** similar to that described above with respect to FIG. **13A** is

integrated into a single stack with a pair of broadband quarter waveplates **1324**, **1326** in a similar manner as described above with respect to FIG. **13D**, except, instead of using adhesive to form an integrated stack, one of the pair of broadband quarter waveplates **1324**, **1326** serves as a substrate on which a TN LC switchable waveplate **1300A** (FIG. **13A**) may be directly formed. For example, on a surface of one or both of the QWP **1324**, **1326**, different layers of the TN LC switchable waveplate **1300A** may be directly formed. Advantageously, one or both of the substrates **1312** of the TN LC switchable waveplate **1300A** may be omitted. Thus, the TN LC switchable waveplate **1300A** is integrated into a compact single stack by being directly formed on one of the pair of broadband QWP **1324**, **1326**, and forming thereon the other one of the pair of broadband QWP **1324**, **1326**.

(205) In each of the embodiments illustrated above with respect to FIGS. **13D** and **13E**, the broadband QWP can be formed of liquid crystal-based materials or other non-liquid crystal-based materials such as, e.g., quartz and MgF₂. In the following, with respect to FIG. **13F**, an embodiment in which broadband QWP comprising liquid crystals is particularly advantageously integrated with a TN LC switchable waveplate into a single stack to serve not only as QWP but also as alignment layers for the TN LC switchable waveplate.

(206) FIG. **13F** illustrates a cross-sectional view of an integrated switchable broadband waveplate **1300F** integrating a TN LC switchable waveplate similar to that described above with respect to FIG. **13A**. The switchable broadband waveplate **1300F** includes a pair of broadband QWP **1324**, **1326** arranged in a similar manner as described above with respect to FIG. **13E**, except, instead of the broadband QWP **1324**, **1326** as substrates for the TN LC layer **1302**, broadband QWP **1324**, **1326** comprises thin polymerized LC layers formed on respective surfaces of substrates **1312**. The LC molecules of the TN LC layer **1302** are inserted into a gap formed between opposing surfaces of broadband QWP **1324**, **1326** by spacers **1350**, which defines the thickness of the TN LC layer **1302**. The method of inserting the LC molecules is further described elsewhere in the specification. In addition, different layers of the TN LC switchable waveplate **1300A** and different layers of the broadband QWP **1324**, **1326** are integrally formed into a single stack. For example, the first broadband QWP **1324** includes a substrate **1312** on which a lower transparent electrode **1316** is formed, followed by an alignment layer **1302-0** and a plurality of TN LC layers **1302-1**, **1302-2**. Similarly, the second broadband QWP **1326** includes a substrate **1312**, on which an upper transparent electrode **1320** is formed, followed by an alignment layer **1302-0** and a plurality of TN LC layers **1302-1**, **1302-2**.

(207) Still referring to FIG. **13F**, advantageously, the outermost LC molecules of the TN LC layer **1302-2** of the first broadband QWP **1324** facing the gap and the outermost LC molecules of the TN LC layer **1302-2** of the second broadband QWP **1326** facing the gap are arranged to serve as alignment layers for the switchable TN LC layer **1302**, such that the outermost LC molecules of the TN LC layer **1302** are self-aligned, in a similar manner as described above with respect to FIG. **13C**. In addition, by integrally stacking different layers the TN LC switchable waveplate **1300A** with different layers of the broadband QWP **1324**, **1326**, the total thickness of the entire stack can be substantially reduced. For instance, while mechanically bonding TN LC switchable waveplate **1300A** as illustrated in FIG. **13A** with the broadband quarter waveplates **1324**, **1326** as illustrated in FIG. **13C** would have resulted in as many as four substrates, the entire stack of the switchable broadband waveplate **1300F** has only two substrates.

(208) In references to FIG. **13F** and various embodiments throughout the specification, a switchable LC layer, e.g., the TN LC layer **1302** inserted into the gap has a thickness of about 1 μm -50 μm , 1-10 μm , 10-20 μm , 20-30 μm , 30-40 μm , 40-50 μm or a value within any range defined by these values. In addition, passive LC layers, e.g., the TN LC layers **1302-1**, **1302-2**, can have a thickness of about 0.1 μm -50 μm , 0.1-1 μm , 1-10 μm , 10-20 μm , 20-30 μm , 30-40 μm , 40-50 μm or a value within any range defined by these values.

(209) In various embodiments described herein, an alignment layer (e.g., **1302-0** in FIGS. **13C**, **13F**) is used to align LC molecules, e.g., align the elongation direction of LC molecules, along a particular direction. For example, as described above with respect to FIGS. **13A-13F**, an alignment layer can be used to define a director (n), or a local average elongation direction of elongated LC molecules, in a predetermined direction. In some other embodiments, an alignment layer may be formed of organic polymers such as polyimides and polyamides that are mechanically rubbed, obliquely deposited inorganic oxides such as SiO₂, or long chain aliphatic siloxanes. In some embodiments, a noncontact alignment layer may be formed of organic polymers using plane-polarized light to generate a surface anisotropy, which in turn defines the director. For example, use of cis-trans photoisomerization of azo dye, which may be deposited directly or dissolved into a standard orientation layer (e.g., polyimide) or the LC mixture, can produce an orientation effect in the alignment layer without rubbing. Noncontact alignment layers that use azo chromophores sometimes employ an intense laser light to induce the isomerization of the dye molecules.

(210) In some other embodiments, a pattern of nanostructures can serve as an alignment layer for aligning the LC molecules. Advantageously, in some embodiments, the pattern of nanostructures can be formed as part of an electrode layer to improve optical transmittance, to reduce process steps, and/or to further reduce the overall

thickness of the broadband waveplates described above, e.g., with respect to FIGS. 13A-13F. To achieve this end, FIG. 14A illustrates a perspective view of a pattern of nanostructures **1400A**, e.g., nanowires formed on a transparent substrate **1312**, that serve a dual function of an alignment layer as well as an electrode layer, according to embodiments. The pattern of nanostructures **1400A** can be patterned on the substrate **1312** using, e.g., a lithographic or a nanoimprinting technique, described in detail elsewhere in the specification. The nanostructures can be formed of a sufficiently thin conducting material that is patterned as elongated metal wires. For example, the conducting material can be gold, silver, copper, aluminum or ITO or any suitable conducting material having a thickness and electrical resistivity such that the resulting pattern of nanostructures can serve simultaneously as an alignment layer and as an electrode layer. In the illustrated embodiment, the pattern of nanostructures **1400A** comprises periodic conducting lines **1404A** extending in a first direction, e.g., x-direction, that are connected to a rail **1408A** for supplying current or voltage to the periodic conducting lines **1404A**. In various embodiments, the periodic conducting lines **1404A** can have a pitch of 1 μm to 1000 μm , 5 μm to 500 μm , 10 μm to 100 μm , or any value within a range defined by these values. The conducting lines **1404** can have a width of 10 nm to 1 μm , 100 nm to 1000 nm, 100 nm to 500 nm, 200 nm to 300 nm, or any value within a range defined by these values. The periodic conducting lines **1404** can have a thickness of 10 nm to 1 μm , 100 nm to 1000 nm, 100 nm to 500 nm, 400 nm to 500 nm, or any value within a range defined by these values. A combination of the material, the thickness and the width of the periodic conducting lines **1404A** can be selected such that a resulting sheet resistance of the periodic conducting lines **1404A** is about 1 Ohms/square to 100 Ohms/square, 2 Ohms/square to 50 Ohms/square, 5 Ohms/square to 20 Ohms/square, or any value within a range defined by these values, for instance about 10 Ohms/square. In addition, a combination of the material and thickness of the conducting lines **1404A** can be selected such that the resulting transmittance in the visible spectrum is 80% to 99%, 90% to 99%, 95% to 99%, 97% to 99%, or any value within a range defined by these values, for instance about 98%. Other dimensions, configurations and values are possible.

(211) FIG. 14B illustrates a perspective view of a pattern of nanostructures **1400B** that is similar to the pattern of nanostructures **1400A** described above with respect to FIG. 14A, except, the pattern of nanostructures **1400B** comprises periodic conducting lines **1404B** extending in a second direction, e.g., the x-direction, that are connected to a rail **1408B** for supplying current to the periodic conducting lines **1404B**.

(212) FIG. 14C illustrates a perspective view of a pair of electrodes **1400C**, according to embodiments. The pair of electrodes **1400C** includes the pattern of nanostructures **1400A** (FIG. 14A) and the pattern of nanostructures **1400B** (FIG. 14B) that are arranged such that the periodic conducting lines **1404A** and the periodic conducting lines **1404B** face and cross each other, and are separated by a gap **1412** configured to dispose one or more LC layers, e.g., TN LC layers, therein. Advantageously, it has been found that each of the patterns of nanostructures **1400A** and **1400B** can serve as an alignment layer similar to the alignment layer **1302-0** described above with respect to FIGS. 13C, 13F such that when nematic LC molecules, e.g., reactive mesogens, are formed thereon, the LC molecules that are immediately adjacent to each of the patterns of nanostructures **1400A** and **1400B** may become aligned, e.g., with the director of the nematic LC molecules generally being aligned in the same direction as the elongation direction of the periodic conducting lines **1404A**, **1404B**. In addition, the LC molecules between the LC molecules immediately adjacent to the periodic conducting lines **1404A**, **1404B** can be configured to undergo a twist using a twisting agent such that an unpolymerized TN LC layers similar to the TN LC layer **1302** described above with respect to FIG. 13A and polymerized TN LC layer(s) similar to the TN LC layers **1302-1**, **1302-2**, . . . **1302-M** described above with respect to FIG. 13C may be formed.

(213) Referring back to FIG. 13F, it will be appreciated that, in some embodiments, by combining the functionality of an electrode and an alignment layer, the pattern of nanostructures **1400A** can replace the combination of the transparent electrode **1316** and the alignment layer **1302-0** of the broadband QWP **1324**, and the pattern of nanostructures **1400B** can replace the combination of the transparent electrode **1320** and the alignment layer **1302-0** of the broadband QWP **1326**, thereby allowing a more compact overall stack.

(214) Still referring to FIG. 14C, in operation, the arrangement of LC molecules with and without an electric field and the corresponding effect on the polarization of light is similar to that described above with respect to FIG. 13A.

(215) FIGS. 15A and 15B illustrate a plan view and a cross-sectional view, respectively, of a TN LC switchable broadband waveplate **1500**, according to embodiments. Unlike the broadband waveplates illustrated above with respect to FIGS. 13A and 13F having vertically separated electrodes for switching, the TN LC switchable broadband waveplate includes an in-plane laterally separated electrodes for switching. The TN LC switchable broadband waveplate **1500** includes an alignment electrode stack **1524** and an alignment layer stack **1526**. In a similar manner as described above with respect to FIG. 13F, LC molecules are inserted into a gap formed by spacers **1350** between opposing surfaces of the alignment electrode stack **1524** and the alignment layer stack **1526**. The method of inserting the LC molecules is described elsewhere in the specification. The alignment

electrode stack **1524** includes first and second electrodes **1500A**, **1500B** formed on an upper transparent substrate **1312**, and further includes an optional upper alignment layer **1302-0**. The alignment layer stack **1526** includes a lower alignment layer **1302-0** formed on a lower transparent substrate **1312**.

(216) Referring to FIG. **15A**, the alignment electrode stack **1524** includes the first and second electrodes **1500A**, **1500B** each including a respective one of first and second periodic conducting lines **1504A**, **1504B**. The periodic conducting lines **1504A** are interdigitated or interlaced and alternating with the periodic conducting lines **1504B**. Each of the first and second periodic conducting lines **1504A**, **1504B** are strapped to rails **1508A**, **1508B**, respectively, in a similar manner as described above with respect to the patterned nanostructures **1400A** (FIG. **14A**), **1400B** (FIG. **14B**). The material, thicknesses, widths and the pitch of the alternating periodic conducting lines **1504A**, **1504B** can be similar to those described above with respect to the patterned nanostructures **1400A** (FIG. **14A**), **1400B** (FIG. **14B**). However, unlike the pair of electrodes **1400C** described above with respect to FIG. **14C** that are vertically separated, the periodic conducting lines **1504A** are alternating with the periodic conducting lines **1504B** in a lateral direction, e.g., y-direction, such that the electric field between the periodic conducting lines **1504A** and the periodic conducting lines **1504B** is directed in the lateral direction.

(217) Referring to the cross-sectional view of the TN LC switchable cell **1500** in FIG. **15B**, in a similar manner as described above with respect to FIG. **13F**, LC molecules are inserted into the gap formed between opposing surfaces of the alignment electrode stack **1524** and the alignment layer stack **1526**, such that a TN LC layer (not shown) similar to the TN LC layer **1302** (FIG. **13A**) can be formed. The method of inserting the LC molecules is described elsewhere in the specification.

(218) In some embodiments, in a similar manner as described above with respect to FIG. **14C**, the alternating periodic conducting lines **1504A**, **1504B** and/or the upper alignment layer **1302-0** in the alignment electrode stack **1524** can serve as alignment layers for outermost LC molecules of a TN LC layer **1302** formed in the gap **1412**, in a similar manner as the alignment layer **1316** described above with respect FIG. **13A** and to the conducting lines **1404B** described above with respect FIG. **14C**. When the alternating periodic conducting lines **1504A**, **1504B** serve as an alignment layer, in some embodiments, the upper alignment layer **1302-0** may be omitted. In a similar manner to the alignment layer **1320** described above with respect FIG. **13A** and to the conducting lines **1404A** described above with respect FIG. **14C**, the lower alignment layer **1302-0** may serve to align LC molecules in the gap **1412** that are immediately adjacent thereto.

(219) While not illustrated, in some embodiments, the illustrated TN LC switchable broadband waveplate **1500** can integrate, in a similar manner as described above with respect to FIG. **1300F**, a plurality of TN LC layers similar to the TN LC layers **1302-1**, **1302-2**, . . . **1302-M** (FIG. **13F**, not shown) between the alternating periodic conducting lines **1504A**, **1504B** and the LC molecules in the gap **1412**, and/or between the lower alignment layer **1302-0** and the LC molecules in the gap **1412**, thereby providing an integrated QWP functionality in a similar manner as described above with respect to FIG. **13F**.

(220) Still referring to FIGS. **15A**, **15B**, in operation, in the absence of an electric field, the alternating periodic conducting lines **1504A**, **1504B** serve as an alignment layer for the LC molecules immediately adjacent to the periodic conducting lines **1504A**, **1504B**, such that the LC molecules have a director generally extending parallel to the periodic conducting lines **1504A**, **1504B**. In the deactivated state, in a similar manner as described above with respect to FIG. **13A**, the switchable broadband waveplate **1500** is configured to flip the polarization of linearly polarized light. On the other hand, when an electric field is applied in a lateral direction, e.g., y-direction, between the periodic conducting lines **1504A** and the periodic conducting lines **1504B**, the LC molecules between immediately adjacent periodic conducting lines **1504A**, **1504B** align with their elongation direction in a direction away from parallel, e.g., between parallel and perpendicular or perpendicular, to the periodic conducting lines **1504A**, **1504B**. In the activated state, in a similar manner as described above with respect to FIG. **13A**, the switchable broadband waveplate **1500** is configured to preserve the polarization of linearly polarized light.

(221) In some embodiments, in addition to combining the functionality of electrodes and an alignment layer, the first and second electrodes **1500A**, **1500B** can, e.g., replace the combination of the transparent electrodes **1316**, **1320** and the upper and lower alignment layers **1302-0** of the broadband waveplate **1300F** (FIG. **13F**), thereby allowing a further more compact overall stack, and even more improved transmittance due to halving of electrode layers.

(222) Liquid Crystal-Based Waveplate Lenses

(223) As described above with respect to FIG. **12A**, to provide images at a plurality of depth planes with high efficiency over a wide range of the visible spectrum, some broadband adaptive waveplate lens assemblies according to embodiments include a switchable waveplate and one or more waveplate lenses, which may be passive or switchable, that are formed of a thin film of birefringent liquid crystals. In the following, example waveplate lenses comprising liquid crystals whose orientations in the plane of the waveplate are adapted for focusing and/or altering the polarization state of light transmitted therethrough are disclosed. In the following,

various embodiments of lenses and waveplates formed of liquid crystals.

(224) One example of liquid crystal-based waveplate lenses is illustrated with respect to FIGS. **16A** and **16B**.

(225) FIGS. **16A** and **16B** illustrate examples of waveplate lenses **1200A** and **1200B**, respectively, each comprising a transparent substrate **1204**, e.g., a glass substrate, having formed thereon liquid crystal molecules **1208** elongated along different elongation directions relative to a direction parallel to an axial direction (e.g., x-direction or y-direction) along a major surface of the substrate **1204**. That is, the liquid crystal molecules **1208** are rotated about a direction (e.g., z-direction) normal to a major surface of the substrate **1204** by different angles (ϕ) of rotation, where ϕ is described as the angle between the direction of elongation of the liquid crystal molecules relative to a direction parallel to the layer normal (e.g., x-direction or y-direction).

(226) In the illustrated implementations, the liquid crystal molecules **1208** at a given radius from a central axis C or the center of the lens have substantially the same angle (q) of rotation. As arranged, the liquid crystal molecules **1208** are configured to focus a collimated beam of light to a point at a focal length. Without being bound to any theory, the angle (ϕ) of rotation of liquid crystal molecules **1208** may be proportional to a power of r , where r is the radial distance from C and has a value between about 1 and 3, e.g., 2. In one implementation, the angle (ϕ) may be proportional to $\pm k \cdot r$, where r is the radial distance from C and $k = 2\pi/\lambda$ is the wavenumber of the light that is to be focused by the diffractive waveplate lens, λ is the wavelength of the light, f is the focal length of the waveplate lenses **1200A**, **1200B**. The + and - sign can correspond to the direction of rotation of the liquid crystal molecules **1208** relative to the liquid crystal molecules **1208** nearest to the center C of the waveplate lenses **1200A**, **1200B**.

(227) It will be appreciated that the patterns of liquid crystal molecules **1208** of waveplate lenses **1200A** and **1200B** represent flipped images of each other. That is, one of the waveplate lenses **1200A** and **1200B** may be obtained by rotating the other of the waveplate lenses **1200B** and **1200B** around an axial direction (e.g., x-direction or y-direction) by 180 degrees. As configured, focal lengths and optical powers of the waveplate lenses **1200A** and **1200B** are the same in magnitude but opposite in sign.

(228) In some implementations, each of waveplate lenses **1200A** and **1200B** may serve as half waveplate lenses. When configured as a half-waveplate lens, each of the waveplate lenses **1200A** and **1200B** rotates the plane of a linearly polarized light by an angle 2α with respect to the polarization of an input beam, where α is the angle between the input polarization direction and the waveplate axis. For a circular polarized beam, this change in angle translates into a phase shift and reversal of the polarization handedness. Thus, a $\pm 2\alpha$ phase shift may be generated in a circularly polarized beam with the sign of the phase shift depending on the polarization handedness.

(229) FIG. **16C** illustrates examples of a waveplate lens that diverges or converges light passing therethrough depending on the polarization of light and the side on which the light is incident, according to some embodiments. When configured as a half-waveplate lens, the illustrated waveplate lens **1200A** may be configured to diverge a right-hand circular polarized (RHCP) light beam **1212** incident on a first side into a left-hand circular polarized (LHCP) beam **1216**. On the other hand, the waveplate lens **1200A** may be configured to converge a RHCP light beam **1220** incident on a second side opposite to the first side into a left-hand circular polarized (LHCP) beam **1224**.

(230) For the waveplate lens **1200B**, the situation is reversed. As illustrated in FIG. **16D**, when configured as a half-waveplate, the waveplate lens **1200B** may be configured to converge a LHCP light beam **1228** incident on a first side into a RHCP beam **1232**. On the other hand, the waveplate lens **1200B** may be configured to diverge a LHCP light beam **1236** incident on a second side opposite the first side into a RHCP beam **1240**.

(231) Thus, by controlling the direction of angle of rotation and the radial distribution of the liquid crystals **1208**, the waveplate lens may be configured to converge or diverge circularly polarized light having either handedness. It will be appreciated that, based on the relationship between the angles of rotation of the liquid crystals, the optical power may be increased or decreased. In addition, in some embodiments, the liquid crystals may be aligned and unaligned by applying an electric field. Thus, it will be appreciated that in the limit where the optical power is near zero, the waveplate lenses may be used as waveplates, e.g., switchable waveplates.

(232) Broadband Adaptive Waveplate Lens Assemblies Including a Switchable Waveplate

(233) As described above with respect to FIG. **12A**, to provide images at a plurality of depth planes with high efficiency over a wide range of the visible spectrum, some broadband adaptive waveplate lens assemblies according to embodiments include a switchable waveplate and one or more waveplate lenses, which may be passive or switchable, that are formed of a thin film of birefringent material, e.g., liquid crystals. In the following, embodiments of broadband adaptive waveplate lens assemblies comprising a switchable broadband waveplate are disclosed. For example, the switchable broadband waveplate may be one of broadband switchable waveplates described above with respect to FIGS. **13A-13F**, FIGS. **14A-14C** and FIGS. **15A-15B**.

(234) FIG. **17A** illustrates an example of a broadband adaptive waveplate lens assembly **1700** comprising

waveplate lenses, e.g., passive waveplate lenses, and a switchable waveplate, according to some embodiments. The broadband adaptive waveplate lens assembly **1700** may be configured, e.g., as either one of the pair of switchable waveplate assemblies **1004**, **1008** described supra with respect to FIGS. **10**, **11A** and **11B**. FIG. **17B** illustrates the broadband adaptive waveplate lens assembly **1700A** in operation when the switchable waveplate of the adaptive lens assembly **1700** illustrated in FIG. **17A** is activated, whereas FIG. **17C** illustrates the broadband adaptive waveplate lens assembly **1700B** in operation when the switchable waveplate of the adaptive lens assembly **1700** illustrated in FIG. **17A** is deactivated. The adaptive lens assembly **1700** is configured to couple and to transmit therethrough the light outcoupled from the waveguide assembly **1012** (FIGS. **10**, **11A**, **11B**). The adaptive lens assembly **1700** comprises a first waveplate lens (L1/HWP1) **1704**, e.g., a first half-waveplate lens, a second waveplate lens (L2/HWP2) **1708**, e.g., a second half-waveplate lens, and a switchable waveplate (HWP3) **1712**, e.g., a switchable half waveplate.

(235) In various embodiments, each of the L1/HWP1 **1704** and L2/HWP2 **1708** is configured to serve as a lens and a half waveplate. As described above with respect to FIGS. **12A** and **12B**, when configured as a half-waveplate, each of the L1/HWP1 **1704** and L2/HWP2 **1708** is configured to convert light having a circular polarization of first handedness (first HCP) to light having a circular polarization of second handedness (second HCP). That is, each of the L1/HWP1 **1704** and L2/HWP2 **1708** is configured to convert light passing therethrough from light having LHCP or RHCP, and to convert light having RHCP or LHCP, respectively.

(236) In various embodiments, each of the L1/HWP1 **1704** and L2/HWP2 **1708** is configured to serve as a lens, for a given polarization, having a first lensing effect or a second lensing effect opposite the second lensing effect. That is, each of the L1/HWP1 **1704** and L2/HWP2 **1708** is configured to either converge or diverge light passing through. In various embodiments, each of the L1/HWP1 **1704** and L2/HWP2 **1708** may be configured to have opposite lensing effects depending on the polarization state of the incident light. For example, each of the L1/HWP1 **1704** and L2/HWP2 **1708** may be configured to focus light incident thereon having a first HCP while being configured to defocus light incident thereon having a second HCP.

(237) In some embodiments, the L1/HWP1 **1704** and L2/HWP2 **1708** are configured to have the same lensing effect for light having a given HCP. That is, both of the L1/HWP1 **1704** and L2/HWP2 **1708** may be configured to focus light having LHCP, focus light having RHCP, defocus light having LHCP or defocus light having RHCP.

(238) In some embodiments, each of the L1/HWP1 **1704** and L2/HWP2 **1708** may comprise liquid crystal molecules that are elongated and rotated such that liquid crystals at a given radius from a central axis of the respective waveplate lenses **1704**, **1708** have the same angle (q) of rotation, as described above with respect to FIGS. **12A** and **12B**. Each of the first and second waveplate lenses **1704**, **1708** is configured to alter a polarization state, e.g., invert a polarization state, of light passing therethrough. The switchable waveplate **1712** is configured to alter a polarization state, e.g., invert a polarization state, of light passing therethrough when electrically deactivated, while being configured to substantially pass light without altering the polarization state of light passing therethrough when activated. The electrical signal, e.g., a current signal or a voltage signal, for switching the switchable waveplate **1712** may be provided by a switching circuit **1716** electrically connected thereto.

(239) In various embodiments, when deactivated, e.g., electrically deactivated using a voltage or a current signal provided by the switching circuit **1716**, the HWP3 **1712B** (FIG. **17C**) serves as a half waveplate. That is, when deactivated, the HWP3 **1712B** (FIG. **17C**) serves as a half waveplate configured to convert light passing therethrough from light having LHCP or RHCP to light having RHCP or LHCP, respectively. Thus, each of the L1/HWP1 **1704**, the L2/HWP2 **1708**, and the HWP3 **1712B** when deactivated (FIG. **17C**) is configured to convert light having a circular polarization of first handedness (first HCP) to light having a circular polarization of second handedness (second HCP).

(240) In various embodiments, when activated, e.g., electrically activated using a voltage or a current signal provided by the switching circuit **1716**, e.g., by removing the voltage or the current signal, the HWP3 **1712A** (FIG. **17B**) serves as transmitting medium for light without affecting the polarization or providing any lensing effect.

(241) In some embodiments, a single waveplate lens **1704** and/or **1708** may function both as a waveplate lens and as a switchable half waveplate. In such embodiments, the dedicated switchable half waveplate **1712** may be omitted.

(242) FIG. **17B** illustrates an example of the adaptive lens assembly of FIG. **17A** in operation with the switchable waveplate activated, according to some embodiments. The adaptive lens assembly **1700A** may be activated when the switchable waveplate **1712** is activated, e.g., when no current or voltage is applied to the switchable waveplate **1712** by the switching circuit **1716**. The adaptive lens assembly **1700A** may correspond to the first adaptive lens assembly **1004** (on the world side) or the second adaptive lens assembly **1008** (on the user side). By way of example only, the adaptive lens assembly **1700A** will be described as corresponding to the first adaptive lens assembly **1004** or the second adaptive lens assembly **1008**, as part of the display device **1000** (FIG. **10**) that

is displaying the view of the real world to the user without displaying a virtual image. For example, the display device **1000** (FIG. **10**) may be used as an ordinary eyeglass or an ordinary goggle. Each of the L1/HWP1 **1704** and L2/HWP2 **1708** may be configured to have a first lensing effect, e.g., diverging effect, on light having a first HCP, e.g., LHCP, passing therethrough. Each of the L1/HWP1 **1704** and L2/HWP2 **1708** may also be configured to have a second lensing effect opposite the first lensing effect, e.g., converging effect, on light having the opposite HCP, e.g., RHCP, passing therethrough.

(243) In the illustrated embodiment, the light beam **1720** may represent a light beam from the world that is incident on either the first adaptive lens assembly **1004** (FIGS. **11A/B**, on the world side) or the second adaptive lens assembly **1008** (FIGS. **11A/B**, on the user side) while the display device **1700A** is being used as ordinary eyeglasses or a goggle, without displaying virtual content. By way of example only, the light beam **1720** having a first HCP, e.g., LHCP, travels, e.g., in a positive z-direction, until the beam **1720** impinges on the L1/HWP1 **1704**, to be transmitted therethrough. The L1/HWP1 **1704** converts the light beam **1720** having LHCP into a light beam **1724** having RHCP. Because the L1/HWP1 **1704** is also configured as a lens, the L1/HWP1 **1704** also diverges the light beam **1720** according to a first optical power P_1 of the L1/HWP1 **1704**.

(244) The light beam **1724** having RHCP is subsequently incident on the HWP3 **1712A** in the activated state. Because the HWP3 **1712A** is activated, the light beam **1724** having RHCP transmits through the HWP3 **1712A** without being substantially affected in terms of polarization or lensing effect, to be incident on the L2/HWP2 **1708**, as light beam **1728A** having RHCP. As described above, when configured as an adaptive lens assembly on the user side (e.g., second adaptive lens assembly **1004** in FIG. **10**), the L2/HWP2 **1708** is configured similarly to L1/HWP1 **1704** in the illustrated embodiment, i.e., to convert the polarization and to diverge light having LHCP while converging light having RHCP. Thus, the light beam **1728A** having RHCP is converted back to light beam **1732** having LHCP. Thus, when HWP3 **1712A** is activated, the L1/HWP1 **1704** and the L2/HWP2 **1708** transmit light beams having opposite polarizations, such that the L1/HWP1 **1704** and the L2/HWP2 **1708** have opposite lensing effect on light passing therethrough. That is, because the light beam **1728A** incident on the L2/HWP2 **1708** has RHCP, the light beam **1732A** exiting the L2/HWP2 **1708** is converged according to a second optical power P_2 , unlike the light beam **1724** exiting the L1/HWP1 **1704** that is diverged according to a first optical power P_1 . Thereafter, upon exiting the adaptive lens assembly **1700A** in the activated state, the light beam **1732A** may be viewed by the eye.

(245) In some embodiments, when the HWP3 **1712A** is activated, the first optical power P_1 of L1/HWP1 **1704**, which may be negative (i.e., diverging), and the second optical power P_2 of L2/HWP2 **1708**, which may be positive (i.e., converging), may have substantially the same or matched magnitudes. In these embodiments, the net optical power P_{net} of the adaptive lens assembly **1700A**, which may be approximately $-P_1+P_2$, may be substantially zero because of the compensation of the lensing effects of the L1/HWP1 **1704** and the L2/HWP2 **1708**. However, embodiments are not so limited, and the first and second optical powers P_1 , P_2 may have different magnitudes, such that the net optical power P_{net} may have a nonzero value. For example, in some embodiments, the nonzero P_{net} may be equal to an eyeglass prescription of the user, thereby allowing for corrections to focusing errors (e.g., refractive focusing errors) of the eyes of the user.

(246) It will be appreciated that, while in the illustrated embodiment, the incident light beam **1720** has LHCP, a similar outcome would result when the incident light beam **1720** has RHCP. That is, when the light beam **1720** has RHCP, the light beams **1724** and **1728A** have LHCP, and unlike the illustrated embodiment, the light beams **1724** and **1728A** are converged relative to the light beam **1720**. Likewise, the L2/HWP2 **1708** diverges the light beam **1728A** converged by the L1/HWP1 **1704**, such that the net optical power P_{net} may be substantially zero.

(247) It will be appreciated that the lensing effects of the L1/HWP1 **1704** and L2/HWP2 **1708** and the selectivity of the lensing effects to the polarization state of incident light beams described above with respect to FIG. **17B** serves as but one example, and other configurations are possible. For example, while in FIG. **17B**, the L1/HWP1 **1704** and L2/HWP2 **1708** is configured to diverge light having LHCP while converging light having RHCP, in other embodiments, the L1/HWP1 **1704** and L2/HWP2 **1708** may be configured to converge light having LHCP while diverging light having RHCP.

(248) In summary, in some embodiments, when the HWP3 **1712A** of the adaptive lens assembly **1700A** is in a activated state, the exiting light beam **1732A** has the same HCP as the incident light beam **1720**, and may be substantially matched to the incident light beam **1720** in terms of the lens effect because of the compensation of the lens effects between P_1 of L1/HWP1 **1704** and P_2 of L2/HWP2 **1708**. As a result, when the user is not viewing virtual content, the view of the world is relatively unaffected by the presence of the adaptive lens assemblies (**1004**, **1008** in FIGS. **10**, **11A**, **11B**).

(249) FIG. **17C** illustrates an example of the adaptive lens assembly of FIG. **17A** in operation with the switchable waveplate deactivated, according to some embodiments. The adaptive lens assembly **1700B** may be deactivated when the switchable waveplate **1712B** is deactivated, e.g., when a current or a voltage is applied to the switchable

waveplate **1712B** by the switching circuit **1716**. The adaptive lens assembly **1700B** may, e.g., correspond to the first adaptive lens assembly **1004** (on the world side) or the second adaptive lens assembly **1008** (on the user side). In the following, by way of example, the adaptive lens assembly **1700B** will be first described as being configured as the second adaptive lens assembly **1008** on the user side, as part of the display device (e.g., display device **1100A** in FIG. **11A**) that is outputting virtual image to the user. Subsequently, the adaptive lens assembly **1700B** will be described as being configured as the first adaptive lens assembly **1004** on the world side, as part of the display device **1100B** (FIG. **11B**) that is simultaneously transmitting the view of the real world while outputting the virtual image to the user, to reduce or essentially eliminate distortion of the view of the real world resulting from the lens effects of the second adaptive lens assembly **1008**.

(250) When configured as the second adaptive lens assembly **1008** on the user side (FIG. **11A**), each of the L1/HWP1 **1704** and L2/HWP2 **1708** may be configured to diverge light having one of HCP, e.g., LHCP, passing therethrough. Each of the L1/HWP1 **1704** and L2/HWP2 **1708** may also be configured to converge light having the other HCP, e.g., RHCP, passing therethrough.

(251) As described above with respect to FIG. **11A**, some of the light propagating in the x-direction, e.g., by total internal reflection, within the waveguide assembly **1012** may be redirected, or out-coupled, in the z-direction. The light out-coupled from the waveguide assembly **1012** (FIG. **11A**) may be incident on the switchable lens assembly **1700B** as a circularly polarized light beam **1720** having LHCP. The light beam **1720** travels, e.g., in a positive z-direction, until the light beam **1720** impinges on the L1/HWP1 **1704**, to be transmitted therethrough. The L1/HWP1 **1704** converts the light beam **1720** having LHCP into a light beam **1724** having RHCP. Because the L1/HWP1 **1704** is configured to diverge light having LHCP, the light beam **1724** is also diverged according to the first optical power P_1 of the L1/HWP1 **1704**.

(252) The light beam **1724** having RHCP is subsequently incident on the HWP3 **1712B** in the deactivated state. Unlike the activated HWP **1712A** illustrated above with respect to FIG. **17B**, because the HWP3 **1712B** is deactivated, the light beam **1724** having RHCP transmitting through the HWP3 **1712B** is converted to light beam **1728B** having LHCP. Subsequently, the light beam **1728B** having LHCP is incident on the L2/HWP2 **1708**. Because, unlike the light beam **1728A** illustrated above with respect to FIG. **17B**, the light beam **1728B** incident on the L2/HWP2 **1708** has LHCP, the L2/HWP2 **1708** further diverges the light beam **1728B** according to a second optical power P_2 into light beam **1732B** having RHCP. That is, unlike the activated state of HWP **1712A** illustrated with respect to FIG. **17B**, because the HWP **1712B** is deactivated, L1/HWP1 **1704** and the L2/HWP1 **1704** are configured to transmit light beams having the same polarization, LHCP. Thus, unlike the L1/HWP1 **1704** and the L2/HWP2 **1708** having the compensating effect illustrated with respect to FIG. **17B**, the L1/HWP1 **1704** and the L2/HWP2 **1708** in FIG. **17C** have additive lensing effect on the light passing therethrough. That is, because the light beam **1720** incident on L1/HWP1 and the light beam **1728B** incident on L2/HWP2 **1704** both have LHCP, light beam **1732B** exiting the L2/HWP2 **1708** will be further diverged, in addition to being diverged by the L1/HWP1 **1704**. Thereafter, upon exiting the adaptive lens assembly **1700B** in the deactivated state, the light beam **1732A** may be viewed by the eye.

(253) In some embodiments, the first optical power P_1 of L1/HWP1 **1704** and the second optical power P_2 of L2/HWP2 **1708** may both be negative (i.e., diverging) and may have substantially the same or matched magnitudes. In these embodiments, the net optical power P_{net} of the adaptive lens assembly **1700B**, which may be approximately $P_1 + P_2$, may be substantially double that of P_1 or P_2 because of the additive lens effect of the combination of L1/HWP1 **1704** and L2/HWP2 **1708**. However, embodiments are not so limited, and the first and second optical powers P_1 , P_2 may have different magnitudes.

(254) It will be appreciated that, while in the illustrated embodiment, the incident light beam **1720** has LHCP, parallel outcome will result when the incident light beam **1720** has RHCP. That is, when the light beam **1720** has RHCP, unlike the illustrated embodiment, the resulting light beam **1732B** has LHCP and is converged by L1/HWP1 **1704** and L2/HWP2 **1708** according to a net optical power P_{net} , which has a magnitude that is approximately a sum of the magnitudes of the first and second optical powers P_1 and P_2 .

(255) It will be appreciated that the lensing effects of the L1/HWP1 **1704** and L2/HWP2 **1708** and the dependence of the lensing effects on the polarization state of incident light beams described above with respect to FIG. **17C** serves as but one example, and other configurations are possible. For example, while in FIG. **17B**, the L1/HWP1 **1704** and L2/HWP2 **1708** are configured to diverge light having LHCP while converging light having RHCP, in other embodiments, the L1/HWP1 **1704** and L2/HWP2 **1708** may be oppositely configured to diverge light having LHCP while converging light having RHCP.

(256) Consequently, in some embodiments, when the switchable half waveplate **1712B** of the adaptive lens assembly **1700B** is in an deactivated state, the exiting light beam **1732B** has the opposite HCP relative to the incident light beam **1720**, and may be diverged according to additive optical powers P_1 of L1/HWP1 **1704** and P_2 of L2/HWP2 **1708**. As a result, when the user is viewing a virtual content, the virtual content is focused into the

eye **210** according to a net optical power whose value is approximately $P_{net}=P_1+P_2$.

(257) In the above, the adaptive lens assembly **1700B** in the deactivated state has been described when configured as the second adaptive lens assembly **1008** on the user side in the display device **1100A** described supra with respect to FIG. **11A**. As described supra with respect to FIG. **11B**, however, activating the second adaptive lens assembly **1008** to display virtual content to the user's eye **210**, without any compensating effect, may result in a defocusing or distortion of the view of the real world, which may be undesirable. Thus, it may be desirable to configure the first adaptive lens assembly **1004** on the world side to at least partially compensate or negate the lens effect of the second adaptive lens assembly **1008** when deactivated to display the virtual content.

(258) Referring back to FIG. **17C**, when configured as the first adaptive lens assembly **1004** (FIG. **11B**) on the world side to negate the lens effect of the second adaptive lens assembly **1008** (FIG. **11B**) on the user side, components of the adaptive lens assembly **1700B** may be configured similarly as described supra with respect to FIG. **11B**. That is, as light transmitted from the world **510** to the eye **210** traverses the first and second adaptive lens assemblies **1004**, **1008**, each may be configured as described above with respect to the adaptive lens assembly **1700B** described with respect to FIG. **17C**. In operation, as described above, the polarization of the light transmitted from the world through the first adaptive lens assembly **1004** is converted from a first polarization state to a second polarization state, e.g., from RHCP to LHCP. Subsequently, the polarization of the light transmitted through the second adaptive lens assembly **1008** is converted back from the second polarization state to the first polarization state, e.g., from LHCP to RHCP. Furthermore, as described above with respect to FIG. **11B**, the light transmitted from the world through the first adaptive lens assembly **1004** undergoes a first lens effect, e.g., converging effect, according to a first net optical power $P_{net1}=P_1+P_2$ having a first sign, e.g., positive sign. Subsequently, the light transmitted through the second adaptive lens assembly **1008** undergoes a second lens effect opposite to the first lens effect, e.g., diverging effect, according to a second net optical power $P_{net2}=P_1'+P_2'$ having a second sign, e.g., negative sign, because the light incident on the second adaptive lens assembly **1008** has an opposite polarization as the light incident on the first adaptive lens assembly **1004**. When P_{net1} and P_{net2} have substantially similar magnitudes, the overall lens effect, approximated by $P=P_{net1}+P_{net2}$ may be substantially zero. As a result, when the user is viewing virtual content by activating the second lens assembly **1008**, as well as viewing real objects in the surrounding world, the view of the world is relatively unaffected by the compensating effect of the first lens assembly **1004**.

(259) In various embodiments, when deactivated, each of the first and second adaptive lens assemblies **1004**, **1008** may provide a net optical power (positive or negative) in the range between about ± 5.0 diopters and 0 diopters, ± 4.0 diopters and 0 diopters, ± 3.0 diopters and 0 diopters, ± 2.0 diopters and 0 diopters, ± 1.0 diopters and 0 diopters, including any range defined by these values, for instance ± 1.5 diopters.

(260) Display Devices Including Adaptive Lens Assemblies Having a Switchable Half Waveplate and Waveplate Lenses

(261) In the following, an example of a display device described supra with respect to FIGS. **10**, **11A** and **11B**. in which an adaptive lens assembly comprising waveplate lenses and a switchable waveplate, e.g., the adaptive lens assembly **1300** described above with respect to FIGS. **17A-17C**, has been integrated, according to some embodiments. The switchable waveplate may be, e.g., one of broadband switchable waveplates described above with respect to FIGS. **13A-13F**, FIGS. **14A-14C** and FIGS. **15A-15B**.

(262) FIGS. **18A** and **18B** illustrate example display devices **1800A/1800B**, each including a waveguide assembly **1012** interposed between a first broadband adaptive waveplate lens assembly **1004** and a second broadband adaptive waveplate lens assembly **1008**. The display device **1800A** is similar to the display device **1100A/1100B** described above with respect to FIGS. **11A/11B**, where each of the first and second adaptive lens assemblies **1004**, **1008** comprises a first waveplate lens (L1/HWP1) **1704**, e.g., a first half-waveplate lens, a second waveplate lens (L2/HWP2) **1708**, e.g., a second half-waveplate lens, and a switchable waveplate (HWP3) **1712**, e.g., a switchable half waveplate.

(263) Referring to FIG. **18A**, the display device **1800A** in operation is described, when the first and second adaptive lens assemblies **1004**, **1008** described above with respect to FIG. **17A** are both activated. The first and second adaptive lens assemblies **1004**, **1008** may be activated when the switchable waveplate **1712** (FIG. **17A**) is activated, e.g., when no current or voltage is applied to the switchable waveplate **1712** by the switching circuits **1816**, **1816'**. As configured, the display device **1800A** may be configured for, e.g., displaying the real world view to the user, without displaying a virtual image. For example, the display device **1800A** may be configured to be used as an ordinary eyeglass or an ordinary goggle, as described in detail with respect to FIG. **17B**. Similar to FIG. **17A**, each of first and second adaptive lens assemblies **1004**, **1008** include a first waveplate lens (L1/HWP1) **1804**, e.g., a first half-waveplate lens, a second waveplate lens (L2/HWP2) **1808**, e.g., a second half-waveplate lens, and a switchable waveplate (HWP3) **1812**, e.g., a switchable half waveplate. As described with respect to FIG. **17A**, each of L1/HWP1 **1804** and L2/HWP2 **1808** may be configured to have a first lensing effect, e.g.,

diverging effect, on light having a first HCP, e.g., LHCP, passing therethrough. In addition, each of the L1/HWP1 **1804** and L2/HWP2 **1808** may also be configured to have a second lensing effect opposite the first lensing effect, e.g., converging effect, on light having the opposite HCP, e.g., RHCP, passing therethrough. When deactivated, e.g., electrically deactivated using a voltage or a current signal provided by the switching circuit **1816**, **1816'**, the HWP3 **1712B** (FIG. **17C**) serves as a waveplate, e.g., a half waveplate. As described above with respect FIG. **17C**, when deactivated, the HWP3 **1712B** (FIG. **17C**) serves as a half waveplate configured to convert light passing therethrough from light having LHCP or RHCP to light having RHCP or LHCP, respectively. On the other hand, when activated, e.g., electrically activated using a voltage or a current signal provided by the switching circuit **1816**, **1816'**, e.g., by removing the voltage or the current signal, the HWP3 **1712A** (FIG. **17B**) serves as transmitting medium for light without affecting the polarization. The detailed operational principles of the first and second adaptive lens assemblies **1004**, **1008** that include the L1/HWP1 **1804**, L2/HWP2 **1808** and HWP3, **1812A** have been provided above with respect to FIGS. **17A** and **17B**, and are omitted herein.

(264) Based on the operational principles described in detail with respect to FIGS. **17B** and **17C**, when the first and second adaptive lens assemblies **1004**, **1008** are in an activated state, the light beam (e.g., **1732A** in FIG. **17B**) exiting from each of the first and second adaptive lens assemblies **1004**, **1008**, has the same HCP as the light beam incident thereon (e.g., **1720** in FIG. **17B**). In addition, the incident light beam **1720** and the exiting light beam **1732A** may be substantially matched in terms of the magnitudes of the lens power because of the compensation of the net optical powers of the first and second lens assemblies **1004**, **1008**, as described above with respect to FIG. **13B**.

(265) FIG. **18B** illustrates an example of the display device of FIG. **18A**, in operation with the switchable waveplate deactivated, according to some embodiments. The first and second adaptive lens assemblies **1004**, **1008** by activating the respective switchable waveplates **1712** (FIG. **17A**), e.g., by applying current or voltage to the switchable waveplate **1712** using the switching circuit **1816**, **1816'**. In the following, the operation of the display device **1800B** that is outputting a virtual image to the user, while also transmitting light from an object in the real world with reduced or essentially eliminated distortion resulting from the lens effects of the adaptive lens assemblies **1004**, **1008**, is described.

(266) When displaying a virtual image, as described above with respect to FIGS. **11A** and **17C**, some of the light propagating in the x-direction within the waveguide within the waveguide assembly **1012** may be redirected, or outcoupled, in the z-direction. The light beam **1720** travels, e.g., in a positive z-direction, until the light beam **1720** impinges on the L1/HWP **1804** of the second adaptive lens assembly **1008**. Based on the operational principles of the second adaptive lens assembly **1008** described above with respect to FIG. **17C**, when the second adaptive lens assembly **1008** is in an deactivated state, the exiting light beam (e.g., **1732B** in FIG. **17C**) has the opposite HCP as the incident light beam (e.g., **1720** in FIG. **17C**), and is diverged according to the second net optical power P_{net2} , for displaying the virtual content at a corresponding virtual depth plane.

(267) In various embodiments, when deactivated, each of the first and second adaptive lens assemblies **1004**, **1008** may provide a net optical power (positive or negative) in the range between about ± 5.0 diopters and 0 diopters, ± 4.0 diopters and 0 diopters, ± 3.0 diopters and 0 diopters, ± 2.0 diopters and 0 diopters, ± 1.0 diopters and 0 diopters, including any range defined by these values, for instance ± 1.5 diopters. In some embodiments, the first adaptive lens assembly **1004** between the waveguide assembly **1012** and the world may have a positive optical power, whereas the second adaptive lens assembly **1008** between the waveguide assembly **1012** and the user may have a negative optical power, such that the optical powers of the first and second switchable assemblies **1004**, **1008** compensate each other in viewing the world.

(268) Consequently, still referring to FIGS. **18A** and **18B**, the display device **1800A/1800B** comprise a pair of adaptive lens assemblies **1004**, **1008** in the optical path between the world **510** and the eye **210**, where each of the pair of adaptive lens assemblies **1004**, **1008** comprises a switchable waveplate (e.g., **1712A/1712B** in FIGS. **17A/17B**) configured to alter a polarization state of light passing therethrough when electrically deactivated. When electrically deactivated, the pair of adaptive lens assemblies have net optical powers (P_{net1} , P_{net2}) having opposite signs such that light passing through the pair of adaptive lens assemblies converges or diverges according to a combined optical power having a magnitude that is about a difference between magnitudes of optical powers the pair of adaptive lens assemblies. The virtual content may be observed by the user at a depth plane according to P_{net2} , which may be negative, while the view of the world is relatively unaffected by P_{net2} that is at least partially compensated by P_{net1} , which may be positive.

(269) In some embodiments, each of the pair of adaptive lens assemblies has a respective net optical power (P_{net1} , P_{net2}) that is electrically adjustable or tunable to one of a plurality of values using the switching circuit **1816**, **1816'**. As described supra, as the images of virtual objects produced by light outcoupled by the waveguide assembly **1012** move in 3D, the second net optical power (P_{net2}) of the second adaptive lens assembly **1008** on the user side is adjusted to adapt to the changing depth of the virtual depth plane. Simultaneously, according to

embodiments, the first net optical power (Pnet1) of the first adaptive lens assembly **1004** is correspondingly adjusted using the switching circuit **1816**, **1816'**, such that the view of the real world does not undesirably become defocused or distorted. To address this and other needs, in some embodiments, the display device **1800A/1800B** comprises a controller **1804** configured such that, when the first net optical power (Pnet1) of a first one of the pair of adaptive lens assemblies **1004**, **1008** is electrically adjusted, a second optical power (Pnet2) of a second one of the pair of adaptive lens assemblies is correspondingly adjusted, such that the combined optical power (Pnet1+Pnet2) remains about constant, e.g., about zero. The controller circuitry and the switchable waveplate **1812** are configured such that the time to switch the first and second net optical powers Pnet, Pnet2, to adjust the virtual depth planes using the second adaptive lens assembly **1008** and to compensate the real world view using the first adaptive lens assembly **1004** as described herein, is less than about 100 milliseconds, less than about 50 milliseconds, less than about 10 milliseconds, less than about 5 milliseconds, less than about 1 millisecond, or a value within a range defined by any of these values.

(270) Broadband Switchable Waveplate Lenses

(271) As described above, according to various embodiments, broadband adaptive waveplate lens assemblies can generate images at multiple depth planes by being selectively switched between a plurality of states having different optical powers. In some embodiments described above, the broadband capability of the broadband adaptive waveplate lens assembly can be enabled by one or more broadband passive waveplate lenses (e.g., **1154A** in FIG. **12A**) coupled with a broadband switchable waveplate (e.g., **1158** in FIG. **12A**). In some other embodiments, the broadband capability of the broadband adaptive waveplate lens assembly can be enabled by broadband switchable waveplate lenses without broadband switchable waveplates (e.g., **1154B** in FIG. **12B**). In the following, structures and configurations of liquid crystal layers of broadband switchable waveplate lenses and broadband adaptive lens assemblies having the same are described, according to embodiments.

(272) FIG. **19A** illustrates a plan view of a broadband waveplate lens **1900** comprising a layer of LC molecules formed on a transparent substrate, according to various embodiments. The spatial distribution of the elongation direction of lowermost LC molecules or the LC molecules closest to the substrate, and/or the local director of LC molecules resulting therefrom, can be distributed according to the pattern of arrows depicted in FIG. **19A**. In the illustrated embodiment, the LC molecules closest to the substrate at a given radius from a central region have generally the same elongation direction.

(273) In the some embodiments, the waveplate lens **1900** is a polarization-type Fresnel zone plate (FZP) lens having a birefringence profile that is radially symmetric and radially modulated. In some embodiments, the orientation of the elongation direction of LC molecules or the local director can vary as a function of radius according to a mathematical function. In the illustrated embodiment, the azimuthal angle ϕ of the local director of LC molecules can have discrete values in different zones disposed at different radii from the center of the waveplate lens **1900**. For example, ϕ in the m -th zone can be expressed as

$$(274) \quad = -(f - \sqrt{f^2 - r^2}) + (m + \frac{1}{2}) \pi,$$

where f is the focal length and r is the distance from the center of the waveplate lens **1900**.

(275) In some other embodiments, the spatial distribution of the elongation direction or the local directors of the LC molecules, or the local birefringence resulting therefrom can be similar to that described above with respect to FIGS. **16A** and **16B**.

(276) In some embodiments, local orientation directions of LC molecules, e.g., elongation directions, above the lowermost LC molecules can be generally the same as those of the lowermost LC molecules closest to the substrate. In some other embodiments, local orientation directions of LC molecules above the lowermost LC molecules can be generally different from those of the lowermost LC molecules closest to the substrate. For example, local orientation directions of LC molecules above the lowermost LC molecules can be successively twisted, as described infra (e.g., FIGS. **20A**, **20B**).

(277) In operation, in a similar manner as the waveplate lenses described above with respect to FIGS. **16A** and **16B**, the broadband waveplate lens **1900** has polarization-selective lens effect of functioning as a convex (or positive) lens (FIG. **19B**) for incident light **1162B** having a first polarization, e.g., right-handed circular polarization (RHCP), while functioning as a concave (or negative) lens (FIG. **19C**) for incident light **1162A** having a second polarization, e.g., left-handed circular polarization (LHCP). In addition, the broadband waveplate lens **1900** flips the polarization of the diffracted light. That is, the incident light **1162B** having RHCP is converted by the broadband waveplate lens **1900** to light **1166A** having LHCP as illustrated in FIG. **19B**, while the incident light **1162A** having LHCP is converted by the waveplate lens **1900** to light **1166B** having RHCP as illustrated in FIG. **19C**. The relative proportion of undiffracted leakage light **1904** determines the diffraction efficiency, as described above.

(278) The inventors have found that further improvements in high bandwidth capability of the waveplate lenses can be achieved by particularly configuring the twist arrangement of LC molecules vertically within one or more

LC layers (e.g., FIGS. 20A, 20B), or by employing a negative dispersion LC material (FIG. 21), to further reduce the undiffracted leakage light **1904** and to increase the diffraction efficiency, which in turn further reduces undesirable visual effects such as ghost images, as described below.

(279) FIGS. 20A and 20B schematically illustrate a plan view and a cross-sectional view, respectively, of a broadband waveplate lens **2000** comprising crystal plurality of LC layers, according to embodiments. The illustrated broadband waveplate lens **2000** comprises a stack of two LC layers **2004**, **2008** having LC molecules that have opposite twist sense, such that retardation of light by one of the LC layers **2004**, **2008** is compensated by the other one of the LC layers **2004**, **2008**. For illustrative purposes only, FIGS. 20A and 20B depict the relative orientations of LC molecules that laterally vary schematically in a particular fashion. However, it will be understood that the lateral arrangement of the LC molecules across the x-y plane at a given depth in the z direction can have any of the various arrangements described above, including those illustrated above with respect to FIGS. 16A and 16B and with respect to FIG. 19A. For example, in some embodiments, the LC molecules closest to the substrate have generally the same local orientation direction, e.g., local elongation direction or local director, at a given radius from the central region and/or have orientation directions that vary as a function of radius, in a similar manner as described above with respect to FIG. 19A. In addition, the arrangement of LC molecules in a given columnar region in the two LC layers **2004**, **2008** can be expressed as having the nematic director $\mathbf{n}$ which varies as a function of vertical location within the LC layer according to

$$(280) \mathbf{n}(x, z) = [\cos(\varphi(x, z)), \sin(\varphi(x, z)), 0],$$

where φ is the azimuth angle of the director $\mathbf{n}$ in the x-z plane. That is, for a given column of LC molecules having a first sense of twist in one of the LC layers **2004**, **2008**, a corresponding column of LC molecules in the other one of the LC layers **2004**, **2008** has an opposite sense of twist. In other words, LC molecules in the two LC layers **2004**, **2008** have mirror images of each of other about an interface between the two LC layers **2004**, **2008**. (281) According to embodiments, reactive mesogens can be employed to create the arrangement of LC molecules in the two LC layers **2004**, **2008**. For example, by suitably configuring an alignment layer **1302-0**, on a substrate **1312**, the bottommost LC molecules in the first LC layer **2004** closest to the alignment layer **1302-0** can be arranged to have a first azimuth angle.

(282) The first azimuth angle can be defined, for example, according to the arrangement of elongation direction of the LC molecules as described above with respect to any of FIGS. 16A, 16B and 19A. In addition, the LC molecules above the bottommost LC molecules in the first LC layer **2004** can be configured to have a first twist by adding chiral agents to the first LC layer **2004**, such that the uppermost LC molecules closest to a surface of the first LC layer **2004** has a second azimuth angle. Thereafter, by suitably configuring the surface region of the first LC layer **2004**, bottommost LC molecules in the second LC layer **2008** closest to the first LC layer **2004** can be arranged to have the second azimuth angle. In addition, the LC molecules above the bottommost LC molecules in the second LC layer **2008** can be configured to have a second chiral twist by adding chiral agents to the second LC layer **2008**, such that uppermost LC molecules closest to the surface of the second LC layer **2008** have a third azimuth angle. In some embodiments, the first and second chiral twist is about the same, such that the bottommost LC molecules of the first LC layer **2004** and the uppermost LC molecules of the second LC layer **2008** have the same first azimuth angle.

(283) In one example configuration, by configuring the LC layers **2004**, **2008** to have suitable thickness, e.g., between about 1 μm and 2 μm or between about 1.5 μm and 2 μm , for instance about 1.7 μm , and a suitable chiral twist between about 50 degrees and 90 degrees or between about 60 degrees and 80 degrees, for instance about 70 degrees, relative bandwidth $\Delta\lambda/\lambda_{\text{sub.o}}$ greater than 40%, 50% or 60%, for instance about 56% can be achieved, within which wavelength range the diffraction efficiency is greater than 99%, according to embodiments.

(284) As described above, diffraction efficiency (η) can be expressed as $\eta = \sin^2(\pi \Delta n d / \lambda)$, where Δn is birefringence, λ is wavelength and d is thickness. Generally, optically anisotropic materials display Δn which decreases with increasing λ (referred to herein as a positive dispersion of Δn). However, a positive dispersion of Δn results in different phase retardation $\Gamma = 2\pi \Delta n d / \lambda$ at different λ . The inventors have recognized that, by employing an optically anisotropic material that displays Δn which increases with increasing λ (referred to herein as having a negative dispersion of Δn), the phase retardation Γ can be kept relatively constant at different λ and the diffraction efficiency η can be kept relatively high and constant over a relatively wide wavelength range, according to embodiments.

(285) FIG. 21 illustrates a cross-sectional view of a broadband waveplate lens **2100** comprising a negative dispersion (ND) liquid crystal (LC) layer **2104** formed on a substrate **1312** and an alignment layer **1312-0**, according to embodiments. Similar to the broadband waveplate lenses described above with respect to FIG. 19A and FIGS. 20A/20B, to provide the lens effect, the ND LC layer **2104** can be arranged, e.g., by suitably arranging the alignment layer **1312-0**, such that the waveplate lens **2100** has a birefringence (Δn) that varies in a radial direction from a central region. In addition, in some embodiments, the bottommost LC molecules closest to the

substrate **1312** can be arranged to generally have the same orientation direction at a given radius from the central region and to generally have orientation directions that vary as a function of radius, in a similar manner as described above with respect to FIGS. **16A**, **16B** and **19A** using, e.g., an alignment layer **1312-0** that is suitably configured as discussed elsewhere in the specification.

(286) In various embodiments, the negative dispersion (ND) liquid crystal (LC) layer **2104** can have an average, a local, a mean, a median, a maximum or a minimum birefringence (Δn) of 0.05-0.10, 0.15-0.20, 0.20-0.25, 0.25-0.30, 0.30-0.35, 0.35-0.40, 0.40-0.45, 0.45-0.50, 0.50-0.55, 0.55-0.60, 0.60-0.65, 0.65-0.70, or a value within a range defined by any of these values. In addition, the negative dispersion (ND) liquid crystal (LC) layer **2104** can have a within-layer birefringence (Δn) range of 0.01-0.05, 0.05-0.10, 0.15-0.20, 0.20-0.25, 0.25-0.30, 0.30-0.35, 0.35-0.40, or a value within a range defined by any of these values.

(287) Still referring to FIG. **21**, unlike the LC molecules described above with respect to FIGS. **20A** and **20B**, the ND LC layer **2104** may be vertically homogenous. For example, in the ND LC layer **2104**, LC crystals formed above the bottommost LC molecules may not be twisted. Instead, in some embodiments, within a given columnar region, the local director n may be substantially constant across the thickness of the ND LC layer **2104**. In some other embodiments, within a given columnar region, the local director n may be substantially random across the thickness of the LC layer **2104**.

(288) According to various embodiments, the ND LC layer **2104** may be formed of a material, e.g., reactive mesogens, having a material property such that Δn increases with increasing wavelength (λ) within at least a portion of the visible spectrum within 400-800 nm, including one or more of a red spectrum which includes wavelengths in the range of about 620-780 nm, a green spectrum which includes wavelengths in the range of about 492-577 nm, and a blue spectrum in the range of about 435-493 nm, or within a range of wavelengths defined by any wavelength within the visible spectrum within about 400 nm to 800 nm, e.g., 400-700 nm, 430-650 nm or 450-630 nm. In some embodiments, within any of these ranges of wavelength, the NC LC layer **2104** has a dispersion of the extraordinary refractive index n_e that is smaller than that of the ordinary refractive index n_o .

(289) In some embodiments, the ND LC layer **2104** comprises smectic liquid crystals (LC), e.g., a smectic LC-polymer composite material.

(290) Advantageously, in some embodiments, the broadband waveplate lens **2100** has a single ND LC layer **2104** having birefringence, unlike, e.g., the broadband waveplate lens **2000** described above with respect to FIGS. **20A** and **20B** having multiple layers.

(291) In various embodiments of broadband waveplate lenses described above with respect to any one of FIGS. **16A**, **16B**, **19A**, **20A/20B** and **21**, the LC layers can be configured to be passive or switchable, according to embodiments. When configured as a passive lens, the layer of LC molecules can be formed of polymerized LC (LCP), while when configured as a switchable lens, the layer of LC molecules can be formed of unpolymerized LC molecules or reactive mesogens. When configured as a switchable lens, the waveplate lenses described above with respect to FIGS. **16A**, **16B**, **19A**, **20A/20B** and **21** further comprises transparent electrodes on both sides (e.g., FIG. **14C**) or on the same side (e.g., FIGS. **15A/15B**) of the layer of LC molecules, in a similar manner as described above with respect to various embodiments describe above.

(292) FIGS. **22A-22C** illustrate a switchable broadband waveplate lens **2200**, which may be similar to any of the broadband waveplate lenses that described above with respect to any one of FIGS. **16A**, **16B**, **19A**, **20A/20B** and **21**, in operation. FIGS. **22A**, **22B** and **22C** illustrate, respectively, a deactivated switchable broadband waveplate lens **2200** having a LHCP light beam incident thereon, a deactivated switchable broadband waveplate lens **2200** having a RHCP light beam incident thereon and an activated switchable broadband waveplate lens **2200** having a LHCP light beam **1162A** or RHCP light beam **1162B** incident thereon.

(293) Referring to FIG. **22A**, the switchable broadband waveplate lens **2200** comprises liquid crystals arranged as described above with respect to any one of FIGS. **16A**, **16B**, **19A**, **20A/20B** and **21** and is configured to be selectively switched between different lens states by electrically activating and deactivating. In operation, the switchable broadband waveplate lens **2200** is configured to diverge light according to optical power $-P$ and to converge light according to optical power P depending on the polarization, e.g., circular polarization, of the incident light **1162A**, **1162B**, according to various embodiments.

(294) Referring to FIG. **22A**, when deactivated, the switchable broadband waveplate lens **2200** is configured to diverge a LHCP light beam **1162A** incident thereon into a RHCP light beam **1166B** according to optical power $-P$. Conversely, referring to FIG. **22B**, when deactivated, e.g., electrically deactivated, the switchable broadband waveplate lens **2200** is configured to converge a RHCP light beam **1162B** incident thereon into a LHCP light beam **1166A** according to optical power P . On the other hand, referring to FIG. **22C**, when activated, e.g., electrically activated, the polarization of the circularly polarized light passing therethrough is preserved (not illustrated), and the RHCP light beam **1162B** and the LHCP light beam **1162A** incident thereon pass through the

switchable broadband waveplate lens **2200** without substantially being converged or diverged (i.e., optical power $P \sim 0$).

(295) Broadband Adaptive Waveplate Lens Assemblies Having Switchable Waveplate Lenses

(296) As described above with respect to FIG. **22A-22C**, a switchable broadband waveplate lens according to embodiments can be configured such that when deactivated, it can exert optical powers P or $-P$, depending on the polarization of the incident light, while when activated, it can exert substantially no optical power. The inventors have recognized that, by combining two or more switchable broadband waveplate lenses, many more lens states can be obtained for displaying virtual images at many different depths of focus. In the following, broadband adaptive lens assemblies comprising a plurality of switchable broadband waveplate lenses are described where, by configuring the broadband waveplate lenses to have different optical powers, 2.sup.n different optical power states can be obtained for an incident light having a given polarization.

(297) FIGS. **23A-23D** illustrate a broadband adaptive lens assembly **2300** comprising a first switchable broadband waveplate lens **2204** and a second switchable broadband waveplate lens **2208**, each of which may operate in a manner similar to the switchable waveplate lens described above with respect to FIGS. **22A-22C**. Each of the switchable broadband waveplate lenses **2204**, **2208** may be arranged in a similar manner as any of the broadband waveplate lenses that described above with respect to any one of FIGS. **16A**, **16B**, **19A**, **20A/20B** and **21**. FIGS. **23A**, **23B**, **23C** and **23D** illustrate combinations of states in which the first switchable broadband waveplate lens **2304**/second switchable broadband waveplate lens **2308** are deactivated/deactivated, deactivated/activated, activated/deactivated, and activated/activated, respectively.

(298) In the illustrated embodiment, the first switchable broadband waveplate lens **2304** is configured in a similar manner compared to the broadband waveplate lens **2200** described above with respect to FIGS. **22A-22C**. That is, when deactivated, the first switchable broadband waveplate lens **2304** is configured to diverge a LHCP light beam **1162A** incident thereon into a RHCP beam **1166B** according to an optical power $-P_1$. In addition, while not illustrated, when deactivated, the first switchable broadband waveplate lens **2304** is configured to converge a RHCP light beam incident thereon into a LHCP beam according to an optical power $+P_1$. On the other hand, when activated, the first switchable broadband waveplate lens **2304** is configured to substantially preserve the polarization of without substantially converging or diverging the circularly polarized light passing therethrough (i.e., optical power $P_1 \sim 0$).

(299) On the other hand, the second switchable broadband waveplate lens **2308** is configured to operate in an opposite manner compared to the broadband waveplate lens **2200** described above with respect to FIGS. **22A-22C**, with respect to the sign of the optical power exerted when deactivated. That is, when deactivated, the second switchable broadband waveplate lens **2308** is configured to converge a LHCP light beam **1162A** incident thereon into a RHCP beam **1166B** according to an optical power $+P_2$. In addition, while not illustrated, when deactivated, the second switchable broadband waveplate lens **2308** is configured to diverge a RHCP light beam incident thereon into a LHCP beam according to an optical power $-P_2$. On the other hand, when activated, the second switchable broadband waveplate lens **2308** is configured to substantially preserve the polarization of without substantially converging or diverging the circularly polarized light passing therethrough (i.e., optical power $P_2 \sim 0$).

(300) Referring to FIG. **23A**, the first switchable broadband waveplate lens **2304** is deactivated and diverges the LHCP light beam **1162A** incident thereon into a RHCP light beam **1166B** according to an optical power $-P_1$. Thereafter, the second switchable broadband waveplate lens **2208** is deactivated and diverges the RHCP light beam **1166B** incident thereon into a LHCP light beam **1170A** according to an optical power $-P_2$. In sum, the LHCP light beam **1162A** incident on the broadband adaptive lens assembly **2300** is diverged into the LHCP light beam **1170A** according to a net optical power of $-(P_1+P_2)$.

(301) Referring to FIG. **23B**, the first switchable broadband waveplate lens **2304** is deactivated and diverges the LHCP light beam **1162A** incident thereon into a RHCP light beam **1166B** according to optical power $-P_1$. Thereafter, the second switchable broadband waveplate lens **2208** is activated and preserves the polarization of the RHCP light beam **1166B** passing therethrough without substantially converging or further diverging. In sum, the LHCP light beam **1162A** incident on the broadband adaptive lens assembly **2300** is diverged into the RHCP light beam **1166BA** according to a net optical power of $-P_1$.

(302) Referring to FIG. **23C**, the first switchable broadband waveplate lens **2304** is activated and preserves the polarization of the LHCP light beam **1162A** passing therethrough without substantially converging or diverging. Thereafter, the second switchable broadband waveplate lens **2308** is deactivated and converges the LHCP light beam **1162A** incident thereon into a RHCP light beam **1170B** according to optical power $+P_2$. In sum, the LHCP light beam **1162B** incident on the broadband adaptive lens assembly **2300** is converged into the RHCP light beam **1170B** according to a net optical power of $+P_2$.

(303) Referring to FIG. **23D**, the first and second switchable broadband waveplate lenses **2304**, **2308** are both activated and preserve the polarization of the LHCP light beam **1162A** passing therethrough without substantially

converging or diverging. Thus, the LHCP light beam **1162B** incident on the broadband adaptive lens assembly **2300** emerges substantially unaffected as the LHCP light beam **1162B**.

(304) In summary, as illustrated in FIGS. **23A-23D**, by selectively switching the first and second switchable broadband waveplate lenses **2304**, **2308**, a broadband adaptive lens assembly **2300** can have four different optical power states of 0, $-P_1$, $+P_2$, and $-(P_1+P_2)$, according to embodiments.

(305) In addition, while not illustrated, in an analogous manner, when the incident light is a RHCP light beam, by selectively switching the first and second switchable broadband waveplate lenses **2304**, **2308**, the broadband adaptive lens assembly **2300** can have four different optical power states would be 0, $+P_1$, $-P_2$, and $+(P_1+P_2)$.

(306) In addition, while not illustrated, in some embodiments, the second switchable broadband waveplate lens **2308** can be configured to operate in the same manner as the first switchable broadband waveplate lens **2304** in terms of the dependence of the sign of optical power on the polarization of the incident light. In these embodiments, e.g., when the incident light is a LHCP light beam, the resulting four different optical power states would be 0, $-P_1$, $-P_2$, and $-(P_1-P_2)$.

(307) In addition, if the second switchable broadband waveplate lens **2308** is configured to operate in the same manner compared to the first broadband waveplate lens **2304** in terms of the dependence of the sign of optical power on the polarization of the incident light, when the incident light is a RHCP light beam, the resulting four different optical power states would be 0, P_1 , P_2 , and (P_1-P_2) .

(308) In FIGS. **23A-23D**, the illustrated broadband adaptive lens assembly **2300** is configured to achieve variable optical powers by independently switching lenses themselves (e.g., first and second switchable broadband waveplate lenses **2304**, **2308**). However, other embodiments are possible in which one or both of first and second switchable broadband waveplate lenses **2204**, **2208** are replaced by a combination of a passive waveplate lens and a switchable waveplate, similar to the combination of the passive waveplate lens **1154A** and switchable waveplate **1158**, as described above with respect to FIG. **12a**.

(309) FIG. **24A** illustrates of an integrated broadband adaptive lens assembly **2400** comprising a switchable layer of LC molecules similar to those described above with respect to any one of FIGS. **19A**, **20A/20B** and **21**, according to embodiments. The integrated broadband adaptive lens assembly **2400** includes a switchable LC layer **2304**, which can be similar to those described above with respect to any one of FIGS. **19A**, **20A/20B** and **21**, except, the switchable LC layer **2304** is interposed between a pair of passive waveplate lens stacks **2308**, **2312**. In a similar manner as described above with respect to FIG. **13F**, LC molecules are inserted into a gap formed between surfaces of the passive waveplate lens stacks **2308**, **2312** that face each other by spacers **1350**, which method of inserting is described elsewhere in the specification. The first passive waveplate lens stack **2308** includes a substrate **1312** on which a lower transparent electrode **1316** is formed, followed by an alignment layer **2302** and a lower polymerized LC (LCP) layer **2302-1**. Similarly, the second passive waveplate lens stack **2312** includes a substrate **1312** on which an upper transparent electrode **1320** is formed, followed by an alignment layer **2302** and an upper polymerized LC (LCP) layer **2302-2**.

(310) Each of the first and second passive waveplate lens stacks **2308**, **2312** serves as waveplate lenses as well as alignment layers for aligning LC molecules in the switchable LC layer **2304**. In a similar manner as described above with respect to FIGS. **13C**, **13F**, the LC molecules of the lower LCP layer **2302-1** closest to the gap and the LC molecules of the upper LCP layer **2302-2** closest to the gap are arranged such that the outermost LC molecules of the switchable LC layer **2304** are self-aligned. However, embodiments are not so limited and in some other embodiments, the outermost LC molecules of the switchable LC layer **2204** may be sufficiently aligned by the upper and/or lower alignment layers **2302** such that one of both of the first and second LCP layers **2302-1**, **2302-2** are omitted.

(311) In references to FIG. **24A** and various embodiments throughout the specification, a switchable LC layer, e.g., the switchable LC layer **2304** inserted into the gap has a thickness of about 1 μm -50 μm , 1-10 μm , 10-20 μm , 20-30 μm , 30-40 μm , 40-50 μm or a value within any range defined by these values. In addition, passive LC layers, e.g., the LCP layers **2302-1**, **2302-2**, can have a thickness of about 0.1 μm -50 μm , 0.1-1 μm , 1-10 μm , 10-20 μm , 20-30 μm , 30-40 μm , 40-50 μm or a value within any range defined by these values.

(312) In the illustrated embodiment, each of the LCP layers **2302-1**, **2302-2** can have LC molecules having a net twist angle of 30-90 degrees, 40-80 degrees, 50-70 degrees, or any angle within a range defined by any of these values, for instance about 60 degrees.

(313) In some embodiments, the switchable LC layer **2304** can be a single layer, similar to the LC layer described above with respect to FIG. **21**. However, embodiments are not so limited. For example, the switchable LC layer **2204** can include a plurality of LC layers, in a similar manner as described above with respect to FIGS. **20A/20B**.

(314) In operation, the integrated broadband adaptive lens assembly **2400** described herein with respect to FIG. **24A** share some characteristics that may be similar to the switchable waveplate **1300F** described above with respect to FIG. **13F**. For example, in both embodiments, a switchable waveplate element (the switchable TN LC

layer **1302** in FIG. **13F** and the switchable LC layer **2304** in FIG. **24A**) is interposed between a pair of passive waveplate elements (the plurality of TN LC layers **1302-1**, **1302-2** in FIG. **13F**, the polymerized LC (LCP) layers **2302-1**, **2302-2**). In both embodiments, the switchable waveplate element is configured to change the polarization of light passing therethrough into an orthogonally polarized light. Similarly, in both embodiments, the passive waveplate elements are similarly aligned by respective alignment layers such that when the switchable waveplate element is electrically activated to pass light therethrough without diffracting, the passive waveplate elements have cancelling effects on each other. On the other hand, when the switchable waveplate element is electrically deactivated to diffract light passing therethrough, the passive waveplate elements have complementary effects. In particular embodiments, when the passive waveplate elements have the same optical power, and when the switchable waveplate element is activated, the net optical power of the assembly is about zero and the polarization of light is unaltered. On the other hand, when the switchable waveplate element is deactivated, the net optical power of the assembly is a net sum of the powers of the switchable and passive waveplate elements having different signs. In the following, with respect to FIGS. **24B-24D**, one particular embodiment is described in which the passive waveplate elements are half waveplate lenses and the switchable waveplate element is also a half waveplate.

(315) FIGS. **24B-24D** illustrate the integrated broadband adaptive lens assembly **2400** in operation, which may be analogous to the adaptive lens assembly described above with respect to FIGS. **17A-17C** except, the switchable half waveplate in the middle is configured as a lens exerting an optical power.

(316) FIG. **24B** illustrates the integrated broadband adaptive lens assembly **2400** described above with respect to FIG. **24A** in terms of optical functionality. FIG. **24C** illustrates the integrated broadband adaptive lens assembly **2400A** (FIG. **24A**) in operation when the switchable waveplate lens **2304** of the adaptive lens assembly **2400** illustrated in FIG. **24B** is activated, whereas FIG. **24D** illustrates the switchable assembly **2400B** in operation when the switchable waveplate lens **2304** of the integrated broadband adaptive lens assembly **2400** illustrated in FIG. **24B** is deactivated. The integrated broadband adaptive lens assembly **2400** is configured to couple and to transmit therethrough the light outcoupled from the waveguide assembly **1012** (FIGS. **10**, **11A**, **11B**). The integrated broadband adaptive lens assembly **2400** comprises a first waveplate lens (L1/HWP1) **2308** corresponding to the passive waveplate lens stack **2308** (FIG. **24A**), e.g., a first half-waveplate lens, a second waveplate lens (L2/HWP2) **2312** corresponding to the passive waveplate lens stack **2312** (FIG. **24A**), e.g., a second half-waveplate lens, and a switchable half waveplate (L3/HWP3) **2304** corresponding to the switchable LC layer **2304** (FIG. **24A**).

(317) In FIGS. **24B-24D**, the L3/HWP **2304B** in a deactivated state (FIG. **24D**), the L1/HWP1 **2308** and the L2/HWP2 **2312** serve as passive half waveplate lenses configured to exert optical powers P_3 , P_1 and P_2 , respectively, and to flip the handedness of a circular polarized light passing therethrough from a first handedness (first HCP) to a second handedness (second HCP). On the other hand, the L3/HWP **2304A** in an activated state (FIG. **24C**) is configured to preserve the handedness of the circular polarized light passing therethrough.

(318) In addition, when deactivated, e.g., electrically deactivated using a voltage or a current signal provided by the switching circuit **1716**, the L3/HWP3 **2304B** (FIG. **24D**) serves as a half waveplate lens having an optical power P_3 . On the other hand, when activated using the switching circuit **1716**, e.g., by removing the voltage or the current signal, the L3/HWP3 **2304A** (FIG. **24C**) serves as transmitting medium for light without affecting the polarization or providing any substantial lensing effect.

(319) FIG. **24C** illustrates the integrated broadband adaptive lens assembly **2400B** in operation when the L3/HWP **2304A** is activated. The integrated broadband adaptive lens assembly **2400B** may correspond to the first adaptive lens assembly **1004** (FIG. **10**, on the world side) or the second adaptive lens assembly **1008** (FIG. **10**, on the user side). By way of example only, integrated broadband adaptive lens assembly **2400A** will be described as corresponding to the first adaptive lens assembly **1004** or the second adaptive lens assembly **1008**, as part of the display device **1000** (FIG. **10**) that is displaying the view of the real world to the user without displaying a virtual image. For example, the display device **1000** (FIG. **10**) may be used as ordinary eyeglasses or ordinary goggles. Each of the L1/HWP1 **2308** and L2/HWP2 **2312** may be configured to have a first lensing effect, e.g., diverging effect, on light having a first HCP, e.g., LHCP, passing therethrough. While not shown, each of the L1/HWP1 **2308** and L2/HWP2 **2312** may also be configured to have a second lensing effect opposite the first lensing effect, e.g., converging effect, on light having the opposite HCP, e.g., RHCP, passing therethrough.

(320) In the illustrated embodiment, the light beam **1720** may represent light beam from the world that is incident on either the first adaptive lens assembly **1004** (on the world side) or the second adaptive lens assembly **1008** (on the user side) while the display device **1000** (FIG. **10**) is being used as ordinary eyeglasses or goggles, without displaying virtual content. By way of example only, the light beam **1720** having a first HCP, e.g., LHCP, travels, e.g., in a positive z-direction, until the beam **1720** passes through the L1/HWP **2308**, to be transmitted therethrough and converted to a light beam **1724** having RHCP while diverging the light beam **1720** according to

a first optical power $-P_1$.

(321) Still referring to FIG. 24C, subsequently, because the L3/HWP3 2304A is activated, the light beam 1724 having RHCP transmits through the L3/HWP3 2304A without being substantially affected in terms of polarization or lensing effect, to be incident on the L2/HWP2 2312, as light beam 1728A having RHCP. As described above, when configured as an adaptive lens assembly on the user side (e.g., second adaptive lens assembly 1004 in FIG. 10), the L2/HWP2 2312 is configured similarly as the L1/HWP1 1704 (FIG. 17B), i.e., to convert the polarization and to diverge light having LHCP while converging light having RHCP. Thus, the light beam 1728A having RHCP is converted back to light beam 1732A having LHCP. Thus, when L3/HWP3 2304A is activated, the L1/HWP1 2308 and the L2/HWP2 2312 transmit light beams having opposite polarizations, such that the L1/HWP1 2308 and the L2/HWP2 2312 have opposite lensing effects on the light passing therethrough. That is, because the light beam 1728A incident on the L2/HWP2 2312 has RHCP, the light beam 1732A exiting the L2/HWP2 2312 is converged according to a second optical power $+P_2$, unlike the light beam 1724 exiting the L1/HWP1 1704 that is diverged according to a first optical power $-P_1$. Thereafter, upon exiting the adaptive lens assembly 1700A in the activated state, the light beam 1732A may be viewed by the eye.

(322) In some embodiments, when the L3/HWP3 2304A is activated, the first optical power $-P_1$ of L1/HWP1 2308 and the second optical power $+P_2$ of L2/HWP2 2312 may have substantially the same or matched magnitudes while having opposite signs. In these embodiments, the net optical power P_{net} of the integrated broadband adaptive lens assembly 2400, which may be approximately $-P_1+P_2$, may be substantially zero, such that the view of the world is substantially unaffected to the viewer. However, embodiments are not so limited, and the first and second optical powers $-P_1$, $+P_2$ may have different magnitudes, such that the net optical power P_{net} may have a nonzero value. For example, in some embodiments, the nonzero P_{net} may be equal to an eyeglass prescription of the user, thereby allowing for corrections to focusing errors (e.g., refractive focusing errors) of the eyes of the user.

(323) While in the illustrated embodiment, the incident light beam 1720 has LHCP, a similar outcome would result when the incident light beam 1720 has RHCP. That is, when the incident light beam 1720 has RHCP, the light beams 1724 and 1728A have LHCP, and unlike the illustrated embodiment, the light beams 1724 and 1728A are converged according to an optical power $+P_1$. Likewise, the light beam 1728A is diverged according to an optical power $-P_2$, such that the net optical power P_{net} may be $+P_1-P_2$, which may be substantially zero.

(324) It will be appreciated that the lensing effects of the L1/HWP1 2308 and L2/HWP2 2312 and the selectivity of the lensing effects to the polarization state of incident light beams described above with respect to FIG. 24C serves as but one example, and other configurations are possible. For example, while in FIG. 24C, the L1/HWP1 2408 and L2/HWP2 2312 is configured to diverge light having LHCP while converging light having RHCP, in other embodiments, the L1/HWP1 2308 and L2/HWP2 2312 may be configured to converge light having LHCP while diverging light having RHCP.

(325) In summary, in some embodiments, when the L3/HWP3 2304A is in an activated state, the exiting light beam 1732A has the same HCP as the incident light beam 1720, and may be substantially matched to the incident light beam 1720 in terms of the lens effect because of the compensation of the lens effects between P_1 of L1/HWP1 2308 and P_2 of L2/HWP2 2312. As a result, when the user is not viewing virtual content, the view of the world is relatively unaffected by the presence of the adaptive lens assemblies (1004, 1008 in FIGS. 10, 11A, 11B).

(326) FIG. 24D illustrates an example of the adaptive lens assembly of FIG. 24B in operation when the L3/HWP3 2304B is deactivated. The integrated broadband adaptive lens assembly 2400B may, e.g., correspond to the first adaptive lens assembly 1004 (on the world side) or the second adaptive lens assembly 1008 (on the user side). In the following, by way of example, integrated broadband adaptive lens assembly 2400B will be first described as being configured as the second adaptive lens assembly 1008 on the user side, as part of the display device (e.g., display device 1100A in FIG. 11A) that is outputting a virtual image to the user. Subsequently, integrated broadband adaptive lens assembly 2400B will be described as being configured as the first adaptive lens assembly 1004 on the world side, as part of the display device 1100B (FIG. 11B) that is simultaneously transmitting the view of the real world while outputting the virtual image to the user, to reduce or essentially eliminate distortion of the view of the real world resulting from the lens effects of the second adaptive lens assembly 1008.

(327) When configured as the second adaptive lens assembly 1008 on the user side (FIG. 11A), each of the L1/HWP1 2308 and L2/HWP2 2312 may be configured to diverge light having one of HCP, e.g., LHCP, passing therethrough. Each of the L1/HWP1 2308 and L2/HWP2 2312 may also be configured to converge light having the other HCP, e.g., RHCP, passing therethrough.

(328) As described above with respect to FIG. 11A, some of the light propagating in the x-direction, e.g., by total internal reflection, within the waveguide assembly 1012 may be redirected, or out-coupled, in the z-direction. The light out-coupled from the waveguide assembly 1012 (FIG. 11A) may be incident on the integrated broadband

adaptive lens assembly **2400B** as a circularly polarized light beam **1720** having LHCP. The light beam **1720** travels, e.g., in a positive z-direction, until the light beam **1720** is transmitted through the L1/HWP **2308** and converted into a light beam **1724** having RHCP while also being diverged according to the first optical power $-P_1$ of the L1/HWP **2308**.

(329) Subsequently, because the L3/HWP **2304B** is deactivated, the light beam **1724** having RHCP transmitting through the L3/HWP **2304B** is converted to light beam **1728B** having LHCP while also being diverged or converged according to third optical power $-/+P_3$. Subsequently, the light beam **1728B** having LHCP is incident on the L2/HWP **2312**. Because, unlike the light beam **1728A** illustrated above with respect to FIG. **24C**, the light beam **1728B** incident on the L2/HWP **2312** has LHCP, the L2/HWP **2312** further diverges the light beam **1728B** according to a second optical power $-P_2$ into light beam **1732B** having RHCP. Thus, unlike the configuration illustrated with respect to FIG. **24C**, the L1/HWP **2308**, the L2/HWP **2312** and L3/HWP **2304B** in FIG. **24D** can have additive lensing effects. Thereafter, upon exiting the adaptive lens assembly **1700B** in the deactivated state, the light beam **1732A** may be viewed by the eye.

(330) In some embodiments, the first optical power $-P_1$ of the L1/HWP **2308** and the second optical power $-P_2$ of the L2/HWP **2312** may both be negative (i.e., diverging) and may have substantially the same or matched magnitudes. In addition, the third optical power $-P_3$ of the L3/HWP **2304B** may be negative. In these embodiments, the net optical power P_{net} of the integrated broadband adaptive lens assembly **2400B**, may be approximately $-(P_1+P_2+P_3)$. However, embodiments are not so limited, and in some other embodiments, the third optical power $+P_3$ of the L3/HWP **2304B** may be positive. In these embodiments, the net optical power P_{net} of the integrated broadband adaptive lens assembly **2400B**, may be approximately $-(P_1+P_2)+P_3$. In addition, the first and second optical powers P_1 , P_2 may have different magnitudes.

(331) While in the illustrated embodiment, the incident light beam **1720** has LHCP, parallel outcome will result when the incident light beam **1720** has RHCP. That is, when the light beam **1720** has RHCP, unlike the illustrated embodiment, the resulting light beam **1732B** has LHCP and can be converged by L1/HWP **2308**, L2/HWP **2312** and L3/HWP **2304B** according to a net optical power $P_{net}=+(P_1+P_2+P_3)$.

(332) The lensing effects of the L1/HWP **2308**, L2/HWP **2312** and L3/HWP **2304B** and the dependence of the lensing effects on the polarization state of incident light beams described above with respect to FIG. **24D** serves as but one example, and other configurations are possible. For example, unlike in the illustrated embodiment, L1/HWP **2308**, L2/HWP **2312** and deactivated L3/HWP **2304B** may each be configured to converge light having LHCP while diverging light having RHCP.

(333) In the above, the integrated broadband adaptive lens assembly **2400B** in the deactivated state has been described when configured as the second adaptive lens assembly **1008** on the user side in the display device **1100A** described supra with respect to FIG. **11A**. As described supra with respect to FIG. **11B**, however, activating the second adaptive lens assembly **1008** to display virtual content to the user's eye **210**, without any compensating effect, may result in a defocusing or distortion of the view of the real world, which may be undesirable. Thus, it may be desirable to configure the first adaptive lens assembly **1004** on the world side to at least partially compensate or negate the lens effect of the second adaptive lens assembly **1008** when deactivated to display the virtual content.

(334) Referring back to FIG. **24D**, when configured as the first adaptive lens assembly **1004** (FIG. **11B**) on the world side to negate the lens effect of the second adaptive lens assembly **1008** (FIG. **11B**) on the user side, components of the adaptive lens assembly **1700B** may be configured similarly as described supra with respect to FIG. **11B**. That is, as light transmitted from the world **510** to the eye **210** traverses the first and second adaptive lens assemblies **1004**, **1008**, each may be configured as described above with respect to the integrated broadband adaptive lens assembly **2400B** described with respect to FIG. **24D**. In operation, as described above, the polarization of the light transmitted from the world through the first adaptive lens assembly **1004** is converted from a first polarization state to a second polarization state, e.g., from RHCP to LHCP. Subsequently, the polarization of the light transmitted through the second adaptive lens assembly **1008** is converted back from the second polarization state to the first polarization state, e.g., from LHCP to RHCP. Furthermore, as described above with respect to FIG. **11B**, the light transmitted from the world through the first adaptive lens assembly **1004** undergoes a first lens effect, e.g., converging effect, according to a first net optical power $P_{net1}=(P_1+P_2+P_3)$ having a first sign, e.g., positive sign. Subsequently, the light transmitted through the second adaptive lens assembly **1008** undergoes a second lens effect opposite to the first lens effect, e.g., diverging effect, according to a second net optical power $P_{net2}=-(P_1'+P_2'+P_3')$ having a second sign, e.g., negative sign, because the light incident on the second adaptive lens assembly **1008** has an opposite polarization as the light incident on the first adaptive lens assembly **1004**. When P_{net1} and P_{net2} have substantially similar magnitudes, the overall lens effect, approximated by $P=P_{net1}+P_{net2}$ may be substantially zero. As a result, when the user is viewing virtual content by activating the second lens assembly **1008**, as well as viewing real objects in the surrounding

world, the view of the world is relatively unaffected by the compensating effect of the first lens assembly **1004**. (335) In various embodiments, when deactivated, each of the first and second adaptive lens assemblies **1004**, **1008** may provide a net optical power (positive or negative) in the range between about ± 5.0 diopters and 0 diopters, ± 4.0 diopters and 0 diopters, ± 3.0 diopters and 0 diopters, ± 2.0 diopters and 0 diopters, ± 1.0 diopters and 0 diopters, including any range defined by these values, for instance ± 1.5 diopters.

(336) FIGS. 25A and 25B are graphs **2500A**, **2500B** illustrating transmission spectra corresponding to the integrated broadband adaptive lens assembly **2400** (FIGS. 24A/24B) in which the L3/HWP3 **2304** is deactivated (FIG. 24C) and activated (FIG. 24D), respectively. The simulations correspond to the integrated broadband adaptive lens assembly **2400** in which the L3/HWP3 **2304** comprises a switchable LC layer **2304** formed of an unpolymerized LC layer (e.g., the switchable LC layer **2304** in FIG. 23) of 10 μm in thickness and having Δn of 0.2, while each of L1/HWP1 **2308** and L2/HWP2 **2312** comprises a polymerized LC layer formed of polymerized twisted LC molecules having a twist angle of 60 degrees (e.g., upper and lower polymerized LC (LCP) layers **2302-1**, **2303-2** in FIG. 24A). As illustrated in the graph **2500A**, when the L3/HWP3 **2304A** is deactivated (FIG. 24C), the diffraction efficiency is high such that leakage light is low (about 20% maximum), indicating that the incident light efficiently diffracted by the integrated broadband adaptive lens assembly **2400A** without substantially leaking through between 400 nm and 800 nm. On the other hand, as illustrated in the graph **2500B**, when the L3/HWP3 **2304B** is activated (FIG. 24D), the diffraction efficiency is very the incident light is mostly transmitted without diffracting (about 100%), indicating that the incident light is largely undiffracted by the integrated broadband adaptive lens assembly **2400A** between 400 nm and 800 nm.

(337) Chromatic Aberration Reduction in Broadband Adaptive Lens Assemblies

(338) While having high efficiency over a wide range of wavelengths, some broadband adaptive lens assemblies can have focal lengths or optical powers that substantially depend on the wavelength of light, thereby leading to significant chromatic aberration. This is because, for relatively large focal lengths, the lens power is proportional to the corresponding wavelength. That is, dependence of optical power $P(\lambda)$ for waveplate lenses at different wavelengths can be approximated as $P(\lambda_{\text{sub.B}}) = P(\lambda_{\text{sub.G}}) \lambda_{\text{sub.B}} / \lambda_{\text{sub.G}}$ and $P(\lambda_{\text{sub.G}}) = P(\lambda_{\text{sub.R}}) \lambda_{\text{sub.G}} / \lambda_{\text{sub.R}}$, where B, G, and R correspond to a wavelength in the blue spectrum, a wavelength in the green spectrum and a wavelength in the red spectrum, respectively. Thus, there is a need to reduce chromatic aberration in broadband adaptive lens assemblies. In the following, methods of reducing chromatic aberration are described, according to embodiments.

(339) In the above, e.g., with respect to FIGS. 23A-23D, embodiments of broadband adaptive lens assemblies having two switchable broadband waveplate lenses have been disclosed, which leads to $2^{\text{sup.2}} = 4$ optical power states for a light having a circular polarization. By extension, a stack comprising more than two (N) switchable broadband waveplate lenses can be formed, having $2^{\text{sup.N}}$ optical power states. For example, for broadband adaptive lens assemblies having three switchable broadband waveplate lenses (N=3), 8 optical power states can be achieved. TABLE 1 illustrates calculated optical powers of a broadband adaptive assembly comprising three switchable broadband waveplate lenses, where each switchable broadband waveplate lens is similar to the switchable broadband waveplate lens described above, e.g., with respect to FIGS. 22A-22C.

(340) TABLE-US-00001

TABLE 1	STATE 1	STATE 2	STATE 3	STATE 4	STATE 5	STATE 6	STATE 7	STATE 8
COLOR	(1, 1, 1)	(1, 1, -1)	(1, -1, 1)	(1, -1, -1)	(-1, 1, 1)	(-1, 1, -1)	(-1, -1, 1)	(-1, -1, -1)
LENS 1 STATE (S1)	1	1	1	1	-1	-1	-1	-1
LENS 1 STATE (S2)	1	1	-1	-1	1	1	-1	-1
LENS 1 STATE (S3)	1	-1	1	-1	1	-1	1	-1
BLUE	2.14	-2.14	0.43	-0.43	1.29	-1.29	1.29	-1.29
GREEN	2.50	-2.50	0.50	-0.50	1.50	-1.50	1.50	-1.50
RED	3.01	-3.01	0.50	-0.50	1.81	-1.81	1.81	-1.81

(341) For a broadband adaptive assembly having three switchable broadband waveplate lenses, the net lens power can be expressed as $P_{\text{net}} = ((S_{\text{sub.1}} * P_{\text{sub.1}} + P_{\text{sub.2}}) * S_{\text{sub.2}} + P_{\text{sub.3}}) * S_{\text{sub.3}}$, where $P_{\text{sub.i}}$ and $S_{\text{sub.i}} = \pm 1$ ($i=1, 2, 3$) are the optical powers and power states of the individual switchable broadband waveplate lenses. For example, an activated state can be represented as $S = +1$ while a deactivated state can be represented as $S = -1$. Referring to TABLE 1, columns labeled State 1 to State 8 correspond to different lens states for each of the three lenses and rows BLUE, GREEN and RED represent calculated optical powers for at wavelengths of 450 nm, 525 nm and 632 nm, respectively, that are representative of blue, green and red colors of light. In the calculation, it has been assumed that only light having one polarization, e.g., first circular polarization reaches the eye and that the other is either recycled or reflected. For illustrative purposes, the optical powers of the three individual broadband waveplate lenses are calculated to be 0.5 D, 0.5 D, and 1.5 D at the green wavelength (525 nm). Based on TABLE 1, it can be seen that to obtain target net optical powers of 0.5 D, 1.5 D, and 2.5 D, lens states 3, 5 and 1 can be selected. However, it is observed that the net optical powers at blue and red wavelengths (450 nm and 632 nm) can cause significant chromatic aberration, e.g., as large as 0.51 D, for the target net optical power of 2.5 D for the red wavelength.

(342) The inventors have recognized, however, that chromatic aberration can be substantially reduced if, instead

of using one state to achieve one target net optical power for the three colors as illustrated in TABLE 1, more than one state is used to achieve a given target net optical power for the different colors. This approach is illustrated in TABLE 2.

(343) TABLE-US-00002

TABLE 2	STATE 1	STATE 2	STATE 3	STATE 4	STATE 5	STATE 6	STATE 7	STATE 8
COLOR	(1, 1, 1)	(1, 1, -1)	(1, -1, 1)	(1, -1, -1)	(-1, 1, 1)	(-1, 1, -1)	(-1, -1, 1)	(-1, -1, -1)
LENS 1 STATE (S1)	1	1	1	1	-1	-1	-1	-1
LENS 1 STATE (S2)	1	1	-1	-1	1	1	-1	-1
LENS 1 STATE (S3)	1	-1	1	-1	1	-1	1	-1
BLUE	2.31	-2.31	0.43	-0.43	1.53	-1.63	1.11	-1.11
GREEN	2.70	-2.70	0.50	-0.50	1.30	-1.90	1.30	-1.30
RED	3.25	-3.25	0.60	-0.60	2.29	-2.29	1.56	-1.56

(344) Referring to TABLE 2, by using more than one state to achieve a given target net optical power for different colors, and slightly different target lens powers, the chromatic aberration can be substantially reduced. Here, the optical powers of the three individual broadband waveplate lenses are 0.4 D, 0.7 D, and 1.6 D at the green wavelength (525 nm). Based on TABLE 2, it can be seen that to obtain target net optical power of 0.5 D, a single lens state 3 can be selected. However, to reduce chromatic aberration, for a target net optical power of 1.5 D, states 5 and 7 can be selected, and for a target net optical power of 2.5 D, states 1 and 5 can be selected. Compared to a chromatic aberration of 0.51 D for the target net optical power of 2.5 D shown in TABLE 1, by using more than one state for different colors, the chromatic aberration for the target net optical power of 2.5 D for the red wavelength can be reduced to 0.2.

(345) FIGS. 26A, 26B and 26C are graphs 2600A, 2600B and 2600C illustrating calculated target power net power versus actual net power for the blue, green and red wavelengths, respectively, illustrating the improved chromatic aberration performance achieved by using the method of using different lens states to for different color wavelengths for achieving target net optical powers, according to embodiments. In each of the graphs 2600A, 2600B and 2600C, solid black lines 2612, 2622 and 2632 represent target net optical power, dotted lines 2604, 2614 and 2624 represent calculated optical power when the method of using a single lens state to obtain a given optical power as described above with respect to TABLE 1 is used and solid gray lines 2608, 2618 and 2628 represent calculated optical power when the method of using multiple lens states to obtain a given optical power as described above with respect to TABLE 2 is used. As observed, the actual powers are closer to the target power when multiple lens states to obtain a given optical power are used.

(346) Fabrication of Broadband Waveplates and Waveplate Lenses Using Photoalignment

(347) FIGS. 27A-27C illustrate an example fabrication method of a broadband waveplate or a broadband waveplate lens. Referring to an intermediate structure 2700A of FIG. 27A, a transparent substrate 1312 is provided, on which an alignment layer 1302-0 is formed. The transparent substrate 1312 can include, e.g., a silicon dioxide, sapphire or any suitable transparent material. It will be understood that, while not shown, additional structures and layers may be present on the substrate 1312, leading up to the formation of the alignment layer 1302-0 according to various embodiments described herein. By way of example, when forming the switchable waveplate 1300F (FIG. 13F), prior to forming the alignment layer 1302-0, a first one of the transparent electrode layers 1316, 1320 may be present on the substrate 1312 prior to formation of the alignment layer 1302-0.

(348) In some embodiments, the alignment layer 1302-0 can be a photo-alignment layer on which, when LC molecules are deposited, the LC molecules may become oriented along a preferential direction, for example, due to anchoring energy exerted on the liquid crystal molecule by the photo-alignment layer. Examples of photo-alignment layers include polyimide, linear-polarization photopolymerizable polymer (LPP), azo-containing polymers, coumarine-containing polymers and cinnamate-containing polymers, to name a few, as well as other compounds described above with respect to FIGS. 13C, 13F.

(349) The alignment layer 1302-0 may be formed by dissolving precursors, e.g., monomers, in a suitable solvent and coating the substrate 1312 with the solution using a suitable process, e.g., spin coating, slot coating, doctor blade coating, spray coating and jet (inkjet) coating, among other deposition processes. The solvent can thereafter be removed from the coated solution. The alignment layer 1302-0 may also be cured, e.g., UV cured, e.g., with a polarizer, in preparation for the subsequent alignment of the LC molecules thereon.

(350) Referring to an intermediate structure 2700B of FIG. 27B, after coating the alignment layer 1302-0, the alignment layer 1302-0 is optically patterned or recorded. The optical patterning can be performed using a holographic two-beam exposure process (FIG. 28) or an optical replication process using a master lens and a one-beam exposure process (FIGS. 29A, 29B).

(351) Referring to an intermediate structure 2700C of FIG. 27C, after coating the alignment layer 1302-0, a LC layer 2704 is formed thereon. The LC layer 2704 may be formed by depositing on the alignment layer 1302-0 a reactive mesogen mixture (including, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) using a suitable process, including, e.g., spin coating, slot coating, doctor blade coating, spray coating and inkjet coating, among other deposition processes.

(352) When LC layer **2704** is integrated as part of a passive waveplate lens or a switchable waveplate, the LC layer **2704** may be cured, e.g., UV cured to photopolymerize the LC layer **2704**, such that the LC molecules can become fixedly oriented, as described above.

(353) In contrast, when LC layer **2704** is integrated as part of a switchable waveplate lens or a switchable waveplate, the LC layer **2704** may be further processed without polymerizing the LC layer **2704**, such that the LC molecules can reorient themselves in response to a switching signal as described above.

(354) Upon deposition, at least the bottommost LC molecules of the liquid crystal (LC) layer **2704** that are immediately above the alignment layer **1302-0** may be self-organized according to the configuration of the alignment layer **1302-0**, depending on various applications described herein. For example, when the LC layer **2704** forms part of a broadband waveplate lens, the alignment layer **1302-0** is configured such that the bottommost LC molecules have local orientations or directors that vary along a radius of the LC layer **2704** that in a radially outward direction from a central region as described, e.g., with respect to any one of FIGS. **16A**, **16B**, **19A**, as described supra. In addition, when the LC layer **2704** forms part of a broadband waveplate, the alignment layer **1302-0** is configured such that the bottommost LC molecules have local orientations or directors that are oriented with their long axes extending generally in a first lateral direction as described, e.g., with respect to FIGS. **13A**, **13C**. Still referring to FIG. **27C**, the LC layer **2704**, in some embodiments, as described elsewhere in the application, LC molecules above the bottommost LC molecules in the LC layer **2704** may be configured to be arranged differently from the bottommost LC molecules in the LC layer **2704**. For example, topmost LC molecules in the LC layer **2704** may be aligned differently by a second alignment layer formed on the LC layer **2704**. In addition, the LC molecules between the topmost LC molecules and the bottommost LC molecules can have a twist, as described with respect to various embodiments, including FIGS. **13C** and **20A/20B**.

(355) After depositing the LC layer **2704** and optionally polymerizing, the intermediate structure **2700C** may be further processed to form additional structures and/or layers, as described according to various embodiments described herein. By way of example, when forming the switchable waveplate **1300F** (FIG. **13F**), after forming the LC layer **2704**, the intermediate structure **2700C** may be further processed to form, e.g., a second alignment layer **1302-0** on the LC layer **2704** and a second one of the transparent electrode layers **1316**, **1320**. In addition, in some embodiments, additional LC layers may be formed on the LC layer **2704**, where bottommost LC molecules of a subsequent LC layer align to topmost LC molecules of a previous LC layer, as described in FIGS. **13F** and **24A**.

(356) FIG. **28** illustrates an example method of configuring an alignment layer as described above with respect to FIG. **27C** for aligning LC molecules in broadband waveplates or broadband waveplate lenses using a two-beam exposure process, sometimes referred to as polarization holography. While most conventional holography uses an intensity modulation, polarization holography involves a modulation of the polarization state as a result of interference of light with different polarization. Referring to an intermediate structure **2800** of FIG. **28**, the illustrated method includes forming an unpolymerized photo-alignment layer **1302-0** on the substrate **1312**, as described above with respect to FIG. **27A**. Thereafter, a plurality of coherent light beams having different polarizations, e.g., a RHCP light beam **2808** and a LHCP light beam **2804**, are directed to the alignment layer **1302-2**. In the illustrated embodiment, the RHCP light beam **2808** and the LHCP light beam **2804** are orthogonal circularly polarized light beams. One of the RHCP light beam **2808** and the LHCP light beam **2804**, which may be a recording beam, may be converging or diverging while other of the RHCP light beam **2808** and the LHCP light beam **2804**, which may be a reference beam, may be collimating. However, embodiments are not so limited. For example, the orthogonally polarized beams can include linear vertically polarized and linear horizontally polarized light beams or linear polarized light beams at +45 degrees. In some implementations, the two-beam exposure of the alignment layer **1302-0** to a polarization hologram may be performed using a UV laser (e.g., HeCd, 325 nm) with orthogonal circular polarizations. The typical recording dose may be around a few J.Math.cm.sup.-2 depending on liquid crystal materials and grating parameters (e.g., thickness d). Thereafter, a reactive mesogen mixture (including, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) is coated to be aligned according to the surface pattern formed by the two-beam exposure, as described above with respect to FIGS. **27A-27C**.

(357) FIGS. **29A-29B** illustrate an example method of configuring an alignment layer for aligning liquid crystal molecules in broadband waveplates or broadband waveplate lenses by fabricating a master waveplate or waveplate lens having a master alignment pattern of LC molecules, and using the master waveplate or waveplate lens to replicate the master alignment pattern of LC molecules onto a target alignment layer. Unlike the two-beam exposure method described above with respect to FIG. **28** in which an interference of two orthogonally polarized light beams is employed to directly configure the alignment layer, in the illustrated embodiment, a master waveplate lens and one polarized beam of light is used to create a similar polarization hologram in the near field. Thus, once a master lens having a master alignment pattern of LC molecules is fabricated, it can be used as a

template to fabricate multiple waveplates and waveplate lenses with a relatively simpler one beam exposure. (358) FIG. 29A illustrates a master waveplate or waveplate lens **2904**. The master waveplate or waveplate lens **2904** may be fabricated using, e.g., the processes described above with respect to FIGS. 27A-27C and 28, including forming an alignment layer using, e.g., a light interference pattern formed by a two-beam exposure process, and thereafter forming a reactive mesogen (RM) mixture layer (including, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) that self-aligns to the alignment layer, followed by blanket UV curing of the RM mixture layer to polymerize the LC molecules in the RM mixture layer. FIG. 29A further illustrates an operational view **2900A** of the master waveplate or waveplate lens **2904**, which is designed to have limited diffraction efficiency such that only a part of polarized incident light is diffracted while passing a part unaffected. For example, in the illustrated embodiment, the master waveplate or a waveplate lens **2904** is configured to diffract a part (e.g., 30-70%, 40%-60%, 45-55% or any value within these values, e.g., about 50%) of incident light **2908** having a first polarization e.g., RHCP, into diffracted light **2912** having a second polarization, e.g., LHCP, while passing part (e.g., 30-70%, 40%-60%, 45-55% or any value within these values, e.g., about 50%) of the incident light **2908** through the master lens **2904** without diffracting as leakage light **2916**, e.g., zero order leakage light, having the same first polarization, e.g., RHCP, as the incident light beam **2908**.

(359) FIG. 29B illustrates an example fabrication configuration **2900B** of the master lens **2904** fabricated and configured as described above with respect to FIG. 29A and an intermediate structure comprising an alignment layer **1302-0** for aligning LC molecules in broadband waveplates or broadband waveplate lenses. Referring to the fabrication configuration **2900B** of FIG. 29B, the illustrated intermediate structure includes an unpolymerized photo-alignment layer **1302-0** on the substrate **1312**, as described above with respect to FIG. 27A. The fabrication configuration **2900B** includes, disposed over the unpolymerized photo-alignment layer **1302-0** the master lens **2904**. An incident light beam **2908** having a first polarization, e.g., a RHCP, is directed to the alignment layer **1302-2**. As described above with respect to FIG. 29A, because the master waveplate or waveplate lens is designed to diffract only a part of the incident light, upon passing through the master waveplate or waveplate lens **2904**, two light beams having opposite polarizations are incident on the alignment layer **1302-0**. In effect, the two light beams incident on the alignment layer **1302-0** serve a similar effect of the two-beam exposure described above with respect to FIGS. 28A, 28B. In the illustrated example, transmitted through the master waveplate or waveplate lens **2904** and incident on the alignment layer **1302-0** are a diffracted light beam **2912** having a second polarization, e.g., LHCP, opposite the first polarization, e.g., RHCP, of the incident light beam **2908**, and a leakage light beam **2916** having the same first polarization, e.g., RHCP, as the incident light beam **2908**. Thus, in a similar manner as described above with respect to FIG. 28, the diffracted light beam **2912**, may be converging or diverging, may serve as a recording beam, while the leakage light beam **2916**, may serve as a reference beam. The interference of the diffracted light beam **2912** and the leakage light beam **2915** causes the alignment layer **1302-0**, in a similar manner as described above with respect to FIG. 20. Thereafter, a reactive mesogen mixture (including, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) may be coated to be aligned according to the surface pattern formed by the two-beam exposure, as described above with respect to FIGS. 27A-27C. Thus, advantageously, once the master lens **2904** is fabricated using a relatively complex two-beam exposure method described above with respect to FIG. 28, subsequent configuration of alignment layers is performed using a relatively simple one-beam exposure as described above with respect to FIG. 29B.

Advantageously, under some circumstances, the method illustrated with respect to FIG. 29B can be performed using fully coherent light sources, e.g., lasers, or partially coherent light sources such as UV lamps or light emitting diodes, etc., with less precise optics, less vibration control and looser alignment compared to the two-beam exposure method described above with respect to FIGS. 28A-28B.

(360) Fabrication of Broadband Waveplates and Waveplate Lenses Using Nanoimprint Alignment Layer

(361) As described throughout the application, in various embodiments, the LC molecules in an LC layer for broadband waveplates and waveplate lenses according to various embodiments can be aligned using an alignment layer, e.g., a photo alignment layer that can be configured using light. In other embodiments, the LC molecules can be aligned using patterned nanostructures. In the following with respect to FIGS. 30A and 30B, a method of aligning LC molecules using patterned nanostructures is described, followed by an example of patterned nanostructures suitable for serving as a waveplate lens is described with respect to FIG. 30C.

(362) FIGS. 30A and 30B illustrate cross-sectional views of intermediate structures **3000A**, **3000B**, respectively, at different stages of fabrication using a nanoimprint process, according to some embodiments.

(363) Referring to the intermediate structure **3000A** of FIG. 30A, a transparent substrate **1312** is provided, in a similar manner as described above with respect to various embodiments. A nanoimprint template (not shown), or a nanoimprint mold, which has predefined topological patterns configured to form an alignment pattern of LC molecules in the subsequently formed LC layer **2704** (FIG. 30B), e.g., at least the bottommost LC molecules in the LC layer **2704** closest to the substrate **1312**, is brought into contact with a blanket base polymer layer (not

shown). Subsequently, the template is pressed into the blanket base polymer layer, which can include a thermoplastic polymer under certain temperature, e.g., above the glass transition temperature of the blanket base polymer layer, thereby transferring the pattern of the template into the softened blanket base polymer layer to form an imprinted alignment layer **3004**. After being cooled down, the template is separated from the imprinted alignment layer **3004**, comprising an alignment pattern having predefined topological patterns configured to form an alignment pattern of LC molecules in the subsequently formed LC layer **2704** (FIG. **30B**). In some other approaches, after being pressed into the base polymer layer, the imprinted alignment layer **3004** is hardened by crosslinking under UV light.

(364) The imprinted alignment layer **3004** can include features that are sub-wavelength in dimensions. For example, the imprinted alignment layer **3004** can include features having dimensions (e.g., length, width and/or depth) of the order of a few nanometers, a few hundred nanometers and/or a few microns. As another example, the imprinted alignment layer **3004** can include features having a length greater than or equal to about 20 nm and less than or equal to about 100 nm. As yet another example, the imprinted alignment layer **3004** can include features having a width greater than or equal to about 20 nm and less than or equal to about 100 nm. As yet another example, the imprinted alignment layer **3004** can include features having a depth greater than or equal to about 10 nm and less than or equal to about 100 nm. In various embodiments, the length and/or width of the features can be greater than the depth of the features. However, in some embodiments, the depth can be approximately equal to the length and/or width of the features. The features of each domain of the imprinted alignment layer **3004** can be arranged to form complex geometric patterns within each domain in which the direction and/or the period between consecutive features changes along length scales of the order of a few nanometers, a few hundred nanometers and/or a few microns.

(365) While an example process of nanoimprinting was described for forming the nanoimprinted alignment layer **3004** with respect to FIG. **30A**, embodiments are not so limited. In other embodiments, the imprinted alignment layer **3004** can be fabricated using other patterning techniques including lithography and etch. In addition, while the imprinted alignment layer **3004** was described as being formed of a polymeric material, embodiments are not so limited and in various other embodiments, the imprinted alignment layer **3004** can comprise a dielectric material, e.g., silicon or a glass material.

(366) Referring to the intermediate structure **3000B** of FIG. **30B**, after forming the alignment layer **3004**, an unpolymerized LC layer **2704**, e.g., a layer of reactive mesogens, is deposited thereon, according to the deposition process described above with respect to FIGS. **27A-27C**. Without being bound to any theory, the imprinted alignment layer **3004** serves as an alignment layer that causes the LC molecules of the LC layer **2704** to align according to the pattern of the imprinted alignment layer **3004**. For example, the elongation direction of LC molecules within a domain may generally align in a direction parallel to the local elongation direction of the nanostructures in the imprinted alignment layer **3004**. Without being bound to any theory, the alignment of the LC molecules to the pattern of the imprinted alignment layer **3004** may be attributed to steric interactions with the liquid crystal molecules, and/or anchoring energy exerted on deposited LC molecules by the imprinted alignment layer **3004**.

(367) Still referring to the intermediate structure **3000B** of FIG. **30B**, the LC layer **2704** may be further processed according to different embodiments, as described above with respect to FIGS. **27A-27C**, including polymerization, further aligning LC molecules above the bottommost LC molecules and stacking multiple LC layers.

(368) FIG. **30C** illustrates a plan view of a nanoimprinted alignment layer **3004** that is fabricated according to the method described above with respect to FIGS. **30A-30B**. The imprinted alignment layer **3004** can serve as an alignment layer to form a layer of LC molecules having various lateral arrangements as described herein including, e.g., the arrangements described above with respect to FIGS. **13A**, **13C**, **16A**, **16B**, **19A**, among other arrangements.

(369) When LC layer resulting from the imprinted alignment layer **3004** forms part of a waveplate lens, the imprinted alignment layer **3004** according to various embodiments comprises a plurality of zones such as, for example, concentric zones **3008-1**, **3008-2**, . . . **3008-n** in the x-y plane, according to various embodiments. The imprinted nanostructures within each of the zones of the imprinted alignment layer **3004** are oriented along a particular orientation. The orientation of the molecules of the liquid crystal material in adjacent zones can be different. For example, the elongated directions or the local directors of the LC molecules in the various zones **3008-1**, **3008-2**, . . . **3008-n** can be successively rotated in a radial direction according to a function that depends on a power of the radius r^n from a central location, where n can vary from about 1 to 3 as described, for example, with respect to FIGS. **16A/16B** and FIG. **19**.

(370) The imprinted nanostructures and the resulting liquid crystal molecules can have elongation directions that are different in different zones **3008-1**, **3008-2**, . . . **3008-n**. For example, the elongation direction of imprinted

nanostructures in successive zones can be rotated in a clock-wise direction by an angle of about 18 degrees with respect each other. However, embodiments are not so limited and the relative rotation angle between successive zones can be less than 1 degree, between about 1 and 45 degrees, between about 1 and 18 degrees, or between about 18 and 45 degrees.

(371) Integration of Broadband Adaptive Lens Assemblies Having Broadband Waveplates and/or Waveplate Lenses

(372) According to various embodiments described above, e.g., broadband adaptive lens assemblies include integrated waveplates and waveplate lenses. In the following, methods of integrating the waveplates and waveplate lenses are described, according to embodiments. FIGS. 31A-31C illustrate an example method of fabricating a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals using a gap fill process. According to various embodiments, the method includes providing a lower stack including a first electrode layer on a first substrate and a first alignment layer formed on the first electrode layer, and includes providing an upper stack including a second electrode layer on a second substrate and a second alignment layer formed on the second electrode layer. The first and second stacks are then stacked into a single stack, such that the first and second alignment layers face each other, where spacers are formed between the lower and upper stacks to create a gap therebetween, which gap is subsequently filled with a liquid LC layer material. Referring to FIG. 31A, the method includes providing a substrate **1312** in a similar manner as described above, e.g., with respect to FIG. 27A, and thereafter forming on the substrate **1312** a first electrode layer **1320**, e.g., a transparent electrode layer, in a similar manner as described above, e.g., with respect to FIG. 27A. Thereafter, referring to FIG. 31B, a first alignment layer **1302-0** is formed on the substrate **1312**, thereby forming a lower stack **3100A**. The alignment layer **1302-2** can be a photo-alignment layer similar to that described above with respect to, e.g., FIGS. 27A-27C, **28** and **29**, or an imprinted alignment layer similar to that described above with respect to, e.g., FIGS. 30A-30C.

(373) Referring to FIG. 31C, in a similar manner as forming the lower stack **3100A**, an upper stack **3100B** is formed, comprising a second substrate **1312** on which a first electrode layer **1320**, e.g., a transparent electrode layer, and a second alignment layer **1302-0** is formed in a similar manner as described above with respect to forming the lower stack **3100A**, as described above with respect to FIG. 31B.

(374) In some embodiments, the first and second alignment layers **1302-0**, which may be photo-alignment layers or imprinted alignment layers, may be configured differently, as described above with respect to various embodiments, such that LC molecules immediately adjacent the first and second alignment layers **1302-0** align differently, e.g., align such that the elongation direction or the director direction of the LC molecules cross each other, e.g., at about 90 degrees.

(375) Still referring to FIGS. 31C, the upper and lower stacks **3100B**, **3100A** are subsequently stacked into a single stack, such that the first and second alignment layers **1302-0** face each other, where a gap **1302** is formed therebetween. The gap **1302** may be formed by spacers **1350** formed between the lower and upper stacks **3100A**, **3100B**.

(376) The spacers **1350** may be formed of a suitable material, e.g., silica beads having a diameter to produce the gap, whose distance defines the target thickness of the subsequently inserted LC material. In some implementations, the spacers **1350** in the form of silica beads, can be dispersed using a dry process over the surface of one or both of the upper and lower stacks **3100B**, **3100A**. In other implementations, the spacers **1350** in the form of silica beads can be mixed with adhesives and applied at the edges of the surfaces of one or both of the upper and lower stacks **3100B**, **3100A**. Thereafter, upper and lower stacks **3100B**, **3100A** are pressed against each other, until a final gap distance corresponding to the resulting thickness of the LC layer, is obtained. The gap distance can be monitored using a Fabry-Perot interference fringes.

(377) After forming the gap **1302**, a LC material is inserted into the gap **1302**. The inserted LC material can be a reactive mesogen mixture including, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants, as described above. The LC material may be inserted in the gap **1302** by capillary force. In some implementations, the insertion is performed under vacuum.

(378) The integration process described above with respect to FIGS. 31A-31C can be applied to any suitable embodiment described herein. For example, the method can be used to form a switchable broadband waveplate similar to that described above with respect to FIG. 13F, including a pair of broadband QWP **1324**, **1326** (FIG. 13F) separated by the switchable TN LC layer **1302** (FIG. 13F) inserted into the gap **1302** as described above. In these embodiments, the lower stack **3100A** includes a plurality of TN LC layers **1302-1**, **1302-2** (FIG. 13F) that are configured to serve as a QWP **1324** (FIG. 13B), and the upper stack **3100B** similarly includes a plurality of TN LC layers **1302-1**, **1302-2** (FIG. 13F) that are configured to serve as a QWP **1326** (FIG. 13B).

(379) To provide another example, the integration process described above with respect to FIGS. 31A-31C can be applied to form an integrated broadband adaptive lens assembly similar to that described above with respect to

FIG. 24A, including a pair of polymerized LC (LCP) layers **2302-1**, **2302-2** (FIG. 24A) separated by the switchable LC layer **2304** (FIG. 24A) inserted into the gap **1302** as described above to serve as the L3/HWP3 **2304** (FIGS. 23B-24D). In these embodiments, the lower stack **3100A** includes the lower polymerized LC (LCP) layer **2302-1** (FIG. 24A) that serves as a L1/HWP2 **2308** (FIGS. 24B-24D), and the upper stack **3100B** similarly includes the upper polymerized LC (LCP) layer **2302-2** (FIG. 24A) that serves as a L2/HWP2 **2312** (FIGS. 24B-24D).

(380) In the following, methods of integrating the waveplates and waveplate lenses are described, according to some other embodiments. In FIGS. 32A-32E, an example method of fabricating a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals employs a layer transfer process. In the layer transfer process, a LC layer is formed on a donor, a sacrificial or a carrier substrate, which may be flexible, and thereafter be transferred to a permanent substrate, which may be rigid. The LC layer formation on such a carrier substrate may allow for higher manufacturing throughput and/or higher manufacturing yield.

(381) FIG. 32A illustrates an intermediate structure **3200A** comprising a carrier substrate **3204**, which may be a suitable substrate having sufficient flexibility while having sufficient thermal stability for subsequent processes including polymerization of a LC layer, on which an alignment layer **1302-0** is formed. The alignment layer **1302-0** can be a photo-alignment layer formed and configured in a similar manner to those described above with respect to, e.g., FIGS. 27A-27C, **28** and **29**, or an imprinted alignment layer formed and configured in a manner similar to that described above with respect to, e.g., FIGS. 30A-30C.

(382) FIG. 32B illustrates an intermediate structure **3200B** comprising a release layer **3208** formed on the alignment layer **3208** and FIG. 32C illustrates an intermediate structure **3200C** comprising an LC layer **3212** formed on the release layer **3208**, thereby temporarily bonding the LC layer **3212** on the alignment layer **3208**.

The LC layer **3212** can be formed and configured in a similar manner as describe above with respect to FIG. 27C. (383) In some embodiments, the release layer **3208** comprises a thin surface layer formed by a surface treatment which weakens the adhesion strength between the LC layer **3212** and the alignment layer **1302-0** without substantially affecting the alignment properties of the alignment layer **3208**.

(384) In some embodiments, the release layer **3208** is a separate suitable thin film that is coated on the alignment layer **1302-0** which adheres with a higher strength to the layer below compared to the layer above the release layer **3208**. In the illustrated example, the release layer **3208** is formed between the alignment layer **1302-0** and a LC layer **3212** (FIG. 32C). Thus, according to some embodiments, release layer **3208** is formed of a suitable material that forms a stronger adhesion interface with the alignment layer compared the LC layer **3212**, such that it separates relatively easily from the LC layer **3212** compared to the alignment layer **3202-2**, upon application of a mechanical force

(385) In some embodiments, the release layer **3208** comprises a separate liquid-like curable adhesive coated on the release layer **3208** that can be cured in place when exposed to UV light for curing the LC layer **3212**. Curing converts the adhesive layer into a 3-D polymer network that is resistant to flow prior to separation. In some other embodiments, the release layer **3208** comprises a separate thermoplastic bonding material coated on the release layer **3203** rather than a curable adhesive material. Thermoplastic bonding material comprises thermoplastic polymers that do not crosslink or cure but instead reversibly soften and then re-harden to a glassy state when cooled to room temperature. At room temperature, the thermoplastic bonding material forms a stiff, resilient bond that allows subsequent processes without substantial deformation.

(386) FIG. 32D illustrates an intermediate structure **3200D** comprising a target substrate **1312**, which may be a permanent substrate, attached on the LC layer **3212** using a glue layer **3216**. The substrate **1312** may be any transparent substrate described elsewhere in the specification.

(387) FIG. 32E illustrates an intermediate structure **3200e** in which a target stack including the target substrate **1312** attached to the LC layer **3212** by the glue layer **3216** is separated from a carrier stack including the carrier substrate **3204**, the alignment layer **1302-0** and the release layer **3208**. In some embodiments, the separation is performed by a mechanical debonding, which is sometimes called peel separation. The separation occurs at an interface between the release layer **3208** and the LC layer **3212**, e.g., at the surface-treated release layer **3208** or one of different types of separately deposited release layers described above. The separate release layer **3208** or the surface treatment are designed to have sufficient adhesion at their interface that the bonded structure can survive normal in-process stresses but not be so strongly bonded that a strong force, which could break the thin device wafer, is needed to separate between the layers. The separation process can involve initiating a delamination between the release layer **3208** and the LC layer **3212** at an edge interface which propagates across the entire interface between the release layer **3208** and the LC layer **3212** using very low force to cause separation. The use of a thermoplastic bonding material and a low-surface-energy polymeric release layer, which can be a curable or thermoplastic composition, can be suitable for mechanical debonding. However, embodiments

are not so limited and in some other embodiments, separation involves laser debonding. These embodiments take advantage of the reversible softening behavior of thermoplastic bonding materials. In this mode, the bonded structure is heated above the softening temperature of the bonding material and an opposing shear force is applied to the device and carrier wafers, causing them to slowly slide past one another until the structure is separated. In yet some other embodiments, separation involves laser debonding. In these embodiments, a laser beam is used to ablate, or decomposes the release layer **3208** into gaseous byproducts and a small amount of carbonaceous residue, when irradiated through the carrier substrate **3204** with a scanning laser.

(388) Still referring to FIG. **32E**, the LC layer **2704** on the thus separated target stack can be further processed, may be further processed according to different embodiments, as described above with respect to FIGS. **27A-27C**, including polymerization, further aligning LC molecules above the bottommost LC molecules and stacking multiple LC layers.

(389) Formation of Broadband Adaptive Lens Assemblies on Selected Substrate Areas

(390) As described above with respect to various display devices, e.g., the wearable display device **1000** (FIG. **10**), broadband adaptive lens assemblies e.g., a pair of broadband adaptive lens assemblies **1004**, **1008** can be formed in an optical path **1016** that are interposed by a waveguide assembly **1012** for displaying both virtual and world images. However, in some implementations as a part of a wearable display device, the broadband adaptive lens assemblies may be formed on a portion of a substrate, e.g., on a portion of the waveguide assembly **1012** or a portion of a lens of goggles where they eye **210** is expected to view virtual images. In the following, various embodiments of forming broadband adaptive lens assemblies on selected substrate areas are described.

(391) FIG. **33** illustrates an example of a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals formed on a portion of a substrate **3300**. The substrate **3300** may represent, e.g., a portion of the waveguide assembly **1012** or a portion of a lens of the wearable display device **1000** (FIG. **10**) such as goggles or eyeglasses. The substrate **3300** comprises a lens area **3204** on which an optically active switchable broadband waveplate or switchable broadband waveplate lens is to be formed, and a clear region **3308** which is to remain free of the switchable broadband waveplate or the switchable broadband waveplate lens.

(392) FIG. **34** illustrates a first example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate **3400** by selectively coating or depositing a LC layer **3404** of the switchable broadband waveplate or the broadband waveplate lens on the lens area **3204** while preventing their formation in the clear area **3308**. The LC layer **3404** may be first coated in the form of a reactive mesogen mixture layer (including, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) as described above with respect to FIGS. **27A-27C**, followed by suitable subsequent processes, e.g., solvent evaporation and optional polymerization (for polymerized LC layers). In some embodiments, the selective coating can be performed using a suitable non-contact or contact process for depositing each layer, such as slot-die coating process, Gravure coating process or jet (ink-jet) coating process.

(393) FIGS. **35A-35C** illustrates an example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate by blanket coating a layer of liquid crystals and subtractively removing. Referring to FIG. **35A**, a reactive mesogen layer **3504** (which may include, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) is initially formed over an entire area of the substrate **3300** (FIG. **33**) in a similar manner as described above with respect to FIGS. **27A-27C**, followed by suitable subsequent processes, e.g., solvent evaporation. Thereafter, referring to FIG. **35B**, the reactive mesogen layer in the lens region **3304** is selectively cured using an optical mask or a reticle to block the UV light in the clear region **3308**, such that a polymerized LC layer **3508** is formed in the lens region **3304** while an uncured reactive mesogen layer **3512** remains in the clear area remains uncured (i.e., unpolymerized). Subsequently, referring to FIG. **35C**, the uncured reactive mesogen layer **3512** is selectively removed from the clear region **3308** using a suitable solvent, resulting in a selectively coated substrate **3500C** having the polymerized **3508** selectively remaining only in the lens region **3304**.

(394) FIG. **36A-36C** illustrates an example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate by using selective optical patterning of an alignment layer. Referring to an intermediate structure **3600A** illustrated in FIG. **36A**, after blanket-depositing a photo-alignment layer, a first optical mask or a reticle **3604** is used to cover the lens area **3304** while exposing the clear region **3308** to uniform linearly polarized light. Thereafter, referring to an intermediate structure **3600B** illustrated in FIG. **36B**, using a second optical mask or a reticle **3616** which may have an inverse mask pattern relative to the first optical mask **3604**, the lens area **3304** is exposed to a polarization hologram using, e.g., the two-beam exposure process using orthogonally polarized UV laser beams described above with respect to FIG. **29**, while the clear region **3308** is covered. As described above with respect to FIGS. **28** and **29A/29B**, an interference of light having orthogonal polarizations causes the alignment layer to

be configured to align the LC crystal molecules subsequently formed thereon according to a waveplate pattern or a waveplate lens pattern described with respect to various embodiments described above. Thus, as a result of the arrangements of the first and second optical masks **3604**, **3616**, the portion of the alignment layer **3616** (FIG. **36B**) in the lens area is selectively configured to align LC molecules subsequently formed thereon. In contrast, the portion of the alignment layer **3608** (FIG. **36A**) in the clear area is configured differently and lacks a waveplate pattern or a waveplate lens pattern described with respect to various embodiments described above. Thereafter, referring to an intermediate structure **3600C** illustrated in FIG. **36C**, reactive mesogen layer **3620** (which may include, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) is blanket deposited over an entire area of the substrate including the clear region and lens area, in a similar manner as described above with respect to FIGS. **27A-27C**, followed by suitable subsequent processes including, e.g., solvent evaporation and optional UV curing. In the resulting intermediate structure **3600C** in FIG. **36C**, while the entire surface area is covered with LC molecules, the LC molecules over the lens area are aligned according to the configuration of the underlying alignment layer and have systematic orientations to serve as a waveplate or a waveplate lens according to various embodiments described above, while the LC molecules over the clear region lack systematic orientations to serve as a waveplate or waveplate lens.

(395) FIG. **37A-37B** illustrates an example method of forming a switchable broadband waveplate comprising liquid crystals or a switchable broadband waveplate lens comprising liquid crystals on a portion of a substrate by using selective nanoimprinting an alignment layer. Referring to an intermediate structure **3700A** illustrated in FIG. **37A**, a nanoimprinted alignment layer is formed over the substrate surface, where the nanoimprinted alignment layer has different patterns between the lens area **3304** and the clear region **3308**. In particular, the portion of the nanoimprinted alignment layer **3708** (FIG. **37A**) in the lens area **3304** is configured to align the LC crystal molecules subsequently formed thereon according to a waveplate pattern or a waveplate lens pattern described with respect to various embodiments described above. In contrast, the portion of the lens alignment layer **3608** (FIG. **37A**) in the clear area is configured differently and lacks a waveplate pattern or a waveplate lens pattern described with respect to various embodiments described above. Subsequently, referring to an intermediate structure **3700B** illustrated in FIG. **37B**, a reactive mesogen layer **3712** (which may include, e.g., liquid crystal monomers, solvents, photoinitiators, and surfactants) may be blanket deposited over both the clear region **3308** and the lens area **3304**, in a similar manner as described above with respect to FIGS. **27A-27C**, followed by suitable subsequent processes including, e.g., solvent evaporation and optional UV curing. In the resulting intermediate structure **3600C**, while the entire surface area is covered with LC molecules, the LC molecules over the lens area **3304** are aligned according to the configuration of the underlying imprinted alignment layer and have systematic orientations to serve as a waveplate or a waveplate lens according to various embodiments described above, while the LC molecules formed over the clear region **3308** lack systematic orientations to serve as a waveplate or waveplate lens.

ADDITIONAL EXAMPLES

(396) In a 1.sup.st example, a display device comprises a waveguide configured to guide light in a lateral direction parallel to an output surface of the waveguide. The waveguide is further configured to outcouple the guided light through the output surface. The display device additionally comprises a broadband adaptive lens assembly configured to incouple and to diffract therethrough the outcoupled light from the waveguide. The broadband adaptive lens assembly comprises a first waveplate lens comprising a liquid crystal (LC) layer arranged such that the waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the first waveplate lens and configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm. The broadband adaptive lens assembly is configured to be selectively switched between a plurality of states having different optical powers.

(397) In a 2.sup.nd example, in the display device of the 1.sup.st example, the Δn of the first waveplate lens increases with increasing wavelength (λ) within the wavelength range.

(398) In a 3.sup.rd example, in the display device of the 1.sup.st example or the 2.sup.nd example, the broadband adaptive lens assembly comprises a plurality of liquid crystal layers, wherein each of the liquid crystal layer comprises liquid crystal molecules that are successively twisted in a layer normal direction.

(399) In a 4.sup.th example, in the display device of any one of 1.sup.st to 3.sup.rd examples, when the outcoupled light has a polarization, the broadband adaptive lens assembly is configured to be selectively switched between at least two lens states. The two lens states include a first lens state configured to converge or diverge the outcoupled light from the waveguide according to a first optical power and to alter a polarization of the outcoupled light, and a second lens state configured to converge or diverge the outcoupled light from the waveguide according to a second optical power without altering the polarization of the outcoupled light.

(400) In a 5.sup.th example, in the display device of any of the 1.sup.st to 4.sup.th examples, the broadband adaptive lens assembly further comprises a second waveplate lens comprising a second liquid crystal layer and a

switchable waveplate interposed between the first waveplate lens and the second waveplate lens, wherein the broadband adaptive lens assembly is configured to be selectively switched between the at least two states by electrically activating and deactivating the switchable waveplate.

(401) In a 6^{sup}.th example, in the display device of any of the 1^{sup}.st to 5^{sup}.th examples, the switchable waveplate comprises twisted nematic liquid crystals, and wherein electrically activating alters a degree twist of the twisted nematic liquid crystals across a thickness of the switchable waveplate.

(402) In a 7^{sup}.th example, in the display device any of the 1^{sup}.st to 5^{sup}.th examples, when the switchable waveplate is activated, the switchable waveplate serves as a half waveplate configured to invert the handedness of a circularly polarized light passing therethrough, while when the switchable waveplate is deactivated, the switchable waveplate is configured to conserve the handedness of the circularly polarized light passing therethrough.

(403) In an 8^{sup}.th example, in the display device of any of the 1^{sup}.st to 7^{sup}.th examples, each of the first and second waveplate lenses is configured to invert the handedness of the circularly polarized light passing therethrough, and wherein when the switchable waveplate is activated, the first and second waveplate lenses exert optical powers having opposite signs.

(404) In a 9^{sup}.th example, in the display device of any of the 1^{sup}.st to 7^{sup}.th examples, each of the first and second waveplate lenses is configured to invert the handedness of the circularly polarized light passing therethrough, and wherein when the switchable waveplate is deactivated, the first and second waveplate lenses exert optical powers having the same sign.

(405) In a 10^{sup}.th example, in the display device any of the 1^{sup}.st to 5^{sup}.th examples, when the switchable waveplate is deactivated, the broadband adaptive lens assembly has a net optical power having a magnitude that is proportional to a sum of magnitudes of optical powers of the first and second waveplate lenses, while when the switchable waveplate is in an activated state, the adaptive lens assembly has a net optical power having a magnitude that is proportional to a difference between magnitudes of optical powers the first and second waveplate lenses.

(406) In an 11^{sup}.th example, in the display device of any of the 1^{sup}.st to 10^{sup}.th examples, the first and second waveplate lenses have optical powers having about the same magnitude, such that when the switchable waveplate is electrically activated, the net optical power is about zero.

(407) In a 12^{sup}.th example, in the display device of any of the 1^{sup}.st to 11^{sup}.th examples, the first waveplate lens is electrically switchable, wherein the broadband adaptive lens assembly further comprises a second waveplate lens that is electrically switchable and comprises a second liquid crystal (LC) layer arranged such that the second waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the second waveplate lens and configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within the wavelength range, wherein the broadband adaptive lens assembly is configured to be selectively switched between the at least two states by switching one or both of the first and second waveplate lenses.

(408) In a 13^{sup}.th example, in the display device of any of the 1^{sup}.st to 12^{sup}.th examples, when activated, each of the first and second switchable waveplates serves as a half waveplate configured to invert the handedness of a circularly polarized light passing therethrough, while when deactivated, each of the first and second switchable waveplates is configured to conserve the handedness of the circularly polarized light passing therethrough.

(409) In a 14^{sup}.th example, in the display device of any of the 1^{sup}.st to 13^{sup}.th examples, each of the first and second waveplate lenses is configured to have optical powers having opposite signs when passing therethrough circularly polarized light having opposite polarizations.

(410) In a 15^{sup}.th example, in the display device of any of the 1^{sup}.st to 14^{sup}.th examples, the broadband adaptive lens assembly has a net optical power having a magnitude that is proportional to a sum of magnitudes of optical powers of the first and second waveplate lenses, such that by selectively activating one or both of the first and second waveplate lenses, for the given polarization of the outcoupled light, the broadband adaptive lens assembly is configured to be selectively switched between four states.

(411) In a 16^{sup}.th example, a broadband adaptive lens assembly for a display device comprises a first waveplate lens comprising a liquid crystal (LC) layer having LC molecules arranged such that the first waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the first waveplate lens and configured to diffract light at a diffraction efficiency greater than 90% within a wavelength in a range spanning at least 450 nm to 630 nm. The broadband adaptive lens assembly additionally comprises a switchable waveplate configured to be electrically activated and deactivated. The broadband adaptive lens assembly is configured to be selectively switched between at least two lens states. The two lens states include a first lens state configured to exert a first lens effect according to a first optical power and to alter a polarization of light passing through the broadband adaptive lens assembly, and a second lens state configured to exert a second lens effect according to a

second optical power and to preserve the polarization of the light passing through the broadband adaptive lens assembly.

(412) In a 17.sup.th example, in the broadband adaptive lens assembly of the 16.sup.th example, the switchable waveplate is a switchable half waveplate (HWP) configured to reverse the handedness of a circular polarized light when deactivated, while preserving the handedness of the circular polarized light when activated.

(413) In an 18.sup.th example, in the broadband adaptive lens assembly of the 16.sup.th example or the 17.sup.th example, the switchable HWP comprises a twisted nematic liquid crystal (TN LC) switch, wherein the TN LC switch comprises a switchable TN LC layer and is configured to reverse the polarization of a linearly polarized light when electrically deactivated, and to preserve the polarization of the linearly polarized light when electrically activated, and wherein the switchable TN LC layer comprises a plurality of elongated nematic LC molecules having twist angles that vary in a layer normal direction of the switchable TN LC layer.

(414) In a 19.sup.th example, in the broadband adaptive lens assembly of any of the 16.sup.th to 18.sup.th examples, the switchable TN LC switch comprises the switchable TN LC layer formed between an upper alignment layer and a lower alignment layer, wherein the upper alignment layer is configured to align a director of the elongated nematic LC molecules that are immediately adjacent to the upper alignment layer in a first lateral direction, and wherein the lower alignment layer is configured to align a director of the elongated nematic LC molecules that are immediately adjacent to the lower alignment layer in a second lateral direction crossing the first lateral direction.

(415) In a 20.sup.th example, in the broadband adaptive lens assembly of any of the 16.sup.th to 19.sup.th examples, one or both of the upper alignment layer and the lower alignment layer comprise a polymer layer comprising polyimide or polyamide.

(416) In a 21.sup.st example, in the broadband adaptive lens assembly of any of the 16.sup.th to 19.sup.th examples, one or both of the upper alignment layer and the lower alignment layer comprise patterned nanostructures.

(417) In a 22.sup.nd example, in the broadband adaptive lens assembly of any of the 16.sup.th to 21.sup.st examples, the one or both of the upper alignment layer and the lower alignment layer serve as an electrode or electrodes configured to apply an electric field across the switchable TN LC layer.

(418) In a 23.sup.rd example, in the broadband adaptive lens assembly of any of the 16.sup.th to 18.sup.th examples, the TN LC switch comprises a pair of interlaced first and second electrodes on one side of the switchable TN LC layer, wherein the TN LC switch is configured to be switched by applying an electric field between the pair of interlaced first and second electrodes.

(419) In a 24.sup.th example, in the broadband adaptive lens assembly of any of the 16.sup.th to 18.sup.th examples, the switchable half waveplate (HWP) comprises the TN LC switch interposed between a pair of broadband quarter waveplate (QWP) stacks.

(420) In a 25.sup.th example, in the broadband adaptive lens assembly of any of the 16.sup.th to 24.sup.th examples, each of the broadband QWP stacks comprises a plurality of directly stacked polymerized TN LC layers.

(421) In a 26.sup.th example, in the broadband adaptive lens assembly of any of the 16.sup.th to 18.sup.th examples, the switchable HWP comprises the switchable TN LC layer that is directly interposed between a pair of one or more polymerized TN LC layers, wherein the polymerized TN LC layers contacting the switchable TN LC layer serve as alignment layers for aligning the elongated nematic LC molecules of the switchable TN LC layer.

(422) In a 27.sup.th example, in the broadband adaptive lens assembly of any of the 16.sup.th to 25.sup.th examples, each of the directly stacked polymerized TN LC layers has a thickness across which LC molecules that are twisted by a twist angle, wherein adjacent ones of the directly stacked TN LC layers have different twist angles.

(423) In a 28.sup.th example, in the broadband adaptive lens assembly of any of the 16.sup.th to 27.sup.th examples, the broadband adaptive lens assembly further comprises a second waveplate lens comprising a second liquid crystal (LC) layer having LC molecules arranged such that the second waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the second waveplate lens and configured to diffract light at a diffraction efficiency greater than 90% within a wavelength in the range spanning at least 450 nm to 630 nm, wherein the switchable waveplate is interposed between the first waveplate lens and the second waveplate lens.29.

(424) In a 29.sup.th example, a broadband adaptive lens assembly for a display device comprises a first waveplate lens comprising a liquid crystal (LC) layer formed on a substrate. The LC layer has LC molecules that are arranged such that the first waveplate lens has birefringence (Δn) that varies in a radially outward direction from a central region of the LC layer and configured to diffract light at a diffraction efficiency greater than 90% within a wavelength range spanning at least 450 nm to 630 nm. Ones of the LC molecules that are the closest to the

substrate have generally the same orientation direction at different locations at the same radius from the central region. The broadband adaptive lens assembly is configured to be selectively switched between at least two lens states. A first lens state is configured to exert a first lens effect according to a first optical power and to alter a polarization of light passing through the broadband adaptive lens assembly. A second lens state is configured to exert a second lens effect according to a second optical power and to preserve the polarization of the light passing through the broadband adaptive lens assembly.

(425) In a 30.sup.th example, in the broadband adaptive lens assembly of the 29.sup.th example, the LC layer is arranged in a plurality of concentric zones, wherein each of the concentric zones has a range of radius within which the ones of the LC molecules that are the closest to the substrate have generally the same orientation direction.

(426) In a 31.sup.st example, in the broadband adaptive lens assembly of the 29.sup.th example or the 30.sup.th example, the ones of the LC molecules that are the closest to the substrate have azimuthal twist angles that vary with radius according to a mathematical function.

(427) In a 32.sup.nd example, in the broadband adaptive lens assembly of any of the 29.sup.th to 31.sup.st examples, the Δn of the LC layer increases with increasing wavelength within the wavelength range.

(428) In a 33.sup.rd example, in the broadband adaptive lens assembly of any of the 29.sup.th to 32.sup.nd examples, ones of the LC molecules that are within the same concentric zone have generally the same twist angle at different depths of the LC layer.

(429) In a 34.sup.th example, in the broadband adaptive lens assembly of any of the 29.sup.th to 33.sup.th examples, the first waveplate lens comprises a plurality of LC layers, wherein each of the LC layers comprises LC molecules that are successively twisted in a layer normal direction.

(430) In a 35.sup.th example, in the broadband adaptive lens assembly of any of the 29.sup.th to 34.sup.th examples, each of the LC layers has a thickness across which the LC molecules are twisted by a twist angle, wherein the LC layers have different twist angles.

(431) In a 36.sup.th example, in the broadband adaptive lens assembly of any of the 29.sup.th to 34.sup.th examples, adjacent ones of the LC layers forming an interface have opposite twist angles.

(432) In a 37.sup.th example, in the broadband adaptive lens assembly any of the 29.sup.th to 36.sup.th examples, the LC molecules of the adjacent ones of the LC layers at about the same depth from the interface have generally the same orientation.

(433) In a 38.sup.th example, in the broadband adaptive lens assembly any of the 29.sup.th to 37.sup.th examples, the first waveplate lens is interposed between a pair of transparent electrodes and configured to be electrically activated and deactivated by application of an electrical signal to the transparent electrodes.

(434) In a 39.sup.th example, the broadband adaptive lens assembly of any of the 29.sup.th to 38.sup.th examples further comprises a first passive waveplate lens having a first optical power (P1) and a second passive waveplate lens having a second optical power (P2), wherein the first waveplate lens is in contact with and interposed between the first and second passive waveplate lenses.

(435) In a 40.sup.th example, in the broadband adaptive lens assembly of any of the 29.sup.th to 39.sup.th examples, the first waveplate lens is configured to have a third optical power (P3) when deactivated and about zero optical power when activated.

(436) In a 41.sup.st example, in the broadband adaptive lens assembly of any of the 29.sup.th to 40.sup.th examples, each of the first and second passive waveplate lenses are half waveplates and the first waveplate lens is configured to be a half waveplate when deactivated.

(437) In a 42.sup.nd example, in the broadband adaptive lens assembly of any of the 29.sup.th to 39.sup.th examples, the first and second passive waveplate lenses and the first waveplate lens are integrated into a single stack.

(438) In a 43.sup.rd example. an integrated broadband adaptive lens assembly for a display device comprises a first electrode, a second electrode and a liquid crystal (LC) layer stack interposed between the first electrode and the second electrode. The LC layer stack comprises a switchable liquid crystal (LC) layer comprising unpolymerized LC molecules interposed between first and second polymerized LC layers each comprising polymerized LC molecules. LC molecules in the switchable LC layer that are adjacent to LC molecules in the first polymerized LC layer are generally elongated in a first direction. LC molecules in the switchable LC layer that are adjacent to LC molecules in the second polymerized LC layer are generally elongated in a second direction crossing the first direction. The switchable LC layer comprises LC molecules configured such that under a first voltage condition across the first and second electrodes, a polarization of incident light passing therethrough is preserved, while under a second voltage condition across the first and second electrodes, the polarization of the incident light passing therethrough is altered.

(439) In a 44.sup.th example, in the integrated broadband adaptive lens assembly of the 43.sup.rd example, the

switchable LC layer contacts at least one of the first and second polymerized LC layers.

(440) In a 45.sup.th example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd example or the 44.sup.th example, the switchable LC layer comprises twisted nematic LC molecules having a net twist angle at about 90 degrees, such that under the second voltage condition, the switchable LC layer converts linearly polarized light having a first polarization direction into linearly polarized light having a second polarization direction perpendicular to the first direction.

(441) In a 46.sup.th example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 45.sup.th examples, each of the first and second polymerized LC layers comprises twisted nematic LC molecules and serves as a quarter wave plate.

(442) In a 47.sup.th example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 46.sup.th examples, the LC layer stack comprises a plurality of polymerized LC layers formed on opposing sides of the switchable LC layer, wherein each of the polymerized LC layers forms an interface with an adjacent one of the polymerized LC layers, and wherein LC molecules adjacent to the interface in the each of the polymerized LC layers are generally elongated in the same direction as LC molecules adjacent to the interface in the adjacent one of the polymerized LC layers.

(443) In a 48.sup.th example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 47.sup.th examples, the LC molecules of each of the switchable LC layer and the first and second polymerized LC layers are arranged such that a birefringence (Δn) of the LC molecules varies in a radially outward direction from a central region.

(444) In a 49.sup.th example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 48.sup.th examples, the Δn increases with increasing wavelength (λ) within a wavelength range including at least 450 nm to 630 nm.

(445) In a 50.sup.th example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 48.sup.th examples, the LC layer stack comprises two switchable LC layers each comprising twisted nematic LC molecules that are successively twisted in a layer normal direction.

(446) In a 51.sup.st example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 50.sup.th examples, the twisted nematic LC molecules of the two switchable LC layers are symmetrically twisted with respect to an interface formed between the two switchable LC layers by a net angle between about 60 degrees and 80 degrees.

(447) In a 52.sup.nd example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 48.sup.th examples, wherein the switchable LC layer comprises twisted nematic LC molecules configured such that under the second voltage condition, the switchable LC layer serves as a half waveplate.

(448) In a 53.sup.rd example, in the integrated broadband adaptive lens assembly of any of the 43.sup.rd to 48.sup.th examples, each of the first and second polymerized LC layers comprises twisted nematic LC molecules and serves as a half wave plate.

(449) In a 54.sup.th example, a display device comprises a pair of adaptive lens assemblies in an optical path. Each of the adaptive lens assemblies comprises a corresponding switchable waveplate configured to diffract light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and to switch between first and second states to selectively alter a polarization state of light passing therethrough. The adaptive lens assemblies have optical powers with opposite signs.

(450) In a 55.sup.th example, in the display device of the 54.sup.th example, each of the adaptive lens assemblies has a respective optical power that is adjustable based upon a state of the switchable waveplate of the adaptive lens assembly.

(451) In a 56.sup.th example, the display device of the 54.sup.th example or the 55.sup.th example further comprises a controller configured such that, when a first optical power of a first one of the pair of adaptive lens assemblies is a first value, a second optical power of a second one of the pair of adaptive lens assemblies is correspondingly adjusted to a second value, such that the net optical power of the pair of adaptive lens assemblies remains at about a constant value.

(452) In a 57.sup.th example, in the display device of any of the 54.sup.th to 56.sup.th examples, the constant value is about 0 m.sup.-1.

(453) In a 58.sup.th example, in the display device of any of the 54.sup.th to 57.sup.th examples, each of the adaptive lens assemblies comprises first and second waveplate lenses interposed by the corresponding switchable waveplate of the lens assembly, wherein each of the waveplate lenses is configured to alter a polarization state of light passing therethrough.

(454) In a 59.sup.th example, in the display device of any of the 54.sup.th to 58.sup.th examples, the display device further comprises a waveguide assembly interposed between the pair of adaptive lens assemblies, wherein the waveguide assembly comprises a waveguide configured to outcouple light propagating therein into one of the

adaptive lens assemblies.

(455) In a 60.sup.th example, in the display device of any of the 54.sup.th to 59.sup.th examples, each of the adaptive lens assemblies comprises a plurality of waveplate lenses and a plurality of switchable waveplates, wherein the waveplate lenses and the switchable waveplates are alternately stacked.

(456) In a 61.sup.st example, in the display device of any of the 54.sup.th to 60.sup.th examples, different ones of the switchable waveplates and waveplate lenses have different optical powers.

(457) In a 62.sup.nd example, an adaptive lens assembly comprises one or more waveplate lenses and one or more switchable waveplates aligned in an optical path. Each of the one or more waveplate lenses is configured to diffract outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm, to alter a polarization state of light passing therethrough, to provide a first optical power for light having a first polarization, and to provide a second optical power for light having a second polarization. Each of the one or more switchable waveplates is configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and is selectively switchable between a first state configured to pass the light therethrough without altering a polarization state of the light, and a second state configured to alter the polarization state of the light passing therethrough.

(458) In a 63.sup.rd example, in the adaptive lens assembly of the 62.sup.nd example, one or both of the waveplate lenses and the switchable waveplates comprise liquid crystals.

(459) In a 64.sup.th example, in the adaptive lens assembly of the 62.sup.nd example or the 63.sup.rd example, each of the one or more switchable waveplates in the second state is a half waveplate configured to invert a handedness of circularly polarized light.

(460) In a 65.sup.th example, in the adaptive lens assembly of any of the 62.sup.nd to 64.sup.th examples, each of the switchable waveplates is interposed between a pair of the one or more waveplate lenses.

(461) In a 66.sup.th example, in the adaptive lens assembly any of the 62.sup.nd to 65.sup.th examples, the adaptive lens assembly comprises a plurality of the waveplate lenses and a plurality of the switchable waveplates, wherein the waveplate lenses and the switchable waveplate are alternately stacked.

(462) In a 67.sup.th example, a wearable augmented reality head-mountable display system comprises a light modulating system configured to output light to form an image, a head mountable frame, one or more waveguides attached to the frame and configured to receive the light from the light modulating system and a pair of adaptive lens assemblies, wherein the one or more waveguides are disposed between the adaptive lens assemblies. Each of the adaptive lens assemblies comprises one or more waveplate lenses configured to diffract outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and to provide a first optical power for light having a first polarization, and to provide a second optical power for light having a second polarization. Each of the adaptive lens assemblies additionally comprises one or more switchable waveplates in an optical path, wherein each of the one or more switchable waveplates is configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and to selectively alter a polarization state of light passing therethrough. The adaptive lens assemblies are configured to provide a respective optical power that is adjustable upon application of a respective electrical signal.

(463) In a 68.sup.th example, a method of integrating a broadband adaptive lens assembly comprises forming a lower stack and an upper stack. The lower stack comprises a first electrode layer formed on a first substrate, a first alignment layer formed on the first electrode layer, and a first polymerized LC layer on the first alignment layer. The upper stack comprises a second electrode layer formed on a second substrate, a second alignment layer formed on the second electrode, and a second polymerized LC layer on the second alignment layer. The method additionally includes, after forming the lower and upper stacks, stacking the upper stack and the lower stack such that the first and second polymerized LC layers face each other, wherein stacking comprises forming spacers to create a gap between the upper and lower stacks. The method additionally comprises filling the gap with unpolymerized LC molecules to form a switchable liquid crystal (LC) layer. Forming the switchable LC layer comprises self-aligning LC molecules in the switchable LC layer that are adjacent to LC molecules in the first polymerized LC layer to be generally elongated in a first direction, and self-aligning LC molecules in the switchable LC layer that are adjacent to LC molecules in the second polymerized LC layer to be generally elongated in a second direction crossing the first direction.

(464) In a 69.sup.th example, in the method of the 68.sup.th example, forming the switchable LC layer comprises configuring LC molecules of the switchable LC layer such that under a first voltage condition across the first and second electrode layers, a polarization of incident light passing therethrough is preserved, while under a second voltage condition across the first and second electrodes, the polarization of the incident light passing therethrough is altered.

(465) In a 70.sup.th example, in the method of the 68.sup.th example or the 69.sup.th example, the switchable LC

layer contacts at least one of the first and second polymerized LC layers.

(466) In a 71.sup.st example, in the method of any of the 68.sup.th to 70.sup.th examples, self-aligning the LC molecules in the switchable LC layer comprises forming twisted nematic LC molecules having a net twist angle at about 90 degrees, such that under the second voltage condition, the switchable LC layer converts linearly polarized light having a first polarization direction into linearly polarized light having a second polarization direction perpendicular to the first direction.

(467) In a 72.sup.nd example, in the method of any of the 68.sup.th to 71.sup.st examples, each of the first and second polymerized LC layers comprises twisted nematic LC molecules and serves as a quarter wave plate.

(468) In a 73.sup.rd example, in the method of any the 68.sup.th to 72.sup.nd examples, each of forming the lower stack and forming the upper stack comprises forming a plurality of polymerized LC layers. Each of the polymerized LC layers forms an interface with an adjacent one of the polymerized LC layers, wherein LC molecules adjacent to the interface in each of the polymerized LC layers are generally elongated in the same direction as LC molecules adjacent to the interface of the adjacent one of the polymerized LC layers.

(469) In a 74.sup.th example, in the method of any of the 68.sup.th to 73.sup.rd examples, the LC molecules of each of the switchable LC layer and the first and second polymerized LC layers are arranged such that a birefringence (Δn) of the LC molecules varies in a radially outward direction from a central region in each of the switchable LC layer and the first and second polymerized LC layers.

(470) In a 75.sup.th example, in the method of any of the 68.sup.th to 74.sup.th examples, the Δn increases with increasing wavelength (λ) within a wavelength range including at least 450 nm to 630 nm.

(471) In a 76.sup.th example, in the method of any of the 68.sup.th to 74.sup.th examples, the LC layer stack comprises two switchable LC layers each comprising twisted nematic LC molecules that are successively twisted in a layer normal direction.

(472) In a 77.sup.th example, the method of any of the 68.sup.th to 76.sup.th examples comprises forming two switchable LC layers that are symmetrically twisted with respect to an interface between the two switchable LC layers by a net angle between about 60 degrees and 80 degrees.

(473) In a 78.sup.th example, in the method of any of the 68.sup.th to 77.sup.th example, the switchable LC layer comprises twisted nematic LC molecules configured such that under the second voltage condition, the switchable LC layer serves as a half waveplate.

(474) In a 79.sup.th example, in the method of any of the 74.sup.th to 78.sup.th examples, each of the first and second polymerized LC layers comprises twisted nematic LC molecules and serves as a half wave plate.

(475) In an 80.sup.th example, a method of fabricating a broadband waveplate lens assembly comprises providing a transparent substrate and forming an alignment layer on the transparent substrate. The alignment layer is configured to cause liquid crystal (LC) molecules formed thereon to align according to a waveplate lens pattern. The method additionally includes forming a LC layer on the alignment layer. LC molecules of the LC layer that are immediately adjacent to the alignment layer align according to the waveplate lens pattern in which the LC molecules of the LC layer at a given radius from a central region of the waveplate lens pattern have elongation directions that are generally aligned in the same direction. The LC layer is configured to diffract light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm. The broadband adaptive lens assembly is configured to be selectively switched between a plurality of states having different optical powers.

(476) In an 81.sup.st example, in the method of the 80.sup.th example, forming the LC layer comprises arranging the LC molecules of the switchable LC layer such that a birefringence (Δn) of the LC layer increases with increasing wavelength (λ) within the wavelength range including at least 450 nm to 630 nm.

(477) In an 82.sup.nd example, the method of the 80.sup.th example or the 81.sup.st example further comprises forming a second LC layer on the LC layer, wherein each of the LC layer and the second LC layer comprises twisted nematic LC molecules that are successively twisted in a layer normal direction.

(478) In an 83.sup.rd example, in the method any of the 80.sup.th to 82.sup.nd examples, the twisted nematic LC molecules of the LC layer and the second LC layer are symmetrically twisted with respect to an interface formed by the LC layer and the second LC layer by a net angle between about 60 degrees and 80 degrees.

(479) In an 84.sup.th example, in the method of any of the 80.sup.th to 83.sup.rd examples, forming the alignment layer comprises configuring a photo-alignment layer by illuminating the alignment layer with two light beams having orthogonal polarizations.

(480) In an 85.sup.th example, in the method of any of the 80.sup.th to 84.sup.th examples, forming the alignment layer comprises configuring a photo-alignment layer by illuminating the alignment layer with a light beam partially diffracted through a master lens, wherein the master lens comprises LC crystals arranged according to the waveplate lens pattern.

(481) In an 86.sup.th example, in the method of any of the 80.sup.th to 85.sup.th examples, forming the alignment

layer comprises forming a nanoimprint alignment layer having nanostructures whose elongation direction has the same dependence on the radius from a central region of the waveplate lens as the elongation directions of the LC molecules of the LC layer.

(482) In an 87.sup.th example, in the method of any of the 80.sup.th to 86.sup.th examples, forming the alignment layer comprises forming a plurality of concentric zones, wherein each of the zones has nanostructures elongated in the same direction.

(483) In an 88.sup.th example, in the method of any of the 80.sup.th to 87.sup.th examples, the transparent substrate is a sacrificial carrier wafer, and the method additionally comprises forming a release layer interposed between the alignment layer and the LC layer. The method additionally comprises attaching a target substrate on the LC layer. The method further comprises transferring the LC layer to the transparent substrate by separating the LC layer from the release layer.

(484) In an 89.sup.th example, the method of any of the 80.sup.th to 88.sup.th examples comprises forming the broadband waveplate lens assembly on a selected portion of the transparent substrate smaller than a major surface area of the transparent substrate.

(485) In a 90.sup.th example, in the method any of the 80.sup.th to 89.sup.th examples, wherein forming the LC layer comprises selectively depositing the LC molecules over the selected portion.

(486) In a 91.sup.st example, in the method of any of the 80.sup.th 90.sup.th examples, forming the LC layer comprises blanket depositing an unpolymerized LC layer over the substrate, selectively exposing the unpolymerized LC layer over the selected portion to form a polymerized LC layer while leaving a portion of the unpolymerized LC layer unpolymerized, and removing the portion of the unpolymerized LC layer.

(487) In a 92.sup.nd example, in the method of any of the 80.sup.th to 91.sup.st examples, forming the alignment layer comprises blanket depositing an alignment layer over the transparent substrate and selectively configuring the LC molecules over the selected area to cause the LC molecules of the LC layer formed thereon to align according to the waveplate pattern, and wherein forming the LC layer comprises blanket depositing an unpolymerized LC layer over the substrate.

(488) In a 93.sup.rd example, in the method of any of the 80.sup.th to 92.sup.nd examples, forming the alignment layer comprises forming patterned nanostructures over the selected area to cause the LC molecules of the LC layer formed thereon to align according to the waveplate pattern, and wherein forming the LC layer comprises blanket depositing an unpolymerized LC layer over the substrate.

(489) In a 94.sup.th example, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of the user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The display system additionally comprises an eyepiece disposed on the frame. At least a portion of the eyepiece is transparent and disposed at a location in front of the user's eye when the user wears the head-mounted display such that the transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. The eyepiece is configured to emit light into the user's eye to display augmented reality image content to the user's vision field. At least one switchable lens assembly comprises a diffractive liquid crystal lens assembly comprising a twisted nematic switchable lens. The twisted nematic switchable lens comprises an active layer of twisted nematic liquid crystal, a first layer of polymerized liquid crystal adjacent to the active layer of twisted nematic liquid crystal, a second layer of polymerized liquid crystal adjacent to the active layer of twisted nematic liquid crystal. The active layer of twisted nematic liquid crystal disposed between the first and second layers of polymerized liquid crystal. The nematic switchable lens further comprises first and second electrodes disposed to applying an electric field to the active layer of twisted nematic liquid crystal. The first and second electrodes are on opposite sides of the active layer and the first and second layers of polymerized liquid crystal such that the active layer and the first and second layers of polymerized liquid crystal are disposed between the first and second electrodes. The head mounted display additionally comprises electronics configured to vary the optical power of the switchable lens by applying an electrical signal to the electrodes. The at least one switchable lens assembly is configured to transmit light from the environment in front of the user to the user's eye.

(490) In a 95.sup.th example, in the display device of the 94.sup.th example, the active layer comprises a diffractive lens.

(491) In a 96.sup.th example, in the display device of the 94.sup.th or 95.sup.th examples, the first and second layers of polymerized liquid crystal comprise diffractive lenses.

(492) In a 97.sup.th example, in the display device of any of the 94.sup.th to 96.sup.th examples, the first and second layers of polymerized liquid crystal are alignment layers for the active liquid crystal layer.

(493) In a 98.sup.th example, the display device of any of the 94.sup.th to 97.sup.th examples further comprises first and second alignment layers disposed adjacent first and second layers of polymerized liquid crystal, respectively. The first and second alignment layers are on respective sides of the first and second layers of

polymerized liquid crystal opposite the active layer.

(494) In a 99.sup.th example, in the display device of any of the 94.sup.th to 98.sup.th examples, at least the first electrodes comprise interdigitated electrodes.

(495) In a 100.sup.th example, in the display device of any of the 94.sup.th to 99.sup.th examples, wherein the at least one switchable lens assembly is configured to transmit light directed into the user's eye to display augmented reality image content to the user's vision field.

(496) In a 101.sup.st example, in the display device of any of the 94.sup.th to 100.sup.th examples, the at least one switchable lens assembly comprises two switchable lens assemblies, where one is disposed to transmit light directed into the user's eye to display augmented reality image content to the user's vision field and both are configured to transmit light from the environment in front of the user to the user's eye.

(497) In a 102.sup.nd example, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of the user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The system additionally comprises an eyepiece disposed on the frame. At least a portion of the eyepiece is transparent and disposed at a location in front of the user's eye when the user wears the head-mounted display such that the transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. The eyepiece is configured to emit light into the user's eye to display augmented reality image content to the user's vision field. The system additionally comprises at least one switchable lenses assembly comprising a diffractive liquid crystal lens assembly. The diffractive liquid crystal lens assembly comprises an active layer comprising a twisted nematic liquid crystal diffractive lens, a first and second retarders comprising polymerized liquid crystal on opposite sides of the active layer, and first and second electrodes disposed to applying an electric field to the active layer of twisted nematic liquid crystal, the first and second electrodes on opposite sides of the active layer. The system further comprises electronics configured to vary the optical power of the switchable lens by applying an electrical signal to the electrodes, wherein the at least one switchable lenses is configured to transmit light from the environment in front of the user to the user's eye.

(498) In a 103.sup.rd example, in the display device of the 102.sup.nd example, the first and second retarders on opposite sides of the active layer of twisted nematic liquid crystal are adjacent to the active layer of twisted nematic liquid crystal.

(499) In a 104.sup.th example, in the display device of the 102.sup.nd or 103.sup.rd examples, polymerized liquid crystal comprising the first and second retarders are alignment layers for the active liquid crystal layer.

(500) In a 105.sup.th example, in the display device of any of the 102.sup.nd to 104.sup.th examples, the first and second retarders are disposed between the first and second electrodes.

(501) In a 106.sup.th example, in the display device of any of the 102.sup.nd to 105.sup.th examples, the first and second retarders each comprise first and second quarter wave retarders comprising polymerized liquid crystal.

(502) In a 107.sup.th example, the display device of any of the 102.sup.nd to 106.sup.th examples further comprises first and second alignment layers disposed adjacent first and second retarders, respectively. The first and second alignment layers are on respective sides of the first and second retarders opposite the active layer.

(503) In a 108.sup.th example, in the display device of any of the 102.sup.nd to 107.sup.th examples, at least the first electrodes comprise interdigitated electrodes.

(504) In a 109.sup.th example, in the display device of any of the 102.sup.nd to 108.sup.th examples, the at least one switchable lens assembly is configured to transmit light directed into the user's eye to display augmented reality image content to the user's vision field.

(505) In a 110.sup.th example, in the display device of any of the 102.sup.nd to 109.sup.th examples, the at least one switchable lens assembly comprises two switchable lens assemblies, where one is disposed to transmit light directed into the user's eye to display augmented reality image content to the user's vision field and both are configured to transmit light from the environment in front of the user to the user's eye.

(506) In a 111.sup.th example, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of the user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The system additionally comprises an eyepiece disposed on the frame. At least a portion of the eyepiece is transparent and disposed at a location in front of the user's eye when the user wears the head-mounted display such that the transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. The eyepiece is configured to emit light into the user's eye to display augmented reality image content to the user's vision field. The system additionally includes at least one switchable lens assembly comprising a plurality of switchable lenses. Each of the switchable lenses has at least two states. The switchable lens assembly has different optical power for different states of the plurality of lenses. The switchable lens assembly has different optical power for different wavelengths when the plurality of lenses are set to a particular state. The system

further comprises electronics in communication with the switchable lenses to alter the state of the plurality of lenses. The electronics are configured to cause different lenses in the plurality of switchable lenses to be in different states for different wavelengths.

(507) In a 112.sup.th example, in the display device of the 111.sup.th example, when the plurality of switchable lenses are set in a first combination of states, the lens assembly produces a power for a red wavelength that is different than a power for a green wavelength, and when the plurality of switchable lenses are in a second combination of states, the lens assembly produces a power for a red wavelength that is different than a power for a green wavelength.

(508) In a 113.sup.th example, in the display device of the 111.sup.th example or the 112.sup.th example, when the plurality of switchable lenses is set in the second combination of states, the power for the red wavelength is closer to the power of the green wavelength when the plurality of lenses are set in the first combination of states than the power for the green wavelength when the plurality of lenses is set in the second combination of states.

(509) In a 114.sup.th example, in the display device of any of the 111.sup.th to 113.sup.th examples, the electronics is configured to set the plurality of lenses in the second state for the red wavelength and in the first state for the green wavelengths for a given power target.

(510) In a 115.sup.th example, a method of fabricating an eyepiece for augmented reality eyewear configured to direct light into a wearer's eye so as to present images to the wearer comprises providing a substrate. The method additionally comprises forming a first lens region on the substrate, where the first lens region comprises a transparent liquid crystal lens having optical power. The method further comprises providing a second region on the substrate that is transparent that does not have optical power.

(511) In a 116.sup.th example, in the method of the 115.sup.th example, the first lens region is surrounded by the second transparent region not having lens power.

(512) In a 117.sup.th example, in the method of the 115.sup.th or 116.sup.th examples, the second lens region includes at least 40% the area of the substrate.

(513) In a 118.sup.th example, in the method of the 115.sup.th or 116.sup.th examples, the second lens region includes at least 30% the area of the substrate.

(514) In a 119.sup.th example, in the method of 115.sup.th or 116.sup.th examples, the second lens region includes at least 20% the area of the substrate.

(515) In a 120.sup.th example, in the method of the 115.sup.th or 116.sup.th examples, the second lens region includes at least 10% the area of the substrate.

(516) In a 121.sup.st example, the method of any of the 115.sup.th to 120.sup.th examples comprises selectively depositing liquid crystal on the first lens region and not on the second transparent region.

(517) In a 122.sup.nd example, the method of any of the 115.sup.th to 121.sup.st examples further comprises depositing liquid crystal on the substrate.

(518) In a 123.sup.rd example, the method of the 122.sup.nd example further comprises selectively polymerizing the liquid crystal in the first lens region and not in the second transparent region.

(519) In a 124.sup.th example, the method of the 123.sup.rd example further comprises removing unpolymerized liquid crystal from the second transparent region.

(520) In a 125.sup.th example, the method of the 124.sup.th example further comprises providing a lens pattern on the first lens region and not on the second transparent region.

(521) In a 126.sup.th example, the method of the 125.sup.th example, further comprising providing a uniform alignment pattern on the second transparent region.

(522) In a 127.sup.th example, the method of the 126.sup.th example further comprises illuminating the second transparent region and not the first lens region with uniformly linearly polarized light.

(523) In a 128.sup.th example, the method of any of the 115.sup.th to 120.sup.th examples comprises nanoimprinting the first lens region and not the second transparent region with a lens pattern that will provide optical power when liquid crystal is deposited thereon and aligned therewith.

(524) In a 129.sup.th example, the method of the 128.sup.th example comprises nanoimprinting the second transparent region with a uniform imprint pattern that will not provide optical power when liquid crystal is deposited thereon.

(525) In a 130.sup.th example, the method of the 129.sup.th example further comprises depositing liquid crystal on the first lens region and the second transparent region.

(526) In a 131.sup.st example, the head mounted display system of the 111.sup.th example is configured to emit different color light into said user's eye at different times to display the augmented reality image content to the user's vision field.

(527) In a 132.sup.nd example, in the head mounted display system of the 131.sup.st example, said electronics is configured to cause different lenses in the plurality of switchable lenses to be in different states at different times

when said different color light is emitted into said user's eye to display the augmented reality image content to the user's vision field.

(528) In a 133.sup.rd example, a head mounted display system is configured to project light to an eye of a user to display augmented reality image content in a vision field of said user. The head-mounted display system comprises a frame configured to be supported on a head of the user. The display system additionally comprises an eyepiece disposed on the frame. At least a portion of said eyepiece is transparent and disposed at a location in front of the user's eye when the user wears said head-mounted display such that said transparent portion transmits light from the environment in front of the user to the user's eye to provide a view of the environment in front of the user. Said eyepiece is configured to emit light into said user's eye to display augmented reality image content to the user's vision field. The display system additionally comprises at least one switchable lens assembly comprising a plurality of switchable lenses, where each of said switchable lenses has at least two states. Variation in the states of said switchable lenses changes the state of the at least one switchable assembly. Said switchable lens assembly has different optical power for different states of said plurality of lenses. Said switchable lens assembly has different optical power for different wavelengths when the plurality of lenses are set to a particular state. The display system further comprises electronics in communication with said switchable lenses to alter the state of said plurality of lenses. Said display device is configured to emit a first color light into said user's eye at a first time and a second color light into said user's eye at a second time to display augmented reality image content to the user's vision field. Said electronics are configured to cause a least one of said lenses to be in different states at first and second times to provide images in said first and second colors.

(529) In a 134.sup.th example, in the display system of the 133.sup.rd example, when said plurality of switchable lenses are set in a first combination of states, said lens assembly produces a power for said first color that is different than a power for said second color, and when said plurality of switchable lenses are in a second combination of states, said lens assembly produces a power for said first color that is different than a power for said second color.

(530) In a 135.sup.th example, in the display system of the 134.sup.th example, when said plurality of switchable lenses is set in said second combination of states, said power for said first color is closer to the power of said second color when said plurality of lenses are set in said first combination of states than said power for said second color when said plurality of lenses is set in said second combination of states.

(531) In a 136.sup.th example, in the display system of the 135.sup.th example, the electronics is configured to set said plurality of lenses in said second state for said first color and in said first state for second wavelengths for a given power target.

(532) In a 137.sup.th example, in the display system of the 133.sup.rd example, when said plurality of switchable lenses are set in a first combination of states, said lens assembly produces a power for a red color that is different than a power for a green color, and when said plurality of switchable lenses are in a second combination of states, said lens assembly produces a power for a red color that is different than a power for a green color.

(533) In a 138.sup.th example, in the display system of the 137.sup.th example, when said plurality of switchable lenses is set in said second combination of states, said power for said red color is closer to the power of said green color when said plurality of lenses are set in said first combination of states than said power for said green color when said plurality of lenses is set in said second combination of states.

(534) In a 139.sup.th example, in the display system of the 138.sup.th example, the electronics is configured to set said plurality of lenses in said second state for said red wavelength and in said first state for green wavelengths for a given power target.

(535) In a 140.sup.th example, in the display system of the 133.sup.rd example, said electronics are configured to cause at least one of said lenses to be in different states at said first and second times to provide images in said first and second colors as if originating from the same depth.

(536) In a 141.sup.st example, in the display system of any of 130.sup.th to 140.sup.th examples, the plurality of switchable lenses comprises liquid crystals.

(537) In a 142.sup.nd example, in the display system of any of 130.sup.th to 141.sup.st examples, the plurality of switchable lenses comprises a waveplate lens comprising a liquid crystal (LC) layer.

(538) In a 143.sup.rd example, in the display system of any of 130.sup.th to 142.sup.nd examples, said electronics are configured to cause at least one of said lenses to be in different states at said first and second times to provide images in said first and second colors with reduced difference in focus of said images resulting from chromatic aberration as compared to said at least one of said lenses being in the same states at said first and second times.

(539) It will be appreciated that any one of the above examples may be combined with or used in the context of a wearable augmented reality head-mountable display system and/or a method of making or using the wearable augmented reality head-mountable display system. The head-mountable display may comprise one or more of the following: a light modulating system configured to output light to form an image, a head mountable frame, and/or

one or more waveguides attached to the frame and configured to receive the light from the light modulating system.

ADDITIONAL CONSIDERATIONS

(540) In the foregoing specification, the invention has been described with reference to specific embodiments thereof. It will, however, be evident that various modifications and changes may be made thereto without departing from the broader spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than restrictive sense.

(541) Indeed, it will be appreciated that the systems and methods of the disclosure each have several innovative aspects, no single one of which is solely responsible or required for the desirable attributes disclosed herein. The various features and processes described above may be used independently of one another, or may be combined in various ways. All possible combinations and subcombinations are intended to fall within the scope of this disclosure. For example, referring to FIG. 15, it will be appreciated that one or more adaptive lens assemblies **1504-1** to **1504-3** may be disposed between individual ones of the waveguides **1012a**, **1012b**, and/or **1012c**.

(542) Certain features that are described in this specification in the context of separate embodiments also may be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment also may be implemented in multiple embodiments separately or in any suitable subcombination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination may in some cases be excised from the combination, and the claimed combination may be directed to a subcombination or variation of a subcombination. No single feature or group of features is necessary or indispensable to each and every embodiment.

(543) It will be appreciated that conditional language used herein, such as, among others, “can,” “could,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. In addition, the articles “a,” “an,” and “the” as used in this application and the appended claims are to be construed to mean “one or more” or “at least one” unless specified otherwise. Similarly, while operations may be depicted in the drawings in a particular order, it is to be recognized that such operations need not be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Further, the drawings may schematically depict one more example processes in the form of a flowchart. However, other operations that are not depicted may be incorporated in the example methods and processes that are schematically illustrated. For example, one or more additional operations may be performed before, after, simultaneously, or between any of the illustrated operations. Additionally, the operations may be rearranged or reordered in other embodiments. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems may generally be integrated together in a single software product or packaged into multiple software products. Additionally, other embodiments are within the scope of the following claims. In some cases, the actions recited in the claims may be performed in a different order and still achieve desirable results.

(544) Accordingly, the claims are not intended to be limited to the embodiments shown herein, but are to be accorded the widest scope consistent with this disclosure, the principles and the novel features disclosed herein.

Claims

1. An integrated broadband adaptive lens assembly for a display, comprising: a first electrode, a second electrode and a liquid crystal (LC) layer stack interposed between the first electrode and the second electrode, wherein the LC layer stack comprises: a switchable liquid crystal (LC) layer comprising unpolymerized LC molecules interposed between first and second polymerized LC layers each comprising polymerized LC molecules, wherein LC molecules in the switchable LC layer that are adjacent to LC molecules in the first polymerized LC layer are generally elongated in a first direction, wherein LC molecules in the switchable LC layer that are adjacent to LC

- molecules in the second polymerized LC layer are generally elongated in a second direction crossing the first direction, wherein the switchable LC layer comprises LC molecules configured such that under a first voltage condition across the first and second electrodes, a polarization of incident light passing therethrough is preserved, while under a second voltage condition across the first and second electrodes, the polarization of the incident light passing therethrough is altered, and wherein the switchable LC layer directly contacts each of the first and second polymerized LC layers without an intervening alignment layer.
2. The integrated broadband adaptive lens assembly of claim 1, wherein the switchable LC layer comprises twisted nematic LC molecules having a net twist angle at about 90 degrees, such that under the second voltage condition, the switchable LC layer converts linearly polarized light having a first polarization direction into linearly polarized light having a second polarization direction perpendicular to the first direction.
 3. The integrated broadband adaptive lens assembly of claim 2, wherein each of the first and second polymerized LC layers comprises twisted nematic LC molecules and serves as a quarter wave plate.
 4. The integrated broadband adaptive lens assembly of claim 2, wherein the LC layer stack comprises a plurality of polymerized LC layers formed on opposing sides of the switchable LC layer, wherein each of the polymerized LC layers forms an interface with an adjacent one of the polymerized LC layers, and wherein LC molecules adjacent to the interface in the each of the polymerized LC layers are generally elongated in the same direction as LC molecules adjacent to the interface in the adjacent one of the polymerized LC layers.
 5. The integrated broadband adaptive lens assembly of claim 1, wherein the LC molecules of each of the switchable LC layer and the first and second polymerized LC layers are arranged such that a birefringence (Δn) of the LC molecules varies in a radially outward direction from a central region.
 6. The integrated broadband adaptive lens assembly of claim 5, wherein the Δn increases with increasing wavelength (λ) within a wavelength range including at least 450 nm to 630 nm.
 7. The integrated broadband adaptive lens assembly of claim 5, wherein the LC layer stack comprises two switchable LC layers each comprising twisted nematic LC molecules that are successively twisted in a layer normal direction.
 8. The integrated broadband adaptive lens assembly of claim 7, wherein the twisted nematic LC molecules of the two switchable LC layers are symmetrically twisted with respect to an interface formed between the two switchable LC layers by a net angle between about 60 degrees and 80 degrees.
 9. The integrated broadband adaptive lens assembly of claim 5, wherein the switchable LC layer comprises twisted nematic LC molecules configured such that under the second voltage condition, the switchable LC layer serves as a half waveplate.
 10. The integrated broadband adaptive lens assembly of claim 5, wherein each of the first and second polymerized LC layers comprises twisted nematic LC molecules and serves as a half wave plate.
 11. An adaptive lens assembly comprising: one or more waveplate lenses and one or more switchable waveplates aligned in a stack in an optical path, wherein each of the one or more waveplate lenses is configured to diffract outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm, to alter a polarization state of light passing therethrough, to provide a first optical power for light having a first polarization, and to provide a second optical power for light having a second polarization, wherein each of the one or more switchable waveplates is configured to diffract the outcoupled light at a diffraction efficiency greater than 90% within a wavelength range including at least 450 nm to 630 nm and is selectively switchable between: a first state configured to pass the light therethrough without altering a polarization state of the light; and a second state configured to alter the polarization state of the light passing therethrough, wherein each of the one or more waveplate lenses comprise polymerized LC layers each comprising polymerized LC molecules, wherein each of the one or more switchable waveplates comprise a switchable liquid crystal (LC) layer comprising unpolymerized LC molecules, and wherein the switchable LC layer of each of the one or more switchable waveplates directly contacts each of opposing polymerized LC layers of the waveplate lenses without an intervening alignment layer.
 12. The adaptive lens assembly of claim 11, wherein each of the one or more switchable waveplates in the second state is a half waveplate configured to invert a handedness of circularly polarized light.
 13. The adaptive lens assembly of claim 11, wherein each of the switchable waveplates is interposed between a pair of the one or more waveplate lenses.
 14. The adaptive lens assembly of claim 13, wherein the adaptive lens assembly comprises a plurality of the waveplate lenses and a plurality of the switchable waveplates, wherein the waveplate lenses and the switchable waveplates are alternatingly stacked.
-