

US Patent & Trademark Office

Patent Public Search | Text View

United States Reissue Patent

RE50565

Kind Code

E

Date of Reissued Patent

September 02, 2025

Inventor(s)

Hill; Garrett

Modular plasma reformer treatment system

Abstract

A modular plasma treatment system has interchangeable and easily accessible inner and outer electrodes that concentrically nest within an outer housing of one or more plasma reformers. The inner and outer electrodes have self-centering features that allow for blind-fitting of the interchangeable inner and outer electrodes during electrode replacement and maintenance. A plurality of reformers that generate different types of plasmas are preferably arranged serially to allow for a mixture of separate plasmas within the same reaction area and to increase utilization of short-lived radicals.

Inventors:	Hill; Garrett (Boulder, CO)
Applicant:	PlasmaFlow, LLC (Lafayette, CO)
Family ID:	65138070
Assignee:	Rimere, LLC (Lafayette, CO)
Appl. No.:	17/321940
Filed:	May 17, 2021

Related U.S. Application Data

division parent-doc US 17319466 20210513 PENDING child-doc US 17321940
reissue parent-doc US 16049795 20180730 US 10293303 20190521 child-doc US 17319466
reissue parent-doc US 16049795 20180730 GRANTED US 10293303 20190521 child-doc US 17321940
us-provisional-application US 62538177 20170728

Publication Classification

Int. Cl.: B01D53/32 (20060101); **B01D53/26** (20060101); **B01D53/92** (20060101); **F01N3/01** (20060101); **F01N3/037** (20060101); **F01N3/08** (20060101)

U.S. Cl.:

CPC B01D53/32 (20130101); **B01D53/261** (20130101); **B01D53/92** (20130101); **F01N3/01** (20130101); **F01N3/037** (20130101); **F01N3/0892** (20130101); B01D2257/404 (20130101); B01D2257/502 (20130101); B01D2257/702 (20130101); F01N2240/22 (20130101); F01N2240/28 (20130101); F01N2240/30 (20130101)

Field of Classification Search

CPC: F01N (3/01); F01N (3/0892); F01N (3/037); F01N (2240/22); F01N (2240/30); F01N (2240/28); B01D (53/32); B01D (53/92); B01D (53/261); B01D (2257/702); B01D (2257/502); B01D (2257/404); Y02T (10/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4585920	12/1985	Hoog et al.	N/A	N/A
4939424	12/1989	Kieser	N/A	N/A
5003152	12/1990	Matsuo	N/A	N/A
5010276	12/1990	Echizen	N/A	N/A
5887554	12/1998	Cohn et al.	N/A	N/A
5993761	12/1998	Czernichowski et al.	N/A	N/A
6158384	12/1999	Ye	N/A	N/A
6176078	12/2000	Balko	60/274	B01D 53/9431
6190507	12/2000	Whealton et al.	N/A	N/A
6994830	12/2005	Raybone et al.	N/A	N/A
7025939	12/2005	Hall et al.	N/A	N/A
8272206	12/2011	Lee	60/275	F01N 3/025
9095835	12/2014	Skoptsov et al.	N/A	N/A
9241396	12/2015	Foret	N/A	N/A
9393543	12/2015	Novoselov	N/A	N/A
9889218	12/2017	Morfill et al.	N/A	N/A
10183881	12/2018	Fraser et al.	N/A	N/A
10188119	12/2018	Foret	N/A	N/A
10308512	12/2018	Tanner et al.	N/A	N/A
10987735	12/2020	Hadidi et al.	N/A	N/A
2003/0140622	12/2002	Taylor, III	60/295	B01D 53/9431
2004/0134890	12/2003	Uhm et al.	N/A	N/A
2005/0208446	12/2004	Jayne	431/264	F02B 23/04
2005/0236374	12/2004	Blankenship	N/A	N/A
2005/0255011	12/2004	Greathouse	422/186.21	B01J 4/002
2006/0070372	12/2005	Lucas et al.	N/A	N/A
2006/0185352	12/2005	Twigg	N/A	N/A

2006/0201139	12/2005	Khadiya	60/286	F01N 3/035
2008/0276600	12/2007	Lee	60/286	F01N 3/025
2009/0129993	12/2008	Kim	422/168	B01D 53/944
2009/0165953	12/2008	Seeley et al.	N/A	N/A
2010/0135879	12/2009	Roesch	423/213.5	B01D 53/945
2011/0298376	12/2010	Kanegae et al.	N/A	N/A
2012/0073756	12/2011	Yamazawa	N/A	N/A
2014/0021035	12/2013	Rabinovich	204/170	B01J 19/08
2014/0191450	12/2013	Boyman	N/A	N/A
2014/0209243	12/2013	Kim	N/A	N/A
2016/0295676	12/2015	Patelli et al.	N/A	N/A
2017/0145890	12/2016	Hill et al.	N/A	N/A
2017/0145980	12/2016	Hill et al.	N/A	N/A
2018/0297122	12/2017	Hadidi et al.	N/A	N/A
2019/0046947	12/2018	Strom et al.	N/A	N/A
2019/0047865	12/2018	Zeller et al.	N/A	N/A
2019/0177835	12/2018	Baduvamanda et al.	N/A	N/A
2020/0312639	12/2019	Tom et al.	N/A	N/A
2020/0402768	12/2019	Stowell et al.	N/A	N/A
2022/0021290	12/2021	Mills	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101844744	12/2009	CN	N/A
205812485	12/2015	CN	N/A
102011077788	12/2011	DE	N/A
2274412	12/1993	GB	N/A
2282738	12/1994	GB	N/A
201186912	12/2010	JP	N/A
5648349	12/2013	JP	N/A
20160097438	12/2015	KR	N/A
WO00/43102	12/1999	WO	N/A
WO 0192694	12/2000	WO	N/A
WO-2011033927	12/2010	WO	N/A

Primary Examiner: Mckane; Elizabeth L

Attorney, Agent or Firm: Fish IP Law, LLP

Background/Summary

(1) This application claims the benefit of priority to U.S. provisional application No. 62/538,177 filed on Jul. 28, 2017. This and all other extrinsic references referenced herein are incorporated by reference in their entirety. .Iadd.More than one reissue application has been filed for U.S. Pat. No. 10,293,303. The reissue applications are application Ser. Nos. 17/319,466, 17/321,940, 17/324,846 and 17/324,933, all of which are divisional reissues of U.S. Pat. No. 10,293,303. .Iaddend.

FIELD OF THE INVENTION

(1) The field of the invention is plasma reformers.

BACKGROUND

(2) The background description includes information that may be useful in understanding the present invention. It is not an admission that any of the information provided herein is prior art or relevant to the presently claimed invention, or that any publication specifically or implicitly referenced is prior art.

(3) All publications herein are incorporated by reference to the same extent as if each individual publication or patent application were specifically and individually indicated to be incorporated by reference. Where a definition or use of a term in an incorporated reference is inconsistent or contrary to the definition of that term provided herein, the definition of that term provided herein applies and the definition of that term in the reference does not apply.

(4) Internal combustion engine exhaust streams contain substances that may be harmful to both humans and machinery if left untreated. However, known reformers to treat exhaust streams are difficult to maintain and don't allow easy access to the fundamental components of the reformers. For example, U.S. Pat. No. 6,994,830 to Raybone and U.S. Pat. No. 7,025,939 to Hall both teach reformers for plasma treatment of gases with electrodes supported within a dielectric tube enclosed in a single enclosure without any easily de-coupleable fasteners that allow service members to maintain the fundamental components. Maintenance of such reformers is time-consuming, expensive, and is sometimes impossible without seriously damaging the reformer walls itself—particularly when electrodes need to be maintained or replaced.

(5) Thus, there remains a need for a system and method for improved reformers that are easy to construct, maintain, and assemble/disassemble.

SUMMARY OF THE INVENTION

(6) The following description includes information that may be useful in understanding the present invention. It is not an admission that any of the information provided herein is prior art or relevant to the presently claimed invention, or that any publication specifically or implicitly referenced is prior art.

(7) The inventive subject matter provides apparatus, systems, and methods in which a modular plasma treatment system is built with interchangeable and easily accessible inner and outer electrodes that nest within an outer housing of one or more plasma reformers.

(8) As used herein, a “reformer” comprises a reactor having a reaction zone that reforms substances within an input stream from one substance to another substance—preferably another substance that is less harmful to humans and/or machinery. Exemplary substances to be reformed include, for example, particulate matter (PM), carbon monoxide (CO), nitrogen monoxide (NO), nitrogen dioxide, (NO₂) and hydrocarbons (HC) which can be altered to a different substance when introduced to a reactive molecular species, or Radical, created by the reformer such as hydrogen, ozone or oxygen. Such substances, if not passed through a reformer, could react with OH[•]—radicals created when water vapor inside of an exhaust stream is passed through plasma of sufficient energy, which can create harmful substances such as nitrous acid (HNO₂) or nitric acid (HNO₃).

(9) As used herein, an “input stream” comprises any stream of flowable substances capable of being directed through a conduit, such as a gas, a liquid, a gas having smaller liquid or solid particulate matter (e.g. less than 3 mm, 2 mm, 1 mm, 500 μm, 50 μm, 10 μm, or even 1 μm in length), or a liquid having a smaller solid particulate matter.

(10) As used herein, the term Hybrid Plasma Reformer (HPR), which is a reformer having 2 or more different types of plasmas in the same reaction zone. Typically such reformers are built serially downstream another reformer, for example a dielectric Barrier Discharge (DBD) reformer that generates DBD plasma placed downstream of a rotating glide-arc reformer that generates glide-arc plasma.

(11) Exemplary reformers comprise concentric inner electrodes within outer electrodes within an outer housing, which all nest within one another within the outer housing. The dimensions of the

outer housing, inner electrodes, and outer electrodes are preferably configured such that, when each is set in place within one another, the inner module does not “substantially move” when set in place. As used herein, “substantially move” comprises moving within 1 mm relative to one another in any direction when dropped on concrete from 5, 10, 20, or 30 cm. in the air. Coupling the inner electrodes and outer electrodes to a voltage transformer, for example a high voltage transformer that provides a voltage difference of at least 1,000, 10,000, 20,000, or even 30,000 volts between the inner electrodes and outer electrodes, the reformer generates plasma between the electrodes to form a reaction zone for streams sent through the reformer. Such voltage power transformers are preferably integrated with a feedthrough of the reformer to deliver power from the voltage power transformer directly to an inner electrode via the feedthrough.

(12) By providing interchangeable inner electrodes and outer electrodes capable of fungibly nesting within the outer housing of a reformer, the system allows for electrodes to be changed to accommodate different voltage differences for different types of plasmas, for example DBD plasma, glide-arc plasma, corona, inductively coupled, and microwave plasma. In some embodiments, the inner electrodes have dimensions that are substantially identical to one another and outer electrodes have dimensions that are substantially identical to one another such that any inner electrode could be fungible with any other inner electrode and any outer electrode can be fungible with any other outer electrode. In other embodiments, only the outer dimensions of the outer electrodes are substantially identical to one another such that the inner dimensions of the outer electrodes and the outer dimensions of the inner electrodes could be shaped differently to accommodate different reformer needs. As used herein, electrodes that are shaped “substantially identical” to one another could replace one another within a nested reformer embodiment without substantially moving relative to one another when set in place.

(13) In some embodiments, the inner dimensions of the outer housing and the outer dimensions of the outer electrodes, and/or the inner dimensions of the outer electrodes and outer dimensions of the inner electrodes, are shaped to have self-centering geometric features that center the inner portion with respect to the outer portion as they are set in place. Such self-centering geometric features could be, for example, a tapered inner wall that hugs the inner portion tighter as the inner portion is slid in place, or a tapered exterior cross-section of the inner portion that expands into a tighter fit as the inner portion is slid in place. Such sliding self-centering features allow for the nested electrodes to have a blind-mate connection (a connection that allows a person to center an electrode in place without need for precise orientation of threads, notches, or other pluralities of protrusions/recesses before sliding an electrode in place). Preferably, the inner apexes of the feedthrough and outlet flanges of the reformer fundamental components comprises self-centering features that allow for such a sliding blind mate between the concentric system components. As used herein, a “fundamental component” of a reformer comprises the outer housing, the inner electrode, and the outer electrode.

(14) Electrodes sized and shaped to generate different types of plasmas could have distinct internal or external geometric features from one another. For example, an outer electrode of a DBD reformer could comprise interior conductive projections that generate electric field gradients between points of the conductive projections. While such conductive projections could be within the interior of the electrode in any manner (e.g. 3-D printed, welded), in preferred embodiments the conductive projections could comprise conductive ferrous screws screwed into holes of the outer electrode. Preferably, the conductive projections comprise different dimensions (lengths, widths, heights, geometric patterns), to provide differing electric field gradients to precipitate particulate matter having different properties.

(15) In some embodiments, inner and/or outer surface features of the inner and outer electrode, and/or inner surface features of the outer housing, could be configured to alter the air pressure in various zones of the reformer to direct input streams in a cyclone motion to points of highest energy density within the excitation chamber. For example, perforations in the wall of the outer

electrode could get wider at near the reaction zone where the inner electrodes and outer electrodes are closest to one another, decreasing the air pressure within that zone to help direct the input stream towards the points with the highest energy density. Altering surface features of the fundamental components could be done in any manner known in the art to help direct input streams towards areas where they are the most effective.

(16) As previously stated, reformers are preferably disposed serially to one another such that a plurality of plasmas are present within the same reaction zone. This increases utilization of short-lived singlet oxygen radicals, and increases the control of the amount and type of reactive nitrogen and reactive oxygen radicals that are created. For example, when a stream is below the PM oxidation temperature of NO₂ (200-500c), ozone can be selectively produced and utilized for PM oxidation, or when the stream is above the temperature where ozone is incapable of being transported relatively long distances to the PM inside a Diesel Particulate Filter (DPF), NO₂ can be selectively produced. Exemplary serialized reformers include, for example, a DBD reformer placed downstream to a glide-arc reformer. The glide-arc reformer preferably has a rotating glide-arc that directs the output stream to rotate in a vortex such that heavier, particulate matter is directed towards the walls of the reaction zone, further ensuring that the heavier particulate matter is directed towards points of highest energy density inside the excitation chamber.

(17) Magnetic fields and/or microwaves could be directed towards the reaction chamber using magnets, electromagnetic resonators and/or microwave generators, respectively. In some embodiments, a magnetic field generator could target its magnetic field to be centrally targeted around co-axial electrodes that discharge into a plasma of any resonator of the system. In some embodiments, a particulate filter that expels the output stream of any reformer could be placed above the output stream to transfer waste heat from the output stream to an oxidant conduit.

(18) Preferably, air that is introduced to the reformer is pre-dried using an air driver that receives intake air from an air source, such as a blower or an on-board turbocharger, and outputs dried air that is introduced to an inlet of the initial reformer. Such air drivers could use a desiccant, such as silica gel, to remove water vapor from the intake air.

(19) Contemplated systems could be used to reform any stream comprising gaseous, liquid and particulate matter, for example an output exhaust of an internal combustion engine to generate CO₂ and H₂O, an oil well flare to generate synthesis gas (H₂ and CO), air and water treatment system to create ozone and NO_x, or an atmospheric control system for a spaceship to generate oxygen from CO₂.

(20) Various objects, features, aspects and advantages of the inventive subject matter will become more apparent from the following detailed description of preferred embodiments, along with the accompanying drawing figures in which like numerals represent like components.

(21) The following discussion provides many example embodiments of the inventive subject matter. Although each embodiment represents a single combination of inventive elements, the inventive subject matter is considered to include all possible combinations of the disclosed elements. Thus if one embodiment comprises elements A, B, and C, and a second embodiment comprises elements B and D, then the inventive subject matter is also considered to include other remaining combinations of A, B, C, or D, even if not explicitly disclosed.

Description

BRIEF DESCRIPTION OF THE DRAWING

(1) FIG. 1 is an exploded view of an exemplary reformer having a plurality of inner and outer electrodes.

(2) FIG. 2 is a cross-sectional view of an exemplary reformer.

(3) FIG. 3 is a cross-sectional view of an alternative exemplary reformer with alternative surface

features.

(4) FIG. 4 is a cross-sectional view of an exemplary reformer having a microwave generator.

(5) FIG. 5 shows an alternative view of the exploded view of the reformer of FIG. 1.

(6) FIG. 6 shows an exterior plan view of an exemplary reformer.

(7) FIG. 7 shows an exterior plan view of an alternative exemplary reformer.

(8) FIG. 8 shows a cross-sectional view of a plasma treatment system having two reformers serially coupled to one another.

(9) FIG. 9 shows a cross-sectional view of a plasma treatment system having two alternative reformers serially coupled to one another.

(10) FIG. 10 shows an exterior plan view of two reformers serially coupled to one another.

(11) FIG. 11 shows an exterior plan view of four reformers coupled to one another in parallel.

(12) FIG. 12 shows an exterior plan view of three reformers serially coupled to one another.

(13) FIG. 13 shows a cross-sectional view of a reformer having an outer housing having geometric features that adhere to the golden ratio.

(14) FIG. 14 shows a cross-sectional view of a reformer with the path and velocity of the gas stream highlighted.

(15) FIG. 15 shows a cross-sectional view of the reformer of FIG. 14.

(16) FIG. 16 shows a blown-up cross-sectional view of a portion of the reformer of FIG. 15.

(17) FIG. 17 shows an exterior plan view of a plasma exhaust system having a filter/catalyst system placed above the reformer.

(18) FIG. 18 shows an exterior plan view of an alternative plasma exhaust system having a filter/catalyst system placed above both the reformer and an internal combustion engine.

(19) FIG. 19-20 shows a plasma exhaust system having a transformer core coupled directly to a feed through of a reformer.

(20) FIG. 21-23 show different embodiments of plasma exhaust systems having air driers introducing dried air to the reformers and having waste heat exchange with the exhaust stream and filter/catalyst.

DETAILED DESCRIPTION

(21) In some embodiments, the numbers expressing quantities of ingredients, properties such as concentration, reaction conditions, and so forth, used to describe and claim certain embodiments of the invention are to be understood as being modified in some instances by the term “about.”

Accordingly, in some embodiments, the numerical parameters set forth in the written description and attached claims are approximations that can vary depending upon the desired properties sought to be obtained by a particular embodiment. In some embodiments, the numerical parameters should be construed in light of the number of reported significant digits and by applying ordinary rounding techniques. Notwithstanding that the numerical ranges and parameters setting forth the broad scope of some embodiments of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as practicable. The numerical values presented in some embodiments of the invention may contain certain errors necessarily resulting from the standard deviation found in their respective testing measurements.

(22) As used in the description herein and throughout the claims that follow, the meaning of “a,” “an,” and “the” includes plural reference unless the context clearly dictates otherwise. Also, as used in the description herein, the meaning of “in” includes “in” and “on” unless the context clearly dictates otherwise.

(23) As used herein, and unless the context dictates otherwise, the term “coupled to” is intended to include both direct coupling (in which two elements that are coupled to each other contact each other) and indirect coupling (in which at least one additional element is located between the two elements). Therefore, the terms “coupled to” and “coupled with” are used synonymously.

(24) Unless the context dictates the contrary, all ranges set forth herein should be interpreted as being inclusive of their endpoints, and open-ended ranges should be interpreted to include

commercially practical values. Similarly, all lists of values should be considered as inclusive of intermediate values unless the context indicates the contrary.

(25) The recitation of ranges of values herein is merely intended to serve as a shorthand method of referring individually to each separate value falling within the range. Unless otherwise indicated herein, each individual value is incorporated into the specification as if it were individually recited herein. All methods described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. The use of any and all examples, or exemplary language (e.g. “such as”) provided with respect to certain embodiments herein is intended merely to better illuminate the invention and does not pose a limitation on the scope of the invention otherwise claimed. No language in the specification should be construed as indicating any non-claimed element essential to the practice of the invention.

(26) Groupings of alternative elements or embodiments of the invention disclosed herein are not to be construed as limitations. Each group member can be referred to and claimed individually or in any combination with other members of the group or other elements found herein. One or more members of a group can be included in, or deleted from, a group for reasons of convenience and/or patentability. When any such inclusion or deletion occurs, the specification is herein deemed to contain the group as modified thus fulfilling the written description of all Markush groups used in the appended claims.

(27) One should appreciate that the disclosed techniques provide many advantageous technical effects including providing a modular system for ease of maintenance, accessibility, and replacement of fundamental components of plasma treatment systems. Blind-mate connections allow for the ease of placement of inner and outer electrodes without necessitating a high degree of accuracy when putting the electrodes in place. The system architecture guides streams towards the highest energy density zones within the plasma reaction zones for optimal paths through the reaction zones. Having a plurality of plasmas within the same reaction zone increases utilization of short-lived singlet oxygen radicals, and increases the control of the amount and type of reactive nitrogen and reactive oxygen radicals that are created. By combining two different plasmas, such as glide-arc plasmas and DBD plasmas for NO₂ production eliminates the need for extremely high voltages that are required with a DBD plasma reformer—which eliminates the need for more expensive insulators and electronics. Utilizing microwave excitation techniques for the production of radicals increases the precision below the threshold of unwanted chemical production. Utilizing ambient air as a feedstock to produce the preferred oxidants with an integrated dryer removes hydrogen and sulfur sources from the air stream, which minimizes the creation of unwanted acidic chemicals as a byproduct. By placing filters/catalyst systems above heat-creating reformers and other modules of the system, the system uses heat exchange to increase the production efficiency of the radicals.

(28) The inventive subject matter provides apparatus, systems, and methods in which a modular plasma treatment system is built with interchangeable and easily accessible inner and outer electrodes that nest within an outer housing of one or more plasma reformers.

(29) In FIG. 1, a reformer **100** has an outer housing **110**, outer electrode #1 **120**, outer electrode #2 **122**, inner electrode #1 **150**, and inner electrode #2 **152**. Outer housing **110** is a housing of a plasma reformer with inlet **116** for an input stream to enter reformer **100** and outlet **118** for an output stream to exit from. Outer housing **110** has a downstream inner housing press-fit mate **114** to an exhaust outlet (not shown) for ease of mating during maintenance. Other suitable coupling systems could be used to couple outlet **118** to an exhaust outlet (not shown), but preferably the coupling system does not require tools (e.g. press-fit systems, hand latches) or commonly available tools (e.g. a screwdriver, a wrench, a bolt socket) to ensure ease of maintenance. Outer housing flange **112** couples with upstream inner housing press-fit mate **130**, and is screwed in place with screws **142** via feedthrough flange **140** and feedthrough flange **162**. Again, other suitable coupling systems could be used such as those already named.

(30) Outer electrode #1 **120** and outer electrode #2 **122** have substantially identical geometric features to allow for either electrode to be interchanged within outer housing **110**. Similarly, inner electrode #1 and inner electrode #2 **152** also have substantially identical geometric features, making them geometrically fungible. Preferably, outer electrode #2 **122** comprises a different conductive material from outer electrode #1 **120**, and inner electrode #1 **150** comprises a different conductive material from inner electrode #2 **152**, giving them different conductive properties from one another, and making outer electrode #1 **120** and inner electrode #1 **150** more appropriate for generating a first plasma and outer electrode #2 **122** and inner electrode #2 **152** more appropriate for generating a second plasma different from the first plasma. In other embodiments, the inner geometric features of outer electrode #2 **122** may be different from the inner geometric features of outer electrode #1 **120**, such that the outer geometric features of inner electrode #2 **152** are made to mate with the inner geometric features of outer electrode #2 **122** and the outer geometric features of inner electrode #1 **150** are made to mate with the inner geometric features of outer electrode #1 **120**.

(31) In FIG. 2, a cross-sectional view of a reformer **200** is shown, having inlet **210**, outlet **220**, inner electrode **230**, outer electrode **240**, and outer housing **250**. Here, each of the fundamental components have self-centering geometric features that centers the nested fundamental components relative to one another as they are set in place. The inner chamber of outer housing **250** is shaped to taper inwards towards the outer walls of outer electrode **240** such that as outer electrode **240** advances within the inner chamber of outer housing **250**, outer electrode **240** self-centers in place and does not substantially move after being fully advanced within outer housing **250**. Similarly, the outer walls of inner electrode **230** are tapered near the base to self-center inner electrode **240** within outer electrode **240** as inner electrode **230** advances in place. This improves the ability for the electrodes to be set in place without need for a high degree of accuracy or even for the installer to be looking inside reformer **200** during installation.

(32) Inner electrode **230** comprises a conductor core **231** coupled to a voltage transformer (not shown) and has a stand off **232**, spark arrestor **233**, outer layer **234**, sleeve **235**, and insulating material **236**. In a preferred embodiment, stand off **232** comprises a quartz stand off, outer layer **234** comprises a quartz outer layer, and insulating material **236** comprises a thin layer of quartz wool surrounding the conductor core **231**, however, any insulating material, or materials, could be used depending on the needs of the reformer. Reaction zone **252** in between inner electrode **2130** and outer electrode **240** has a plurality of conductive projections **242** that each provide electric field gradients in between one another to precipitate particulate matter. Here, the conductive projections **242** are steel screw heads screwed into holes of outer electrode **240**, however conductive projections **242** could be implemented in a plurality of ways, such as 3-D printed or welded in place. Preferably, conductive projections **242** have different dimensions from one another. Here, conductive projections **242** only have a difference in height, such that screws of the same width but different length can provide different electric field gradients to precipitate particulate matter having different properties from one another.

(33) While reformer **200** shows electrodes with geometries most appropriate for a DBD plasma reformer, outer housing **250** could be utilized to generate other types of plasma by replacing the inner and outer electrodes set in place.

(34) In FIG. 3, reformer **300** has an inlet **310**, outlet **320**, inner electrode **330**, outer electrode **340**, and outer housing **350**. Here, inner electrode **330** has a slightly different geometry to inner electrode **220**, providing a self-centering outer wall that slowly tapers from the tip to the base of inner electrode **330**. Here, also, outer electrode **340** has a different geometry to outer electrode **240**, without the conductive projections of outer electrode **240**. While inner electrode **330** has a different geometry to inner electrode **230**, and outer electrode **340** has a different geometry to inner electrode **240**, both sets of electrodes could be installed interchangeably in outer housing **250** or outer housing **350**, allowing for functionally fungible electrode pairs if need be.

(35) Inner electrode **330** has a conductive core **331** that mates with sleeve **335**, and is coated with insulator **332** and **334** at its base, insulating spark arrestor **333** from external electromagnetic waves. Spark arrestor **333** allows for an overvoltage spark within a cavity, which is inside the feedthrough and not in the atmosphere or outside the reformer. Feedthrough flange **336** allows for a transformer (not shown) to provide voltage to core **331**, while housing flange **337** allows for the transformer to provide voltage to outer electrode **340**.

(36) While reformer **300** shows electrodes with geometries most appropriate for a rotating glide-arc plasma reformer, outer housing **350** could be utilized to generate other types of plasma by replacing the inner and outer electrodes set in place.

(37) In FIG. **4**, reformer **400** shows a reformer **400** having an inlet **410**, outlet **420**, inner electrode **430**, outer electrode **440**, and outer housing **450**. Here, outer housing **450** has a waveguide **462** that guides microwaves from microwave generator **460** towards the area where inlet **410** and outlet **420** are, exposing the stream to microwave transmissions as the stream enters and exits reformer **400**. Waveguide **462** is held in place by choke flange **464**.

(38) Inlet **410** guides the input stream in a circular vortex pattern about the outer reaction stream path into reaction zone **452** between outer electrode **440** and inner electrode **430**. As the vortex pattern approaches the best of inner electrode **430**, the densest portions of the stream flow along the inner wall of outer housing **250** and converge where the walls of outer electrode **440** and inner electrode **430** are the closest, and disperse in a vortex pattern within reaction zone **452** towards outlet **420**. Inner electrode **430** has a core **431** surrounded by insulator **432**, and feedthrough flange is conductively coupled to core **431** of inner electrode **430** while housing flange **434** is conductively coupled to outer electrode **440**.

(39) FIGS. **5-7** illustrate external views of exemplary reformer configurations. FIG. **5** shows an exploded view of reformer **500** having inner electrode **530**, outer electrode **540**, and outer housing **550**, where the inlet and outlet are disposed close to one another, providing an optimal geometry for a single microwave generator to be pointed at a section where both the inlet and outlet streams pass. FIG. **6** shows a reformer **600** having an inlet **610** and an outlet **620** disposed on opposing sides of the reformer, illustrating a path along the longest length of reformer **600**. FIG. **7** shows a reformer **700** having an inlet **710** and an outlet **720** on opposing sides of the reformer providing a more linear path optimal for chaining several reformers with one another.

(40) FIGS. **8-9** show cross-sectional views of exemplary chained reformers that each produce different plasmas. FIG. **8** shows a plasma treatment system **800** having an inlet **812** into a glide-arc plasma reformer **810** that feeds into a DBD plasma reformer **820** to an outlet **822**. FIG. **9** shows a plasma treatment system **900** having an inlet **912** into a glide-arc plasma reformer **910** with a microwave generator that feeds into a DBD plasma reformer **920** to an outlet **922**. Many alternative geometries and serial paths could be adapted from the designs presented.

(41) For example, FIGS. **10-12** show alternative plan views of chained reformers. FIG. **10** shows a plan view of a chained plasma treatment system **1000** having inlet **1010** and outlet **1020** which is a representation of the cross-sectional view of plasma treatment system **800**. FIG. **11** shows a plan view of a plasma treatment system **1110** with reformers coupled in parallel to one another, having a single inlet **1110** leading to four separate reformers, whose output streams are joined at outlet **1120**. FIG. **12** shows a plan view of a plasma treatment system **1200** with three reformers joined in serial having inlet **1210** and outlet **1220**. Plasma treatment system **1200** could be utilized with three different sets of electrodes to provide three different plasmas, or could have the same electrodes to utilize the same plasma in an extended reformation cycle.

(42) FIG. **13** shows a reformer **1300** having a golden ratio designed into the exterior walls of the outer housing, with dimension a for the first length of the first tapered section from the inlet to a second tapered section, dimension b for the second length of the second tapered section from the first tapered section to the base, and dimension c for the total length of both the first and second tapered sections. Experimental data has revealed that utilizing this golden ratio of a to b and b to c

provides for an advantageous stream path along the interior wall of reformer **1300**.

(43) FIGS. **14-16** illustrate a reformer **1400** having an input gas stream path whose velocity enters the point of the highest energy density inside the reaction zone at its highest velocity. FIG. **14** illustrates the input gas stream path as having a high density at the top as it enters the reformer, decreasing in density as it travels down to the base of the inner electrode. FIG. **15** shows how reformer **1400** has been divided into three pressure zones—low pressure zone **1510**, medium pressure zone **1520**, and high pressure zone **1530**, which forces the stream path to naturally flow and operate in the low pressure zone **1510**. Low pressure zone **1510** is generated by altering the surface features of either the outside electrode or the inner surface wall of the outer housing, or both. Here, the outside electrode in zone **1510** has perforations spaced a distance of 0.15" from one another, zone **1520** has perforations spaced a distance of 0.25" from one another, and zone **1530** has perforations spaced a distance of 0.4" from one another. Differing the spacing of the perforations varies the air pressure zones along the path of the input stream, focusing the input stream towards areas of highest energy density at its highest velocity. FIG. **16** shows how the highest density particulate matters hug the inner wall of the outer housing as the vortex travels down towards the base of the inner electrode. Both centrifugal motion and centripetal motion help to direct the stream accordingly.

(44) FIGS. **17-18** illustrate alternative embodiments where a filter substrate and/or catalyst, such as particulate filters (PF), diesel oxidation catalysts (DOC) or selective catalytic reduction (SCR) can be placed above either the reactor, an engine, or both to use heat exchange to increase the production efficiency of the radicals.

(45) FIGS. **19-20** illustrate a plasma treatment system **1900** having a transformer core **1910** that is directly coupled to the reformer to deliver high voltage power directly to the inner and outer electrode. Here, the transformer core **1910** is coupled directly to the inner and outer electrodes of the reformer with primary coil **1920** and secondary coil **1930** transforming the low voltage power input **2010** to high voltage power out. Ground from the high voltage power out **2020** is coupled directly to inner electrode **2030** while the positive VDD from high voltage power out **2020** is coupled directly to outer electrode **2030** to provide a voltage potential directly to the electrodes.

(46) FIGS. **21-23** illustrate additional configurations of plasma treatment systems. In FIG. **21**, plasma treatment system **2100** treats exhaust from an internal combustion engine **2110**. Air from an air source, such as from a blower or a turbocharger, is received by dryer **2120**, which minimizes the formation of unwanted acidic chemicals by removing hydrogen and sulfur sources from ambient air and sends a stream of dried air to reformers **2130**. Preferably, dryer **2120** uses a dessicant or some other dryer to remove hydrogen and sulfur sources from the air. Reformers **2130** generates plasma to form radicals, such as NO₂ radicals, O₁, and O₃, which combine with the exhaust stream from internal combustion engine **2110** to reform substances within the exhaust stream as well as to oxidize soot captured in Diesel Particulate Filter (DPF) **2140**. By placing DPF **2140** above heat-producing reformer **2130**, plasma treatment system **2100** uses heat exchange properties to increase the production efficiency of the radicals.

(47) In FIG. **22**, plasma treatment system **2200** receives an exhaust stream **2210** from a source (not shown), which is passed immediately through DPF **2220**. Air from an input air stream **2230** is passed through air dryer **2240** to be fed into reformers **2250**, which transmits radicals to the input stream **2210** before the input stream is filtered by DPF **2220**. Here, heat is recaptured in several areas: (1) heat is recaptured by the heat exchanger recapturing heat from the output exhaust stream from DPF **2220**, (2) heat is recaptured by placing DPF **2220** above reactors **2250**, and (3) heat is recaptured by placing the pipe from reactors **2250** to the input exhaust stream **2210** above DPF **2220**.

(48) In FIG. **23**, plasma treatment system **2300** receives an exhaust stream **2310** from a source (not shown), which is, again, passed through DPF **2220**. In this embodiment, output radicals from reformers **2230** are, again, introduced to exhaust stream **2310** prior to the exhaust stream being

filtered through DPF, reforming some of the particles from exhaust stream **2310**. Here, reformers **2330** are placed above DPF **2320**, helping to recapture and utilize some of the heat from DPF **2320**, as well as from the output exhaust stream from DPF **2320** via the heat exchanger running from air dryer **2340** to reformers **2330**.

(49) It should be apparent to those skilled in the art that many more modifications besides those already described are possible without departing from the inventive concepts herein. The inventive subject matter, therefore, is not to be restricted except in the scope of the appended claims. Moreover, in interpreting both the specification and the claims, all terms should be interpreted in the broadest possible manner consistent with the context. In particular, the terms “comprises” and “comprising” should be interpreted as referring to elements, components, or steps in a non-exclusive manner, indicating that the referenced elements, components, or steps may be present, or utilized, or combined with other elements, components, or steps that are not expressly referenced. Where the specification claims refers to at least one of something selected from the group consisting of A, B, C . . . and N, the text should be interpreted as requiring only one element from the group, not A plus N, or B plus N, etc.

Claims

.[.1. A modular plasma treatment system, comprising: a first outer housing of a first plasma reformer having a first exhaust inlet for receiving a first input gaseous stream and a first exhaust outlet for expelling a first output gaseous stream, wherein the first outer housing comprises a first housing inner receiving chamber; a first outer electrode sized and dimensioned to abut first housing portions of the first housing inner receiving chamber such that the first outer electrode does not substantially move when set in place within the first housing inner receiving chamber, wherein the first outer electrode comprises a first electrode inner receiving chamber; a second outer electrode sized and dimensioned to abut the first housing portions of the first housing inner receiving chamber such that the second outer electrode does not substantially move when set in place within the first housing inner receiving chamber, wherein the second outer electrode comprises a second electrode inner receiving chamber; a first inner electrode sized and dimensioned to abut first electrode portions of the first electrode inner receiving chamber such that the first inner electrode does not substantially move when set in place within the first electrode inner receiving chamber; and a second inner electrode sized and dimensioned to abut second electrode portions of the second electrode inner receiving chamber such that the second inner electrode does not substantially move when set in place within the second electrode inner receiving chamber..].

.[.2. The modular plasma treatment system of claim 1, wherein the first housing inner receiving chamber and a first exterior portion of the first outer electrode comprise self-centering features that center the first outer electrode with respect to the first outer housing as the first outer electrode is set in place within the first housing inner receiving chamber..].

.[.3. The modular plasma treatment system of claim 2, wherein the self-centering features comprise a tapered wall of the first housing inner receiving chamber that centers the first and second outer electrodes when either is set in place within the first housing inner receiving chamber..].

.[.4. The modular plasma treatment system of claim 2, wherein the self-centering features comprise a tapered exterior cross-section of the first outer electrode that widens against the first housing portions of the first housing inner receiving chamber as the first outer electrode is set in place within the first housing inner receiving chamber..].

.[.5. The modular plasma treatment system of claim 1, wherein the first electrode inner receiving chamber and a first exterior portion of the first inner electrode comprise self-centering features that center the first inner electrode with respect to the first inner electrode inner receiving chamber as the first inner electrode is set in place within the first inner electrode inner receiving chamber..].

.[.6. The modular plasma treatment system of claim 5, wherein the self-centering features comprise

a tapered wall of the first electrode inner receiving chamber that centers the first inner electrode when the first inner electrode is set in place within the first electrode inner receiving chamber..].

. [.7. The modular plasma treatment system of claim 5, wherein the self-centering features comprise a tapered exterior cross-section of the first inner electrode that widens against the first electrode portions of the first electrode inner receiving chamber as the first inner electrode is set in place within the first electrode inner receiving chamber..].

. [.8. The modular plasma treatment system of claim 1, wherein the first outer electrode and the first inner electrode, when set in place within the first housing inner receiving chamber, are configured to provide a first plasma gap for a first plasma and wherein the second outer electrode and the second inner electrode, when set in place within the first housing inner receiving chamber, are configured to provide a second plasma gap for a second plasma different from the first plasma..].

. [.9. The modular plasma treatment system of claim 1, wherein the first plasma reformer comprises a dielectric barrier discharge plasma reformer to generate a dielectric barrier discharge plasma..].

. [.10. The modular plasma treatment system of claim 9, wherein the first outer electrode comprises interior conductive formertions to generate electric field gradients between points of the conductive projections..].

. [.11. The modular plasma treatment system of claim 10, wherein the interior conductive projections comprise conductive screw tips screwed into holes of the first outer electrode..].

. [.12. The modular plasma treatment system of claim 10, wherein at least two of the interior conductive projections comprise different dimensions from one another to provide different electric field gradients to precipitate particulate matter having different properties..].

. [.13. The modular plasma treatment system of claim 9, wherein the first exhaust inlet comprises surface features that alter air pressure within an excitation chamber of the first plasma reformer to direct the first input gaseous stream in a cyclone motion to points of highest energy density inside the excitation chamber..].

. [.14. The modular plasma treatment system of claim 13, wherein the first plasma reformer comprises a rotating glide arc reformer and the second plasma reformer comprises a DBD plasma reformer, at least one of the first outer electrode and the first inner electrode rotate a textured surface to direct the first input gaseous stream in a cyclone motion to points of highest energy density inside an excitation chamber of the rotating glide arc reformer..].

. [.15. The modular plasma treatment system of claim 14, further comprising coaxial electrodes that discharge into each of the glide-arc plasma and the DBD plasma..].

. [.16. The modular plasma treatment system of claim 1, further comprising: a second outer housing of a second plasma reformer having a second exhaust inlet for receiving a second input gaseous stream and a second exhaust outlet for expelling a second output gaseous stream, wherein the second outer housing comprises a second housing inner receiving chamber; a third outer electrode sized and dimensioned to abut second housing portions of the second housing inner receiving chamber such that the third outer electrode does not substantially move when set in place within the second housing inner receiving chamber, wherein the third outer electrode comprises a third electrode inner receiving chamber; a fourth outer electrode sized and dimensioned to abut the second housing portions of the second housing inner receiving chamber such that the fourth outer electrode does not substantially move when set in place within the second housing inner receiving chamber, wherein the fourth outer electrode comprises a fourth electrode inner receiving chamber; a third inner electrode sized and dimensioned to abut third electrode portions of the third electrode inner receiving chamber such that the third inner electrode does not substantially move when set in place within the third electrode inner receiving chamber; and a fourth inner electrode sized and dimensioned to abut fourth electrode portions of the fourth electrode inner receiving chamber such that the fourth inner electrode does not substantially move when set in place within the fourth electrode inner receiving chamber, wherein the first output gaseous stream feeds the second input gaseous stream..].

. [17. The modular plasma treatment system of claim 16, wherein the rotating glide arc reformer generates a glide-arc plasma and the DBD plasma reformer generates a DBD plasma..].

. [18. The modular plasma treatment system of claim 17, further comprising a magnetic field generator that generates a magnetic field around the co-axial electrodes..].

. [19. The modular plasma treatment system of claim 18, wherein the first outer housing of the first plasma reformer is disposed above a particulate filter expelling the first output gaseous stream to transfer waste heat from the first output gaseous stream to an oxidant conduit..].

. [20. The modular plasma treatment system of claim 19, wherein the air source comprises at least one of a blower and an on-board turbocharger..].

. [21. The modular plasma treatment system of claim 1, wherein the plasma treatment system oxidizes particulate matter in a reaction zone between the first inner electrode and the first outer electrode..].

. [22. The modular plasma treatment system of claim 21, wherein the air dryer uses a desiccant to remove water vapor from the intake air..].

. [23. The modular plasma treatment system of claim 1, further comprising an air drier that receives intake air from an air source and outputs dried air, wherein the first exhaust inlet receives the dried air and outputs oxidants to the first output gaseous stream..].

. [24. The modular plasma treatment system of claim 1, further comprising a voltage transformer integrated with a feedthrough of the first plasma reformer to deliver power from the voltage power transformer to the first outer electrode and the first inner electrode..].

. [25. The modular plasma treatment system of claim 1, further comprising a fuel injector that injects fuel into the first input gaseous stream..].

. [26. The modular plasma treatment system of claim 25, wherein the first plasma reformer comprises at least one of a DBD reformer and a rotating glide-arc reformer..].

. [27. The modular plasma treatment system of claim 1, further comprising a microwave generator that generates microwaves directed towards the first outer housing..].

. Iadd.28. A method of treating a gas stream, the method comprising: directing the gas stream into a first reaction zone; energizing the gas stream to generate a first plasma comprising a dielectric barrier discharge (DBD) plasma between a first inner electrode nested within a second electrode in the first reaction zone; further energizing, within a second reaction zone, the gas stream energized in the first reaction zone to generate a second plasma comprising one of a rotating glide-arc plasma or a microwave plasma, wherein the first and second reaction zones are disposed serially such that the first inner electrode is directly coupled to a common reaction zone common to the first and second reaction zones and configured to sustain therein the first plasma. .Iaddend.

. Iadd.29. The method of claim 28, wherein the gas stream comprises a hydrocarbon. .Iaddend.

. Iadd.30. The method of claim 28, wherein the gas stream is treated to produce hydrogen. .Iaddend.

. Iadd.31. The method of claim 28, wherein the first inner electrode contacts the second plasma in the common reaction zone. .Iaddend.

. Iadd.32. The method of claim 28, wherein the first reaction zone is in linear sequence to the second reaction zone. .Iaddend.

. Iadd.33. The method of claim 28, wherein a dielectric layer is disposed between the first inner electrode and the second electrode. .Iaddend.

. Iadd.34. The method of claim 28, wherein the rotating glide-arc plasma is generated in the second reaction zone. .Iaddend.

. Iadd.35. The method of claim 34, wherein the rotating glide-arc plasma is formed between a third electrode nested within a fourth electrode, and wherein a gap between the third and fourth electrode increases along an axis of the third electrode. .Iaddend.

. Iadd.36. The method of claim 28, wherein the DBD plasma is generated in linear sequence to the second plasma. .Iaddend.

. Iadd.37. The method of claim 28, further comprising generating a low pressure zone within the

first reaction zone. .Iaddend.

.Iadd.38. The method of claim 37, wherein the low pressure zone is downstream of the gas stream energized in the first reaction zone. .Iaddend.

.Iadd.39. The method of claim 37, wherein the low pressure zone is downstream of the DBD plasma. .Iaddend.

.Iadd.40. The method of claim 28, further comprising an electric field gradient overlapping the first reaction zone, and wherein the second plasma is the microwave plasma. .Iaddend.

.Iadd.41. The method of claim 28, further comprising directing the gas stream into a third reaction zone comprising a third plasma. .Iaddend.

.Iadd.42. The method of claim 28, wherein the first inner electrode is arranged co-axially with the second electrode. .Iaddend.

.Iadd.43. The method of claim 42, wherein a third plasma is formed by a third electrode arranged co-axially with a fourth electrode. .Iaddend.

.Iadd.44. A method of generating a product from a gas stream, comprising: energizing the gas stream in a first reaction zone, wherein the first reaction zone comprises a dielectric barrier discharge (DBD) plasma; directing the energized gas stream into a second reaction zone, and further energizing the energized gas stream in the second reaction zone to generate therein a glide-arc plasma; wherein a first inner electrode of the first reaction zone is directly coupled to a common reaction zone common to the first and second reaction zones and configured to sustain therein the glide-arc plasma; and directing an exhaust comprising the product out of one of the first or the second reaction zones. .Iaddend.

.Iadd.45. The method of claim 44, wherein the product is hydrogen and the gas stream comprises a hydrocarbon. .Iaddend.

.Iadd.46. The method of claim 44, wherein the DBD plasma is formed between the first inner electrode coaxial with a second electrode, wherein a dielectric layer is disposed between the first inner electrode and the second electrode. .Iaddend.

.Iadd.47. The method of claim 44, wherein the second reaction zone is downstream of the first reaction zone. .Iaddend.

.Iadd.48. The method of claim 47, wherein the glide-arc plasma is formed between a third electrode coaxial with a fourth electrode, wherein a gap between the third electrode and the fourth electrode increases along an axis of the third electrode. .Iaddend.

.Iadd.49. The method of claim 44, further comprising generating a third plasma different than the second plasma, wherein the third plasma is downstream from the second reaction zone. .Iaddend.

.Iadd.50. A method of generating a product from a gas stream, comprising: energizing the gas stream in a first reaction zone; directing the energized gas stream into a second reaction zone, and further energizing the energized gas stream to generate a second plasma; wherein one of the first reaction zone or the second reaction zone comprises a glide-arc plasma, wherein a first inner electrode of the first reaction zone is directly coupled to a common reaction zone common to the first and second reaction zones and configured to sustain therein the glide-arc plasma, and wherein the gas stream is energized in the first reaction zone by the first inner electrode nested within a second electrode; and directing an exhaust comprising the product out of one of the first or the second reaction zones. .Iaddend.

.Iadd.51. A plasma device, comprising: a first reaction zone configured to energize a gas stream using a first electrode co-axial with a second electrode; a second reaction zone configured to generate a plasma using a third electrode co-axial with a fourth electrode, wherein a gap between the third and fourth electrodes increases along an axis of the third electrode; wherein the first electrode is directly coupled to a common reaction zone common to the first and second reaction zones and configured to sustain therein the plasma; and a microwave generator directed toward the second reaction zone. .Iaddend.

.Iadd.52. The plasma device of claim 51, wherein the first electrode is upstream of the third

electrode. .Iaddend.

.Iadd.53. The plasma device of claim 51, wherein the first electrode comprises a dielectric layer on a surface facing the second electrode. .Iaddend.

.Iadd.54. The plasma device of claim 51, wherein the second reaction zone is downstream of the first reaction zone. .Iaddend.

.Iadd.55. A method of treating a gas stream, the method comprising: directing the gas stream into a first reaction zone; generating, within the first reaction zone, an energized gas stream; directing the energized gas stream toward a plasma in a second reaction zone, wherein a first electrode of the first reaction zone is directly coupled to a common reaction zone common to the first and second reaction zones and configured to sustain therein the plasma, and wherein a gap between the first electrode and a second electrode in the first reaction zone increases along an axis of the first electrode; directing a microwave at the second reaction zone; and reforming the gas stream in the second reaction zone to form a product. .Iaddend.

.Iadd.56. The method of claim 55, wherein the microwave is directed toward an inlet of the second reaction zone. .Iaddend.

.Iadd.57. The method of claim 55, wherein the microwave is directed toward an outlet of the second reaction zone. .Iaddend.

.Iadd.58. The method of claim 55, wherein the microwave is directed toward the first and second reaction zones. .Iaddend.

.Iadd.59. The method of claim 55, further comprising using a waveguide to direct the microwave at one of the first reaction zone, an inlet of the first reaction zone, an outlet of the first reaction zone, the energized gas stream, or the plasma. .Iaddend.
