

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283999

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Fiederer; Lukas et al.

Method for Operating a Measuring Device

Abstract

A computer-implemented method for operating a measuring device, in particular a wall diagnostic device, includes (i) receiving radar data of a radar sensor unit of the measuring device, (ii) performing wall diagnostics by performing an analysis of the radar data and providing diagnostic results via a diagnostic module of the measuring device, and (iii) determining feedback information.

Inventors: Fiederer; Lukas (Balingen, DE), Frischen; Andreas (Leonberg, DE), Koelsch; Andreas (Peiting, DE), Giliard; Anke (Stuttgart, DE), Moster; Benjamin (Niefern-Oeschelbronn, DE), Sgarz; Heiko (Leonberg, DE), Steuler; Jan Linus (Woelfersheim, DE), Borowski; Judith (Ho Chi Minh City, VN), Troeltzsch; Uwe (Roesrath, DE)

Applicant: Robert Bosch GmbH (Stuttgart, DE)

Family ID: 1000008589184

Appl. No.: 19/072486

Filed: March 06, 2025

Foreign Application Priority Data

DE 10 2024 202 229.2

Mar. 11, 2024

Publication Classification

Int. Cl.: G01S13/88 (20060101); G06N20/00 (20190101)

U.S. Cl.:

CPC G01S13/888 (20130101); G06N20/00 (20190101)

Background/Summary

[0001] This application claims priority under 35 U.S.C. § 119 to application no. DE 10 2024 202 229.2, filed on Mar. 11, 2024 in Germany, the disclosure of which is incorporated herein by reference in its entirety.

[0002] The present disclosure relates to a method for operating a measuring device, in particular a wall diagnostic device.

BACKGROUND

[0003] Diagnostic devices for performing wall diagnostics and detecting objects formed in the walls are known from prior art.

[0004] An object of the present disclosure is to provide an improved method for operating a measuring device, in particular a wall diagnostic device. It is further an object to provide an improved method for training an artificial intelligence of a measuring device.

[0005] The object is achieved by the method as set forth below. Advantageous embodiments are subject-matter also set forth below.

SUMMARY

[0006] According to one aspect, a computer-implemented method of operating a measuring device, in particular a wall diagnostic device is provided, comprising: [0007] receiving radar data from a radar sensor unit of the measuring device, wherein the radar data depicts a wall on which diagnostics are to be performed; [0008] performing wall diagnostics by performing an analysis of the radar data and providing diagnostic results via a diagnostic module of the measuring device, wherein the wall diagnostics comprise: [0009] performing a wall type classification and determining a wall type of the wall by way of the diagnostic module, wherein the diagnostic results comprise at least the wall type of the wall; and/or [0010] performing an object recognition of an object disposed in the wall using the diagnostic module, wherein the object recognition comprises an object detection and an object classification, and determining an object position in the wall and an object type of the object, and wherein the diagnostic results comprise at least the object position and/or the object type; [0011] determining feedback information, wherein the feedback information describes whether the diagnostic results match a current state of the wall.

[0012] The technical advantage can thereby be achieved that an improved method for operating a measuring device, in particular a wall diagnostic device, can be provided. For this purpose, radar data of a radar sensor unit of the measuring device for a wall to be diagnosed is first received. Based on the radar data, a wall diagnostics is subsequently performed of the wall to be diagnosed by a diagnostic module of the measuring device.

[0013] The wall diagnostics includes performing a wall type classification and determining a wall type of the wall and/or performing object recognition for an object disposed in the wall using the diagnostic module. The object recognition includes object detection with the determination of an object position and an object classification with the determination of an object type.

[0014] Feedback information is also determined. The feedback information here describes determining whether the diagnostic results generated during the wall diagnostics match a current state of the wall.

[0015] By using the correspondingly configured diagnostic module, it can be achieved that no additional sensor information is needed in addition to the radar data for the wall diagnostics, in particular for determining the wall type and/or determining the object type. The wall type and/or the object type may be determined solely based on the radar data of the radar sensor unit. The measuring device therefore need not be equipped with additional sensors.

[0016] By automatically determining the wall type as part of the wall diagnostics, it can be avoided that the user of the measuring device must manually enter the present wall type of the wall to be

examined. Further, because the diagnostic module automatically determines the wall type, the correspondingly determined wall type can be used in the further wall diagnostics, for example as a background correction for object recognition. This may further improve the quality of the wall diagnostics.

[0017] By determining the feedback information, the quality of the wall diagnostics performed may be checked directly. The feedback information may in particular be used to improve the wall diagnostics, for example, by updating the diagnostic module.

[0018] According to one embodiment, the method furthermore comprises: providing the feedback information to an external server unit to take the feedback information into account in an update of the diagnostic module.

[0019] By doing so, the technical advantage may be achieved that, by providing the feedback information to an external server unit, the feedback information provided accordingly may be used to improve the performance of the diagnostic module. For example, the feedback information may be from a plurality of measuring devices which are in operation. The performance of the diagnostic modules installed in the measuring devices can be checked by the server unit using the comprehensive feedback information gathered in this way. This allows for a targeted update of the software of the diagnostic module, wherein the goal of the respective update is to improve the aspects of the diagnostic module that have insufficient performance according to the feedback information.

[0020] According to one embodiment, the corresponding radar data of the external server unit is provided in addition to the feedback information.

[0021] This may achieve the technical advantage that, by providing the radar data of the measuring devices in addition to the feedback information of the external server unit, a comprehensive description of the situation in which the measuring device created the diagnostic results and that resulted in the feedback information can be provided. The update or improvement of the diagnostic module can thereby be further improved.

[0022] According to one embodiment, performing the wall diagnostics further comprises: performing an object depth determination and determining an object depth of the object in the wall using the diagnostic module, wherein the object depth is defined as a distance of the object to a surface of the wall; and/or performing an object extent determination and determining an object extent of the object along a predefined direction by the diagnostic module, wherein the diagnostic results further comprise at least the object depth and/or the object extent of the object.

[0023] This may achieve the technical advantage that a comprehensive wall diagnostics can be performed. To this end, the wall diagnostics include determining an object depth and/or determining an object extent in addition to determining the wall type and/or the object position and/or the object type. By considering the object depth and/or the object extent, a detailed description of the objects detected by the measuring device can be provided.

[0024] According to one embodiment, a plurality of possible object positions and/or a plurality of possible object types of the object are determined in the object recognition as stand-alone diagnostic results, and/or wherein a plurality of possible wall types of the wall are determined as stand-alone diagnostic results in the wall type classification, and/or wherein a plurality of possible object depths are determined as stand-alone diagnostic results in the object depth determination and/or wherein a plurality of possible object depths of the object are determined as stand-alone diagnostic results in the object extent determination, wherein each of the plurality of diagnostic results are displayed in a display unit of the measuring device.

[0025] This can achieve the technical advantage of enabling a detailed wall diagnostics. In that multiple object positions and/or multiple object types and/or multiple object depths and/or multiple object extents and/or multiple wall types are determined in the wall diagnostics and displayed in the display unit of the measuring device, a comprehensive image of the wall to be diagnosed can be provided to the user.

[0026] According to one embodiment, the method furthermore comprises: [0027] providing a first selection function and/or a second selection function, wherein, when the first selection function is carried out a user of the measuring device, at least one of the displayed wall types and/or one of the displayed object positions and/or object types and/or object depths and/or object extents is selectable, and/or wherein, when the second selection is carried out function by the user of the measuring device, the automatic determination of the wall type during the wall diagnostics and/or the display of the automatically determined wall type in the display unit can be deactivated and a wall type is manually selectable by the user.

[0028] This can achieve the technical advantage that the first selection function allows the user to select the appropriate wall type for the wall to be examined from the plurality of wall types displayed. If the wall type of the wall to be examined is known, the user can select the best suitable possible wall type provided by the measuring device. The selected wall type can be used for further wall diagnostics, while the non-selected wall types are not taken into account. This may further improve the quality of the wall diagnostics.

[0029] By way of the second selection function, the user can deactivate the automatic determination of the wall type and select the appropriate wall type manually. This may be particularly advantageous for diagnostic situations in which the user knows the wall type of the present wall and the possible wall types provided by the measuring device do not completely depict the wall type actually present. Again, this may increase the quality of the wall diagnostics.

[0030] According to one embodiment, the method furthermore comprises: providing a feedback function, wherein, when the user carries out the feedback function, a match between the displayed wall type and/or the displayed object position and/or the displayed object type and/or the displayed object depth and/or the displayed object extent and the actual wall type and/or the actual object position and/or the actual object type and/or the actual object depth and/or the actual object extent can be determined.

[0031] This may achieve the technical advantage that, through provision of the feedback function, clear feedback information regarding whether the displayed wall types match the actual wall type and/or the displayed object position and/or the displayed object type and/or the displayed object depth and/or the displayed object extent match the actual object positions, the actual object types, the actual object depths and/or the actual object extents. Thus, by actuating the feedback function, it is possible to actively provide feedback information regarding the quality of the wall diagnostics performed. This will allow for the determination of detailed and relevant feedback information. For example, the feedback feature comprises an input feature that allows the user to manually enter the feedback.

[0032] According to one embodiment, determining the feedback information comprises: receiving selection commands of the first and/or second selection functions and/or feedback commands of the feedback function and determining the feedback information based on the selection commands and/or feedback commands, wherein corresponding selections are made in the selection commands according to the first and/or second selection functions, and wherein the feedback commands contain corresponding feedback information provided by the user.

[0033] This may achieve the technical advantage that the feedback information may be determined based on the received selection commands of the first and second selection functions and/or the feedback commands of the feedback function. This may make it possible to provide detailed feedback information on the quality of the wall diagnostics performed.

[0034] According to one embodiment, determining the feedback information comprises: [0035] determining, using the diagnostic module, whether there are deviations from the diagnostic results determined in the wall diagnostics when repeated diagnostics are carried out for a same position of the measuring device relative to the wall; and [0036] displaying the deviations in the display unit; and [0037] receiving feedback commands from the user regarding the deviations, wherein the displayed deviations are confirmed or refuted in the feedback commands.

[0038] This can achieve the technical advantage of enabling improved wall diagnostics. As a result, using the diagnostic module, deviations between the diagnostic results of several wall diagnoses performed by the measuring device for identical positions of the measuring device relative to the wall are determined. The deviations may be displayed in the display unit. The user may provide feedback information regarding the deviations in which the deviations are confirmed or refuted via the feedback function. The consistency of the wall diagnostics can thereby be checked and documented. The corresponding feedback information may further be considered for improving the diagnostic module.

[0039] According to one embodiment, the measuring device further comprises at least one of an induction sensor and/or an eddy current sensor and/or a capacitance sensor and/or an AC current sensor and/or an NMR sensor and/or an ultrasonic sensor for providing additional sensor data, wherein the diagnostic module is configured to perform the wall diagnostics by taking into account the additional sensor data.

[0040] The technical advantage can thereby be achieved that, through further sensor data, additional sensors, each of which is configured to detect different physical variables, can provide additional information in addition to the radar data of the radar sensor unit, for incorporation into the wall diagnostics. This additional information, which is preferably complementary to the information of the radar data of the radar sensor unit, allows further precise specification of the wall diagnostics and the object recognition, respectively.

[0041] According to one embodiment, the diagnostic module comprises at least one correspondingly trained artificial intelligence configured to perform an object recognition and/or a wall classification and/or an object depth determination and/or an object extent determination based on the radar data and/or the additional sensor data.

[0042] The technical advantage can thereby be achieved that, because the diagnostic module is configured as a correspondingly trained artificial intelligence structure, which is trained based on the radar data, or, if applicable, taking into account the information of the additional sensors, to perform an object recognition and/or a wall classification and/or an object depth determination and/or an object extension determination, a reliable and powerful diagnostic module can be provided. By using the artificial intelligence technology, precise wall diagnostics can be provided.

[0043] According to one embodiment, the object classes of the object type of the object comprise: metallic/non-metallic object, low voltage cable, cable with single phase AC signal, cable with multiphase AC signal, wood beam, metal beam, plastic pipe, water filled plastic pipe, for example fresh water pipe, non-water filled plastic pipe, for example waste water pipe, and/or wherein the wall type classes of the wall comprise: Concrete wall, plasterboard/drywall wall, brick wall and/or bricks of the wall and/or wall with surface heating, such as underfloor heating or wall heating.

[0044] The technical advantage may thereby be achieved that objects and walls of different types may be detected and classified. For example, metallic objects may include metallic pipes, metallic rods, metallic beams, metallic cables, and any other metallic objects commonly found in wall structures.

[0045] According to one aspect, a method for training an artificial intelligence structure of a wall diagnostic measuring device is provided, comprising: [0046] providing a training dataset for training an artificial intelligence, wherein the training dataset comprises a wall and radar data depicting an object formed in the wall as well as the feedback information provided according to the method for operating a measuring device; [0047] training the artificial intelligence based on the training dataset and taking into account the feedback information to perform object recognition of an object formed in a wall, wherein the object recognition comprises at least one object detection and one object classification.

[0048] In this way, the technical advantage can be achieved that improved training of the artificial intelligence of the wall diagnostic device, in particular post-training, is enabled, in which feedback is taken into account by the user of the wall diagnostic devices.

[0049] Provided according to one aspect is a computing unit configured to perform the method of operating a measuring device according to one of the preceding embodiments and/or the method of training an artificial intelligence.

[0050] According to one aspect, a computer program product is provided, comprising instructions that, when the program is executed by a data processing unit, cause the data processing unit to perform the method for operating a measuring device according to one embodiment and/or the method for training an artificial intelligence.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0051] Embodiments of the disclosure are described with reference to the following figures. The figures show:

[0052] FIG. **1** a schematic representation of a measuring device according to one embodiment;

[0053] FIG. **2** a further schematic representation of the measuring device according to a further embodiment;

[0054] FIG. **3** a further schematic representation of the measuring device according to a further embodiment;

[0055] FIG. **4** a schematic representation of a measurement of the measuring device according to one embodiment,

[0056] FIG. **5** a further schematic representation of the measuring device according to a further embodiment;

[0057] FIG. **6** a schematic representation of a system for operating a measuring device according to one embodiment,

[0058] FIG. **7** a flowchart of a method for operating a measuring device according to one embodiment,

[0059] FIG. **8** another flowchart of the method for operating a measuring device according to a further embodiment,

[0060] FIG. **9** another flowchart of the method for operating a measuring device according to a further embodiment,

[0061] FIG. **10** a flowchart of a method for training an artificial intelligence of a measuring device according to one embodiment, and

[0062] FIG. **11** a schematic representation of a computer program product.

DETAILED DESCRIPTION

[0063] FIG. **1** shows a schematic representation of a measuring device **100** according to one embodiment.

[0064] The present disclosure relates to a measuring device, in particular a wall diagnostic device for examining walls **105** to be worked on. Wall diagnostic devices are known from the prior art that are used to detect objects located in walls. Such devices allow a user to examine walls to be processed to search for objects disposed in the walls in order to be able to perform planned work, for example drilling in walls, based on this such that damage to the objects disposed in the walls can be avoided.

[0065] In the embodiment shown, the measuring device **100** comprises a housing **150** having a handle **152** for grasping of the measuring device **100** by a user, a display unit **111** for displaying diagnostic results **109** of the wall diagnostics, and controls **154** for switching the measuring device **100** to various operating modes.

[0066] According to the disclosure, the measuring device **100** comprises at least one radar sensor unit **101**. By way of the radar sensor unit **101**, radar signals may be transmitted towards the wall **105** to be examined, and radar signals reflected by the wall **105** may be received.

[0067] For example, the radar sensor unit **101** may be configured as a narrow band radar detector device in the 2.4 GHz to 2.4835 GHz frequency range.

[0068] The measuring device **100** further comprises a diagnostic module **107** executable on a computing unit **151** of the measuring device **100** to perform the wall diagnostics. The diagnostic module **107** is configured to perform corresponding diagnostics on the wall to be examined based on the radar data **103** of the radar sensor unit **101**. The radar data **103** of the radar sensor unit **101** thereby depicts the wall **105** to be examined and, if applicable, objects **113** located within the wall **105**.

[0069] The wall diagnostics carried out by the diagnostic module **107** comprise at least performing object recognition. The object recognition comprises an object detection and an object classification of the object **113** located in the wall **105**. The object detection comprises at least the determination of an object position **115**. The object position describes the positioning of the object located in the wall **105** with respect to a reference system defined by the measuring device **100**. The object classification of the detected object **113** comprises at least determining an object type **117** of the detected object **113**.

[0070] The diagnostic results of the wall diagnostics determined in this way, i.e. at least the determined object position **115** and/or the determined object type **117** of the object **113** disposed in the wall **105**, are subsequently presented in a display unit **111** of the measuring device **100** to a user of the measuring device **100**. For example, the display unit **111** may be configured as a corresponding display, and the diagnostic results **109** may be visually displayed. Additionally, the display of the diagnostic results **109** may be supported via audible and/or haptic signals. For example, the haptic signals may be realized via corresponding vibration signals.

[0071] The object **113** may be shown in the display, for example, by way of a corresponding icon. The object **113** can be shown in the corresponding object position **115** in the display. The object extension **121** may be visualized by a corresponding size of the displayed icon. The particular object type **117** of the object **113** may be visualized with a corresponding term or color highlighting of the icon, or by a specific shape of the icon representing the object **113**.

[0072] Alternatively, the wall diagnostics may additionally comprise determining a wall type **123** in the form of a wall type classification of the wall **105** to be examined. The wall type **123** describes the respective type of the wall **105** to be examined. For example, the wall type may be associated with corresponding wall type classes, which may comprise: Concrete wall, plasterboard/drywall wall, brick wall and/or wall bricks, underfloor heating, wall heating or similar wall types found in buildings.

[0073] According to one embodiment, the diagnostic module **107** is further configured to determine an object depth **119** of the object **113** within the wall **105** based on the radar data **103**. The object depth **119** is defined by a distance of the object formed in the wall **105** to a surface of the wall **105**. The distance may be defined on the object side, for example with respect to an object surface or with respect to an object center point. The distance to the surface of the wall **105** describes a shortest distance defined by a direction perpendicular to the surface of the wall **105**.

[0074] According to one embodiment, the diagnostic module **107** is further configured to determine an object extension **121** of the object **113** in at least one predefined direction based on the radar data **103**. The object extension **121** of the object **113** describes a spatial extension of the object **113** in at least one spatial direction, preferably in two spatial directions, particularly preferably in three spatial directions. The object **113** may be described here as a one-dimensional, two-dimensional, or three-dimensional object **113**.

[0075] In conventional use, the measuring device **100** is placed on the surface of the wall **105** to be examined. Radar signals are transmitted towards the wall **105**, and radar signals reflected from the wall **105** or the objects **113** located behind it are received, via the radar sensor unit **101**. This radar data **103** of the radar sensor unit **101** is used by the diagnostic module **107** to perform the wall diagnostics described above and to determine corresponding diagnostic results **109**.

[0076] For example, the diagnostic results **109** may comprise the object position **115** and/or object type **117** of the object **113** located in the wall **105**. Alternatively or additionally, the diagnostic results **109** may comprise the wall type **123** of the wall **105** and/or the object depth **119** and/or the object extension **121** of the object **113**.

[0077] The diagnostic results **109** configured in this manner may subsequently be displayed to a user of the measuring device **100** in a display unit **111** of the measuring device **100**. The display unit **111** can be configured as a corresponding display, for example. The diagnostic results **109** may be displayed in graphical or textual form in the display unit **111**.

[0078] According to one embodiment, the measuring device **100** further comprises a motion detection unit **141**. The motion detection unit **141** may be used to detect movement of the measuring device **100** relative to the wall **105**. The motion detection unit **141** may comprise, for example, at least one roller element for this purpose. When the roller element is placed on the wall surface of the wall **105**, movement of the measuring device **100** relative to the wall **105** can be detected when the measuring device **100** moves along a direction of movement **153** by rolling the roller element. Alternatively, the motion detection unit **141** may have a different configuration by which a relative movement of the measuring device **100** relative to the wall **105** can be detected.

[0079] By moving the measuring device **100** relative to the wall **105**, radar data **103** of the radar sensor unit **101** may be captured for a plurality of different positions of the measuring device **100** relative to the wall **105**. This allows a larger spatial area of the wall **105** to be examined than the effective range of the radar sensor unit **101**. This allows for objects **113** to be captured that have a greater spatial extent than the effective range of the radar sensor unit **101**.

[0080] While the measuring device **100** moves along the direction of movement **153**, radar data **103** of the radar sensor unit **101** may be captured continuously. The wall diagnostics may be evaluated by the diagnostic module **107** based on this radar data **103** while the measuring device **100** is moving along the direction of movement **153**. This allows for accelerated wall diagnostics, taking into account the positioning of the measuring device **100** relative to the wall **105**.

[0081] According to its embodiment, the diagnostic module **107** is configured as a correspondingly trained artificial intelligence **125**. The artificial intelligence **125** is trained to perform the above-mentioned wall diagnostics based on the radar data **103** of the radar sensor unit **101** and to determine at least the object position **115** and the object type **117** of an object **113** located in the wall **105**. The object classification or determination of the object type **117**, respectively, comprises assigning the detected object **113** to predefined object classes.

[0082] The object classes may comprise: Metallic/non-metallic object, low voltage cable, single phase AC signal cable, multiphase AC signal cable, wood beam, metal beam, plastic pipe, water filled plastic pipe, for example fresh water pipe, non-water filled plastic pipe, for example waste water pipe, or other elements commonly installed in building walls.

[0083] Furthermore, the artificial intelligence **125** may be trained to determine the wall type **123** of the wall **105** to be examined at least based on the radar data **103** of the radar sensor unit **101**.

Possible wall types **123** may comprise: Concrete wall, plasterboard/drywall wall, brick wall and/or individual bricks of the brick wall, underfloor heating, wall heating or other similar wall types commonly installed in buildings.

[0084] According to one embodiment, in addition to the radar sensor unit **101**, the measuring device **100** may comprise further additional sensors by way of which additional physical variables are detectable. For example, the measuring device **100** may comprise an induction sensor and/or an eddy current sensor and/or a capacitance sensor and/or an AC current sensor and/or an NMR sensor and/or an ultrasonic sensor or other sensors commonly used in wall diagnostic devices.

[0085] The diagnostic module **107**, in particular the correspondingly trained artificial intelligence **125**, can be configured to perform wall diagnostics based on the radar data **103** of the radar sensor unit **101** and taking into account the additional sensor information of the further sensors described above. The additional information of the additional sensors mentioned above can particularly be

used for object recognition of the objects **113** located in the walls **105**. The additional sensor information may possibly provide improved detection of the objects **113** and may possibly provide improved classification of the objects **113**.

[0086] For example, the material of the objects **113**, for example as a metallic or non-metallic material, can be particularly improved and classified by using the additional sensor information.

[0087] FIG. **2** shows another schematic representation of the measuring device **100** according to a further embodiment.

[0088] In the embodiment shown, the measuring device **100** comprises a pre-processing module **127** in addition to the diagnostic module **107**. For wall diagnostics, the measuring device **100** first receives the radar data **103** of the radar sensor unit **101**. Pre-processing of the receiving radar data **103** is performed via the pre-processing module **127**. For example, via pre-processing by the pre-processing module **127**, the radar data may be brought into a corresponding data structure required for wall diagnostics by the diagnostic module **107**.

[0089] As described above, during wall diagnostics, the diagnostic module **107** generates the diagnostic results **109** described above. For example, the diagnostic results **109** may comprise the object position **115** and/or object type **117** and/or object depth **119** and/or object extension **121** of an object **113** formed in the wall **105** to be examined and/or the wall type **123** of the wall **105** to be examined. The correspondingly generated diagnostic results **109** may subsequently be displayed in the display unit **111** of the measuring device **100**.

[0090] According to one embodiment, in addition to the radar data **103** of the radar sensor unit **101**, the additional sensor information of the additional sensors described above may be considered during the wall diagnostics of diagnostic module **107**. A corresponding pre-processing of the additional sensor information may be performed accordingly by the pre-processing module **127**.

[0091] In the embodiment shown, the diagnostic module **107** comprises a wall type classification module **129** and an object recognition module **131**. The pre-processing module **127** comprises a first pre-processing module **135** and a second pre-processing module **137**. The first pre-processing module **135** comprises an S matrix reduction **155**. The second pre-processing module **137** comprises a background correction **157**, an inverse Fast Fourier transformation **159**, and a focusing and migration **161**. During the pre-processing of the radar data **103** by the pre-processing module **127**, the radar data **103** is first pre-processed by the first pre-processing module **135** and the S-matrix reduction **155** contained therein.

[0092] When doing so, the first pre-processing module **135** generates input data **133** based on the radar data **103**. The input data **133** serves as input data for the wall type classification module **129**. The wall type classification module **129** performs a wall type classification of the wall **105** to be examined based on the input data **133** and generates wall type information **139**. The wall type information **139** contains the wall type **123** of the wall **105** to be examined, as determined in the wall type classification.

[0093] Subsequently, the second pre-processing module **137** performs pre-processing based on the radar data **103** and the wall type information **139**. A background correction **157** of the radar data **103** is performed during this, taking into account the wall type **123** determined in the wall type information **139**. Depending on the wall type **123** of the wall **105** to be examined, different effects can occur on the radar data **103**.

[0094] These effects, which are primarily based on the respective wall type **123** and can affect object recognition, can be corrected by the background correction **157**. After the background correction has been performed, further pre-processing can be carried out by performing the inverse Fast Fourier transformation **159** or focusing and migration **161**, respectively, and input data **133** can be created for the object recognition module **131** once again. Based on the input data **133** provided by the second pre-processing module **137**, the object recognition module **131** performs object recognition of the object **113** located in the wall **105** to be examined and determines at least the object position **115** and the object type **117** of the respective object **113**. Additionally, the object

depth **119** and the object extension **121** may be determined by the object recognition module **131**.

[0095] According to one embodiment, the diagnostic module is further configured to determine an object depth of the object within the wall based on the radar data, wherein the object depth is defined by a distance of the object formed in the wall to a surface of the wall.

[0096] The pre-processing is optional. Depending on the algorithm used for the diagnostic module **107**, completely unprocessed radar echoes of different frequencies may be used as radar data **103** and as input data for the diagnostic module **107**. Alternatively, radar data **103** processed via multiple steps may be used. The pre-processing steps comprise, for example, the transformation of the signals from the frequency domain to the time or distance domain, background deduction, noise removal, and normalization of the signals. For radar data **103** which is available in the form of complex numbers, only the absolute value can be processed. Alternatively or additionally, the phase information may be considered.

[0097] FIG. **3** shows a further schematic representation of the measuring device **100** according to a further embodiment.

[0098] In the embodiment shown, the diagnostic module **107** comprises a plurality of parallel processing paths **102**. Each processing path **102** includes a pre-processing module **127**, the diagnostic module **107**, comprising the wall type classification module **129** and/or the object recognition module **131**, for example, according to the embodiment in FIG. **2**, and a post-processing module **163**.

[0099] In FIG. **3**, primarily the radar data **103** is shown as input data for the wall diagnostics. In addition to the radar data shown, however, the additional information from the additional sensors may also serve as input data for the wall diagnostics. The different information from the different types of sensors in the different parallel processing paths **102** can be processed and the corresponding wall diagnostics performed separately on the different sensor information. Upon completion of the wall diagnostics, a summary module may be used to assemble a summary of the individual partial analysis results for the diagnostic results **109** of the wall diagnostics.

[0100] Alternatively or additionally, different sub-aspects of wall diagnostics may be performed by the different processing paths **102** based on the same sensor information.

[0101] For example, the individual processing paths **102** may process different radar data **103** captured during movement of the measuring device **100** relative to the wall **105** for different positions of the measuring device **100** relative to the wall **105**. The radar data **103**, thus representing different regions of the wall **105** and captured sequentially in time as the measuring device **100** moves relative to the wall **105**, may then be processed in the different processing paths **102** by the modules shown.

[0102] The various processing paths perform stand-alone wall diagnostics including at least determining the object position **115** and/or the object type **117** of the object **113** located in the wall **105**.

[0103] By way of the summary module **165**, the partial results of the stand-alone wall diagnostics of the different regions of the wall **105** provided in the individual processing paths **102** can be summarized to a contiguous diagnostic result **109**. The contiguous diagnostic result describes the wall diagnostics of a contiguous spatial area that was scanned during movement of the measuring device **100** relative to the wall **105** and depicted by the corresponding captured radar data **103**. The parallel processing of the radar data **103** or additional sensor information **104** of the additional sensor elements in the different processing paths **102** thus enables accelerated wall diagnostics.

[0104] Alternatively, various wall diagnostic functions may also be performed in the different processing paths **102**. For example, in one processing path **102**, the wall type classification and the determination of the wall type **123** of the wall **105** to be examined can be performed. In another processing path **102**, object recognition of the object **113** located in the wall can be performed. The object detection can be performed with the determination of the object position **115** and the object classification can be performed with the determination of the object type **113** in one processing

path **102**.

[0105] Alternatively, the object detection and object classification may then also be performed in two separate processing paths **102**. In further processing paths **102**, the object depth determination, i.e., the determination of the object depth **119** and/or the determination of the object extension **121** may each be carried out. In the summary module **165**, the various partial results of the wall diagnostics may be summarized into corresponding diagnostic results **109**.

[0106] The diagnostic module **107** can be divided into different artificial intelligence structures **125**, as already shown in the embodiment in FIG. 2. For example, the diagnostic module **107** may comprise a wall type classification module **129** and an object recognition module **131**. The object recognition module may in turn be divided into an object detection module and an object classification module. The diagnostic module **107** may further comprise an object depth determination module and object extension module, respectively configured to determine the object depth **119** and the object extension **121**.

[0107] The respective modules may each be configured as stand-alone artificial intelligence structures **125**, for example, neural networks. Alternatively, the various modules may form portions of an overall artificial neural network that are connected to an overall neural network according to structures known from prior art.

[0108] FIG. 4 shows a schematic illustration of a measurement by the measuring device **100** according to one embodiment.

[0109] For pre-processing, the radar data **103** or the additional sensor information **104** of the remaining sensors may be normalized, in particular to numerically stabilize the subsequent steps performed by the diagnostic module **107** during the wall diagnostics. For example, an amplitude and/or offset compensation may be performed for this purpose. Moreover, to reduce interference, filtering of the radar data **103** may be carried out, and to reduce the data rate, the corresponding sensor data may be sampled. Additionally, the radar data **103** or the additional sensor information **104** may be transformed into the respectively required frequency range or time range. Methods known from the prior art can be used for this purpose.

[0110] Furthermore, the captured radar data **103** or additional sensor information **104** may be divided into temporal or spatial windows **167**. Temporal windows **167** may be generated by recording the radar data **103** or the additional sensor information or the pre-processed radar data **103** over a fixed time interval. Spatial windows **167**, on the other hand, may be generated from a mapping of the radar data **103** or additional sensor information **104** to positions of the measuring device **100** relative to the wall **105** along the direction of movement **153**.

[0111] Graph a) of FIG. 4 shows such a data matrix resulting from the steps described above. The data matrix of the window **167** shown in graph a) shows a plurality of sensor data **173**, which may comprise, for example, radar data **103** or additional sensor information **104** of the further sensors plotted along a frequency channel axis **171** or along a space/time axis **169**, respectively.

[0112] A width of the temporal windows **167** may be selected such that different sampling rates of the sensors may be balanced and a new window **167** may be provided frequently enough so that a display of the diagnostic results **109** of the wall diagnostics in the display unit **111** may be shown without too great of a time delay while the measurement is being performed or shortly after the measurement by the measuring device **100** ends.

[0113] A rate of 2 to 20 windows per second of the data recording of the sensor data **173** may be advantageous for this purpose. For spatial windows, the spatial sampling rates can be selected to achieve the desired local accuracy. Advantageously, 1 mm to 1 cm sampling rates can be used. This means that corresponding sensor data **173** is captured every 1 mm to 1 cm of movement of the measuring device **100** along the direction of movement **153**.

[0114] A width of the spatial windows **167** may be selected such that contiguous information relating to an object **113** is contained in a window. Advantageously, a width of the respective spatial windows **167** can be 1 cm to 20 cm. This results in 4 to 100 measured values per window **167**. This

allows for further efficient algorithmic processing of the correspondingly recorded radar data **103** or additional sensor information by the diagnostic module **107**.

[0115] A further temporal window **167** or spatial window **167** can be provided as soon as one or more sampling points are available.

[0116] The diagnostic module **107** may be oriented such that a matrix corresponding to the window size of the respective spatial or temporal window **167** may be included as input data, for example of each processing path **102** of the embodiment in FIG. **3** as well. According to the embodiment in FIG. **2**, the corresponding input data can comprise the respective pre-processed sensor data, i.e. radar data **103** and additional sensor information **104** of the additional sensors.

[0117] As stated above, the wall diagnostics may be performed by the diagnostic module **107** based on a correspondingly trained artificial intelligence. Alternatively, different processing paths may also be calculated by way of rule-based algorithms. In addition, within a processing path **102**, a combination of artificial intelligence and rule-based algorithm is possible in the form of a parallel operation or concatenation.

[0118] The diagnostic results **109** of the wall diagnostics may be expressed as numeric values, vectors, or matrices. Furthermore, for the object detection, the probability of detection, or for the wall type classification and/or the object classification, respectively, a probability of the specified object classes and/or wall type classifications can be indicated. The same may apply to the position and/or depth determination, for which corresponding probability values can also be indicated.

[0119] In addition to the radar data **103**, if the additional sensor information of the further sensor types is processed in a processing path **102**, these may either be merged within the artificial intelligence **125** or combined by way of rule-based combinations.

[0120] During the post-processing of each processing path **102**, of the embodiment in FIG. **3**, multiple algorithm results based on multiple windows **167** may be summarized by the summary module **165**. This summary can in particular be realized by way of majority formation, sum formation or also by multiplication of successive probability values.

[0121] Furthermore, by clustering multiple results, for example, it is possible to detect which objects, of multiple detected objects located close to one another, are the same object so that they are not incorrectly detected multiple times.

[0122] Likewise, it is possible to multiplicatively apply a weighting function **177** when summarizing the results from multiple windows **167**. Advantageously, the diagnostic partial results **175** corresponding to corresponding data points in the space may be weighted with respect to positioning of the diagnostic partial results **175** relative to a center point of the respective window **167**. This is illustrated by way of example in graph b), in which the individual diagnostic partial results **175** are weighted according to the weighting function **177** shown with respect to the center point of the window **167** shown.

[0123] According to one embodiment, the results of one processing path **102** after post-processing **163** may influence the extension of another processing path **102**. Weighting parameters may be adjusted that may depend on the particular result from the processing path **102** for each window.

[0124] For example, the result of an object classification in which the object type **117** of an object located in the wall **105** is defined, can be used to increase the weight of a wall type classification, in which the wall type **123** of the respective wall **105** is determined, during the post-processing at locations without objects **113**, because the respective radar data **103** at these locations is less influenced by reflections of the objects **113**.

[0125] FIG. **5** shows a further schematic representation of the measuring device **100** according to a further embodiment.

[0126] Graphs a) and b) of FIG. **5** show two different alternatives of joint data processing of radar data **103** and additional sensor information **104** by the diagnostic module **107**.

[0127] Graph b) illustrates a joint processing of the radar data **103** and the additional sensor information **104** of the additional sensors by the diagnostic module **107**. For this purpose, the radar

data **103** and the additional sensor information **104** are collectively used as input data of the diagnostic module **107** configured as an artificial intelligence, in particular as an artificial neural network. The diagnostic module **107** here comprises multiple convolutions **108** and multiple dense layers **106**. The radar data **103** and the additional sensor information **104** are processed jointly as input data via the convolutions **108** and dense layers **106**. The aforementioned diagnostic results **109** are created as output data of the diagnostic module **107** based on this.

[0128] On the other hand, in graph b) the radar data **103** and the additional sensor information **104** are used as stand-alone input data of the diagnostic module **107**. The diagnostic module **107** becomes multiple processing paths **102**. The processing paths **102** each comprise multiple convolutions **108** and at least one dense layer **106**. In the various processing paths **102**, wall diagnostics are performed separately by the diagnostic module **107** based on the radar data **103** and the additional sensor information **104**, respectively.

[0129] In an additional concatenation layer **148**, the partial results of the partial diagnostics of the different processing paths **102** are combined and fed to a final dense layer **106**. The output data of the diagnostic module **107** corresponds to the diagnostic results **109** described above.

[0130] The correspondingly configured diagnostic module **107** is configured to perform wall diagnostics as described above, including the features described above, based on the radar data **103** and the additional sensor information **104**.

[0131] In the embodiment shown, the diagnostic module **107** is configured as an artificial neural network, in particular as a convolutional network. Corresponding network architectures with convolutions **108**, dense layers **106**, and concatenation layers **148** are known from the prior art.

[0132] FIG. **6** shows a schematic representation of a system **600** for operating a measuring device **100** according to one embodiment.

[0133] In the embodiment shown, the system **600** for operating a measuring device **100** comprises an external server unit **114** in addition to the measuring device **100**.

[0134] According to the disclosure, the measuring device **100** is configured to perform the wall diagnostics of the wall **105** to be examined including the objects **113** disposed therein using the diagnostic module **107** based on the radar data **103** of the radar sensor unit **101** and, if necessary, taking into account the additional sensor information **104**.

[0135] According to the disclosure, the wall diagnostics comprises at least determining the wall type **123** of the wall **105** and/or determining the object position **115** and/or the object type **117** of the at least one object **113** disposed in the wall. The correspondingly provided diagnostic results **109** thus include at least the determined wall type **123** and/or the determined object position **115** and/or the object type **117**.

[0136] Alternatively, the wall diagnostics may also include determining the object depth **119** and/or the object extent **121**.

[0137] According to the disclosure, feedback information **112** is determined by the measuring device **100**. Feedback information **112** describes a match of the diagnostic results **109** with a current state of the wall **105**. The current state of the wall **105** relates to the actual present wall type **123** and/or the actual present object position **115** or the actual object type **117** of the at least one object **113** disposed in the wall.

[0138] In the embodiment shown, the feedback information **112** of the measuring device **100** is provided to the external server unit **114**. The external server unit **114** is configured to use the feedback information **112** to improve the software of the diagnostic module **107**, for example, by re-training the diagnostic module **107**. In particular, the external server unit **114** is configured to generate a training dataset **143** for re-training the diagnostic module **107**, taking into account the feedback information **112**.

[0139] According to one embodiment, radar data **103** may be provided by the measuring device **100** of the external server unit **114** along with the feedback information **112**, on the basis of which the wall diagnostics were performed by the diagnostic module **107** to which the feedback

information **112** was provided by the user of the measuring device.

[0140] In the embodiment shown, the measuring device **100** further provides a first selection function **116** and a second selection function **118**.

[0141] Via the first selection function **116**, the user of the measuring device **100** may select a wall type **123** and/or an object position **115** and/or an object type **117** and/or an object depth **119** and/or an object extent **121** from a plurality of possible wall types **123** provided by the measuring device **100** and/or a plurality of possible object positions **115** and/or a plurality of possible object types **117** and/or a plurality of possible object depths **119** and/or a plurality of possible object extents **121**, provided as diagnostic results **109** by the diagnostic module **107** during wall diagnostics. The user may thus select the diagnostic results **109** which, in their opinion, best reflect the actual state of the wall **105** by actuating the first selection function **116**.

[0142] By way of the second selection function **118**, the user may deactivate the automatic wall type determination. Further, the user may manually input a present wall type **123**.

[0143] In the embodiment shown, the measuring device **100** further provides a feedback function **122**. The feedback function **122** allows the user to provide direct feedback on whether the wall diagnostics match the actual state of the wall **105**.

[0144] For this purpose, the selection commands **120** of the first and second selection functions **116**, **118** input by the user are received from the diagnostic module **107**. The selection commands **120** here describe the selections made by the user from the diagnostic results **109** provided by the diagnostic module **107** by actuating the first selection function **116** and/or the second selection function **118** or by terminating the automatic performance of the wall type determination.

[0145] Further, corresponding feedback commands **124** of the feedback function **122** may be received by the diagnostic module **107**. The feedback commands **124** include the feedback information **112** provided by the user by actuating the feedback function **122**.

[0146] In addition to the feedback commands **124**, the measuring device **100** is configured to determine the feedback information **112** based on the selection commands **120** of the first and second selection functions **116**, **118**. For example, if a plurality of possible wall types **123** are provided, selecting one of the wall types **123** will provide positive feedback regarding the respective wall type **123** selected, while negatively evaluating the non-selected wall types **123**, respectively. Accordingly, when the second selection function **118** is activated, in which the automatic wall type determination is deactivated, negative feedback is registered regarding the wall type determination. The same applies to the selections for the further diagnostic results **109**.

[0147] According to one embodiment, the diagnostic module **107** is further configured to determine deviations between the repeated wall diagnostics or diagnostic results **109** during the wall diagnostics respectively performed at the same positions of the measuring device **100** relative to the wall **105**.

[0148] Further, the measuring device **100** is configured to display the corresponding deviations in the display unit **111**. By actuating the feedback function **122**, the user can confirm or refute the deviations with corresponding feedback commands **124**.

[0149] For example, the selection commands **120** and/or the feedback commands **124** may be input by controls **154**. Alternatively, the display unit **111** may be configured as a touch screen, for example, via which the selection commands **120** and/or feedback commands **124** can be input by the user.

[0150] The deviations between the diagnostic results **109** of the different wall diagnoses for the same position of the measuring device **100** relative to the wall **105** may be determined using the diagnostic module **107**, for example, by comparative processes between the diagnostic results **109** determined in the different wall diagnostics at different times. For this purpose, the diagnostic module **107** may comprise a correspondingly configured comparison module.

[0151] FIG. 7 shows a flowchart of a method **200** for operating a measuring device **100** according to one embodiment.

[0152] To operate the measuring device **100**, the radar data **103** of the radar sensor unit **101** of the measuring device **100** depicting the wall **105** to be diagnosed is first received in a method step **201**.

[0153] In another method step **203**, the wall diagnostics are performed by the diagnostic module **107** based on the radar data **103**, and diagnostic results **109** are provided.

[0154] For this purpose, a wall type classification is carried out by the diagnostic module **107** and the wall type **123** of the wall **105** is determined in a method step **205**.

[0155] In a further method step **207**, an object recognition of the at least one object **113** disposed in the wall **105** is performed by the diagnostic module **107**. The object recognition includes an object detection and the determination of the object position **115** and the object classification with the determination of the object type **117**. The diagnostic results **109** provided by the diagnostic module **107** include at least the object position **115** and/or the object type **117** and the wall type **123**, respectively.

[0156] Further, feedback information **112** is determined in a method step **209**. Feedback information **112** describes whether the diagnostic results **109** match the current state of the wall **105**.

[0157] FIG. **8** shows another flowchart of the method **200** for operating a measuring device **100** according to a further embodiment.

[0158] The embodiment shown in FIG. **8** is based on the embodiment in FIG. **7** and comprises all the method steps described there.

[0159] In the embodiment shown, the wall diagnostics further comprises performing the object depth determination and determining the object depth **119** of the object **113** in a method step **213**.

[0160] Further, in a method step **215**, the object extension determination is performed and the object extension **121** of the object **113** is determined.

[0161] Further, in a method step **211**, the feedback information **112** is provided to an external server unit **114** to take the feedback information **112** into consideration in an update to the diagnostic module **107**.

[0162] FIG. **9** shows another flowchart of the method **200** for operating a measuring device **100** according to a further embodiment.

[0163] The embodiment shown in FIG. **9** is based on the embodiment in FIG. **8** and comprises all the method steps described there.

[0164] In the embodiment shown, the first selection function **116** and/or the second selection function **118** is provided in a method step **217**.

[0165] By performing the first selection function **116**, a suitable wall type **123** and/or a suitable object position **115** and/or a suitable object type **117** and/or a suitable object depth **119** and/or a suitable object extent **121** can be selected from the plurality of possible wall types **123** and/or possible object positions **115** and/or possible object types **117** and/or possible object depths **119** and/or possible object extents **121**.

[0166] By performing the second selection function **118**, the automatic wall type determination may be disabled and the wall type **123** may be manually selected.

[0167] Further, the feedback function **122** is provided in a further method step **219**. By actuating the feedback function **122**, the user can provide the feedback information **112**. The feedback information **112** may be used to provide the feedback regarding whether the provided diagnostic results **109** match the actual state of the wall **105**.

[0168] In the embodiment shown, determining **209** the feedback information **112** further includes receiving selection commands **120** from the first and/or second selection functions **116**, **118**, and/or feedback commands **124** from the feedback function **122** and determining the feedback information **112** based on the selection commands **120** and/or the feedback commands **124** in a method step **221**.

[0169] Further, in a method step **223**, the diagnostic module **107** determines whether there are deviations from the diagnostic results **109** determined in the wall diagnostics in repeated wall

diagnostics of a same position of the measuring device **100** relative to the wall **105**.

[0170] In a further method step **225**, the deviations are displayed in the display unit **111**.

[0171] In a further method step **227**, feedback commands **124** are received regarding the deviations, wherein the displayed deviations are confirmed or rejected in the feedback commands **124**.

[0172] According to one embodiment, the corresponding radar data **103** on which the wall diagnostics were previously performed is provided in the external server unit **114**, in addition to the feedback information **112**. The feedback information **112** may be provided to the external server unit **114** by a plurality of measuring devices **100** that are in use by users.

[0173] FIG. **10** shows a flowchart of a method **400** for generating a training dataset for training an artificial intelligence **125** of a measuring device **100** according to one embodiment.

[0174] To train the artificial intelligence, in a first method step **401**, firstly the training dataset **143** generated according to method **200** is provided, wherein the training dataset **143** comprises the radar data **103** depicting the wall **105** to be diagnosed and the at least one object **113** configured in the wall **105** and the feedback information **112** provided according to method **200** for operating a measuring device **100** according to any of the preceding embodiments.

[0175] In a further method step **403**, the artificial intelligence **125** is trained based on the training dataset **143** and taking into account feedback information **112** for performing an object recognition of an object **113** formed in a wall **105**. The training is carried out in such a way that the feedback information **112** is considered by the correspondingly trained artificial intelligence when performing the wall diagnostics.

[0176] FIG. **11** shows a schematic representation of a computer program product **500** comprising instructions that, when the program is executed by a data processing unit, cause the latter to perform the method **200** for operating a measuring device **100** and/or the method **400** for training an artificial intelligence **125**.

[0177] In the embodiment shown, the computer program product **500** is stored on a storage medium **501**. The storage medium **501** can in this case be any desired storage medium known from the prior art.

Claims

1. A computer-implemented method of operating a measuring device, comprising: receiving radar data of a radar sensor unit of the measuring device, wherein the radar data depicts a wall on which diagnostics are to be performed; and performing wall diagnostics by performing an analysis of the radar data and providing diagnostic results by a diagnostic module of the measuring device, wherein the performing wall diagnostics comprise: performing a wall type classification and determining a wall type of the wall by way of the diagnostic module, wherein the diagnostic results comprise at least the wall type of the wall; and/or performing an object recognition of an object disposed in the wall using the diagnostic module, wherein the object recognition comprises an object detection and an object classification and determining an object position in the wall and an object type of the object, and wherein the diagnostic results comprise at least the object position and/or the object type; and determining feedback information, wherein the feedback information describes whether the diagnostic results match a current state of the wall.

2. The method according to claim 1, further comprising: providing the feedback information to an external server unit to take the feedback information into account in an update to the diagnostic module.

3. The method of claim 2, wherein in addition to the feedback information, the corresponding radar data is provided to the external server unit.

4. The method of claim 1, wherein the performing wall diagnostics further comprises: performing an object depth determination and determining an object depth of the object in the wall using the

diagnostic module, wherein the object depth is defined as a distance of the object to a surface of the wall; and/or performing an object extent determination and determining an object extent of the object along a predefined direction using the diagnostic module, wherein the diagnostic results further comprise at least the object depth and/or the object extent of the object.

5. The method of claim 1, wherein a plurality of possible object positions and/or a plurality of possible object types of the object are determined in the object recognition as stand-alone diagnostic results, and/or wherein a plurality of possible wall types of the wall are determined in the wall type classification as independent diagnostic results, and/or wherein a plurality of possible object depths are determined as stand-alone diagnostic results in the object depth determination and/or wherein a plurality of possible object extents of the object are determined in the object extent determination as stand-alone diagnostic results, wherein each of the plurality of diagnostic results is displayed in a display unit of the measuring device.

6. The method according to claim 5, further comprising: providing a first selection function and/or a second selection function, wherein at least one of the displayed wall types and/or one of the displayed object positions and/or object types and/or object depths and/or object extents is selectable by a user of the measuring device by performing the first selection function, and/or wherein the automatic determination of the wall type can be deactivated during the wall diagnostics and/or the display of the automatically determined wall type in the display unit can be deactivated by the user of the measuring device by performing the second selection function, and a wall type is manually selectable by the user.

7. The method according to claim 6, further comprising: providing a feedback function, wherein, when the user performs the feedback function, they can indicate whether the displayed wall type and/or the displayed object position and/or the displayed object type and/or the displayed object depth and/or the displayed object extent match the actual wall type and/or the actual object position and/or the actual object type and/or the actual object depth and/or the actual object extent.

8. The method of claim 6, wherein determining the feedback information comprises: receiving selection commands from the first and/or second selection function and/or feedback commands from the feedback function and determining the feedback information based on the selection commands and/or feedback commands, wherein corresponding selections are made in the selection commands, according to the first and/or second selection functions, and wherein corresponding feedback information provided by the user is included in the feedback commands.

9. The method according to claim 1, wherein determining the feedback information comprises: determining, using the diagnostic module, whether there are deviations from the diagnostic results determined in the wall diagnostics when repeated diagnostics are carried out for a same position of the measuring device relative to the wall; displaying the deviations in the display unit; and receiving feedback commands from the user regarding the deviations, wherein the displayed deviations are confirmed or refuted in the feedback commands.

10. The method according to claim 1, wherein the measuring device further comprises at least one of an induction sensor and/or an eddy current sensor and/or a capacitance sensor and/or an AC current sensor and/or an NMR sensor and/or an ultrasonic sensor for providing additional sensor data, and wherein the diagnostic module is configured to perform the wall diagnostics by taking into account the additional sensor data.

11. The method according to claim 1, wherein the diagnostic module comprises at least one correspondingly trained artificial intelligence configured to perform object detection and/or a wall classification and/or an object depth determination and/or an object extension determination based on the radar data and/or the additional sensor data.

12. The method according to claim 1, wherein object classes of the object type of the object comprise: metallic/non-metallic object, low voltage cable, magnetic/non-magnetic objects, cable with single phase AC signal, cable with multiphase AC signal, wood beam, metal beam, plastic pipe, water filled plastic pipe, non-water filled plastic pipe, and/or wherein the wall type classes of

the wall type of the wall comprise: concrete wall, plasterboard/drywall wall, brick wall and/or bricks of the wall, underfloor heating, wall heating.

13. A method for training an artificial intelligence of a measuring device, comprising: providing a training dataset for training the artificial intelligence, wherein the training dataset comprises a wall and radar data depicting an object formed in the wall, as well as the feedback information provided according to the method for operating a measuring device according to claim 1; and training the artificial intelligence based on the training dataset and taking into account the feedback information for performing object recognition of an object formed in a wall, wherein the object recognition comprises at least one of object detection and object classification.

14. A computing unit configured to perform the method for operating a measuring device according to claim 1.

15. A computer program product comprising instructions that, when the program is executed by a data processing unit, cause the latter to perform the method for operating a measuring device according to claim 1.

16. The method according to claim 1, wherein the measuring device is a wall diagnostic device.

17. The method according to claim 12, wherein: the water filled plastic pipe is a fresh water pipe, and the non-water filled plastic pipe is a waste water pipe.

18. A computing unit configured to perform the method for training an artificial intelligence of a measuring device for wall diagnostics according to claim 13.

19. A computer program product comprising instructions that, when the program is executed by a data processing unit, cause the latter to perform the method for training an artificial intelligence of a measuring device to perform wall diagnostics according to claim 13.
