


(19) **United States**(12) **Patent Application Publication**
WIND et al.(10) **Pub. No.: US 2025/0278718 A1**(43) **Pub. Date: Sep. 4, 2025**(54) **SYSTEMS AND METHODS FOR DYNAMIC
APPLICATION OF TOKENS IN CREDIT
AUTHORIZATION**(71) Applicant: **Worldpay, LLC**, Symmes Township,
OH (US)(72) Inventors: **Andrew WIND**, Minneapolis, MN
(US); **Derrick KOES**, Pelham, NH
(US); **Tao HONG**, Acton, MA (US)(21) Appl. No.: **19/213,527**(22) Filed: **May 20, 2025****Related U.S. Application Data**(63) Continuation of application No. 16/718,444, filed on
Dec. 18, 2019, now Pat. No. 12,333,525.**Publication Classification**(51) **Int. Cl.**
G06Q 20/36 (2012.01)
G06Q 20/02 (2012.01)
G06Q 20/20 (2012.01)
G06Q 20/38 (2012.01)
G06Q 20/40 (2012.01)(52) **U.S. Cl.**CPC **G06Q 20/3674** (2013.01); **G06Q 20/02**
(2013.01); **G06Q 20/20** (2013.01); **G06Q**
20/381 (2013.01); **G06Q 20/401** (2013.01);
G06Q 20/4097 (2013.01); **G06Q 2220/123**
(2013.01)(57) **ABSTRACT**

A computer-implemented method for optimizing transaction authorization conversion rates based on the use of network tokens may include receiving, at an acquirer processor, a payment transaction from a merchant, determining whether the payment transaction includes a network token, upon determining that the payment transaction does not include a network token, determining whether the payment transaction should be modified to include a network token based on a likelihood that the payment transaction will be authorized by a financial institution will be increased when the payment transaction includes a network token, upon determining whether the payment transaction should be modified to include a network token, obtaining a network token for the payment transaction, and modifying the payment transaction to include the obtained network token, and submitting the modified payment transaction to the financial institution for processing.






FIG. 1

134




FIG. 2





FIG. 3

**FIG. 4**




FIG. 5

508




FIG. 6




FIG. 7

SYSTEMS AND METHODS FOR DYNAMIC APPLICATION OF TOKENS IN CREDIT AUTHORIZATION

CROSS-REFERENCE TO RELATED APPLICATION(S)

[0001] This application is a continuation of and claims the benefit of priority to U.S. Non-provisional patent application Ser. No. 16/718,444, filed Dec. 18, 2019, the entirety of which is incorporated by reference herein.

TECHNICAL FIELD

[0002] Various embodiments of the present disclosure relate generally to the field of electronic transaction processing and, more particularly, to optimizing authorization requests for higher transaction conversion rates.

BACKGROUND

[0003] Electronic transactions and networks are used for a great number of purchases and sales between merchants and bank card holders. A normal bank card transaction may involve a number of parties, including an account holder who possesses a card, a merchant, an acquirer processor, an issuer processor, an issuer financial institution, and a card association network. Millions of such transactions occur daily at merchants using a variety of payment card types, such as credit cards, debit cards, prepaid cards, and so forth. A transaction based on account information received from an account holder may be declined for a number of different reasons, such as insufficient funds, card expiration, expired account information, or a variety of other occurrences. However, additional factors, such as the presence or absence of some items of account information, may also affect the rate of acceptance, or conversion, of payment transactions.

[0004] In addition, one reality of the modern Internet-connected world is that the storage and transfer of sensitive and secure electronic data is potentially vulnerable to data breaches. Further, as electronic systems, such as point of sales ("POS") systems, become more complex, and as hackers become more sophisticated, security concerns are continually increasing.

[0005] In the early days of electronic transactions, dedicated magnetic card readers would scan unencrypted sensitive data on a credit card and transfer it to a transaction service for completion of the transaction. These communications were typically made over a dial-up connection and required basic encryption in the reader device in order to maintain security of the packet.

[0006] Over time, the reader devices have become more advanced, often with Internet connections and data input ports that enable malware to infect POS terminals. Further, as more and more merchants have moved to transfer data over the Internet, additional security features have been developed.

[0007] Most notably, "tokenization" is a means for replacing sensitive data with a "token" of data that may be non-decryptable or non-detokenizable by the merchant or other tokenization users (e.g. because they require third party decryption). Merchants, for example, might not ever store sensitive data themselves, thus enhancing data security.

[0008] Tokenization has become a popular method for securing payment transaction data (e.g., primary account numbers, etc.) and many disparate token service providers

have emerged to provide this functionality. A client, such as a merchant, may want to bundle functionalities from multiple transaction processing services that do not share common token service providers. Since each token service provider may be proprietary and may not share data with others, there has been no option for a client to operate across token boundaries (i.e., across transaction platforms utilizing disparate tokens) in a secure manner.

[0009] Financial institutions, thus, may have a preference for transaction requests including tokenized data and may preferentially approve such transactions even in the presence of other factors that may lead to a declined transaction. Declined transactions may lead to a variety of undesirable outcomes for the merchant and the account holder. Conventional methods for submitting electronic transactions may submit such transactions according to factors specific to the acquirer processor or to the merchant, but do not consider factors that might be shown to affect transaction conversion in past transactions, including the use of network tokens.

[0010] The present disclosure is directed to overcoming one or more of these above-referenced challenges.

SUMMARY OF THE DISCLOSURE

[0011] According to certain aspects of the present disclosure, systems and methods are disclosed for optimizing transaction authorization conversion rates based on the use of network tokens.

[0012] In one embodiment, a computer-implemented method is disclosed for optimizing transaction authorization conversion rates based on the use of network tokens, the method comprising: receiving, at an acquirer processor, a payment transaction from a merchant, determining whether the payment transaction includes a network token, upon determining that the payment transaction does not include a network token, determining whether the payment transaction should be modified to include a network token based on a likelihood that the payment transaction will be authorized by a financial institution will be increased when the payment transaction includes a network token, upon determining whether the payment transaction should be modified to include a network token, obtaining a network token for the payment transaction, and modifying the payment transaction to include the obtained network token, and submitting the modified payment transaction to the financial institution for processing.

[0013] In accordance with another embodiment, a system is disclosed for optimizing transaction authorization conversion rates based on the use of network tokens, the system comprising: a data storage device storing instructions for optimizing transaction authorization conversion rates based on the use of network tokens in an electronic storage medium; and a processor configured to execute the instructions to perform a method including: receiving, at an acquirer processor, a payment transaction from a merchant, determining whether the payment transaction includes a network token, upon determining that the payment transaction does not include a network token, determining whether the payment transaction should be modified to include a network token based on a likelihood that the payment transaction will be authorized by a financial institution will be increased when the payment transaction includes a network token, upon determining whether the payment transaction should be modified to include a network token, obtaining a network token for the payment transaction, and

modifying the payment transaction to include the obtained network token, and submitting the modified payment transaction to the financial institution for processing.

[0014] In accordance with another embodiment, a non-transitory machine-readable medium storing instructions that, when executed by the a computing system, causes the computing system to perform a method for optimizing transaction authorization conversion rates based on the use of network tokens, the method including: receiving, at an acquirer processor, a payment transaction from a merchant, determining whether the payment transaction includes a network token, upon determining that the payment transaction does not include a network token, determining whether the payment transaction should be modified to include a network token based on a likelihood that the payment transaction will be authorized by a financial institution will be increased when the payment transaction includes a network token, upon determining whether the payment transaction should be modified to include a network token, obtaining a network token for the payment transaction, and modifying the payment transaction to include the obtained network token, and submitting the modified payment transaction to the financial institution for processing.

[0015] Additional objects and advantages of the disclosed embodiments will be set forth in part in the description that follows, and in part will be apparent from the description, or may be learned by practice of the disclosed embodiments. The objects and advantages of the disclosed embodiments will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims.

[0016] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the disclosed embodiments, as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate various exemplary embodiments and together with the description, serve to explain the principles of the disclosed embodiments.

[0018] FIG. 1 depicts a block diagram of an example payment system and network in which optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments.

[0019] FIG. 2 depicts a dataset of processing results, according to one or more embodiments.

[0020] FIG. 3 depicts a block diagram of an example process logic flow for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments.

[0021] FIG. 4 is a flow chart depicting an example process for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments.

[0022] FIG. 5 depicts a block diagram of an example system and process flow for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments.

[0023] FIG. 6 depicts a block diagram of an example process logic flow and modules for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments.

[0024] FIG. 7 depicts a computing device for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments.

DETAILED DESCRIPTION OF EMBODIMENTS

[0025] While principles of the present disclosure are described herein with reference to illustrative embodiments for particular applications, it should be understood that the disclosure is not limited thereto. Those having ordinary skill in the art and access to the teachings provided herein will recognize additional modifications, applications, embodiments, and substitution of equivalents all fall within the scope of the embodiments described herein. Accordingly, the invention is not to be considered as limited by the foregoing description.

[0026] Various non-limiting embodiments of the present disclosure will now be described to provide an overall understanding of the principles of the structure, function, and use of systems and methods disclosed herein for the scheduling of transaction payment requests.

[0027] For simplicity, the description that follows will be provided by reference to a “payment vehicle,” which generally refers to any type of financial alternative to currency. As is to be clear to those skilled in the art, no aspect of the present disclosure is limited to a specific type of payment vehicle. Therefore, it is intended that the following description encompasses the use of the present disclosed techniques with many other forms of financial alternatives to currency, including credit cards, debit cards, smart cards, single-use cards, pre-paid cards, electronic currency (such as might be provided through a cellular telephone or personal digital assistant), and the like. Payment vehicles may be traditional plastic transaction cards, titanium-containing, or other metal-containing, transaction cards, clear and/or translucent transaction cards, foldable or otherwise unconventionally-sized transaction cards, radio-frequency enabled transaction cards, or other types of transaction cards, such as credit, charge, debit, pre-paid or stored-value cards, or any other like financial transaction instrument. A payment vehicle may also have electronic functionality provided by a network of electronic circuitry that is printed or otherwise incorporated onto or within the payment vehicle (and typically referred to as a “smart card”), or be a fob having a transponder and an RFID reader, or may operate as a mobile wallet or by near field communication (NFC).

[0028] Tokenization of payment vehicle information in authorization requests is used as a method to provide data security for sensitive data, such as a primary account number (PAN). Through tokenization, a requesting client may be given non-sensitive reference data in exchange for the sensitive data elements. The reference data may be considered non-sensitive since the associated sensitive data may only be retrieved through security controls that authenticate and authorize the requestor. This allows clients to store non-sensitive reference data and to offload any sensitive data storage to tokenization providers, reducing auditing requirements as well as any potential sensitive data loss should a security incident occur.

[0029] The following discussion relates to methods and systems for optimizing authorization requests for higher transaction conversion rates through dynamic use of network tokens during authorization. Such methods and systems may infer the sensitivity of payment vehicle issuer

preferences for the use of network tokens and may dynamically change elements of an authorization to improve the likelihood of approval.

[0030] As described above, declined transaction payment requests may lead to undesirable outcomes, and associated increased costs, for merchants and account holders. Thus, the embodiments of the present disclosure are directed to improving (i.e., increasing) the successful authorization of transaction payment requests.

[0031] In accordance with one or more embodiments, and as described in more detail below, an acquirer processor may maintain a database of past transactions and the associated authorization results. Analysis of these transaction results by statistical methods or other means may be used to determine patterns of acceptance or denial of transaction payment requests based on factors associated with the transactions, including, for example, presence of a billing address, presence of a card verification code (CVV), the merchant categorization code (MCC), presence of an expiration date, etc. The transaction may be modified with respect to these factors, as determined at least in part by such an analysis of historical authorization success rates. According to one or more embodiments, a modified authorization request may be submitted to the payment network.

[0032] One or more examples of these non-limiting embodiments are illustrated in the selected examples disclosed and described in detail with reference to FIGS. 1-7 in the accompanying drawings. Those of ordinary skill in the art will understand that systems and methods specifically described herein and illustrated in the accompanying drawings are non-limiting embodiments. The features illustrated or described in connection with one non-limiting embodiment may be combined with the features of other non-limiting embodiments. Such modifications and variations are intended to be included within the scope of the present disclosure.

[0033] FIG. 1 depicts a block diagram of an example payment environment 100 for optimizing transaction authorization conversion rates based on the use of network tokens. In the example payment environment 100, a payment vehicle 126 (e.g., a credit card) may be issued to an account holder 113 by an issuer financial institution 114. Issuer financial institution 114 may be any of a variety of financial institutions that is capable of issuing a payment vehicle to an account holder. Payment vehicle 126 may be used to pay a merchant 116 for a purchase transaction at a merchant point of sale (POS) device 118. Merchant POS device 118 may be any device that facilitates receipt of a payment vehicle for payment of a purchase, such as for example, a POS terminal or a web interface. Further, merchant 116 may be any type of merchant or service provider, such as, for example, a brick-and-mortar merchant, an online merchant, a mobile merchant, a kiosk, or any other type of merchant or device configured to receive payment cards, or electronic or mobile wallets, from account holders as a form of payment.

[0034] POS device 118 may be configured to interact with payment vehicle 126 to obtain account information about a consumer account affiliated with account holder 113. As shown in the depicted callout of POS device 118, in one or more embodiments, POS device 118 may include a memory 167 coupled to processor 151, which may control the operations of a reader 163, an input device 153, an output device 165, and a network interface 161. Memory 167 may

store instructions for processor 151 and/or data, such as, for example, an identifier that is associated with merchant account 112.

[0035] In one or more embodiments, reader 163 may include a magnetic strip reader. In one or more embodiments, reader 163 may include a contactless reader, such as, for example, a radio frequency identification (RFID) reader, a near field communications (NFC) device configured to read data via magnetic field coupling (in accordance with ISO standard 14443/NFC), a Bluetooth transceiver, a Wi-Fi transceiver, an infrared transceiver, a laser scanner, and so forth.

[0036] In one or more embodiments, input device 153 may include key buttons that may be used to enter the account information directly into POS device 118 without the physical presence of payment vehicle 126. Input device 153 may be configured to provide further information to initiate a transaction, such as, for example, a personal identification number (PIN), password, zip code, etc., or in combination with the account information obtained from payment vehicle 126. In one or more embodiments, output device 165 may include a display, a speaker, and/or a printer to present information, such as, for example, the result of an authorization request, a receipt for the transaction, an advertisement, and so forth.

[0037] In one or more embodiments, network interface 161 may be configured to communicate with acquirer processor 122 such as, for example, via a telephone connection, an Internet connection, or a dedicated data communication channel.

[0038] In one or more embodiments, the instructions stored in memory 167 may be configured at least to cause POS device 118 to send an authorization request message to acquirer processor 122 to initiate a transaction. POS device 118 may or may not send a separate request for the clearing and settling of the transaction. The instructions stored in memory 167 also may be configured to cause POS device 118 to perform other types of functions discussed in this description.

[0039] In one or more embodiments, POS device 118 may have fewer components than those illustrated in FIG. 1. For example, in one or more embodiments, POS device 118 may be configured for “card-not-present” transactions; and POS device 118 may not have a reader 163. In one or more embodiments, POS device 118 may have more components than those illustrated in FIG. 1.

[0040] During a purchase event, merchant POS device 118 may send an authorization request 120 for the purchase transaction to acquirer processor 122 that processes payment vehicle transactions for merchant 116. Additional intermediary entities, such as one or more payment gateways, may assist with the handling and routing of authorization request 120 or other related messaging. For the purposes of illustration, such intermediary entities may be considered part of acquirer processor 122. Authorization request 120 may include identifying information from payment vehicle 126, such as a BIN number, an expiration date, and a first and last name of the account holder, for example. Authorization request 120 may further include identifying information from the purchase, such as an amount and identifying information from merchant POS device 118 and/or merchant 116, for example.

[0041] In one or more embodiments, payment vehicle 126 may be used to establish a recurring billing arrangement

between account holder **113** and merchant **116**. An initial transaction may allow merchant **116** to store account information that may be used for subsequent billing events. The account information may be stored in a cards-on-file storage **136**. For example, the purchase event illustrated in FIG. 1 may be associated with a subscription, membership plan, installment payment plan between merchant **116** and account holder **113**, and so on. For subsequent transactions, merchant **116** may access cards-on-file storage **136** to retrieve the relevant account information. The subsequent transactions may not require direct involvement from account holder **113**. In one or more embodiments, account holder **113** may trigger the subsequent transaction, but may not provide payment vehicle **126** to merchant **116**, as merchant **116** may access the cardholder's account information in cards-on-file storage **136**.

[0042] A payment processing computing system **124** at acquirer processor **122** may receive authorization request **120** from merchant **116**. A network token and cryptogram for authorization request **120** may be obtained by dynamic network token service **138**, such as by a request to network token service provider **140**.

[0043] The network token may be, for example, a randomly generated number. The token may also be a pseudo-random number, encrypted information, or other character sequence. The token may be unique per customer/person or account number per merchant or organization. Thus, if a given user makes a purchase at merchant A, token A may be generated, but if a given user makes a purchase at merchant B, even if using the same credit card, token B may be generated.

[0044] By relying upon a token, a merchant system **116** may no longer be required to send credit card information or other sensitive data for subsequent transactions, and may instead use the token, such as for follow-up activities. For example, a restaurant may initially run a transaction for the cost of a meal, and perform a follow-up transaction using the token for processing the tip. Alternatively, in a card-not-present context, an online merchant may run multiple transactions for a recurring web subscription using one or more tokens. Another example may include recurring transactions for a gym membership. A merchant may use tokens for returns or price adjustments rather than resending sensitive transaction information over a network. Using tokenization, a merchant or merchant may enhance security by not storing sensitive data of customers on its own systems.

[0045] The operation of dynamic network token service **138** and network token service provider **140** will be discussed in greater detail below.

[0046] Payment processing computing system **124** may translate authorization request **120**, if necessary, and may provide authorization request **120** to a payment network **142**. Payment network **142** may be, for example, a network of a credit card association affiliated with payment vehicle **126**. Nonlimiting examples of credit card associations include VISA, MASTERCARD, DISCOVER, and AMERICAN EXPRESS, and so on. Authorization request **120** then may be provided to a payment processing computing system **128** at an issuer processor **130**. In response to receiving the authorization request, and based on the type of payment vehicle **126**, payment processing computing system **128** may provide authorization request **120** to issuer financial institution **114**. Using information from authorization request **120**, issuer financial institution **114** may associate

the purchase transaction with an account **131** of account holder **113** held by issuer financial institution **114**. Issuer financial institution **114** then may send an authorization response **132** which may either approve or deny the transaction. Authorization response **132** may be provided to payment processing computing system **128** at issuer processor **130** and then provided to payment network **142**. Authorization response **132** then may be provided to payment processing computing system **124** at acquirer processor **122**. Upon receiving authorization response **132**, payment processing computing system **124** may send either an approval message or a denial message to merchant POS device **118** to complete the purchase transaction. If the purchase transaction is approved, it may be posted to account holder's account **131** and reconciled later with account holder **113** and merchant **116**.

[0047] Transaction records may be stored in one or more locations within system **100**. In one or more embodiments, the transaction record may be stored within a transaction data database **134** of acquirer processor **122**. The transaction data may be received by transaction data database **134** from various sources, such as merchant POS device **118**, merchant **116**, acquirer processor **122**, and so on. A plurality of transaction parameters associated with the purchase transaction may be stored in each transaction record, which may generally be used for settlement and financial recordkeeping. While the transaction parameters stored in each transaction record may vary, example transaction parameters may include, without limitation, account number, card number, payment vehicle information, product information (such as product type, product serial number, and so forth), loyalty account information, merchant information, transaction amount, response code, transaction date, transaction time, whether the transaction was a "card present" transaction, and so on.

[0048] FIG. 2 depicts a dataset of processing results, according to one or more embodiments. Dataset of processing results **134** may include historical transaction information that may be processed and analyzed in order to optimize transaction conversion rates, as shown in FIG. 3 based on, for example, an analysis of trends and/or correlations. Dataset **134** may include transaction parameters **220** such as, for example, a billing address **222**, a card verification value (CVV) **224**, whether a network token **226** was submitted, a payment vehicle expiration date **228**, a payment vehicle issuer token **230**, a merchant classification code (MCC) **236**, and additional parameters **238**. Dataset **134** may also include an authorization result **240**, which may indicate whether the particular combination of transaction parameters **220** led to an authorization (**232**) and a reason response code (RRC) related to the authorization result (**234**). Further, while dataset of processing results **134** may include many different transaction parameters **220**, in some embodiments only a subset of the parameters may be used for optimizing transaction authorization conversion rates.

[0049] FIG. 3 depicts a block diagram of an example process logic flow for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments. As shown in FIG. 3, a process for optimizing transaction authorization conversion rates may include identifying factors for authorization of transaction requests to produce a database of transaction requests **134**. For example, such identification may include applying data science methods to database of transaction

requests **134**. However, other methods may be used such as machine learning, etc. Database of transaction requests **134** may further include information produced by performance manager **355** based on issuer preferences **365** and factor success data **360**, possibly in conjunction with a process or generating and updating factor success data **360**. For example, performance manager **355** may interpret issuer preferences **365** to determine whether an issuer associated with payment vehicle **126** prefers to receive network token for an authorization request, such as authorization request **120**. However, analysis of factor success data **360** may indicate that for some authorization requests, issuer preferences **365** may be overridden with respect to the use of a network token. Issuer preferences **365** may include preferences for the specification of other transaction parameters **220**. Performance manager **355** may interpret issuer preferences **365** with respect to these parameters and may give added weight to the issuer preferences. However, issuer preferences **365** may be overridden with respect to the setting or alteration of these transaction parameters.

[0050] Factor success data **360** may aggregate test and control groups. Data stored in factor success data **360** may be used to determine the effectiveness of optimizing transaction requests, such as by comparing results for optimized transactions (test transactions) and non-optimized transactions (control transaction). Such a determination may be specific to particular factors employed for optimization of test transactions. Factor success data **360** may further include measurement, for example, at the level of the specific issuer and account range (generally associated with a card product of a particular issuer), of the sensitivity of a factor. That is, an assessment of whether a manipulation (inclusion, exclusion, alteration) of a factor resulted in an improvement or decrease in the rate of authorization approvals at that issuer/account range. Performance manager **355** may automatically calibrate optimization factors employed by dynamic network token service **138** through analysis of factor success data **360** and transaction scenarios stored in dataset of processing results **134**. Performance management may include, for example, the modification of prior rules based on continuing assessment of the results from transactions sent to the issuer/account range. It may include and take into account negative results besides the authorization denial, such as an increase in the rate of chargebacks or fraud alerts generated by the issuer. These negative effects may occur, for example, even if the authorization is approved.

[0051] A merchant, such as merchant **116** depicted in FIG. 1, may submit a transaction request, such as authorization request **120** depicted in FIG. 1, to acquirer processor **122**. The transaction request may be interpreted by dynamic network token service **138** of the acquirer processor based on the database of transaction requests, issuer preferences **365**, and the factor success data **360**. For example, if preferred by issuer preferences **365** and supported by the analysis performed by performance manager **355**, dynamic network token service (DNTS) **138** may call network token service provider (NTSP) **140** to obtain a network token and cryptogram. In some embodiments, the call to the NTSP may return immediately before generating the network token. This ensures that the NTSP call has low latency and may allow the dynamic network token service to continue processing the request without waiting for the initial NTSP call to complete. Once the network token is prepared, or the processing by the NTSP is otherwise completed, the network

token or other processing result may be returned to the dynamic network token service by any of a callback method, shared memory, or any other suitable means.

[0052] If a network token is obtained from NTSP **140**, authorization request **120** may be altered to include the network token in place of sensitive information. Authorization request **120** may then be provided to payment network **142**. In some embodiments, the network token may be used for subsequent related transactions including, for example, deposit transactions, refund transactions, and authorization reversal transactions. Use of the network token for subsequent related transactions may facilitate identification of related transactions during later processing.

[0053] In some embodiments, a cryptogram returned by NTSP **140** may be provided to issuer processor **130**. The cryptogram may be provided in the authorization request or through an alternative communication channel. Issuer processor **130** may utilize the cryptogram while processing an authorization request including a network token. Providing the cryptogram to issuer processor **130** may ensure that the authorization request is accepted.

[0054] In some embodiments, if an authorization request including a network token is declined then DNTS **138** may resubmit the authorization request with the sensitive information restored in place of the network token.

[0055] In some embodiments, DNTS **138** may validate the formatting of data items returned by NTSP **140**. For example, if a date format for an expiration date of a network token returned by NTSP **140** does not match a format required by issuer processor **130**, DNTS **138** may correct the format of the date or may substitute a null date.

[0056] In some embodiments, DNTS **138** may handle generated network tokens on behalf of merchant **116** without the knowledge of merchant **116** and without changing the behavior of other portions of the system. For example, a chargeback for a transaction submitted with a generated network token may be marked with the deposit identifier of the matching deposit rather than the generated network token. In another scenario, detailed information for a chargeback may show both the generated network token as well as the deposit's identifier. That is, when the chargeback has a deposit ID and the deposit has a different account number than the chargeback then a display of the chargeback case detail may show the sensitive information of the transaction, such as the PAN along with the network token information. In another scenario, when a chargeback is entered for a transaction submitted with a generated network token that is different from the original deposit's account number, a search of transaction information using the original deposit's account number may return both the original deposit transaction and the chargeback.

[0057] In some embodiments, DNTS **138** may recognize that a transaction request includes a network token and may not generate an additional network token for the transaction request.

[0058] In some embodiments, DNTS **138** may not request a network token from NTSP **140** if the transaction request is for a refund transaction.

[0059] The transaction processing by the acquirer processor may also include a validation and reporting functions, such as A/B testing and reporting of authorization success metrics **340**. Such reporting functions may further include

storing communications between DNTS **138** and NTSP **140** for later analysis and diagnosis of transaction request failures.

[0060] FIG. 4 is a flow chart depicting an example process for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments. As shown in FIG. 4, at operation **405**, acquirer processor **122** may generate factor success data, such as factor success data **360** depicted in FIG. 3, from a dataset of processing results, such as transaction database **134** depicted in FIG. 1, and issuer preferences **365** depicted in FIG. 3. For example, generating factor success data may include applying data science methods, machine learning, or other suitable methods to the dataset of processing results. At operation **410**, acquirer processor **122** may receive a payment transaction from a merchant, such as merchant **116** depicted in FIG. 1. The payment transaction may include, in addition to a transaction amount, primary account identifier, customer identification, etc., for example, a billing address, a card verification value (CVV), a payment processing network, a payment vehicle expiration date, a payment vehicle issuer token, a merchant classification code (MCC), and additional parameters. At operation **415**, acquirer processor **122** may determine parameters of the payment transaction, such as authorization request **120** depicted in FIG. 1. Determining the parameters of the payment transaction may include identifying parameters that are not present in the transaction, such as the CVV, expiration data, billing address, etc. At operation **420**, acquirer processor **122** may compare one or more parameters of the payment transaction to the factor success data. Such comparison may include applying factor weights from the factor success data to the parameters of the transaction. Such factor weights may be determined by any suitable method, including, for example, statistical methods including regression analysis, machine learning, artificial intelligence methods such as neural networks, etc. At operation **425**, acquirer processor **122** may compare one or more parameters of the payment transaction to issuer preferences for network tokens. For example, issuer preferences **365** may indicate that a network token should be used for all transactions, for no transactions, or for transactions having particular combinations of transaction parameters. At operation **430** acquirer processor **122** may determine whether to use a network token based on the parameters of the payment transaction and the issuer preferences. If acquirer processor **122** determines a network token should be used, then at operation **435**, acquirer processor **122** may obtain network token and cryptogram from a network token service provider, such as network token service provider **140** depicted in FIG. 3. Processing may then continue with operation **440**. At operation **440**, acquirer processor **122** may submit the transaction for processing by an issuer processor, such as issuer processor **130** depicted in FIG. 1. If a network token was obtained in operation **435**, then the transaction may be modified to include the network token in place of sensitive information prior to submission to the issuer processor. At operation **445**, acquirer processor **122** may receive a transaction authorization result from the issuer processor. At operation **450**, acquirer processor **122** may add the transaction authorization result and the parameters of the payment transaction to the dataset of processing results. The process may then resume at operation **405** in order to process subsequent transactions.

[0061] FIG. 5 depicts a block diagram of an example process flow for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments. A payment transaction **506** may be received from a merchant **502** by an acquirer processor **508**. Payment transaction **506** may be based on account information **504** maintained by merchant **502**, or elsewhere, as may be appropriate. Payment transaction **506** may include typical transaction data, such as, for example, an amount, an account identifier, a billing address, a card verification value (CVV), a payment vehicle expiration date, a payment vehicle issuer token, a merchant classification code (MCC), etc. At least some of the transaction data transmitted in the payment transaction may include data that was originally received by merchant **502** during an initial payment transaction originating with a payment vehicle and stored in a cards-on-file storage **136**, for example. A payment processing computing system of acquirer processor **508** may determine the card association that is affiliated with the payment transaction **506** (e.g., VISA, MASTERCARD, and so forth), to determine the proper processing channels for the transaction such as, for example, a payment processing network.

[0062] Acquirer processor **508** may transmit an authorization attempt or transaction request **514** to a payment network, which in turn may transmit transaction request **516** to an issuer financial institution **518**. Issuer financial institution **518** may approve or reject the authorization request based on a status of a financial account **530** associated with the transaction or cardholder, or other factors, such as, for example, the presence or absence of a billing address, the presence or absence of a card verification value (CVV), the presence or absence of a payment vehicle expiration date, the presence or absence of a payment vehicle issuer token, a merchant classification code (MCC), a selection of a payment processing network, etc. Generally, all authorization requests include an MCC, however some merchants view certain MCCs as riskier than others and therefore the selection of which MCC to include in the authorization requests—assuming the merchant qualifies for more than one—can influence the approval. Issuer financial institution **518** may also preferentially approve transactions including a network token. Such preferential processing may lead to inconsistencies in approval rates between transaction requests including sensitive information, such as a primary account number (PAN), and those including a network token. Such preferential processing may result from issuer financial institution **518** applying distinct fraud rule sets for authorizations including a network token and those including a PAN. These unique rule sets can establish preferences for a specific attribute by issuers for a given authorization. Acquirer processor **508** may store such issuer preferences, whether specified expressly by issuer financial institution **518** or inferred by acquirer processor **508**, in issuer preferences database **365**. A determination of whether to submit payment transaction **506** with a network token may be made by dynamic network token service **138** of acquirer processor **138**. If dynamic network token service **138** determines that a network token will be included in payment transaction **506**, such a network token may be obtained, for example, from network token service provider **140**.

[0063] Acquirer processor **508** may communicate the authorization result of transaction request **516** to merchant **502** by, for example, an authorization response **507**. Finan-

cial account **530** can be any suitable account, such as a DDA account, a gift card account, a prepaid account, or any other type of account that can be linked to or accessed by payment vehicle. The available account balance of financial account **530** may vary over time as the account holder withdraws funds and deposits funds. Transaction requests may be rejected, for example, for reasons associated with financial account **530**, such as non-sufficient funds, out-of-date account information, parameters provided with or absent from the transaction request etc. Acquirer processor **508** may store factors associated with transaction request **516**, including the inclusion of sensitive information or a network token in the transaction request, in dataset of processing results **134** that may be used to determine a likelihood of authorization or conversion for subsequent transaction requests. As described above with respect to FIG. 2, factors associated with transaction request **516** may include, for example, billing address **222**, card verification value (CVV) **224**, payment processing network **226**, payment vehicle expiration date **228**, presence of a payment vehicle issuer token **230**, merchant classification code (MCC) **236**, additional parameters **238**, reason response code (RRC) **234**, and so forth. In accordance with one or more embodiments, acquirer processor **508** may, as discussed in greater detail below in reference to FIG. 6, include performance manager **355** to process payment transaction **506** based on transaction data **134** and factor success data **360**.

[0064] FIG. 6 depicts a block diagram of an example process logic flow and modules for optimizing transaction authorization conversion rates based on the use of network tokens, according to one or more embodiments. As shown in FIG. 6, acquirer processor **508** may receive payment transaction **506**. Payment transaction **506** may include transaction data such as, for example, a billing address **622**, a card verification value (CVV) **624**, a payment processing network **626**, a payment vehicle expiration date **628**, a payment vehicle issuer token **630**, a merchant classification code (MCC) **636**. Payment transaction **506** may include additional parameters not shown in FIG. 6. Performance manager **355** of acquirer processor **508** may take in the transaction data for processing. Such processing may include querying dataset of processing results **134** for other potentially corresponding transactions. Performance manager **355** may further read factor success metrics from factor success data **360** as well as issuer preference data **365**, as shown in FIG. 5. Based on the corresponding transaction data received from dataset of processing results **134**, issuer preference data **365**, and the factor success metrics from factor success data **360**, performance manager **355** may determine that the likelihood of obtaining authorization for payment transaction **506** from issuer financial institution **518** may be improved by altering the presentation of one or more aspects of the transaction data. For example performance manager **355** may determine that presentation of payment transaction **506** with a network token in place of sensitive information, such as a primary account number (PAN), may improve the likelihood of obtaining authorization. In particular, transaction data received from dataset of processing results **134**, issuer preference data **365**, and the factor success metrics from factor success data **360** may indicate that the issuer financial institution **518** may preferentially approve transaction requests including a network token over transaction requests including sensitive information.

[0065] Use of a network token may be combined with other alterations to the transaction information. For example, performance manager **355** may determine that the likelihood of obtaining authorization for payment transaction **506** from issuer financial institution **518** may be improved by altering the presentation of one or more aspects of the transaction data. For example, performance manager **355** may determine that presentation of payment transaction **506** without billing address information may improve the likelihood of obtaining authorization. In particular, transaction data received from dataset of processing results **134** and the factor success metrics from factor success data **360** may indicate that the issuer financial institution **518** may issue two responses: one indicating overall approval or denial, and one indicating whether transaction information, such as, for example, a supplied billing address, matches account information on file with the issuer financial institution **518**. If issuer financial institution **518** is known to authorize transactions lacking certain transaction information and deny transactions having mismatched information, then presenting payment transaction **506** without potentially may improve the likelihood of obtaining authorization. Similarly, transaction data received from dataset of processing results **134** and the factor success metrics from factor success data **360** may indicate that omitting CVV **624** or expiration date **628** when presenting payment transaction **506** may improve the likelihood of obtaining authorization. In addition, a merchant may qualify for multiple different MCCs based on the nature of the businesses conducted by the merchant. Transaction data received from dataset of processing results **134** and the factor success metrics from factor success data **360** may indicate that one of the available MCCs may have a greater likelihood of obtaining authorization. performance manager **355** may, accordingly, present payment transaction **506** with the MCC with the greatest likelihood of obtaining authorization. Likewise, transaction request **506** may have multiple payment networks **532** available for submission to issuer financial institution **518** for processing. Transaction data received from dataset of processing results **134** and the factor success metrics from factor success data **360** may indicate that one of the available payment networks **532** may yield a greater likelihood of obtaining authorization. Performance manager **355** may, accordingly, select the payment network with the greatest likelihood of obtaining authorization.

[0066] Upon completing the processing of payment transaction, performance manager **355** may appropriately modify payment transaction **506** based on the processing of payment transaction **506**. For example, if a network token is to be included in payment transaction **506**, a network token and cryptogram may be obtained by dynamic network token service **138**, such as by a request to network token service provider **140**. A modified transaction request **514** may be submitted to issuer financial institution **518** by way of payment network **514**.

[0067] The processes described herein may be performed on or between one or more computing devices that are specially configured to perform the processing described herein. Referring now to FIG. 7, an example computing device **700** is presented. A computing device **700** may be, for example, a server, a computing device that is integrated with other systems or subsystems, a mobile computing device, a cloud-based computing capability, and so forth. The computing device **700** can be any suitable computing device as

would be understood in the art, including without limitation, for example, a custom chip, an embedded processing device, a tablet computing device, a POS device **118**, a payment processing computing system **124**, a payment processing computing system **128**, a personal data assistant (PDA), a desktop, a laptop, a microcomputer, a minicomputer, a server, a mainframe, or any other suitable programmable device. According to one or more embodiments, a single component can be replaced by multiple components and multiple components can be replaced by a single component to perform a given function or functions. Except where such substitution would not be operative, such substitution is within the intended scope of the one or more embodiments.

[0068] The computing device **700** may include a processor **702** that may be any suitable type of processing unit such as, for example, a general purpose central processing unit (CPU), a reduced instruction set computer (RISC), a processor that has a pipeline or multiple processing capability including having multiple cores, a complex instruction set computer (CISC), a digital signal processor (DSP), an application specific integrated circuits (ASIC), a programmable logic devices (PLD), and a field programmable gate array (FPGA), among others. The computing resources may further include, for example, distributed computing devices, cloud computing resources, and virtual computing resources in general, etc.

[0069] The computing device **700** also may include one or more memories **706** such as, for example, read only memory (ROM), random access memory (RAM), cache memory associated with the processor **702**, or other memories such as dynamic RAM (DRAM), static ram (SRAM), programmable ROM (PROM), electrically erasable PROM (EEPROM), flash memory, a removable memory card or disk, a solid state drive, and so forth. The computing device **700** also may include storage media such as, for example, a storage device that can be configured to have multiple modules, such as magnetic disk drives, floppy drives, tape drives, hard drives, optical drives and media, magneto-optical drives and media, compact disk drives, Compact Disk Read Only Memory (CD-ROM), Compact Disk Recordable (CD-R), Compact Disk Rewriteable (CD-RW), a suitable type of Digital Versatile Disk (DVD) or BluRay disk, and so forth. Storage media such as flash drives, solid state hard drives, redundant array of individual disks (RAID), virtual drives, networked drives and other memory means including storage media on the processor **702**, or memories **706** are also contemplated as storage devices. It can be appreciated that such memory can be internal or external with respect to operation of the disclosed embodiments. It can be appreciated that certain portions of the processes described herein may be performed using instructions stored on a non-transitory computer-readable medium or media that direct a computer system to perform the process steps. Non-transitory computer-readable media, as used herein, comprises all computer-readable media except for transitory, propagating signals.

[0070] Network and communication interfaces **712** may be configured to transmit to, or receive data from, other computing devices **700** across a network **714**. The network and communication interfaces **712** may be, for example, an Ethernet interface, a radio interface, a Universal Serial Bus (USB) interface, or any other suitable communications interface and can include receivers, transmitter, and transceivers. For purposes of clarity, a transceiver may be referred to as

a receiver or a transmitter when referring to only the input or only the output functionality of the transceiver. Example communication interfaces **712** may include, for example, wired data transmission links such as Ethernet and TCP/IP. The communication interfaces **712** may include, for example, wireless protocols for interfacing with private or public networks **714**. For example, the network and communication interfaces **712** and protocols may include interfaces for communicating with private wireless networks such as, for example, a Wi-Fi network, one of the IEEE 802.11x family of networks, or another suitable wireless network. The network and communication interfaces **712** may include interfaces and protocols for communicating with public wireless networks **712**, using, for example, wireless protocols used by cellular network providers, including Code Division Multiple Access (CDMA) and Global System for Mobile Communications (GSM), etc. A computing device **700** may use network and communication interfaces **712** to communicate with hardware modules such as, for example, a database or data store, or one or more servers or other networked computing resources. Data may be encrypted or protected from unauthorized access.

[0071] According to one or more embodiments, the computing device **700** may include a system bus **716** for interconnecting the various components of the computing device **700**, or the computing device **700** may be integrated into one or more chips such as, for example, a programmable logic device or an application specific integrated circuit (ASIC), etc. The system bus **716** may include, for example, a memory controller, a local bus, or a peripheral bus for supporting input and output devices **704**, and communication interfaces **712**, etc. Example input and output devices **704** may include keyboards, keypads, gesture or graphical input devices, motion input devices, touchscreen interfaces, one or more displays, audio units, voice recognition units, vibratory devices, computer mice, and any other suitable user interface.

[0072] The processor **702** and memory **706** may include nonvolatile memory for storing, for example, computer-readable instructions, data, data structures, program modules, code, microcode, and other software components for storing the computer-readable instructions in non-transitory computer-readable mediums in connection with the other hardware components for carrying out the methodologies described herein. Software components may include, for example, source code, compiled code, interpreted code, executable code, static code, dynamic code, encrypted code, or any other suitable type of code or computer instructions implemented using any suitable methodology including, for example, high-level, low-level, object-oriented, visual, compiled, or interpreted programming language, etc.

[0073] These and other embodiments of the systems and methods may be used as would be recognized by those skilled in the art. The above descriptions of various systems and methods are intended to illustrate specific examples and describe certain ways of making and using the systems disclosed and described here. These descriptions are neither intended to be nor should be taken as an exhaustive list of the possible ways in which these systems can be made and used. A number of modifications, including substitutions of systems between or among examples and variations among combinations can be made. Those modifications and variations should be apparent to those of ordinary skill in this area after having read this disclosure.

[0074] The systems, apparatuses, devices, and methods disclosed herein are described in detail by way of examples and with reference to the figures. The examples discussed herein are examples only and are provided to assist in the explanation of the apparatuses, devices, systems and methods described herein. None of the features or components shown in the drawings or discussed below should be taken as mandatory for any specific implementation of any of these the apparatuses, devices, systems or methods unless specifically designated as mandatory. For ease of reading and clarity, certain components, modules, or methods may be described solely in connection with a specific figure. In this disclosure, any identification of specific techniques, arrangements, etc., are either related to a specific example presented or are merely a general description of such a technique, arrangement, etc. Identifications of specific details or examples are not intended to be, and should not be, construed as mandatory or limiting unless specifically designated as such. Any failure to specifically describe a combination or sub-combination of components should not be understood as an indication that any combination or sub-combination is not possible. It will be appreciated that modifications to disclosed and described examples, arrangements, configurations, components, elements, apparatuses, devices, systems, methods, etc., can be made and may be desired for a specific application. Also, for any methods described, regardless of whether the method is described in conjunction with a flow diagram, it should be understood that unless otherwise specified or required by context, any explicit or implicit ordering of steps performed in the execution of a method does not imply that those steps must be performed in the order presented but instead may be performed in a different order or in parallel.

[0075] Reference throughout the specification to “various embodiments,” “some embodiments,” “one embodiment,” “some example embodiments,” “one example embodiment,” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with any embodiment is included in at least one embodiment. Thus, appearances of the phrases “in various embodiments,” “in some embodiments,” “in one embodiment,” “some example embodiments,” “one example embodiment,” or “in an embodiment” in places throughout the specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more embodiments.

[0076] Throughout this disclosure, references to components or modules generally refer to items that logically can be grouped together to perform a function or group of related functions. Like reference numerals are generally intended to refer to the same or similar components. Components and modules can be implemented in software, hardware, or a combination of software and hardware. The term “software” is used expansively to include not only executable code, for example machine-executable or machine-interpretable instructions, but also data structures, data stores and computing instructions stored in any suitable electronic format, including firmware, and embedded software. The terms “information” and “data” are used expansively and includes a wide variety of electronic information, including executable code; content such as text, video data, and audio data, among others; and various codes or flags. The terms “information,” “data,” and “content” are sometimes used inter-

changeably when permitted by context. It should be noted that although for clarity and to aid in understanding some examples discussed herein might describe specific features or functions as part of a specific component or module, or as occurring at a specific layer of a computing device (for example, a hardware layer, operating system layer, or application layer), those features or functions may be implemented as part of a different component or module or operated at a different layer of a communication protocol stack. Those of ordinary skill in the art will recognize that the systems, apparatuses, devices, and methods described herein can be applied to, or easily modified for use with, other types of equipment, can use other arrangements of computing systems such as client-server distributed systems, and can use other protocols, or operate at other layers in communication protocol stacks, than are described.

[0077] It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims.

What is claimed is:

1. A computer-implemented method for optimizing authorization rates based on use of network tokens, the computer-implemented method comprising:

receiving, via a network interface, a payment transaction from a point of sale (POS) device as a first data structure including identifying information from one or more of a payment vehicle or a purchase;

determining, via a processor, whether the first data structure includes a network token associated with the identifying information;

determining, via the processor, a first likelihood of authorization approval based at least in part on the first data structure;

determining, via the processor, a second likelihood of authorization approval based at least in part on the first data structure not including the network token and supplementing the first data structure with a generated network token;

determining, via the processor, that a second data structure should be generated based on the second likelihood exceeding the first likelihood by a threshold;

sending, via the processor, a request to a network token service provider, for the generated network token;

modifying, by the processor, the first data structure to include the generated network token to obtain the second data structure; and

transmitting, by the processor, the second data structure for approval.

2. The computer-implemented method of claim 1, wherein the network token is obtained from the network token service provider using a dynamic network token service.

3. The computer-implemented method of claim 1, wherein a likelihood that the second data structure will be authorized by a financial institution is determined based on predetermined preferences of the financial institution.

4. The computer-implemented method of claim 3, wherein the likelihood that the second data structure will be authorized by the financial institution is further determined based on authorization success factors for each of a plurality of payment transaction parameters based on parameters retrieved from payment transaction parameters and authorization results for a plurality of past payment transactions retrieved from a database.

5. The computer-implemented method of claim 4, further comprising:

- comparing the parameters retrieved from the payment transaction to the authorization success factors; and
- modifying each parameter of the payment transaction where the authorization success factors indicate a greater likelihood of authorization of the payment transaction.

6. The computer-implemented method of claim 1, further comprising:

- obtaining a cryptogram corresponding to the network token; and
- providing the cryptogram to a financial institution.

7. The computer-implemented method of claim 1, further comprising:

- determining a merchant classification code having a greatest likelihood of authorization among a plurality of qualifying merchant classification codes for a merchant based on a viewed risk of the qualifying merchant classification codes by the merchant; and
- modifying the second data structure to include the merchant classification code having the greatest likelihood of authorization among the plurality of qualifying merchant classification codes for the merchant, wherein the merchant classification code classifies transactions according to a type of merchant.

8. The computer-implemented method of claim 1, further comprising:

- receiving an authorization result for the transmitted second data structure; and
- upon determining that the second data structure was not approved, transmitting the first data structure.

9. A system for optimizing authorization rates based on use of network tokens, the system comprising:

- a data storage device storing instructions for optimizing the authorization rates based on the use of the network tokens in an electronic storage medium; and
- one or more processors configured to execute the instructions to perform a method including:

- receiving, via a network interface, a payment transaction from a point of sale (POS) device as a first data structure including identifying information from one or more of a payment vehicle or a purchase;

- determining, via the one or more processors, whether the first data structure includes a network token associated with the identifying information;

- determining, via the one or more processors, a first likelihood of authorization approval based at least in part on the first data structure;

- determining, via the one or more processors, a second likelihood of authorization approval based at least in part on the first data structure not including the network token and supplementing the first data structure with a generated network token;

- determining, via the one or more processors, that a second data structure should be generated based on the second likelihood exceeding the first likelihood by a threshold;
- sending, via the one or more processors, a request to a network token service provider, for the generated network token;

- modifying, by the one or more processors, the first data structure to include the generated network token to obtain a second data structure; and

- transmitting, by the one or more processors, the second data structure for approval.

10. The system of claim 9, wherein a likelihood that the second data structure will be authorized by a financial institution is determined based on predetermined preferences of the financial institution.

11. The system of claim 10, wherein the likelihood that the second data structure will be authorized by the financial institution is further determined based on authorization success factors for each of a plurality of payment transaction parameters based on parameters retrieved from the payment transaction parameters and authorization results for a plurality of past payment transactions retrieved from a database.

12. The system of claim 11, wherein the system is further configured for:

- comparing the parameters retrieved from the payment transaction to the authorization success factors; and
- modifying each parameter of the payment transaction where the authorization success factors indicate a greater likelihood of authorization of the payment transaction.

13. A non-transitory machine-readable medium storing instructions that, when executed by a computing system, causes the computing system to perform a method for optimizing authorization rates based on use of network tokens, the method including:

- receiving, via a network interface, a payment transaction from a point of sale (POS) device as a first data structure including identifying information from one or more of a payment vehicle or a purchase;

- determining, via a processor, whether the first data structure includes a network token associated with the identifying information;

- determining, via the processor, a first likelihood of authorization approval based at least in part on the first data structure;

- determining, via the processor, a second likelihood of authorization approval based at least in part on the first data structure not including the network token and supplementing the first data structure with a generated network token;

- determining, via the processor, that a second data structure should be generated based on the second likelihood exceeding the first likelihood by a threshold;

- sending, via the processor, a request to a network token service provider, for the generated network token;

- modifying, by the processor, the first data structure to include the generated network token to obtain a second data structure; and

- transmitting, by the processor, the second data structure for approval.

14. The non-transitory machine-readable medium of claim 13, wherein the network token is obtained from the network token service provider using a dynamic network token service.

15. The non-transitory machine-readable medium of claim 13, wherein a likelihood that the second data structure will be authorized by a financial institution is determined based on predetermined preferences of the financial institution.

16. The non-transitory machine-readable medium of claim 15, wherein the likelihood that the second data structure will be authorized by the financial institution is further determined based on authorization success factors for each

of a plurality of payment transaction parameters based on parameters retrieved from the payment transaction parameters and authorization results for a plurality of past payment transactions retrieved from a database.

17. The non-transitory machine-readable medium of claim **16**, the method further comprising:

comparing the parameters retrieved from the payment transaction to the authorization success factors; and
modifying each parameter of the payment transaction where the authorization success factors indicate a greater likelihood of authorization of the payment transaction.

18. The non-transitory machine-readable medium of claim **13**, the method further comprising:

obtaining a cryptogram corresponding to the obtained network token; and
providing the cryptogram to a financial institution.

19. The non-transitory machine-readable medium of claim **18**, wherein the obtained cryptogram is provided to the financial institution as part of the payment transaction.

20. The non-transitory machine-readable medium of claim **13**, the method further comprising:

receiving an authorization result for the transmitted second data structure; and
upon determining that the second data structure was not approved, transmitting the first data structure.

* * * * *