

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403423
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Carson; Christopher S. et al.

Systems and methods of renewable natural gas processing

Abstract

Example gas recovery systems include a source gas conditioning assembly configured to condition and compress the inlet source gas to provide a conditioned source gas, a first membrane assembly configured to separate the conditioned source gas into a hydrocarbon enriched stream and a recovery stream, a second membrane assembly fluidly coupled to the hydrocarbon enriched stream, and configured to separate the hydrocarbon enriched stream into a hydrocarbon product stream and a recycle stream, a carbon dioxide (CO₂) plant assembly fluidly coupled to the recovery stream configured to provide a carbon dioxide product stream and an enriched recycle stream, a standalone membrane assembly configured to separate the enriched recycle stream into a hydrocarbon enriched recycle stream and an effluent stream, and wherein the source gas conditioning assembly is fluidly coupled to the recycle stream and the hydrocarbon enriched recycle stream.

Inventors: Carson; Christopher S. (Bussum, NL), Leinwand; Noah A. (New York, NY), Leist; Casey J. (Atlanta, GA)

Applicant: Alchemy CO2, PBC (Atlanta, GA)

Family ID: 93794551

Assignee: Alchemy CO2, PBC (Atlanta, GA)

Appl. No.: 19/046317

Filed: February 05, 2025

Prior Publication Data

Document Identifier	Publication Date
US 20250177910 A1	Jun. 05, 2025

Related U.S. Application Data

continuation parent-doc WO PCT/US2024/033071 20240607 PENDING child-doc US 19046317
us-provisional-application US 63545070 20231020
us-provisional-application US 63471630 20230607
us-provisional-application US 63471626 20230607
us-provisional-application US 63471625 20230607
us-provisional-application US 63471624 20230607

Publication Classification

Int. Cl.: **B01D53/22** (20060101); **B01D53/00** (20060101); **B01D53/04** (20060101)

U.S. Cl.:

CPC **B01D53/226** (20130101); **B01D53/002** (20130101); **B01D53/04** (20130101);
 B01D53/229 (20130101); B01D2053/221 (20130101); B01D2256/22 (20130101);
 B01D2256/24 (20130101); B01D2256/245 (20130101); B01D2257/504 (20130101);
 B01D2258/05 (20130101); B01D2311/14 (20130101); C10L2290/10 (20130101);
 C10L2290/548 (20130101); F25J2210/66 (20130101); Y02C20/40 (20200801)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4374657	12/1982	Schendel et al.	N/A	N/A
4602477	12/1985	Lucadamo	N/A	N/A
4639257	12/1986	Duckett et al.	N/A	N/A
4659343	12/1986	Kelly	N/A	N/A
4701187	12/1986	Choe et al.	N/A	N/A
4772295	12/1987	Shibuya et al.	N/A	N/A
4936887	12/1989	Waldo et al.	N/A	N/A
5089034	12/1991	Markovs et al.	N/A	N/A
5727903	12/1997	Borray et al.	N/A	N/A
6128919	12/1999	Daus et al.	N/A	N/A
6572679	12/2002	Baker et al.	N/A	N/A
6610124	12/2002	Dolan et al.	N/A	N/A
6630011	12/2002	Baker et al.	N/A	N/A
8999038	12/2014	Ungerank et al.	N/A	N/A
11980846	12/2023	Bikson	N/A	N/A
12139681	12/2023	Bikson	N/A	N/A
12139682	12/2023	Bikson	N/A	N/A
2004/0018144	12/2003	Briscoe	N/A	N/A
2004/0099138	12/2003	Karode et al.	N/A	N/A
2004/0103782	12/2003	Wascheck et al.	N/A	N/A
2007/0166205	12/2006	Holst et al.	N/A	N/A

2007/0243127	12/2006	Fedorov et al.	N/A	N/A
2009/0165377	12/2008	Koh et al.	N/A	N/A
2010/0256245	12/2009	Iaccino et al.	N/A	N/A
2011/0094378	12/2010	Mitariten	N/A	N/A
2012/0121497	12/2011	Terrien et al.	N/A	N/A
2012/0180389	12/2011	Knaebel	N/A	N/A
2012/0291483	12/2011	Terrien et al.	N/A	N/A
2012/0292574	12/2011	Terrien et al.	N/A	N/A
2013/0131199	12/2012	Lien et al.	N/A	N/A
2013/0142720	12/2012	Chen et al.	N/A	N/A
2015/0122122	12/2014	W Mustapa et al.	N/A	N/A
2015/0323248	12/2014	Terrien	62/619	F25J 3/0223
2015/0360165	12/2014	Carson et al.	N/A	N/A
2016/0001219	12/2015	Ho et al.	N/A	N/A
2017/0283292	12/2016	Kim	N/A	B01D 53/226
2018/0133643	12/2017	Ho et al.	N/A	N/A
2018/0250627	12/2017	Zick et al.	N/A	N/A
2019/0030482	12/2018	Ding et al.	N/A	N/A
2019/0060835	12/2018	Ding et al.	N/A	N/A
2020/0203738	12/2019	Jolly et al.	N/A	N/A
2020/0307997	12/2019	Tranier	N/A	N/A
2023/0119784	12/2022	Reinertsen et al.	N/A	N/A
2024/0019205	12/2023	Prince	N/A	F25J 3/0257
2025/0035376	12/2024	Valentin	N/A	F25J 3/0252
2025/0066272	12/2024	O'brien et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
107758664	12/2017	CN	N/A
WO-2022055125	12/2021	WO	N/A
2024254496	12/2023	WO	N/A
2024254503	12/2023	WO	N/A
2024254510	12/2023	WO	N/A
2024254496	12/2024	WO	N/A
2024254503	12/2024	WO	N/A
2024254510	12/2024	WO	N/A

OTHER PUBLICATIONS

WO2022055125A1_Eng (Espacenet machine translation of Chang) (Year: 2022). cited by examiner

PCT/US2024/033071 , “International Application Serial No. PCT/US2024/033071, International Search Report and Written Opinion mailed Nov. 27, 2024”, Alchemy CO2, PBC, 34 pages. cited by applicant

PCT/US2024/033071 , “International Application Serial No. PCT/US2024/033071, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Sep. 12, 2024”, Alchemy CO2, PBC, 3 pages. cited by applicant

PCT/US2024/033079 , “International Application Serial No. PCT/US2024/033079, International Search Report and Written Opinion mailed Nov. 5, 2024”, Alchemy CO2, PBC, 19 pages. cited by applicant

PCT/US2024/033079 , “International Application Serial No. PCT/US2024/033079, Invitation to

Pay Additional Fees and, Where Applicable, Protest Fee mailed Sep. 10, 2024”, Alchemy CO2, PBC, 3 pages. cited by applicant
PCT/US2024/033087 , “International Application Serial No. PCT/US2024/033087, International Search Report and Written Opinion mailed Nov. 27, 2024”, Alchemy CO2, PBC, 25 pages. cited by applicant
PCT/US2024/033087 , “International Application Serial No. PCT/US2024/033087, Invitation to Pay Additional Fees and, Where Applicable, Protest Fee mailed Sep. 10, 2024”, Alchemy CO2, PBC, 3 pages. cited by applicant

Primary Examiner: Gitman; Gabriel E

Attorney, Agent or Firm: GTC Law Group PC & Affiliates

Background/Summary

CLAIM TO PRIORITY (1) This application is a continuation of PCT International Patent Application Serial Number PCT/US2024/033071 (ACO2-0001-WO), filed on Jun. 7, 2024, which is incorporated by reference herein for all purposes. (2) PCT/US2024/033071 relates to, incorporates by reference for all purposes, and claims priority to United States Application Ser. Nos. 63/471,624 filed Jun. 7, 2023 (2112.0003), 63/471,625 filed Jun. 7, 2023 (2112.0004), 63/471,626 filed Jun. 7, 2023 (2112.0005), 63/471,630 filed Jun. 7, 2023 (2112.0007), and 63/545,070 filed Oct. 20, 2023 (2112.0009).

BACKGROUND

(1) Presently known gas recovery systems suffer from a number of challenges. For example, recovery gas streams, such as landfill gas, have a number of constituents that are not primary natural gas constituents (e.g., methane). Accordingly, those constituents lead to excessive energy utilization to maintain high recycle rates, a significant portion of pumping energy committed to recycling non-valuable gas constituents, loss of hydrocarbon product gas to purge streams, or the like.

SUMMARY

(2) Example embodiments of the present disclosure provide for systems capable to perform essentially 100% recovery of a primary product (e.g., natural gas or methane) and a secondary product (e.g., CO.sub.2), from a gas source such as landfill gas and/or a biogas. Example embodiments of the present disclosure provide for gas compression costs and recycle rates for a membrane based gas recovery system. Example embodiments of the present disclosure utilize residual pressure from a CO.sub.2 plant to operate a standalone membrane, and/or drive recycle gas for the gas recovery system. Example embodiments of the present disclosure integrate secondary recovery of a primary product, for example from a standalone membrane, for recycling to a gas source (e.g., a hydrocarbon enriched stream) and/or to a CO.sub.2 plant (e.g., a CO.sub.2 enriched stream). Example embodiments of the present disclosure provide for a zero emission system.

(3) These and other systems, methods, objects, features, and advantages of the present disclosure will be apparent to those skilled in the art from the following detailed description of the preferred embodiment and the drawings.

(4) All documents mentioned herein are hereby incorporated in their entirety by reference. References to items in the singular should be understood to include items in the plural, and vice versa, unless explicitly stated otherwise or clear from the text. Grammatical conjunctions are

intended to express any and all disjunctive and conjunctive combinations of conjoined clauses, sentences, words, and the like, unless otherwise stated or clear from the context.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) The disclosure and the following detailed description of certain embodiments thereof may be understood by reference to the following figures:

(2) FIG. 1 depicts an example gas recovery system.

(3) FIG. 2 depicts an example gas recovery system.

(4) FIG. 3 depicts an example gas recovery system.

(5) FIG. 4 depicts an example gas recovery system.

(6) FIG. 5 depicts an example gas recovery system.

(7) FIG. 6 depicts an example gas recovery system.

(8) FIG. 7 depicts an example gas recovery system.

(9) FIG. 8 depicts an example gas recovery system.

(10) FIG. 9 depicts an example gas recovery system.

DETAILED DESCRIPTION

(11) Before the present disclosure is described in further detail, it is to be understood that the disclosure is not limited to the particular embodiments described. It is also understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting. The scope of the present disclosure will be limited only by the claims. As used herein, the singular forms “a”, “an”, and “the” include plural embodiments unless the context clearly dictates otherwise.

(12) In this application, unless otherwise clear from context, (i) the term “a” may be understood to mean “at least one”; (ii) the term “or” may be understood to mean “and/or”; (iii) the terms “comprising” and “including” may be understood to encompass itemized components or steps whether presented by themselves or together with one or more additional components or steps; and (iv) the terms “about” and “approximately” are used as equivalents and may be understood to permit standard variation as would be understood by those of ordinary skill in the art; and (v) where ranges are provided, endpoints are included.

(13) Composition: as used herein, may be used to refer to a discrete physical entity that comprises one or more specified components. In general, unless otherwise specified, a composition may be of any form—e.g., gas, gel, liquid, solid, etc. In some embodiments, “composition” may refer to a combination of two or more entities for use in a single embodiment or as part of the same article. It is not required in all embodiments that the combination of entities result in physical admixture, that is, combination as separate co-entities of each of the components of the composition is possible; however many practitioners in the field may find it advantageous to prepare a composition that is an admixture of two or more of the ingredients in a pharmaceutically acceptable carrier, diluent, or excipient, making it possible to administer the component ingredients of the combination at the same time.

(14) Improve, increase, or reduce: as used herein or grammatical equivalents thereof, indicate values that are relative to a baseline measurement, such as a measurement in a similar composition made according to previously known methods.

(15) It should be apparent to those skilled in the art that many additional modifications beside those already described are possible without departing from the inventive concepts. In interpreting this disclosure, all terms should be interpreted in the broadest possible manner consistent with the context. Variations of the term “comprising” should be interpreted as referring to elements, components, or steps in a non-exclusive manner, so the referenced elements, components, or steps

may be combined with other elements, components, or steps that are not expressly referenced. Embodiments referenced as “comprising” certain elements are also contemplated as “consisting essentially of” and “consisting of” those elements. When two or more ranges for a particular value are recited, this disclosure contemplates all combinations of the upper and lower bounds of those ranges that are not explicitly recited. For example, recitation of a value of between 1 and 10 or between 2 and 9 also contemplates a value of between 1 and 9 or between 2 and 10.

(16) As used herein, the terms “include” and “including” have the same meaning as the terms “comprise” and “comprising.” The terms “comprise” and “comprising” should be interpreted as being “open” transitional terms that permit the inclusion of additional components further to those components recited in the claims. The terms “consist” and “consisting of” should be interpreted as being “closed” transitional terms that do not permit the inclusion of additional components other than the components recited in the claims. The term “consisting essentially of” should be interpreted to be partially closed and allowing the inclusion only of additional components that do not fundamentally alter the nature of the claimed subject matter.

(17) Embodiments herein provide for systems, procedures, and/or apparatuses for providing recovered process streams for renewable natural gas recovery and/or upgrading. Aspects of the present disclosure reference “natural gas” for clarity of the description. The term “natural gas” should be understood broadly, and includes renewable natural gas, landfill gas, fossil fuel natural gas, gas from biodigesters, and the like. Example recovered process streams include, without limitation, improved natural gas recovery (e.g., volume, composition, and/or recovery cost), secondary natural gas recovery, and/or carbon dioxide product recovery. In certain embodiments, example systems, procedures, and/or apparatuses for renewable natural gas recovery are applicable to any type of natural gas stream, and/or gas stream including typical natural gas constituents (e.g., low carbon count hydrocarbons, such as methane, ethane, propane, butane, etc.) as a major portion thereof, including for example processing of landfill gases, or any other type of gases, such as biogas, coming from certain food waste streams, farm product streams, manure sources, waste treatment plants, wineries, and/or any facility having organic waste associated therewith. Example and non-limiting product streams for embodiments herein include, without limitation, one or more of a primary natural gas stream, a secondary natural gas stream, and/or a carbon dioxide stream. In certain embodiments, a product stream, as utilized herein, may be provided as an explicit product stream (e.g., provided to an external system, such as a natural gas pipeline, etc.), utilized internally (e.g., in a burner, as a constituent supply stream, for in-situ electricity generation, etc.), stored for later delivery and/or utilization, etc. The description herein referencing a product stream should be understood broadly, where a product stream includes any stream that has been processed herein and is ready for utilization or further processing for a purpose. Throughout this disclosure, the terms carbon dioxide and CO₂ are used interchangeably.

(18) The description herein referencing certain streams as a permeate stream and/or a retentate stream are non-limiting examples for clarity of the present description. The number and arrangement of membranes, streams, and the like, is dependent upon the constituents of various streams, the characteristics of the membranes utilized (e.g., selectivity, permeability to various constituents being separated, operating pressures, etc.), system pressures, temperatures, and/or flow rates, or the like. The description herein referencing certain streams as product streams, permeate streams, retentate streams, intermediate streams, recycle streams, recovery streams, or the like, are non-limiting examples provided for clarity of the present description. Arrangements depicted herein, including arrangements described herein and/or consistent with descriptions herein, are non-limiting examples, and can be adjusted as described herein and/or as understood to one of skill in the art having the benefit of the present disclosure, and further such arrangements are not limited to naming conventions utilized herein.

(19) Gas separation and purification processes may be used to maximize the value of carbon dioxide (CO₂) capture and/or recovery at renewable natural gas (RNG) facilities and organic

waste processing facilities, such as landfills and biodigesters. Disclosed herein are systems, apparatus, and methods that enable the capture of CO.sub.2 from organic waste. The disclosed systems, apparatus, and methods may also enable the conversion of captured CO.sub.2 into a usable form.

(20) Systems depicted herein are depicted schematically, and depicted components thereof may be omitted and/or an omitted component may be added and/or substituted. For example, components to implement and/or adjust stream order and/or connection points (e.g., valves and/or manifolds) may be added, omitted, and/or substituted to implement described flow arrangements. In another example, pressurization components (e.g., a pump) may be added, for example to ensure desired flow rates and/or operating pressures are maintained, and/or depicted pressurization components may be omitted if they are not needed to support the desired flow rates and/or operating pressures for a particular embodiment.

(21) It can be seen that embodiments herein can be configured for zero emissions, or stated differently, the source gas may be completely separated into a hydrocarbon product stream and a CO.sub.2 product stream, with no significant mass vented from the system as a purge gas, effluent, or the like. In certain embodiments, for example where some components are removed in conditioning steps (e.g., H.sub.2S, water, volatile organic compounds, etc.), a zero emission embodiment is one where the entire remainder of the source gas after the conditioning is separated into a hydrocarbon product stream and a CO.sub.2 product stream, with no significant mass vented from the system. It will be understood that the embodiments herein provide for numerous benefits to gas recovery systems, and systems with zero emissions or with non-zero emissions are contemplated herein.

(22) Selection of components, stream arrangements, or the like, for embodiments herein may be selected or implemented based on a number of factors, such as the existing biogas upgrading process being employed, the purity and/or cleanliness of the inlet gas (e.g., presence of trace compounds, contaminants, the product fraction of the inlet gas including natural gas and/or CO.sub.2), the volume of methane and/or carbon dioxide that can potentially be re-captured, the intended utilization (e.g., on-site vs. shipping off-site), a comparison of grid electricity costs vs. using the methane to produce electricity on-site, the need or ability to use the electricity for non-CO.sub.2 related uses, if returned methane (and/or natural gas) is desired as an outcome of the process, to meet one or more emissions requirements or comply with a policy, a capital expenditure associated with methane utilization, available space and/or infrastructure for new and/or upgraded equipment, a potential amount of revenue generated through renewable identification numbers (RINs) or other government incentive, an available transportation equipment, supply and demand for a given market, or the like.

(23) Referring now to FIG. 1, a stand-alone membrane may be used to recover methane from the non-condensable stream of a CO.sub.2 plant and, in some examples, the hydrocarbon-enriched recycle stream from the CO.sub.2 plant back to the conditioning/compression portion of the process is at a higher average pressure than the recycle stream from the second membrane back to the conditioning/compression steps. The example gas recovery system **100** may include “n” membranes, where “n” is 1 to 3, and in some examples, may be more than 3. Permeate may be passed to the CO.sub.2 plant from any of the “n” membranes, specifically including the 3.sup.rd membrane, the standalone membrane assembly **134** on the non-condensable side of the CO.sub.2 plant (as shown here). Examples of a gas recovery system **100** include a source gas conditioning assembly **102** fluidly coupled to an inlet source gas **104**, and configured to condition **103** and compress **106** the inlet source gas **104** to provide a conditioned source gas **140**. The example gas recovery system **100** also includes a first membrane assembly **108** fluidly coupled to the conditioned source gas **140**, and configured to separate the conditioned source gas **140** into a hydrocarbon-enriched stream **110** and a recovery stream **112**. The example gas recovery system **100** a second membrane assembly **114** fluidly coupled to the hydrocarbon enriched stream, and

configured to separate the hydrocarbon enriched stream **110** into a hydrocarbon product stream **118** and a recycle stream **120**. The example gas recovery system **100** further includes a carbon dioxide (CO.sub.2) plant assembly **122** fluidly coupled to the recovery stream **112**, and configured to provide a carbon dioxide product stream **124** and an enriched recycle stream **128**. The example gas recovery system **100** further includes a standalone membrane assembly **134** fluidly coupled to the enriched recycle stream **128**, and configured to separate the enriched recycle stream **128** into a hydrocarbon-enriched recycle stream **130** and an effluent stream **132**. In examples of the gas recovery system **100**, the source gas conditioning assembly **102** is fluidly coupled to the recycle stream **120** and the hydrocarbon-enriched recycle stream **130**.

(24) In examples of the gas recovery system **100**, the hydrocarbon enriched recycle stream **130** includes a retentate of a standalone membrane of the standalone membrane assembly **134**. The source gas conditioning assembly **102** includes a first fluid coupling to the hydrocarbon-enriched recycle stream **130** and a second fluid coupling to the recycle stream **120**, and wherein the first fluid coupling is downstream of the second fluid coupling. In some examples, the first fluid coupling includes a higher average pressure position than the second fluid coupling. In some examples, the first fluid coupling is downstream of a compressor component **106** of the source gas conditioning assembly **102**. In some examples, the recycle stream **120** includes a permeate of a second membrane of the second membrane assembly **114**. In some examples, the recovery stream **112** includes a permeate of a first membrane of the first membrane assembly **108**. In some examples, the enriched recycle stream **128** includes non-condensable gases from the CO.sub.2 plant assembly **122**. The enriched recycle stream **128** passes directly from the CO.sub.2 plant assembly **122** to the standalone membrane assembly **134** without being pressurized. In some examples, the CO.sub.2 plant assembly **122** includes a carbon adsorption bed, a gas compression component, a gas dehydration component, and a liquefaction component.

(25) A method of treating gas includes conditioning and compressing an inlet source gas to provide a conditioned source gas, separating the conditioned source gas into a hydrocarbon-enriched stream and a recovery stream, optionally with a first membrane assembly, and separating the hydrocarbon-enriched stream into a hydrocarbon product stream and a recycle stream, optionally with a second membrane assembly. The method for treating gas also includes processing the recovery stream, such as with a carbon dioxide (CO.sub.2) plant assembly, to provide a carbon dioxide product stream and an enriched recycle stream. The method for treating gas also includes separating the enriched recycle stream into a hydrocarbon-enriched recycle stream and an effluent stream, optionally with a standalone membrane assembly. In examples of the method, the hydrocarbon-enriched recycle stream includes a retentate of a standalone membrane of the standalone membrane assembly. In examples of the method, the recycle stream includes a permeate of a second membrane of the second membrane assembly. In examples of the method, the recovery stream includes a permeate of a first membrane of the first membrane assembly. In examples of the method, the enriched recycle stream includes non-condensable gases from the CO.sub.2 plant assembly, and in some examples, the enriched recycle stream passes directly from the CO.sub.2 plant assembly to the standalone membrane assembly without being pressurized.

(26) Referring to FIG. 2, examples of an apparatus **200** include a standalone membrane assembly **134** configured to receive a treated waste gas stream **228**, the treated waste gas stream **228** comprising a purge stream of a CO.sub.2 plant assembly **122**, separate the treated waste gas stream **228** into a hydrocarbon enriched stream **230** and an effluent stream **132**, and provide the hydrocarbon enriched stream **230** to a waste gas recovery facility (e.g., a facility including all or a portion of the apparatus **200**), wherein the hydrocarbon enriched stream **230** is recycled to a position upstream of the CO.sub.2 plant assembly **122**. The hydrocarbon enriched stream **230** includes a retentate stream of a standalone membrane of the standalone membrane assembly **134**.

(27) Referring now to FIG. 3, a stand-alone membrane may be used to recover both CH.sub.4 and CO.sub.2 from the non-condensable stream of the CO.sub.2 plant, and in some examples, CH.sub.4

is returned to the RNG plant. Examples of a gas recovery system **300** include a source gas conditioning assembly **102** fluidly coupled to an inlet source gas **104**, and configured to condition **103** and compress **106** the inlet source gas **104** to provide a conditioned source gas **140**. The example gas recovery system **300** also includes a first membrane assembly **108** fluidly coupled to the conditioned source gas **140**, and configured to separate the conditioned source gas **140** into a hydrocarbon enriched stream **110** and a recovery stream **112**. The example gas recovery system **300** also includes a second membrane assembly **114** fluidly coupled to the hydrocarbon enriched stream **110**, and configured to separate the hydrocarbon enriched stream **110** into a hydrocarbon product stream **118** and a recycle stream **120**. The example gas recovery system **300** also includes a carbon dioxide (CO.sub.2) plant assembly **122** fluidly coupled to the recovery stream **112**, and configured to provide a carbon dioxide product stream **124** and an enriched recycle stream **128**. The example gas recovery system **300** also includes a standalone membrane assembly **134** fluidly coupled to the enriched recycle stream **128**, and configured to separate the enriched recycle stream **128** into a hydrocarbon-enriched recycle stream **130** and a secondary recovery stream **302**. In examples of the gas recovery system **300**, the source gas conditioning assembly **102** is fluidly coupled to the recycle stream **120** and the hydrocarbon-enriched recycle stream **130**, and the CO.sub.2 plant assembly **122** is fluidly coupled to the secondary recovery stream **302**. In examples of the gas recovery system **300**, the hydrocarbon-enriched recycle stream **130** includes a retentate of a standalone membrane of the standalone membrane assembly **134**. The source gas conditioning assembly **102** includes a first fluid coupling to the hydrocarbon-enriched recycle stream and a second fluid coupling to the recycle stream, and wherein the first fluid coupling is downstream of the second fluid coupling. The first fluid coupling includes a higher average pressure position than the second fluid coupling. The first fluid coupling is downstream of a compressor component of the source gas conditioning assembly.

(28) An example apparatus includes a standalone membrane assembly **134** configured to receive a treated waste gas stream including a purge stream of a CO.sub.2 plant assembly **122**, separate the treated waste gas stream into a hydrocarbon-enriched stream **130** and a secondary recovery stream **302**, provide the hydrocarbon-enriched stream **130** to a waste gas recovery facility, wherein the hydrocarbon-enriched stream **130** is recycled to a position upstream of the CO.sub.2 plant assembly **122**, and provide the secondary recovery stream **302** to the CO.sub.2 plant assembly **122**. The hydrocarbon-enriched stream **130** includes a retentate stream of a standalone membrane of the standalone membrane assembly **134**.

(29) A method of treating gas includes conditioning and compressing an inlet source gas to provide a conditioned source gas, separating the conditioned source gas into a hydrocarbon-enriched stream and a recovery stream optionally with a first membrane assembly, and separating the hydrocarbon-enriched stream into a hydrocarbon product stream and a recycle stream optionally with a second membrane assembly. The method further includes providing a carbon dioxide product stream and an enriched recycle stream optionally with a carbon dioxide (CO.sub.2) plant assembly. The method further includes separating the enriched recycle stream into a hydrocarbon-enriched recycle stream and a secondary recovery stream optionally with a standalone membrane assembly.

(30) Referring now to FIG. 4, a stand-alone membrane may be used to recover CH.sub.4 from the non-condensable stream of the CO.sub.2 plant, and CH.sub.4 may be used mainly for other on-site uses. An example gas recovery system **400** includes a source gas conditioning assembly **102** fluidly coupled to an inlet source gas **104**, and configured to condition **103** and compress **106** the inlet source gas **104** to provide a conditioned source gas **140**. The example gas recovery system **400** includes a first membrane assembly fluidly coupled to the conditioned source gas **140**, and configured to separate the conditioned source gas **140** into a hydrocarbon-enriched stream **110** and a recovery stream **112**. The example gas recovery system **400** includes a second membrane assembly **114** fluidly coupled to the hydrocarbon-enriched stream **110**, and configured to separate the hydrocarbon-enriched stream **110** into a hydrocarbon product stream **118** and a recycle stream

120. The example gas recovery system **400** includes a carbon dioxide (CO.sub.2) plant assembly **122** fluidly coupled to the recovery stream **112**, and configured to provide a carbon dioxide product stream **124** and an enriched recycle stream **128**. The example gas recovery system **400** includes a standalone membrane assembly **134** fluidly coupled to the enriched recycle stream **128**, and configured to separate the enriched recycle stream **128** into a hydrocarbon-enriched recycle stream **402** and a secondary recovery stream **302**. The example gas recovery system **400** includes an energy recovery assembly **404** fluidly coupled to the hydrocarbon-enriched recycle stream **402** and configured to extract energy therefrom. The source gas conditioning assembly **102** is fluidly coupled to the recycle stream **120**, and the CO.sub.2 plant assembly **122** is fluidly coupled to the secondary recovery stream **302**. In examples, the energy recovery assembly **404** includes a burner, a fuel cell, or a generator.

(31) An example apparatus includes a standalone membrane assembly **134** configured to receive a treated waste gas stream, the treated waste gas stream including a purge stream of a CO.sub.2 plant assembly **122**, separate the treated waste gas stream into a hydrocarbon-enriched stream **402** and a secondary recovery stream **302**, provide the hydrocarbon-enriched stream **402** to an energy recovery assembly **404**, and provide the secondary recovery stream **302** to the CO.sub.2 plant assembly **122**.

(32) An example method of treating gas includes conditioning and compressing the inlet source gas to provide a conditioned source gas, separating the conditioned source gas into a hydrocarbon-enriched stream and a recovery stream optionally with a first membrane assembly, and separating the hydrocarbon-enriched stream into a hydrocarbon product stream and a recycle stream optionally with a second membrane assembly. The example method may further include providing a carbon dioxide product stream and an enriched recycle stream optionally with a carbon dioxide (CO.sub.2) plant assembly. The example method may further include separating the enriched recycle stream into a hydrocarbon-enriched recycle stream and a secondary recovery stream optionally with a standalone membrane assembly. The example method may further include extracting energy from the hydrocarbon-enriched recycle stream optionally with an energy recovery assembly.

(33) Referring now to FIG. 5, a stand-alone membrane may be used to capture permeate from a 2.sup.nd stage membrane, recycling CH.sub.4 to an RNG plant and CO.sub.2 to a CO.sub.2 plant. An example gas recovery system **500** includes a source gas conditioning assembly **550** fluidly coupled to an inlet source gas **544**, and configured to condition the inlet source gas **544** to provide a conditioned source gas **548**. The example gas recovery system **500** also includes an adsorption assembly **510** fluidly coupled to the conditioned source gas **548**, and configured to provide a scrubbed source gas **542**, the adsorption assembly **510** including at least one of a temperature swing adsorber or a pressure swing adsorber. The example gas recovery system **500** also includes a first membrane assembly **540** fluidly coupled to the scrubbed source gas **542**, and configured to separate the scrubbed source gas **542** into a hydrocarbon enriched stream **522** and a flush stream **552**. The example gas recovery system **500** a second membrane assembly **520** fluidly coupled to the hydrocarbon-enriched stream **522**, and configured to separate the hydrocarbon enriched stream **522** into a hydrocarbon product stream **516** and a recovery stream **524**. The example gas recovery system **500** a standalone membrane assembly **528** fluidly coupled to the recovery stream **524**, and configured to separate the recovery stream **524** into a carbon dioxide (CO.sub.2) enriched stream **530** and a recycle stream **532**. The example gas recovery system **500** a CO.sub.2 plant assembly **534** fluidly coupled to the CO.sub.2 enriched stream **530**, and configured to provide a carbon dioxide product stream **538**. The adsorption assembly **510** is at least selectively fluidly coupled to the flush stream **552**, and configured to utilize the flush stream **552** for regeneration operations. The source gas conditioning assembly **550** is fluidly coupled to the recycle stream **532**. In examples, the adsorption assembly **510** further includes an activated carbon bed component **512**. In examples, the example gas recovery system **500** further includes a nitrogen removal assembly **514**

fluidly interposed between the hydrocarbon product stream **516** and a final hydrocarbon product stream **518**. In examples, the source gas conditioning assembly **550** is further configured to condition the inlet source gas **544** by dehydrating **554** the inlet source gas **544**. In examples, the source gas conditioning assembly **550** is further configured to condition the inlet source gas **544** by removing sulfur **558** from the inlet source gas **544**. In examples, the example gas recovery system **500** includes an energy recovery assembly fluidly coupled to a flush gas outlet **562** of the adsorption assembly **510**, and configured to extract energy from the flush stream **552**. In examples, the example gas recovery system **500** further includes a thermal oxidizer **560** coupled to a flush gas outlet **562** of the adsorption assembly **510**, and configured to treat the flush stream **552**. In examples, the CO.sub.2 plant assembly **534** is further configured to provide a secondary recovery stream **569**, including for energy recovery, venting, or further processing with a standalone membrane. In examples, the example gas recovery system **500** includes an energy recovery assembly (not shown) fluidly coupled to the secondary recovery stream **569**. In examples, the source gas conditioning assembly **550** is fluidly coupled to the secondary recovery stream **569**. It should be understood that “A” from the standalone membrane assembly **528** can return anywhere in the source gas conditioning assembly **550**, including before or after the compression step **559**. The example of FIG. 5 includes a pump **564**, or other pressurizing component, for example to provide sufficient operating pressure to the recovery stream **524** to operate the standalone membrane assembly **528** (e.g., where the recovery stream **524** is a permeate of the second membrane assembly **520**).

(34) An example apparatus includes a standalone membrane assembly **528** configured to receive a recovery stream **524** including a residual from separating a hydrocarbon-enriched stream **522** from a conditioned source gas **548**, separate the recovery stream **524** into a carbon dioxide (CO.sub.2) enriched stream **530** and a recycle stream **532**, provide the CO.sub.2 enriched stream **530** to a CO.sub.2 plant assembly **534**, and provide the recycle stream **532** to a source gas conditioning assembly **550**, wherein the recycle stream **532** is recycled to a position upstream of the CO.sub.2 plant assembly **534**. The recycle stream **532** includes a retentate stream of a standalone membrane of the standalone membrane assembly **528**.

(35) A method of treating gas includes conditioning an inlet source gas to provide a conditioned source gas, processing the conditioned source gas at an adsorption assembly to provide a scrubbed source gas, separating the scrubbed source gas into a hydrocarbon enriched stream and a flush stream, separating the hydrocarbon-enriched stream into a hydrocarbon product stream and a recovery stream, separating the recovery stream into a carbon dioxide (CO.sub.2) enriched stream and a recycle stream, and processing the CO.sub.2 enriched stream at a CO.sub.2 plant assembly to provide a carbon dioxide product stream.

(36) Referring now to FIG. 6, CO.sub.2 PSA technology along with a CO.sub.2 Plant/standalone membrane (SAM) can be used to recover CO.sub.2 and CH.sub.4 slip. An example gas recovery system **600** includes a source gas conditioning assembly **102** fluidly coupled to an inlet source gas **104**, and configured to condition **103** and compress **106** the inlet source gas **104** to provide a conditioned source gas **140**. The example gas recovery system **600** also includes a first membrane assembly **108** fluidly coupled to the conditioned source gas **140**, and configured to separate the conditioned source gas **140** into a hydrocarbon-enriched stream **110** and a recovery stream **112**. The example gas recovery system **600** also includes a second membrane assembly **114** fluidly coupled to the hydrocarbon-enriched stream **110**, and configured to separate the hydrocarbon-enriched stream **110** into a hydrocarbon product stream **118** and a recycle stream **120**. The example gas recovery system **600** also includes a CO.sub.2 adsorption assembly **602** fluidly coupled to the recovery stream **112**, and configured to separate the recovery stream **112** into an enriched recovery stream **608** and a CO.sub.2 enriched stream **604**. The example gas recovery system **600** also includes a carbon dioxide (CO.sub.2) plant assembly **122** fluidly coupled to the CO.sub.2 enriched stream **604**, and configured to provide a carbon dioxide product stream **124** and a second enriched

recovery stream **610**. The example gas recovery system **600** also includes a standalone membrane assembly **134** fluidly coupled to the second enriched recovery stream **610**, and configured to separate the second enriched recovery stream **610** into a hydrocarbon enriched recycle stream and an effluent stream **132**. In examples, the source gas conditioning assembly is fluidly coupled to the recycle stream and the hydrocarbon-enriched recycle stream **130**. In examples, the source gas conditioning assembly **102** is fluidly coupled to the enriched recovery stream **610**. In examples, the CO.sub.2 plant is fluidly coupled to the effluent stream **132**.

(37) A method of treating gas includes conditioning and compressing an inlet source gas to provide a conditioned source gas, separating the conditioned source gas into a hydrocarbon enriched stream and a recovery stream, separating the hydrocarbon enriched stream into a hydrocarbon product stream and a recycle stream, separating the recovery stream into an enriched recovery stream and a CO.sub.2 enriched stream, processing the CO.sub.2 enriched stream at a carbon dioxide (CO.sub.2) plant assembly to provide a carbon dioxide product stream and an enriched recovery stream, and separating the enriched recovery stream into a hydrocarbon enriched recycle stream and an effluent stream.

(38) Referring now to FIG. 7, an example gas recovery system **700** includes a source gas conditioning assembly **102** fluidly coupled to an inlet source gas **104**, and configured to condition **103** and compress **106** the inlet source gas **104** to provide a conditioned source gas **140**. The example gas recovery system **700** includes a first membrane assembly **108** fluidly coupled to the conditioned source gas **140**, and configured to separate the conditioned source gas **140** into a hydrocarbon-enriched stream **110** and a recovery stream **112**. The example gas recovery system **700** includes a second membrane assembly **114** fluidly coupled to the hydrocarbon-enriched stream **110**, and configured to separate the hydrocarbon-enriched stream **110** into a hydrocarbon product stream **118** and a second recovery stream **707**. The example gas recovery system **700** includes a CO.sub.2 adsorption assembly **602** fluidly coupled to the second recovery stream **707**, and configured to separate the second recovery stream **707** into an enriched recycle stream **702** and a CO.sub.2 enriched stream **604**. The example gas recovery system **700** includes a carbon dioxide (CO.sub.2) plant assembly **122** fluidly coupled to the recovery stream **112** and the CO.sub.2 enriched stream, and configured to provide a carbon dioxide product stream **124** and an enriched recovery stream **610**. The example gas recovery system **700** includes a standalone membrane assembly **134** fluidly coupled to the enriched recovery stream **610**, and configured to separate the enriched recovery stream **610** into a hydrocarbon enriched recycle stream **130** and an effluent stream **132**. The source gas conditioning assembly **102** is fluidly coupled to the enriched recycle stream **702** and the hydrocarbon enriched recycle stream **130**. In examples, the example gas recovery system **700** includes an energy recovery assembly (not shown) fluidly coupled to the hydrocarbon enriched recycle stream **130**. In examples, the CO.sub.2 plant is fluidly coupled to the effluent stream.

(39) A method of treating gas includes conditioning and compressing an inlet source gas to provide a conditioned source gas, separating the conditioned source gas into a hydrocarbon-enriched stream and a recovery stream, separating the hydrocarbon-enriched stream into a hydrocarbon product stream and a recycle stream, providing a carbon dioxide product stream and an enriched recovery stream optionally via a carbon dioxide (CO.sub.2) plant assembly, separating the recycle stream into an enriched recycle stream and a CO.sub.2 enriched stream, and separating the enriched recovery stream into a hydrocarbon enriched recycle stream and an effluent stream, optionally via a standalone membrane assembly.

(40) Referring now to FIG. 8, an example gas recovery system **800** includes a source gas conditioning assembly **102** fluidly coupled to an inlet source gas **104**, and configured to condition **103** and compress **106** the inlet source gas **104** to provide a conditioned source gas **140**. The example gas recovery system **800** includes a first membrane assembly **108** fluidly coupled to the conditioned source gas **140**, and configured to separate the conditioned source gas **140** into a

hydrocarbon-enriched stream **110** and a first recovery stream **808**. The example gas recovery system **800** includes a second membrane assembly **114** fluidly coupled to the hydrocarbon-enriched stream **110**, and configured to separate the hydrocarbon-enriched stream **110** into a hydrocarbon product stream **118** and a second recovery stream **804**. The example gas recovery system **800** includes a CO.sub.2 adsorption assembly **602** fluidly coupled to the first recovery stream **808** and the second recovery stream **804**, and configured to provide an enriched recycle stream **802** and a CO.sub.2 enriched stream **604**. The example gas recovery system **800** includes a carbon dioxide (CO.sub.2) plant assembly **122** fluidly coupled to the CO.sub.2 enriched stream **604**, and configured to provide a carbon dioxide product stream **124** and an enriched recovery stream **610**. The example gas recovery system **800** includes a standalone membrane assembly **134** fluidly coupled to the enriched recovery stream **610**, and configured to separate the enriched recovery stream **610** into a hydrocarbon-enriched recycle stream **130** and an effluent stream **132**. The source gas conditioning assembly **102** is fluidly coupled to the enriched recycle stream **802** and the hydrocarbon enriched recycle stream **130**. In examples, the CO.sub.2 plant is fluidly coupled to the effluent stream.

(41) An example method includes conditioning and compressing an inlet source gas to provide a conditioned source gas, separating the conditioned source gas into a hydrocarbon-enriched stream and a first recovery stream, separating the hydrocarbon-enriched stream into a hydrocarbon product stream and a second recovery stream, providing an enriched recycle stream and a CO.sub.2 enriched stream optionally with a CO.sub.2 adsorption assembly, providing a carbon dioxide product stream and an enriched recovery stream optionally with a carbon dioxide (CO.sub.2) plant assembly, and separating the enriched recycle stream into a hydrocarbon-enriched recycle stream and an effluent stream optionally with a standalone membrane assembly.

(42) Referring now to FIG. 9, an example gas recovery system **900** is shown where recovery occurs at a second membrane assembly **114** and recycle occurs at a first membrane assembly **108**. The example gas recovery system **900** includes a source gas conditioning assembly **102** fluidly coupled to an inlet source gas **104**, and configured to condition **103** and compress **106** the inlet source gas **104** to provide a conditioned source gas **140**. The example gas recovery system **900** includes a first membrane assembly **108** fluidly coupled to the conditioned source gas **140**, and configured to separate the conditioned source gas **140** into a hydrocarbon enriched stream **110** and a recycle stream **120**. The example gas recovery system **900** includes a second membrane assembly **114** fluidly coupled to the hydrocarbon enriched stream **110**, and configured to separate the hydrocarbon enriched stream **110** into a hydrocarbon product stream **118** and a recovery stream **112**. example gas recovery system **900** includes a carbon dioxide (CO.sub.2) plant assembly **122** fluidly coupled to the recovery stream **112**, and configured to provide a carbon dioxide product stream **124** and an enriched recycle stream **128**. example gas recovery system **900** includes a standalone membrane assembly **134** fluidly coupled to the enriched recycle stream **128**, and configured to separate the enriched recycle stream **128** into a hydrocarbon enriched recycle stream **130** and an effluent stream **132**, wherein the source gas conditioning assembly **102** is fluidly coupled to the recycle stream **120** and the hydrocarbon enriched recycle stream **130**. The hydrocarbon enriched recycle stream **130** comprises a retentate of a standalone membrane of the standalone membrane assembly **134**. The source gas conditioning assembly **102** comprises a first fluid coupling to the hydrocarbon enriched recycle stream **130** and a second fluid coupling to the recycle stream **120**, wherein the first fluid coupling is downstream of the second fluid coupling. The first fluid coupling comprises a higher average pressure position than the second fluid coupling. The first fluid coupling is downstream of a compressor component **106** of the source gas conditioning assembly. The recycle stream includes a permeate of a first membrane of the first membrane assembly **108**. The recovery stream comprises a permeate of a first membrane of the second membrane assembly **114**. The enriched recycle stream **128** includes non-condensable gases from the CO.sub.2 plant assembly **122**. The enriched recycle stream **128** passes directly from the

CO.sub.2 plant assembly **122** to the standalone membrane assembly **134** without being pressurized. The CO.sub.2 plant assembly **122** includes a carbon adsorption bed, a gas compression component, a gas dehydration component, and a liquefaction component.

(43) A method of treating gas may include conditioning and compressing an inlet source gas to provide a conditioned source gas, separating the conditioned source gas into a hydrocarbon enriched stream and a recycle stream, separating the hydrocarbon enriched stream into a hydrocarbon product stream and a recovery stream, providing a carbon dioxide product stream and an enriched recycle stream optionally via a carbon dioxide (CO.sub.2) plant assembly fluidly coupled to the recovery stream, and separating the enriched recycle stream into a hydrocarbon enriched recycle stream and an effluent stream optionally via a standalone membrane assembly fluidly coupled to the enriched recycle stream.

(44) An example 2-stage renewable natural gas (RNG) upgrading process is described following, which may be embodied in whole or part by embodiments throughout the present disclosure. The depicted process utilizes a two-stage membrane system, such as is used in biodigesters such as dairy waste digesters, food waste digesters, poultry processing plants, wastewater treatment plants, or the like. A biogas inlet stream from a digester is received, for example as a source gas. The process includes a purification and gas conditioning component, for example removing certain gas constituents (e.g., H.sub.2S, sulfur, volatile organic compounds, etc.), dehydration, pressurization, or the like. The biogas is compressed after which it moves through two stages of membranes. The selected pressures and temperature of the outlet biogas may be configured according to the membrane components utilized, which will be understood to the person of skill in the art having the benefit of the present disclosure and information ordinarily available when contemplating a particular system, for example such information including: the composition of the biogas, the desired separation efficiency and/or degree of separation, membrane characteristics, subsequent treatment for the retentate, and/or subsequent treatment for the permeate. The membranes may be hollow fiber membranes or any other suitable, at least partially permeable technology, and may exhibit durability, such as having a lifespan on the order of years (e.g., 3 to 10 years) and selectivity for desired molecules/compounds and/or molecule/compound sizes. Material that passes through the membrane, due to its size or other characteristic, may be known as permeate, while material that does not pass through the membrane, and is therefore retained within the system, may be known as retentate. The retentate may collect at an annulus of the membrane, depending upon the physical configuration of the membrane system, and may be removed from the annulus. Gas flow through the membrane may be in the direction of the hollow fibers. In practice, the membrane may be situated within a system, such as in a pipe, where headers for gas distribution and collection may be on either side of the membrane. The example system is a two-stage membrane system, but may include three membranes, with recycle locations (e.g., gases recycled to be combined with the source gas) selected from any of the three membranes, and/or recovery locations (e.g., gases provided to a CO.sub.2 plant for CO.sub.2 recovery) from any one or two of the three membranes. In certain embodiments, a single membrane system provides a hydrocarbon product stream directly, and a separate recovery stream that is provided to a CO.sub.2 plant, which may be ultimately recycled (e.g., as a non-condensable stream from the CO.sub.2 plant assembly, to a standalone membrane, with the hydrocarbon enriched portion of the standalone membrane separation being recycled).

(45) The example system includes a highly purified methane (CH.sub.4) slip stream return via a standalone membrane unit. The depicted process includes returning excess methane slip that has been removed as part of the CO.sub.2 plant liquefaction process to the RNG producer at high purity to ensure maximum value creation and emission reduction at the site. The return of the methane at high purity improves the process efficiency of the biogas upgrading equipment. The methane slip is purified with a standalone membrane unit as part of the CO.sub.2 recovery process enabling both the recycling of methane with the recovery of CO.sub.2 for potentially revenue-generating end

uses. This enables the RNG producer to achieve essentially 100% methane capture and use. The effluent stream (e.g., the permeate, where the retentate is recycled) may be vented, have an energy capture operation (e.g., oxidizing any remaining hydrocarbons and/or operating a fuel cell) performed on it, and/or recycled to the CO.sub.2 plant to further extract any remaining CO.sub.2. The permeate may have a high fraction of CO.sub.2, such as 90% or greater.

(46) An example CO.sub.2 plant includes one or more of: polishing of raw CO.sub.2 with carbon beds (e.g., to remove VOC's and sulfur), other gas conditioning processes, CO.sub.2 compression (e.g., to 300 psi), liquid removal (e.g., drying to -70 degrees F. (-56 degrees C.)), cooling (e.g., using a refrigerant, cooling to ~-25 degrees centigrade), liquefaction (e.g., in a stripper column), or non-condensable gas (e.g., methane, oxygen, nitrogen) removal from the stripper column. The CO.sub.2 plant may produce purified liquid CO.sub.2 from a re-boiler, such as a purity of greater than 99.9%. In some embodiments, the purified CO.sub.2 is directed to storage tanks, and/or otherwise passed into a CO.sub.2 utilization and/or storage system. In addition to providing higher recovery of methane and capture of CO.sub.2 that would otherwise be vented, and at high purity, example systems herein further reduce the operating cost of the RNG plant (e.g., to support higher recycle rates), and increase the capacity of the RNG plant (e.g., allowing a greater portion of the steady state flow through the system to be realized as product stream, e.g., due to the lower recycle rates).

(47) The non-condensable gases from the CO.sub.2 plant, also known as purge gas, which may be a mixture of CO.sub.2 and CH.sub.4, such as a +/-25% CH.sub.4, 75% CO.sub.2 mixture, may be removed from a stripper column of the CO.sub.2 plant at high pressure (e.g., 18 bar, 300 psi). The purge gas may be recycled to the source gas, but the purge gas pressure may need to be let down. In certain embodiments, the purge gas is directed to a standalone membrane, where the elevated pressure effectively operates the standalone membrane, potentially with no additional pressurization. The utilization of the standalone membrane results in greater recovery of CH.sub.4 using less input energy to the process since waste purge stream pressure, also known as waste compression energy, from the CO.sub.2 plant is recovered and used to drive the stand-alone membrane unit to separate CO.sub.2 and methane. Recovery of this waste purge stream pressure enables a more economical recovery of purified, commercially usable, methane. By leveraging the waste pressure of the purge stream, no additional energy needs to be added to the methane slip stream to process the stream through the standalone membrane unit. The pressure available in the waste stream, which is typically wasted, is utilized to further purify the overall waste stream into high purity streams: a high pressure CH.sub.4 stream (e.g., the retentate), and a low pressure CO.sub.2 stream (e.g., the permeate). This high pressure, high purity CH.sub.4 stream can be used for many commercial purposes, such as injection into pipeline, use as an on-site fuel, use in a fuel cell, re-injected into the RNG upgrading process (e.g., at the front end, before compression, after compression, between the first and second stage membranes, etc.), use in a combined heat and power (CHP) system, or the like. In one example, the retentate from the stand-alone membrane unit is returned to the RNG inlet to be combined with the source gas.

(48) Non-condensable gases purged from the CO.sub.2 plant that are not processed through the stand-alone membrane unit may not be suitable to be returned to the process with the conditioned source gas, but may be returned upstream of conditioning components before recycling, and/or may be vented. The retentate may have a variable composition, such as 98% CH.sub.4/2% CO.sub.2, 90% CH.sub.4/10% CO.sub.2, 85% CH.sub.4/15% CO.sub.2, or the like. In embodiments, the composition may be selectable based on a number of factors, such as the size of the membrane, the pressure of the purge gas stream, the temperature of the purge gas stream, the quality of the biogas inlet stream, or the like. In some embodiments, there may be a waste stream of CO.sub.2 or non-condensables from the stand-alone membrane unit.

(49) Another example 2-stage renewable natural gas (RNG) upgrading process is described following. The example process includes passing the low pressure CO.sub.2 stream from a

standalone membrane back to the CO.sub.2 plant as a recycle, improving the overall CO.sub.2 recovery of the system. The low pressure CO.sub.2 stream from the standalone membrane may have a significant CO.sub.2 fraction (e.g., 90% or greater), and can significantly increase CO.sub.2 recovery with the recycle to the CO.sub.2 plant. In the example system, both methane and carbon dioxide may be recovered at high rates, such as nearly or equal to 100%, during the RNG upgrading process. In some embodiments, the pressure of the membrane may be varied to achieve specific outcomes for CH.sub.4 and CO.sub.2 recovery. For example, the pressure on the standalone membrane may be optimized to achieve a particular level of methane and/or carbon dioxide suitable for a particular intended use or application, and/or to balance stream flow rates, recycle rates, or the like to achieve the desired recovery fraction.

(50) In certain embodiments, the utilization of an additional recycle of the membrane permeate to the CO.sub.2 plant enhances the overall CO.sub.2 recovery of the system. The amount of additional CO.sub.2 recovery depends upon several variables in the system, including the purity of the CO.sub.2 feedgas (the membrane permeate to the CO.sub.2 plant). An example system having a 97% CO.sub.2 purity will result in about 10% additional CO.sub.2 recovery. Another example system having an 88% CO.sub.2 purity will result in about 42% additional CO.sub.2 recovery. The actual amount of additional CO.sub.2 recovery for a given system will depend on a number of factors, for example the temperatures of streams in the system, the pressure drop across various separation membranes, and/or the properties of various separation membranes. The utilization of the additional recycle of the membrane permeate to the CO.sub.2 plant may enhance operations of the CO.sub.2 plant, for example by increasing the average CO.sub.2 purity of streams being processed by the CO.sub.2 plant. The utilization of the additional recycle of the membrane permeate to the CO.sub.2 plant allows for manipulation of energy usage and/or sub-assembly capability of various parts of the overall system, the membrane units, thereby allowing the system to be adapted to the composition of feedgas and the priorities for the system (e.g., operational costs, capital costs, energy costs, maintenance costs, etc.).

(51) Another example 2-stage renewable natural gas (RNG) upgrading process is described following. The example process involves a two-stage membrane system such as is used in biodigesters such as dairy waste digesters, food waste digesters, poultry processing plants, wastewater treatment plants, or the like. The example process includes a highly purified methane (CH.sub.4) slip stream via a standalone membrane unit, which is passed to an energy recovery device. The energy recovery device may be a fuel cell (e.g., operating on methane), a burner, an oxidizer, a generator (e.g., driven by the thermal, chemical, and/or mechanical residual energy in the slip stream), and/or any other energy recovery device. The permeate from the standalone membrane may be recaptured and directed back to the CO.sub.2 plant, and/or may be vented. In certain embodiments, the permeate from the standalone membrane may be utilized as a flush gas, for example where a temperature and/or pressure swing adsorber component is included as a conditioning component for the source gas.

(52) Another example RNG upgrading process is described following. In certain embodiments, a system of the process includes an adsorption component to condition the source gas, for example to remove volatile organic compounds (VOCs) from the source gas before application to membrane separation. Adsorption components often utilize a pressure swing and/or temperature swing operation to switch between capture and regenerate operating modes, periodically purging the captured VOCs (or other constituents) using a flush gas. In certain embodiments, multiple VOC components may be operated in parallel, for example allowing components to regenerate the adsorber without requiring a shutdown of operations. The example RNG upgrading process includes utilization of a stream as flush gas for the VOC component of the source gas conditioning, for example a permeate stream of the first membrane, and/or a permeate stream of the second membrane.

(53) A further example RNG upgrading process includes landfill gas (LFG) entering the process as

an inlet stream, is dehydrated, and hydrogen sulfide (H₂S) is removed. The stream is directed to a thermal or pressure swing absorption vessel (TSA/PSA) to remove VOC content and any trace siloxane, after which the stream proceeds to activated carbon beds for further polishing and is then directed to a first stage membrane, and then a second stage membrane to remove CO₂, oxygen, and nitrogen. In some embodiments, the stream from the TSA/PSA during flush operations is directed to a thermal oxidizer (TOX). In some embodiments, the 1st stage membrane permeate is directed back to flush the TSA/PSA and then is directed to the TOX. In some embodiments, the second stage membrane permeate is returned to the RNG inlet before dehydration. The retentate from the second stage membrane is directed to a nitrogen removal component and provided as a hydrocarbon product stream, leaving the system. In certain embodiments, finishing operations for the hydrocarbon product stream, such as an N₂ removal operation, may be a part of the system (e.g., hydrocarbon product stream is ready for a pipeline or other system), or not a part of the system (e.g., hydrocarbon product stream is ready for a finishing operation).

(54) Another example RNG upgrading process is described following. An example system of the process includes a CO₂ PSA/TSA/VPSA adsorption component that processes a recovery stream from one of the membranes, for example a permeate of the first membrane and/or a permeate of the second membrane. The example CO₂ PSA/TSA/VPSA adsorption component generates a CO₂ enriched stream that is relatively pure CO₂ (97% purity or higher), and which is then fed to a CO₂ plant. A tail gas stream from CO₂ PSA/TSA/VPSA adsorption component is an enriched hydrocarbon stream (e.g., +/-15 to 25%) that can be used for other purposes, and/or recycled into the source gas for the RNG upgrading process. PSA/TSA/VPSA references Pressure Swing Adsorption technology (PSA), Temperature Swing Adsorption technology (TSA), Vacuum Pressure Swing Adsorption technology (VPSA), or a combination of these technologies used together.

(55) By increasing the purity of the CO₂ inlet stream to the CO₂ plant, removal of CO₂ from the stripper column, can be increased from, for instance, 60% to 95% of the available CO₂, thereby reducing the capital expenses required for CO₂ capture and processing, and significantly decreasing the required specific energy (kWh per ton of finished product).

(56) In certain embodiments, the permeate from the first membrane is passed to the CO₂ PSA/TSA/VPSA adsorption component, which generates a CO₂ enriched stream that is passed to the CO₂ plant, and the permeate from the second membrane is recycled to the source gas. In certain embodiments, the permeate from the first membrane is passed to the CO₂ plant, and the permeate from the second membrane is passed to a CO₂ PSA/TSA/VPSA adsorption component, which generates a CO₂ enriched stream that is passed to the CO₂ plant. In certain embodiments the permeate from both membranes is passed to the CO₂ PSA/TSA/VPSA adsorption component, which generates a CO₂ enriched stream that is passed to the CO₂ plant. Any one or more of the foregoing examples includes a standalone membrane, for example operating on a non-condensable stream from the CO₂ plant, that provides a hydrocarbon enriched stream (e.g., for recycle to the source gas, utilization for energy recovery, treatment with an oxidizer, vented, etc.), and an effluent stream that may be recycled (e.g., to the CO₂ plant), vented, or the like. An example permeate from the 2nd stage membrane is +/-50% CO₂ (and roughly 45% CH₄). An example CO₂ PSA/TSA/VPSA adsorption component generates a relatively pure CO₂ (e.g., 97% purity or higher) stream and a tail gas stream that is enriched in CH₄ (e.g., +/-60 to 70%), which may be recycled to the source gas. Due to the fact that significant volumes of CO₂ have already been removed from the permeate stream via the PSA/TSA/VPSA technology, the volume to be re-processed by the RNG upgrading system is up to 50% lower, thereby freeing up throughput capacity in the compression and membrane configuration, saving in the required capital costs of the

RNG upgrading system, and also saving on operating costs of the RNG upgrading system (e.g., compression costs are reduced by $\pm 15\%$).

(57) A further example includes the permeate from the 1st stage membrane, which is usually vented to atmosphere, optionally combined with the product stream from the PSA/TSA/VPSA system and sent to the CO.sub.2 plant assembly **122** for recovery of the CO.sub.2 and CH.sub.4 slip. Although this will somewhat dilute the purity of the combined product stream going to the CO.sub.2 plant, it will enable the capture of virtually all of the CO.sub.2 from biogas stream, as well as all of the CH.sub.4 stream.

(58) Another example RNG upgrading process for a landfill gas is schematically depicted. An example system for the RNG upgrading process includes conditioning of a source gas, including dehydration, H.sub.2S removal, compression, and/or VOC removal using a TSA/PSA component. The example system includes providing a permeate of the first membrane to a CO.sub.2 PSA/TSA/VPSA adsorption component, which provides a CO.sub.2 stream to a CO.sub.2 plant, and which utilizes the tail gas for a recycle to the source gas, provides the tail gas to an energy recovery assembly, and/or vents the tail gas. The example system includes recycling a second membrane permeate to the source gas, and/or recycling non-condensable gas from the CO.sub.2 plant to the source gas. In the example system, an alternative gas (e.g., compressed air and/or nitrogen) may be utilized as a flush gas for the TSA/PSA component. In an alternate arrangement, the permeate from the first membrane may be utilized as a flush gas for the TSA/PSA component, and/or be passed as a feed gas to a CO.sub.2 PSA/TSA/VPSA adsorption component, whether alternatively (e.g., the permeate provided as the flush gas, or as the feed gas for the CO.sub.2 PSA/TSA/VPSA adsorption component), additionally (provided to both, with flush gas as needed), and/or in serial (e.g., all or a portion of the permeate is utilized to flush the TSA/PSA component, which is then passed on to the CO.sub.2 PSA/TSA/VPSA adsorption component). An example system includes a standalone membrane that treats the non-condensable stream from the CO.sub.2 plant, recycling and/or otherwise utilizing a hydrocarbon enriched portion, and venting or recycling to the CO.sub.2 plant and/or to the CO.sub.2 PSA/TSA/VPSA adsorption component a remainder portion (e.g., CO.sub.2 enriched). In a further example, a permeate from the second membrane may be utilized as a recycle to the source gas, and/or provided as a feed gas for the CO.sub.2 PSA/TSA/VPSA adsorption component. In a further example, a retentate from the second membrane may be utilized as a hydrocarbon product stream.

(59) Certain logical groupings of operations herein, for example methods or procedures of the current disclosure, are provided to illustrate aspects of the present disclosure. Operations described herein are schematically described and/or depicted, and operations may be combined, divided, re-ordered, added, or removed in a manner consistent with the disclosure herein. It is understood that the context of an operational description may require an ordering for one or more operations, and/or an order for one or more operations may be explicitly disclosed, but the order of operations should be understood broadly, where any equivalent grouping of operations to provide an equivalent outcome of operations is specifically contemplated herein. For example, if a value is used in one operational step, the determining of the value may be required before that operational step in certain contexts (e.g., where the time delay of data for an operation to achieve a certain effect is important), but may not be required before that operation step in other contexts (e.g. where usage of the value from a previous execution cycle of the operations would be sufficient for those purposes). Accordingly, in certain embodiments an order of operations and grouping of operations as described is explicitly contemplated herein, and in certain embodiments re-ordering, subdivision, and/or different grouping of operations is explicitly contemplated herein.

(60) Example and illustrative embodiments are set forth herein to provide a clear description of aspects of the present disclosure. Methods described herein may be embodied, in whole or part, in systems that perform the steps thereof, and may be distributed across devices in a number of ways, or all of the functionality may be integrated into a dedicated, standalone device, or other hardware.

Components of systems set forth herein may be arranged in a number of ways to achieve goals as set forth herein, and/or to achieve other goals that are evident from the disclosure herein. All such permutations and combinations are intended to fall within the scope of the present disclosure.

Claims

1. A carbon dioxide recovery system, comprising: a primary recovery system comprising a plurality of membranes; a carbon dioxide (CO.sub.2) plant assembly fluidly coupled to a permeate of a membrane of the plurality of membranes, the CO.sub.2 plant assembly configured to provide a liquid CO.sub.2 product stream and a non-condensable stream; and a standalone membrane assembly fluidly coupled to the non-condensable stream, and configured to separate the non-condensable stream into a hydrocarbon enriched stream and a CO.sub.2 enriched stream, wherein the CO.sub.2 plant assembly is fluidly coupled to the CO.sub.2 enriched stream.
 2. The carbon dioxide recovery system of claim 1, wherein the membrane of the plurality of membranes comprises a first sequential membrane.
 3. The carbon dioxide recovery system of claim 1, wherein the membrane of the plurality of membranes comprises a second sequential membrane.
 4. The carbon dioxide recovery system of claim 1, further comprising: wherein the primary recovery system comprises an adsorption component; and wherein the adsorption component is at least selectively coupled to the CO.sub.2 enriched stream as a flush gas.
 5. The carbon dioxide recovery system of claim 1, further comprising: wherein the primary recovery system is fluidly coupled to the hydrocarbon enriched stream as a recycle gas.
 6. The carbon dioxide recovery system of claim 1, wherein the non-condensable stream is not pressurized between the CO.sub.2 plant assembly and the standalone membrane assembly.
-